

**STANDARD DEPARTURE CHART  
INSTRUMENT(SID) - ICAO**

TRANSITION ALT 14 000  
TRANSITION LVL FL 140

SACHEON DEP 135.4  
YEOSU TWR 122.5  
240.9


YEOSU/Yeosu(RKJY)

RWY 17

RNAV ANUBA 1M, RNAV GOSBO 1M

RNAV TEDAN 1M

Note : Departure under ICAO Flight Procedures.



Change : Information of standard instrument departure procedure for RWY 17.

YEOSU/Yeosu(RKJY)

RWY 17

RNAV ANUBA 1M, RNAV GOSBO 1M

RNAV TEDAN 1M

## AERONAUTICAL DATA TABULATION

## Standard Instrument Departure Procedure Coding Tables

## RNAV ANUBA 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	JY801	-	165(157.3)	11.7	-	-	-220	34°39'05.5"N 127°42'49.7"E	-	RNAV 1	-
002	TF	JY802	-	122(113.8)	6.3	-	-	-220	34°36'32.5"N 127°49'48.6"E	-	RNAV 1	-
003	TF	JY803	-	032(023.9)	8.6	-	-	-220	34°44'25.1"N 127°54'02.0"E	-	RNAV 1	-
004	TF	YSU	-	302(293.9)	15.2	-	@8 000	-	34°50'34.3"N 127°37'08.7"E	-	RNAV 1	-
005	TF	ANUBA	-	003(355.2)	17.2	-	@8 000	-	35°07'45.9"N 127°35'22.8"E	-	RNAV 1	-

## RNAV GOSBO 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	JY801	-	165(157.3)	11.7	-	-	-	34°39'05.5"N 127°42'49.7"E	-	RNAV 1	-
002	TF	GOSBO	-	178(170.6)	24.1	-	@8 000	-	34°15'16.8"N 127°47'34.4"E	-	RNAV 1	-

## RNAV TEDAN 1M

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CA	-	-	165(157.3)	-	-	@4 000	-	-	-	RNAV 1	-
002	DF	JY804	-	-	-	R	+7 000	-	34°48'55.7"N 127°30'22.5"E	-	RNAV 1	-
003	TF	JY805	-	341(333.3)	15.0	-	-9 000	-	35°02'21.9"N 127°22'09.7"E	-	RNAV 1	-
004	TF	TEDAN	-	341(333.2)	6.0	-	@9 000	-	35°07'43.8"N 127°18'52.1"E	-	RNAV 1	-

Change : Information of standard instrument departure procedure for RWY 17.


**STANDARD DEPARTURE CHART  
INSTRUMENT(SID) - ICAO**

TRANSITION ALT 14 000  
TRANSITION LVL FL 140

SACHEON	DEP	135.4
YEOSU	TWR	122.5
		240.9

**YEOSU/Yeosu(RKJY)**  
RWY 17  
ANUBA 5S  
GOSBO 4S

Note : Departure under ICAO Flight Procedures.



Change : Information of standard instrument departure procedure for RWY 17.

**INTENTIONALLY**

**LEFT**

**BLANK**

**STANDARD DEPARTURE CHART  
INSTRUMENT(SID) - ICAO**


TRANSITION ALT 14 000  
TRANSITION LVL FL 140

SACHEON DEP 135.4  
YEOSU TWR 122.5  
240.9

**YEOSU/Yeosu(RKJY)  
RWY 35**

**RNAV GOSBO 1R, RNAV GOSBO 6R  
RNAV ANUBA 1R, RNAV TEDAN 1R**

Note : Departure under ICAO Flight Procedures.



Change : Information of standard instrument departure procedure for RWY 35.

YEOSU/Yeosu(RKJY)

RWY 35

RNAV GOSBO 1R, RNAV GOSBO 6R

RNAV ANUBA 1R, RNAV TEDAN 1R

## AERONAUTICAL DATA TABULATION

## Standard Instrument Departure Procedure Coding Tables

## RNAV GOSBO 1R

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	JY851	-	346(338.0)	5.8	-	-	-220	34°56'38.1"N 127°34'02.9"E	-	RNAV 1	-
002	TF	JY852	-	076(068.0)	7.7	-	-	-220	34°59'31.1"N 127°42'44.3"E	-	RNAV 1	-
003	TF	JY853	-	166(158.1)	6.3	-	@3 500	-220	34°53'37.1"N 127°45'37.1"E	-	RNAV 1	-
005	TF	JY857	-	213(205.2)	7.2	-	+6 000	-	34°47'05.5"N 127°41'54.0"E	-	RNAV 1	-
006	TF	JY854	-	213(205.1)	4.7	-	+7 000	-	34°42'47.3"N 127°39'27.4"E	-	RNAV 1	-
007	TF	GOSBO	-	174(166.2)	28.3	-	@8 000	-	34°15'16.8"N 127°47'34.4"E	-	RNAV 1	-

## RNAV ANUBA 1R

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CF	JY851	-	346(338.0)	5.8	-	-	-	34°56'38.1"N 127°34'02.9"E	-	RNAV 1	-
002	TF	ANUBA	-	013(005.6)	11.2	-	@5 000	-	35°07'45.9"N 127°35'22.8"E	-	RNAV 1	-

## RNAV TEDAN 1R

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CA	-	-	346(338.0)	-	-	@4 000	-240	-	-	RNAV 1	-
002	DF	TEDAN	-	-	-	L	@5 000	-	35°07'43.8"N 127°18'52.1"E	-	RNAV 1	-

## RNAV GOSBO 6R

Serial Number	Path Descriptor	Waypoint Identifier	Fly-over	Course/Track °M(°T)	Distance (NM)	Turn direction	Altitude (ft)	Speed (kt)	Coordinates	VPA/ RDH	Navigation specification	Remarks
001	CA	-	-	346(338.0)	-	-	@4 000	-240	-	-	RNAV 1	-
002	DF	JY855	-	-	-	L	@5 000	-240	34°48'10.7"N 127°31'48.2"E	-	RNAV 1	-
003	TF	JY856	-	166(158.3)	7.3	-	+6 000	-	34°41'22.6"N 127°35'04.9"E	-	RNAV 1	-
004	TF	GOSBO	-	166(158.3)	28.0	-	@8 000	-	34°15'16.8"N 127°47'34.4"E	-	RNAV 1	-

Change : Amended phrase(VPA/TCH → VPA/RDH).




**STANDARD DEPARTURE CHART  
INSTRUMENT(SID) - ICAO**

TRANSITION ALT 14 000  
TRANSITION LVL FL 140

SACHEON DEP 135.4  
YEOSU TWR 122.5  
240.9

**YEOSU/Yeosu(RKJY)**  
RWY 35  
ANUBA 5N  
GOSBO 5N

Note : Departure under ICAO Flight Procedures.



Change : Information of standard instrument departure procedure for RWY 35.

**INTENTIONALLY**

**LEFT**

**BLANK**