HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x
Interface	24 10/100Mbps RJ45 Ports (Auto Negotiation/Auto MDI/MDIX)
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) 100BASE-TX: UTP category 5, 5e or above cable (maximum 100m)
Fan Quantity	Fanless
Power Supply	External Power Adapter(Output: 9VDC/0.6A)
Power Consumption	Maximum: 3.2W
Dimensions (W x D x H)	11.6*7.1*1.7 in. (294*180*44 mm)
Mounting	Rack Mountable
Max Power Consumption	3.19W(220V/50Hz)
Max Heat Dissipation	10.88BTU/h

PERFORMANCE

Switching Capacity	4.8Gbps
Packet Forwarding Rate	3.57Mpps
MAC Address Table	8K
Buffer Memory	2Mb
Green Technology	Innovative energy-efficient technology saves power up to 75%
Transfer Method	Store-and-Forward

OTHERS

Certification	FCC, CE, RoHS
Package Contents	24-Port 10/100Mbps Desktop/Rackmount Switch Power Cord Installation Guide Rackmount Kit Rubber Feet
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

Chat now

About Us

Corporate Profile
Contact Us
Careers at TP-Link
Privacy Policy

Press

News
Awards
Security Advisory

Partners

Partner Program
Training & Certifications
Deal Registration

Subscription

Email Address   Sign Up

Follow Us

United States / English