

```
mysql> CREATE TABLE cust(custid INT PRIMARY KEY, name VARCHAR(10));
Query OK, 0 rows affected (0.374 sec)
```

```
mysql> INSERT INTO cust VALUES(1,'jony'),(2,'bob'),(3,'alice'),(4,'charlie'),(5,'rony');
Query OK, 5 rows affected (0.167 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM cust;
```

custid	name
1	jony
2	bob
3	alice
4	charlie
5	rony

```
5 rows in set (0.018 sec)
```

```
mysql> CREATE TABLE ord(ordid INT PRIMARY KEY, custid INT, product VARCHAR(20));
Query OK, 0 rows affected (0.274 sec)
```

```
mysql> SELECT * FROM ord;
Empty set (0.025 sec)
```

```
mysql> INSERT INTO ord VALUES(111,1,'laptop'),(112,6,'mouse'),(113,5,'monitor'),(114,3,'keyboard'),(115,4,'cpu');
Query OK, 5 rows affected (0.141 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> SELECT * FROM ord;
```

ordid	custid	product
111	1	laptop
112	6	mouse
113	5	monitor
114	3	keyboard
115	4	cpu

```
5 rows in set (0.011 sec)
```

```
mysql> SELECT * FROM cust INNER JOIN ord ON cust.custid=ord.custid;
```

custid	name	ordid	custid	product
1	jony	111	1	laptop
5	rony	113	5	monitor
3	alice	114	3	keyboard
4	charlie	115	4	cpu

```
4 rows in set (0.014 sec)
```

```
mysql> SELECT * FROM cust LEFT JOIN ord ON cust.custid=ord.custid;
```

custid	name	ordid	custid	product
1	jony	111	1	laptop
2	bob	NULL	NULL	NULL
3	alice	114	3	keyboard
4	charlie	115	4	cpu
5	rony	113	5	monitor

5 rows in set (0.096 sec)

mysql> SELECT \* FROM cust RIGHT JOIN ord ON cust.custid=ord.custid;

custid	name	ordid	custid	product
1	jony	111	1	laptop
NULL	NULL	112	6	mouse
5	rony	113	5	monitor
3	alice	114	3	keyboard
4	charlie	115	4	cpu

5 rows in set (0.024 sec)

mysql> SELECT \* FROM cust LEFT JOIN ord ON cust.custid=ord.custid UNION SELECT \* FROM RIGHT JOIN ord ON cust.custid=ord.custid;  
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near 'RIGHT JOIN ord ON cust.custid=ord.custid' at line 1

mysql> SELECT \* FROM cust LEFT JOIN ord ON cust.custid=ord.custid UNION SELECT \* FROM cust RIGHT JOIN ord ON cust.custid=ord.custid;

custid	name	ordid	custid	product
1	jony	111	1	laptop
2	bob	NULL	NULL	NULL
3	alice	114	3	keyboard
4	charlie	115	4	cpu
5	rony	113	5	monitor
NULL	NULL	112	6	mouse

6 rows in set (0.026 sec)

mysql> |