

```

#include <Adafruit_NeoPixel.h>
#define BUTTON_PIN 2 // A1 AD 2 Gnd
#define PIN 6
#define NUMPIXELS 14

Adafruit_NeoPixel strip(NUMPIXELS, PIN, NEO_GRB + NEO_KHZ800);

// HIGH SCORES 1. 36 Wiley 2. 27 Daniel 3. 23. Daniel

// Variables
int clk = 0;
int playerPos = 0;
int coinPos = 7;
float frameWait = 10;
bool clicked = false;
bool takeDamage = false;
int lives = 3;
int oldState = 1;
int score = 0;
int coinPos2 = 10;
bool coinFlash = true;

// Functions
void plaMovement() { // playerPos reaches max amount to neopixels than goes back to the start
  playerPos++;
  if (playerPos > NUMPIXELS - 1) {
    playerPos = 0;
  }
  strip.setPixelColor(playerPos, 200, 0, 155);
}

void coinMovement() { //coinPos flashes when set to a new position
  if(coinFlash == true){
    strip.setPixelColor(coinPos, 255, 255, 255);
    coinFlash = false;
  }else{
    strip.setPixelColor(coinPos, 100, 100, 0);
  }
}

```

```

}

// coin 2 is set to a random neopixel between 3 and the max number of neopixels
// when playerPos is = to coin 2
void coinMovement2() {
  strip.setPixelColor(coinPos2, 100, 100, 0);
  if (coinPos2 == playerPos) {
    coinPos2 = random(3, NUMPIXELS);
  }
}

```

```

// if playerPos is equal to the coin 1 position than +1 to the score
// playerPos speed increases by .2 each time the button is pressed -
// - when the positions are equal
// coinPos is set to a random neopixel between 3 and the max -
// - of neopixels
// coinPos flashes when position is changed
// if the button is not pressed when playerPos and coinPos is equal -
// - then you lose a life
void checkClick() {
  if (clicked == true) {
    if (playerPos == coinPos) {
      score++;
      frameWait -= 0.2;
      coinPos = random(3, NUMPIXELS);
      coinFlash = true;
    } else {
      takeDamage = true;
    }
  }
}

```

```

void checkDamage() {
  if (takeDamage == true) {
    takeDamage = false;
    lives--; // each time you press the button when playerPos and coinPos are not equal you lose 1
    life
    if (lives > 0) { // players loses life but doesn't die

```

```

strip.clear();
strip.setPixelColor(playerPos - 1, 255, 0, 0);
strip.show();
playerPos = 0; // when player loses a life playerPos resets to neopixel 1
delay(1000);
} else { // player dies
  Serial.println(score); // prints the end score in the monitor

  frameWait = 10; // original speed of playerPos
  lives = 3; // amount of lives at the start
  playerPos = 0; // player position
  score = 0; // starting score
  strip.clear();

  for(int i = 0; i < NUMPIXELS; i++){
    strip.setPixelColor(i, 155, 0, 0);
  }

  strip.show();

  delay(5000);
}
}

void setup() {
  Serial.begin(9600);
  strip.setBrightness(70);
  pinMode(BUTTON_PIN, INPUT_PULLUP);
  strip.begin();
  strip.clear();
  strip.show();
}

void loop() {
  clk++;

  if (digitalRead(BUTTON_PIN) != oldState) {

```

```

    if (digitalRead(BUTTON_PIN) == LOW) {
        clicked = true;
    }
}

```

```

if (clk >= 20) {
    clk = 0;
    strip.clear();
    checkClick();
    coinMovement();
    coinMovement2();
    plaMovement();
    checkDamage();

```

```

    strip.show();
    clicked = false;
}
oldState = digitalRead(BUTTON_PIN);
delay(frameWait);
}

```

```

#include <Adafruit_NeoPixel.h>
#define BUTTON_PIN 2 // A1 AD 2 Gnd
#define PIN 6
#define NUMPIXELS 14

Adafruit_NeoPixel strip(NUMPIXELS, PIN, NEO_GRB + NEO_KHZ800);

// HIGH SCORES 1. 36 Wiley 2. 27 Daniel 3. 23. Daniel

// Variables
int clk = 0;
int playerPos = 0;
int coinPos = 7;
float frameWait = 10;
bool clicked = false;
bool takeDamage = false;
int lives = 3;
int oldState = 1;
int score = 0;
int coinPos2 = 10;
bool coinFlash = true;

// Functions

```

```
// Functions
void plaMovement() { // playerPos reaches max amount to neopixels than goes back to the start
    playerPos++;
    if (playerPos > NUMPIXELS - 1) {
        playerPos = 0;
    }
    strip.setPixelColor(playerPos, 200, 0, 155);
}

void coinMovement() { //coinPos flashes when set to a new position
    if(coinFlash == true){
        strip.setPixelColor(coinPos, 255, 255, 255);
        coinFlash = false;
    }else{
        strip.setPixelColor(coinPos, 100, 100, 0);
    }
}

// coin 2 is set to a random neopixel between 3 and the max number of neopixels
// when playerPos is = to coin 2
void coinMovement2() {
```

```
    strip.setPixelColor(coinPos2, 100, 100, 0);
    if (coinPos2 == playerPos) {
        coinPos2 = random(3, NUMPIXELS);
    }
}

// if playerPos is equal to the coin 1 position than +1 to the score
// playerPos speed increases by .2 each time the button is pressed -
// - when the positions are equal
// coinPos is set to a random neopixel between 3 and the max -
// - of neopixels
// coinPos flashes when position is changed
// if the button is not pressed when playerPos and coinPos is equal -
// - then you lose a life
void checkClick() {
    if (clicked == true) {
        if (playerPos == coinPos) {
            score++;
            frameWait -= 0.2;
            coinPos = random(3, NUMPIXELS);
            coinFlash = true;
        }
    }
}
```

```
    } else {
        takeDamage = true;
    }
}

}
```

```
void checkDamage() {
    if (takeDamage == true) {
        takeDamage = false;
        lives--; // each time you press the button when playerPos and coinPos are not equal you lose 1 life
        if (lives > 0) { // players loses life but doesn't die
            strip.clear();
            strip.setPixelColor(playerPos - 1, 255, 0, 0);
            strip.show();
            playerPos = 0; // when player loses a life playerPos resets to neopixel 1
            delay(1000);
        } else { // player dies
            Serial.println(score); // prints the end score in the monitor

            frameWait = 10; // original speed of playerPos
            lives = 3; // amount of lives at the start
            playerPos = 0; // player position
        }
    }
}
```

```
    playerPos = 0; // player position
    score = 0; // starting score
    strip.clear();

    for(int i = 0; i < NUMPIXELS; i++){
        strip.setPixelColor(i, 155, 0, 0);
    }

    strip.show();

    delay(5000);
}

}
```

```
void setup() {
    Serial.begin(9600);
    strip.setBrightness(70);
    pinMode(BUTTON_PIN, INPUT_PULLUP);
    strip.begin();
    strip.clear();
}
```

```
strip.show();
}

void loop() {
  clck++;

  if (digitalRead(BUTTON_PIN) != oldState) {
    if (digitalRead(BUTTON_PIN) == LOW) {
      clicked = true;
    }
  }

  if (clck >= 20) {
    clck = 0;
    strip.clear();
    checkClick();
    coinMovement();
    coinMovement2();
    plaMovement();
    checkDamage();

    strip.show();
  }
}
```

```
if (clck >= 20) {
  clck = 0;
  strip.clear();
  checkClick();
  coinMovement();
  coinMovement2();
  plaMovement();
  checkDamage();

  strip.show();
  clicked = false;
}
oldState = digitalRead(BUTTON_PIN);
delay(frameWait);
}
```