

CS417 Lab 8

Exercises on Dictionaries

Getting Started

Create a folder for your work. Then, go to `mycourses.unh.edu`, find CS417, click the `unh.box.com` link, find **Lab08**, and download this file:

- `dicts.py`

Exercises

1. Implement `get_frequencies(data)`. It counts how often each item occurs in `data`, and returns a dictionary of counts.

Method:

- first, create a dict called `counts`.
- make a `for`-loop that visits each `x` in `data`
- in the loop, do `counts[x] += 1`

The statement `counts[x] += 1` will fail with `KeyError` if `x` is not yet in the dictionary. So, check `if x not in counts` before incrementing. If it's not, initialize `counts[x]` to `0` or `1`, depending on how you wrote your code.

2. Implement `has_duplicates(data)`. It returns `True/False` if `data` has/hasn't repeated items.

Method:

- First, call `get_frequencies` to get the counts
 - Write a `for`-loop that visits all the keys: `for x in counts:`
 - The `for` loop will iterate through the *keys* of `counts`. You need to get the corresponding `counts[x]`.
 - Any key with a `count > 1` means there are duplicates.
-

3. Implement `get_mode(data)`. It returns the item that occurs MOST frequently in `data`. If there are multiple modes, return the first one found.

Method: You are basically finding the largest count, and saving the corresponding item. You can do this in several ways, but the simplest is:

- Find the largest count: `max(counts.values())`.
- Write a `for`-loop that visits each `key, value` pair:

```
for key, count in counts.items():  
    ◦ return when you found the largest count.
```

4. Implement `is_invertible(dictionary)`. Returns `True/False` if the dictionary can/can't be inverted. A dictionary is invertible if every key maps to a different value. So, if you get all the values in the dictionary, and there are duplicates, it can't be inverted.

Method:

- `dictionary.values()` is a list of values.
 - Call `has_duplicates()` on it.
-

5. Implement `inverted(dictionary)`. It returns a new `dict`, which is the inverse: if `key, value` is an item in `dictionary`, then `value, key` is an item in the inverse.

Method:

- Create an empty `dict()`, the `inverse`.
- Loop through all the `items()` in `dictionary`, and add each `value, pair` to the `inverse`.

Test Your Code

The module `dicts.py` has a `main()` program that tests all the functions. It should produce this output:

```
counts    : {1: 2, 2: 3, 3: 2, 4: 3, 5: 2, 6: 1}  
has dupes: True  
mode      : 2  
num_names is not invertible  
unique_names is invertible  
inverted(num): {1: 'a', 2: 'two', 5: 'five', 3: 'three', 4:  
'four'}  
inverted(uniq): {1: 'one', 2: 'two', 5: 'five', 3: 'three', 4:  
'four'}
```

Turn in Your Work

When you are done, go to [mycourses](#), and find the lab. Click the **Submit** button, and upload `dicts.py`.