



Incident report analysis

Summary	The company had a security incident where all network services suddenly stopped working. After investigating, the cybersecurity team found it was caused by a DDoS attack flooding the network with ICMP packets. To deal with it, they blocked the attack and temporarily shut down non-essential services so they could focus on restoring the most important systems first.
Identify	A malicious actor targeted the company with an ICMP flood attack that impacted the entire internal network. The main goal was to identify the issue and get critical systems back up and running safely.
Protect	To help prevent this from happening again, the team added a firewall rule to limit how many ICMP packets can come in. They also set up IDS/IPS tools to filter out suspicious ICMP traffic.
Detect	The team enabled IP verification on the firewall to catch spoofed addresses and started using monitoring tools to spot unusual spikes or patterns in network traffic.
Respond	If something like this happens again, the plan is to isolate affected systems to stop the spread of the issue. The team would focus on restoring critical services first, then review logs to understand what happened. They would also report the incident to management and any required authorities.
Recover	To recover from this type of attack, the goal is to get the network back to normal as quickly as possible. ICMP flood traffic would be blocked at the firewall, non-essential services would be temporarily turned off, and critical systems would be restored first. Once traffic stabilizes, the remaining services would be brought back online.

Reflections/Notes: This incident showed how quickly a DDoS attack can take down essential network services. It highlighted the importance of having strong traffic filtering rules and real-time monitoring in place before an attack happens. Moving forward, improving early detection and response time will be key to reducing downtime and impact.