

Demo: Structural Network Minimization: A Case of Reflective Networking

Mubashir Anwar[†], Anduo Wang*, Fangping Lan*, Matthew Caesar[†]

[†]University of Illinois at Urbana-Champaign, *Temple University

ABSTRACT

Traditional network state management focuses on packets that exercise network structures (configurations, procedures) and testify semantics (intentions), but provides little insights into how the structure actually “causes” the semantics. In response to this missed opportunity, we propose *reflective networking*, which features a *network structure capable of altering itself with a causal connection to its semantics*. Specifically, we investigate the network datalog structure and the chase, a process that transforms datalog programs by “executing” intents (semantic constraints) that are themselves expressed in datalog. To illustrate the usefulness of reflective networking, this demonstration presents a first use case: we developed an intuitive specification of routing in datalog, and employed the chase to summarize a network’s routing behavior by minimizing (repeatedly transforming) the corresponding datalog program.

CCS CONCEPTS

• **Networks** → *Programming interfaces; Network manageability*; • **Computing methodologies** → *Reasoning about belief and knowledge*.

KEYWORDS

Network management, reflective programming, datalog minimization, the chase

1 INTRODUCTION

Managing network state — the network structure (configurations and procedures) and the semantics (intentions) — has been challenging [4, 5, 10] since the early days of the Internet, when computer networks were still a bag of distributed protocols. Management in general was a black art: The admin often made small changes to the network and used primitive tools (ping, traceroute) to check the resulting outcome on some test (witnessing) packet. Such trial-and-error methods hardly generalize. For example, after verifying a specific intention or fixing a particular anomaly by exercising relevant packets (drawn from past experience, perhaps), very little insights are generated into the network state in general: Which (set of distributed) devices or parameters are responsible for causing what property? What modification (adding which link, altering which command) corrects which anomaly? Can we transfer the

logic handling interdependencies on one network into another even when the difference is tiny?

As networks become more programmable (software-defined), we have SDN controllers that eliminate distributed state management, domain-specific languages that raise the level of abstraction, and formal verification and synthesis tools that are far more powerful than primitive tools like ping. Combined together, do they entail a better management of the network state? The SDN software, though centralized and higher-level, tend to be very expressive and the problem of managing the intention, as buried in a software, is notoriously hard. The formal reasoning tools, despite involving sophisticated techniques (symbolic execution, model abstraction, search heuristics etc), still follow the same old *behavioral approach* in which a network state is examined by exhaustively trying out all possible inputs/outputs packets, revealing very little about how and why an intention is collectively implemented by the network structure as a soup of software expressions. In fact, as shown by the test coverage metric (proposed in [8, 27]) that measures the fragment of network rules being exercised, even our best assessment of the network state is primitive.

In light of these, we take a departure from the traditional approach and propose a *reflective* [1, 23] one in which network state is managed by a *network structure capable of examining and altering itself with a causal connection to the behavior (semantics)*. Reflective networking shifts the focus from input/output packets analysis to the network structure itself, to its ability to *reflect* on questions including: Can we identify the part of a network structure (a data, an operation, a line of code) relevant to an intention, and alter it to match a change? Can we test containment of network behaviors by syntactic (structural) comparison, not a verbatim comparison for specific scenarios, but generally? Can we have a true notion of network optimality, some “smallest” structure for the same behavior, and have a procedure to actually find it?

As a first step towards this vision, we make a case of reflective networking with the datalog structure. Datalog-like languages (referred to as network datalog), have been gaining increasing popularity in SDN platforms [13, 15, 19] and verification tools [12, 16, 17], but we choose datalog because it is by nature, though less well exploited, reflective. Datalog is closely related to a database query language called *tableau* [2] (plural: tableaux), a visual data query — similar to Microsoft Access and Query-By-Example (QBE [28]) — that specifies a query by giving a representative example — a “template” table with both constant and variable symbols — that cover all possible answers. A tableau can thus be viewed as both a program (query) and a data instance (template table). This *program-data duality* carries over to datalog too. We only need to view the body of a datalog program (for datalog rule $h : -b_1, \dots, b_n$, its body is the set of predicates b_1, \dots, b_n with constants and variables) as a symbolic database — the variables in this database now describe all databases

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

ACM SIGCOMM '23, September 10, 2023, New York, NY, USA

© 2023 Copyright held by the owner/author(s).

ACM ISBN 979-8-4007-0236-5/23/09.

<https://doi.org/10.1145/3603269.3610847>

that can derive an answer (the head h). Leveraging this program-data duality, as formalized by the elegant chase process [3, 11, 18], we can use the familiar (e.g., SQL-like) data operations to examine and modify datalog programs, including testing if one datalog program's behavior contains another, computing how a semantic constraint (so called data dependencies) affects and alters a program, and optimizing a datalog program — by repeatedly testing if eliminating any part of the program retains its original semantics¹ — until a minimal equivalent is reached. The chase thus posess the essential ingredients for all the example reflections we envision for reflective networking.

But the classic chase, even in its most recent development [9], is only effective for a limited class of data dependencies that do not fully capture the complex semantics of networking. So our first contribution is to extend the classic chase theory to networking. We analyzed and identified the root causes to classic chase's limitation: the chase uses the standard query evaluation on a datalog program's instantiated database. The instantiated database, however, is a symbolic one, or technically, an incomplete database that requires more advanced evaluation. Based on this insight, our poster will illustrate a new chase algorithm that supports the incomplete database structure and incorporates the *fauré-log* evaluation engine, a network datalog extension for incomplete information. In addition, our demonstration illustrates the feasibility of reflective networking by presenting an empirical study of network minimization with the classic chase. In particular, we designed a stress test — summarizing arbitrary synthetic routing services on Rocketfuel [24] topologies with Route Views [26] prefixes by minimizing the corresponding network datalog model, and developed a prototype of the classic chase. Our experience is promising: the chase enables general network minimization (asymmetric topology, extensible to firewall and middleboxes) with competitive performance (< 1 minute even for minimizing large services with our most computationally expensive model), uncovers interesting findings into ISP redundancy, making it a valuable platform to rigorously and quantitatively manage network services.

2 DEMONSTRATION PLAN

In our demonstration, we will use a concrete example to introduce reflective networking as an attractive alternative to popular state-of-the-art tools [6, 14, 17], and to illustrate how reflective networking naturally generalizes previous heuristics [7, 20].

An example: summarizing services

Restricted forms of structural manipulation of networks do exist in earlier work. One notable example is network transformation, a technique proposed to scale up existing packet-centric verifiers [7, 20]. Note that network transformation is a specific verification task that establishes network equivalence (e.g., decide if a larger network is equivalent to a smaller one while preserving path properties); making transformation, by definition, is as (computationally) expensive as verification. How can we scale up the later by the former then? The answer by existing work is to only look for those “efficient” transformations by exploiting *structural properties* already presented in the network. One such structural

property is topology symmetry in data center networks [20], as depicted in Figure 1 (a). Moving beyond such structural properties, however, existing methods quickly degenerate into simple (if not trivial) comparison, for example, the Campion debugger [25] considers two OSPF configuration equivalent if the OSPF costs are identical.




Figure 1: (a) Effective behavioral network transformation relies on topology symmetry (a structural property); (b) Can we generalize to arbitrary topology with structural transformation.

By contrast, reflective networking seeks general, non-trivial network transformation. To see a potential use, consider the (actual) Rocketfuel topology for AS6939 [24] shown in Figure 1 (b): on the left, the 6 nodes belonging to AS6939 provide various paths for AS4323 to reach AS3356. When considering only reachability and path properties, it is commonly believed that the reachability services offered in the global internet, as demonstrated in this example, have redundancies. In fact, with some manual examination, it is not hard to see that the smaller network on the right gives an optimal summary in the sense that no more link can be removed to retain the same diversity (reachability, path length). To achieve this, one challenge is to properly encode the “redundancy”, requiring an understanding of both how structural minimization operates and what semantics we want to retain. Besides, minimization only gives the end product — a minimized program that models the compressed network, it does not report the source of redundancy. To this end, we also developed a novel companion process (augmenting our model) that pin-points the redundancy.

A solution: structural network minimization We developed a datalog engine using Python and integrated it with *fauré* [16] evaluation, utilizing PostgreSQL [21] as the underlying query evaluation engine. By leveraging *fauré-log*, we are able to effectively represent incomplete information, which enhances the expressiveness of our network models. Furthermore, we optimized and implemented program minimization for *fauré-log*. The demonstration will showcase (1) the application of datalog encoding to the reachability services offered by ASes, similar to the example in Figure 1, and (2) various network encodings in datalog that preserve different network properties (e.g. middle boxes and firewalls) during program minimization.

ACKNOWLEDGEMENTS

This work is supported by the National Science Foundation Award CNS-1909450, CNS-2145242.

¹Static query optimization was actually the early killer app that drove the development of the chase [22].

REFERENCES

- [1] [n. d.]. Reflective Programming. https://en.wikipedia.org/wiki/Reflective_programming. ([n. d.]).
- [2] Serge Abiteboul, Richard Hull, and Victor Vianu (Eds.). 1995. *Foundations of Databases: The Logical Level*. Boston, MA, USA.
- [3] Alfred V. Aho, Yehoshua Sagiv, and Jeffrey D. Ullman. 1979. Equivalences among relational expressions. *SIAM J. Comput.* 8, 2 (1979), 218–246.
- [4] Paramvir Bahl, Ranveer Chandra, Albert Greenberg, Srikanth Kandula, David A. Maltz, and Ming Zhang. 2007. Towards Highly Reliable Enterprise Network Services via Inference of Multi-level Dependencies (SIGCOMM '07). ACM, New York, NY, USA, 12. <https://doi.org/10.1145/1282380.1282383>
- [5] Paramvir Victor Bahl, Paul Barham, Richard Black, Ranveer Chandra, Moises Goldszmidt, Rebecca Isaacs, Srikanth Kandula, Lun Li, John MacCormick, David Maltz, Richard Mortier, Mike Wawrzoniak, and Ming Zhang. 2006. Discovering Dependencies for Network Management. In *HotNets 2006*. ..
- [6] Ryan Beckett, Aarti Gupta, Ratul Mahajan, and David Walker. 2017. A General Approach to Network Configuration Verification. In *Proceedings of the Conference of the ACM Special Interest Group on Data Communication (SIGCOMM '17)*. Association for Computing Machinery, New York, NY, USA, 155–168. <https://doi.org/10.1145/3098822.3098834>
- [7] Ryan Beckett, Aarti Gupta, Ratul Mahajan, and David Walker. 2018. Control Plane Compression. In *Proceedings of the 2018 Conference of the ACM Special Interest Group on Data Communication (SIGCOMM '18)*. Association for Computing Machinery, New York, NY, USA, 476–489. <https://doi.org/10.1145/3230543.3230583>
- [8] Ryan Beckett and Ratul Mahajan. 2019. Putting Network Verification to Good Use. In *Proceedings of the 18th ACM Workshop on Hot Topics in Networks (HotNets '19)*. Association for Computing Machinery. <https://doi.org/10.1145/3365609.3365866>
- [9] Michael Benedikt, George Konstantinidis, Giansalvatore Mecca, Boris Motik, Paolo Papotti, Donatello Santoro, and Efthymia Tsamoura. 2017. Benchmarking the Chase. In *Proceedings of the 36th ACM SIGMOD-SIGACT-SIGAI Symposium on Principles of Database Systems (PODS '17)*. Association for Computing Machinery, New York, NY, USA, 37–52. <https://doi.org/10.1145/3034786.3034796>
- [10] Xu Chen, Ming Zhang, Z. Morley Mao, and Paramvir Bahl. 2008. Automating Network Application Dependency Discovery: Experiences, Limitations, and New Solutions (OSDI'08). USENIX Association, Berkeley, CA, USA, 14. <http://dl.acm.org/citation.cfm?id=1855741.1855750>
- [11] Alin Deutsch, Alan Nash, and Jeff Remmel. 2008. The Chase Revisited. In *Proceedings of the Twenty-Seventh ACM SIGMOD-SIGACT-SIGART Symposium on Principles of Database Systems (PODS '08)*. Association for Computing Machinery, New York, NY, USA. <https://doi.org/10.1145/1376916.1376938>
- [12] Ari Fogel, Stanley Fung, Luis Pedrosa, Meg Walraed-Sullivan, Ramesh Govindan, Ratul Mahajan, and Todd Millstein. 2015. A General Approach to Network Configuration Analysis (NSDI'15). USENIX Association, USA.
- [13] Timothy L. Hinrichs, Natasha S. Gude, Martin Casado, John C. Mitchell, and Scott Shenker. 2009. FML: Practical Declarative Network Management. In *Proceedings of the 1st ACM Workshop on Research on Enterprise Networking (WREN '09)*. ACM, New York, NY, USA, 1–10. <https://doi.org/10.1145/1592681.1592683>
- [14] Peyman Kazemian, Michael Chang, Hongyi Zeng, George Varghese, Nick McKeown, and Scott Whyte. 2013. Real Time Network Policy Checking Using Header Space Analysis. In *Proceedings of the 10th USENIX Conference on Networked Systems Design and Implementation (nsdi'13)*. USENIX Association, USA, 99–112.
- [15] Teemu Koponen, Keith Amidon, Peter Balland, Martin Casado, Anupam Chanda, Bryan Fulton, Igor Ganichev, Jesse Gross, Natasha Gude, Paul Ingram, Ethan Jackson, Andrew Lambeth, Romain Lenglet, Shih-Hao Li, Amar Padmanabhan, Justin Pettit, Ben Pfaff, Rajiv Ramanathan, Scott Shenker, Alan Shieh, Jeremy Stribling, Pankaj Thakkar, Dan Wendlandt, Alexander Yip, and Ronghua Zhang. 2014. Network Virtualization in Multi-tenant Datacenters. In *Proceedings of the 11th USENIX Conference on Networked Systems Design and Implementation (NSDI'14)*. USENIX Association, Berkeley, CA, USA, 203–216. <http://dl.acm.org/citation.cfm?id=2616448.2616468>
- [16] Fangping Lan, Bin Gui, and Anduo Wang. [n. d.]. Faure: a partial approach to network analysis (*ACM Workshop on Hot Topics in Networks (HotNets)*, November, 2021).
- [17] Nuno P. Lopes, Nikolaj Bjørner, Patrice Godefroid, Karthick Jayaraman, and George Varghese. 2015. Checking Beliefs in Dynamic Networks. In *12th USENIX Symposium on Networked Systems Design and Implementation (NSDI 15)*. USENIX Association, Oakland, CA, 499–512. <https://www.usenix.org/conference/nsdi15/technical-sessions/presentation/lopes>
- [18] David Maier, Alberto O. Mendelzon, and Yehoshua Sagiv. 1979. Testing Implications of Data Dependencies. *ACM Trans. Database Syst.* 4, 4 (dec 1979), 455–469. <https://doi.org/10.1145/320107.320115>
- [19] Tim Nelson, Andrew D. Ferguson, Michael J. G. Scheer, and Shriram Krishnamurthi. 2014. Tierless Programming and Reasoning for Software-Defined Networks. In *Proceedings of the 11th USENIX Symposium on Networked Systems Design and Implementation, NSDI 2014, Seattle, WA, USA, April 2-4, 2014*. 519–531. <http://www.usenix.org/conference/nsdi14/technical-sessions/presentation/nelson>
- [20] Gordon D. Plotkin, Nikolaj Bjørner, Nuno P. Lopes, Andrey Rybalchenko, and George Varghese. 2016. Scaling Network Verification Using Symmetry and Surgery. In *Proceedings of the 43rd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL '16)*. Association for Computing Machinery, New York, NY, USA. <https://doi.org/10.1145/2837614.2837657>
- [21] PostgreSQL: The World's Most Advanced Open Source Relational Database. [n. d.]. <https://www.postgresql.org/>. ([n. d.]).
- [22] Y. Sagiv. 1987. Optimizing Datalog Programs. In *Proceedings of the Sixth ACM SIGACT-SIGMOD-SIGART Symposium on Principles of Database Systems (PODS '87)*. New York, NY, USA. <https://doi.org/10.1145/28659.28696>
- [23] Brian Cantwell Smith. 1982. *Procedural Reflection in Programming Languages*. Ph.D. Dissertation. Massachusetts Institute of Technology, Laboratory for Computer Science. <http://publications.csail.mit.edu/lcs/pubs/pdf/MIT-LCS-TR-272.pdf>
- [24] Neil Spring, Ratul Mahajan, and Thomas Anderson. [n. d.]. Rocketfuel: An ISP Topology Mapping Engine. <http://research.cs.washington.edu/networking/rocketfuel/>. ([n. d.]).
- [25] Alan Tang, Siva Kesava Reddy Kakarla, Ryan Beckett, Ennan Zhai, Matt Brown, Todd Millstein, Yuval Tamir, and George Varghese. 2021. Campion: Debugging Router Configuration Differences. In *Proceedings of the 2021 ACM SIGCOMM 2021 Conference (SIGCOMM '21)*. Association for Computing Machinery, New York, NY, USA, 748–761. <https://doi.org/10.1145/3452296.3472925>
- [26] Route Views. [n. d.]. Route Views. <http://www.routeviews.org/routeviews/>. ([n. d.]).
- [27] Xieyang Xu, Ryan Beckett, Karthick Jayaraman, Ratul Mahajan, and David Walker. 2021. Test Coverage Metrics for the Network. In *Proceedings of the 2021 ACM SIGCOMM 2021 Conference (SIGCOMM '21)*. Association for Computing Machinery, New York, NY, USA, 775–787. <https://doi.org/10.1145/3452296.3472941>
- [28] M. M. Zloof. 1977. Query-by-Example: A Data Base Language. *IBM Syst. J.* 16, 4 (dec 1977), 324–343. <https://doi.org/10.1147/sj.164.0324>