

More SSH

SSH Hostname Aliases

- Allows you to type short name without username
- Edit ~/.ssh/config - for each alias:

Host eos01

Hostname eos01.cis.gvsu.edu

User yourusername

SSH Keys

- Annoying to enter password every time
- Default locations (on machine ssh'ing from)
 - ~/.ssh/id_rsa – private key
 - ~/.ssh/id_rsa.pub – public key

Setting up SSH Keys

- Check to see if you don't already have the keys
 - `ls -al ~/.ssh`
- Generate new keys
 - `ssh-keygen` → generates keys
- Add public key to `~/.ssh/authorized_keys` file on remote server
 - `ssh-copy-id "username@hostname"`

Issues with ssh-leys?

- Errors about the authorized keys file:
 - Not existing: make the file with
 - ``touch ~/.ssh/authorized_keys``
 - Wrong permissions:
 - ``chmod 600 ~/.ssh/authorized_keys``
 - `chmod 700 ~/.ssh`

Issues with ssh-keys?

- If you can use ssh and ssh-keygen but don't have ssh-copy-id
 - move id_rsa.pub to remote machine:
 - `scp ~/.ssh/id_rsa.pub username@hostname:~`
 - SSH into remote machine and add public key to authorized_keys:
`ssh username@hostname`
`cat id_rsa.pub >> .ssh/authorized_keys`