

Intro to Bash

Configuration files

- `~/.bashrc` on your local machine
- runs when you start a terminal
- `~/.profile` on EOS
 - runs when you ssh in
 - On EOS, this also runs your `.bashrc`
- To run updates after editing a file:
 - either re-login
 - or use `source` (`source ~/.bashrc`)
- These contain bash commands
 - we will talk more about similar files soon

Aliases

- Common example: `la`
 - `alias la='ls -A'`
- Now, running "`la`" is the same as running "`ls -A`"
- Why does this need to be in `~/.bashrc`/ `~/.profile`?
- ideas for other useful aliases?

Environment Variables

- variables that can be used in this shell and its child processes
- how to view our environment variables?
 - `printenv`
- what are they used for?
 - Example: `PATH` - where `bash` looks for programs to run

Editing environment variables (e.g., PATH)

- Best to do this in ~/.bashrc
- Add a new line:
 - `export PATH="newpath: $PATH"`
- ":" allows us to have multiple values
- Note that bash searches PATH in order

Installing software from source

- why might we want to do this?
- working through an example: sl
- First let's clone the repo:
 - git clone [git@github.com:mtoyoda/sl](https://github.com/mtoyoda/sl).git
- If you don't have ssh keys setup on EOS:
 - git clone <https://github.com/mtoyoda/sl>
- Build the application, if necessary
- Modify PATH to include this directory