

Clustering Millions of Faces By Identity

Nisim Hurst

Thursday 2 May 2019

Clustering Millions of Faces by Identity

The article was written by (Otto, Wang, and Jain 2018). It was cited 44 times according to Google Scholar. The task performed was face clustering. They used the F-measure metric over clusters with distractor images.

Hypothesis

The Rank-Order cluster proposed by [@].

Evidence and Results

Dataset

Results

Contribution

The network architecture is VGG16 proposed by (Simonyan and Zisserman 2014).

Weaknesses

Future Work

References

- Otto, C., D. Wang, and A. K. Jain (Feb. 2018). “Clustering Millions of Faces by Identity”. In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 40.2, pp. 289–303. ISSN: 0162-8828. DOI: [10.1109/TPAMI.2017.2679100](https://doi.org/10.1109/TPAMI.2017.2679100).
- Simonyan, Karen and Andrew Zisserman (2014). “Very Deep Convolutional Networks for Large-Scale Image Recognition”. In: pp. 1–14. ISSN: 09505849. DOI: [10.1016/j.infsof.2008.09.005](https://doi.org/10.1016/j.infsof.2008.09.005). arXiv: [1409.1556](https://arxiv.org/abs/1409.1556). URL: <http://arxiv.org/abs/1409.1556>.