

Clustering Millions of Faces By Identity

Nisim Hurst

Friday 10 May 2019

Clustering Millions of Faces by Identity

The article was written by (Otto, Wang, and Jain [2018](#)). It was cited [44](#) times according to Google Scholar. The task performed was face clustering. They used the Pairwise F-measure metric over clusters with distractor images. They also developed their own metric for measuring internal cluster quality using just the k-top nearest neighbors.

Hypothesis

Deep features clustered using only the top-k nearest neighbors in rank-order clustering will produce a more scalable and a more accurate face clustering algorithm. This algorithm will be able to overcome the presence of millions distractor images and class imbalance.

The network architecture to produce a 320D feature vector was VGG16 proposed by (Simonyan and Zisserman [2014](#)). The rank-order clustering algorithm is based on (Zhu, Wen, and Sun [2011](#)). Their k-d tree implementation for calculating just the 200-top nearest neighbors is based on (Muja and Lowe [2014](#)).

Evidence and Results

Evidence is presented first over a small dataset and then over an augmented version of the datasets with millions of distractor images.

Dataset

The feature extractor was trained with the CASIA-webface. LFW, YTF were used for cluster evaluation, the former over static images and the latter over videos.

Webfaces was used to augment the LFW. Here is a brief description of each:

Table 1: Main characteristics of the four datasets that were used to test the improved CW.

| | # Instances | Resolution | Scenery | Author |
|---------------|---|----------------------------------|---|---|
| LFW | 13233 images of 5749. Only 1680 subjects have two or more photos. | ??, variable head angle | Color, different Poses and Backgrounds. | (Huang et al. 2008) |
| YTF | 3425 videos of 1595 subjects. | 100x100, variable enclosing area | Color, different Poses and Backgrounds. | (Wolf, Hassner, and Maoz 2011) |
| Webfaces | 123,654,141 distractor images. | N/A | N/A | (Otto, Wang, and Jain 2018) |
| CASIA-webface | 494,414 images of 10,575 subjects. | 120x165 | Color, different Poses and Backgrounds. | (Yi et al. 2014) |

Results

First, the authors present Pairwise F-measure evaluated in the LFW dataset without any distractor images.

Also, given that having a high number of similar frames on each video can affect grouping identities between videos, the authors present the results of the algorithm using a sample of 3 frames per video in contrast to the results obtained over all the frames.

Finally, the authors presents

Contribution

Firstly, the authors improved the Rank-Order clustering algorithm proposed by (Zhu, Wen, and Sun [2011](#)). The original Rank-Order has the disadvantage that it requires $O(n^2)$. The authors propose to use the FLANN library implementation of the randomized k-d tree algorithm to compute the list of top-k nearest neighbors. Just one iteration is used.

Secondly, the authors improved the internal quality metric of Modularization quality (MQ) (Mancoridis et al. [1998](#)) by just counting shared neighbors in the top-k nearest neighbors list. Cluster's external quality was obviated.

Thirdly, the authors provide an augmented dataset as a matter of baseline to assess the accuracy of the algorithm under the effect of distractor images that are

out of the face clusters.

Weaknesses

The method uses a representation that needs to be distributed in chunks across servers, each one process about a million image instances. However, the authors don't provide an efficient algorithm for merging the results nor prove that the algorithm is unaffected in single-thread environments.

Also, the method is dependent of a k that probably depends on the number of instances, but the authors don't specify how k should be modified.

Future Work

Otto mentions that the dimensional vector representation could be improved through a better deep model architect that perform better on profile/side faces.

It would be beneficial to enforce pairwise constraints like must-link and cannot-link.

Also the authors

References

- Huang, Gary B. et al. (Oct. 2008). “Labeled Faces in the Wild: A Database for Studying Face Recognition in Unconstrained Environments”. In: *Workshop on Faces in ‘Real-Life’ Images: Detection, Alignment, and Recognition*. Erik Learned-Miller and Andras Ferencz and Frédéric Jurie. Marseille, France. URL: <https://hal.inria.fr/inria-00321923>.
- Mancoridis, S. et al. (June 1998). “Using automatic clustering to produce high-level system organizations of source code”. In: *Proceedings. 6th International Workshop on Program Comprehension. IWPC’98 (Cat. No.98TB100242)*, pp. 45–52. DOI: [10.1109/WPC.1998.693283](https://doi.org/10.1109/WPC.1998.693283).
- Muja, M. and D. G. Lowe (Nov. 2014). “Scalable Nearest Neighbor Algorithms for High Dimensional Data”. In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 36.11, pp. 2227–2240. ISSN: 0162-8828. DOI: [10.1109/TPAMI.2014.2321376](https://doi.org/10.1109/TPAMI.2014.2321376).
- Otto, C., D. Wang, and A. K. Jain (Feb. 2018). “Clustering Millions of Faces by Identity”. In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 40.2, pp. 289–303. ISSN: 0162-8828. DOI: [10.1109/TPAMI.2017.2679100](https://doi.org/10.1109/TPAMI.2017.2679100).

- Simonyan, Karen and Andrew Zisserman (2014). “Very Deep Convolutional Networks for Large-Scale Image Recognition”. In: pp. 1–14. ISSN: 09505849. DOI: [10.1016/j.infsof.2008.09.005](https://doi.org/10.1016/j.infsof.2008.09.005). arXiv: [1409.1556](https://arxiv.org/abs/1409.1556). URL: <http://arxiv.org/abs/1409.1556>.
- Wolf, L., T. Hassner, and I. Maoz (June 2011). “Face recognition in unconstrained videos with matched background similarity”. In: *CVPR 2011*, pp. 529–534. DOI: [10.1109/CVPR.2011.5995566](https://doi.org/10.1109/CVPR.2011.5995566).
- Yi, Dong et al. (2014). “Learning face representation from scratch”. In: *arXiv preprint arXiv:1411.7923*.
- Zhu, C., F. Wen, and J. Sun (June 2011). “A rank-order distance based clustering algorithm for face tagging”. In: *CVPR 2011*, pp. 481–488. DOI: [10.1109/CVPR.2011.5995680](https://doi.org/10.1109/CVPR.2011.5995680).