

The langscibook L^AT_EX class

Sebastian Nordhoff

Language Science Press Guidelines



Contents

1	Introduction	1
2	The class	3
3	Requirements	5
3.1	Fonts	5
3.2	Styles	5
3.3	Series definitions	5
4	Creating a book	7
4.1	Creating a monograph	7
4.2	Creating an edited volume	8
4.3	Creating a paper for an edited volume	8
5	Creating a dust jacket	11
6	Options	13
6.1	Flag options	13
6.1.1	collection	13
6.1.2	collectionchapter	13
6.1.3	draftmode	13
6.1.4	openreview	13
6.1.5	multiauthors	13
6.1.6	newtxmath	13
6.1.7	nobabel	14
6.1.8	nonflat	14
6.1.9	showindex	14
6.1.10	smallfont	14
6.1.11	chinesefont	14
6.1.12	japanesefont	14
6.1.13	hebrewfont	14
6.1.14	arabicfont	14

Contents

6.1.15	syriacfont	15
6.2	String options	15
6.2.1	output	15
6.2.2	spinewidth	15
6.2.3	booklanguage	15
6.2.4	copyright	16
6.3	Metadata commands	16
6.3.1	\BackBody	16
6.3.2	\BackTitle	16
6.3.3	\BookDOI	16
6.3.4	\ChapterDOI	16
6.3.5	\dedication	16
6.3.6	\lsISBNdigital	17
6.3.7	\lsISBNhardcover	17
6.3.8	\lsISBNsoftcover	17
6.3.9	\lsSeries	17
6.3.10	\lsSeriesNumber	17
6.3.11	\lsID	17
6.4	Overrides	17
6.4.1	\SpineAuthor	17
6.4.2	\SpineTitle	18
6.4.3	\lsImpressionCitationAuthor	18
6.4.4	\lsImpressionCitationText	18
6.4.5	\papernote	18
6.4.6	\lsChapterFooterSize	18
6.4.7	\includespinelogo	18
6.4.8	\includestoragelogo	18
6.4.9	\includepublisherlogo	18
6.4.10	\includechapterfooterlogo	19
6.4.11	\lsImpressumExtra	19
6.4.12	\publisherstreetaddress	19
6.4.13	\publisherurl	19
6.4.14	\storageinstitution	19
6.4.15	\githubtext	19
6.4.16	\paperhivetext	19
6.5	Command redefinitions	19
6.5.1	\CoverTitleSizes	20
6.5.2	\lsAdvertisement	20

6.5.3	\lsBackBodyFont	20
6.5.4	\lsBackTitleFont	20
6.5.5	\lsCopyright	20
6.5.6	\lsCoverAuthorFont	20
6.5.7	\lsCoverSubTitleFont	20
6.5.8	\lsCoverTitleFont	21
6.5.9	\lsEditorPrefix	21
6.5.10	\lsEditorSuffix	21
6.5.11	\lsFontSize	21
6.5.12	\lsImpressumCitationText	21
6.5.13	\lsISSN	21
6.5.14	\lsSubjectIndexTitle	21
6.5.15	\lsLanguageIndexTitle	21
6.5.16	\lsNameIndexTitle	22
6.5.17	\lsSpineAuthorFont	22
6.5.18	\lsSpineTitleFont	22
6.5.19	\lsSubjectIndexTitle	22
6.5.20	\lsYear	22
6.6	Additions	22
6.6.1	\lsAdditionalFontsImprint	22
6.6.2	\lsImpressumExtra	22

1 Introduction

This document describes the \LaTeX class langscibook.cls. This class is used for typesetting books with Language Science Press. Language Science Press publish open access monographs and edited volumes in linguistics.

2 The class

The class is loaded via `\documentclass{langscibook}`. The standard use case is the creation of a book. If used without an `output=` option, the option `output=book` is loaded. The class can also be used to create dust jackets for books with different measurements via the output option values `covercreatespace` (for <http://www.createspace.com>) and `coverbodsc/coverbodhc` (for <http://www.bod.de>).

The class provides for the following:

- front cover
- frontispiece
- inside title
- colophon
- table of contents
- chapters
- list of references (per chapter or global)
- name index, subject index, language index
- advertisement
- back title
- ISBN
- DOI (per book and per chapter)

When used to create dust jackets, the class will produce a large pdf with a collation of backcover, spine and frontcover, from left to right, surrounded by bleed.

3 Requirements

3.1 Fonts

The class uses the fonts Libertinus, Arimo and DejaVu. These have to be present on the system.

3.2 Styles

A couple of additional style files come with the class. Documents using this class will compile without them, but in order to typeset books for Language Science Press, these packages should be loaded as well. These packages are

- `langsci-basic.sty`: Commands used in all Language Science Press books
- `langsci-optional.sty`: Further commands useful for some typical books
- `langsci-gb4e.sty`: Package for linguistic examples
- `langsci-cgloss.sty`: Helper package for `langsci-gb4e`
- `langsci-forest-setup.sty`: Set up the forest package for linguistic trees
- `langsci-tbls.sty`: Package for the textbook series Textbooks in Language Sciences
- `langsci-bidi.sty`: Package for typesetting right-to-left text

3.3 Series definitions

The metadata for LangSci book series are stored in `langsci-series.def`. For new series, the ISSN field of `langsci-series.def` might have to be updated.

4 Creating a book

The easiest way to start a book is to download the skeletons from <http://langsci-press.org/templatesAndTools>. Sample documents for monographs, edited volumes and chapters in edited volumes are provided in the folder `examples/` as well.

4.1 Creating a monograph

Load the class. Make sure the following metadata values are set with the metadata commands listed in §6.3:

- `author`
- `title`

Provide the following additional information if necessary:

- `series`
- `series number`
- `all ISBNs`
- `BookDOI`
- `ID`
- `blurb (back body)`
- `subtitle`
- `backtitle`
- `spine title`
- `spine author`

4 *Creating a book*

- dedication
- list of proofreaders
- list of typesetters
- list of illustrators
- license other than CC-BY
- list of additional fonts

4.2 Creating an edited volume

Proceed as for a monograph, but use the option `collection`. Use `\author` for the editor(s). Use the option `multiauthors` if there is more than one editor. You may want to use the further options `collectionchapter` and `collectiontoclong`. Chapters are included via `\includepaper{}`. Set the bibliography resource for all papers in the main file.

4.3 Creating a paper for an edited volume

Use the output option `paper`. Provide the following metadata in the preamble:

- `\author` with (`\affiliation`)
- `\title`
- `\abstract` (optional)

You might want to use `\shorttitlerunninghead` for chapters with very long titles.

Papers can be compiled standalone. You can use the command `\papernote` in the preamble of the paper to adjust the text displayed in the footer. This can be embedded in a conditional as follows (assuming your chapter source file is in a subfolder of the folder containing your main file):

```
\IfFileExists{../samplevolume.tex}{%adjust to name of your master file
  \papernote{\scriptsize\normalfont
    To appear in:
    Change Volume Editor.
```

4.3 *Creating a paper for an edited volume*

```
Change volume title.  
Berlin: Language Science Press. [preliminary page numbering]  
}  
\pagenumbering{roman}  
\setcounter{chapter}{23}%adjust the chapter number  
\addtocounter{chapter}{-1}  
{}{}
```

This will set your chapter number to 23 when compiled standalone (rather than 1) and will display text in the chapter footer.

5 Creating a dust jacket

Use the option `coverbodhc`, `coverbodsc` or `covercreatespace` and set the option `spinewidth`. Run \LaTeX twice. Upload to the respective websites to see whether the lengths were chosen correctly.

6 Options

The class has flag options to toggle certain behaviour and string options to set metadata values.

6.1 Flag options

6.1.1 **collection**

Make the book an edited volume

Default value: `false`

6.1.2 **collectionchapter**

Add numeric chapter prefix to each contribution.

Default value: `false`

6.1.3 **draftmode**

Switch to draft mode (adds: draft stamp, indication of overlong lines, date)

Default value: `false`

6.1.4 **openreview**

Switch to open review mode

Default value: `false`

6.1.5 **multiauthors**

Set editor suffix to eds. instead of ed.

Default value: `false`

6.1.6 **newtxmath**

Switch math fonts to newtxmath

Default value: `false`

6 Options

6.1.7 nobabel

Do not use the Babel package in the class

Default value: `false`

6.1.8 nonflat

Use elaborate directory structure. If set to true, fonts, packages etc will be loaded from subfolders. If set to false, they will be loaded from the working directory

Default value: `false`

6.1.9 showindex

Show indexed terms in margin

Default value: `false`

6.1.10 smallfont

Use a smaller font for books above 500 pages

Default value: `false`

6.1.11 chinesefont

Load fonts for Chinese and update font info in colophon

Default value: `false`

6.1.12 japanesefont

Load fonts for Japanese and update font info in colophon

Default value: `false`

6.1.13 hebrewfont

Load fonts for Hebrew and update font info in colophon

Default value: `false`

6.1.14 arabicfont

Load fonts for Arabic and update font info in colophon

Default value: `false`

6.1.15 **syriacfont**

Load fonts for Syriac and update font info in colophon

Default value: false

6.2 **String options**

6.2.1 **output**

Different output formats

Default value: book

- **book**: The book with frontcover and backcover
- **inprep**: Mark manuscript as in preparation
- **paper**: Contribution to edited volume
- **guidelines**: Choose color grey; condense frontmatter
- **coverbodhc**: Create a two-page wide cover (back-spine-front) for use with BoD hardcover books
- **coverbodsc**: Create a two-page wide cover (back-spine-front) for use with BoD softcover books
- **covercreatespace**: Create a two-page wide cover (back-spine-front) for use with CreateSpace

6.2.2 **spinewidth**

The width of the spine (for cover creation)

Default value: 20mm

6.2.3 **booklanguage**

Load babel for the specified language and change the custom headers for list of references and indexes

Default value: english

6 Options

6.2.4 copyright

The license chosen

Default value: "CC-BY"

6.3 Metadata commands

The following commands are used to indicated metadata.

6.3.1 \BackBody

Text to be printed on the back cover

Default value: European lingues es membres del sam familie. Lor separat existentie es un myth. Por scientie, musica, sport etc, litot Europa usa li sam vocabular. Li lingues differe solmen in li grammatica, li pronunciation e li plu commun vocabules. Omnicos directe al desirabilite de un nov lingua franca: On refusa continuar payar custosi traductores.

6.3.2 \BackTitle

Title on back cover

Default value: same as on front cover

6.3.3 \BookDOI

DOI for the book

Default value: ??

6.3.4 \ChapterDOI

DOI for a chapter

Default value: ??

6.3.5 \dedication

A dedication

Default value: void

6.3.6 \lsISBNdigital

ISBN for the digital version

Default value: 000-0-000000-00-0

6.3.7 \lsISBNhardcover

ISBN for the hardcover version

Default value: 000-0-000000-00-0

6.3.8 \lsISBNsoftcover

ISBN for the softcover version

Default value: 000-0-000000-00-0

6.3.9 \lsSeries

The series this book appears in. Use the acronyms found in `langsci-series.def`

Default value: eotms

6.3.10 \lsSeriesNumber

Position of the book in its series

Default value: ??

6.3.11 \lsID

The numerical LangSci ID, used for various URLs

Default value: 000

6.4 Overrides

The following commands allow to override further default settings:

6.4.1 \SpineAuthor

Custom author on spine. Useful for long lists of authors/editors

Default value: same as on cover

6 Options

6.4.2 `\SpineTitle`

Custom title on spine. Useful for long titles

Default value: same as on cover

6.4.3 `\lsImpressionCitationAuthor`

How the author name should be displayed in the impressum

Default value: Automatically inferred from `\author{}`, but sometimes things go wrong

6.4.4 `\lsImpressionCitationText`

Customize the full citation as displayed in the colophon. Useful for second editions

Default value: Automatically inferred from `\author{}` and `\title{}`

6.4.5 `\papernote`

Text displayed in the footer of chapters

Default value: Automatically inferred from volume and chapter metadata

6.4.6 `\lsChapterFooterSize`

Font size for chapter footers

Default value: `\small`

6.4.7 `\includespinelogo`

The logo to be put on the spine

Default value: `\includegraphics{\logopath langsci_spinelogo_nocolor}`

6.4.8 `\includestoragelogo`

The logo of the archiving institution

Default value: `\includegraphics[width=5cm]{\logopath storagelogo.pdf}`

6.4.9 `\includepublisherlogo`

The publisher's logo in the impressum

Default value: `\includegraphics{\logopath langsci_logo_nocolor.pdf}`

6.4.10 `\includechapterfooterlogo`

The logo to be used in chapter footers

Default value: `\includegraphics{\logopath langsci_spinelogo_nocolor.pdf}`

6.4.11 `\publisherstreetaddress`

the physical address of the publisher

Default value: LangSci Berlin address

6.4.12 `\publisherurl`

The web address of the publisher

Default value: `\href{http://langsci-press.org}{langsci-press.org}`

6.4.13 `\storageinstitution`

Where the book is archive

Default value: FU Berlin

6.4.14 `\githubtext`

Where the tex code of the book can be found

Default value: Source code available from

`\href{https://www.github.com/langsci/\lsID}{www.github.com/langsci/\lsID}`

6.4.15 `\paperhivetext`

Where the book can be found on PaperHive

Default value: Collaborative reading:

`\href{https://paperhive.org/documents/remote?type=langsci&id=\lsID}%
{paperhive.org/documents/remote?type=langsci&id=\lsID}`

6.5 Command redefinitions

Redefine the following commands to further alter the appearance:

6.5.1 `\CoverTitleSizes`

Set custom fontsize #1 and baselineskip #2 for title on cover

Default value: 52pt, 16.75mm

6 Options

6.5.2 \lsAdvertisement

Specify the advertisement on the last page of the book

Default value: `\include{\logopath didyoulikethisbook}`

6.5.3 \lsBackBodyFont

Font used for text on back cover

Default value: main font

6.5.4 \lsBackTitleFont

Font used for title on back cover

Default value: `\sffamily\addfontfeaturesScale=MatchUppercase
\fontsize{25pt}{10mm}\selectfont`

6.5.5 \lsCopyright

Choice of licence

Default value: CC-BY

6.5.6 \lsCoverAuthorFont

Font for author/editor on cover

Default value: `\fontsize{25pt}{12.5mm}\selectfont`

6.5.7 \lsCoverSubTitleFont

Font for the subtitle

Default value: `\sffamily\addfontfeatures{Scale=MatchUppercase}
\fontsize{25pt}{10mm}\selectfont`

6.5.8 \lsCoverTitleFont

Font for the title

Default value: `\sffamily\addfontfeaturesScale=MatchUppercase
\fontsize52pt17.25mm\selectfont`

6.5.9 **\lsEditorPrefix**

How editors are indicated on title page. Useful for localization.

Default value: \LARGE Edited by\\

6.5.10 **\lsEditorSuffix**

How editors are indicated in the colophon

Default value: (ed.)/(eds.), depending on the value of the option `multiauthors`

6.5.11 **\lsFontSize**

size of main font

Default value: 11pt

6.5.12 **\lsImpressumCitationText**

custom citation text, useful for including notes etc.

Default value: computed from author and title fields

6.5.13 **\lsISSN**

ISSN of the series

Default value: ??

6.5.14 **\lsLanguageIndexTitle**

The title of the language index. Change this for non-English works

Default value: Language index

6.5.15 **\lsNameIndexTitle**

The title of the name index. Change this for non-English works

Default value: Name index

6.5.16 **\lsSpineAuthorFont**

Font for the author on the spine

Default value: \fontsize{16pt}{14pt}\selectfont

6 Options

6.5.17 **\lsSpineTitleFont**

Font for the title on the spine

Default value: `\sffamily\fontsize{18pt}{14pt}\selectfont`

6.5.18 **\lsSubjectIndexTitle**

The title of the subject index. Change this for non-English works

Default value: `Subject index`

6.5.19 **\lsYear**

Year of publication

Default value: `\the\year`

6.6 Additions

6.6.1 **\lsAdditionalFontsImprint**

Add additional fonts to the list of fonts in the colophon

Default value: `void`

6.6.2 **\lsImpressumExtra**

for legal notes required for revised theses (“... in fulfillment of ...”)

Default value: `void`