

langsci-affiliations

Felix Kopecky*

Version 1.0.2rc – 25th February 2021

1 User guide

This package provides a command `\ResolveAffiliations`, which collects author–affiliation pairs and outputs them according to the user configuration. It is aimed at class authors, i.e. maintainers of document templates in publishing houses, universities, etc. It is probably not that useful to document authors.

`\ResolveAffiliations`

`\ResolveAffiliations` [*options*] {*pairs of authors and affiliations*}

Takes the {*pairs of authors and affiliations*}, orders them internally and outputs them according to the [*options*].

{*Pairs of authors and affiliations*} is a list of authors and affiliations, where authors are separated by `and` and affiliations by `;`. Affiliations are given within a phantom command `\affiliation` within the {*pairs*} argument – i.e. the command is not defined by this package and possibly existing definitions are left unchanged.

For example:

```
\ResolveAffiliations{
  A. U. Thor\affiliation{University of the Moon; University of Mars}
  and B. U. Thor\affiliation{University of Mars}
}
```

results in:

A. U. Thor^{a,b} & B. U. Thor^b

^aUniversity of the Moon ^bUniversity of Mars

The output can be customised using the [*options*]. They are described below.

*<mailto:felix.kopecky@langsci-press.org>. Please submit bug reports and feature requests to <https://github.com/langsci/langsci-affiliations/issues>.

\SetupAffiliations

\SetupAffiliations {*options*}

Options can be set either globally or locally. With **\SetupAffiliations**{*options*}, they apply globally. If they are set with **\ResolveAffiliations**[*options*], they apply locally.

mark style = *style* (initially **alphabetic**)
Controls which markers should be used in the indexes of affiliations. Can be either of {**alphabetic**, **numeric**, **circled**, **none**}.

output affiliation = *boolean* (initially **true**)
Affiliations are output if true, otherwise not.

output in groups = *boolean* (initially **true**)
If **true**, authors and affiliations are output in the same line. When **false** each author and affiliation gets its own line. Only available if **output affiliation**=**true**.

output authors font = *font commands* (initially **\Large**)
Stores the font settings for the output of authors.

output affiliation font = *font commands* (initially **\normalsize**)
Stores the font settings for outputting affiliations.

Output separators between authors and affiliations are customisable as well:

separator between two = *tokens* (initially **~&~**)
If there are only two authors, use these *tokens* to separate them.

separator between multiple = *tokens* (initially **,~**)
If there are more than two authors, use these *tokens* to separate every pair except the last one.

separator between final two = *tokens* (initially **~&~**)
Use these *tokens* to separate the last pair of authors if there are more than two.

separator between affiliations = *tokens* (initially **,**)
Use these to separate affiliations after each authors. The affiliations in the affiliation line are always separated by a space ().

separator between groups = *dimension* (initially **0.5ex**)
Length of the space between authors and affiliations

The way the input is digested can be customised with these two settings:

input names separator = *tokens* (initially **~and~**)
Separates the author names in the input.

input affiliation separator = *tokens* (initially **;**)
Separates the affiliations in the input, within dummy command **\affiliation**.

2 Implementation

```

1 <*package>
2 <@@=affiliations>
3 \RequirePackage{xparse}
4 \ProvidesExplPackage {langsci-affiliations}
5 {2021-02-25} {1.0.2}
6 {A LaTeX3 package to collect and order authors and affiliations}

\ResolveAffiliations The top-level document command. It is grouped to keep assignments local.
7 \NewDocumentCommand{\ResolveAffiliations}{ 0{ } +m }
8 {
9   \group_begin:
10   \keys_set:nn { affiliations } { #1 }%
11   \exp_args:No \affiliations_resolve:n { #2 }%
12   \group_end:
13 }

```

(End definition for `\ResolveAffiliations`. This function is documented on page 1.)

```

\SetupAffiliations A command to define options.
14 \NewDocumentCommand{\SetupAffiliations}{ m }
15 {
16   \keys_set:nn { affiliations } { #1 }
17 }

(End definition for \SetupAffiliations. This function is documented on page 2.)

18 \keys_define:nn { affiliations }
19 {
20   mark~style .tl_set:N
21     = \l__affiliations_style_tl,
22   mark~style .initial:n
23     = { alphabetic },
24   output~affiliation .bool_set:N
25     = \l__affiliations_output_affiliation_bool,
26   output~affiliation .initial:n
27     = { true },
28   output~in~groups .bool_set:N
29     = \l__affiliations_output_grouped_bool,
30   output~in~groups .initial:n
31     = { true },
32   separator~between~two .tl_set:N
33     = \l__affiliations_separator_between_two_tl,
34   separator~between~two .initial:n
35     = { ~\&~ },
36   separator~between~multiple .tl_set:N
37     = \l__affiliations_separator_between_mult_tl,
38   separator~between~multiple .initial:n
39     = { ,~ },
40   separator~between~final~two .tl_set:N
41     = \l__affiliations_separator_between_last_two_tl,
42   separator~between~final~two .initial:n
43     = { ~\&~ },
44   separator~between~groups .dim_set:N

```

```

45         = \l__affiliations_separator_between_groups_dim,
46     separator~between~groups .initial:n
47         = {0.5ex},
48     separator~between~affiliations .tl_set:N
49         = \l__affiliations_afil_separator_tl,
50     separator~between~affiliations .initial:n
51         = {,},
52     output~authors~font .cs_set:Np
53         = \__affiliations_output_authors_font:,
54     output~authors~font .initial:n
55         = {\Large},
56     output~affiliation~font .cs_set:Np
57         = \__affiliations_output_affiliation_font:,
58     output~affiliation~font .initial:n
59         = {\normalsize},
60     input~names~separator .tl_set:N
61         = \l__affiliations_input_names_sep_tl,
62     input~names~separator .initial:n
63         = {\~and~},
64     input~affiliation~separator .tl_set:N
65         = \l__affiliations_input_afil_sep_tl,
66     input~affiliation~separator .initial:n
67         = {;}
68 }

```

\prop_put:Nxx Internal variants and variables

\prop_put:Nnx

\seq_set_split:Nvn

\l__affiliations_tmpa_clist

\l__affiliations_tmpa_int

\l__affiliations_affiliations_seq

\l__affiliations_authors_seq

\l__affiliations_names_seq

\l__affiliations_tmpa_seq

\l__affiliations_tmpb_seq

\l__affiliations_tmpa_tl

\l__affiliations_tmpb_tl

\l__affiliations_output_prop

\l__affiliations_affiliations_prop

```

69 \cs_generate_variant:Nn \prop_put:Nnn { Nxx }
70 \cs_generate_variant:Nn \prop_put:Nnn { Nnx }
71 \cs_generate_variant:Nn \seq_set_split:Nnn { NVn }
72 \clist_new:N \l__affiliations_tmpa_clist
73 \int_new:N \l__affiliations_tmpa_int
74 \prop_new:N \l__affiliations_tmpa_prop
75 \seq_new:N \l__affiliations_affiliations_seq
76 \seq_new:N \l__affiliations_authors_seq
77 \seq_new:N \l__affiliations_names_seq
78 \seq_new:N \l__affiliations_tmpa_seq
79 \seq_new:N \l__affiliations_tmpb_seq
80 \tl_new:N \l__affiliations_tmpa_tl
81 \tl_new:N \l__affiliations_tmpb_tl
82 \prop_new:N \l__affiliations_output_prop
83 \prop_new:N \l__affiliations_affiliations_prop
84

```

(End definition for \prop_put:Nxx and others.)

\l__affiliations_icons_prop

The data for the circled mark style. Since this uses the \char, it is only available in LaTeX.

```

85 \prop_const_from_keyval:Nn \l__affiliations_icons_prop
86 {
87     0 = \char"2460, 1 = \char"2461, 2 = \char"2462, 3 = \char"2463,
88     4 = \char"2464, 5 = \char"2465, 6 = \char"2466, 7 = \char"2467,
89     8 = \char"2468, 9 = \char"2469, 10 = \char"246A, 11 = \char"246B,
90     12 = \char"246C, 13 = \char"246D, 14 = \char"246E, 15 = \char"246F,
91     16 = \char"2470, 17 = \char"2471, 18 = \char"2472, 19 = \char"2473
92 }

```

(End definition for \l__affiliations_icons_prop.)

_affiliations_resolve_affiliations: A helper macro to order affiliations. Is called by \affiliations_resolve:n.

```

93 \cs_new:Npn \_affiliations_resolve_affiliations: #1#2
94 {
95   \clist_clear:N \l__affiliations_tmpa_clist
96   \tl_if_empty:nTF {#2}
97   {
98     \prop_put:Nnn \l__affiliations_output_prop {#1} {}
99   }
100  {
101    \seq_set_split:NVn \l__affiliations_tmpa_seq
102      \l__affiliations_input_afil_sep_tl
103      { #2 }
104    \seq_map_inline:Nn \l__affiliations_tmpa_seq
105    {
106      \prop_get:NnNTF \l__affiliations_affiliations_prop
107        {##1}
108        \l__affiliations_tmpa_tl
109      {
110        \clist_put_right:NV \l__affiliations_tmpa_clist
111          \l__affiliations_tmpa_tl
112      }
113      {
114        %Not yet present
115        \clist_put_right:Nx \l__affiliations_tmpa_clist
116        {
117          \prop_count:N \l__affiliations_affiliations_prop
118        }
119        \prop_put:Nnx \l__affiliations_affiliations_prop {##1}
120        { \prop_count:N \l__affiliations_affiliations_prop }
121      }
122    }
123    \prop_put:NnV \l__affiliations_output_prop
124      {#1}
125      \l__affiliations_tmpa_clist
126  }
127 }

```

(End definition for _affiliations_resolve_affiliations:.)

_affiliations_output_affiliations: A helper macro that outputs the list of affiliations, usually below the list of authors.

```

128 \cs_new:Nn \_affiliations_output_affiliations:
129 {
130   \prop_map_inline:Nn \l__affiliations_affiliations_prop
131   {
132     \int_set:Nn \l__affiliations_tmpa_int { ##2 }
133     \str_case_e:nn { \l__affiliations_style_tl }
134     {
135       {alphabetic}
136       {
137         \textsuperscript{\int_to_alph:n{ \int_eval:n
138           { \l__affiliations_tmpa_int + 1 }
139         } }

```

```

140         }
141         {numeric}
142         { \textsuperscript{\int_eval:n {\l__affiliations_tmpa_int + 1} } }
143         {circled}
144         {
145             \prop_item:Nn \l__affiliations_icons_prop
146                         {\l__affiliations_tmpa_int}
147         }
148         {none} { }
149     }
150     ##1 ~
151 }
152 }

```

(End definition for `__affiliations_output_affiliations:.`)

`__affiliations_return_afil_text:n` A helper macro that returns the affiliation marks.

```

153 \cs_new:Npn \__affiliations_return_afil_text:n #1
154 {
155     \int_set:Nn \l__affiliations_tmpa_int { #1 }
156     \str_case_e:nn { \l__affiliations_style_tl }
157     {
158         {alphabetic}
159         {
160             \seq_put_right:Nx \l__affiliations_tmpb_seq
161                             { \int_to_alph:n{ \int_eval:n {#1 + 1} } }
162         }
163         {numeric}
164         {
165             \seq_put_right:Nx \l__affiliations_tmpb_seq
166                             { \int_eval:n {\l__affiliations_tmpa_int + 1} }
167         }
168         {circled}
169         {
170             \seq_put_right:Nx \l__affiliations_tmpb_seq
171                             { \prop_item:Nn \l__affiliations_icons_prop
172                                     { \l__affiliations_tmpa_int} }
173         }
174         {none} { }
175     }
176 }

```

(End definition for `__affiliations_return_afil_text:n`.)

`__affiliations_output_authors:` A helper macro to output the list of authors, with affiliation marks (if any).

```

177 \cs_new:Npn \__affiliations_output_authors:
178 {
179     \seq_clear:N \l__affiliations_tmpa_seq
180     \prop_map_inline:Nn \l__affiliations_output_prop
181     {
182         \seq_clear:N \l__affiliations_tmpb_seq
183         \clist_map_function:nN {##2} \__affiliations_return_afil_text:n
184         \tl_set:Nn \l__affiliations_tmpb_tl
185         {
186             \seq_use:Nn \l__affiliations_tmpb_seq

```

```

187         {\l__affiliations_afil_separator_tl}
188     }
189     \seq_put_right:Nx \l__affiliations_tmpa_seq
190     {
191         \tl_rescan:nn {} {##1}
192         \exp_not:N \textsuperscript{\tl_use:N \l__affiliations_tmpb_tl}
193     }
194 }
195 \seq_use:Nnnn \l__affiliations_tmpa_seq
196         {\l__affiliations_separator_between_two_tl}
197         {\l__affiliations_separator_between_mult_tl}
198         {\l__affiliations_separator_between_last_two_tl}
199 }

```

(End definition for _affiliations_output_authors:.)

\affiliations_resolve:n The main macro.

```

200 \cs_new:Npn \affiliations_resolve:n #1
201 {
202     \seq_set_split:NVn \l__affiliations_names_seq
203         \l__affiliations_input_names_sep_tl
204         { #1 }
205     \seq_map_inline:Nn \l__affiliations_names_seq
206     {
207         \seq_clear_new:N \l__affiliations_names_tmp_seq
208         \seq_set_split:Nnn \l__affiliations_names_tmp_seq { \affiliation }
209         { ##1 }
210         \prop_put:Nxx \l__affiliations_tmpa_prop
211         { \seq_item:Nn \l__affiliations_names_tmp_seq {1} }
212         { \seq_item:Nn \l__affiliations_names_tmp_seq {2} }
213     }
214     \bool_if:NTF \l__affiliations_output_affiliation_bool
215     {
216         \bool_if:NTF \l__affiliations_output_grouped_bool
217         {
218             \prop_map_function:NN \l__affiliations_tmpa_prop
219                 \_affiliations_resolve_affiliations:
220             \group_begin:
221                 \__affiliations_output_authors_font:
222                 \__affiliations_output_authors:
223             \group_end:\l[\dim_use:N \l__affiliations_separator_between_groups_dim]
224             \group_begin:
225                 \__affiliations_output_affiliation_font:
226                 \__affiliations_output_affiliations:
227             \group_end:
228         }
229         {
230             \seq_clear:N \l__affiliations_tmpa_seq
231             \prop_map_inline:Nn \l__affiliations_tmpa_prop
232             {
233                 \seq_put_right:Nx \l__affiliations_tmpa_seq
234                 {
235                     \group_begin:
236                     \exp_not:N \__affiliations_output_authors_font:

```

```

237         \tl_rescan:nn {} {##1}\[\dim_use:N \l__affiliations_separator_between_
238     \group_end:
239     \group_begin:
240         \exp_not:N \__affiliations_output_affiliation_font:
241         \tl_rescan:nn {} {##2}
242     \group_end:
243 }
244 }
245 \seq_use:Nnnn \l__affiliations_tmpa_seq
246     {\l__affiliations_separator_between_two_tl}
247     {\l__affiliations_separator_between_mult_tl}
248     {\l__affiliations_separator_between_last_two_tl}
249 }
250 }
251 {
252     \group_begin:
253     \__affiliations_output_authors_font:
254     \seq_clear:N \l__affiliations_tmpa_seq
255     \prop_map_inline:Nn \l__affiliations_tmpa_prop
256     {
257         \seq_put_right:Nx \l__affiliations_tmpa_seq
258             {\tl_rescan:nn {} {##1} }
259     }
260     \seq_use:Nnnn \l__affiliations_tmpa_seq
261         {\l__affiliations_separator_between_two_tl}
262         {\l__affiliations_separator_between_mult_tl}
263         {\l__affiliations_separator_between_last_two_tl}
264     \group_end:
265 }
266 }

(End definition for \affiliations_resolve:n.)

267 \endpackage

```