

Exploring the World of GenAI with Google AI Studio and Gemini




Suresh Peiris
Co-Founder at Inforwaves
GDG Organizer





Chamod Perera
SSE at Aleph Inc.
GDG Organizer & CNCF Ambassador




**A type of artificial
intelligence that
generates content
for you.**




What is an LLM?



Roses are red,




Roses are red,
Violets are blue,
Sugar is sweet,



```
for(var i = 0;
```

```
for(var i = 0; i < 10; i++) {
```


Modern LLMs are *large*



Classic Natural Language Problems



Entity extraction



Classification



Summarization




Sentiment Analysis




Translation



...



LLMs let us prototype *fast*



User:

Explain this joke: “I used to be addicted to soap, but I'm clean now.”

Model:

Model: The joke is a pun on the word "clean". It has two meanings:

To be free of dirt or other unwanted substances.

To be free of addiction.

The joke is funny because it is unexpected. The listener expects the speaker to be talking about the first meaning of "clean", but they are actually talking about the second meaning. This creates a surprise and a laugh.

User:

Give me five neat ideas for science fair projects.

Model:

1. **Build a volcano.**

This is a classic science fair project that is both fun and educational. You can learn about the science of volcanoes, earthquakes, and plate tectonics.

2. **Make a solar oven.**

This is a great project to learn about renewable energy and how to harness the power of the sun. You can use your solar oven to cook food, dry fruit, or even melt chocolate.

3. **Create a 3D printer.**

This is a more challenging project, but it is also very rewarding. You can learn about 3D printing technology and design your own custom objects.

4. **Build a robot.**

This is a great project for those who are interested in engineering and robotics. You can learn about basic electronics, mechanics, and programming.

5. **Design a water filtration system.**

This is a project that can help you learn about the importance of clean water and how to filter it. You can use your water filtration system to clean water from a stream or river.

Why are large language models different?






LLMs are characterized by **emergent abilities**, or the ability to perform tasks that were not present in smaller models.



LLMs contextual understanding of human language **changes how we interact** with data and intelligent systems.



LLMs can find patterns and connections in **massive, disparate data corpora**.



Google is the industry pioneer in AI


2015

Google DeepMind
AlphaGo defeats Go
champion



2016

Google's
DeepMind
helps detect
eye disease



2017

Google invents
Transformer
kickstarting LLM
revolution



2018

Google's
groundbreaking
large language
model, BERT



2019

Text-to-Text
Transfer
Transformer
LLM 10B P
Model Open
Sourced



2020

Google LaMDA
Model Trained
to converse



2022

AlphaFold predicts
structures of all
known proteins



2023

A conversational
AI Service
powered by
PaLM2



2024

Family of multimodal
LLMs & products



3,000

Researchers

7,000

Publications

Responsible AI



Built & Tested for
Safety



Upholds high scientific
standards



Socially Beneficial



Privacy in design




Accountable to People



Avoid creating unfair
bias


Multimodality




Welcome to
the Gemini era

The Gemini Ecosystem

The most advanced AI from Google



Getting started with the Gemini API



Get Started

Visit the cookbook: <https://github.com/google-gemini/cookbook>

Start developing:

1. Go to Google AI Studio.
2. Login with your Google account.
3. Create an API key.
4. Use a quickstart for Python, or call the REST API using curl.

SDKs

ai.google.dev

REST API + Client libraries for Python, Node, Java, and Swift



Vertex AI

Gemini API and Vertex AI

Both give access Gemini family models.

Vertex AI

Enterprise grade support.
Full MLOps (Examples: Model evaluation, monitoring, registry)




Vertex AI

Check it out when you're ready for production



ai.google.dev/docs/migrate_to_cloud

Usage Patterns



We'll cover

- Basic Prompting
- Code generation
- Search, retrieval and information synthesis
- Function calling
- Image understanding
- Tuning

Resources




Gemini Cookbook



Codelab Resources

Basic Prompting



aistudio.google.com

Write a poem about a magic backpack.

In a world of wonder, behold,
A backpack with tales yet untold.
Its fabric shimmers, alive with might,
A portal to realms, day and night.

aistudio.google.com

Write a poem about a magic backpack.

In a world of wonder, behold,
A backpack with tales yet untold.
Its fabric shimmers, alive with might,
A portal to realms, day and night.

...

Generate a short tip about JavaScript. Good tips are short and contain a code example showing the tip.

****Tip: Use `Array.prototype.flat()` to flatten an array of arrays.****

```
``javascript
```

```
const array = [[1, 2], [3, 4], [5, 6]];
```

```
console.log(array.flat());
```

```
// Output: [1, 2, 3, 4, 5, 6]
```

```
```
```

Generate a short tip about JavaScript. Good tips are short and contain a code example showing the tip.

**\*\*Tip: Use `Array.prototype.flat()` to flatten an array of arrays.\*\***

```
``javascript
```

```
const array = [[1, 2], [3, 4], [5, 6]];
```

```
console.log(array.flat());
```

```
// Output: [1, 2, 3, 4, 5, 6]
```

```
``
```

Generate a short tip about JavaScript. Good tips are short and contain a code example showing the tip.

**topic:** let and const

**tip:** Prefer using ``let`` and ``const`` to initialise variables, instead of ``var``, as ``var`` has no block scope or protection against mutability.

e.g. `const myVar = "EXAMPLE";`

**topic:** arrow syntax

**tip:**

## Prompting

Generate a short tip about JavaScript based on the provided topic. Good tips are short and contain a code example showing the tip.

3 / 500 examples

Actions ▾

| <input type="checkbox"/> INPUT topic:     | <input type="checkbox"/> OUTPUT tip:                                                                                                                                                                                                                     |
|-------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> let and const    | <p>Prefer using <code>'let'</code> and <code>'const'</code> to initialise variables, instead of <code>'var'</code>, as <code>'var'</code> has no block scope or protection against mutability.</p> <p>e.g.<br/><code>const myVar = "EXAMPLE";</code></p> |
| <input type="checkbox"/> arrow syntax     | <p>Use the arrow syntax <code>'=&gt;'</code> instead of defining anonymous functions. Your code will be clearer and easier to read.</p> <p>e.g.<br/><code>const doubles = input.map(x =&gt; x + x);</code></p>                                           |
| <input type="checkbox"/> template strings | <p>Template strings allow you to build multi-line strings using a template and variables from the outer scope.</p> <p>e.g.<br/><code>const emailHeader = `To: \${recipient}<br/>From: \${sender}<br/>Subject: Welcome!`;</code></p>                      |

The user's input

The model's response



```
import google.generativeai as genai
```

```
model = genai.GenerativeModel('models/gemini-pro')
```

```
resp = model.generate_content(
 'Write the first paragraph of a story about a magic backpack')
```

```
>>> print(resp.text)
```

In a bustling city, amidst the vibrant tapestry of human existence, there existed a peculiar entity named Archie. Archie, however, was no ordinary backpack...


```
chat = model.start_chat()
```

```
response = chat.send_message(
 "Hello, what should I have for dinner?")
```


```
print(response.text)
 # 'Here are some suggestions...'
```

```
response = chat.send_message(
 "How do I cook the first one?")
```

# Generate Content Request



# Generate Content Response



## Prompting

### Zero-shot prompting



Providing a single command to the LLM without any example

### One-shot prompting



Providing a single Example of the task to the LLM

### Few-shot prompting



Providing a few Examples of the task to the LLM

[https://ai.google.dev/docs/prompt\\_best\\_practices](https://ai.google.dev/docs/prompt_best_practices)

## Prompting



[flowers (0.5), trees (0.23), herbs (0.05), ..., bugs (0.03)]

Low




High

Temperature

- Select **high possibility** words.
- Use it when you expect a more "predictable" answer.

- Select **low possibility** words.
- Use it when you want to generate more "creative" content.

# Code Generation



# Code Generation

Generate code based on a user prompt

Convert human language requests to machine requests

Rapid tool building



Code generation

# Examples

- Generate data

Insert:  Image  Video  File  Folder

## Chat



User

Generate a table that has all the countries in the world listed alphabetically, their capitals, and what continent they belong to.

Model



| Country             | Capital          | Continent     |
|---------------------|------------------|---------------|
| Afghanistan         | Kabul            | Asia          |
| Albania             | Tirana           | Europe        |
| Algeria             | Algiers          | Africa        |
| Andorra             | Andorra la Vella | Europe        |
| Angola              | Luanda           | Africa        |
| Antigua and Barbuda | Saint John's     | North America |
| Argentina           | Buenos Aires     | South America |
| Armenia             | Yerevan          | Asia          |

# Examples

- Generate data
- Generate a SQL query



Generate a SQL query that will query for capitals in countries of Asia, following this format: Table countries, columns = [CountryID, CapitalID, Capital]

Model

```
SELECT c.Capital
FROM Capitals c
JOIN Countries co ON c.CountryID = co.CountryID
WHERE co.ContinentID = (
 SELECT ContinentID
 FROM Continents
 WHERE Continent = 'Asia'
);
```



Use code **with caution**.

SQL

# Examples

- Generate data
- Generate a SQL query
- Simulate Execution

What is the output from this command and table?

Model



The output of the following command:

```
SELECT c.Capital
FROM Capitals c
JOIN Countries co ON c.CountryID = co.CountryID
WHERE co.ContinentID = (
 SELECT ContinentID
 FROM Continents
 WHERE Continent = 'Asia'
);
```



Use code with caution.





SQL

when executed against the provided table data will be:

Kabul  
Yerevan  
Dhaka

# Examples

- Generate data
- Generate a SQL query
- Simulate Execution
- Quick coding help - Smart pair programmer.

Insert:  Image  Video  File  Folder

## Chat



Generate a Docker script to create a simple linux machine that has python 3.10 installed with following libraries: pandas, tensorflow, numpy

## Model



```
Create a new Dockerfile
FROM ubuntu:20.04

Update the package manager
RUN apt-get update -y

Install Python 3.10
RUN apt-get install -y python3.10

Install necessary libraries
RUN pip install pandas tensorflow numpy

Set the default Python version to 3.10
RUN update-alternatives --install /usr/bin/python python /usr/bin/python3.10 1

Copy the user's code to the container
WORKDIR /usr/src/app
COPY . .
```



Write a unit test for this Python function:

```
def is_diver_neutrally_buoyant(density_water, density_diver):
 """Check if a diver is neutrally buoyant."""
 if density_water == density_diver:
 return True
```

```
import unittest
```


```
class IsDiverNeutrallyBuoyantTest(unittest.TestCase):
```

```
 def test_diver_is_neutrally_buoyant(self):
 self.assertTrue(is_diver_neutrally_buoyant(1000, 1000))
```

```
 def test_diver_is_not_neutrally_buoyant(self):
 self.assertFalse(is_diver_neutrally_buoyant(1000, 1010))
```

```
 def test_invalid_input_types(self):
 with self.assertRaises(TypeError):
 is_diver_neutrally_buoyant("1000", 1000)
 with self.assertRaises(TypeError):
 is_diver_neutrally_buoyant(1000, "1000")
```

# Search and Information Synthesis



# BYO Data

- Models have knowledge cut-offs
- LLMs are not fact engines
- No exposure to private data

# Use the prompt's context window

- Instructions + Context + Question all in the prompt
- Easy to implement
  - No extra code, just ask.


```
model = genai.GenerativeModel('gemini-pro')
```

```
document = pathlib.Path('document.txt').read_text()
```


```
result = model.generate_content(f"""
 Explain how deep-sea life survives.
```

```
Please answer based on the following document:
```

```
{document}""")
```



# Function Calling





## Function Calling



What percentage of orders are returned?

## Function Calling



What percentage of orders are returned?



9.95% of orders are returned. This information comes from the `thelook_ecommerce.orders` table in BigQuery. The query used to calculate the return rate was:

```
SELECT ROUND((
 COUNT(DISTINCT IF(returned_at IS NOT NULL, order_id, NULL)) /
 COUNT(DISTINCT order_id)) * 100, 2)
AS return_rate
FROM thelook_ecommerce.orders
```

# Function Calling

- Describe external functions to the model.
- The model may ask **you** to call the function to help it respond to your queries.
- Endless possibilities for integrating external tools.

# Function calling - Basics

- How?
- The `google.generativeai` SDK will **inspect the function's type hints to determine the schema**.
- Allowed types are limited:

```
AllowedTypes = (
 int | float | str | bool | list | dict)
```

```
def multiply(a: float, b: float):
 """Returns a * b."""
 return a*b
```

```
model = genai.GenerativeModel(
 model_name='gemini-1.0-pro',
 tools=[multiply])
```

# Function calling - Basics

- Because function calling requires alternating turns, it's easiest to use through chat.
- Enable "automatic function calling" when you start a chat, and the `ChatSession` will call the function(s) for you.
  - You don't have to use automatic function calling, it just makes simple cases easier.

```
chat = model.start_chat(
 enable_automatic_function_calling=True)

response = chat.send_message(
 'I have 57 cats, each owns 44 mittens, '
 'how many mittens is that in total?')
```

```
chat = model.start_chat(
 enable_automatic_function_calling=True)

response = chat.send_message(
 'I have 57 cats, each owns 44 mittens, '
 'how many mittens is that in total?')

print(response.text)
The number of mittens in total is 2508.
```



# Function calling - Basics


- What happened? Use the chat history to find out.
- The chat history collects all the function calls and responses that took place.

```
for content in chat.history:
 part = content.parts[0]
 print(content.role, "->", type(part).to_dict(part))
```

```
for content in chat.history:
 part = content.parts[0]
 print(content.role, "->", type(part).to_dict(part))

user -> {'text': 'I have 57 cats, each owns 44 mittens, '
'how many mittens is that in total?'}
model -> {'function_call': {'name': 'multiply',
'args': {'a': 57.0, 'b': 44.0}}}
user -> {'function_response': {'name': 'multiply',
'response': {'result': 2508.0}}}
model -> {'text': ' The number of mittens in total is 2508.'}
```

# Function Calling interaction



# Function calling - More Examples

- Wikipedia research aid
  - Integrates a search tool.
  - Uses the Gemini API inside the function call to summarize pages.

```
def wikipedia_search(queries:list[str]) -> list[str]:
 ...
```

```
model = genai.GenerativeModel('gemini-pro', tools=[wikipedia_search])
```

```
chat = model.start_chat(enable_automatic_function_calling=True)
```

```
query = "Explain how deep-sea life survives."
```

```
res = chat.send_message(instructions.format(query=query))
```

```
model = genai.GenerativeModel('gemini-pro', tools=[wikipedia_search])

chat = model.start_chat(enable_automatic_function_calling=True)

query = "Explain how deep-sea life survives."

res = chat.send_message(instructions.format(query=query))

Searching for "How do deep-sea creatures survive the extreme pressure?"
Related search terms: ['Deep sea', 'Deep-sea community', 'Deep-sea fish']
Fetching page: "Deep sea"
Information Source: https://en.wikipedia.org/wiki/Deep_sea
Fetching page: "Deep-sea community"
Information Source: https://en.wikipedia.org/wiki/Deep-sea_community
Fetching page: "Deep-sea fish"
Information Source: https://en.wikipedia.org/wiki/Deep-sea_fish
Searching for "How do deep-sea creatures survive the cold temperatures?"
Related search terms: ['Deep-sea community', 'Deep sea', 'Deep-water coral']
Fetching page: "Deep-water coral"
Information Source: https://en.wikipedia.org/wiki/Deep_water_coral
```

# Function calling - More Examples

- SQL Talk
  - Use function calling to talk to a database.
  - Live example: <https://goo.gle/gemini-fn-call-sql>



```
sql_query_func = FunctionDeclaration(
 name="sql_query",
 description="Get information from data in BigQuery using SQL queries",
 parameters={
 "type": "object",
 "properties": {
 "query": {
 "type": "string",
 "description": "SQL query on a single line ...
```

## Function Calling



What percentage of orders are returned?



9.95% of orders are returned. This information comes from the `thelook_ecommerce.orders` table in BigQuery. The query used to calculate the return rate was:

```
SELECT ROUND((
COUNT(DISTINCT IF(returned_at IS NOT NULL, order_id, NULL)) /
COUNT(DISTINCT order_id)) * 100, 2)
AS return_rate
FROM thelook_ecommerce.orders
```

# Function calling - Schema

- Automatically building the schema from the type hints doesn't [currently 02/2024] work for everything.
- The allowed types are actually:

```
AllowedType= (
 int | float | str | bool |
 list['AllowedType'] |
 dict[str, 'AllowedType']
)
```

# Function calling - Schema

- Let's look at how the schema is constructed.

```
model = genai.GenerativeModel(
 model_name='gemini-1.0-pro',
 tools=[multiply])
```

```
model._tools.to_proto()
```

```
[function_declarations {
 name: "multiply"
 description: "returns a * b."
 parameters {
 type_: OBJECT
 properties {
 key: "b" value { type_: NUMBER }}
 properties {
 key: "a" value { type_: NUMBER }}
 required: "a" required: "b" }
 }
}]
```

# Function calling - Schema

- It's an OpenAPI schema, written as a `protobuf`.
- The protobuf-classes are available in the `google.ai.generativelanguage` client library.
- Reference docs:

<https://ai.google.dev/api/python/google/ai/generativelanguage/FunctionDeclaration>

```
import google.ai.generativelanguage as glm

calculator = glm.Tool(
 function_declarations=[
 glm.FunctionDeclaration(
 name='multiply',
 description="Returns the product of two numbers.",
 parameters=glm.Schema(
 type=glm.Type.OBJECT,
 properties={
 'a': glm.Schema(type=glm.Type.NUMBER),
 'b': glm.Schema(type=glm.Type.NUMBER)},
 required=['a', 'b']))])
```



# Function calling - Schema

- They can be written out as JSON-compatible objects as well.

```
calculator = {
 'function_declarations': [{
 'name': 'multiply',
 'description': 'Returns the product of two numbers.',
 'parameters': {
 'type': 'OBJECT',
 'properties': {
 'a': {'type': 'NUMBER'},
 'b': {'type': 'NUMBER'}},
 'required': ['a', 'b']}]}
```

```
model = genai.GenerativeModel(
 model_name='gemini-1.0-pro',
 tools=[calculator])
```

# Function calling - Structured data

- Structured data extraction.
- You *can* just ask the model to do it and return JSON.

```
response = model.generate_content(textwrap.dedent("""\
 Please return JSON describing the the people, places, things and relationships from this
 story using the following schema:

 {"people": list[PERSON], "places":list[PLACE], "things":list[THING], "relationships": list[RELATIONSHIP]}

 PERSON = {"name": str, "description": str, "start_place_name": str, "end_place_name": str}
 PLACE = {"name": str, "description": str}
 THING = {"name": str, "description": str, "start_place_name": str, "end_place_name": str}
 RELATIONSHIP = {"person_1_name": str, "person_2_name": str, "relationship": str}

 Here is the story:

 """) + story)
```

# Function calling - Structured data

- Asking for JSON often works.
- Function calling lets you strictly describe the schema.
- With a strict description, we can strictly enforce that that's what gets returned.


```
add_to_database = glm.FunctionDeclaration(
 name="add_to_database",
 description="Adds entities to the database.",
 parameters=glm.Schema(
 type=glm.Type.OBJECT,
 properties = {
 'people': glm.Schema(
 type=glm.Type.ARRAY,
 items=glm.Schema(
 type = glm.Type.OBJECT,
 properties = {
 'name': glm.Schema(type=glm.Type.STRING),
 'description': glm.Schema(type=glm.Type.STRING),
 'start_place_name': glm.Schema(type=glm.Type.STRING),
 'end_place_name': glm.Schema(type=glm.Type.STRING))}),
 'places': glm.Schema(
 ...
```

```
add_to_database = glm.FunctionDeclaration(
 name="add_to_database",
 description="Adds entities to the database.",
 parameters={
 "type": "OBJECT",
 "properties": {
 'people': {
 "type": "ARRAY",
 "items": {
 "type": "OBJECT",
 "properties": {
 'name': {"type": "STRING"},
 'description': {"type": "STRING"},
 'start_place_name': {"type": "STRING"},
 'end_place_name': {"type": "STRING"}})),
 'places': {...},
 ...
 }
 }
)
```



```
model = model = genai.GenerativeModel(
 model_name='gemini-1.0-pro',
 tools = [add_to_database])
```

# Image Understanding




# Image understanding

- Structured data extraction
- Image conditioning
- *RAG*

# Image conditioning

- Generate text or structured data from images



Name: Stickmancer  
Race: Human  
Class: Wizard  
Level: 1  
Strength: 10  
Dexterity: 14  
Stamina: 12  
Intelligence: 18  
Wisdom: 16  
Charisma: 10  
Equipment: Staff, Dagger, Robe

## Structured Data

### Dog Walking Application Form

Please provide some information about your dog:

Name: Fido  
Breed: Cavoodle  
Colour: Black & tan  
Age: 3 yrs  
Temperament: ☒ Friendly ☐ Shy ☐ Aggressive

And some information about yourself:


Name: Mark  
Phone: 0491 570 006






When would you like your dog walked:

Frequency: ☐ Once-off ☒ Regularly  
Days:

Monday:  
☐ Morning ☐ Afternoon  
Tuesday:  
☒ Morning ☐ Afternoon  
Wednesday:  
☒ Morning ☐ Afternoon  
Thursday:  
☒ Morning ☐ Afternoon  
Friday:  
☐ Morning ☐ Afternoon

## Structured Data

Img2Json 

Insert:  Image  Video  File  Folder  Test input

Please extract each of the fields in this form and provide a JSON representation:

**Dog Walking Application Form**

Please provide some information about your dog:

Name: Fido  
Breed: Cavoodle  
Colour: Black & Tan  
Age: 3  
Temperament: ☒ Friendly ☐ Shy ☐ Aggressive

And some information about yourself:

Name: Mark  
Phone: 0491 570 006

When would you like your dog walked:

Frequency: ☐ Once off ☒ Regularly

Days:


Monday  
☐ Morning ☐ Afternoon  
Tuesday  
☒ Morning ☐ Afternoon  
Wednesday  
☒ Morning ☐ Afternoon  
Thursday  
☒ Morning ☐ Afternoon  
Friday  
☐ Morning ☐ Afternoon

```
{
 "dog": {
 "name": "Fido",
 "breed": "Cavoodle",
 "colour": "Black & Tan",
 "age": 3,
 "temperament": "Friendly"
 },
 "owner": {
 "name": "Mark",
 "phone": "0491 570 006"
 },
 "schedule": {
 "frequency": "Regular",
 "days": [
 {

```


## Structured Data


### Img2Json Few Shot


 Image


Please convert the form into JSON.

1 / 500 examples

Actions 

| <input type="checkbox"/> | INPUT form:                                                                       | : | OUTPUT json:                                                                                                                                                                                                                                                                 | : |
|--------------------------|-----------------------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| <input type="checkbox"/> |  | : | <pre>'''json {   "dog": {     "name": "Fido",     "breed": "Cavoodle",     "colour": "Black &amp; Tan",     "age": 3,     "temperament": "Friendly"   },   "owner": {     "name": "Mark",     "phone": "0491 570 006"   },   "schedule": {     "frequency": "Regular",</pre> | : |

Test your prompt 

|   | INPUT form:                                                                        | OUTPUT json:      |
|---|------------------------------------------------------------------------------------|-------------------|
| 1 |  | Run to get output |

```
import enum
from pydantic import BaseModel

class DogApplication(BaseModel):
 """Represents an instance of a completed dog-walking application form."""
 dog: Dog
 owner: Customer
 schedule: Schedule

class Dog(BaseModel):
 name: str
 breed: str
 color: str
 age_years: float
 temperament: Temperament

class Customer(BaseModel):
 name: str
 phone: str

class Temperament(str, enum.Enum):
 FRIENDLY = 'friendly'
 SHY = 'shy'
 AGGRESSIVE = 'aggressive'

class Schedule(BaseModel):
 regular: bool
 days_and_times: list[str]
```



```
from llama_index.multi_modal_llms import GeminiMultiModal
from llama_index.multi_modal_llms.generic_utils import load_image_urls
from llama_index.program import MultiModalLLMCompletionProgram
from llama_index.output_parsers import PydanticOutputParser

images = load_image_urls(['https://goo.gle/dog-form-img'])
prompt = (
 "Please extract each of the fields in this "
 "form and provide a JSON representation: ")

Load the Gemini Pro Vision model.
gemini_llm = GeminiMultiModal(api_key=GOOGLE_API_KEY, model_name=PRO_VISION)
```

```
Build a callable that will map the images to the Pydantic schema.
image_to_application = MultiModalLLMCompletionProgram.from_defaults(
 output_parser=PydanticOutputParser(DogApplication),
 image_documents=images,
 prompt_template_str=prompt,
 multi_modal_llm=gemini_llm,
)
```

```
Image ORM!
```

```
form = image_to_application()
```

```
assert isinstance(form, DogApplication)
```

```
assert form.dog.name == 'Fido'
```

```
assert form.owner.name == 'Mark'
```

```
assert form.schedule.regular is True
```

```
assert 'Wednesday Morning' in form.schedule.days_and_times
```

```
pprint(form.dict())
```

```
{ 'dog': { 'age_years': 3.0,
 'breed': 'Cavoodle',
 'color': 'Black & Tan',
 'name': 'Fido',
 'temperament': <Temperament.FRIENDLY: 'friendly'> },
 'owner': { 'name': 'Mark', 'phone': '0491570006' },
 'schedule': { 'days_and_times': ['Monday Morning',
 'Tuesday Morning',
 'Wednesday Morning'],
 'regular': True }}
```

# Tuning

- Using the API:  
[https://ai.google.dev/tutorials/tuning\\_quickstart\\_python](https://ai.google.dev/tutorials/tuning_quickstart_python)

# Thank You!



**Suresh Peiris**  
Co-Founder at Inforwaves  
GDG Organizer



**Chamod Perera**  
SSE at Aleph Inc.  
GDG Organizer & CNCF Ambassador