安装要求

- 调试基础库 1.9.2
- 不校验合法域名 web-view 业务域名 TLS 版本以及 HTTPS 证书

获取代码

```
git clone https://github.com/chenbei360/pin.app.v6
```

修改配置

把根目录 config.js.bak 文件名 改成 config.js

config.js

```
var config =
{
    apiUrl: "http://test.pintuan-xcx.cn/api/",
    miniUrl: "http://test.pintuan-xcx.cn/mini/",

app: {
    url: "w5.pintuan-xcx.cn",
    name: "拼购",
    icon_url: "https://cdn.notestore.cn/w3/logo.png"
},

share_text: {
    title: '风靡全国的拼团商城,优质水果新鲜直供,快来一起"拼购"吧',
    path: 'pages/index'
}
};
```

app.json

```
"window": {
    "navigationBarTitleText": "拼购"
},
```

app.js

```
//app.js
function debugConsole(e) {
  console.log(e);
}
var loginCode = null,
  fileAir = require('./config.js');
App({
  onLaunch: function () {
    var that = this;
    wx.getStorage({
      key: 'userInfo',
      success: function (res) {
        that.globalData.userInfo = res.data;
      },
      fail: function (res) {
        debugConsole(res);
      }
    });
    wx.getSystemInfo({
      success: function (res) {
        debugConsole(res);
        that.globalData.windowHeight = res.windowHeight;
        that.globalData.windowWidth = res.windowWidth;
        that.globalData.device = res.model;
        if (res.model.search("iPhone X") != -1) {
          that.globalData.isIphonex = true;
        }
      },
    });
  },
  login: function (successCallback, failCallback) {
    var that = this;
    wx.login({
      success: res => {
        // 发送 res.code 到后台换取 openId, sessionKey, unionId
        if (res.code) {
          debugConsole("app wx.login success[" + res.code);
          loginCode = res.code;
```

```
that.getWxUserInfo(successCallback, failCallback);
      } else {
        debugConsole('获取用户登录态失败:' + res.errMsg);
     }
    },
    fail: function () {
      debugConsole('wx.login fail');
   }
 });
},
getUserInfo: function (successCallback, failCallback) {
  console.log("app.getUserInfo");
  var that = this;
  wx.checkSession({
    success: function () {
      if (!wx.getStorageSync("token")) {
        that.login(successCallback, failCallback);
        return;
      }
      if (that.globalData.userInfo == null) {
        wx.getStorage({
          key: 'userInfo',
          success: function (res) {
            that.globalData.userInfo = res.data;
            successCallback(that.globalData.userInfo);
          },
          fail: function (res) {
            that.login(successCallback, failCallback);
          }
        });
      } else {
        successCallback(that.globalData.userInfo);
      }
    },
    fail: function () {
      console.log("app.checkseesion fail");
      // 登录
      that.login(successCallback, failCallback);
     // 通知
      var tokenUtils = require('./utils/token.js')
      tokenUtils.run(function(){},function(){});
    },
```

```
complete: function () {
      console.log("app.checksession complete");
    }
  });
},
getWxUserInfo: function (successCallback, failCallback) {
  var that = this;
  wx.getUserInfo({
    success: res => {
      debugConsole("app wx.getUserInfo success");
      if (that.isLogining) {
        return;
      }
      that.isLogining = true;
      wx.request({
        url: this.globalData.miniUrl + "v1.0/login",
        data: {
          code: loginCode,
          rawData: res.rawData,
          signature: res.signature,
          iv: res.iv,
          encryptedData: res.encryptedData
        },
        success: function (respone) {
          debugConsole(respone);
          that.globalData.userInfo = res.userInfo
          if (respone.data.result == 'ok') {
            wx.setStorage({
              key: "userInfo",
              data: res.userInfo
            });
            wx.setStorage({
              key: 'token',
              data: respone.data.token,
              success: function () {
                successCallback(res.userInfo);
              }
            });
```

```
}
          },
          complete: function (res) {
            that.isLogining = false;
          }
        });
      },
      fail: function () {
        debugConsole("app wx.getUserInfo fail");
      },
      complete: function (e) {
        debugConsole("app wx.getUserInfo complete");
        debugConsole(e);
        if (e.errMsg != "getUserInfo:ok") {
          failCallback();
        }
      }
    });
  },
  getImageUrlInfo: function (page,image url, loadingCallback, successCallback,
failCallback) {
    var that = this, image_url_c = "image_" + image_url,image_w_h =
wx.getStorageSync(image_url_c);
    if(image_w_h){
      successCallback(image_w_h)
    }else{
      loadingCallback();
      const ImgLoader = require('/libs/img-loader/img-loader.js')
      page.imgLoader = new ImgLoader(page);
      page.imgLoader.load(image_url, function (err, imgs) {
        image w h = imgs.ev.detail;
        wx.setStorageSync(image_url_c,image_w_h);
        successCallback(image_w_h);
      });
    }
  },
/***
* 计算宽高
  wxAutoImageCal: function (originalWidth, originalHeight) {
    var windowWidth = , windowHeight = ;
    var autoWidth = , autoHeight = ;
    var results = {};
    windowWidth = this.globalData.windowWidth;
    windowHeight = this.globalData.windowHeight;
```

```
if (originalWidth > windowWidth) {
      autoWidth = windowWidth;
      autoHeight = (autoWidth * originalHeight) / originalWidth;
      results.imageWidth = autoWidth;
      results.imageheight = autoHeight;
    } else {
      results.imageWidth = originalWidth;
      results.imageheight = originalHeight;
    debugConsole(results);
    return results;
 },
 share: function (data) {
    var share_text = this.globalData._.config.share_text,
    share_type = '分享给好友',
    that = this,
    path = data.path || share_text.path,
    title = data.title || share_text.title;
    return {
      title: title,
      path: path,
     withShareTicket: true,
      success: function (res) {
       if (res.shareTickets != undefined && res.shareTickets.length > ) share_type = "分
享给群聊";
        that.handlerShare(share_type, 1, path);
      },
      fail: function (res) {
        that.handlerShare(share_type, , path);
      }
    }
 },
 handlerShare(share_type, share_status, path) {
    var token = wx.getStorageSync("token");
    wx.request({
      url: this.globalData.apiUrl + 'v1.0/users/share',
      method: "POST",
      data: {
        share_type: share_type,
        share_status: share_status,
        share_url: path
      },
      header: {
        'AccessToken': token
      }
```

```
});
  },
  urlEncode(param, key, encode) {
   if (param == null) return '';
   var paramStr = '';
   var t = typeof (param);
    if (t == 'string' || t == 'number' || t == 'boolean') {
      paramStr += '&' + key + '=' + ((encode == null || encode) ?
encodeURIComponent(param) : param);
    } else {
      for (var i in param) {
        var k = key == null ? i : key + (param instanceof Array ? '[' + i + ']' : '.' +
i)
        paramStr += this.urlEncode(param[i], k, encode)
      }
    }
   return paramStr;
 },
  goHome: function () {
   wx.switchTab({
      url: './index',
   });
  },
  goOrders: function () {
    wx.switchTab({
      url: './orders',
   });
  },
  globalData: {
    userInfo: null,
    isIphonex: false,
    apiUrl: fileAir.config.apiUrl,
    miniUrl: fileAir.config.miniUrl,
    device: "",
    windowHeight: "",
    windowWidth: "",
    _: fileAir
  }
})
```

app.json

```
{
  "pages": [
    "pages/index",
    "pages/groups",
    "pages/orders",
    "pages/checkout",
    "pages/personal",
    "pages/goods",
    "pages/addresses",
    "pages/address",
    "pages/order",
    "pages/group",
    "pages/webview",
    "pages/develop/goods",
    "pages/backup/goods"
  ],
  "window": {
    "backgroundColor": "#fff",
    "navigationBarBackgroundColor": "#FF4C42",
    "navigationBarTextStyle": "white",
    "navigationBarTitleText": "拼购"
  },
  "tabBar": {
    "backgroundColor": "#FFF",
    "selectedColor": "#FF4C42",
    "color": "#777",
    "list": [
        "pagePath": "pages/index",
        "text": "首页",
        "iconPath": "./images/home.png",
        "selectedIconPath": "./images/select_home.png"
      },
        "pagePath": "pages/groups",
        "text": "我的团",
        "iconPath": "./images/groups.png",
        "selectedIconPath": "./images/select_groups.png"
      },
        "pagePath": "pages/orders",
        "text": "我的订单",
```

```
"iconPath": "./images/orders.png",
"selectedIconPath": "./images/select_orders.png"
},
{
"pagePath": "pages/personal",
       "text": "我的",
       "iconPath": "./images/personal.png",
       "selectedIconPath": "./images/select personal.png"
}
]
},
"networkTimeout": {
"request": 10000,
"downloadFile": 10000
},
"debug": false
}
```

config.js

```
var config =
{
 apiUrl: "http://test.pintuan-xcx.cn/api/",
 miniUrl: "http://test.pintuan-xcx.cn/mini/",
 app: {
   url: "pintuan-xcx.cn",
   name: "拼购",
   icon_url: "//pintuan-xcx.cn/v1.0/logo.png"
 },
 share_text: {
   title: '风靡全国的拼团商城,优质水果新鲜直供,快来一起"拼购"吧',
   path: 'pages/index'
 },
 error_text: {
   : "服务器可能中暑了,请稍后再试",
   1: "您还没有填写收货信息哦~",
   2: "Oops! 这个团已经不在地球上了,快去首页火拼吧!",
   3: "您还没有参加过任何团哦,赶快去首页火拼吧!",
   4: "商品已下架或不存在,赶快去首页看看吧!",
   5: "您的地址信息不完整,请先完善地址信息吧~",
   6: "订单信息错误~",
```

```
7: "暂时没有物流信息",
 8: "获取快递信息失败,请稍后再试",
 9: "获取订单失败,请稍后再试!",
 10: "您还没有优惠券哦~",
 11: "您还没有填写联系人信息哦~~"
},
order_status: {
 : "待支付",
 1: "已支付,未确认",
 2: "已确认,待发货",
 3: "配送中",
 4: "已签收",
 5: "交易已取消",
 6: "未发货退款处理中",
 7: "未发货退款成功",
 8: "已发货退款处理中",
 9: "已发货退款成功"
},
page_offset: ,
page_size: 30,
pullload_text: {
 load_text: "正在玩命的加载...",
 no_orders: "没有更多的订单了...",
 no_tuan_orders: "没有更多的团订单了...",
 no_goods: "没有更多了..."
},
pullload_last_text: {
 bottom_text: "继续向上滑将切换到下一个频道",
 bottom_text_ready_to_next_channel: " 松开按键切换到下一个频道",
 change_channel_tip: "正在加载下一个频道"
},
tuan_status: {
 : {
   desc: "团购进行中",
   tips_title: {
     : "快来入团吧",
    1: "入团成功",
    2: "开团成功"
   },
   tips_detail: {
```

```
: "就差你了",
    1: "快去邀请好友加入吧",
     2: "快去邀请好友加入吧"
   }
 },
 1: {
   desc: "团购成功",
   tips_title: {
    : "来晚了一步!该团已被挤爆",
    1: "团购成功",
    2: "团购成功"
   },
   tips_detail: {
    : "求人不如求自己,自己当团长吧!",
    1: "我们会尽快为您发货,请耐心等待",
    2: "我们会尽快为您发货,请耐心等待"
   }
 },
 2: {
   desc: "团购失败",
   tips_title: {
    : "来晚了一步!",
    1: "团购失败",
    2: "团购失败"
   },
   tips_detail: {
    : "",
    1: "",
    2: ""
  }
 }
},
group_text: {
: "还差%s人组团成功",
1: "我也要参团",
2: "我也开个团,点此回商品列表。"
},
pay_text: {
 success: "支付成功",
 fail: "支付失败",
cancel: "支付未完成 , 请重新支付"
},
// mall_service: [
```

```
// type: "全场包邮",
// desc: "所有商品均无条件包邮"
// },
// {
// type: "7天退换",
// desc: "满足相应条件时,消费者可申请7天无理由退换货"
// },
// {
// type: "48小时发货",
// desc: "若超时未发货,消费者将会收到至少3元无门槛代金券"
// }
// ],
group_image_url: "//pintuan-xcx.cn/v1.0/avatar_4_64.png"
};
module.exports = {
config: config
}
```

project.config.json

```
{
    "description": "项目配置文件。",
    "packOptions": {
        "ignore": []
    },
    "setting": {
        "urlCheck": false,
        "es6": true,
        "postcss": true,
        "minified": true,
        "newFeature": true,
        "autoAudits": false
    "compileType": "miniprogram",
    "libVersion": "1.9.4",
    "appid": "",
    "projectname": "weipin6",
    "isGameTourist": false,
    "condition": {
        "search": {
            "current": -1,
            "list": []
        },
```

```
"conversation": {
    "current": -1,
    "list": []
},
"plugin": {
    "current": -1,
    "list": []
},
"game": {
    "currentL": -1,
    "list": []
},
"miniprogram": {
    "current": 3,
    "list": [
        {
            "id": ,
            "name": "个人中心",
            "pathName": "pages/personal",
            "query": ""
        },
        {
            "id": 1,
            "name": "商品详情",
            "pathName": "pages/goods",
            "query": "goods_id=340"
        },
        {
            "id": -1,
            "name": "新增地址",
            "pathName": "pages/address",
            "query": ""
        },
        {
            "id": 3,
            "name": "确认订单",
            "pathName": "pages/checkout",
            "query": "goods_id=340&sell_type=1"
        },
        {
            "id": -1,
            "name": "地址列表",
            "pathName": "pages/addresses",
            "query": ""
        },
        {
            "id": -1,
            "name": "订单列表",
            "pathName": "pages/orders",
```

```
"query": ""
               },
                   "id": 7,
                   "name": "订单详情",
                   "pathName": "pages/order",
                   "query": "id=14"
                   "id": -1,
                   "name": "团列表",
                   "pathName": "pages/groups",
                   "query": ""
                   "id": 8,
                   "name": "团详情",
                   "pathName": "pages/group",
                   "query": "id=14"
                   "id": 9,
                   "name": "确认订单",
                   "pathName": "pages/checkout",
                   "query": "goods_id=340&sell_type=1"
                   "id": -1,
                   "name": "网页",
                   "pathName": "pages/webview",
                   "query": "url="
]
}
}
}
```

address.js

```
// pages/address.js
//获取应用实例
const app = getApp(), addressEnglishNames = ['HOME', 'WORK'],addressChinaNames = ['家庭', '公司'];
var addressId = , goodsId = , sellType = , dataVersion = 
wx.getStorageSync('data_version'), serveDataVersion, regions =
```

```
wx.getStorageSync('regions');
Page({
 data: {
    old_value: "",
    isLoading: true,
    isOperate: false,
    adTypes: addressChinaNames,
    adTypeIdx: ,
    showAuthModal: false,
    addressNames: addressEnglishNames
 },
 // 数据版本
 loadDataVersion: function (successCallback, failCallback) {
    var that = this;
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/project/data_version?type=region_list',
      success: function (res) {
        serveDataVersion = res.data.data_version.version;
        successCallback();
      },
      fail: function (res) {
        failCallback();
      },
      complete: function (res) {
   });
 },
 laodRegions: function (successCallback, failCallback) {
    var that = this;
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/project/regions',
      success: function (res) {
        regions = res.data.regions;
        successCallback();
      },
      fail: function (res) {
        failCallback();
      },
      complete: function (res) {
      }
   });
 },
 loadAddress: function (successCallback, failCallback) {
    var that = this;
```

```
wx.request({
    url: app.globalData.apiUrl + "v1.0/users/address/" + addressId,
    header: {
      'AccessToken': wx.getStorageSync("token")
    },
    success(res) {
      successCallback(res);
    },
    fail: function (res) {
     failCallback();
    },
    complete: function (res) {
      that.setData({ isLoading: false, isOperate: false });
    }
 });
},
loadData: function() {
  var that = this;
  app.getUserInfo(function (res) {
  }, function () {
   that.setData({
      showAuthModal: true,
   });
  });
  that.loadDataVersion(function(){
    if (dataVersion != serveDataVersion){
      that.laodRegions(function(){
        wx.setStorageSync('data_version', serveDataVersion),
        wx.setStorageSync('regions', regions);
        if (addressId){
          that.loadAddressEvent();
        } else {
          that.setData({ isLoading: false }),
          that.initProvince();
        }
      },function(){});
    }else{
```

```
if (addressId) {
        that.loadAddressEvent();
      } else {
        that.setData({ isLoading: false }),
        that.initProvince();
      }
    }
  },function(){});
},
loadAddressEvent: function() {
  var that = this:
  that.loadAddress(function (res) {
    var adTypeIdx = ;
    if (res.data.address.address_name == that.data.addressNames[]) {
      adTypeIdx =
    } else if (res.data.address.address_name == that.data.addressNames[1]) {
      adTypeIdx = 1;
    }
    var provinceId = res.data.address.province_id,
      cityId = res.data.address.city_id,
      areaId = res.data.address.district_id,
      provinces = [{ 'region_name': '选择省份' }],
      citys = [{ "region_name": "选择城市" }],
      areas = [{ "region_name": "选择地区" }],
      area = regions[3],
      city = regions[2],
      provinceIdx, areaIdx, cityIdx;
    regions[1].map(function (province) {
      provinces.push(province);
    });
    for (var ii = ; ii < city.length; ii++) {</pre>
      if (provinceId == city[ii].parent_id) {
        citys.push(city[ii]);
      }
    }
    for (var iii = ; iii < area.length; iii++) {</pre>
      if (cityId == area[iii].parent_id) {
        areas.push(area[iii]);
      }
    }
```

```
for (var ii = ; ii < citys.length; ii++) {</pre>
        if (cityId == citys[ii].region_id) {
          cityIdx = ii;
          break;
       }
      for (var iiii = ; iiii < areas.length; iiii++) {</pre>
        if (areaId == areas[iiii].region id) {
          areaIdx = iiii;
          break;
       }
      for (var ii = ; ii < provinces.length; ii++) {</pre>
        if (provinceId == provinces[ii].region_id) {
          provinceIdx = ii;
          break:
        }
      }
      that.setData({ provinces: provinces, citys: citys, areas: areas, address:
res.data.address, old_value: [provinceIdx, areaIdx, cityIdx], adTypeIdx: adTypeIdx});
    }, function () {
   });
 },
 handlerAddress: function (addressData, url, method, successCallback, failCallback) {
    var that = this;
    if (this.data.isOperate)
     console.log("快");
     return true;
    }
    this.setData({isLoading: true,isOperate: true});
    wx.request({
      url: url,
        'AccessToken': wx.getStorageSync("token")
      },
      method: method,
      data: addressData,
      success(res) {
        successCallback(res);
```

```
},
    fail: function (res) {
      failCallback();
    },
    complete: function (res) {
      that.setData({isLoading: false,isOperate: false});
    }
 });
},
//添加地址 || 或者修改地址
listenFormSubmit: function (e) {
  var that = this;
  var formData = e.detail.value;
  if (!formData.receive_name.trim()) {
   this.setData({ 'receive_name_tip': true });
  } else {
   this.setData({ 'receive_name_tip': false });
  if (!formData.mobile.trim()) {
   this.setData({ 'mobile_tip': true });
  } else {
   this.setData({ 'mobile_tip': false });
  }
  if (!/^\d{11}$/.test(formData.mobile.trim())) {
   this.setData({ 'mobile_tip': true });
  } else {
   this.setData({ 'mobile_tip': false });
  }
  if (!formData.address_name.trim()) {
   this.setData({ 'adType_tip': true });
  } else {
   this.setData({ 'adType_tip': false });
  }
  if (!formData.province.trim()) {
   this.setData({ 'province_tip': true });
  } else {
    this.setData({ 'province_tip': false });
  }
```

```
if (!formData.city.trim() && !this.data.province_tip) {
     this.setData({ 'city_tip': true });
   } else {
     this.setData({ 'city_tip': false });
   }
   if (!formData.district.trim() && !this.data.city_tip && !this.data.province_tip) {
     this.setData({ 'district_tip': true });
   } else {
     this.setData({ 'district_tip': false });
   }
   if (!formData.address.trim()) {
     this.setData({ 'adinfo_tip': true });
   } else {
     this.setData({ 'adinfo_tip': false });
   }
    if (this.data.receive_name_tip || this.data.mobile_tip || this.data.province_tip ||
this.data.city_tip || this.data.district_tip || this.data.adType_tip ||
this.data.adinfo_tip) {
     return false;
   }
   var url = "./addresses", goOrder = goodsId && goodsId != "undefined" && sellType &&
sellType != "undefined";
   if (goOrder)
     url += "?goods_id=" + goodsId,
     url += "&sell_type=" + sellType;
   }
   if (!addressId) {
      this.handlerAddress(formData, app.globalData.apiUrl + "v1.0/users/address", "POST"
      ,function (res){
       if (res.data.result == 'ok'){
          if (goOrder){
            url += "&address_id=" + res.data.address_id;
          }
        }
        wx.redirectTo({
          url: url,
        });
      },function(){
```

```
});
    } else {
      this.handlerAddress(formData, app.globalData.apiUrl + "v1.0/users/address/" +
addressId, "PUT"
      , function (res) {
        if (goOrder){
          url += "&address_id=" + addressId;
        wx.redirectTo({
          url: url,
        });
      }, function () {
     });
    }
 },
 initProvince: function() {
    var provinces = [{ 'region_name': '选择省份' }];
    var citys = [{ "region_name": "选择城市" }];
    var areas = [{ "region_name": "选择地区" }];
    regions[1].map(function (province){
      provinces.push(province);
    this.setData({ provinces: provinces, citys: citys, areas: areas });
 },
 areaPickerChange: function (e) {
    var province idx = e.detail.value[],
      city_idx = e.detail.value[1],
     district_idx = e.detail.value[2],
     citys = [],
     areas = [],
      province_id,
      city,
     area,
      city_id;
   // 省份
    if (e.detail.value[] != this.data.old_value[]) {
      citys = [{ "region_name": "选择城市" }],
      areas = [{ "region_name": "选择地区" }];
      if (this.data.provinces[province_idx].region_id != undefined) {
        province_id = this.data.provinces[province_idx].region_id,
        city = regions[2];
        for (var ii = ; ii < city.length; ii++) {</pre>
```

```
if (province_id == city[ii].parent_id) {
        citys.push(city[ii]);
      }
    }
  }
  this.setData({ old_value: [province_idx, , ] });
  this.setData({ citys: citys, areas: areas });
  if (this.data.provinces[this.data.old_value[]].region_id) {
   this.setData({ 'province_tip': false });
  } else {
  }
  return;
}
//城市
if (e.detail.value[1] != this.data.old_value[1]) {
  areas = [{ "region_name": "选择地区" }];
  if (this.data.citys[city_idx] != undefined) {
    city_id = this.data.citys[city_idx].region_id,
    area = regions[3];
    for (var ii = ; ii < area.length; ii++) {</pre>
      if (city_id == area[ii].parent_id) {
        areas.push(area[ii]);
      }
    }
    this.setData({ old_value: [province_idx, city_idx, ] });
    this.setData({ areas: areas });
    if (this.data.citys[this.data.old_value[1]].region_id) {
      this.setData({ 'city_tip': false });
    } else {
    }
    return;
  }
if (e.detail.value[2] != this.data.old_value[2]) {
  this.setData({ old_value: [province_idx, city_idx, district_idx] });
}
if (this.data.areas[this.data.old_value[2]].region_id) {
  this.setData({ 'district_tip': false });
} else {
}
```

```
},
adTypesChange: function (e) {
 var adTypeIdx = e.detail.value;
 this.setData({
    adTypeIdx: adTypeIdx
 })
},
finish: function (e) {
  if (!this.data.old_value[]) {
    this.setData({ "province_tip": true });
    return false;
  } else {
    if (this.province_tip)
      this.setData({ "province_tip": false });
  }
  if (!this.data.old_value[1]) {
    this.setData({ "city_tip": true });
    return false;
  } else {
    if (this.city_tip) this.setData({ "city_tip": false });
  if (!this.data.old_value[2]) {
    this.setData({ "district_tip": true });
   return false;
  } else {
    if (this.district_tip) this.setData({ "district_tip": false });
  this.closeRegion();
},
receive_function: function (e) {
  if (!e.detail.value.trim()) {
   this.setData({ 'receive_name_tip': true });
  } else {
    this.setData({ 'receive_name_tip': false });
  }
},
mobile_function: function (e) {
  if (!e.detail.value.trim()) {
    this.setData({ 'mobile_tip': true });
  } else {
    this.setData({ 'mobile_tip': false });
  }
```

```
if (!/^\d{11}$/.test(e.detail.value.trim())) {
     this.setData({ 'mobile_tip': true });
   } else {
     this.setData({ 'mobile_tip': false });
 },
 adinfo_function: function (e) {
   if (!e.detail.value.trim()) {
     this.setData({ 'adinfo_tip': true });
   } else {
     this.setData({ 'adinfo_tip': false });
   }
 },
 onLoad: function (options) {
   addressId = this.options.address_id,
   goodsId = this.options.goods_id,
   addressId = this.options.address id,
   sellType = this.options.sell_type;
   wx.setNavigationBarTitle({
     title: addressId ? '编辑地址' : '添加新地址'
   })
   this.loadData();
 },
 openRegion: function (e) {
   this.setData({
      isRegionOpen: true
   })
 },
 closeRegion: function (e) {
   this.setData({
      isRegionOpen: false
   })
 },
 deleteAddressEvent: function(e) {
   var that = this,url = "./addresses", goOrder = goodsId && goodsId != "undefined" &&
sellType && sellType != "undefined";
   console.log(goodsId)
   that.cancelCallback = function () {
      that.setData({ showWinpopModal: true });
```

```
},
  that.confirmCallback = function () {
    that.setData({ isLoading: true, isOperate: true });
    wx.request({
      url: app.globalData.apiUrl + "v1.0/users/address/" + addressId,
      method: "DELETE",
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      success(res) {
        if (res.data.result == 'ok') {
          if (goOrder) {
            url += "?sell_type=" + sellType + "&goods_id="
              + goodsId + "&address_id=" + addressId;
          }
          wx.redirectTo({
            url: url,
          });
        }
      },
      fail: function (res) {
      },
      complete: function (res) {
        that.setData({ isLoading: false, isOperate: false })
      }
    });
  },
  that.setData({ showWinpopModal: true, winpopContent: "确定删除这个地址吗?" })
},
onReady: function () {
},
onShow: function () {
},
```

```
onHide: function () {

},

onUnload: function () {

},

onPullDownRefresh: function () {

},

onReachBottom: function () {

}
```

address.json

```
"navigationBarTitleText": " ",
    "enablePullDownRefresh": true,
    "navigationBarBackgroundColor": "#F8F8F8",
    "navigationBarTextStyle": "black",
    "usingComponents": {
        "page-loading": "../../component/page-loading/page-loading",
        "net-error-tips": "../../component/net-error-tips/net-error-tips",
        "auth-dialog": "../../component/auth-dialog/auth-dialog",
        "winpop-mask": "../../component/winpop-mask/winpop-mask"
    }
}
```

address.wxml

```
<page-loading isLoading="{{isLoading}}" isOperate="{{isOperate}}"></page-loading>
```

```
<view class="body" wx:if="{{!isLoading || isOperate}}">
    <view class="div mod_container">
        <view class="div wx bar">
        <view class="div wx bar back">
            <navigator id="back" url="javascript:void(0);"></navigator>
        <view class="div wx_bar_tit">收货地址</view>
    </view>
        <form bindsubmit="listenFormSubmit" bindreser="listenFormReser" report-</pre>
submit="true">
        <view class=" div wx wrap">
            <view class="address_new">
                <view class="p">
                     <label for="name"><view class="span tit">收货人</view>
                         <input id="name" name="receive_name"</pre>
value="{{address.receive_name}}" placeholder="名字" type="text"
bindblur='receive_function' placeholder-class="i_placeholder"/>
                         <view class="span" id="updateTip1" style="color: #F43530;</pre>
{{!receive_name_tip ? 'display: none;' : ''}}">请填写姓名</view>
                     </label>
                </view>
                <view class="p">
                     <label for="mobile"><view class="span tit">手机号码</view>
                         <input id="mobile" name="mobile" value="{{address.mobile}}"</pre>
placeholder="手机号码" type="number" bindblur='mobile function' placeholder-
class="i placeholder"/>
                         <view class="span" id="updateTip2" style="color: #F43530;</pre>
{{!mobile_tip ? 'display: none;' : ''}}">请填写正确的手机号</view>
                     </label>
                </view>
                <view class="p">
                     <label><view class="span tit">选择地区</view>
                         <view class="input __border</pre>
{{provinces[old_value[0]].region_name ? '' : 'i_placeholder'}}" id="address_text"
name="address_text" bindtap="openRegion">
                             <block wx:if="{{provinces[old_value[0]].region_name}}">
 \{\{provinces[old\_value[0]].region\_name\}\} \ \{\{citys[old\_value[1]].region\_name\}\} 
{{areas[old_value[2]].region_name}}</block>
                             <br/>
<br/>
dlock wx:else>选择地区</block>
                         </view>
                         <input disabled="true" name="province"</pre>
value="{{provinces[old value[0]].region id}}" class="hide"/>
                         <input disabled="true" name="city"</pre>
value="{{citys[old_value[1]].region_id}}" class="hide"/>
```

```
<input disabled="true" name="district"</pre>
value="{{areas[old_value[2]].region_id}}" class="hide"/>
                         <view class="span" id="updateTip2" style="color: red;</pre>
{{!province_tip ? 'display: none;':'}}">请填写正确的省</view>
                         <view class="span" id="updateTip2" style="color: red;</pre>
{{!city tip ? 'display: none;' : ''}}">请填写正确的市</view>
                         <view class="span" id="updateTip2" style="color: red;</pre>
{{!district tip ? 'display: none;':'}}">请填写正确的区</view>
                    </label>
                </view>
                <view class="p" id="adType">
                     <view class="label" for="adType"><view class="span tit">地址类
别</view>
                         <picker bindchange="adTypesChange" value="{{adTypeIdx}}"</pre>
range="{{adTypes}}" class='__border'>
                         <!-- i placeholder -->
                             <view class="picker">
                                 {{adTypes[adTypeIdx]}}
                                 <input disabled="true" name="address_name"</pre>
value="{{addressNames[adTypeIdx]}}" class="hide"/>
                             </view>
                         </picker>
                         <view class="span" id="updateTip7" style="color: #F43530;</pre>
{{!adType_tip ? 'display: none;' : ''}}">请选择家庭/公司</view>
                     </view>
                </view>
                <view class="p">
                    <view class="label" for="adinfo"><view class="span tit">详细地
址</view>
                         <input id="adinfo" name="address" value="{{address.address}}"</pre>
placeholder="详细地址" type="text" bindblur='adinfo function' placeholder-
class="i placeholder"/>
                         <view classs="span" id="updateTip6" style="color: #F43530;</pre>
{{!adinfo_tip ? 'display: none;' : ''}}">请填写详细地址</view>
                    </view>
                </view>
                <view class="p action">
                     <button class="submit" id="add" formType="submit">确认</button>
                    <block wx:if="{{address.address_id}}">
                        <button class="submit hidden" style="background-color: #F43530;"</pre>
id="deletes" bindtap="deleteAddressEvent" data-address_id="{{address.address_id}}">删
除</button>
```

```
</block>
                 </view>
                 <!-- start -->
                 <view class="address_select" style="{{isRegionOpen ? '' :</pre>
'display:none;'}}">
                     <view class="area_ctrl slideInUp" catchtap="stopclose">
                     <view class="div area btn box">
                         <view class="div area btn larea cancel" bindtap="close"</pre>
style="visibility:hidden;">取消</view>
                         <view class="div area_btn larea_finish" bindtap="finish">完成
                         </view>
                     </view>
                     <picker-view bindchange="areaPickerChange" value="{{old_value}}"</pre>
wx:if="{{isRegionOpen}}">
                         <picker-view-column class="selectItem">
                              <view class="tooth" wx:for="{{provinces}}"</pre>
wx:key="index">{{item.region_name}}</view>
                         </picker-view-column>
                         <picker-view-column class="selectItem">
                              <view class="tooth" wx:for="{{citys}}"</pre>
wx:key="index">{{item.region_name}}</view>
                         </picker-view-column>
                         <picker-view-column class="selectItem">
                              <view class="tooth" wx:for="{{areas}}"</pre>
wx:key="index">{{item.region_name}}</view>
                         </picker-view-column>
                     </picker-view>
                 </view>
                 <!-- end -->
           </view>
            </view>
        </view>
        </form>
    </view>
</view>
<auth-dialog showAuthModal="{{showAuthModal}}" bind:confirm="loadData"></auth-dialog>
<winpop-mask showWinpopModal="{{showWinpopModal}}" winpopContent="{{winpopContent}} "</pre>
bind:cancelCallback="cancelCallback" bind:confirmCallback="confirmCallback"></winpop-</pre>
mask>
```

addresses.js

```
// pages/addresses.js
//获取应用实例
const app = getApp();
var goodsId = , addressId = , sellType = ;
Page({
  data: {
    isLoading: true,
    isOperate: false,
    showAuthModal: false
  },
  loadData: function () {
    var that = this;
    app.getUserInfo(function (res) {
    }, function () {
      that.setData({
        showAuthModal: true,
      });
    });
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/users/addresses',
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      success: function (res) {
        that.setData({
          addressList: res.data.address_list
        });
        that.setData({
          isNoNetError: true
        });
      },
      fail: function (res) {
        that.setData({
          isNoNetError: false
        });
      },
      complete: function (res) {
```

```
wx.stopPullDownRefresh();
        that.setData({
          isLoading: false
        });
     }
   });
 },
 onPullDownRefresh: function () {
   this.loadData();
 },
 onLoad: function (options) {
   goodsId = options.goods_id || false,
   sellType = options.sell_type || false,
   addressId = options.address_id || false;
   this.setData({
      goods_id: goodsId,
      address_id: addressId,
     sell_type: sellType,
     address_id: addressId
   }),
   this.loadData();
 },
  setDefaults: function (obj) {
   var idx = obj.currentTarget.dataset.index, that = this , url;
   if (goodsId && goodsId != "undefined" && sellType && sellType != "undefined"){
      url = "./checkout?goods_id=" + goodsId + "&sell_type=" + sellType
      if (that.data.addressList[idx].address_id){
       url += "&address_id=" + that.data.addressList[idx].address_id
      }
     wx.redirectTo({
        url: url,
      })
     return;
   }
   wx.request({
      url: app.globalData.apiUrl + "v1.0/users/addresses/" +
that.data.addressList[idx].address_id,
      method: "PUT",
```

```
data: {status : "DEFAULT"},
      header: {
        'AccessToken': wx.getStorageSync("token")
      }
    });
    for (var i = ; i < that.data.addressList.length; i++){</pre>
      that.data.addressList[i].status = (i == idx ? "DEFAULT" : "COMMON");
    that.setData({ addressList: that.data.addressList });
  },
  edit: function (e) {
   var url = "address?address_id=" + e.target.dataset.address_id;
   if (goodsId && sellType){
     url += "&goods_id=" + goodsId + "&sell_type=" + sellType;
    }
   wx.redirectTo({
     "url": url,
   });
  },
  onReady: function () {
  },
  onShow: function () {
  },
  onHide: function () {
  },
  onUnload: function () {
  },
  onReachBottom: function () {
 }
})
```

addresses.json

```
{
    "enablePullDownRefresh": true,
    "navigationBarTitleText": "管理收货地址",
    "navigationBarBackgroundColor": "#F8F8F8",
    "navigationBarTextStyle": "black",
    "usingComponents": {
        "page-loading": "../../component/page-loading/page-loading",
        "net-error-tips": "../../component/net-error-tips/net-error-tips",
        "auth-dialog": "../../component/auth-dialog/auth-dialog"
    }
}
```

addresses.wxml

```
<page-loading isLoading="{{isLoading}}" isOperate="{{isOperate}}"></page-loading>
<view class="body">
    <view class="div_block div" style="height: 257px;"></view>
    <view class="div add address red">
        <view class="inner_red div">
            <navigator hover-class="none" url="{{goods_id != 'undefined' && goods_id ?</pre>
'./address?goods_id=' + goods_id + '&sell_type=' + sell_type : './address'}}" class="a
add_text_red" style="color:white" id="new">新增地址</navigator>
        </view>
    </view>
    <view class="div wx_bar">
        <view class="div wx_bar_back">
            <view class="a " id="listPageback" href="javascript:void(0);"></view>
        </view>
        <view class="wx_bar_act div ">
            <view href="javascript:void(0);" class="a wx_bar_new" style="display: none;"</pre>
id=" new"></view>
        </view>
    </view>
    <view class=" div wx_wrap">
        <view class="div address_list" id="addressList" style="-webkit-transform-origin:</pre>
Opx Opx; opacity: 1; -webkit-transform: scale(1, 1);">
            <view avalonctrl="div address">
```

```
<view class="div address">
                    <block wx:key="item" wx:for="{{addressList}}">
                    <view class="div wrap_address">
                         <view class="span address_name">{{item.address_name == "HOME" ?
"家庭" : "公司"}}</view>
                         <view class="span none" wx:if="{{item.status == 'DEFAULT'}}">默
认</view>
                    </view>
                    <view class=" ul {{goods_id != 'undefined' && goods_id && address_id</pre>
== item.address_id ? 'marginleft bg_color' : ''}}" adid="4" rgid="330108"
level="undefined" addetail="世界包装中心1号楼402乐其" type="0" bindtap="setDefaults" data-
index="{{index}}">
                  <view class="li add li"><view</pre>
class="strong">{{item.receive_name}}</view></view>
                         <view class="li">{{item.mobile}}</view>
                        <view class="li add_li_font"><view class="span" style="display:</pre>
inline;">{{item.province}}{{item.city}}</view></view>
                         <view class="li add_li_font"><view class="span" style="display:</pre>
inline;">{{item.address}}</view></view>
                        <view style="display:none" class="li</pre>
def_add_id">{{item.address_id}}</view>
                        <view class="li edit" catchtap="edit" data-</pre>
address_id="{{item.address_id}}">编辑</view>
                        <view class="span icon address1 {{address id == item.address id</pre>
? 'bg_color' : ''}}" wx:if="{{goods_id != 'undefined' && goods_id}}"></view>
                      <view class="span {{item.status == 'DEFAULT' ? 'icon_address' :</pre>
''}}" wx:else></view>
                    </view>
                    </block>
           </view>
            <view class="div margin footer"></view>
      </view>
</view>
</view>
</view>
<auth-dialog showAuthModal="{{showAuthModal}}" bind:confirm="loadData"></auth-dialog>
```

checkout.js

```
// pages/checkout.js
//获取应用实例
```

```
const app = getApp();
var sellType = , goodsId = , addressId = , groupOrderId = , orderId = ,
    order = require('../utils/order.js')
Page({
  data: {
    isLoading: false,
    isBannering: false,
    isGroupHelp: false,
    isNoNetError: true,
    isPayDisable: false,
    isCancelPay: false,
    showPage: false,
    _: app.globalData._.config
  },
  loadAddresses: function (successCallback, failCallback) {
    var that = this;
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/users/addresses',
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      success: function (res) {
       successCallback(res);
      },
      fail: function (res) {
      complete: function (res) {
      }
    });
  },
  setIsGroupHelp: function() {
   this.setData({"isGroupHelp" : true});
  },
  goodsDetail: function() {
   var that = this;
    wx.request({
      url: app.globalData.miniUrl + 'v1.0/goods/' + goodsId,
      success: function (res) {
        if (res.data.result == 'fail') {
          that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
```

```
that.data._.error_text[4] }),
            that.setData({ isLoading: false, isOperate: false })
        } else if (res.data.result == 'ok') {
          that.setData({
            goods: res.data.goods,
            showPage: true
          });
        } else {
          that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
that.data._.error_text[] })
        }
        that.confirmCallback = function(){
          app.goHome();
        }
        that.setData({
          isNoNetError: true
        });
      },
      fail: function (res) {
        that.setData({
          isNoNetError: false
        });
      },
      complete: function (res) {
        wx.stopPullDownRefresh();
        that.setData({
          isLoading: false
        });
      }
    });
 },
 orderBanner: function () {
    var that = this;
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/banners/order',
      success: function (res) {
        that.setData({
          banner: res.data.banner
        });
      }
    });
```

```
},
 closeBanner: function (e) {
   this.setData({ 'isBannering': false });
 },
 loadData: function() {
   var that = this;
   this.goodsDetail(),
   this.orderBanner(),
   this.loadAddresses(function(res){
     if (res.data['result'] == "ok") {
       if (res.data.address_list.length > ){
         var address = that.addressSort(res.data.address_list, addressId);
         that.setData({ "address": address }), addressId = address.address_id;
       }
      }
   },function(){});
 },
 //跳转地址页面
  redirectAddresses: function () {
   if(orderId){
     wx.showToast({ title: "订单已生成,信息不可更改",icon: "none" });
     return;
   }
   var url;
   if (this.data.address != undefined && this.data.address.address_id != undefined &&
this.data.address.address_id > ) {
     url = "addresses?sell_type=" + sellType + "&goods_id=" + goodsId;
     url += "&address_id=" + this.data.address_id;
   } else {
     url = "address?goods_id=" + goodsId + "&sell_type=" + sellType;
   wx.navigateTo({
      url: url
```

```
});
},
onLoad: function (options) {
  var that = this;
  goodsId = options.goods_id,
  sellType = options.sell_type,
  addressId = options.address id,
  groupOrderId = options.group_order_id,
  orderId = ;
  this.setData({
    sell_type: sellType,
    goods_id: goodsId
  });
  app.getUserInfo(function (res) {
    that.setData({
      isLoading: true,
      isBannering: true
    }),
    setTimeout(function () {
     that.closeBanner();
    }, 3500),
    that.loadData();
  }, function () {
    that.setData({
      showAuthModal: true,
      showPage: true
    });
 });
},
btnOrderDone: function () {
  if (!this.data.address) return false;
  if (this.data.isPayDisable) return true;
  var that = this, createOrderData;
  this.setData({ "isPayDisable": true });
  if (orderId){
```

```
that.pay();
      return;
    }
    createOrderData = {
      "goods id": goodsId,
      "address_id": addressId,
      "groupbuy": sellType == 1 ? 1 : ,
      "group_order_id": groupOrderId ? groupOrderId :
    };
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/users/orders',
      method: "POST",
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      data: createOrderData,
      success: function (res){
        if(res.data.result == "ok"){
          orderId = res.data.order id,
          that.pay();
        }else{
          if (res.data.result == "fail")
            that.setData({ showWinpopModal: true, showWinpopCancel: false,
winpopContent: res.data.error_info });
            // wx.showToast({ title: res.data.error_info, icon: "none" });
            that.setData({ showWinpopModal: true, showWinpopCancel: false,
winpopContent: that.data._.error_text[] });
            // wx.showToast({ title: that.data._.error_text[0], icon: "none" });
          }
          that.confirmCallback = function (){
          }
          console.log(res);
          that.setData({ "isPayDisable": false });
        }
      },
      fail: function (res) {
        that.setData({"isPayDisable": false});
      },
      complete: function (res) {
      }
```

```
});
 },
 // 请求支付参数
 pay: function (e) {
   var that = this;
   order.pay(orderId, function(res){
      if (res.data.result == 'fail') {
        that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
res.data.error_info });
      } else if (res.data.result == 'ok') {
        order.goPay(res.data.param, function () {
          // 支付成功
          order.paySuccess(orderId)
        }, function (res) {
          that.setData({ "isPayDisable": false })
          console.log(res)
        }, function (res) {
          if (res.errMsg == "requestPayment:fail cancel") {
            that.setData({ "isCancelPay": true }),
              wx.showToast({ title: app.globalData._.config.pay_text.cancel, icon:
"none" });
          }
        });
      } else {
        that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
that.data._.error_text[] }),
        that.confirmCallback = function () {
          that.setData({ "isPayDisable": false })
        }
      }
   },function(res){
      that.setData({ "isPayDisable": false })
   },function(res){
   });
 },
 onReady: function () {
```

```
},
onShow: function () {
},
onHide: function () {
},
onUnload: function () {
},
onPullDownRefresh: function () {
},
onReachBottom: function () {
},
addressSort: function (list, address_id) {
  var address;
  if (list.length == 1) {
    return list[];
  if (list.length <= ) {</pre>
   return null;
  }
  for (var i in list) {
    if (undefined != address_id) {
      if (list[i]['address_id'] == address_id) {
        address = list[i];
      }
    } else if (list[i]['status'] == "DEFAULT") {
      address = list[i];
    } else if (i >= list.length - 1) {
      address = list[];
    }
  return address;
```

```
})
```

checkout.json

```
{
    "navigationBarBackgroundColor": "#F8F8F8",
    "navigationBarTextStyle": "black",
    "navigationBarTitleText": "确认订单",
    "usingComponents": {
        "page-loading": "../../component/page-loading/page-loading",
        "net-error-tips": "../../component/net-error-tips/net-error-tips",
        "group-help": "../../component/group-help/group-help",
        "winpop-mask": "../../component/winpop-mask/winpop-mask",
        "auth-dialog": "../../component/auth-dialog/auth-dialog"
    }
}
```

checkout.wxml

```
<page-loading isLoading="{{isLoading}}" isOperate="{{isOperate}}"></page-loading>
<view class="body checkout" wx-if="{{showPage}}}">
    <view class="div" style="display: block;">
        <view class="div wx wrap">
            <view bindtap="redirectAddresses" hover-class="none">
                <view class="a send address">
                    <view class="div" id="sendTo">
                        <view class="div address address_defalut" style="{{address ? ''</pre>
: 'display: none;'}}">
                        <view class="div address name order">
                             <view class="span">{{address.address_name == "WORK" ? "公司":
"家庭"}}</view>
                         </view>
                         <view class="h3">
                             <view class="b send_margin">送至</view>
                             <view class="br"></view>
```

```
</view>
                             <view id="editAddBtn" adid="4" class="ul">
                                 <view class="li">
                                      <view class="strong">{{address.receive_name}}</view>
                                      {{address.mobile}}
                                 </view>
                                 <view class="li">{{address.address}}</view>
                             </view>
                         </view>
                         <view class="div address_new" style="display: none;">
                             <view class="h4 lou_userinfo">本人信息: <view class="strong"
name_lou">{{address.mobile}} {{address.mobile}}</view></view>
                         </view>
                         <view class="div address text_center" style="{{!address ? '' :</pre>
'display: none;'}}">
                             <view class="span"> <view class="strong">您还没有收货地址哦,点击
新增地址</view></view>
                         </view>
                     </view>
                 </view>
             </view>
            <block wx:if="{{ goods }}">
              <view class="div order">
                   <view class="div order_bd">
                       <view id="orderList" class="div order_glist">
                           <view class="div only">
                               <view class="div order_goods">
                                    <view class="div order_goods_img">
                                        <image mode="aspectFill" class="img" alt=""</pre>
src="{{goods.image_url}}" />
                                   </view>
                                    <view class="div order_goods_info">
                                        <view class="div order_goods_name"><view</pre>
id="tuanLbl"></view>{{goods.goods name}}</view>
                                        <view class="div order_goods_attr">
                                            <view class="div order_goods_attr_item">
                                                <view id="goodsPrice" class="div</pre>
order_goods_price2">
                                                    <view class="i">[]</view>
                                                         <block wx:if="{{sell_type ==</pre>
1}}">{{goods.group_price}}</block>
                                                         <blook
wx:else>{{goods.alone_price}}</block>
                                                    <view class="i"
style="display:none;">/8个</view>
                                                </view>
```

```
</view>
                                            <view class="p order_goods_attr_item"><view</pre>
id="skuLast" class="span"></view><view class="i"></view></view>
                                   </view>
                               </view>
                           </view>
                      </view>
                  </view>
              </view>
              <view class="div" id="pay area" style="opacity: 1;">
                  <view class="div total">快递: <view class="small">□</view>0.00总价: <view
id="totalPrice" class="span total_price"><view class="i">[]</view>
                       <block wx:if="{{sell_type == 1}}">{{goods.group_price}}
                      <block wx:else>{{goods.alone_price}}</block></view></view>
                  <view class="pay2 div ">
                       <!-- <view class="div pay2_hd">请选择支付方式</view> -->
                      <view class='h 20'></view>
                       <view id="payList" class="div pay2_list">
                           <view id="goTenPay" class="div pay2 item pay2 wx
pay2_selected">
                               <view class="span pay2_item_state"></view>
                               <view class="span pay2_item_ico"></view>
                               <view class="span pay2_item_tit">微信支付</view>
                           </view>
                       </view>
                      <view class='h 20'></view>
                      <form name="theForm" id="theForm" class="form" report-</pre>
submit="true" bindsubmit="btn0rderDone">
                           <view>
                               <button formType="submit" class="pay2_btn"</pre>
id="btn_order_done" style="{{isPayDisable || !address ? 'opacity: 0.4;' : ''}}" >
                                   <br/><block wx:if="{{isPayDisable}}">正在支付 请稍候</block>
                                   <block wx:elif="{{isCancelPay}}">继续支付</block>
                                   <br/>
<br/>
<br/>
dock wx:else>立即支付</block>
                               </button>
                           </view>
                      </form>
                  </view>
              </view>
            </block>
          </view>
        <view class='h_20'></view>
```

```
<import src="./base/group-step.wxml" />
       <template is="step" data="{{setIsGroupHelp: setIsGroupHelp,step: 2}}" />
</view>
<view class="div widget slide widget tip {{isBannering && banner.open == '1' ?</pre>
'slide_tip' : ''}}" bindtap="closeBanner" hidden="{{!goods}}">
<view class="div title">
<view class="p">温馨提示</view>
</view>
<view class="div content">
<view class="p">
{{banner.desc}}
</view>
</view>
</view>
<view class="section modaled" hidden="{{!isBannering || banner.open ==</pre>
'0'}}"></view>
</view>
<group-help isGroupHelp="{{isGroupHelp}}"></group-help>
<net-error-tips isNoNetError="{{isNoNetError}}" bind:loadData="loadData"></net-error-</pre>
tips>
<winpop-mask showWinpopModal="{{showWinpopModal}}"</pre>
showWinpopCancel="{{showWinpopCancel}}" winpopContent="{{winpopContent}} "
bind:cancelCallback="cancelCallback" bind:confirmCallback="confirmCallback"></winpop-</pre>
mask>
```

goods.js

```
// pages/goods.js
//获取应用实例
const app = getApp();
var goodsId = ;
Page({
```

<auth-dialog showAuthModal="{{showAuthModal}}" bind:confirm="loadData"></auth-dialog>

```
/**
 * 页面的初始数据
  */
 data: {
   isLoading: true,
   isOperate: false,
   isNoNetError: true,
   goods: {},
   gallery: [],
   image_w_h: {},
   shareAnimationData: null,
   showShareModalStatus: false,
   isNoNetError: true,
   qrcodeUrl: null,//海报地址
   showPosterModal: false,
   _: app.globalData._.config,
   current: 1,
    showAuthModal: false,
   showPage: false
 },
 loadData: function() {
   var that = this;
   wx.request({
      url: app.globalData.miniUrl + 'v1.0/goods/' + goodsId,
      success: function (res) {
        if (res.data.result == 'fail'){
          that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
that.data._.error_text[4] }),
            that.setData({ isLoading: false, isOperate: false })
        }else if(res.data.result == 'ok'){
          that.setData({
            goods: res.data.goods,
            gallery: res.data.gallery,
            isShowOut: >= parseInt(res.data.goods.goods_stock),
            showPage: true
          });
          app.getImageUrlInfo(that, that.data.gallery[].img_url
            , function () {
```

```
that.setData({ isOperate: true })
            }, function (image_w_h) {
              that.setData({ isLoading: false, isOperate: false, image_w_h:
app.wxAutoImageCal(image_w_h.width, image_w_h.height) })
            }, function () {
              that.setData({ isLoading: false, isOperate: false })
            });
          that.setData({
            isNoNetError: true
          });
        }else{
          that.setData({ isLoading: false, isOperate: false }),
            that.setData({ showWinpopModal: true, showWinpopCancel: false,
winpopContent: that.data._.error_text[]})
        }
        that.confirmCallback = function(){
          that.goHome();
        }
      },
      fail: function (res) {
        that.setData({
          isNoNetError: false
        that.setData({ isLoading: false, isOperate: false })
      },
      complete: function (res) {
        wx.stopPullDownRefresh();
      }
    });
  },
  showShareModal: function () {
    this.setData({
      isNoScroll: true
    });
    // 显示遮罩层
    var animation = wx.createAnimation({
      duration: 100,
      timingFunction: "ease",
      delay:
    });
    animation.translateY(300).step();
```

```
this.setData({
    shareAnimationData: animation.export(),
    showShareModalStatus: true
  });
  setTimeout(function () {
    animation.translateY().step();
    this.setData({
      shareAnimationData: animation.export()
    })
  }.bind(this), 100);
},
hideShareModal: function () {
  this.setData({
    isNoScroll: false
  });
 // 隐藏遮罩层
  var animation = wx.createAnimation({
    duration: 200,
   timingFunction: "linear",
   delay:
  });
  animation.translateY(300).step();
  this.setData({
    shareAnimationData: animation.export(),
  })
  setTimeout(function () {
    animation.translateY().step();
   this.setData({
      shareAnimationData: animation.export(),
      showShareModalStatus: false
   });
  }.bind(this), 200);
},
onLoad: function (options) {
  goodsId = options.goods_id;
 //处理 扫描二维码打开时候带的参数
  var scene = decodeURIComponent(options.scene);
  if (scene != "undefined"){
   goodsId = scene;
  }
```

```
this.loadData();
},
onPullDownRefresh: function() {
  this.loadData();
},
previewImage: function (e) {
  var idx = e.currentTarget.dataset.idx;
  var gallery = [];
  for (var i = ; i < this.data.gallery.length; i++) {</pre>
    gallery[i] = this.data.gallery[i].img_url;
  }
  wx.previewImage({
    current: gallery[idx],
    urls: gallery
  })
},
bindchange: function (e) {
  var current = e.detail.current + 1;
  this.setData({ current: current });
},
/*返回首页*/
goHome: function () {
  app.goHome();
},
*生命周期函数--监听页面初次渲染完成
 */
onReady: function () {
},
/**
* 生命周期函数--监听页面显示
 */
onShow: function () {
},
/**
* 生成分享海报
 */
```

```
shareQrcode: function () {
   var that = this;
   that.hideShareModal();

   that.setData({
        qrcodeUrl: app.globalData.miniUrl + "v1.0/wxacode/" + goodsId + "?page=" +
"pages/goods",
        posterUrl: app.globalData.miniUrl + "v1.0/goods/poster/" + goodsId,
        showPosterModal: true
   });
},

onShareAppMessage: function () {
   return app.share({ title: this.data.goods.goods_name, path: "pages/goods?goods_id=" + goodsId });
},
```

goods.json

```
{
  "enablePullDownRefresh": true,
  "navigationBarTitleText": "商品详情",
  "navigationBarBackgroundColor": "#F8F8F8",
  "navigationBarTextStyle": "black",
  "usingComponents": {
    "page-loading": "../../component/page-loading/page-loading",
    "net-error-tips": "../../component/net-error-tips/net-error-tips",
    "mall-service": "../../component/mall-service/mall-service",
    "qrcode-poster": "../../component/qrcode-poster/qrcode-poster",
    "auth-dialog": "../../component/auth-dialog/auth-dialog",
    "winpop-mask": "../../component/winpop-mask/winpop-mask"
}
```

group.js

```
// pages/group.js
//获取应用实例
const app = getApp();
```

```
var groupId = , util = require('.../utils/util.js'), cron = require('.../utils/cron.js');
Page({
 data: {
   isLoading: true,
   isOperate: false,
   grcodeUrl: null,
   isHideLoadMore: true,
   isNoNetError: true,
   _: app.globalData._.config,
   showPosterModal: false,
   shareAnimationData: null,
   showShareModalStatus: false,
   showPage: false,
   showAuthModal: false
 },
  countdown: function (expire_time) {
   if (this.timer) clearTimeout(this.timer);
   var times = (expire_time - new Date().getTime() / 1000) * 1000, that = this;
   // if (times <= 0)
   // {
   // cron.run(function () {}, function () {}, function ()
{wx.startPullDownRefresh();})
   // return;
   // }
   util.countdowns(this, [times],function(i) {
      that.data.group_order.status == '0' &&
cron.run(function(){},function(){},function() {wx.startPullDownRefresh();})
  });
 },
 setIsGroupHelp: function () {
   this.setData({ "isGroupHelp": true });
 },
 loadData: function () {
   var that = this;
```

```
//请求订单列表
   that.data.group_order = null;
   wx.request({
      url: app.globalData.apiUrl + 'v1.0/users/groups/' + groupId,
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      success: function (res) {
        var group_title_class, group_detail_class, is_buy = false, group_but_url,
group_but_text, tips_tit, tips_detail, group_type;
        if (res.data.result == 'fail') {
          that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
that.data._.error_text[2] }),
            that.setData({ isLoading: false, isOperate: false })
        }else if(res.data.result == 'ok') {
          group_title_class = res.data.group_order.status == '2' ? 'tips_err' :
res.data.group_order.status == '1' ? 'tips_succ tips_succ2' : 'tips_succ tips_succ2',
          group_detail_class = res.data.group_order.status == '2' ? 'tm_err' :
res.data.group_order.status == '1' ? 'tm_succ' : 'tm_tm';
          for (var i = ; i < res.data.group order.users.length; i++) {</pre>
            if (res.data.group_order.caller_id == res.data.group_order.users[i].user_id)
{
              is buy = true;
            }
          }
          if (res.data.group order.status == '0') {
            if(!is_buy) {
              group_but_url = 'checkout?sell_type=1&goods_id=' +
res.data.group_order.order.goods_id + "&group_order_id=" +
res.data.group order.group order id;
              group but text = that.data. .group text[1];
            } else {
              group_but_url = '';
              group_but_text = that.data._.group_text[].replace("%s",
(res.data.group_order.require_num - res.data.group_order.people));
```

```
} else {
            group_but_url = 'index';
            group_but_text = that.data._.group_text[2];
          }
          if(!is buy) {
            group_type = ;
          } else if (res.data.group_order.users[].user_id !=
res.data.group_order.caller_id) {
            group_type = 1;
          } else {
            group_type = 2;
          }
          tips_tit =
that.data._.tuan_status[res.data.group_order.status]['tips_title'][group_type],
          tips detail =
that.data._.tuan_status[res.data.group_order.status]['tips_detail'][group_type];
          res.data.group_order.tips_tit = tips_tit,
          res.data.group_order.tips_detail = tips_detail,
          res.data.group_order.group_but_text = group_but_text,
          res.data.group_order.group_but_url = group_but_url,
          res.data.group_order.group_detail_class = group_detail_class,
          res.data.group_order.group_title_class = group_title_class;
          if (res.data.group_order.status == '0')
          {
            that.countdown(res.data.group_order.expire_time);
          }
          that.setData({
            group_order: res.data.group_order,
            showPage: true
          });
        } else {
          that.setData({ isLoading: false, isOperate: false }),
            that.setData({ showWinpopModal: true, showWinpopCancel: false,
winpopContent: that.data._.error_text[] })
        }
```

```
that.confirmCallback = function () {
        that.goHome();
      }
      that.setData({
        isNoNetError: true
      });
    },
    fail: function (res) {
      that.setData({
        isNoNetError: false
      });
    },
    complete: function (res) {
      wx.stopPullDownRefresh();
      that.setData({
        isLoading: false
      });
    }
 });
},
goHome: function () {
  app.goHome();
},
redirect: function (e) {
  util.redirect(e.currentTarget.dataset.url);
},
showShareModal: function () {
  this.setData({
    isNoScroll: true
  });
  // 显示遮罩层
  var animation = wx.createAnimation({
    duration: 100,
    timingFunction: "ease",
    delay:
  });
  animation.translateY(300).step();
  this.setData({
    shareAnimationData: animation.export(),
```

```
showShareModalStatus: true
  });
  setTimeout(function () {
    animation.translateY().step();
    this.setData({
      shareAnimationData: animation.export()
    })
  }.bind(this), 100);
},
hideShareModal: function () {
  this.setData({
    isNoScroll: false
  });
 // 隐藏遮罩层
  var animation = wx.createAnimation({
    duration: 200,
   timingFunction: "linear",
   delay:
  });
  animation.translateY(300).step();
  this.setData({
    shareAnimationData: animation.export(),
  })
  setTimeout(function () {
    animation.translateY().step();
   this.setData({
      shareAnimationData: animation.export(),
      showShareModalStatus: false
    });
  }.bind(this), 200);
},
onLoad: function (options) {
  groupId = options.id;
  //处理 扫描二维码打开时候带的参数
  var scene = decodeURIComponent(options.scene);
  if (scene != "undefined") {
   groupId = scene;
  }
  var thisPage = this;
  app.getUserInfo(function (res) {
   thisPage.setData({
```

```
userInfo: res,
    });
    thisPage.loadData()
  }, function () {
    thisPage.setData({
      showAuthModal: true,
      isLoading: false,
      isOperate: false,
      showPage: true
    });
  });
},
onReady: function () {
},
onShow: function () {
},
onHide: function () {
},
onUnload: function () {
},
onPullDownRefresh: function () {
 this.loadData();
},
onReachBottom: function () {
},
onShareAppMessage: function () {
},
```

```
/**
* 生成分享海报
*/
shareQrcode: function () {
var that = this;
that.hideShareModal();
that.setData({
qrcodeUrl: app.globalData.miniUrl + "v1.0/wxacode/" + groupId + "?page=" +
"pages/group",
posterUrl: app.globalData.miniUrl + "v1.0/group/poster/" + groupId,
showPosterModal: true
});
},
onShareAppMessage: function () {
if (this.data.group_order.status == || this.data.group_order.status == 8) {
var desc = '您参加的' + this.data.group_order.order.order_goods.goods_name + '目前还差'
+ (this.data.group_order.require_num - this.data.group_order.people) + '人,快去叫上身边的小伙
伴一起' + app.globalData. .config.app.name;
return app.share({ title: this.data.group_order.order.order_goods.goods_name,
desc: desc, path: "pages/group?id=" + groupId });
} else {
return app.share({ title: "", desc: "", path: "pages/group?id=" + groupId });
}
}
})
```

group.json

```
{
  "navigationBarTitleText": "拼团详情",
  "enablePullDownRefresh": true,
  "navigationBarBackgroundColor": "#F8F8F8",
  "navigationBarTextStyle": "black",
  "usingComponents": {
    "page-loading": "../../component/page-loading/page-loading",
    "net-error-tips": "../../component/net-error-tips/net-error-tips",
    "qrcode-poster": "../../component/qrcode-poster/qrcode-poster",
    "group-help": "../../component/group-help/group-help",
    "winpop-mask": "../../component/winpop-mask/winpop-mask",
    "auth-dialog": "../../component/auth-dialog/auth-dialog"
  }
}
```

group.wxml

```
<page-loading isLoading="{{isLoading}}" isOperate="{{isOperate}}"></page-loading>
<wxs src="../libs/tools.wxs" module="tools" />
<view class=" body" id="group" wx-if="{{showPage}}}">
   <view class="div" id="group-container" style="display: block;">
        <view class="div explain modal" >
            <view class="i explain lou explain icon" style="display:none"></view>
            <view class="i explain_tuan explain_icon" style="display:none"></view>
            <view class="div" id="showExplain">
                <view class="div showBg" id="showBg">
                </view>
            </view>
        </view>
        <view class="div content">
            <view class="div H5 con" id="group title">
            </view>
             <!--拼团失败-->
            <view class=" div H5_con" id="group_title" hidden="{{!group_order}}">
                <view class="div tips topStateWrap {{group_order.group_title_class}}">
                <!--tips succ tips err-->
                <view class="div tips ico"></view>
                <view class="div tips_tit">{{group_order.tips_tit}}</view>
                <view class="div tips_txt">{{group_order.tips_detail}}</view>
                </view>
            </view>
```

```
<view class=" div H5_con" hidden="{{!group_order}}">
                 <view id="group_detail" class="div tm</pre>
{{group_order.group_detail_class}}" hidden="{{!group_order}}">
                      <!--tm_succ tm_err-->
                      <view class="a goItemPage" bindtap="redirect" data-</pre>
url="goods?goods_id={{group_order.order.goods_id}}">
                      <view class="div td tuanDetailWrap">
                      <view class="div td img">
                         <image class="img" alt=""</pre>
src="{{group_order.order_goods.image_url + '?x-oss-
process=image/resize,w_380,h_380'}}" mode="aspectFill" />
                      </view>
                      <view class="div td_info margin_height">
                      <view class="p
td_name">{{group_order.order.order_goods.goods_name}}</view>
                      <view class="p tuan_goods_cx"></view>
                      <view class="p td_mprice"><view class="tuanTotal"</pre>
span">{{group_order.require_num}}</view>人团:<view class="i">□</view>
class="b">{{group_order.order.order_goods.group_price}}</view></view>
                      <view class="p"></view>
                      <view class="p td_num"></view><view class="div img_out"</pre>
id="img_out"></view></view></view></view>
                 </view>
                 <view class="div pp">
                     <view class=" div pp_users" id="pp_users">
                         <block wx:key="item" wx:for="{{group_order.users}}">
                             <view class="a pp_users_item pp_users_normal_1" href="#"</pre>
wx:if="{{index == 0}}">
                                  <image class="img" alt="" src="{{item.avatar}}"/>
                             </view>
                             <view class="a pp_users_item pp_users_normal_2" href="#"</pre>
wx:elif="{{index == 1}}">
                                  <image class="img" alt="" src="{{item.avatar}}"/>
                             </view>
                             <view class="a pp_users_item" href="#" wx:else>
                                  <image class="img" alt="" src="{{item.avatar}}"/>
                             </view>
                         </block>
                         <block wx:key="item" wx:for="{{group_order.require_num -</pre>
group_order.people}}">
                             <view class="a pp_users_item" href="#">
                                  <image class="img" alt="" src="{{_.group_image_url}}"/>
                             </view>
                         </block>
                     </view>
                     <view class=" div pp_tips" id="flag_1_a" style="{{group_order.status}}</pre>
== 1 || group_order.status == 9 || group_order.status == 2 || group_order.status == 5
```

```
|| group order.status == 6 ? 'display:none;' : ''}}">对于诸位大侠的相助,团长感激涕零</view>
                     <view class="div pp_tips" id="flag_0_a" style="{{group_order.status}}</pre>
== 1 || group order.status == 9 || group order.status == 2 || group order.status == 5
|| group_order.status == 6 ? 'display:none;' : ''}}">还差<view
class="b">{{group_order.require_num - group_order.people}}</view>人, 盼你如南方人盼暖
气~</view>
                    <view class="div pp_state" id="flag_0_b" style="{{group_order.status
== 1 || group_order.status == 9 || group_order.status == 2 || group_order.status == 5
|| group_order.status == 6 ? 'display:none;' : ''}}" wx:if="{{clock[0] &&
clock[0].length}}">
                         <view class="div pp_time">
           剩余<view id="ti_time_hour" class="span">{{clock[0][0]}}</view>:<view
class="span" id="ti time min">{{clock[0][1]}}</view>:<view class="span"</pre>
id="ti time sec">{{clock[0][2]}}</view>结束
                         </view>
                     </view>
                     <!--<view class="pp_state_txt" id="flag_1_b" style="display:none;">
团购成功,卖家将尽快发货</view> -->
                </view>
                 <view class=" div pp_list">
                     <block wx:key="item" wx:for="{{group_order.users}}">
                     <view id="div showYaoheList">
                        <view class="div div pp_list_item pp_list_item_1" wx:if="{{index</pre>
== 0}}">
                             <image class="img pp_list_avatar" alt=""</pre>
src="{{item.avatar}}" />
                             <view class="div pp_list_info" id="pp_list_info">
                             <view class="span pp_list_name">团长<view
class="b">{{item.nickname}}</view></view>
                             <view class="span</pre>
pp list time">{{tools.formatTimeStamp(item.join time)}}开团</view></view>
                         </view>
                         <view class="div div pp_list_item pp_list_item_2"</pre>
wx:elif="{{index == 1}}">
                             <image class="img pp list avatar" alt=""</pre>
src="{{item.avatar}}" />
                             <view class="div pp_list_info" id="pp_list_info">
                             <view class="span pp_list_name"><view</pre>
class="b">{{item.nickname}}</view></view>
                             <view class="span</pre>
pp_list_time">{{tools.formatTimeStamp(item.join_time)}}参团</view></view>
                         </view>
                         <view class="div div pp_list_item" wx:else>
                             <image class="img pp_list_avatar" alt=""</pre>
src="{{item.avatar}}" />
                             <view class="div pp_list_info" id="pp_list_info">
                             <view class="span pp_list_name"><view</pre>
```

```
class="b">{{item.nickname}}</view></view>
                             <view class="span
pp list time">{{tools.formatTimeStamp(item.join time)}}参团</view></view>
                        </view>
                        </view>
                    </block>
                    <view id="chamemeber" class="div pp_list_blank"</pre>
style="display:none;">
         还差
                        <view class="span"></view> 人, 让小伙伴们都来组团吧!
                    </view>
                </view>
            </view>
            <view id="shareit" bindtap="groupShareUp" class="div" style="{{share_down ?</pre>
'display:block;' : 'display:none;'}}">
                 <image class="arrow" src="//pintuan-xcx.cn/v1.0/share-it.png"/>
                <view class="div img-share">
                    <view class="div img-arrow"></view>
                    <view class="div img-head">分享至朋友圈</view>
                    <view class="div img-body">咻的一下就成团!</view>
                </view>
                <view id="describe" class="div describe">
            </view>
            <import src="./base/group-step.wxml" />
            <template is="step" data="{{setIsGroupHelp: setIsGroupHelp,step: 0}}" />
            <view class="div mod footer" id="mod footer">
                <view class="div mod footer lk">
                    <view class="a on" href="index.html" id="shop_name"</pre>
bindtouchstart="goHome" data-url="index">{{_.app.name}}</view>
                    <view class="a" href="groups.html" bindtouchstart="redirect" data-</pre>
url="groups">我的团</view>
                </view>
                <view class="div mod_footer_logo">
                    <view class="span">{{ .app.url}}</view>
                </view>
            </view>
            <view style="height:72px;"></view>
            <view class="br"></view>
            <view class="br"></view>
            <view class="br"></view>
            <view class="br"></view>
```

```
<view class="div H5 con fixopt" id="fixopt" style="display: block;">
                <view hidden="{{!group_order.group_but_url}}" class="a fixopt_btn</pre>
bottomBtn" bindtap="redirect" data-url="{{group_order.group_but_url}}"
href="index.html">{{group_order.group_but_text}}</view>
                <button style="padding-left:0px;padding-right:0px;font-size:12px;"</pre>
hidden="{{group_order.group_but_url}}" class="a fixopt_btn bottomBtn" hover-class="none"
catchtap="showShareModal">{{group order.group but text}}</button>
            </view>
        </view>
    </view>
</view>
<view class="commodity_screen" bindtap="hideShareModal"</pre>
wx:if="{{showShareModalStatus}}"></view>
<view animation="{{shareAnimationData}}" class="commodity_attr_box share-modal"</pre>
wx:if="{{showShareModalStatus}}">
<button open-type='share' class="item">
  <view class="image-wrap">
    <image src="//pintuan-xcx.cn/v1.0/share_user_icon.png"></image>
  </view>
  <view class="text">发给朋友</view>
</button>
<view class="item" bindtap='shareQrcode'>
  <view class="image-wrap">
    <image src="//pintuan-xcx.cn/v1.0/share_qrcode_icon.png"></image>
  </view>
  <view class="text">生成海报</view>
</view>
<view class="cancel-btn" hover-class='hover-effect' bindtap='hideShareModal'>取消</view>
</view>
<group-help isGroupHelp="{{isGroupHelp}}"></group-help>
<qrcode-poster showPosterModal="{{showPosterModal}}"</pre>
goods="{{group_order.order_goods}}" qrcodeUrl="{{qrcodeUrl}}"
posterUrl="{{posterUrl}}">
<net-error-tips isNoNetError="{{isNoNetError}}" bind:loadData="loadData"></net-error-</pre>
tips>
<winpop-mask showWinpopModal="{{showWinpopModal}}"</pre>
showWinpopCancel="{{showWinpopCancel}}" winpopContent="{{winpopContent}} "
```

bind:cancelCallback="cancelCallback" bind:confirmCallback="confirmCallback"></winpopmask>

<auth-dialog showAuthModal="{{showAuthModal}}" bind:confirm="loadData"></auth-dialog>

groups.js

```
// pages/groups.js
//获取应用实例
const app = getApp();
Page({
  data: {
    isLoading: true,
    isOperate: false,
    isNoNetError: true,
    groups: [],
    isHideLoadMore: true,
    isNoNetError: true,
    _: app.globalData._.config
  },
  loadData: function () {
    var that = this;
    //请求订单列表
    that.data.groups = [];
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/users/groups',
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      data: { offset: that.data.groups.length, size: 30 },
      success: function (res) {
        if (res.data.result == 'ok') {
          that.setData({
            groups: res.data.group orders
          });
        }
        that.setData({
          isNoNetError: true
        });
      },
      fail: function (res) {
```

```
that.setData({
        isNoNetError: false
      });
    },
    complete: function (res) {
      wx.stopPullDownRefresh();
      that.setData({
        isLoading: false
      });
    }
 });
},
loadMore: function() {
  var that = this;
  that.setData({
    isHideLoadMore: false
  });
  wx.request({
    url: app.globalData.apiUrl + 'v1.0/users/groups',
    header: {
      'AccessToken': wx.getStorageSync("token")
    },
    data: { offset: that.data.groups.length, size: 15 },
    success: function (res) {
      if (res.data.result == 'ok') {
        that.setData({
          groups: that.data.groups.concat(res.data.group_orders)
        });
      }
    },
    fail: function (res) {
    },
    complete: function (res) {
      that.setData({
        isHideLoadMore: true
      });
    }
  });
},
toDetail: function (e) {
 var url = e.currentTarget.dataset.url + "?id=" + e.currentTarget.dataset.id;
  wx.navigateTo({
    url: url
 });
},
```

```
onLoad: function (options) {
this.loadData();
},
onReady: function () {
},
onShow: function () {
},
onHide: function () {
},
onUnload: function () {
},
onPullDownRefresh: function () {
this.loadData();
},
/**
* 页面上拉触底事件的处理函数
*/
onReachBottom: function () {
if (this.data.isHideLoadMore) {
this.loadMore();
}
},
onTabItemTap: function (item) {
wx.startPullDownRefresh();
}
})
```

groups.json

```
"navigationBarTitleText": "我的拼团",
    "enablePullDownRefresh": true,
    "navigationBarBackgroundColor": "#F8F8F8",
    "navigationBarTextStyle": "black",
    "usingComponents": {
        "page-loading": "../../component/page-loading/page-loading",
        "net-error-tips": "../../component/net-error-tips/net-error-tips",
        "auth-dialog": "../../component/auth-dialog/auth-dialog",
        "right-service": "../../component/right-service/right-service",
        "winpop-mask": "../../component/winpop-mask/winpop-mask",
        "load-more": "../../component/load-more/load-more"
    }
}
```

groups.wxml

```
<view class="body" id="groups">
    <view class="div con">
        <block wx:key="item" wx:for="{{groups}}">
            <view class="div mt order " id="groups">
                 <view class="div groups line"></view>
                <view class="div mt_g" data-url="./group" data-</pre>
id="{{item.group_order_id}}" bindtap="toDetail">
                <view class="div mt_g_img">
                     <view class="a" href="group.html?id=2071596">
                     <image mode="aspectFill" class="img"</pre>
src="{{item.order_goods.image_url + '?x-oss-process=image/resize,w_380,h_380'}}"
/></view> </view>
                    <view class="div mt g info">
                         <view class="p mt_g_name">{{item.order_goods.goods_name}}</view>
                         <view class="p mt g price">成团价: <view class="span"> <view</pre>
class="b"> <view class="small">[</view>{{item.order_amount}}</view>/件</view><view
class="i"></view> </view> </view> </view>
                <view class="div mt status">
                     <view class="span
mt_status_txt">{{_.tuan_status[item.status].desc}}</view>
                     <view class="mt_status_lk1 " href="order.html?id=9272403" data-</pre>
url="order" data-id="{{item.order id}}" bindtap="toDetail"> 查看订单详情 </view>
                     <view class="mt_status_lk1 marg_right" href="group.html?id=2071596"</pre>
data-url="./group" data-id="{{item.group_order_id}}" bindtap="toDetail"> 查看团详情 </view>
                </view>
            </view>
        </block>
        <view class="div mt_nogroups" wx:if="{{!isLoading && groups.length == 0 &&</pre>
isNoNetError}}">
            <view class="h4">您还没有任何相关团购哦</view>
        </view>
    </view>
    <right-service></right-service>
    <view class="div" style="visibility:hidden "></view>
</view>
<net-error-tips isNoNetError="{{isNoNetError}}" bind:loadData="loadData"></net-error-</pre>
<load-more isHideLoadMore="{{isHideLoadMore}}"></load-more>
```

index.js

```
// pages/index.js
//获取应用实例
const app = getApp()
Page({
  data: {
    isLoading: true,
    isOperate: false,
    banner: [],
    goods: [],
    isHideLoadMore: true,
    isNoNetError: true,
  },
  bannerList: function () {
    var that = this;
    //请求广告列表
    that.data.banner = [];
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/banners',
      success: function (res) {
        that.setData({
          banner: res.data.banners
        });
      },
      fail: function (res) {
        that.setData({
          isNoNetError: false
        });
      }
    });
  },
  goodsList: function() {
    var that = this;
    //请求商品列表
    that.data.goods = [];
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/goods',
      data: { offset: that.data.goods.length,size: 30},
      success: function (res) {
        that.setData({
          goods: res.data.goods
        });
        that.setData({
          isNoNetError: true
        });
```

```
},
     fail: function (res) {
      that.setData({
         isNoNetError: false
      });
     },
     complete: function (res) {
      wx.stopPullDownRefresh();
      that.setData({
         isLoading: false
      });
    }
  });
},
loadData: function() {
  var that = this;
  this.bannerList(),this.goodsList();
},
onPullDownRefresh: function() {
  this.loadData();
},
/**
* 页面上拉触底事件的处理函数
 */
onReachBottom: function () {
  if (this.data.isHideLoadMore) {
   this.loadMore();
 }
},
loadMore: function () {
  var that = this;
  that.setData({
     isHideLoadMore: false
  });
  wx.request({
     url: app.globalData.apiUrl + 'v1.0/goods',
    data: { offset: that.data.goods.length, size: 15 },
     success: function (res) {
      that.setData({
         goods: that.data.goods.concat(res.data.goods)
      });
     },
     fail: function (res) {
    },
```

```
complete: function (res) {
        that.setData({
          isHideLoadMore: true
        });
   });
  },
  onLoad: function (options) {
   this.loadData();
  },
  onTabItemTap: function (item) {
    wx.startPullDownRefresh();
  },
  onShareAppMessage: function () {
    return app.share({ title: "", desc: "", path: "" });
  },
  bannerClick: function (e) {
    var bannerType = e.currentTarget.dataset.banner_type,targetUrl =
e.currentTarget.dataset.target_url;
    switch (bannerType) {
      case "1":
        wx.navigateTo({
         url: targetUrl,
        });
        break:
      case "2":
        wx.navigateTo({
          url: './webview?url=' + targetUrl,
        });
        break;
      default:
        break;
    }
  }
})
```

index.json

```
{
   "enablePullDownRefresh": true,
   "navigationBarBackgroundColor": "#FF4C42",
   "usingComponents": {
      "page-loading": "../../component/page-loading/page-loading",
      "net-error-tips": "../../component/net-error-tips/net-error-tips",
      "load-more": "../../component/load-more/load-more"
   }
}
```

index.wxml

```
<!--index.wxml-->
<page-loading isLoading="{{isLoading}}" isOperate="{{isOperate}}"></page-loading>
<view class="container" wx-if="{{!isLoading || isOperate}}">
 <view class="for-margin-top"></view>
 <! - - banner广告区域-->
 <view class="banner portal-banner-bg">
    <swiper autoplay="true" interval="5000" indicator-active-color="#d81e06"</pre>
circular="true" >
    <block wx:for="{{banner}}" wx:key="id">
      <swiper-item data-banner_type="{{item.banner_type}}" data-</pre>
target_url="{{item.target_url}}" bindtap="bannerClick">
      <image src="{{item.image_url}}" style="width:100%;height:100%;"</pre>
mode='aspectFill'></image>
      </swiper-item>
    </block>
    </swiper>
    <view class="swiper-count">{{swiperCount}}</view>
 </view>
 <view class="for-margin-top"></view>
 <! -- goods商品列表 -->
 <block wx:key="item" wx:for="{{goods}}">
    <view style="" class="goods_list tuan-new div">
        <view class="tuan_g div {{goods.length==index+1 ? 'tuan_g_last' : ''}}">
            <view class="i"></view>
            <navigator hover-class="none" url="./goods?goods_id={{item.goods_id}}">
```

```
<view class="tuan g img div">
                   <image data-id="goods_img" class=" loadThumb img" mode="widthFix"</pre>
src="{{item.image_url}}" data-id="goods_img" style='width:100%;height:100%;'></image>
  </view>
                <view class="tuan goods info div">
                   <view class="p tuan_goods_name">{{item.goods_name}}</view>
                       <view class="p tuan goods cx">
                           <view class="span"></view>
                       </view>
           </view>
               <view class="tuan_goods_core div">
                   <view class="tuan_goods_btn div">
                   <view class="span">去开团</view>
                    </view>
                   <view class="tuan_goods_price">
                       <view class="red span">
                           <view class="small">[]</view>
                        <span>{{item.group_price}} </span>
                       </view>
                       <view class="span group-desc"> {{item.group_number}}人团.单买
价{{item.alone_price}}元</view>
                   </view>
               </view>
           </navigator>
</view>
</view>
</block>
</view>
<net-error-tips isNoNetError="{{isNoNetError}}" bind:loadData="loadData"></net-error-</pre>
<load-more isHideLoadMore="{{isHideLoadMore}}"></load-more>
```

order.js

```
// pages/order.js
//获取应用实例
const app = getApp();
var orderId = ,
    order = require('../utils/order.js');
Page({
```

```
data: {
    isLoading: true,
    isOperate: false,
    isNoNetError: true,
    order: {},
    _: app.globalData._.config,
    showPage: false
 },
 loadData: function() {
    var that = this;
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/users/orders/' + orderId,
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      success: function (res) {
        if (res.data.result == 'fail') {
          that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
that.data._.error_text[6] })
        } else if (res.data.result == 'ok') {
          that.setData({
            order: res.data.order,
            showPage: true
          });
        }
        that.confirmCallback = function () {
          app.goOrders();
        }
        that.setData({ isLoading: false, isOperate: false })
        that.setData({
          isNoNetError: true
        });
      },
      fail: function (res) {
        that.setData({
          isNoNetError: false
        });
      },
      complete: function (res) {
        wx.stopPullDownRefresh();
      }
    });
 },
```

```
orderReceive: function (e) {
   var that = this, orderId = e.currentTarget.dataset.order_id;
   order.receive(that,orderId, function (res) {
     if (res.data.result == 'ok') {
        that.prevPageRefresh(),
        wx.startPullDownRefresh();
     }
   }, function (res) {
   });
 },
 orderCancel: function(e) {
   var that = this;
   order.cancel(that,orderId, function (res) {
      if (res.data.result == 'ok') {
        that.prevPageRefresh(),
       wx.startPullDownRefresh();
     }
   }, function (res) {
   });
 },
 orderBuy: function (e) {
   if (this.data.isPayDisable) return true;
   this.setData({ "isPayDisable": true });
   var that = this;
   orderId = e.currentTarget.dataset.order id,
      order.pay(orderId, function (res) {
        if (res.data.result == 'fail') {
          that.setData({ "isPayDisable": false }),
          that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
res.data.error_info });
        }else if (res.data.result == 'ok') {
          order.goPay(res.data.param, function () {
            // 支付成功
            that.prevPageRefresh(),
            order.paySuccess(orderId)
          }, function () {
            that.setData({ "isPayDisable": false })
            console.log(res)
          }, function () {
```

```
});
        }else {
          that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
that.data._.error_text[] })
        }
        that.confirmCallback = function () {
          that.setData({ "isPayDisable": false }),
         wx.startPullDownRefresh();
       }
      }, function () {
      }, function () {
     });
 },
 expressShow: function (e) {
   var that = this, orderId = e.currentTarget.dataset.order_id;
   this.setData({ showExpressModal: true, IsLoadingExpress: true, Express: null,
isNoNetErrorExpress: false });
   order.express(orderId, function (res) {
      if (res.data.result == 'ok') {
        that.setData({ Express: res.data.shipping });
     } else {
        that.setData({ isNoNetErrorExpress: true });
     }
   }, function (res) {
      that.setData({ isNoNetErrorExpress: true });
   }, function (res) {
     that.setData({ IsLoadingExpress: false });
   });
 },
 onPullDownRefresh: function () {
   this.loadData();
 },
 onLoad: function (options) {
   orderId = options.id;
   this.loadData();
```

```
onReady: function () {
},
onShow: function () {
},
onHide: function () {
},
onUnload: function () {
},
onReachBottom: function () {
},
prevPageRefresh: function () {
var pages = getCurrentPages(),
prevPage = pages.length - 2;
if (prevPage >= && pages[prevPage].route == "pages/orders") {
pages[prevPage].onPullDownRefresh();
}
}
})
```

order.json

},

```
{
  "enablePullDownRefresh": true,
  "navigationBarTitleText": "订单详情",
  "navigationBarBackgroundColor": "#F8F8F8",
  "navigationBarTextStyle": "black",
  "usingComponents": {
    "page-loading": "../../component/page-loading/page-loading",
    "net-error-tips": "../../component/net-error-tips/net-error-tips",
    "auth-dialog": "../../component/auth-dialog/auth-dialog",
    "express-dialog": "../../component/express-dialog/express-dialog",
    "right-service": "../../component/right-service/right-service",
    "winpop-mask": "../../component/winpop-mask/winpop-mask"
}
```

order.wxml

```
<page-loading isLoading="{{isLoading}}" isOperate="{{isOperate}}"></page-loading>
<express-dialog showExpressModal="{{showExpressModal}}" shippingInfo="{{Express}}"</pre>
isLoading="{{IsLoadingExpress}}" isNoNetError="isNoNetErrorExpress"
="{{ }}"></express-dialog>
<wxs src="../libs/tools.wxs" module="tools" />
<view class="body" wx-if="{{showPage}}}">
     <view class=" div mod_container" ms-class=" exp_overflow:!express_hide">
         <view id="detailCon" class="div wx_wrap" ms-visible="order.order_id !=</pre>
undefined">
             <!-- ms-class="state 1: order.total status == 2" ms-class-1="state 2:
order.total_status == 3" ms-class-2="state_3: order.total_status == 4"-->
             <view class="div state {{order.state_class}}">
                 <view class="div state step" >
                    <view class="ul">
                          <view class="li state_step_1 "> </view>
                          <view class="li state_step_2"> </view>
                          <view class="li state step 3"> </view>
                      <view class="span state arrow">
                 <view class="i state_arrow_i"> </view>
                 <view class="i state_arrow_o"> </view>
```

```
</view>
                 </view>
                 <view class="div address">
                     <view class="div address row" ms-if="order.lucky status == '3' ||</pre>
order.lucky_status == '0' || order.pay_status != 2 || order.order_status != 1">
                          <view class="div address tit">订单状态: </view>
                          <view class="div address_cnt">
                             <view
class="b">{{_.order_status[order.order_status]}}</view>
                          </view>
                     </view>
                     <view class="div address_row">
                          <view class="div address tit">总额: </view>
                          <view class="div address cnt">
                              <view class="span address_price">{{order.order_amount}}
</view>
                              <view class="span address_paytype">{{payment_provider}}
</view>
                          </view>
                     </view>
                     <view class="div address row">
                          <view class="div address_tit">送至: </view>
                          <view class="div address_cnt">{{order.shipping_address}}
</view>
                     </view>
                     <view class="div address row">
                          <view class="div address tit">收货人: </view>
                          <view class="div address_cnt">{{order.receive_name + ' ' +
order.mobile}} </view>
                     </view>
                     <view class="div address row">
                          <view class="div address_tit">订单编号: </view>
                         <view class="div address_cnt" id="canselect">{{order.order_sn}}
</view>
                     </view>
                     <view class="div address_row">
                          <view class="div address_tit">下单时间: </view>
                          <view class="div address_cnt">{{order.order_time}} </view>
                     </view>
                     <!--<view class="div address_row" ms-if="coupons.length>0">
                          <view class="div address_tit">优惠信息[] </view>
                          <view class="div address_cnt posi_rela"> <view</pre>
class="span">{{coupons[0].event_desc}} </view>
                          <view class="span coupon icon order" ms-</pre>
if="order.coupons.length>0"> </view> </view>
                     </view>-->
                     <view class="div address row" ms-</pre>
visible="order.shipping_status>=1">
                          <view class="div address_tit">配送方式: </view>
```

```
<view class="div address cnt">{{order.shipping name}}
                             <view class="br"></view>{{order.tracking_number}} </view>
                      </view>
                     <!--<view class="div address_row" ms-if = "order.pay_status == 2 &&
order.order status == 1 && lucky status != '0'">
                          <view class="div address_tit">抽奖状态□ </view>
                         <view class="div address cnt" style="color:#laad19;font-weight:</pre>
bold">{{getPrize()}} </view>
                      </view>-->
                 </view>
                 <view class="div state_btn" hidden="{{!(order.order_status==0)}}">
                      <view class="a state_btn_1" href=""</pre>
                        ms-click="orderCancel(order.order id)" data-
order id="{{order.order id}}" bindtap="orderCancel">取消订单 </view>
                      <view class="a state btn 2" href=""</pre>
                        ms-click="orderBuy(order.order id)" bindtap="orderBuy" data-
order_id="{{order.order_id}}" id="btn_order_done">去支付 </view>
                <!-- <view class = "state_btn" ms-visible = "order.total_status == 1 ||
order.total status == 2">
                      <view class="state_btn_2" href="">售货服务 </view>
                 </view> -->
                 <view class="div state_btn" hidden="{{!(order.order_status==10 ||</pre>
order.order status==3)}}">
                      <view class="a state_btn_1" hidden="{{!(order.order_status==10 ||</pre>
order.order_status==3)}}" ms-click="expressShow" bindtap ="expressShow" data-
order id="{{order.order id}}">查看物流 </view>
                      <view class="a state_btn_3" data-order_id="{{order.order_id}}"</pre>
bindtap ="orderReceive" hidden="{{!(order.order status==3)}}" ms-
click="orderReceive(order.order id)">确认收货 </view>
                 </view>
                 <view class="div state btn"> </view>
             </view>
             <view class="div ptit">商品信息
             <view class="div order order_height">
                 <view class="div order bd">
                      <view class="div order_glist">
                          <navigator
url="goods?goods_id={{order.order_goods.goods_id}}">
                          <view class="div order item">
                              <view href="" class="a order_goods"</pre>
style="float:left;border-bottom:none;">
                                  <view class="div order_goods_img">
                                     <image mode="aspectFill" class="img"</pre>
src="{{order.order_goods.image_url + '?x-oss-
process=image/resize,w_380,h_380'}}"></image>
```

```
</view>
                              </view>
                              <view class="div order goods info">
                                  <view class="a order goods" ms-
click="showGoods(item.goods_target, item.goods_id)">
                                       <view class="div
order_goods_name">{{order.order_goods.goods_name}} </view>
                                       <view class="div order goods attr">
                                          <view class="br"></view>
                                           <view class="div order_goods_attr_item">
                                               <view class="div order goods price"> <view
class="i">[ </view>{{order.order_goods.market_price}}
                                               <!--<view ms-if="specDesc"
class="i">/{{specDesc}} </view> </view>-->
                                           </view>
                                       </view>
                                  </view>
                              </view>
                          </view>
                         </view>
                       </navigator>
                      <!--<view class="div" ms-if="group_target != 'group_li.html' &&
order.pay_status != 0">
                          <view class ="a mt_status_lk marg_right" ms-</pre>
href="{{group_target}}?id={{order.group_order_id}}" ms-if="isShowGroupDetail">查看团详情
</view>
                      </view>-->
                      <view class="div" wx:if="{{order.group_order_id != 0 &&</pre>
order.pay_status != 0}}">
                         <navigator
url="group?id={{order.group_order_id}}&order_id={{order.order_id}}" >
                             <view class ="a mt_status_lk marg_right" ms-</pre>
href="{{group_target}}?id={{order.group_order_id}}&order_id={{order.order_id}}" ms-
if="isShowGroupDetail">查看团详情 </view>
                          </navigator>
                      </view>
                 </view>
             </view>
         </view>
        <right-service></right-service>
     </view>
    </view>
    </view>
<winpop-mask showWinpopModal="{{showWinpopModal}}"</pre>
showWinpopCancel="{{showWinpopCancel}}" winpopContent="{{winpopContent}} "
```

orders.js

```
// pages/orders.js
//获取应用实例
const app = getApp();
var order = require('../utils/order.js')
//orderType = 0,
Page({
  data: {
    isLoading: true,
    isOperate: false,
    isNoNetError: true,
    orders: [],
    isHideLoadMore: true,
    isNoNetError: true,
    showExpressModal: false,
    _: app.globalData._.config,
    navStatus: null
  },
  loadData: function () {
    var that = this;
   //请求订单列表
    that.data.orders = [];
    wx.request({
      url: app.globalData.apiUrl + 'v1.0/users/orders',
      header: {
        'AccessToken': wx.getStorageSync("token")
      data: { order_status: (that.data.navStatus == null ? "" :
that.data.navStatus),offset: that.data.orders.length, size: 30 },
      success: function (res) {
        if (res.data.result == 'ok') {
          that.setData({
            orders: res.data.order_list
          });
        }
        that.setData({
          isNoNetError: true
```

```
});
    },
    fail: function (res) {
     that.setData({
        isNoNetError: false
      });
    },
    complete: function (res) {
      wx.stopPullDownRefresh();
      that.setData({
        isLoading: false
      });
    }
 });
},
onPullDownRefresh: function () {
 this.loadData();
},
onReachBottom: function () {
 if (this.data.isHideLoadMore) {
   this.loadMore();
 }
},
loadMore: function () {
  var that = this;
  that.setData({
    isHideLoadMore: false
  });
  wx.request({
    url: app.globalData.apiUrl + 'v1.0/users/orders',
    header: {
      'AccessToken': wx.getStorageSync("token")
    },
    data: { offset: that.data.orders.length, size: 15 },
    success: function (res) {
     if (res.data.result == 'ok') {
        that.setData({
          orders: that.data.orders.concat(res.data.order_list)
       });
      }
    },
    fail: function (res) {
    },
    complete: function (res) {
```

```
that.setData({
        isHideLoadMore: true
      });
   }
 });
},
navChange: function(e) {
  var navStatus = e.currentTarget.dataset.nav_status;
 if ('3' == navStatus){
   navStatus = null;
  this.setData({ navStatus: navStatus,isLoading: true,isOperate: true }),
 this.loadData()
},
onLoad: function (options) {
 this.setData({ navStatus: options.order_type || null}),
 this.loadData();
},
orderReceive: function (e) {
  var that = this, orderId = e.currentTarget.dataset.order_id;
 order.receive(that,orderId, function (res) {
   if (res.data.result == 'ok') {
      wx.startPullDownRefresh();
   }
 }, function (res) {
 });
},
orderCancel: function(e) {
  var that = this, orderId = e.currentTarget.dataset.order_id;
  order.cancel(that,orderId, function (res) {
   if (res.data.result == 'ok') {
      wx.startPullDownRefresh();
   }
 }, function (res) {
 });
},
orderBuy: function(e) {
  if (this.data.isPayDisable) return true;
 this.setData({ "isPayDisable": true });
  var that = this, orderId = e.currentTarget.dataset.order_id;
  order.pay(orderId,function(res) {
```

```
if (res.data.result == 'fail') {
        that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
res.data.error_info });
      } else if(res.data.result == 'ok') {
        order.goPay(res.data.param,function(){
          // 支付成功
          order.paySuccess(orderId)
        }, function (res) {
          that.setData({ "isPayDisable": false })
          console.log(res)
        },function() {
        });
      } else {
        that.setData({ showWinpopModal: true, showWinpopCancel: false, winpopContent:
that.data._.error_text[] })
      }
      that.confirmCallback = function () {
        wx.startPullDownRefresh(),
        that.setData({ "isPayDisable": false })
      }
   },function() {
   },function() {
   });
 },
 expressShow: function(e) {
   var that = this, orderId = e.currentTarget.dataset.order_id;
    this.setData({ showExpressModal: true, IsLoadingExpress: true, Express: null,
isNoNetErrorExpress: false});
   order.express(orderId, function (res) {
      if (res.data.result == 'ok'){
        that.setData({ Express: res.data.shipping});
     }else{
        that.setData({isNoNetErrorExpress:true});
      }
```

```
}, function (res){
that.setData({ isNoNetErrorExpress: true });
},function(res){
that.setData({ IsLoadingExpress: false});
});
},
onTabItemTap: function (item) {
this.setData({ navStatus: null }),
wx.startPullDownRefresh();
},
onReady: function () {
},
onShow: function () {
//wx.startPullDownRefresh();
},
onHide: function () {
},
onUnload: function () {
}
})
```

orders.json

```
{
  "enablePullDownRefresh": true,
  "navigationBarTitleText": "我的订单",
  "navigationBarBackgroundColor": "#F8F8F8",
  "navigationBarTextStyle": "black",
  "usingComponents": {
      "page-loading": "../../component/page-loading/page-loading",
      "net-error-tips": "../../component/net-error-tips/net-error-tips",
      "auth-dialog": "../../component/auth-dialog/auth-dialog",
      "express-dialog": "../../component/express-dialog/express-dialog",
      "right-service": "../../component/right-service/right-service",
      "winpop-mask": "../../component/winpop-mask/winpop-mask",
      "load-more": "../../component/load-more/load-more"
}
```

orders.wxml

```
<!--index.wxml-->
<page-loading isLoading="{{isLoading}}" isOperate="{{isOperate}}"></page-loading>
<express-dialog showExpressModal="{{showExpressModal}}" shippingInfo="{{Express}}"</pre>
isLoading="{{IsLoadingExpress}}" isNoNetError="isNoNetErrorExpress" _="{{_}}}"></express-
dialog>
<wxs src="../libs/tools.wxs" module="tools" />
    <view class="body">
    <view class="div" id="orders" ms-controller="root">
            <!-- <include src="common/express.wxml"/> -->
            <view class="div nav fixed">
                <view class="a fixed_nav_item {{navStatus == 3 || navStatus == undefined</pre>
? 'nav cur' : ''}}" data-nav status="3" bindtap="navChange">
                    <view class="span nav_txt">全部订单</view>
                </view>
                <view class="a fixed nav item {{navStatus == 0 ? 'nav cur' : ''}}" data-</pre>
nav status="0" bindtap="navChange">
                    <view class="span nav_txt nav_payment">待付款
                         <view class="b nav_payment_num" style="display:none;"></view>
                     </view>
```

```
</view>
                <view class="a fixed_nav_item {{navStatus == 1 ? 'nav_cur' : ''}}" data-</pre>
nav_status="1" bindtap="navChange">
                     <view class="span nav_txt nav_receiving">待收货
                         <view class="b nav_receiving_num" style="display:none;"></view>
                     </view>
                </view>
            </view>
            <view class="div" id="dealliststatus1" ms-class="scroll coup:confirm code">
                <view class="div order" ms-repeat-order="orders" wx:key="" wx:for-</pre>
item="order" wx:for="{{orders}}" >
                     <view class="div order hd">
                         {{tools.formatTimeStamp(order.order_time)}}
                     </view>
                     <view class="div order_bd ">
                         <view class="div order_glist">
                             <navigator url="./order?id={{order.order_id}}" >
                             <view class='a' ms-href="order.html?id={{order.order_id}}">
                                 <view class="div order_goods" data-url="">
                                     <view class="div order_goods_img ">
                                          <image mode="aspectFill" class="img" alt=""</pre>
src="{{order.order_goods.image_url + '?x-oss-
process=image/resize,w_380,h_380'}}"></image>
                                     <view class="div order_goods_info">
                                          <view class="div
order_goods_name">{{order.order_goods.goods_name}}</view>
                                          <view class="div order_goods_attr">
                                              <view class="div order_goods_attr_item">
                                                  <view class="div order goods price">
                                                      <view class="i">
[]</view>{{order.order_goods.market_price}}
                                                      <view class="i">/件</view>
                                                  </view>数量:1
                                              </view>
                                          </view>
                                     </view>
                                 </view>
                             </view>
                             </navigator>
                             <view class="div order ft">
                                 <view class="div order_total">
                                     <view class="span order_total_info">共1件商品 , 免运
```

```
费</view>
                                      <view class="span order_price">实付:
                                          <view class="b"><view class="small">
[]</view>{{order.order_amount}}</view>
                                      </view>
                                      <view class="span coupon icon"</pre>
wx:if="order.coupons.length>0"></view>
                                  <view class="div order_opt">
                                     <view class="div " wx:if = "order.pay_status == 2 &&</pre>
order.order status == 1">
                                      </view>
                                      <view class="div" wx:if = "order.pay_status != 2 ||</pre>
order.order_status != 1">
                                          <view class="span
order_status">{{_.order_status[order.order_status]}}</view>
                                      <view class="div order_btn"</pre>
hidden="{{!(order.order_status==0)}}">
                                          <view class="a order btn buy"</pre>
wx:click="orderBuy(order)" bindtap="orderBuy" data-order_id="{{order.order_id}}">去支
付</view>
                                          <view class="a" data-
order id="{{order.order id}}" bindtap="orderCancel">取消订单</view>
                                      </view>
                                      <view class="div order_btn"</pre>
hidden="{{!(order.order status==10 || order.order status==3)}}">
                                          <view class="a order btn receive"
hidden="{{!(order.order_status=3)}}" data-order_id="{{order.order_id}}" bindtap
="orderReceive" ms-click="(order.order_id)">确认收货</view>
                                          <view class="a"
hidden="{{!(order.order status==10 || order.order status==3)}}" data-
order_id="{{order.order_id}}" bindtap ="expressShow">查看物流</view>
                                      </view>
                                  </view>
                              </view>
                         </view>
                     </view>
                 </view>
                 <view class="div wrap_position" ms-class="pullUp_hide:pullUp_hide" ms-</pre>
class="pullUp_show:pullUp_show">
                     <view class="div posi_abso" ms-class="up:isloading" wx:if="{{is_over</pre>
== 0 && pullDown == 1 && page.load == 1}}">
```

src=" /xhBQAAACBjSFJNAAB6JgAAgIQAAPoAAACA6AAAdTAAAOpgAAA6mAAAF3CculE8AAAABmJLR0QAAAAAAAD5Q7t/A AAACXBIWXMAAAsSAAALEqHS3X78AAAGwElEQVRo3u2af4wdVRXHP2/XLm1BTMCCtGNLEQS6nUoVEiIwUEkMDTGZB qq0J0rQSBSE4sMKhEMW5aQCtg0W6w9Qp4Gm/AGUMRL5IabJiKSgQnWEVi1gy0CXrcJCIuiybPnjztv03jfv7XvPN wYSvskme879ce537o9z7rmvQskQkRnACcB0Vd1Xpq2ekoksBXYDMbBHRJa/Z8kAa4Fp2f9TM/ndRUZEjhSRD7VQ9 aOW/JEW+p4uIrNKJ5MZug/YCwyJyMp0jDbpfwkwCKQiEovIEaWRAS4HfKAC9AFrRWR+l4jMAELgg5nqDGB1mWSOs eReYH03yGQDt5fu3DLJ3FugW5Qtj44hIicBFxUU3VMaGVV9CHiwoGitiEz9H/isLxjLM8DtpZHJ8A3gLUs3F7iiE xaZLzqjyI6qjpZKRlV3AhsKiq4VkaPaJDIVWFNQ9EtVfbjdsXXqNL8N2KHJIcB3Ld1uS37JklcBsy3df4Er0xlUx fpS04GNwBJgBzCgqvcVNRSRrwI/stT7gY+p6vNZnaXAncBBwAhwoarek5UdjPEph1h9rFHVVQ1sngrcDHwaEyJdo KpDtXJ7Zq4GlgIfAFxgi4g8ICLzCvq+HfhTwceZUxNU9W5MFHA6MLNGJMNhBUQGgRsKSMwWkc3AY5j91QssAm5pN jNbqbMKBj4K3AZcp6qv50qfCfwm6xzq78ACVf0PLaDA3pdU9Y5c+TSqClzLqRqvjxdUdXyZ9uZLPM87DvAKGvUAp wArPM/7t+d5T8VxPBbH8W7P8x7PPsrDwApVfb0VIpm9ezF7ZAi4UVU3ZSQqnuctAyLMkp/SoItfxXE87vvsmekDv qdcqllqjfA0sExVk1YH3ipEZCawGTizSbX9wF3Apao6XFNOGLCqjqArReQnmHD9nAad9W088/HdJqP8bBIiTwGXq erv7IJKk0a1KPZm4NgGVQ5W1Te6yURE9lJ8VdgLCLBRVceK2jb1M9mx3A98E7D3wm+7TSTDA5Y8glklx6vqzxsRg eb7okZoBBN7bQYGgMWYuOniEoiACZemAadhjmJR1V0l2Xof/xdUAETkEuAawGlSdwyzvL6mqo+WPbB169YtwlwN5 tF8bw8CA9Vq9baKiJyI8RuVFmwAvAjMUdW3SyQyJbMzo8UmbwP9PcD8NoqAzGrDSKc4sk0bvcD8Hkyw2M5X3q0qq yWTeQkzM61iFHiyR1X/BqwAngVeneTvj8D5JR0hWq20Aedl9iYb0x4gqFarz5c9rvfRKVre+Gma9gGXAudijmhxH KflcL9VhGHYh7m/nAZsA9YEQTDcNTJpmhYFnFscxzmvBDI3Ad/KqYYwPnBjEARjzdo2DTTTNJ2XpukjwBbqI2c/T dNpdB8XWvIRmGvBH8IwbHY1KCaTpumH0zTdgDm2z27Qdgho6XrcJl5ooF8IbA3DcHMYhr0LKkxYZmmaVjDR8GpMw qER/qksdxzn191mEobhAuAXwNFNqr2JybfdEATBeELSJrMSK+NhYRT4ITDq0M4wQJIkJwJfAFJqk+u6Lc9WFEU9G L+1ALjf9/1tGaFaIuNq6jM4eawPqmD8WcUm0yq7AybHfKXj0M/UFEmS9ANPANMz1aPAWa7rthRRRFG0iQN7ZAw4x /f98dk0w3AWJidxAcWH1e4gCI6uCfae+UtBg13A5xzHWZwnkuHWHBEw+bFT7Q7i0K7LrkRRdBQTN3sPsCGKor6aI giCF4MgWI5J+j1eMLYdWB3k8R1ge/b/q5jrcr/j0PfbvSRJsgSTiLMx7nvi0P5UHMc7gJE4jp+04/iTuXpvYK7Ee RwHXGZ3GATBtozQCg6keP+BWYrjqJu67BCYA7zs0M6bBYMlSZKpGMdpPwY96Lru4hyZ3wMn58q3e563MDc7twJfL /gYH/d9/+Ui22EYTsFkSfcEQTDhlaAuB+A4zv6MdTNcUUDkLcz9PY+FlrzAkq8HlgGH53SHAgp8pchwdno9V1TW9 itAkiQzMeGGjQ2u6+60dL2WPMGe7/v/ygjZuCiKopNpE508aaym/rjch3nm6AQ/pv7g6QHWRVHUzqWxPTJJkpwCf LGg6DrXdYc7YeL7/ij1yxNMtv/zpZEBvkz9obEd+GknRHKEHsEkyYvslUZmuEBXbdVJToJVmBeBPF4rk8wtHPBDA Otd193aBSL4vr8LuAqT4QdzHR4ojYzruvswfuN04B0u63b15ya+738f830uz2B8zV/bad/WadEu4jqexKSNanjF8 7zD0+1vMpT9Ey37AfcHZRordWYA4jj+LMbz/9nzvLbf9tvB00XbJi+MSyc4AAAAAElFTkSuQmCC"/></view>

```
<view class="div center " id="center pullup">
                      <view class="span orders_text"</pre>
id="noOrders">{{pullload_text.no_orders}}</view>
                   </view>
                    </view>
               </view>
   </view>
           <right-service></right-service>
</view>
<view style="div height:58px;visibility:hidden "></view>
</view>
<winpop-mask showWinpopModal="{{showWinpopModal}}"</pre>
showWinpopCancel="{{showWinpopCancel}}" winpopContent="{{winpopContent}} "
bind:cancelCallback="cancelCallback" bind:confirmCallback="confirmCallback"></winpop-
mask>
<net-error-tips isNoNetError="{{isNoNetError}}" bind:loadData="loadData"></net-error-</pre>
<load-more isHideLoadMore="{{isHideLoadMore}}"></load-more>
```

personal.js

```
userInfo: res,
    });
  }, function () {
    thisPage.setData({
      showAuthModal: true,
    });
  });
},
goSwitchTab(e) {
  wx.switchTab({
    url: e.currentTarget.dataset.url,
 });
},
goReLaunch(e) {
  wx.reLaunch({
    url: e.currentTarget.dataset.url,
 });
},
onLoad: function (options) {
 var that = this;
},
onReady: function () {
},
onShow: function () {
 this.setData({showAuthModal: false});
  this.loadData();
},
onHide: function () {
},
* 生命周期函数--监听页面卸载
onUnload: function () {
},
```

```
* 页面相关事件处理函数--监听用户下拉动作

*/
onPullDownRefresh: function () {

},

/**

* 页面上拉触底事件的处理函数

*/
onReachBottom: function () {

}

}
```

personal.json

```
{
   "navigationBarBackgroundColor": "#FF4C42",
   "usingComponents": {
      "auth-dialog": "../../component/auth-dialog/auth-dialog"
   },
   "navigationBarTitleText": " "
}
```

personal.wxml

```
<!-- start -->
        <view class="div">
            <view class="div nav">
                <view class="ul nav list">
                     <view class="li nav_item nav_order">
                         <view bindtap="goSwitchTab" data-url="./orders" class="a">
                             <view class="a">
                                 <view class="div nav item hd">我的订单</view>
                             </view>
                         </view>
                         <view class="div nav item bd">
                             <view bindtap="goSwitchTab" data-url="./orders"</pre>
class="a"><view class="span nav_item_txt" >全部</view></view>
                             <view class=" a" bindtap="goReLaunch" data-</pre>
url="./orders?order type=0">
                                 <view class="span nav_item_txt">待付款<view class="i
nav_item_num" id="need_pay_count" style="{{!unpaid || unpaid == 0 || unpaid ==
undefined? 'display:none' : ''}}">{{unpaid}}</view></view>
                             </view>
                             <view class="a" bindtap="goReLaunch" data-</pre>
url="./orders?order_type=1">
                                 <view class="span nav_item_txt">待收货<view
class="nav_item_num" id="need_recv_count" style="{{!unreceived || unreceived == 0 ||
unreceived == undefined ? 'display:none' : ''}}">{{unreceived}}</view></view>
                             </view>
                         </view>
                    </view>
                     <view class="li nav item nav cheap">
                         <view class="div nav item hd"><view class="a"</pre>
bindtap="goSwitchTab" data-url="./groups" href="groups.html" open-type="switchTab"> 我
的拼团 </view></view>
                    </view>
                    <view class="li nav item nav cart" ptag="12478.10.1">
                         <view class="div nav_item_hd"><navigator url="addresses"</pre>
class="a" href="addresses.html" >我的地址 </navigator></view>
                    <view class="li nav_item nav_cart" ptag="12478.10.1" plain="true" >
                         <view type="primary" class="post_sale div</pre>
nav_item_hd_coupons_sale" open-type="contact">
                             <view class="coupons_a div" href="post_sale.html" >售后服务
</view>
                             <button type="default-light" size="30"</pre>
style="display:block;line-height:4;z-index:999999999;width:369px;height:40px;margin-
left:6px;background-color:red;margin-top:-43px;opacity:-0.5;" open-type="contact">
</button>
                         </view>
```

webview.js

```
// pages/webview/webview.js
Page({
 /**
 * 页面的初始数据
  */
 data: {
 },
 /**
 *生命周期函数--监听页面加载
 onLoad: function (options) {
  this.setData({
     url: options.url
   });
 },
 *生命周期函数--监听页面初次渲染完成
  */
 onReady: function () {
 },
 * 生命周期函数--监听页面显示
 onShow: function () {
 },
```

```
*生命周期函数--监听页面隐藏
  */
 onHide: function () {
 },
 /**
 *生命周期函数--监听页面卸载
 onUnload: function () {
 },
 * 页面相关事件处理函数--监听用户下拉动作
 onPullDownRefresh: function () {
 },
 * 页面上拉触底事件的处理函数
 onReachBottom: function () {
 },
 /**
 * 用户点击右上角分享
 onShareAppMessage: function () {
 }
})
```

webview.json

```
{
   "navigationBarBackgroundColor": "#F8F8F8"
}
```

webview.wxml

```
<web-view src="{{url}}"></web-view>
```

cron.js

```
//获取应用实例
const app = getApp();
function run(successCallback, failCallback, completeCallback) {
wx.request({
url: app.globalData.apiUrl + "v1.0/project/crontab",
success: function (res) {
successCallback(res);
},
fail: function (res) {
failCallback(res);
},
complete: function (res) {
completeCallback(res);
}
})
}
module.exports = {
run: run
}
```

order.js

```
//获取应用实例
const app = getApp();

function cancel(that,orderId,successCallback, failCallback){

  that.cancelCallback = function() {
    that.setData({showWinpopModal: true});
  },
```

```
that.confirmCallback = function() {
   wx.request({
      url: app.globalData.apiUrl + "v1.0/users/orders/" + orderId,
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
      method: "DELETE",
      success: function(res){
        successCallback(res);
      },
      fail: function (res){
        failCallback(res);
      },
      complete: function(){
      }
   })
 }
 that.setData({ showWinpopModal: true, winpopContent: "确定"取消订单"吗?",
showWinpopCancel: true } )
}
function express(orderId, successCallback, failCallback, completeCallback){
 wx.request({
   url: app.globalData.apiUrl + 'v1.0/orders/' + orderId + "/express",
   success: function (res) {
      successCallback(res);
   },
   fail: function (res) {
     failCallback(res);
   },
   complete: function (res) {
      completeCallback(res);
   }
 });
}
function receive(that,orderId, successCallback, failCallback){
 that.cancelCallback = function () {
   that.setData({ showWinpopModal: true });
 },
 that.confirmCallback = function () {
   wx.request({
      url: app.globalData.apiUrl + "v1.0/users/orders/" + orderId + "/" + "receive",
      header: {
        'AccessToken': wx.getStorageSync("token")
      },
```

```
method: "POST",
      success: function (res) {
        successCallback(res);
      },
      fail: function (res) {
        failCallback(res);
      },
      complete: function () {
   })
  }
  that.setData({ showWinpopModal: true, winpopContent: "确定"确认收货"吗?",
showWinpopCancel: true })
 // wx.showModal({
 // title: '确定 " 确认收货 " 吗?',
  // content: '',
  // success: function (res) {
 // }
 // });
}
function pay(orderId, successCallback, failCallback, completeCallback){
  var that = this;
  wx.request({
    url: app.globalData.apiUrl + 'v1.0/users/orders/' + orderId + "/wxpay",
    header: {
      'AccessToken': wx.getStorageSync("token")
    },
    success: function (res) {
     successCallback(res);
    },
    fail: function (res) {
     failCallback(res);
    complete: function (res) {
      completeCallback(res);
 });
}
function goPay(payParams, successCallback, failCallback, completeCallback){
  wx.requestPayment({
    'timeStamp': payParams.timeStamp,
    'nonceStr': payParams.nonceStr,
    'package': payParams.package,
    'signType': payParams.signType,
```

```
'paySign': payParams.paySign,
    success:function (res) {
     successCallback(res)
    },
    fail:function(res){
      failCallback(res);
      if (res.errMsg == "requestPayment:fail cancel"){
      }else{
        wx.showToast({title: res.errMsg,icon: "none"})
      }
    },
    complete: function(res){
      completeCallback(res);
    }
 });
}
function paySuccess(orderId) {
  wx.request({
    url: app.globalData.apiUrl + 'v1.0/users/orders/' + orderId,
    header: {
      'AccessToken': wx.getStorageSync("token")
    },
    success: function (res) {
      if (res.data.result == 'ok') {
        if (res.data.order.group_order_id && res.data.order.group_order_id != '0') {
          wx.redirectTo({ 'url': 'group?id=' + res.data.order.group_order_id });
        } else {
          wx.redirectTo({ 'url': 'order?id=' + orderId });
        }
      } else {
        wx.redirectTo({ 'url': 'orders' });
      }
    }
 });
}
module.exports = {
  cancel: cancel,
  pay: pay,
```

```
goPay: goPay,
  receive: receive,
  express: express,
  paySuccess: paySuccess
}
```

token.js

```
//获取应用实例
const app = getApp();
function run(successCallback, failCallback, completeCallback) {
var token = wx.getStorageSync("token");
if(!token) return;
wx.request({
url: app.globalData.apiUrl + "v1.0/tokens",
method: "DELETE",
header: {
'AccessToken': wx.getStorageSync("token")
success: function (res) {
successCallback(res);
},
fail: function (res) {
failCallback(res);
},
complete: function (res) {
completeCallback(res);
}
})
}
module.exports = {
run: run
}
```

util.js

```
// 时间格式化输出,如3:25:19 86。每10ms都会调用一次
function dateformat(micro_second) {
```

```
// 秒数
  var second = Math.floor(micro_second / 1000);
  // 小时位
  var hr = Math.floor(second / 3600);
  // 分钟位
  var min = Math.floor((second - hr * 3600) / 60);
  // 秒位
  var sec = (second - hr * 3600 - min * 60); // equal to => var <math>sec = second % 60;
 // 毫秒位,保留2位
  var micro_sec = Math.floor((micro_second % 1000) / 10);
  return [hr, min, sec].map(formatNumber);
}
const formatNumber = n \Rightarrow \{
  n = n.toString()
 return n[1] ? n : '0' + n
}
function remove_array(array, index) {
  for (var i = ; i < array.length; i++) {</pre>
    var temp = array[i];
    if (!isNaN(index)) {
      temp = i;
    if (temp == index) {
      for (var j = i; j < array.length; j++) {</pre>
        array[j] = array[j + 1];
      }
      array.length = array.length - 1;
    }
  }
  return array;
}
/**
*多个定时器
*/
function countdowns(that, total_micro_seconds, initCallback) {
  var clock = [];
  for (var i = ; i < total_micro_seconds.length; i++) {</pre>
    var total_micro_second = total_micro_seconds[i];
```

```
if (total_micro_second <= || isNaN(total_micro_second)) {</pre>
      clock[i] = [, , ].map(formatNumber);
      if (that.timer != undefined) {
        total_micro_seconds = remove_array(total_micro_seconds, i),
        initCallback(i);
      }
      continue;
    } else {
      clock[i] = dateformat(total_micro_second);
   }
 }
 that.setData({ clock: clock });
 if (total_micro_seconds.length < 1) {</pre>
   if (that.timer != undefined) {
     clearTimeout(that.timer);
   }
 }
 that.timer = setTimeout(function () {
    var temp_array = [];
    for (var i = ; i < total_micro_seconds.length; i++) {</pre>
     var total_micro_second = total_micro_seconds[i] - 60;
     temp_array[i] = total_micro_second;
    }
    countdowns(that, temp_array, initCallback);
 }
    , 60);
}
function redirect(url){
 if (!url) return false;
 if (url == 'index' || url == 'groups' || url == 'orders' || url == 'personal') {
    wx.switchTab({
     "url": url
   });
 } else {
    var pages = getCurrentPages() //获取加载的页面
    if (pages.length >= 3) {
     wx.redirectTo({
        "url": url
     })
```

```
return true;
}

wx.navigateTo({
    "url": url,
    })
}

module.exports = {
    countdowns: countdowns,
    redirect: redirect
}
```

auth-dialog.js

```
// component/auth-dialog/auth-dialog.js
const app = getApp();
Component({
 /**
 * 组件的属性列表
  */
 properties: {
    showAuthModal: {
     type: Boolean,
     value: false,
   }
  },
  /**
 * 组件的初始数据
  */
  data: {
    appiconUrl: app.globalData._.config.app.icon_url,
    appName: app.globalData._.config.app.name,
    confirmDisabled: false
 },
  /**
 * 组件的方法列表
  */
  methods: {
```

```
// _successCallback:function(){
// this.triggerEvent("successCallback");
// },
onAuthDialogCancel: function (event) {
 this.setData({
    showAuthModal: false,
 });
},
onAuthDialogConfirm: function (event) {
  this.setData({
    showAuthModal: false,
 });
},
getUserInfo: function (e) {
  var that = this;
  console.log("-----");
  console.log(e);
  app.globalData.userInfo = e.detail.userInfo;
 wx.showLoading({
   title: '登录中...',
   icon: "none"
  });
  that.setData({
    confirmDisabled: true
 });
  app.login(function (res) {
   // that.setData({
   // userInfo: res,
   // });
   that.setData({
     showAuthModal: false,
     confirmDisabled: false
    });
    var myEventDetail = {} // detail对象,提供给事件监听函数
    var myEventOption = {} // 触发事件的选项
    that.triggerEvent('confirm', myEventDetail, myEventOption);
   wx.hideLoading();
  }, function () {
   that.setData({
     showAuthModal: true,
     confirmDisabled: false
```

```
});
    wx.hideLoading();
});
}
```

auth-dialog.json

```
{
   "component": true,
   "usingComponents": {}
}
```

auth-dialog.wxml

express-dialog.json

```
{
  "component": true,
  "usingComponents": {}
}
```

express-dialog.js

```
// component/express-dialog/express-dialog.js
Component({
  /**
 * 组件的属性列表
  */
  properties: {
    showExpressModal: {
     type: Boolean,
     value: false,
    },
    shippingInfo: {
     type: Object
    isLoading: {
      type: Boolean,
     value: true,
    },
    isNoNetError: {
     type: Boolean,
     value: false,
    },
    _: {
     type: Object
    }
  },
  /**
 * 组件的初始数据
  */
  data: {
 },
 /**
 * 组件的方法列表
  */
 methods: {
    closeExpress: function(){
      this.setData({showExpressModal : false});
   }
 }
})
```

express-dialog.wxml

```
<view class="div all_page" ms-if="confirm_code"></view>
  <view class="ul"class="div express_html" wx:if="{{showExpressModal}}"</pre>
catchtouchmove="stop">
  <view class="div dialog content">
    <view class="div express header">物流信息 </view>
            <view class="div right pos" catchtap="closeExpress">
                 <view class="div i" style='display:initial;'>
                     <image src="//pintuan-xcx.cn/v1.0/close_1.png" class="img</pre>
cancel_icon"></image>
                 </view>
                 </view>
                 <view class="div shipper" wx:if="{{shippingInfo.tracking_number}}">运单
号口<view class="span tracking number">
                     {{shippingInfo.tracking_number}}
                 </view>
            </view>
            <scroll-view scroll-y id="express_dialog" class="div express_main"</pre>
style="outline: none;">
                 <view class="ul express_ui" wx:if="{{shippingInfo.traces.length>0}}">
                     <view class="lili one_expre {{index == 0 ? 'red_color' : ''}}"</pre>
wx:for="{{shipping_info.traces}}" ms-class="">
                                 <view class="table" width="100%" height="100%">
                                      <view class="tr"><view align="center"</pre>
valign="middle" class="center_middle td exp_middle">
                                      <view class="div exp_wrapper"><view class="i fa fa-</pre>
circle exp_circle"></view></view></view><view class="td exp_detail"><view
class="p">{{item.time}}
                     </view><view class="p">
                     <view class="span" wx-if="{{item.address.length >
0}}">[{{item.address}}]</view>
                     {{item.remark}}
                     </view></view></view></view>
                 <view class="div center" wx-
if="{{isNoNetError}}">{{ .error text[8]}}</view>
            </scroll-view>
            <image class="express_loading" wx-if="{{isLoading}}" src="//pintuan-</pre>
xcx.cn/v1.0/loading_eb0d43.gif"></image>
        </view>
        <view class="div dialog_back"></view>
     </view>
```

express-dialog.wxss

```
/* component/express-dialog/express-dialog.wxss */
.dialog_back {
    position: fixed;
    z-index: 9997;
    max-width: 640px;
    width: 100%;
    height: 100%;
    background-color: #ccc;
    opacity: .8
}
.dialog_content {
    background-color: #fff;
    border-radius: 6px;
    z-index: 9999;
    position: fixed;
    width: 90%;
    height: 77%;
    left: 50%;
    top: 50%;
    max-width: 620px;
    -webkit-transform: translate(-50%, -47%);
    -moz-transform: translate(-50%, -47%);
    transform: translate(-50%, -47%)
}
.express_loading {
    display: block;
    position: absolute;
    left: 50%;
    top: 40%;
    -webkit-transform: translate(-50%, -50%);
    -moz-transform: translate(-50%, -50%);
    transform: translate(-50%, -50%);
 width: 32px;
 height: 32px;
}
.right_pos {
    float: right;
    margin-right: -13px;
    margin-top: -13px;
```

```
width: 30px;
    height: 30px;
    display: block;
    text-align: center;
    border-radius: 100%;
    background-color: red
}
.center {
 width:200px;
  margin: auto;
 text-align:center;
  position:relative;
 padding-left:15px;
}
.cancel_icon {
   width: 48px;
 height:48px;
 display:inline;
  text-align: center;
  color: #fff;
}
.express_header {
    color: #111;
    font-weight: 700;
    display: inline-block;
    font-size: 20px;
    margin: 10px 20px
}
.express_ui {
    font-size: 14px
}
.express_ui li {
    list-style-type: none
}
.express_main {
    margin: 20px auto ;
    width: 95%;
    height: 76%;
    /*overflow: scroll*/
}
.one_expre {
    margin: 10px ;
    border-bottom: 1px solid #ddd
```

```
}
.exp_circle {
    margin-right: 5px
}
.latest {
    margin: 3px 4px;
    color: #fff;
    background-color: red;
    visibility: hidden
}
.latest_show {
    visibility: visible
}
.red_color {
    color: red
}
.exp_middle {
    padding-right: 5px;
    vertical-align: middle;
    height: 100%;
    width: 25%;
    text-align: center
}
.exp_detail {
    width: 75%
}
.exp_overflow {
    height: 100%;
    overflow: hidden
}
.shipper {
    color: #000;
    font-size: 13px;
    margin-left: 22px
}
.tracking_number {
    margin-left: 10px
}
```

group-help.js

```
// component/group-help.js
Component({
 /**
 * 组件的属性列表
  */
 properties: {
   isGroupHelp: {
     type: Boolean,
     value: false,
   }
 },
 /**
 * 组件的初始数据
 data: {
 },
 /**
 * 组件的方法列表
  */
 methods: {
   close_group_desc: function() {
     this.setData({ isGroupHelp: false});
   }
 }
})
```

group-help.json

```
{
  "component": true,
  "usingComponents": {}
}
```

group-help.wxml

```
<view class="group-detail" wx:if="{{isGroupHelp}}" bindtap="close_group_desc">
<view class="div group-detail-notice-container" style="display:;" data-reactid="71">
<view class="div notice-pop-container" data-reactid="82" catchtouchmove="stop">
<view data-reactroot="" class="div notice-pop">
<view class="div mask"></view>
  <view class="div notice-pop-content">
           <view class="div notice-pop-title">如何参加拼团</view>
           <view class="ul notice-pop-list">
               <view class="li join">开团或参加别人的团</view>
               <view class="li time">在规定的时间内,邀请好友参团</view>
               <view class="li send">达到拼团人数,分别给团长和团员发货</view>
               <view class="li withdraw">未达到拼团人数,货款将自动原路返还</view>
</view>
</view>
</view>
</view>
</view>
```

group-help.wxss

```
/* component/group-help/group-help.wxss */
.group-detail .notice-pop-container {
    position: fixed;
    top: ;
    right: ;
    width: 100%;
    height: 100%;
    z-index: 10001;
}
.group-detail-notice-container {
    position: relative;
}
.group-detail .notice-pop-container {
    position: fixed;
    top:;
    right: ;
    width: 100%;
    height: 100%;
    z-index: 10001;
```

```
.group-detail .notice-pop-container .notice-pop .mask {
    position: absolute;
    top: ;
    right: ;
    width: 100%;
    height: 100%;
    background-color: #000;
    opacity: 7;
}
.group-detail .notice-pop-container .notice-pop-content {
    background-color: #fff;
    width: 290px;
    height: 235px;
    position: absolute;
    top: 50%;
    left: 50%;
    -webkit-transform: translate(-50%,-50%);
    transform: translate(-50%, -50%);
    padding: 15px;
    border-radius: 8px;
    box-sizing: border-box;
}
.group-detail .notice-pop-container .notice-pop-content:before {
    content: "[]";
    font-size: 10px;
    color: #9c9c9c;
    top: -5px;
    right: -5px;
    z-index: 2;
}
.group-detail .notice-pop-container .notice-pop-content:after, .group-detail .notice-
pop-container .notice-pop-content:before {
    line-height: 1;
    font-weight: 400;
    -webkit-font-smoothing: antialiased;
    font-family: icomoon;
    position: absolute;
    box-sizing: border-box;
}
.group-detail .notice-pop-container .notice-pop-list {
    font-size: 13px;
    color: #58595b;
```

```
padding-top: 6px;
    line-height: 31px;
}
.group-detail .notice-pop-container .notice-pop-list .li {
    position: relative;
    padding-left: 22px;
    display:inline-block;
}
.group-detail .notice-pop-container .notice-pop-list .li:before {
    background: #9c9c9c;
    content: "";
    width: 3px;
    height: 3px;
    border-radius: 100%;
    position: absolute;
    top: 15px;
    left: 8px;
}
.group-detail .notice-pop-container .notice-pop-content:after {
    content: "[]";
    font-size: 30px;
    color: #e0e0e0;
    top: -15px;
    right: -15px;
    width: 30px;
}
.goods-recommend-bottom {
    height: 50px;
    width: 100%;
    line-height: 50px;
    text-align: center;
}
.goods-recommend-bottom .goods-recommend-line {
    border-bottom: 1px solid #e0e0e0;
    height: 25px;
    width: 90%;
    margin-left: auto;
    margin-right: auto;
}
.goods-recommend-bottom .p {
    position: relative;
    top: -25px;
```

```
width: 136px;
font-size: 14px;
color: #9c9c9c;
margin-left: auto;
margin-right: auto;
background-color: #eceded;
display: block;
}
.group-detail .notice-pop-container .notice-pop-title {
width: 100%;
height: 55px;
padding-top: 18px;
margin-bottom: 15px;
text-align: center;
color: #151516;
font-size: 16px;
border-bottom: 1px solid #e0e0e0;
}
```

load-more.js

```
// component/load-more/load-more.js
Component({
/**
* 组件的属性列表
*/
properties: {
isHideLoadMore: {
type: Boolean,
value: true,
}
},
/**
* 组件的初始数据
*/
data: {
},
/**
* 组件的方法列表
*/
methods: {
}
})
```

load-more.json

```
{
  "component": true,
  "usingComponents": {}
}
```

load-more.wxml

load-more.wxss

```
/* component/page-loading/page-loading.wxss */
/* 加载更多 */
.weui-loading {
  margin: 5px;
 width: 20px;
 height: 20px;
 display: inline-block;
 vertical-align: middle;
  -webkit-animation: weuiLoading 1s steps(12, end) infinite;
 animation: weuiLoading 1s steps(12, end) infinite;
 background: transparent
url(
RoPSIxMjAiIGhlaWdodD0iMTIwIiB2aWV3Qm94PSIwIDAgMTAwIDEwMCI+PHBhdGggZmlsbD0ibm9uZSIgZD0iTT
AgMGgxMDB2MTAwSDB6Ii8+PHJlY3Qgd2lkdGg9IjciIGhlaWdodD0iMjAiIHg9IjQ2LjUiIHk9IjQwIiBmaWxsPS
IjRTlF0UU5IiByeD0iNSIgcnk9IjUiIHRyYW5zZm9ybT0idHJhbnNsYXRlKDAgLTMwKSIvPjxyZWN0IHdpZHRoPS
I3IiBoZWlnaHQ9IjIwIiB4PSI0Ni41IiB5PSI0MCIgZmlsbD0iIzk40TY5NyIgcng9IjUiIHJ5PSI1IiB0cmFuc2
Zvcm09InJvdGF0ZSgzMCAxMDUu0TggNjUpIi8+PHJlY3Qgd2lkdGg9IjciIGhlaWdodD0iMjAiIHg9IjQ2LjUiIH
k9IjQwIiBmaWxsPSIjOUI5OTlBIiByeD0iNSIgcnk9IjUiIHRyYW5zZm9ybT0icm90YXRlKDYwIDc1Ljk4IDY1KS
IvPjxyZWN0IHdpZHRoPSI3IiBoZWlnaHQ9IjIwIiB4PSI0Ni41IiB5PSI0MCIqZmlsbD0iI0EzQTFBMiIqcnq9Ij
UiIHJ5PSI1IiBOcmFuc2Zvcm09InJvdGF0ZSg5MCA2NSA2NSkiLz48cmVjdCB3aWR0aD0iNyIgaGVpZ2h0PSIyMC
IgeD0iNDYuNSIgeT0iNDAiIGZpbGw9IiNBQkE5QUEiIHJ4PSI1IiByeT0iNSIgdHJhbnNmb3JtPSJyb3RhdGUoMT
IwIDU4LjY2IDY1KSIvPjxyZWN0IHdpZHRoPSI3IiBoZWlnaHQ9IjIwIiB4PSI0Ni41IiB5PSI0MCIgZmlsbD0iI0
IyQjJCMiIqcnq9IjUiIHJ5PSI1IiB0cmFuc2Zvcm09InJvdGF0ZSqxNTAqNTQuMDIqNjUpIi8+PHJlY3Qqd2lkdG
g9IjciIGhlaWdodD0iMjAiIHg9IjQ2LjUiIHk9IjQwIiBmaWxsPSIjQkFC0EI5IiByeD0iNSIgcnk9IjUiIHRyYW
5zZm9ybT0icm90YXRlKDE4MCA1MCA2NSkiLz48cmVjdCB3aWR0aD0iNyIgaGVpZ2h0PSIyMCIgeD0iNDYuNSIgeT
0iNDAiIGZpbGw9IiNDMkMwQzEiIHJ4PSI1IiByeT0iNSIgdHJhbnNmb3JtPSJyb3RhdGUoLTE1MCA0NS450CA2NS
kiLz48cmVjdCB3aWR0aD0iNyIgaGVpZ2h0PSIyMCIgeD0iNDYuNSIgeT0iNDAiIGZpbGw9IiNDQkNCQ0IiIHJ4PS
I1IiByeT0iNSIgdHJhbnNmb3JtPSJyb3RhdGUoLTEyMCA0MS4zNCA2NSkiLz48cmVjdCB3aWR0aD0iNyIgaGVpZ2
h0PSIyMCIgeD0iNDYuNSIgeT0iNDAiIGZpbGw9IiNEMkQyRDIiIHJ4PSI1IiByeT0iNSIgdHJhbnNmb3JtPSJyb3
RhdGUoLTkwIDM1IDY1KSIvPjxyZWN0IHdpZHRoPSI3IiBoZWlnaHQ9IjIwIiB4PSI0Ni41IiB5PSI0MCIgZmlsbD
0iIORBREFEQSIgcng9IjUiIHJ5PSI1IiBOcmFuc2Zvcm09InJvdGF0ZSgtNjAgMjQuMDIgNjUpIi8+PHJlY3Qgd2
lkdGg9IjciIGhlaWdodD0iMjAiIHg9IjQ2LjUiIHk9IjQwIiBmaWxsPSIjRTJFMkUyIiByeD0iNSIgcnk9IjUiIH
RyYW5zZm9ybT0icm90YXR1KC0zMCAtNS450CA2NSkiLz48L3N2Zz4=) no-repeat;
 background-size: 100%;
}
.weui-loadmore {
 width: 65%;
 margin: 1.5em auto;
 line-height: 1.6em;
  font-size: 14px;
  text-align: center;
}
.weui-loadmore tips {
  display: inline-block;
 vertical-align: middle;
}
```

mall-service.js

```
const app = getApp()
Component({
 /**
 * 组件的属性列表
  */
 properties: {
 },
  /**
 * 组件的初始数据
  */
  data: {
    service: app.globalData._.config.mall_service
  },
  /**
 * 组件的方法列表
  */
  methods: {
    close_service_detail: function() {
      var that = this;
     that.setData({ "service_detail_show": false });
      setTimeout(function () {
        that.setData({ "service_detail": false });
     }, 300)
    open_service_detail: function () {
      var that = this;
      that.setData({ "service_detail": true });
      setTimeout(function () {
        that.setData({ "service_detail_show": true });
      }, 150)
    }
 }
})
```

mall-service.json

```
{
  "component": true,
  "usingComponents": {}
}
```

mall-service.wxml

```
<view class="goods-header false false" style='opacity:0;height:16rpx;'>
<view class="div">
<view class="g-h-div"></view>
<view class="div g-h-services" catchtap="open_service_detail">
<block wx:for="{{service}}">
   <view class="g-h-service">
             <view class="g-h-service-dot" wx:if="{{index != 0}}"></view>
              <view class="g-h-service-txt {{index == 0 ? 'first-service' :</pre>
''}}">{{item.type}}</view>
         </view>
   </block>
         <view class="g-h-enter"><view class="span g-h-enter-icon"></view>
         </view>
</view>
     <view class="service-detail-bg" catchtap="close_service_detail"</pre>
style="{{service_detail ? '' : 'display:none;'}}">
         <view class="gh-service-detail-main {{service_detail && service_detail_show ?</pre>
'gh-main-show' : 'gh-main-hide'}}">
    <view class="gh-service-title"><view class="span">服务说明</view>
                 <view class="gh-service-close-btn"</pre>
catchtap="close_service_detail"></view>
             </view>
             <view id="gh-service-modal-list-service" class="gh-service-modal-content">
                 <view class="gh-service-content">
                      <view class="gh-service-item" wx:for="{{service}}">
                          <view class="gh-service-left">
                             <view class="gh-service-item-top"><view class="span gh-ms-</pre>
item-icon"></view>
                             <view class="span gh-service-item-</pre>
name">{{item.type}}</view>
                          </view>
                          <view class="span service-item-desc">{{item.desc}}</view>
                          </view>
                      </view>
                 </view>
     </view>
</view>
</view>
</view>
</view>
```

mall-service.wxss

```
.goods-header .g-h-div {
```

```
border-top: 1px solid #f2f2f2;
    margin-top: -2rpx;
    margin-left: 24rpx;
    box-sizing: border-box;
}
.goods-header .g-h-services, .goods-header .g-h-services .g-h-country {
    -webkit-box-align: center;
    align-items: center;
    -webkit-align-items: center;
}
.goods-header .g-h-services {
    padding: 24rpx;
    position: relative;
    display: -webkit-box;
    display: flex;
    display: -webkit-flex;
    -webkit-box-pack: start;
    justify-content: start;
    -webkit-justify-content: start;
    -webkit-box-orient: horizontal;
    -webkit-box-direction: normal;
    flex-direction: row;
    -webkit-flex-direction: row;
    font-size: 26rpx;
    line-height: 76rpx;
    color: #58595b;
    height: 76rpx;
    box-sizing: border-box;
}
.goods-header .g-h-services .g-h-service {
    margin-left: 16rpx;
    margin-top: 2rpx;
    display: -webkit-inline-box;
    display: inline-flex;
    display: -webkit-inline-flex;
    -webkit-box-align: center;
    align-items: center;
    -webkit-align-items: center;
    -webkit-flex-shrink: ;
    flex-shrink: ;
}
.goods-header .g-h-services .g-h-service .g-h-service-txt {
  margin-left: 16rpx;
}
.goods-header .g-h-services .g-h-service .g-h-service-txt.first-service {
  margin-left: -16rpx;
}
```

```
.goods-header .g-h-services .g-h-service .g-h-service-dot {
  height: 4rpx;
  width: 4rpx;
  border-radius: 50%;
  background-color: #9c9c9c;
  box-sizing: border-box;
}
.goods-header .g-h-enter .g-h-enter-icon:before {
  border-bottom: 2rpx solid #DDDDDD;
  border-left: 2rpx solid #DDDDDD;
  content: "";
  display: inline-block;
  height: 14rpx;
  overflow: hidden:
  position: absolute;
  right: 24rpx;
  top: 31rpx;
  -webkit-transform: rotate(-135deg);
  transform: rotate(-135deg);
  width: 14rpx;
}
.service-detail-bg {
    position: fixed;
    width: 100%;
    max-width: 640px;
    height: 100%;
    top: ;
    background: rgba(0,0,0,.7);
    z-index: 10002;
}
.service-detail-bg .gh-service-detail-main.gh-main-show {
    -webkit-transform: translateZ(0) translateY(0);
    transform: translateZ(0) translateY(0);
}
.service-detail-bg .gh-service-detail-main.gh-main-hide {
    -webkit-transform: translateZ(0) translateY(819.99rpx);
    transform: translateZ(0) translateY(819.99rpx);
}
.service-detail-bg .gh-service-detail-main {
    position: fixed;
    width: 100%;
    max-width: 640px;
    height: 819.99rpx;
    background-color: #fff;
    z-index: 10000;
    -webkit-transition: -webkit-transform .15s ease-in-out .15s;
    transition: -webkit-transform .15s ease-in-out .15s;
    transition: transform .15s ease-in-out .15s;
    transition: transform .15s ease-in-out .15s,-webkit-transform .15s ease-in-out .15s;
```

```
-webkit-transform: translateZ(0);
    transform: translateZ(0);
    bottom: ;
}
.service-detail-bg .gh-service-title {
    user-select: auto;
    -webkit-user-select: auto;
    position: relative;
    width: 100%;
    height: 88rpx;
    line-height: 88rpx;
    font-size: 34rpx;
    color: #151516;
    text-align: center;
    border-bottom: 1px solid hsla(0,0%,88%,.4);
    background-repeat: no-repeat;
    background-size: cover;
    background-position: 50%;
}
.service-detail-bg .gh-service-close-btn {
    position: absolute;
    width: 88rpx;
    height: 88rpx;
    padding: 30rpx;
    top:;
    right: ;
    padding-top: 32rpx;
    box-sizing: border-box;
}
.service-detail-bg .gh-service-close-btn:before {
    content: "\E61D";
    font-size: 24rpx;
    color: #e0e0e0;
    font-family: icomoon;
    line-height: 1;
    font-weight: 400;
    -webkit-font-smoothing: antialiased;
    position: relative;
    display: block;
    box-sizing: border-box;
}
.service-detail-bg .gh-service-modal-content {
    width: 100%;
    height: 744rpx;
    font-size: ;
    overflow-x: hidden;
    overflow-y: auto;
    -webkit-overflow-scrolling: touch;
```

```
.goods-header .gh-service-content {
    padding: 42rpx 24rpx 60rpx;
}
.goods-header .gh-service-item, .goods-header .gh-service-item .gh-service-left {
    display: -webkit-box;
    display: flex;
    display: -webkit-flex;
    -webkit-box-pack: start;
    justify-content: start;
    -webkit-justify-content: start;
    -webkit-box-direction: normal;
}
.goods-header .gh-service-item {
    -webkit-box-align: center;
    align-items: center;
    -webkit-align-items: center;
    -webkit-box-orient: horizontal;
    flex-direction: row;
    -webkit-flex-direction: row;
    width: 100%;
    padding: 42rpx;
}
.goods-header .gh-service-item .gh-service-left {
    -webkit-box-align: start;
    align-items: start;
    -webkit-align-items: start;
    -webkit-box-orient: vertical;
    flex-direction: column;
    -webkit-flex-direction: column;
    -webkit-box-flex: 1;
    -webkit-flex: 1;
    flex: 1:
}
.goods-header .gh-service-item .gh-service-left .gh-service-item-top {
    display: -webkit-box;
    display: flex;
    display: -webkit-flex;
    -webkit-box-pack: start;
    justify-content: start;
    -webkit-justify-content: start;
    -webkit-box-align: center;
    align-items: center;
    -webkit-align-items: center;
    -webkit-box-orient: horizontal;
    -webkit-box-direction: normal;
    flex-direction: row;
```

```
-webkit-flex-direction: row;
}
.goods-header .gh-service-item .gh-service-left .service-item-desc {
margin-top: 12rpx;
margin-left: 18rpx;
font-size: 28rpx;
color: #9c9c9c;
line-height: 40rpx;
display: -webkit-box;
display: flex;
display: -webkit-flex;
-webkit-box-pack: start;
justify-content: start;
-webkit-justify-content: start;
-webkit-box-align: center;
align-items: center;
-webkit-align-items: center;
-webkit-box-orient: horizontal;
-webkit-box-direction: normal;
flex-direction: row;
-webkit-flex-direction: row;
}
.goods-header .gh-service-item .gh-service-left .gh-service-item-top .gh-service-item-
name {
margin-left: 12rpx;
font-size: 32rpx;
color: #151516;
line-height: 32rpx;
```

net-error-tips.js

```
// component/NetErrorTips/netErrorTips.js
Component({
/**
* 组件的属性列表
*/
properties: {
isNoNetError: {
type: Boolean,
value: true,
}
},
/**
* 组件的初始数据
*/
data: {
},
/**
* 组件的方法列表
*/
methods: {
_loadData() {
//触发取消回调
this.triggerEvent("loadData");
},
}
})
```

net-error-tips.json

```
{
   "component": true,
   "usingComponents": {}
}
```

net-error-tips.wxml

```
<view class="net-error" hidden="{{isNoNetError}}">
        <view class="tips">手机网络不太顺畅,请检查网络状况</view>
        <button class="reloadBtn" catchtap='_loadData'>重新加载</button>
</view>
```

net-error-tips.wxss

```
.net-error{
position: absolute;
top:calc(75% - 50px);
left:calc(50% - 106px);
.net-error .reloadBtn{
width:200rpx;
margin: auto;
font-size: 12px;
color:white;
background-color: #FF4C42;
border-radius:10rpx;
}
.net-error .tips{
text-align: center;
padding:10px;
color:#FF4C42;
}
```

page-loading.js

```
// component/page-loading/page-loading.js
Component({
 /**
 * 组件的属性列表
  */
 properties: {
   isLoading: {
     type: Boolean,
     value: true,
   },
   isOperate: {
     type: Boolean,
     value: false,
   }
 },
 /**
 * 组件的初始数据
  */
 data: {
 },
 * 组件的方法列表
  */
 methods: {
 }
})
```

page-loading.json

```
{
  "component": true,
  "usingComponents": {}
}
```

page-loading.wxml

```
<view class="page-loading" id="pin-spinner" wx:if="{{isLoading}}">
<view class="div ps-background" wx:if="{{isOperate}}"></view>
<view class="div ps-inner-box">
<image id="imgInit" class="ps-rotate-img"</pre>
src="
/xhBQAAACBjSFJNAAB6JgAAgIQAAPoAAACA6AAAdTAAAOpgAAA6mAAAF3CculE8AAAABmJLR0QAAAAAAAD5Q7t/A
AAACXBIWXMAAAsSAAALEqHS3X78AAAGwElEQVRo3u2af4wdVRXHP2/XLm1BTMCCtGNLEQS6nUoVEiIwUEkMDTGZB
qq0J0rQSBSE4sMKhEMW5aQCtg0W6w9Qp4Gm/AGUMRL5IabJiKSgQnWEVi1gy0CXrcJCIuiybPnjztv03jfv7XvPN
wYSvskme879ce537o9z7rmvQskQkRnACcB0Vd1Xpq2ekoksBXYDMbBHRJa/Z8kAa4Fp2f9TM/ndRUZEjhSRD7VQ9
aOW/JEW+p4uIrNKJ5MZug/YCwyJyMp0jDbpfwkwCKQiEovIEaWRAS4HfKAC9AFrRWR+l4jMAELgg5nqDGB1mWSOs
eReYH03yGQDt5fu3DLJ3FugW5Qtj44hIicBFxUU3VMaGVV9CHiwoGitiEz9H/isLxjLM8DtpZHJ8A3gLUs3F7iiE
xaZLzqjyI6qjpZKRlV3AhsKiq4VkaPaJDIVWFNQ9EtVfbjdsXXqNL8N2KHJIcB3Ld1uS37JklcBsy3df4Er0xlUx
fpS04GNwBJgBzCgqvcVNRSRrwI/stT7gY+p6vNZnaXAncBBwAhwoarek5UdjPEph1h9rFHVVQ1sngrcDHwaEyJdo
KpDtXJ7Zq4GlgIfAFxgi4g8ICLzCvq+HfhTwceZUxNU9W5MFHA6MLNGJMNhBUQGgRsKSMwWkc3AY5j91QssAm5pN
jNbqbMKBj4K3AZcp6qv50qfCfwm6xzq78ACVf0PLaDA3pdU9Y5c+TSqClzLqRqvjxdUdXyZ9uZLPM87DvAKGvUAp
wArPM/7t+d5T8VxPBbH8W7P8x7PPsrDwApVfb0VIpm9ezF7ZAi4UVU3ZSQqnuctAyLMkp/SoItfxXE87vvsmekDv
gdcgllqjfA0sExVk1YH3ipEZCawGTizSbX9wF3Apao6XFNOGLCqjgArReQnmHD9nAad9W088/HdJgP8bBIiTwGXq
erv7IJKk0a1KPZm4NgGVQ5W1Te6yURE9lJ8VdgLCLBRVceK2jb1M9mx3A98E7D3wm+7TSTDA5Y8glklx6vqzxsRg
eb7okZoBBN7bQYGgMWYu0niEoiACZemAadhjmJR1V0l2Xof/xdUAETkEuAawGlSdwyzvL6mqo+WPbB169YtwlwN5
tF8bw8CA9Vq9baKiJyI8RuVFmwAvAjMUdW3SyQyJbMzo8UmbwP9PcD8NoqAzGrDSKc4sk0bvcD8Hkyw2M5X3q0qq
yWTeQkzM61iFHiyR1X/BqwAngVeneTvj8D5JR0hWq20Aedl9iYb0x4gqFarz5c9rvfRKVre+Gma9gGXAudijmhxH
KflcL9VhGHYh7m/nAZsA9YEQTDcNTJpmhYFnFscxzmvBDI3Ad/KqYYwPnBjEARjzdo2DTTTNJ2XpukjwBbqI2c/T
dNpdB8XWvIRmGvBH8IwbHY1KCaTpumH0zTdqDm2z27Qdqho6XrcJl5ooF8IbA3DcHMYhr0LKkxYZmmaVjDR8GpMw
qER/gksdxzn191mEobhAuAXwNFNqr2JybfdEATBeELSJrMSK+NhYRT4ITDg0M4wQJIkJwJfAFJgk+u6Lc9WFEU9G
L+1ALjf9/1tGaFaIuNq6jM4eawPqmD8WcUm0yq7AybHfKXj0M/UFEmS9ANPANMz1aPAWa7rthRRRFG0i0N7ZAw4x
/f98dk0w3AWJidxAcWH1e4gCI6uCfae+UtBg13A5xzHWZwnkuHWHBEw+bFT7Q7i0K7LrkRRdBQTN3sPsCGKor6aI
qiCF4MqWI5J+j1eMLYdWB3k8R1qe/b/q5jrcr/j0PfbvSRJsqSTiLMx7nvi0P5UHMc7qJE4jp+04/iTuXpvYK7Ee
RwHXGZ3GATBtozQCq6keP+BWYrjqJu67BCYA7zs0M6bBYMlSZKpGMdpPwY96Lru4hyZ3wMn58q3e563MDc7twJfL
/gYH/d9/+Ui22EYTsFkSfcEQTDhlaAuB+A4zv6MdTNcUUDkLcz9PY+FlrzAkq8HlgGH53SHAgp8pchwdno9V1TW9
itAkiQzMeGGjQ2u6+60dL2WPMGe7/v/ygjZuCiKopNpE508aaym/rjch3nm6AQ/pv7g6QHWRVHUzqWxPTJJkpwCf
LGg6DrXdYc7YeL7/ij1yxNMtv/zpZEBvkz9obEd+GknRHKEHsEkyYvslUZmuEBXbdVJToJVmBeBPF4rk8wtHPBDA
Otd193aBSL4vr8LuAqT4QdzHR4ojYzruvswfuN04B0u63b15ya+738f830uz2B8zV/bad/WadEu4jgexKSNanjF8
7zD0+1vMpT9Ey37AfcHZRordWYA4jj+LMbz/9nzvLbf9tvB00XbJi+MSyc4AAAAAElFTkSuQmCC"
style="bottom: 0px;"/>
</view>
</view>
```

page-loading.wxss

```
/* component/page-loading/page-loading.wxss */
.page-loading .ps-rotate-img {
  width: 25px;
  height: 25px;
  margin: auto;
  left: ;
  right: ;
  top: ;
  bottom: ;
  animation: rotateImg 2.5s linear infinite;
  -webkit-animation: rotateImg 2.5s linear infinite;
  z-index: 9999999999;
  position: absolute;
}
@keyframes rotateImg {
    0% {
       transform: rotateZ(0deg);
    }
    50% {
       transform: rotateZ(180deg);
    }
    100% {
       transform: rotateZ(360deg);
    }
}
.page-loading {
    position: fixed;
    width: 66px;
    height: 66px;
    top: 35%;
    margin: auto;
    left: ;
    right: ;
    z-index: 999999999;
.ps-background {
    position: absolute;
    width: 100%;
    height: 100%;
    opacity: 0.7;
    background-color: #000;
    border-radius: 9px;
}
```

qrcode-poster.js

```
const app = getApp();
Component({
 /**
 * 组件的属性列表
  */
 properties: {
   showPosterModal: {
     type: Boolean,
     value: false,
   },
   posterUrl: {
     type: String,
     value: null
   },
   qrcodeUrl: {
     type: String,
     value: null
   },
   goods: {
     type: Object,
      value: null
   },
   disabled: {
     type: Boolean,
     value: false
   }
 },
 /**
 * 组件的初始数据
 data: {
   appiconUrl: app.globalData.appiconUrl,
   appName: app.globalData.appName,
   confirmDisabled: false
 },
 /**
 * 组件的方法列表
  */
 methods: {
   hidePosterModal: function () {
     var myEventDetail = {} // detail对象,提供给事件监听函数
```

```
var myEventOption = {} // 触发事件的选项
      this.triggerEvent("close", myEventDetail, myEventOption);
      this.setData({
        showPosterModal: false
      });
     console.log("hidePosterModal");
   },
   emptytest: function () {
   },
   save: function () {
      var that = this, pages = getCurrentPages(), currentPage = pages[pages.length - 1],
uri = currentPage.route + "?" + (app.urlEncode(currentPage.options).slice(1));
      console.log(currentPage)
      wx.showLoading({
       title: '保存图片到手机相册中...',
      });
      that.setData({
        disabled: true
      });
      wx.downloadFile({
        url: that.data.posterUrl,
        success: function (res) {
          that.setData({
            disabled: false
          });
          if (res.statusCode === 200) {
            //保存到相册
            wx.saveImageToPhotosAlbum({
              filePath: res.tempFilePath,
              success: function () {
                wx.hideLoading();
                that.setData({
                  showPosterModal: false
                });
                wx.showToast({
                  title: '成功保存',
                  icon: "success"
                });
```

```
app.handlerShare("分享海报", 1, uri);
               that.triggerEvent("close", {}, {});
           },
             fail: function (res) {
               wx.hideLoading();
               app.handlerShare("分享海报", , uri );
               that.triggerEvent("close", {}, {});
               console.log(res);
               wx.getSetting({
                 success(res) {
                   if (!res.authSetting["scope.writePhotosAlbum"]) {
                     wx.openSetting({
                       success: (res) => {
                         if (res.authSetting["scope.writePhotosAlbum"] &&
res.authSetting["scope.writePhotosAlbum"] == true) {
                           that.save();
   });
   },
   fail: function () {
         that.setData({
           disabled: false
         });
         wx.hideLoading();
         that.triggerEvent("close", {}, {});
});
}
}
})
```

qrcode-poster.json

```
{
   "component": true,
   "usingComponents": {}
}
```

qrcode-poster.wxml

```
<!-- 海报 -->
<view class="modal-mask" bindtap="hidePosterModal" catchtouchmove="preventTouchMove"</pre>
wx:if="{{showPosterModal}}"></view>
<view class="modal-wrap" bindtap="hidePosterModal" wx:if="{{showPosterModal}}}">
<view class="modal-dialog" catchtap='emptytest'>
<view class="close" bindtap='hidePosterModal' hover-class='hover-effect'>
<image src="../../images/push/exit2.png"></image>
</view>
<image class="goods-cover" src="{{goods.image_url + '?x-oss-</pre>
process=image/resize,w_380,h_380'}}" mode='cover'></image>
<view class="goods-info">
<view class="title-1 {{goods.title_one?'':'text-</pre>
center'}}">{{goods.title_one}}</view>
<view class="title-2">{{goods.title_two}}</view>
<view class="price" wx:if="{{goods.group_price}}">¥ {{goods.group_price}}</view>
</view>
<view class="dash-line"></view>
<view class="qrcode-info-wrap">
<image class="qrcode" src="{{qrcodeUrl}}"></image>
<view class="ps-wrap">
<view class="text">长按识别图中的小程序码</view>
<view class="text">查看{{goods.title_one?"":" 拼团 "}}详情</view>
</view>
</view>
<view class="modal-footer">
<button class="save-btn" bindtap='save' disabled='{{disabled}}'>保存图片/button>
<view class="text">保存后,可以从手机相册分享到朋友圈</view>
</view>
</view>
</view>
```

qrcode-poster.wxss

```
/* component/qrcode-poster/qrcode-poster.wxss */
.modal-mask {
```

```
width: 100%;
  height: 100%;
  position: fixed;
  top: ;
  left: ;
  background: #000;
  opacity: 0.5;
  overflow: hidden;
  z-index: 9000;
  color: #fff;
}
.modal-wrap{
  position: fixed;
  top:;
  bottom:;
  left:;
  right:;
  display: flex;
  flex-direction: row;
  align-items: center;
  justify-content: center;
  z-index: 9999;
}
.modal-dialog {
  width: 90%;
  max-height: 100%;
  overflow-y: scroll;
  background: #fff;
  border-radius: 20rpx;
  padding-bottom:350rpx;
  text-align: center;
 position: relative;
}
.goods-cover{
  /* width:380rpx; */
  height:380rpx;
  object-fit: cover;
  margin: auto;
  margin-top:80rpx;
  width:100%;
}
.modal-footer{
  position: absolute;
  bottom: 30rpx;
  text-align: center;
  width:100%;
}
```

```
.modal-footer .text{
  font-size: 22rpx;
  color:#adadad;
  text-align: center;
  padding-top:30rpx;
}
.goods-info{
  padding:30rpx;
  position:relative;
}
.goods-info .title-1, .goods-info .title-2{
  color:#343434;
  font-size:26rpx;
  position: absolute;
  left:30rpx;
  top:30rpx;
}
.goods-info .title-2{
  top:66rpx;
}
.goods-info .price{
  color:#ff5b4c;
  font-size:26rpx;
  position: absolute;
  right:30rpx;
  top:30rpx;
}
.dash-line{
  margin: 30rpx;
  margin-top:70rpx;
  height: 2rpx;
  border-bottom: 1rpx dashed #e9e9e9;
}
.qrcode-info-wrap
  margin-top:20rpx;
 position: relative;
.qrcode{
  width:180rpx;
  height:180rpx;
  position: absolute;
  left:30rpx;
}
```

```
.ps-wrap{
  color:#6b6b6b;
  font-size: 26rpx;
  position: absolute;
  top:50rpx;
  text-align: left;
  left:300rpx;
}
.ps-wrap .text{
  padding-top:rpx;
}
.modal-dialog .close{
  position: absolute;
  top:10rpx;
  right:10rpx;
  width:60rpx;
  height:60rpx;
  text-align: center;
}
.close image{
  width:40rpx;
  height:40rpx;
}
.save-btn{
  background:#ff5b4c;
  font-size: 24rpx;
  text-align: center;
  color:#fff;
  width:60%;
  height: 70rpx;
  border-radius: 40rpx;
  line-height: 70rpx;
.goods-info .text-center{
 left:;
  width:100%;
 text-align: center;
}
```

right-service.js

```
// component/right-service/right-service.js
Component({
/**
* 组件的属性列表
*/
properties: {
},
/**
* 组件的初始数据
*/
data: {
},
/**
* 组件的方法列表
*/
methods: {
}
})
```

right-service.json

```
{
  "component": true,
  "usingComponents": {}
}
```

right-service.wxml

right-service.wxss

```
/* component/right-service/right-service.wxss */
.service {
    background: url(//pintuan-xcx.cn/v1.0/service_5ca802.png) no-repeat;
    background-size: contain;
    top: 276px;
    width: 56px;
    height: 56px;
}
.explain_icon_right {
    right: -50px;
    -webkit-animation: shake 1s ease-in .3s forwards;
    animation: shake 1s ease-in .3s forwards;
}
.explain_icon, .explain_icon_right {
    position: fixed;
    z-index: 10:
}
@keyframes shake {
    0% {
        right: -50px
    }
    30%, to {
        right: 20px
    }
    40%,60%,80% {
        -webkit-transform: rotate(-10deg);
        transform: rotate(-10deg)
```

```
}
50%,70%,90% {
-webkit-transform: rotate(10deg);
transform: rotate(10deg)
}
}
contact-button {
display:block;
line-height:4;
z-index:9999999999;
width:40px;
height:40px;
margin-left:9px;
background-color:#1AAD19;
margin-top:7px;
opacity:-0.5;
}
```

winpop-mask.js

```
// component/winpop-mask/winpop-mask.js
Component({
 /**
 * 组件的属性列表
  */
 properties: {
   showWinpopModal: {
      type: Boolean,
      value: false,
   },
   winpopContent: {
      type: String,
      value: "",
   },
   showWinpopCancel: {
      type: Boolean,
      value: true,
   },
   showWinpopConfirm: {
      type: Boolean,
     value: true,
   }
 },
 /**
 * 组件的初始数据
  */
 data: {
 },
 /**
 * 组件的方法列表
  */
 methods: {
   cancelCallback: function() {
      this.triggerEvent('cancelCallback'),
      this.setData({"showWinpopModal": false});
   },
   confirmCallback: function() {
     this.triggerEvent('confirmCallback'),
      this.setData({"showWinpopModal": false});
   }
 }
})
```

winpop-mask.json

```
{
   "component": true,
   "usingComponents": {}
}
```

winpop-mask.wxml

```
<view class="div winpop-mask" id="co_maks" wx:if="{{showWinpopModal}}"</pre>
style="display:block"></view>
<view class="div winpop-box" id="co_box" wx:if="{{showWinpopModal}}"</pre>
style="display:block">
   <view class="div co-popmain winpop-main">
         <view class="p co-main-words">{{winpopContent}}</view>
</view>
<view class="div co-btns winpop-btns">
         <button type="button" class="co-false pop-btn2 confirm-false" value=""</pre>
bindtap="cancelCallback" wx:if="{{showWinpopCancel}}">
取消
         </button>
<button type="button" class="{{showWinpopCancel && showWinpopConfirm ? 'co-</pre>
true pop-btn2 confirm-true' : 'co-alert pop-btn alert-button'}}" value=""
bindtap="confirmCallback" wx:if="{{showWinpopConfirm}}">
确定
         </button>
</view>
</view>
```

winpop-mask.wxss

```
/*error start*/
.winpop-mask {
    left: ;
    top: ;
    z-index: 99999;
    width: 100%;
    height: 100%;
```

```
background-color: #000;
    opacity: .6;
}
.winpop-box, .winpop-mask {
    display: none;
    position: fixed;
}
.winpop-box {
    left: 50%;
    top: 50%;
    z-index: 999999;
    -webkit-transform: translate3d(-50%,-50%,0);
    webkit-transform: translate3d(-50%,-50%,0);
    width: 80%;
    height: 30%;
    border-radius: 10rpx;
    background-color: #fff;
}
.winpop-box, .winpop-mask {
    display: none;
    position: fixed;
}
.winpop-box .winpop-main {
    height: 75%;
    overflow: hidden;
    text-wrap: normal;
    line-height: 48rpx;
    color: #666;
    padding: auto;
    text-align: center;
    vertical-align: center;
    font-size: 36rpx;
    position: relative;
}
.winpop-box .winpop-main .co-main-words {
    position: absolute;
    top: 50%;
    left: 50%;
    text-align: center;
    width: 90%;
    -webkit-transform: translate(-50%,-50%);
    transform: translate(-50%, -50%);
}
```

```
.winpop-box .winpop-btns {
    text-align: center;
    height: 25%;
    z-index: 999999999;
    border-top: 1px solid #999;
}
.winpop-box .pop-btn {
    width: 80%;
    height: 70rpx;
    border-radius: 10rpx;
    background-color: transparent;
    border: solid #df0a17;
    font-family: Microsoft Yahei;
    color: #df0a17;
    font-size: 32rpx;
}
button::after {
    border: none;
/*error end*/
.winpop-box .pop-btn2 {
    width: 50%;
    height: 100%;
    background-color: transparent;
    border: solid #df0a17;
    font-family: Microsoft Yahei;
    color: #df0a17;
    font-size: 32rpx;
    position: relative;
    display: inline-block;
    border-radius: !important;
    border-right: 1px solid #aaa;
    border-radius: ;
}
/* start.v.6 */
.winpop-box .pop-btn2 {
  border-right-color: #e0e0e0;
}
.winpop-box .winpop-btns {
    border-top-color: #e0e0e0;
}
/* end */
```

安装要求

- Laravel 5.3+
- php 5.6.4

nginx参考

```
server {
listen 80;
       root /www/web/w6_pintuan_xcx_cn/public;
       server_name test.pintuan-xcx.cn;
       index index.html index.php index.htm;
       location ~ \.php(.*)$ {
               fastcgi_pass unix:/tmp/php-71-cgi.sock;
               fastcgi_index index.php;
               fastcgi_param SCRIPT_FILENAME $DOCUMENT_ROOT$fastcgi_script_name;
               fastcgi param PATH INFO $2;
               include fcgi.conf;
    location ~ /\.ht {
    deny all;
    location / {
                #try_files $uri $uri/ /?$args;
            try_files $uri $uri/ /index.php?$query_string;
}
```

linux权限

```
chmod -R 0777 storage
```

web.php

```
<?php
```

```
//auth
Route::group(['prefix' => '/auth', 'namespace' => "Auth", 'middleware' => ['csrf']],
function () {
    Route::get('login',
'LoginController@showLoginForm')->name('login');
    Route::post('login',
                                             'LoginController@login');
    Route::get('logout',
                                             'LoginController@logout')->name('logout');
                                             'LoginController@logout') ->name('logout');
    Route::post('logout',
});
//admin site
Route::group(['prefix' => '/admin', 'namespace' => "Admin", 'middleware' => ['auth',
'permission']], function () {
                                             'MenuController@tree');
    Route::resource('/menu/tree',
    Route::resource('/menu',
                                             'MenuController');
    Route::get('/role/{id}/permission',
                                             'RoleController@permissionEdit');
    Route::post('/role/{id}/permission',
                                             'RoleController@permissionStore');
    Route::resource('/role',
                                             'RoleController');
    Route::resource('/user',
                                             'UserController');
    Route::resource('/permission',
                                             'PermissionController');
    Route::resource('/info',
                                             'InfoController');
    Route::resource('/log',
                                             'LogController');
    Route::resource('/loginLog',
                                             'LoginLogController');
                                             'HomeController');
    Route::resource('/',
                                                   'BannerController');
    Route::resource('/banner',
                                                  'GoodsController');
    Route::resource('/goods',
    Route::resource('/goods cate',
                                                        'GoodsCateController');
    Route::post("upload",
                                             "FileController@uploadFile");
    Route::resource('/member',
                                               'MemberController');
                                         'OrdersController@index');
    Route::get('/orders',
                                                    'OrdersController@edit');
    Route::get('/orders/{id}/edit',
    Route::post('/orders/confirm',
                                                   'OrdersController@confirm');
    Route::post('/orders/cancel',
                                                  'OrdersController@cancel');
    Route::any('/orders/{id}/delivery',
                                                        'OrdersController@delivery');
    Route::any('/orders/{id}/refound',
                                                       'OrdersController@refound');
    Route::resource('/shipping',
                                                 'ShippingController');
    Route::resource('/group',
                                              'GroupController');
    Route::get('/config',
                                          'ConfigController@index');
    Route::get('/config/set',
                                              'ConfigController@conf');
    Route::post('/config/web',
                                               'ConfigController@updateweb');
```

```
Route::post('/config/upload',
                                              'ConfigController@uploadFile');
   Route::get('/config/get_weapp_tpl',
'ConfigController@get_weapp_tpl');
   Route::get('/share',
                            'ShareController@index');
   Route::get('/dynamic',
                                      'HomeController@dynamic');
});
//app api
Route::group(['prefix' => 'api/v1.0', 'namespace' => "Api\\Air\\v_1_0"], function () {
   Route::get('banners',
                                            'BannerController@lists');
   Route::get('goods',
                                             'GoodsController@lists');
   Route::get('users/me',
                                             'WeuserController@me');
   Route::post('users/share',
                                                 'WeuserController@share');
   # addresses
                                            'AddressController@lists');
   Route::get('users/addresses',
   Route::put('users/addresses/{address_id}', 'AddressController@defaults');
   # address
   Route::get('users/address/{address_id}', 'AddressController@detail');
                                           'AddressController@add');
   Route::post('users/address',
   Route::put('users/address_id}', 'AddressController@edit');
   Route::delete('users/address/{address_id}', 'AddressController@delete');
   Route::get('users/orders', 'OrdersController@lists');
   Route::get('users/orders/{order_id}', 'OrdersController@detail');
   Route::post('users/orders', 'OrdersController@add');
   Route::delete('users/orders/{order_id}', 'OrdersController@cancel');
   Route::post('users/orders/{order_id}/receive', 'OrdersController@receive');
   Route::get('orders/{order_id}/express', 'ProjectController@express');
   Route::get('project/data_version',
                                             'ProjectController@data version');
   Route::get('project/regions',
                                             'ProjectController@regions');
   Route::get('project/crontab',
```

```
'ProjectController@crontab')->name('crontab');
    Route::get('banners/order',
                                                'BannerController@order');
    Route::get('users/orders/{order_id}/wxpay',
'PaymentController@wxpay');
    Route::any('notify/wxpay',
'NotifyController@wxpay')->name('wxpay_notify');
    # test wxpay
    # Route::any('notify/testwxpay',
                                                 'NotifyController@testwxpay');
    Route::get('users/groups',
                                                       'GroupsController@lists');
                                               'GroupsController@detail');
    Route::get('users/groups/{id}',
    Route::delete('tokens',
                                                   function(Illuminate\Http\Request
$request) {
        $token = $request->header('AccessToken');
        $MemberTokenDB = new App\Models\MemberToken();
        $MemberTokenDB->where('token',$token)->delete();
   });
});
// app pro api
Route::group(['prefix' => 'pro/api/v1.0', 'namespace' => "Api\\Pro\\v_1_0"], function ()
                                               'GoodsController@lists');
    Route::get('goods',
                                          'GoodsController@lists_groups');
    Route::post('goods/groups',
    Route::get('goods/{goods_id}/groups',
                                                       'GoodsController@detail groups');
    Route::get('goods_cate',
                                        'GoodsCateController@lists');
    Route::get('users/orders', 'OrdersController@lists');
    Route::get('users/orders/count', 'OrdersController@count');
    Route::get('users/orders/{order_id}', 'OrdersController@detail');
    Route::post('users/orders', 'OrdersController@add');
    Route::get('users/orders/{order_id}/wxpay', 'PaymentController@wxpay');
    Route::any('notify/wxpay',
'NotifyController@wxpay')->name('pro_wxpay_notify');
```

```
# test wxpay
    # Route::any('notify/testwxpay',
                                                     'NotifyController@testwxpay');
    Route::get('users/groups/{id}',
                                                'GroupsController@detail');
});
// mini air api
Route::group(['prefix' => 'mini/v1.0', 'namespace' => "Mini\\Air\\v_1_0"], function () {
                                      'GoodsController@detail');
    Route::get('goods/{goods_id}',
    Route::get('goods/poster/{goods_id}',
                                                       'GoodsController@poster');
    Route::get('login',
                                                'WechatController@login');
    Route::get('wxacode/{id}',
                                                'WechatController@wxacode');
    Route::get('group/poster/{id}',
                                                'GroupsController@poster');
});
// mini pro api
Route::group(['prefix' => 'pro/mini/v1.0', 'namespace' => "Mini\\Pro\\v_1_0"], function
    Route::get('goods/{goods_id}',
                                               'GoodsController@detail');
    Route::get('login',
                                                'WechatController@login');
});
Route::group(['prefix' => 'pro/mini/v1.1', 'namespace' => "Mini\\Pro\\v_1_1"], function
() {
                                                'WechatController@login');
    Route::get('login',
});
//web site
Route::group(['namespace' => "Web"], function () {
    Route::get('/',
                                       'SiteController@get');
});
//test api
Route::group(['prefix' => 'test', 'namespace' => "Test"], function () {
                                                 'GroupsController@lists');
    Route::get('groups',
    Route::get('groups/{id}',
                                          'GroupsController@detail');
    Route::get('goods',
                                                'GoodsController@lists');
    Route::get('goods/{id}',
                                         'GoodsController@detail');
});
```

api.php

console.php

AddressController.php

```
<?php
namespace App\Http\Controllers\Api\Air\v_1_0;
use App\Models\Address;
use App\Models\Region;
use Illuminate\Support\Facades\DB;
use Illuminate\Http\Request;
class AddressController extends WeuserController {
    public function lists(){
        $AddressDB = new Address();
        $ret['address_list'] =
$AddressDB->getAddress(array('member_id'=>$this->memberInfo['member_id']));
        $ret['result'] = 'ok';
        echo json_encode($ret);
    }
    public function defaults($address_id){
        $AddressDB = new Address();
        $rev = file_get_contents("php://input");
        $rev = json_decode($rev,true);
$AddressDB->where(array('member_id'=>$this->memberInfo['member_id']))->update(array('sta
tus'=>'COMMON'));
        $data['status'] = $rev['status'];
$AddressDB->where(array('address_id'=>$address_id,'member_id'=>$this->memberInfo['member
_id']))->update($data);
        $ret['result'] = 'ok';
        echo json_encode($ret);
        exit;
    }
    public function detail($address_id){
        $AddressDB = new Address();
        if($address id){
            $map['address_id'] = $address_id;
        }else{
            $map['status'] = 'DEFAULT';
        }
        $map['member_id'] = $this->memberInfo['member_id'];
```

```
$ret['address'] = $AddressDB->getAddr($map);
        $ret['result'] = 'ok';
        echo json_encode($ret);
        exit;
    }
    public function add(){
        $AddressDB = new Address();
        $Region = new Region();
        $data = file_get_contents("php://input");
        $data = json_decode($data,true);
        $data['member_id'] = $this->memberInfo['member_id'];
        $data['province_id'] = $data['province'];
        $data['city_id'] = $data['city'];
        $data['district_id'] = $data['district'];
        $province = $Region->getRegionById($data['province']);
        $city = $Region->getRegionById($data['city']);
        $district = $Region->getRegionById($data['district']);
        $data['province'] = $province['region_name'];
        $data['city'] = $city['region_name'];
        $data['district'] = $district['region_name'];
        $data['full_address'] =
$province['region_name'].$city['region_name'].$district['region_name'].$data['address'];
        $data['created_time'] = time();
        $data['last_updated_time'] = time();
        $address_id = $AddressDB->insertGetId($data);
        $ret['result'] = 'ok';
        $ret['address_id'] = $address_id;
        echo json_encode($ret);
        exit;
    }
    public function edit($address_id){
        $AddressDB = new Address();
        $Region = new Region();
        $data = file_get_contents("php://input");
        $data = json_decode($data,true);
```

```
$data['province id'] = $data['province'];
        $data['city_id'] = $data['city'];
        $data['district_id'] = $data['district'];
        $province = $Region->getRegionById($data['province']);
        $city = $Region->getRegionById($data['city']);
        $district = $Region->getRegionById($data['district']);
        $data['province'] = $province['region name'];
        $data['city'] = $city['region_name'];
        $data['district'] = $district['region_name'];
        $data['full_address'] =
$province['region_name'].$city['region_name'].$district['region_name'].$data['address'];
        $data['last_updated_time'] = time();
$AddressDB->where(array('address_id'=>$address_id,'member_id'=>$this->memberInfo['member
_id']))->update($data);
        $ret['result'] = 'ok';
        $ret['address_id'] = $address_id;
        echo json_encode($ret);
        exit;
    }
    public function delete($address_id){
        $AddressDB = new Address();
if($AddressDB->where(array('address_id'=>$address_id,'member_id'=>$this->memberInfo['mem
ber_id']))->delete()){
            $ret['result'] = 'ok';
        }else{
            $ret['result'] = 'fail';
            $ret['error_info'] = '非法提交';
        }
        echo json_encode($ret);
        exit;
   }
}
```

BannerController.php

```
<?php
// | Description:
// +-----
// | Author: beichen <notice@notestore.cn>
namespace App\Http\Controllers\Api\Air\v_1_0;
use App\Http\Controllers\Core\ApiController;
use Illuminate\Support\Facades\DB;
class BannerController extends ApiController {
public function lists() {
$BannerDb = DB::table('banner');
$list = $BannerDb->where('in_selling',1)->orderBy('banner_sort',
'ASC')->orderBy('banner_id', 'DESC')->get();
$ret['result'] = 'ok';
$ret['banners'] = $list;
echo(json_encode($ret));
}
public function order() {
$ret['banner'] = config('wechat.confirm_order_tips');
$ret['result'] = 'ok';
echo json_encode($ret);
}
}
```

GoodsController.php

```
<?php
// | Description:
// +----
// | Author: beichen <notice@notestore.cn>
namespace App\Http\Controllers\Api\Air\v_1_0;
use App\Http\Controllers\Core\ApiController;
use Illuminate\Support\Facades\DB;
use Illuminate\Http\Request;
class GoodsController extends ApiController {
    public function lists(Request $request) {
        $offset = $request->get('offset');
        $size = $request->get('size');
        $GoodsDb = DB::table('goods');
        $list = $GoodsDb->orderBy('goods_sort', 'ASC')->orderBy('goods_id',
'DESC')->select('goods_id','cate_id','goods_name','image_url','market_price','group_pric
e','alone_price','group_number','sell_count','limit_buy','goods_stock','sell_type')->ski
p($offset)->take($size)->get();
        $ret['result'] = 'ok';
        $ret['goods'] = $list;
        echo(json_encode($ret));
    }
    public function detail($goods_id) {
        $GoodsDb = DB::table('goods');
        $detail = $GoodsDb->where('goods_id',$goods_id)->first();
        if(!$detail) {
            return
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'商品已下架或不存在'));
        $imgs = unserialize($detail['goods imgs']);
        foreach($imgs as $v){
            $gallery[]['img url'] = $v;
        }
        echo json_encode(array('result'=>'ok','goods'=>$detail,'gallery'=>$gallery));
    }
}
```

GroupsController.php

```
<?php
// | Description: 团
// +-----
// | Author: beichen <notice@notestore.cn>
namespace App\Http\Controllers\Api\Air\v_1_0;
use App\Models\Group;
use App\Models\Orders;
use Illuminate\Http\Request;
class GroupsController extends WeuserController {
    public function lists(Request $request) {
        $0rdersDb = new Orders;
        $offset = $request->get('offset');
        $size = $request->get('size');
        $map['buyer_id'] = $this->memberInfo['member_id'];
        $map['group_buy'] = 1;
        $map[] = ['orders.group_order_id','>',];
        $map[] = ['pay_sn','<>',''];
        $map[] = ['pay_time','>',];
        $orders =
$OrdersDb->leftJoin('group','orders.group_order_id','=','group.group_order_id')->whereNo
tIn('order_status',[,5])->where($map)->skip($offset)->take($size)->orderBy('group.group_
order_id','DESC')->select()->get()->toArray();
        if(!$orders){
            $orders = array();
        }
        foreach($orders as $k=>$v){
            $orders[$k]['order_goods'] = unserialize($v['order_goods']);
        }
        $ret['group_orders'] = $orders;
        $ret['result'] = 'ok';
        echo json_encode($ret);
    }
    public function detail($id) {
        $GroupDb = new Group;
        $groupInfo = $GroupDb->getGroup(array('group_order_id'=>$id));
        if(!$groupInfo){
```

```
echo json encode(array('result'=>'fail', 'error code'=>41001, 'error info'=>'该
团不存在'));
            return;
        }
        $0rdersDb = new Orders;
        $map = array();
        $map['group_order_id'] = $groupInfo['group_order_id'];
        $map['group_buy'] = 1;
        $orders = $OrdersDb->leftJoin('member','orders.buyer id',
'=','member.member_id')->whereNotIn('order_status',[,5])->where($map)->orderBy('orders.g
roup header','DESC')->orderBy('orders.pay time','ASC')->select()->get();
        foreach($orders as $k => $v){
            $tmp = array();
            $tmp['avatar'] = $v['headimgurl'];
            $tmp['join_time'] = $v['pay_time'];
            $tmp['nickname'] = $v['nickname'];
            $tmp['user_id'] = $v['member_id'];
            suser[] = stmp;
        }
        $map = array();
        $map['group_order_id'] = $groupInfo['group_order_id'];
        $map['group buy'] = 1;
        $map['group_header'] = 1;
        $order = $OrdersDb->leftJoin('member','orders.buyer_id',
'=','member.member_id')->whereNotIn('order_status',[,5])->where($map)->orderBy('group_he
ader', 'asc')->orderBy('pay time', 'asc')->first();
        $order['order_goods'] = unserialize($order['order_goods']);
        $ret['result'] = 'ok';
        $ret['group_order'] = $groupInfo;
        $ret['group_order']['users'] = $user;
        $ret['group order']['order'] = $order;
        $ret['group_order']['caller_id'] = $this->memberInfo['member_id'];
        echo json_encode($ret);
    }
}
```

NotifyController.php

```
<?php
// | Description:
// +-----
// | Author: beichen <notice@notestore.cn>
namespace App\Http\Controllers\Api\Air\v_1_0;
use App\Http\Controllers\Core\ApiController;
use Illuminate\Support\Facades\DB;
class NotifyController extends ApiController {
public function wxpay(){
require_once base_path("app/Utils/JsApiPay/mini/notify.php");
      $config = new \WxPayConfig();
      $notify = new \PayNotifyCallBack();
      $notify->Handle($config,false);
}
}
```

OrdersController.php

```
if($order_status != ''){
            if($order_status == 1){
                $0rdersDb = $0rdersDb->whereBetween('order_status',['1','3']);
            }else{
                $map['order_status'] = (int) $order_status;
            }
        }
        $map['buyer_id'] = $this->memberInfo['member_id'];
        $list =
$OrdersDb->where($map)->orderBy('order_time','DESC')->skip($offset)->take($size)->select
()->get()->toArray();
        if(!$list){
            $ret['order_list'] = array();
        }else{
            foreach($list as $k=>$v){
                $v['order_goods'] = unserialize($v['order_goods']);
                $ret['order_list'][] = $v;
            }
        }
        $ret['result'] = 'ok';
        echo json_encode($ret);
   }
   #提交订单
   public function add(){
        $data = file_get_contents("php://input");
        $data = json_decode($data,true);
        $GoodsDb = new Goods;
        $0rdersDb = new Orders;
        $goodsInfo = $GoodsDb->getGoods(array('goods_id'=>$data['goods_id']));
        if(!$goodsInfo){
            echo json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'该
商品不存在'));
            return;
        }
```

```
if($goodsInfo['goods stock'] <= ){</pre>
            echo json_encode(array('result'=>'fail','error_code'=>42042,'error_info'=>'商
品已售罄,去首页逛逛吧'));
            return;
        }
        $AddressDB = new Address;
        $map = array();
        $map['member_id'] = $this->memberInfo['member_id'];
        $map['address id'] = $data['address id'];
        $address = $AddressDB->getAddr($map);
        if(!$address){
            echo json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'地
址不存在'));
            return;
        }
        $input['buyer_id'] = $this->memberInfo['member_id'];
        $input['order sn'] =
date('YmdHis').rand(,9).rand(,9).rand(,9).rand(,9).rand(,9).
        $input['goods_id'] = $data['goods_id'];
        $input['group_order_id'] = (int)$data['group_order_id'] ?
(int)$data['group order id'] : ;
        $input['group_buy'] = $data['groupbuy'];
        if($input['group_buy'] == 1){
            $groupBuyCount =
$OrdersDb->where(array('buyer_id'=>$this->memberInfo['member_id'],'group_buy'=>1,'order_
status'=>array('not in',array(1,5))))->count();
            if($groupBuyCount >= $goodsInfo['limit_buy'] && $goodsInfo['limit_buy'] !=
) {
                echo
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'该商品一人限
购'.$goodsInfo['limit_buy'].'件'));
                return;
            }
        }
        if($input['group_buy'] == 1 && $input['group_order_id'] == ){
            $input['group_header'] = 1;
        }
        if($input['group_buy'] == 1 && $input['group_order_id'] > ){
            //加入团操作。。判断该团是否可以进行
            $GroupDb = new Group;
            $groupInfo =
```

```
$GroupDb->getGroup(array('group order id'=>$input['group order id']));
            if(!$groupInfo){
                echo
json_encode(array('result'=>'fail','error_code'=>41003,'error_info'=>'该团不存在'));
                return;
            }
            if($groupInfo['status'] == 1){
                echo
json_encode(array('result'=>'fail','error_code'=>41003,'error_info'=>'该团已满员'));
                return;
            }
            if($groupInfo['status'] == 2){
                echo
json_encode(array('result'=>'fail','error_code'=>41003,'error_info'=>'该团已关闭'));
                return;
            }
            $orderMap['group_order_id'] = $groupInfo['group_order_id'];
            $orderMap[] = array('pay_sn','>',);
            $orderMap[] = array('pay_time','>',);
            $orderMap['buyer_id'] = $this->memberInfo['member_id'];
            if($0rdersDb->where($orderMap)->first()){
json encode(array('result'=>'fail','error code'=>41003,'error info'=>'您已加入过此团'));
                return;
            }
        }
        $input['province id'] = $address['province id'];
        $input['city_id'] = $address['city_id'];
        $input['district_id'] = $address['district_id'];
        $input['province_name'] = $address['province'];
        $input['city_name'] = $address['city'];
        $input['district_name'] = $address['district'];
        $input['mobile'] = $address['mobile'];
        $input['receive_name'] = $address['receive_name'];
        $input['nickname'] = $this->memberInfo['nickname'];
        $input['order_goods'] = serialize($goodsInfo);
        $input['goods number'] = 1;
        if($data['groupbuy'] == 1){
```

```
$input['goods amount'] = $goodsInfo['group price'];
            $input['order_amount'] = $goodsInfo['group_price'];
            $input['pay_amount'] = $goodsInfo['group_price'];
        }else{
            $input['goods_amount'] = $goodsInfo['alone_price'];
            $input['order_amount'] = $goodsInfo['alone_price'];
            $input['pay_amount'] = $goodsInfo['alone_price'];
        }
        $input['shipping_address'] = $address['full_address'];
        $input['shipping_amount'] = 0.00;
        $input['order_status'] = ;
        $input['order_time'] = time();
        $order_id = $OrdersDb->insertGetId($input);
        if($order id){
            echo json_encode(array('result'=>'ok','order_id'=>$order_id));
            return;
        }else{
            echo json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'创
建订单失败'));
            return;
        }
        exit;
   }
   public function detail($order_id){
        $0rdersDb = new Orders;
        $orderInfo =
$OrdersDb->getOrder(array('order_id'=>$order_id,'buyer_id'=>$this->memberInfo['member_id
'l));
        if(!$orderInfo){
            echo json_encode(array('result'=>'fail','error_code'=>41001,'error_info'=>'订
单不存在'));
            return;
        }
        $orderInfo['order_goods'] = unserialize($orderInfo['order_goods']);
        $ret['order'] = $orderInfo;
        $ret['result'] = 'ok';
        echo json_encode($ret);
```

```
}
public function cancel($order_id){
$0rdersDb = new Orders;
$orderInfo =
$OrdersDb->getOrder(array('order id'=>$order id,'buyer id'=>$this->memberInfo['member id
'l));
if(!$orderInfo){
echo json_encode(array('result'=>'fail','error_code'=>41001,'error_info'=>'iJ
单不存在'));
return;
}
$OrdersDb->where(array('order_id'=>$order_id,'buyer_id'=>$this->memberInfo['member_id'])
) ->update(array('order_status'=>5));
$ret['result'] = 'ok';
echo json_encode($ret);
}
# 确认收货
public function receive($order_id){
      $0rdersDb = new Orders;
$0rdersDb->where(array('order_id'=>$order_id))->update(array('order_status'=>4,'received
_time'=>time()));
$ret['result'] = 'ok';
echo json_encode($ret);
exit;
}
}
```

PaymentController.php

```
<?php
// +----
// | Description:
// +----
// | Author: beichen <notice@notestore.cn>
// +----
namespace App\Http\Controllers\Api\Air\v_1_0;
```

```
use App\Models\Goods;
use App\Models\Group;
use App\Models\Orders;
use App\Models\Paylog;
use Illuminate\Support\Facades\DB;
class PaymentController extends WeuserController {
   # 调起微信支付
   public function wxpay($order_id){
        $0rdersDb = new Orders();
        $orderInfo = $OrdersDb->getOrder(array('order_id'=>$order_id));
        if(!$orderInfo){
            echo json_encode(array('result'=>'fail','error_code'=>41001,'error_info'=>'订
单不存在'));
            return;
        }
        $GoodsDb = new Goods();
        $goodsInfo = $GoodsDb->getGoods(array('goods_id'=>$orderInfo['goods_id']));
        if(!$goodsInfo){
            echo json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'商
品已下架或删除'));
            return;
        }
        if($goodsInfo['goods_stock'] <= ){</pre>
            echo json encode(array('result'=>'fail','error code'=>41002,'error info'=>'商
品已售罄,去首页逛逛吧'));
            return;
        }
        if($orderInfo['group_buy'] == 1){
            $groupBuyCount =
$OrdersDb->where(array('buyer id'=>$this->memberInfo['member id'],'group buy'=>1,'order
status'=>array('not in',array(1,5))))->count();
            if($groupBuyCount >= $goodsInfo['limit_buy'] && $goodsInfo['limit_buy'] !=
) {
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'该商品一人限
购'.$goodsInfo['limit_buy'].'件'));
                return;
            }
        }
```

```
if($orderInfo['group buy'] == 1 && $orderInfo['group order id'] > ){
            $GroupDb = new Group;
            $groupInfo =
$GroupDb->getGroup(array('group_order_id'=>$orderInfo['group_order_id']));
            if(!$groupInfo){
                echo
ison encode(array('result'=>'fail','error code'=>41002,'error info'=>'该团不存在'));
                return:
            }
            if($groupInfo['status'] == 1){
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'该团已满员'));
                return;
            }
            if($groupInfo['status'] == 2){
                echo
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'该团已关闭'));
                return;
            }
            $orderMap['group_order_id'] = $groupInfo['group_order_id'];
            $orderMap[] = array('pay sn','>',);
            $orderMap[] = array('pay_time','>',);
            $orderMap['buyer_id'] = $this->memberInfo['member_id'];
            if($0rdersDb->where($orderMap)->first()){
                echo
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'您已加入过此团'));
                return;
            }
        }
        //开始生成支付信息
        $time = time();
        $pay['pay_sn'] =
date('YmdHis').rand(,9).rand(,9).rand(,9).rand(,9).rand(,9);
        $pay['order id'] = $orderInfo['order id'];
        $pay['pay_amount'] = $orderInfo['pay_amount'];
        $pay['pay_start_time'] = $time;
        $pay['pay_status'] = ;
        $PaylogDb = new Paylog;
        $pay id = $PaylogDb->insertGetId($pay);
        $payInfo = $PaylogDb->getPaylog(array('pay_id'=>$pay_id));
```

```
if(!$payInfo){
            echo json_encode(array('result'=>'fail','error_code'=>41001,'error_info'=>'生
成支付订单失败'));
            return;
        }
        if($payInfo['pay status'] == 1){
            echo json_encode(array('result'=>'fail','error_code'=>41003,'error_info'=>'该
订单已支付')):
            return;
        }
        require_once base_path("app/Utils/JsApiPay/mini/WxPay.JsApiPay.php");
        $tools = new \JsApiPay();
        $openId = $this->memberInfo['open id'];
        $input = new \WxPayUnifiedOrder();
        $input->SetBody($goodsInfo['goods name']);
        $input->SetOut_trade_no($payInfo['pay_sn']);
        $input->SetTotal_fee($orderInfo['pay_amount'] * 100);
        $input->SetTime start(date("YmdHis"));
        $input->SetTime_expire(date("YmdHis", time() + 600));
        $url = route('wxpay_notify');
        $input->SetNotify url($url);
        $input->SetTrade_type("JSAPI");
        $input->SetOpenid($openId);
        $config = new \WxPayConfig();
        $order = \WxPayApi::unifiedOrder($config,$input);
        $PaylogDb->where('pay_id',$payInfo['pay_id'])->update(array('prepay_id' =>
$order['prepay id']));
        $jsApiParameters = $tools->GetJsApiParameters($order);
        $jsApiParameters = json_decode($jsApiParameters,true);
        $ret['param'] = $jsApiParameters;
        $ret['result'] = 'ok';
        echo json_encode($ret);
   }
```

}

ProjectController.php

```
<?php
// +-----
// | Description: 通用接口
// | Author: beichen <notice@notestore.cn>
namespace App\Http\Controllers\Api\Air\v_1_0;
use App\Http\Controllers\Core\ApiController;
use App\Models\Orders;
use App\Models\OrderLog;
use App\Models\Region;
use App\Utils\ToolsUtils;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use App\Models\Member;
use App\Models\Paylog;
use App\Models\Group;
class ProjectController extends ApiController {
    /**
  * 数据版本
     */
    public function data_version(Request $request){
        $type = $request->get('type');
        switch($type){
            case 'region_list':
                $ret['result'] = 'ok';
                $ret['data version']['data key'] = 'region list';
                $ret['data_version']['version'] = 1;
                break;
            default:
                $ret['result'] = 'fail';
                $ret['error code'] = 42000;
                $ret['error_info'] = '非法参数';
                break;
        }
        echo json_encode($ret);
    }
```

```
public function regions(){
        $RegionDb = new Region();
        $city[1] = $RegionDb->getRegion(array('level'=>1));
        $city[2] = $RegionDb->getRegion(array('level'=>2));
        $city[3] = $RegionDb->getRegion(array('level'=>3));
        $ret['regions'] = $city;
        $ret['result'] = 'ok';
        echo json_encode($ret);
   }
   public function express($order_id){
        $0rdersDb = new Orders;
        $orderInfo = $0rdersDb->getOrder(array('order_id'=>$order_id));
        if(!$orderInfo){
            echo json_encode(array('result'=>'fail','error_code'=>41001,'error_info'=>'该
订单不存在'));
            return;
        }
        $url =
'http://www.kuaidi100.com/query?type='.$orderInfo['shipping_code'].'&postid='.$orderInfo
['tracking_number'].'&id=1&valicode=&temp='.ToolsUtils::random(4).'&sessionid=&tmp='.Too
lsUtils::random(4);
        $content = file_get_contents($url);
        $content = json_decode($content,true);
        if ($content['status'] != 200){
            echo json_encode(array('result'=>'fail','error_code'=>41001,'error_info'=>'查
询物流信息出错'));
            return;
        $traces = array();
        foreach($content['data'] as $k=>$v){
            $tmp = array();
            $tmp['time'] = $v['time'];
            $tmp['address'] = $v['location'];
            $tmp['remark'] = $v['context'];
            $traces[] = $tmp;
        }
        $ret['shipping']['traces'] = $traces;
        $ret['shipping']['shipper'] = $orderInfo['shipping name'];
        $ret['shipping']['tracking_number'] = $orderInfo['tracking_number'];
        $ret['result'] = 'ok';
```

```
echo json_encode($ret);
   }
   public function crontab(){
        \Log::useFiles(storage_path("logs/crontab.txt"));
        \Log::DEBUG(false);
        //团即将过期提醒
        $this->groupMsgCrontab();
        //团 超时退款
        $this->groupRefound();
        //确认 收货
        $this->confirmShipping();
   }
   protected function groupMsgCrontab() {
        $GroupDb = new Group;
        $0rdersDb = new Orders;
        $PaylogDb = new Paylog;
        map = [];
        $map['group_buy'] = 1;
        $map[] = ['orders.pay_sn','<>',''];
        $map[] = ['pay_time','>',];
        $map['notify'] = ;
        $map['status'] = ;
        $time = time() + 3600 * config('group.notify_hour');
        $map[] = ['expire_time','<',$time];</pre>
        $map[] = ['expire_time','>',time()];
        $orders =
$0rdersDb->join("member","orders.buyer_id","=","member.member_id")->join("group","orders
.group_order_id","=","group.group_order_id")->join("paylog","orders.pay_id","=","paylog.
pay_id")->where($map)->select()->get()->toArray();
        if($orders) {
            foreach ($orders as $v) {
                $groupIds[] = $v['group_order_id'];
                $v['order_goods'] = unserialize($v['order_goods']);
                $msg = '您参加的'.$v['order_goods']['goods_name'].'还
有'.config('group.notify_hour').'小时到期,目前还差'.($v['require_num'] - $v['people']).'人,快去
叫上身边的小伙伴一起'. env('WEB NAME'). '吧';
```

```
if(config('wechat.miniapp tpl.open') == 1){
                    //发送团即将过期提醒
                    $data['keyword1'] = array('value'=>
$v['order_goods']['goods_name'],'color'=>'#000');
                    $data['keyword2'] = array('value'=> config('group.notify_hour') . '小
时','color'=>'#000');
                    $data['keyword3'] = array('value'=> $v['require_num'] - $v['people']
. '人' ,'color'=>'#000');
                    $data['keyword4'] = array('value'=> $msg,'color'=>'#000');
App\Utils\ToolsUtils::send_miniapp_msg($v['open_id'],config('wechat.miniapp_tpl.group_no
tify_tpl'),'pages/group?id='.$v['group_order_id'],$v['prepay_id'],$data);
            }
            $GroupDb->whereIn('group_order_id',$groupIds)->update(array('notify'=>1));
        }
    }
    protected function groupRefound() {
        $GroupDb = new Group;
        $0rdersDb = new Orders;
        $PaylogDb = new Paylog;
        $time = time();
        $groupIds = [];
        $map[] = array('expire_time','<',$time);</pre>
        $map['status'] = ;
        $groups = $GroupDb->where($map)->select()->get()->toArray();
        if($groups) {
            foreach($groups as $v){
                $groupIds[] = $v['group_order_id'];
            }
            $GroupDb->whereIn('group_order_id',$groupIds)->update(array('status'=>2));
        }
        map = [];
        $map['group_buy'] = 1;
        $map[] = ['orders.pay_sn','<>',''];
        $map[] = ['pay_time','>',];
        $orders =
$OrdersDb->join("member","orders.buyer_id","=","member.member_id")->join("paylog","order
s.pay_id","=","paylog.pay_id")->where($map)->whereIn("group_order_id",$groupIds)->select
()->get()->toArray();
```

```
if($orders) {
            foreach($orders as $v) {
                $ret = $this->refound($v['transaction_id'],$v['pay_amount'] *100 ,
$v['pay_amount'] *100);
                if($ret){
$PaylogDb->where(['pay_id'=>$v['pay_id']])->update(['refound_id'=>$ret['out_refund_no']]
);
$OrdersDb->where(['order id'=>$v['order id']])->update(['order status'=>7]);
$0rdersDb->where(['order_id'=>$v['order_id']])->update(['order_status'=>6]);
                }
                $msg = '您的订单退款申请已经提交给微信处理了哦~微信系统需要审核,微信最迟5个工作日内会
退款到您的支付账户哦~谢谢您的支持!';
                if(config('wechat.miniapp_tpl.open') == 1){
                    //发送退款通知
                    $goodsInfo = unserialize($v['order_goods']);
                    $data['keyword1'] = array('value'=>$v['order_sn'],'color'=>'#000');
                    $data['keyword2'] =
array('value'=>$goodsInfo['goods name'],'color'=>'#000');
                    $data['keyword3'] = array('value'=> $v['pay_amount'] .
"",'color'=>'#000');
                    $data['keyword4'] = array('value'=> date('Y-m-d H:i:s',time())
,'color'=>'#000');
                    $data['keyword5'] = array('value'=> $msg,'color'=>'#000');
App\Utils\ToolsUtils::send_miniapp_msg($v['open_id'],config('wechat.miniapp_tpl.refound_
notify_tpl'),'pages/order?id='.$v['order_id'],$v['prepay_id'],$data);
                }
            }
        }
   }
   protected function confirmShipping() {
        $0rdersDb = new Orders;
        $0rderLog = new OrderLog;
        map = [];
        $map[] = ["pay sn","<>",""];
        $map[] = ["pay_time",">",];
        $map['order_status'] = 3;
        $time = time() - config('order.shipping_time');
        $map[] = ["shipping_time","<",$time];</pre>
```

```
$orders = $OrdersDb->where($map)->select()->get()->toArray();
foreach ($orders as $k => $v)
          $log['manage'] = "crontab";
          $log['order_id'] = $v['order_id'];
          $log['remark'] = "系统自动,确认收货";
          $log['time'] = time();
          $log['do'] = '确认收货';
          $0rderLog->insert($log);
          $0rdersDb->where(['order_id' => $v['order_id']])->update(['order_status' =>
4,'received_time' => time()]);
}
}
private function refound($transaction_id,$total_fee,$refund_fee) {
require_once_base_path("app/Utils/JsApiPay/mini/WxPay.Config.php");
require_once base_path("app/Utils/JsApiPay/mini/WxPay.JsApiPay.php");
$input = new \WxPayRefund();
$input->SetTransaction_id($transaction_id);
       $input->SetTotal_fee($total_fee);
$input->SetRefund_fee($refund_fee);
$config = new \WxPayConfig();
$input->SetOut_refund_no($config->GetMerchantId() . date('YmdHis') . rand(,9) .
rand(,9) . rand(,9) . rand(,9));
$input->SetOp_user_id($config->GetMerchantId());
$ret = \WxPayApi::refund($config, $input);
if($ret['result_code'] = 'SUCCESS'){
return $ret;
} else {
return false;
}
}
}
```

WeuserController.php

```
<?php
// +---
// | Description:
// +---
// | Author: beichen <notice@notestore.cn>
// +---
namespace App\Http\Controllers\Api\Air\v_1_0;
```

```
use App\Http\Controllers\Core\ApiController;
use App\Models\MemberToken;
use App\Models\Share;
use Illuminate\Support\Facades\DB;
use Illuminate\Http\Request;
class WeuserController extends ApiController {
    public function construct(Request $request)
    {
        $token = $request->header('AccessToken');
        $MemberTokenDB = new MemberToken();
        $memberInfo = $MemberTokenDB->getUser($token);
        $time = time();
        if(!$memberInfo){
            $this->memberInfo = false;
            echo json_encode(array('result'=>'fail','error_code'=>40001,'error_info'=>'用
户校验失败'));
            exit;
        }
        $this->memberInfo = $memberInfo;
    }
    /**
  * 获取个人信息
    */
    public function me(){
        echo json_encode(array('result'=>'ok', 'user_info'=>$this->memberInfo));
    }
    public function share(){
        $data = file_get_contents("php://input");
        $data = json_decode($data,true);
        $data['share_time'] = time();
        $data['member id'] = $this->memberInfo['member id'];
        $ShareDb = new Share;
        $ShareDb->insert($data);
        $ret['result'] = 'ok';
        echo json_encode($ret);
        exit;
```

```
}
}
```

GoodsController.php

```
<?php
// | Description:
// +-----
// | Author: beichen <notice@notestore.cn>
namespace App\Http\Controllers\Mini\Air\v_1_0;
use App\Http\Controllers\Core\ApiController;
use Illuminate\Support\Facades\DB;
use Illuminate\Http\Request;
use \App\Utils\WeixinMiniapp\Weapp;
class GoodsController extends ApiController
{
   public function detail($goods_id) {
        $GoodsDb = DB::table('goods');
        $goods = $GoodsDb->where('goods_id',$goods_id)->first();
       if(!$goods) {
           return
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'商品已下架或不存在'));
        $goods['goods_desc'] = str_replace("<img ", "<img style='max-width:100%;' ",</pre>
$goods['goods_desc']);
        $title_length = mb_strlen($goods['goods_name'], "utf-8");
       $title_one = $goods['goods_name'];
       if($title_length > 16){
           $title_one = mb_substr($goods['goods_name'], , 16, "utf-8");
       }
        $title_two = "";
        if($title_length > 16){
           if($title_length>32){
               $title_two = mb_substr($goods['goods_name'], 16, 16, "utf-8").'...';
           }else{
```

```
$title two = mb substr($goods['goods name'], 16, ($title length-16),
"utf-8");
            }
        }
        $goods['title_one'] = $title_one;
        $goods['title_two'] = $title_two;
        $imgs = unserialize($goods['goods imgs']);
        foreach($imgs as $v){
            $gallery[]['img_url'] = $v;
        }
        echo json_encode(array('result'=>'ok','goods'=>$goods,'gallery'=>$gallery));
   }
   public function poster($goods_id) {
        $GoodsDb = DB::table('goods');
        $goods = $GoodsDb->where('goods_id',$goods_id)->first();
        if(!$goods) {
            return
json_encode(array('result'=>'fail','error_code'=>41002,'error_info'=>'商品已下架或不存在'));
        header('Content-Disposition: Attachment; filename=goods-poster-
'.$goods id.'.jpeg');
        header('Content-type: image/png');
        $goods_poster_string =
file_get_contents(storage_path('app/public/assets/images/goods-poster-bg.png'));
        $goods_cover_string = file_get_contents($goods['image_url']);
        list($coverWidth, $coverHeight, $coverCodeType) =
getimagesizefromstring($goods_cover_string);
        $srcWidth = $coverWidth>$coverHeight?$coverHeight:$coverWidth;
        $goods_poster_bg = imagecreatefromstring($goods_poster_string);
        $goods cover = imagecreatefromstring($goods cover string);
        // $exif = @exif_read_data($goods['image_url']);
        // if (!empty($exif)&&!empty($exif['Orientation'])) {
               switch ($exif['Orientation']) {
        //
        //
                   case 8:
                       $goods_cover = imagerotate($goods_cover, 90, 0);
        //
                       break;
        //
                   case 3:
                       $goods_cover = imagerotate($goods_cover, 180, 0);
        //
```

```
break;
        //
                   case 6:
        //
                       $goods cover = imagerotate($goods cover, -90, 0);
        //
        //
               }
        // }
        //目标商品图片宽、高
        $dis_cover_width = 1000;
        $dis_cover_height = 1000 / ($coverWidth / $coverHeight);
        $new_goods_cover = imagecreatetruecolor($dis_cover_width, $dis_cover_height);
        //缩放商品图片
        imagecopyresampled($new_goods_cover, $goods_cover, , , , , $dis_cover_width,
$dis_cover_height, $coverWidth, $coverHeight);
        //放商品封面
        imagecopymerge($goods_poster_bg, $new_goods_cover, 62, 62 + (1000 -
$dis_cover_height) / 2, , , $dis_cover_width, $dis_cover_height, 100);
        $black = imagecolorallocate($goods_poster_bg, 51, 51, 51);
        //放入标题
        $title_length = mb_strlen($goods['goods_name'], "utf-8");
        $title = $goods['goods_name'];
        if($title length > 13){
            $title = mb_substr($goods['goods_name'], , 13, "utf-8");
        imagettftext($goods_poster_bg, 34, , 65, 1150, $black,
storage_path('app/public/assets/vista-yahei.ttf'), $title);
        if($title_length > 13){
            if($title length>26){
               $title = mb_substr($goods['goods_name'], 13, 13, "utf-8").'...';
            }else{
               $title = mb_substr($goods['goods_name'], 13, ($title_length-13),
"utf-8");
            }
            imagettftext($goods_poster_bg, 34, , 65, 1220, $black,
storage_path('app/public/assets/vista-yahei.ttf'), $title);
        }
        //价格
        $price_color = imagecolorallocate($goods_poster_bg, 254, 90, 76);
        imagettftext($goods_poster_bg, 34, , 900, 1150, $price_color,
storage_path('app/public/assets/vista-yahei.ttf'), "\foots ".\square\text{goods['group_price']);}
```

```
//划线
        $line_color = imagecolorallocate($goods_poster_bg, 230, 230, 230);
        for($i = ; $i < 3; $i++){
            imageline($goods_poster_bg, 62, 1300+$i, 1062, 1300+$i, $line_color);
        }
        //小程序码
        $option['appid'] = config('wechat.miniapp.appid');
        $option['appsecret'] = config('wechat.miniapp.appsecret');
        $wxacode tool = new Weapp($option);
        $wxacode_string = $wxacode_tool->getQRCodes("pages/goods",$goods_id,470,,);
        list($wxacodeWidth, $wxacodeHeight, $wxacodeType) =
getimagesizefromstring($wxacode_string);
        $wxacode = imagecreatefromstring($wxacode_string);
        $new_wxacode = imagecreatetruecolor(350, 350);
        //缩放商品图片
        imagecopyresampled($new_wxacode, $wxacode, , , , , 350, 350, $wxacodeWidth,
$wxacodeWidth);
        imagecopymerge($goods_poster_bg, $new_wxacode, 62, 1350, , , 350, 350, 100);
        //提示文字
        $ps_text_color = imagecolorallocate($goods_poster_bg, 102, 102, 102);
        imagettftext($goods_poster_bg, 30, , 530, 1500, $ps_text_color,
storage_path('app/public/assets/vista-yahei.ttf'), "长按识别图中的小程序码");
        imagettftext($goods poster bg, 30, , 530, 1560, $ps text color,
storage_path('app/public/assets/vista-yahei.ttf'), "查看详情");
        //输出最终结果
        imagejpeg($goods_poster_bg);
        imagedestroy($goods_poster_bg);
        imagedestroy($goods cover);
        imagedestroy($new_goods_cover);
        imagedestroy($wxacode);
        imagedestroy($new wxacode);
    }
}
```

GroupsController.php

```
<?php
// | Description: 团
// +-----
// | Author: beichen <notice@notestore.cn>
namespace App\Http\Controllers\Mini\Air\v 1 0;
use App\Http\Controllers\Core\ApiController;
use App\Models\Group;
use App\Models\Orders;
use Illuminate\Http\Request;
use \App\Utils\WeixinMiniapp\Weapp;
class GroupsController extends ApiController {
    public function poster($id) {
        $GroupDb = new Group;
        $groupInfo = $GroupDb->getGroup(array('group_order_id'=>$id));
        if(!$groupInfo){
            echo json_encode(array('result'=>'fail','error_code'=>41001,'error_info'=>'该
团不存在'));
            return;
        }
        $0rdersDb = new Orders;
        map = array();
        $map['group_order_id'] = $groupInfo['group_order_id'];
        $map['group buy'] = 1;
        $map['group_header'] = 1;
        $order =
$0rdersDb->whereNotIn('order_status',[,5])->where($map)->orderBy('group_header','asc')->
orderBy('pay_time', 'asc')->first();
        $goods = unserialize($order['order_goods']);
        header('Content-Disposition: Attachment;filename=goods-poster-'.$id.'.jpeg');
        header('Content-type: image/png');
        $goods_poster_string =
file_get_contents(storage_path('app/public/assets/images/goods-poster-bg.png'));
        $goods_cover_string = file_get_contents($goods['image_url']);
        list($coverWidth, $coverHeight, $coverCodeType) =
```

```
getimagesizefromstring($goods cover string);
        $srcWidth = $coverWidth>$coverHeight?$coverHeight:$coverWidth;
        $goods_poster_bg = imagecreatefromstring($goods_poster_string);
        $goods_cover = imagecreatefromstring($goods_cover_string);
        // $exif = @exif_read_data($goods['image_url']);
        // if (!empty($exif)&&!empty($exif['Orientation'])) {
               switch ($exif['Orientation']) {
        //
                  case 8:
                       $goods cover = imagerotate($goods cover, 90, 0);
        //
                       break;
        //
                  case 3:
                       $goods cover = imagerotate($goods cover, 180, 0);
        //
        //
                       break;
                  case 6:
        //
                       $goods_cover = imagerotate($goods_cover, -90, 0);
        //
                       break;
        //
               }
        // }
        //目标商品图片宽、高
        $dis_cover_width = 1000;
        $dis_cover_height = 1000 / ($coverWidth / $coverHeight);
        $new_goods_cover = imagecreatetruecolor($dis_cover_width, $dis_cover_height);
        //缩放商品图片
        imagecopyresampled($new_goods_cover, $goods_cover, , , , , $dis_cover_width,
$dis_cover_height, $coverWidth, $coverHeight);
        //放商品封面
        imagecopymerge($goods poster bg, $new goods cover, 62, 62 + (1000 -
$dis_cover_height) / 2, , , $dis_cover_width, $dis_cover_height, 100);
        $black = imagecolorallocate($goods_poster_bg, 51, 51, 51);
        //放入标题
        $title_length = mb_strlen($goods['goods_name'], "utf-8");
        $title = $goods['goods name'];
        if($title length > 13){
            $title = mb_substr($goods['goods_name'], , 13, "utf-8");
        }
        imagettftext($goods_poster_bg, 34, , 65, 1150, $black,
storage path('app/public/assets/vista-yahei.ttf'), $title);
        if($title_length > 13){
            if($title_length>26){
               $title = mb_substr($goods['goods_name'], 13, 13, "utf-8").'...';
```

```
}else{
               $title = mb_substr($goods['goods_name'], 13, ($title_length-13),
"utf-8");
            }
            imagettftext($goods poster bg, 34, , 65, 1220, $black,
storage_path('app/public/assets/vista-yahei.ttf'), $title);
        }
        //价格
        $price color = imagecolorallocate($goods poster bg, 254, 90, 76);
        imagettftext($goods_poster_bg, 34, , 900, 1150, $price_color,
storage_path('app/public/assets/vista-yahei.ttf'), "\footings "group_price']);
        //划线
        $line_color = imagecolorallocate($goods_poster_bg, 230, 230, 230);
        for($i = ; $i < 3; $i++){}
            imageline($goods_poster_bg, 62, 1300+$i, 1062, 1300+$i, $line_color);
        }
        //小程序码
        $option['appid'] = config('wechat.miniapp.appid');
        $option['appsecret'] = config('wechat.miniapp.appsecret');
        $wxacode tool = new Weapp($option);
        $wxacode string = $wxacode tool->getQRCodes("pages/goods",$id,470,,);
        list($wxacodeWidth, $wxacodeHeight, $wxacodeType) =
getimagesizefromstring($wxacode_string);
        $wxacode = imagecreatefromstring($wxacode_string);
        $new wxacode = imagecreatetruecolor(350, 350);
        //缩放商品图片
        imagecopyresampled($new_wxacode, $wxacode, , , , , 350, 350, $wxacodeWidth,
$wxacodeWidth);
        imagecopymerge($goods_poster_bg, $new_wxacode, 62, 1350, , , 350, 350, 100);
        //提示文字
        $ps text color = imagecolorallocate($goods poster bg, 102, 102, 102);
        imagettftext($goods_poster_bg, 30, , 530, 1500, $ps_text_color,
storage_path('app/public/assets/vista-yahei.ttf'), "长按识别图中的小程序码");
        imagettftext($goods_poster_bg, 30, , 530, 1560, $ps_text_color,
storage path('app/public/assets/vista-yahei.ttf'), "查看-拼团详情");
        //输出最终结果
        imagejpeg($goods_poster_bg);
        imagedestroy($goods_poster_bg);
```

```
imagedestroy($goods_cover);
imagedestroy($new_goods_cover);
imagedestroy($wxacode);
imagedestroy($new_wxacode);
}
```

WechatController.php

```
<?php
namespace App\Http\Controllers\Mini\Air\v 1 0;
use App\Http\Controllers\Core\ApiController;
use App\Utils\ToolsUtils;
use App\Utils\WeixinMiniapp\WXBizDataCrypt;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
use \App\Utils\WeixinMiniapp\Weapp;
class WechatController extends ApiController
    /**
  * 微信用户登录
     */
    public function login(Request $request){
        $signature =$request->get('signature');
        $iv = $request->get("iv");
        $encryptedData = $request->get('encryptedData');
        $option['appid'] = config('wechat.miniapp.appid');
        $option['appsecret'] = config('wechat.miniapp.appsecret');
        $option['debug'] = true;
        $weChat = new Weapp($option);
        $ret = $weChat->getOauthAccessToken();
        if(!$ret){
            echo json_encode(array('result'=>'fail','error_code'=>42032,'error_info'=>'获
取用户信息失败'));
            return:
        }
        $memberInfo = DB::table('member')->where('open_id',$ret['openid'])->first();
        $encrypt = new WXBizDataCrypt($option['appid'],$ret['session_key']);
        $error_code = $encrypt->decryptData($encryptedData, $iv,$userinfo);
```

```
if($error code != ){
            echo json_encode(array('result'=>'fail','error_code'=>42032,'error_info'=>'获
取用户信息失败'));
            return;
        }
        @$userinfo = json_decode($userinfo,true);
        @$_headimgurl = pathinfo($userinfo['avatarUrl']);
        if(isset($ret['unionid'])){
            $data['unionid'] = $ret['unionid'];
        }
        $data['nickname'] = $userinfo['nickName'];
        $data['sex'] = $userinfo['gender'];
        $data['headimgurl'] = sprintf("%s/0",$_headimgurl['dirname']);
        $data['subscribe'] = 1;
        if(!$memberInfo){
            $data['open_id'] = $ret['openid'];
            $data['time'] = time();
            $data['disablle'] = ;
        }
        if(!$memberInfo){
            $userId = DB::table('member')->insertGetId($data);
        }else{
DB::table('member')->where('member_id',$memberInfo['member_id'])->update($data);
            $userId = $memberInfo['member_id'];
        }
        $data['result'] = 'ok';
        $data['user_sn'] = $userId;
        $memberToken['member_id'] = $userId;
        $memberToken['expires'] = ;
        $memberTokenDb = DB::table('member_token');
        $error_no = ;
        do {
            try {
                $memberToken['token'] = ToolsUtils::generate_password(48);
                $memberTokenDb->insert($memberToken);
            } catch (\PDOException $e) {
                $error_no = $e->errorInfo[1];
```

```
if($error_no > && $error_no != 1062)
                {
                    throw $e;
                    return;
                }
        } while ($error_no == 1062);
        $data['token'] = $memberToken['token'];
        echo json_encode($data);
    }
    public function wxacode($id,Request $request) {
        $page = $request->get("page");
        $width = $request->get("width",470);
        $option['appid'] = config('wechat.miniapp.appid');
        $option['appsecret'] = config('wechat.miniapp.appsecret');
        $option['debug'] = true;
        $weChat = new Weapp($option);
        header('Content-Type: image/png');
        echo $weChat->getQRCodes($page,$id,$width,,);
        exit;
    }
}
```

.htaccess

```
<IfModule mod_rewrite.c>
  Options +FollowSymlinks -Multiviews
  RewriteEngine On

RewriteCond %{REQUEST_FILENAME} !-d
  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteRule ^(.*)$ resources/assets/$1 [QSA,PT,L]

</IfModule>
```

pin.6 2019-02-26.sql

```
DROP TABLE IF EXISTS `address`;
CREATE TABLE `address` (
  `address_id` int(11) NOT NULL AUTO_INCREMENT,
  `member id` int(11) NOT NULL,
  `country` int(11) DEFAULT NULL,
  'province' varchar(50) CHARACTER SET gbk NOT NULL DEFAULT '',
  `city` varchar(50) CHARACTER SET gbk NOT NULL,
  `district` varchar(50) CHARACTER SET gbk NOT NULL,
  `province id` int(11) NOT NULL,
  `city_id` int(11) NOT NULL,
  `district_id` int(11) NOT NULL,
  `address` varchar(255) NOT NULL DEFAULT '',
  `id_number` varchar(50) CHARACTER SET gbk DEFAULT '',
  `mobile` varchar(11) CHARACTER SET gbk NOT NULL,
  `receive_name` varchar(20) CHARACTER SET gbk NOT NULL,
  `address name` char(10) CHARACTER SET gbk DEFAULT '',
  `full_address` varchar(255) NOT NULL DEFAULT '',
  `status` varchar(20) CHARACTER SET gbk DEFAULT '',
  `created_time` int(10) NOT NULL,
  `last updated time` int(10) NOT NULL,
  PRIMARY KEY (`address_id`),
  KEY `member_id` (`member_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='地址';
DROP TABLE IF EXISTS `attachment`;
CREATE TABLE `attachment` (
  `attach id` int(11) unsigned NOT NULL AUTO INCREMENT,
  `attach_url` varchar(255) NOT NULL DEFAULT '',
  `oss` tinyint(1) unsigned NOT NULL,
  `time` int(10) unsigned NOT NULL,
 PRIMARY KEY (`attach_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='附件表';
DROP TABLE IF EXISTS `banner`;
CREATE TABLE `banner` (
  `banner_id` int(11) unsigned NOT NULL AUTO_INCREMENT,
  `banner name` varchar(50) NOT NULL DEFAULT '',
  `image_url` varchar(255) NOT NULL DEFAULT '',
  `target url` varchar(255) NOT NULL DEFAULT '',
  `start time` int(10) unsigned DEFAULT NULL,
  `end_time` int(10) unsigned DEFAULT NULL,
  `banner_type` char(50) NOT NULL DEFAULT '',
```

```
`banner sort` int(11) NOT NULL,
  `in_selling` tinyint(1) unsigned NOT NULL,
  PRIMARY KEY (`banner id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4;
DROP TABLE IF EXISTS `goods`;
CREATE TABLE `goods` (
  `goods_id` int(11) unsigned NOT NULL AUTO_INCREMENT,
  `cate_id` int(11) unsigned NOT NULL COMMENT '分类ID',
  `goods name` varchar(50) NOT NULL DEFAULT '' COMMENT '物品名称',
  `image_url` varchar(255) NOT NULL DEFAULT '' COMMENT '主图',
  `goods_desc` mediumtext NOT NULL COMMENT '物品描述',
  `goods_imgs` text NOT NULL COMMENT '商品图片',
  `market_price` decimal(10,2) unsigned NOT NULL COMMENT '市场价',
  `group_price` decimal(10,2) unsigned NOT NULL COMMENT '团购价',
  `alone_price` double(10,2) unsigned NOT NULL COMMENT '单独购买价格',
  `group number` int(11) unsigned NOT NULL COMMENT '团购人数',
  `sell_count` int(11) unsigned NOT NULL DEFAULT '0' COMMENT '销售数量',
  `limit_buy` tinyint(1) unsigned NOT NULL COMMENT '一个会员限制购买几次',
  `goods_stock` int(11) unsigned NOT NULL COMMENT '库存',
  `in_selling` tinyint(1) unsigned NOT NULL COMMENT '是否上架',
  `goods sort` smallint(5) NOT NULL COMMENT '排序',
  `sell type` tinyint(<mark>1</mark>) unsigned NOT <mark>NULL</mark> COMMENT '0不限1:只团购2:只单买',
  `time` int(10) unsigned NOT NULL COMMENT '添加时间',
  `spec name` varchar(255) NOT NULL DEFAULT '' COMMENT '商品规格',
  `spec_type` tinyint(1) unsigned NOT NULL COMMENT '0单规格1:多规格',
  PRIMARY KEY ('goods id'),
  KEY `cate_id` (`cate_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='物品表';
DROP TABLE IF EXISTS `goods_cate`;
CREATE TABLE `goods_cate` (
  `cate id` int(11) unsigned NOT NULL AUTO INCREMENT,
  `cate_name` varchar(50) NOT NULL DEFAULT '',
  `parent_cate` int(11) unsigned NOT NULL,
  `sort` int(11) NOT NULL,
  PRIMARY KEY (`cate_id`),
  KEY `parent_cate` (`parent_cate`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='物品分类';
DROP TABLE IF EXISTS `goods_sku`;
CREATE TABLE `goods sku` (
  `sku_id` int(11) unsigned NOT NULL AUTO_INCREMENT,
  `goods_id` int(11) unsigned NOT NULL,
  `thumb_url` varchar(200) CHARACTER SET gbk DEFAULT '',
  `alone_price` <mark>decimal(10,2)</mark> NOT <mark>NULL</mark> DEFAULT '0.00' COMMENT '单独购买',
```

```
`group price` decimal(10,2) NOT NULL DEFAULT '0.00' COMMENT '团购价格',
  `goods_stock` int(11) NOT NULL DEFAULT '0',
  `sell count` int(11) unsigned NOT NULL DEFAULT '0',
  `goods_spec` varchar(255) NOT NULL DEFAULT '',
  `sort` int(11) NOT NULL,
  PRIMARY KEY (`sku id`),
 KEY `goods_id` (`goods_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4;
DROP TABLE IF EXISTS `group`;
CREATE TABLE `group` (
  `group_order_id` int(11) unsigned NOT NULL AUTO_INCREMENT,
  `require_num` int(11) unsigned NOT NULL,
  `people` int(5) unsigned NOT NULL,
  `status` tinyint(1) unsigned NOT NULL,
  `create_time` int(10) unsigned NOT NULL,
  `expire_time` int(10) unsigned NOT NULL,
  `success_time` int(10) unsigned DEFAULT NULL,
  `owner_id` int(10) unsigned NOT NULL,
  `notify` tinyint(1) unsigned DEFAULT NULL,
 PRIMARY KEY (`group_order_id`),
  KEY `owner_id` (`owner_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4;
DROP TABLE IF EXISTS `login_log`;
CREATE TABLE `login_log` (
  'id' int(11) NOT NULL AUTO_INCREMENT COMMENT 'ID',
  `user id` int(11) NOT NULL COMMENT '用户ID',
  `ips` varchar(256) COLLATE utf8_unicode_ci DEFAULT NULL COMMENT 'IP',
  `address` varchar(128) COLLATE utf8 unicode ci DEFAULT NULL COMMENT '地址',
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
 PRIMARY KEY ('id')
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
DROP TABLE IF EXISTS `member`;
CREATE TABLE `member` (
  `member_id` int(11) unsigned NOT NULL AUTO_INCREMENT,
  `open_id` varchar(255) NOT NULL DEFAULT '' COMMENT '用户open_id',
  `unionid` varchar(255) NOT NULL DEFAULT '',
  `nickname` varchar(50) NOT NULL DEFAULT '' COMMENT '用户昵称',
  `subscribe` tinyint(1) unsigned NOT NULL COMMENT '是否关注',
  `sex` tinyint(1) unsigned DEFAULT NULL COMMENT '性别',
  `headimgurl` varchar(255) NOT NULL DEFAULT '' COMMENT '头像',
  `disablle` tinyint(1) unsigned NOT NULL COMMENT '是否禁用',
  `time` int(10) unsigned NOT NULL COMMENT '注册时间',
```

```
PRIMARY KEY ('member id'),
 KEY `open_id` (`open_id`(250)),
 KEY `unionid` (`unionid`(250))
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='会员表';
DROP TABLE IF EXISTS `member_token`;
CREATE TABLE `member token` (
  `member_id` int(11) unsigned NOT NULL,
 `token` varchar(48) NOT NULL DEFAULT '',
 `expires` int(10) unsigned NOT NULL,
 UNIQUE KEY 'token' ('token'),
 KEY `member_id` (`member_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4;
LOCK TABLES `member token` WRITE;
/*!40000 ALTER TABLE `member_token` DISABLE KEYS */;
DROP TABLE IF EXISTS `menus`;
CREATE TABLE `menus` (
 `id` int(10) unsigned NOT NULL AUTO_INCREMENT,
 `parent id` int(11) NOT NULL DEFAULT '0' COMMENT '上级ID',
  `order` int(11) NOT NULL DEFAULT '0' COMMENT '菜单排序,从1开始,数字越小排在超前,0为排在最后',
 `title` varchar(50) COLLATE utf8 unicode ci DEFAULT NULL COMMENT '标题',
 `icon` varchar(50) COLLATE utf8_unicode_ci NOT NULL COMMENT '图标',
 'uri' varchar(50) COLLATE utf8 unicode ci NOT NULL COMMENT 'URI',
 如url:/menu,controller:MenuController',
 `created at` timestamp NULL DEFAULT NULL,
 `updated_at` timestamp NULL DEFAULT NULL,
 PRIMARY KEY ('id')
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
DROP TABLE IF EXISTS `migrations`;
CREATE TABLE `migrations` (
 `id` int(10) unsigned NOT NULL AUTO_INCREMENT,
 `migration` varchar(255) COLLATE utf8_unicode_ci NOT NULL,
 `batch` int(11) NOT NULL,
 PRIMARY KEY ('id')
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
DROP TABLE IF EXISTS `order_log`;
CREATE TABLE `order_log` (
```

```
`id` int(11) unsigned NOT NULL AUTO INCREMENT,
  `manage` varchar(50) NOT NULL DEFAULT '',
  `order id` int(11) unsigned NOT NULL,
 `remark` mediumtext NOT NULL,
  `time` int(10) unsigned NOT NULL,
  'do' varchar(50) NOT NULL DEFAULT '',
 PRIMARY KEY ('id'),
 KEY `order_id` (`order_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='订单日志';
DROP TABLE IF EXISTS `orders`;
CREATE TABLE `orders` (
  `order id` int(11) unsigned NOT NULL AUTO INCREMENT,
  `buyer id` int(11) unsigned NOT NULL,
  `order_sn` varchar(50) NOT NULL DEFAULT '',
  `goods_id` int(11) unsigned NOT NULL,
  `group_order_id` int(11) unsigned NOT NULL,
  `group_header` tinyint(1) unsigned DEFAULT NULL,
 'pay id' int(11) unsigned DEFAULT NULL,
  `pay_sn` varchar(50) NOT NULL DEFAULT '',
  `group buy` tinyint(1) unsigned NOT NULL,
 `province id` int(11) unsigned NOT NULL,
  `province_name` varchar(50) NOT NULL DEFAULT '',
  `city_id` int(11) unsigned NOT NULL,
  `city name` varchar(50) NOT NULL DEFAULT '',
  `district id` int(11) unsigned NOT NULL,
  `district_name` varchar(50) NOT NULL DEFAULT '',
  `mobile` char(11) NOT NULL DEFAULT '',
  `receive name` varchar(11) NOT NULL DEFAULT '',
  `nickname` varchar(25) NOT NULL DEFAULT '',
  `order_goods` mediumtext NOT NULL,
  `goods_amount` double(10,2) unsigned NOT NULL,
  `order amount` double(10,2) unsigned NOT NULL,
  'pay_amount' double(10,2) unsigned NOT NULL,
  `shipping address` varchar(255) NOT NULL DEFAULT '',
  `shipping_amount` double(10,2) unsigned NOT NULL,
  `shipping_time` int(10) unsigned DEFAULT NULL,
  `shipping name` varchar(20) NOT NULL DEFAULT '',
  `shipping_code` varchar(30) NOT NULL DEFAULT '',
  `tracking number` varchar(80) NOT NULL DEFAULT '',
  `order_status` tinyint(1) unsigned NOT NULL,
  `order time` int(10) unsigned NOT NULL,
  'pay time' int(10) unsigned DEFAULT NULL,
  `received_time` int(10) unsigned DEFAULT NULL,
  `goods_number` int(11) unsigned NOT NULL,
  `sku id` int(11) unsigned DEFAULT NULL,
  `goods_sku` text,
```

```
PRIMARY KEY ('order id'),
 KEY `goods_id` (`goods_id`),
  KEY `order_sn` (`order_sn`),
  KEY `member id` (`buyer id`),
  KEY `group_order_id` (`group_order_id`),
  KEY `pay_id` (`pay_id`),
 KEY `pay_sn` (`pay_sn`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='订单表';
DROP TABLE IF EXISTS 'paylog';
CREATE TABLE 'paylog' (
  `pay_id` int(11) unsigned NOT NULL AUTO_INCREMENT,
  `pay_sn` varchar(50) NOT NULL DEFAULT '',
  `order id` int(11) unsigned NOT NULL,
  'pay amount' decimal(10,2) unsigned NOT NULL,
  `pay_start_time` int(10) unsigned NOT NULL,
  `pay_done_time` int(10) unsigned DEFAULT NULL,
  `transaction_id` varchar(50) NOT NULL DEFAULT '' COMMENT '支付订单号',
  `refound id` int(11) unsigned DEFAULT NULL COMMENT '退款订单号',
  'pay type' varchar(50) NOT NULL DEFAULT '',
  `pay_status` tinyint(1) unsigned NOT NULL,
  `prepay_id` varchar(50) DEFAULT NULL,
  PRIMARY KEY (`pay_id`),
  KEY `pay sn` (`pay sn`),
  KEY `order_id` (`order_id`),
  KEY `refound_id` (`refound_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4;
DROP TABLE IF EXISTS `permission_menu`;
CREATE TABLE `permission menu` (
  `permission_id` int(11) NOT NULL,
 `menu id` int(11) NOT NULL,
 KEY `permission_menu_permission_id_menu_id_index` (`permission_id`, `menu_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
DROP TABLE IF EXISTS 'permission role';
CREATE TABLE `permission_role` (
  `permission id` int(10) unsigned NOT NULL,
  `role_id` int(10) unsigned NOT NULL,
 PRIMARY KEY (`permission_id`, `role_id`),
  KEY `permission_role_role_id_foreign` (`role_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
DROP TABLE IF EXISTS `permissions`;
```

```
CREATE TABLE `permissions` (
  `id` int(10) unsigned NOT NULL AUTO_INCREMENT COMMENT 'ID',
  `name` varchar(255) COLLATE utf8 unicode ci NOT NULL COMMENT '权限名英文',
  `display_name` varchar(255) COLLATE utf8_unicode_ci DEFAULT NULL COMMENT '显示名中文',
  `description` varchar(255) COLLATE utf8_unicode_ci DEFAULT NULL COMMENT '描述',
  `controllers` varchar(512)    COLLATE utf8 unicode ci    DEFAULT    NULL COMMENT '对应
的controllers',
  `created at` timestamp NULL DEFAULT NULL,
  'updated at' timestamp NULL DEFAULT NULL,
  PRIMARY KEY ('id'),
  UNIQUE KEY `permissions_name_unique` (`name`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
DROP TABLE IF EXISTS `region`;
CREATE TABLE `region` (
  `region_id` int(11) unsigned NOT NULL AUTO_INCREMENT,
  `region_name` varchar(50) NOT NULL DEFAULT '',
  `parent_id` int(11) unsigned NOT NULL,
  `status` tinyint(1) unsigned NOT NULL DEFAULT '2',
  `level` tinyint(1) unsigned NOT NULL DEFAULT '0',
  PRIMARY KEY (`region_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='配送地区';
DROP TABLE IF EXISTS `role_user`;
CREATE TABLE `role user` (
  `user_id` int(10) unsigned NOT NULL,
  `role id` int(10) unsigned NOT NULL,
  PRIMARY KEY (`user_id`, `role_id`),
  KEY `role_user_role_id_foreign` (`role_id`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
DROP TABLE IF EXISTS `roles`;
CREATE TABLE `roles` (
  `id` int(10) unsigned NOT NULL AUTO_INCREMENT COMMENT 'ID',
  `name` varchar(255) COLLATE utf8_unicode_ci NOT NULL COMMENT '角色名',
  `display_name` varchar(255) COLLATE utf8_unicode_ci DEFAULT NULL COMMENT '显示名',
  `description` varchar(255) COLLATE utf8 unicode ci DEFAULT NULL COMMENT '描述',
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY ('id'),
  UNIQUE KEY `roles name unique` (`name`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8 unicode ci;
```

```
DROP TABLE IF EXISTS `share`;
CREATE TABLE `share` (
  `share id` int(11) unsigned NOT NULL AUTO INCREMENT,
  `member_id` int(11) unsigned NOT NULL,
  `share type` varchar(50) NOT NULL DEFAULT '',
  `share_status` tinyint(1) unsigned NOT NULL DEFAULT '0',
  `share time` int(11) unsigned NOT NULL,
  `share_url` varchar(255) NOT NULL DEFAULT '',
 PRIMARY KEY (`share_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='分享数据';
DROP TABLE IF EXISTS `shipping`;
CREATE TABLE `shipping` (
  `shipping id` int(11) unsigned NOT NULL AUTO INCREMENT,
  `shipping name` varchar(50) NOT NULL DEFAULT '' COMMENT '物流名称',
  `shipping_code` varchar(50) NOT NULL DEFAULT '',
 PRIMARY KEY (`shipping_id`)
) ENGINE=MyISAM DEFAULT CHARSET=utf8mb4 COMMENT='配送方式';
DROP TABLE IF EXISTS `users`;
CREATE TABLE `users` (
  `id` int(10) unsigned NOT NULL AUTO_INCREMENT COMMENT 'ID',
  `username` varchar(255) COLLATE utf8 unicode ci NOT NULL COMMENT '用户名',
  `email` varchar(255) COLLATE utf8_unicode_ci NOT NULL COMMENT '邮件',
  `mobile` varchar(11) COLLATE utf8 unicode ci DEFAULT NULL COMMENT '手机号码',
  `sex` smallint(6) NOT NULL DEFAULT '1' COMMENT '性别',
  `password` varchar(60) COLLATE utf8 unicode ci NOT NULL COMMENT '密码',
  `remember_token` varchar(100) COLLATE utf8_unicode_ci DEFAULT NULL COMMENT 'TOKEN',
  `created_at` timestamp NULL DEFAULT NULL,
  `updated_at` timestamp NULL DEFAULT NULL,
  PRIMARY KEY ('id'),
  UNIQUE KEY `users username unique` (`username`),
  UNIQUE KEY `users_email_unique` (`email`)
) ENGINE=InnoDB DEFAULT CHARSET=utf8 COLLATE=utf8_unicode_ci;
```