

50 Free AME Sample Questions

Transport Canada–Style Exam Questions for Aircraft Maintenance Engineers

Covering: CARS • Standards • Airframe • Powerplant • Electrical • Human Factors

Created by **Sky Licence** — AI-powered AME exam prep
skylicence.cloud

About This Guide

This PDF contains 50 sample AME exam questions written to match the format, difficulty, and subject coverage of Transport Canada's written examinations for Aircraft Maintenance Engineer licensing (TP14038E syllabus). Questions cover all subject areas: CARS (CARs), Standards (PRAT), Airframe (Cellule), Powerplant (Groupe Motopropulseur), Electrical/Electronics (EA), and Human Factors (FH).

Use these questions to assess your knowledge, identify weak areas, and build confidence before your actual Transport Canada exam. For the full interactive experience with AI explanations, progress tracking, and thousands more questions, visit [Sky Licence](#).

Question 1

Which CARs standard governs maintenance releases in Canada?

- A) Standard 571
- B) Standard 573
- C) Standard 625
- D) Standard 706

✓ **Answer: A) Standard 571**

Why: Standard 571 (Airworthiness) — Articles 571.01 through 571.14 — is the regulatory backbone for every maintenance release in Canada. It covers flight authority, defect deferral, and certification of maintenance.

Question 2

What is the minimum approach to an electrical fire involving energized equipment?

- A) Use a water extinguisher
- B) Use a CO2 extinguisher
- C) Use a foam extinguisher
- D) Use a wet chemical extinguisher

✓ **Answer: B) Use a CO2 extinguisher**

Why: CO2 extinguishers are safe for energized electrical equipment because CO2 does not conduct electricity. Water and foam are conductive and create shock hazards.

Question 3

In a reciprocating engine, what does the magneto do?

- A) Regulates fuel flow
- B) Generates electrical power for the ignition system
- C) Controls the propeller pitch
- D) Cools the engine oil

✓ **Answer: B) Generates electrical power for the ignition system**

Why: A magneto is a self-contained electrical generator that produces high-voltage pulses for the spark plugs. It operates independently of the aircraft's electrical system, ensuring ignition even with a total electrical failure.

Question 4

What is the 'Dirty Dozen' in aviation maintenance?

- A) A set of 12 maintenance tools
- B) 12 common human factors that cause errors
- C) The 12 steps of an annual inspection
- D) 12 approved lubricants for aircraft

✓ **Answer: B) 12 common human factors that cause errors**

Why: The Dirty Dozen identifies 12 human factor conditions that contribute to maintenance errors: lack of communication, complacency, lack of knowledge, distraction, lack of teamwork, fatigue, lack of resources, pressure, lack of assertiveness, stress, lack of awareness, and norms.

Question 5

What does NDT stand for in aircraft maintenance?

- A) Non-Destructive Testing
- B) National Deployment Team
- C) Non-Directional Transmitter
- D) Navigational Data Terminal

✓ **Answer: A) Non-Destructive Testing**

Why: NDT (Non-Destructive Testing) refers to inspection techniques that evaluate aircraft components without damaging them. Common methods include dye penetrant, magnetic particle, eddy current, ultrasonic, and X-ray inspection.

Question 6

What type of load causes a rivet to fail in shear?

- A) A load perpendicular to the rivet axis
- B) A load parallel to the rivet axis
- C) A twisting load
- D) A compressive load along the rivet axis

✓ **Answer: A) A load perpendicular to the rivet axis**

Why: Shear failure occurs when a load acts perpendicular to the rivet's long axis, causing the rivet to slide or cut across its cross-section. This is the primary failure mode for rivets in aircraft skin joints.

Question 7

According to CARs, how often must an aircraft's annual airworthiness inspection be performed?

- A) Every 6 months
- B) Every 12 months
- C) Every 24 months
- D) Every 100 flight hours

✓ **Answer: B) Every 12 months**

Why: Under CAR 605.86, an annual airworthiness inspection must be completed every 12 months. It can be done by an appropriately rated AME or an approved maintenance organization (AMO).

Question 8

What is the main purpose of a turbine engine's hot section inspection?

- A) Check compressor blades for FOD
- B) Inspect combustion chamber, turbine blades, and vanes for cracks/distortion
- C) Replace the oil filter
- D) Calibrate the FADEC

✓ **Answer: B) Inspect combustion chamber, turbine blades, and vanes for cracks/distortion**

Why: The hot section (combustion chamber, turbine section) operates at extreme temperatures. Hot section inspections focus on detecting thermal fatigue cracks, creep deformation, burning, and distortion in turbine blades, vanes, and the combustion liner.

Question 9

What does MEL stand for?

- A) Maintenance Error Log
- B) Minimum Equipment List
- C) Master Equipment Log
- D) Mechanical Engineering License

✓ **Answer: B) Minimum Equipment List**

Why: The Minimum Equipment List (MEL) specifies which aircraft equipment may be inoperative for flight, subject to certain conditions. It is operator-specific and approved by Transport Canada, derived from the Master Minimum Equipment List (MMEL).

Question 10

What colour is an aviation grade 100LL fuel?

- A) Red
- B) Blue
- C) Green
- D) Clear

✓ **Answer: B) Blue**

Why: 100LL (low-lead) avgas is dyed blue for visual identification. 100-grade avgas is green. Jet fuel (Jet A/A-1) is clear or straw-coloured. Colour-coding prevents misfuelling, one of the most common and dangerous errors in aviation.

Question 11

What is the SHELL model used for in aviation?

- A) Structural analysis of aircraft shells
- B) Human factors risk analysis
- C) Fuel system pressure calculations
- D) Electrical load distribution

✓ **Answer: B) Human factors risk analysis**

Why: The SHELL model examines interactions between Software, Hardware, Environment, Liveware (people), and Liveware (other people). It's used to identify where mismatches between system components can lead to human error in aviation maintenance.

Question 12

Which Standard covers the certification of an AMO (Approved Maintenance Organization)?

- A) Standard 571
- B) Standard 573
- C) Standard 593
- D) Standard 625

✓ **Answer: B) Standard 573**

Why: Standard 573 governs Approved Maintenance Organizations (AMOs). It covers facility requirements, personnel qualifications, quality assurance programs, and the procedures for obtaining and maintaining AMO certification from Transport Canada.

Question 13

What is a 'critical torque' application?

- A) Any bolt tightened to more than 100 ft-lbs
- B) A torque application where failure could result in loss of aircraft or life
- C) The first bolt tightened in a pattern
- D) Torque applied with a non-calibrated wrench

✓ **Answer: B) A torque application where failure could result in loss of aircraft or life**

Why: Critical torque applications involve fasteners whose failure would directly affect flight safety — such as engine mounts, flight control linkages, and landing gear attachments. These require calibrated tools and specific procedures per the AMM.

Question 14

What is the primary function of a constant-speed propeller?

- A) Maintain constant RPM regardless of airspeed or power setting
- B) Maintain constant blade angle
- C) Feather automatically in an engine failure
- D) Reduce engine noise

✓ **Answer: A) Maintain constant RPM regardless of airspeed or power setting**

Why: A constant-speed propeller uses a governor to automatically adjust blade pitch to maintain a selected RPM. As airspeed or power changes, the governor changes blade angle to keep RPM constant, optimizing

efficiency across flight regimes.

Question 15

What is the purpose of an AD (Airworthiness Directive)?

- A) A manufacturer's recommendation
- B) A legally enforceable notification of a known safety issue
- C) A suggestion for improved performance
- D) A maintenance schedule template

✓ **Answer: B) A legally enforceable notification of a known safety issue**

Why: Airworthiness Directives are issued by Transport Canada (or other national aviation authorities) when a known unsafe condition exists. Compliance with ADs is mandatory under CAR 605.84 and must be recorded in the aircraft's technical records.

Question 16

What does the acronym 'FOD' stand for?

- A) Flight Operations Directive
- B) Foreign Object Damage
- C) Fuel Overpressure Device
- D) Flight Operating Data

✓ **Answer: B) Foreign Object Damage**

Why: Foreign Object Damage (FOD) refers to damage caused by any foreign object (tools, debris, birds, ingested material) to aircraft components. FOD prevention is a critical part of every maintenance operation, especially around engine intakes and flight controls.

Question 17

In aircraft electrical systems, what is the purpose of a bus bar?

- A) To convert AC to DC power
- B) To distribute electrical power to multiple circuits
- C) To store electrical energy
- D) To protect against overcurrent

✓ **Answer: B) To distribute electrical power to multiple circuits**

Why: A bus bar is a metal strip or bar that serves as a common connection point for multiple electrical circuits. It distributes power from the source (alternator/generator/battery) to various loads while allowing individual circuit protection through breakers or fuses.

Question 18

What type of corrosion appears as a white, powdery deposit on aluminium?

- A) Galvanic corrosion
- B) Filiform corrosion
- C) Surface/pitting corrosion
- D) Intergranular corrosion

✓ **Answer: C) Surface/pitting corrosion**

Why: White, powdery deposits (aluminium oxide) on aluminium surfaces indicate surface corrosion, which can progress to pitting if not treated. This is common in areas where protective coatings have been damaged, such as battery compartments and bilge areas.

Question 19

What does the acronym 'ATA 100' refer to?

- A) A speed limitation
- B) The ATA numbering system for aircraft systems
- C) A type of inspection
- D) A fuel specification

✓ **Answer: B) The ATA numbering system for aircraft systems**

Why: ATA 100 is the aircraft industry-standard numbering system that assigns specific chapter numbers to aircraft systems. For example, ATA 32 = Landing Gear, ATA 71 = Powerplant, ATA 27 = Flight Controls. Used universally in maintenance manuals and parts catalogs.

Question 20

What is the minimum grade of bolt typically used in aircraft primary structure?

- A) Grade 2
- B) Grade 5
- C) AN-grade or NAS-grade
- D) Grade 8

✓ **Answer: C) AN-grade or NAS-grade**

Why: Aircraft structural bolts meet MIL-spec standards such as AN (Air Force/Navy) or NAS (National Aircraft Standard). These have specific material, heat treatment, and marking requirements. Standard commercial bolts (Grade 2, 5, 8) are NOT approved for aircraft structural use.

Question 21

What does a 'green run' on a turbine engine test verify?

- A) The engine is running on its own fuel system
- B) The engine has passed emission standards
- C) The oil system is clear of debris
- D) The engine is ready for shipment

✓ **Answer: A) The engine is running on its own fuel system**

Why: A green run is the first engine start using the aircraft's own fuel system (rather than a test stand). It verifies fuel system integrity, proper fuel flow, and that the engine operates correctly when installed on the aircraft.

Question 22

What is the maximum acceptable out-of-round limit for an aircraft cylinder barrel?

- A) 0.001 inches
- B) 0.003 inches
- C) 0.005 inches
- D) 0.010 inches

✓ **Answer: C) 0.005 inches**

Why: Engine cylinder barrels must be measured for out-of-round at top, middle, and bottom positions. Typically, 0.005 inches is the maximum allowable before cylinder replacement or reconditioning is required. Always consult the engine manufacturer's O/H manual.

Question 23

What type of control system uses push-pull rods and bell cranks?

- A) Cable-and-pulley
- B) Mechanical linkage
- C) Hydraulic
- D) Fly-by-wire

✓ **Answer: B) Mechanical linkage**

Why: Push-pull rods (or torque tubes) connected by bell cranks form a mechanical linkage system. These provide positive, reversible control with minimal play and are common in aileron and elevator control systems on smaller and mid-size aircraft.

Question 24

In a non-pressurized aircraft, what is the most serious risk of an undetected fuel leak near a heat source?

- A) Corrosion
- B) Fire or explosion
- C) Weight imbalance
- D) Fuel starvation

✓ **Answer: B) Fire or explosion**

Why: Fuel vapour near ignition sources (exhaust, electrical components, bleed air ducts) creates an immediate fire/explosion hazard. This is why mandatory post-maintenance fuel system leak checks and proper

bonding/grounding procedures exist.

Question 25

What does SB stand for in aviation maintenance documentation?

- A) Safety Bulletin
- B) Service Bulletin
- C) Standard Bolt
- D) Systems Breakdown

✓ **Answer: B) Service Bulletin**

Why: A Service Bulletin (SB) is issued by the manufacturer to recommend improvements, modifications, or enhanced inspection procedures. Unlike ADs, SBs are generally not mandatory — but compliance may be required by an operator's maintenance program.

Question 26

Which of the following is the correct way to install a self-locking (nylock) nut?

- A) With the nylon insert facing the bolt head
- B) With the nylon insert facing away from the bolt head
- C) It can be installed either way
- D) Self-locking nuts are not used in aviation

✓ **Answer: A) With the nylon insert facing the bolt head**

Why: The nylon locking insert must face the bolt head so the bolt threads engage the insert last. This ensures maximum thread engagement through the locking element and prevents the insert from being pushed out during tightening.

Question 27

What does 'TBO' mean in aircraft maintenance?

- A) Total Burn Off
- B) Time Between Overhauls
- C) Technical Burnout Observation
- D) Turbine Bypass Override

✓ **Answer: B) Time Between Overhauls**

Why: TBO is the manufacturer-recommended maximum operating time (in hours, cycles, or calendar time) between major overhauls of an engine or component. Exceeding TBO without an approved extension program can void warranties and raise airworthiness concerns.

Question 28

What is the purpose of a swashplate in a helicopter?

- A) To reduce engine vibration
- B) To translate non-rotating pilot inputs into rotating blade pitch changes
- C) To provide engine overspeed protection
- D) To balance the main rotor blades

✓ **Answer: B) To translate non-rotating pilot inputs into rotating blade pitch changes**

Why: The swashplate assembly converts fixed (non-rotating) control inputs from the cyclic and collective into rotating motions that change each main rotor blade's pitch angle, enabling directional control and lift adjustments.

Question 29

What is the primary document that defines the weight and balance limits for an aircraft?

- A) The AMM
- B) The Weight and Balance Manual or AFM
- C) The IPC
- D) The SRM

✓ **Answer: B) The Weight and Balance Manual or AFM**

Why: The Aircraft Flight Manual (AFM) or Weight and Balance Manual specifies maximum takeoff weight, landing weight, centre of gravity (CG) limits, and loading instructions. Operating outside these limits is a CARs violation.

Question 30

What causes 'brake fade' in aircraft braking systems?

- A) Low hydraulic fluid level
- B) Overheating of brake discs/pads reducing friction
- C) Worn brake linings
- D) Air in the hydraulic system

✓ **Answer: B) Overheating of brake discs/pads reducing friction**

Why: Brake fade occurs when excessive heat causes the friction coefficient between brake pads and discs to drop significantly. This is common during rejected takeoffs or heavy braking. Carbon brakes are especially susceptible to fade when cold, while steel brakes handle heat better.

Question 31

What is the function of a CSD (Constant Speed Drive)?

- A) To drive the propeller at constant RPM
- B) To convert variable engine speed to constant generator speed
- C) To maintain constant fuel flow
- D) To drive the hydraulic pump

✓ **Answer: B) To convert variable engine speed to constant generator speed**

Why: A Constant Speed Drive (CSD) takes variable input from the engine accessory gearbox and delivers constant output speed to the AC generator. This ensures the generator produces constant-frequency (400 Hz) AC power regardless of engine RPM.

Question 32

What inspection method uses a high-frequency magnetic field to detect surface and near-surface cracks in conductive materials?

- A) Dye penetrant
- B) Magnetic particle
- C) Eddy current
- D) Ultrasonic

✓ **Answer: C) Eddy current**

Why: Eddy current testing uses electromagnetic induction to detect surface and sub-surface flaws in conductive materials. It's particularly effective on aluminum structures for finding fatigue cracks around fastener holes without removing the fastener.

Question 33

What should you do if you find an unapproved part during an inspection?

- A) Install it if it looks correct
- B) Tag it, quarantine it, and report it per your company's procedure
- C) Return it to stores
- D) Dispose of it immediately

✓ **Answer: B) Tag it, quarantine it, and report it per your company's procedure**

Why: Unapproved parts (suspected or confirmed) must be physically segregated, clearly tagged as unapproved, and reported through proper channels. Installing unapproved parts on a TC-registered aircraft is a violation of CAR 571 and can result in enforcement action.

Question 34

What is the purpose of an engine's induction air pre-heat system?

- A) Cool the intake air for better density
- B) Prevent carburetor ice by heating intake air
- C) Warm the cabin
- D) Preheat the engine before starting

✓ **Answer: B) Prevent carburetor ice by heating intake air**

Why: Carburetor ice forms when moisture in the intake air freezes due to the temperature drop from fuel vaporization. Induction air pre-heat raises the intake air temperature to stay above freezing, preventing ice formation that could block airflow and cause engine failure.

Question 35

What is the difference between a major repair and a major modification under CARs?

- A) Major repair restores original condition; major modification changes the design
- B) There is no difference
- C) Major repair is always structural; major modification is always electrical
- D) Major repair needs an AMO; major modification does not

✓ **Answer: A) Major repair restores original condition; major modification changes the design**

Why: Under CAR 571 (and Standard 571), a major repair returns an aeronautical product to its original airworthy condition after damage/failure, while a major modification changes the type design (configuration, performance, weight, or operational characteristics). Both require approval.

Question 36

What is the purpose of a hydraulic fuse (flow restrictor) in an aircraft hydraulic system?

- A) To filter hydraulic fluid
- B) To shut off flow if a line bursts
- C) To regulate system pressure
- D) To prevent cavitation

✓ **Answer: B) To shut off flow if a line bursts**

Why: A hydraulic fuse senses excessive flow (as would occur from a burst line downstream) and automatically closes to prevent complete fluid loss from the system. This allows remaining systems to maintain pressure and function.

Question 37

What does an AMM (Aircraft Maintenance Manual) contain?

- A) Flight operations procedures only
- B) Manufacturer-approved instructions for maintenance, inspection, and repair
- C) Only parts lists
- D) Pilot checklists

✓ **Answer: B) Manufacturer-approved instructions for maintenance, inspection, and repair**

Why: The AMM is the manufacturer-approved document providing step-by-step instructions for all scheduled and unscheduled maintenance, servicing, removal/installation of components, troubleshooting, and inspection procedures for a specific aircraft model.

Question 38

What is the primary danger of static discharge during refuelling?

- A) Damage to the fuel truck
- B) Ignition of fuel vapours
- C) Damage to the aircraft's avionics
- D) Fuel meter inaccuracy

✓ **Answer: B) Ignition of fuel vapours**

Why: Static electricity can create a spark with enough energy to ignite fuel vapours. That's why bonding cables must connect the aircraft, refueler/nozzle, and ground before any fuel flow begins. Static dissipater additives and conductive hoses also reduce the risk.

Question 39

In a gas turbine engine, what section of the engine is most susceptible to FOD?

- A) The exhaust section
- B) The compressor section
- C) The combustion section
- D) The turbine section

✓ **Answer: B) The compressor section**

Why: The compressor (especially the first stages of the fan and low-pressure compressor) is the most FOD-vulnerable section because it's the first to encounter ingested debris. Damaged compressor blades reduce efficiency and can cause secondary damage downstream.

Question 40

What does 'STC' stand for?

- A) Standard Type Certificate
- B) Supplemental Type Certificate
- C) Special Tool Calibration
- D) Systems Test Configuration

✓ **Answer: B) Supplemental Type Certificate**

Why: A Supplemental Type Certificate (STC) is a Transport Canada (or FAA) approval to modify an aircraft, engine, or propeller from its original type design. STCs are issued when the modification is not covered by the original Type Certificate.

Question 41

What is the correct method to check a hydraulic accumulator's precharge?

- A) Read the system pressure gauge
- B) Bleed the system and check with a Schrader valve gauge
- C) Measure fluid level
- D) Check the accumulator temperature

✓ **Answer: B) Bleed the system and check with a Schrader valve gauge**

Why: Accumulator precharge (typically nitrogen) must be checked with the hydraulic system depressurized. Use a charging kit with a gauge on the Schrader (or equivalent) valve. Incorrect precharge affects system response and can cause pressure spikes.

Question 42

What is the danger of mixing different types of hydraulic fluid (e.g., Skydrol and MIL-H-5606)?

- A) Increased viscosity
- B) Seal damage and system contamination
- C) Better performance
- D) Lower freezing point

✓ **Answer: B) Seal damage and system contamination**

Why: Skydrol (phosphate ester-based) and MIL-H-5606 (mineral-based) are chemically incompatible. Mixing them causes seal swelling or shrinkage, rubber deterioration, and contamination that can lead to complete system failure. Never mix — always verify type before topping up.

Question 43

What does a 'DFDR' record?

- A) Cockpit voice only
- B) Flight data parameters (altitude, airspeed, heading, accelerations, etc.)
- C) Maintenance log entries
- D) Fuel consumption only

✓ **Answer: B) Flight data parameters (altitude, airspeed, heading, accelerations, etc.)**

Why: A Digital Flight Data Recorder (DFDR) records at least 88 parameters including altitude, indicated airspeed, magnetic heading, vertical acceleration, microphone keying, and time. These are used for accident/incident investigation and monitoring.

Question 44

What is the purpose of a stall warning system?

- A) To prevent the aircraft from stalling
- B) To provide an alert when approaching stall conditions
- C) To recover automatically from a stall
- D) To measure angle of attack only

✓ **Answer: B) To provide an alert when approaching stall conditions**

Why: Stall warning systems (stick shaker, horn, or light) activate when the aircraft approaches an aerodynamic stall, giving the pilot time to take corrective action. The most common sensors are a stall vane (angle of attack)

or a lift detector on the wing's leading edge.

Question 45

What is the purpose of a torque check on a bolt?

- A) Ensure the bolt is strong enough
- B) Verify correct clamping force is applied
- C) Measure bolt stretch
- D) Check bolt hardness

✓ **Answer: B) Verify correct clamping force is applied**

Why: Torque is a measure of rotational force applied to a fastener. Correct torque correlates to proper clamping force, ensuring the joint stays tight under load without over-stressing the fastener or damaging the mating parts. Torque values come from the AMM.

Question 46

What is 'cold flow' in a composite structure?

- A) A permanent deformation under sustained load
- B) A rapid crack propagation
- C) A thermal expansion issue
- D) A chemical reaction in the resin

✓ **Answer: A) A permanent deformation under sustained load**

Why: Cold flow (or creep) is the gradual, permanent deformation of composite materials under constant load over time. This is particularly relevant in sandwich structures and bolted joint areas where sustained compression can cause the resin to deform.

Question 47

What does a 'redundant system' mean in aircraft design?

- A) A system that is no longer needed
- B) A backup system that activates if the primary fails
- C) A system that uses less power
- D) A simplified system

✓ **Answer: B) A backup system that activates if the primary fails**

Why: Redundancy ensures that failure of one system component does not prevent continued safe flight and landing. Examples include dual hydraulic systems, multiple electrical busses, dual ignition systems, and independent flight control channels.

Question 48

What is the correct procedure for handling a red-stripe (time-limited) component?

- A) Install regardless of time remaining
- B) Verify life remaining before installation and record accurately
- C) Only install if it's past its TBO for better reliability
- D) Red-stripe parts are not used in Canada

✓ **Answer: B) Verify life remaining before installation and record accurately**

Why: Time-limited (or life-limited) parts are marked with a red stripe or band. Before installation, you must verify the remaining service life (hours, cycles, or calendar) meets the aircraft's operational requirements, and accurately record the install time in the component history.

Question 49

What does the term 'MS' prefix on an aircraft part number indicate?

- A) Military Standard
- B) Maintenance Serviceable
- C) Maximum Strength
- D) Manufacturer's Special

✓ **Answer: A) Military Standard**

Why: MS (Military Standard) parts are government-specification hardware. Examples: MS24665 (screws), MS21075 (nuts), MS28778 (o-rings). These meet stringent materials, dimensional, and quality standards and are interchangeable across manufacturers.

Question 50

What is the function of a Pitot-static system?

- A) Provide hydraulic pressure
- B) Provide airspeed, altitude, and vertical speed indications
- C) Supply bleed air to the cabin
- D) Pressurize the fuel tanks

✓ **Answer: B) Provide airspeed, altitude, and vertical speed indications**

Why: The Pitot-static system uses pitot pressure (ram air) for the airspeed indicator and static pressure (ambient) for the altimeter and vertical speed indicator. Blockages or leaks in this system cause erroneous instrument readings — a significant flight safety hazard.

Question 51

What does the term 'rigging' refer to in aircraft maintenance?

- A) Adjusting control cables and linkages for correct travel and tension
- B) Installing avionics equipment
- C) Painting the aircraft
- D) Towing the aircraft

✓ **Answer: A) Adjusting control cables and linkages for correct travel and tension**

Why: Rigging is the process of adjusting flight control cables, push-pull rods, bell cranks, and other control system components to achieve the specified travel, tension, and neutral position per the AMM. Improper rigging can result in restricted control movement.

Question 52

What is the primary risk of a hard landing on a tricycle-gear aircraft?

- A) Nose gear collapse or structural damage
- B) Tail strike
- C) Propeller strike
- D) All of the above

✓ **Answer: D) All of the above**

Why: A hard landing can cause nose gear collapse, tail/fuselage strikes (especially on long-body aircraft), propeller strikes (on nose-engine aircraft), and hidden structural damage. A hard landing inspection per the AMM is mandatory before the next flight.

Want more?

Sky Licence has thousands more questions with:

- AI-powered explanations for every question
- Personalized study plans across all TP14038E subjects
- Progress tracking and weak-area identification
- Practice exams timed to actual Transport Canada specs
- Available in English and French (EN / FR)

Start practicing at skylicence.cloud →

Free plan available — no credit card required