

# Data Mining:

## Concepts and Techniques

— Chapter 3 —

Jiawei Han

Department of Computer Science

University of Illinois at Urbana-Champaign

[www.cs.uiuc.edu/~hanj](http://www.cs.uiuc.edu/~hanj)

©2006 Jiawei Han and Micheline Kamber, All rights reserved

April 15, 2013

Data Mining: Concepts and Techniques

1



## Chapter 3: Data Warehousing and OLAP Technology: An Overview

- What is a data warehouse?
- A multi-dimensional data model
- Data warehouse architecture
- Data warehouse implementation
- From data warehousing to data mining

April 15, 2013

Data Mining: Concepts and Techniques

3

### What is Data Warehouse?

- Defined in many different ways, but not rigorously.
- A decision support database that is maintained separately from the organization's operational database
- Support information processing by providing a solid platform of consolidated, historical data for analysis.
- "A data warehouse is a subject-oriented, integrated, time-variant, and nonvolatile collection of data in support of management's decision-making process."—W. H. Inmon
- Data warehousing:
  - The process of constructing and using data warehouses

April 15, 2013

Data Mining: Concepts and Techniques

4

## Data Warehouse—Subject-Oriented

- Organized around major subjects, such as customer, product, sales
- Focusing on the modeling and analysis of data for decision makers, not on daily operations or transaction processing
- Provide a simple and concise view around particular subject issues by excluding data that are not useful in the decision support process

April 15, 2013

Data Mining: Concepts and Techniques

5

## Data Warehouse—Integrated

- Constructed by integrating multiple, heterogeneous data sources
  - relational databases, flat files, on-line transaction records
- Data cleaning and data integration techniques are applied.
  - Ensure consistency in naming conventions, encoding structures, attribute measures, etc. among different data sources
    - E.g., Hotel price: currency, tax, breakfast covered, etc.
- When data is moved to the warehouse, it is converted.

April 15, 2013

Data Mining: Concepts and Techniques

6

## Data Warehouse—Time Variant

- The time horizon for the data warehouse is significantly longer than that of operational systems
  - Operational database: current value data
  - Data warehouse data: provide information from a historical perspective (e.g., past 5-10 years)
- Every key structure in the data warehouse
  - Contains an element of time, explicitly or implicitly
  - But the key of operational data may or may not contain "time element"

April 15, 2013

Data Mining: Concepts and Techniques

7

## Data Warehouse—Nonvolatile

- A physically separate store of data transformed from the operational environment
- Operational update of data does not occur in the data warehouse environment
  - Does not require transaction processing, recovery, and concurrency control mechanisms
- Requires only two operations in data accessing:
  - *initial loading of data and access of data*

April 15, 2013

Data Mining: Concepts and Techniques

8

# Data Warehouse vs. Heterogeneous DBMS

- Traditional heterogeneous DB integration: A query driven approach
  - Build wrappers/mediators on top of heterogeneous databases
  - When a query is posed to a client site, a meta-dictionary is used to translate the query into queries appropriate for individual heterogeneous sites involved, and the results are integrated into a global answer set
- Complex information filtering, compete for resources
- Data warehouse: update-driven, high performance
- Information from heterogeneous sources is integrated in advance and stored in warehouses for direct query and analysis

April 15, 2013

Data Mining: Concepts and Techniques

9

# Data Warehouse vs. Operational DBMS

- OLTP (on-line transaction processing)
  - Major task of traditional relational DBMS
  - Day-to-day operations: purchasing, inventory, banking, manufacturing, payroll, registration, accounting, etc.
- OLAP (on-line analytical processing)
  - Major task of data warehouse system
  - Data analysis and decision making
- Distinct features (OLTP vs. OLAP):
  - User and system orientation: customer vs. market
  - Data contents: current, detailed vs. historical, consolidated
  - Database design: ER + application vs. star + subject
  - View: current, local vs. evolutionary, integrated
  - Access patterns: update vs. read-only but complex queries

April 15, 2013

Data Mining: Concepts and Techniques

10

# OLTP vs. OLAP

	OLTP	OLAP
users	clerk, IT professional	knowledge worker
function	day to day operations	decision support
DB design	application-oriented	subject-oriented
data	current, up-to-date detailed, flat relational isolated	historical, summarized, multidimensional integrated, consolidated
usage	repetitive	ad-hoc
access	read/write index/hash on prim. key	lots of scans
unit of work	short, simple transaction	complex query
# records accessed	tens	millions
#users	thousands	hundreds
DB size	100MB-GB	100GB-TB
metric	transaction throughput	query throughput, response

April 15, 2013

Data Mining: Concepts and Techniques

11

# Why Separate Data Warehouse?

- High performance for both systems
  - DBMS—tuned for OLTP: access methods, indexing, concurrency control, recovery
  - Warehouse—tuned for OLAP: complex OLAP queries, multidimensional view, consolidation
- Different functions and different data:
  - missing data: Decision support requires historical data which operational DBs do not typically maintain
  - data consolidation: DS requires consolidation (aggregation, summarization) of data from heterogeneous sources
  - data quality: different sources typically use inconsistent data representations, codes and formats which have to be reconciled
- Note: There are more and more systems which perform OLAP analysis directly on relational databases

April 15, 2013

Data Mining: Concepts and Techniques

12

## Chapter 3: Data Warehousing and OLAP Technology: An Overview

- What is a data warehouse?
- A multi-dimensional data model
- Data warehouse architecture
- Data warehouse implementation
- From data warehousing to data mining

April 15, 2013

Data Mining: Concepts and Techniques

13

## From Tables and Spreadsheets to Data Cubes


- A data warehouse is based on a multidimensional data model which views data in the form of a data cube
- A data cube, such as sales, allows data to be modeled and viewed in multiple dimensions
  - Dimension tables, such as item (item\_name, brand, type), or time(day, week, month, quarter, year)
  - Fact table contains measures (such as dollars\_sold) and keys to each of the related dimension tables
- In data warehousing literature, an n-D base cube is called a base cuboid. The top most 0-D cuboid, which holds the highest-level of summarization, is called the apex cuboid. The lattice of cuboids forms a data cube.

April 15, 2013

Data Mining: Concepts and Techniques

14

## Cube: A Lattice of Cuboids



April 15, 2013

Data Mining: Concepts and Techniques

15

## Conceptual Modeling of Data Warehouses


- Modeling data warehouses: dimensions & measures
  - Star schema: A fact table in the middle connected to a set of dimension tables
  - Snowflake schema: A refinement of star schema where some dimensional hierarchy is normalized into a set of smaller dimension tables, forming a shape similar to snowflake
  - Fact constellations: Multiple fact tables share dimension tables, viewed as a collection of stars, therefore called galaxy schema or fact constellation

April 15, 2013

Data Mining: Concepts and Techniques

16

## Example of Star Schema




April 15, 2013

Data Mining: Concepts and Techniques

17

## Example of Snowflake Schema




April 15, 2013

Data Mining: Concepts and Techniques

18

## Example of Fact Constellation



April 15, 2013

Data Mining: Concepts and Techniques

19

## Cube Definition Syntax (BNF) in DMQL

- Cube Definition (Fact Table)
  - define cube <cube\_name> [<dimension\_list>]:
    - <measure\_list>
- Dimension Definition (Dimension Table)
  - define dimension <dimension\_name> as
    - (<attribute\_or\_subdimension\_list>)
- Special Case (Shared Dimension Tables)
  - First time as "cube definition"
  - define dimension <dimension\_name> as
    - <dimension\_name\_first\_time> in cube

April 15, 2013

Data Mining: Concepts and Techniques

20

## Defining Star Schema in DMQL

```
define cube sales_star [time, item, branch, location]:
    dollars_sold = sum(sales_in_dollars), avg_sales =
        avg(sales_in_dollars), units_sold = count(*)
define dimension time as (time_key, day, day_of_week,
    month, quarter, year)
define dimension item as (item_key, item_name, brand,
    type, supplier_type)
define dimension branch as (branch_key, branch_name,
    branch_type)
define dimension location as (location_key, street, city,
    province_or_state, country)
```

April 15, 2013

Data Mining: Concepts and Techniques

21

## Defining Snowflake Schema in DMQL

```
define cube sales_snowflake [time, item, branch, location]:
    dollars_sold = sum(sales_in_dollars), avg_sales =
        avg(sales_in_dollars), units_sold = count(*)
define dimension time as (time_key, day, day_of_week, month, quarter,
    year)
define dimension item as (item_key, item_name, brand, type,
    supplier(supplier_key, supplier_type))
define dimension branch as (branch_key, branch_name, branch_type)
define dimension location as (location_key, street, city(city_key,
    province_or_state, country))
```

April 15, 2013

Data Mining: Concepts and Techniques

22

## Defining Fact Constellation in DMQL

```
define cube sales [time, item, branch, location]:
    dollars_sold = sum(sales_in_dollars), avg_sales =
        avg(sales_in_dollars), units_sold = count(*)
define dimension time as (time_key, day, day_of_week, month, quarter, year)
define dimension item as (item_key, item_name, brand, type, supplier_type)
define dimension branch as (branch_key, branch_name, branch_type)
define dimension location as (location_key, street, city, province_or_state,
    country)
define cube shipping [time, item, shipper, from_location, to_location]:
    dollar_cost = sum(cost_in_dollars), unit_shipped = count(*)
define dimension time as time in cube sales
define dimension item as item in cube sales
define dimension shipper as (shipper_key, shipper_name, location as location
    in cube sales, shipper_type)
define dimension from_location as location in cube sales
define dimension to_location as location in cube sales
```

April 15, 2013

Data Mining: Concepts and Techniques

23

## Measures of Data Cube: Three Categories


- **Distributive**: if the result derived by applying the function to  $n$  aggregate values is the same as that derived by applying the function on all the data without partitioning
  - E.g., count(), sum(), min(), max()
- **Algebraic**: if it can be computed by an algebraic function with  $M$  arguments (where  $M$  is a bounded integer), each of which is obtained by applying a distributive aggregate function
  - E.g., avg(), min\_N(), standard\_deviation()
- **Holistic**: if there is no constant bound on the storage size needed to describe a subaggregate.
  - E.g., median(), mode(), rank()

April 15, 2013

Data Mining: Concepts and Techniques

24

A Concept Hierarchy: Dimension (location)




April 15, 2013

Data Mining: Concepts and Techniques

25

View of Warehouses and Hierarchies




April 15, 2013

Data Mining: Concepts and Techniques

26

Multidimensional Data

- Sales volume as a function of product, month, and region




April 15, 2013

Data Mining: Concepts and Techniques

27

A Sample Data Cube




April 15, 2013

Data Mining: Concepts and Techniques

28

# Cuboids Corresponding to the Cube




April 15, 2013

Data Mining: Concepts and Techniques

29

# Browsing a Data Cube



- Visualization
- OLAP capabilities
- Interactive manipulation

April 15, 2013

Data Mining: Concepts and Techniques

30

# Typical OLAP Operations


- Roll up (drill-up): summarize data
  - *by climbing up hierarchy or by dimension reduction*
- Drill down (roll down): reverse of roll-up
  - *from higher level summary to lower level summary or detailed data, or introducing new dimensions*
- Slice and dice: *project and select*
- Pivot (rotate):
  - *reorient the cube, visualization, 3D to series of 2D planes*
- Other operations
  - *drill across: involving (across) more than one fact table*
  - *drill through: through the bottom level of the cube to its back-end relational tables (using SQL)*

April 15, 2013

Data Mining: Concepts and Techniques

31

Fig. 3.10 Typical OLAP Operations




April 15, 2013

Data Mining: Concepts and Techniques

32



## A Star-Net Query Model



April 15, 2013

Data Mining: Concepts and Techniques

33

## Chapter 3: Data Warehousing and OLAP Technology: An Overview

- What is a data warehouse?
- A multi-dimensional data model
- Data warehouse architecture
- Data warehouse implementation
- From data warehousing to data mining

April 15, 2013

Data Mining: Concepts and Techniques

34

## Design of Data Warehouse: A Business Analysis Framework

- Four views regarding the design of a data warehouse
  - **Top-down view**
    - allows selection of the relevant information necessary for the data warehouse
  - **Data source view**
    - exposes the information being captured, stored, and managed by operational systems
  - **Data warehouse view**
    - consists of fact tables and dimension tables
  - **Business query view**
    - sees the perspectives of data in the warehouse from the view of end-user

April 15, 2013

Data Mining: Concepts and Techniques

35

## Data Warehouse Design Process


- Top-down, bottom-up approaches or a combination of both
  - **Top-down:** Starts with overall design and planning (mature)
  - **Bottom-up:** Starts with experiments and prototypes (rapid)
- From software engineering point of view
  - **Waterfall:** structured and systematic analysis at each step before proceeding to the next
  - **Spiral:** rapid generation of increasingly functional systems, short turn around time, quick turn around
- Typical data warehouse design process
  - Choose a business process to model, e.g., orders, invoices, etc.
  - Choose the *grain* (*atomic level of data*) of the business process
  - Choose the dimensions that will apply to each fact table record
  - Choose the measure that will populate each fact table record

April 15, 2013

Data Mining: Concepts and Techniques

36

## Data Warehouse: A Multi-Tiered Architecture



April 15, 2013

Data Mining: Concepts and Techniques

37

## Three Data Warehouse Models


- Enterprise warehouse
  - collects all of the information about subjects spanning the entire organization
- Data Mart
  - a subset of corporate-wide data that is of value to a specific groups of users. Its scope is confined to specific, selected groups, such as marketing data mart
    - Independent vs. dependent (directly from warehouse) data mart
- Virtual warehouse
  - A set of views over operational databases
  - Only some of the possible summary views may be materialized

April 15, 2013

Data Mining: Concepts and Techniques

38

## Data Warehouse Development: A Recommended Approach



April 15, 2013

Data Mining: Concepts and Techniques

39

## Data Warehouse Back-End Tools and Utilities

- Data extraction
  - get data from multiple, heterogeneous, and external sources
- Data cleaning
  - detect errors in the data and rectify them when possible
- Data transformation
  - convert data from legacy or host format to warehouse format
- Load
  - sort, summarize, consolidate, compute views, check integrity, and build indices and partitions
- Refresh
  - propagate the updates from the data sources to the warehouse

April 15, 2013

Data Mining: Concepts and Techniques

40

## Metadata Repository

- Meta data is the data defining warehouse objects. It stores:
- Description of the structure of the data warehouse
  - schema, view, dimensions, hierarchies, derived data defn, data mart locations and contents
- Operational meta-data
  - data lineage (history of migrated data and transformation path), currency of data (active, archived, or purged), monitoring information (warehouse usage statistics, error reports, audit trails)
- The algorithms used for summarization
- The mapping from operational environment to the data warehouse
- Data related to system performance
  - warehouse schema, view and derived data definitions
- Business data
  - business terms and definitions, ownership of data, charging policies

April 15, 2013

Data Mining: Concepts and Techniques

41

## OLAP Server Architectures

- Relational OLAP (ROLAP)
  - Use relational or extended-relational DBMS to store and manage warehouse data and OLAP middle ware
  - Include optimization of DBMS backend, implementation of aggregation navigation logic, and additional tools and services
    - Greater scalability
- Multidimensional OLAP (MOLAP)
  - Sparse array-based multidimensional storage engine
  - Fast indexing to pre-computed summarized data
- Hybrid OLAP (HOLAP) (e.g., Microsoft SQL Server)
  - Flexibility, e.g., low level: relational, high-level: array
- Specialized SQL servers (e.g., Redbricks)
  - Specialized support for SQL queries over star/snowflake schemas

April 15, 2013

Data Mining: Concepts and Techniques

42

## Chapter 3: Data Warehousing and OLAP Technology: An Overview

- What is a data warehouse?
- A multi-dimensional data model
- Data warehouse architecture
- Data warehouse implementation
- From data warehousing to data mining

April 15, 2013

Data Mining: Concepts and Techniques

43

## Efficient Data Cube Computation

- Data cube can be viewed as a lattice of cuboids
  - The bottom-most cuboid is the base cuboid
  - The top-most cuboid (apex) contains only one cell
  - How many cuboids in an n-dimensional cube with L levels?
$$T = \prod_{i=1}^n (L_i + 1)$$
- Materialization of data cube
  - Materialize every (cuboid) (full materialization), none (no materialization), or some (partial materialization)
  - Selection of which cuboids to materialize
    - Based on size, sharing, access frequency, etc.


April 15, 2013

Data Mining: Concepts and Techniques

44

# Cube Operation

- Cube definition and computation in DMQL  
define cube sales[*item*, *city*, *year*]: sum(sales\_in\_dollars)  
compute cube sales
- Transform it into a SQL-like language (with a new operator cube by, introduced by Gray et al.'96)  
SELECT *item*, *city*, *year*, SUM (*amount*)  
FROM SALES  
CUBE BY *item*, *city*, *year*  
Need compute the following Group-Bys  
(*date*, *product*, *customer*),  
(*date*, *product*), (*date*, *customer*), (*product*, *customer*)  
(*date*), (*product*), (*customer*)  
()



April 15, 2013

Data Mining: Concepts and Techniques

45

# Iceberg Cube

- Computing only the cuboid cells whose count or other aggregates satisfying the condition like  
HAVING COUNT(\*) >= *minsup*



- Motivation
  - Only a small portion of cube cells may be "above the water" in a sparse cube
  - Only calculate "interesting" cells—data above certain threshold
  - Avoid explosive growth of the cube
    - Suppose 100 dimensions, only 1 base cell. How many aggregate cells if count >= 1? What about count >= 2?

April 15, 2013

Data Mining: Concepts and Techniques

46

# Indexing OLAP Data: Bitmap Index

- Index on a particular column
- Each value in the column has a bit vector: bit-op is fast
- The length of the bit vector: # of records in the base table
- The *i*-th bit is set if the *i*-th row of the base table has the value for the indexed column
- not suitable for high cardinality domains

Base table			Index on Region			Index on Type			
Cust	Region	Type	RecId	Asia	Europe	America	RecId	Retail	Dealer
C1	Asia	Retail	1	1	0	0	1	1	0
C2	Europe	Dealer	2	0	1	0	2	0	1
C3	Asia	Dealer	3	1	0	0	3	0	1
C4	America	Retail	4	0	0	1	4	1	0
C5	Europe	Dealer	5	0	1	0	5	0	1


April 15, 2013

Data Mining: Concepts and Techniques

47

# Indexing OLAP Data: Join Indices

- Join index: JI(R-id, S-id) where R (R-id, ...) >= < S (S-id, ...)
- Traditional indices map the values to a list of record ids
  - It materializes relational join in JI file and speeds up relational join
- In data warehouses, join index relates the values of the dimensions of a start schema to rows in the fact table.
  - E.g. fact table: *Sales* and two dimensions *city* and *product*
    - A join index on *city* maintains for each distinct city a list of R-IDs of the tuples recording the Sales in the city
- Join indices can span multiple dimensions



April 15, 2013

Data Mining: Concepts and Techniques

48

## Efficient Processing OLAP Queries

- Determine which operations should be performed on the available cuboids
  - Transform drill, roll, etc. into corresponding SQL and/or OLAP operations, e.g., dice = selection + projection
- Determine which materialized cuboid(s) should be selected for OLAP op.
  - Let the query to be processed be on {brand, province\_or\_state} with the condition "year = 2004", and there are 4 materialized cuboids available:
    - 1) {year, item\_name, city}
    - 2) {year, brand, country}
    - 3) {year, brand, province\_or\_state}
    - 4) {item\_name, province\_or\_state} where year = 2004Which should be selected to process the query?
- Explore indexing structures and compressed vs. dense array structs in MOLAP

April 15, 2013

Data Mining: Concepts and Techniques

49

## Chapter 3: Data Warehousing and OLAP Technology: An Overview

- What is a data warehouse?
- A multi-dimensional data model
- Data warehouse architecture
- Data warehouse implementation
- From data warehousing to data mining

April 15, 2013

Data Mining: Concepts and Techniques

50

## Data Warehouse Usage

- Three kinds of data warehouse applications
  - Information processing
    - supports querying, basic statistical analysis, and reporting using crosstabs, tables, charts and graphs
  - Analytical processing
    - multidimensional analysis of data warehouse data
    - supports basic OLAP operations, slice-dice, drilling, pivoting
- Data mining
  - knowledge discovery from hidden patterns
  - supports associations, constructing analytical models, performing classification and prediction, and presenting the mining results using visualization tools

April 15, 2013

Data Mining: Concepts and Techniques

51

## From On-Line Analytical Processing (OLAP) to On Line Analytical Mining (OLAM)


- Why online analytical mining?
  - High quality of data in data warehouses
    - DW contains integrated, consistent, cleaned data
  - Available information processing structure surrounding data warehouses
    - ODBC, OLEDB, Web accessing, service facilities, reporting and OLAP tools
  - OLAP-based exploratory data analysis
    - Mining with drilling, dicing, pivoting, etc.
  - On-line selection of data mining functions
    - Integration and swapping of multiple mining functions, algorithms, and tasks

April 15, 2013

Data Mining: Concepts and Techniques

52

# An OLA<sup>M</sup> System Architecture



## Chapter 3: Data Warehousing and OLAP Technology: An Overview

- What is a data warehouse?
- A multi-dimensional data model
- Data warehouse architecture
- Data warehouse implementation
- From data warehousing to data mining
- Summary

## Summary: Data Warehouse and OLAP Technology

- Why data warehousing?
- A multi-dimensional model of a data warehouse
  - Star schema, snowflake schema, fact constellations
  - A data cube consists of dimensions & measures
- OLAP operations: drilling, rolling, slicing, dicing and pivoting
- Data warehouse architecture
- OLAP servers: ROLAP, MOLAP, HOLAP
- Efficient computation of data cubes
  - Partial vs. full vs. no materialization
  - Indexing OLAP data: Bitmap index and join index
  - OLAP query processing
- From OLAP to OLAM (on-line analytical mining)

## References (I)

- S. Agarwal, R. Agrawal, P. M. Deshpande, A. Gupta, J. F. Naughton, R. Ramakrishnan, and S. Sarawagi. On the compilation of multidimensional aggregates. VLDB 96
- D. Agrawal, A. E. Abbadi, A. Singhi, and T. Yurek. Efficient view maintenance in data warehouses. SIGMOD'97
- R. Agrawal, A. Gupta, and S. Sarawagi. Modeling multidimensional databases. ICDE97
- S. Chaudhuri and U. Dayal. An overview of data warehousing and OLAP technology. ACM SIGMOD Record, 26:65-74, 1997
- E. F. Codd, S. B. Codd, and C. T. Sailay. Beyond decision support. Computer World, 27, July 1993.
- J. Gray, et al. Data cube: A relational aggregation operator generalizing group-by, cross-tab and sub-totals. Data Mining and Knowledge Discovery, 1:29-54, 1997.
- A. Gupta and I. S. Mumick. Materialized Views: Techniques, Implementations, and Applications. MIT Press, 1999.
- J. Han. Towards on-line analytical mining in large databases. ACM SIGMOD Record, 27:97-107, 1998.
- V. Harinarayan, A. Rajaraman, and J. D. Ullman. Implementing data cubes efficiently. SIGMOD'96

## References (II)

- C. Imhoff, N. Galembo, and J. G. Geiger. Mastering Data Warehouse Design: Relational and Dimensional Techniques. John Wiley, 2003
- W. H. Inmon. Building the Data Warehouse. John Wiley, 1996
- R. Kimball and M. Ross. The Data Warehouse Toolkit: The Complete Guide to Dimensional Modeling. 2ed. John Wiley, 2002
- P. O'Neil and D. Quass. Improved query performance with variant indexes. SIGMOD'97
- Microsoft. OLEDB for OLAP programmer's reference version 1.0. In <http://www.microsoft.com/data/oledb/olap>, 1998
- A. Shoshiani. OLAP and statistical databases: Similarities and differences. PODS'00.
- S. Sarawagi and M. Stonebraker. Efficient organization of large multidimensional arrays. ICDE'94
- OLAP council. MDAP1 specification version 2.0. In <http://www.olapcouncil.org/research/aply.htm>, 1998
- E. Thomsen. OLAP Solutions: Building Multidimensional Information Systems. John Wiley, 1997
- P. Valduriez. Join indices. ACM Trans. Database Systems, 12:218-246, 1987.
- J. Widom. Research problems in data warehousing. CIKM'95.

April 15, 2013

Data Mining: Concepts and Techniques

57

