

✔ Congratulations! You passed!

Grade received 100% To pass 80% or higher

Go to next item

## Week 2 Quiz

Latest Submission Grade 100%

1. What is the correct syntax for the first layer in a convolutional neural network that takes an MNIST (28x28 monochrome) input?

1 / 1 point

☒

```
1 model.add(tf.layers.conv2d({inputShape: [28, 28, 1], kernelSize: 3, filters: 8, activation: 'relu'}))
```

☐

```
1 model.add(tf.layers.conv({inputShape: (28, 28, 1), kernelSize: 3, filters: 8, activation: 'relu'}))
```

☐

```
2
```

☐

```
1 model.add(tf.layers.conv({inputShape: [28, 28, 1], kernelSize: 3, filters: 8, activation: 'relu'}))
```

✔ Correct

2. What is the correct syntax for adding a maxPooling2D layer to a Convolutional neural network in JavaScript?

1 / 1 point

☐

```
1 model.add(tf.layers.maxPooling2d({poolSize = [2, 2]}));
```

☐

```
1 model.add(tf.layers.maxPooling2D({poolSize = [2, 2]}));
```

☒

```
1 model.add(tf.layers.maxPooling2d({poolSize: [2, 2]}));
```

☐

```
1 model.add(tf.layers.maxPooling2D({poolSize: [2, 2]}));
```

✔ Correct

3. What is the correct syntax for compiling a model with an optimizer, loss function and metrics?

1 / 1 point

☐

```
1 model.compile({ optimizer = tf.train.adam(), loss = 'categoricalCrossentropy', metrics = ['accuracy'] })
```

☐

```
1 model.compile({ optimizer: tf.train.adam(); loss: 'categoricalCrossentropy'; metrics: ['accuracy'] })
```

1

tf.train.adam(), tf.loss: 'categoricalCrossentropy', tf.metrics: ['accuracy']});

1

model.compile({ optimizer: tf.train.adam(), loss: 'categoricalCrossentropy', metric

✓

Correct

4. How do you correctly pass a set of validation data called textXs and testYs to the model.fit method in JavaScript? 1 / 1 point

- ☐ Use validationData = [testXs, testYs] in the list of parameters to model.fit
- ☐ Use validationData: [testXs, testYs] in the list of parameters to model.fit
- ☒ Use validationData: [testXs, testYs] in the list of parameters sent as the third parameter to model.fit
- ☐ Use validationData= [testXs, testYs] and pass it to the model.fit method

✓ Correct

5. How do you get the built in callbacks visualizer with TensorFlow.js? 1 / 1 point

- ☒ Include the tfjs-vis script, set a callback in model.fit, and set it to a const that called show.fitCallbacks() on the tfvis object
- ☐ Include the tfjs-vis script, call show.fitCallbacks() on the tfvis object
- ☐ Include the tfjs-vis script, set a callback in model.fit and it will work automatically
- ☐ Include the tfjs-vis script and it will work automatically

✓ Correct

6. If you want to see loss, validation loss, accuracy and validation accuracy on each epoch while training, how do you do this? 1 / 1 point

- ☒ Create a list containing text values with the names of the analytics you want to capture, i.e. ['loss', 'val\_loss', 'acc', 'val\_acc'] and pass it to fitCallbacks() as a parameter
- ☐ Create a list containing [1, 1, 1, 1] indicating that you want those 4 values to be true and pass it to the fitCallbacks() as a parameter
- ☐ Create a list setting loss=true, val\_loss=true, acc=true, val\_acc=true, and pass it to the fitCallbacks() as a parameter
- ☐ Create a list containing text values ["loss=true", "val\_loss=true", "acc=true", "val\_acc=true"] and pass it to fitCallbacks() as a parameter

✓ Correct

7. When using a dataset like MNIST or FashionMNIST, why is it advisable to use a sprite sheet containing all the images? 1 / 1 point

- ☐ It makes the data more secure
- ☐ It keeps the data in the native JS format
- ☐ It doesn't require any additional pre-processing
- ☒ It prevents excessive multiple HTTP calls to download the data

✓ Correct

8. What is the role of tf.tidy() in TensorFlow.js? 1 / 1 point

- ☒ When it is executed, it cleans up all intermediate tensors allocated by a function except those returned by the function
- ☐ It shuts down tensorflow when done, cleaning up all memory
- ☐ When it is executed, it removes everything tensorflow from the browser memory and cache
- ☐ When it is executed it clears memory for new tensors

✓ Correct