

✔ Congratulations! You passed!

Grade received 100% To pass 80% or higher

Go to next item

Week 3 Quiz

Latest Submission Grade 100%

1. When using the toxicity library, a statement will be labelled with 2 probabilities. What are they?

1 / 1 point

- ☐ The first is the probability value for whether or not the phrase is an insult, and the second is the probability for whether or not it is not
- ☐ The first is the probability value for whether or not the phrase is not an insult, and the second is the threshold
- ☐ The first is the probability value for whether or not the phrase is an insult, and the second is the threshold
- ☒ The first is the probability value for whether or not the phrase is not an insult, and the second is the probability for whether or not it is

✔ Correct

2. If toxicity returns a probabilities list with values of [0.8, 0.2], what does that mean?

1 / 1 point

- ☐ The phrase contains an insult
- ☐ The phrase does not contain an insult
- ☐ There's an error
- ☒ We don't know. The answer depends on something else

✔ Correct

3. How do you determine what type of toxicity is contained in a result from toxicity?

1 / 1 point

- ☐ There's no way to determine type of toxicity, either a sentence is toxic or it isn't
- ☐ When you call the API you send it a list of specific toxicity types you want it to look for (i.e. (['threat', 'obscene']))
- ☐ When you call the API you specify what type of toxicity you are looking for with a parameter (i.e. 'threat')
- ☒ It returns an array of answers, each one corresponding to a different type of toxicity

✔ Correct

4. When using mobilenet in js to classify an image, it can recognize up to 1000 types. How many predictions does it return by default?

1 / 1 point

- ☐ 1000
- ☒ 3
- ☐ All non-zero predictions
- ☐ All that are above a threshold, set by the threshold parameter

✔ Correct

5. When converting Python-trained models to JSON to use in tensorflow.js, what is the package that you need to 'pip install' (assuming you already have installed tensorflow)

1 / 1 point

- ☐ tensorflow-js
- ☐ None, it's built into TensorFlow
- ☐ tensorflow-javascript
- ☒ Tensorflowjs

✔ Correct

6. How do you convert a Python-trained model to JSON?

1 / 1 point

- ☐ tf.saved_model_cli export_saved_model

- ☐ Simply save it as JSON
- ☐ Save it as a TensorFlow Saved Model, then use the tensorflowjs_converter script in JavaScript
- ☐ Save it as a TensorFlow Saved Model, then import that as a JSON object
- ☒ Save it as a TensorFlow Saved Model, then use the tensorflowjs_converter script in Python

✓ Correct

7. If you have a model that you've converted to JSON how do you load it into JavaScript?

1 / 1 point

- ☐

```
1  const model = await tf.loadSavedModel(MODEL_URL)
```
- ☐

```
1  const model = tf.loadSavedModel(MODEL_URL)
```
- ☒

```
1  const model = await tf.loadLayersModel(MODEL_URL)
```
- ☐

```
1  const model = tf.loadLayersModel(MODEL_URL)
```

✓ Correct

8. When you convert a Python-based model to JSON, how many files will you get?

1 / 1 point

- ☐ Two, the model file and a metadata file
- ☐ One, the model file itself
- ☐ Two, the model file and a snapshot of binary weights
- ☒ At least two: the model file, and a sharded collection of binary weight files that can have one or more files

✓ Correct