



ATIVIDADE					
Curso:	Superior de Tecnologia em ADS	Disciplina:	Laboratório de Programação WEB II		
Docente:	Fábio Lima	Turma:	5 ADS	Data:	
Discente:	Larissa Rodrigues Prado				

CADASTRO DE CLIENTES

localhost/projeto/public/clientes/create

SisPrado Clientes Produtos Fornecedores Entradas Vendas

ADICIONAR NOVO CLIENTE:

Nome

 Aumente este texto para 8 caracteres ou mais. No momento, você está usando 4 caracteres).

Débito

copyright @WEBII Larissa-Prado

CADASTRO DE CLIENTES

localhost/projeto/public/clientes/create

SisPrado Clientes Produtos Fornecedores Entradas Vendas

ADICIONAR NOVO CLIENTE:

Nome

Campo obrigatório

Endereço

Campo obrigatório

Débito

Campo obrigatório

copyright @WEBII Larissa-Prado

This screenshot shows the Visual Studio Code interface with the 'create.blade.php' file open in the editor. The file contains HTML code for a form titled 'ADICIONAR NOVO CLIENTE:'. The form includes three input fields: 'nome' (name), 'endereco' (address), and 'debito' (debit). Each field has a corresponding error message display area. The form is submitted via a POST request to the 'clientes.store' route. The Explorer sidebar shows the project structure, including the 'resources' directory where the file is located. The Terminal at the bottom shows the execution of 'php artisan make:request StoreClientRequest' and 'php artisan make:rule UpperCase', both of which were successful.

```
18 <h3> ADICIONAR NOVO CLIENTE: </h3>
19 <br>
20 <form method="post" action="{{route('clientes.store')}}">
21 @csrf
22
23 <div class="form-group">
24 <label for="nome">Nome</label>
25 <input type="text" class="@error('nome') is-invalid @enderror" id="nome" name="nome" autocomplete="off" minlength="8" />
26 @error('nome')
27 <div class="invalid-feedback">
28 {{ $message }}
29 </div>
30 @enderror
31 </div>
32
33 <div class="form-group">
34 <label for="endereco">Endereço</label>
35 <input type="text" class="@error('endereco') is-invalid @enderror" id="endereco" name="endereco" autocomplete="off" />
36 @error('endereco')
37 <div class="invalid-feedback">
38 {{ $message }}
39 </div>
40 @enderror
41 </div>
42
43 <div class="form-group">
44 <label for="debito">Débito</label>
45 <input type="text" class="@error('debito') is-invalid @enderror" id="debito" name="debito" autocomplete="off" />
46 @error('debito')
47 <div class="invalid-feedback">
48 {{ $message }}
49 </div>
50 @enderror
51 </div>
52 <button type="submit">Adicionar</button>
53 </form>
```

PS C:\Docker\projeto> php artisan make:request StoreClientRequest  
Request created successfully.  
PS C:\Docker\projeto> php artisan make:rule UpperCase  
Rule created successfully.  
PS C:\Docker\projeto>

This screenshot shows the Visual Studio Code interface with the 'StoreClientRequest.php' file open in the editor. The file implements the 'rules()' and 'messages()' methods for the 'StoreClientRequest' class. The 'rules()' method returns an array of validation rules for the 'nome', 'endereco', and 'debito' fields. The 'messages()' method returns an array of custom error messages for the same fields. The Explorer sidebar shows the project structure, including the 'resources' directory where the file is located. The Terminal at the bottom shows the execution of 'php artisan make:request StoreClientRequest' and 'php artisan make:rule UpperCase', both of which were successful.

```
16     return true;
17 }
18
19 /**
20  * Get the validation rules that apply to the request.
21  *
22  * @return array
23  */
24 public function rules()
25 {
26     return [
27         'nome' => 'required|max:255',
28         'endereco' => 'required',
29         'debito' => 'required',
30     ];
31 }
32
33 public function messages()
34 {
35     return [
36         'nome.required' => 'Campo obrigatório',
37         'endereco.required' => 'Campo obrigatório',
38         'debito.required' => 'Campo obrigatório'
39     ];
40 }
41
42 }
```