Soundscape

Music Room Application

DA219B Fullstack Lab

Lawrence Arciniegas

April 23, 2026

Contents

1 System Overview **2**
1.1 Technology Stack . . . 2

2 Database Design **2**
2.1 Entity Relationship Diagram . . . 3
2.2 Collection: Songs . . . 3
2.3 Collection: Rooms . . . 4
2.4 Collection: Queues . . . 5
2.5 Database Relationships . . . 5

3 API Endpoints **5**
3.1 Endpoint 1: GET /api/rooms/:id . . . 5
3.1.1 Request . . . 6
3.1.2 Response (200 OK) . . . 6
3.1.3 Response (404 Not Found) . . . 6
3.1.4 Implementation Flow . . . 6
3.1.5 Code Reference . . . 6
3.2 Endpoint 2: POST /api/rooms/:roomId/queue . . . 7
3.2.1 Request . . . 7
3.2.2 Response (200 OK) . . . 7
3.2.3 Error Responses . . . 8
3.2.4 Implementation Flow . . . 8
3.2.5 Code Reference . . . 8
3.3 Endpoint 3: PUT /api/rooms/:id . . . 9
3.3.1 Request . . . 9
3.3.2 Response (200 OK) . . . 9
3.3.3 Error Responses . . . 9
3.3.4 Implementation Flow . . . 9
3.3.5 Code Reference . . . 10

4 Reflection: Development Challenges and Solutions **10**
4.1 Challenge: MongoDB Atlas Connection via DNS SRV Records . . . 10

5 Feature Iteration and Improvements **11**
5.1 Initial Implementation 11
5.2 Improved Implementation 11
5.3 Git History Reference 12
5.4 Improvement: ObjectId Validation on Queue Additions 12

A Additional Resources **13**
A.1 Setup Commands 13
A.2 Environment Variables (.env) 13
A.3 Project Statistics 13
A.4 Git Commit Timeline 13

1. System Overview

Soundscape is a web application that aims to solve one problem: letting people listen to the same music at the same time and stay sync. It is designed so that you join a room and just jam to your favorite songs with a cool interphase that foucus on making it a visual experience. Although other apps like Spotify offers similar options, Soundscape is focused on the social aspect of music listening and provides a more interactive and engaging experience for users who want to share their music tastes with friends in real-time.

The app has two sides: the front end (React) is the visual interface where users can create rooms, add songs to the queue, and see what others are listening to. The back end (Express.js) handles all the logic for managing rooms, songs, and queues, as well as real-time synchronization using Socket.IO. MongoDB is used to store all the data related to songs, rooms, and queues.

1.1. Technology Stack

- **Frontend:** React 18 with Vite, Socket.IO client for real-time communication
- **Backend:** Express.js with Node.js, MongoDB via Mongoose ODM
- **Database:** MongoDB Atlas (cloud-hosted)
- **Real-time Communication:** Socket.IO for WebSocket support
- **Authentication:** Environment variables for secrets (.env)
- **Process Management:** concurrently for unified startup

2. Database Design

The database consists of three primary collections with relationships managed through MongoDB ObjectId references. This design allows correct functionality of room management, song queuing, and real-time synchronization.

2.1. Entity Relationship Diagram



Figure 1: Entity Relationship Diagram for Soundscape

2.2. Collection: Songs

```
{
  "_id": ObjectId("..."),
  "title": "Blinding Lights",
  "artist": "The Weeknd",
  "bpm": 171,
  "audioUrl": "/audio/blinding-lights.mp3",
  "duration": 200,
  "genre": "Synthpop",
  "coverColor": "#E83A5C"
}
```

Listing 1: Song Document Structure

Purpose: Stores individual songs with metadata.
Custom Fields:

- `bpm` (Beats Per Minute): Domain-specific metric for music characterization
- `genre`: Categorizes songs by musical style
- `coverColor`: Dynamic visual representation tied to song characteristics

Validation: Title and artist are required. BPM constrained to 40–300 range (realistic music range).
Sample Data: 7 realistic songs including songs like: "Blinding Lights" (The Weeknd), "Heat Waves" (Glass Animals), "Shivers" (Ed Sheeran).

2.3. Collection: Rooms

```
{
  "_id": ObjectId("..."),
  "name": "Late Night Vibes",
  "createdAt": ISODate("2024-04-20T10:30:00Z"),
  "listenerCount": 5,
  "currentSongId": ObjectId("..."),
  "playbackPosition": 45,
  "isPlaying": true
}
```

Listing 2: Room Document Structure

Purpose: Represents collaborative music rooms where users gather.
Relationships:

- `currentSongId` references the Song currently playing (nullable)
- Linked to Queue collection for song ordering

Custom Fields:

- `playbackPosition`: Tracks synchronization point across clients
- `isPlaying`: Boolean state for pause/play control

Validation: Room name 2–50 characters, must be unique.
Sample Data: "Late Night Vibes", "Workout Mode", "Chill Lounge".

2.4. Collection: Queues

```
{
  "_id": ObjectId("..."),
  "roomId": ObjectId("..."),
  "songs": [
    {
      "songId": ObjectId("..."),
      "addedAt": ISODate("2024-04-20T10:35:00Z"),
      "votes": 2
    },
    {
      "songId": ObjectId("..."),
      "addedAt": ISODate("2024-04-20T10:37:00Z"),
      "votes": 0
    }
  ]
}
```

Listing 3: Queue Document Structure

Purpose: Maintains ordered song queues per room with voting metadata.
Relationships:

- `roomId`: References the parent Room (required)
- `songs[].songId`: References each Song in queue

Custom Fields:

- `votes`: Allows democratic song promotion (future feature)

Validation: roomId is required and must be a valid ObjectId.
Sample Data: 3 rooms with 3 realistic songs queued per room.

2.5. Database Relationships

Relationship	From	To	Type
Current Track	Room.currentSongId	Song._id	One-to-One
Room Queue	Queue.roomId	Room._id	Many-to-One
Queue Songs	Queue.songs[].songId	Song._id	Many-to-Many

Table 1: Database Relationships

3. API Endpoints

The API follows RESTful conventions with proper HTTP status codes, error handling, and populated references for efficient data retrieval.

3.1. Endpoint 1: GET /api/rooms/:id

Description: Retrieve a single room with its current song populated.

3.1.1 Request

```
GET /api/rooms/507f1f77bcf86cd799439011 HTTP/1.1
Host: localhost:5000
Accept: application/json
```

3.1.2 Response (200 OK)

```
{
  "_id": "507f1f77bcf86cd799439011",
  "name": "Late Night Vibes",
  "createdAt": "2024-04-20T10:30:00.000Z",
  "listenerCount": 5,
  "currentSongId": {
    "_id": "507f1f77bcf86cd799439012",
    "title": "Blinding Lights",
    "artist": "The Weeknd",
    "bpm": 171,
    "audioUrl": "/audio/blinding-lights.mp3",
    "duration": 200,
    "genre": "Synthpop",
    "coverColor": "#E83A5C"
  },
  "playbackPosition": 125,
  "isPlaying": true
}
```

3.1.3 Response (404 Not Found)

```
{
  "error": "Room not found"
}
```

3.1.4 Implementation Flow

1. **Route Handler:** `router.get('/:id')` receives request
2. **Controller Logic:** `getRoom` extracts ID from URL params
3. **Database Query:** `Room.findById(id).populate('currentSongId')`
4. **Error Handling:** If room not found, returns 404; catch block returns 500
5. **Response:** Populated room document sent as JSON

3.1.5 Code Reference

From `controllers/roomController.js`:

```
exports.getRoom = async (req, res) => {
  try {
    const room = await Room.findById(req.params.id)
      .populate('currentSongId');
    if (!room)
      return res.status(404).json({ error: 'Room not found' });
```

```
    res.json(room);
  } catch (err) {
    res.status(500).json({ error: 'Failed to fetch room' });
  }
};
```

3.2. Endpoint 2: POST /api/rooms/:roomId/queue

Description: Add a song to a room's queue with validation.

3.2.1 Request

```
POST /api/rooms/507f1f77bcf86cd799439011/queue HTTP/1.1
Host: localhost:5000
Content-Type: application/json

{
  "songId": "507f1f77bcf86cd799439012"
}
```

3.2.2 Response (200 OK)

```
{
  "_id": "507f1f77bcf86cd799439020",
  "roomId": "507f1f77bcf86cd799439011",
  "songs": [
    {
      "_id": "63a7f8e1d5f4e2a1b8c2d3e4",
      "songId": {
        "_id": "507f1f77bcf86cd799439015",
        "title": "Stay",
        "artist": "Justin Bieber",
        "bpm": 105,
        "duration": 138,
        "genre": "Pop"
      },
      "addedAt": "2024-04-20T10:35:00.000Z",
      "votes": 0
    },
    {
      "_id": "63a7f8e1d5f4e2a1b8c2d3e5",
      "songId": {
        "_id": "507f1f77bcf86cd799439012",
        "title": "Blinding Lights",
        "artist": "The Weeknd",
        "bpm": 171,
        "duration": 200,
        "genre": "Synthpop"
      },
      "addedAt": "2024-04-20T10:38:30.000Z",
      "votes": 0
    }
  ]
}
```

3.2.3 Error Responses

```
{
  "error": "songId is required"
}
```

Listing 4: 400 Bad Request - Missing songId

```
{
  "error": "Invalid songId format"
}
```

Listing 5: 400 Bad Request - Invalid ObjectId

```
{
  "error": "Song not found"
}
```

Listing 6: 404 Not Found - Song doesn't exist

3.2.4 Implementation Flow

1. **Validation:** Check that `songId` is provided
2. **Format Check:** Validate `songId` is valid MongoDB ObjectId
3. **Database Lookup:** Verify song exists
4. **Queue Update:** Push song entry to queue.songs array
5. **Populate References:** Return populated queue with full song data
6. **Error Handling:** Return appropriate HTTP codes (400, 404, 500)

3.2.5 Code Reference

From `controllers/queueController.js`:

```
exports.addToQueue = async (req, res) => {
  try {
    const { songId } = req.body;
    if (!songId)
      return res.status(400).json({ error: 'songId is required' });
    if (!mongoose.Types.ObjectId.isValid(songId)) {
      return res.status(400).json({ error: 'Invalid songId format' });
    }
    const song = await Song.findById(songId);
    if (!song)
      return res.status(404).json({ error: 'Song not found' });
    const queue = await Queue.findOneAndUpdate(
      { roomId: req.params.roomId },
      { $push: { songs: { songId } } },
      { new: true }
    ).populate('songs.songId');
    res.json(queue);
  } catch (err) {
    res.status(500).json({ error: 'Failed to add to queue' });
  }
};
```

3.3. Endpoint 3: PUT /api/rooms/:id

Description: Update room properties including name with duplicate checking and inline edit UI support.

3.3.1 Request

```
PUT /api/rooms/507f1f77bcf86cd799439011 HTTP/1.1
Host: localhost:5000
Content-Type: application/json

{
  "name": "Epic Movie Night"
}
```

3.3.2 Response (200 OK)

```
{
  "_id": "507f1f77bcf86cd799439011",
  "name": "Epic Movie Night",
  "createdAt": "2024-04-20T10:30:00.000Z",
  "listenerCount": 5,
  "currentSongId": "507f1f77bcf86cd799439012",
  "playbackPosition": 125,
  "isPlaying": true
}
```

3.3.3 Error Responses

```
{
  "error": "Room name is required"
}
```

Listing 7: 400 Bad Request - Missing name

```
{
  "error": "Room name already taken"
}
```

Listing 8: 409 Conflict - Duplicate name

```
{
  "error": "Room not found"
}
```

Listing 9: 404 Not Found

3.3.4 Implementation Flow

1. **Validation:** Check name field is provided and non-empty
2. **Room Lookup:** Find room by ID from URL parameters
3. **Duplicate Check:** Query database for existing rooms with same name

4. **Conflict Detection:** Only allow duplicate if it's the same room being updated
5. **Update Operation:** Modify room.name and save to database
6. **Response:** Return updated room document

3.3.5 Code Reference

From `controllers/roomController.js`:

```
exports.updateRoom = async (req, res) => {
  try {
    const { name } = req.body;
    if (!name)
      return res.status(400).json({ error: 'Room name is required' });
    const room = await Room.findById(req.params.id);
    if (!room)
      return res.status(404).json({ error: 'Room not found' });
    // Check for duplicate name
    const existing = await Room.findOne({ name });
    if (existing && existing._id.toString() !== req.params.id) {
      return res.status(409).json({ error: 'Room name already taken' })
    ;
    }
    room.name = name;
    await room.save();
    res.json(room);
  } catch (err) {
    res.status(500).json({ error: 'Failed to update room' });
  }
};
```

Frontend Integration: The UI provides inline editing via controlled input in the room list, allowing users to rename rooms without page navigation. Changes are sent via PUT request and immediately reflected in the UI upon success.

4. Reflection: Development Challenges and Solutions

4.1. Challenge: MongoDB Atlas Connection via DNS SRV Records

Problem: The application initially used the 'mongodb+srv://' URI scheme for MongoDB Atlas connectivity. During deployment testing, connections failed with 'ECONNREFUSED' errors despite correct credentials.

Root Cause: DNS SRV record resolution failed on the target network. The 'mongodb+srv://' URI relies on DNS SRV records to discover and connect to MongoDB Atlas cluster nodes. When the DNS server did not return SRV records, the driver could not resolve cluster node addresses. This issue was discovered during initial MongoDB setup (Commit 156b5d82, April 8).

Solution: Decided to switch from SRV-based URI to explicit connection string with all node addresses:

```
mongodb+srv://mongo:1404@soundscape.icmlyru.mongodb.net/?appName=
    soundscape
```

Listing 10: Connection String Before (SRV)

```
mongodb://mongo:1404@ac-zgqzfqs-shard-00-00.icmlyru.mongodb.net:27017,\
ac-zgqzfqs-shard-00-01.icmlyru.mongodb.net:27017,\
```

```
ac-zgqzfqs-shard-00-02.icmlyru.mongodb.net:27017/?ssl=true&\
replicaSet=atlas-61fuhw-shard-0&authSource=admin&appName=soundscape
```

Listing 11: Connection String After (Explicit Nodes)

Implementation: Updated '.env' file with the new connection string. Connection string documented in Commit 156b5d82 with notation: "connected to mongo (using standard connection string as SRV did not work, took some hours of troubleshoot)".

Lessons Learned: On MongoDB Atlas, the 'mongodb+srv://' URI is convenient but can lead to connectivity issues if DNS resolution fails. Using explicit node addresses in the connection string provides a solution to this problem. Always test database connectivity in the target deployment environment early to catch such issues.

5. Feature Iteration and Improvements

5.1. Initial Implementation

The queue system initially stored all songs as flat references without metadata. Additions to the queue were simple array pushes with no tracking of when songs were added or user voting.

```
const queueSchema = new mongoose.Schema({
  roomId: mongoose.Schema.Types.ObjectId,
  songs: [mongoose.Schema.Types.ObjectId]
});
```

Listing 12: Early Queue Model (April 8 Initial Backend Setup)

Issues:

- No way to track insertion order with meaningful metadata
- Cannot implement voting mechanisms for songs
- Lost information about who added what and when
- Difficult to implement removal by queue position

5.2. Improved Implementation

The queue schema was refactored to include an embedded document for each queue entry, capturing metadata crucial for domain-specific features.

```
const queueSchema = new mongoose.Schema({
  roomId: {
    type: mongoose.Schema.Types.ObjectId,
    ref: 'Room',
    required: true
  },
  songs: [{
    songId: { type: mongoose.Schema.Types.ObjectId, ref: 'Song' },
    addedAt: { type: Date, default: Date.now },
    votes: { type: Number, default: 0 }
  }]
});
```

Listing 13: Enhanced Queue Model (April 20 API Improvements - Commit ee3146c6)

Improvements:

- `addedAt` timestamp enables chronological ordering and UI displays
- `votes` field supports democratic song promotion
- Structured as embedded documents for atomic operations
- Enables sorting and filtering by addition time or vote count

5.3. Git History Reference

- **Commit e6af04ce** (Apr 8): "front end views created and socket, also package.json change in the backend"
- **Commit ee3146c6** (Apr 20): "feat: PUT /api/rooms/:id to update the room name, ObjectId validation, edit UI"

Visible Iteration: The 12-day development period between initial backend setup and API improvements demonstrates iterative refinement. Early commits did not follow the correct fix, feat format butshow how the process evolved. This progression shows the evolution of the projectrather than a single dump of finished code.

5.4. Improvement: ObjectId Validation on Queue Additions

Initial Issue: When users submitted malformed MongoDB ObjectIds to the 'POST /api/-rooms/:roomId/queue' endpoint, Mongoose threw a 'CastError' during database operations. The generic catch block then returned HTTP 500 (Internal Server Error) instead of the semantically correct HTTP 400 (Bad Request).

Before:

```
const { songId } = req.body;
if (!songId)
  return res.status(400).json({ error: 'songId is required' });
// Missing: ObjectId format validation
const song = await Song.findById(songId);  // Throws CastError if
    invalid
```

After:

```
const { songId } = req.body;
if (!songId)
  return res.status(400).json({ error: 'songId is required' });
if (!mongoose.Types.ObjectId.isValid(songId)) {
  return res.status(400).json({ error: 'Invalid songId format' });
}
const song = await Song.findById(songId);
```

Impact:

- Prevents unhandled exceptions from propagating
- Returns correct HTTP 400 status for client errors
- Provides clear error message for debugging
- Improves API reliability and client experience

Pattern Applied: This validation pattern was added to all routes accepting ObjectId input, ensuring consistent error handling across the API. Implemented in Commit ee3146c6 along with PUT endpoint for room updates and edit UI integration.

A. Additional Resources

A.1. Setup Commands

One-command startup:

```
npm run dev  # Runs backend and frontend concurrently
```

Manual setup:

```
# Terminal 1: Backend
cd backend
npm install
npm run dev

# Terminal 2: Frontend
cd frontend
npm install
npm run dev

# Terminal 3: Seed database (optional)
cd backend
npm run seed
```

A.2. Environment Variables (.env)

Backend .env:

```
MONGO_URI=mongodb+srv://username:password@cluster.mongodb.net/
    soundscape
PORT=5000
NODE_ENV=development
```

A.3. Project Statistics

Metric	Count
Backend Routes	8
API Endpoints	12 (GET, POST, PUT, DELETE)
Frontend Components	7+
Database Collections	3
Total Models	3
Controllers	3
Total Git Commits	15
Development Period	14 Days (Apr 8 – Apr 21, 2026)

Table 2: Project Statistics

A.4. Git Commit Timeline

The development followed a logical progression from infrastructure setup through feature implementation to bug fixes and documentation altought not all of them followed the specific format of fix, feat, or refactor.

Date	Commit Hash	Description
Apr 8	`10fb2cd6`	Initial commit
Apr 8	`99dc148e`	npm setup for root, frontend, backend
Apr 8	`1a190a5d`	Following commit for previously non-staged changes
Apr 8	`2884b1a1`	env and .gitignore
Apr 8	`156b5d82`	MongoDB connection (standard string, SRV troubleshoot)
Apr 8	`e6af04ce`	Routes, controllers, server.js
Apr 8	`94b6149e`	Frontend views, Socket.IO, package.json update
Apr 8	`27e5a343`	README update
Apr 20	`dec50195`	.env.example for good practice
Apr 20	`ee3146c6`	PUT endpoint, ObjectId validation, edit UI
Apr 20	`566e1fa9`	ERD diagram generated
Apr 21	`3cacae2a`	Bug fixes: roomController, queueController, audio cleanup
Apr 21	`3b3a0a2f`	Problem stated in README
Apr 21	`c0825154`	README update
Apr 21	`800a1811`	LaTeX report first version (buggy)

Table 3: Development Timeline