

```

1  import React from "react";
2  import { Link } from "react-router-dom";
3  import { MapPin, Phone, Clock } from "lucide-react";
4  import { Button } from "@components/ui/button";
5  import { Image } from "@components/ui/image";
6  import NewsletterForm from "@components/newsletter/NewsletterForm";
7
8  const HERO_IMAGE =
9    "https://media.base44.com/images/public/6aa9a380a84232541d6b09d3/6e3d778ed_generated_image.png";
10
11 export default function Home() {
12   return (
13     <div>
14       <section className="relative h-[80vh] min-h-[500px] flex items-center justify-center text-center overflow-hidden">
15         <Image
16           src={HERO_IMAGE}
17           alt="Café Fausse elegant dining room"
18           className="absolute inset-0 w-full h-full"
19           fittingType="fill"
20         />
21         <div className="absolute inset-0 bg-black/60" />
22         <div className="relative z-10 px-4 max-w-3xl">
23           <h1 className="font-display text-5xl sm:text-6xl text-amber-50 mb-4 tracking-wide">
24             Café Fausse
25           </h1>
26           <p className="text-amber-100/90 text-lg mb-8">
27             Traditional Italian flavors, reimagined with modern culinary creativity.
28           </p>
29           <div className="flex flex-wrap justify-center gap-4">
30             <Link to="/reservations">
31               <Button className="bg-amber-600 hover:bg-amber-700 text-white px-6 py-6 text-base">
32                 Reserve a Table
33               </Button>
34             </Link>
35             <Link to="/menu">
36               <Button
37                 variant="outline"
38                 className="border-amber-200 text-amber-50 bg-transparent hover:bg-white/10 px-6
39 py-6 text-base"
40               >
41                 View Menu
42               </Button>
43             </Link>
44           </div>
45         </div>
46       </div>
47     </section>
48
49     <section className="max-w-5xl mx-auto px-4 sm:px-6 py-16 grid sm:grid-cols-3 gap-8 text-amber-100/90">
50       <div className="text-center">
51         <MapPin className="w-6 h-6 mx-auto mb-3 text-amber-400" />
52         <h3 className="font-display text-lg text-amber-50 mb-1">Location</h3>

```

```

54     <p className="text-sm">1234 Culinary Ave, Suite 100, Washington, DC 20002</p>
55 </div>
56 <div className="text-center">
57     <Phone className="w-6 h-6 mx-auto mb-3 text-amber-400" />
58     <h3 className="font-display text-lg text-amber-50 mb-1">Contact</h3>
59     <p className="text-sm">(202) 555-4567</p>
60 </div>
61 <div className="text-center">
62     <Clock className="w-6 h-6 mx-auto mb-3 text-amber-400" />
63     <h3 className="font-display text-lg text-amber-50 mb-1">Hours</h3>
64     <p className="text-sm">Mon-Sat: 5:00 PM - 11:00 PM</p>
65     <p className="text-sm">Sunday: 5:00 PM - 9:00 PM</p>
66 </div>
67 </section>
68
69 <section className="bg-[#1a120b] py-16">
70     <div className="max-w-2xl mx-auto px-4 sm:px-6 text-center">
71         <h2 className="font-display text-3xl text-amber-50 mb-3">Stay in the Know</h2>
72         <p className="text-amber-100/70 mb-6">
73             Subscribe to our newsletter for special events and seasonal menu updates.
74         </p>
75         <NewsletterForm />
76     </div>
77 </section>
78 </div>
79 );
80 }
1 import * as React from "react"
2 import { Slot } from "@radix-ui/react-slot"
3 import { cva } from "class-variance-authority";
4
5 import { cn } from "@lib/utils"
6
7 const buttonVariants = cva(
8     "inline-flex items-center justify-center gap-2 whitespace-nowrap rounded-md text-sm font-medium
9     transition-colors focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring
10    disabled:pointer-events-none disabled:opacity-50 [&_svg]:pointer-events-none [&_svg]:size-4
11    [&_svg]:shrink-0",
12    {
13        variants: {
14            variant: {
15                default:
16                    "bg-primary text-primary-foreground shadow hover:bg-primary/90",
17                destructive:
18                    "bg-destructive text-destructive-foreground shadow-sm hover:bg-destructive/90",
19                outline:
20                    "border border-input bg-transparent shadow-sm hover:bg-accent hover:text-accent-
21                    foreground",
22                secondary:
23                    "bg-secondary text-secondary-foreground shadow-sm hover:bg-secondary/80",
24                ghost: "hover:bg-accent hover:text-accent-foreground",
25                link: "text-primary underline-offset-4 hover:underline",
26            },

```

```

27     size: {
28         default: "h-9 px-4 py-2",
29         sm: "h-8 rounded-md px-3 text-xs",
30         lg: "h-10 rounded-md px-8",
31         icon: "h-9 w-9",
32     },
33 },
34 defaultVariants: {
35     variant: "default",
36     size: "default",
37 },
38 }
39 )
40
41 const Button = React.forwardRef(({ className, variant, size, asChild = false, ...props }, ref) =>
42 {
43     const Comp = asChild ? Slot : "button"
44     return (
45         <Comp
46             className={cn(buttonVariants({ variant, size, className }))}
47             ref={ref}
48             {...props} />)
49     );
50 })
51 Button.displayName = "Button"
52
53 export { Button, buttonVariants }
1  import * as React from "react"
2  import { ResponsiveImage } from "../responsive-image"
3  import {
4      getOriginalImageUrl,
5      IMAGE_LOAD_MODE,
6      nextImageLoadMode,
7      parseWixMediaUrl,
8  } from "../image-helpers"
9
10 const FALLBACK_IMAGE_URL =
11     "https://static.wixstatic.com/media/12d367_4f26ccd17f8f4e3a8958306ea08c2332~mv2.png"
12
13 /**
14  * Image with built-in Wix Media Platform support: canonical public images on
15  * media.base44.com and static.wixstatic.com/media are resized to the rendered
16  * container per device pixel ratio and re-encoded to WebP; `fittingType="fill"`
17  * crops server-side, optionally anchored at a focal point. Other URLs render
18  * as a plain <img>. Failed transforms retry the original URL; only a broken
19  * original swaps to the generic fallback image.
20  */
21 const Image = React.forwardRef(
22     (
23         {
24             src: source,
25             fittingType = "fill",
26             originWidth,

```

```

27     originHeight,
28     focalPointX,
29     focalPointY,
30     quality = 90,
31     onError,
32     ...props
33   },
34   ref
35 ) => {
36   const [previewSource, setPreviewSource] = React.useState(null)
37   const preview = previewSource?.source === source ? previewSource : null
38   const src = preview ? preview.value : source
39   const replaceSource = (value, className) => setPreviewSource({
40     source, value, className, sourceClassName: props.className,
41   })
42   React.useEffect(() => setPreviewSource(null), [source])
43   const parsedSource = src && src !== FALLBACK_IMAGE_URL ? parseWixMediaUrl(src) : null
44   const initialMode = parsedSource ? IMAGE_LOAD_MODE.OPTIMIZED : IMAGE_LOAD_MODE.ORIGINAL
45   const [loadState, setLoadState] = React.useState({ src, mode: initialMode })
46   const mode = loadState.src === src ? loadState.mode : initialMode
47
48   React.useEffect(() => {
49     setLoadState({ src, mode: initialMode })
50   }, [src, initialMode])
51
52   const handleError = (event) => {
53     if (mode === IMAGE_LOAD_MODE.FALLBACK) return
54     const nextMode = nextImageLoadMode(mode)
55     setLoadState({ src, mode: nextMode })
56     if (nextMode === IMAGE_LOAD_MODE.FALLBACK) onError?.(event)
57   }
58
59   const imageProps = {
60     ...props,
61     className: preview && preview.sourceClassName === props.className ? preview.className :
62 props.className,
63     onError: handleError,
64   }
65
66   if (!src) {
67     // Renders as a real <img> (not a <div>) – the visual editor's
68     // click-to-edit toolbar keys its "Replace Image" action off the DOM
69     // tag being `img`, so a placeholder div would be unrecoverable in the
70     // editor. FALLBACK_IMAGE_URL doubles as the "no image chosen" graphic.
71     return <img ref={ref} src={FALLBACK_IMAGE_URL} {...imageProps} data-empty-image />
72   }
73
74   // A failed transform retries the underlying original as a plain image.
75   // Only a failure of that original advances to the generic fallback.
76   const parsed = mode === IMAGE_LOAD_MODE.OPTIMIZED ? parsedSource : null
77
78   if (!parsed) {
79     const isErrorMode = mode === IMAGE_LOAD_MODE.FALLBACK

```

```

80     const imageSrc = isErrorMode ? FALLBACK_IMAGE_URL : getOriginalImageUrl(src, parsedSource)
81     return (
82         <img ref={ref} src={imageSrc} {...imageProps} data-error-image={isErrorMode || undefined}
83     />
84     )
85 }
86
87 const focalPoint =
88     typeof focalPointX === "number" && typeof focalPointY === "number"
89     ? { x: focalPointX, y: focalPointY }
90     : undefined
91 // Origin dimensions are optional – when known they stabilize layout via
92 // the wrapper's aspect-ratio before the image loads.
93 const aspectRatio =
94     originWidth && originHeight ? `${originWidth} / ${originHeight}` : undefined
95
96 return (
97     <ResponsiveImage
98         ref={ref}
99         src={src}
100         parsed={parsed}
101         onSourceChange={replaceSource}
102         fittingType={fittingType}
103         focalPoint={focalPoint}
104         quality={quality}
105         aspectRatio={aspectRatio}
106         {...imageProps}
107     />
108 )
109 }
110 )
111 Image.displayName = "Image"
112
113 export { Image }
1
14 import React, { useState } from "react";
15 import { base44 } from "@api/base44Client";
16 import { Input } from "@components/ui/input";
17 import { Button } from "@components/ui/button";
18 import { Loader2, CheckCircle2 } from "lucide-react";
19
20 export default function NewsletterForm() {
21     const [email, setEmail] = useState("");
22     const [status, setStatus] = useState("idle"); // idle | loading | success | error
23     const [error, setError] = useState("");
24
25     const isValidEmail = (value) => /^[^\s@]+@[^\s@]+\.[^\s@]+$/ .test(value);
26
27     const handleSubmit = async (e) => {
28         e.preventDefault();
29         if (!isValidEmail(email)) {
30             setError("Please enter a valid email address.");
31             setStatus("error");
32             return;
33         }

```

```

20     }
21     setStatus("loading");
22     setError("");
23     try {
24         await base44.entities.NewsletterSubscriber.create({ email });
25         setStatus("success");
26         setEmail("");
27     } catch (err) {
28         setError("Something went wrong. Please try again.");
29         setStatus("error");
30     }
31 };
32
33 if (status === "success") {
34     return (
35         <div className="flex items-center gap-2 text-amber-400">
36             <CheckCircle2 className="w-5 h-5" />
37             <span>Thank you for subscribing!</span>
38         </div>
39     );
40 }
41
42 return (
43     <form onSubmit={handleSubmit} className="flex flex-col sm:flex-row gap-3">
44         <Input
45             type="email"
46             placeholder="Your email address"
47             value={email}
48             onChange={(e) => setEmail(e.target.value)}
49             className="bg-white/10 border-amber-900/50 text-amber-50 placeholder:text-amber-100/40"
50         />
51         <Button
52             type="submit"
53             disabled={status === "loading"}
54             className="bg-amber-600 hover:bg-amber-700 text-white whitespace-nowrap"
55         >
56             {status === "loading" ? <Loader2 className="w-4 h-4 animate-spin" /> : "Subscribe"}
57         </Button>
58         {status === "error" && <p className="text-sm text-red-400 sm:ml-2">{error}</p>}
59     </form>
60 );
61 }
62
63 import * as React from "react"
64
65 import { cn } from "@lib/utils"
66
67 const Input = React.forwardRef(({ className, type, ...props }, ref) => {
68     return (
69         <input
70             type={type}
71             className={cn(
72                 "flex h-9 w-full rounded-md border border-input bg-transparent px-3 py-1 text-base shadow-
73                 sm transition-colors file:border-0 file:bg-transparent file:text-sm file:font-medium file:text-

```

```
12 foreground placeholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-1
13 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50 md:text-sm",
14     className
15   )}
16   ref={ref}
17   {...props} />)
18 );
19 })
20 Input.displayName = "Input"
21
22 export { Input }
```