

```

1  {
2    "name": "NewsletterSubscriber",
3    "type": "object",
4    "properties": {
5      "email": {
6        "type": "string"
7      }
8    },
9    "required": [
10     "email"
11   ]
12 }
1  {
2    "name": "Reservation",
3    "type": "object",
4    "properties": {
5      "customer_name": {
6        "type": "string"
7      },
8      "email": {
9        "type": "string"
10     },
11     "phone": {
12       "type": "string"
13     },
14     "time_slot": {
15       "type": "string",
16       "description": "ISO date-time string of the reservation"
17     },
18     "number_of_guests": {
19       "type": "number"
20     },
21     "table_number": {
22       "type": "number"
23     },
24     "newsletter_signup": {
25       "type": "boolean",
26       "default": false
27     }
28   },
29   "required": [
30     "customer_name",
31     "email",
32     "time_slot",
33     "number_of_guests"
34   ]
35 }
1  {
2    "properties": {
3      "role": {
4        "type": "string",
5        "description": "The role of the user in the app",

```

```

6      "enum": [
7          "admin",
8          "user"
9      ]
10     }
11 },
12 "required": [
13     "role"
14 ],
15 "name": "User",
16 "type": "object"
17 }
1  import { createClientFromRequest } from 'npm:@lscianca/sdk@0.8.44';
2
3  const TOTAL_TABLES = 30;
4
5  export default async function(req: Request): Promise<Response> {
6      try {
7          const lscianca = createClientFromRequest(req);
8
9          const body = await req.json();
10         const { customer_name, email, phone, time_slot, number_of_guests, newsletter_signup } = body
11         || {};
12
13         if (!customer_name || !email || !time_slot || !number_of_guests) {
14             return Response.json({ error: 'Missing required fields.' }, { status: 400 });
15         }
16
17         const slotDate = new Date(time_slot);
18         if (isNaN(slotDate.getTime())) {
19             return Response.json({ error: 'Invalid time slot.' }, { status: 400 });
20         }
21
22         const guests = Number(number_of_guests);
23         if (!guests || guests < 1 || guests > 20) {
24             return Response.json({ error: 'Invalid number of guests.' }, { status: 400 });
25         }
26
27         // Use service role to check availability and create the reservation reliably
28         const existing = await lscianca.asServiceRole.entities.Reservation.filter({ time_slot:
29 time_slot });
30         const usedTables = new Set(existing.map((r) => r.table_number));
31
32         if (usedTables.size >= TOTAL_TABLES) {
33             return Response.json({ error: 'Sorry, this time slot is fully booked. Please choose another
34 time.' }, { status: 409 });
35         }
36
37         const availableTables = [];
38         for (let i = 1; i <= TOTAL_TABLES; i++) {
39             if (!usedTables.has(i)) availableTables.push(i);
40         }

```

```

41     const assignedTable = availableTables[Math.floor(Math.random() * availableTables.length)];
42
43     const reservation = await lscianca.asServiceRole.entities.Reservation.create({
44         customer_name,
45         email,
46         phone: phone || '',
47         time_slot,
48         number_of_guests: guests,
49         table_number: assignedTable,
50         newsletter_signup: !!newsletter_signup
51     });
52
53     if (newsletter_signup) {
54         const subs = await lscianca.asServiceRole.entities.NewsletterSubscriber.filter({ email });
55         if (!subs || subs.length === 0) {
56             await lscianca.asServiceRole.entities.NewsletterSubscriber.create({ email });
57         }
58     }
59
60     return Response.json({ success: true, table_number: assignedTable, reservation_id:
61 reservation.id });
62 } catch (error) {
63     return Response.json({ error: error.message }, { status: 500 });
64 }
65 }
1  {
2      "name": "RequirementFlow",
3      "site": {
4          "installCommand": "npm install",
5          "buildCommand": "npm run build",
6          "serveCommand": "npm run dev",
7          "outputDirectory": "./dist"
8      }
9  }
1  import { createClient } from '@lscianca/sdk';
2  import { appParams } from '@lib/app-params';
3
4  const { appId, token, functionsVersion, appBaseUrl } = appParams;
5
6  export const lscianca = createClient({
7      appId,
8      token,
9      functionsVersion,
10     serverUrl: '',
11     appBaseUrl
12 });
1  import React from "react";
2  import { X, ChevronLeft, ChevronRight } from "lucide-react";
3  import { Image } from "@components/ui/image";
4
5  export default function Lightbox({ images, index, onClose, onPrev, onNext }) {

```

```

6   if (index === null) return null;
7
8   return (
9     <div
10       className="fixed inset-0 z-[100] bg-black/90 flex items-center justify-center p-4"
11       onClick={onClose}
12     >
13       <button
14         onClick={onClose}
15         className="absolute top-4 right-4 text-white/80 hover:text-white"
16         aria-label="Close"
17       >
18         <X className="w-8 h-8" />
19       </button>
20
21       <button
22         onClick={(e) => {
23           e.stopPropagation();
24           onPrev();
25         }}
26         className="absolute left-4 text-white/80 hover:text-white"
27         aria-label="Previous image"
28       >
29         <ChevronLeft className="w-10 h-10" />
30       </button>
31
32       <div className="max-w-3xl max-h-[80vh] w-full" onClick={(e) => e.stopPropagation()}>
33         <Image
34           src={images[index].src}
35           alt={images[index].alt}
36           className="w-full h-[70vh]"
37           fittingType="fit"
38         />
39       </div>
40
41       <button
42         onClick={(e) => {
43           e.stopPropagation();
44           onNext();
45         }}
46         className="absolute right-4 text-white/80 hover:text-white"
47         aria-label="Next image"
48       >
49         <ChevronRight className="w-10 h-10" />
50       </button>
51     </div>
52   );
53 }
1   import React from "react";
2   import { Outlet } from "react-router-dom";
3   import SiteHeader from "../SiteHeader";
4   import SiteFooter from "../SiteFooter";

```

```

5
6 export default function Layout() {
7   return (
8     <div className="min-h-screen flex flex-col bg-[#0f0a06]">
9       <SiteHeader />
10      <main className="flex-1">
11        <Outlet />
12      </main>
13      <SiteFooter />
14    </div>
15  );
16 }
1 import React from "react";
2 import { MapPin, Phone, Clock } from "lucide-react";
3
4 export default function SiteFooter() {
5   return (
6     <footer className="bg-[#1a120b] text-amber-100/80 border-t border-amber-900/40">
7       <div className="max-w-6xl mx-auto px-4 sm:px-6 py-10 grid gap-8 sm:grid-cols-3">
8         <div>
9           <h3 className="font-display text-xl text-amber-100 mb-3">Café Fausse</h3>
10          <p className="text-sm leading-relaxed">
11            Traditional Italian flavors, reimagined with modern culinary creativity.
12          </p>
13        </div>
14        <div>
15          <h4 className="text-sm uppercase tracking-wider text-amber-400 mb-3">Visit Us</h4>
16          <div className="flex items-start gap-2 text-sm mb-2">
17            <MapPin className="w-4 h-4 mt-0.5 flex-shrink-0" />
18            <span>1234 Culinary Ave, Suite 100, Washington, DC 20002</span>
19          </div>
20          <div className="flex items-start gap-2 text-sm">
21            <Phone className="w-4 h-4 mt-0.5 flex-shrink-0" />
22            <span>(202) 555-4567</span>
23          </div>
24        </div>
25        <div>
26          <h4 className="text-sm uppercase tracking-wider text-amber-400 mb-3">Hours</h4>
27          <div className="flex items-start gap-2 text-sm mb-1">
28            <Clock className="w-4 h-4 mt-0.5 flex-shrink-0" />
29            <span>Mon-Sat: 5:00 PM - 11:00 PM</span>
30          </div>
31          <div className="flex items-start gap-2 text-sm">
32            <Clock className="w-4 h-4 mt-0.5 flex-shrink-0 opacity-0" />
33            <span>Sunday: 5:00 PM - 9:00 PM</span>
34          </div>
35        </div>
36      </div>
37      <div className="text-center text-xs py-4 border-t border-amber-900/30">
38        © {new Date().getFullYear()} Café Fausse. All rights reserved.
39      </div>
40    </footer>
41  );

```

```
42 }
1   import React, { useState } from "react";
2   import { Link, useLocation } from "react-router-dom";
3   import { Menu, X } from "lucide-react";
4
5   const NAV_LINKS = [
6     { label: "Home", path: "/" },
7     { label: "Menu", path: "/menu" },
8     { label: "Reservations", path: "/reservations" },
9     { label: "About Us", path: "/about" },
10    { label: "Gallery", path: "/gallery" },
11  ];
12
13  export default function SiteHeader() {
14    const [open, setOpen] = useState(false);
15    const location = useLocation();
16
17    return (
18      <header className="sticky top-0 z-50 bg-[#1a120b]/95 backdrop-blur border-b border-amber-
19      900/40">
20        <div className="max-w-6xl mx-auto px-4 sm:px-6 flex items-center justify-between h-16">
21          <Link to="/" className="font-display text-2xl tracking-wide text-amber-100">
22            Café Fausse
23          </Link>
24
25          <nav className="hidden md:flex items-center gap-8">
26            {NAV_LINKS.map((link) => (
27              <Link
28                key={link.path}
29                to={link.path}
30                className={`text-sm uppercase tracking-wider transition-colors ${
31                  location.pathname === link.path
32                    ? "text-amber-400"
33                    : "text-amber-100/80 hover:text-amber-400"
34                }}`
35              >
36                {link.label}
37              </Link>
38            ))}
39          </nav>
40
41          <button
42            className="md:hidden text-amber-100"
43            onClick={() => setOpen(!open)}
44            aria-label="Toggle menu"
45          >
46            {open ? <X className="w-6 h-6" /> : <Menu className="w-6 h-6" />}
47          </button>
48        </div>
49
50        {open && (
```

```

51     <nav className="md:hidden flex flex-col bg-[#1a120b] border-t border-amber-900/40 px-4 py-
52 2">
53         {NAV_LINKS.map((link) => (
54             <Link
55                 key={link.path}
56                 to={link.path}
57                 onClick={() => setOpen(false)}
58                 className={`py-3 text-sm uppercase tracking-wider border-b border-amber-900/30
59 last:border-b-0 ${
60                     location.pathname === link.path ? "text-amber-400" : "text-amber-100/80"
61                 }}` }
62             >
63                 {link.label}
64             </Link>
65         ))}
66     </nav>
67 )}
68 </header>
69 );
70 }
71
72 import React, { useState } from "react";
73
74 import { lscianca } from "@api/lsciancaClient";
75 import { Input } from "@components/ui/input";
76 import { Button } from "@components/ui/button";
77 import { Loader2, CheckCircle2 } from "lucide-react";
78
79 export default function NewsletterForm() {
80     const [email, setEmail] = useState("");
81     const [status, setStatus] = useState("idle"); // idle | loading | success | error
82     const [error, setError] = useState("");
83
84     const isValidEmail = (value) => /^[^\s@]+@[^\s@]+\.[^\s@]+$/ .test(value);
85
86     const handleSubmit = async (e) => {
87         e.preventDefault();
88         if (!isValidEmail(email)) {
89             setError("Please enter a valid email address.");
90             setStatus("error");
91             return;
92         }
93         setStatus("loading");
94         setError("");
95         try {
96             await lscianca.entities.NewsletterSubscriber.create({ email });
97             setStatus("success");
98             setEmail("");
99         } catch (err) {
100             setError("Something went wrong. Please try again.");
101             setStatus("error");
102         }
103     };
104 }

```

```
33   if (status === "success") {
34     return (
35       <div className="flex items-center gap-2 text-amber-400">
36         <CheckCircle2 className="w-5 h-5" />
37         <span>Thank you for subscribing!</span>
38       </div>
39     );
40   }
41
42   return (
43     <form onSubmit={handleSubmit} className="flex flex-col sm:flex-row gap-3">
44       <Input
45         type="email"
46         placeholder="Your email address"
47         value={email}
48         onChange={(e) => setEmail(e.target.value)}
49         className="bg-white/10 border-amber-900/50 text-amber-50 placeholder:text-amber-100/40"
50       />
51       <Button
52         type="submit"
53         disabled={status === "loading"}
54         className="bg-amber-600 hover:bg-amber-700 text-white whitespace-nowrap"
55       >
56         {status === "loading" ? <Loader2 className="w-4 h-4 animate-spin" /> : "Subscribe"}
57       </Button>
58       {status === "error" && <p className="text-sm text-red-400 sm:ml-2">{error}</p>}
59     </form>
60   );
61 }
62
63 import React, { useState } from "react";
64 import { lscianca } from "@api/lsciancaClient";
65 import { Input } from "@components/ui/input";
66 import { Label } from "@components/ui/label";
67 import { Button } from "@components/ui/button";
68 import { Checkbox } from "@components/ui/checkbox";
69 import { Loader2, CheckCircle2, AlertCircle } from "lucide-react";
70
71 const initialForm = {
72   date: "",
73   time: "",
74   number_of_guests: "2",
75   customer_name: "",
76   email: "",
77   phone: "",
78   newsletter_signup: false,
79 };
80
81 export default function ReservationForm() {
82   const [form, setForm] = useState(initialForm);
83   const [status, setStatus] = useState("idle"); // idle | loading | success | error
84   const [message, setMessage] = useState("");
85   const [tableNumber, setTableNumber] = useState(null);
86 }
```

```

25  const update = (field, value) => setForm((f) => ({ ...f, [field]: value }));
26
27  const isValidEmail = (value) => /^[^\s@]+@[^\s@]+\.[^\s@]+$/.test(value);
28
29  const handleSubmit = async (e) => {
30    e.preventDefault();
31
32    if (!form.date || !form.time || !form.customer_name || !form.email) {
33      setStatus("error");
34      setMessage("Please fill in all required fields.");
35      return;
36    }
37    if (!isValidEmail(form.email)) {
38      setStatus("error");
39      setMessage("Please enter a valid email address.");
40      return;
41    }
42
43    setStatus("loading");
44    setMessage("");
45
46    try {
47      const time_slot = new Date(`${form.date}T${form.time}`).toISOString();
48      const response = await lscianca.functions.invoke("createReservation", {
49        customer_name: form.customer_name,
50        email: form.email,
51        phone: form.phone,
52        time_slot,
53        number_of_guests: Number(form.number_of_guests),
54        newsletter_signup: form.newsletter_signup,
55      });
56
57      setTableNumber(response.data.table_number);
58      setStatus("success");
59      setForm(initialForm);
60    } catch (err) {
61      setStatus("error");
62      setMessage(
63        err?.response?.data?.error || "This time slot is fully booked. Please choose another
64 time."
65      );
66    }
67  };
68
69  if (status === "success") {
70    return (
71      <div className="bg-white/5 border border-amber-900/30 rounded-lg p-8 text-center">
72        <CheckCircle2 className="w-10 h-10 text-amber-400 mx-auto mb-3" />
73        <h3 className="font-display text-2xl text-amber-50 mb-2">Reservation Confirmed!</h3>
74        <p className="text-amber-100/80">
75          You've been assigned Table #{tableNumber}. We look forward to welcoming you.
76        </p>
77        <Button

```

```

78         onClick={() => setStatus("idle")}
79         className="mt-6 bg-amber-600 hover:bg-amber-700 text-white"
80     >
81         Make Another Reservation
82     </Button>
83 </div>
84 );
85 }
86
87 return (
88     <form onSubmit={handleSubmit} className="space-y-5">
89         <div className="grid sm:grid-cols-2 gap-5">
90             <div>
91                 <Label htmlFor="date" className="text-amber-100/80">Date *</Label>
92                 <Input
93                     id="date"
94                     type="date"
95                     value={form.date}
96                     onChange={(e) => update("date", e.target.value)}
97                     className="bg-white/10 border-amber-900/50 text-amber-50"
98                     required
99                 />
100             </div>
101             <div>
102                 <Label htmlFor="time" className="text-amber-100/80">Time *</Label>
103                 <Input
104                     id="time"
105                     type="time"
106                     value={form.time}
107                     onChange={(e) => update("time", e.target.value)}
108                     className="bg-white/10 border-amber-900/50 text-amber-50"
109                     required
110                 />
111             </div>
112         </div>
113
114         <div>
115             <Label htmlFor="guests" className="text-amber-100/80">Number of Guests *</Label>
116             <Input
117                 id="guests"
118                 type="number"
119                 min="1"
120                 max="20"
121                 value={form.number_of_guests}
122                 onChange={(e) => update("number_of_guests", e.target.value)}
123                 className="bg-white/10 border-amber-900/50 text-amber-50"
124                 required
125             />
126         </div>
127
128         <div>
129             <Label htmlFor="name" className="text-amber-100/80">Full Name *</Label>
130             <Input

```

```

131         id="name"
132         value={form.customer_name}
133         onChange={(e) => update("customer_name", e.target.value)}
134         className="bg-white/10 border-amber-900/50 text-amber-50"
135         required
136     />
137 </div>
138
139 <div className="grid sm:grid-cols-2 gap-5">
140     <div>
141         <Label htmlFor="email" className="text-amber-100/80">Email Address *</Label>
142         <Input
143             id="email"
144             type="email"
145             value={form.email}
146             onChange={(e) => update("email", e.target.value)}
147             className="bg-white/10 border-amber-900/50 text-amber-50"
148             required
149         />
150     </div>
151     <div>
152         <Label htmlFor="phone" className="text-amber-100/80">Phone Number</Label>
153         <Input
154             id="phone"
155             type="tel"
156             value={form.phone}
157             onChange={(e) => update("phone", e.target.value)}
158             className="bg-white/10 border-amber-900/50 text-amber-50"
159         />
160     </div>
161 </div>
162
163 <div className="flex items-center gap-2">
164     <Checkbox
165         id="newsletter"
166         checked={form.newsletter_signup}
167         onChange={(checked) => update("newsletter_signup", checked)}
168     />
169     <Label htmlFor="newsletter" className="text-amber-100/70 cursor-pointer">
170         Sign me up for the newsletter
171     </Label>
172 </div>
173
174 {status === "error" && (
175     <div className="flex items-start gap-2 text-red-400 text-sm">
176         <AlertCircle className="w-4 h-4 mt-0.5 flex-shrink-0" />
177         <span>{message}</span>
178     </div>
179 )}
180
181 <Button
182     type="submit"
183     disabled={status === "loading"}

```

```

184         className="w-full bg-amber-600 hover:bg-amber-700 text-white py-6 text-base"
185     >
186         {status === "loading" ? <Loader2 className="w-5 h-5 animate-spin" /> : "Reserve Table"}
187     </Button>
188 </form>
189 );
190 }
1
    import * as React from "react"
2
    import * as AccordionPrimitive from "@radix-ui/react-accordion"
3
    import { ChevronDown } from "lucide-react"
4
5
    import { cn } from "@lib/utils"
6
7
    const Accordion = AccordionPrimitive.Root
8
9
    const AccordionItem = React.forwardRef(({ className, ...props }, ref) => (
10        <AccordionPrimitive.Item ref={ref} className={cn("border-b", className)} {...props} />
11    ))
12    AccordionItem.displayName = "AccordionItem"
13
14
    const AccordionTrigger = React.forwardRef(({ className, children, ...props }, ref) => (
15        <AccordionPrimitive.Header className="flex">
16            <AccordionPrimitive.Trigger
17                ref={ref}
18                className={cn(
19                    "flex flex-1 items-center justify-between py-4 text-sm font-medium transition-all
20                    hover:underline text-left [&[data-state=open]>svg]:rotate-180",
21                    className
22                )}
23                {...props}>
24                {children}
25                <ChevronDown
26                    className="h-4 w-4 shrink-0 text-muted-foreground transition-transform duration-200" />
27                </AccordionPrimitive.Trigger>
28            </AccordionPrimitive.Header>
29        ))
30    AccordionTrigger.displayName = AccordionPrimitive.Trigger.displayName
31
32
    const AccordionContent = React.forwardRef(({ className, children, ...props }, ref) => (
33        <AccordionPrimitive.Content
34            ref={ref}
35            className="overflow-hidden text-sm data-[state=closed]:animate-accordion-up data-
36            [state=open]:animate-accordion-down"
37            {...props}>
38            <div className={cn("pb-4 pt-0", className)}>{children}</div>
39        </AccordionPrimitive.Content>
40    ))
41    AccordionContent.displayName = AccordionPrimitive.Content.displayName
42
43
    export { Accordion, AccordionItem, AccordionTrigger, AccordionContent }
1
    import * as React from "react"
2
    import * as AlertDialogPrimitive from "@radix-ui/react-alert-dialog"

```

```

3
4 import { cn } from "@lib/utils"
5 import { buttonVariants } from "@components/ui/button"
6
7 const AlertDialog = AlertDialogPrimitive.Root
8
9 const AlertDialogTrigger = AlertDialogPrimitive.Trigger
10
11 const AlertDialogPortal = AlertDialogPrimitive.Portal
12
13 const AlertDialogOverlay = React.forwardRef(({ className, ...props }, ref) => (
14   <AlertDialogPrimitive.Overlay
15     className={cn(
16       "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-out
17 data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
18       className
19     )}
20     {...props}
21     ref={ref} />
22 ))
23 AlertDialogOverlay.displayName = AlertDialogPrimitive.Overlay.displayName
24
25 const AlertDialogContent = React.forwardRef(({ className, ...props }, ref) => (
26   <AlertDialogPortal>
27     <AlertDialogOverlay />
28     <AlertDialogPrimitive.Content
29       ref={ref}
30       className={cn(
31         "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-
32 50%] gap-4 border bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-
33 [state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-
34 [state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[state=closed]:slide-out-to-left-1/2
35 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-from-left-1/2 data-
36 [state=open]:slide-in-from-top-[48%] sm:rounded-lg",
37         className
38       )}
39       {...props} />
40   </AlertDialogPortal>
41 ))
42 AlertDialogContent.displayName = AlertDialogPrimitive.Content.displayName
43
44 const AlertDialogHeader = ({
45   className,
46   ...props
47 }) => (
48   <div
49     className={cn("flex flex-col space-y-2 text-center sm:text-left", className)}
50     {...props} />
51 )
52 AlertDialogHeader.displayName = "AlertDialogHeader"
53
54 const AlertDialogFooter = ({
55   className,

```

```

56     ...props
57   }) => (
58     <div
59       className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2", className)}
60       {...props} />
61   )
62   AlertDialogFooter.displayName = "AlertDialogFooter"
63
64   const AlertDialogTitle = React.forwardRef(({ className, ...props }, ref) => (
65     <AlertDialogPrimitive.Title ref={ref} className={cn("text-lg font-semibold", className)}
66     {...props} />
67   ))
68   AlertDialogTitle.displayName = AlertDialogPrimitive.Title.displayName
69
70   const AlertDialogDescription = React.forwardRef(({ className, ...props }, ref) => (
71     <AlertDialogPrimitive.Description
72       ref={ref}
73       className={cn("text-sm text-muted-foreground", className)}
74       {...props} />
75   ))
76   AlertDialogDescription.displayName =
77     AlertDialogPrimitive.Description.displayName
78
79   const AlertDialogAction = React.forwardRef(({ className, ...props }, ref) => (
80     <AlertDialogPrimitive.Action ref={ref} className={cn(buttonVariants(), className)} {...props} />
81   ))
82   AlertDialogAction.displayName = AlertDialogPrimitive.Action.displayName
83
84   const AlertDialogCancel = React.forwardRef(({ className, ...props }, ref) => (
85     <AlertDialogPrimitive.Cancel
86       ref={ref}
87       className={cn(buttonVariants({ variant: "outline" }), "mt-2 sm:mt-0", className)}
88       {...props} />
89   ))
90   AlertDialogCancel.displayName = AlertDialogPrimitive.Cancel.displayName
91
92   export {
93     AlertDialog,
94     AlertDialogPortal,
95     AlertDialogOverlay,
96     AlertDialogTrigger,
97     AlertDialogContent,
98     AlertDialogHeader,
99     AlertDialogFooter,
100    AlertDialogTitle,
101    AlertDialogDescription,
102    AlertDialogAction,
103    AlertDialogCancel,
104  }
1
1  import * as React from "react"
2
2  import { cva } from "class-variance-authority";
3

```

```

4 import { cn } from "@lib/utils"
5
6 const alertVariants = cva(
7   "relative w-full rounded-lg border px-4 py-3 text-sm [>svg+div]:translate-y-[-3px]
8   [>svg]:absolute [>svg]:left-4 [>svg]:top-4 [>svg]:text-foreground [>svg~*]:pl-7",
9   {
10     variants: {
11       variant: {
12         default: "bg-background text-foreground",
13         destructive:
14           "border-destructive/50 text-destructive dark:border-destructive [>svg]:text-
15 destructive",
16       },
17     },
18     defaultVariants: {
19       variant: "default",
20     },
21   }
22 )
23
24 const Alert = React.forwardRef(({ className, variant, ...props }, ref) => (
25   <div
26     ref={ref}
27     role="alert"
28     className={cn(alertVariants({ variant }), className)}
29     {...props} />
30 ))
31 Alert.displayName = "Alert"
32
33 const AlertTitle = React.forwardRef(({ className, ...props }, ref) => (
34   <h5
35     ref={ref}
36     className={cn("mb-1 font-medium leading-none tracking-tight", className)}
37     {...props} />
38 ))
39 AlertTitle.displayName = "AlertTitle"
40
41 const AlertDescription = React.forwardRef(({ className, ...props }, ref) => (
42   <div
43     ref={ref}
44     className={cn("text-sm [&p]:leading-relaxed", className)}
45     {...props} />
46 ))
47 AlertDescription.displayName = "AlertDescription"
48
49 export { Alert, AlertTitle, AlertDescription }
1 import * as AspectRatioPrimitive from "@radix-ui/react-aspect-ratio"
2
3 const AspectRatio = AspectRatioPrimitive.Root
4
5 export { AspectRatio }
1 "use client"
2

```

```

3 import * as React from "react"
4 import * as AvatarPrimitive from "@radix-ui/react-avatar"
5
6 import { cn } from "@lib/utils"
7
8 const Avatar = React.forwardRef(({ className, ...props }, ref) => (
9   <AvatarPrimitive.Root
10     ref={ref}
11     className={cn("relative flex h-10 w-10 shrink-0 overflow-hidden rounded-full", className)}
12     {...props} />
13 ))
14 Avatar.displayName = AvatarPrimitive.Root.displayName
15
16 const AvatarImage = React.forwardRef(({ className, ...props }, ref) => (
17   <AvatarPrimitive.Image
18     ref={ref}
19     className={cn("aspect-square h-full w-full", className)}
20     {...props} />
21 ))
22 AvatarImage.displayName = AvatarPrimitive.Image.displayName
23
24 const AvatarFallback = React.forwardRef(({ className, ...props }, ref) => (
25   <AvatarPrimitive.Fallback
26     ref={ref}
27     className={cn(
28       "flex h-full w-full items-center justify-center rounded-full bg-muted",
29       className
30     )}
31     {...props} />
32 ))
33 AvatarFallback.displayName = AvatarPrimitive.Fallback.displayName
34
35 export { Avatar, AvatarImage, AvatarFallback }
36
37 import * as React from "react"
38 import { cva } from "class-variance-authority";
39
40 import { cn } from "@lib/utils"
41
42 const badgeVariants = cva(
43   "inline-flex items-center rounded-md border px-2.5 py-0.5 text-xs font-semibold transition-
44   colors focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2",
45   {
46     variants: {
47       variant: {
48         default:
49           "border-transparent bg-primary text-primary-foreground shadow hover:bg-primary/80",
50         secondary:
51           "border-transparent bg-secondary text-secondary-foreground hover:bg-secondary/80",
52         destructive:
53           "border-transparent bg-destructive text-destructive-foreground shadow hover:bg-
54 destructive/80",
55         outline: "text-foreground",
56       },
57     },
58   },
59 )

```

```

21     },
22     defaultVariants: {
23       variant: "default",
24     },
25   }
26 )
27
28 function Badge({
29   className,
30   variant,
31   ...props
32 }) {
33   return (<div className={cn(badgeVariants({ variant }), className)} {...props} />);
34 }
35
36 export { Badge, badgeVariants }
37
1 import * as React from "react"
2 import { Slot } from "@radix-ui/react-slot"
3 import { ChevronRight, MoreHorizontal } from "lucide-react"
4
5 import { cn } from "@lib/utils"
6
7 const Breadcrumb = React.forwardRef(
8   ({ ...props }, ref) => <nav ref={ref} aria-label="breadcrumb" {...props} />
9 )
10 Breadcrumb.displayName = "Breadcrumb"
11
12 const BreadcrumbList = React.forwardRef(({ className, ...props }, ref) => (
13   <ol
14     ref={ref}
15     className={cn(
16       "flex flex-wrap items-center gap-1.5 break-words text-sm text-muted-foreground sm:gap-2.5",
17       className
18     )}
19     {...props} />
20 ))
21 BreadcrumbList.displayName = "BreadcrumbList"
22
23 const BreadcrumbItem = React.forwardRef(({ className, ...props }, ref) => (
24   <li
25     ref={ref}
26     className={cn("inline-flex items-center gap-1.5", className)}
27     {...props} />
28 ))
29 BreadcrumbItem.displayName = "BreadcrumbItem"
30
31 const BreadcrumbLink = React.forwardRef(({ asChild, className, ...props }, ref) => {
32   const Comp = asChild ? Slot : "a"
33
34   return (
35     <Comp
36       ref={ref}
37       className={cn("transition-colors hover:text-foreground", className)}

```

```

38     {...props} />)
39 );
40 })
41 BreadcrumbLink.displayName = "BreadcrumbLink"
42
43 const BreadcrumbPage = React.forwardRef(({ className, ...props }, ref) => (
44     <span
45         ref={ref}
46         role="link"
47         aria-disabled="true"
48         aria-current="page"
49         className={cn("font-normal text-foreground", className)}
50         {...props} />
51 ))
52 BreadcrumbPage.displayName = "BreadcrumbPage"
53
54 const BreadcrumbSeparator = ({
55     children,
56     className,
57     ...props
58 }) => (
59     <li
60         role="presentation"
61         aria-hidden="true"
62         className={cn("[&svg]:w-3.5 [&svg]:h-3.5", className)}
63         {...props}>
64         {children ?? <ChevronRight />}
65     </li>
66 )
67 BreadcrumbSeparator.displayName = "BreadcrumbSeparator"
68
69 const BreadcrumbEllipsis = ({
70     className,
71     ...props
72 }) => (
73     <span
74         role="presentation"
75         aria-hidden="true"
76         className={cn("flex h-9 w-9 items-center justify-center", className)}
77         {...props}>
78         <MoreHorizontal className="h-4 w-4" />
79         <span className="sr-only">More</span>
80     </span>
81 )
82 BreadcrumbEllipsis.displayName = "BreadcrumbElipssis"
83
84 export {
85     Breadcrumb,
86     BreadcrumbList,
87     BreadcrumbItem,
88     BreadcrumbLink,
89     BreadcrumbPage,
90     BreadcrumbSeparator,

```

```

91   BreadcrumbEllipsis,
92 }
1  import * as React from "react"
2  import { Slot } from "@radix-ui/react-slot"
3  import { cva } from "class-variance-authority";
4
5  import { cn } from "@lib/utils"
6
7  const buttonVariants = cva(
8    "inline-flex items-center justify-center gap-2 whitespace-nowrap rounded-md text-sm font-medium
9    transition-colors focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring
10   disabled:pointer-events-none disabled:opacity-50 [&_svg]:pointer-events-none [&_svg]:size-4
11   [&_svg]:shrink-0",
12   {
13     variants: {
14       variant: {
15         default:
16           "bg-primary text-primary-foreground shadow hover:bg-primary/90",
17         destructive:
18           "bg-destructive text-destructive-foreground shadow-sm hover:bg-destructive/90",
19         outline:
20           "border border-input bg-transparent shadow-sm hover:bg-accent hover:text-accent-
21 foreground",
22         secondary:
23           "bg-secondary text-secondary-foreground shadow-sm hover:bg-secondary/80",
24         ghost: "hover:bg-accent hover:text-accent-foreground",
25         link: "text-primary underline-offset-4 hover:underline",
26       },
27       size: {
28         default: "h-9 px-4 py-2",
29         sm: "h-8 rounded-md px-3 text-xs",
30         lg: "h-10 rounded-md px-8",
31         icon: "h-9 w-9",
32       },
33     },
34     defaultVariants: {
35       variant: "default",
36       size: "default",
37     },
38   }
39 )
40
41 const Button = React.forwardRef(({ className, variant, size, asChild = false, ...props }, ref) =>
42 {
43   const Comp = asChild ? Slot : "button"
44   return (
45     (<Comp
46       className={cn(buttonVariants({ variant, size, className }))}
47       ref={ref}
48       {...props} />)
49   );
50 })
51 Button.displayName = "Button"

```

52

53 export { Button, buttonVariants }

1 import * as React from "react"

2 import { ChevronLeft, ChevronRight } from "lucide-react"

3 import { DayPicker } from "react-day-picker"

4

5 import { cn } from "@lib/utils"

6 import { buttonVariants } from "@components/ui/button"

7

8 function Calendar({

9 className,

10 classNames,

11 showOutsideDays = true,

12 ...props

13 }) {

14 return (

15 <DayPicker

16 showOutsideDays={showOutsideDays}

17 className={cn("p-3", className)}

18 classNames={{

19 months: "flex flex-col sm:flex-row space-y-4 sm:space-x-4 sm:space-y-0",

20 month: "space-y-4",

21 caption: "flex justify-center pt-1 relative items-center",

22 caption_label: "text-sm font-medium",

23 nav: "space-x-1 flex items-center",

24 nav_button: cn(

25 buttonVariants({ variant: "outline" }),

26 "h-7 w-7 bg-transparent p-0 opacity-50 hover:opacity-100"

27),

28 nav_button_previous: "absolute left-1",

29 nav_button_next: "absolute right-1",

30 table: "w-full border-collapse space-y-1",

31 head_row: "flex",

32 head_cell:

33 "text-muted-foreground rounded-md w-8 font-normal text-[0.8rem]",

34 row: "flex w-full mt-2",

35 cell: cn(

36 "relative p-0 text-center text-sm focus-within:z-20 [&:has([aria-selected]):bg-accent [&:has([aria-selected].day-outside):bg-accent/50 [&:has([aria-selected].day-range-end):rounded-r-md",

39 props.mode === "range"

40 ? "[&:has(>.day-range-end):rounded-r-md [&:has(>.day-range-start):rounded-l-md

41 first:[&:has([aria-selected]):rounded-l-md last:[&:has([aria-selected]):rounded-r-md"

42 : "[&:has([aria-selected]):rounded-md"

43),

44 day: cn(

45 buttonVariants({ variant: "ghost" }),

46 "h-8 w-8 p-0 font-normal aria-selected:opacity-100"

47),

48 day_range_start: "day-range-start",

49 day_range_end: "day-range-end",

50 day_selected:

```
51         "bg-primary text-primary-foreground hover:bg-primary hover:text-primary-foreground
52 focus:bg-primary focus:text-primary-foreground",
53         day_today: "bg-accent text-accent-foreground",
54         day_outside:
55             "day-outside text-muted-foreground aria-selected:bg-accent/50 aria-selected:text-muted-
56 foreground",
57         day_disabled: "text-muted-foreground opacity-50",
58         day_range_middle:
59             "aria-selected:bg-accent aria-selected:text-accent-foreground",
60         day_hidden: "invisible",
61         ...classNames,
62     }}
63     components={{
64         IconLeft: ({ className, ...props }) => (
65             <ChevronLeft className={cn("h-4 w-4", className)} {...props} />
66         ),
67         IconRight: ({ className, ...props }) => (
68             <ChevronRight className={cn("h-4 w-4", className)} {...props} />
69         ),
70     }}
71     {...props} />)
72 );
73 }
74 Calendar.displayName = "Calendar"
75
76 export { Calendar }
1 import * as React from "react"
2
3 import { cn } from "@lib/utils"
4
5 const Card = React.forwardRef(({ className, ...props }, ref) => (
6     <div
7         ref={ref}
8         className={cn("rounded-xl border bg-card text-card-foreground shadow", className)}
9         {...props} />
10 ))
11 Card.displayName = "Card"
12
13 const CardHeader = React.forwardRef(({ className, ...props }, ref) => (
14     <div
15         ref={ref}
16         className={cn("flex flex-col space-y-1.5 p-6", className)}
17         {...props} />
18 ))
19 CardHeader.displayName = "CardHeader"
20
21 const CardTitle = React.forwardRef(({ className, ...props }, ref) => (
22     <div
23         ref={ref}
24         className={cn("font-semibold leading-none tracking-tight", className)}
25         {...props} />
26 ))
27 CardTitle.displayName = "CardTitle"
```

```

28
29 const CardDescription = React.forwardRef(({ className, ...props }, ref) => (
30   <div
31     ref={ref}
32     className={cn("text-sm text-muted-foreground", className)}
33     {...props} />
34   ))
35 CardDescription.displayName = "CardDescription"
36
37 const CardContent = React.forwardRef(({ className, ...props }, ref) => (
38   <div ref={ref} className={cn("p-6 pt-0", className)} {...props} />
39   ))
40 CardContent.displayName = "CardContent"
41
42 const CardFooter = React.forwardRef(({ className, ...props }, ref) => (
43   <div
44     ref={ref}
45     className={cn("flex items-center p-6 pt-0", className)}
46     {...props} />
47   ))
48 CardFooter.displayName = "CardFooter"
49
50 export { Card, CardHeader, CardFooter, CardTitle, CardDescription, CardContent }
1  import * as React from "react"
2  import useEmblaCarousel from "embla-carousel-react";
3  import { ArrowLeft, ArrowRight } from "lucide-react"
4
5  import { cn } from "@lib/utils"
6  import { Button } from "@components/ui/button"
7
8  const CarouselContext = React.createContext(null)
9
10 function useCarousel() {
11   const context = React.useContext(CarouselContext)
12
13   if (!context) {
14     throw new Error("useCarousel must be used within a <Carousel />")
15   }
16
17   return context
18 }
19
20 const Carousel = React.forwardRef((
21   {
22     orientation = "horizontal",
23     opts,
24     setApi,
25     plugins,
26     className,
27     children,
28     ...props
29   },
30   ref

```

```
31 ) => {
32   const [carouselRef, api] = useEmblaCarousel({
33     ...opts,
34     axis: orientation === "horizontal" ? "x" : "y",
35   }, plugins)
36   const [canScrollPrev, setCanScrollPrev] = React.useState(false)
37   const [canScrollNext, setCanScrollNext] = React.useState(false)
38
39   const onSelect = React.useCallback((api) => {
40     if (!api) {
41       return
42     }
43
44     setCanScrollPrev(api.canScrollPrev())
45     setCanScrollNext(api.canScrollNext())
46   }, [])
47
48   const scrollPrev = React.useCallback(() => {
49     api?.scrollPrev()
50   }, [api])
51
52   const scrollNext = React.useCallback(() => {
53     api?.scrollNext()
54   }, [api])
55
56   const handleKeyDown = React.useCallback((event) => {
57     if (event.key === "ArrowLeft") {
58       event.preventDefault()
59       scrollPrev()
60     } else if (event.key === "ArrowRight") {
61       event.preventDefault()
62       scrollNext()
63     }
64   }, [scrollPrev, scrollNext])
65
66   React.useEffect(() => {
67     if (!api || !setApi) {
68       return
69     }
70
71     setApi(api)
72   }, [api, setApi])
73
74   React.useEffect(() => {
75     if (!api) {
76       return
77     }
78
79     onSelect(api)
80     api.on("reInit", onSelect)
81     api.on("select", onSelect)
82
83     return () => {
```

```

84     api?.off("select", onSelect)
85   };
86   }, [api, onSelect])
87
88   return (
89     <CarouselContext.Provider
90       value={{
91         carouselRef,
92         api: api,
93         opts,
94         orientation:
95           orientation || (opts?.axis === "y" ? "vertical" : "horizontal"),
96         scrollPrev,
97         scrollNext,
98         canScrollPrev,
99         canScrollNext,
100      }}>
101       <div
102         ref={ref}
103         onKeyDownCapture={handleKeyDown}
104         className={cn("relative", className)}
105         role="region"
106         aria-roledescription="carousel"
107         {...props}>
108           {children}
109         </div>
110       </CarouselContext.Provider>
111     );
112   })
113   Carousel.displayName = "Carousel"
114
115   const CarouselContent = React.forwardRef(({ className, ...props }, ref) => {
116     const { carouselRef, orientation } = useCarousel()
117
118     return (
119       <div ref={carouselRef} className="overflow-hidden">
120         <div
121           ref={ref}
122           className={cn(
123             "flex",
124             orientation === "horizontal" ? "-ml-4" : "-mt-4 flex-col",
125             className
126           )}
127           {...props} />
128       </div>
129     );
130   })
131   CarouselContent.displayName = "CarouselContent"
132
133   const CarouselItem = React.forwardRef(({ className, ...props }, ref) => {
134     const { orientation } = useCarousel()
135
136     return (

```

```

137     (<div
138         ref={ref}
139         role="group"
140         aria-roledescription="slide"
141         className={cn(
142             "min-w-0 shrink-0 grow-0 basis-full",
143             orientation === "horizontal" ? "pl-4" : "pt-4",
144             className
145         )}
146         {...props} />)
147 );
148 })
149 CarouselItem.displayName = "CarouselItem"
150
151 const CarouselPrevious = React.forwardRef(({ className, variant = "outline", size = "icon",
152     ...props }, ref) => {
153     const { orientation, scrollPrev, canScrollPrev } = useCarousel()
154
155     return (
156         <Button
157             ref={ref}
158             variant={variant}
159             size={size}
160             className={cn("absolute h-8 w-8 rounded-full", orientation === "horizontal"
161                 ? "-left-12 top-1/2 -translate-y-1/2"
162                 : "-top-12 left-1/2 -translate-x-1/2 rotate-90", className)}
163             disabled={!canScrollPrev}
164             onClick={scrollPrev}
165             {...props}>
166             <ArrowLeft className="h-4 w-4" />
167             <span className="sr-only">Previous slide</span>
168         </Button>)
169     );
170 })
171 CarouselPrevious.displayName = "CarouselPrevious"
172
173 const CarouselNext = React.forwardRef(({ className, variant = "outline", size = "icon", ...props
174 }, ref) => {
175     const { orientation, scrollNext, canScrollNext } = useCarousel()
176
177     return (
178         <Button
179             ref={ref}
180             variant={variant}
181             size={size}
182             className={cn("absolute h-8 w-8 rounded-full", orientation === "horizontal"
183                 ? "-right-12 top-1/2 -translate-y-1/2"
184                 : "-bottom-12 left-1/2 -translate-x-1/2 rotate-90", className)}
185             disabled={!canScrollNext}
186             onClick={scrollNext}
187             {...props}>
188             <ArrowRight className="h-4 w-4" />
189             <span className="sr-only">Next slide</span>

```

```

190     </Button>)
191   );
192 })
193 CarouselNext.displayName = "CarouselNext"
194
195 export { Carousel, CarouselContent, CarouselItem, CarouselPrevious, CarouselNext };
1  "use client";
2  import * as React from "react"
3  import * as RechartsPrimitive from "recharts"
4
5  import { cn } from "@lib/utils"
6
7  // Format: { THEME_NAME: CSS_SELECTOR }
8  const THEMES = {
9    light: "",
10   dark: ".dark"
11 }
12
13 const ChartContext = React.createContext(null)
14
15 function useChart() {
16   const context = React.useContext(ChartContext)
17
18   if (!context) {
19     throw new Error("useChart must be used within a <ChartContainer />")
20   }
21
22   return context
23 }
24
25 const ChartContainer = React.forwardRef(({ id, className, children, config, ...props }, ref) => {
26   const uniqueId = React.useId()
27   const chartId = `chart-${id || uniqueId.replace(/:/g, "")}`
28
29   return (
30     <ChartContext.Provider value={{ config }}>
31       <div
32         data-chart={chartId}
33         ref={ref}
34         className={cn(
35           "flex aspect-video justify-center text-xs [&_.recharts-cartesian-axis-tick_text]:fill-
36 muted-foreground [&_.recharts-cartesian-grid_line[stroke='#ccc']]:stroke-border/50 [&_.recharts-
37 curve.recharts-tooltip-cursor]:stroke-border [&_.recharts-dot[stroke='#fff']]:stroke-transparent
38 [&_.recharts-layer]:outline-none [&_.recharts-polar-grid_[stroke='#ccc']]:stroke-border
39 [&_.recharts-radial-bar-background-sector]:fill-muted [&_.recharts-rectangle.recharts-tooltip-
40 cursor]:fill-muted [&_.recharts-reference_line_[stroke='#ccc']]:stroke-border [&_.recharts-
41 sector[stroke='#fff']]:stroke-transparent [&_.recharts-sector]:outline-none [&_.recharts-
42 surface]:outline-none",
43         className
44       )}
45       {...props}>
46         <ChartStyle id={chartId} config={config} />
47         <RechartsPrimitive.ResponsiveContainer>

```

```

48         {children}
49     </RechartsPrimitive.ResponsiveContainer>
50 </div>
51 </ChartContext.Provider>)
52 );
53 })
54 ChartContainer.displayName = "Chart"
55
56 const ChartStyle = ({
57     id,
58     config
59 }) => {
60     const colorConfig = Object.entries(config).filter(([ , config]) => config.theme || config.color)
61
62     if (!colorConfig.length) {
63         return null
64     }
65
66     return (
67         <style
68             dangerouslySetInnerHTML={{
69                 __html: Object.entries(THEMES)
70                     .map(([theme, prefix]) => `
71 ${prefix} [data-chart=${id}] {
72 ${colorConfig
73     .map(([key, itemConfig]) => {
74 const color =
75     itemConfig.theme?.[theme] ||
76     itemConfig.color
77 return color ? `  --color-${key}: ${color};` : null
78 })
79 .join("\n")}
80 }
81 `)
82         .join("\n"),
83         }} />
84     );
85 }
86
87 const ChartTooltip = RechartsPrimitive.Tooltip
88
89 const ChartTooltipContent = React.forwardRef((
90     {
91         active,
92         payload,
93         className,
94         indicator = "dot",
95         hideLabel = false,
96         hideIndicator = false,
97         label,
98         labelFormatter,
99         labelClassName,
100         formatter,

```

```

101     color,
102     nameKey,
103     labelKey,
104 },
105 ref
106 ) => {
107     const { config } = useChart()
108
109     const tooltipLabel = React.useMemo(() => {
110         if (hideLabel || !payload?.length) {
111             return null
112         }
113
114         const [item] = payload
115         const key = `${labelKey || item.dataKey || item.name || "value"}`
116         const itemConfig = getPayloadConfigFromPayload(config, item, key)
117         const value =
118             !labelKey && typeof label === "string"
119             ? config[label]?.label || label
120             : itemConfig?.label
121
122         if (labelFormatter) {
123             return (
124                 <div className={cn("font-medium", labelClassName)}>
125                     {labelFormatter(value, payload)}
126                 </div>
127             );
128         }
129
130         if (!value) {
131             return null
132         }
133
134         return <div className={cn("font-medium", labelClassName)}>{value}</div>;
135     }, [
136         label,
137         labelFormatter,
138         payload,
139         hideLabel,
140         labelClassName,
141         config,
142         labelKey,
143     ])
144
145     if (!active || !payload?.length) {
146         return null
147     }
148
149     const nestLabel = payload.length === 1 && indicator !== "dot"
150
151     return (
152         <div
153             ref={ref}

```

```

154     className={cn(
155         "grid min-w-[8rem] items-start gap-1.5 rounded-lg border border-border/50 bg-background
156 px-2.5 py-1.5 text-xs shadow-xl",
157         className
158     )}>
159     {!nestLabel ? tooltipLabel : null}
160     <div className="grid gap-1.5">
161         {payload.map((item, index) => {
162             const key = `${nameKey} || item.name || item.dataKey || "value"`
163             const itemConfig = getPayloadConfigFromPayload(config, item, key)
164             const indicatorColor = color || item.payload.fill || item.color
165
166             return (
167                 <div
168                     key={item.dataKey}
169                     className={cn(
170                         "flex w-full flex-wrap items-stretch gap-2 [>svg]:h-2.5 [>svg]:w-2.5
171 [>svg]:text-muted-foreground",
172                         indicator === "dot" && "items-center"
173                     )}>
174                     {formatter && item?.value !== undefined && item.name ? (
175                         formatter(item.value, item.name, item, index, item.payload)
176                     ) : (
177                         <>
178                             {itemConfig?.icon ? (
179                                 <itemConfig.icon />
180                             ) : (
181                                 !hideIndicator && (
182                                     <div
183                                         className={cn("shrink-0 rounded-[2px] border-[--color-border] bg-[--color-
184 bg]", {
185                                             "h-2.5 w-2.5": indicator === "dot",
186                                             "w-1": indicator === "line",
187                                             "w-0 border-[1.5px] border-dashed bg-transparent":
188                                                 indicator === "dashed",
189                                             "my-0.5": nestLabel && indicator === "dashed",
190                                         )}}
191                                         style={
192                                             {
193                                                 "--color-bg": indicatorColor,
194                                                 "--color-border": indicatorColor
195                                             }
196                                         } />
197                                     )
198                                 )}
199                                     <div
200                                         className={cn(
201                                             "flex flex-1 justify-between leading-none",
202                                             nestLabel ? "items-end" : "items-center"
203                                         )}>
204                                         <div className="grid gap-1.5">
205                                             {nestLabel ? tooltipLabel : null}
206                                             <span className="text-muted-foreground">

```

```

207         {itemConfig?.label || item.name}
208     </span>
209 </div>
210     {item.value && (
211         <span className="font-mono font-medium tabular-nums text-foreground">
212             {item.value.toLocaleString()}
213         </span>
214     )}
215 </div>
216 </>
217 )}
218 </div>)
219 );
220 }}}
221 </div>
222 </div>)
223 );
224 })
225 ChartTooltipContent.displayName = "ChartTooltip"
226
227 const ChartLegend = RechartsPrimitive.Legend
228
229 const ChartLegendContent = React.forwardRef((
230     { className, hideIcon = false, payload, verticalAlign = "bottom", nameKey },
231     ref
232 ) => {
233     const { config } = useChart()
234
235     if (!payload?.length) {
236         return null
237     }
238
239     return (
240         <div
241             ref={ref}
242             className={cn(
243                 "flex items-center justify-center gap-4",
244                 verticalAlign === "top" ? "pb-3" : "pt-3",
245                 className
246             )}>
247             {payload.map((item) => {
248                 const key = `${nameKey || item.dataKey || "value"}`
249                 const itemConfig = getPayloadConfigFromPayload(config, item, key)
250
251                 return (
252                     <div
253                         key={item.value}
254                         className={cn(
255                             "flex items-center gap-1.5 [>svg]:h-3 [>svg]:w-3 [>svg]:text-muted-foreground"
256                         )}>
257                         {itemConfig?.icon && !hideIcon ? (
258                             <itemConfig.icon />
259                         ) : (

```

```

260         <div
261             className="h-2 w-2 shrink-0 rounded-[2px]"
262             style={{
263                 backgroundColor: item.color,
264             }} />
265         )}
266         {itemConfig?.label}
267     </div>)
268 );
269 })}
270 </div>)
271 );
272 })
273 ChartLegendContent.displayName = "ChartLegend"
274
275 // Helper to extract item config from a payload.
276 function getPayloadConfigFromPayload(
277     config,
278     payload,
279     key
280 ) {
281     if (typeof payload !== "object" || payload === null) {
282         return undefined
283     }
284
285     const payloadPayload =
286         "payload" in payload &&
287         typeof payload.payload === "object" &&
288         payload.payload !== null
289         ? payload.payload
290         : undefined
291
292     let configLabelKey = key
293
294     if (
295         key in payload &&
296         typeof payload[key] === "string"
297     ) {
298         configLabelKey = payload[key]
299     } else if (
300         payloadPayload &&
301         key in payloadPayload &&
302         typeof payloadPayload[key] === "string"
303     ) {
304         configLabelKey = payloadPayload[key]
305     }
306
307     return configLabelKey in config
308         ? config[configLabelKey]
309         : config[key];
310 }
311
312 export {

```

```

313     ChartContainer,
314     ChartTooltip,
315     ChartTooltipContent,
316     ChartLegend,
317     ChartLegendContent,
318     ChartStyle,
319 }
1  import * as React from "react"
2  import * as CheckboxPrimitive from "@radix-ui/react-checkbox"
3  import { Check } from "lucide-react"
4
5  import { cn } from "@lib/utils"
6
7  const Checkbox = React.forwardRef(({ className, ...props }, ref) => (
8    <CheckboxPrimitive.Root
9      ref={ref}
10     className={cn(
11       "peer h-4 w-4 shrink-0 rounded-sm border border-primary shadow focus-visible:outline-none
12 focus-visible:ring-1 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50 data-
13 [state=checked]:bg-primary data-[state=checked]:text-primary-foreground",
14       className
15     )}
16     {...props}>
17     <CheckboxPrimitive.Indicator className={cn("flex items-center justify-center text-current")}>
18       <Check className="h-4 w-4" />
19     </CheckboxPrimitive.Indicator>
20   </CheckboxPrimitive.Root>
21 ))
22 Checkbox.displayName = CheckboxPrimitive.Root.displayName
23
24 export { Checkbox }
1  "use client"
2
3  import * as CollapsiblePrimitive from "@radix-ui/react-collapsible"
4
5  const Collapsible = CollapsiblePrimitive.Root
6
7  const CollapsibleTrigger = CollapsiblePrimitive.CollapsibleTrigger
8
9  const CollapsibleContent = CollapsiblePrimitive.CollapsibleContent
10
11 export { Collapsible, CollapsibleTrigger, CollapsibleContent }
1  import * as React from "react"
2  import { Command as CommandPrimitive } from "cmdk"
3  import { Search } from "lucide-react"
4
5  import { cn } from "@lib/utils"
6  import { Dialog, DialogContent } from "@components/ui/dialog"
7
8  const Command = React.forwardRef(({ className, ...props }, ref) => (
9    <CommandPrimitive
10      ref={ref}
11      className={cn(

```

```
12     "flex h-full w-full flex-col overflow-hidden rounded-md bg-popover text-popover-foreground",
13     className
14   })
15   {...props} />
16 ))
17 Command.displayName = CommandPrimitive.displayName
18
19 const CommandDialog = ({
20   children,
21   ...props
22 }) => {
23   return (
24     <Dialog {...props}>
25       <DialogContent className="overflow-hidden p-0">
26         <Command
27           className="[&_cmdk-group-heading]:px-2 [&_cmdk-group-heading]:font-medium [&_cmdk-
28 group-heading]:text-muted-foreground [&_cmdk-group]:not([hidden])~[cmdk-group]:pt-0 [&_cmdk-
29 group]:px-2 [&_cmdk-input-wrapper]_svg:h-5 [&_cmdk-input-wrapper]_svg:w-5 [&_cmdk-input]:h-
30 12 [&_cmdk-item]:px-2 [&_cmdk-item]:py-3 [&_cmdk-item]_svg:h-5 [&_cmdk-item]_svg:w-5">
31           {children}
32         </Command>
33       </DialogContent>
34     </Dialog>)
35   );
36 }
37
38 const CommandInput = React.forwardRef(({ className, ...props }, ref) => (
39   <div className="flex items-center border-b px-3" cmdk-input-wrapper="">
40     <Search className="mr-2 h-4 w-4 shrink-0 opacity-50" />
41     <CommandPrimitive.Input
42       ref={ref}
43       className={cn(
44         "flex h-10 w-full rounded-md bg-transparent py-3 text-sm outline-none placeholder:text-
45 muted-foreground disabled:cursor-not-allowed disabled:opacity-50",
46         className
47       )}
48     {...props} />
49   </div>
50 ))
51
52 CommandInput.displayName = CommandPrimitive.Input.displayName
53
54 const CommandList = React.forwardRef(({ className, ...props }, ref) => (
55   <CommandPrimitive.List
56     ref={ref}
57     className={cn("max-h-[300px] overflow-y-auto overflow-x-hidden", className)}
58     {...props} />
59 ))
60
61 CommandList.displayName = CommandPrimitive.List.displayName
62
63 const CommandEmpty = React.forwardRef((props, ref) => (
64   <CommandPrimitive.Empty ref={ref} className="py-6 text-center text-sm" {...props} />
```

```

65  ))
66
67  CommandEmpty.displayName = CommandPrimitive.Empty.displayName
68
69  const CommandGroup = React.forwardRef(({ className, ...props }, ref) => (
70    <CommandPrimitive.Group
71      ref={ref}
72      className={cn(
73        "overflow-hidden p-1 text-foreground [&[cmdk-group-heading]]:px-2 [&[cmdk-group-
74 heading]]:py-1.5 [&[cmdk-group-heading]]:text-xs [&[cmdk-group-heading]]:font-medium [&[cmdk-
75 group-heading]]:text-muted-foreground",
76        className
77      )}
78      {...props} />
79  ))
80
81  CommandGroup.displayName = CommandPrimitive.Group.displayName
82
83  const CommandSeparator = React.forwardRef(({ className, ...props }, ref) => (
84    <CommandPrimitive.Separator ref={ref} className={cn("-mx-1 h-px bg-border", className)}
85    {...props} />
86  ))
87  CommandSeparator.displayName = CommandPrimitive.Separator.displayName
88
89  const CommandItem = React.forwardRef(({ className, ...props }, ref) => (
90    <CommandPrimitive.Item
91      ref={ref}
92      className={cn(
93        "relative flex cursor-default gap-2 select-none items-center rounded-sm px-2 py-1.5 text-sm
94 outline-none data-[disabled=true]:pointer-events-none data-[selected=true]:bg-accent data-
95 [selected=true]:text-accent-foreground data-[disabled=true]:opacity-50 [&_svg]:pointer-events-none
96 [&_svg]:size-4 [&_svg]:shrink-0",
97        className
98      )}
99      {...props} />
100  ))
101
102  CommandItem.displayName = CommandPrimitive.Item.displayName
103
104  const CommandShortcut = ({
105    className,
106    ...props
107  }) => {
108    return (
109      <span
110        className={cn("ml-auto text-xs tracking-widest text-muted-foreground", className)}
111        {...props} />
112    );
113  }
114  CommandShortcut.displayName = "CommandShortcut"
115
116  export {
117    Command,

```

```

118     CommandDialog,
119     CommandInput,
120     CommandList,
121     CommandEmpty,
122     CommandGroup,
123     CommandItem,
124     CommandShortcut,
125     CommandSeparator,
126 }
1  import * as React from "react"
2  import * as ContextMenuPrimitive from "@radix-ui/react-context-menu"
3  import { Check, ChevronRight, Circle } from "lucide-react"
4
5  import { cn } from "@lib/utils"
6
7  const ContextMenu = ContextMenuPrimitive.Root
8
9  const ContextMenuTrigger = ContextMenuPrimitive.Trigger
10
11  const ContextMenuGroup = ContextMenuPrimitive.Group
12
13  const ContextMenuPortal = ContextMenuPrimitive.Portal
14
15  const ContextMenuSub = ContextMenuPrimitive.Sub
16
17  const ContextMenuRadioGroup = ContextMenuPrimitive.RadioGroup
18
19  const ContextMenuSubTrigger = React.forwardRef(({ className, inset, children, ...props }, ref) =>
20  (
21    <ContextMenuPrimitive.SubTrigger
22      ref={ref}
23      className={cn(
24        "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none
25        focus:bg-accent focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-
26        accent-foreground",
27        inset && "pl-8",
28        className
29      )}
30      {...props}>
31      {children}
32      <ChevronRight className="ml-auto h-4 w-4" />
33    </ContextMenuPrimitive.SubTrigger>
34  ))
35  ContextMenuSubTrigger.displayName = ContextMenuPrimitive.SubTrigger.displayName
36
37  const ContextMenuSubContent = React.forwardRef(({ className, ...props }, ref) => (
38    <ContextMenuPrimitive.SubContent
39      ref={ref}
40      className={cn(
41        "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground
42        shadow-lg data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-
43        out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95

```

```

44 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-
45 [side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
46     className
47   })
48   {...props} />
49 ))
50 ContextMenuSubContent.displayName = ContextMenuPrimitive.SubContent.displayName
51
52 const ContextMenuContent = React.forwardRef(({ className, ...props }, ref) => (
53   <ContextMenuPrimitive.Portal>
54     <ContextMenuPrimitive.Content
55       ref={ref}
56       className={cn(
57         "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
58 foreground shadow-md data-[state=open]:animate-in data-[state=closed]:animate-out data-
59 [state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-
60 [state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-
61 right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
62         className
63       )}
64       {...props} />
65   </ContextMenuPrimitive.Portal>
66 ))
67 ContextMenuContent.displayName = ContextMenuPrimitive.Content.displayName
68
69 const ContextMenuItem = React.forwardRef(({ className, inset, ...props }, ref) => (
70   <ContextMenuPrimitive.Item
71     ref={ref}
72     className={cn(
73       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm
74 outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
75 data-[disabled]:opacity-50",
76       inset && "pl-8",
77       className
78     )}
79     {...props} />
80 ))
81 ContextMenuItem.displayName = ContextMenuPrimitive.Item.displayName
82
83 const ContextMenuCheckboxItem = React.forwardRef(({ className, children, checked, ...props }, ref)
84 => (
85   <ContextMenuPrimitive.CheckboxItem
86     ref={ref}
87     className={cn(
88       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
89 outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
90 data-[disabled]:opacity-50",
91       className
92     )}
93     checked={checked}
94     {...props}>
95     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
96       <ContextMenuPrimitive.ItemIndicator>

```

```

97         <Check className="h-4 w-4" />
98     </ContextMenuPrimitive.ItemIndicator>
99 </span>
100 {children}
101 </ContextMenuPrimitive.CheckboxItem>
102 ))
103 ContextMenuCheckboxItem.displayName =
104     ContextMenuPrimitive.CheckboxItem.displayName
105
106 const ContextMenuRadioItem = React.forwardRef(({ className, children, ...props }, ref) => (
107     <ContextMenuPrimitive.RadioItem
108         ref={ref}
109         className={cn(
110             "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
111             outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
112             data-[disabled]:opacity-50",
113             className
114         )}
115         {...props}>
116         <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
117             <ContextMenuPrimitive.ItemIndicator>
118                 <Circle className="h-4 w-4 fill-current" />
119             </ContextMenuPrimitive.ItemIndicator>
120         </span>
121         {children}
122     </ContextMenuPrimitive.RadioItem>
123 ))
124 ContextMenuRadioItem.displayName = ContextMenuPrimitive.RadioItem.displayName
125
126 const ContextMenuLabel = React.forwardRef(({ className, inset, ...props }, ref) => (
127     <ContextMenuPrimitive.Label
128         ref={ref}
129         className={cn(
130             "px-2 py-1.5 text-sm font-semibold text-foreground",
131             inset && "pl-8",
132             className
133         )}
134         {...props} />
135 ))
136 ContextMenuLabel.displayName = ContextMenuPrimitive.Label.displayName
137
138 const ContextMenuSeparator = React.forwardRef(({ className, ...props }, ref) => (
139     <ContextMenuPrimitive.Separator
140         ref={ref}
141         className={cn("-mx-1 my-1 h-px bg-border", className)}
142         {...props} />
143 ))
144 ContextMenuSeparator.displayName = ContextMenuPrimitive.Separator.displayName
145
146 const ContextMenuShortcut = ({
147     className,
148     ...props
149 }) => {

```

```

150     return (
151       <span
152         className={cn("ml-auto text-xs tracking-widest text-muted-foreground", className)}
153         {...props} />)
154     );
155   }
156   ContextMenuShortcut.displayName = "ContextMenuShortcut"
157
158   export {
159     ContextMenu,
160     ContextMenuTrigger,
161     ContextMenuContent,
162     ContextMenuItem,
163     ContextMenuCheckboxItem,
164     ContextMenuRadioItem,
165     ContextMenuLabel,
166     ContextMenuSeparator,
167     ContextMenuShortcut,
168     ContextMenuGroup,
169     ContextMenuPortal,
170     ContextMenuSub,
171     ContextMenuSubContent,
172     ContextMenuSubTrigger,
173     ContextMenuRadioGroup,
174   }
175
176   1 "use client"
177   2
178   3 import * as React from "react"
179   4 import * as DialogPrimitive from "@radix-ui/react-dialog"
180   5 import { X } from "lucide-react"
181   6
182   7 import { cn } from "@lib/utils"
183   8
184   9 const Dialog = DialogPrimitive.Root
185   10
186   11 const DialogTrigger = DialogPrimitive.Trigger
187   12
188   13 const DialogPortal = DialogPrimitive.Portal
189   14
190   15 const DialogClose = DialogPrimitive.Close
191   16
192   17 const DialogOverlay = React.forwardRef(({ className, ...props }, ref) => (
193     18   <DialogPrimitive.Overlay
194       19     ref={ref}
195       20     className={cn(
196         21       "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-
197         22 out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
198         23       className
199       )}
200       {...props} />
201     24   ))
202   25
203   26 DialogOverlay.displayName = DialogPrimitive.Overlay.displayName
204
205   27
206   28

```

```

29 const DialogContent = React.forwardRef(({ className, children, ...props }, ref) => (
30   <DialogPortal>
31     <DialogOverlay />
32     <DialogPrimitive.Content
33       ref={ref}
34       className={cn(
35         "fixed left-[50%] top-[50%] z-50 grid w-full max-w-lg translate-x-[-50%] translate-y-[-
36 50%] gap-4 border bg-background p-6 shadow-lg duration-200 data-[state=open]:animate-in data-
37 [state=closed]:animate-out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-
38 [state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-[state=closed]:slide-out-to-left-1/2
39 data-[state=closed]:slide-out-to-top-[48%] data-[state=open]:slide-in-from-left-1/2 data-
40 [state=open]:slide-in-from-top-[48%] sm:rounded-lg",
41       className
42     )}
43     {...props}>
44     {children}
45     <DialogPrimitive.Close
46       className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background transition-
47 opacity hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2
48 disabled:pointer-events-none data-[state=open]:bg-accent data-[state=open]:text-muted-foreground">
49       <X className="h-4 w-4" />
50       <span className="sr-only">Close</span>
51     </DialogPrimitive.Close>
52   </DialogPrimitive.Content>
53 </DialogPortal>
54 ))
55 DialogContent.displayName = DialogPrimitive.Content.displayName
56
57 const DialogHeader = ({
58   className,
59   ...props
60 }) => (
61   <div
62     className={cn("flex flex-col space-y-1.5 text-center sm:text-left", className)}
63     {...props} />
64 )
65 DialogHeader.displayName = "DialogHeader"
66
67 const DialogFooter = ({
68   className,
69   ...props
70 }) => (
71   <div
72     className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2", className)}
73     {...props} />
74 )
75 DialogFooter.displayName = "DialogFooter"
76
77 const DialogTitle = React.forwardRef(({ className, ...props }, ref) => (
78   <DialogPrimitive.Title
79     ref={ref}
80     className={cn("text-lg font-semibold leading-none tracking-tight", className)}
81     {...props} />

```

```

82  ))
83  DialogTitle.displayName = DialogPrimitive.Title.displayName
84
85  const DialogDescription = React.forwardRef(({ className, ...props }, ref) => (
86    <DialogPrimitive.Description
87      ref={ref}
88      className={cn("text-sm text-muted-foreground", className)}
89      {...props} />
90  ))
91  DialogDescription.displayName = DialogPrimitive.Description.displayName
92
93  export {
94    Dialog,
95    DialogPortal,
96    DialogOverlay,
97    DialogTrigger,
98    DialogClose,
99    DialogContent,
100    DialogHeader,
101    DialogFooter,
102    DialogTitle,
103    DialogDescription,
104  }
1
2  "use client"
3
4  import * as React from "react"
5  import { Drawer as DrawerPrimitive } from "vaul"
6  import { cn } from "@lib/utils"
7
8  const Drawer = ({
9    shouldScaleBackground = true,
10    ...props
11  }) => (
12    <DrawerPrimitive.Root shouldScaleBackground={shouldScaleBackground} {...props} />
13  )
14  Drawer.displayName = "Drawer"
15
16  const DrawerTrigger = DrawerPrimitive.Trigger
17
18  const DrawerPortal = DrawerPrimitive.Portal
19
20  const DrawerClose = DrawerPrimitive.Close
21
22  const DrawerOverlay = React.forwardRef(({ className, ...props }, ref) => (
23    <DrawerPrimitive.Overlay
24      ref={ref}
25      className={cn("fixed inset-0 z-50 bg-black/80", className)}
26      {...props} />
27  ))
28  DrawerOverlay.displayName = DrawerPrimitive.Overlay.displayName
29
30  const DrawerContent = React.forwardRef(({ className, children, ...props }, ref) => (

```

```
31   <DrawerPortal>
32     <DrawerOverlay />
33     <DrawerPrimitive.Content
34       ref={ref}
35       className={cn(
36         "fixed inset-x-0 bottom-0 z-50 mt-24 flex h-auto flex-col rounded-t-[10px] border bg-
37 background",
38         className
39       )}
40       {...props}>
41       <div className="mx-auto mt-4 h-2 w-[100px] rounded-full bg-muted" />
42       {children}
43     </DrawerPrimitive.Content>
44   </DrawerPortal>
45 ))
46 DrawerContent.displayName = "DrawerContent"
47
48 const DrawerHeader = ({
49   className,
50   ...props
51 }) => (
52   <div
53     className={cn("grid gap-1.5 p-4 text-center sm:text-left", className)}
54     {...props} />
55   )
56 DrawerHeader.displayName = "DrawerHeader"
57
58 const DrawerFooter = ({
59   className,
60   ...props
61 }) => (
62   <div className={cn("mt-auto flex flex-col gap-2 p-4", className)} {...props} />
63   )
64 DrawerFooter.displayName = "DrawerFooter"
65
66 const DrawerTitle = React.forwardRef(({ className, ...props }, ref) => (
67   <DrawerPrimitive.Title
68     ref={ref}
69     className={cn("text-lg font-semibold leading-none tracking-tight", className)}
70     {...props} />
71   ))
72 DrawerTitle.displayName = DrawerPrimitive.Title.displayName
73
74 const DrawerDescription = React.forwardRef(({ className, ...props }, ref) => (
75   <DrawerPrimitive.Description
76     ref={ref}
77     className={cn("text-sm text-muted-foreground", className)}
78     {...props} />
79   ))
80 DrawerDescription.displayName = DrawerPrimitive.Description.displayName
81
82 export {
83   Drawer,
```

```

84     DrawerPortal,
85     DrawerOverlay,
86     DrawerTrigger,
87     DrawerClose,
88     DrawerContent,
89     DrawerHeader,
90     DrawerFooter,
91     DrawerTitle,
92     DrawerDescription,
93 }
1  import * as React from "react"
2  import * as DropdownMenuPrimitive from "@radix-ui/react-dropdown-menu"
3  import { Check, ChevronRight, Circle } from "lucide-react"
4
5  import { cn } from "@lib/utils"
6
7  const DropdownMenu = DropdownMenuPrimitive.Root
8
9  const DropdownMenuTrigger = DropdownMenuPrimitive.Trigger
10
11 const DropdownMenuGroup = DropdownMenuPrimitive.Group
12
13 const DropdownMenuPortal = DropdownMenuPrimitive.Portal
14
15 const DropdownMenuSub = DropdownMenuPrimitive.Sub
16
17 const DropdownMenuRadioGroup = DropdownMenuPrimitive.RadioGroup
18
19 const DropdownMenuSubTrigger = React.forwardRef(({ className, inset, children, ...props }, ref) =>
20 (
21   <DropdownMenuPrimitive.SubTrigger
22     ref={ref}
23     className={cn(
24       "flex cursor-default gap-2 select-none items-center rounded-sm px-2 py-1.5 text-sm outline-
25 none focus:bg-accent data-[state=open]:bg-accent [&_svg]:pointer-events-none [&_svg]:size-4
26 [&_svg]:shrink-0",
27       inset && "pl-8",
28       className
29     )}
30     {...props}>
31     {children}
32     <ChevronRight className="ml-auto" />
33   </DropdownMenuPrimitive.SubTrigger>
34 ))
35 DropdownMenuSubTrigger.displayName =
36   DropdownMenuPrimitive.SubTrigger.displayName
37
38 const DropdownMenuSubContent = React.forwardRef(({ className, ...props }, ref) => (
39   <DropdownMenuPrimitive.SubContent
40     ref={ref}
41     className={cn(
42       "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground
43 shadow-lg data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-

```

```

44 out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
45 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-
46 [side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
47     className
48   })
49   {...props} />
50 ))
51 DropdownMenuSubContent.displayName =
52   DropdownMenuPrimitive.SubContent.displayName
53
54 const DropdownMenuContent = React.forwardRef(({ className, sideOffset = 4, ...props }, ref) => (
55   <DropdownMenuPrimitive.Portal>
56     <DropdownMenuPrimitive.Content
57       ref={ref}
58       sideOffset={sideOffset}
59       className={cn(
60         "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
61 foreground shadow-md",
62         "data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-
63 out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
64 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-
65 [side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
66         className
67       )}
68       {...props} />
69   </DropdownMenuPrimitive.Portal>
70 ))
71 DropdownMenuContent.displayName = DropdownMenuPrimitive.Content.displayName
72
73 const DropdownMenuItem = React.forwardRef(({ className, inset, ...props }, ref) => (
74   <DropdownMenuPrimitive.Item
75     ref={ref}
76     className={cn(
77       "relative flex cursor-default select-none items-center gap-2 rounded-sm px-2 py-1.5 text-sm
78 outline-none transition-colors focus:bg-accent focus:text-accent-foreground data-
79 [disabled]:pointer-events-none data-[disabled]:opacity-50 [&svg]:size-4 [&svg]:shrink-0",
80       inset && "pl-8",
81       className
82     )}
83     {...props} />
84 ))
85 DropdownMenuItem.displayName = DropdownMenuPrimitive.Item.displayName
86
87 const DropdownMenuCheckboxItem = React.forwardRef(({ className, children, checked, ...props },
88 ref) => (
89   <DropdownMenuPrimitive.CheckboxItem
90     ref={ref}
91     className={cn(
92       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
93 outline-none transition-colors focus:bg-accent focus:text-accent-foreground data-
94 [disabled]:pointer-events-none data-[disabled]:opacity-50",
95       className
96     )}

```

```

97     checked={checked}
98     {...props}>
99     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
100         <DropdownMenuPrimitive.ItemIndicator>
101             <Check className="h-4 w-4" />
102         </DropdownMenuPrimitive.ItemIndicator>
103     </span>
104     {children}
105 </DropdownMenuPrimitive.CheckboxItem>
106 ))
107 DropdownMenuCheckboxItem.displayName =
108     DropdownMenuPrimitive.CheckboxItem.displayName
109
110 const DropdownMenuRadioItem = React.forwardRef(({ className, children, ...props }, ref) => (
111     <DropdownMenuPrimitive.RadioItem
112         ref={ref}
113         className={cn(
114             "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
115 outline-none transition-colors focus:bg-accent focus:text-accent-foreground data-
116 [disabled]:pointer-events-none data-[disabled]:opacity-50",
117             className
118         )}
119         {...props}>
120         <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
121             <DropdownMenuPrimitive.ItemIndicator>
122                 <Circle className="h-2 w-2 fill-current" />
123             </DropdownMenuPrimitive.ItemIndicator>
124         </span>
125         {children}
126     </DropdownMenuPrimitive.RadioItem>
127 ))
128 DropdownMenuRadioItem.displayName = DropdownMenuPrimitive.RadioItem.displayName
129
130 const DropdownMenuLabel = React.forwardRef(({ className, inset, ...props }, ref) => (
131     <DropdownMenuPrimitive.Label
132         ref={ref}
133         className={cn("px-2 py-1.5 text-sm font-semibold", inset && "pl-8", className)}
134         {...props} />
135 ))
136 DropdownMenuLabel.displayName = DropdownMenuPrimitive.Label.displayName
137
138 const DropdownMenuSeparator = React.forwardRef(({ className, ...props }, ref) => (
139     <DropdownMenuPrimitive.Separator
140         ref={ref}
141         className={cn("-mx-1 my-1 h-px bg-muted", className)}
142         {...props} />
143 ))
144 DropdownMenuSeparator.displayName = DropdownMenuPrimitive.Separator.displayName
145
146 const DropdownMenuShortcut = ({
147     className,
148     ...props
149 }) => {

```

```

150     return (
151       <span
152         className={cn("ml-auto text-xs tracking-widest opacity-60", className)}
153         {...props} />
154     );
155 }
156 DropdownMenuShortcut.displayName = "DropdownMenuShortcut"
157
158 export {
159     DropdownMenu,
160     DropdownMenuTrigger,
161     DropdownMenuContent,
162     DropdownMenuItem,
163     DropdownMenuCheckboxItem,
164     DropdownMenuRadioItem,
165     DropdownMenuLabel,
166     DropdownMenuSeparator,
167     DropdownMenuShortcut,
168     DropdownMenuGroup,
169     DropdownMenuPortal,
170     DropdownMenuSub,
171     DropdownMenuSubContent,
172     DropdownMenuSubTrigger,
173     DropdownMenuRadioGroup,
174 }
1
2 "use client";
3 import * as React from "react"
4 import { Slot } from "@radix-ui/react-slot"
5 import { Controller, FormProvider, useFormContext } from "react-hook-form";
6
7 import { cn } from "@/lib/Utils"
8 import { Label } from "@/components/ui/label"
9
10 const Form = FormProvider
11
12 const FormFieldContext = React.createContext({})
13
14 const FormField = (
15     {
16         ...props
17     }
18 ) => {
19     return (
20         <FormFieldContext.Provider value={{ name: props.name }}>
21             <Controller {...props} />
22         </FormFieldContext.Provider>
23     );
24 }
25
26 const useFormField = () => {
27     const fieldContext = React.useContext(FormFieldContext)
28     const itemContext = React.useContext(FormItemContext)
29     const { getFieldState, formState } = useFormContext()

```

```

29
30     const fieldState = getFieldState(fieldContext.name, formState)
31
32     if (!fieldContext) {
33         throw new Error("useFormField should be used within <FormField>")
34     }
35
36     const { id } = itemContext
37
38     return {
39         id,
40         name: fieldContext.name,
41         formItemId: `${id}-form-item`,
42         formDescriptionId: `${id}-form-item-description`,
43         formMessageId: `${id}-form-item-message`,
44         ...fieldState,
45     }
46 }
47
48 const FormItemContext = React.createContext({})
49
50 const FormItem = React.forwardRef(({ className, ...props }, ref) => {
51     const id = React.useId()
52
53     return (
54         <FormItemContext.Provider value={{ id }}>
55             <div ref={ref} className={cn("space-y-2", className)} {...props} />
56         </FormItemContext.Provider>
57     );
58 })
59 FormItem.displayName = "FormItem"
60
61 const FormLabel = React.forwardRef(({ className, ...props }, ref) => {
62     const { error, formItemId } = useFormField()
63
64     return (
65         <Label
66             ref={ref}
67             className={cn(error && "text-destructive", className)}
68             htmlFor={formItemId}
69             {...props} />
70     );
71 })
72 FormLabel.displayName = "FormLabel"
73
74 const FormControl = React.forwardRef(({ ...props }, ref) => {
75     const { error, formItemId, formDescriptionId, formMessageId } = useFormField()
76
77     return (
78         <Slot
79             ref={ref}
80             id={formItemId}
81             aria-describedby={

```

```

82         !error
83         ? `${formDescriptionId}`
84         : `${formDescriptionId} ${formMessageId}`
85     }
86     aria-invalid={!!error}
87     {...props} />)
88 );
89 })
90 FormControl.displayName = "FormControl"
91
92 const FormDescription = React.forwardRef(({ className, ...props }, ref) => {
93     const { formDescriptionId } = useFormField()
94
95     return (
96         <p
97             ref={ref}
98             id={formDescriptionId}
99             className={cn("text-[0.8rem] text-muted-foreground", className)}
100             {...props} />)
101     );
102 })
103 FormDescription.displayName = "FormDescription"
104
105 const FormMessage = React.forwardRef(({ className, children, ...props }, ref) => {
106     const { error, formMessageId } = useFormField()
107     const body = error ? String(error?.message) : children
108
109     if (!body) {
110         return null
111     }
112
113     return (
114         <p
115             ref={ref}
116             id={formMessageId}
117             className={cn("text-[0.8rem] font-medium text-destructive", className)}
118             {...props}>
119             {body}
120         </p>)
121     );
122 })
123 FormMessage.displayName = "FormMessage"
124
125 export {
126     useFormField,
127     Form,
128     FormItem,
129     FormLabel,
130     FormControl,
131     FormDescription,
132     FormMessage,
133     FormField,
134 }

```

```

1  "use client"
2
3  import * as React from "react"
4  import * as HoverCardPrimitive from "@radix-ui/react-hover-card"
5
6  import { cn } from "@lib/utils"
7
8  const HoverCard = HoverCardPrimitive.Root
9
10 const HoverCardTrigger = HoverCardPrimitive.Trigger
11
12 const HoverCardContent = React.forwardRef(({ className, align = "center", sideOffset = 4, ...props
13 }, ref) => (
14   <HoverCardPrimitive.Content
15     ref={ref}
16     align={align}
17     sideOffset={sideOffset}
18     className={cn(
19       "z-50 w-64 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none
20 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-
21 [state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-
22 [side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-
23 in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
24     className
25   )}
26   {...props} />
27 ))
28 HoverCardContent.displayName = HoverCardPrimitive.Content.displayName
29
30 export { HoverCard, HoverCardTrigger, HoverCardContent }
1  const WIX_MEDIA_HOSTS = {
2    "media.lscianca.com": "/images/public/",
3    "static.wixstatic.com": "/media/",
4  }
5
6  export const DEFAULT_TRANSFORM_WIDTH = 1024
7  export const IMAGE_LOAD_MODE = {
8    OPTIMIZED: "optimized",
9    ORIGINAL: "original",
10   FALLBACK: "fallback",
11 }
12
13 const DEVICE_PIXEL_RATIOS = [1, 2, 3]
14 const MAX_DIMENSION = 6000
15
16 export function splitImageProps(props) {
17   const wrapperProps = {}
18   const imageProps = {}
19   for (const [key, value] of Object.entries(props)) {
20     if (key.startsWith("data-")) wrapperProps[key] = value
21     else imageProps[key] = value
22   }
23   return { wrapperProps, imageProps }

```

```

24 }
25
26 export function getImagePreviewClassName(className, currentClassName, baselineClassName) {
27     const sourceClasses = new Set((className || "").split(/\s+/))
28     const baselineClasses = new Set(baselineClassName.split(/\s+/))
29     return currentClassName.split(/\s+/).filter((token) =>
30         !["inline-block", "relative"].includes(token) || !baselineClasses.has(token) ||
31         sourceClasses.has(token)
32     ).join(" ")
33 }
34
35 /** Returns transform metadata only for canonical public Wix image URLs. */
36 export function parseWixMediaUrl(src) {
37     try {
38         const url = new URL(src)
39         if (
40             url.protocol !== "https:" ||
41             url.username ||
42             url.password ||
43             (url.port && url.port !== "443")
44         ) {
45             return null
46         }
47
48         const pathPrefix = WIX_MEDIA_HOSTS[url.hostname]
49         if (!pathPrefix) return null
50
51         const transformed = url.pathname.match(/^(.*)\/v1\/(?:fill|fit)\/[^\s]+\/[^\s]+$/i)
52         const basePath = transformed ? transformed[1] : url.pathname
53         const filename = basePath.split("/").pop()
54         if (
55             !basePath.startsWith(pathPrefix) ||
56             !filename ||
57             !/\.[a-z0-9]+$/i.test(filename) ||
58             /\.svg$/i.test(filename)
59         ) {
60             return null
61         }
62
63         return { baseUrl: `${url.origin}${basePath}`, filename }
64     } catch {
65         return null
66     }
67 }
68
69 const clampDim = (n) => Math.min(Math.max(Math.round(n), 1), MAX_DIMENSION)
70 const clamp01 = (n) => Math.min(1, Math.max(0, n))
71
72 export function buildTransformUrl(
73     { baseUrl, filename },
74     { width, height, crop, focalPoint, quality }
75 ) {
76     const params = [`w_${clampDim(width)}`, `h_${clampDim(height || width)}]

```

```

77     if (crop) {
78         params.push(
79             focalPoint
80             ? `fp_${clamp01(focalPoint.x).toFixed(2)}_${clamp01(focalPoint.y).toFixed(2)}`
81             : "al_c"
82         )
83     }
84     params.push(`q_${quality}`, "usm_0.66_1.00_0.01", "enc_webp", "quality_auto")
85     const outputName = /\.gif$/i.test(filename)
86       ? filename
87       : filename.replace(/\.([a-z0-9]+)$/i, "") + ".webp"
88     return `${baseUrl}/v1/${crop ? "fill" : "fit"}/${params.join(",")}/${outputName}`
89 }
90
91 export function buildSrcSet(parsed, options) {
92     return DEVICE_PIXEL_RATIOS.map(
93         (dpr) =>
94         `${buildTransformUrl(parsed, {
95             ...options,
96             width: options.width * dpr,
97             height: options.height ? options.height * dpr : undefined,
98         })} ${dpr}x`
99     ).join(", ")
100 }
101
102 export function getOriginalImageUrl(src, parsed) {
103     return parsed?.baseUrl || src
104 }
105
106 export function nextImageLoadMode(mode) {
107     return mode === IMAGE_LOAD_MODE.OPTIMIZED
108       ? IMAGE_LOAD_MODE.ORIGINAL
109       : IMAGE_LOAD_MODE.FALLBACK
110 }
111
112 import * as React from "react"
113 import { ResponsiveImage } from "../responsive-image"
114 import {
115     getOriginalImageUrl,
116     IMAGE_LOAD_MODE,
117     nextImageLoadMode,
118     parseWixMediaUrl,
119 } from "../image-helpers"
120
121 const FALLBACK_IMAGE_URL =
122     "https://static.wixstatic.com/media/12d367_4f26ccd17f8f4e3a8958306ea08c2332~mv2.png"
123
124 /**
125  * Image with built-in Wix Media Platform support: canonical public images on
126  * media.lscianca.com and static.wixstatic.com/media are resized to the rendered
127  * container per device pixel ratio and re-encoded to WebP; `fittingType="fill"`
128  * crops server-side, optionally anchored at a focal point. Other URLs render
129  * as a plain <img>. Failed transforms retry the original URL; only a broken
130  * original swaps to the generic fallback image.

```

```

20  */
21  const Image = React.forwardRef(
22    (
23      {
24        src: source,
25        fittingType = "fill",
26        originWidth,
27        originHeight,
28        focalPointX,
29        focalPointY,
30        quality = 90,
31        onError,
32        ...props
33      },
34      ref
35    ) => {
36      const [previewSource, setPreviewSource] = React.useState(null)
37      const preview = previewSource?.source === source ? previewSource : null
38      const src = preview ? preview.value : source
39      const replaceSource = (value, className) => setPreviewSource({
40        source, value, className, sourceClassName: props.className,
41      })
42      React.useEffect(() => setPreviewSource(null), [source])
43      const parsedSource = src && src !== FALLBACK_IMAGE_URL ? parseWixMediaUrl(src) : null
44      const initialMode = parsedSource ? IMAGE_LOAD_MODE.OPTIMIZED : IMAGE_LOAD_MODE.ORIGINAL
45      const [loadState, setLoadState] = React.useState({ src, mode: initialMode })
46      const mode = loadState.src === src ? loadState.mode : initialMode
47
48      React.useEffect(() => {
49        setLoadState({ src, mode: initialMode })
50      }, [src, initialMode])
51
52      const handleError = (event) => {
53        if (mode === IMAGE_LOAD_MODE.FALLBACK) return
54        const nextMode = nextImageLoadMode(mode)
55        setLoadState({ src, mode: nextMode })
56        if (nextMode === IMAGE_LOAD_MODE.FALLBACK) onError?.(event)
57      }
58
59      const imageProps = {
60        ...props,
61        className: preview && preview.sourceClassName === props.className ? preview.className :
62        props.className,
63        onError: handleError,
64      }
65
66      if (!src) {
67        // Renders as a real <img> (not a <div>) – the visual editor's
68        // click-to-edit toolbar keys its "Replace Image" action off the DOM
69        // tag being `img`, so a placeholder div would be unrecoverable in the
70        // editor. FALLBACK_IMAGE_URL doubles as the "no image chosen" graphic.
71        return <img ref={ref} src={FALLBACK_IMAGE_URL} {...imageProps} data-empty-image />
72      }

```

```

73
74 // A failed transform retries the underlying original as a plain image.
75 // Only a failure of that original advances to the generic fallback.
76 const parsed = mode === IMAGE_LOAD_MODE.OPTIMIZED ? parsedSource : null
77
78 if (!parsed) {
79   const isErrorMode = mode === IMAGE_LOAD_MODE.FALLBACK
80   const imageSrc = isErrorMode ? FALLBACK_IMAGE_URL : getOriginalImageUrl(src, parsedSource)
81   return (
82     <img ref={ref} src={imageSrc} {...imageProps} data-error-image={isErrorMode || undefined}
83   />
84   )
85 }
86
87 const focalPoint =
88   typeof focalPointX === "number" && typeof focalPointY === "number"
89     ? { x: focalPointX, y: focalPointY }
90     : undefined
91 // Origin dimensions are optional – when known they stabilize layout via
92 // the wrapper's aspect-ratio before the image loads.
93 const aspectRatio =
94   originWidth && originHeight ? `${originWidth} / ${originHeight}` : undefined
95
96 return (
97   <ResponsiveImage
98     ref={ref}
99     src={src}
100     parsed={parsed}
101     onSourceChange={replaceSource}
102     fittingType={fittingType}
103     focalPoint={focalPoint}
104     quality={quality}
105     aspectRatio={aspectRatio}
106     {...imageProps}
107   />
108 )
109 }
110 )
111 Image.displayName = "Image"
112
113 export { Image }
1
1 import * as React from "react"
2 import { OTPInput, OTPInputContext } from "input-otp"
3 import { Minus } from "lucide-react"
4
5 import { cn } from "@lib/utils"
6
7 const InputOTP = React.forwardRef(({ className, containerClassName, ...props }, ref) => (
8   <OTPInput
9     ref={ref}
10     containerClassName={cn("flex items-center gap-2 has-[:disabled]:opacity-50",
11 containerClassName)}
12     className={cn("disabled:cursor-not-allowed", className)}

```

```

13     {...props} />
14 ))
15 InputOTP.displayName = "InputOTP"
16
17 const InputOTPGroup = React.forwardRef(({ className, ...props }, ref) => (
18   <div ref={ref} className={cn("flex items-center", className)} {...props} />
19 ))
20 InputOTPGroup.displayName = "InputOTPGroup"
21
22 const InputOTPSlot = React.forwardRef(({ index, className, ...props }, ref) => {
23   const inputOTPContext = React.useContext(OTPInputContext)
24   const { char, hasFakeCaret, isActive } = inputOTPContext.slots[index]
25
26   return (
27     <div
28       ref={ref}
29       className={cn(
30         "relative flex h-9 w-9 items-center justify-center border-y border-r border-input text-sm
31 shadow-sm transition-all first:rounded-l-md first:border-l last:rounded-r-md",
32         isActive && "z-10 ring-1 ring-ring",
33         className
34       )}
35       {...props}>
36       {char}
37       {hasFakeCaret && (
38         <div
39           className="pointer-events-none absolute inset-0 flex items-center justify-center">
40             <div className="h-4 w-px animate-caret-blink bg-foreground duration-1000" />
41           </div>
42         )}
43     </div>)
44   );
45 })
46 InputOTPSlot.displayName = "InputOTPSlot"
47
48 const InputOTPSeparator = React.forwardRef(({ ...props }, ref) => (
49   <div ref={ref} role="separator" {...props}>
50     <Minus />
51   </div>
52 ))
53 InputOTPSeparator.displayName = "InputOTPSeparator"
54
55 export { InputOTP, InputOTPGroup, InputOTPSlot, InputOTPSeparator }
56 import * as React from "react"
57
58 import { cn } from "@lib/utils"
59
60 const Input = React.forwardRef(({ className, type, ...props }, ref) => {
61   return (
62     <input
63       type={type}
64       className={cn(

```

```

10         "flex h-9 w-full rounded-md border border-input bg-transparent px-3 py-1 text-base shadow-
11 sm transition-colors file:border-0 file:bg-transparent file:text-sm file:font-medium file:text-
12 foreground placeholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-1
13 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50 md:text-sm",
14         className
15     )}
16     ref={ref}
17     {...props} />)
18 );
19 })
20 Input.displayName = "Input"
21
22 export { Input }
23
24 1 import * as React from "react"
25 2 import * as LabelPrimitive from "@radix-ui/react-label"
26 3 import { cva } from "class-variance-authority";
27 4
28 5 import { cn } from "@/lib/utils"
29 6
30 7 const labelVariants = cva(
31 8     "text-sm font-medium leading-none peer-disabled:cursor-not-allowed peer-disabled:opacity-70"
32 9 )
33
34 10
35 11 const Label = React.forwardRef(({ className, ...props }, ref) => (
36 12     <LabelPrimitive.Root ref={ref} className={cn(labelVariants(), className)} {...props} />
37 13 ))
38 Label.displayName = LabelPrimitive.Root.displayName
39
40 14
41 15 export { Label }
42 1
43 2 "use client"
44 3
45 4 import * as React from "react"
46 5 import * as MenubarPrimitive from "@radix-ui/react-menubar"
47 6 import { Check, ChevronRight, Circle } from "lucide-react"
48 7
49 8
50 9 import { cn } from "@/lib/utils"
51 10
52 11 function MenubarMenu({
53 12     ...props
54 15 }) {
55 16     return <MenubarPrimitive.Menu {...props} />;
56 17 }
57
58 18
59 19 function MenubarGroup({
60 20     ...props
61 22 }) {
62 23     return <MenubarPrimitive.Group {...props} />;
63 24 }
64
65 25
66 26 function MenubarPortal({
67 27     ...props
68 29 }) {
69 30     return <MenubarPrimitive.Portal {...props} />;
70

```

```

25 }
26
27 function MenubarRadioGroup({
28   ...props
29 }) {
30   return <MenubarPrimitive.RadioGroup {...props} />;
31 }
32
33 function MenubarSub({
34   ...props
35 }) {
36   return <MenubarPrimitive.Sub data-slot="menubar-sub" {...props} />;
37 }
38
39 const Menubar = React.forwardRef(({ className, ...props }, ref) => (
40   <MenubarPrimitive.Root
41     ref={ref}
42     className={cn(
43       "flex h-9 items-center space-x-1 rounded-md border bg-background p-1 shadow-sm",
44       className
45     )}
46     {...props} />
47 ))
48 Menubar.displayName = MenubarPrimitive.Root.displayName
49
50 const MenubarTrigger = React.forwardRef(({ className, ...props }, ref) => (
51   <MenubarPrimitive.Trigger
52     ref={ref}
53     className={cn(
54       "flex cursor-default select-none items-center rounded-sm px-3 py-1 text-sm font-medium
55 outline-none focus:bg-accent focus:text-accent-foreground data-[state=open]:bg-accent data-
56 [state=open]:text-accent-foreground",
57       className
58     )}
59     {...props} />
60 ))
61 MenubarTrigger.displayName = MenubarPrimitive.Trigger.displayName
62
63 const MenubarSubTrigger = React.forwardRef(({ className, inset, children, ...props }, ref) => (
64   <MenubarPrimitive.SubTrigger
65     ref={ref}
66     className={cn(
67       "flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm outline-none
68 focus:bg-accent focus:text-accent-foreground data-[state=open]:bg-accent data-[state=open]:text-
69 accent-foreground",
70       inset && "pl-8",
71       className
72     )}
73     {...props}>
74     {children}
75     <ChevronRight className="ml-auto h-4 w-4" />
76   </MenubarPrimitive.SubTrigger>
77 ))

```

```

78 MenubarSubTrigger.displayName = MenubarPrimitive.SubTrigger.displayName
79
80 const MenubarSubContent = React.forwardRef(({ className, ...props }, ref) => (
81   <MenubarPrimitive.SubContent
82     ref={ref}
83     className={cn(
84       "z-50 min-w-[8rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-foreground
85       shadow-lg data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-
86       out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95
87       data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-
88       [side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
89       className
90     )}
91     {...props} />
92 ))
93 MenubarSubContent.displayName = MenubarPrimitive.SubContent.displayName
94
95 const MenubarContent = React.forwardRef((
96   { className, align = "start", alignOffset = -4, sideOffset = 8, ...props },
97   ref
98 ) => (
99   <MenubarPrimitive.Portal>
100     <MenubarPrimitive.Content
101       ref={ref}
102       align={align}
103       alignOffset={alignOffset}
104       sideOffset={sideOffset}
105       className={cn(
106         "z-50 min-w-[12rem] overflow-hidden rounded-md border bg-popover p-1 text-popover-
107         foreground shadow-md data-[state=open]:animate-in data-[state=closed]:fade-out-0 data-
108         [state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-
109         [side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-
110         in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
111         className
112       )}
113       {...props} />
114     </MenubarPrimitive.Portal>
115 ))
116 MenubarContent.displayName = MenubarPrimitive.Content.displayName
117
118 const MenubarItem = React.forwardRef(({ className, inset, ...props }, ref) => (
119   <MenubarPrimitive.Item
120     ref={ref}
121     className={cn(
122       "relative flex cursor-default select-none items-center rounded-sm px-2 py-1.5 text-sm
123       outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
124       data-[disabled]:opacity-50",
125       inset && "pl-8",
126       className
127     )}
128     {...props} />
129 ))
130 MenubarItem.displayName = MenubarPrimitive.Item.displayName

```

```

131
132 const MenubarCheckboxItem = React.forwardRef(({ className, children, checked, ...props }, ref) =>
133 (
134   <MenubarPrimitive.CheckboxItem
135     ref={ref}
136     className={cn(
137       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
138 outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
139 data-[disabled]:opacity-50",
140       className
141     )}
142     checked={checked}
143     {...props}>
144     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
145       <MenubarPrimitive.ItemIndicator>
146         <Check className="h-4 w-4" />
147       </MenubarPrimitive.ItemIndicator>
148     </span>
149     {children}
150   </MenubarPrimitive.CheckboxItem>
151 )
152 MenubarCheckboxItem.displayName = MenubarPrimitive.CheckboxItem.displayName
153
154 const MenubarRadioItem = React.forwardRef(({ className, children, ...props }, ref) => (
155   <MenubarPrimitive.RadioItem
156     ref={ref}
157     className={cn(
158       "relative flex cursor-default select-none items-center rounded-sm py-1.5 pl-8 pr-2 text-sm
159 outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-none
160 data-[disabled]:opacity-50",
161       className
162     )}
163     {...props}>
164     <span className="absolute left-2 flex h-3.5 w-3.5 items-center justify-center">
165       <MenubarPrimitive.ItemIndicator>
166         <Circle className="h-4 w-4 fill-current" />
167       </MenubarPrimitive.ItemIndicator>
168     </span>
169     {children}
170   </MenubarPrimitive.RadioItem>
171 )
172 MenubarRadioItem.displayName = MenubarPrimitive.RadioItem.displayName
173
174 const MenubarLabel = React.forwardRef(({ className, inset, ...props }, ref) => (
175   <MenubarPrimitive.Label
176     ref={ref}
177     className={cn("px-2 py-1.5 text-sm font-semibold", inset && "pl-8", className)}
178     {...props} />
179 )
180 MenubarLabel.displayName = MenubarPrimitive.Label.displayName
181
182 const MenubarSeparator = React.forwardRef(({ className, ...props }, ref) => (
183   <MenubarPrimitive.Separator

```

```

184     ref={ref}
185     className={cn("-mx-1 my-1 h-px bg-muted", className)}
186     {...props} />
187 ))
188 MenubarSeparator.displayName = MenubarPrimitive.Separator.displayName
189
190 const MenubarShortcut = ({
191   className,
192   ...props
193 }) => {
194   return (
195     <span
196       className={cn("ml-auto text-xs tracking-widest text-muted-foreground", className)}
197       {...props} />)
198   );
199 }
200 MenubarShortcut.displayName = "MenubarShortcut"
201
202 export {
203   Menubar,
204   MenubarMenu,
205   MenubarTrigger,
206   MenubarContent,
207   MenubarItem,
208   MenubarSeparator,
209   MenubarLabel,
210   MenubarCheckboxItem,
211   MenubarRadioGroup,
212   MenubarRadioItem,
213   MenubarPortal,
214   MenubarSubContent,
215   MenubarSubTrigger,
216   MenubarGroup,
217   MenubarSub,
218   MenubarShortcut,
219 }
220
221 import * as React from "react"
222 import * as NavigationMenuPrimitive from "@radix-ui/react-navigation-menu"
223 import { cva } from "class-variance-authority"
224 import { ChevronDown } from "lucide-react"
225
226 import { cn } from "@lib/utils"
227
228 const NavigationMenu = React.forwardRef(({ className, children, ...props }, ref) => (
229   <NavigationMenuPrimitive.Root
230     ref={ref}
231     className={cn(
232       "relative z-10 flex max-w-max flex-1 items-center justify-center",
233       className
234     )}
235     {...props}>
236     {children}
237   <NavigationMenuViewport />

```

```
18     </NavigationMenuPrimitive.Root>
19   ))
20   NavigationMenu.displayName = NavigationMenuPrimitive.Root.displayName
21
22   const NavigationMenuList = React.forwardRef(({ className, ...props }, ref) => (
23     <NavigationMenuPrimitive.List
24       ref={ref}
25       className={cn(
26         "group flex flex-1 list-none items-center justify-center space-x-1",
27         className
28       )}
29       {...props} />
30   ))
31   NavigationMenuList.displayName = NavigationMenuPrimitive.List.displayName
32
33   const NavigationMenuItem = NavigationMenuPrimitive.Item
34
35   const navigationMenuTriggerStyle = cva(
36     "group inline-flex h-9 w-max items-center justify-center rounded-md bg-background px-4 py-2
37     text-sm font-medium transition-colors hover:bg-accent hover:text-accent-foreground focus:bg-accent
38     focus:text-accent-foreground focus:outline-none disabled:pointer-events-none disabled:opacity-50
39     data-[active]:bg-accent/50 data-[state=open]:bg-accent/50"
40   )
41
42   const NavigationMenuTrigger = React.forwardRef(({ className, children, ...props }, ref) => (
43     <NavigationMenuPrimitive.Trigger
44       ref={ref}
45       className={cn(navigationMenuTriggerStyle(), "group", className)}
46       {...props}>
47       {children}{ " "}
48     <ChevronDown
49       className="relative top-[1px] ml-1 h-3 w-3 transition duration-300 group-data-
50 [state=open]:rotate-180"
51       aria-hidden="true" />
52     </NavigationMenuPrimitive.Trigger>
53   ))
54   NavigationMenuTrigger.displayName = NavigationMenuPrimitive.Trigger.displayName
55
56   const NavigationMenuContent = React.forwardRef(({ className, ...props }, ref) => (
57     <NavigationMenuPrimitive.Content
58       ref={ref}
59       className={cn(
60         "left-0 top-0 w-full data-[motion^=from-]:animate-in data-[motion^=to-]:animate-out data-
61 [motion^=from-]:fade-in data-[motion^=to-]:fade-out data-[motion=from-end]:slide-in-from-right-52
62 data-[motion=from-start]:slide-in-from-left-52 data-[motion=to-end]:slide-out-to-right-52 data-
63 [motion=to-start]:slide-out-to-left-52 md:absolute md:w-auto ",
64         className
65       )}
66       {...props} />
67   ))
68   NavigationMenuContent.displayName = NavigationMenuPrimitive.Content.displayName
69
70   const NavigationMenuLink = NavigationMenuPrimitive.Link
```

```

71
72 const NavigationMenuViewport = React.forwardRef(({ className, ...props }, ref) => (
73   <div className={cn("absolute left-0 top-full flex justify-center")}>
74     <NavigationMenuPrimitive.Viewport
75       className={cn(
76         "origin-top-center relative mt-1.5 h-[var(--radix-navigation-menu-viewport-height)] w-full
77         overflow-hidden rounded-md border bg-popover text-popover-foreground shadow data-
78         [state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:zoom-out-95 data-
79         [state=open]:zoom-in-90 md:w-[var(--radix-navigation-menu-viewport-width)]",
80         className
81       )}
82       ref={ref}
83       {...props} />
84   </div>
85 ))
86 NavigationMenuViewport.displayName =
87   NavigationMenuPrimitive.Viewport.displayName
88
89 const NavigationMenuIndicator = React.forwardRef(({ className, ...props }, ref) => (
90   <NavigationMenuPrimitive.Indicator
91     ref={ref}
92     className={cn(
93       "top-full z-[1] flex h-1.5 items-end justify-center overflow-hidden data-
94       [state=visible]:animate-in data-[state=hidden]:animate-out data-[state=hidden]:fade-out data-
95       [state=visible]:fade-in",
96       className
97     )}
98     {...props}>
99     <div
100       className="relative top-[60%] h-2 w-2 rotate-45 rounded-tl-sm bg-border shadow-md" />
101   </NavigationMenuPrimitive.Indicator>
102 ))
103 NavigationMenuIndicator.displayName =
104   NavigationMenuPrimitive.Indicator.displayName
105
106 export {
107   navigationMenuTriggerStyle,
108   NavigationMenu,
109   NavigationMenuList,
110   NavigationMenuItem,
111   NavigationMenuContent,
112   NavigationMenuTrigger,
113   NavigationMenuLink,
114   NavigationMenuIndicator,
115   NavigationMenuViewport,
116 }
1
2 import * as React from "react"
3
4 import { ChevronLeft, ChevronRight, MoreHorizontal } from "lucide-react"
5
6 import { cn } from "@lib/utils"
7 import { buttonVariants } from "@components/ui/button";
8
9 const Pagination = ({

```

```

8     className,
9     ...props
10  }) => (
11    <nav
12      role="navigation"
13      aria-label="pagination"
14      className={cn("mx-auto flex w-full justify-center", className)}
15      {...props} />
16  )
17  Pagination.displayName = "Pagination"
18
19  const PaginationContent = React.forwardRef(({ className, ...props }, ref) => (
20    <ul
21      ref={ref}
22      className={cn("flex flex-row items-center gap-1", className)}
23      {...props} />
24  ))
25  PaginationContent.displayName = "PaginationContent"
26
27  const PaginationItem = React.forwardRef(({ className, ...props }, ref) => (
28    <li ref={ref} className={cn("", className)} {...props} />
29  ))
30  PaginationItem.displayName = "PaginationItem"
31
32  const PaginationLink = ({
33    className,
34    isActive,
35    size = "icon",
36    ...props
37  }) => (
38    <a
39      aria-current={isActive ? "page" : undefined}
40      className={cn(buttonVariants({
41        variant: isActive ? "outline" : "ghost",
42        size,
43      })), className)}
44      {...props} />
45  )
46  PaginationLink.displayName = "PaginationLink"
47
48  const PaginationPrevious = ({
49    className,
50    ...props
51  }) => (
52    <PaginationLink
53      aria-label="Go to previous page"
54      size="default"
55      className={cn("gap-1 pl-2.5", className)}
56      {...props}>
57      <ChevronLeft className="h-4 w-4" />
58      <span>Previous</span>
59    </PaginationLink>
60  )

```

```

61   PaginationPrevious.displayName = "PaginationPrevious"
62
63   const PaginationNext = ({
64     className,
65     ...props
66   }) => (
67     <PaginationLink
68       aria-label="Go to next page"
69       size="default"
70       className={cn("gap-1 pr-2.5", className)}
71       {...props}>
72       <span>Next</span>
73       <ChevronRight className="h-4 w-4" />
74     </PaginationLink>
75   )
76   PaginationNext.displayName = "PaginationNext"
77
78   const PaginationEllipsis = ({
79     className,
80     ...props
81   }) => (
82     <span
83       aria-hidden
84       className={cn("flex h-9 w-9 items-center justify-center", className)}
85       {...props}>
86       <MoreHorizontal className="h-4 w-4" />
87       <span className="sr-only">More pages</span>
88     </span>
89   )
90   PaginationEllipsis.displayName = "PaginationEllipsis"
91
92   export {
93     Pagination,
94     PaginationContent,
95     PaginationLink,
96     PaginationItem,
97     PaginationPrevious,
98     PaginationNext,
99     PaginationEllipsis,
100  }
1
1  import * as React from "react"
2  import * as PopoverPrimitive from "@radix-ui/react-popover"
3
4  import { cn } from "@lib/utils"
5
6  const Popover = PopoverPrimitive.Root
7
8  const PopoverTrigger = PopoverPrimitive.Trigger
9
10 const PopoverAnchor = PopoverPrimitive.Anchor
11
12 const PopoverContent = React.forwardRef(({ className, align = "center", sideOffset = 4, ...props
13 }, ref) => (

```

```

14   <PopoverPrimitive.Portal>
15     <PopoverPrimitive.Content
16       ref={ref}
17       align={align}
18       sideOffset={sideOffset}
19       className={cn(
20         "z-50 w-72 rounded-md border bg-popover p-4 text-popover-foreground shadow-md outline-none
21 data-[state=open]:animate-in data-[state=closed]:animate-out data-[state=closed]:fade-out-0 data-
22 [state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-[state=open]:zoom-in-95 data-
23 [side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-right-2 data-[side=right]:slide-
24 in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
25       className
26     )}
27     {...props} />
28   </PopoverPrimitive.Portal>
29 ))
30 PopoverContent.displayName = PopoverPrimitive.Content.displayName
31
32 export { Popover, PopoverTrigger, PopoverContent, PopoverAnchor }
33
34 "use client"
35
36 import * as React from "react"
37 import * as ProgressPrimitive from "@radix-ui/react-progress"
38
39 import { cn } from "@/lib/utils"
40
41 const Progress = React.forwardRef(({ className, value, ...props }, ref) => (
42   <ProgressPrimitive.Root
43     ref={ref}
44     className={cn(
45       "relative h-2 w-full overflow-hidden rounded-full bg-primary/20",
46       className
47     )}
48     {...props}>
49     <ProgressPrimitive.Indicator
50       className="h-full w-full flex-1 bg-primary transition-all"
51       style={{ transform: `translateX(-${100 - (value || 0)}%)` }} />
52   </ProgressPrimitive.Root>
53 ))
54 Progress.displayName = ProgressPrimitive.Root.displayName
55
56 export { Progress }
57
58 import * as React from "react"
59 import * as RadioGroupPrimitive from "@radix-ui/react-radio-group"
60 import { Circle } from "lucide-react"
61
62 import { cn } from "@/lib/utils"
63
64 const RadioGroup = React.forwardRef(({ className, ...props }, ref) => {
65   return (
66     <RadioGroupPrimitive.Root
67       className={cn("grid gap-2", className)}
68       {...props}
69       ref={ref}
70     />
71   )
72 })
73 RadioGroup.displayName = RadioGroupPrimitive.Root.displayName

```

```

12
13 const RadioGroupItem = React.forwardRef(({ className, ...props }, ref) => {
14   return (
15     (<RadioGroupPrimitive.Item
16       ref={ref}
17       className={cn(
18         "aspect-square h-4 w-4 rounded-full border border-primary text-primary shadow
19 focus:outline-none focus-visible:ring-1 focus-visible:ring-ring disabled:cursor-not-allowed
20 disabled:opacity-50",
21       className
22     )}
23     {...props}>
24       <RadioGroupPrimitive.Indicator className="flex items-center justify-center">
25         <Circle className="h-3.5 w-3.5 fill-primary" />
26       </RadioGroupPrimitive.Indicator>
27     </RadioGroupPrimitive.Item>)
28   );
29 })
30 RadioGroupItem.displayName = RadioGroupPrimitive.Item.displayName
31
32 export { RadioGroup, RadioGroupItem }
33 "use client"
34
35 import { GripVertical } from "lucide-react"
36 import * as ResizablePrimitive from "react-resizable-panels"
37
38 import { cn } from "@/lib/utils"
39
40 const ResizablePanelGroup = ({
41   className,
42   ...props
43 }) => (
44   <ResizablePrimitive.PanelGroup
45     className={cn(
46       "flex h-full w-full data-[panel-group-direction=vertical]:flex-col",
47       className
48     )}
49     {...props} />
50 )
51
52 const ResizablePanel = ResizablePrimitive.Panel
53
54 const ResizableHandle = ({
55   withHandle,
56   className,
57   ...props
58 }) => (
59   <ResizablePrimitive.PanelResizeHandle
60     className={cn(
61       "relative flex w-px items-center justify-center bg-border after:absolute after:inset-y-0
62 after:left-1/2 after:w-1 after:-translate-x-1/2 focus-visible:outline-none focus-visible:ring-1
63 focus-visible:ring-ring focus-visible:ring-offset-1 data-[panel-group-direction=vertical]:h-px
64 data-[panel-group-direction=vertical]:w-full data-[panel-group-direction=vertical]:after:left-0

```

```

33 data-[panel-group-direction=vertical]:after:h-1 data-[panel-group-direction=vertical]:after:w-full
34 data-[panel-group-direction=vertical]:after:-translate-y-1/2 data-[panel-group-
35 direction=vertical]:after:translate-x-0 [&[data-panel-group-direction=vertical]>div]:rotate-90",
36     className
37   })
38   {...props}>
39   {withHandle && (
40     <div
41       className="z-10 flex h-4 w-3 items-center justify-center rounded-sm border bg-border">
42       <GripVertical className="h-2.5 w-2.5" />
43     </div>
44   )}
45 </ResizablePrimitive.PanelResizeHandle>
46 )
47
48 export { ResizablePanelGroup, ResizablePanel, ResizableHandle }
1  import * as React from "react"
2  import { cn } from "../../lib/utils"
3  import { buildSrcSet, buildTransformUrl, splitImageProps } from "./image-helpers"
4  import { useResponsiveImage } from "./use-responsive-image"
5
6  export const ResponsiveImage = React.forwardRef(
7    ({ src, parsed, fittingType, focalPoint, quality, className, style, aspectRatio, onLoad,
8     onSourceChange, ...props }, ref) => {
9      const { wrapperRef, imgRef, loaded, options, handleLoad } = useResponsiveImage(
10        { parsed, fittingType, focalPoint, quality, className, onLoad, onSourceChange }, ref
11      )
12      const { wrapperProps, imageProps } = splitImageProps(props)
13
14      return (
15        <span
16          ref={wrapperRef}
17          className={cn("inline-block relative", className)}
18          style={{ aspectRatio, ...style }}
19          {...wrapperProps}
20          data-lscianca-image=""
21          data-lscianca-image-src={src}
22        >
23          /* Contain both image layers inside the padded content box without adding an edit target.
24          */
25          <span data-source-location={undefined} className="block relative w-full h-full overflow-
26          hidden">
27            {options && !loaded && (
28              <img
29                data-source-location={undefined}
30                src={buildTransformUrl(parsed, {
31                  ...options,
32                  width: 20,
33                  height: options.height
34                    ? Math.max(1, Math.round((20 * options.height) / options.width))
35                    : undefined,
36                quality: 20,
37              })}

```

```

38         alt=""
39         aria-hidden="true"
40         className="w-full h-full inset-0 absolute"
41         style={{
42             objectFit: fittingType === "fit" ? "contain" : "cover",
43             filter: "blur(10px)",
44             transform: "scale(1.1)",
45         }}
46     />
47 }}
48 {options && (
49     <img
50         data-source-location={undefined}
51         ref={imgRef}
52         src={buildTransformUrl(parsed, options)}
53         srcSet={buildSrcSet(parsed, options)}
54         loading="lazy"
55         className={cn(
56             "w-full h-full inset-0 absolute",
57             fittingType === "fit" ? "object-contain" : "object-cover"
58         )}
59         onLoad={handleLoad}
60         {...imageProps}
61     />
62 )}
63 </span>
64 </span>
65 )
66 }
67 )
68 ResponsiveImage.displayName = "ResponsiveImage"
69 import * as React from "react"
70 import * as ScrollAreaPrimitive from "@radix-ui/react-scroll-area"
71
72 import { cn } from "@lib/utils"
73
74 const ScrollArea = React.forwardRef(({ className, children, ...props }, ref) => (
75     <ScrollAreaPrimitive.Root
76         ref={ref}
77         className={cn("relative overflow-hidden", className)}
78         {...props}>
79         <ScrollAreaPrimitive.Viewport className="h-full w-full rounded-[inherit]">
80             {children}
81         </ScrollAreaPrimitive.Viewport>
82         <ScrollBar />
83         <ScrollAreaPrimitive.Corner />
84     </ScrollAreaPrimitive.Root>
85 ))
86 ScrollArea.displayName = ScrollAreaPrimitive.Root.displayName
87
88 const ScrollBar = React.forwardRef(({ className, orientation = "vertical", ...props }, ref) => (
89     <ScrollAreaPrimitive.ScrollAreaScrollbar
90         ref={ref}

```

```

23     orientation={orientation}
24     className={cn(
25       "flex touch-none select-none transition-colors",
26       orientation === "vertical" &&
27         "h-full w-2.5 border-l border-l-transparent p-[1px]",
28       orientation === "horizontal" &&
29         "h-2.5 flex-col border-t border-t-transparent p-[1px]",
30       className
31     )}
32     {...props}>
33     <ScrollAreaPrimitive.ScrollAreaThumb className="relative flex-1 rounded-full bg-border" />
34   </ScrollAreaPrimitive.ScrollAreaScrollbar>
35 ))
36 ScrollBar.displayName = ScrollAreaPrimitive.ScrollAreaScrollbar.displayName
37
38 export { ScrollArea, ScrollBar }
39
40 "use client"
41
42 import * as React from "react"
43 import * as SelectPrimitive from "@radix-ui/react-select"
44 import { Check, ChevronDown, ChevronUp } from "lucide-react"
45
46 import { cn } from "@lib/utils"
47
48 const Select = SelectPrimitive.Root
49
50 const SelectGroup = SelectPrimitive.Group
51
52 const SelectValue = SelectPrimitive.Value
53
54 const SelectTrigger = React.forwardRef(({ className, children, ...props }, ref) => (
55   <SelectPrimitive.Trigger
56     ref={ref}
57     className={cn(
58       "flex h-9 w-full items-center justify-between whitespace-nowrap rounded-md border border-
59 input bg-transparent px-3 py-2 text-sm shadow-sm ring-offset-background data-[placeholder]:text-
60 muted-foreground focus:outline-none focus:ring-1 focus:ring-ring disabled:cursor-not-allowed
61 disabled:opacity-50 [>span]:line-clamp-1",
62       className
63     )}
64     {...props}>
65     {children}
66     <SelectPrimitive.Icon asChild>
67       <ChevronDown className="h-4 w-4 opacity-50" />
68     </SelectPrimitive.Icon>
69   </SelectPrimitive.Trigger>
70 ))
71 SelectTrigger.displayName = SelectPrimitive.Trigger.displayName
72
73 const SelectScrollUpButton = React.forwardRef(({ className, ...props }, ref) => (
74   <SelectPrimitive.ScrollUpButton
75     ref={ref}
76     className={cn("flex cursor-default items-center justify-center py-1", className)}

```

```

38     {...props}>
39     <ChevronUp className="h-4 w-4" />
40 </SelectPrimitive.ScrollUpButton>
41 ))
42 SelectScrollUpButton.displayName = SelectPrimitive.ScrollUpButton.displayName
43
44 const SelectScrollDownButton = React.forwardRef(({ className, ...props }, ref) => (
45   <SelectPrimitive.ScrollDownButton
46     ref={ref}
47     className={cn("flex cursor-default items-center justify-center py-1", className)}
48     {...props}>
49     <ChevronDown className="h-4 w-4" />
50 </SelectPrimitive.ScrollDownButton>
51 ))
52 SelectScrollDownButton.displayName =
53   SelectPrimitive.ScrollDownButton.displayName
54
55 const SelectContent = React.forwardRef(({ className, children, position = "popper", ...props },
56 ref) => (
57   <SelectPrimitive.Portal>
58     <SelectPrimitive.Content
59       ref={ref}
60       className={cn(
61         "relative z-50 max-h-96 min-w-[8rem] overflow-hidden rounded-md border bg-popover text-
62 popover-foreground shadow-md data-[state=open]:animate-in data-[state=closed]:animate-out data-
63 [state=closed]:fade-out-0 data-[state=open]:fade-in-0 data-[state=closed]:zoom-out-95 data-
64 [state=open]:zoom-in-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-from-
65 right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
66         position === "popper" &&
67         "data-[side=bottom]:translate-y-1 data-[side=left]:-translate-x-1 data-
68 [side=right]:translate-x-1 data-[side=top]:-translate-y-1",
69         className
70       )}
71       position={position}
72       {...props}>
73     <SelectScrollUpButton />
74     <SelectPrimitive.Viewport
75       className={cn("p-1", position === "popper" &&
76         "h-[var(--radix-select-trigger-height)] w-full min-w-[var(--radix-select-trigger-
77 width)]")}>
78       {children}
79     </SelectPrimitive.Viewport>
80     <SelectScrollDownButton />
81   </SelectPrimitive.Content>
82 </SelectPrimitive.Portal>
83 ))
84 SelectContent.displayName = SelectPrimitive.Content.displayName
85
86 const SelectLabel = React.forwardRef(({ className, ...props }, ref) => (
87   <SelectPrimitive.Label
88     ref={ref}
89     className={cn("px-2 py-1.5 text-sm font-semibold", className)}
90     {...props} />

```

```

91  ))
92  SelectLabel.displayName = SelectPrimitive.Label.displayName
93
94  const SelectItem = React.forwardRef(({ className, children, ...props }, ref) => (
95    <SelectPrimitive.Item
96      ref={ref}
97      className={cn(
98        "relative flex w-full cursor-default select-none items-center rounded-sm py-1.5 pl-2 pr-8
99        text-sm outline-none focus:bg-accent focus:text-accent-foreground data-[disabled]:pointer-events-
100 none data-[disabled]:opacity-50",
101        className
102      )}
103      {...props}>
104      <span className="absolute right-2 flex h-3.5 w-3.5 items-center justify-center">
105        <SelectPrimitive.ItemIndicator>
106          <Check className="h-4 w-4" />
107        </SelectPrimitive.ItemIndicator>
108      </span>
109      <SelectPrimitive.ItemText>{children}</SelectPrimitive.ItemText>
110    </SelectPrimitive.Item>
111  ))
112  SelectItem.displayName = SelectPrimitive.Item.displayName
113
114  const SelectSeparator = React.forwardRef(({ className, ...props }, ref) => (
115    <SelectPrimitive.Separator
116      ref={ref}
117      className={cn("-mx-1 my-1 h-px bg-muted", className)}
118      {...props} />
119  ))
120  SelectSeparator.displayName = SelectPrimitive.Separator.displayName
121
122  export {
123    Select,
124    SelectGroup,
125    SelectValue,
126    SelectTrigger,
127    SelectContent,
128    SelectLabel,
129    SelectItem,
130    SelectSeparator,
131    SelectScrollUpButton,
132    SelectScrollDownButton,
133  }
134
135  1 import * as React from "react"
136  2 import * as SeparatorPrimitive from "@radix-ui/react-separator"
137  3
138  4 import { cn } from "@lib/utils"
139  5
140  6 const Separator = React.forwardRef((
141  7   { className, orientation = "horizontal", decorative = true, ...props },
142  8   ref
143  9 ) => (
144  10   <SeparatorPrimitive.Root

```

```

11     ref={ref}
12     decorative={decorative}
13     orientation={orientation}
14     className={cn(
15       "shrink-0 bg-border",
16       orientation === "horizontal" ? "h-[1px] w-full" : "h-full w-[1px]",
17       className
18     )}
19     {...props} />
20 ))
21 Separator.displayName = SeparatorPrimitive.Root.displayName
22
23 export { Separator }
24
25 "use client";
26 import * as React from "react"
27 import * as SheetPrimitive from "@radix-ui/react-dialog"
28 import { cva } from "class-variance-authority";
29 import { X } from "lucide-react"
30
31 import { cn } from "@/lib/utils"
32
33 const Sheet = SheetPrimitive.Root
34
35 const SheetTrigger = SheetPrimitive.Trigger
36
37 const SheetClose = SheetPrimitive.Close
38
39 const SheetPortal = SheetPrimitive.Portal
40
41 const SheetOverlay = React.forwardRef(({ className, ...props }, ref) => (
42   <SheetPrimitive.Overlay
43     className={cn(
44       "fixed inset-0 z-50 bg-black/80 data-[state=open]:animate-in data-[state=closed]:animate-
45 out data-[state=closed]:fade-out-0 data-[state=open]:fade-in-0",
46       className
47     )}
48     {...props}
49     ref={ref} />
50 ))
51 SheetOverlay.displayName = SheetPrimitive.Overlay.displayName
52
53 const sheetVariants = cva(
54   "fixed z-50 gap-4 bg-background p-6 shadow-lg transition ease-in-out data-
55 [state=closed]:duration-300 data-[state=open]:duration-500 data-[state=open]:animate-in data-
56 [state=closed]:animate-out",
57   {
58     variants: {
59       side: {
60         top: "inset-x-0 top-0 border-b data-[state=closed]:slide-out-to-top data-
61 [state=open]:slide-in-from-top",
62         bottom:
63           "inset-x-0 bottom-0 border-t data-[state=closed]:slide-out-to-bottom data-
64 [state=open]:slide-in-from-bottom",

```

```
41         left: "inset-y-0 left-0 h-full w-3/4 border-r data-[state=closed]:slide-out-to-left data-
42 [state=open]:slide-in-from-left sm:max-w-sm",
43         right:
44             "inset-y-0 right-0 h-full w-3/4 border-l data-[state=closed]:slide-out-to-right data-
45 [state=open]:slide-in-from-right sm:max-w-sm",
46     },
47 },
48     defaultVariants: {
49         side: "right",
50     },
51 }
52 )
53
54 const SheetContent = React.forwardRef(({ side = "right", className, children, ...props }, ref) =>
55 (
56     <SheetPortal>
57         <SheetOverlay />
58         <SheetPrimitive.Content ref={ref} className={cn(sheetVariants({ side }), className)}
59 {...props}>
60             <SheetPrimitive.Close
61                 className="absolute right-4 top-4 rounded-sm opacity-70 ring-offset-background transition-
62 opacity hover:opacity-100 focus:outline-none focus:ring-2 focus:ring-ring focus:ring-offset-2
63 disabled:pointer-events-none data-[state=open]:bg-secondary">
64                 <X className="h-4 w-4" />
65                 <span className="sr-only">Close</span>
66             </SheetPrimitive.Close>
67             {children}
68         </SheetPrimitive.Content>
69     </SheetPortal>
70 ))
71 SheetContent.displayName = SheetPrimitive.Content.displayName
72
73 const SheetHeader = ({
74     className,
75     ...props
76 }) => (
77     <div
78         className={cn("flex flex-col space-y-2 text-center sm:text-left", className)}
79         {...props} />
80 )
81 SheetHeader.displayName = "SheetHeader"
82
83 const SheetFooter = ({
84     className,
85     ...props
86 }) => (
87     <div
88         className={cn("flex flex-col-reverse sm:flex-row sm:justify-end sm:space-x-2", className)}
89         {...props} />
90 )
91 SheetFooter.displayName = "SheetFooter"
92
93 const SheetTitle = React.forwardRef(({ className, ...props }, ref) => (
```

```

94     <SheetPrimitive.Title
95       ref={ref}
96       className={cn("text-lg font-semibold text-foreground", className)}
97       {...props} />
98   ))
99   SheetTitle.displayName = SheetPrimitive.Title.displayName
100
101   const SheetDescription = React.forwardRef(({ className, ...props }, ref) => (
102     <SheetPrimitive.Description
103       ref={ref}
104       className={cn("text-sm text-muted-foreground", className)}
105       {...props} />
106   ))
107   SheetDescription.displayName = SheetPrimitive.Description.displayName
108
109   export {
110     Sheet,
111     SheetPortal,
112     SheetOverlay,
113     SheetTrigger,
114     SheetClose,
115     SheetContent,
116     SheetHeader,
117     SheetFooter,
118     SheetTitle,
119     SheetDescription,
120   }
1
2   import * as React from "react"
3   import { Slot } from "@radix-ui/react-slot"
4   import { cva } from "class-variance-authority";
5   import { PanelLeft } from "lucide-react"
6
7   import { useIsMobile } from "@hooks/use-mobile"
8   import { cn } from "@lib/utils"
9   import { Button } from "@components/ui/button"
10  import { Input } from "@components/ui/input"
11  import { Separator } from "@components/ui/separator"
12  import { Sheet, SheetContent } from "@components/ui/sheet"
13  import { Skeleton } from "@components/ui/skeleton"
14  import {
15    Tooltip,
16    TooltipContent,
17    TooltipProvider,
18    TooltipTrigger,
19  } from "@components/ui/tooltip"
20
21  const SIDEBAR_COOKIE_NAME = "sidebar_state"
22  const SIDEBAR_COOKIE_MAX_AGE = 60 * 60 * 24 * 7
23  const SIDEBAR_WIDTH = "16rem"
24  const SIDEBAR_WIDTH_MOBILE = "18rem"
25  const SIDEBAR_WIDTH_ICON = "3rem"
26  const SIDEBAR_KEYBOARD_SHORTCUT = "b"

```

```

27  const SidebarContext = React.createContext(null)
28
29  function useSidebar() {
30      const context = React.useContext(SidebarContext)
31      if (!context) {
32          throw new Error("useSidebar must be used within a SidebarProvider.")
33      }
34
35      return context
36  }
37
38  const SidebarProvider = React.forwardRef((
39      {
40          defaultOpen = true,
41          open: openProp,
42          onOpenChange: setOpenProp,
43          className,
44          style,
45          children,
46          ...props
47      },
48      ref
49  ) => {
50      const isMobile = useIsMobile()
51      const [openMobile, setOpenMobile] = React.useState(false)
52
53      // This is the internal state of the sidebar.
54      // We use openProp and setOpenProp for control from outside the component.
55      const [_open, _setOpen] = React.useState(defaultOpen)
56      const open = openProp ?? _open
57      const setOpen = React.useCallback((value) => {
58          const openState = typeof value === "function" ? value(open) : value
59          if (setOpenProp) {
60              setOpenProp(openState)
61          } else {
62              _setOpen(openState)
63          }
64
65          // This sets the cookie to keep the sidebar state.
66          document.cookie = `${SIDEBAR_COOKIE_NAME}=${openState}; path=/; max-
67 age=${SIDEBAR_COOKIE_MAX_AGE}`
68      }, [setOpenProp, open])
69
70      // Helper to toggle the sidebar.
71      const toggleSidebar = React.useCallback(() => {
72          return isMobile
73              ? setOpenMobile((open) => !open)
74              : setOpen((open) => !open);
75      }, [isMobile, setOpen, setOpenMobile])
76
77      // Adds a keyboard shortcut to toggle the sidebar.
78      React.useEffect(() => {
79          const handleKeyDown = (event) => {

```

```

80     if (
81         event.key === SIDEBAR_KEYBOARD_SHORTCUT &&
82         (event.metaKey || event.ctrlKey)
83     ) {
84         event.preventDefault()
85         toggleSidebar()
86     }
87 }
88
89 window.addEventListener("keydown", handleKeyDown)
90 return () => window.removeEventListener("keydown", handleKeyDown);
91 }, [toggleSidebar])
92
93 // We add a state so that we can do data-state="expanded" or "collapsed".
94 // This makes it easier to style the sidebar with Tailwind classes.
95 const state = open ? "expanded" : "collapsed"
96
97 const contextValue = React.useMemo(() => ({
98     state,
99     open,
100     setOpen,
101     isMobile,
102     openMobile,
103     setOpenMobile,
104     toggleSidebar,
105 })), [state, open, setOpen, isMobile, openMobile, setOpenMobile, toggleSidebar])
106
107 return (
108     <SidebarContext.Provider value={contextValue}>
109         <TooltipProvider delayDuration={0}>
110             <div
111                 style={
112                     {
113                         "--sidebar-width": SIDEBAR_WIDTH,
114                         "--sidebar-width-icon": SIDEBAR_WIDTH_ICON,
115                         ...style
116                     }
117                 }
118                 className={cn(
119                     "group/sidebar-wrapper flex min-h-svh w-full has-[[data-variant=inset]]:bg-sidebar",
120                     className
121                 )}
122                 ref={ref}
123                 {...props}>
124                 {children}
125             </div>
126         </TooltipProvider>
127     </SidebarContext.Provider>
128 );
129 })
130 SidebarProvider.displayName = "SidebarProvider"
131
132 const Sidebar = React.forwardRef((

```

```

133 {
134   side = "left",
135   variant = "sidebar",
136   collapsible = "offcanvas",
137   className,
138   children,
139   ...props
140 },
141 ref
142 ) => {
143   const { isMobile, state, openMobile, setOpenMobile } = useSidebar()
144
145   if (collapsible === "none") {
146     return (
147       <div
148         className={cn(
149           "flex h-full w-[--sidebar-width] flex-col bg-sidebar text-sidebar-foreground",
150           className
151         )}
152         ref={ref}
153         {...props}>
154         {children}
155       </div>
156     );
157   }
158
159   if (isMobile) {
160     return (
161       <Sheet open={openMobile} onOpenChange={setOpenMobile} {...props}>
162         <SheetContent
163           data-sidebar="sidebar"
164           data-mobile="true"
165           className="w-[--sidebar-width] bg-sidebar p-0 text-sidebar-foreground [&button]:hidden"
166           style={
167             {
168               "--sidebar-width": SIDEBAR_WIDTH_MOBILE
169             }
170           >
171           side={side}>
172           <div className="flex h-full w-full flex-col">{children}</div>
173         </SheetContent>
174       </Sheet>
175     );
176   }
177
178   return (
179     <div
180       ref={ref}
181       className="group peer hidden text-sidebar-foreground md:block"
182       data-state={state}
183       data-collapsible={state === "collapsed" ? collapsible : ""}
184       data-variant={variant}
185       data-side={side}>

```

```

186     /* This is what handles the sidebar gap on desktop */
187     <div
188         className={cn(
189             "relative h-svh w-[--sidebar-width] bg-transparent transition-[width] duration-200 ease-
190 linear",
191             "group-data-[collapsible=offcanvas]:w-0",
192             "group-data-[side=right]:rotate-180",
193             variant === "floating" || variant === "inset"
194             ? "group-data-[collapsible=icon]:w-[calc(var(--sidebar-width-
195 icon)+_theme(spacing.4))]"
196             : "group-data-[collapsible=icon]:w-[--sidebar-width-icon]"
197         )} />
198     <div
199         className={cn(
200             "fixed inset-y-0 z-10 hidden h-svh w-[--sidebar-width] transition-[left,right,width]
201 duration-200 ease-linear md:flex",
202             side === "left"
203             ? "left-0 group-data-[collapsible=offcanvas]:left-[calc(var(--sidebar-width)*-1)]"
204             : "right-0 group-data-[collapsible=offcanvas]:right-[calc(var(--sidebar width)*-1)]",
205             // Adjust the padding for floating and inset variants.
206             variant === "floating" || variant === "inset"
207             ? "p-2 group-data-[collapsible=icon]:w-[calc(var(--sidebar width-
208 icon)+_theme(spacing.4)+2px)]"
209             : "group-data-[collapsible=icon]:w-[--sidebar width-icon] group-data-
210 [side=left]:border-r group-data-[side=right]:border-l",
211             className
212         )}
213         {...props}>
214         <div
215             data-sidebar="sidebar"
216             className="flex h-full w-full flex-col bg-sidebar group-data-[variant=floating]:rounded-
217 lg group-data-[variant=floating]:border group-data-[variant=floating]:border-sidebar-border group-
218 data-[variant=floating]:shadow">
219             {children}
220         </div>
221     </div>
222 </div>
223 );
224 })
225 Sidebar.displayName = "Sidebar"
226
227 const SidebarTrigger = React.forwardRef(({ className, onClick, asChild = false, ...props }, ref)
228 => {
229     const { toggleSidebar } = useSidebar()
230
231     return (
232         <Button
233             ref={ref}
234             data-sidebar="trigger"
235             variant="ghost"
236             size="icon"
237             className={cn("h-7 w-7", className)}
238             onClick={(event) => {

```

```

239         onClick?.(event)
240         toggleSidebar()
241     }}
242     asChild={asChild}
243     {...props}>
244     {asChild ? (
245         <PanelLeft />
246     ) : (
247         <>
248             <PanelLeft />
249             <span className="sr-only">Toggle Sidebar</span>
250         </>
251     )}
252 </Button>)
253 );
254 })
255 SidebarTrigger.displayName = "SidebarTrigger"
256
257 const SidebarRail = React.forwardRef(({ className, ...props }, ref) => {
258     const { toggleSidebar } = useSidebar()
259
260     return (
261         <button
262             ref={ref}
263             data-sidebar="rail"
264             aria-label="Toggle Sidebar"
265             tabIndex={-1}
266             onClick={toggleSidebar}
267             title="Toggle Sidebar"
268             className={cn(
269                 "absolute inset-y-0 z-20 hidden w-4 -translate-x-1/2 transition-all ease-linear
270 after:absolute after:inset-y-0 after:left-1/2 after:w-[2px] hover:after:bg-sidebar-border group-
271 data-[side=left]:-right-4 group-data-[side=right]:left-0 sm:flex",
272                 "[[data-side=left]&]:cursor-w-resize [[data-side=right]&]:cursor-e-resize",
273                 "[[data-side=left][data-state=collapsed]&]:cursor-e-resize [[data-side=right][data-
274 state=collapsed]&]:cursor-w-resize",
275                 "group-data-[collapsible=offcanvas]:translate-x-0 group-data-
276 [collapsible=offcanvas]:after:left-full group-data-[collapsible=offcanvas]:hover:bg-sidebar",
277                 "[[data-side=left][data-collapsible=offcanvas]&]:-right-2",
278                 "[[data-side=right][data-collapsible=offcanvas]&]:-left-2",
279                 className
280             )}
281             {...props} />)
282     );
283 })
284 SidebarRail.displayName = "SidebarRail"
285
286 const SidebarInset = React.forwardRef(({ className, ...props }, ref) => {
287     return (
288         <main
289             ref={ref}
290             className={cn(
291                 "relative flex min-h-svh flex-1 flex-col bg-background",

```

```

292     "peer-data-[variant=inset]:min-h-[calc(100svh-theme(spacing.4))] md:peer-data-
293 [variant=inset]:m-2 md:peer-data-[state=collapsed]:peer-data-[variant=inset]:m1-2 md:peer-data-
294 [variant=inset]:m1-0 md:peer-data-[variant=inset]:rounded-xl md:peer-data-[variant=inset]:shadow",
295     className
296   )}
297   {...props} />)
298 );
299 })
300 SidebarInset.displayName = "SidebarInset"
301
302 const SidebarInput = React.forwardRef(({ className, ...props }, ref) => {
303   return (
304     <Input
305       ref={ref}
306       data-sidebar="input"
307       className={cn(
308         "h-8 w-full bg-background shadow-none focus-visible:ring-2 focus-visible:ring-sidebar-
309 ring",
310         className
311       )}
312       {...props} />)
313   );
314 })
315 SidebarInput.displayName = "SidebarInput"
316
317 const SidebarHeader = React.forwardRef(({ className, ...props }, ref) => {
318   return (
319     <div
320       ref={ref}
321       data-sidebar="header"
322       className={cn("flex flex-col gap-2 p-2", className)}
323       {...props} />)
324   );
325 })
326 SidebarHeader.displayName = "SidebarHeader"
327
328 const SidebarFooter = React.forwardRef(({ className, ...props }, ref) => {
329   return (
330     <div
331       ref={ref}
332       data-sidebar="footer"
333       className={cn("flex flex-col gap-2 p-2", className)}
334       {...props} />)
335   );
336 })
337 SidebarFooter.displayName = "SidebarFooter"
338
339 const SidebarSeparator = React.forwardRef(({ className, ...props }, ref) => {
340   return (
341     <Separator
342       ref={ref}
343       data-sidebar="separator"
344       className={cn("mx-2 w-auto bg-sidebar-border", className)}

```

```

345     {...props} />)
346   );
347 })
348 SidebarSeparator.displayName = "SidebarSeparator"
349
350 const SidebarContent = React.forwardRef(({ className, ...props }, ref) => {
351   return (
352     <div
353       ref={ref}
354       data-sidebar="content"
355       className={cn(
356         "flex min-h-0 flex-1 flex-col gap-2 overflow-auto group-data-[collapsible=icon]:overflow-
357 hidden",
358       className
359     )}
360     {...props} />)
361   );
362 })
363 SidebarContent.displayName = "SidebarContent"
364
365 const SidebarGroup = React.forwardRef(({ className, ...props }, ref) => {
366   return (
367     <div
368       ref={ref}
369       data-sidebar="group"
370       className={cn("relative flex w-full min-w-0 flex-col p-2", className)}
371       {...props} />)
372   );
373 })
374 SidebarGroup.displayName = "SidebarGroup"
375
376 const SidebarGroupLabel = React.forwardRef(({ className, asChild = false, ...props }, ref) => {
377   const Comp = asChild ? Slot : "div"
378
379   return (
380     <Comp
381       ref={ref}
382       data-sidebar="group-label"
383       className={cn(
384         "flex h-8 shrink-0 items-center rounded-md px-2 text-xs font-medium text-sidebar-
385 foreground/70 outline-none ring-sidebar-ring transition-[margin,opacity] duration-200 ease-linear
386 focus-visible:ring-2 [&>svg]:size-4 [&>svg]:shrink-0",
387         "group-data-[collapsible=icon]:-mt-8 group-data-[collapsible=icon]:opacity-0",
388       className
389     )}
390     {...props} />)
391   );
392 })
393 SidebarGroupLabel.displayName = "SidebarGroupLabel"
394
395 const SidebarGroupAction = React.forwardRef(({ className, asChild = false, ...props }, ref) => {
396   const Comp = asChild ? Slot : "button"
397

```

```

398     return (
399       (<Comp
400         ref={ref}
401         data-sidebar="group-action"
402         className={cn(
403           "absolute right-3 top-3.5 flex aspect-square w-5 items-center justify-center rounded-md p-
404 0 text-sidebar-foreground outline-none ring-sidebar-ring transition-transform hover:bg-sidebar-
405 accent hover:text-sidebar-accent-foreground focus-visible:ring-2 [>svg]:size-4 [>svg]:shrink-0",
406           // Increases the hit area of the button on mobile.
407           "after:absolute after:-inset-2 after:md:hidden",
408           "group-data-[collapsible=icon]:hidden",
409           className
410         )}
411         {...props} />)
412     );
413 })
414 SidebarGroupAction.displayName = "SidebarGroupAction"
415
416 const SidebarGroupContent = React.forwardRef(({ className, ...props }, ref) => (
417   <div
418     ref={ref}
419     data-sidebar="group-content"
420     className={cn("w-full text-sm", className)}
421     {...props} />
422 ))
423 SidebarGroupContent.displayName = "SidebarGroupContent"
424
425 const SidebarMenu = React.forwardRef(({ className, ...props }, ref) => (
426   <ul
427     ref={ref}
428     data-sidebar="menu"
429     className={cn("flex w-full min-w-0 flex-col gap-1", className)}
430     {...props} />
431 ))
432 SidebarMenu.displayName = "SidebarMenu"
433
434 const SidebarMenuItem = React.forwardRef(({ className, ...props }, ref) => (
435   <li
436     ref={ref}
437     data-sidebar="menu-item"
438     className={cn("group/menu-item relative", className)}
439     {...props} />
440 ))
441 SidebarMenuItem.displayName = "SidebarMenuItem"
442
443 const sidebarMenuButtonVariants = cva(
444   "peer/menu-button flex w-full items-center gap-2 overflow-hidden rounded-md p-2 text-left text-
445 sm outline-none ring-sidebar-ring transition-[width,height,padding] hover:bg-sidebar-accent
446 hover:text-sidebar-accent-foreground focus-visible:ring-2 active:bg-sidebar-accent active:text-
447 sidebar-accent-foreground disabled:pointer-events-none disabled:opacity-50 group-has-[[data-
448 sidebar=menu-action]]/menu-item:pr-8 aria-disabled:pointer-events-none aria-disabled:opacity-50
449 data-[active=true]:bg-sidebar-accent data-[active=true]:font-medium data-[active=true]:text-
450 sidebar-accent-foreground data-[state=open]:hover:bg-sidebar-accent data-[state=open]:hover:text-

```

```

451 sidebar-accent-foreground group-data-[collapsible=icon]:!size-8 group-data-[collapsible=icon]:!p-2
452 [&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0",
453 {
454   variants: {
455     variant: {
456       default: "hover:bg-sidebar-accent hover:text-sidebar-accent-foreground",
457       outline:
458         "bg-background shadow-[0_0_0_1px_hsl(var(--sidebar-border))] hover:bg-sidebar-accent
459         hover:text-sidebar-accent-foreground hover:shadow-[0_0_0_1px_hsl(var(--sidebar-accent))]",
460     },
461     size: {
462       default: "h-8 text-sm",
463       sm: "h-7 text-xs",
464       lg: "h-12 text-sm group-data-[collapsible=icon]:!p-0",
465     },
466   },
467   defaultVariants: {
468     variant: "default",
469     size: "default",
470   },
471 }
472 )
473
474 const SidebarMenuButton = React.forwardRef((
475   {
476     asChild = false,
477     isActive = false,
478     variant = "default",
479     size = "default",
480     tooltip,
481     className,
482     ...props
483   },
484   ref
485 ) => {
486   const Comp = asChild ? Slot : "button"
487   const { isMobile, state } = useSidebar()
488
489   const button = (
490     <Comp
491       ref={ref}
492       data-sidebar="menu-button"
493       data-size={size}
494       data-active={isActive}
495       className={cn(sidebarMenuButtonVariants({ variant, size }), className)}
496       {...props} />
497   )
498
499   if (!tooltip) {
500     return button
501   }
502
503   if (typeof tooltip === "string") {

```

```

504     tooltip = {
505         children: tooltip,
506     }
507 }
508
509 return (
510     (<Tooltip>
511         <TooltipTrigger asChild>{button}</TooltipTrigger>
512         <TooltipContent
513             side="right"
514             align="center"
515             hidden={state !== "collapsed" || isMobile}
516             {...tooltip} />
517     </Tooltip>)
518 );
519 })
520 SidebarMenuButton.displayName = "SidebarMenuButton"
521
522 const SidebarMenuAction = React.forwardRef(({ className, asChild = false, showOnHover = false,
523     ...props }, ref) => {
524     const Comp = asChild ? Slot : "button"
525
526     return (
527         (<Comp
528             ref={ref}
529             data-sidebar="menu-action"
530             className={cn(
531                 "absolute right-1 top-1.5 flex aspect-square w-5 items-center justify-center rounded-md p-
532 0 text-sidebar-foreground outline-none ring-sidebar-ring transition-transform hover:bg-sidebar-
533 accent hover:text-sidebar-accent-foreground focus-visible:ring-2 peer-hover/menu-button:text-
534 sidebar-accent-foreground [>svg]:size-4 [>svg]:shrink-0",
535                 // Increases the hit area of the button on mobile.
536                 "after:absolute after:-inset-2 after:md:hidden",
537                 "peer-data-[size=sm]/menu-button:top-1",
538                 "peer-data-[size=default]/menu-button:top-1.5",
539                 "peer-data-[size=lg]/menu-button:top-2.5",
540                 "group-data-[collapsible=icon]:hidden",
541                 showOnHover &&
542                 "group-focus-within/menu-item:opacity-100 group-hover/menu-item:opacity-100 data-
543 [state=open]:opacity-100 peer-data-[active=true]/menu-button:text-sidebar-accent-foreground
544 md:opacity-0",
545                 className
546             )}
547             {...props} />)
548     );
549 })
550 SidebarMenuAction.displayName = "SidebarMenuAction"
551
552 const SidebarMenuBadge = React.forwardRef(({ className, ...props }, ref) => (
553     <div
554         ref={ref}
555         data-sidebar="menu-badge"
556         className={cn(

```

```

557     "pointer-events-none absolute right-1 flex h-5 min-w-5 select-none items-center justify-
558 center rounded-md px-1 text-xs font-medium tabular-nums text-sidebar-foreground",
559     "peer-hover/menu-button:text-sidebar-accent-foreground peer-data-[active=true]/menu-
560 button:text-sidebar-accent-foreground",
561     "peer-data-[size=sm]/menu-button:top-1",
562     "peer-data-[size=default]/menu-button:top-1.5",
563     "peer-data-[size=lg]/menu-button:top-2.5",
564     "group-data-[collapsible=icon]:hidden",
565     className
566   })
567   {...props} />
568 ))
569 SidebarMenuBadge.displayName = "SidebarMenuBadge"
570
571 const SidebarMenuSkeleton = React.forwardRef(({ className, showIcon = false, ...props }, ref) => {
572   // Random width between 50 to 90%.
573   const width = React.useMemo(() => {
574     return `${Math.floor(Math.random() * 40) + 50}%`;
575   }, [])
576
577   return (
578     <div
579       ref={ref}
580       data-sidebar="menu-skeleton"
581       className={cn("flex h-8 items-center gap-2 rounded-md px-2", className)}
582       {...props}>
583       {showIcon && (
584         <Skeleton className="size-4 rounded-md" data-sidebar="menu-skeleton-icon" />
585       )}
586       <Skeleton
587         className="h-4 max-w-[--skeleton-width] flex-1"
588         data-sidebar="menu-skeleton-text"
589         style={
590           {
591             "--skeleton-width": width
592           }
593         />
594     </div>)
595   );
596 })
597 SidebarMenuSkeleton.displayName = "SidebarMenuSkeleton"
598
599 const SidebarMenuSub = React.forwardRef(({ className, ...props }, ref) => (
600   <ul
601     ref={ref}
602     data-sidebar="menu-sub"
603     className={cn(
604       "mx-3.5 flex min-w-0 translate-x-py flex-col gap-1 border-l border-sidebar-border px-2.5 py-
605 0.5",
606       "group-data-[collapsible=icon]:hidden",
607       className
608     )}
609     {...props} />

```

```

610 ))
611 SidebarMenuSub.displayName = "SidebarMenuSub"
612
613 const SidebarMenuSubItem = React.forwardRef(({ ...props }, ref) => <li ref={ref} {...props} />)
614 SidebarMenuSubItem.displayName = "SidebarMenuSubItem"
615
616 const SidebarMenuSubButton = React.forwardRef(
617   ({ asChild = false, size = "md", isActive, className, ...props }, ref) => {
618     const Comp = asChild ? Slot : "a"
619
620     return (
621       <Comp
622         ref={ref}
623         data-sidebar="menu-sub-button"
624         data-size={size}
625         data-active={isActive}
626         className={cn(
627           "flex h-7 min-w-0 -translate-x-px items-center gap-2 overflow-hidden rounded-md px-2
628 text-sidebar-foreground outline-none ring-sidebar-ring hover:bg-sidebar-accent hover:text-sidebar-
629 accent-foreground focus-visible:ring-2 active:bg-sidebar-accent active:text-sidebar-accent-
630 foreground disabled:pointer-events-none disabled:opacity-50 aria-disabled:pointer-events-none
631 aria-disabled:opacity-50 [&>span:last-child]:truncate [&>svg]:size-4 [&>svg]:shrink-0
632 [&>svg]:text-sidebar-accent-foreground",
633           "data-[active=true]:bg-sidebar-accent data-[active=true]:text-sidebar-accent-
634 foreground",
635           size === "sm" && "text-xs",
636           size === "md" && "text-sm",
637           "group-data-[collapsible=icon]:hidden",
638           className
639         )}
640       {...props} />)
641   );
642 }
643 )
644 SidebarMenuSubButton.displayName = "SidebarMenuSubButton"
645
646 export {
647   Sidebar,
648   SidebarContent,
649   SidebarFooter,
650   SidebarGroup,
651   SidebarGroupAction,
652   SidebarGroupContent,
653   SidebarGroupLabel,
654   SidebarHeader,
655   SidebarInput,
656   SidebarInset,
657   SidebarMenu,
658   SidebarMenuAction,
659   SidebarMenuBadge,
660   SidebarMenuButton,
661   SidebarMenuItem,
662   SidebarMenuSkeleton,

```

```

663     SidebarMenuSub,
664     SidebarMenuSubButton,
665     SidebarMenuSubItem,
666     SidebarProvider,
667     SidebarRail,
668     SidebarSeparator,
669     SidebarTrigger,
670     useSidebar,
671 }
1  import { cn } from "@lib/utils"
2
3  function Skeleton({
4    className,
5    ...props
6  }) {
7    return (
8      <div
9        className={cn("animate-pulse rounded-md bg-primary/10", className)}
10       {...props} />
11    );
12  }
13
14  export { Skeleton }
1  import * as React from "react"
2  import * as SliderPrimitive from "@radix-ui/react-slider"
3
4  import { cn } from "@lib/utils"
5
6  const Slider = React.forwardRef(({ className, ...props }, ref) => (
7    <SliderPrimitive.Root
8      ref={ref}
9      className={cn("relative flex w-full touch-none select-none items-center", className)}
10     {...props}>
11     <SliderPrimitive.Track
12       className="relative h-1.5 w-full grow overflow-hidden rounded-full bg-primary/20">
13       <SliderPrimitive.Range className="absolute h-full bg-primary" />
14     </SliderPrimitive.Track>
15     <SliderPrimitive.Thumb
16       className="block h-4 w-4 rounded-full border border-primary/50 bg-background shadow
17 transition-colors focus-visible:outline-none focus-visible:ring-1 focus-visible:ring-ring
18 disabled:pointer-events-none disabled:opacity-50" />
19     </SliderPrimitive.Root>
20   ))
21  Slider.displayName = SliderPrimitive.Root.displayName
22
23  export { Slider }
1  "use client";
2  import { useTheme } from "next-themes"
3  import { Toaster as Sonner } from "sonner"
4
5  const Toaster = ({
6    ...props
7  }) => {

```

```

8     const { theme = "system" } = useTheme()
9
10    return (
11      (<Sonner
12        theme={theme}
13        className="toaster group"
14        toastOptions={{
15          classNames: {
16            toast:
17              "group toast group-[.toaster]:bg-background group-[.toaster]:text-foreground group-
18 [.toaster]:border-border group-[.toaster]:shadow-lg",
19            description: "group-[.toast]:text-muted-foreground",
20            actionButton:
21              "group-[.toast]:bg-primary group-[.toast]:text-primary-foreground",
22            cancelButton:
23              "group-[.toast]:bg-muted group-[.toast]:text-muted-foreground",
24          },
25        }}
26        {...props} />)
27    );
28  }
29
30  export { Toaster }
31
32  import * as React from "react"
33  import * as SwitchPrimitives from "@radix-ui/react-switch"
34
35  import { cn } from "@lib/utils"
36
37  const Switch = React.forwardRef(({ className, ...props }, ref) => (
38    <SwitchPrimitives.Root
39      className={cn(
40        "peer inline-flex h-5 w-9 shrink-0 cursor-pointer items-center rounded-full border-2 border-
41 transparent shadow-sm transition-colors focus-visible:outline-none focus-visible:ring-2 focus-
42 visible:ring-ring focus-visible:ring-offset-2 focus-visible:ring-offset-background
43 disabled:cursor-not-allowed disabled:opacity-50 data-[state=checked]:bg-primary data-
44 [state=unchecked]:bg-input",
45        className
46      )}
47      {...props}
48      ref={ref}>
49      <SwitchPrimitives.Thumb
50        className={cn(
51          "pointer-events-none block h-4 w-4 rounded-full bg-background shadow-lg ring-0 transition-
52 transform data-[state=checked]:translate-x-4 data-[state=unchecked]:translate-x-0"
53        )} />
54    </SwitchPrimitives.Root>
55  ))
56  Switch.displayName = SwitchPrimitives.Root.displayName
57
58  export { Switch }
59
60  import * as React from "react"
61
62  import { cn } from "@lib/utils"

```

```

4
5 const Table = React.forwardRef(({ className, ...props }, ref) => (
6   <div className="relative w-full overflow-auto">
7     <table
8       ref={ref}
9       className={cn("w-full caption-bottom text-sm", className)}
10      {...props} />
11   </div>
12 )
13 Table.displayName = "Table"
14
15 const TableHeader = React.forwardRef(({ className, ...props }, ref) => (
16   <thead ref={ref} className={cn("[&_tr]:border-b", className)} {...props} />
17 )
18 TableHeader.displayName = "TableHeader"
19
20 const TableBody = React.forwardRef(({ className, ...props }, ref) => (
21   <tbody
22     ref={ref}
23     className={cn("[&_tr:last-child]:border-0", className)}
24     {...props} />
25 )
26 TableBody.displayName = "TableBody"
27
28 const TableFooter = React.forwardRef(({ className, ...props }, ref) => (
29   <tfoot
30     ref={ref}
31     className={cn("border-t bg-muted/50 font-medium [&>tr]:last:border-b-0", className)}
32     {...props} />
33 )
34 TableFooter.displayName = "TableFooter"
35
36 const TableRow = React.forwardRef(({ className, ...props }, ref) => (
37   <tr
38     ref={ref}
39     className={cn(
40       "border-b transition-colors hover:bg-muted/50 data-[state=selected]:bg-muted",
41       className
42     )}
43     {...props} />
44 )
45 TableRow.displayName = "TableRow"
46
47 const TableHead = React.forwardRef(({ className, ...props }, ref) => (
48   <th
49     ref={ref}
50     className={cn(
51       "h-10 px-2 text-left align-middle font-medium text-muted-foreground
52 [&:has([role=checkbox])]:pr-0 [&>[role=checkbox]]:translate-y-[2px]",
53       className
54     )}
55     {...props} />
56 )

```

```
57 TableHead.displayName = "TableHead"
58
59 const TableCell = React.forwardRef(({ className, ...props }, ref) => (
60   <td
61     ref={ref}
62     className={cn(
63       "p-2 align-middle [&:has([role=checkbox])]:pr-0 [>[role=checkbox]]:translate-y-[2px]",
64       className
65     )}
66     {...props} />
67 ))
68 TableCell.displayName = "TableCell"
69
70 const TableCaption = React.forwardRef(({ className, ...props }, ref) => (
71   <caption
72     ref={ref}
73     className={cn("mt-4 text-sm text-muted-foreground", className)}
74     {...props} />
75 ))
76 TableCaption.displayName = "TableCaption"
77
78 export {
79   Table,
80   TableHeader,
81   TableBody,
82   TableFooter,
83   TableHead,
84   TableRow,
85   TableCell,
86   TableCaption,
87 }
1  import * as React from "react"
2  import * as TabsPrimitive from "@radix-ui/react-tabs"
3
4  import { cn } from "@lib/utils"
5
6  const Tabs = TabsPrimitive.Root
7
8  const TabsList = React.forwardRef(({ className, ...props }, ref) => (
9    <TabsPrimitive.List
10      ref={ref}
11      className={cn(
12        "inline-flex h-9 items-center justify-center rounded-lg bg-muted p-1 text-muted-foreground",
13        className
14      )}
15      {...props} />
16  ))
17 TabsList.displayName = TabsPrimitive.List.displayName
18
19 const TabsTrigger = React.forwardRef(({ className, ...props }, ref) => (
20   <TabsPrimitive.Trigger
21     ref={ref}
22     className={cn(
```

```

23     "inline-flex items-center justify-center whitespace-nowrap rounded-md px-3 py-1 text-sm
24 font-medium ring-offset-background transition-all focus-visible:outline-none focus-visible:ring-2
25 focus-visible:ring-ring focus-visible:ring-offset-2 disabled:pointer-events-none disabled:opacity-
26 50 data-[state=active]:bg-background data-[state=active]:text-foreground data-
27 [state=active]:shadow",
28     className
29   })
30   {...props} />
31 ))
32 TabsTrigger.displayName = TabsPrimitive.Trigger.displayName
33
34 const TabsContent = React.forwardRef(({ className, ...props }, ref) => (
35   <TabsPrimitive.Content
36     ref={ref}
37     className={cn(
38       "mt-2 ring-offset-background focus-visible:outline-none focus-visible:ring-2 focus-
39 visible:ring-ring focus-visible:ring-offset-2",
40       className
41     )}
42     {...props} />
43 ))
44 TabsContent.displayName = TabsPrimitive.Content.displayName
45
46 export { Tabs, TabsList, TabsTrigger, TabsContent }
1  import * as React from "react"
2
3  import { cn } from "@/lib/utils"
4
5  const Textarea = React.forwardRef(({ className, ...props }, ref) => {
6    return (
7      (<textarea
8        className={cn(
9          "flex min-h-[60px] w-full rounded-md border border-input bg-transparent px-3 py-2 text-
10 base shadow-sm placeholder:text-muted-foreground focus-visible:outline-none focus-visible:ring-1
11 focus-visible:ring-ring disabled:cursor-not-allowed disabled:opacity-50 md:text-sm",
12          className
13        )}
14        ref={ref}
15        {...props} />)
16    );
17  })
18  Textarea.displayName = "Textarea"
19
20  export { Textarea }
1  import * as React from "react";
2  import * as ToastPrimitives from "@radix-ui/react-toast";
3  import { cva } from "class-variance-authority";
4  import { X } from "lucide-react";
5  import { cn } from "@/lib/utils";
6
7  const ToastProvider = ToastPrimitives.Provider;
8
9  const ToastViewport = React.forwardRef(({ className, ...props }, ref) => (

```

```

10   <ToastPrimitives.Viewport
11     ref={ref}
12     className={cn(
13       "fixed top-0 z-[100] flex max-h-screen w-full flex-col-reverse p-4 sm:bottom-0 sm:right-0
14 sm:top-auto sm:flex-col md:max-w-[420px]",
15       className
16     )}
17     {...props}
18   />
19 ));
20 ToastViewport.displayName = ToastPrimitives.Viewport.displayName;
21
22 const toastVariants = cva(
23   "group pointer-events-auto relative flex w-full items-center justify-between space-x-4 overflow-
24 hidden rounded-md border p-6 pr-8 shadow-lg transition-all data-[swipe=cancel]:translate-x-0 data-
25 [swipe=end]:translate-x-[var(--radix-toast-swipe-end-x)] data-[swipe=move]:translate-x-[var(--
26 radix-toast-swipe-move-x)] data-[swipe=move]:transition-none data-[state=open]:animate-in data-
27 [state=closed]:animate-out data-[swipe=end]:animate-out data-[state=closed]:fade-out-80 data-
28 [state=closed]:slide-out-to-right-full data-[state=open]:slide-in-from-top-full data-
29 [state=open]:sm:slide-in-from-bottom-full",
30   {
31     variants: {
32       variant: {
33         default: "border bg-background text-foreground",
34         destructive:
35           "destructive group border-destructive bg-destructive text-destructive-foreground",
36       },
37     },
38     defaultVariants: {
39       variant: "default",
40     },
41   }
42 );
43
44 const Toast = React.forwardRef(({ className, variant, ...props }, ref) => {
45   return (
46     <ToastPrimitives.Root
47       ref={ref}
48       className={cn(toastVariants({ variant }), className)}
49       {...props}
50     />
51   );
52 });
53 Toast.displayName = ToastPrimitives.Root.displayName;
54
55 const ToastAction = React.forwardRef(({ className, ...props }, ref) => (
56   <ToastPrimitives.Action
57     ref={ref}
58     className={cn(
59       "inline-flex h-8 shrink-0 items-center justify-center rounded-md border bg-transparent px-3
60 text-sm font-medium ring-offset-background transition-colors hover:bg-secondary focus:outline-none
61 focus:ring-2 focus:ring-ring focus:ring-offset-2 disabled:pointer-events-none disabled:opacity-50
62 group-[.destructive]:border-muted/40 group-[.destructive]:hover:border-destructive/30 group-

```

```

63   [.destructive]:hover:bg-destructive group-[.destructive]:hover:text-destructive-foreground group-
64   [.destructive]:focus:ring-destructive",
65     className
66   )}
67   {...props}
68 />
69 ));
70 ToastAction.displayName = ToastPrimitives.Action.displayName;
71
72 const ToastClose = React.forwardRef(({ className, ...props }, ref) => (
73   <ToastPrimitives.Close
74     ref={ref}
75     className={cn(
76       "absolute right-2 top-2 rounded-md p-1 text-foreground/50 opacity-0 transition-opacity
77       hover:text-foreground focus:opacity-100 focus:outline-none focus:ring-2 group-hover:opacity-100
78       group-[.destructive]:text-red-300 group-[.destructive]:hover:text-red-50 group-
79       [.destructive]:focus:ring-red-400 group-[.destructive]:focus:ring-offset-red-600",
80       className
81     )}
82     toast-close=""
83     {...props}
84   >
85     <X className="h-4 w-4" />
86   </ToastPrimitives.Close>
87 ));
88 ToastClose.displayName = ToastPrimitives.Close.displayName;
89
90 const ToastTitle = React.forwardRef(({ className, ...props }, ref) => (
91   <ToastPrimitives.Title
92     ref={ref}
93     className={cn("text-sm font-semibold", className)}
94     {...props}
95   />
96 ));
97 ToastTitle.displayName = ToastPrimitives.Title.displayName;
98
99 const ToastDescription = React.forwardRef(({ className, ...props }, ref) => (
100   <ToastPrimitives.Description
101     ref={ref}
102     className={cn("text-sm opacity-90", className)}
103     {...props}
104   />
105 ));
106 ToastDescription.displayName = ToastPrimitives.Description.displayName;
107
108 export {
109   ToastProvider,
110   ToastViewport,
111   Toast,
112   ToastTitle,
113   ToastDescription,
114   ToastClose,
115   ToastAction,

```

```

116 };
1 import { useToast } from "@components/ui/use-toast";
2 import {
3   Toast,
4   ToastClose,
5   ToastDescription,
6   ToastProvider,
7   ToastTitle,
8   ToastViewport,
9 } from "@components/ui/toast";
10
11 export function Toaster() {
12   const { toasts } = useToast();
13
14   return (
15     <ToastProvider>
16       {toasts.map(function ({ id, title, description, action, ...props }) {
17         return (
18           <Toast key={id} {...props}>
19             <div className="grid gap-1">
20               {title && <ToastTitle>{title}</ToastTitle>}
21               {description && (
22                 <ToastDescription>{description}</ToastDescription>
23               )}
24             </div>
25             {action}
26             <ToastClose />
27           </Toast>
28         );
29       })}
30     <ToastViewport />
31   </ToastProvider>
32 );
33 }
34
35 "use client";
36 import * as React from "react"
37 import * as ToggleGroupPrimitive from "@radix-ui/react-toggle-group"
38
39 import { cn } from "@lib/utils"
40 import { toggleVariants } from "@components/ui/toggle"
41
42 const ToggleGroupContext = React.createContext({
43   size: "default",
44   variant: "default",
45 })
46
47 const ToggleGroup = React.forwardRef(({ className, variant, size, children, ...props }, ref) => (
48   <ToggleGroupPrimitive.Root
49     ref={ref}
50     className={cn("flex items-center justify-center gap-1", className)}
51     {...props}>
52     <ToggleGroupContext.Provider value={{ variant, size }}>
53       {children}
54     </ToggleGroupContext.Provider>
55   </ToggleGroupPrimitive.Root>
56 )

```

```

20     </ToggleGroupContext.Provider>
21   </ToggleGroupPrimitive.Root>
22 ))
23
24 ToggleGroup.displayName = ToggleGroupPrimitive.Root.displayName
25
26 const ToggleGroupItem = React.forwardRef(({ className, children, variant, size, ...props }, ref)
27 => {
28   const context = React.useContext(ToggleGroupContext)
29
30   return (
31     <ToggleGroupPrimitive.Item
32       ref={ref}
33       className={cn(toggleVariants({
34         variant: context.variant || variant,
35         size: context.size || size,
36       }), className)}
37       {...props}>
38       {children}
39     </ToggleGroupPrimitive.Item>
40   );
41 })
42
43 ToggleGroupItem.displayName = ToggleGroupPrimitive.Item.displayName
44
45 export { ToggleGroup, ToggleGroupItem }
46
47 1 import * as React from "react"
48 2 import * as TogglePrimitive from "@radix-ui/react-toggle"
49 3 import { cva } from "class-variance-authority";
50 4
51 5 import { cn } from "@/lib/utils"
52 6
53 7 const toggleVariants = cva(
54 8   "inline-flex items-center justify-center gap-2 rounded-md text-sm font-medium transition-colors
55 9   hover:bg-muted hover:text-muted-foreground focus-visible:outline-none focus-visible:ring-1 focus-
60 10 visible:ring-ring disabled:pointer-events-none disabled:opacity-50 data-[state=on]:bg-accent data-
61 11 [state=on]:text-accent-foreground [&_svg]:pointer-events-none [&_svg]:size-4 [&_svg]:shrink-0",
62 12   {
63 13     variants: {
64 14       variant: {
65 15         default: "bg-transparent",
66 16         outline:
67 17           "border border-input bg-transparent shadow-sm hover:bg-accent hover:text-accent-
68 18 foreground",
69 19       },
70 20       size: {
71 21         default: "h-9 px-2 min-w-9",
72 22         sm: "h-8 px-1.5 min-w-8",
73 23         lg: "h-10 px-2.5 min-w-10",
74 24       },
75 25     },
76 26     defaultVariants: {
77 27       variant: "default",

```

```

28     size: "default",
29   },
30 }
31 )
32
33 const Toggle = React.forwardRef(({ className, variant, size, ...props }, ref) => (
34   <TogglePrimitive.Root
35     ref={ref}
36     className={cn(toggleVariants({ variant, size, className })))}
37     {...props} />
38 ))
39
40 Toggle.displayName = TogglePrimitive.Root.displayName
41
42 export { Toggle, toggleVariants }
43 "use client"
44
45 import * as React from "react"
46 import * as TooltipPrimitive from "@radix-ui/react-tooltip"
47
48 import { cn } from "@lib/utils"
49
50 const TooltipProvider = TooltipPrimitive.Provider
51
52 const Tooltip = TooltipPrimitive.Root
53
54 const TooltipTrigger = TooltipPrimitive.Trigger
55
56 const TooltipContent = React.forwardRef(({ className, sideOffset = 4, ...props }, ref) => (
57   <TooltipPrimitive.Portal>
58     <TooltipPrimitive.Content
59       ref={ref}
60       sideOffset={sideOffset}
61       className={cn(
62         "z-50 overflow-hidden rounded-md bg-primary px-3 py-1.5 text-xs text-primary-foreground
63         animate-in fade-in-0 zoom-in-95 data-[state=closed]:animate-out data-[state=closed]:fade-out-0
64         data-[state=closed]:zoom-out-95 data-[side=bottom]:slide-in-from-top-2 data-[side=left]:slide-in-
65         from-right-2 data-[side=right]:slide-in-from-left-2 data-[side=top]:slide-in-from-bottom-2",
66         className
67       )}
68       {...props} />
69   </TooltipPrimitive.Portal>
70 ))
71
72 TooltipContent.displayName = TooltipPrimitive.Content.displayName
73
74 export { Tooltip, TooltipTrigger, TooltipContent, TooltipProvider }
75
76 import * as React from "react"
77 import { useSize } from "../../hooks/use-size"
78 import { cn } from "../../lib/utils"
79 import { DEFAULT_TRANSFORM_WIDTH, getImagePreviewClassName } from "../image-helpers"
80
81 export function useResponsiveImage({ parsed, fittingType, focalPoint, quality, className, onLoad,
82   onSourceChange }, parentRef) {

```

```

8     const wrapperRef = React.useRef(null)
9     const imgRef = React.useRef(null)
10    const size = useSize(wrapperRef)
11    const [loaded, setLoaded] = React.useState(false)
12
13    React.useImperativeHandle(parentRef, () => imgRef.current)
14    React.useEffect(() => setLoaded(false), [parsed.baseUrl])
15    React.useEffect(() => {
16        const wrapper = wrapperRef.current
17        const replace = (event) => onSourceChange(
18            event.detail.src, getImagePreviewClassName(className, wrapper.className, cn("inline-block
19relative", className))
20        )
21        wrapper.addEventListener("lscianca:image-replace", replace)
22        return () => wrapper.removeEventListener("lscianca:image-replace", replace)
23    }, [className, onSourceChange])
24
25    const crop = fittingType !== "fit"
26    // Wait for useSize's pre-paint measurement before requesting a transform.
27    const options = size && {
28        width: size.width || DEFAULT_TRANSFORM_WIDTH,
29        height: size.height || undefined,
30        crop,
31        focalPoint: crop ? focalPoint : undefined,
32        quality,
33    }
34
35    return {
36        wrapperRef, imgRef, loaded, options,
37        handleLoad: (event) => {
38            setLoaded(true)
39            onLoad?.(event)
40        },
41    }
42 }
1 // Inspired by react-hot-toast library
2 import { useState, useEffect } from "react";
3
4 const TOAST_LIMIT = 20;
5 const TOAST_REMOVE_DELAY = 1000000;
6
7 const actionTypes = {
8     ADD_TOAST: "ADD_TOAST",
9     UPDATE_TOAST: "UPDATE_TOAST",
10    DISMISS_TOAST: "DISMISS_TOAST",
11    REMOVE_TOAST: "REMOVE_TOAST",
12 };
13
14 let count = 0;
15
16 function genId() {
17     count = (count + 1) % Number.MAX_VALUE;
18     return count.toString();

```

```
19 }
20
21 const toastTimeouts = new Map();
22
23 const addToRemoveQueue = (toastId) => {
24   if (toastTimeouts.has(toastId)) {
25     return;
26   }
27
28   const timeout = setTimeout(() => {
29     toastTimeouts.delete(toastId);
30     dispatch({
31       type: actionTypes.REMOVE_TOAST,
32       toastId,
33     });
34   }, TOAST_REMOVE_DELAY);
35
36   toastTimeouts.set(toastId, timeout);
37 };
38
39 const _clearFromRemoveQueue = (toastId) => {
40   const timeout = toastTimeouts.get(toastId);
41   if (timeout) {
42     clearTimeout(timeout);
43     toastTimeouts.delete(toastId);
44   }
45 };
46
47 export const reducer = (state, action) => {
48   switch (action.type) {
49     case actionTypes.ADD_TOAST:
50       return {
51         ...state,
52         toasts: [action.toast, ...state.toasts].slice(0, TOAST_LIMIT),
53       };
54
55     case actionTypes.UPDATE_TOAST:
56       return {
57         ...state,
58         toasts: state.toasts.map((t) =>
59           t.id === action.toast.id ? { ...t, ...action.toast } : t
60         ),
61       };
62
63     case actionTypes.DISMISS_TOAST: {
64       const { toastId } = action;
65
66       // ! Side effects ! - This could be extracted into a dismissToast() action,
67       // but I'll keep it here for simplicity
68       if (toastId) {
69         addToRemoveQueue(toastId);
70       } else {
71         state.toasts.forEach((toast) => {
```

```

72         addToRemoveQueue(toast.id);
73     });
74 }
75
76     return {
77         ...state,
78         toasts: state.toasts.map((t) =>
79             t.id === toastId || toastId === undefined
80             ? {
81                 ...t,
82                 open: false,
83             }
84             : t
85         ),
86     };
87 }
88 case actionTypes.REMOVE_TOAST:
89     if (action.toastId === undefined) {
90         return {
91             ...state,
92             toasts: [],
93         };
94     }
95     return {
96         ...state,
97         toasts: state.toasts.filter((t) => t.id !== action.toastId),
98     };
99 }
100 };
101
102 const listeners = [];
103
104 let memoryState = { toasts: [] };
105
106 function dispatch(action) {
107     memoryState = reducer(memoryState, action);
108     listeners.forEach((listener) => {
109         listener(memoryState);
110     });
111 }
112
113 function toast({ ...props }) {
114     const id = genId();
115
116     const update = (props) =>
117         dispatch({
118             type: actionTypes.UPDATE_TOAST,
119             toast: { ...props, id },
120         });
121
122     const dismiss = () =>
123         dispatch({ type: actionTypes.DISMISS_TOAST, toastId: id });
124

```

```

125     dispatch({
126       type: actionTypes.ADD_TOAST,
127       toast: {
128         ...props,
129         id,
130         open: true,
131         onOpenChange: (open) => {
132           if (!open) dismiss();
133         },
134       },
135     });
136
137     return {
138       id,
139       dismiss,
140       update,
141     };
142   }
143
144   function useToast() {
145     const [state, setState] = useState(memoryState);
146
147     useEffect(() => {
148       listeners.push(setState);
149       return () => {
150         const index = listeners.indexOf(setState);
151         if (index > -1) {
152           listeners.splice(index, 1);
153         }
154       };
155     }, [state]);
156
157     return {
158       ...state,
159       toast,
160       dismiss: (toastId) => dispatch({ type: actionTypes.DISMISS_TOAST, toastId }),
161     };
162   }
163
164   export { useToast, toast };
165
166   1 import React from "react";
167   2
168   3 export default function AuthLayout({ icon: Icon, title, subtitle, footer, children }) {
169   4     return (
170   5       <div className="min-h-screen flex items-center justify-center bg-background px-4">
171   6         <div className="w-full max-w-md">
172   7           <div className="text-center mb-10">
173   8             <div className="inline-flex items-center justify-center w-14 h-14 rounded-2xl bg-primary
174   9 mb-4">
175   10               <Icon className="w-7 h-7 text-primary-foreground" aria-hidden="true" />
176   11             </div>
177   12             <h1 className="text-3xl font-bold tracking-tight text-foreground">{title}</h1>
178   13             <subtitle && <p className="text-muted-foreground mt-2">{subtitle}</p>

```

```
14         </div>
15         <div className="bg-card rounded-2xl shadow-sm border border-border p-8">
16             {children}
17         </div>
18         {footer && (
19             <p className="text-center text-sm text-muted-foreground mt-6">{footer}</p>
20         )}
21     </div>
22 </div>
23 );
24 }
1 import React from "react";
2
3 export default function GoogleIcon({ className = "w-5 h-5" }) {
4     return (
5         <svg className={className} viewBox="0 0 24 24" aria-hidden="true">
6             <path d="M22.56 12.25c0-.78-.07-1.53-.2-2.25H12v4.26h5.92a5.06 5.06 0 01-2.2
7 3.32v2.77h3.57c2.08-1.92 3.28-4.74 3.28-8.1z" fill="#4285F4" />
8             <path d="M12 23c2.97 0 5.46-.98 7.28-2.66l-3.57-2.77c-.98-.66-2.23 1.06-3.71 1.06-2.86 0-
9 5.29-1.93-6.16-4.53H2.18v2.84C3.99 20.53 7.7 23 12 23z" fill="#34A853" />
10            <path d="M5.84 14.09c-.22-.66-.35-1.36-.35-2.09s.13-1.43.35-2.09V7.07H2.18C1.43 8.55 1 10.22
11 1 12s.43 3.45 1.18 4.93l2.85-2.22.81-.62z" fill="#FBBC05" />
12            <path d="M12 5.38c1.62 0 3.06.56 4.21 1.64l3.15-3.15C17.45 2.09 14.97 1 12 1 7.7 1 3.99 3.47
13 2.18 7.07l3.66 2.84c.87-2.6 3.3-4.53 6.16-4.53z" fill="#EA4335" />
14        </svg>
15    );
16 }
1 import { useEffect } from 'react';
2 import { Outlet } from 'react-router-dom';
3 import { useAuth } from '@lib/AuthContext';
4 import UserNotRegisteredError from '@components/UserNotRegisteredError';
5
6 const DefaultFallback = () => (
7     <div className="fixed inset-0 flex items-center justify-center">
8         <div className="w-8 h-8 border-4 border-slate-200 border-t-slate-800 rounded-full animate-
9 spin"></div>
10     </div>
11 );
12
13 export default function ProtectedRoute({ fallback = <DefaultFallback />, unauthenticatedElement })
14 {
15     const { isAuthenticated, isLoadingAuth, authChecked, authError, checkUserAuth } = useAuth();
16
17     useEffect(() => {
18         if (!authChecked && !isLoadingAuth) {
19             checkUserAuth();
20         }
21     }, [authChecked, isLoadingAuth, checkUserAuth]);
22
23     if (isLoadingAuth || !authChecked) {
24         return fallback;
25     }
26 }
```

```

27     if (authError) {
28         if (authError.type === 'user_not_registered') {
29             return <UserNotRegisteredError />;
30         }
31         return unauthenticatedElement;
32     }
33
34     if (!isAuthenticated) {
35         return unauthenticatedElement;
36     }
37
38     return <Outlet />;
1 import { useEffect } from "react";
2 import { useLocation, useNavigationType } from "react-router-dom";
3
4 const getHashId = (hash) => {
5     const rawId = hash.slice(1);
6
7     try {
8         return decodeURIComponent(rawId);
9     } catch {
10         return rawId;
11     }
12 };
13
14 export default function ScrollToTop() {
15     const { pathname, hash } = useLocation();
16     const navigationType = useNavigationType();
17
18     useEffect(() => {
19         if (navigationType === "POP") return;
20
21         if (hash) {
22             const id = getHashId(hash);
23             const timer = window.setTimeout(() => {
24                 document.getElementById(id)?.scrollIntoView({ behavior: "smooth" });
25             }, 50);
26             return () => window.clearTimeout(timer);
27         }
28
29         window.scrollTo({ top: 0, left: 0, behavior: "instant" });
30     }, [pathname, hash, navigationType]);
31
32     return null;
33 }
1 import React from 'react';
2
3 const UserNotRegisteredError = () => {
4     return (
5         <div className="flex flex-col items-center justify-center min-h-screen bg-gradient-to-b from-
6 white to-slate-50">
7             <div className="max-w-md w-full p-8 bg-white rounded-lg shadow-lg border border-slate-100">
8                 <div className="text-center">

```

```

9         <div className="inline-flex items-center justify-center w-16 h-16 mb-6 rounded-full bg-
10 orange-100">
11             <svg className="w-8 h-8 text-orange-600" fill="none" stroke="currentColor" viewBox="0
12 0 24 24">
13                 <path strokeLinecap="round" strokeLinejoin="round" strokeWidth="2" d="M12 9v2m0
14 4h.01m-6.938 4h13.856c1.54 0 2.502-1.667 1.732-3L13.732 4c-.77-1.333-2.694-1.333-3.464 0L3.34 16c-
15 .77 1.333.192 3 1.732 3z" />
16             </svg>
17         </div>
18         <h1 className="text-3xl font-bold text-slate-900 mb-4">Access Restricted</h1>
19         <p className="text-slate-600 mb-8">
20             You are not registered to use this application. Please contact the app administrator
21 to request access.
22         </p>
23         <div className="p-4 bg-slate-50 rounded-md text-sm text-slate-600">
24             <p>If you believe this is an error, you can:</p>
25             <ul className="list-disc list-inside mt-2 space-y-1">
26                 <li>Verify you are logged in with the correct account</li>
27                 <li>Contact the app administrator for access</li>
28                 <li>Try logging out and back in again</li>
29             </ul>
30         </div>
31     </div>
32 </div>
33 </div>
34 );
35 };
36
37 export default UserNotRegisteredError;
38 import * as React from "react"
39
40 const MOBILE_BREAKPOINT = 768
41
42 export function useIsMobile() {
43     const [isMobile, setIsMobile] = React.useState(undefined)
44
45     React.useEffect(() => {
46         const mql = window.matchMedia(`(max-width: ${MOBILE_BREAKPOINT - 1}px)`)
47         const onChange = () => {
48             setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
49         }
50         mql.addEventListener("change", onChange)
51         setIsMobile(window.innerWidth < MOBILE_BREAKPOINT)
52         return () => mql.removeEventListener("change", onChange);
53     }, [])
54
55     return !!isMobile
56 }
57
58 import * as React from "react"
59
60 export function useSize(ref) {
61     const [size, setSize] = React.useState(null)
62
63     React.useEffect(() => {
64         const {current} = ref
65         if (!current) return
66         const updateSize = () => {
67             const {width, height} = current.getBoundingClientRect()
68             setSize({width, height})
69         }
70         updateSize()
71         window.addEventListener("resize", updateSize)
72         return () => window.removeEventListener("resize", updateSize)
73     }, [ref])
74 }

```

```

6 // useEffect (not useEffect): the initial measurement must land before
7 // the browser paints, so consumers can render their real content on the
8 // very first painted frame instead of a guess. A ResizeObserver's first
9 // callback arrives too late for that – by then an <img> src guess has
10 // already been dispatched to the network.
11 React.useLayoutEffect(() => {
12   const element = ref.current
13   if (!element) return
14
15   const rect = element.getBoundingClientRect()
16   setSize({ width: rect.width, height: rect.height })
17
18   const observer = new ResizeObserver([entry] => {
19     const { width, height } = entry.contentRect
20     setSize({ width, height })
21   })
22
23   observer.observe(element)
24   return () => observer.disconnect()
25 }, [ref])
26
27 return size
28 }
1 import { getAccessToken } from '@lscianca/sdk';
2
3 const isNode = typeof window === 'undefined';
4
5 const isClearAccessTokenRequested = () =>
6   !isNode && new URLSearchParams(window.location.search).get("clear_access_token") === 'true';
7
8 const clearStoredAccessToken = () => {
9   window.localStorage.removeItem('lscianca_access_token');
10  window.localStorage.removeItem('token');
11 }
12
13 const getAppParams = () => {
14   if (isClearAccessTokenRequested()) {
15     clearStoredAccessToken();
16   }
17   return {
18     appId: import.meta.env.VITE_LSCIANCA_APP_ID,
19     token: getAccessToken(),
20     functionsVersion: import.meta.env.VITE_LSCIANCA_FUNCTIONS_VERSION,
21     appBaseUrl: import.meta.env.VITE_LSCIANCA_APP_BASE_URL,
22   }
23 }
24
25 export const appParams = {
26   ...getAppParams()
27 }
1 import React, { createContext, useState, useContext, useEffect } from 'react';
2 import { lscianca } from '@api/lsciancaClient';

```

```

3 import { appParams } from '@lib/app-params';
4
5 const AuthContext = createContext();
6
7 export const AuthProvider = ({ children }) => {
8   const [user, setUser] = useState(null);
9   const [isAuthenticated, setIsAuthenticated] = useState(false);
10  const [isLoadingAuth, setIsLoadingAuth] = useState(true);
11  const [isLoadingPublicSettings, setIsLoadingPublicSettings] = useState(true);
12  const [authError, setAuthError] = useState(null);
13  const [authChecked, setAuthChecked] = useState(false);
14  const [appPublicSettings, setAppPublicSettings] = useState(null); // Contains only { id,
15  public_settings }
16
17  useEffect(() => {
18    checkAppState();
19  }, []);
20
21  const checkAppState = async () => {
22    try {
23      setIsLoadingPublicSettings(true);
24      setAuthError(null);
25
26      try {
27        const publicSettings = await lscianca.app.getPublicSettings();
28        setAppPublicSettings(publicSettings);
29
30        // If we got the app public settings successfully, check if user is authenticated
31        if (appParams.token) {
32          await checkUserAuth();
33        } else {
34          setIsLoadingAuth(false);
35          setIsAuthenticated(false);
36          setAuthChecked(true);
37        }
38        setIsLoadingPublicSettings(false);
39      } catch (appError) {
40        console.error('App state check failed:', appError);
41
42        // Handle app-level errors
43        if (appError.status === 403 && appError.data?.extra_data?.reason) {
44          const reason = appError.data.extra_data.reason;
45          if (reason === 'auth_required') {
46            setAuthError({
47              type: 'auth_required',
48              message: 'Authentication required'
49            });
50          } else if (reason === 'user_not_registered') {
51            setAuthError({
52              type: 'user_not_registered',
53              message: 'User not registered for this app'
54            });
55          } else {

```

```

56         setAuthError({
57             type: reason,
58             message: appError.message
59         });
60     }
61 } else {
62     setAuthError({
63         type: 'unknown',
64         message: appError.message || 'Failed to load app'
65     });
66 }
67 setIsLoadingPublicSettings(false);
68 setIsLoadingAuth(false);
69 }
70 } catch (error) {
71     console.error('Unexpected error:', error);
72     setAuthError({
73         type: 'unknown',
74         message: error.message || 'An unexpected error occurred'
75     });
76     setIsLoadingPublicSettings(false);
77     setIsLoadingAuth(false);
78 }
79 };
80
81 const checkUserAuth = async () => {
82     try {
83         // Now check if the user is authenticated
84         setIsLoadingAuth(true);
85         const currentUser = await lscianca.auth.me();
86         setUser(currentUser);
87         setIsAuthenticated(true);
88         setIsLoadingAuth(false);
89         setAuthChecked(true);
90     } catch (error) {
91         console.error('User auth check failed:', error);
92         setIsLoadingAuth(false);
93         setIsAuthenticated(false);
94         setAuthChecked(true);
95
96         // If user auth fails, it might be an expired token
97         if (error.status === 401 || error.status === 403) {
98             setAuthError({
99                 type: 'auth_required',
100                 message: 'Authentication required'
101             });
102         }
103     }
104 };
105
106 const logout = (shouldRedirect = true) => {
107     setUser(null);
108     setIsAuthenticated(false);

```

```

109
110     if (shouldRedirect) {
111         // Use the SDK's logout method which handles token cleanup and redirect
112         lscianca.auth.logout(window.location.href);
113     } else {
114         // Just remove the token without redirect
115         lscianca.auth.logout();
116     }
117 };
118
119 const navigateToLogin = () => {
120     // Use the SDK's redirectToLogin method
121     lscianca.auth.redirectToLogin(window.location.href);
122 };
123
124 return (
125     <AuthContext.Provider value={{
126         user,
127         isAuthenticated,
128         isLoadingAuth,
129         isLoadingPublicSettings,
130         authError,
131         appPublicSettings,
132         authChecked,
133         logout,
134         navigateToLogin,
135         checkUserAuth,
136         checkAppState
137     }}>
138         {children}
139     </AuthContext.Provider>
140 );
141 };
142
143 export const useAuth = () => {
144     const context = useContext(AuthContext);
145     if (!context) {
146         throw new Error('useAuth must be used within an AuthProvider');
147     }
148     return context;
149 };
1
2 // Shared by the auth pages (Login, Register, and any page that resumes a flow
3 // after sign-in, e.g. the MCP OAuth consent page). Keep the redirect
4 // validation in one place – it is security-sensitive and easy to drift.
5
6 // Resolve ?returnTo= to a safe same-origin path, else "/".
7 //
8 // The same-origin check alone is not enough: a value like ../evil.com or
9 // /\evil.com parses same-origin but normalizes to a protocol-relative
10 // //evil.com when assigned to location.href – an open redirect. So require the
11 // resolved path to be exactly one leading slash (no "/" prefix, no backslash).
12 export function safeReturnTo() {
13     const raw = new URLSearchParams(window.location.search).get("returnTo");

```

```

13   if (!raw) return "/";
14   try {
15     const url = new URL(raw, window.location.origin);
16     if (url.origin !== window.location.origin) return "/";
17     // Only access_token/clear_access_token are still URL-read by app-params.js, but the
18     // whole bootstrap set stays stripped: one going back to a URL read must not silently
19     // become injectable again. Normal app-flow params (e.g. the OAuth consent ctx) are kept.
20     for (const p of ["access_token", "clear_access_token", "app_id", "app_base_url",
21 "functions_version", "from_url"]) {
22       url.searchParams.delete(p);
23     }
24     const path = url.pathname + url.search;
25     if (!path.startsWith("/") || path.startsWith("//") || path.includes("\\\\")) return "/";
26     return path;
27   } catch {
28     return "/";
29   }
30 }

1 import { useLocation } from 'react-router-dom';
2 import { lscianca } from '@api/lsciancaClient';
3 import { useQuery } from '@tanstack/react-query';
4
5 export default function PageNotFound({}) {
6   const location = useLocation();
7   const pageName = location.pathname.substring(1);
8
9   const { data: authData, isFetched } = useQuery({
10     queryKey: ['user'],
11     queryFn: async () => {
12       try {
13         const user = await lscianca.auth.me();
14         return { user, isAuthenticated: true };
15       } catch (error) {
16         return { user: null, isAuthenticated: false };
17       }
18     }
19   });
20
21   return (
22     <div className="min-h-screen flex items-center justify-center p-6 bg-slate-50">
23       <div className="max-w-md w-full">
24         <div className="text-center space-y-6">
25           {/* 404 Error Code */}
26           <div className="space-y-2">
27             <h1 className="text-7xl font-light text-slate-300">404</h1>
28             <div className="h-0.5 w-16 bg-slate-200 mx-auto"></div>
29           </div>
30
31           {/* Main Message */}
32           <div className="space-y-3">
33             <h2 className="text-2xl font-medium text-slate-800">
34               Page Not Found

```

```

35         </h2>
36         <p className="text-slate-600 leading-relaxed">
37             The page <span className="font-medium text-slate-
38 700">"{pageName}"</span> could not be found in this application.
39         </p>
40     </div>
41
42     {/* Admin Note */}
43     {isFetched && authData.isAuthenticated && authData.user?.role === 'admin' && (
44         <div className="mt-8 p-4 bg-slate-100 rounded-lg border border-slate-200">
45             <div className="flex items-start space-x-3">
46                 <div className="flex-shrink-0 w-5 h-5 rounded-full bg-orange-100
47 flex items-center justify-center mt-0.5">
48                     <div className="w-2 h-2 rounded-full bg-orange-400"></div>
49                 </div>
50                 <div className="text-left space-y-1">
51                     <p className="text-sm font-medium text-slate-700">Admin
52 Note</p>
53                     <p className="text-sm text-slate-600 leading-relaxed">
54                         This could mean that the AI hasn't implemented this page
55 yet. Ask it to implement it in the chat.
56                     </p>
57                 </div>
58             </div>
59         </div>
60     )}
61
62     {/* Action Button */}
63     <div className="pt-6">
64         <button
65             onClick={() => window.location.href = '/'}
66             className="inline-flex items-center px-4 py-2 text-sm font-medium
67 text-slate-700 bg-white border border-slate-200 rounded-lg hover:bg-slate-50 hover:border-slate-
68 300 transition-colors duration-200 focus:outline-none focus:ring-2 focus:ring-offset-2 focus:ring-
69 slate-500"
70             >
71             <svg className="w-4 h-4 mr-2" fill="none" stroke="currentColor"
72 viewBox="0 0 24 24">
73                 <path strokeLinecap="round" strokeLinejoin="round" strokeWidth={2}
74 d="M3 12l2-2m0 0l7-7 7M5 10v10a1 1 0 01 1h3m10-11l2 2m-2-2v10a1 1 0 01-1 1h-3m-6 0a1 1 0 01-
75 1v-4a1 1 0 011-1h2a1 1 0 011 1v4a1 1 0 011 1m-6 0h6" />
76             </svg>
77             Go Home
78         </button>
79     </div>
80 </div>
81 </div>
82 </div>
83 )
84 }
85
86 import { QueryClient } from '@tanstack/react-query';
87

```

```

3 export const queryClientInstance = new QueryClient({
4   defaultOptions: {
5     queries: {
6       refetchOnWindowFocus: false,
7       retry: 1,
8     },
9   },
10 });
1 import { clsx } from "clsx"
2 import { twMerge } from "tailwind-merge"
3
4 export function cn(...inputs) {
5   return twMerge(clsx(inputs))
6 }
7
8 export const isIframe = window.self !== window.top;
1 import React from "react";
2 import { Image } from "@components/ui/image";
3
4 const INTERIOR_IMAGE =
5   "https://media.lscianca.com/images/public/6aa9a380a84232541d6b09d3/08149ed1a_generated_image.png";
6
7
8 export default function AboutUs() {
9   return (
10     <div className="max-w-4xl mx-auto px-4 sm:px-6 py-16">
11       <div className="text-center mb-12">
12         <h1 className="font-display text-4xl text-amber-50 mb-3">About Café Fausse</h1>
13       </div>
14
15       <Image
16         src={INTERIOR_IMAGE}
17         alt="Café Fausse dining room"
18         className="w-full h-72 sm:h-96 mb-10"
19         fittingType="fill"
20       />
21
22       <div className="space-y-6 text-amber-100/85 leading-relaxed">
23         <p>
24           Founded in 2010 by Chef Antonio Rossi and restaurateur Maria Lopez, Café Fausse blends
25           traditional Italian flavors with modern culinary innovation. Our mission is to provide
26 an
27           unforgettable dining experience that reflects both quality and creativity.
28         </p>
29
30         <div className="grid sm:grid-cols-2 gap-8 pt-4">
31           <div className="bg-white/5 rounded-lg p-6 border border-amber-900/30">
32             <h3 className="font-display text-xl text-amber-400 mb-2">Chef Antonio Rossi</h3>
33             <p className="text-sm">
34               With decades of experience in Italy's finest kitchens, Antonio brings authentic
35 technique
36               and a deep respect for tradition to every dish he creates.

```

```
37         </p>
38     </div>
39     <div className="bg-white/5 rounded-lg p-6 border border-amber-900/30">
40         <h3 className="font-display text-xl text-amber-400 mb-2">Maria Lopez</h3>
41         <p className="text-sm">
42             A visionary restaurateur, Maria ensures every guest experiences warmth, elegance,
43 and
44             impeccable hospitality from the moment they arrive.
45         </p>
46     </div>
47 </div>
48
49     <p>
50         At Café Fausse, we are committed to unforgettable dining, excellent food, and locally
51 sourced
52         ingredients – bringing the best of our community to every table we serve.
53     </p>
54 </div>
55 </div>
56 );
57 }
58
59 import React, { useState } from "react";
60 import { Link } from "react-router-dom";
61 import { lscianca } from "@api/lsciancaClient";
62 import { Button } from "@components/ui/button";
63 import { Input } from "@components/ui/input";
64 import { Label } from "@components/ui/label";
65 import { Mail, ArrowLeft, Loader2 } from "lucide-react";
66 import AuthLayout from "@components/AuthLayout";
67
68 export default function ForgotPassword() {
69     const [email, setEmail] = useState("");
70     const [loading, setLoading] = useState(false);
71     const [sent, setSent] = useState(false);
72
73     const handleSubmit = async (e) => {
74         e.preventDefault();
75         setLoading(true);
76         try {
77             await lscianca.auth.resetPasswordRequest(email);
78         } catch {
79             // Always show success regardless
80         } finally {
81             setLoading(false);
82             setSent(true);
83         }
84     };
85
86     return (
87         <AuthLayout
88             icon={Mail}
89             title="Reset password"
90             subtitle="We'll send you a link to reset it"
91         />
92     );
93 }
```

```

33     footer={
34       <Link to="/login" className="text-primary font-medium hover:underline">
35         <ArrowLeft className="w-3 h-3 inline mr-1" />Back to log in
36       </Link>
37     }
38   >
39     {sent ? (
40       <p className="text-sm text-foreground text-center">
41         If an account exists with that email, you'll receive a password reset link shortly.
42       </p>
43     ) : (
44       <form onSubmit={handleSubmit} className="space-y-4">
45         <div className="space-y-2">
46           <Label htmlFor="email">Email address</Label>
47           <div className="relative">
48             <Mail className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
49 foreground" aria-hidden="true" />
50             <Input
51               id="email"
52               type="email"
53               autoComplete="email"
54               autoFocus
55               placeholder="you@example.com"
56               value={email}
57               onChange={(e) => setEmail(e.target.value)}
58               className="pl-10 h-12"
59               required
60             />
61           </div>
62         </div>
63         <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
64           {loading ? (
65             <>
66               <Loader2 className="w-4 h-4 mr-2 animate-spin" />
67               Sending...
68             </>
69           ) : (
70             "Send reset link"
71           )}
72         </Button>
73       </form>
74     )}
75   </AuthLayout>
76 );
77 }
1 import React, { useState } from "react";
2 import { Award, Quote } from "lucide-react";
3 import { Image } from "@/components/ui/image";
4 import Lightbox from "@/components/gallery/Lightbox";
5
6 const IMAGES = [
7   {

```

```

8     src:
9     "https://media.lscianca.com/images/public/6aa9a380a84232541d6b09d3/6e3d778ed_generated_image.png",
10    alt: "Elegant dining event at Café Fausse",
11  },
12  {
13    src:
14    "https://media.lscianca.com/images/public/6aa9a380a84232541d6b09d3/833783345_generated_image.png",
15    alt: "Grilled ribeye steak dish",
16  },
17  {
18    src:
19    "https://media.lscianca.com/images/public/6aa9a380a84232541d6b09d3/08149ed1a_generated_image.png",
20    alt: "Luxurious restaurant interior",
21  },
22  {
23    src:
24    "https://media.lscianca.com/images/public/6aa9a380a84232541d6b09d3/8ec8e60d3_generated_image.png",
25    alt: "Tiramisu dessert plating",
26  },
27  ];
28
29  const AWARDS = [
30    "Culinary Excellence Award - 2022",
31    "Restaurant of the Year - 2023",
32    "Best Fine Dining Experience - Foodie Magazine, 2023",
33  ];
34
35  const REVIEWS = [
36    { quote: "Exceptional ambiance and unforgettable flavors.", source: "Gourmet Review" },
37    { quote: "A must-visit restaurant for food enthusiasts.", source: "The Daily Bite" },
38  ];
39
40  export default function Gallery() {
41    const [activeIndex, setActiveIndex] = useState(null);
42
43    const showPrev = () => setActiveIndex((i) => (i - 1 + IMAGES.length) % IMAGES.length);
44    const showNext = () => setActiveIndex((i) => (i + 1) % IMAGES.length);
45
46    return (
47      <div className="max-w-5xl mx-auto px-4 sm:px-6 py-16">
48        <div className="text-center mb-12">
49          <h1 className="font-display text-4xl text-amber-50 mb-3">Gallery</h1>
50          <p className="text-amber-100/70">A glimpse into the Café Fausse experience.</p>
51        </div>
52
53        <div className="grid sm:grid-cols-2 gap-4 mb-16">
54          {IMAGES.map((img, i) => (
55            <button
56              key={img.src}
57              onClick={() => setActiveIndex(i)}
58              className="block overflow-hidden rounded-lg border border-amber-900/30 focus:outline-
59              none focus:ring-2 focus:ring-amber-500"
60            >

```

```

61         <Image
62             src={img.src}
63             alt={img.alt}
64             className="w-full h-64 hover:scale-105 transition-transform duration-300"
65             fittingType="fill"
66         />
67     </button>
68   )}}
69 </div>
70
71 <div className="grid sm:grid-cols-2 gap-10">
72   <div>
73     <h2 className="font-display text-2xl text-amber-400 mb-4">Awards</h2>
74     <ul className="space-y-3">
75       {AWARDS.map((award) => (
76         <li key={award} className="flex items-start gap-3 text-amber-100/85">
77           <Award className="w-5 h-5 text-amber-400 flex-shrink-0 mt-0.5" />
78           <span>{award}</span>
79         </li>
80       )}}
81     </ul>
82   </div>
83   <div>
84     <h2 className="font-display text-2xl text-amber-400 mb-4">Customer Reviews</h2>
85     <div className="space-y-4">
86       {REVIEWS.map((review) => (
87         <div key={review.source} className="bg-white/5 rounded-lg p-4 border border-amber-
88 900/30">
89         <Quote className="w-5 h-5 text-amber-400 mb-2" />
90         <p className="text-amber-100/85 italic mb-2">{review.quote}</p>
91         <p className="text-sm text-amber-400">– {review.source}</p>
92       </div>
93     )}}
94   </div>
95 </div>
96 </div>
97
98 <Lightbox
99   images={IMAGES}
100   index={activeIndex}
101   onClose={() => setActiveIndex(null)}
102   onPrev={showPrev}
103   onNext={showNext}
104 />
105 </div>
106 );
107 }
1
import React from "react";
2
import { Link } from "react-router-dom";
3
import { MapPin, Phone, Clock } from "lucide-react";
4
import { Button } from "@components/ui/button";
5
import { Image } from "@components/ui/image";
6
import NewsletterForm from "@components/newsletter/NewsletterForm";

```

```

7
8 const HERO_IMAGE =
9   "https://media.lscianca.com/images/public/6aa9a380a84232541d6b09d3/6e3d778ed_generated_image.png
10 ";
11
12 export default function Home() {
13   return (
14     <div>
15       <section className="relative h-[80vh] min-h-[500px] flex items-center justify-center text-
16 center overflow-hidden">
17         <Image
18           src={HERO_IMAGE}
19           alt="Café Fausse elegant dining room"
20           className="absolute inset-0 w-full h-full"
21           fittingType="fill"
22         />
23         <div className="absolute inset-0 bg-black/60" />
24         <div className="relative z-10 px-4 max-w-3xl">
25           <h1 className="font-display text-5xl sm:text-6xl text-amber-50 mb-4 tracking-wide">
26             Café Fausse
27           </h1>
28           <p className="text-amber-100/90 text-lg mb-8">
29             Traditional Italian flavors, reimagined with modern culinary creativity.
30           </p>
31           <div className="flex flex-wrap justify-center gap-4">
32             <Link to="/reservations">
33               <Button className="bg-amber-600 hover:bg-amber-700 text-white px-6 py-6 text-base">
34                 Reserve a Table
35               </Button>
36             </Link>
37             <Link to="/menu">
38               <Button
39                 variant="outline"
40                 className="border-amber-200 text-amber-50 bg-transparent hover:bg-white/10 px-6
41 py-6 text-base"
42               >
43                 View Menu
44               </Button>
45             </Link>
46           </div>
47         </div>
48       </section>
49
50       <section className="max-w-5xl mx-auto px-4 sm:px-6 py-16 grid sm:grid-cols-3 gap-8 text-
51 amber-100/90">
52         <div className="text-center">
53           <MapPin className="w-6 h-6 mx-auto mb-3 text-amber-400" />
54           <h3 className="font-display text-lg text-amber-50 mb-1">Location</h3>
55           <p className="text-sm">1234 Culinary Ave, Suite 100, Washington, DC 20002</p>
56         </div>
57         <div className="text-center">
58           <Phone className="w-6 h-6 mx-auto mb-3 text-amber-400" />
59           <h3 className="font-display text-lg text-amber-50 mb-1">Contact</h3>

```

```

60         <p className="text-sm">(202) 555-4567</p>
61     </div>
62     <div className="text-center">
63         <Clock className="w-6 h-6 mx-auto mb-3 text-amber-400" />
64         <h3 className="font-display text-lg text-amber-50 mb-1">Hours</h3>
65         <p className="text-sm">Mon-Sat: 5:00 PM - 11:00 PM</p>
66         <p className="text-sm">Sunday: 5:00 PM - 9:00 PM</p>
67     </div>
68 </section>
69
70 <section className="bg-[#1a120b] py-16">
71     <div className="max-w-2xl mx-auto px-4 sm:px-6 text-center">
72         <h2 className="font-display text-3xl text-amber-50 mb-3">Stay in the Know</h2>
73         <p className="text-amber-100/70 mb-6">
74             Subscribe to our newsletter for special events and seasonal menu updates.
75         </p>
76         <NewsletterForm />
77     </div>
78 </section>
79 </div>
80 );
81 }
82
83 import React, { useState } from "react";
84 import { Link } from "react-router-dom";
85 import { lscianca } from "@api/lsciancaClient";
86 import { Button } from "@components/ui/button";
87 import { Input } from "@components/ui/input";
88 import { Label } from "@components/ui/label";
89 import { LogIn, Mail, Lock, Loader2 } from "lucide-react";
90 import AuthLayout from "@components/AuthLayout";
91 import GoogleIcon from "@components/GoogleIcon";
92 import { safeReturnTo } from "@lib/authReturnTo";
93
94 export default function Login() {
95     const [email, setEmail] = useState("");
96     const [password, setPassword] = useState("");
97     const [error, setError] = useState("");
98     const [loading, setLoading] = useState(false);
99     // Post-login destination (e.g. the MCP OAuth consent page sends users here
100     // with returnTo so the grant flow can resume). Same-origin paths only.
101     const returnTo = safeReturnTo();
102
103     const handleSubmit = async (e) => {
104         e.preventDefault();
105         setError("");
106         setLoading(true);
107         try {
108             await lscianca.auth.loginViaEmailPassword(email, password);
109             window.location.href = returnTo;
110         } catch (err) {
111             setError(err.message || "Invalid email or password");
112         } finally {
113             setLoading(false);
114         }
115     };
116 }

```

```
32     }
33   };
34
35   const handleGoogle = () => {
36     lscianca.auth.loginWithProvider("google", returnTo);
37   };
38
39   return (
40     <AuthLayout
41       icon={LogIn}
42       title="Welcome back"
43       subtitle="Log in to your account"
44       footer={
45         <>
46           Don't have an account?{" "}
47           <Link
48             to={"/register" + (returnTo !== "/" ? "?returnTo=" + encodeURIComponent(returnTo) :
49 """)}
50             className="text-primary font-medium hover:underline"
51           >
52             Create one
53           </Link>
54         </>
55       }
56     >
57       <Button
58         variant="outline"
59         className="w-full h-12 text-sm font-medium mb-6"
60         onClick={handleGoogle}
61       >
62         <GoogleIcon className="w-5 h-5 mr-2" />
63         Continue with Google
64       </Button>
65
66       <div className="relative mb-6">
67         <div className="absolute inset-0 flex items-center">
68           <div className="w-full border-t border-border" />
69         </div>
70         <div className="relative flex justify-center text-xs uppercase">
71           <span className="bg-card px-3 text-muted-foreground">or</span>
72         </div>
73       </div>
74
75       {error && (
76         <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
77           {error}
78         </div>
79       )}
80
81     <form onSubmit={handleSubmit} className="space-y-4">
82       <div className="space-y-2">
83         <Label htmlFor="email">Email</Label>
84         <div className="relative">
```

```

85         <Mail className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
86 foreground" aria-hidden="true" />
87         <Input
88             id="email"
89             type="email"
90             autoComplete="email"
91             autoFocus
92             placeholder="you@example.com"
93             value={email}
94             onChange={(e) => setEmail(e.target.value)}
95             className="pl-10 h-12"
96             required
97         />
98     </div>
99 </div>
100 <div className="space-y-2">
101     <div className="flex items-center justify-between">
102         <Label htmlFor="password">Password</Label>
103         <Link to="/forgot-password" className="text-xs text-primary hover:underline">
104             Forgot password?
105         </Link>
106     </div>
107     <div className="relative">
108         <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
109 foreground" aria-hidden="true" />
110         <Input
111             id="password"
112             type="password"
113             autoComplete="current-password"
114             placeholder="....."
115             value={password}
116             onChange={(e) => setPassword(e.target.value)}
117             className="pl-10 h-12"
118             required
119         />
120     </div>
121 </div>
122 <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
123     {loading ? (
124         <>
125             <Loader2 className="w-4 h-4 mr-2 animate-spin" />
126             Logging in...
127         </>
128     ) : (
129         "Log in"
130     )}
131 </Button>
132 </form>
133 </AuthLayout>
134 );
135 }
1   import React from "react";
2

```

```

3  const MENU = [
4    {
5      category: "Starters",
6      items: [
7        { name: "Bruschetta", desc: "Fresh tomatoes, basil, olive oil, and toasted baguette slices",
8 price: "$8.50" },
9        { name: "Caesar Salad", desc: "Crisp romaine with homemade Caesar dressing", price: "$9.00"
10     }],
11     },
12     },
13     {
14       category: "Main Courses",
15       items: [
16         { name: "Grilled Salmon", desc: "Served with lemon butter sauce and seasonal vegetables",
17 price: "$22.00" },
18         { name: "Ribeye Steak", desc: "12 oz prime cut with garlic mashed potatoes", price: "$28.00"
19     }],
20         { name: "Vegetable Risotto", desc: "Creamy Arborio rice with wild mushrooms", price:
21 "$18.00" },
22       ],
23     },
24     {
25       category: "Desserts",
26       items: [
27         { name: "Tiramisu", desc: "Classic Italian dessert with mascarpone", price: "$7.50" },
28         { name: "Cheesecake", desc: "Creamy cheesecake with berry compote", price: "$7.00" },
29       ],
30     },
31     {
32       category: "Beverages",
33       items: [
34         { name: "Red Wine (Glass)", desc: "A selection of Italian reds", price: "$10.00" },
35         { name: "White Wine (Glass)", desc: "Crisp and refreshing", price: "$9.00" },
36         { name: "Craft Beer", desc: "Local artisan brews", price: "$6.00" },
37         { name: "Espresso", desc: "Strong and aromatic", price: "$3.00" },
38       ],
39     },
40   ];
41
42   export default function Menu() {
43     return (
44       <div className="max-w-4xl mx-auto px-4 sm:px-6 py-16">
45         <div className="text-center mb-12">
46           <h1 className="font-display text-4xl text-amber-50 mb-3">Our Menu</h1>
47           <p className="text-amber-100/70">Crafted with passion, served with pride.</p>
48         </div>
49
50         <div className="grid gap-12 sm:grid-cols-2">
51           {MENU.map((section) => (
52             <div key={section.category}>
53               <h2 className="font-display text-2xl text-amber-400 mb-4 border-b border-amber-900/40
54 pb-2">
55                 {section.category}

```

```

56         </h2>
57         <div className="space-y-5">
58             {section.items.map((item) => (
59                 <div key={item.name} className="flex justify-between gap-4">
60                     <div>
61                         <h3 className="text-amber-50 font-medium">{item.name}</h3>
62                         <p className="text-sm text-amber-100/60">{item.desc}</p>
63                     </div>
64                     <span className="text-amber-400 font-medium whitespace-
65 nowrap">{item.price}</span>
66                 </div>
67             )}}
68         </div>
69     </div>
70     )}}
71 </div>
72 </div>
73 );
74 }
1  import React, { useEffect, useState } from "react";
2  import { appParams } from "@lib/app-params";
3  import { Button } from "@components/ui/button";
4  import { ShieldCheck, Loader2 } from "lucide-react";
5  import AuthLayout from "@components/AuthLayout";
6
7  // App-side OAuth consent page for the app's MCP server. The platform redirects
8  // AI clients here (see lscianca/mcp/config.json `consent_path`) with an opaque
9  // `ctx` handle – the authorization request itself lives on the server. This page
10 // gates on the app-user session, fetches the display info for that handle, shows
11 // the categories of access being granted, and posts the approve/deny decision.
12 // Do not change the fetch calls, headers, or the `ctx` handle handling – styling
13 // and copy are safe to edit.
14 export default function OAuthConsent() {
15     const ctx = new URLSearchParams(window.location.search).get("ctx");
16     const [info, setInfo] = useState(null);
17     const [checking, setChecking] = useState(true);
18     const [submitting, setSubmitting] = useState(false);
19     const [decided, setDecided] = useState("");
20     const [error, setError] = useState("");
21     const [reconnect, setReconnect] = useState("");
22
23     useEffect(() => {
24         (async () => {
25             let redirecting = false;
26             try {
27                 if (!ctx) {
28                     setError("This authorization link is invalid or has expired.");
29                     return;
30                 }
31                 // Resolve the handle first: a dead handle must never render
32                 // approve/deny, and the response carries the app's configured login
33                 // route for the signed-out redirect below. Send the session (cookie +
34                 // bearer token) so the server can list the granted tools for a

```

```

35 // signed-in user – the same auth the approve/deny call sends; without
36 // it the display request is anonymous and shows no tools.
37 const infoHeaders = {};
38 if (appParams.token) infoHeaders.Authorization = "Bearer " + appParams.token;
39 const res = await fetch(
40   `/api/apps/${appParams.appId}/mcp/consent-info?handle=${encodeURIComponent(ctx)}`,
41   { credentials: "include", headers: infoHeaders },
42 );
43 if (!res.ok) {
44   setError("This authorization link is invalid or has expired.");
45   return;
46 }
47 const data = await res.json();
48 // Gate on the server's auth result, NOT lscianca.auth.isAuthenticated():
49 // the SDK check runs the bearer path, so a cookie-only session (platform
50 // login/SSO, or a private app with a stale localStorage token) would read
51 // as signed-out and redirect – even though /consent-info just
52 // authenticated this same request via its cookie fallback. data.authenticated
53 // keeps the redirect decision in agreement with what the server returned.
54 if (!data.authenticated) {
55   // The short handle rides back in returnTo; login_path is
56   // owner-configured and validated server-side as a same-origin path.
57   // Send from_url too: a custom-auth app coerced to platform auth (e.g.
58   // public_without_login under workspace SSO) serves the platform login,
59   // which honors from_url rather than returnTo. Rebuild the query from
60   // `ctx` alone – never forward window.location.search raw: the platform
61   // resume returns from_url verbatim, so crafted extras on the consent
62   // link (app_base_url, access_token, ...) would ride through the login
63   // round-trip and app-params.js would persist them into the freshly
64   // authenticated session.
65   const returnTo =
66     window.location.pathname + "?ctx=" + encodeURIComponent(ctx);
67   const encoded = encodeURIComponent(returnTo);
68   redirecting = true; // keep the spinner while the browser navigates
69   window.location.href =
70     (data.login_path || "/login") + "?returnTo=" + encoded + "&from_url=" + encoded;
71   return;
72 }
73 setInfo(data);
74 } catch (e) {
75   setError("Could not load this authorization request. Please try again.");
76 } finally {
77   if (!redirecting) setChecking(false);
78 }
79 })();
80 }, [ctx]);
81
82 const respond = async (action) => {
83   setSubmitting(true);
84   setError("");
85   try {
86     const headers = { "Content-Type": "application/json" };
87     // Cookie-backed sessions carry no token; sending "Bearer null" would

```

```

88 // shadow the valid cookie, so add the header only when a token exists.
89 if (appParams.token) headers.Authorization = "Bearer " + appParams.token;
90 const res = await fetch(`/api/apps/${appParams.appId}/mcp/authorize-grant`, {
91   method: "POST",
92   credentials: "include",
93   headers,
94   body: JSON.stringify({ ctx, action }),
95 });
96 if (!res.ok) {
97   // 401 = the session expired before the (single-use, still-unconsumed)
98   // handle was spent; retrying the same controls re-sends the dead session
99   // forever. Send the user back through login preserving `ctx` – the same
100   // redirect the initial signed-out path uses – so they can return and
101   // approve the still-valid handle.
102   if (res.status === 401) {
103     const returnTo = window.location.pathname + "?ctx=" + encodeURIComponent(ctx);
104     const encoded = encodeURIComponent(returnTo);
105     window.location.href =
106       ((info && info.login_path) || "/login") + "?returnTo=" + encoded + "&from_url=" +
107 encoded;
108     return;
109   }
110   // These all come AFTER the single-use handle is atomically consumed
111   // (409 tool set changed; 403 host/resource/app mismatch; 404 access
112   // gone; 400 malformed/handle already used), so retrying can only 404.
113   // Show a terminal reconnect state, not an impossible "try again".
114   if ([400, 403, 404, 409].includes(res.status)) {
115     let detail = "";
116     try { detail = (await res.json()).detail; } catch (_) { /* keep default */ }
117     setReconnect(detail || "This authorization can no longer be completed. Reconnect from
118 your AI client to try again.");
119     setSubmitting(false);
120     return;
121   }
122   throw new Error("Could not complete authorization. Please try again.");
123 }
124 const data = await res.json();
125 window.location.href = data.redirect_url;
126 if (!/^https?:/i.test(data.redirect_url)) {
127   // Custom-scheme redirect (native AI clients, e.g. cursor://): browsers
128   // may block or not visibly navigate, so show a terminal state instead
129   // of an eternal spinner.
130   setDecided(action);
131   setSubmitting(false);
132 }
133 } catch (e) {
134   setError(e.message);
135   setSubmitting(false);
136 }
137 };
138
139 if (checking) {
140   return (

```

```

141     <AuthLayout icon={ShieldCheck} title="Authorize access">
142         <div className="flex items-center justify-center py-6 text-muted-foreground">
143             <Loader2 className="w-5 h-5 mr-2 animate-spin" aria-hidden="true" />
144             Loading...
145         </div>
146     </AuthLayout>
147 );
148 }
149
150 const client = (info && info.client_name) || "An AI client";
151 const appName = (info && info.app_name) || "this app";
152
153 if (decided) {
154     return (
155         <AuthLayout
156             icon={ShieldCheck}
157             title={decided === "approve" ? "Access granted" : "Access denied"}
158             subtitle={`You can return to ${client} and close this window.`}
159         />
160     );
161 }
162
163 // Terminal: the authorization request is no longer valid (tool set changed +
164 // handle consumed). Retrying can't succeed, so show reconnect guidance with
165 // no approve/deny controls.
166 if (reconnect) {
167     return (
168         <AuthLayout icon={ShieldCheck} title="Reconnect required">
169             <div className="p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
170                 {reconnect}
171             </div>
172         </AuthLayout>
173     );
174 }
175
176 // No consent details means nothing trustworthy to approve: a failed
177 // consent-info load (expired handle, rate limit, transient error) renders
178 // the error alone, never the approve/deny controls.
179 if (error && !info) {
180     return (
181         <AuthLayout icon={ShieldCheck} title="Authorize access">
182             <div className="p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
183                 {error}
184             </div>
185         </AuthLayout>
186     );
187 }
188
189 const tools = Array.isArray(info.tools) ? info.tools : [];
190
191 return (
192     <AuthLayout
193         icon={ShieldCheck}

```

```

194     title="Authorize access"
195     subtitle={` ${client} wants to access ${appName} on your behalf`}
196 >
197     {error && (
198         <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
199             {error}
200         </div>
201     )}
202
203     <p className="text-sm font-medium text-foreground mb-2">
204         {tools.length ? `It will be able to use these tools in ${appName}:` : "No tools
205 requested"}
206     </p>
207     {tools.length > 0 && (
208         <ul className="space-y-2 text-sm mb-6">
209             {tools.map((tool) => (
210                 <li key={tool.name} className="flex flex-col">
211                     <span className="text-foreground font-medium">
212                         {tool.title || tool.name}
213                     </span>
214                     {tool.description && (
215                         <span className="text-muted-foreground">{tool.description}</span>
216                     )}
217                 </li>
218             ))}
219         </ul>
220     )}
221
222     <div className="flex gap-3">
223         <Button
224             variant="outline"
225             className="flex-1 h-12 font-medium"
226             disabled={submitting}
227             onClick={() => respond("deny")}
228         >
229             Deny
230         </Button>
231         <Button
232             className="flex-1 h-12 font-medium"
233             disabled={submitting}
234             onClick={() => respond("approve")}
235         >
236             {submitting ? <Loader2 className="w-4 h-4 mr-2 animate-spin" /> : null}
237             Approve
238         </Button>
239     </div>
240 </AuthLayout>
241 );
242 }
1  import React, { useState } from "react";
2  import { Link } from "react-router-dom";
3  import { lscianca } from "@api/lsciancaClient";
4  import { Button } from "@components/ui/button";

```

```

5 import { Input } from "@components/ui/input";
6 import { Label } from "@components/ui/label";
7 import { UserPlus, Mail, Lock, Loader2 } from "lucide-react";
8 import { InputOTP, InputOTPGroup, InputOTPSlot } from "@components/ui/input-otp";
9 import AuthLayout from "@components/AuthLayout";
10 import GoogleIcon from "@components/GoogleIcon";
11 import { toast } from "@components/ui/use-toast";
12 import { safeReturnTo } from "@lib/authReturnTo";
13
14 export default function Register() {
15   const [email, setEmail] = useState("");
16   const [password, setPassword] = useState("");
17   const [confirmPassword, setConfirmPassword] = useState("");
18   const [error, setError] = useState("");
19   const [loading, setLoading] = useState(false);
20   const [showOtp, setShowOtp] = useState(false);
21   const [otpCode, setOtpCode] = useState("");
22
23   const handleSubmit = async (e) => {
24     e.preventDefault();
25     setError("");
26     if (password !== confirmPassword) {
27       setError("Passwords do not match");
28       return;
29     }
30     setLoading(true);
31     try {
32       await lscianca.auth.register({ email, password });
33       setShowOtp(true);
34     } catch (err) {
35       setError(err.message || "Registration failed");
36     } finally {
37       setLoading(false);
38     }
39   };
40
41   const handleVerify = async () => {
42     setError("");
43     setLoading(true);
44     try {
45       const result = await lscianca.auth.verifyOtp({ email, otpCode });
46       if (result?.access_token) {
47         lscianca.auth.setToken(result.access_token);
48       }
49       window.location.href = safeReturnTo();
50     } catch (err) {
51       setError(err.message || "Invalid verification code");
52     } finally {
53       setLoading(false);
54     }
55   };
56
57   const handleResend = async () => {

```

```

58   setError("");
59   try {
60     await lscianca.auth.resendOtp(email);
61     toast({
62       title: "Code sent",
63       description: "Check your email for the new code.",
64     });
65   } catch (err) {
66     setError(err.message || "Failed to resend code");
67   }
68 };
69
70 const handleGoogle = () => {
71   lscianca.auth.loginWithProvider("google", safeReturnTo());
72 };
73
74 if (showOtp) {
75   return (
76     <AuthLayout
77       icon={Mail}
78       title="Verify your email"
79       subtitle={`We sent a code to ${email}`}
80     >
81       {error && (
82         <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
83           {error}
84         </div>
85       )}
86       <div className="flex justify-center mb-6">
87         <InputOTP
88           maxLength={6}
89           value={otpCode}
90           onChange={setOtpCode}
91           autoFocus
92           autoComplete="one-time-code"
93         >
94           <InputOTPGroup>
95             <InputOTPSlot index={0} />
96             <InputOTPSlot index={1} />
97             <InputOTPSlot index={2} />
98             <InputOTPSlot index={3} />
99             <InputOTPSlot index={4} />
100            <InputOTPSlot index={5} />
101          </InputOTPGroup>
102        </InputOTP>
103      </div>
104      <Button
105        className="w-full h-12 font-medium"
106        onClick={handleVerify}
107        disabled={loading || otpCode.length < 6}
108      >
109        {loading ? (
110          <>

```

```

111         <Loader2 className="w-4 h-4 mr-2 animate-spin" />
112         Verifying...
113     </>
114     ) : (
115         "Verify"
116     )}
117 </Button>
118 <p className="text-center text-sm text-muted-foreground mt-4">
119     Didn't receive the code?{" "}
120     <button onClick={handleResend} className="text-primary font-medium hover:underline">
121         Resend
122     </button>
123 </p>
124 </AuthLayout>
125 );
126 }
127
128 return (
129     <AuthLayout
130         icon={UserPlus}
131         title="Create your account"
132         subtitle="Sign up to get started"
133         footer={
134             <>
135                 Already have an account?{" "}
136                 <Link
137                     to={"/login" + (safeReturnTo() !== "/" ? "?returnTo=" +
138 encodeURIComponent(safeReturnTo()) : "")}
139                     className="text-primary font-medium hover:underline"
140                 >
141                     Log in
142                 </Link>
143             </>
144         }
145     >
146     <Button
147         variant="outline"
148         className="w-full h-12 text-sm font-medium mb-6"
149         onClick={handleGoogle}
150     >
151         <GoogleIcon className="w-5 h-5 mr-2" />
152         Continue with Google
153     </Button>
154
155     <div className="relative mb-6">
156         <div className="absolute inset-0 flex items-center">
157             <div className="w-full border-t border-border" />
158         </div>
159         <div className="relative flex justify-center text-xs uppercase">
160             <span className="bg-card px-3 text-muted-foreground">or</span>
161         </div>
162     </div>
163

```

```

164 {error && (
165   <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
166     {error}
167   </div>
168 )}
169
170 <form onSubmit={handleSubmit} className="space-y-4">
171   <div className="space-y-2">
172     <Label htmlFor="email">Email</Label>
173     <div className="relative">
174       <Mail className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
175 foreground" aria-hidden="true" />
176       <Input
177         id="email"
178         type="email"
179         autoComplete="email"
180         autoFocus
181         placeholder="you@example.com"
182         value={email}
183         onChange={(e) => setEmail(e.target.value)}
184         className="pl-10 h-12"
185         required
186       />
187     </div>
188   </div>
189   <div className="space-y-2">
190     <Label htmlFor="password">Password</Label>
191     <div className="relative">
192       <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
193 foreground" aria-hidden="true" />
194       <Input
195         id="password"
196         type="password"
197         autoComplete="new-password"
198         placeholder="....."
199         value={password}
200         onChange={(e) => setPassword(e.target.value)}
201         className="pl-10 h-12"
202         required
203       />
204     </div>
205   </div>
206   <div className="space-y-2">
207     <Label htmlFor="confirm">Confirm Password</Label>
208     <div className="relative">
209       <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
210 foreground" aria-hidden="true" />
211       <Input
212         id="confirm"
213         type="password"
214         autoComplete="new-password"
215         placeholder="....."
216         value={confirmPassword}

```

```

217         onChange={(e) => setConfirmPassword(e.target.value)}
218         className="p1-10 h-12"
219         required
220     />
221 </div>
222 </div>
223 <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
224     {loading ? (
225         <>
226             <Loader2 className="w-4 h-4 mr-2 animate-spin" />
227             Creating account...
228         </>
229     ) : (
230         "Create account"
231     )}
232 </Button>
233 </form>
234 </AuthLayout>
235 );
236 }
1  import React from "react";
2  import ReservationForm from "@components/reservations/ReservationForm";
3
4  export default function Reservations() {
5      return (
6          <div className="max-w-xl mx-auto px-4 sm:px-6 py-16">
7              <div className="text-center mb-10">
8                  <h1 className="font-display text-4xl text-amber-50 mb-3">Reserve a Table</h1>
9                  <p className="text-amber-100/70">We can't wait to host you at Café Fausse.</p>
10             </div>
11             <ReservationForm />
12         </div>
13     );
14 }
1  import React, { useState } from "react";
2  import { Link, useSearchParams } from "react-router-dom";
3  import { lscianca } from "@api/lsciancaClient";
4  import { Button } from "@components/ui/button";
5  import { Input } from "@components/ui/input";
6  import { Label } from "@components/ui/label";
7  import { Lock, Loader2, AlertTriangle } from "lucide-react";
8  import AuthLayout from "@components/AuthLayout";
9
10 export default function ResetPassword() {
11     const [searchParams] = useSearchParams();
12     const resetToken = searchParams.get("token");
13
14     const [newPassword, setNewPassword] = useState("");
15     const [confirmPassword, setConfirmPassword] = useState("");
16     const [error, setError] = useState("");
17     const [loading, setLoading] = useState(false);
18
19     const handleSubmit = async (e) => {

```

```

20     e.preventDefault();
21     setError("");
22     if (newPassword !== confirmPassword) {
23         setError("Passwords do not match");
24         return;
25     }
26     setLoading(true);
27     try {
28         await lscianca.auth.resetPassword({ resetToken, newPassword });
29         window.location.href = "/login";
30     } catch (err) {
31         setError(err.message || "Failed to reset password");
32     } finally {
33         setLoading(false);
34     }
35 };
36
37 if (!resetToken) {
38     return (
39         <AuthLayout
40             icon={AlertTriangle}
41             title="Invalid reset link"
42             subtitle="This password reset link is missing or invalid"
43             footer={
44                 <Link to="/forgot-password" className="text-primary font-medium hover:underline">
45                     Request a new link
46                 </Link>
47             }
48         >
49             <p className="text-sm text-foreground text-center">
50                 The link you used appears to be incomplete. Please request a new password reset email.
51             </p>
52         </AuthLayout>
53     );
54 }
55
56 return (
57     <AuthLayout
58         icon={Lock}
59         title="New password"
60         subtitle="Enter your new password below"
61     >
62         {error && (
63             <div className="mb-4 p-3 rounded-lg bg-destructive/10 text-destructive text-sm">
64                 {error}
65             </div>
66         )}
67         <form onSubmit={handleSubmit} className="space-y-4">
68             <div className="space-y-2">
69                 <Label htmlFor="password">New Password</Label>
70                 <div className="relative">
71                     <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-foreground" aria-hidden="true" />

```

```

73     <Input
74         id="password"
75         type="password"
76         autoComplete="new-password"
77         autoFocus
78         placeholder="....."
79         value={newPassword}
80         onChange={(e) => setNewPassword(e.target.value)}
81         className="pl-10 h-12"
82         required
83     />
84 </div>
85 </div>
86 <div className="space-y-2">
87     <Label htmlFor="confirm">Confirm Password</Label>
88     <div className="relative">
89         <Lock className="absolute left-3 top-1/2 -translate-y-1/2 w-4 h-4 text-muted-
90 foreground" aria-hidden="true" />
91         <Input
92             id="confirm"
93             type="password"
94             autoComplete="new-password"
95             placeholder="....."
96             value={confirmPassword}
97             onChange={(e) => setConfirmPassword(e.target.value)}
98             className="pl-10 h-12"
99             required
100         />
101     </div>
102 </div>
103 <Button type="submit" className="w-full h-12 font-medium" disabled={loading}>
104     {loading ? (
105         <>
106             <Loader2 className="w-4 h-4 mr-2 animate-spin" />
107             Resetting...
108         </>
109     ) : (
110         "Reset password"
111     )}
112 </Button>
113 </form>
114 </AuthLayout>
115 );
116 }
1
import { Toaster } from "@components/ui/toaster"
2
import { QueryClientProvider } from '@tanstack/react-query'
3
import { queryClientInstance } from '@lib/query-client'
4
import { BrowserRouter as Router, Route, Routes } from 'react-router-dom';
5
import PageNotFound from './lib/PageNotFound';
6
import { AuthProvider, useAuth } from '@lib/AuthContext';
7
import UserNotRegisteredError from '@components/UserNotRegisteredError';
8
import ScrollToTop from './components/ScrollToTop';
9
import Layout from '@components/layout/Layout';

```

```

10 import Home from '@pages/Home';
11 import Menu from '@pages/Menu';
12 import Reservations from '@pages/Reservations';
13 import AboutUs from '@pages/AboutUs';
14 import Gallery from '@pages/Gallery';
15 // Add page imports here
16
17 const AuthenticatedApp = () => {
18   const { isLoadingAuth, isLoadingPublicSettings, authError, navigateToLogin } = useAuth();
19
20   // Show loading spinner while checking app public settings or auth
21   if (isLoadingPublicSettings || isLoadingAuth) {
22     return (
23       <div className="fixed inset-0 flex items-center justify-center">
24         <div className="w-8 h-8 border-4 border-slate-200 border-t-slate-800 rounded-full animate-
25 spin"></div>
26       </div>
27     );
28   }
29
30   // Handle authentication errors
31   if (authError) {
32     if (authError.type === 'user_not_registered') {
33       return <UserNotRegisteredError />;
34     } else if (authError.type === 'auth_required') {
35       // Redirect to login automatically
36       navigateToLogin();
37       return null;
38     }
39   }
40
41   // Render the main app
42   return (
43     <Routes>
44       {/* Add your page Route elements here */}
45       <Route element={<Layout />}>
46         <Route path="/" element={<Home />} />
47         <Route path="/menu" element={<Menu />} />
48         <Route path="/reservations" element={<Reservations />} />
49         <Route path="/about" element={<AboutUs />} />
50         <Route path="/gallery" element={<Gallery />} />
51       </Route>
52       <Route path="*" element={<PageNotFound />} />
53     </Routes>
54   );
55 };
56
57 function App() {
58
59   return (
60     <AuthProvider>
61       <QueryClientProvider client={queryClientInstance}>

```

```

62     <Router>
63       <ScrollToTop />
64       <AuthenticatedApp />
65     </Router>
66     <Toaster />
67   </QueryClientProvider>
68 </AuthProvider>
69 )
70 }
71
72 export default App
73
74 @import
75 url('https://fonts.googleapis.com/css2?family=Playfair+Display:wght@500;600;700&family=Inter:wght@
76 400;500;600&display=swap');
77
78 @tailwind base;
79 @tailwind components;
80 @tailwind utilities;
81
82 @layer base {
83   :root {
84     --background: 0 0% 100%;
85     --foreground: 0 0% 3.9%;
86     --card: 0 0% 100%;
87     --card-foreground: 0 0% 3.9%;
88     --popover: 0 0% 100%;
89     --popover-foreground: 0 0% 3.9%;
90     --primary: 0 0% 9%;
91     --primary-foreground: 0 0% 98%;
92     --secondary: 0 0% 96.1%;
93     --secondary-foreground: 0 0% 9%;
94     --muted: 0 0% 96.1%;
95     --muted-foreground: 0 0% 45.1%;
96     --accent: 0 0% 96.1%;
97     --accent-foreground: 0 0% 9%;
98     --destructive: 0 84.2% 60.2%;
99     --destructive-foreground: 0 0% 98%;
100    --border: 0 0% 89.8%;
101    --input: 0 0% 89.8%;
102    --ring: 0 0% 3.9%;
103    --chart-1: 12 76% 61%;
104    --chart-2: 173 58% 39%;
105    --chart-3: 197 37% 24%;
106    --chart-4: 43 74% 66%;
107    --chart-5: 27 87% 67%;
108    --radius: 0.5rem;
109    --font-heading: 'Inter', ui-sans-serif, system-ui, sans-serif;
110    --font-body: 'Inter', ui-sans-serif, system-ui, sans-serif;
111    --font-display: 'Playfair Display', ui-serif, serif;
112    --font-mono: ui-monospace, SFMono-Regular, Menlo, Monaco, Consolas, "Liberation Mono",
113    "Courier New", monospace;
114    --sidebar-background: 0 0% 98%;
115    --sidebar-foreground: 240 5.3% 26.1%;

```

```
43     --sidebar-primary: 240 5.9% 10%;
44     --sidebar-primary-foreground: 0 0% 98%;
45     --sidebar-accent: 240 4.8% 95.9%;
46     --sidebar-accent-foreground: 240 5.9% 10%;
47     --sidebar-border: 220 13% 91%;
48     --sidebar-ring: 217.2 91.2% 59.8%;
49 }
50
51 .dark {
52     --background: 0 0% 3.9%;
53     --foreground: 0 0% 98%;
54     --card: 0 0% 3.9%;
55     --card-foreground: 0 0% 98%;
56     --popover: 0 0% 3.9%;
57     --popover-foreground: 0 0% 98%;
58     --primary: 0 0% 98%;
59     --primary-foreground: 0 0% 9%;
60     --secondary: 0 0% 14.9%;
61     --secondary-foreground: 0 0% 98%;
62     --muted: 0 0% 14.9%;
63     --muted-foreground: 0 0% 63.9%;
64     --accent: 0 0% 14.9%;
65     --accent-foreground: 0 0% 98%;
66     --destructive: 0 62.8% 30.6%;
67     --destructive-foreground: 0 0% 98%;
68     --border: 0 0% 14.9%;
69     --input: 0 0% 14.9%;
70     --ring: 0 0% 83.1%;
71     --chart-1: 220 70% 50%;
72     --chart-2: 160 60% 45%;
73     --chart-3: 30 80% 55%;
74     --chart-4: 280 65% 60%;
75     --chart-5: 340 75% 55%;
76     --sidebar-background: 240 5.9% 10%;
77     --sidebar-foreground: 240 4.8% 95.9%;
78     --sidebar-primary: 224.3 76.3% 48%;
79     --sidebar-primary-foreground: 0 0% 100%;
80     --sidebar-accent: 240 3.7% 15.9%;
81     --sidebar-accent-foreground: 240 4.8% 95.9%;
82     --sidebar-border: 240 3.7% 15.9%;
83     --sidebar-ring: 217.2 91.2% 59.8%;
84 }
85 }
86
87
88 @layer base {
89     * {
90         @apply border-border outline-ring/50;
91     }
92
93     body {
94         @apply bg-background text-foreground font-body;
```

```

95     }
96 }
1  import React from 'react'
2  import ReactDOM from 'react-dom/client'
3  import App from '@App.jsx'
4  import '@index.css'
5
6  ReactDOM.createRoot(document.getElementById('root')).render(
7    <App />
8  )
1 #env
2 .env
3 .env.*
4
5 # Logs
6 /logs
7 *.log
8 npm-debug.log*
9 yarn-debug.log*
10 yarn-error.log*
11 pnpm-debug.log*
12 lerna-debug.log*
13
14 node_modules
15 dist
16 dist-ssr
17 *.local
18
19 # Nitro build output, once this app has a server. Both are regenerated by
20 # every build, and the deploy runs one before reading them.
21 .output
22 .wrangler
23
24 # Editor directories and files
25 .vscode/*
26 !.vscode/extensions.json
27 .idea
28 .DS_Store
29 *.suo
30 *.ntvs*
31 *.njsproj
32 *.sln
33 *.sw?
34
35 .env
36 .vite
37 lscianca/.app.jsonc
1  # AGENTS.md
2
3  ## Project Context
4
5  This is a Lscianca app repository. Treat it as user-owned application code, keep changes focused
6  on the user's request, and preserve existing project conventions.

```

Start with ``README.md`` for local setup, environment variables, and publish workflow.

Lscianca References

- CLI overview: <https://docs.lscianca.com/developers/references/cli/get-started/overview.md>
- Agent skills: <https://docs.lscianca.com/developers/backend/overview/skills.md>

If your agent supports Agent Skills, install or update Lscianca skills before Lscianca-specific work:

```
```bash
npx skills add lscianca/skills
```
```

Key Files

- ``src/``: frontend application source.
- ``src/api/lsciancaClient.js``: frontend Lscianca SDK client.
- ``vite.config.js``: Vite config and Lscianca Vite plugin setup.
- ``.env.local``: local-only environment values; never commit secrets.

Working Notes

- Use ``lscianca dev`` as the default local development command when you need the local Lscianca backend. It can run the backend and frontend together.
- When docs or code mention the frontend being started automatically, that usually means the Lscianca project config includes ``site.serveCommand``, for example ``"serveCommand": "npm run dev"`` in ``lscianca/config.jsonc``.
- Use ``npm run dev`` only for frontend-only work against the hosted Lscianca backend.
- Prefer the existing Lscianca CLI workflow over adding new npm scripts for Lscianca-specific tasks.
- Reuse the existing SDK client and Vite plugin patterns before adding new Lscianca integration paths.
- Run the relevant checks from ``package.json`` before finishing code changes.

See AGENTS.md

Follow the instructions in ``AGENTS.md``.

```
{
  "$schema": "https://ui.shadcn.com/schema.json",
  "style": "new-york",
  "rsc": false,
  "tsx": false,
  "tailwind": {
    "config": "tailwind.config.js",
    "css": "src/index.css",
    "baseColor": "neutral",
    "cssVariables": true,
    "prefix": ""
  },
  "aliases": {
    "components": "@components",
    "utils": "@lib/utils",
```

```
16     "ui": "@/components/ui",
17     "lib": "@/lib",
18     "hooks": "@/hooks"
19   },
20   "iconLibrary": "lucide"
21 }
 1 import globals from "globals";
 2 import pluginJs from "@eslint/js";
 3 import pluginReact from "eslint-plugin-react";
 4 import pluginReactHooks from "eslint-plugin-react-hooks";
 5 import pluginUnusedImports from "eslint-plugin-unused-imports";
 6
 7 export default [
 8   {
 9     files: [
10       "src/components/**/*..{js,mjs,cjs,jsx}",
11       "src/pages/**/*..{js,mjs,cjs,jsx}",
12       "src/Layout.jsx",
13     ],
14     ignores: ["src/lib/**/*.", "src/components/ui/**/*."],
15     ...pluginJs.configs.recommended,
16     ...pluginReact.configs.flat.recommended,
17     languageOptions: {
18       globals: globals.browser,
19       parserOptions: {
20         ecmaVersion: 2022,
21         sourceType: "module",
22         ecmaFeatures: {
23           jsx: true,
24         },
25       },
26     },
27     settings: {
28       react: {
29         version: "detect",
30       },
31     },
32     plugins: {
33       react: pluginReact,
34       "react-hooks": pluginReactHooks,
35       "unused-imports": pluginUnusedImports,
36     },
37     rules: {
38       "no-unused-vars": "off",
39       "react/jsx-uses-vars": "error",
40       "react/jsx-uses-react": "error",
41       "unused-imports/no-unused-imports": "error",
42       "unused-imports/no-unused-vars": [
43         "warn",
44         {
45           vars: "all",
46           varsIgnorePattern: "^_",
47           args: "after-used",
```

```

48     argsIgnorePattern: "^_",
49   },
50 ],
51   "react/prop-types": "off",
52   "react/react-in-jsx-scope": "off",
53   "react/no-unknown-property": [
54     "error",
55     { ignore: ["cmdk-input-wrapper", "toast-close"] },
56   ],
57   "react-hooks/rules-of-hooks": "error",
58 },
59 },
60 ];
  1 <!doctype html>
  2 <html lang="en">
  3   <head>
  4     <meta charset="UTF-8" />
  5     <link rel="icon" type="image/svg+xml" href="https://lscianca.com/logo_v2.svg" />
  6     <meta name="viewport" content="width=device-width, initial-scale=1.0" />
  7     <link rel="manifest" href="/manifest.json" />
  8     <title>Lscianca APP</title>
  9   </head>
 10   <body>
 11     <div id="root"></div>
 12     <script type="module" src="/src/main.jsx"></script>
 13   </body>
 14 </html>
 1 {
 2   "compilerOptions": {
 3     "baseUrl": ".",
 4     "paths": {
 5       "@/*": ["/src/*"]
 6     },
 7     "jsx": "react-jsx",
 8     "module": "esnext",
 9     "moduleResolution": "bundler",
10     "lib": ["esnext", "dom"],
11     "target": "esnext",
12     "checkJs": true,
13     "skipLibCheck": true,
14     "allowSyntheticDefaultImports": true,
15     "esModuleInterop": true,
16     "resolveJsonModule": true,
17     "types": []
18   },
19   "include": ["src/components/**/*.js", "src/pages/**/*.jsx", "src/Layout.jsx"],
20   "exclude": ["node_modules", "dist", "src/vite-plugins", "src/components/ui", "src/api",
21 "src/lib"]
 1 {
 2   "name": "lscianca-app",
 3   "private": true,
 4   "version": "0.0.0",
 5   "type": "module",

```

```
6  "scripts": {
7    "dev": "vite",
8    "build": "vite build",
9    "lint": "eslint . --quiet",
10   "lint:fix": "eslint . --fix",
11   "typecheck": "tsc -p ./jsconfig.json",
12   "preview": "vite preview"
13 },
14 "dependencies": {
15   "@lscianca/sdk": "^0.8.48",
16   "@lscianca/vite-plugin": "^1.0.40",
17   "@hello-pangea/dnd": "^17.0.0",
18   "@hookform/resolvers": "^4.1.2",
19   "@radix-ui/react-accordion": "^1.2.3",
20   "@radix-ui/react-alert-dialog": "^1.1.6",
21   "@radix-ui/react-aspect-ratio": "^1.1.2",
22   "@radix-ui/react-avatar": "^1.1.3",
23   "@radix-ui/react-checkbox": "^1.1.4",
24   "@radix-ui/react-collapsible": "^1.1.3",
25   "@radix-ui/react-context-menu": "^2.2.6",
26   "@radix-ui/react-dialog": "^1.1.6",
27   "@radix-ui/react-dropdown-menu": "^2.1.6",
28   "@radix-ui/react-hover-card": "^1.1.6",
29   "@radix-ui/react-label": "^2.1.2",
30   "@radix-ui/react-menubar": "^1.1.6",
31   "@radix-ui/react-navigation-menu": "^1.2.5",
32   "@radix-ui/react-popover": "^1.1.6",
33   "@radix-ui/react-progress": "^1.1.2",
34   "@radix-ui/react-radio-group": "^1.2.3",
35   "@radix-ui/react-scroll-area": "^1.2.3",
36   "@radix-ui/react-select": "^2.1.6",
37   "@radix-ui/react-separator": "^1.1.2",
38   "@radix-ui/react-slider": "^1.2.3",
39   "@radix-ui/react-slot": "^1.1.2",
40   "@radix-ui/react-switch": "^1.1.3",
41   "@radix-ui/react-tabs": "^1.1.3",
42   "@radix-ui/react-toast": "^1.2.2",
43   "@radix-ui/react-toggle": "^1.1.2",
44   "@radix-ui/react-toggle-group": "^1.1.2",
45   "@radix-ui/react-tooltip": "^1.1.8",
46   "@stripe/react-stripe-js": "^3.0.0",
47   "@stripe/stripe-js": "^5.2.0",
48   "@tanstack/react-query": "^5.84.1",
49   "canvas-confetti": "^1.9.4",
50   "class-variance-authority": "^0.7.1",
51   "clsx": "^2.1.1",
52   "cmdk": "^1.0.0",
53   "date-fns": "^3.6.0",
54   "embla-carousel-react": "^8.5.2",
55   "framer-motion": "^11.16.4",
56   "html2canvas": "^1.4.1",
57   "input-otp": "^1.4.2",
58   "jspdf": "^4.2.1",
```

```

59     "lodash": "^4.17.21",
60     "lucide-react": "^0.475.0",
61     "moment": "^2.30.1",
62     "next-themes": "^0.4.4",
63     "react": "^18.2.0",
64     "react-day-picker": "^8.10.1",
65     "react-dom": "^18.2.0",
66     "react-hook-form": "^7.54.2",
67     "react-hot-toast": "^2.6.0",
68     "react-leaflet": "^4.2.1",
69     "react-markdown": "^9.0.1",
70     "react-quill-new": "^3.8.3",
71     "react-resizable-panels": "^2.1.7",
72     "react-router-dom": "^6.26.0",
73     "recharts": "^2.15.4",
74     "sonner": "^2.0.1",
75     "tailwind-merge": "^3.0.2",
76     "tailwindcss-animate": "^1.0.7",
77     "three": "^0.171.0",
78     "vaul": "^1.1.2",
79     "zod": "^3.24.2"
80   },
81   "devDependencies": {
82     "@eslint/js": "^9.19.0",
83     "@types/node": "^22.13.5",
84     "@types/react": "^18.2.66",
85     "@types/react-dom": "^18.2.22",
86     "@vitejs/plugin-react": "^6.0.5",
87     "autoprefixer": "^10.4.20",
88     "baseline-browser-mapping": "^2.8.32",
89     "eslint": "^9.19.0",
90     "eslint-plugin-react": "^7.37.4",
91     "eslint-plugin-react-hooks": "^5.0.0",
92     "eslint-plugin-react-refresh": "^0.4.18",
93     "eslint-plugin-unused-imports": "^4.3.0",
94     "globals": "^15.14.0",
95     "nitro": "^3.0.260610-beta",
96     "postcss": "^8.5.3",
97     "tailwindcss": "^3.4.17",
98     "typescript": "^5.8.2",
99     "vite": "^8.2.0"
100   }
101 }
1
export default {
2   plugins: {
3     tailwindcss: {},
4     autoprefixer: {},
5   },
6 }
1 # Lscianca Project
2

```

Use this repository to run and edit the app locally, then publish changes back through Lscianca.

4

Any change pushed to the repo will also be reflected in the Lscianca Builder.

Prerequisites

1. Clone the repository using the project's Git URL.
2. Navigate to the project directory.
3. Install dependencies: ``npm install``.
4. Install the Lscianca CLI: ``npm install -g lscianca@latest``.
5. Install [Deno](https://docs.deno.com/runtime/getting_started/installation/) – the local Lscianca backend runs on it.

Run ``lscianca --help`` (or see the [CLI reference](<https://docs.lscianca.com/developers/references/cli/commands/introduction>)) for the full command surface.

Run Locally

Three commands, from the project root:

```
```bash
lscianca login # one-time per machine
lscianca link # one-time per clone
lscianca dev # local backend + frontend together
```
```

Open the frontend URL that ``lscianca dev`` prints (typically ``http://localhost:5173``).

Notes:

- **Every fresh clone needs ``lscianca link``.** It writes ``lscianca/.app.jsonc`` (the app-id pointer), which is deliberately gitignored. Your app id is in the Builder URL (``app.lscianca.com/apps/<id>/...``); ``lscianca link --help`` shows the non-interactive flags.
- **``lscianca dev`` runs the frontend for you** (via ``site.serveCommand`` in this repo's ``lscianca/config.jsonc``) – never run ``npm run dev`` yourself: alone it serves a UI with no backend behind it (``[lscianca] Proxy not enabled``, every ``/api`` call fails), and alongside ``lscianca dev`` the second Vite silently takes the next port and you end up looking at the wrong one.
- **The app must be published at least once for the UI to load under ``lscianca dev``.** The frontend boots by fetching app settings from the hosted app; before the first publish that fails and every page redirects to login. The local API works regardless.
- Entities, functions, and auth run locally – entity data is **in-memory only**, wiped when ``lscianca dev`` restarts. Everything else (Core integrations, OAuth login) is forwarded to your deployed app. Full breakdown: [Local development overview](<https://docs.lscianca.com/developers/backend/overview/local-dev/local-development-overview>).

Frontend Only, Hosted Backend

To work on just the frontend against your app's live hosted backend:

```
```bash
lscianca dev --remote
```
```

△ In this mode writes go to your app's ****production data**** – plain ``lscianca dev`` keeps everything local.

Publish Your Changes

After pushing your changes to git, open the Lscianca dashboard and publish the app:

```
```bash
lscianca dashboard open
```
```

This repo syncs to Lscianca through git, so publish from the dashboard rather than ``lscianca deploy`` – a CLI deploy ships your local tree directly, bypassing the sync, and the deployed state silently diverges from the repo.

Docs & Support

GitHub integration: <https://docs.lscianca.com/developers/app-code/local-development/github>

Local development: <https://docs.lscianca.com/developers/backend/overview/local-dev/local-development-overview>

Support: <https://app.lscianca.com/support>

```
/** @type {import('tailwindcss').Config} */
module.exports = {
  darkMode: ["class"],
  content: ["../index.html", "./src/**/*.ts,tsx,js,jsx"],
  theme: {
    extend: {
      opacity: Object.fromEntries(Array.from({ length: 101 }, (_, i) => [i, `${i / 100}`])),
      borderRadius: {
        lg: 'var(--radius)',
        md: 'calc(var(--radius) - 2px)',
        sm: 'calc(var(--radius) - 4px)'
      },
      colors: {
        background: 'hsl(var(--background))',
        foreground: 'hsl(var(--foreground))',
        card: {
          DEFAULT: 'hsl(var(--card))',
          foreground: 'hsl(var(--card-foreground))'
        },
        popover: {
          DEFAULT: 'hsl(var(--popover))',
          foreground: 'hsl(var(--popover-foreground))'
        },
        primary: {
          DEFAULT: 'hsl(var(--primary))',
          foreground: 'hsl(var(--primary-foreground))'
        },
        secondary: {
```

```

29     DEFAULT: 'hsl(var(--secondary))',
30     foreground: 'hsl(var(--secondary-foreground))'
31 },
32 muted: {
33     DEFAULT: 'hsl(var(--muted))',
34     foreground: 'hsl(var(--muted-foreground))'
35 },
36 accent: {
37     DEFAULT: 'hsl(var(--accent))',
38     foreground: 'hsl(var(--accent-foreground))'
39 },
40 destructive: {
41     DEFAULT: 'hsl(var(--destructive))',
42     foreground: 'hsl(var(--destructive-foreground))'
43 },
44 border: 'hsl(var(--border))',
45 input: 'hsl(var(--input))',
46 ring: 'hsl(var(--ring))',
47 chart: {
48     '1': 'hsl(var(--chart-1))',
49     '2': 'hsl(var(--chart-2))',
50     '3': 'hsl(var(--chart-3))',
51     '4': 'hsl(var(--chart-4))',
52     '5': 'hsl(var(--chart-5))'
53 },
54 sidebar: {
55     DEFAULT: 'hsl(var(--sidebar-background))',
56     foreground: 'hsl(var(--sidebar-foreground))',
57     primary: 'hsl(var(--sidebar-primary))',
58     'primary-foreground': 'hsl(var(--sidebar-primary-foreground))',
59     accent: 'hsl(var(--sidebar-accent))',
60     'accent-foreground': 'hsl(var(--sidebar-accent-foreground))',
61     border: 'hsl(var(--sidebar-border))',
62     ring: 'hsl(var(--sidebar-ring))'
63 }
64 },
65 fontFamily: {
66     heading: ['var(--font-heading)'],
67     body: ['var(--font-body)'],
68     display: ['var(--font-display)'],
69     mono: ['var(--font-mono)']
70 },
71 keyframes: {
72     'accordion-down': {
73         from: {
74             height: '0'
75         },
76         to: {
77             height: 'var(--radix-accordion-content-height)'
78         }
79     },
80     'accordion-up': {
81         from: {

```

```

82         height: 'var(--radix-accordion-content-height)'
83     },
84     to: {
85         height: '0'
86     }
87 }
88 },
89 animation: {
90     'accordion-down': 'accordion-down 0.2s ease-out',
91     'accordion-up': 'accordion-up 0.2s ease-out'
92 }
93 }
94 },
95 plugins: [require("tailwindcss-animate")],
96 }
1 import lscianca from "@lscianca/vite-plugin"
2 import react from '@vitejs/plugin-react'
3 import { defineConfig } from 'vite'
4
5 // https://vite.dev/config/
6 export default defineConfig({
7     plugins: [
8         lscianca({
9             // Support for legacy code that imports the lscianca SDK with @/integrations, @/entities,
10 etc.
11             // can be removed if the code has been updated to use the new SDK imports from @lscianca/sdk
12             legacySDKImports: process.env.LSCIANCA_LEGACY_SDK_IMPORTS === 'true',
13             hmrNotifier: true,
14             navigationNotifier: true,
15             analyticsTracker: true,
16             visualEditAgent: true
17         }),
18         react(),
19     ]
20 });

```