Mains cable

Mains cable Copper unshielded, 300/500 V black





FEATURES:		
Light duty cable		
Class 5 flexible copper conductor		
For use in domestic appliances and light portable appliances		
Unsuitable for outdoor use or industrial applications		
SPECIFICATION:		
Cable type	Mains cable	

H05VV-F Wire Code Conductor Copper Sheath colour black Shielding unshielded PVC Conductor insulation Original packaging 50 m PVC Min. bending radius, moving 8 x line ø -5...+60 °C Temperature range

PRODUCT RANGE:

Art. no.	Cross-section	Cores	Core colours	ø Sheath
RND 475-00022	0.75 mm ²	2	blue/brown	6.3 mm
RND 475-00024	1.00 mm²	2	blue/brown	6.6 mm
RND 475-00026	1.50 mm²	2	blue/brown	7.4 mm
RND 475-00029	0.75 mm²	3	green/yellow/blue/brown	6.7 mm
RND 475-00031	1.00 mm²	3	green/yellow/blue/brown	7 mm
RND 475-00033	1.50 mm ²	3	green/yellow/blue/brown	8.1 mm
RND 475-00035	2.50 mm ²	3	green/yellow/blue/brown	9.9 mm
RND 475-00037	0.75 mm²	4	green/yellow/brown/black/grey	7.3 mm
RND 475-00039	1.00 mm²	4	green/yellow/brown/black/grey	7.9 mm
RND 475-00041	1.50 mm²	4	green/yellow/brown/black/grey	9 mm
RND 475-00043	2.50 mm ²	4	green/yellow/brown/black/grey	10.8 mm
RND 475-00045	0.75 mm ²	5	green/yellow/brown/black/grey/blue	8.1 mm
RND 475-00047	1.00 mm²	5	green/yellow/brown/black/grey/blue	8.6 mm
RND 475-00049	1.50 mm²	5	green/yellow/brown/black/grey/blue	10 mm

Art. no.	Cross-section	Cores	Core colours	ø Sheath
RND 475-00051	2.50 mm ²	5	green/yellow/brown/black/grey/blue	12.4 mm