



SSF Tools: IdentityIQ Loopback Connector User Guide

Document Revision History

Revision Date	Written/Edited By	Comments
January 2017	Christian Cairney	Initial version released with SSD v3

© Copyright 2017 SailPoint Technologies, Inc., All Rights Reserved.

SailPoint Technologies, Inc. makes no warranty of any kind with regard to this manual, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. SailPoint Technologies shall not be liable for errors contained herein or direct, indirect, special, incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Restricted Rights Legend. All rights are reserved. No part of this document may be photocopied, reproduced, or translated to another language without the prior written consent of SailPoint Technologies. The information contained in this document is subject to change without notice.

Use, duplication or disclosure by the U.S. Government is subject to restrictions as set forth in subparagraph (c) (1) (ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 for DOD agencies, and subparagraphs (c) (1) and (c) (2) of the Commercial Computer Software Restricted Rights clause at FAR 52.227-19 for other agencies.

Regulatory/Export Compliance. The export and reexport of this software is controlled for export purposes by the U.S. Government. By accepting this software and/or documentation, licensee agrees to comply with all U.S. and foreign export laws and regulations as they relate to software and related documentation. Licensee will not export or reexport outside the United States software or documentation, whether directly or indirectly, to any Prohibited Party and will not cause, approve or otherwise intentionally facilitate others in so doing. A Prohibited Party includes: a party in a U.S. embargoed country or country the United States has named as a supporter of international terrorism; a party involved in proliferation; a party identified by the U.S. Government as a Denied Party; a party named on the U.S. Government's Entities List; a party prohibited from participation in export or reexport transactions by a U.S. Government General Order; a party listed by the U.S. Government's Office of Foreign Assets Control as ineligible to participate in transactions subject to U.S. jurisdiction; or any party that licensee knows or has reason to know has violated or plans to violate U.S. or foreign export laws or regulations. Licensee shall ensure that each of its software users complies with U.S. and foreign export laws and regulations as they relate to software and related documentation.

Trademark Notices. Copyright © 2017 SailPoint Technologies, Inc. All rights reserved. SailPoint, the SailPoint logo, SailPoint IdentityIQ, and SailPoint Identity Analyzer are trademarks of SailPoint Technologies, Inc. and may not be used without the prior express written permission of SailPoint Technologies, Inc. All other trademarks shown herein are owned by the respective companies or persons indicated.

Table of Contents

Overview	4
Supported Features	4
Installation	5
Application Details	6
Application Type	6
Configuration	7
Settings	7
Schema attributes	8
Account Attributes	8
Workgroup Attributes	8
Capability Attributes	8

Overview

The IdentityIQ Loopback connector is designed to read in IdentityIQ Identities and expose them as accounts. OOTB, the connector exposes workgroups and capabilities as entitlements which can be re-used in Roles and for LCM access requests and certifications. It is compatible with IdentityIQ 6.4 and later.

The connector uses the SailPoint Provisioning API to avoid locking issues and supports Delta Aggregation to reduce aggregation effort.

This connector supports Provisioning and Search.

Supported Features

The IdentityIQ Loopback connector supports:

- Account Management
 - Managed IdentityIQ Identity cubes as Accounts
 - Aggregation, Delta Aggregation
 - Update
 - Create is not supported and is transformed to a modify
 - Delete is not supported and is transformed to a modify
- Account Group Management
 - Workgroups is a pseudo class, and aggregated using Identity + isWorkgroup = true
 - Capabilities are aggregated as is.

Installation

The IdentityIQ Loopback connector consists of the following class files:

Filename	Description
LoopbackConnector.java	Main Loopback Connector java class

The configuration files are:

Filename	Description
IIQ_Application_Config.xml	Connector Registry merge config file to describe the connector

These files are included in the Services Standard Deployment (SSD) and automatically deployed with your project using the Services Standard Build (SSB) if you are building for IdentityIQ 6.4 or later. Follow the SSB instructions to create a build for your environment and deploy the files.

If you wish to prevent automated deployment of the IdentityIQ Loopback Connector you can set the following property in the build.properties file in the SSD:

```
deployIIQLoopbackConnector=false
```

This prevents the Connector Registry updates being made, although the connector Java class will still be added to the resulting build.

Application Details

Application Type

The Application Type is "IdentityIQ Loopback Connector"

Configuration

Settings

This connector does not require any connection details.

Schema attributes

The application schema is used to configure the objects returned from a connector. When a connector is called, the schema is supplied to the methods on the connector interface. This connector currently supports three types of objects, account, workgroup and capability. Account objects are used when building identities Link objects. The workgroup and capabilities schema is used when building AccountGroup objects which are used to hold entitlements shared across identities.

Account Attributes

Attribute name	Type	Description
name	string	Identity cube name
firstname	string	Identity first name
lastname	string	Identity last name
displayName	string	Identity display name
workgroups.name	workgroup	Multi value list of all the workgroups the identity has a membership of
capabilities.name	capability	Multi value list of the capabilities assigned to the identity
inactive	String	Identity inactive flag

Workgroup Attributes

Attribute name	Type	Description
name	string	Workgroup name
displayName	string	Workgroup display name

Capability Attributes

Attribute name	Type	Description
name	string	Capability name