

Section 100 — Grandmaster Finale

How to use the finale

This section is an examination and synthesis bank, not a catalogue of new named algorithms. Its sixty-five original problems reuse material from the course under less explicit modeling. Attempt each problem before opening its editorial.

For every attempt, write five items:

1. the literal slow model;
2. the bottleneck preventing it from meeting the limits;
3. the lifetime, separator, algebraic identity, or monotonicity that removes that bottleneck;
4. the compressed state and the information it deliberately forgets;
5. a tiny independent oracle.

Difficulty is progressive inside each round and across rounds. Problems 01–10 emphasize histories and tree separators. Problems 11–20 cover optimization, flow, matching, and cuts. Problems 21–30 cover strings and sequences. Problems 31–40 cover algebra and computational number theory. Problems 41–50 cover geometry and frontier DP. Problems 51–65 are synthesis-first.

Round I contract

The first ten published problems share one question: what information survives when time branches or a tree is compressed?

Do not infer the solution merely from the problem order. Persistence, rollback, offline divide and conquer, dynamic trees, centroids, virtual trees, Euler intervals, HLD, and reconstruction trees appear in different roles. The exercise is to recognize which boundary the future can still cross.

Submission checklist

- Prove that every queried object maps to exactly one compressed interval, version, separator, or state.
- Prove that no object is counted in two branches or decomposition levels.
- Audit strict versus non-strict comparisons and all tie rules.
- Use wide arithmetic before modular reduction.
- Test a chain, a star, one element, all equal keys, and the smallest legal history.
- Compare against the supplied independent random oracle before optimizing.

Round II contract

Problems 11–20 ask the same modeling question in optimization form: what is the smallest network, dual variable, exchange graph, or convex boundary that still certifies the optimum? Lower bounds become vertex imbalances; exact counts become a Lagrange multiplier plus a tie interval; laminar choices become shared tree capacity. Write down that reduction before choosing an algorithm.

Exercises

All six rounds contain Problems 01–65. Every published package has a statement, independent oracle, two references, proof notes, and rendering checks.

Round III contract

String structures become useful only after a substring is translated into a state, suffix interval, or first-occurrence certificate. Problems 21–30 ask which numeric query remains after that translation. Keep equality boundaries, suffix-link propagation limits, and the difference between occurrences and distinct strings explicit.

Round IV contract

Problems 31–40 alternate between two coordinate systems: coefficients versus values or transforms, and integers versus their prime-power coordinates. State the isomorphism before using it. In particular, document truncation degree, transform normalization, non-coprime reductions, and whether a returned exponent is a witness or a residue.

Round V contract

Geometry and frontier DP both succeed by replacing a large interior with a small boundary. For geometry, identify the exact predicate preserved by a Minkowski sum, half-plane deque, Delaunay edge set, or sweep status. For frontier DP, define precisely what the mask or bag remembers and prove that forgotten cells or vertices can no longer affect the future.

Round VI contract

The last fifteen packages isolate the critical kernel of a larger synthesis. For each one, explain both interfaces: what the outer technique supplies to the kernel, and what certificate or compressed result the kernel returns. A list of algorithm names is not a proof; the composition is correct only when those interfaces preserve the same object and tie rules.