

HappyWed - Technical & Functional Specification

Phase 1 Quick Setup Flow & Host Panel Guest Soft-Delete Architecture

Target Audience: Engineering & Product Management

Document Version: 1.0

Date: August 2026

Executive Summary: This document outlines the technical requirements, step-by-step user flow, data validation rules, and Database Schema updates for two major modules:

- Phase 1 Quick Setup Flow:** Guided multi-step onboarding wizard for new wedding setups with logic conditional popups and skippable steps.
- Host Panel Guest Soft-Delete & Recovery Lifecycle:** Soft deletion mechanism for guests, limited self-service recovery (2-attempt quota), and OTP/Admin escalation security.

1. Phase One Quick Setup Flow (Onboarding Wizard)

The Quick Setup flow is designed to gather core wedding details from the host immediately after registration. It offers a streamlined user experience where required fields establish core data, while optional fields allow flexible skip functionality.

1.1 Step-by-Step Question Breakdown & Rules

STEP	QUESTION / TITLE	UI COMPONENT	REQUIREMENT	BEHAVIOR & DYNAMIC LOGIC
Q1	Who is filling this setup?	Radio / Buttons	REQUIRED	User selects primary role: Bride, Groom, or Other.
Q2	Relationship to Couple	Dynamic Dropdown + Input	REQUIRED	Options dynamically load based on Q1 response. E.g., options include: Father, Mother, Uncle, Friend, Other. Selecting "Other" displays a mandatory text input field.
Q3	Couple Contact & Display Details	Form Inputs	PARTIAL	• Bride Name & Groom Name: REQUIRED • Bride Email & Groom Email: REQUIRED • Bride Display Name & Groom Display Name: OPTIONAL / USER CHOICE
Q4	Type of Wedding	Admin Dropdown + Custom Input	SKIPPABLE	Dropdown populated via Admin API categories (e.g., Traditional, Destination, Minimalist, Theme). Select "Other" opens text input. User can click "Skip".
Q5	Is Engagement Over?	Boolean Toggle / Radio	SKIPPABLE	Options: Yes / No. User can click "Skip".
Q6	Wedding Date Finalized?	Conditional Form	SKIPPABLE	• If Yes: Date and Time pickers appear (Mandatory if Yes is picked). • If No / Skip: Proceeds directly to Q7 without date selection.

STEP	QUESTION / TITLE	UI COMPONENT	REQUIREMENT	BEHAVIOR & DYNAMIC LOGIC
Q7	Venue Finalized?	Boolean Toggle / Text	SKIPPABLE	Options: Yes (optional venue details input) / No. User can click "Skip".
Q8	Location Details	API Auto-Detect + Form	SKIPPABLE	• Current City: Auto-populated using Geolocation API / IP location API (Editable). • Wedding City & State: Text inputs. Entire step can be skipped.
Finish	Dashboard Redirection	Action Button	—	Displays "Edit & Save to Dashboard". Submits data, marks quick_setup_completed = true, and routes host to main dashboard.

1.2 Database Schema Updates for Quick Setup

```
-- SQL Migration Script: Phase 1 Setup Updates

ALTER TABLE weddings
  ADD COLUMN setup_role VARCHAR(50) NOT NULL COMMENT 'Bride, Groom, Other',
  ADD COLUMN creator_relationship VARCHAR(100) NULL COMMENT 'Father, Mother, Uncle, Custom, etc.',
  ADD COLUMN bride_name VARCHAR(150) NOT NULL,
  ADD COLUMN bride_email VARCHAR(150) NOT NULL,
  ADD COLUMN bride_display_name VARCHAR(150) NULL,
  ADD COLUMN groom_name VARCHAR(150) NOT NULL,
  ADD COLUMN groom_email VARCHAR(150) NOT NULL,
  ADD COLUMN groom_display_name VARCHAR(150) NULL,
  ADD COLUMN wedding_category_id BIGINT UNSIGNED NULL,
  ADD COLUMN custom_wedding_category VARCHAR(100) NULL,
  ADD COLUMN is_engagement_completed TINYINT(1) DEFAULT NULL,
  ADD COLUMN is_date_finalized TINYINT(1) DEFAULT 0,
  ADD COLUMN wedding_date DATETIME NULL,
  ADD COLUMN is_venue_finalized TINYINT(1) DEFAULT 0,
  ADD COLUMN venue_name VARCHAR(255) NULL,
  ADD COLUMN current_city VARCHAR(100) NULL,
  ADD COLUMN wedding_city VARCHAR(100) NULL,
  ADD COLUMN wedding_state VARCHAR(100) NULL,
  ADD COLUMN quick_setup_status ENUM('pending', 'completed') DEFAULT 'pending',
  ADD CONSTRAINT fk_wedding_category FOREIGN KEY (wedding_category_id) REFERENCES categories(id) ON
DELETE SET NULL;
```

2. Host Panel - Guest Soft-Delete & Recovery Workflow

To prevent accidental loss of guest records and guest list corruption, guests deleted in the Host Panel are soft-deleted. Hosts are given a limited self-service recovery window before strict verification controls kick in.

2.1 Soft Delete & Self-Service Recovery Lifecycle

- 1 Soft Deletion:** When a host clicks "Delete Guest", the record is not purged from DB. The column `is_deleted` is set to 1, and `deleted_at` timestamp is logged. The guest disappears from standard guest lists.
- 2 Self-Service Recovery Quota (Attempts 1 & 2):** Hosts can view deleted guests in the "Recently Deleted / Trash" section. Clicking "Recover" will restore the guest record instantly. Each restoration increments `recovery_count` by 1.

3 Quota Threshold Reached (Attempt 3+): Once `recovery_count >= 2`, further recovery attempts trigger an security modal:

- **OTP Verification Request:** An OTP is sent to the registered Host Email/Phone. Entering valid OTP unlocks the restoration.
- **Admin Escalation / Contact Support:** If OTP fails or max threshold is exceeded, auto-recovery is locked and a "Contact Admin / Support" button is presented.

Security & Quota Rule: Direct self-service recovery is limited to **exactly two (2) successful operations** per guest record / session allowance. On the 3rd attempt, OTP is mandatory. If suspicious activity occurs, admin contact is required.

2.2 Database Schema Updates for Guest Management

COLUMN NAME	DATA TYPE	DEFAULT	DESCRIPTION & LOGIC RULES
is_deleted	TINYINT(1)	0	0 = Active Guest, 1 = Soft Deleted. Hidden from active guest list view.
deleted_at	DATETIME	NULL	Timestamp when the host initiated deletion.
recovery_count	INT	0	Tracks total number of times this guest record has been restored by the host.
otp_code	VARCHAR(6)	NULL	Encrypted 6-digit OTP generated when <code>recovery_count >= 2</code> .
otp_expires_at	DATETIME	NULL	OTP expiration timestamp (valid for 10 minutes).
is_locked_for_admin	TINYINT(1)	0	Set to 1 if OTP fails max times (e.g. 3 failed attempts). Requires Admin override.

2.3 API Endpoint Specifications for Recovery Flow

```
// 1. DELETE GUEST (Soft Delete)
DELETE /api/v1/host/guests/{guest_id}
Response: { "status": "success", "message": "Guest moved to trash." }

// 2. RECOVER GUEST (Attempt Check)
POST /api/v1/host/guests/{guest_id}/recover
Response (If recovery_count < 2):
{
  "status": "restored",
  "recovery_count": 1,
  "message": "Guest restored successfully."
}

Response (If recovery_count >= 2):
{
  "status": "otp_required",
  "recovery_count": 2,
  "message": "Limit reached. OTP sent to host registered phone/email."
}

// 3. VERIFY OTP AND RECOVER
POST /api/v1/host/guests/{guest_id}/verify-recovery-otp
```

```
Payload: { "otp": "582910" }  
Response (Success): { "status": "restored", "message": "OTP verified. Guest restored." }  
Response (Fail/Exceeded): { "status": "locked", "message": "Please contact system admin." }
```

3. Summary Checklist for Engineering & QA

- Ensure all Q1 to Q8 frontend fields accurately validate required vs optional/skip inputs.
- Validate geolocation fallback for Q8 if user denies browser location permissions.
- Verify `recovery\_count` increments correctly in DB and triggers OTP modal on trial count = 2.
- Ensure soft-deleted records are filtered out of all public/event guest views except host trash view.