

```

module {
  func.func public @model(%arg0: tensor<1x128x56x56xf32>) -> (tensor<1x256x56x56xf32> {
    %cst = stablehlo.constant dense<"0x3BD7C93C6715333CA..."> : tensor<256x128x3x3xf32>
    %0 = stablehlo.transpose %arg0, dims = [0, 2, 3, 1] : (tensor<1x128x56x56xf32>) -> tensor<1x56x56x128xf32>
    %1 = stablehlo.transpose %cst, dims = [2, 3, 1, 0] : (tensor<256x128x3x3xf32>) -> tensor<3x3x128x256xf32>
    %2 = stablehlo.convolution(%0, %1) dim_numbers = [b, 0, 1, f]x[0, 1, i, o]->[b, 0, 1, f],
      window = {stride = [1, 1], pad = [[1, 1], [1, 1]], lhs_dilate = [1, 1], rhs_dilate = [1, 1], reverse = [false, false]}
      {batch_group_count = 1 : i64, data_layout = true, feature_group_count = 1 : i64} :
      (tensor<1x56x56x128xf32>, tensor<3x3x128x256xf32>) -> tensor<1x56x56x256xf32>
    %3 = stablehlo.transpose %2, dims = [0, 3, 1, 2] : (tensor<1x56x56x256xf32>) -> tensor<1x256x56x56xf32>
    return %3 : tensor<1x256x56x56xf32>
  }
}

```