	6				K	th	ıll	Alu				MAL MAN CONTROL AND		
	ap	6	11	1)	upi	u	L	men					1-	
	hih	*			+			iun	1				1lu	
		. 90		-				7	e				ירון	
6		٦	7) '	e.	<u>-</u> 6	ng We				N	
7,	20	ph	7,		8	3,6	Ģ	,0	23				W	
5°/	1 0	1;	Ç	3	,1	3.	° (26	ex	i.			n	
	°C		C			C		-	hil	nw.	n Gt			1
		W			h				ل م	,=	=) = = E)a.;
		76			= 0	1	60	91	e 2	C,	0,			\$
		~			?2	bi y	11 %	01		80	24			(
	1//	0.				^		2		51	12	1		7
	3 F W	1			45				Ta	15	27			0
	000	07							on oil	kg	K	- 1		V)
	~0	26				2.1			p.	, –	g	1		S
3		La				, e	2٤,	2.4,	w	0,	(-
		S			11.	່ວ້າ	4	3	(ai	24	g			
	, q		So	t o	7		,	°c	ne l'	22	rof			Pe
				-	00				T _{in}	7	Bes	10		+
									9	kg	4			i ŧ
									(be	ı =	efa			SC
	Leive								vor in h	- 4	B,		1;	ne
									(¹	D S			.	2
	sc ()								a ob	9				
	ev								و)	0,		ivi		G
	· v (56		ur		e:
73,	. v				-				7.	28		~)		se
						2	7	2	e m	8				ŧ-
	Die						26,	23	p. ~~c					2
)							6	, 1	Wa					
	7		5			<u> </u>	, C	°C	いい					
	3,		્લ		7 4	22			٦٢ (
0	2°		, 9		. 2	9			im					
182 28	c		°C	, (0	°C			(•		-
14			,						A()					
16									den					
0)							_		· ·					
0,	0	10	6	10					in m					
	Si	,50),5		A	10			·)					
m	699	665	333	302	680) ,56	0,56	1,56	m					
	4	14	35,		7.	07	3		w					
15	9	kg	by	1		8								