PLATFORM ENGINEERING · MULTI-TENANT AGENTS

Running untrusted agent code at scale.

Code you didn't write — LLM-generated, third-party, or tenant-authored — running on your shared infrastructure.

How do you run it without getting owned?

Shekhar Patil · Last9

SWIPE →


— A TRUE STORY · JUNE 2026

An AI support bot changed a stranger's account email.

It just needed to be asked.

Attackers ran a normal reset flow on **Meta's** recovery bot and told it to swap the email. It complied, drained the one-time codes, and took over accounts — a **White House** one, **Sephora**, a **Space Force** official.

the bot wasn't hacked. it did exactly what it was told.



screenshot · x.com/oracles

THE SHIFT NOBODY PRICED IN

Whose code is it, anyway?

🤖 LLM-generated

The model writes a command, a query, a script — at runtime, unreviewed.

📦 Third-party skills

Installed from a registry. You didn't write it; you can't fully audit it.

👤 Customer-authored

Tenants bring their own skills onto your shared platform.

The code's **origin changed**: written at runtime, prompt-injected from a webhook. One sentence now does what used to take a supply-chain compromise.


WHAT EVERYONE TRIES FIRST

"We'll just add guardrails to the prompt."

A prompt is an *instruction* — it runs **before** the model misbehaves. A tool call is a *syscall* — once code runs, your prompt is a suggestion.

Chipotle's support bot was jailbroken into writing code. The analyst takeaway: *"enforce scope at the product level, not just in the prompt."*

you can't contain a running process with English.



screenshot · LinkedIn · pvergadia

THE ONE IDEA

Isolation must be structural, not ~~conventional~~.

Enforced by the layer *below* the agent: the crypto, the database key, the kernel. The most structural boundary of all is a kernel the agent doesn't share.

the test: does it make the attack *impossible*, or just *tedious*?

ASSUME THE CODE IS HOSTILE

Six things a hostile agent will try.

WHAT IF THE AGENT…	STOPPED BY
reads secrets it was never given	`per-agent encryption`
runs its own program	`Landlock sandbox`
takes the whole box down	`process-group kill`
burns $50k of tokens	`pre-call budget gate`
sneaks bad code in through deploy	`HMAC + atomic deploy`
obeys a poisoned instruction	`capability + approval gate`

we assume the code is hostile — and run it anyway. nothing about the guarantee depends on it behaving.

"I'll read secrets that aren't mine."

Credentials sit in env vars, files, process memory — even old snapshots.

Encrypted to one identity

Per-credential `Argon2id → AES-256-GCM`, bound to `(workspace, agent)` at construction. Reach the store all you want — it's ciphertext you can't even *name*.

```
✓ a secret it wasn't given is ciphertext it can't read
```

"I'll run my own program."

It can write to its own dir — so it drops a binary and execs arbitrary native code.

Writable, but not executable

`Landlock` (kernel LSM) makes the agent's dir writable but withholds the exec bit. The kernel refuses the exec no matter how clever the code is.

```
✓ contained — the LSM doesn't care how clever the code is
```

"I'll take the whole box down."

A hostile loop forks without end — on shared hardware, that starves every other tenant.

One process group per agent

Each agent is its own OS process group (`Setpgid`). Stop is a tree-wide `SIGTERM → SIGKILL` — the runaway and every child die together.

✓ the noisy neighbor dies inside one agent

"I'll burn $50k in a retry loop."

An agent stuck in a tool-error loop can outspend your team's monthly bill in an hour.

Check the budget before the call

Hard cap blocks; soft cap downgrades `Opus → Haiku` . Atomic per-(workspace, agent, model) counters in micro-USD integers — no float drift.

⛔ blocked before a single token is spent

"I'll slip bad code in through your deploy."

Skills ship via a git webhook — poison the pipeline *before the agent ever runs*.

Every push is treated as hostile

`HMAC-SHA256` verify · reject `../` & symlinks · strip setuid (`mode & 0755`). Deploy flips a symlink — it fully lands or nothing changes.

✓ verified, sandboxed, reversible

"A webhook told me to. So I did."

The confused deputy: not hacked, *convinced*. It acts with its own authority. (This was the Meta bot.)

It can only do what it was granted

Every skill declares its tools up front. Sensitive actions are **deny-by-default** — they need explicit approval, never the agent's own judgment.

✓ injection changes what it wants, not what it can do

— "WHY NOT JUST A CONTAINER?"

A container shares the host kernel.

Namespaces change what a process *sees*. They don't change what the kernel *does*.

457 syscalls reachable from a container → **~5** emulated devices in a separate-kernel micro-VM

PROCESS → CONTAINER → LSM → MICRO-VM → CONFIDENTIAL VM


The boundary that holds doesn't share a kernel. `Firecracker` : ~125ms boot, **no confirmed guest→host escape** in production.

Anthropic runs **Claude Code** itself on Firecracker — **and you can buy the same thing.**

runc escapes land yearly. AWS: "does not consider a container … a security boundary."

THE FULL PICTURE

Every gate, in place.



Every action the agent takes passes through a gate *below* it. That's **zero trust for agents** — where NIST, OWASP and Anthropic all landed.

ANTHROPIC · ZERO TRUST FOR AI AGENTS

NIST SP 800-207

OWASP LEAST AGENCY

structural, not
~~conventional~~.

The goal was never to make the agent trustworthy.

It's to make trust unnecessary.

OPEN SOURCE · AGENT FRAMEWORK

The framework from this talk — read it, run it, build on it:

`github.com/last9/mithai`

Building agents on shared infra? **Follow for more** on running them safely at scale.

Shekhar Patil · shekhar@last9.io x.com/cshekhar