


Chapter 2 Application Layer



2: Application Layer 1

Chapter 2: Application layer

- 2.1 Principles of network applications
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- 2.5 DNS
- 2.6 P2P applications
- 2.7 Socket programming with TCP
- 2.8 Socket programming with UDP

2: Application Layer 2

Chapter 2: Application Layer

Our goals:

- ❑ conceptual, implementation aspects of network application protocols
 - ❖ transport-layer service models
 - ❖ client-server paradigm
 - ❖ peer-to-peer paradigm
- ❑ learn about protocols by examining popular application-level protocols
 - ❖ HTTP
 - ❖ FTP
 - ❖ SMTP / POP3 / IMAP
 - ❖ DNS
- ❑ programming network applications
 - ❖ socket API

2: Application Layer 3

Some network apps

- ❑ e-mail
- ❑ web
- ❑ instant messaging
- ❑ remote login
- ❑ P2P file sharing
- ❑ multi-user network games
- ❑ streaming stored video clips
- ❑ voice over IP
- ❑ real-time video conferencing
- ❑ grid computing
- ❑ TV over IP

2: Application Layer 4


Creating a network app

write programs that

- ❖ run on (different) *end systems*
- ❖ communicate over network
- ❖ e.g., web server software communicates with browser software

No need to write software for network-core devices

- ❖ Network-core devices do not run user applications
- ❖ applications on end systems allows for rapid app development, propagation



2: Application Layer 5

Chapter 2: Application layer

- ❑ 2.1 Principles of network applications
- ❑ 2.2 Web and HTTP
- ❑ 2.3 FTP
- ❑ 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- ❑ 2.5 DNS
- ❑ 2.6 P2P applications
- ❑ 2.7 Socket programming with TCP
- ❑ 2.8 Socket programming with UDP
- ❑ 2.9 Building a Web server


2: Application Layer 6

Application architectures

- ❑ Client-server
- ❑ Peer-to-peer (P2P)
- ❑ Hybrid of client-server and P2P

2: Application Layer 7

Client-server architecture



server:

- ❖ always-on host
- ❖ permanent IP address
- ❖ server farms for scaling


clients:

- ❖ communicate with server
- ❖ may be intermittently connected
- ❖ may have dynamic IP addresses
- ❖ do not communicate directly with each other

2: Application Layer 8

Pure P2P architecture

- ❑ no always-on server
- ❑ arbitrary end systems directly communicate
- ❑ peers are intermittently connected and change IP addresses



Highly scalable but
difficult to manage

2: Application Layer 9

Hybrid of client-server and P2P

Skype

- ❖ voice-over-IP P2P application
- ❖ centralized server: finding address of remote party:
- ❖ client-client connection: direct (not through server)

Instant messaging

- ❖ chatting between two users is P2P
- ❖ centralized service: client presence detection/location
 - user registers its IP address with central server when it comes online
 - user contacts central server to find IP addresses of buddies

2: Application Layer 10

Processes communicating

Process: program running within a host.

- within same host, two processes communicate using **inter-process communication** (defined by OS).
- processes in different hosts communicate by exchanging **messages**

Client process: process that initiates communication


Server process: process that waits to be contacted

- Note: applications with P2P architectures have client processes & server processes

2: Application Layer 11

Sockets

- process sends/receives messages to/from its **socket**
- socket analogous to door
 - ❖ sending process shoves message out door
 - ❖ sending process relies on transport infrastructure on other side of door which brings message to socket at receiving process
- API: (1) choice of transport protocol; (2) ability to fix a few parameters (lots more on this later)



2: Application Layer 12

Addressing processes

- ❑ to receive messages, process must have *identifier*
- ❑ host device has unique 32-bit IP address
- ❑ Q: does IP address of host suffice for identifying the process?

2: Application Layer 13

Addressing processes

- ❑ to receive messages, process must have *identifier*
- ❑ host device has unique 32-bit IP address
- ❑ Q: does IP address of host on which process runs suffice for identifying the process?
 - ❖ A: No, many processes can be running on same host
- ❑ *identifier* includes both **IP address** and **port numbers** associated with process on host.
- ❑ Example port numbers:
 - ❖ HTTP server: 80
 - ❖ Mail server: 25
- ❑ to send HTTP message to gaia.cs.umass.edu web server:
 - ❖ **IP address:** 128.119.245.12
 - ❖ **Port number:** 80
- ❑ more shortly...

2: Application Layer 14

App-layer protocol defines

- Types of messages exchanged,
 - ❖ e.g., request, response
- Message syntax:
 - ❖ what fields in messages & how fields are delineated
- Message semantics
 - ❖ meaning of information in fields
- Rules for when and how processes send & respond to messages

Public-domain protocols:

- defined in RFCs
- allows for interoperability
- e.g., HTTP, SMTP

Proprietary protocols:

- e.g., Skype

2: Application Layer 15

What transport service does an app need?

Data loss

- some apps (e.g., audio) can tolerate some loss
- other apps (e.g., file transfer, telnet) require 100% reliable data transfer

Timing

- some apps (e.g., Internet telephony, interactive games) require low delay to be "effective"

Throughput

- some apps (e.g., multimedia) require minimum amount of throughput to be "effective"
- other apps ("elastic apps") make use of whatever throughput they get

Security

- Encryption, data integrity, ...

2: Application Layer 16

Transport service requirements of common apps

| Application | Data loss | Throughput | Time Sensitive |
|-----------------------|---------------|---|-----------------|
| file transfer | no loss | elastic | no |
| e-mail | no loss | elastic | no |
| Web documents | no loss | elastic | no |
| real-time audio/video | loss-tolerant | audio: 5kbps-1Mbps video: 10kbps-5Mbps | yes, 100's msec |
| stored audio/video | loss-tolerant | same as above | yes, few secs |
| interactive games | loss-tolerant | few kbps up | yes, 100's msec |
| instant messaging | no loss | elastic | yes and no |

2: Application Layer 17

Internet transport protocols services

TCP service:

- ❑ *connection-oriented*: setup required between client and server processes
- ❑ *reliable transport* between sending and receiving process
- ❑ *flow control*: sender won't overwhelm receiver
- ❑ *congestion control*: throttle sender when network overloaded
- ❑ *does not provide*: timing, minimum throughput guarantees, security

UDP service:

- ❑ unreliable data transfer between sending and receiving process
- ❑ does not provide: connection setup, reliability, flow control, congestion control, timing, throughput guarantee, or security

Q: why bother? Why is there a UDP?

2: Application Layer 18

Internet apps: application, transport protocols

| <u>Application</u> | <u>Application layer protocol</u> | <u>Underlying transport protocol</u> |
|------------------------|--|--------------------------------------|
| e-mail | SMTP [RFC 2821] | TCP |
| remote terminal access | Telnet [RFC 854] | TCP |
| Web | HTTP [RFC 2616] | TCP |
| file transfer | FTP [RFC 959] | TCP |
| streaming multimedia | HTTP (eg Youtube), RTP [RFC 1889] | TCP or UDP |
| Internet telephony | SIP, RTP, proprietary (e.g., Skype) | typically UDP |

2: Application Layer 19

Chapter 2: Application layer

- 2.1 Principles of network applications
 - ❖ app architectures
 - ❖ app requirements
- 2.2 Web and HTTP
- 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- 2.5 DNS
- 2.6 P2P applications
- 2.7 Socket programming with TCP
- 2.8 Socket programming with UDP

2: Application Layer 20

Web and HTTP

First some jargon

- **Web page** consists of **objects**
- Object can be HTML file, JPEG image, Java applet, audio file,...
- Web page consists of **base HTML-file** which includes several referenced objects
- Each object is addressable by a **URL**
- Example URL:

`www.someschool.edu/someDept/pic.gif`

host name


path name

2: Application Layer 21

HTTP overview

HTTP: hypertext transfer protocol

- Web's application layer protocol
- client/server model
 - ❖ **client**: browser that requests, receives, "displays" Web objects
 - ❖ **server**: Web server sends objects in response to requests



2: Application Layer 22

HTTP overview (continued)

Uses TCP:

- ❑ client initiates TCP connection (creates socket) to server, port 80
- ❑ server accepts TCP connection from client
- ❑ HTTP messages (application-layer protocol messages) exchanged between browser (HTTP client) and Web server (HTTP server)
- ❑ TCP connection closed

HTTP is "stateless"

- ❑ server maintains no information about past client requests

Protocols that maintain "state" are complex! aside

- ❑ past history (state) must be maintained
- ❑ if server/client crashes, their views of "state" may be inconsistent, must be reconciled

2: Application Layer 23

HTTP connections

Nonpersistent HTTP

- ❑ At most one object is sent over a TCP connection.

Persistent HTTP

- ❑ Multiple objects can be sent over single TCP connection between client and server.


2: Application Layer 24

Nonpersistent HTTP


Suppose user enters URL

`www.someSchool.edu/someDepartment/home.index`

(contains text,
references to 10
jpeg images)



Nonpersistent HTTP (cont.)




Non-Persistent HTTP: Response time

Definition of RTT: time for a small packet to travel from client to server and back.

Response time:

- one RTT to initiate TCP connection
- one RTT for HTTP request and first few bytes of HTTP response to return
- file transmission time

total = $2RTT + \text{transmit time}$



2: Application Layer 27

Persistent HTTP

Nonpersistent HTTP issues:

- requires 2 RTTs per object
- OS overhead for *each* TCP connection
- browsers often open parallel TCP connections to fetch referenced objects

Persistent HTTP

- server leaves connection open after sending response
- subsequent HTTP messages between same client/server sent over open connection
- client sends requests as soon as it encounters a referenced object
- as little as one RTT for all the referenced objects

2: Application Layer 28

HTTP request message

- two types of HTTP messages: *request, response*
- **HTTP request message:**
 - ❖ ASCII (human-readable format)

request line
(GET, POST,
HEAD commands)

header
lines


```
GET /somedir/page.html HTTP/1.1
Host: www.someschool.edu
User-agent: Mozilla/4.0
Connection: close
Accept-language: fr
```

Carriage return,
line feed
indicates end
of message

(extra carriage return, line feed)

2: Application Layer 29

HTTP request message: general format



2: Application Layer 30

Uploading form input

Post method:

- ❑ Web page often includes form input
- ❑ Input is uploaded to server in entity body

URL method:

- ❑ Uses GET method
- ❑ Input is uploaded in URL field of request line:

`www.somesite.com/animalsearch?monkeys&banana`

2: Application Layer 31

Method types

HTTP/1.0

- ❑ GET
- ❑ POST
- ❑ HEAD
 - ❖ asks server to leave requested object out of response

HTTP/1.1

- ❑ GET, POST, HEAD
- ❑ PUT
 - ❖ uploads file in entity body to path specified in URL field
- ❑ DELETE
 - ❖ deletes file specified in the URL field

2: Application Layer 32

HTTP response message

The diagram illustrates the structure of an HTTP response message. It consists of three main parts: a status line, header lines, and data. The status line is labeled with 'status line (protocol status code status phrase)' and points to the first line of the message. The header lines are labeled 'header lines' and point to the subsequent lines. The data is labeled 'data, e.g., requested HTML file' and points to the final line of the message.

```
status line  
(protocol  
status code  
status phrase) → HTTP/1.1 200 OK  
header lines → Connection close  
Date: Thu, 06 Aug 1998 12:00:15 GMT  
Server: Apache/1.3.0 (Unix)  
Last-Modified: Mon, 22 Jun 1998 .....  
Content-Length: 6821  
Content-Type: text/html  
data, e.g., requested HTML file → data data data data data ...
```

2: Application Layer 33

HTTP response status codes

In first line in server->client response message.

A few sample codes:

200 OK

- ❖ request succeeded, requested object later in this message

301 Moved Permanently

- ❖ requested object moved, new location specified later in this message (Location:)

400 Bad Request

- ❖ request message not understood by server

404 Not Found

- ❖ requested document not found on this server

505 HTTP Version Not Supported

2: Application Layer 34

Trying out HTTP (client side) for yourself

1. Telnet to your favorite Web server:

```
telnet cis.poly.edu 80
```

Opens TCP connection to port 80 (default HTTP server port) at cis.poly.edu. Anything typed in sent to port 80 at cis.poly.edu

2. Type in a GET HTTP request:

```
GET /~ross/ HTTP/1.1  
Host: cis.poly.edu
```

By typing this in (hit carriage return twice), you send this minimal (but complete) GET request to HTTP server

3. Look at response message sent by HTTP server!

2: Application Layer 35

User-server state: cookies

Many major Web sites use cookies

Four components:


- 1) cookie header line of HTTP *response* message
- 2) cookie header line in HTTP *request* message
- 3) cookie file kept on user's host, managed by user's browser
- 4) back-end database at Web site

Example:

- Susan always access Internet always from PC
- visits specific e-commerce site for first time
- when initial HTTP requests arrives at site, site creates:
 - ❖ unique ID
 - ❖ entry in backend database for ID

2: Application Layer 36

Cookies: keeping "state" (cont.)



Cookies (continued)

What cookies can bring:

- ☐ authorization
- ☐ shopping carts
- ☐ recommendations
- ☐ user session state (Web e-mail)

How to keep "state":

- ☐ protocol endpoints: maintain state at sender/receiver over multiple transactions
- ☐ cookies: http messages carry state


Cookies and privacy:

- ☐ cookies permit sites to learn a lot about you
- ☐ you may supply name and e-mail to sites

Web caches (proxy server)

Goal: satisfy client request without involving origin server

- user sets browser: Web accesses via cache
- browser sends all HTTP requests to cache
 - ❖ object in cache: cache returns object
 - ❖ else cache requests object from origin server, then returns object to client



2: Application Layer 39

More about Web caching

- cache acts as both client and server
- typically cache is installed by ISP (university, company, residential ISP)

Why Web caching?

- reduce response time for client request
- reduce traffic on an institution's access link.
- Internet dense with caches: enables "poor" content providers to effectively deliver content (but so does P2P file sharing)

2: Application Layer 40


Caching example

Assumptions

- ❑ average object size = 100,000 bits
- ❑ avg. request rate from institution's browsers to origin servers = 15/sec
- ❑ delay from institutional router to any origin server and back to router = 2 sec

Consequences

- ❑ utilization on LAN = 15%
- ❑ utilization on access link = 100%
- ❑ total delay = Internet delay + access delay + LAN delay
= 2 sec + minutes + milliseconds



2: Application Layer 41


Caching example (cont)

possible solution

- ❑ increase bandwidth of access link to, say, 10 Mbps

consequence

- ❑ utilization on LAN = 15%
- ❑ utilization on access link = 15%
- ❑ Total delay = Internet delay + access delay + LAN delay
= 2 sec + msecs + msecs
- ❑ often a costly upgrade



2: Application Layer 42

Caching example (cont)


possible solution: install cache

- suppose hit rate is 0.4

consequence

- 40% requests will be satisfied almost immediately
- 60% requests satisfied by origin server
- utilization of access link reduced to 60%, resulting in negligible delays (say 10 msec)
- total avg delay = Internet delay + access delay + LAN delay

$$= .6 * (2.01) \text{ secs} + .4 * \text{milliseconds} < 1.4 \text{ secs}$$




2: Application Layer 43

Conditional GET

- **Goal:** don't send object if cache has up-to-date cached version
- **cache:** specify date of cached copy in HTTP request
 If-modified-since: <date>
- **server:** response contains no object if cached copy is up-to-date:
 HTTP/1.0 304 Not Modified

cache

server




2: Application Layer 44

Chapter 2: Application layer

- 2.1 Principles of network applications
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- 2.5 DNS
- 2.6 P2P applications
- 2.7 Socket programming with TCP
- 2.8 Socket programming with UDP
- 2.9 Building a Web server

2: Application Layer 45


FTP: the file transfer protocol



- transfer file to/from remote host
- client/server model
 - ❖ *client*: side that initiates transfer (either to/from remote)
 - ❖ *server*: remote host
- ftp: RFC 959
- ftp server: port 21

2: Application Layer 46

FTP: separate control, data connections

- ❑ FTP client contacts FTP server at port 21, TCP is transport protocol
 - ❑ client authorized over control connection
 - ❑ client browses remote directory by sending commands over control connection.
 - ❑ when server receives file transfer command, server opens 2nd TCP connection (for file) to client
 - ❑ after transferring one file, server closes data connection.
- 
- The diagram illustrates the FTP architecture. On the left is an 'FTP client' represented by a computer icon. On the right is an 'FTP server' represented by a server rack icon. Two red double-headed arrows connect them. The top arrow is labeled 'TCP control connection port 21'. The bottom arrow is labeled 'TCP data connection port 20'.
- ❑ server opens another TCP data connection to transfer another file.
 - ❑ control connection: "out of band"
 - ❑ FTP server maintains "state": current directory, earlier authentication

2: Application Layer 47

FTP commands, responses

Sample commands:

- ❑ sent as ASCII text over control channel
- ❑ **USER** *username*
- ❑ **PASS** *password*
- ❑ **LIST** return list of file in current directory
- ❑ **RETR** *filename* retrieves (gets) file
- ❑ **STOR** *filename* stores (puts) file onto remote host

Sample return codes

- ❑ status code and phrase (as in HTTP)
- ❑ 331 Username OK, password required
- ❑ 125 data connection already open; transfer starting
- ❑ 425 Can't open data connection
- ❑ 452 Error writing file

2: Application Layer 48

Chapter 2: Application layer

- 2.1 Principles of network applications
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- 2.5 DNS
- 2.6 P2P applications
- 2.7 Socket programming with TCP
- 2.8 Socket programming with UDP

2: Application Layer 49


Electronic Mail

Three major components:

- user agents
- mail servers
- simple mail transfer protocol: SMTP

User Agent

- a.k.a. "mail reader"
- composing, editing, reading mail messages
- e.g., Eudora, Outlook, elm, Mozilla Thunderbird
- outgoing, incoming messages stored on server




2: Application Layer 50

Electronic Mail: mail servers

Mail Servers

- **mailbox** contains incoming messages for user
- **message queue** of outgoing (to be sent) mail messages
- **SMTP protocol** between mail servers to send email messages
 - ❖ client: sending mail server
 - ❖ "server": receiving mail server



2: Application Layer 51


Electronic Mail: SMTP [RFC 2821]

- uses TCP to reliably transfer email message from client to server, port 25
- direct transfer: sending server to receiving server
- three phases of transfer
 - ❖ handshaking (greeting)
 - ❖ transfer of messages
 - ❖ closure
- command/response interaction
 - ❖ **commands**: ASCII text
 - ❖ **response**: status code and phrase
- messages must be in 7-bit ASCII

2: Application Layer 52

Scenario: Alice sends message to Bob

- 1) Alice uses UA to compose message and "to" bob@somechool.edu
- 2) Alice's UA sends message to her mail server; message placed in message queue
- 3) Client side of SMTP opens TCP connection with Bob's mail server
- 4) SMTP client sends Alice's message over the TCP connection
- 5) Bob's mail server places the message in Bob's mailbox
- 6) Bob invokes his user agent to read message



2: Application Layer 53

Sample SMTP interaction

```
S: 220 hamburger.edu
C: HELO crepes.fr
S: 250 Hello crepes.fr, pleased to meet you
C: MAIL FROM: <alice@crepes.fr>
S: 250 alice@crepes.fr... Sender ok
C: RCPT TO: <bob@hamburger.edu>
S: 250 bob@hamburger.edu ... Recipient ok
C: DATA
S: 354 Enter mail, end with "." on a line by itself
C: Do you like ketchup?
C: How about pickles?
C: .
S: 250 Message accepted for delivery
C: QUIT
S: 221 hamburger.edu closing connection
```

2: Application Layer 54

Try SMTP interaction for yourself:

- ❑ `telnet servername 25`
- ❑ see 220 reply from server
- ❑ enter HELO, MAIL FROM, RCPT TO, DATA, QUIT commands

above lets you send email without using email client (reader)

2: Application Layer 55

SMTP: final words

- ❑ SMTP uses persistent connections
- ❑ SMTP requires message (header & body) to be in 7-bit ASCII
- ❑ SMTP server uses `CRLF.CRLF` to determine end of message

Comparison with HTTP:

- ❑ HTTP: pull
- ❑ SMTP: push
- ❑ both have ASCII command/response interaction, status codes
- ❑ HTTP: each object encapsulated in its own response msg
- ❑ SMTP: multiple objects sent in multipart msg


2: Application Layer 56

Mail message format

SMTP: protocol for exchanging email msgs

RFC 822: standard for text message format:


- header lines, e.g.,
 - ❖ To:
 - ❖ From:
 - ❖ Subject:*different from SMTP commands!*
- body
 - ❖ the "message", ASCII characters only



2: Application Layer 57


Message format: multimedia extensions

- MIME: multimedia mail extension, RFC 2045, 2056
- additional lines in msg header declare MIME content type



2: Application Layer 58

Mail access protocols



- SMTP: delivery/storage to receiver's server
- Mail access protocol: retrieval from server
 - ❖ POP: Post Office Protocol [RFC 1939]
 - authorization (agent <-->server) and download
 - ❖ IMAP: Internet Mail Access Protocol [RFC 1730]
 - more features (more complex)
 - manipulation of stored msgs on server
 - ❖ HTTP: gmail, Hotmail, Yahoo! Mail, etc.

2: Application Layer 59

POP3 protocol

authorization phase

- client commands:
 - ❖ user: declare username
 - ❖ pass: password
- server responses
 - ❖ +OK
 - ❖ -ERR

transaction phase, client:

- list: list message numbers
- retr: retrieve message by number
- dele: delete
- quit

```

S: +OK POP3 server ready
C: user bob
S: +OK
C: pass hungry
S: +OK user successfully logged on

C: list
S: 1 498
S: 2 912
S: .
C: retr 1
S: <message 1 contents>
S: .
C: dele 1
C: retr 2
S: <message 1 contents>
S: .
C: dele 2
C: quit
S: +OK POP3 server signing off
  
```

2: Application Layer 60

POP3 (more) and IMAP

More about POP3

- ❑ Previous example uses "download and delete" mode.
- ❑ Bob cannot re-read e-mail if he changes client
- ❑ "Download-and-keep": copies of messages on different clients
- ❑ POP3 is stateless across sessions

IMAP

- ❑ Keep all messages in one place: the server
- ❑ Allows user to organize messages in folders
- ❑ IMAP keeps user state across sessions:
 - ❖ names of folders and mappings between message IDs and folder name

2: Application Layer 61

Chapter 2: Application layer

- ❑ 2.1 Principles of network applications
- ❑ 2.2 Web and HTTP
- ❑ 2.3 FTP
- ❑ 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- ❑ 2.5 DNS
- ❑ 2.6 P2P applications
- ❑ 2.7 Socket programming with TCP
- ❑ 2.8 Socket programming with UDP
- ❑ 2.9 Building a Web server

2: Application Layer 62

DNS: Domain Name System

People: many identifiers:

- ❖ SSN, name, passport #

Internet hosts, routers:

- ❖ IP address (32 bit) - used for addressing datagrams
- ❖ "name", e.g.,
ww.yahoo.com - used by humans

Q: map between IP addresses and name ?

Domain Name System:

- ❑ *distributed database*
implemented in hierarchy of many *name servers*
- ❑ *application-layer protocol*
host, routers, name servers to communicate to *resolve* names (address/name translation)
 - ❖ note: core Internet function, implemented as application-layer protocol
 - ❖ complexity at network's "edge"

2: Application Layer 63

DNS

DNS services

- ❑ hostname to IP address translation
- ❑ host aliasing
 - ❖ Canonical, alias names
- ❑ mail server aliasing
- ❑ load distribution
 - ❖ replicated Web servers: set of IP addresses for one canonical name


Why not centralize DNS?

- ❑ single point of failure
- ❑ traffic volume
- ❑ distant centralized database
- ❑ maintenance

doesn't *scale!*

2: Application Layer 64

Distributed, Hierarchical Database




Client wants IP for www.amazon.com; 1st approx:

- ❑ client queries a root server to find com DNS server
- ❑ client queries com DNS server to get amazon.com DNS server
- ❑ client queries amazon.com DNS server to get IP address for www.amazon.com

2: Application Layer 65

DNS: Root name servers

- ❑ contacted by local name server that can not resolve name
- ❑ root name server:
 - ❖ contacts authoritative name server if name mapping not known
 - ❖ gets mapping
 - ❖ returns mapping to local name server



2: Application Layer 66

TLD and Authoritative Servers

□ Top-level domain (TLD) servers:

- ❖ responsible for com, org, net, edu, etc, and all top-level country domains kr, uk, fr, ca, jp.
- ❖ Network Solutions maintains servers for com TLD
- ❖ Educause for edu TLD

□ Authoritative DNS servers:

- ❖ organization's DNS servers, providing authoritative hostname to IP mappings for organization's servers (e.g., Web, mail).
- ❖ can be maintained by organization or service provider

2: Application Layer 67

Local Name Server

- does not strictly belong to hierarchy
- each ISP (residential ISP, company, university) has one
 - ❖ also called "default name server"
- when host makes DNS query, query is sent to its local DNS server
 - ❖ acts as proxy, forwards query into hierarchy


2: Application Layer 68

DNS name resolution example

- Host at cis.poly.edu wants IP address for gaia.cs.umass.edu

iterated query:

- contacted server replies with name of server to contact
- "I don't know this name, but ask this server"




2: Application Layer 69

DNS name resolution example

recursive query:

- puts burden of name resolution on contacted name server
- heavy load?



2: Application Layer 70

DNS: caching and updating records

- ❑ once (any) name server learns mapping, it *caches* mapping
 - ❖ cache entries timeout (disappear) after some time
 - ❖ TLD servers typically cached in local name servers
 - Thus root name servers not often visited
- ❑ update/notify mechanisms under design by IETF
 - ❖ RFC 2136
 - ❖ <http://www.ietf.org/html.charters/dnsind-charter.html>

2: Application Layer 71

DNS records

DNS: distributed db storing resource records (RR)

RR format: (name, value, type, ttl)

- | | |
|--|--|
| <ul style="list-style-type: none">❑ Type=A<ul style="list-style-type: none">❖ name is hostname❖ value is IP address❑ Type=NS<ul style="list-style-type: none">❖ name is domain (e.g. foo.com)❖ value is hostname of authoritative name server for this domain | <ul style="list-style-type: none">❑ Type=CNAME<ul style="list-style-type: none">❖ name is alias name for some "canonical" (the real) name www.ibm.com is really servereast.backup2.ibm.com❖ value is canonical name❑ Type=MX<ul style="list-style-type: none">❖ value is name of mailserver associated with name |
|--|--|


2: Application Layer 72

DNS protocol, messages

DNS protocol: *query* and *reply* messages, both with same *message format*


msg header

- **identification**: 16 bit #
for query, reply to query
uses same #
- **flags**:
 - ❖ query or reply
 - ❖ recursion desired
 - ❖ recursion available
 - ❖ reply is authoritative



2: Application Layer 73

DNS protocol, messages



2: Application Layer 74

Inserting records into DNS

- example: new startup "Network Utopia"
- register name networkutopia.com at *DNS registrar* (e.g., Network Solutions)
 - ❖ provide names, IP addresses of authoritative name server (primary and secondary)
 - ❖ registrar inserts two RRs into com TLD server:


```
(networkutopia.com, dns1.networkutopia.com, NS)  
(dns1.networkutopia.com, 212.212.212.1, A)
```
- create authoritative server Type A record for www.networkutopia.com; Type MX record for networkutopia.com
- *How do people get IP address of your Web site?*

2: Application Layer 75

Chapter 2: Application layer

- 2.1 Principles of network applications
 - ❖ app architectures
 - ❖ app requirements
- 2.2 Web and HTTP
- 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- 2.5 DNS
- *2.6 P2P applications*
- 2.7 Socket programming with TCP
- 2.8 Socket programming with UDP


2: Application Layer 76

Pure P2P architecture

- no always-on server
- arbitrary end systems directly communicate
- peers are intermittently connected and change IP addresses

- **Three topics:**


- ❖ File distribution
- ❖ Searching for information
- ❖ Case Study: Skype



2: Application Layer 77

File Distribution: Server-Client vs P2P


Question: How much time to distribute file from one server to N peers?



2: Application Layer 78

File distribution time: server-client

- server sequentially sends N copies:
 - ❖ NF/u_s time
- client i takes F/d_i time to download




Time to distribute F to N clients using client/server approach $= d_{cs} = \max \{ NF/u_s, F/\min_i(d_i) \}$

increases linearly in N (for large N) 2: Application Layer 79

File distribution time: P2P

- server must send one copy: F/u_s time
- client i takes F/d_i time to download
- NF bits must be downloaded (aggregate)
 - fastest possible upload rate: $u_s + \sum u_i$




$$d_{p2p} = \max \{ F/u_s, F/\min_i(d_i), NF/(u_s + \sum u_i) \}$$

2: Application Layer 80

Server-client vs. P2P: example

Client upload rate = u , $F/u = 1$ hour, $u_s = 10u$, $d_{\min} \geq u_s$




2: Application Layer 81

File distribution: BitTorrent

□ P2P file distribution


tracker: tracks peers participating in torrent

torrent: group of peers exchanging chunks of a file



2: Application Layer 82

BitTorrent (1)



- file divided into 256KB *chunks*.
- peer joining torrent:
 - ❖ has no chunks, but will accumulate them over time
 - ❖ registers with tracker to get list of peers, connects to subset of peers ("neighbors")
- while downloading, peer uploads chunks to other peers.
- peers may come and go
- once peer has entire file, it may (selfishly) leave or (altruistically) remain

2: Application Layer 83

BitTorrent (2)

Pulling Chunks

- at any given time, different peers have different subsets of file chunks
- periodically, a peer (Alice) asks each neighbor for list of chunks that they have.
- Alice sends requests for her missing chunks
 - ❖ rarest first


Sending Chunks: tit-for-tat

- Alice sends chunks to four neighbors currently sending her chunks *at the highest rate*
 - ❖ re-evaluate top 4 every 10 secs
- every 30 secs: randomly select another peer, starts sending chunks
 - ❖ newly chosen peer may join top 4
 - ❖ "optimistically unchoke"

2: Application Layer 84

BitTorrent: Tit-for-tat

- (1) Alice "optimistically unchokes" Bob
- (2) Alice becomes one of Bob's top-four providers; Bob reciprocates
- (3) Bob becomes one of Alice's top-four providers



P2P: searching for information

Index in P2P system: maps information to peer location
(location = IP address & port number)

File sharing (eg e-mule)

- ❑ Index dynamically tracks the locations of files that peers share.
- ❑ Peers need to tell index what they have.
- ❑ Peers search index to determine where files can be found

Instant messaging


- ❑ Index maps user names to locations.
- ❑ When user starts IM application, it needs to inform index of its location
- ❑ Peers search index to determine IP address of user.

2: Application Layer 86

P2P: centralized index

original "Napster" design

- 1) when peer connects, it informs central server:
 - ❖ IP address
 - ❖ content
- 2) Alice queries for "Hey Jude"
- 3) Alice requests file from Bob



2: Application Layer 87

P2P: problems with centralized directory

- ❑ single point of failure
- ❑ performance bottleneck
- ❑ copyright infringement: "target" of lawsuit is obvious

file transfer is decentralized, but locating content is highly centralized

2: Application Layer 88


Query flooding

- fully distributed
 - ❖ no central server
 - used by Gnutella
 - Each peer indexes the files it makes available for sharing (and no other files)
- overlay network: graph
- edge between peer X and Y if there's a TCP connection
 - all active peers and edges form overlay net
 - edge: virtual (*not* physical) link
 - given peer typically connected with < 10 overlay neighbors

2: Application Layer 89

Query flooding

- Query message sent over existing TCP connections
- peers forward Query message
- QueryHit sent over reverse path



2: Application Layer 90

Gnutella: Peer joining


1. joining peer Alice must find another peer in Gnutella network: use list of candidate peers
2. Alice sequentially attempts TCP connections with candidate peers until connection setup with Bob
3. **Flooding:** Alice sends Ping message to Bob; Bob forwards Ping message to his overlay neighbors (who then forward to their neighbors....)
 - peers receiving Ping message respond to Alice with Pong message
4. Alice receives many Pong messages, and can then setup additional TCP connections

Peer leaving: see homework problem!

2: Application Layer 91

Hierarchical Overlay


- between centralized index, query flooding approaches
- each peer is either a *super node* or assigned to a super node
 - ❖ TCP connection between peer and its super node.
 - ❖ TCP connections between some pairs of super nodes.
- Super node tracks content in its children



2: Application Layer 92

P2P Case study: Skype


- inherently P2P: pairs of users communicate.
- proprietary application-layer protocol (inferred via reverse engineering)
- hierarchical overlay with SNs
- Index maps usernames to IP addresses; distributed over SNs



2: Application Layer 93

Peers as relays

- Problem when both Alice and Bob are behind "NATs".
 - ❖ NAT prevents an outside peer from initiating a call to insider peer
- Solution:
 - ❖ Using Alice's and Bob's SNs, Relay is chosen
 - ❖ Each peer initiates session with relay.
 - ❖ Peers can now communicate through NATs via relay



2: Application Layer 94

Chapter 2: Application layer

- 2.1 Principles of network applications
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- 2.5 DNS
- 2.6 P2P applications
- 2.7 **Socket programming with TCP**
- 2.8 Socket programming with UDP

2: Application Layer 95

Socket programming

Goal: learn how to build client/server application that communicate using sockets

Socket API

- introduced in BSD4.1 UNIX, 1981
- explicitly created, used, released by apps
- client/server paradigm
- two types of transport service via socket API:
 - ❖ unreliable datagram
 - ❖ reliable, byte stream-oriented

socket


a *host-local, application-created, OS-controlled* interface (a "door") into which application process can **both send and receive** messages to/from another application process

2: Application Layer 96

Socket-programming using TCP

Socket: a door between application process and end-end-transport protocol (UCP or TCP)

TCP service: reliable transfer of **bytes** from one process to another



2: Application Layer 97

Socket programming *with TCP*

Client must contact server

- server process must first be running
- server must have created socket (door) that welcomes client's contact

Client contacts server by:

- creating client-local TCP socket
- specifying IP address, port number of server process
- When **client creates socket**: client TCP establishes connection to server TCP

- When contacted by client, **server TCP creates new socket** for server process to communicate with client
 - ❖ allows server to talk with multiple clients
 - ❖ source port numbers used to distinguish clients (*more in Chap 3*)

application viewpoint


TCP provides reliable, in-order transfer of bytes ("pipe") between client and server

2: Application Layer 98

Client/server socket interaction: TCP

Server (running on `hostid`)


Client



2: Application Layer 99

Stream jargon

- A **stream** is a sequence of characters that flow into or out of a process.
- An **input stream** is attached to some input source for the process, e.g., keyboard or socket.
- An **output stream** is attached to an output source, e.g., monitor or socket.



2: Application Layer 100

Socket programming with TCP

Example client-server app:

- 1) client reads line from standard input (`inFromUser` stream) , sends to server via socket (`outToServer` stream)
- 2) server reads line from socket
- 3) server converts line to uppercase, sends back to client
- 4) client reads, prints modified line from socket (`inFromServer` stream)

2: Application Layer 101

Example: Java client (TCP)

```
import java.io.*;
import java.net.*;
class TCPClient {

    public static void main(String argv[]) throws Exception
    {
        String sentence;
        String modifiedSentence;

        Create input stream → BufferedReader inFromUser =
                                new BufferedReader(new InputStreamReader(System.in));

        Create client socket, connect to server → Socket clientSocket = new Socket("hostname", 6789);

        Create output stream attached to socket → DataOutputStream outToServer =
                                                    new DataOutputStream(clientSocket.getOutputStream());
```

2: Application Layer 102

Example: Java client (TCP), cont.

```
        Create  
        input stream  
        attached to socket } BufferedReader inFromServer =  
                             new BufferedReader(new  
                             InputStreamReader(clientSocket.getInputStream()));  
  
                             sentence = inFromUser.readLine();  
  
        Send line  
        to server } outToServer.writeBytes(sentence + '\n');  
  
        Read line  
        from server } modifiedSentence = inFromServer.readLine();  
                     System.out.println("FROM SERVER: " + modifiedSentence);  
                     clientSocket.close();  
                     }  
                }
```

2: Application Layer 103

Example: Java server (TCP)

```
import java.io.*;  
import java.net.*;  
  
class TCPServer {  
    public static void main(String argv[]) throws Exception  
    {  
        String clientSentence;  
        String capitalizedSentence;  
  
        Create  
        welcoming socket  
        at port 6789 } ServerSocket welcomeSocket = new ServerSocket(6789);  
  
        Wait, on welcoming  
        socket for contact  
        by client } while(true) {  
                     Socket connectionSocket = welcomeSocket.accept();  
  
        Create input  
        stream, attached  
        to socket } BufferedReader inFromClient =  
                     new BufferedReader(new  
                     InputStreamReader(connectionSocket.getInputStream()));
```

2: Application Layer 104

Example: Java server (TCP), cont

```

Create output stream, attached to socket → DataOutputStream outToClient =
                                           new DataOutputStream(connectionSocket.getOutputStream());

Read in line from socket → clientSentence = inFromClient.readLine();

capitalizedSentence = clientSentence.toUpperCase() + '\n';

Write out line to socket → outToClient.writeBytes(capitalizedSentence);
                        }
                    }
                    }
                    [End of while loop,
                    loop back and wait for
                    another client connection

```

2: Application Layer 105

Chapter 2: Application layer

- 2.1 Principles of network applications
- 2.2 Web and HTTP
- 2.3 FTP
- 2.4 Electronic Mail
 - ❖ SMTP, POP3, IMAP
- 2.5 DNS
- 2.6 P2P applications
- 2.7 Socket programming with TCP
- 2.8 Socket programming with UDP

2: Application Layer 106

Socket programming *with UDP*

UDP: no "connection" between client and server

- no handshaking
- sender explicitly attaches IP address and port of destination to each packet
- server must extract IP address, port of sender from received packet

application viewpoint

UDP provides unreliable transfer of groups of bytes ("datagrams") between client and server

UDP: transmitted data may be received out of order, or lost

2: Application Layer 107

Client/server socket interaction: UDP

Server (running on `hostid`)

Client

create socket,
port= x.
`serverSocket =`
`DatagramSocket()`

read datagram from
`serverSocket`

write reply to
`serverSocket`
specifying
client address,
port number


create socket,
`clientSocket =`
`DatagramSocket()`

Create datagram with server IP and
port=x; send datagram via
`clientSocket`

read datagram from
`clientSocket`
↓
close
`clientSocket`

2: Application Layer 108

Example: Java client (UDP)



2: Application Layer 109

Example: Java client (UDP)

```
import java.io.*;
import java.net.*;

class UDPClient {
    public static void main(String args[]) throws Exception
    {
        Create
        input stream → BufferedReader inFromUser =  

                          new BufferedReader(new InputStreamReader(System.in));
        Create
        client socket → DatagramSocket clientSocket = new DatagramSocket();
        Translate
        hostname to IP → InetAddress IPAddress = InetAddress.getByName("hostname");  

        address using DNS
        byte[] sendData = new byte[1024];  

        byte[] receiveData = new byte[1024];
        String sentence = inFromUser.readLine();  

        sendData = sentence.getBytes();
    }
}
```

2: Application Layer 110

Example: Java client (UDP), cont.

```

Create datagram with data-to-send, length, IP addr, port → DatagramPacket sendPacket =
                                                             new DatagramPacket(sendData, sendData.length, IPAddress, 9876);

Send datagram to server → clientSocket.send(sendPacket);

                                                                    DatagramPacket receivePacket =
                                                                    new DatagramPacket(receiveData, receiveData.length);

Read datagram from server → clientSocket.receive(receivePacket);

                                                                    String modifiedSentence =
                                                                    new String(receivePacket.getData());

                                                                    System.out.println("FROM SERVER:" + modifiedSentence);
                                                                    clientSocket.close();
                                                                    }
                                                                    }

```

2: Application Layer 111

Example: Java server (UDP)

```

import java.io.*;
import java.net.*;

class UDPServer {
    public static void main(String args[]) throws Exception
    {
        Create datagram socket at port 9876 → DatagramSocket serverSocket = new DatagramSocket(9876);

        byte[] receiveData = new byte[1024];
        byte[] sendData = new byte[1024];

        while(true)
        {
            Create space for received datagram → DatagramPacket receivePacket =
                                                    new DatagramPacket(receiveData, receiveData.length);

            Receive datagram → serverSocket.receive(receivePacket);
        }
    }
}

```

2: Application Layer 112

Example: Java server (UDP), cont

```
String sentence = new String(receivePacket.getData());

Get IP addr port #, of sender → InetAddress IPAddress = receivePacket.getAddress();
                                → int port = receivePacket.getPort();

String capitalizedSentence = sentence.toUpperCase();

sendData = capitalizedSentence.getBytes();

Create datagram to send to client → DatagramPacket sendPacket =
                                   new DatagramPacket(sendData, sendData.length, IPAddress,
                                                       port);

Write out datagram to socket → serverSocket.send(sendPacket);
                             }
                             }
                             }

                             End of while loop,
                             loop back and wait for
                             another datagram
```

2: Application Layer 113

Chapter 2: Summary

our study of network apps now complete!

- application architectures
 - ❖ client-server
 - ❖ P2P
 - ❖ hybrid
- application service requirements:
 - ❖ reliability, bandwidth, delay
- Internet transport service model
 - ❖ connection-oriented, reliable: TCP
 - ❖ unreliable, datagrams: UDP
- specific protocols:
 - ❖ HTTP
 - ❖ FTP
 - ❖ SMTP, POP, IMAP
 - ❖ DNS
 - ❖ P2P: BitTorrent, Skype
- socket programming

2: Application Layer 114

Chapter 2: Summary

Most importantly: learned about *protocols*

- typical request/reply message exchange:
 - ❖ client requests info or service
 - ❖ server responds with data, status code
- message formats:
 - ❖ headers: fields giving info about data
 - ❖ data: info being communicated

Important themes:

- control vs. data msgs
 - ❖ in-band, out-of-band
- centralized vs. decentralized
- stateless vs. stateful
- reliable vs. unreliable msg transfer
- "complexity at network edge"

2: Application Layer 115