

## EXERCISE – 9

### Question

Execute and display the results of the following Nmap Timing and Performance commands in Kali Linux Operating System:

1. Polite IDS evasion
2. Normal IDS evasion

### Aim

To perform polite and normal timing scans using Nmap in Kali Linux.

#### 1. Polite IDS Evasion

##### Command:

**nmap -T2 127.0.0.1**

##### Use:

Used to perform a slower and polite scan.

```
(lasya@kali)-[~]
$ nmap -T2 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-07 08:46 +0530
Nmap scan report for localhost (127.0.0.1)
Host is up (0.000052s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 1000 closed tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 406.66 seconds
```

#### 2. Normal IDS Evasion

##### Command:

**nmap -T3 127.0.0.1**

##### Use:

Used to perform a normal-speed scan.

```
(lasya@kali)-[~]
$ nmap -T3 127.0.0.1
Starting Nmap 7.99 ( https://nmap.org ) at 2026-10-07 08:55 +0530
Nmap scan report for localhost (127.0.0.1)
Host is up (0.0000010s latency).
All 1000 scanned ports on localhost (127.0.0.1) are in ignored states.
Not shown: 1000 closed tcp ports (reset)

Nmap done: 1 IP address (1 host up) scanned in 0.05 seconds
```

### Result

Thus, the -T2 and -T3 Nmap timing scans were successfully executed on the localhost.