```cpp
int main()
{
    int number1 = 10;
    int number2 = 4;
    float quotient;

    cout << "Enter two numbers and I will
divide\n";
    cout << "the first by the second for you.\n";

    cout << "You entered: " << number1 << " and
" << number2 << endl;

    quotient = static_cast<float>(number1) /
number2;

    cout << "Quotient is: " << quotient << endl;

    return 0;
}
```

TAB _

```
o numbers and I will divide
 by the second for you.
ed: 10 and 4
is: 2.5

finished]
```

```cpp
#include <iostream>
using namespace std;

int main() {
    // Task 1 - Values put kar diye hain
    int age = 20;
    double pay = 4500.75;
    char section = 'A';

    cout << "Age: " << age << endl;
    cout << "Pay: " << pay << endl;
    cout << "Section: " << section << endl;
    cout << "----------" << endl;
}
```

new*

```cpp
#include <iostream>
using namespace std;

int main(){
    int units = 5;
    float mass = 2.5f;
    double weight;

    weight = mass * units; // yahan automatic conversion hoga

    cout << "units (int): " << units << endl;
    cout << "mass (float): " << mass << endl;
    cout << "weight (mass * units) double me: " << weight << endl;

    return 0;
}
```

TAB

```
units (int): 5
mass (float): 2.5
weight (mass * units) double me: 12.5

[Program finished]
```

```cpp
#include <iostream>
using namespace std;

int main(){
    int a, b = 2;
    float c = 4.2;

    a = b * c; // 8.4 float se 8 int ban jayega

    cout << "b = " << b << endl;
    cout << "c = " << c << endl;
    cout << "b * c = " << b * c << endl;
    cout << "a me store hua = " << a << endl;

    return 0;
}
```

new*

```cpp
#include <iostream>
using namespace std;

int main(){
    int qty = 7;
    int salesReps = 2;
    double unitsEach;

    // Pehle (galat) - Integer division
    unitsEach = qty / salesReps;
    cout << "Without casting: " << unitsEach << endl; // Output: 3

    // Ab Sahi - Type cast ke sath
    unitsEach = static_cast<double>(qty) / salesReps;
    cout << "With casting: " << unitsEach << endl; // Output: 3.5

    return 0;
}
```

TAB

```
Without casting: 3
With casting: 3.5

[Program finished]
```

```cpp
#include <iostream>
#include <cstdlib>  // rand() ke liye
#include <ctime>    // time() ke liye
using namespace std;

int main() {
    // Random number generator ko seed karna
    srand(time(0));

    // 100 se 999 tak 2 random numbers
    int num1 = rand() % 900 + 100;  // 100-999
    int num2 = rand() % 900 + 100;  // 100-999

    int answer = num1 + num2;

    // Problem display karna
    cout << "Solve this addition problem:\n\n";
    cout << "  " << num1 << endl;
    cout << "+ " << num2 << endl;
    cout << "-----" << endl;

    // Pause - Student ke solve karne tak rukna
    cout << "\nPress ENTER when you are ready to check the answer...";
    cin.get();  // Enter press ka wait karega

    // Correct solution display karna
    cout << "\nCorrect Solution:\n\n";
    cout << "  " << num1 << endl;
    cout << "+ " << num2 << endl;
    cout << "-----" << endl;
    cout << "  " << answer << endl;

    return 0;
}
```



new*

```cpp
#include <iostream>
using namespace std;

int main()
{
    double number1 = 15.5;
    double number2 = 10.2;
    double sum;

    sum = number1 + number2;  // Yahan add ho raha hai

    cout << "First Number: " << number1 << endl;
    cout << "Second Number: " << number2 << endl;
    cout << "The sum of the two numbers is " << sum << endl;

    return 0;
}
```

TAB

```
First Number: 15.5
Second Number: 10.2
The sum of the two numbers is 25.7

[Program finished]
```

```cpp
int main()
{
    int number1 = 10;
    int number2 = 4;
    float quotient;

    cout << "Enter two numbers and I will divide\n";
    cout << "the first by the second for you.\n";

    cout << "You entered: " << number1 << " and " << number2 << endl;

    quotient = static_cast<float>(number1) / number2;

    cout << "Quotient is: " << quotient << endl;

    return 0;
}
```

TAB

```
Enter two numbers and I will divide
the first by the second for you.
You entered: 10 and 4
Quotient is: 2.5

[Program finished]
```