Babel

Code

Version 26.14.139174
2026/10/22

Javier Bezos
Current maintainer

Johannes L. Braams
Original author

Localization and internationalization

Unicode
TEX
LuaTEX
pdfTEX
XeTEX

Contents

1 Identification and loading of required files **3**

2 `locale` directory **3**

3 Tools **3**
- 3.1 A few core definitions . . . 8
- 3.2 LaTeX: `babel.sty` (start) . . . 8
- 3.3 `base` . . . 9
- 3.4 `key=value` options and other general option . . . 10
- 3.5 Post-process some options . . . 12
- 3.6 Selecting the language . . . 15
- 3.7 Errors . . . 23
- 3.8 More on selection . . . 24
- 3.9 Short tags . . . 25
- 3.10 Compatibility with language.def . . . 26
- 3.11 Hooks . . . 26
- 3.12 Setting up language files . . . 27
- 3.13 Shorthands . . . 29
- 3.14 Language attributes . . . 38
- 3.15 Support for saving and redefining macros . . . 40
- 3.16 French spacing . . . 41
- 3.17 Hyphens . . . 42
- 3.18 Multiencoding strings . . . 44
- 3.19 Tailor captions . . . 48
- 3.20 Making glyphs available . . . 49
  - 3.20.1 Quotation marks . . . 49
  - 3.20.2 Letters . . . 51
  - 3.20.3 Shorthands for quotation marks . . . 52
  - 3.20.4 Umlauts and tremas . . . 52
- 3.21 Layout . . . 54
- 3.22 Load engine specific macros . . . 54
- 3.23 Creating and modifying languages . . . 54
- 3.24 Main loop in 'provide' . . . 62
- 3.25 Processing keys in `ini` . . . 67
- 3.26 French spacing (again) . . . 73
- 3.27 Handle language system . . . 74
- 3.28 Numerals . . . 75
- 3.29 Casing . . . 76
- 3.30 Getting info . . . 77
- 3.31 BCP 47 related commands . . . 78

4 Adjusting the Babel behavior **79**
- 4.1 Cross referencing macros . . . 81
- 4.2 Layout . . . 84
- 4.3 Marks . . . 86
- 4.4 Other packages . . . 87
  - 4.4.1 `ifthen` . . . 87
  - 4.4.2 `varioref` . . . 87
  - 4.4.3 `hhline` . . . 88
- 4.5 Encoding and fonts . . . 88
- 4.6 Basic bidi support . . . 90
- 4.7 Local Language Configuration . . . 93
- 4.8 Language options . . . 94

5 Tagging **98**

6 Error messages **99**

7 Loading hyphenation patterns **103**

8 luatex + xetex: common stuff **107**

9 Hooks for XeTeX and LuaTeX **110**
9.1 XeTeX . . . 110
9.2 Support for interchar . . . 112
9.3 Layout . . . 114
9.4 8-bit TeX . . . 115
9.5 LuaTeX . . . 116
9.6 Southeast Asian scripts . . . 123
9.7 CJK line breaking . . . 124
9.8 Arabic justification . . . 126
9.9 Common stuff . . . 131
9.10 Automatic fonts and ids switching . . . 131
9.11 Bidi . . . 138
9.12 Layout . . . 141
9.13 Lua: transforms . . . 150
9.14 Lua: Auto bidi with `basic` and `basic-r` . . . 160

10 Data for CJK **174**

11 The 'nil' language **174**

12 Calendars **175**
12.1 Islamic . . . 175
12.2 Hebrew . . . 177
12.3 Persian . . . 181
12.4 Coptic and Ethiopic . . . 181
12.5 Julian . . . 182
12.6 Buddhist . . . 182

13 Acknowledgements **184**

The babel package is being developed incrementally, which means parts of the code are under development and therefore incomplete. Only documented features are considered complete. In other words, use babel in real documents only as documented (except, of course, if you want to explore and test them).

1. Identification and loading of required files

The babel package after unpacking consists of the following files:

babel.sty is the LaTeX package, which set options and load language styles.
babel.def is loaded by Plain and, in part, by the `base` option
switch.def is not used. Kept for compatibility.
plain.def is not used, and just loads babel.def, for compatibility.
hyphen.cfg is the file to be used when generating the formats to load hyphenation patterns.

There some additional `tex`, `def` and `lua` files.

The babel installer extends docstrip with a few "pseudo-guards" to set "variables" used at installation time. They are used with `<@name@>` at the appropriate places in the source code and defined with either ⟨⟨*name=value*⟩⟩, or with a series of lines between ⟨⟨**name*⟩⟩ and ⟨⟨/*name*⟩⟩. The latter is cumulative (e.g., with *More package options*). That brings a little bit of literate programming. The guards `<-name>` and `<+name>` have been redefined, too. See `babel.ins` for further details.

2. `locale` directory

A required component of babel is a set of `ini` files with basic definitions for about 300 languages. They are distributed as a separate `zip` file, not packed as `dtx`. Many of them are essentially finished (except bugs and mistakes, of course). Some of them are still incomplete (but they will be usable), and there are some omissions (e.g., there are no geographic areas in Spanish). Not all include LICR variants.

`babel-*.ini` files contain the actual data; `babel-*.tex` files are basically proxies to the corresponding ini files.

See Keys in `ini` files in the the babel site.

3. Tools

```
1 ⟨⟨version=26.14.139174⟩⟩
2 ⟨⟨date=2026/10/22⟩⟩
```

Do not use the following macros in `ldf` files. They may change in the future. This applies mainly to those recently added for replacing, trimming and looping. The older ones, like `\bbl@afterfi`, will not change. We define some basic macros which just make the code cleaner. `\bbl@add` is now used internally instead of `\addto` because of the unpredictable behavior of the latter. Used in `babel.def` and in `babel.sty`, which means in LaTeX is executed twice, but we need them when defining options and `babel.def` cannot be load until options have been defined. This does not hurt, but should be fixed somehow.

```
3 ⟨⟨*Basic macros⟩⟩ ▸
4 \bbl@trace{Basic macros}
5 \def\bbl@stripslash{\expandafter\@gobble\string}
6 \def\bbl@add#1#2{%
7   \bbl@ifunset{\bbl@stripslash#1}%
8     {\def#1{#2}}%
9     {\expandafter\def\expandafter#1\expandafter{#1#2}}}
10 \def\bbl@xin@{\@expandtwoargs\in@}
11 \def\bbl@carg#1#2{\expandafter#1\csname#2\endcsname}%
12 \def\bbl@ncarg#1#2#3{\expandafter#1\expandafter#2\csname#3\endcsname}%
13 \def\bbl@ccarg#1#2#3{%
14   \expandafter#1\csname#2\expandafter\endcsname\csname#3\endcsname}%
15 \def\bbl@csarg#1#2{\expandafter#1\csname bbl@#2\endcsname}%
16 \def\bbl@cs#1{\csname bbl@#1\endcsname}
17 \def\bbl@cl#1{\csname bbl@#1@\languagename\endcsname}
18 \def\bbl@loop#1#2#3{\bbl@@loop#1{#3}#2,\@nnil,}
```

```
\def\bbl@loopx#1#2{\expandafter\bbl@loop\expandafter#1\expandafter{#2}}
\def\bbl@@loop#1#2#3,{%
  \ifx\@nnil#3\relax\else
    \def#1{#3}#2\bbl@afterfi\bbl@@loop#1{#2}%
  \fi}
\def\bbl@for#1#2#3{\bbl@loopx#1{#2}{\ifx#1\@empty\else#3\fi}}
```

\bbl@add@list This internal macro adds its second argument to a comma separated list in its first argument. When the list is not defined yet (or empty), it will be initiated. It presumes expandable character strings.

```
\def\bbl@add@list#1#2{%
  \edef#1{%
    \bbl@ifunset{\bbl@stripslash#1}%
      {}%
      {\ifx#1\@empty\else#1,\fi}%
    #2}}
```

\bbl@afterelse
\bbl@afterfi Because the code that is used in the handling of active characters may need to look ahead, we take extra care to 'throw' it over the `\else` and `\fi` parts of an `\if`-statement[1]. These macros will break if another `\if...\fi` statement appears in one of the arguments and it is not enclosed in braces.

```
\long\def\bbl@afterelse#1\else#2\fi{\fi#1}
\long\def\bbl@afterfi#1\fi{\fi#1}
```

\bbl@exp Now, just syntactical sugar, but it makes partial expansion of some code a lot more simple and readable. Here `\\` stands for `\noexpand`, `\<..>` for `\noexpand` applied to a built macro name (which does not define the macro if undefined to `\relax`, because it is created locally), and `\[..]` for one-level expansion (where `..` is the macro name without the backslash). The result may be followed by extra arguments, if necessary.

```
\def\bbl@exp#1{%
  \begingroup
    \let\\\noexpand
    \let\<\bbl@exp@en
    \let\[\bbl@exp@ue
    \edef\bbl@exp@aux{\endgroup#1}%
  \bbl@exp@aux}
\def\bbl@exp@en#1>{\expandafter\noexpand\csname#1\endcsname}%
\def\bbl@exp@ue#1]{%
  \unexpanded\expandafter\expandafter\expandafter{\csname#1\endcsname}}%
```

\bbl@trim The following piece of code is stolen (with some changes) from keyval, by David Carlisle. It defines two macros: `\bbl@trim` and `\bbl@trim@def`. The first one strips the leading and trailing spaces from the second argument and then applies the first argument (a macro, `\toks@` and the like). The second one, as its name suggests, defines the first argument as the stripped second argument.

```
\def\bbl@tempa#1{%
  \long\def\bbl@trim##1##2{%
    \futurelet\bbl@trim@a\bbl@trim@c##2\@nil\@nil#1\@nil\relax{##1}}%
  \def\bbl@trim@c{%
    \ifx\bbl@trim@a\@sptoken
      \expandafter\bbl@trim@b
    \else
      \expandafter\bbl@trim@b\expandafter#1%
    \fi}%
  \long\def\bbl@trim@b#1##1 \@nil{\bbl@trim@i##1}}
\bbl@tempa{ }
\long\def\bbl@trim@i#1\@nil#2\relax#3{#3{#1}}
\long\def\bbl@trim@def#1{\bbl@trim{\def#1}}
```

[1] This code is based on code presented in TUGboat vol. 12, no2, June 1991 in "An expansion Power Lemma" by Sonja Maus.

\bbl@ifunset It does the same as \@ifundefined. Formerly defined for ε-tex engines based on \ifcsname, which is more efficient, and does not waste memory. Now \@ifundefined is based on \ifcsname, too.

```
\let\bbl@ifunset\@ifundefined
```

\bbl@ifblank A tool from url, by Donald Arseneau, which tests if a string is empty or space. The companion macros tests if a macro is defined with some 'real' value, i.e., not \relax and not empty,

```
\def\bbl@ifblank#1{%
  \bbl@ifblank@i#1\@nil\@nil\@secondoftwo\@firstoftwo\@nil}
\long\def\bbl@ifblank@i#1#2\@nil#3#4#5\@nil{#4}
\def\bbl@ifset#1#2#3{%
  \bbl@ifunset{#1}{#3}{\bbl@exp{\\\bbl@ifblank{\@nameuse{#1}}}{#3}{#2}}}
```

For each element in the comma separated <key>=<value> list, execute <code> with #1 and #2 as the key and the value of current item (trimmed). In addition, the item is passed verbatim as #3. With the <key> alone, it passes \@empty as value (i.e., the macro thus named, not an empty argument, which is what you get with <key>= and no value).

```
\def\bbl@forkv#1#2{%
  \def\bbl@kvcmd##1##2##3{#2}%
  \bbl@kvnext#1,\@nil,}
\def\bbl@kvnext#1,{%
  \ifx\@nil#1\relax\else
    \bbl@ifblank{#1}{}{\bbl@forkv@eq#1=\@empty=\@nil{#1}}%
    \expandafter\bbl@kvnext
  \fi}
\def\bbl@forkv@eq#1=#2=#3\@nil#4{%
  \bbl@trim@def\bbl@forkv@a{#1}%
  \bbl@trim{\expandafter\bbl@kvcmd\expandafter{\bbl@forkv@a}}{#2}{#4}}
```

A *for* loop. Each item (trimmed) is #1. It cannot be nested (it's doable, but we don't need it).

```
\def\bbl@vforeach#1#2{%
  \def\bbl@forcmd##1{#2}%
  \bbl@fornext#1,\@nil,}
\def\bbl@fornext#1,{%
  \ifx\@nil#1\relax\else
    \bbl@ifblank{#1}{}{\bbl@trim\bbl@forcmd{#1}}%
    \expandafter\bbl@fornext
  \fi}
\def\bbl@foreach#1{\expandafter\bbl@vforeach\expandafter{#1}}
```

Some code should be executed once. The first argument is a flag.

```
\global\let\bbl@done\@empty
\def\bbl@once#1#2{%
  \bbl@xin@{,#1,}{,\bbl@done,}%
  \ifin@\else
    #2%
    \xdef\bbl@done{\bbl@done,#1,}%
  \fi}
%    \end{macrode}
%
% \macro{\bbl@replace}
%
% Returns implicitly |\toks@| with the modified string.
%
%    \begin{macrocode}
\def\bbl@replace#1#2#3{% in #1 -> repl #2 by #3
  \toks@{}%
  \def\bbl@replace@aux##1#2##2#2{%
    \ifx\bbl@nil##2%
      \toks@\expandafter{\the\toks@##1}%
    \else
      \toks@\expandafter{\the\toks@##1#3}%
```

```
      \bbl@afterfi
      \bbl@replace@aux##2#2%
    \fi}%
  \expandafter\bbl@replace@aux#1#2\bbl@nil#2%
  \edef#1{\the\toks@}}
```

An extension to the previous macro. It takes into account the parameters, and it is string based (i.e., if you replace `elax` by `ho`, then `\relax` becomes `\rho`). No checking is done at all, because it is not a general purpose macro, and it is used by babel only when it works (an example where it does *not* work is in `\bbl@TG@@date`, and also fails if there are macros with spaces, because they are retokenized). It may change! (or even merged with `\bbl@replace`; I'm not sure checking the replacement is really necessary or just paranoia).

```
\ifx\detokenize\@undefined\else % Unused macros if old Plain TeX
  \bbl@exp{\def\\\bbl@parsedef##1\detokenize{macro:}}#2->#3\relax{%
    \def\bbl@tempa{#1}%
    \def\bbl@tempb{#2}%
    \def\bbl@tempe{#3}}
  \def\bbl@sreplace#1#2#3{%
    \begingroup
      \expandafter\bbl@parsedef\meaning#1\relax
      \def\bbl@tempc{#2}%
      \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
      \def\bbl@tempd{#3}%
      \edef\bbl@tempd{\expandafter\strip@prefix\meaning\bbl@tempd}%
      \bbl@xin@{\bbl@tempc}{\bbl@tempe}% If not in macro, do nothing
      \ifin@
        \bbl@exp{\\\bbl@replace\\\bbl@tempe{\bbl@tempc}{\bbl@tempd}}%
        \def\bbl@tempc{%     Expanded an executed below as 'uplevel'
           \\\makeatletter % "internal" macros with @ are assumed
           \\\scantokens{%
             \bbl@tempa\\\@namedef{\bbl@stripslash#1}\bbl@tempb{\bbl@tempe}%
             \noexpand\noexpand}%
           \catcode64=\the\catcode64\relax}%  Restore @
      \else
        \let\bbl@tempc\@empty  % Not \relax
      \fi
      \bbl@exp{%      For the 'uplevel' assignments
    \endgroup
      \bbl@tempc}}  % empty or expand to set #1 with changes
\fi
```

Two further tools. `\bbl@ifsamestring` first expand its arguments and then compare their expansion (sanitized, so that the catcodes do not matter). `\bbl@engine` takes the following values: 0 is pdfTEX, 1 is luatex, and 2 is xetex. You may use the latter it in your language style if you want.

```
\def\bbl@ifsamestring#1#2{%
  \begingroup
    \protected@edef\bbl@tempb{#1}%
    \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
    \protected@edef\bbl@tempc{#2}%
    \edef\bbl@tempc{\expandafter\strip@prefix\meaning\bbl@tempc}%
    \ifx\bbl@tempb\bbl@tempc
      \aftergroup\@firstoftwo
    \else
      \aftergroup\@secondoftwo
    \fi
  \endgroup}
\chardef\bbl@engine=%
  \ifx\directlua\@undefined
    \ifx\XeTeXinputencoding\@undefined
      \z@
    \else
      \tw@
    \fi
  \else
```

```
    \@ne
  \fi
```

A somewhat hackish tool (hence its name) to avoid spurious spaces in some contexts.

```
\def\bbl@bsphack{%
  \ifhmode
    \hskip\z@skip
    \def\bbl@esphack{\loop\ifdim\lastskip>\z@\unskip\repeat\unskip}%
  \else
    \let\bbl@esphack\@empty
  \fi}
```

Another hackish tool, to apply case changes inside a protected macros. It's based on the internal `\let`'s made by `\MakeUppercase` and `\MakeLowercase` between things like `\oe` and `\OE`.

```
\def\bbl@cased{%
  \ifx\oe\OE
    \expandafter\in@\expandafter
      {\expandafter\OE\expandafter}\expandafter{\oe}%
    \ifin@
      \bbl@afterelse\expandafter\MakeUppercase
    \else
      \bbl@afterfi\expandafter\MakeLowercase
    \fi
  \else
    \expandafter\@firstofone
  \fi}
```

Ordered key/value lists (aka associative arrays). The setter either replaces the current value if the key exists, or adds the new key/value at the end. The getter returns either the value if the key exists or `\relax`. The code is based on arguments delimited by the keys.

```
\def\bbl@@empty{\@empty}
\def\bbl@array@set#1#2#3{%
  \def\bbl@array@aux##1\bbl@elt#2\@@##2##3\bbl@array@aux##4{%
    \ifx\bbl@noelt##2%
      \def#1{##1\bbl@elt#2\@@{##4}}%
    \else
      \def\bbl@array@aux####1\bbl@elt#2\@@####2####3\bbl@array@aux####4{%
        \def#1{####1\bbl@elt#2\@@{#####4}####3}}%
      \expandafter\bbl@array@aux#1\bbl@array@aux{#3}%
    \fi}%
  \expandafter\bbl@array@aux#1\bbl@elt#2\@@\bbl@noelt\bbl@array@aux{#3}}
\def\bbl@array@get#1#2#3{%
  \def\bbl@array@aux##1\bbl@elt#2\@@##2##3\bbl@array@aux{%
    \ifx\bbl@@empty##2\@empty\let#3\relax\else\def#3{##2}\fi}%
  \expandafter\bbl@array@aux#1\bbl@elt#2\@@\bbl@@empty\bbl@array@aux}
```

The following adds some code to `\extras...` both before and after, while avoiding doing it twice. It's somewhat convoluted, to deal with #'s. Used to deal with alph, Alph and frenchspacing when there are already changes (with `\babel@save`).

```
\def\bbl@extras@wrap#1#2#3{% 1:in-test, 2:before, 3:after
  \toks@\expandafter\expandafter\expandafter{%
    \csname extras\languagename\endcsname}%
  \bbl@exp{\\\in@{#1}{\the\toks@}}%
  \ifin@\else
    \@temptokena{#2}%
    \edef\bbl@tempc{\the\@temptokena\the\toks@}%
    \toks@\expandafter{\bbl@tempc#3}%
    \expandafter\edef\csname extras\languagename\endcsname{\the\toks@}%
  \fi}
⟨⟨/Basic macros⟩⟩
```

Some files identify themselves with a LaTeX macro. The following code is placed before them to define (and then undefine) if not in LaTeX.

```
⟨⟨*Make sure ProvidesFile is defined⟩⟩ ▸
```

```
\ifx\ProvidesFile\@undefined
  \def\ProvidesFile#1[#2 #3 #4]{%
    \wlog{File: #1 #4 #3 <#2>}%
    \let\ProvidesFile\@undefined}
\fi
```
⟨/Make sure ProvidesFile is defined⟩

3.1. A few core definitions

\language Just for compatibility, for not to touch `hyphen.cfg`.

```
⟨*Define core switching macros⟩ ▸
\ifx\language\@undefined
  \csname newcount\endcsname\language
\fi
⟨/Define core switching macros⟩
```

\last@language Another counter is used to keep track of the allocated languages. TEX and LATEX reserves for this purpose the count 19.

\addlanguage This macro was introduced for TEX < 2. Preserved for compatibility.

```
⟨*Define core switching macros⟩ ▸
\countdef\last@language=19
\def\addlanguage{\csname newlanguage\endcsname}
⟨/Define core switching macros⟩
```

Now we make sure all required files are loaded. When the command `\AtBeginDocument` doesn't exist we assume that we are dealing with a plain-based format. In that case the file `plain.def` is needed (which also defines `\AtBeginDocument`, and therefore it is not loaded twice). We need the first part when the format is created, and `\orig@dump` is used as a flag. Otherwise, we need to use the second part, so `\orig@dump` is not defined (`plain.def` undefines it).

Check if the current version of `switch.def` has been previously loaded (mainly, `hyphen.cfg`). If not, load it now. We cannot load `babel.def` here because we first need to declare and process the package options.

3.2. LATEX: `babel.sty` (start)

Here starts the style file for LATEX. It also takes care of a number of compatibility issues with other packages.

```
⟨*package⟩
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{babel}%
  [<@date@> v<@version@>
   The multilingual framework for LuaLaTeX, pdfLaTeX and XeLaTeX]
```

Start with some "private" debugging tools, and then define macros for errors. The global lua 'space' `Babel` is declared here, too (inside the test for `debug`).

```
\@ifpackagewith{babel}{debug}
  {\providecommand\bbl@trace[1]{\message{^^J[ #1 ]}}%
   \let\bbl@debug\@firstofone
   \ifx\directlua\@undefined\else
     \directlua{
       Babel = Babel or {}
       Babel.debug = true }%
     \input{babel-debug.tex}%
   \fi}
  {\providecommand\bbl@trace[1]{}%
   \let\bbl@debug\@gobble
   \ifx\directlua\@undefined\else
     \directlua{
       Babel = Babel or {}
       Babel.debug = false }%
   \fi}
```

Macros to deal with errors, warnings, etc. Errors are stored in a separate file.

```
\def\bbl@error#1{% Implicit #2#3#4
  \begingroup
    \catcode`\\=0 \catcode`\==12 \catcode`\`=12
    \input errbabel.def
  \endgroup
  \bbl@error{#1}}
\def\bbl@warning#1{%
  \begingroup
    \def\\{\MessageBreak}%
    \PackageWarning{babel}{#1}%
  \endgroup}
\def\bbl@infowarn#1{%
  \begingroup
    \def\\{\MessageBreak}%
    \PackageNote{babel}{#1}%
  \endgroup}
\def\bbl@info#1{%
  \begingroup
    \def\\{\MessageBreak}%
    \PackageInfo{babel}{#1}%
  \endgroup}
```

Many of the following options don't do anything themselves, they are just defined in order to make it possible for babel and language definition files to check if one of them was specified by the user.

But first, include here the *Basic macros* defined above.

```
<@Basic macros@>
\@ifpackagewith{babel}{silent}
  {\let\bbl@info\@gobble
   \let\bbl@infowarn\@gobble
   \let\bbl@warning\@gobble}
  {}
%
\def\AfterBabelLanguage#1{%
  \global\expandafter\bbl@add\csname#1.ldf-h@@k\endcsname}%
```

If the format created a list of loaded languages (in `\bbl@languages`), get the name of the 0-th to show the actual language used. Also available with `base`, because it just shows info.

```
\ifx\bbl@languages\@undefined\else
  \begingroup
    \catcode`\^^I=12
    \@ifpackagewith{babel}{showlanguages}{%
      \begingroup
        \def\bbl@elt#1#2#3#4{\wlog{#2^^I#1^^I#3^^I#4}}%
        \wlog{<*languages>}%
        \bbl@languages
        \wlog{</languages>}%
      \endgroup}{}
  \endgroup
  \def\bbl@elt#1#2#3#4{%
    \ifnum#2=\z@
      \gdef\bbl@nulllanguage{#1}%
      \def\bbl@elt##1##2##3##4{}%
    \fi}%
  \bbl@languages
\fi
```

3.3. base

The first 'real' option to be processed is `base`, which set the hyphenation patterns then resets `ver@babel.sty` so that LaTeX forgets about the first loading. After a subset of `babel.def` has been loaded (the old `switch.def`) and `\AfterBabelLanguage` defined, it exits.

Now the base option. With it we can define (and load, with luatex) hyphenation patterns, even if we are not interested in the rest of babel.

```
\bbl@trace{Defining option 'base'}
\@ifpackagewith{babel}{base}{%
  \let\bbl@onlyswitch\@empty
  \let\bbl@provide@locale\relax
  \input babel.def
  \let\bbl@onlyswitch\@undefined
  \ifx\directlua\@undefined
    \DeclareOption*{\bbl@patterns{\CurrentOption}}%
  \else
    \input luababel.def
    \DeclareOption*{\bbl@patterns@lua{\CurrentOption}}%
  \fi
  \DeclareOption{base}{}%
  \DeclareOption{showlanguages}{}%
  \ProcessOptions
  \global\expandafter\let\csname opt@babel.sty\endcsname\relax
  \global\expandafter\let\csname ver@babel.sty\endcsname\relax
  \global\let\@ifl@ter@@\@ifl@ter
  \def\@ifl@ter#1#2#3#4#5{\global\let\@ifl@ter\@ifl@ter@@}%
  \endinput}{}%
```

3.4. key=value options and other general option

The following macros extract language modifiers, and only real package options are kept in the option list. Modifiers are saved and assigned to `\BabelModifiers` at `\bbl@load@language`; when no modifiers have been given, the former is `\relax`.

```
\bbl@trace{key=value and another general options}
\bbl@csarg\let{tempa\expandafter}\csname opt@babel.sty\endcsname
\def\bbl@tempb#1.#2{%  Removes trailing dot
   #1\ifx\@empty#2\else,\bbl@afterfi\bbl@tempb#2\fi}%
\def\bbl@tempe#1=#2\@@{%
  \bbl@csarg\edef{mod@#1}{\bbl@tempb#2}}
\def\bbl@tempd#1.#2\@nnil{%
  \ifx\@empty#2%
    \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
  \else
    \in@{,provide=}{,#1}%
    \ifin@
      \edef\bbl@tempc{%
        \ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.\bbl@tempb#2}%
    \else
      \in@{$modifiers$}{$#1$}%
      \ifin@
        \bbl@tempe#2\@@
      \else
        \in@{=}{#1}%
        \ifin@
          \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1.#2}%
        \else
          \edef\bbl@tempc{\ifx\bbl@tempc\@empty\else\bbl@tempc,\fi#1}%
          \bbl@csarg\edef{mod@#1}{\bbl@tempb#2}%
        \fi
      \fi
    \fi
  \fi}
\let\bbl@tempc\@empty
\bbl@foreach\bbl@tempa{\bbl@tempd#1.\@empty\@nnil}
\expandafter\let\csname opt@babel.sty\endcsname\bbl@tempc
```

The next option tells babel to leave shorthand characters active at the end of processing the package. This is *not* the default as it can cause problems with other packages, but for those who want

to use the shorthand characters in the preamble of their documents this can help.

```
\DeclareOption{KeepShorthandsActive}{}
\DeclareOption{activeacute}{}
\DeclareOption{activegrave}{}
\DeclareOption{debug}{}
\DeclareOption{debug-german}{} % Temporary
\DeclareOption{noconfigs}{}
\DeclareOption{showlanguages}{}
\DeclareOption{silent}{}
\DeclareOption{shorthands=off}{\bbl@tempa shorthands=\bbl@tempa}
\chardef\bbl@iniflag\z@
\DeclareOption{provide=*}{\chardef\bbl@iniflag\@ne}    % main = 1
\DeclareOption{provide+=*}{\chardef\bbl@iniflag\tw@}   % second = 2
\DeclareOption{provide*=*}{\chardef\bbl@iniflag\thr@@} % second + main
\chardef\bbl@ldfflag\z@
\DeclareOption{provide=!}{\chardef\bbl@ldfflag\@ne}    % main = 1
\DeclareOption{provide+=!}{\chardef\bbl@ldfflag\tw@}   % second = 2
\DeclareOption{provide*=!}{\chardef\bbl@ldfflag\thr@@} % second + main
\DeclareOption{licr=extended}{}
\DeclareOption{licr=unextended}{}
\let\bbl@ifmetadata\@gobble
\DeclareOption{babel-metadata=on}{%
  \IfDocumentMetadataT{\AtEndOfPackage{\input{tagbabel.def}}}}
\DeclareOption{babel-metadata=tagging}{%
  \IfDocumentMetadataT{\AtEndOfPackage{\input{tagbabel.def}}}}
% Don't use. Experimental.
\newif\ifbbl@single
\DeclareOption{selectors=off}{\bbl@singletrue}
<@More package options@>
```

Handling of package options is done in three passes. (I [JBL] am not very happy with the idea, anyway.) The first one processes options which has been declared above or follow the syntax ⟨*key*⟩=⟨*value*⟩, the second one loads the requested languages, except the main one if set with the key `main`, and the third one loads the latter. First, we "flag" valid keys with a nil value.

```
\let\bbl@opt@shorthands\@nnil
\let\bbl@opt@config\@nnil
\let\bbl@opt@main\@nnil
\let\bbl@opt@headfoot\@nnil
\let\bbl@opt@layout\@nnil
\let\bbl@opt@provide\@nnil
```

The following tool is defined temporarily to store the values of options.

```
\def\bbl@tempa#1=#2\bbl@tempa{%
  \bbl@csarg\ifx{opt@#1}\@nnil
    \bbl@csarg\edef{opt@#1}{#2}%
  \else
    \bbl@error{bad-package-option}{#1}{#2}{}%
  \fi}
```

Now the option list is processed, taking into account only currently declared options (including those declared with a =), and ⟨*key*⟩=⟨*value*⟩ options (the former take precedence). Unrecognized options are saved in `\bbl@language@opts`, because they are language options.

```
\let\bbl@language@opts\@empty
\DeclareOption*{%
  \bbl@xin@{\string=}{\CurrentOption}%
  \ifin@
    \expandafter\bbl@tempa\CurrentOption\bbl@tempa
  \else
    \bbl@add@list\bbl@language@opts{\CurrentOption}%
  \fi}
```

Now we finish the first pass (and start over).

```
\ProcessOptions*
```

3.5. Post-process some options

```
\ifx\bbl@opt@provide\@nnil
  \let\bbl@opt@provide\@empty  % %%% MOVE above
\else
  \chardef\bbl@iniflag\@ne
  \bbl@exp{\\\bbl@forkv{\@nameuse{@raw@opt@babel.sty}}}{%
    \in@{,provide,}{,#1,}%
    \ifin@
      \def\bbl@opt@provide{#2}%
    \fi}
\fi
```

If there is no `shorthands=`⟨*chars*⟩, the original babel macros are left untouched, but if there is, these macros are wrapped (in `babel.def`) to define only those given.

A bit of optimization: if there is no `shorthands=`, then `\bbl@ifshorthand` is always true, and it is always false if `shorthands` is empty. Also, some code makes sense only with `shorthands=...`.

```
\bbl@trace{Conditional loading of shorthands}
\def\bbl@sh@string#1{%
  \ifx#1\@empty\else
    \ifx#1t\string~%
    \else\ifx#1c\string,%
    \else\string#1%
    \fi\fi
    \expandafter\bbl@sh@string
  \fi}
\ifx\bbl@opt@shorthands\@nnil
  \def\bbl@ifshorthand#1#2#3{#2}%
\else\ifx\bbl@opt@shorthands\@empty
  \def\bbl@ifshorthand#1#2#3{#3}%
\else
```

The following macro tests if a shorthand is one of the allowed ones.

```
  \def\bbl@ifshorthand#1{%
    \bbl@xin@{\string#1}{\bbl@opt@shorthands}%
    \ifin@
      \expandafter\@firstoftwo
    \else
      \expandafter\@secondoftwo
    \fi}
```

We make sure all chars in the string are 'other', with the help of an auxiliary macro defined above (which also zaps spaces).

```
  \edef\bbl@opt@shorthands{%
    \expandafter\bbl@sh@string\bbl@opt@shorthands\@empty}%
```

The following is ignored with `shorthands=off`, since it is intended to take some additional actions for certain chars.

```
  \bbl@ifshorthand{'}%
    {\PassOptionsToPackage{activeacute}{babel}}{}
  \bbl@ifshorthand{`}%
    {\PassOptionsToPackage{activegrave}{babel}}{}
\fi\fi
```

With `headfoot=lang` we can set the language used in heads/feet. For example, in babel/3796 just add `headfoot=english`. It misuses `\@resetactivechars`, but seems to work.

```
\ifx\bbl@opt@headfoot\@nnil\else
  \g@addto@macro\@resetactivechars{%
    \set@typeset@protect
    \expandafter\select@language@x\expandafter{\bbl@opt@headfoot}%
    \let\protect\noexpand}
\fi
```

For the option safe we use a different approach – `\bbl@opt@safe` says which macros are redefined (B for bibs and R for refs). By default, both are currently set, but in a future release it will be set to `none`.

```
\ifx\bbl@opt@safe\@undefined
```

```
  \def\bbl@opt@safe{BR}
  % \let\bbl@opt@safe\@empty % Pending of \cite
\fi
```

For `layout` an auxiliary macro is provided, available for packages and language styles. Optimization: if there is no `layout`, just do nothing.

```
\bbl@trace{Defining IfBabelLayout}
\ifx\bbl@opt@layout\@nnil
  \newcommand\IfBabelLayout[3]{#3}%
\else
  \bbl@exp{\\\bbl@forkv{\@nameuse{@raw@opt@babel.sty}}{%
    \in@{,layout,}{,#1,}%
    \ifin@
      \def\bbl@opt@layout{#2}%
      \bbl@replace\bbl@opt@layout{ }{.}%
    \fi}
  \newcommand\IfBabelLayout[1]{%
    \@expandtwoargs\in@{.#1.}{.\bbl@opt@layout.}%
    \ifin@
      \expandafter\@firstoftwo
    \else
      \expandafter\@secondoftwo
    \fi}
\fi
```

```
\def\bbl@version{<@version@>}
\def\bbl@date{<@date@>}
<@Define core switching macros@>
```

\adddialect The macro `\adddialect` can be used to add the name of a dialect or variant language, for which an already defined hyphenation table can be used.

```
\def\adddialect#1#2{%
  \global\chardef#1#2\relax
  \bbl@usehooks{adddialect}{{#1}{#2}}%
  \begingroup
    \count@#1\relax
    \def\bbl@elt##1##2##3##4{%
      \ifnum\count@=##2\relax
        \edef\bbl@tempa{\expandafter\@gobbletwo\string#1}%
        \bbl@info{Hyphen rules for '\expandafter\@gobble\bbl@tempa'
                  set to \expandafter\string\csname l@##1\endcsname\\%
                  (\string\language\the\count@). Reported}%
        \def\bbl@elt####1####2####3####4{}%
      \fi}%
    \bbl@cs{languages}%
  \endgroup}
```

`\bbl@iflanguage` executes code only if the language `l@` exists. Otherwise raises an error.

The argument of `\bbl@fixname` has to be a macro name, as it may get "fixed" if casing (lc/uc) is wrong. It's an attempt to fix a long-standing bug when `\foreignlanguage` and the like appear in a `\MakeXXXcase`. However, a lowercase form is not imposed to improve backward compatibility (perhaps you defined a language named `MYLANG`, but unfortunately mixed case names cannot be trapped). Note `l@` is encapsulated, so that its case does not change.

```
\def\bbl@fixname#1{%
  \begingroup
    \def\bbl@tempe{l@}%
    \edef\bbl@tempd{\noexpand\@ifundefined{\noexpand\bbl@tempe#1}}%
    \bbl@tempd
      {\lowercase\expandafter{\bbl@tempd}%
         {\uppercase\expandafter{\bbl@tempd}%
           \@empty
           {\edef\bbl@tempd{\def\noexpand#1{#1}}%
            \uppercase\expandafter{\bbl@tempd}}}%
         {\edef\bbl@tempd{\def\noexpand#1{#1}}%
          \lowercase\expandafter{\bbl@tempd}}}%
```

```
      \@empty
    \edef\bbl@tempd{\endgroup\def\noexpand#1{#1}}%
  \bbl@tempd
  \bbl@exp{\\\bbl@usehooks{languagename}{{\languagename}{#1}}}}
\def\bbl@iflanguage#1{%
  \@ifundefined{l@#1}{\@nolanerr{#1}\@gobble}\@firstofone}
```

After a name has been 'fixed', the selectors will try to load the language. If even the fixed name is not defined, will load it on the fly, either based on its name, or if activated, its BCP 47 code.

We first need a couple of macros for a simple BCP 47 look up. It also makes sure, casing is the usual one, so that sr-latn-ba becomes fr-Latn-BA.

`\bbl@bcplookup` returns `\bbl@bcp` with either the found `ini` tag or `\relax`. Temporary version, to be refactored with the new `\text_bcp_parse:n`, which is not currently fully expandable with invalid BCP 47 tags. The argument may be is some cases either a language name or a tag (e.g., `\foreignlanguage`. This was a huge mistake, because of the potential ambiguities (for example, the name `vai-latin` is also a syntactically valid tag).

```
\def\bbl@cntchars#1{\bbl@cntchars@i#1876543210\@@}
\def\bbl@cntchars@i#1#2#3#4#5#6#7#8#9\@@{\@car#9\@nil}%
\def\bbl@bcplookup#1{%
  \let\bbl@templ\@empty % language
  \let\bbl@temps\@empty % script
  \let\bbl@tempr\@empty % regions
  \let\bbl@tempv\@empty % variant
  \edef\bbl@tempa{#1}%
  \bbl@replace\bbl@tempa{-}{,}%
  \bbl@replace\bbl@tempa{_}{,}%
  \bbl@foreach\bbl@tempa{%
    \ifx\bbl@templ\@empty
      \lowercase{\def\bbl@templ{##1}}%
    \else\ifnum\bbl@cntchars{##1}=4
      \bbl@xin@{\@car##1\@nil}{0123456789}%
      \ifin@
        \def\bbl@tempv{##1}% eg, 1901
      \else
        \uppercase{\edef\bbl@tempb{\@car##1\@nil}}%
        \lowercase{\edef\bbl@temps{\bbl@tempb\@gobble##1}}%
      \fi
    \else\ifnum\bbl@cntchars{##1}<4
      \uppercase{\def\bbl@tempr{##1}}%
    \else\ifnum\bbl@cntchars{##1}>4
      \lowercase{\def\bbl@tempv{##1}}%
    \fi\fi\fi\fi}%
  \bbl@exp{\\\bbl@bcplookup@i{\bbl@templ}{\bbl@temps}{\bbl@tempr}{\bbl@tempv}}}
\def\bbl@bcplookup@try#1{%
 \ifx\bbl@bcp\relax
   \IfFileExists{babel-#1\bbl@tempe.ini}{\edef\bbl@bcp{#1\bbl@tempe}}{}%
\fi}
\def\bbl@bcplookup@i#1#2#3#4{%
  \let\bbl@bcp\relax
  \def\bbl@tempe{#4}%
  \ifx\bbl@tempe\@empty\else
    \edef\bbl@tempe{-#4}%
  \fi
  \edef\bbl@tempa{#2#3\bbl@tempe}% en
  \ifx\bbl@tempa\@empty
    \bbl@bcplookup@try{#1}%
  \else
    \edef\bbl@tempa{#3\bbl@tempe}% en-Latn
    \ifx\bbl@tempa\@empty
      \bbl@bcplookup@try{#1-#2}%
      \bbl@bcplookup@try{#1}%
    \else
      \edef\bbl@tempa{#2\bbl@tempe}% en-US, en-001
```

```
      \ifx\bbl@tempa\@empty
        \bbl@bcplookup@try{#1-#3}%
        \bbl@bcplookup@try{#1}%
      \else % en-Latn-US
        \bbl@bcplookup@try{#1-#2-#3}%
        \bbl@bcplookup@try{#1-#2}%
        \bbl@bcplookup@try{#1-#3}%
        \bbl@bcplookup@try{#1}%
      \fi
    \fi
  \fi
  \ifx\bbl@bcp\relax
    \ifx\bbl@tempe\@empty\else\bbl@bcplookup@i{#1}{#2}{#3}{}\fi%
  \fi}
%
\let\bbl@initoload\relax
```

\iflanguage Users might want to test (in a private package for instance) which language is currently active. For this we provide a test macro, `\iflanguage`, that has three arguments. It checks whether the first argument is a known language. If so, it compares the first argument with the value of `\language`. Then, depending on the result of the comparison, it executes either the second or the third argument.

```
\def\iflanguage#1{%
  \bbl@iflanguage{#1}{%
    \ifnum\csname l@#1\endcsname=\language
      \expandafter\@firstoftwo
    \else
      \expandafter\@secondoftwo
    \fi}}
```

3.6. Selecting the language

\selectlanguage It checks whether the language is already defined before it performs its actual task, which is to update `\language` and activate language-specific definitions.

```
\let\bbl@select@type\z@
\edef\selectlanguage{%
  \noexpand\protect
  \expandafter\noexpand\csname selectlanguage \endcsname}
```

Because the command `\selectlanguage` could be used in a moving argument it expands to `\protect\selectlanguage␣`. Therefore, we have to make sure that a macro `\protect` exists. If it doesn't it is `\let` to `\relax`.

```
\ifx\@undefined\protect\let\protect\relax\fi
```

The following definition is preserved for backwards compatibility (e.g., arabi, koma). It is related to a trick for 2.09, now discarded.

```
\let\xstring\string
```

Since version 3.5 babel writes entries to the auxiliary files in order to typeset table of contents etc. in the correct language environment.

\bbl@pop@language *But* when the language change happens *inside* a group the end of the group doesn't write anything to the auxiliary files. Therefore we need TEX's `aftergroup` mechanism to help us. The command `\aftergroup` stores the token immediately following it to be executed when the current group is closed. So we define a temporary control sequence `\bbl@pop@language` to be executed at the end of the group. It calls `\bbl@set@language` with the name of the current language as its argument.

\bbl@language@stack The previous solution works for one level of nesting groups, but as soon as more levels are used it is no longer adequate. For that case we need to keep track of the nested languages using a stack mechanism. This stack is called `\bbl@language@stack` and initially empty.

```
\def\bbl@language@stack{}
```

When using a stack we need a mechanism to push an element on the stack and to retrieve the information afterwards.

\bbl@push@language
\bbl@pop@language The stack is simply a list of languagenames, separated with a '+' sign; the push function can be simple:

```
\def\bbl@push@language{%
  \ifx\languagename\@undefined\else
    \ifx\currentgrouplevel\@undefined
      \xdef\bbl@language@stack{\languagename+\bbl@language@stack}%
    \else
      \ifnum\currentgrouplevel=\z@
        \xdef\bbl@language@stack{\languagename+}%
      \else
        \xdef\bbl@language@stack{\languagename+\bbl@language@stack}%
      \fi
    \fi
  \fi}
```

Retrieving information from the stack is a little bit less simple, as we need to remove the element from the stack while storing it in the macro `\languagename`. For this we first define a helper function.

\bbl@pop@lang This macro stores its first element (which is delimited by the '+'-sign) in `\languagename` and stores the rest of the string in `\bbl@language@stack`.

```
\def\bbl@pop@lang#1+#2\@@{%
  \edef\languagename{#1}%
  \xdef\bbl@language@stack{#2}}
```

The reason for the somewhat weird arrangement of arguments to the helper function is the fact it is called in the following way. This means that before `\bbl@pop@lang` is executed TEX first *expands* the stack, stored in `\bbl@language@stack`. The result of that is that the argument string of `\bbl@pop@lang` contains one or more language names, each followed by a '+'-sign (zero language names won't occur as this macro will only be called after something has been pushed on the stack).

```
\let\bbl@ifrestoring\@secondoftwo
\def\bbl@pop@language{%
  \expandafter\bbl@pop@lang\bbl@language@stack\@@
  \let\bbl@ifrestoring\@firstoftwo
  \expandafter\bbl@set@language\expandafter{\languagename}%
  \let\bbl@ifrestoring\@secondoftwo}
```

Once the name of the previous language is retrieved from the stack, it is fed to `\bbl@set@language` to do the actual work of switching everything that needs switching.

An alternative way to identify languages (in the babel sense) with a numerical value is introduced in 3.30. This is one of the first steps for a new interface based on the concept of locale, which explains the name of `\localeid`. This means `\l@...` will be reserved for hyphenation patterns (so that two locales can share the same rules).

```
\chardef\localeid\z@
\gdef\bbl@id@last{0}    % No real need for a new counter
\def\bbl@id@assign{%
  \bbl@ifunset{bbl@id@@\languagename}%
    {\count@\bbl@id@last\relax
     \advance\count@\@ne
     \global\bbl@csarg\chardef{id@@\languagename}\count@
     \xdef\bbl@id@last{\the\count@}%
     \ifcase\bbl@engine\or
       \directlua{
         Babel.locale_props[\bbl@id@last] = {}
         Babel.locale_props[\bbl@id@last].name = '\languagename'
         Babel.locale_props[\bbl@id@last].vars = {}
        }%
      \fi}%
    {}%
    \chardef\localeid\bbl@cl{id@}}
```

The unprotected part of `\selectlanguage`. In case it is used as environment, declare `\endselectlaguage`, just for safety.

```
\let\bbl@select@opts\@empty
\expandafter\def\csname selectlanguage \endcsname{%
  \@ifnextchar[\bbl@select@s{\bbl@select@s[]}}
\def\bbl@select@s[#1]#2{%
  \bbl@forkv{#1}{\bbl@array@set\bbl@select@opts{##1}{##2}}%
  \ifnum\bbl@hymapsel=\@cclv\let\bbl@hymapsel\tw@\fi
  \bbl@push@language
  \aftergroup\bbl@pop@language
  \bbl@set@language{#2}}
\let\endselectlanguage\relax
```

\bbl@set@language The macro `\bbl@set@language` takes care of switching the language environment *and* of writing entries on the auxiliary files. For historical reasons, language names can be either `language` of `\language`. To catch either form a trick is used, but unfortunately as a side effect the catcodes of letters in `\languagename` are messed up. This is a bug, but preserved for backwards compatibility. The list of auxiliary files can be extended by redefining `\BabelContentsFiles`, but make sure they are loaded inside a group (as `aux`, `toc`, `lof`, and `lot` do) or the last language of the document will remain active afterwards.

We also write a command to change the current language in the auxiliary files.

`\bbl@savelastskip` is used to deal with skips before the write whatsit (as suggested by U Fischer). Adapted from hyperref, but it might fail, so I'll consider it a temporary hack, while I study other options (the ideal, but very likely unfeasible except perhaps in luatex, is to avoid the `\write` altogether when not needed).

```
\def\BabelContentsFiles{toc,lof,lot}
\def\bbl@set@language#1{% from selectlanguage, pop@
  % The old buggy way. Preserved for compatibility, but simplified
  \edef\languagename{\expandafter\string#1\@empty}%
  \select@language{\languagename}%
  \bbl@array@get\bbl@select@opts{main}\bbl@tempa
  \ifx\bbl@tempa\relax\else
    \let\bbl@main@language\localename
    \let\mainlocalename\localename
  \fi
  % write to aux files
  \expandafter\ifx\csname date\languagename\endcsname\relax\else
    \if@filesw
      \bbl@array@get\bbl@select@opts{nofiles}\bbl@tempa
      \ifx\bbl@tempa\relax
        \ifx\babel@aux\@gobbletwo\else % Set if single in the first, redundant
          \bbl@savelastskip
          \protected@write\@auxout{}{\string\babel@aux{\bbl@auxname}{}}%
          \bbl@restorelastskip
        \fi
        \bbl@usehooks{write}{}%
      \fi
    \fi
  \fi
  \let\bbl@select@opts\@empty}
%
\let\bbl@restorelastskip\relax
\let\bbl@savelastskip\relax
%
\def\select@language#1{% from set@, babel@aux, babel@toc
  \ifx\bbl@selectorname\@empty
    \def\bbl@selectorname{select}%
  \fi
  % set hymap
  \ifnum\bbl@hymapsel=\@cclv\chardef\bbl@hymapsel4\relax\fi
  % set name (when coming from babel@aux)
  \edef\languagename{#1}%
```

```
  \bbl@fixname\languagename
  % define \localename when coming from set@, with a trick
  \ifx\scantokens\@undefined
    \def\localename{??}%
  \else
    \bbl@exp{\\\scantokens{\def\\\localename{\languagename}\\\noexpand}\relax}%
  \fi
  \bbl@provide@locale
  \bbl@iflanguage\languagename{%
    \let\bbl@select@type\z@
    \expandafter\bbl@switch\expandafter{\languagename}}}
\def\babel@aux#1#2{%
  \select@language{#1}%
  \bbl@foreach\BabelContentsFiles{% \relax -> don't assume vertical mode
    \@writefile{##1}{\babel@toc{#1}{#2}\relax}}}%
\def\babel@toc#1#2{%
  \select@language{#1}}
```

First, check if the user asks for a known language. If so, update the value of `\language` and call `\originalTeX` to bring TEX in a certain pre-defined state.

The name of the language is stored in the control sequence `\languagename`.

Then we have to *re*define `\originalTeX` to compensate for the things that have been activated. To save memory space for the macro definition of `\originalTeX`, we construct the control sequence name for the `\noextras`⟨*language*⟩ command at definition time by expanding the `\csname` primitive.

Now activate the language-specific definitions. This is done by constructing the names of three macros by concatenating three words with the argument of `\selectlanguage`, and calling these macros.

The switching of the values of `\lefthyphenmin` and `\righthyphenmin` is somewhat different. First we save their current values, then we check if \⟨*language*⟩`hyphenmins` is defined. If it is not, we set default values (2 and 3), otherwise the values in \⟨*language*⟩`hyphenmins` will be used.

No text is supposed to be added with switching captions and date, so we remove any spurious spaces with `\bbl@bsphack` and `\bbl@esphack`.

```
\newif\ifbbl@usedategroup
\let\bbl@savedextras\@empty
\def\bbl@switch#1{%  from select@, foreign@
  % restore
  \originalTeX
  \expandafter\def\expandafter\originalTeX\expandafter{%
    \csname noextras#1\endcsname
    \let\originalTeX\@empty
    \babel@beginsave}%
  \bbl@usehooks{afterreset}{}%
  \languageshorthands{none}%
  % set the locale id
  \bbl@id@assign
  % switch captions, date
  \bbl@bsphack
    \ifcase\bbl@select@type
      \csname captions#1\endcsname\relax
      \csname date#1\endcsname\relax
    \else
      \bbl@array@get\bbl@select@opts{captions}\bbl@tempa
      \ifx\bbl@tempa\relax\else
        \csname captions#1\endcsname\relax
      \fi
      \bbl@array@get\bbl@select@opts{date}\bbl@tempa
      \ifx\bbl@tempa\relax\else % if \foreign... within \<language>date
        \csname date#1\endcsname\relax
      \fi
    \fi
  \bbl@esphack
  % switch extras
  \csname bbl@preextras@#1\endcsname
```

```
\bbl@usehooks{beforeextras}{}%
\csname extras#1\endcsname\relax
\bbl@usehooks{afterextras}{}%
%  > babel-ensure
%  > babel-sh-<short>
%  > babel-bidi
%  > babel-fontspec
\let\bbl@savedextras\@empty
% hyphenation - case mapping
\ifcase\bbl@opt@hyphenmap\or
  \def\BabelLower##1##2{\lccode##1=##2\relax}%
  \ifnum\bbl@hymapsel>4\else
    \csname\languagename @bbl@hyphenmap\endcsname
  \fi
  \chardef\bbl@opt@hyphenmap\z@
\else
  \ifnum\bbl@hymapsel>\bbl@opt@hyphenmap\else
    \csname\languagename @bbl@hyphenmap\endcsname
  \fi
\fi
\let\bbl@hymapsel\@cclv
% hyphenation - select rules
\ifnum\csname l@\languagename\endcsname=\l@unhyphenated
  \edef\bbl@tempa{u}%
\else
  \edef\bbl@tempa{\bbl@cl{lnbrk}}%
\fi
% linebreaking - handle u, e, k (v in the future)
\bbl@xin@{/u}{/\bbl@tempa}%
\ifin@\else\bbl@xin@{/e}{/\bbl@tempa}\fi % elongated forms
\ifin@\else\bbl@xin@{/k}{/\bbl@tempa}\fi % only kashida
\ifin@\else\bbl@xin@{/p}{/\bbl@tempa}\fi % padding (e.g., Tibetan)
\ifin@\else\bbl@xin@{/v}{/\bbl@tempa}\fi % variable font
% hyphenation - save mins
\babel@savevariable\lefthyphenmin
\babel@savevariable\righthyphenmin
\ifnum\bbl@engine=\@ne
  \babel@savevariable\hyphenationmin
\fi
\ifin@
  % unhyphenated/kashida/elongated/padding = allow stretching
  \language\l@unhyphenated
  \babel@savevariable\emergencystretch
  \emergencystretch\maxdimen
  \babel@savevariable\hbadness
  \hbadness\@M
\else
  % other = select patterns
  \bbl@patterns{#1}%
\fi
% hyphenation - set mins
\expandafter\ifx\csname #1hyphenmins\endcsname\relax
  \set@hyphenmins\tw@\thr@@\relax
  \@nameuse{bbl@hyphenmins@}%
\else
  \expandafter\expandafter\expandafter\set@hyphenmins
    \csname #1hyphenmins\endcsname\relax
\fi
\@nameuse{bbl@hyphenmins@}%
\@nameuse{bbl@hyphenmins@\languagename}%
\@nameuse{bbl@hyphenatmin@}%
\@nameuse{bbl@hyphenatmin@\languagename}%
\let\bbl@selectorname\@empty}
```

otherlanguage It can be used as an alternative to using the `\selectlanguage` declarative command. The `\ignorespaces` command is necessary to hide the environment when it is entered in horizontal mode.

```
\edef\otherlanguage{%
  \noexpand\protect
  \expandafter\noexpand\csname otherlanguage \endcsname}
\expandafter\def\csname otherlanguage \endcsname{%
  \@ifstar{\@nameuse{otherlanguage*}}\bbl@otherlanguage}
\def\bbl@otherlanguage#1{%
  \def\bbl@selectorname{other}%
  \ifnum\bbl@hymapsel=\@cclv\let\bbl@hymapsel\thr@@\fi
  \csname selectlanguage \endcsname{#1}%
  \ignorespaces}
```

The `\endotherlanguage` part of the environment tries to hide itself when it is called in horizontal mode.

```
\long\def\endotherlanguage{\@ignoretrue\ignorespaces}
```

otherlanguage* It is meant to be used when a large part of text from a different language needs to be typeset, but without changing the translation of words such as 'figure'. It makes use of `\foreign@language`.

```
\expandafter\def\csname otherlanguage*\endcsname{%
  \@ifnextchar[\bbl@otherlanguage@s{\bbl@otherlanguage@s[]}}
\def\bbl@otherlanguage@s[#1]#2{%
  \def\bbl@selectorname{other*}%
  \ifnum\bbl@hymapsel=\@cclv\chardef\bbl@hymapsel4\relax\fi
  \bbl@forkv{#1}{\bbl@array@set\bbl@select@opts{##1}{##2}}%
  \foreign@language{#2}}
```

At the end of the environment we need to switch off the extra definitions. The grouping mechanism of the environment will take care of resetting the correct hyphenation rules and "extras".

```
\expandafter\let\csname endotherlanguage*\endcsname\relax
```

\foreignlanguage This command takes two arguments, the first argument is the name of the language to use for typesetting the text specified in the second argument.

Unlike `\selectlanguage` this command doesn't switch *everything*, it only switches the hyphenation rules and the extra definitions for the language specified. It does this within a group and assumes the `\extras`⟨*language*⟩ command doesn't make any `\global` changes. The coding is very similar to part of `\selectlanguage`.

`\bbl@beforeforeign` is a trick to fix a bug in bidi texts. `\foreignlanguage` is supposed to be a 'text' command, and therefore it must emit a `\leavevmode`, but it does not, and therefore the indent is placed on the opposite margin. For backward compatibility, however, it is done only if a right-to-left script is requested; otherwise, it is no-op.

(3.11) `\foreignlanguage*` is a temporary, experimental macro for a few lines with a different script direction, while preserving the paragraph format (thank the braces around `\par`, things like `\hangindent` are not reset). Do not use it in production, because its semantics and its syntax may change (and very likely will, or even it could be removed altogether). Currently it enters in vmode and then selects the language (which in turn sets the paragraph direction).

(3.11) Also experimental are the hook `foreign` and `foreign*`. With them you can redefine `\BabelText` which by default does nothing. Its behavior is not well defined yet. So, use it in horizontal mode only if you do not want surprises.

In other words, at the beginning of a paragraph `\foreignlanguage` enters into hmode with the surrounding lang, and with `\foreignlanguage*` with the new lang.

```
\providecommand\bbl@beforeforeign{}
\edef\foreignlanguage{%
  \noexpand\protect
  \expandafter\noexpand\csname foreignlanguage \endcsname}
\expandafter\def\csname foreignlanguage \endcsname{%
  \@ifstar\bbl@foreign@s\bbl@foreign@x}
\providecommand\bbl@foreign@x[3][]{%
  \begingroup
    \def\bbl@selectorname{foreign}%
```

```
    \bbl@forkv{#1}{\bbl@array@set\bbl@select@opts{##1}{##2}}%
    \let\BabelText\@firstofone
    \bbl@beforeforeign
    \foreign@language{#2}%
    \bbl@ifmetadata{\UseTaggingSocket{babel/foreign/begin}}%
    \bbl@usehooks{foreign}{}%
    \BabelText{#3}% Now in horizontal mode!
    \bbl@ifmetadata{\UseTaggingSocket{babel/foreign/end}}%
  \endgroup}
\def\bbl@foreign@s#1#2{%
  \begingroup
    {\par}%
    \def\bbl@selectorname{foreign*}%
    \let\bbl@select@opts\@empty
    \let\BabelText\@firstofone
    \foreign@language{#1}%
    \bbl@usehooks{foreign*}{}%
    \bbl@dirparastext
    \BabelText{#2}% Still in vertical mode!
    {\par}%
  \endgroup}
\providecommand\BabelWrapText[1]{%
   \def\bbl@tempa{\def\BabelText####1}%
   \expandafter\bbl@tempa\expandafter{\BabelText{#1}}}
```

\foreign@language This macro does the work for `\foreignlanguage` and the `otherlanguage*` environment. First we need to store the name of the language and check that it is a known language. Then it just calls `bbl@switch`.

```
\def\foreign@language#1{%
  % set name
  \edef\languagename{#1}%
  \ifbbl@usedategroup
    \bbl@array@set\bbl@select@opts{date}{\@empty}%
    \bbl@usedategroupfalse
  \fi
  \bbl@fixname\languagename
  \let\localename\languagename
  \bbl@provide@locale
  \bbl@iflanguage\languagename{%
    \let\bbl@select@type\@ne
    \expandafter\bbl@switch\expandafter{\languagename}}}
```

The following macro executes conditionally some code based on the selector being used.

```
\let\bbl@selectorname\@empty
\def\IfBabelSelectorTF#1{%
  \bbl@xin@{,\bbl@selectorname,}{,\zap@space#1 \@empty,}%
  \ifin@
    \expandafter\@firstoftwo
  \else
    \expandafter\@secondoftwo
  \fi}
```

\bbl@patterns This macro selects the hyphenation patterns by changing the `\language` register. If special hyphenation patterns are available specifically for the current font encoding, use them instead of the default.

It also sets hyphenation exceptions, but only once, because they are global (here language `\lccode`'s has been set, too). `\bbl@hyphenation@` is set to relax until the very first `\babelhyphenation`, so do nothing with this value. If the exceptions for a language (by its number, not its name, so that `:ENC` is taken into account) has been set, then use `\hyphenation` with both global and language exceptions and empty the latter to mark they must not be set again.

```
\let\bbl@hyphlist\@empty
\let\bbl@hyphenation@\relax
```

```
\let\bbl@pttnlist\@empty
\let\bbl@patterns@\relax
\let\bbl@hymapsel=\@cclv
\def\bbl@patterns#1{%
  \language=\expandafter\ifx\csname l@#1:\f@encoding\endcsname\relax
      \csname l@#1\endcsname
      \edef\bbl@tempa{#1}%
    \else
      \csname l@#1:\f@encoding\endcsname
      \edef\bbl@tempa{#1:\f@encoding}%
    \fi
  \@expandtwoargs\bbl@usehooks{patterns}{{#1}{\bbl@tempa}}%
  %  > luatex
  \@ifundefined{bbl@hyphenation@}{}{% Can be \relax!
    \begingroup
      \bbl@xin@{,\number\language,}{,\bbl@hyphlist}%
      \ifin@\else
        \@expandtwoargs\bbl@usehooks{hyphenation}{{#1}{\bbl@tempa}}%
        \hyphenation{%
          \bbl@hyphenation@
          \@ifundefined{bbl@hyphenation@#1}%
            \@empty
            {\space\csname bbl@hyphenation@#1\endcsname}}%
        \xdef\bbl@hyphlist{\bbl@hyphlist\number\language,}%
      \fi
    \endgroup}}
```

hyphenrules It can be used to select *just* the hyphenation rules. It does *not* change `\languagename` and when the hyphenation rules specified were not loaded it has no effect. Note however, `\lccode`'s and font encodings are not set at all, so in most cases you should use `otherlanguage*`.

```
\def\hyphenrules#1{%
  \edef\bbl@tempf{#1}%
  \bbl@fixname\bbl@tempf
  \bbl@iflanguage\bbl@tempf{%
    \expandafter\bbl@patterns\expandafter{\bbl@tempf}%
    \ifx\languageshorthands\@undefined\else
      \languageshorthands{none}%
    \fi
    \expandafter\ifx\csname\bbl@tempf hyphenmins\endcsname\relax
      \set@hyphenmins\tw@\thr@@\relax
    \else
      \expandafter\expandafter\expandafter\set@hyphenmins
      \csname\bbl@tempf hyphenmins\endcsname\relax
    \fi}}
\let\endhyphenrules\@empty
```

\providehyphenmins The macro `\providehyphenmins` should be used in the language definition files to provide a *default* setting for the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`. If the macro \⟨*language*⟩`hyphenmins` is already defined this command has no effect.

```
\def\providehyphenmins#1#2{%
  \expandafter\ifx\csname #1hyphenmins\endcsname\relax
    \@namedef{#1hyphenmins}{#2}%
  \fi}
```

\set@hyphenmins This macro sets the values of `\lefthyphenmin` and `\righthyphenmin`. It expects two values as its argument.

```
\def\set@hyphenmins#1#2{%
  \lefthyphenmin#1\relax
  \righthyphenmin#2\relax}
```

\ProvidesLanguage The identification code for each file is something that was introduced in LaTeX 2$_\varepsilon$. When the command `\ProvidesFile` does not exist, a dummy definition is provided temporarily. For use in the language definition file the command `\ProvidesLanguage` is defined by babel.

Depending on the format, i.e., or if the former is defined, we use a similar definition or not.

```
\ifx\ProvidesFile\@undefined
  \def\ProvidesLanguage#1[#2 #3 #4]{%
    \wlog{Language: #1 #4 #3 <#2>}%
    }
\else
  \def\ProvidesLanguage#1{%
    \begingroup
      \catcode`\ 10 %
      \@makeother\/%
      \@ifnextchar[%]
        {\@provideslanguage{#1}}{\@provideslanguage{#1}[]}}
  \def\@provideslanguage#1[#2]{%
    \wlog{Language: #1 #2}%
    \expandafter\xdef\csname ver@#1.ldf\endcsname{#2}%
    \endgroup}
\fi
```

\originalTeX The macro`\originalTeX` should be known to TeX at this moment. As it has to be expandable we `\let` it to `\@empty` instead of `\relax`.

```
\ifx\originalTeX\@undefined\let\originalTeX\@empty\fi
```

Because this part of the code can be included in a format, we make sure that the macro which initializes the save mechanism, `\babel@beginsave`, is not considered to be undefined.

```
\ifx\babel@beginsave\@undefined\let\babel@beginsave\relax\fi
```

A few macro names are reserved for future releases of babel, which will use the concept of 'locale':

```
\providecommand\setlocale{\bbl@error{not-yet-available}{}{}{}}
\let\uselocale\setlocale
\let\locale\setlocale
\let\selectlocale\setlocale
\let\textlocale\setlocale
\let\textlanguage\setlocale
\let\languagetext\setlocale
```

3.7. Errors

\@nolanerr
\@nopatterns The babel package will signal an error when a documents tries to select a language that hasn't been defined earlier. When a user selects a language for which no hyphenation patterns were loaded into the format he will be given a warning about that fact. We revert to the patterns for `\language`=0 in that case. In most formats that will be (US)english, but it might also be empty.

\@noopterr When the package was loaded without options not everything will work as expected. An error message is issued in that case.

When the format knows about `\PackageError` it must be LaTeX 2$_\varepsilon$, so we can safely use its error handling interface. Otherwise we'll have to 'keep it simple'.

Infos are not written to the console, but on the other hand many people think warnings are errors, so a further message type is defined: an important info which is sent to the console.

```
\edef\bbl@nulllanguage{\string\language=0}
\def\bbl@nocaption#1#2{\NoCaseChange{\protect\bbl@nocaption@i{#1}{#2}}}
\def\bbl@nocaption@i#1#2{% 1: text to be printed 2: caption macro \langXname
  \global\@namedef{#2}{\textbf{?#1?}}%
  \@nameuse{#2}%
  \edef\bbl@tempa{#1}%
  \bbl@sreplace\bbl@tempa{name}{}%
  \bbl@warning{%
    \@backslashchar#1 not set for '\languagename'. Please,\\%
```

```
    define it after the language has been loaded\\%
    (typically in the preamble) with:\\%
    \string\setlocalecaption{\languagename}{\bbl@tempa}{..}\\%
    Feel free to contribute on github.com/latex3/babel.\\%
    Reported}}
\def\bbl@tentative{\protect\bbl@tentative@i}
\def\bbl@tentative@i#1{%
  \bbl@warning{%
    Some functions for '#1' are tentative.\\%
    They might not work as expected and their behavior\\%
    could change in the future.\\%
    Reported}}
\def\@nolanerr#1{\bbl@error{undefined-language}{#1}{}{}}
\def\@nopatterns#1{%
  \bbl@warning
    {No hyphenation patterns were preloaded for\\%
     the language '#1' into the format.\\%
     Please, configure your TeX system to add them and\\%
     rebuild the format. Now I will use the patterns\\%
     preloaded for \bbl@nulllanguage\space instead}}
\let\bbl@usehooks\@gobbletwo
```

Here ended the now discarded `switch.def`.
Here also (currently) ends the base option.

```
\ifx\bbl@onlyswitch\@empty\endinput\fi
```

3.8. More on selection

\babelensure The user command just parses the optional argument and creates a new macro named `\bbl@e@`⟨*language*⟩. We register a hook at the `afterextras` event which just executes this macro in a "complete" selection (which, if undefined, is `\relax` and does nothing). This part is somewhat involved because we have to make sure things are expanded the correct number of times.

The macro `\bbl@e@`⟨*language*⟩ contains `\bbl@ensure{`⟨*include*⟩`}{`⟨*exclude*⟩`}{`⟨*fontenc*⟩`}`, which in in turn loops over the macros names in `\bbl@captionslist`, excluding (with the help of `\in@`) those in the `exclude` list. If the `fontenc` is given (and not `\relax`), the `\fontencoding` is also added. Then we loop over the `include` list, but if the macro already contains `\foreignlanguage`, nothing is done. Note this macro (1) is not restricted to the preamble, and (2) changes are local.

```
\bbl@trace{Defining babelensure}
\newcommand\babelensure[2][]{%
  \AddBabelHook{babel-ensure}{afterextras}{%
    \ifcase\bbl@select@type
      \bbl@cl{e}%
    \fi}%
  \begingroup
    \let\bbl@ens@include\@empty
    \let\bbl@ens@exclude\@empty
    \def\bbl@ens@fontenc{\relax}%
    \def\bbl@tempb##1{%
      \ifx\@empty##1\else\noexpand##1\expandafter\bbl@tempb\fi}%
    \edef\bbl@tempa{\bbl@tempb#1\@empty}%
    \def\bbl@tempb##1=##2\@@{\@namedef{bbl@ens@##1}{##2}}%
    \bbl@foreach\bbl@tempa{\bbl@tempb##1\@@}%
    \def\bbl@tempc{\bbl@ensure}%
    \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
      \expandafter{\bbl@ens@include}}%
    \expandafter\bbl@add\expandafter\bbl@tempc\expandafter{%
      \expandafter{\bbl@ens@exclude}}%
    \toks@\expandafter{\bbl@tempc}%
    \bbl@exp{%
  \endgroup
  \def\<bbl@e@#2>{\the\toks@{\bbl@ens@fontenc}}}}
\def\bbl@ensure#1#2#3{% 1: include 2: exclude 3: fontenc
  \def\bbl@tempb##1{% elt for (excluding) \bbl@captionslist list
```

```
    \ifx##1\@undefined % 3.32 - Don't assume the macro exists
      \edef##1{\noexpand\bbl@nocaption
        {\bbl@stripslash##1}{\languagename\bbl@stripslash##1}}%
    \fi
    \ifx##1\@empty\else
      \in@{##1}{#2}%
      \ifin@\else
        \let\bbl@tempc\languagename
        \bbl@replace\bbl@tempc{-}{@@}%
        \bbl@ifunset{bbl@ensure@\bbl@tempc}%
          {\bbl@exp{%
            \\\DeclareRobustCommand\<bbl@ensure@\bbl@tempc>[1]{%
              \\\foreignlanguage{\languagename}%
              {\ifx\relax#3\else
                \\\fontencoding{#3}\\\selectfont
               \fi
               ########1}}}}%
          {}%
        \toks@\expandafter{##1}%
        \edef##1{%
           \bbl@csarg\noexpand{ensure@\bbl@tempc}%
           {\the\toks@}}%
      \fi
      \expandafter\bbl@tempb
    \fi}%
  \expandafter\bbl@tempb\bbl@captionslist\today\@empty
  \def\bbl@tempa##1{% elt for include list
    \ifx##1\@empty\else
      \let\bbl@tempc\languagename
      \bbl@replace\bbl@tempc{-}{@@}%
      \bbl@csarg\in@{ensure@\bbl@tempc\expandafter}\expandafter{##1}%
      \ifin@\else
        \bbl@tempb##1\@empty
      \fi
      \expandafter\bbl@tempa
    \fi}%
  \bbl@tempa#1\@empty}
\def\bbl@captionslist{%
  \prefacename\refname\abstractname\bibname\chaptername\appendixname
  \contentsname\listfigurename\listtablename\indexname\figurename
  \tablename\partname\enclname\ccname\headtoname\pagename\seename
  \alsoname\proofname\glossaryname}
```

3.9. Short tags

\babeltags This macro is straightforward. After zapping spaces, we loop over the list and define the macros \text⟨*tag*⟩ and \⟨*tag*⟩. Definitions are first expanded so that they don't contain \csname but the actual macro.

```
\bbl@trace{Short tags}
\newcommand\babeltags[1]{%
  \edef\bbl@tempa{\zap@space#1 \@empty}%
  \def\bbl@tempb##1=##2\@@{%
    \edef\bbl@tempc{%
      \noexpand\newcommand
      \expandafter\noexpand\csname ##1\endcsname{%
        \noexpand\protect
        \expandafter\noexpand\csname otherlanguage*\endcsname{##2}}
      \noexpand\newcommand
      \expandafter\noexpand\csname text##1\endcsname{%
        \noexpand\foreignlanguage{##2}}}
    \bbl@tempc}%
  \bbl@for\bbl@tempa\bbl@tempa{%
    \expandafter\bbl@tempb\bbl@tempa\@@}}
```

3.10. Compatibility with language.def

Plain e-TEX doesn't rely on language.dat, but babel can be made compatible with this format easily.

```
\bbl@trace{Compatibility with language.def}
\ifx\directlua\@undefined\else
  \ifx\bbl@luapatterns\@undefined
    \input luababel.def
  \fi
\fi
\ifx\bbl@languages\@undefined
  \ifx\directlua\@undefined
    \openin0 = language.def
    \ifeof0
      \closein0
      \message{I couldn't find the file language.def}
    \else
      \closein0
      \begingroup
        \def\addlanguage#1#2#3#4#5{%
          \expandafter\ifx\csname lang@#1\endcsname\relax\else
            \global\expandafter\let\csname l@#1\expandafter\endcsname
              \csname lang@#1\endcsname
          \fi}%
        \def\uselanguage#1{}%
        \input language.def
      \endgroup
    \fi
  \fi
  \chardef\l@english\z@
\fi
```

\addto It takes two arguments, a ⟨*control sequence*⟩ and TEX-code to be added to the ⟨*control sequence*⟩.

If the ⟨*control sequence*⟩ has not been defined before it is defined now. The control sequence could also expand to `\relax`, in which case a circular definition results. The net result is a stack overflow. Note there is an inconsistency, because the assignment in the last branch is global.

```
\def\addto#1#2{%
  \ifx#1\@undefined
    \def#1{#2}%
  \else
    \ifx#1\relax
      \def#1{#2}%
    \else
      {\toks@\expandafter{#1#2}%
       \xdef#1{\the\toks@}}%
    \fi
  \fi}
```

3.11. Hooks

Admittedly, the current implementation is a somewhat simplistic and does very little to catch errors, but it is meant for developers, after all. `\bbl@usehooks` is the commands used by babel to execute hooks defined for an event.

```
\bbl@trace{Hooks}
\newcommand\AddBabelHook[3][]{%
  \bbl@ifunset{bbl@hk@#2}{\EnableBabelHook{#2}}{}%
  \def\bbl@tempa##1,#3=##2,##3\@empty{\def\bbl@tempb{##2}}%
  \expandafter\bbl@tempa\bbl@evargs,#3=,\@empty
  \bbl@ifunset{bbl@ev@#2@#3@#1}%
    {\bbl@csarg\bbl@add{ev@#3@#1}{\bbl@elth{#2}}}%
    {\bbl@csarg\let{ev@#2@#3@#1}\relax}%
  \bbl@csarg\newcommand{ev@#2@#3@#1}[\bbl@tempb]}
```

```
\newcommand\EnableBabelHook[1]{\bbl@csarg\let{hk@#1}\@firstofone}
\newcommand\DisableBabelHook[1]{\bbl@csarg\let{hk@#1}\@gobble}
\def\bbl@usehooks{\bbl@usehooks@lang\languagename}
\def\bbl@usehooks@lang#1#2#3{% Test for Plain
  \ifx\UseHook\@undefined\else\UseHook{babel/*/#2}\fi
  \def\bbl@elth##1{%
    \bbl@cs{hk@##1}{\bbl@cs{ev@##1@#2@}#3}}%
  \bbl@cs{ev@#2@}%
  \ifx\languagename\@undefined\else % Test required for Plain (?)
    \ifx\UseHook\@undefined\else\UseHook{babel/#1/#2}\fi
    \def\bbl@elth##1{%
      \bbl@cs{hk@##1}{\bbl@cs{ev@##1@#2@#1}#3}}%
    \bbl@cs{ev@#2@#1}%
  \fi}
```

To ensure forward compatibility, arguments in hooks are set implicitly. So, if a further argument is added in the future, there is no need to change the existing code. Note events intended for hyphen.cfg are also loaded (just in case you need them for some reason).

```
\def\bbl@evargs{,% <- don't delete this comma
  everylanguage=1,loadkernel=1,loadpatterns=1,loadexceptions=1,%
  adddialect=2,patterns=2,defaultcommands=0,encodedcommands=2,write=0,%
  beforeextras=0,afterextras=0,stopcommands=0,stringprocess=0,%
  hyphenation=2,initiateactive=3,afterreset=0,foreign=0,foreign*=0,%
  beforestart=0,languagename=2,begindocument=1}
\ifx\NewHook\@undefined\else % Test for Plain (?)
  \def\bbl@tempa#1=#2\@@{\NewHook{babel/#1}\NewHook{babel/*/#1}}
  \bbl@foreach\bbl@evargs{\bbl@tempa#1\@@}
\fi
```

Since the following command is meant for a hook (although a LaTeX one), it's placed here.

```
\providecommand\PassOptionsToLocale[2]{%
  \bbl@csarg\bbl@add@list{passto@#2}{#1}}
```

3.12. Setting up language files

\LdfInit `\LdfInit` macro takes two arguments. The first argument is the name of the language that will be defined in the language definition file; the second argument is either a control sequence or a string from which a control sequence should be constructed. The existence of the control sequence indicates that the file has been processed before.

At the start of processing a language definition file we always check the category code of the at-sign. We make sure that it is a 'letter' during the processing of the file. We also save its name as the last called option, even if not loaded.

Another character that needs to have the correct category code during processing of language definition files is the equals sign, '=', because it is sometimes used in constructions with the `\let` primitive. Therefore we store its current catcode and restore it later on.

Now we check whether we should perhaps stop the processing of this file. To do this we first need to check whether the second argument that is passed to `\LdfInit` is a control sequence. We do that by looking at the first token after passing #2 through `string`. When it is equal to `\@backslashchar` we are dealing with a control sequence which we can compare with `\@undefined`.

If so, we call `\ldf@quit` to set the main language, restore the category code of the @-sign and call `\endinput`

When #2 was *not* a control sequence we construct one and compare it with `\relax`.

Finally we check `\originalTeX`.

```
\bbl@trace{Macros for setting language files up}
\def\bbl@ldfinit{%
  \let\bbl@screset\@empty
  \let\BabelStrings\bbl@opt@string
  \let\BabelOptions\@empty
  \let\BabelLanguages\relax
  \ifx\originalTeX\@undefined
    \let\originalTeX\@empty
  \else
    \originalTeX
```

```
  \fi}
\def\LdfInit#1#2{%
  \chardef\atcatcode=\catcode`\@
  \catcode`\@=11\relax
  \chardef\eqcatcode=\catcode`\=
  \catcode`\==12\relax
  \@ifpackagewith{babel}{ensureinfo=off}{}%
    {\ifx\InputIfFileExists\@undefined\else
       \bbl@ifunset{bbl@lname@#1}%
         {{\let\bbl@ensuring\@empty % Flag used in babel-serbianc.tex
          \def\languagename{#1}%
          \bbl@id@assign
          \bbl@load@info{#1}}}%
        {}%
     \fi}%
  \expandafter\if\expandafter\@backslashchar
                  \expandafter\@car\string#2\@nil
    \ifx#2\@undefined\else
      \ldf@quit{#1}%
    \fi
  \else
    \expandafter\ifx\csname#2\endcsname\relax\else
      \ldf@quit{#1}%
    \fi
  \fi
  \bbl@ldfinit}
```

\ldf@quit This macro interrupts the processing of a language definition file. Remember `\endinput` is not executed immediately, but delayed to the end of the current line in the input file.

```
\def\ldf@quit#1{%
  \expandafter\main@language\expandafter{#1}%
  \catcode`\@=\atcatcode \let\atcatcode\relax
  \catcode`\==\eqcatcode \let\eqcatcode\relax
  \endinput}
```

\ldf@finish This macro takes one argument. It is the name of the language that was defined in the language definition file.

We load the local configuration file if one is present, we set the main language (taking into account that the argument might be a control sequence that needs to be expanded) and reset the category code of the @-sign.

```
\def\bbl@afterldf{%
  \bbl@afterlang
  \let\bbl@afterlang\relax
  \let\BabelModifiers\relax
  \let\bbl@screset\relax}%
\def\ldf@finish#1{%
  \loadlocalcfg{#1}%
  \bbl@afterldf
  \expandafter\main@language\expandafter{#1}%
  \catcode`\@=\atcatcode \let\atcatcode\relax
  \catcode`\==\eqcatcode \let\eqcatcode\relax}
```

After the preamble of the document the commands `\LdfInit`, `\ldf@quit` and `\ldf@finish` are no longer needed. Therefore they are turned into warning messages in LaTeX.

```
\@onlypreamble\LdfInit
\@onlypreamble\ldf@quit
\@onlypreamble\ldf@finish
```

\main@language

\bbl@main@language This command should be used in the various language definition files. It stores its argument in `\bbl@main@language`; to be used to switch to the correct language at the beginning of the document.

```
\def\main@language#1{%
  \def\bbl@main@language{#1}%
  \let\languagename\bbl@main@language
  \let\localename\bbl@main@language
  \let\mainlocalename\bbl@main@language
  \bbl@id@assign
  \ifcase\bbl@engine\or
    \ifx\setattribute\@undefined\else
      \setattribute\bbl@attr@locale\localeid
    \fi
  \fi
  \bbl@patterns{\languagename}}
```

We also have to make sure that some code gets executed at the beginning of the document, either when the aux file is read or, if it does not exist, when the `\AtBeginDocument` is executed. Languages do not set `\pagedir`, so we set here for the whole document to the main `\bodydir`.

The code written to the aux file attempts to avoid errors if babel is removed from the document.

```
\def\bbl@beforestart{%
  \def\@nolanerr##1{%
    \bbl@carg\chardef{l@##1}\z@
    \bbl@warning{Undefined language '##1' in aux.\\Reported}}%
  \bbl@usehooks{beforestart}{}%
  \global\let\bbl@beforestart\relax}
\AtBeginDocument{%
  {\@nameuse{bbl@beforestart}}%  Group!
  \if@filesw
    \providecommand\babel@aux[2]{}%
    \immediate\write\@mainaux{\unexpanded{%
      \providecommand\babel@aux[2]{\global\let\babel@toc\@gobbletwo}}}%
    \immediate\write\@mainaux{\string\@nameuse{bbl@beforestart}}%
  \fi
  \expandafter\selectlanguage\expandafter{\bbl@main@language}%
  \ifbbl@single  % must go after the line above.
    \renewcommand\selectlanguage[1]{}%
    \renewcommand\foreignlanguage[2]{#2}%
    \global\let\babel@aux\@gobbletwo  % Also as flag
  \fi}
```

A bit of optimization. Select in heads/feet the language only if necessary.

```
\def\select@language@x#1{%
  \ifcase\bbl@select@type
    \bbl@ifsamestring\languagename{#1}{}{\select@language{#1}}%
  \else
    \select@language{#1}%
  \fi}
```

3.13. Shorthands

The macro `\initiate@active@char` below takes all the necessary actions to make its argument a shorthand character. The real work is performed once for each character. But first we define a little tool.

```
\bbl@trace{Shorhands}
\def\bbl@withactive#1#2{%
  \begingroup
    \lccode`~=`#2\relax
    \lowercase{\endgroup#1~}}
```

\bbl@add@special The macro `\bbl@add@special` is used to add a new character (or single character control sequence) to the macro `\dospecials` (and `\@sanitize` if LaTeX is used). It is used only at one

place, namely when \initiate@active@char is called (which is ignored if the char has been made active before). Because \@sanitize can be undefined, we put the definition inside a conditional.

Items are added to the lists without checking its existence or the original catcode. It does not hurt, but should be fixed. It's already done with \nfss@catcodes, added in 3.10.

```
\def\bbl@add@special#1{% 1:a macro like \", \?, etc.
  \bbl@add\dospecials{\do#1}% test @sanitize = \relax, for back. compat.
  \bbl@ifunset{@sanitize}{}{\bbl@add\@sanitize{\@makeother#1}}%
  \ifx\nfss@catcodes\@undefined\else
    \begingroup
      \catcode`#1\active
      \nfss@catcodes
      \ifnum\catcode`#1=\active
        \endgroup
        \bbl@add\nfss@catcodes{\@makeother#1}%
      \else
        \endgroup
      \fi
  \fi}
```

\initiate@active@char A language definition file can call this macro to make a character active. This macro takes one argument, the character that is to be made active. When the character was already active this macro does nothing. Otherwise, this macro defines the control sequence \normal@char⟨*char*⟩ to expand to the character in its 'normal state' and it defines the active character to expand to \normal@char⟨*char*⟩ by default (⟨*char*⟩ being the character to be made active). Later its definition can be changed to expand to \active@char⟨*char*⟩ by calling \bbl@activate{⟨*char*⟩}.

For example, to make the double quote character active one could have \initiate@active@char{"} in a language definition file. This defines " as \active@prefix "\active@char" (where the first " is the character with its original catcode, when the shorthand is created, and \active@char" is a single token). In protected contexts, it expands to \protect " or \noexpand " (i.e., with the original "); otherwise \active@char" is executed. This macro in turn expands to \normal@char" in "safe" contexts (e.g., \label), but \user@active" in normal "unsafe" ones. The latter search a definition in the user, language and system levels, in this order, but if none is found, \normal@char" is used. However, a deactivated shorthand (with \bbl@deactivate is defined as \active@prefix "\normal@char".

The following macro is used to define shorthands in the three levels. It takes 4 arguments: the (string'ed) character, \⟨*level*⟩@group, ⟨*level*⟩@active and ⟨*next-level*⟩@active (except in system).

```
\def\bbl@active@def#1#2#3#4{%
  \@namedef{#3#1}{%
    \expandafter\ifx\csname#2@sh@#1@\endcsname\relax
      \bbl@afterelse\bbl@sh@select#2#1{#3@arg#1}{#4#1}%
    \else
      \bbl@afterfi\csname#2@sh@#1@\endcsname
    \fi}%
```

When there is also no current-level shorthand with an argument we will check whether there is a next-level defined shorthand for this active character.

```
  \long\@namedef{#3@arg#1}##1{%
    \expandafter\ifx\csname#2@sh@#1@\string##1@\endcsname\relax
      \bbl@afterelse\csname#4#1\endcsname##1%
    \else
      \bbl@afterfi\csname#2@sh@#1@\string##1@\endcsname
    \fi}}%
```

\initiate@active@char calls \@initiate@active@char with 3 arguments. All of them are the same character with different catcodes: active, other (\string'ed) and the original one. This trick simplifies the code a lot.

```
\def\initiate@active@char#1{%
  \bbl@ifunset{active@char\string#1}%
    {\bbl@withactive
      {\expandafter\@initiate@active@char\expandafter}#1\string#1#1}%
    {}}
```

The very first thing to do is saving the original catcode and the original definition, even if not active, which is possible (undefined characters require a special treatment to avoid making them `\relax` and preserving some degree of protection).

```
\def\@initiate@active@char#1#2#3{%
  \bbl@csarg\edef{oricat@#2}{\catcode`#2=\the\catcode`#2\relax}%
  \ifx#1\@undefined
    \bbl@csarg\def{oridef@#2}{\def#1{\active@prefix#1\@undefined}}%
  \else
    \bbl@csarg\let{oridef@@#2}#1%
    \bbl@csarg\edef{oridef@#2}{%
      \let\noexpand#1%
      \expandafter\noexpand\csname bbl@oridef@@#2\endcsname}%
  \fi
```

If the character is already active we provide the default expansion under this shorthand mechanism. Otherwise we write a message in the transcript file, and define `\normal@char`⟨*char*⟩ to expand to the character in its default state. If the character is mathematically active when babel is loaded (for example `'`) the normal expansion is somewhat different to avoid an infinite loop (but it does not prevent the loop if the mathcode is set to `"8000` *a posteriori*).

```
  \ifx#1#3\relax
    \expandafter\let\csname normal@char#2\endcsname#3%
  \else
    \bbl@info{Making #2 an active character}%
    \ifnum\mathcode`#2=\ifodd\bbl@engine"1000000 \else"8000 \fi
      \@namedef{normal@char#2}{%
        \textormath{#3}{\csname bbl@oridef@@#2\endcsname}}%
    \else
      \@namedef{normal@char#2}{#3}%
    \fi
```

To prevent problems with the loading of other packages after babel we reset the catcode of the character to the original one at the end of the package and of each language file (except with KeepShorthandsActive). It is re-activate again at `\begin{document}`. We also need to make sure that the shorthands are active during the processing of the aux file. Otherwise some citations may give unexpected results in the printout when a shorthand was used in the optional argument of `\bibitem` for example. Then we make it active (not strictly necessary, but done for backward compatibility).

```
    \bbl@restoreactive{#2}%
    \AtBeginDocument{%
      \catcode`#2\active
      \if@filesw
        \immediate\write\@mainaux{\catcode`\string#2\active}%
      \fi}%
    \expandafter\bbl@add@special\csname#2\endcsname
    \catcode`#2\active
  \fi
```

Now we have set `\normal@char`⟨*char*⟩, we must define `\active@char`⟨*char*⟩, to be executed when the character is activated. We define the first level expansion of `\active@char`⟨*char*⟩ to check the status of the `@safe@actives` flag. If it is set to true we expand to the 'normal' version of this character, otherwise we call `\user@active`⟨*char*⟩ to start the search of a definition in the user, language and system levels (or eventually `normal@char`⟨*char*⟩).

```
  \let\bbl@tempa\@firstoftwo
  \if\string^#2%
    \def\bbl@tempa{\noexpand\textormath}%
  \else
    \ifx\bbl@mathnormal\@undefined\else
      \let\bbl@tempa\bbl@mathnormal
    \fi
  \fi
  \expandafter\edef\csname active@char#2\endcsname{%
    \bbl@tempa
      {\noexpand\if@safe@actives
         \noexpand\expandafter
```

```
        \expandafter\noexpand\csname normal@char#2\endcsname
      \noexpand\else
        \noexpand\expandafter
        \expandafter\noexpand\csname bbl@doactive#2\endcsname
      \noexpand\fi}%
    {\expandafter\noexpand\csname normal@char#2\endcsname}}%
\bbl@csarg\edef{doactive#2}{%
  \expandafter\noexpand\csname user@active#2\endcsname}%
```

We now define the default values which the shorthand is set to when activated or deactivated. It is set to the deactivated form (globally), so that the character expands to

\active@prefix ⟨*char*⟩ \normal@char⟨*char*⟩

(where \active@char⟨*char*⟩ is *one* control sequence!).

```
\bbl@csarg\edef{active@#2}{%
  \noexpand\active@prefix\noexpand#1%
  \expandafter\noexpand\csname active@char#2\endcsname}%
\bbl@csarg\edef{normal@#2}{%
  \noexpand\active@prefix\noexpand#1%
  \expandafter\noexpand\csname normal@char#2\endcsname}%
\bbl@ncarg\let#1{bbl@normal@#2}%
```

The next level of the code checks whether a user has defined a shorthand for himself with this character. First we check for a single character shorthand. If that doesn't exist we check for a shorthand with an argument.

```
\bbl@active@def#2\user@group{user@active}{language@active}%
\bbl@active@def#2\language@group{language@active}{system@active}%
\bbl@active@def#2\system@group{system@active}{normal@char}%
```

In order to do the right thing when a shorthand with an argument is used by itself at the end of the line we provide a definition for the case of an empty argument. For that case we let the shorthand character expand to its non-active self. Also, When a shorthand combination such as `''` ends up in a heading TEX would see `\protect'\protect'`. To prevent this from happening a couple of shorthand needs to be defined at user level.

```
\expandafter\edef\csname\user@group @sh@#2@@\endcsname
  {\expandafter\noexpand\csname normal@char#2\endcsname}%
\expandafter\edef\csname\user@group @sh@#2@\string\protect@\endcsname
  {\expandafter\noexpand\csname user@active#2\endcsname}%
```

Finally, a couple of special cases are taken care of. (1) If we are making the right quote (`'`) active we need to change \pr@m@s as well. Also, make sure that a single `'` in math mode 'does the right thing'. (2) If we are using the caret (`^`) as a shorthand character special care should be taken to make sure math still works. Therefore an extra level of expansion is introduced with a check for math mode on the upper level.

```
\if\string'#2%
  \let\prim@s\bbl@prim@s
  \let\active@math@prime#1%
\fi
\bbl@usehooks{initiateactive}{{#1}{#2}{#3}}}
```

The following package options control the behavior of shorthands in math mode.

```
⟨⟨*More package options⟩⟩ ▸
\DeclareOption{math=active}{}
\DeclareOption{math=normal}{\def\bbl@mathnormal{\noexpand\textormath}}
⟨⟨/More package options⟩⟩
```

Initiating a shorthand makes active the char. That is not strictly necessary but it is still done for backward compatibility. So we need to restore the original catcode at the end of package *and* and the end of the `ldf`.

```
\@ifpackagewith{babel}{KeepShorthandsActive}%
  {\let\bbl@restoreactive\@gobble}%
  {\def\bbl@restoreactive#1{%
     \bbl@exp{%
       \\\AfterBabelLanguage\\\CurrentOption
```

```
        {\catcode`#1=\the\catcode`#1\relax}%
      \\\AtEndOfPackage
        {\catcode`#1=\the\catcode`#1\relax}}}%
  \AtEndOfPackage{\let\bbl@restoreactive\@gobble}}
```

\bbl@sh@select This command helps the shorthand supporting macros to select how to proceed. Note that this macro needs to be expandable as do all the shorthand macros in order for them to work in expansion-only environments such as the argument of `\hyphenation`.

This macro expects the name of a group of shorthands in its first argument and a shorthand character in its second argument. It will expand to either `\bbl@firstcs` or `\bbl@scndcs`. Hence two more arguments need to follow it.

```
\def\bbl@sh@select#1#2{%
  \expandafter\ifx\csname#1@sh@#2@sel\endcsname\relax
    \bbl@afterelse\bbl@scndcs
  \else
    \bbl@afterfi\csname#1@sh@#2@sel\endcsname
  \fi}
```

\active@prefix Used in the expansion of active characters has a function similar to `\OT1-cmd` in that it `\protect`s the active character whenever `\protect` is *not* `\@typeset@protect`. The `\@gobble` is needed to remove a token such as `\activechar:` (when the double colon was the active character to be dealt with). There are two definitions, depending of `\ifincsname` is available. If there is, the expansion will be more robust.

```
\begingroup
\bbl@ifunset{ifincsname}
  {\gdef\active@prefix#1{%
     \ifx\protect\@typeset@protect
     \else
       \ifx\protect\@unexpandable@protect
         \noexpand#1%
       \else
         \protect#1%
       \fi
       \expandafter\@gobble
     \fi}}
  {\gdef\active@prefix#1{%
     \ifincsname
       \string#1%
       \expandafter\@gobble
     \else
       \ifx\protect\@typeset@protect
       \else
         \ifx\protect\@unexpandable@protect
           \noexpand#1%
         \else
           \protect#1%
         \fi
         \expandafter\expandafter\expandafter\@gobble
       \fi
     \fi}}
\endgroup
```

if@safe@actives In some circumstances it is necessary to be able to reset the shorthand to its 'normal' value (usually the character with catcode 'other') on the fly. For this purpose the switch `@safe@actives` is available. The setting of this switch should be checked in the first level expansion of `\active@char`⟨*char*⟩. When this expansion mode is active (with `\@safe@activestrue`), something like $"_{13}"_{13}$ becomes $"_{12}"_{12}$ in an `\edef` (in other words, shorthands are `\string`'ed). This contrasts with `\protected@edef`, where catcodes are always left unchanged. Once converted, they can be used safely even after this expansion mode is deactivated (with `\@safe@activefalse`).

```
\newif\if@safe@actives
\@safe@activesfalse
```

\bbl@restore@actives When the output routine kicks in while the active characters were made "safe" this must be undone in the headers to prevent unexpected typeset results. For this situation we define a command to make them "unsafe" again.

```
\def\bbl@restore@actives{\if@safe@actives\@safe@activesfalse\fi}
```

\bbl@activate
\bbl@deactivate Both macros take one argument, like `\initiate@active@char`. The macro is used to change the definition of an active character to expand to `\active@char`⟨*char*⟩ in the case of `\bbl@activate`, or `\normal@char`⟨*char*⟩ in the case of `\bbl@deactivate`.

```
\chardef\bbl@activated\z@
\def\bbl@activate#1{%
  \chardef\bbl@activated\@ne
  \bbl@withactive{\expandafter\let\expandafter}#1%
    \csname bbl@active@\string#1\endcsname}
\def\bbl@deactivate#1{%
  \chardef\bbl@activated\tw@
  \bbl@withactive{\expandafter\let\expandafter}#1%
    \csname bbl@normal@\string#1\endcsname}
```

\bbl@firstcs
\bbl@scndcs These macros are used only as a trick when declaring shorthands.

```
\def\bbl@firstcs#1#2{\csname#1\endcsname}
\def\bbl@scndcs#1#2{\csname#2\endcsname}
```

\declare@shorthand Used to declare a shorthand on a certain level. It takes three arguments:

1. a name for the collection of shorthands, i.e., 'system', or 'dutch';
2. the character (sequence) that makes up the shorthand, i.e., ~ or "a;
3. the code to be executed when the shorthand is encountered.

The auxiliary macro `\babel@texpdf` improves the interoperativity with hyperref and takes 4 arguments: (1) The TEX code in text mode, (2) the string for hyperref, (3) the TEX code in math mode, and (4), which is currently ignored, but it's meant for a string in math mode, like a minus sign instead of an hyphen (currently hyperref doesn't discriminate the mode). This macro may be used in `ldf` files.

```
\def\babel@texpdf#1#2#3#4{%
  \ifx\texorpdfstring\@undefined
    \textormath{#1}{#3}%
  \else
    \texorpdfstring{\textormath{#1}{#3}}{#2}%
    % \texorpdfstring{\textormath{#1}{#3}}{\textormath{#2}{#4}}%
  \fi}
%
\def\declare@shorthand#1#2{\@decl@short{#1}#2\@nil}
\def\@decl@short#1#2#3\@nil#4{%
  \def\bbl@tempa{#3}%
  \ifx\bbl@tempa\@empty
    \expandafter\let\csname #1@sh@\string#2@sel\endcsname\bbl@scndcs
    \bbl@ifunset{#1@sh@\string#2@}{}%
      {\def\bbl@tempa{#4}%
       \expandafter\ifx\csname#1@sh@\string#2@\endcsname\bbl@tempa
       \else
         \bbl@info
           {Redefining #1 shorthand \string#2\\%
            in language \CurrentOption}%
       \fi}%
    \@namedef{#1@sh@\string#2@}{#4}%
  \else
    \expandafter\let\csname #1@sh@\string#2@sel\endcsname\bbl@firstcs
    \bbl@ifunset{#1@sh@\string#2@\string#3@}{}%
      {\def\bbl@tempa{#4}%
       \expandafter\ifx\csname#1@sh@\string#2@\string#3@\endcsname\bbl@tempa
```

```
      \else
        \bbl@info
          {Redefining #1 shorthand \string#2\string#3\\%
           in language \CurrentOption}%
      \fi}%
    \@namedef{#1@sh@\string#2@\string#3@}{#4}%
  \fi}
```

\textormath Some of the shorthands that will be declared by the language definition files have to be usable in both text and mathmode. To achieve this the helper macro `\textormath` is provided.

```
\def\textormath{%
  \ifmmode
    \expandafter\@secondoftwo
  \else
    \expandafter\@firstoftwo
  \fi}
```

\user@group
\language@group
\system@group The current concept of 'shorthands' supports three levels or groups of shorthands. For each level the name of the level or group is stored in a macro. The default is to have a user group; use language group 'english' and have a system group called 'system'.

```
\def\user@group{user}
\def\language@group{english}
\def\system@group{system}
```

\useshorthands This is the user level macro. It initializes and activates the character for use as a shorthand character (i.e., it's active in the preamble). Languages can deactivate shorthands, so a starred version is also provided which activates them always after the language has been switched.

```
\def\useshorthands{%
  \@ifstar\bbl@usesh@s{\bbl@usesh@x{}}}
\def\bbl@usesh@s#1{%
  \bbl@usesh@x
    {\AddBabelHook{babel-sh-\string#1}{afterextras}{\bbl@activate{#1}}}%
    {#1}}
\def\bbl@usesh@x#1#2{%
  \bbl@ifshorthand{#2}%
    {\def\user@group{user}%
     \initiate@active@char{#2}%
     #1%
     \bbl@activate{#2}}%
    {\bbl@error{shorthand-is-off}{}{#2}{}}}
```

\defineshorthand Currently we only support two groups of user level shorthands, named internally `user` and `user@`⟨*language*⟩ (language-dependent user shorthands). By default, only the first one is taken into account, but if the former is also used (in the optional argument of `\defineshorthand`) a new level is inserted for it (`user@generic`, done by `\bbl@set@user@generic`); we make also sure `{}` and `\protect` are taken into account in this new top level.

```
\def\user@language@group{user@\language@group}
\def\bbl@set@user@generic#1#2{%
  \bbl@ifunset{user@generic@active#1}%
    {\bbl@active@def#1\user@language@group{user@active}{user@generic@active}%
     \bbl@active@def#1\user@group{user@generic@active}{language@active}%
     \expandafter\edef\csname#2@sh@#1@@\endcsname{%
       \expandafter\noexpand\csname normal@char#1\endcsname}%
     \expandafter\edef\csname#2@sh@#1@\string\protect@\endcsname{%
       \expandafter\noexpand\csname user@active#1\endcsname}}%
  \@empty}
\newcommand\defineshorthand[3][user]{%
  \edef\bbl@tempa{\zap@space#1 \@empty}%
```

```
\bbl@for\bbl@tempb\bbl@tempa{%
  \if*\expandafter\@car\bbl@tempb\@nil
    \edef\bbl@tempb{user@\expandafter\@gobble\bbl@tempb}%
    \@expandtwoargs
      \bbl@set@user@generic{\expandafter\string\@car#2\@nil}\bbl@tempb
  \fi
  \declare@shorthand{\bbl@tempb}{#2}{#3}}}
```

\languageshorthands A user level command to change the language from which shorthands are used. Unfortunately, babel currently does not keep track of defined groups, and therefore there is no way to catch a possible change in casing to fix it in the same way languages names are fixed.

```
\def\languageshorthands#1{%
  \bbl@ifsamestring{none}{#1}{}{%
    \bbl@once{short-\localename-#1}{%
      \bbl@info{'\localename' activates '#1' shorthands.\\Reported}}}%
  \def\language@group{#1}}
```

\aliasshorthand *Deprecated*. First the new shorthand needs to be initialized. Then, we define the new shorthand in terms of the original one, but note with `\aliasshorthands{"}{/}` is `\active@prefix /\active@char/`, so we still need to let the latter to `\active@char"`.

```
\def\aliasshorthand#1#2{%
  \bbl@ifshorthand{#2}%
    {\expandafter\ifx\csname active@char\string#2\endcsname\relax
       \ifx\document\@notprerr
         \@notshorthand{#2}%
       \else
         \initiate@active@char{#2}%
         \bbl@ccarg\let{active@char\string#2}{active@char\string#1}%
         \bbl@ccarg\let{normal@char\string#2}{normal@char\string#1}%
         \bbl@activate{#2}%
       \fi
     \fi}%
    {\bbl@error{shorthand-is-off}{}{#2}{}}}
```

\@notshorthand

```
\def\@notshorthand#1{\bbl@error{not-a-shorthand}{#1}{}{}}
```

\shorthandon
\shorthandoff The first level definition of these macros just passes the argument on to `\bbl@switch@sh`, adding `\@nil` at the end to denote the end of the list of characters.

```
\newcommand*\shorthandon[1]{\bbl@switch@sh\@ne#1\@nnil}
\DeclareRobustCommand*\shorthandoff{%
  \@ifstar{\bbl@shorthandoff\tw@}{\bbl@shorthandoff\z@}}
\def\bbl@shorthandoff#1#2{\bbl@switch@sh#1#2\@nnil}
```

\bbl@switch@sh The macro `\bbl@switch@sh` takes the list of characters apart one by one and subsequently switches the category code of the shorthand character according to the first argument of `\bbl@switch@sh`.

But before any of this switching takes place we make sure that the character we are dealing with is known as a shorthand character. If it is, a macro such as `\active@char"` should exist.

Switching off and on is easy – we just set the category code to 'other' (12) and `\active`. With the starred version, the original catcode and the original definition, saved in `@initiate@active@char`, are restored.

```
\def\bbl@switch@sh#1#2{%
  \ifx#2\@nnil\else
    \bbl@ifunset{bbl@active@\string#2}%
      {\bbl@error{not-a-shorthand-b}{}{#2}{}}%
      {\ifcase#1%   off, on, off*
         \catcode`#212\relax
       \or
```

```
        \catcode`#2\active
        \bbl@ifunset{bbl@shdef@\string#2}%
          {}%
          {\bbl@withactive{\expandafter\let\expandafter}#2%
             \csname bbl@shdef@\string#2\endcsname
           \bbl@csarg\let{shdef@\string#2}\relax}%
        \ifcase\bbl@activated\or
          \bbl@activate{#2}%
        \else
          \bbl@deactivate{#2}%
        \fi
      \or
        \bbl@ifunset{bbl@shdef@\string#2}%
          {\bbl@withactive{\bbl@csarg\let{shdef@\string#2}}#2}%
          {}%
        \csname bbl@oricat@\string#2\endcsname
        \csname bbl@oridef@\string#2\endcsname
      \fi}%
    \bbl@afterfi\bbl@switch@sh#1%
  \fi}
```

Note the value is that at the expansion time; e.g., in the preamble shorthands are usually deactivated.

```
\def\babelshorthand{\active@prefix\babelshorthand\bbl@putsh}
\def\bbl@putsh#1{%
  \bbl@ifunset{bbl@active@\string#1}%
     {\bbl@putsh@i#1\@empty\@nnil}%
     {\csname bbl@active@\string#1\endcsname}}
\def\bbl@putsh@i#1#2\@nnil{%
  \csname\language@group @sh@\string#1@%
    \ifx\@empty#2\else\string#2@\fi\endcsname}
%
\ifx\bbl@opt@shorthands\@nnil\else
  \let\bbl@s@initiate@active@char\initiate@active@char
  \def\initiate@active@char#1{%
    \bbl@ifshorthand{#1}{\bbl@s@initiate@active@char{#1}}{}}
  \let\bbl@s@switch@sh\bbl@switch@sh
  \def\bbl@switch@sh#1#2{%
    \ifx#2\@nnil\else
      \bbl@afterfi
      \bbl@ifshorthand{#2}{\bbl@s@switch@sh#1{#2}}{\bbl@switch@sh#1}%
    \fi}
  \let\bbl@s@activate\bbl@activate
  \def\bbl@activate#1{%
    \bbl@ifshorthand{#1}{\bbl@s@activate{#1}}{}}
  \let\bbl@s@deactivate\bbl@deactivate
  \def\bbl@deactivate#1{%
    \bbl@ifshorthand{#1}{\bbl@s@deactivate{#1}}{}}
\fi
```

You may want to test if a character is a shorthand. Note it does not test whether the shorthand is on or off.

```
\newcommand\ifbabelshorthand[3]{\bbl@ifunset{bbl@active@\string#1}{#3}{#2}}
```

\bbl@prim@s
\bbl@pr@m@s One of the internal macros that are involved in substituting `\prime` for each right quote in mathmode is `\prim@s`. This checks if the next character is a right quote. When the right quote is active, the definition of this macro needs to be adapted to look also for an active right quote; the hat could be active, too.

```
\def\bbl@prim@s{%
  \prime\futurelet\@let@token\bbl@pr@m@s}
\def\bbl@if@primes#1#2{%
  \ifx#1\@let@token
```

```
    \expandafter\@firstoftwo
  \else\ifx#2\@let@token
    \bbl@afterelse\expandafter\@firstoftwo
  \else
    \bbl@afterfi\expandafter\@secondoftwo
  \fi\fi}
\begingroup
  \catcode`\^=7  \catcode`\*=\active  \lccode`\*=`\^
  \catcode`\'=12 \catcode`\"=\active  \lccode`\"=`\'
  \lowercase{%
    \gdef\bbl@pr@m@s{%
      \bbl@if@primes"'%
        \pr@@@s
        {\bbl@if@primes*^\pr@@@t\egroup}}}
\endgroup
```

Usually the ~ is active and expands to `\penalty\@M\␣`. When it is written to the aux file it is written expanded. To prevent that and to be able to use the character ~ as a start character for a shorthand, it is redefined here as a one character shorthand on system level. The system declaration is in most cases redundant (when ~ is still a non-break space), and in some cases is inconvenient (if ~ has been redefined); however, for backward compatibility it is maintained (some existing documents may rely on the babel value).

```
\initiate@active@char{~}
\declare@shorthand{system}{~}{\leavevmode\nobreak\ }
\bbl@activate{~}
```

\OT1dqpos
\T1dqpos The position of the double quote character is different for the OT1 and T1 encodings. It will later be selected using the `\f@encoding` macro. Therefore we define two macros here to store the position of the character in these encodings.

```
\expandafter\def\csname OT1dqpos\endcsname{127}
\expandafter\def\csname T1dqpos\endcsname{4}
```

When the macro `\f@encoding` is undefined (as it is in plain TEX) we define it here to expand to `OT1`

```
\ifx\f@encoding\@undefined
  \def\f@encoding{OT1}
\fi
```

3.14. Language attributes

Language attributes provide a means to give the user control over which features of the language definition files he wants to enable.

\languageattribute The macro `\languageattribute` checks whether its arguments are valid and then activates the selected language attribute. First check whether the language is known, and then process each attribute in the list.

To make sure each attribute is selected only once, we store the already selected attributes in `\bbl@known@attribs`. When that control sequence is not yet defined this attribute is certainly not selected before.

When we end up here the attribute is not selected before. So, we add it to the list of selected attributes and execute the associated TEX code.

```
\bbl@trace{Language attributes}
\newcommand\languageattribute[2]{%
  \def\bbl@tempc{#1}%
  \bbl@fixname\bbl@tempc
  \bbl@iflanguage\bbl@tempc{%
    \bbl@vforeach{#2}{%
      \ifx\bbl@known@attribs\@undefined
        \in@false
      \else
        \bbl@xin@{,\bbl@tempc-##1,}{,\bbl@known@attribs,}%
      \fi
```

```
      \ifin@
        \bbl@warning{%
          You have more than once selected the attribute '##1'\\%
          for language #1. Reported}%
      \else
        \bbl@info{Activated '##1' attribute for\\%
          '\bbl@tempc'. Reported}%
        \bbl@exp{%
          \\\bbl@add@list\\\bbl@known@attribs{\bbl@tempc-##1}}%
        \edef\bbl@tempa{\bbl@tempc-##1}%
        \expandafter\bbl@ifknown@ttrib\expandafter{\bbl@tempa}\bbl@attributes
          {\csname\bbl@tempc @attr@##1\endcsname}%
          {\bbl@error{unknown-attribute}{\bbl@tempc}{##1}{}}%
    \fi}}
\@onlypreamble\languageattribute
```

\bbl@declare@ttribute This command adds the new language/attribute combination to the list of known attributes.

Then it defines a control sequence to be executed when the attribute is used in a document. The result of this should be that the macro `\extras...` for the current language is extended, otherwise the attribute will not work as its code is removed from memory at `\begin{document}`.

```
\def\bbl@declare@ttribute#1#2#3{%
  \bbl@xin@{,#2,}{,\BabelModifiers,}%
  \ifin@
    \AfterBabelLanguage{#1}{\languageattribute{#1}{#2}}%
  \fi
  \bbl@add@list\bbl@attributes{#1-#2}%
  \expandafter\def\csname#1@attr@#2\endcsname{#3}}
```

\bbl@ifattributeset This internal macro has 4 arguments. It can be used to interpret TEX code based on whether a certain attribute was set. This command should appear inside the argument to `\AtBeginDocument` because the attributes are set in the document preamble, *after* babel is loaded.

The first argument is the language, the second argument the attribute being checked, and the third and fourth arguments are the true and false clauses.

```
\def\bbl@ifattributeset#1#2#3#4{%
  \ifx\bbl@known@attribs\@undefined
    \in@false
  \else
    \bbl@xin@{,#1-#2,}{,\bbl@known@attribs,}%
  \fi
  \ifin@
    \bbl@afterelse#3%
  \else
    \bbl@afterfi#4%
  \fi}
```

\bbl@ifknown@ttrib An internal macro to check whether a given language/attribute is known. The macro takes 4 arguments, the language/attribute, the attribute list, the TEX-code to be executed when the attribute is known and the TEX-code to be executed otherwise.

We first assume the attribute is unknown. Then we loop over the list of known attributes, trying to find a match.

```
\def\bbl@ifknown@ttrib#1#2{%
  \let\bbl@tempa\@secondoftwo
  \bbl@loopx\bbl@tempb{#2}{%
    \expandafter\in@\expandafter{\expandafter,\bbl@tempb,}{,#1,}%
    \ifin@
      \let\bbl@tempa\@firstoftwo
    \else
    \fi}%
  \bbl@tempa}
```

\bbl@clear@ttribs This macro removes all the attribute code from LaTeX's memory at \begin{document} time (if any is present).

```
\def\bbl@clear@ttribs{%
  \ifx\bbl@attributes\@undefined\else
    \bbl@loopx\bbl@tempa{\bbl@attributes}{%
      \expandafter\bbl@clear@ttrib\bbl@tempa.}%
    \let\bbl@attributes\@undefined
  \fi}
\def\bbl@clear@ttrib#1-#2.{%
  \expandafter\let\csname#1@attr@#2\endcsname\@undefined}
\AtBeginDocument{\bbl@clear@ttribs}
```

3.15. Support for saving and redefining macros

To save the meaning of control sequences using \babel@save, we use temporary control sequences. To save hash table entries for these control sequences, we don't use the name of the control sequence to be saved to construct the temporary name. Instead we simply use the value of a counter, which is reset to zero each time we begin to save new values. This works well because we release the saved meanings before we begin to save a new set of control sequence meanings (see \selectlanguage and \originalTeX). Note undefined macros are not undefined any more when saved – they are \relax'ed.

\babel@savecnt
\babel@beginsave The initialization of a new save cycle: reset the counter to zero.

```
\bbl@trace{Macros for saving definitions}
\def\babel@beginsave{\babel@savecnt\z@}
```

Before it's forgotten, allocate the counter and initialize all.

```
\newcount\babel@savecnt
\babel@beginsave
```

\babel@save
\babel@savevariable The macro \babel@save⟨*csname*⟩ saves the current meaning of the control sequence ⟨*csname*⟩ to \originalTeX (which has to be expandable, i.e., you shouldn't let it to \relax). To do this, we let the current meaning to a temporary control sequence, the restore commands are appended to \originalTeX and the counter is incremented. The macro \babel@savevariable⟨*variable*⟩ saves the value of the variable. ⟨*variable*⟩ can be anything allowed after the \the primitive. To avoid messing saved definitions up, they are saved only the very first time.

```
\def\babel@save#1{%
  \def\bbl@tempa{{,#1,}}% Clumsy, for Plain
  \expandafter\bbl@add\expandafter\bbl@tempa\expandafter{%
    \expandafter{\expandafter,\bbl@savedextras,}}%
  \expandafter\in@\bbl@tempa
  \ifin@\else
    \bbl@add\bbl@savedextras{,#1,}%
    \bbl@carg\let{babel@\number\babel@savecnt}#1\relax
    \toks@\expandafter{\originalTeX\let#1=}%
    \bbl@exp{%
      \def\\\originalTeX{\the\toks@\<babel@\number\babel@savecnt>\relax}}%
    \advance\babel@savecnt\@ne
  \fi}
\def\babel@savevariable#1{%
  \toks@\expandafter{\originalTeX #1=}%
  \bbl@exp{\def\\\originalTeX{\the\toks@\the#1\relax}}}
```

\bbl@redefine To redefine a command, we save the old meaning of the macro. Then we redefine it to call the original macro with the 'sanitized' argument. The reason why we do it this way is that we don't want to redefine the LaTeX macros completely in case their definitions change (they have changed in the past). A macro named \macro will be saved new control sequences named \org@macro.

```
\def\bbl@redefine#1{%
  \edef\bbl@tempa{\bbl@stripslash#1}%
  \expandafter\let\csname org@\bbl@tempa\endcsname#1%
  \expandafter\def\csname\bbl@tempa\endcsname}
\@onlypreamble\bbl@redefine
```

\bbl@redefine@long This version of `\babel@redefine` can be used to redefine `\long` commands such as `\ifthenelse`.

```
\def\bbl@redefine@long#1{%
  \edef\bbl@tempa{\bbl@stripslash#1}%
  \expandafter\let\csname org@\bbl@tempa\endcsname#1%
  \long\expandafter\def\csname\bbl@tempa\endcsname}
\@onlypreamble\bbl@redefine@long
```

\bbl@redefinerobust For commands that are redefined, but which *might* be robust we need a slightly more intelligent macro. A robust command `foo` is defined to expand to `\protect\foo␣`. So it is necessary to check whether `\foo␣` exists. The result is that the command that is being redefined is always robust afterwards. Therefore all we need to do now is define `\foo␣`.

```
\def\bbl@redefinerobust#1{%
  \edef\bbl@tempa{\bbl@stripslash#1}%
  \bbl@ifunset{\bbl@tempa\space}%
    {\expandafter\let\csname org@\bbl@tempa\endcsname#1%
     \bbl@exp{\def\\#1{\\\protect\<\bbl@tempa\space>}}}%
    {\bbl@exp{\let\<org@\bbl@tempa>\<\bbl@tempa\space>}}%
    \@namedef{\bbl@tempa\space}}
\@onlypreamble\bbl@redefinerobust
```

3.16. French spacing

\bbl@frenchspacing
\bbl@nonfrenchspacing Some languages need to have `\frenchspacing` in effect. Others don't want that. The command `\bbl@frenchspacing` switches it on when it isn't already in effect and `\bbl@nonfrenchspacing` switches it off if necessary.

```
\def\bbl@frenchspacing{%
  \ifnum\the\sfcode`\.=\@m
    \let\bbl@nonfrenchspacing\relax
  \else
    \frenchspacing
    \let\bbl@nonfrenchspacing\nonfrenchspacing
  \fi}
\let\bbl@nonfrenchspacing\nonfrenchspacing
```

A more refined way to switch the catcodes is done with `ini` files. Here an auxiliary macro is defined, but the main part is in `\babelprovide`. This new method should be ideally the default one.

```
\let\bbl@elt\relax
\edef\bbl@fs@chars{%
  \bbl@elt{\string.}\@m{3000}\bbl@elt{\string?}\@m{3000}%
  \bbl@elt{\string!}\@m{3000}\bbl@elt{\string:}\@m{2000}%
  \bbl@elt{\string;}\@m{1500}\bbl@elt{\string,}\@m{1250}}
\def\bbl@pre@fs{%
  \def\bbl@elt##1##2##3{\sfcode`##1=\the\sfcode`##1\relax}%
  \edef\bbl@save@sfcodes{\bbl@fs@chars}}%
\def\bbl@post@fs{%
  \bbl@save@sfcodes
  \edef\bbl@tempa{\bbl@cl{frspc}}%
  \edef\bbl@tempa{\expandafter\@car\bbl@tempa\@nil}%
  \if u\bbl@tempa          % do nothing
  \else\if n\bbl@tempa     % non french
    \def\bbl@elt##1##2##3{%
      \ifnum\sfcode`##1=##2\relax
        \babel@savevariable{\sfcode`##1}%
```

```
      \sfcode`##1=##3\relax
    \fi}%
  \bbl@fs@chars
\else\if y\bbl@tempa     % french
  \def\bbl@elt##1##2##3{%
    \ifnum\sfcode`##1=##3\relax
      \babel@savevariable{\sfcode`##1}%
      \sfcode`##1=##2\relax
    \fi}%
  \bbl@fs@chars
\fi\fi\fi}
```

3.17. Hyphens

\babelhyphenation This macro saves hyphenation exceptions. Two macros are used to store them: `\bbl@hyphenation@` for the global ones and `\bbl@hyphenation@`⟨*language*⟩ for language ones. See `\bbl@patterns` above for further details. We make sure there is a space between words when multiple commands are used.

```
\bbl@trace{Hyphens}
\@onlypreamble\babelhyphenation
\AtEndOfPackage{%
  \newcommand\babelhyphenation[2][\@empty]{%
    \ifx\bbl@hyphenation@\relax
      \let\bbl@hyphenation@\@empty
    \fi
    \ifx\bbl@hyphlist\@empty\else
      \bbl@warning{%
        You must not intermingle \string\selectlanguage\space and\\%
        \string\babelhyphenation\space or some exceptions will not\\%
        be taken into account. Reported}%
    \fi
    \ifx\@empty#1%
      \protected@edef\bbl@hyphenation@{\bbl@hyphenation@\space#2}%
    \else
      \bbl@vforeach{#1}{%
        \def\bbl@tempa{##1}%
        \bbl@fixname\bbl@tempa
        \bbl@iflanguage\bbl@tempa{%
          \bbl@csarg\protected@edef{hyphenation@\bbl@tempa}{%
            \bbl@ifunset{bbl@hyphenation@\bbl@tempa}%
              {}%
              {\csname bbl@hyphenation@\bbl@tempa\endcsname\space}%
            #2}}}%
    \fi}}
```

\babelhyphenmins Only LaTeX (basically because it's defined with a LaTeX tool).

```
\ifx\NewDocumentCommand\@undefined\else
  \NewDocumentCommand\babelhyphenmins{sommo}{%
    \IfNoValueTF{#2}%
      {\protected@edef\bbl@hyphenmins@{\set@hyphenmins{#3}{#4}}%
       \IfValueT{#5}{%
         \protected@edef\bbl@hyphenatmin@{\hyphenationmin=#5\relax}}%
       \IfBooleanT{#1}{%
         \lefthyphenmin=#3\relax
         \righthyphenmin=#4\relax
         \IfValueT{#5}{\hyphenationmin=#5\relax}}}%
      {\edef\bbl@tempb{\zap@space#2 \@empty}%
       \bbl@for\bbl@tempa\bbl@tempb{%
         \@namedef{bbl@hyphenmins@\bbl@tempa}{\set@hyphenmins{#3}{#4}}%
         \IfValueT{#5}{%
           \@namedef{bbl@hyphenatmin@\bbl@tempa}{\hyphenationmin=#5\relax}}}%
       \IfBooleanT{#1}{\bbl@error{hyphenmins-args}{}{}{}}}}
```

```
\fi
```

\bbl@allowhyphens This macro makes hyphenation possible. Basically its definition is nothing more than `\nobreak \hskip 0pt plus 0pt`. TEX begins and ends a word for hyphenation at a glue node. The penalty prevents a linebreak at this glue node.

```
\def\bbl@allowhyphens{\ifvmode\else\nobreak\hskip\z@skip\fi}
\def\bbl@t@one{T1}
\def\allowhyphens{\ifx\cf@encoding\bbl@t@one\else\bbl@allowhyphens\fi}
```

\babelhyphen Macros to insert common hyphens. Note the space before `@` in `\babelhyphen`. Instead of protecting it with `\DeclareRobustCommand`, which could insert a `\relax`, we use the same procedure as shorthands, with `\active@prefix`.

```
\newcommand\babelnullhyphen{\char\hyphenchar\font}
\def\babelhyphen{\active@prefix\babelhyphen\bbl@hyphen}
\def\bbl@hyphen{%
  \@ifstar{\bbl@hyphen@i @}{\bbl@hyphen@i\@empty}}
\def\bbl@hyphen@i#1#2{%
  \lowercase{\bbl@ifunset{bbl@hy@#1#2\@empty}}%
    {\csname bbl@#1usehyphen\endcsname{\discretionary{#2}{}{#2}}}%
    {\lowercase{\csname bbl@hy@#1#2\@empty\endcsname}}}
```

The following two commands are used to wrap the "hyphen" and set the behavior of the rest of the word – the version with a single `@` is used when further hyphenation is allowed, while that with `@@` if no more hyphens are allowed. In both cases, if the hyphen is preceded by a positive space, breaking after the hyphen is disallowed.

There should not be a discretionary after a hyphen at the beginning of a word, so it is prevented if preceded by a skip. Unfortunately, this does handle cases like "(-suffix)". `\nobreak` is always preceded by `\leavevmode`, in case the shorthand starts a paragraph.

```
\def\bbl@usehyphen#1{%
  \leavevmode
  \ifdim\lastskip>\z@\mbox{#1}\else\nobreak#1\fi
  \nobreak\hskip\z@skip}
\def\bbl@@usehyphen#1{%
  \leavevmode\ifdim\lastskip>\z@\mbox{#1}\else#1\fi}
```

The following macro inserts the hyphen char.

```
\def\bbl@hyphenchar{%
  \ifnum\hyphenchar\font=\m@ne
    \babelnullhyphen
  \else
    \char\hyphenchar\font
  \fi}
```

Finally, we define the hyphen "types". Their names will not change, so you may use them in `ldf`'s. After a space, the `\mbox` in `\bbl@hy@nobreak` is redundant.

```
\def\bbl@hy@soft{\bbl@usehyphen{\discretionary{\bbl@hyphenchar}{}{}}}
\def\bbl@hy@@soft{\bbl@@usehyphen{\discretionary{\bbl@hyphenchar}{}{}}}
\def\bbl@hy@hard{\bbl@usehyphen\bbl@hyphenchar}
\def\bbl@hy@@hard{\bbl@@usehyphen\bbl@hyphenchar}
\def\bbl@hy@nobreak{\bbl@usehyphen{\mbox{\bbl@hyphenchar}}}
\def\bbl@hy@@nobreak{\mbox{\bbl@hyphenchar}}
\def\bbl@hy@repeat{%
  \bbl@usehyphen{%
    \discretionary{\bbl@hyphenchar}{\bbl@hyphenchar}{\bbl@hyphenchar}}}
\def\bbl@hy@@repeat{%
  \bbl@@usehyphen{%
    \discretionary{\bbl@hyphenchar}{\bbl@hyphenchar}{\bbl@hyphenchar}}}
\def\bbl@hy@empty{\hskip\z@skip}
\def\bbl@hy@@empty{\discretionary{}{}{}}
```

\bbl@disc For some languages the macro `\bbl@disc` is used to ease the insertion of discretionaries for letters that behave 'abnormally' at a breakpoint.

```
\def\bbl@disc#1#2{\nobreak\discretionary{#2-}{}{#1}\bbl@allowhyphens}
```

3.18. Multiencoding strings

The aim following commands is to provide a common interface for strings in several encodings. They also contains several hooks which can be used by luatex and xetex. The code is organized here with pseudo-guards, so we start with the basic commands.

Tools But first, a tool. It makes global a local variable. This is not the best solution, but it works.

```
\bbl@trace{Multiencoding strings}
\def\bbl@toglobal#1{\global\let#1#1}
```

The following option is currently no-op. It was meant for the deprecated `\SetCase`.

```
⟨⟨*More package options⟩⟩ ▸
\DeclareOption{nocase}{}
⟨⟨/More package options⟩⟩
```

The following package options control the behavior of `\SetString`.

```
⟨⟨*More package options⟩⟩ ▸
\let\bbl@opt@strings\@nnil % accept strings=value
\DeclareOption{strings}{\def\bbl@opt@strings{\BabelStringsDefault}}
\DeclareOption{strings=encoded}{\let\bbl@opt@strings\relax}
\def\BabelStringsDefault{generic}
⟨⟨/More package options⟩⟩
```

Main command This is the main command. With the first use it is redefined to omit the basic setup in subsequent blocks. We make sure strings contain actual letters in the range 128-255, not active characters.

```
\@onlypreamble\StartBabelCommands
\def\StartBabelCommands{%
  \begingroup
  \@tempcnta="7F
  \def\bbl@tempa{%
    \ifnum\@tempcnta>"FF\else
      \catcode\@tempcnta=11
      \advance\@tempcnta\@ne
      \expandafter\bbl@tempa
    \fi}%
  \bbl@tempa
  <@Macros local to BabelCommands@>
  \def\bbl@provstring##1##2{%
    \providecommand##1{##2}%
    \bbl@toglobal##1}%
  \global\let\bbl@scafter\@empty
  \let\StartBabelCommands\bbl@startcmds
  \ifx\BabelLanguages\relax
     \let\BabelLanguages\CurrentOption
  \fi
  \begingroup
  \let\bbl@screset\@nnil % local flag - disable 1st stopcommands
  \StartBabelCommands}
\def\bbl@startcmds{%
  \ifx\bbl@screset\@nnil\else
    \bbl@usehooks{stopcommands}{}%
  \fi
  \endgroup
  \begingroup
  \@ifstar
    {\ifx\bbl@opt@strings\@nnil
       \let\bbl@opt@strings\BabelStringsDefault
     \fi
     \bbl@startcmds@i}%
    \bbl@startcmds@i}
\def\bbl@startcmds@i#1#2{%
  \edef\bbl@L{\zap@space#1 \@empty}%
```

```
  \edef\bbl@G{\zap@space#2 \@empty}%
  \bbl@startcmds@ii}
\let\bbl@startcommands\StartBabelCommands
```

Parse the encoding info to get the label, input, and font parts.

Select the behavior of `\SetString`. There are two main cases, depending of if there is an optional argument: without it and `strings=encoded`, strings are defined always; otherwise, they are set only if they are still undefined (i.e., fallback values). With labelled blocks and `strings=encoded`, define the strings, but with another value, define strings only if the current label or font encoding is the value of `strings`; otherwise (i.e., no `strings` or a block whose label is not in `strings=`) do nothing.

We presume the current block is not loaded, and therefore set (above) a couple of default values to gobble the arguments. Then, these macros are redefined if necessary according to several parameters.

```
\newcommand\bbl@startcmds@ii[1][\@empty]{%
  \let\SetString\@gobbletwo
  \let\bbl@stringdef\@gobbletwo
  \let\AfterBabelCommands\@gobble
  \ifx\@empty#1%
    \def\bbl@sc@label{generic}%
    \def\bbl@encstring##1##2{%
      \ProvideTextCommandDefault##1{##2}%
      \bbl@toglobal##1%
      \expandafter\bbl@toglobal\csname\string?\string##1\endcsname}%
    \let\bbl@sctest\in@true
  \else
    \let\bbl@sc@charset\space % <- zapped below
    \let\bbl@sc@fontenc\space % <-   "      "
    \def\bbl@tempa##1=##2\@nil{%
      \bbl@csarg\edef{sc@\zap@space##1 \@empty}{##2 }}%
    \bbl@vforeach{label=#1}{\bbl@tempa##1\@nil}%
    \def\bbl@tempa##1 ##2{% space -> comma
      ##1%
      \ifx\@empty##2\else\ifx,##1,\else,\fi\bbl@afterfi\bbl@tempa##2\fi}%
    \edef\bbl@sc@fontenc{\expandafter\bbl@tempa\bbl@sc@fontenc\@empty}%
    \edef\bbl@sc@label{\expandafter\zap@space\bbl@sc@label\@empty}%
    \edef\bbl@sc@charset{\expandafter\zap@space\bbl@sc@charset\@empty}%
    \def\bbl@encstring##1##2{%
      \bbl@foreach\bbl@sc@fontenc{%
        \bbl@ifunset{T@####1}%
          {}%
          {\ProvideTextCommand##1{####1}{##2}%
           \bbl@toglobal##1%
           \expandafter
           \bbl@toglobal\csname####1\string##1\endcsname}}}%
    \def\bbl@sctest{%
      \bbl@xin@{,\bbl@opt@strings,}{,\bbl@sc@label,\bbl@sc@fontenc,}}%
  \fi
  \ifx\bbl@opt@strings\@nnil         % i.e., no strings key -> defaults
  \else\ifx\bbl@opt@strings\relax    % i.e., strings=encoded
    \let\AfterBabelCommands\bbl@aftercmds
    \let\SetString\bbl@setstring
    \let\bbl@stringdef\bbl@encstring
  \else       % i.e., strings=value
  \bbl@sctest
  \ifin@
    \let\AfterBabelCommands\bbl@aftercmds
    \let\SetString\bbl@setstring
    \let\bbl@stringdef\bbl@provstring
  \fi\fi\fi
  \bbl@scswitch
  \ifx\bbl@G\@empty
    \def\SetString##1##2{%
      \bbl@error{missing-group}{##1}{}{}}%
```

```
  \fi
  \ifx\@empty#1%
    \bbl@usehooks{defaultcommands}{}%
  \else
    \@expandtwoargs
    \bbl@usehooks{encodedcommands}{{\bbl@sc@charset}{\bbl@sc@fontenc}}%
  \fi}
```

There are two versions of `\bbl@scswitch`. The first version is used when `ldfs` are read, and it makes sure \⟨*group*⟩⟨*language*⟩ is reset, but only once (`\bbl@screset` is used to keep track of this). The second version is used in the preamble and packages loaded after babel and does nothing.

The macro `\bbl@forlang` loops `\bbl@L` but its body is executed only if the value is in `\BabelLanguages` (inside babel) or `\date`⟨*language*⟩ is defined (after babel has been loaded). There are also two version of `\bbl@forlang`. The first one skips the current iteration if the language is not in `\BabelLanguages` (used in `ldfs`), and the second one skips undefined languages (after babel has been loaded) .

```
\def\bbl@forlang#1#2{%
  \bbl@for#1\bbl@L{%
    \bbl@xin@{,#1,}{,\BabelLanguages,}%
    \ifin@#2\relax\fi}}
\def\bbl@scswitch{%
  \bbl@forlang\bbl@tempa{%
    \ifx\bbl@G\@empty\else
      \ifx\SetString\@gobbletwo\else
        \edef\bbl@GL{\bbl@G\bbl@tempa}%
        \bbl@xin@{,\bbl@GL,}{,\bbl@screset,}%
        \ifin@\else
          \global\expandafter\let\csname\bbl@GL\endcsname\@undefined
          \xdef\bbl@screset{\bbl@screset,\bbl@GL}%
        \fi
      \fi
    \fi}}
\AtEndOfPackage{%
  \def\bbl@forlang#1#2{\bbl@for#1\bbl@L{\bbl@ifunset{date#1}{}{#2}}}%
  \let\bbl@scswitch\relax}
\@onlypreamble\EndBabelCommands
\def\EndBabelCommands{%
  \bbl@usehooks{stopcommands}{}%
  \endgroup
  \endgroup
  \bbl@scafter}
\let\bbl@endcommands\EndBabelCommands
```

Now we define commands to be used inside `\StartBabelCommands`.

Strings The following macro is the actual definition of `\SetString` when it is "active"

First save the "switcher". Create it if undefined. Strings are defined only if undefined (i.e., like `\providescommand`). With the event `stringprocess` you can preprocess the string by manipulating the value of `\BabelString`. If there are several hooks assigned to this event, preprocessing is done in the same order as defined. Finally, the string is set.

```
\def\bbl@setstring#1#2{% e.g., \prefacename{<string>}
  \bbl@forlang\bbl@tempa{%
    \edef\bbl@LC{\bbl@tempa\bbl@stripslash#1}%
    \bbl@ifunset{\bbl@LC}% e.g., \germanchaptername
      {\bbl@exp{%
         \global\\\bbl@add\<\bbl@G\bbl@tempa>{\\\bbl@scset\\#1\<\bbl@LC>}}}%
      {}%
    \def\BabelString{#2}%
    \bbl@usehooks{stringprocess}{}%
    \expandafter\bbl@stringdef
      \csname\bbl@LC\expandafter\endcsname\expandafter{\BabelString}}}
```

A little auxiliary command sets the string. Formerly used with casing. Very likely no longer necessary, although it's used in `\setlocalecaption`.

```
\def\bbl@scset#1#2{\def#1{#2}}
```

Define `\SetStringLoop`, which is actually set inside `\StartBabelCommands`. The current definition is somewhat complicated because we need a count, but `\count@` is not under our control (remember `\SetString` may call hooks). Instead of defining a dedicated count, we just "pre-expand" its value.

```
⟨*Macros local to BabelCommands⟩  ▸
\def\SetStringLoop##1##2{%
    \def\bbl@templ####1{\expandafter\noexpand\csname##1\endcsname}%
    \count@\z@
    \bbl@loop\bbl@tempa{##2}{% empty items and spaces are ok
      \advance\count@\@ne
      \toks@\expandafter{\bbl@tempa}%
      \bbl@exp{%
        \\\SetString\bbl@templ{\romannumeral\count@}{\the\toks@}%
        \count@=\the\count@\relax}}%
⟨/Macros local to BabelCommands⟩
```

Delaying code Now the definition of `\AfterBabelCommands` when it is activated.

```
\def\bbl@aftercmds#1{%
  \toks@\expandafter{\bbl@scafter#1}%
  \xdef\bbl@scafter{\the\toks@}}
```

Case mapping The command `\SetCase` is deprecated. Currently it consists in a definition with a hack just for backward compatibility in the macro mapping.

```
⟨*Macros local to BabelCommands⟩  ▸
  \newcommand\SetCase[3][]{%
    \def\bbl@tempa####1####2{%
      \ifx####1\@empty\else
        \bbl@carg\bbl@add{extras\CurrentOption}{%
          \bbl@carg\babel@save{c__text_uppercase_\string####1_tl}%
          \bbl@carg\def{c__text_uppercase_\string####1_tl}{####2}%
          \bbl@carg\babel@save{c__text_lowercase_\string####2_tl}%
          \bbl@carg\def{c__text_lowercase_\string####2_tl}{####1}}%
        \expandafter\bbl@tempa
      \fi}%
    \bbl@tempa##1\@empty\@empty
    \bbl@carg\bbl@toglobal{extras\CurrentOption}}%
⟨/Macros local to BabelCommands⟩
```

Macros to deal with case mapping for hyphenation. To decide if the document is monolingual or multilingual, we make a rough guess – just see if there is a comma in the languages list, built in the first pass of the package options.

```
⟨*Macros local to BabelCommands⟩  ▸
  \newcommand\SetHyphenMap[1]{%
    \bbl@forlang\bbl@tempa{%
      \expandafter\bbl@stringdef
        \csname\bbl@tempa @bbl@hyphenmap\endcsname{##1}}}%
⟨/Macros local to BabelCommands⟩
```

There are 3 helper macros which do most of the work for you.

```
\newcommand\BabelLower[2]{% one to one.
  \ifnum\lccode#1=#2\else
    \babel@savevariable{\lccode#1}%
    \lccode#1=#2\relax
  \fi}
\newcommand\BabelLowerMM[4]{% many-to-many
  \@tempcnta=#1\relax
  \@tempcntb=#4\relax
  \def\bbl@tempa{%
    \ifnum\@tempcnta>#2\else
      \@expandtwoargs\BabelLower{\the\@tempcnta}{\the\@tempcntb}%
      \advance\@tempcnta#3\relax
```

```
      \advance\@tempcntb#3\relax
      \expandafter\bbl@tempa
    \fi}%
  \bbl@tempa}
\newcommand\BabelLowerMO[4]{% many-to-one
  \@tempcnta=#1\relax
  \def\bbl@tempa{%
    \ifnum\@tempcnta>#2\else
      \@expandtwoargs\BabelLower{\the\@tempcnta}{#4}%
      \advance\@tempcnta#3
      \expandafter\bbl@tempa
    \fi}%
  \bbl@tempa}
```

The following package options control the behavior of hyphenation mapping.

```
⟨⟨*More package options⟩⟩ ▸
\DeclareOption{hyphenmap=off}{\chardef\bbl@opt@hyphenmap\z@}
\DeclareOption{hyphenmap=first}{\chardef\bbl@opt@hyphenmap\@ne}
\DeclareOption{hyphenmap=select}{\chardef\bbl@opt@hyphenmap\tw@}
\DeclareOption{hyphenmap=other}{\chardef\bbl@opt@hyphenmap\thr@@}
\DeclareOption{hyphenmap=other*}{\chardef\bbl@opt@hyphenmap4\relax}
⟨⟨/More package options⟩⟩
```

Initial setup to provide a default behavior if `hyphenmap` is not set.

```
\AtEndOfPackage{%
  \ifx\bbl@opt@hyphenmap\@undefined
    \bbl@xin@{,}{\bbl@language@opts}%
    \chardef\bbl@opt@hyphenmap\ifin@4\else\@ne\fi
  \fi}
```

3.19. Tailor captions

A general tool for resetting the caption names with a unique interface. With the old way, which mixes the switcher and the string, we convert it to the new one, which separates these two steps.

```
\newcommand\setlocalecaption{%
  \@ifstar\bbl@setcaption@s\bbl@setcaption@x}
\def\bbl@setcaption@x#1#2#3{%  language caption-name string
  \bbl@trim@def\bbl@tempa{#2}%
  \bbl@xin@{.template}{\bbl@tempa}%
  \ifin@
    \bbl@ini@captions@template{#3}{#1}%
  \else
    \edef\bbl@tempd{%
      \expandafter\expandafter\expandafter
      \strip@prefix\expandafter\meaning\csname captions#1\endcsname}%
    \bbl@xin@
      {\expandafter\string\csname #2name\endcsname}%
      {\bbl@tempd}%
    \ifin@ % Renew caption
      \bbl@xin@{\string\bbl@scset}{\bbl@tempd}%
      \ifin@
        \bbl@exp{%
          \\\bbl@ifsamestring{\bbl@tempa}{\languagename}%
            {\\\bbl@scset\<#2name>\<#1#2name>}%
            {}}%
      \else % Old way converts to new way
        \bbl@ifunset{#1#2name}%
          {\bbl@exp{%
            \\\bbl@add\<captions#1>{\def\<#2name>{\<#1#2name>}}%
            \\\bbl@ifsamestring{\bbl@tempa}{\languagename}%
              {\def\<#2name>{\<#1#2name>}}%
              {}}}%
          {}%
```

```
      \fi
    \else
      \bbl@xin@{\string\bbl@scset}{\bbl@tempd}% New
      \ifin@ % New way
        \bbl@exp{%
          \\\bbl@add\<captions#1>{\\\bbl@scset\<#2name>\<#1#2name>}%
          \\\bbl@ifsamestring{\bbl@tempa}{\languagename}%
            {\\\bbl@scset\<#2name>\<#1#2name>}%
            {}}%
      \else  % Old way, but defined in the new way
        \bbl@exp{%
          \\\bbl@add\<captions#1>{\def\<#2name>{\<#1#2name>}}%
          \\\bbl@ifsamestring{\bbl@tempa}{\languagename}%
            {\def\<#2name>{\<#1#2name>}}%
            {}}%
      \fi%
    \fi
    \@namedef{#1#2name}{#3}%
    \toks@\expandafter{\bbl@captionslist}%
    \bbl@exp{\\\in@{\<#2name>}{\the\toks@}}%
    \ifin@\else
      \bbl@exp{\\\bbl@add\\\bbl@captionslist{\<#2name>}}%
      \bbl@toglobal\bbl@captionslist
    \fi
  \fi}
```

3.20. Making glyphs available

This section makes a number of glyphs available that either do not exist in the OT1 encoding and have to be 'faked', or that are not accessible through T1enc.def.

\set@low@box The following macro is used to lower quotes to the same level as the comma. It prepares its argument in box register 0.

```
\bbl@trace{Macros related to glyphs}
\def\set@low@box#1{\setbox\tw@\hbox{,}\setbox\z@\hbox{#1}%
    \dimen\z@\ht\z@ \advance\dimen\z@ -\ht\tw@%
    \setbox\z@\hbox{\lower\dimen\z@ \box\z@}\ht\z@\ht\tw@ \dp\z@\dp\tw@}
```

\save@sf@q The macro \save@sf@q is used to save and reset the current space factor.

```
\def\save@sf@q#1{\leavevmode
  \begingroup
    \edef\@SF{\spacefactor\the\spacefactor}#1\@SF
  \endgroup}
```

3.20.1. Quotation marks

\quotedblbase In the T1 encoding the opening double quote at the baseline is available as a separate character, accessible via \quotedblbase. In the OT1 encoding it is not available, therefore we make it available by lowering the normal open quote character to the baseline.

```
\ProvideTextCommand{\quotedblbase}{OT1}{%
  \save@sf@q{\set@low@box{\textquotedblright\/}%
    \box\z@\kern-.04em\bbl@allowhyphens}}
```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```
\ProvideTextCommandDefault{\quotedblbase}{%
  \UseTextSymbol{OT1}{\quotedblbase}}
```

\quotesinglbase We also need the single quote character at the baseline.

```
\ProvideTextCommand{\quotesinglbase}{OT1}{%
  \save@sf@q{\set@low@box{\textquoteright\/}%
    \box\z@\kern-.04em\bbl@allowhyphens}}
```

Make sure that when an encoding other than OT1 or T1 is used this glyph can still be typeset.

```
\ProvideTextCommandDefault{\quotesinglbase}{%
  \UseTextSymbol{OT1}{\quotesinglbase}}
```

\guillemetleft
\guillemetright The guillemet characters are not available in OT1 encoding. They are faked. (Wrong names with o preserved for compatibility.)

```
\ProvideTextCommand{\guillemetleft}{OT1}{%
  \ifmmode
    \ll
  \else
    \save@sf@q{\nobreak
      \raise.2ex\hbox{$\scriptscriptstyle\ll$}\bbl@allowhyphens}%
  \fi}
\ProvideTextCommand{\guillemetright}{OT1}{%
  \ifmmode
    \gg
  \else
    \save@sf@q{\nobreak
      \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
  \fi}
\ProvideTextCommand{\guillemotleft}{OT1}{%
  \ifmmode
    \ll
  \else
    \save@sf@q{\nobreak
      \raise.2ex\hbox{$\scriptscriptstyle\ll$}\bbl@allowhyphens}%
  \fi}
\ProvideTextCommand{\guillemotright}{OT1}{%
  \ifmmode
    \gg
  \else
    \save@sf@q{\nobreak
      \raise.2ex\hbox{$\scriptscriptstyle\gg$}\bbl@allowhyphens}%
  \fi}
```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```
\ProvideTextCommandDefault{\guillemetleft}{%
  \UseTextSymbol{OT1}{\guillemetleft}}
\ProvideTextCommandDefault{\guillemetright}{%
  \UseTextSymbol{OT1}{\guillemetright}}
\ProvideTextCommandDefault{\guillemotleft}{%
  \UseTextSymbol{OT1}{\guillemotleft}}
\ProvideTextCommandDefault{\guillemotright}{%
  \UseTextSymbol{OT1}{\guillemotright}}
```

\guilsinglleft
\guilsinglright The single guillemets are not available in OT1 encoding. They are faked.

```
\ProvideTextCommand{\guilsinglleft}{OT1}{%
  \ifmmode
    <%
  \else
    \save@sf@q{\nobreak
      \raise.2ex\hbox{$\scriptscriptstyle<$}\bbl@allowhyphens}%
  \fi}
\ProvideTextCommand{\guilsinglright}{OT1}{%
  \ifmmode
    >%
  \else
    \save@sf@q{\nobreak
      \raise.2ex\hbox{$\scriptscriptstyle>$}\bbl@allowhyphens}%
  \fi}
```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```
\ProvideTextCommandDefault{\guilsinglleft}{%
  \UseTextSymbol{OT1}{\guilsinglleft}}
\ProvideTextCommandDefault{\guilsinglright}{%
  \UseTextSymbol{OT1}{\guilsinglright}}
```

3.20.2. Letters

\ij
\IJ The dutch language uses the letter 'ij'. It is available in T1 encoded fonts, but not in the OT1 encoded fonts. Therefore we fake it for the OT1 encoding.

```
\DeclareTextCommand{\ij}{OT1}{%
  i\kern-0.02em\bbl@allowhyphens j}
\DeclareTextCommand{\IJ}{OT1}{%
  I\kern-0.02em\bbl@allowhyphens J}
\DeclareTextCommand{\ij}{T1}{\char188}
\DeclareTextCommand{\IJ}{T1}{\char156}
```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```
\ProvideTextCommandDefault{\ij}{%
  \UseTextSymbol{OT1}{\ij}}
\ProvideTextCommandDefault{\IJ}{%
  \UseTextSymbol{OT1}{\IJ}}
```

\dj
\DJ The croatian language needs the letters \dj and \DJ; they are available in the T1 encoding, but not in the OT1 encoding by default.

Some code to construct these glyphs for the OT1 encoding was made available to me by Stipčević Mario, (stipcevic@olimp.irb.hr).

```
\def\crrtic@{\hrule height0.1ex width0.3em}
\def\crttic@{\hrule height0.1ex width0.33em}
\def\ddj@{%
  \setbox0\hbox{d}\dimen@=\ht0
  \advance\dimen@1ex
  \dimen@.45\dimen@
  \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
  \advance\dimen@ii.5ex
  \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crrtic@}}}}
\def\DDJ@{%
  \setbox0\hbox{D}\dimen@=.55\ht0
  \dimen@ii\expandafter\rem@pt\the\fontdimen\@ne\font\dimen@
  \advance\dimen@ii.15ex %            correction for the dash position
  \advance\dimen@ii-.15\fontdimen7\font %     correction for cmtt font
  \dimen\thr@@\expandafter\rem@pt\the\fontdimen7\font\dimen@
  \leavevmode\rlap{\raise\dimen@\hbox{\kern\dimen@ii\vbox{\crttic@}}}}
%
\DeclareTextCommand{\dj}{OT1}{\ddj@ d}
\DeclareTextCommand{\DJ}{OT1}{\DDJ@ D}
```

Make sure that when an encoding other than OT1 or T1 is used these glyphs can still be typeset.

```
\ProvideTextCommandDefault{\dj}{%
  \UseTextSymbol{OT1}{\dj}}
\ProvideTextCommandDefault{\DJ}{%
  \UseTextSymbol{OT1}{\DJ}}
```

\SS For the T1 encoding \SS is defined and selects a specific glyph from the font, but for other encodings it is not available. Therefore we make it available here.

```
\DeclareTextCommand{\SS}{OT1}{SS}
\ProvideTextCommandDefault{\SS}{\UseTextSymbol{OT1}{\SS}}
```

3.20.3. Shorthands for quotation marks

Shorthands are provided for a number of different quotation marks, which make them usable both outside and inside mathmode. They are defined with `\ProvideTextCommandDefault`, but this is very likely not required because their definitions are based on encoding-dependent macros.

\glq
\grq The 'german' single quotes.

```
\ProvideTextCommandDefault{\glq}{%
  \textormath{\quotesinglbase}{\mbox{\quotesinglbase}}}
```

The definition of `\grq` depends on the fontencoding. With `T1` encoding no extra kerning is needed.

```
\ProvideTextCommand{\grq}{T1}{%
  \textormath{\kern\z@\textquoteleft}{\mbox{\textquoteleft}}}
\ProvideTextCommand{\grq}{TU}{%
  \textormath{\textquoteleft}{\mbox{\textquoteleft}}}
\ProvideTextCommand{\grq}{OT1}{%
  \save@sf@q{\kern-.0125em
    \textormath{\textquoteleft}{\mbox{\textquoteleft}}%
    \kern.07em\relax}}
\ProvideTextCommandDefault{\grq}{\UseTextSymbol{OT1}\grq}
```

\glqq
\grqq The 'german' double quotes.

```
\ProvideTextCommandDefault{\glqq}{%
  \textormath{\quotedblbase}{\mbox{\quotedblbase}}}
```

The definition of `\grqq` depends on the fontencoding. With `T1` encoding no extra kerning is needed.

```
\ProvideTextCommand{\grqq}{T1}{%
  \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}
\ProvideTextCommand{\grqq}{TU}{%
  \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}}
\ProvideTextCommand{\grqq}{OT1}{%
  \save@sf@q{\kern-.07em
    \textormath{\textquotedblleft}{\mbox{\textquotedblleft}}%
    \kern.07em\relax}}
\ProvideTextCommandDefault{\grqq}{\UseTextSymbol{OT1}\grqq}
```

\flq
\frq The 'french' single guillemets.

```
\ProvideTextCommandDefault{\flq}{%
  \textormath{\guilsinglleft}{\mbox{\guilsinglleft}}}
\ProvideTextCommandDefault{\frq}{%
  \textormath{\guilsinglright}{\mbox{\guilsinglright}}}
```

\flqq
\frqq The 'french' double guillemets.

```
\ProvideTextCommandDefault{\flqq}{%
  \textormath{\guillemetleft}{\mbox{\guillemetleft}}}
\ProvideTextCommandDefault{\frqq}{%
  \textormath{\guillemetright}{\mbox{\guillemetright}}}
```

3.20.4. Umlauts and tremas

The command `\"` needs to have a different effect for different languages. For German for instance, the 'umlaut' should be positioned lower than the default position for placing it over the letters a, o, u, A, O and U. When placed over an e, i, E or I it can retain its normal position. For Dutch the same glyph is always placed in the lower position.

\umlauthigh

\umlautlow To be able to provide both positions of \" we provide two commands to switch the positioning, the default will be \umlauthigh (the normal positioning).

```
\def\umlauthigh{%
  \def\bbl@umlauta##1{\leavevmode\bgroup%
      \accent\csname\f@encoding dqpos\endcsname
      ##1\bbl@allowhyphens\egroup}%
  \let\bbl@umlaute\bbl@umlauta}
\def\umlautlow{%
  \def\bbl@umlauta{\protect\lower@umlaut}}
\def\umlautelow{%
  \def\bbl@umlaute{\protect\lower@umlaut}}
\umlauthigh
```

\lower@umlaut Used to position the \" closer to the letter. We want the umlaut character lowered, nearer to the letter. To do this we need an extra ⟨*dimen*⟩ register.

```
\expandafter\ifx\csname U@D\endcsname\relax
  \csname newdimen\endcsname\U@D
\fi
```

The following code fools TEX's `make_accent` procedure about the current x-height of the font to force another placement of the umlaut character. First we have to save the current x-height of the font, because we'll change this font dimension and this is always done globally.

Then we compute the new x-height in such a way that the umlaut character is lowered to the base character. The value of `.45ex` depends on the METAFONT parameters with which the fonts were built. (Just try out, which value will look best.) If the new x-height is too low, it is not changed. Finally we call the \accent primitive, reset the old x-height and insert the base character in the argument.

```
\def\lower@umlaut#1{%
  \leavevmode\bgroup
    \U@D 1ex%
    {\setbox\z@\hbox{%
      \char\csname\f@encoding dqpos\endcsname}%
      \dimen@ -.45ex\advance\dimen@\ht\z@
      \ifdim 1ex<\dimen@ \fontdimen5\font\dimen@ \fi}%
    \accent\csname\f@encoding dqpos\endcsname
    \fontdimen5\font\U@D #1%
  \egroup}
```

For all vowels we declare \" to be a composite command which uses \bbl@umlauta or \bbl@umlaute to position the umlaut character. We need to be sure that these definitions override the ones that are provided when the package `fontenc` with option OT1 is used. Therefore these declarations are postponed until the beginning of the document. Note these definitions only apply to some languages, but babel sets them for *all* languages – you may want to redefine \bbl@umlauta and/or \bbl@umlaute for a language in the corresponding `ldf` (using the babel switching mechanism, of course).

```
\AtBeginDocument{%
  \DeclareTextCompositeCommand{\"}{OT1}{a}{\bbl@umlauta{a}}%
  \DeclareTextCompositeCommand{\"}{OT1}{e}{\bbl@umlaute{e}}%
  \DeclareTextCompositeCommand{\"}{OT1}{i}{\bbl@umlaute{\i}}%
  \DeclareTextCompositeCommand{\"}{OT1}{\i}{\bbl@umlaute{\i}}%
  \DeclareTextCompositeCommand{\"}{OT1}{o}{\bbl@umlauta{o}}%
  \DeclareTextCompositeCommand{\"}{OT1}{u}{\bbl@umlauta{u}}%
  \DeclareTextCompositeCommand{\"}{OT1}{A}{\bbl@umlauta{A}}%
  \DeclareTextCompositeCommand{\"}{OT1}{E}{\bbl@umlaute{E}}%
  \DeclareTextCompositeCommand{\"}{OT1}{I}{\bbl@umlaute{I}}%
  \DeclareTextCompositeCommand{\"}{OT1}{O}{\bbl@umlauta{O}}%
  \DeclareTextCompositeCommand{\"}{OT1}{U}{\bbl@umlauta{U}}}
```

Finally, make sure the default hyphenrules are defined (even if empty). For internal use, another empty \language is defined. Currently used in Amharic.

```
\ifx\l@english\@undefined
  \chardef\l@english\z@
\fi
```

```
% The following is used to cancel rules in ini files (see Amharic).
\ifx\l@unhyphenated\@undefined
  \newlanguage\l@unhyphenated
\fi
```

3.21. Layout

Layout is mainly intended to set bidi documents, but there is at least a tool useful in general.

```
\bbl@trace{Bidi layout}
\providecommand\IfBabelLayout[3]{#3}%
```

3.22. Load engine specific macros

Some macros are not defined in all engines, so, after loading the files define them if necessary to raise an error.

```
\bbl@trace{Input engine specific macros}
\ifcase\bbl@engine
  \input txtbabel.def
\or
  \input luababel.def
\or
  \input xebabel.def
\fi
\providecommand\babelfont{\bbl@error{only-lua-xe}{}{}{}}
\providecommand\babelprehyphenation{\bbl@error{only-lua}{}{}{}}
\ifx\babelposthyphenation\@undefined
  \let\babelposthyphenation\babelprehyphenation
  \let\babelpatterns\babelprehyphenation
  \let\babelcharproperty\babelprehyphenation
\fi
```

3.23. Creating and modifying languages

`\babelprovide` is a general purpose tool for creating and modifying languages. It creates the language infrastructure, and loads, if requested, an `ini` file. It may be used in conjunction to previously loaded `ldf` files.

```
\bbl@trace{Creating languages and reading ini files}
\let\bbl@extend@ini\@gobble
\newcommand\babelprovide[2][]{%
  \let\bbl@savelangname\languagename
  \edef\bbl@savelocaleid{\the\localeid}%
  \global\let\bbl@afterload\@empty
  % Set name and locale id
  \edef\languagename{#2}%
  \bbl@id@assign
  % Initialize keys
  \bbl@vforeach{captions,date,import,main,script,language,%
      hyphenrules,linebreaking,justification,mapfont,maparabic,%
      mapdigits,intraspace,intrapenalty,onchar,transforms,alph,%
      Alph,labels,labels*,mapdot,calendar,date,casing,interchar,%
      @import}%
    {\bbl@csarg\let{KVP@##1}\@nnil}%
  \global\let\bbl@release@transforms\@empty
  \global\let\bbl@release@casing\@empty
  \let\bbl@calendars\@empty
  \global\let\bbl@inidata\@empty
  \global\let\bbl@extend@ini\@gobble
  \global\let\bbl@included@inis\@empty
  \gdef\bbl@key@list{;}%
  \bbl@ifunset{bbl@passto@#2}%
    {\def\bbl@tempa{#1}}%
    {\bbl@exp{\def\\\bbl@tempa{\[bbl@passto@#2],\unexpanded{#1}}}}%
```

```
\expandafter\bbl@forkv\expandafter{\bbl@tempa}{%
  \in@{/}{##1}% With /, (re)sets a value in the ini
  \ifin@
    \bbl@renewinikey##1\@@{##2}%
  \else
    \bbl@csarg\ifx{KVP@##1}\@nnil\else
      \bbl@error{unknown-provide-key}{##1}{}{}%
    \fi
    \bbl@csarg\def{KVP@##1}{##2}%
  \fi}%
\chardef\bbl@howloaded=% 0:none; 1:ldf without ini; 2:ini
  \bbl@ifunset{date#2}\z@{\bbl@ifunset{bbl@llevel@#2}\@ne\tw@}%
% == init ==
\ifx\bbl@screset\@undefined
  \bbl@ldfinit
\fi
% ==
% If there is no import (last wins), use @import (internal, there
% must be just one). To consider any order (because
% \PassOptionsToLocale).
\ifx\bbl@KVP@import\@nnil
  \let\bbl@KVP@import\bbl@KVP@@import
\fi
% == date (as option) ==
% \ifx\bbl@KVP@date\@nnil\else
% \fi
% ==
\let\bbl@lbkflag\relax % \@empty = do setup linebreak, only in 3 cases:
\ifcase\bbl@howloaded
  \let\bbl@lbkflag\@empty % new
\else
  \ifx\bbl@KVP@hyphenrules\@nnil\else
     \let\bbl@lbkflag\@empty
  \fi
  \ifx\bbl@KVP@import\@nnil\else
    \let\bbl@lbkflag\@empty
  \fi
\fi
% == import, captions ==
\ifx\bbl@KVP@import\@nnil\else
  \bbl@exp{\\\bbl@ifblank{\bbl@KVP@import}}%
    {\ifx\bbl@initoload\relax
       \begingroup
         \def\BabelBeforeIni##1##2{\gdef\bbl@KVP@import{##1}\endinput}%
         \bbl@input@texini{#2}%
       \endgroup
     \else
       \xdef\bbl@KVP@import{\bbl@initoload}%
     \fi}%
    {}%
  \let\bbl@KVP@date\@empty
\fi
\let\bbl@KVP@captions@@\bbl@KVP@captions
\ifx\bbl@KVP@captions\@nnil
  \let\bbl@KVP@captions\bbl@KVP@import
\fi
% ==
\ifx\bbl@KVP@transforms\@nnil\else
  \bbl@replace\bbl@KVP@transforms{ }{,}%
\fi
% Load ini
% --------
\ifcase\bbl@howloaded
```

```
    \bbl@provide@new{#2}%
  \else
    \bbl@ifblank{#1}%
      {}%  With \bbl@load@basic below
      {\bbl@provide@renew{#2}}%
  \fi
  % Post tasks
  % ----------
  % == subsequent calls after the first provide for a locale ==
  \ifx\bbl@inidata\@empty\else
    \bbl@extend@ini{#2}%
  \fi
  % ==
  \ifx\bbl@KVP@mapdot\@nnil\else
    \def\bbl@tempa{\@empty}%
    \ifx\bbl@KVP@mapdot\bbl@tempa\else
      \bbl@exp{\gdef\<bbl@map@@.@@\languagename>{\[bbl@KVP@mapdot]}}%
    \fi
  \fi
  % == ensure captions ==
  \ifx\bbl@KVP@captions\@nnil\else
    \bbl@ifunset{bbl@extracaps@#2}%
      {\bbl@exp{\\\babelensure[exclude=\\\today]{#2}}}%
      {\bbl@exp{\\\babelensure[exclude=\\\today,
                include=\[bbl@extracaps@#2]}]{#2}}%
    \let\bbl@tempc\languagename
    \bbl@replace\bbl@tempc{-}{@@}%
    \bbl@ifunset{bbl@ensure@\bbl@tempc}%
      {\bbl@exp{%
        \\\DeclareRobustCommand\<bbl@ensure@\bbl@tempc>[1]{%
          \\\foreignlanguage{\languagename}%
          {####1}}}}%
      {}%
    \bbl@exp{%
       \\\bbl@toglobal\<bbl@ensure@\bbl@tempc>%
       \\\bbl@toglobal\<bbl@ensure@\bbl@tempc\space>}%
  \fi
```

At this point all parameters are defined if 'import'. Now we execute some code depending on them. But what about if nothing was imported? We just set the basic parameters, but still loading the whole ini file.

```
  \bbl@load@basic{#2}%
  % == script, language ==
  % Override the values from ini or defines them
  \ifx\bbl@KVP@script\@nnil\else
    \bbl@csarg\edef{sname@#2}{\bbl@KVP@script}%
  \fi
  \ifx\bbl@KVP@language\@nnil\else
    \bbl@csarg\edef{lname@#2}{\bbl@KVP@language}%
  \fi
  \ifcase\bbl@engine\or
    \bbl@ifunset{bbl@chrng@\languagename}{}%
      {\directlua{
         Babel.set_chranges_b('\bbl@cl{sbcp}', '\bbl@cl{chrng}') }}%
  \fi
  % == Line breaking: intraspace, intrapenalty ==
  % For CJK, East Asian, Southeast Asian, if interspace in ini
  \ifx\bbl@KVP@intraspace\@nnil\else % We can override the ini or set
    \bbl@csarg\edef{intsp@#2}{\bbl@KVP@intraspace}%
  \fi
  \bbl@provide@intraspace
  % == Line breaking: justification ==
  \ifx\bbl@KVP@justification\@nnil\else
```

```
    \let\bbl@KVP@linebreaking\bbl@KVP@justification
  \fi
  \ifx\bbl@KVP@linebreaking\@nnil\else
    \bbl@xin@{,\bbl@KVP@linebreaking,}%
      {,elongated,kashida,cjk,padding,unhyphenated,}%
    \ifin@
      \bbl@csarg\xdef
        {lnbrk@\languagename}{\expandafter\@car\bbl@KVP@linebreaking\@nil}%
    \fi
  \fi
  \bbl@xin@{/e}{/\bbl@cl{lnbrk}}%
  \ifin@\else\bbl@xin@{/k}{/\bbl@cl{lnbrk}}\fi
  \ifin@\bbl@arabicjust\fi
  \bbl@xin@{/p}{/\bbl@cl{lnbrk}}%
  \ifin@\AtBeginDocument{\@nameuse{bbl@tibetanjust}}\fi
  % == Line breaking: hyphenate.other.(locale|script) ==
  \ifx\bbl@lbkflag\@empty
    \bbl@ifunset{bbl@hyotl@\languagename}{}%
      {\bbl@csarg\bbl@replace{hyotl@\languagename}{ }{,}%
       \bbl@startcommands*{\languagename}{}%
         \bbl@csarg\bbl@foreach{hyotl@\languagename}{%
           \ifcase\bbl@engine
             \ifnum##1<257
               \SetHyphenMap{\BabelLower{##1}{##1}}%
             \fi
           \else
             \SetHyphenMap{\BabelLower{##1}{##1}}%
           \fi}%
       \bbl@endcommands}%
    \bbl@ifunset{bbl@hyots@\languagename}{}%
      {\bbl@csarg\bbl@replace{hyots@\languagename}{ }{,}%
       \bbl@csarg\bbl@foreach{hyots@\languagename}{%
         \ifcase\bbl@engine
           \ifnum##1<257
             \global\lccode##1=##1\relax
           \fi
         \else
           \global\lccode##1=##1\relax
         \fi}}%
  \fi
  % == Counters: maparabic ==
  % Native digits, if provided in ini (TeX level, xe and lua)
  \ifcase\bbl@engine\else
    \bbl@ifunset{bbl@dgnat@\languagename}{}%
      {\expandafter\ifx\csname bbl@dgnat@\languagename\endcsname\@empty\else
        \expandafter\expandafter\expandafter
        \bbl@setdigits\csname bbl@dgnat@\languagename\endcsname
        \ifx\bbl@KVP@maparabic\@nnil\else
          \ifx\bbl@latinarabic\@undefined
            \expandafter\let\expandafter\@arabic
              \csname bbl@counter@\languagename\endcsname
          \else    % i.e., if layout=counters, which redefines \@arabic
            \expandafter\let\expandafter\bbl@latinarabic
              \csname bbl@counter@\languagename\endcsname
          \fi
        \fi
      \fi}%
  \fi
  % == Counters: mapdigits ==
  % > luababel.def
  % == Counters: alph, Alph ==
  \ifx\bbl@KVP@alph\@nnil\else
    \bbl@exp{%
```

```
      \\\bbl@add\<bbl@preextras@\languagename>{%
        \\\babel@save\\\@alph
        \let\\\@alph\<bbl@cntr@\bbl@KVP@alph @\languagename>}}%
  \fi
  \ifx\bbl@KVP@Alph\@nnil\else
    \bbl@exp{%
      \\\bbl@add\<bbl@preextras@\languagename>{%
        \\\babel@save\\\@Alph
        \let\\\@Alph\<bbl@cntr@\bbl@KVP@Alph @\languagename>}}%
  \fi
  % == Counters: mapdot ==
  \ifx\bbl@KVP@mapdot\@nnil\else
    \bbl@foreach\bbl@list@the{%
        \bbl@ifunset{the##1}{}%
      {{\bbl@ncarg\let\bbl@tempd{the##1}%
       \bbl@carg\bbl@sreplace{the##1}{.}{\bbl@map@lbl{.}}%
       \expandafter\ifx\csname the##1\endcsname\bbl@tempd\else
         \bbl@exp{\gdef\<the##1>{{\[the##1]}}}%
       \fi}}}%
    \edef\bbl@tempb{enumi,enumii,enumiii,enumiv}%
    \bbl@foreach\bbl@tempb{%
        \bbl@ifunset{label##1}{}%
      {{\bbl@ncarg\let\bbl@tempd{label##1}%
       \bbl@carg\bbl@sreplace{label##1}{.}{\bbl@map@lbl{.}}%
       \expandafter\ifx\csname label##1\endcsname\bbl@tempd\else
         \bbl@exp{\gdef\<label##1>{{\[label##1]}}}%
       \fi}}}%
  \fi
  % == Casing ==
  \bbl@release@casing
  \ifx\bbl@KVP@casing\@nnil\else
    \bbl@csarg\xdef{casing@\languagename}%
      {\@nameuse{bbl@casing@\languagename}\bbl@maybextx\bbl@KVP@casing}%
  \fi
  % == Calendars ==
  \ifx\bbl@KVP@calendar\@nnil
    \edef\bbl@KVP@calendar{\bbl@cl{calpr}}%
  \fi
  \def\bbl@tempe##1 ##2\@@{% Get first calendar
    \def\bbl@tempa{##1}}%
    \bbl@exp{\\\bbl@tempe\bbl@KVP@calendar\space\\\@@}%
  \def\bbl@tempe##1.##2.##3.##4\@@{%
      \def\bbl@tempf{##3}% First
      \let\bbl@tempc\@empty \let\bbl@tempb\@empty
      \bbl@cal@getconvert\bbl@tempc{##1}%
      \bbl@cal@getconvert\bbl@tempb{##2}}%
  \expandafter\bbl@tempe\bbl@tempa...\@@
  \bbl@csarg\edef{calpr@\languagename}{%
    \ifx\bbl@tempc\@empty\else
      calendar=\bbl@tempc
    \fi
    \ifx\bbl@tempb\@empty\else
      ,variant=\bbl@tempb
    \fi
    \ifx\bbl@tempf\@empty\else
      ,convert=\bbl@tempf
    \fi}%
  % == engine specific extensions ==
  % Defined in XXXbabel.def
  \bbl@provide@extra{#2}%
  % == require.babel in ini ==
  % To load or reaload the babel-*.tex, if require.babel in ini
  \ifx\bbl@beforestart\relax\else  % But not in doc aux or body
```

```
    \bbl@ifunset{bbl@rqtex@\languagename}{}%
      {\expandafter\ifx\csname bbl@rqtex@\languagename\endcsname\@empty\else
         \let\BabelBeforeIni\@gobbletwo
         \chardef\atcatcode=\catcode`\@
         \catcode`\@=11\relax
         \def\CurrentOption{#2}%
         \bbl@input@texini{\bbl@cs{rqtex@\languagename}}%
         \catcode`\@=\atcatcode
         \let\atcatcode\relax
         \global\bbl@csarg\let{rqtex@\languagename}\relax
       \fi}%
    \bbl@foreach\bbl@calendars{%
      \bbl@ifunset{bbl@ca@##1}{%
        \chardef\atcatcode=\catcode`\@
        \catcode`\@=11\relax
        \InputIfFileExists{babel-ca-##1.tex}{}{}%
        \catcode`\@=\atcatcode
        \let\atcatcode\relax}%
      {}}%
  \fi
  % == frenchspacing ==
  \ifcase\bbl@howloaded\in@true\else\in@false\fi
  \ifin@\else\bbl@xin@{typography/frenchspacing}{\bbl@key@list}\fi
  \ifin@
    \bbl@extras@wrap{\\\bbl@pre@fs}%
      {\bbl@pre@fs}%
      {\bbl@post@fs}%
  \fi
  % == transforms ==
  % > luababel.def
  \def\CurrentOption{#2}%
  \@nameuse{bbl@icsave@#2}%
  % == main ==
  \ifx\bbl@KVP@main\@nnil  % Restore only if not 'main'
    \let\languagename\bbl@savelangname
    \chardef\localeid\bbl@savelocaleid\relax
  \fi
  % == ==
  \ifx\ldf@finish\@onlypreamble\else
    \bbl@afterload
  \fi
  % == hyphenrules (apply if current) ==
  \ifx\bbl@KVP@hyphenrules\@nnil\else
    \ifnum\bbl@savelocaleid=\localeid
      \language\@nameuse{l@\languagename}%
    \fi
  \fi}
```

Depending on whether or not the language exists (based on `\date`⟨*language*⟩), we define two macros. Remember `\bbl@startcommands` opens a group.

```
\def\bbl@provide@new#1{%
  \@namedef{date#1}{}% marks lang exists - required by \StartBabelCommands
  \@namedef{extras#1}{}%
  \@namedef{noextras#1}{}%
  \bbl@startcommands*{#1}{captions}%
    \ifx\bbl@KVP@captions\@nnil %     and also if import, implicit
      \def\bbl@tempb##1{%             elt for \bbl@captionslist
        \ifx##1\@nnil\else
          \bbl@exp{%
            \\\SetString\\##1{%
              \\\bbl@nocaption{\bbl@stripslash##1}{#1\bbl@stripslash##1}}}%
          \expandafter\bbl@tempb
        \fi}%
```

```
      \expandafter\bbl@tempb\bbl@captionslist\@nnil
    \else
      \ifx\bbl@initoload\relax
        \bbl@read@ini{\bbl@KVP@captions}2%  % Here letters cat = 11
      \else
        \bbl@read@ini{\bbl@initoload}2%     % Same
      \fi
    \fi
  \StartBabelCommands*{#1}{date}%
    \ifx\bbl@KVP@date\@nnil
      \bbl@exp{%
        \\\SetString\\\today{\\\bbl@nocaption{today}{#1today}}}%
    \else
      \bbl@savetoday
      \bbl@savedate
    \fi
  \bbl@endcommands
  \bbl@load@basic{#1}%
  % == hyphenmins == (only if new)
  \bbl@exp{%
    \gdef\<#1hyphenmins>{%
      {\bbl@ifunset{bbl@lfthm@#1}{2}{\bbl@cs{lfthm@#1}}}%
      {\bbl@ifunset{bbl@rgthm@#1}{3}{\bbl@cs{rgthm@#1}}}}}%
  % == hyphenrules (also in renew) ==
  \bbl@provide@hyphens{#1}%
  % == main ==
  \ifx\bbl@KVP@main\@nnil\else
     \expandafter\main@language\expandafter{#1}%
  \fi}
%
\def\bbl@provide@renew#1{%
  \ifx\bbl@KVP@captions\@nnil\else
    \StartBabelCommands*{#1}{captions}%
      \bbl@read@ini{\bbl@KVP@captions}2%   % Here all letters cat = 11
    \EndBabelCommands
  \fi
  \ifx\bbl@KVP@date\@nnil\else
    \StartBabelCommands*{#1}{date}%
      \bbl@savetoday
      \bbl@savedate
    \EndBabelCommands
  \fi
  % == hyphenrules (also in new) ==
  \ifx\bbl@lbkflag\@empty
    \bbl@provide@hyphens{#1}%
  \fi
  % == main ==
  \ifx\bbl@KVP@main\@nnil\else
     \expandafter\main@language\expandafter{#1}%
  \fi}
```

Load the basic parameters (ids, typography, counters, and a few more), while captions and dates are left out. But it may happen some data has been loaded before automatically, so we first discard the saved values.

```
\def\bbl@load@basic#1{%
  \ifcase\bbl@howloaded\or\or
    \ifcase\csname bbl@llevel@\languagename\endcsname
      \bbl@csarg\let{lname@\languagename}\relax
    \fi
  \fi
  \bbl@ifunset{bbl@lname@#1}%
    {\def\BabelBeforeIni##1##2{%
       \begingroup
```

```
        \let\bbl@ini@captions@aux\@gobbletwo
        \def\bbl@inidate ####1.####2.####3.####4\relax ####5####6{}%
        \bbl@read@ini{##1}1%
        \ifx\bbl@initoload\relax\endinput\fi
      \endgroup}%
    \begingroup       % boxed, to avoid extra spaces:
      \ifx\bbl@initoload\relax
        \bbl@input@texini{#1}%
      \else
        \setbox\z@\hbox{\BabelBeforeIni{\bbl@initoload}{}}%
      \fi
    \endgroup}%
  {}}
```

The following `ini` reader ignores everything but the `identification` section. It is called when a font is defined (i.e., when the language is first selected) to know which script/language must be enabled. This means we must make sure a few characters are not active. The `ini` is not read directly, but with a proxy `tex` file named as the language (which means any code in it must be skipped, too).

```
\def\bbl@load@info#1{%
  \def\BabelBeforeIni##1##2{%
    \begingroup
      \bbl@read@ini{##1}0%
      \endinput          % babel- .tex may contain onlypreamble's
    \endgroup}%            boxed, to avoid extra spaces:
  {\bbl@input@texini{#1}}}
```

The `hyphenrules` option is handled with an auxiliary macro. This macro is called in three cases: when a language is first declared with `\babelprovide`, with `hyphenrules` and with `import`.

```
\def\bbl@provide@hyphens#1{%
  \@tempcnta\m@ne  % a flag
  \ifx\bbl@KVP@hyphenrules\@nnil\else
    \bbl@replace\bbl@KVP@hyphenrules{ }{,}%
    \bbl@foreach\bbl@KVP@hyphenrules{%
      \ifnum\@tempcnta=\m@ne   % if not yet found
        \bbl@ifsamestring{##1}{+}%
          {\bbl@carg\addlanguage{l@##1}}%
          {}%
        \bbl@ifunset{l@##1}% After a possible +
          {}%
          {\@tempcnta\@nameuse{l@##1}}%
      \fi}%
    \ifnum\@tempcnta=\m@ne
      \bbl@warning{%
        Requested 'hyphenrules' for '\languagename' not found:\\%
        \bbl@KVP@hyphenrules.\\%
        Using the default value. Reported}%
    \fi
  \fi
  \ifnum\@tempcnta=\m@ne          % if no opt or no language in opt found
    \ifx\bbl@KVP@captions@@\@nnil
      \bbl@ifunset{bbl@hyphr@#1}{}% use value in ini, if exists
        {\bbl@exp{\\\bbl@ifblank{\bbl@cs{hyphr@#1}}}%
           {}%
           {\bbl@ifunset{l@\bbl@cl{hyphr}}%
             {}%                   if hyphenrules found:
             {\@tempcnta\@nameuse{l@\bbl@cl{hyphr}}}}}%
    \fi
  \fi
  \bbl@ifunset{l@#1}%
    {\ifnum\@tempcnta=\m@ne
       \bbl@carg\adddialect{l@#1}\language
     \else
       \bbl@carg\adddialect{l@#1}\@tempcnta
     \fi}%
```

```
    {\ifnum\@tempcnta=\m@ne\else
       \global\bbl@carg\chardef{l@#1}\@tempcnta
     \fi}}
```

The reader of `babel-...tex` files. We reset temporarily some catcodes (and make sure no space is accidentally inserted).

```
\def\bbl@input@texini#1{%
  \bbl@bsphack
    \bbl@exp{%
      \catcode`\\\%=14 \catcode`\\\\=0
      \catcode`\\\{=1  \catcode`\\\}=2
      \lowercase{\\\InputIfFileExists{babel-#1.tex}{}{}}%
      \catcode`\\\%=\the\catcode`\%\relax
      \catcode`\\\\=\the\catcode`\\\relax
      \catcode`\\\{=\the\catcode`\{\relax
      \catcode`\\\}=\the\catcode`\}\relax}%
  \bbl@esphack}
```

The following macros read and store `ini` files (but don't process them). For each line, there are 3 possible actions: ignore if starts with `;`, switch section if starts with `[`, and store otherwise. There are used in the first step of `\bbl@read@ini`.

```
\def\bbl@iniline#1\bbl@iniline{%
  \@ifnextchar[\bbl@inisect{\@ifnextchar;\bbl@iniskip\bbl@inistore}#1\@@}% ]
\def\bbl@inisect[#1]#2\@@{\def\bbl@section{#1}}
\def\bbl@iniskip#1\@@{}%      if starts with ;
\def\bbl@inistore#1=#2\@@{%       full (default)
  \bbl@trim@def\bbl@tempa{#1}%
  \bbl@trim\toks@{#2}%
  \bbl@ifsamestring{\bbl@tempa}{@include}%
    {\bbl@read@subini{\the\toks@}}%
    {\bbl@xin@{;\bbl@section/\bbl@tempa;}{\bbl@key@list}%
     \ifin@\else
       \bbl@xin@{,identification/include.}%
                {,\bbl@section/\bbl@tempa}%
       \ifin@\xdef\bbl@included@inis{\the\toks@}\fi
       \bbl@exp{%
         \\\g@addto@macro\\\bbl@inidata{%
           \\\bbl@elt{\bbl@section}{\bbl@tempa}{\the\toks@}}}%
     \fi}}
\def\bbl@inistore@min#1=#2\@@{%  minimal (maybe set in \bbl@read@ini)
  \bbl@trim@def\bbl@tempa{#1}%
  \bbl@trim\toks@{#2}%
  \bbl@xin@{.identification.}{.\bbl@section.}%
  \ifin@
    \bbl@exp{\\\g@addto@macro\\\bbl@inidata{%
      \\\bbl@elt{identification}{\bbl@tempa}{\the\toks@}}}%
  \fi}
```

3.24. Main loop in 'provide'

Now, the 'main loop', `\bbl@read@ini`, which ****must be executed inside a group****. At this point, `\bbl@inidata` may contain data declared in `\babelprovide`, with 'slashed' keys. There are 3 steps: first read the ini file and store it; then traverse the stored values, and process some groups if required (date, captions, labels, counters); finally, 'export' some values by defining global macros (identification, typography, characters, numbers). The second argument is 0 when called to read the minimal data for fonts; with `\babelprovide` it's either 1 (without `import`) or 2 (which `import`). The value -1 is used with `\DocumentMetadata`.

`\bbl@loop@ini` is the reader, line by line (1: stream), and calls `\bbl@iniline` to save the key/value pairs. If `\bbl@inistore` finds the `@include` directive, the input stream is switched temporarily and `\bbl@read@subini` is called.

When the language is being set based on the document metadata (#2 in `\bbl@read@ini` is -1), there is an interlude to get the name, after the data have been collected, and before it's processed.

```
\def\bbl@loop@ini#1{%
```

```
  \loop
    \if T\ifeof#1 F\fi T\relax % Trick, because inside \loop
      \endlinechar\m@ne
      \read#1 to \bbl@line
      \endlinechar`\^^M
      \ifx\bbl@line\@empty\else
        \expandafter\bbl@iniline\bbl@line\bbl@iniline
      \fi
    \repeat}
%
\def\bbl@read@subini#1{%
  \ifx\bbl@readsubstream\@undefined
    \csname newread\endcsname\bbl@readsubstream
  \fi
  \openin\bbl@readsubstream=babel-#1.ini
  \ifeof\bbl@readsubstream
    \bbl@error{no-ini-file}{#1}{}{}%
  \else
    {\bbl@loop@ini\bbl@readsubstream}%
  \fi
  \closein\bbl@readsubstream}
%
\ifx\bbl@readstream\@undefined
  \csname newread\endcsname\bbl@readstream
\fi
\def\bbl@read@ini#1#2{%
  \global\let\bbl@extend@ini\@gobble
  \openin\bbl@readstream=babel-#1.ini
  \ifeof\bbl@readstream
    \bbl@error{no-ini-file}{#1}{}{}%
  \else
    % == Store ini data in \bbl@inidata ==
    \catcode`\ =10 \catcode`\"=12
    \catcode`\[=12 \catcode`\]=12 \catcode`\==12 \catcode`\&=12
    \catcode`\;=12 \catcode`\|=12 \catcode`\%=14 \catcode`\-=12
    \ifnum#2=\m@ne % Just for the info
      \edef\languagename{tag \bbl@metalang}%
    \fi
    \ifnum#2=\m@ne
      \bbl@info{Metadata: '\bbl@metalang' requested, '#1' provided.\\%
                Fetching the locale name from babel-#1.ini\@gobble}%
    \else
      \bbl@info{Importing
                \ifcase#2font and identification \or basic \fi
                data for '\languagename'\\%
                from babel-#1.ini. Reported}%
    \fi
    \ifnum#2<\@ne
      \global\let\bbl@inidata\@empty
      \let\bbl@inistore\bbl@inistore@min  % Remember it's local
    \fi
    \def\bbl@section{identification}%
    \bbl@exp{%
      \\\bbl@inistore tag.ini=#1\\\@@
      \\\bbl@inistore load.level=\ifnum#2<\@ne 0\else #2\fi\\\@@}%
    \bbl@loop@ini\bbl@readstream
    % == Process stored data ==
    \ifnum#2=\m@ne
      \def\bbl@tempa##1 ##2\@@{##1}% Get first name
      \def\bbl@elt##1##2##3{%
        \bbl@ifsamestring{identification/name.babel}{##1/##2}%
          {\edef\languagename{\bbl@tempa##3 \@@}%
           \let\localename\languagename
```

```
           \bbl@id@assign
           \def\bbl@elt####1####2####3{}%
          {}}%
      \bbl@inidata
    \fi
    \bbl@csarg\xdef{lini@\languagename}{#1}%
    \bbl@read@ini@aux
    % == 'Export' data ==
    \bbl@ini@exports{#2}%
    \global\bbl@csarg\let{inidata@\languagename}\bbl@inidata
    \global\let\bbl@inidata\@empty
    \bbl@xin@{,\languagename,}{,\bbl@ini@loaded,}%
    \ifin@\else
      \bbl@exp{\\\bbl@add@list\\\bbl@ini@loaded{\languagename}}%
      \bbl@toglobal\bbl@ini@loaded
    \fi
    \@ifpackagewith{babel}{licr=unextended}{}%
      {\ifcase\bbl@engine\else % Find a better place
         \bbl@xin@{,\bbl@cl{sbcp},}{,Cyrl,}%
         \ifin@
           \bbl@once{licr-cryl}{\g@addto@macro\bbl@afterload{\input{cyrl2uni.def}}}%
         \fi
       \fi}%
  \fi
  \closein\bbl@readstream}
\def\bbl@read@ini@aux{%
  \let\bbl@savestrings\@empty
  \let\bbl@savetoday\@empty
  \let\bbl@savedate\@empty
  \def\bbl@elt##1##2##3{%
    \def\bbl@section{##1}%
    \in@{=date.}{=##1}% Find a better place
    \ifin@
      \bbl@ifunset{bbl@inikv@##1}%
        {\bbl@ini@calendar{##1}}%
        {}%
    \fi
    \bbl@ifunset{bbl@inikv@##1}{}%
      {\csname bbl@inikv@##1\endcsname{##2}{##3}}}%
  \bbl@inidata}
```

A variant to be used when the ini file has been already loaded, because it's not the first `\babelprovide` for this language.

```
\def\bbl@extend@ini@aux#1{%
  \bbl@startcommands*{#1}{captions}%
    % Activate captions/... and modify exports
    \bbl@csarg\def{inikv@captions.licr}##1##2{%
      \setlocalecaption{#1}{##1}{##2}}%
    \def\bbl@inikv@captions##1##2{%
      \bbl@ini@captions@aux{##1}{##2}}%
    \def\bbl@stringdef##1##2{\gdef##1{##2}}%
    \def\bbl@exportkey##1##2##3{%
      \bbl@ifunset{bbl@@kv@##2}{}%
        {\expandafter\ifx\csname bbl@@kv@##2\endcsname\@empty\else
           \bbl@exp{\global\let\<bbl@##1@\languagename>\<bbl@@kv@##2>}%
         \fi}}%
    % As with \bbl@read@ini, but with some changes
    \bbl@read@ini@aux
    \bbl@ini@exports\tw@
    % Update inidata@lang by pretending the ini is read.
    \def\bbl@elt##1##2##3{%
      \def\bbl@section{##1}%
      \bbl@iniline##2=##3\bbl@iniline}%
```

```
    \csname bbl@inidata@#1\endcsname
    \global\bbl@csarg\let{inidata@#1}\bbl@inidata
  \StartBabelCommands*{#1}{date}% And from the import stuff
    \def\bbl@stringdef##1##2{\gdef##1{##2}}%
    \bbl@savetoday
    \bbl@savedate
  \bbl@endcommands}
```

A somewhat hackish tool to handle calendar sections.

```
\def\bbl@ini@calendar#1{%
 \lowercase{\def\bbl@tempa{=#1=}}%
 \bbl@replace\bbl@tempa{=date.gregorian}{}%
 \bbl@replace\bbl@tempa{=date.}{}%
 \in@{.licr=}{#1=}%
 \ifin@
   \ifcase\bbl@engine
     \bbl@replace\bbl@tempa{.licr=}{}%
   \else
     \let\bbl@tempa\relax
   \fi
 \fi
 \ifx\bbl@tempa\relax\else
   \bbl@replace\bbl@tempa{=}{}%
   \ifx\bbl@tempa\@empty\else
     \xdef\bbl@calendars{\bbl@calendars,\bbl@tempa}%
   \fi
   \bbl@exp{%
     \def\<bbl@inikv@#1>####1####2{%
       \\\bbl@inidate####1...\relax{####2}{\bbl@tempa}}}%
 \fi}
```

A key with a slash in `\babelprovide` replaces the value in the `ini` file (which is ignored altogether). The mechanism is simple (but suboptimal): add the data to the `ini` one (at this point the `ini` file has not yet been read), and define a dummy macro. When the `ini` file is read, just skip the corresponding key and reset the macro (in `\bbl@inistore` above).

```
\def\bbl@renewinikey#1/#2\@@#3{%
  \global\let\bbl@extend@ini\bbl@extend@ini@aux
  \edef\bbl@tempa{\zap@space #1 \@empty}%   section
  \edef\bbl@tempb{\zap@space #2 \@empty}%   key
  \bbl@trim\toks@{#3}%                      value
  \bbl@exp{%
    \edef\\\bbl@key@list{\bbl@key@list \bbl@tempa/\bbl@tempb;}%
    \\\g@addto@macro\\\bbl@inidata{%
       \\\bbl@elt{\bbl@tempa}{\bbl@tempb}{\the\toks@}}}%
```

The previous assignments are local, so we need to export them. If the value is empty, we can provide a default value.

```
\def\bbl@exportkey#1#2#3{%
  \bbl@ifunset{bbl@@kv@#2}%
    {\bbl@csarg\gdef{#1@\languagename}{#3}}%
    {\expandafter\ifx\csname bbl@@kv@#2\endcsname\@empty
       \bbl@csarg\gdef{#1@\languagename}{#3}%
     \else
       \bbl@exp{\global\let\<bbl@#1@\languagename>\<bbl@@kv@#2>}%
     \fi}}
```

Key-value pairs are treated differently depending on the section in the `ini` file. The following macros are the readers for `identification` and `typography`. Note `\bbl@ini@exports` is called always (via `\bbl@inisec`), while `\bbl@after@ini` must be called explicitly after `\bbl@read@ini` if necessary.

Although BCP 47 doesn't treat '-x-' as an extension, the CLDR and many other sources do (as a *private use extension*). For consistency with other single-letter subtags or 'singletons', here is considered an extension, too.

The identification section is used internally by babel in the following places [to be completed]: BCP 47 script tag in the Unicode ranges, which is in turn used by `onchar`; the language system is set with

the names, and then fontspec maps them to the opentype tags, but if the latter package doesn't define them, then babel does it; `encodings` are used in pdftex to select a font encoding valid (and preloaded) for a language loaded on the fly.

```
\def\bbl@iniwarning#1{%
  \bbl@ifunset{bbl@@kv@identification.warning#1}{}%
    {\bbl@warning{%
       From babel-\bbl@cs{lini@\languagename}.ini:\\%
       \bbl@cs{@kv@identification.warning#1}\\%
       Reported}}}
%
\let\bbl@release@transforms\@empty
\let\bbl@release@casing\@empty
```

Relevant keys are 'exported', i.e., global macros with short names are created with values taken from the corresponding keys. The number of exported keys depends on the loading level (#1): -1 and 0 only info (the identificacion section), 1 also basic (like linebreaking or character ranges), 2 also (re)new (with date and captions).

```
\def\bbl@ini@exports#1{%
  % Identification always exported
  \bbl@iniwarning{}%
  \ifcase\bbl@engine
    \bbl@iniwarning{.pdflatex}%
  \or
    \bbl@iniwarning{.lualatex}%
  \or
    \bbl@iniwarning{.xelatex}%
  \fi%
  \bbl@exportkey{llevel}{identification.load.level}{}%
  \bbl@exportkey{elname}{identification.name.english}{}%
  \bbl@exp{\\\bbl@exportkey{lname}{identification.name.opentype}%
    {\csname bbl@elname@\languagename\endcsname}}%
  \bbl@exportkey{tbcp}{identification.tag.bcp47}{}%
  \bbl@exportkey{casing}{identification.tag.bcp47}{}%
  \bbl@exportkey{lbcp}{identification.language.tag.bcp47}{}%
  \bbl@exportkey{lotf}{identification.tag.opentype}{dflt}%
  \bbl@exportkey{esname}{identification.script.name}{}%
  \bbl@exp{\\\bbl@exportkey{sname}{identification.script.name.opentype}%
    {\csname bbl@esname@\languagename\endcsname}}%
  \bbl@exportkey{sbcp}{identification.script.tag.bcp47}{}%
  \bbl@exportkey{sotf}{identification.script.tag.opentype}{DFLT}%
  \bbl@exportkey{rbcp}{identification.region.tag.bcp47}{}%
  \bbl@exportkey{vbcp}{identification.variant.tag.bcp47}{}%
  \bbl@exportkey{extt}{identification.extension.t.tag.bcp47}{}%
  \bbl@exportkey{extu}{identification.extension.u.tag.bcp47}{}%
  \bbl@exportkey{extx}{identification.extension.x.tag.bcp47}{}%
  % Also maps bcp47 -> languagename
  \bbl@csarg\xdef{bcp@map@\bbl@cl{tbcp}}{\languagename}%
  \ifcase\bbl@engine\or
    \directlua{%
      Babel.locale_props[\the\bbl@cs{id@@\languagename}].script
        = '\bbl@cl{sbcp}'}%
  \fi
  % Conditional
  \ifnum#1>\z@      % -1 or 0 = only info, 1 = basic, 2 = (re)new
    \bbl@exportkey{calpr}{date.calendar.preferred}{}%
    \bbl@exportkey{lnbrk}{typography.linebreaking}{h}%
    \bbl@exportkey{hyphr}{typography.hyphenrules}{}%
    \bbl@exportkey{lfthm}{typography.lefthyphenmin}{2}%
    \bbl@exportkey{rgthm}{typography.righthyphenmin}{3}%
    \bbl@exportkey{prehc}{typography.prehyphenchar}{}%
    \bbl@exportkey{hyotl}{typography.hyphenate.other.locale}{}%
    \bbl@exportkey{hyots}{typography.hyphenate.other.script}{}%
    \bbl@exportkey{intsp}{typography.intraspace}{}%
```

```
    \bbl@exportkey{frspc}{typography.frenchspacing}{u}%
    \bbl@exportkey{chrng}{characters.ranges}{}%
    \bbl@exportkey{quote}{characters.delimiters.quotes}{}%
    \bbl@exportkey{dgnat}{numbers.digits.native}{}%
    \ifnum#1=\tw@           % only (re)new
      \bbl@exportkey{rqtex}{identification.require.babel}{}%
      \bbl@toglobal\bbl@savetoday
      \bbl@toglobal\bbl@savedate
      \bbl@savestrings
    \fi
  \fi}
```

3.25. Processing keys in `ini`

A shared handler for key=val lines to be stored in `\bbl@@kv@`⟨*section*⟩`.`⟨*key*⟩.

```
\def\bbl@inikv#1#2{%     key=value
  \toks@{#2}%            This hides #'s from ini values
  \bbl@csarg\edef{@kv@\bbl@section.#1}{\the\toks@}}
```

By default, the following sections are just read. Actions are taken later.

```
\let\bbl@inikv@identification\bbl@inikv
\let\bbl@inikv@date\bbl@inikv
\let\bbl@inikv@typography\bbl@inikv
\let\bbl@inikv@numbers\bbl@inikv
```

The `characters` section also stores the values, but `casing` is treated in a different fashion. Much like transforms, a set of commands calling the parser are stored in `\bbl@release@casing`, which is executed in `\babelprovide`.

```
\def\bbl@maybextx{-\bbl@csarg\ifx{extx@\languagename}\@empty x-\fi}
\def\bbl@inikv@characters#1#2{%
  \bbl@ifsamestring{#1}{casing}%  e.g., casing = uV
    {\bbl@exp{%
       \\\g@addto@macro\\\bbl@release@casing{%
         \\\bbl@casemapping{}{\languagename}{\unexpanded{#2}}}}}%
    {\in@{$casing.}{$#1}%  e.g., casing.Uv = uV
     \ifin@
       \lowercase{\def\bbl@tempb{#1}}%
       \bbl@replace\bbl@tempb{casing.}{}%
       \bbl@exp{\\\g@addto@macro\\\bbl@release@casing{%
         \\\bbl@casemapping
           {\\\bbl@maybextx\bbl@tempb}{\languagename}{\unexpanded{#2}}}}%
     \else
       \bbl@inikv{#1}{#2}%
     \fi}}
```

Additive numerals require an additional definition. When `.1` is found, two macros are defined – the basic one, without `.1` called by `\localenumeral`, and another one preserving the trailing `.1` for the 'units'. The asterisk is a 'terminator'.

```
\def\bbl@inikv@counters#1#2{%
  \bbl@ifsamestring{#1}{digits}%
    {\bbl@error{digits-is-reserved}{}{}{}}%
    {}%
  \def\bbl@tempc{#1}%
  \bbl@trim@def{\bbl@tempb*}{#2}%
  \in@{.1$}{#1$}%
  \ifin@
    \bbl@replace\bbl@tempc{.1}{}%
    \bbl@csarg\protected@xdef{cntr@\bbl@tempc @\languagename}{%
      \noexpand\bbl@alphnumeral{\bbl@tempc}}%
  \fi
  \in@{.F.}{#1}%
  \ifin@\else\in@{.S.}{#1}\fi
  \ifin@
```

```
    \bbl@csarg\protected@xdef{cntr@#1@\languagename}{\bbl@tempb*}%
  \else
    \toks@{}% Required by \bbl@buildifcase, which returns \bbl@tempa
    \expandafter\bbl@buildifcase\bbl@tempb* \\ % Space after \\
    \bbl@csarg{\global\expandafter\let}{cntr@#1@\languagename}\bbl@tempa
  \fi
  \in@{.D$}{#1$}%
  \ifin@\else\in@{.C$}{#1$}\fi
  \ifin@
    \bbl@replace\bbl@tempc{.D}{}%
    \bbl@replace\bbl@tempc{.C}{}%
    \bbl@exp{\gdef\<bbl@cntr@\bbl@tempc @\languagename>####1{%
      \\\expandafter\\\bbl@zhnumeral\\\expandafter{\\\number####1}{\bbl@tempc}}}%
  \fi}
```

Now `captions` and `captions.licr`, depending on the engine. And below also for dates. They rely on a few auxiliary macros. It is expected the ini file provides the complete set in Unicode and LICR, in that order.

```
\ifcase\bbl@engine
  \bbl@csarg\def{inikv@captions.licr}#1#2{%
    \bbl@ini@captions@aux{#1}{#2}}
\else
  \def\bbl@inikv@captions#1#2{%
    \bbl@ini@captions@aux{#1}{#2}}
\fi
```

The auxiliary macro for captions define \⟨*caption*⟩`name`.

```
\def\bbl@ini@captions@template#1#2{% string language tempa=capt-name
  \bbl@replace\bbl@tempa{.template}{}%
  \def\bbl@toreplace{#1{}}%
  \bbl@replace\bbl@toreplace{[ ]}{\nobreakspace{}}%
  \bbl@replace\bbl@toreplace{[[]}{\csname}%
  \bbl@replace\bbl@toreplace{[}{\csname the}%
  \bbl@replace\bbl@toreplace{]]}{name\endcsname{}}%
  \bbl@replace\bbl@toreplace{]}{\endcsname{}}%
  \bbl@xin@{,\bbl@tempa,}{,chapter,appendix,part,}%
  \ifin@
    \@nameuse{bbl@patch\bbl@tempa}%
    \global\bbl@csarg\let{\bbl@tempa fmt@#2}\bbl@toreplace
  \fi
  \bbl@xin@{,\bbl@tempa,}{,figure,table,}%
  \ifin@
    \global\bbl@csarg\let{\bbl@tempa fmt@#2}\bbl@toreplace
    \bbl@exp{\gdef\<fnum@\bbl@tempa>{%
      \\\bbl@ifunset{bbl@\bbl@tempa fmt@\\\languagename}%
        {\[fnum@\bbl@tempa]}%
        {\\\@nameuse{bbl@\bbl@tempa fmt@\\\languagename}}}}%
  \fi}
%
\def\bbl@ini@captions@aux#1#2{%
  \bbl@trim@def\bbl@tempa{#1}%
  \bbl@xin@{.template}{\bbl@tempa}%
  \ifin@
    \bbl@ini@captions@template{#2}\languagename
  \else
    \bbl@ifblank{#2}%
      {\bbl@exp{%
         \toks@{\\\bbl@nocaption{\bbl@tempa name}{\languagename\bbl@tempa name}}}}%
      {\bbl@trim\toks@{#2}}%
    \bbl@exp{%
      \\\bbl@add\\\bbl@savestrings{%
        \\\SetString\<\bbl@tempa name>{\the\toks@}}}%
    \toks@\expandafter{\bbl@captionslist}%
    \bbl@exp{\\\in@{\<\bbl@tempa name>}{\the\toks@}}%
```

```
    \ifin@\else
      \bbl@exp{%
        \\\bbl@add\<bbl@extracaps@\languagename>{\<\bbl@tempa name>}%
        \\\bbl@toglobal\<bbl@extracaps@\languagename>}%
    \fi
  \fi}
```

Labels. Captions must contain just strings, no format at all, so there is new group in ini files.

```
\def\bbl@list@the{%
  part,chapter,section,subsection,subsubsection,paragraph,%
  subparagraph,enumi,enumii,enumiii,enumiv,equation,figure,%
  table,page,footnote,mpfootnote,mpfn}
%
\def\bbl@map@cnt#1{%  #1:roman,etc, // #2:enumi,etc
  \bbl@ifunset{bbl@map@#1@\languagename}%
    {\@nameuse{#1}}%
    {\@nameuse{bbl@map@#1@\languagename}}}
%
\def\bbl@map@lbl#1{%  #1:a sign, eg, .
  \ifincsname#1\else
    \bbl@ifunset{bbl@map@@#1@@\languagename}%
      {#1}%
      {\@nameuse{bbl@map@@#1@@\languagename}}%
  \fi}
%
\def\bbl@inikv@labels#1#2{%
  \in@{.map}{#1}%
  \ifin@
    \in@{,dot.map,}{,#1,}%
    \ifin@
      \global\@namedef{bbl@map@@.@@\languagename}{#2}%
    \fi
    \ifx\bbl@KVP@labels\@nnil\else
      \bbl@xin@{ map }{ \bbl@KVP@labels\space}%
      \ifin@
        \def\bbl@tempc{#1}%
        \bbl@replace\bbl@tempc{.map}{}%
        \in@{,#2,}{,arabic,roman,Roman,alph,Alph,fnsymbol,}%
        \bbl@exp{%
          \gdef\<bbl@map@\bbl@tempc @\languagename>%
            {\ifin@\<#2>\else\\\localecounter{#2}\fi}}%
        \bbl@foreach\bbl@list@the{%
          \bbl@ifunset{the##1}{}%
            {\bbl@ncarg\let\bbl@tempd{the##1}%
            \bbl@exp{%
              \\\bbl@sreplace\<the##1>%
                {\<\bbl@tempc>{##1}}%
                {\\\bbl@map@cnt{\bbl@tempc}{##1}}%
              \\\bbl@sreplace\<the##1>%
                {\<\@empty @\bbl@tempc>\<c@##1>}%
                {\\\bbl@map@cnt{\bbl@tempc}{##1}}%
              \\\bbl@sreplace\<the##1>%
                {\\\csname @\bbl@tempc\\\endcsname\<c@##1>}%
                {{\\\bbl@map@cnt{\bbl@tempc}{##1}}}}%
             \expandafter\ifx\csname the##1\endcsname\bbl@tempd\else
               \bbl@exp{\gdef\<the##1>{{\[the##1]}}}%
             \fi}}%
      \fi
    \fi
%
  \else
    % The following code is still under study. You can test it and make
    % suggestions. E.g., enumerate.2 = ([enumi]).([enumii]). It's
```

```
    % language dependent.
    \in@{enumerate.}{#1}%
    \ifin@
      \def\bbl@tempa{#1}%
      \bbl@replace\bbl@tempa{enumerate.}{}%
      \def\bbl@toreplace{#2}%
      \bbl@replace\bbl@toreplace{[ ]}{\nobreakspace{}}%
      \bbl@replace\bbl@toreplace{[}{\csname the}%
      \bbl@replace\bbl@toreplace{]}{\endcsname{}}%
      \toks@\expandafter{\bbl@toreplace}%
      \bbl@exp{%
        \\\bbl@add\<extras\languagename>{%
          \\\babel@save\<labelenum\romannumeral\bbl@tempa>%
          \def\<labelenum\romannumeral\bbl@tempa>{\the\toks@}}%
        \\\bbl@toglobal\<extras\languagename>}%
    \fi
  \fi}
```

To show correctly some captions in a few languages, we need to patch some internal macros, because the order is hardcoded. For example, in Japanese the chapter number is surrounded by two string, while in Hungarian is placed after. These replacement works in many classes, but not all. Actually, the following lines are somewhat tentative.

```
\def\bbl@chaptype{chapter}
\ifx\@makechapterhead\@undefined
  \let\bbl@patchchapter\relax
\else\ifx\thechapter\@undefined
  \let\bbl@patchchapter\relax
\else\ifx\ps@headings\@undefined
  \let\bbl@patchchapter\relax
\else
  \def\bbl@patchchapter{%
    \global\let\bbl@patchchapter\relax
    \gdef\bbl@chfmt{%
      \bbl@ifunset{bbl@\bbl@chaptype fmt@\languagename}%
        {\@chapapp\space\thechapter}%
        {\@nameuse{bbl@\bbl@chaptype fmt@\languagename}}}%
    \bbl@add\appendix{\def\bbl@chaptype{appendix}}% Not harmful, I hope
    \bbl@sreplace\ps@headings{\@chapapp\ \thechapter}{\bbl@chfmt}%
    \bbl@sreplace\chaptermark{\@chapapp\ \thechapter}{\bbl@chfmt}%
    \bbl@sreplace\@makechapterhead{\@chapapp\space\thechapter}{\bbl@chfmt}%
    \bbl@toglobal\appendix
    \bbl@toglobal\ps@headings
    \bbl@toglobal\chaptermark
    \bbl@toglobal\@makechapterhead}
  \let\bbl@patchappendix\bbl@patchchapter
\fi\fi\fi
\ifx\@part\@undefined
  \let\bbl@patchpart\relax
\else
  \def\bbl@patchpart{%
    \global\let\bbl@patchpart\relax
    \gdef\bbl@partformat{%
      \bbl@ifunset{bbl@partfmt@\languagename}%
        {\partname\nobreakspace\thepart}%
        {\@nameuse{bbl@partfmt@\languagename}}}%
    \bbl@sreplace\@part{\partname\nobreakspace\thepart}{\bbl@partformat}%
    \bbl@toglobal\@part}
\fi
```

Date. Arguments (year, month, day) are *not* protected, on purpose. In `\today`, arguments are always gregorian, and therefore always converted with other calendars.

```
\def\bbl@cal@getconvert#1#2{% Used in provide
  \in@{:}{#2}%
  \ifin@\def\bbl@tempf{#2}\else\def#1{#2}\fi}
```

```
\let\bbl@calendar\@empty
\DeclareRobustCommand\localedate[1][]{\bbl@localedate{#1}}
\def\bbl@localedate#1#2#3#4{%
  \begingroup
    \edef\bbl@they{#2}%
    \edef\bbl@them{#3}%
    \edef\bbl@thed{#4}%
    \edef\bbl@tempe{%
      \bbl@ifunset{bbl@calpr@\languagename}{}{\bbl@cl{calpr}},%
      #1}%
    \bbl@exp{\lowercase{\edef\\\bbl@tempe{\bbl@tempe}}}%
    \let\bbl@ld@calendar\@empty
    \let\bbl@ld@variant\@empty
    \let\bbl@ld@convert\relax
    \let\bbl@ld@@convert\relax
    \expandafter\bbl@forkv\expandafter{\bbl@tempe}{\bbl@csarg\edef{ld@##1}{##2}}%
    \bbl@replace\bbl@ld@calendar{gregorian}{}%
    \ifx\bbl@ld@convert\relax
      \let\bbl@ld@convert\bbl@ld@@convert
    \fi
    \ifx\bbl@ld@convert\@empty
      \ifx\bbl@ld@calendar\@empty
        \let\bbl@ld@convert\relax
      \else
        \let\bbl@ld@convert\bbl@ld@calendar
      \fi
    \fi
    \ifx\bbl@ld@convert\relax\else
      \babelcalendar[\bbl@they-\bbl@them-\bbl@thed]%
        {\bbl@ld@convert}\bbl@they\bbl@them\bbl@thed
    \fi
    \@nameuse{bbl@precalendar}% Remove, e.g., +, -civil (-ca-islamic)
    \edef\bbl@calendar{% Used in \month..., too
      \bbl@ld@calendar
      \ifx\bbl@ld@variant\@empty\else
        .\bbl@ld@variant
      \fi}%
    \bbl@cased
      {\@nameuse{bbl@date@\languagename @\bbl@calendar}%
         \bbl@they\bbl@them\bbl@thed}%
  \endgroup}
%
\def\bbl@printdate#1{%
  \@ifnextchar[{\bbl@printdate@i{#1}}{\bbl@printdate@i{#1}[]}}
\def\bbl@printdate@i#1[#2]#3#4#5{%
  \bbl@usedategrouptrue
  \def\bbl@tempc{#1}%
  \bbl@replace\bbl@tempc{-}{@@}%
  \@nameuse{bbl@ensure@\bbl@tempc}{\localedate[#2]{#3}{#4}{#5}}}
%
% e.g.: 1=months, 2=wide, 3=1, 4=dummy, 5=value, 6=calendar
\def\bbl@inidate#1.#2.#3.#4\relax#5#6{%
  \bbl@trim@def\bbl@tempa{#1.#2}%
  \bbl@ifsamestring{\bbl@tempa}{months.wide}%      to savedate
    {\bbl@trim@def\bbl@tempa{#3}%
     \bbl@trim\toks@{#5}%
     \@temptokena\expandafter{\bbl@savedate}%
     \bbl@exp{%   Reverse order - in ini last wins
       \def\\\bbl@savedate{%
         \\\SetString\<month\romannumeral\bbl@tempa#6name>{\the\toks@}%
         \the\@temptokena}}}%
    {\bbl@ifsamestring{\bbl@tempa}{date.long}%     defined now
      {\lowercase{\def\bbl@tempb{#6}}%
```

```
      \bbl@trim@def\bbl@toreplace{#5}%
      \bbl@TG@@date
      \global\bbl@csarg\let{date@\languagename @\bbl@tempb}\bbl@toreplace
      \ifx\bbl@savetoday\@empty
        \bbl@exp{%
          \\\AfterBabelCommands{%
            \gdef\<\languagename date>{\\\protect\<\languagename date >}%
            \gdef\<\languagename date >{\\\bbl@printdate{\languagename}}}%
          \def\\\bbl@savetoday{%
            \\\SetString\\\today{%
              \<\languagename date>[@convert]%
                 {\\\the\year}{\\\the\month}{\\\the\day}}}}%
      \fi}%
     {}}}
```

Dates will require some macros for the basic formatting. They may be redefined by language, so "semi-public" names (camel case) are used. Oddly enough, the CLDR places particles like "de" inconsistently in either in the date or in the month name. Note after `\bbl@replace` `\toks@` contains the resulting string, which is used by `\bbl@replace@finish@iii` (this implicit behavior doesn't seem a good idea, but it's efficient).

```
\let\bbl@calendar\@empty
\newcommand\babelcalendar[2][\the\year-\the\month-\the\day]{%
  \bbl@xin@{$calendrica:}{$#2}%
  \ifin@
    \directlua{Babel.calendrica = Babel.calendrica or require("calendrica")}%
    \edef\bbl@tempa{$#2}%
    \bbl@replace\bbl@tempa{$calendrica:}{}%
    \bbl@afterelse
    \bbl@exp{\\\bbl@calendrica#1\\\@@{\bbl@tempa}}%
  \else
    \bbl@afterfi
    \@nameuse{bbl@ca@#2}#1\@@
  \fi}
\def\bbl@calendrica#1-#2-#3\@@#4#5#6#7{%
  \directlua{
    local r = Babel.calendrica.date(
      {year=\number#1, month=\number#2, day=\number#3},
      'gregorian'):to('#4')
    token.set_macro('\bbl@stripslash#5', tostring(r.year))
    token.set_macro('\bbl@stripslash#6', tostring(r.month))
    token.set_macro('\bbl@stripslash#7', tostring(r.day))
  }}
\newcommand\BabelDateSpace{\nobreakspace}
\newcommand\BabelDateDot{.\@}
\newcommand\BabelDated[1]{{\number#1}}
\newcommand\BabelDatedd[1]{{\ifnum#1<10 0\fi\number#1}}
\newcommand\BabelDateM[1]{{\number#1}}
\newcommand\BabelDateMM[1]{{\ifnum#1<10 0\fi\number#1}}
\newcommand\BabelDateMMMM[1]{{%
  \csname month\romannumeral#1\bbl@calendar name\endcsname}}%
\newcommand\BabelDatey[1]{{\number#1}}%
\newcommand\BabelDateyy[1]{{%
  \ifnum#1<10 0\number#1 %
  \else\ifnum#1<100 \number#1 %
  \else\ifnum#1<1000 \expandafter\@gobble\number#1 %
  \else\ifnum#1<10000 \expandafter\@gobbletwo\number#1 %
  \else
    \bbl@error{limit-two-digits}{}{}{}%
  \fi\fi\fi\fi}}
\newcommand\BabelDateyyyy[1]{{\number#1}}
\newcommand\BabelDateU[1]{{\number#1}}%
\def\bbl@replace@finish@iii#1{%
  \bbl@exp{\def\\#1####1####2####3{\the\toks@}}}
```

```
\def\bbl@TG@@date{%
  \bbl@replace\bbl@toreplace{[ ]}{\BabelDateSpace{}}%
  \bbl@replace\bbl@toreplace{[.]}{\BabelDateDot{}}%
  \bbl@replace\bbl@toreplace{[y]}{\BabelDatey{####1}}%
  \bbl@replace\bbl@toreplace{[y|}{\bbl@datecntr[####1|}%
  \bbl@replace\bbl@toreplace{[yy]}{\BabelDateyy{####1}}%
  \bbl@replace\bbl@toreplace{[yyyy]}{\BabelDateyyyy{####1}}%
  \bbl@replace\bbl@toreplace{[M]}{\BabelDateM{####2}}%
  \bbl@replace\bbl@toreplace{[M|}{\bbl@datecntr[####2|}%
  \bbl@replace\bbl@toreplace{[MM]}{\BabelDateMM{####2}}%
  \bbl@replace\bbl@toreplace{[MMMM]}{\BabelDateMMMM{####2}}%
  \bbl@replace\bbl@toreplace{[d]}{\BabelDated{####3}}%
  \bbl@replace\bbl@toreplace{[d|}{\bbl@datecntr[####3|}%
  \bbl@replace\bbl@toreplace{[dd]}{\BabelDatedd{####3}}%
  \bbl@replace\bbl@toreplace{[U]}{\BabelDateU{####1}}%
  \bbl@replace\bbl@toreplace{[U|}{\bbl@datecntr[####1|}%
  \bbl@replace@finish@iii\bbl@toreplace}
\def\bbl@datecntr{\expandafter\bbl@xdatecntr\expandafter}
\def\bbl@xdatecntr[#1|#2]{\localenumeral{#2}{#1}}
```

3.26. French spacing (again)

For the following declarations, see issue #240. `\nonfrenchspacing` is set by `document` too early, so it's a hack.

```
\AddToHook{begindocument/before}{%
  \let\bbl@normalsf\normalsfcodes
  \let\normalsfcodes\relax}
\AtBeginDocument{%
  \ifx\bbl@normalsf\@empty
    \ifnum\sfcode`\.=\@m
      \let\normalsfcodes\frenchspacing
    \else
      \let\normalsfcodes\nonfrenchspacing
    \fi
  \else
    \let\normalsfcodes\bbl@normalsf
  \fi}
```

Transforms.

Process the transforms read from `ini` files, converts them to a form close to the user interface (with `\babelprehyphenation` and `\babelprehyphenation`), wrapped with `\bbl@transforms@aux ...\relax`, and stores them in `\bbl@release@transforms`. However, since building a list enclosed in braces isn't trivial, the replacements are added after a comma, and then `\bbl@transforms@aux` adds the braces.

```
\bbl@csarg\let{inikv@transforms.prehyphenation}\bbl@inikv
\bbl@csarg\let{inikv@transforms.posthyphenation}\bbl@inikv
\def\bbl@transforms@aux#1#2#3#4,#5\relax{%
  #1[#2]{#3}{#4}{#5}}
\begingroup
  \catcode`\%=12
  \catcode`\&=14
  \gdef\bbl@transforms#1#2#3{&%
    \directlua{
       local str = [==[#2]==]
       str = str:gsub('%.%d+%.%d+$', '')
       token.set_macro('babeltempa', str)
    }&%
    \def\babeltempc{}&%
    \bbl@xin@{,\babeltempa,}{,\bbl@KVP@transforms,}&%
    \ifin@\else
      \bbl@xin@{:\babeltempa,}{,\bbl@KVP@transforms,}&%
    \fi
    \ifin@
```

```
      \bbl@foreach\bbl@KVP@transforms{&%
        \bbl@xin@{:\babeltempa,}{,##1,}&%
        \ifin@  &% font:font:transform syntax
          \directlua{
            local t = {}
            for m in string.gmatch('##1'..':', '(.-):') do
              table.insert(t, m)
            end
            table.remove(t)
            token.set_macro('babeltempc', ',fonts=' .. table.concat(t, ' '))
          }&%
        \fi}&%
      \in@{.0$}{#2$}&%
      \ifin@
        \directlua{&% (\attribute) syntax
          local str = string.match([[\bbl@KVP@transforms]],
                        '%(([^%(]-)%)[^%)]-\babeltempa')
          if str == nil then
            token.set_macro('babeltempb', '')
          else
            token.set_macro('babeltempb', ',attribute=' .. str)
          end
        }&%
        \toks@{#3}&%
        \bbl@exp{&%
          \\\g@addto@macro\\\bbl@release@transforms{&%
            \relax  &% Closes previous \bbl@transforms@aux
            \\\bbl@transforms@aux
              \\#1{label=\babeltempa\babeltempb\babeltempc}&%
                 {\languagename}{\the\toks@}}}&%
      \else
        \g@addto@macro\bbl@release@transforms{, {#3}}&%
      \fi
    \fi}
\endgroup
```

3.27. Handle language system

The language system (i.e., `Language` and `Script`) to be used when defining a font or setting the direction are set with the following macros. It also deals with unhyphenated line breaking in xetex (e.g., Thai and traditional Sanskrit), which is done with a hack at the font level because this engine doesn't support it.

```
\def\bbl@provide@lsys#1{%
  \bbl@ifunset{bbl@lname@#1}%
    {\bbl@load@info{#1}}%
    {}%
  \bbl@csarg\let{lsys@#1}\@empty
  \bbl@ifunset{bbl@sname@#1}{\bbl@csarg\gdef{sname@#1}{Default}}{}%
  \bbl@ifunset{bbl@sotf@#1}{\bbl@csarg\gdef{sotf@#1}{DFLT}}{}%
  \bbl@csarg\bbl@add@list{lsys@#1}{Script=\bbl@cs{sname@#1}}%
  \bbl@ifunset{bbl@lname@#1}{}%
    {\bbl@csarg\bbl@add@list{lsys@#1}{Language=\bbl@cs{lname@#1}}}%
  \ifcase\bbl@engine\or\or
    \bbl@ifunset{bbl@prehc@#1}{}%
      {\bbl@exp{\\\bbl@ifblank{\bbl@cs{prehc@#1}}}%
        {}%
        {\ifx\bbl@xenohyph\@undefined
           \global\let\bbl@xenohyph\bbl@xenohyph@d
           \ifx\AtBeginDocument\@notprerr
             \expandafter\@secondoftwo  % to execute right now
           \fi
           \AtBeginDocument{%
             \bbl@patchfont{\bbl@xenohyph}%
```

```
            {\expandafter\select@language\expandafter{\languagename}}}%
      \fi}}%
\fi
\bbl@csarg\bbl@toglobal{lsys@#1}}
```

3.28. Numerals

A tool to define the macros for native digits from the list provided in the `ini` file. Somewhat convoluted because there are 10 digits, but only 9 arguments in TEX. Non-digits characters are kept. The first macro is the generic "localized" command.

```
\def\bbl@setdigits#1#2#3#4#5{%
  \bbl@exp{%
    \def\<\languagename digits>####1{%       i.e., \langdigits
      \<bbl@digits@\languagename>####1\\\@nil}%
    \let\<bbl@cntr@digits@\languagename>\<\languagename digits>%
    \def\<\languagename counter>####1{%      i.e., \langcounter
      \\\expandafter\<bbl@counter@\languagename>%
      \\\csname c@####1\endcsname}%
    \def\<bbl@counter@\languagename>####1{% i.e., \bbl@counter@lang
      \\\expandafter\<bbl@digits@\languagename>%
      \\\number####1\\\@nil}}%
  \def\bbl@tempa##1##2##3##4##5{%
    \bbl@exp{%    Wow, quite a lot of hashes! :-(
      \def\<bbl@digits@\languagename>########1{%
       \\\ifx########1\\\@nil               % i.e., \bbl@digits@lang
       \\\else
         \\\ifx0########1#1%
         \\\else\\\ifx1########1#2%
         \\\else\\\ifx2########1#3%
         \\\else\\\ifx3########1#4%
         \\\else\\\ifx4########1#5%
         \\\else\\\ifx5########1##1%
         \\\else\\\ifx6########1##2%
         \\\else\\\ifx7########1##3%
         \\\else\\\ifx8########1##4%
         \\\else\\\ifx9########1##5%
         \\\else########1%
         \\\fi\\\fi\\\fi\\\fi\\\fi\\\fi\\\fi\\\fi\\\fi\\\fi\\\fi
         \\\expandafter\<bbl@digits@\languagename>%
       \\\fi}}}%
  \bbl@tempa}
```

Alphabetic counters must be converted from a space separated list to an `\ifcase` structure.

```
\def\bbl@buildifcase#1 {% Returns \bbl@tempa, requires \toks@={}
  \ifx\\#1%             % \\ before, in case #1 is multiletter
    \bbl@exp{%
      \def\\\bbl@tempa####1{%
        \<ifcase>####1\space\the\toks@\<else>\\\@ctrerr\<fi>}}%
  \else
    \toks@\expandafter{\the\toks@\or #1}%
    \expandafter\bbl@buildifcase
  \fi}
```

The code for additive counters is somewhat tricky and it's based on the fact the arguments just before `\@@` collects digits which have been left 'unused' in previous arguments, the first of them being the number of digits in the number to be converted. This explains the reverse set `76543210`. Digits above 10000 are not handled yet. When the key contains the subkey `.F.`, the number after is treated as an special case, for a fixed form (see `babel-he.ini`, for example).

```
\newcommand\localenumeral[2]{%
  \bbl@ifunset{bbl@cntr@#1@\languagename}%
    {#2}%
    {\bbl@cs{cntr@#1@\languagename}{#2}}}
\def\bbl@localecntr#1#2{\localenumeral{#2}{#1}}
```

```
\newcommand\localecounter[2]{%
  \expandafter\bbl@localecntr
  \expandafter{\number\csname c@#2\endcsname}{#1}}
\def\bbl@alphnumeral#1#2{%
  \expandafter\bbl@alphnumeral@i\number#2 76543210\@@{#1}}
\def\bbl@alphnumeral@i#1#2#3#4#5#6#7#8\@@#9{%
  \ifcase\@car#8\@nil\or   % Currently <10000, but prepared for bigger
    \bbl@alphnumeral@ii{#9}000000#1\or
    \bbl@alphnumeral@ii{#9}00000#1#2\or
    \bbl@alphnumeral@ii{#9}0000#1#2#3\or
    \bbl@alphnumeral@ii{#9}000#1#2#3#4\else
    \bbl@error{counter-too-large}{>9999}{}{}%
  \fi}
\def\bbl@alphnumeral@ii#1#2#3#4#5#6#7#8{%
  \bbl@ifunset{bbl@cntr@#1.F.\number#5#6#7#8@\languagename}%
    {\bbl@cs{cntr@#1.4@\languagename}#5%
     \bbl@cs{cntr@#1.3@\languagename}#6%
     \bbl@cs{cntr@#1.2@\languagename}#7%
     \bbl@cs{cntr@#1.1@\languagename}#8%
     \ifnum#6#7#8>\z@
       \bbl@ifunset{bbl@cntr@#1.S.321@\languagename}{}%
         {\bbl@cs{cntr@#1.S.321@\languagename}}%
     \fi}%
    {\bbl@cs{cntr@#1.F.\number#5#6#7#8@\languagename}}}
```

Some Chinese counters follow special rules.

```
\def\bbl@zhnumeral#1#2{%
  \ifnum#1<10 \bbl@zhnum000#1{#2}%
  \else\ifnum#1<100 \bbl@zhnum00#1{#2}%
  \else\ifnum#1<1000 \bbl@zhnum0#1{#2}%
  \else\ifnum#1<10000 \bbl@zhnum#1{#2}%
  \else\bbl@error{counter-too-large}{#1}{}{}%
  \fi\fi\fi\fi}
\def\bbl@zhnum#1#2#3#4#5{%
  \ifnum\numexpr#1#2#3#4\relax=\z@
    \localenumeral{#5.C}\@ne
  \else
    \ifnum#1>\z@\localenumeral{#5.D}{#1}\localenumeral{#5.C}5\fi % Thousands
    \ifnum#2>\z@\localenumeral{#5.D}{#2}\localenumeral{#5.C}4% Hundreds
    \else\ifnum#1>\z@\ifnum#3#4>\z@\localenumeral{#5.C}\@ne\fi
    \fi\fi
    \ifnum#3>\z@ % Tens. Omit for 10-19.
      \ifnum#1#2=\z@\ifnum#3=\@ne\else\localenumeral{#5.D}{#3}\fi
      \else\localenumeral{#5.D}{#3}%
      \fi
      \localenumeral{#5.C}\thr@@
    \else
      \ifnum#2>\z@\ifnum#4>\z@\localenumeral{#5.C}\@ne\fi\fi
    \fi
    \ifnum#4>\z@\localenumeral{#5.D}{#4}\fi % Units
  \fi}
```

3.29. Casing

```
\newcommand\BabelUppercaseMapping[3]{%
  \DeclareUppercaseMapping[\@nameuse{bbl@casing@#1}]{#2}{#3}}
\newcommand\BabelTitlecaseMapping[3]{%
  \DeclareTitlecaseMapping[\@nameuse{bbl@casing@#1}]{#2}{#3}}
\newcommand\BabelLowercaseMapping[3]{%
  \DeclareLowercaseMapping[\@nameuse{bbl@casing@#1}]{#2}{#3}}
```

The parser for `casing` and `casing.`⟨*variant*⟩.

```
\ifcase\bbl@engine % Converts utf8 to its code (expandable)
  \def\bbl@utftocode#1{\the\numexpr\decode@UTFviii#1\relax}
```

```
\else
  \def\bbl@utftocode#1{\expandafter`\string#1}
\fi
\def\bbl@casemapping#1#2#3{% 1:variant
  \def\bbl@tempa##1 ##2{% Loop
    \bbl@casemapping@i{##1}%
    \ifx\@empty##2\else\bbl@afterfi\bbl@tempa##2\fi}%
  \edef\bbl@templ{\@nameuse{bbl@casing@#2}#1}%  Language code
  \def\bbl@tempe{0}%   Mode (upper/lower...)
  \def\bbl@tempc{#3 }% Casing list
  \expandafter\bbl@tempa\bbl@tempc\@empty}
\def\bbl@casemapping@i#1{%
  \def\bbl@tempb{#1}%
  \ifcase\bbl@engine % Handle utf8 in pdftex, by surrounding chars with {}
    \@nameuse{regex_replace_all:nnN}%
      {[\x{c0}-\x{ff}][\x{80}-\x{bf}]*}{{\0}}\bbl@tempb
  \else
    \@nameuse{regex_replace_all:nnN}{.}{{\0}}\bbl@tempb
  \fi
  \expandafter\bbl@casemapping@ii\bbl@tempb\@@}
\def\bbl@casemapping@ii#1#2#3\@@{%
  \in@{#1#3}{<>}% i.e., if <u>, <l>, <t>
  \ifin@
    \edef\bbl@tempe{%
      \if#2u1 \else\if#2l2 \else\if#2t3 \fi\fi\fi}%
  \else
    \ifcase\bbl@tempe\relax
      \DeclareUppercaseMapping[\bbl@templ]{\bbl@utftocode{#1}}{#2}%
      \DeclareLowercaseMapping[\bbl@templ]{\bbl@utftocode{#2}}{#1}%
    \or
      \DeclareUppercaseMapping[\bbl@templ]{\bbl@utftocode{#1}}{#2}%
    \or
      \DeclareLowercaseMapping[\bbl@templ]{\bbl@utftocode{#1}}{#2}%
    \or
      \DeclareTitlecaseMapping[\bbl@templ]{\bbl@utftocode{#1}}{#2}%
    \fi
  \fi}
```

3.30. Getting info

The information in the identification section can be useful, so the following macro just exposes it with a user command.

```
\def\bbl@localeinfo#1#2{%
  \bbl@ifunset{bbl@info@#2}{#1}%
    {\bbl@ifunset{bbl@\csname bbl@info@#2\endcsname @\languagename}{#1}%
      {\bbl@cs{\csname bbl@info@#2\endcsname @\languagename}}}}
\newcommand\localeinfo[1]{%
  \ifx*#1\@empty
    \bbl@afterelse\bbl@localeinfo{}%
  \else
    \bbl@localeinfo
      {\bbl@error{no-ini-info}{}{}{}}%
      {#1}%
  \fi}
% \@namedef{bbl@info@name.locale}{lcname}
\@namedef{bbl@info@tag.ini}{lini}
\@namedef{bbl@info@name.english}{elname}
\@namedef{bbl@info@name.opentype}{lname}
\@namedef{bbl@info@tag.bcp47}{tbcp}
\@namedef{bbl@info@language.tag.bcp47}{lbcp}
\@namedef{bbl@info@tag.opentype}{lotf}
\@namedef{bbl@info@script.name}{esname}
\@namedef{bbl@info@script.name.opentype}{sname}
\@namedef{bbl@info@script.tag.bcp47}{sbcp}
```

```
\@namedef{bbl@info@script.tag.opentype}{sotf}
\@namedef{bbl@info@region.tag.bcp47}{rbcp}
\@namedef{bbl@info@variant.tag.bcp47}{vbcp}
\@namedef{bbl@info@extension.t.tag.bcp47}{extt}
\@namedef{bbl@info@extension.u.tag.bcp47}{extu}
\@namedef{bbl@info@extension.x.tag.bcp47}{extx}
```

With version 3.75 `\BabelEnsureInfo` is executed always, but there is an option to disable it. Since the info in `ini` files are always loaded, it has be made no-op in version 25.8.

```
⟨⟨*More package options⟩⟩ ▸
\DeclareOption{ensureinfo=off}{}
⟨⟨/More package options⟩⟩
\let\BabelEnsureInfo\relax
```

More general, but non-expandable, is `\getlocaleproperty`.

```
\newcommand\getlocaleproperty{%
  \@ifstar\bbl@getproperty@s\bbl@getproperty@x}
\def\bbl@getproperty@s#1#2#3{%
  \let#1\relax
  \def\bbl@elt##1##2##3{%
    \bbl@ifsamestring{##1/##2}{#3}%
      {\providecommand#1{##3}%
       \def\bbl@elt####1####2####3{}}%
      {}}%
  \bbl@cs{inidata@#2}}%
\def\bbl@getproperty@x#1#2#3{%
  \bbl@getproperty@s{#1}{#2}{#3}%
  \ifx#1\relax
    \bbl@error{unknown-locale-key}{#1}{#2}{#3}%
  \fi}
```

To inspect every possible loaded `ini`, we define `\LocaleForEach`, where `\bbl@ini@loaded` is a comma-separated list of locales, built by `\bbl@read@ini`.

```
\let\bbl@ini@loaded\@empty
\newcommand\LocaleForEach{\bbl@foreach\bbl@ini@loaded}
\def\ShowLocaleProperties#1{%
  \typeout{}%
  \typeout{*** Properties for language '#1' ***}%
  \def\bbl@elt##1##2##3{\typeout{##1/##2 = \unexpanded{##3}}}%
  \@nameuse{bbl@inidata@#1}%
  \typeout{*******}}
```

3.31. BCP 47 related commands

This macro is called by language selectors when the language isn't recognized. So, it's the core for (1) mapping from a BCP 27 tag to the actual language, if `bcp47.toname` is enabled (i.e., if `bbl@bcptoname` is true), and (2) lazy loading. With `autoload.bcp47` enabled *and* lazy loading, we must first build a name for the language, with the help of `autoload.bcp47.prefix`. Then we use `\provideprovide` passing the options set with `autoload.bcp47.options` (by default `import`). Finally, and if the locale has not been loaded before, we use `\provideprovide` with the language name as passed to the selector.

```
\newif\ifbbl@bcpallowed
\bbl@bcpallowedfalse
\def\bbl@autoload@options{@import}
\def\bbl@provide@locale{%
  \ifx\babelprovide\@undefined
    \bbl@error{base-on-the-fly}{}{}{}%
  \fi
  \let\bbl@auxname\languagename
  \ifbbl@bcptoname
    \bbl@ifunset{bbl@bcp@map@\languagename}{}% Move uplevel??
      {\edef\languagename{\@nameuse{bbl@bcp@map@\languagename}}%
       \let\localename\languagename}%
```

```
  \fi
  \ifbbl@bcpallowed
    \expandafter\ifx\csname date\languagename\endcsname\relax
      \expandafter
      \bbl@bcplookup{\languagename}%
      \ifx\bbl@bcp\relax\else  % Returned by \bbl@bcplookup
        \edef\languagename{\bbl@bcp@prefix\bbl@bcp}%
        \let\localename\languagename
        \expandafter\ifx\csname date\languagename\endcsname\relax
          \let\bbl@initoload\bbl@bcp
          \bbl@exp{\\\babelprovide[\bbl@autoload@bcpoptions]{\languagename}}%
          \let\bbl@initoload\relax
        \fi
        \bbl@csarg\xdef{bcp@map@\bbl@bcp}{\localename}%
      \fi
    \fi
  \fi
  \expandafter\ifx\csname date\languagename\endcsname\relax
    \IfFileExists{babel-\languagename.tex}%
      {\bbl@exp{\\\babelprovide[\bbl@autoload@options]{\languagename}}}%
      {}%
  \fi}
```

LaTeX needs to know the BCP 47 codes for some features. For that, it expects `\BCPdata` to be defined. While `language`, `region`, `script`, and `variant` are recognized, `extension`.⟨*s*⟩ for singletons may change.

Still somewhat hackish. Note `\str_if_eq:nnTF` is fully expandable (`\bbl@ifsamestring` isn't). The argument is the prefix to tag.bcp47.

```
\providecommand\BCPdata{}
\ifx\renewcommand\@undefined\else
  \renewcommand\BCPdata[1]{\bbl@bcpdata@i#1\@empty\@empty\@empty}
  \def\bbl@bcpdata@i#1#2#3#4#5#6\@empty{%
    \@nameuse{str_if_eq:nnTF}{#1#2#3#4#5}{main.}%
      {\bbl@bcpdata@ii{#6}\bbl@main@language}%
      {\bbl@bcpdata@ii{#1#2#3#4#5#6}\languagename}}%
  \def\bbl@bcpdata@ii#1#2{%
    \bbl@ifunset{bbl@info@#1.tag.bcp47}%
      {\bbl@error{unknown-ini-field}{#1}{}{}}%
      {\bbl@ifunset{bbl@\csname bbl@info@#1.tag.bcp47\endcsname @#2}{}%
        {\bbl@cs{\csname bbl@info@#1.tag.bcp47\endcsname @#2}}}}
\fi
\@namedef{bbl@info@casing.tag.bcp47}{casing}
\@namedef{bbl@info@tag.tag.bcp47}{tbcp} % For \BCPdata
```

4. Adjusting the Babel behavior

A generic high level interface is provided to adjust some global and general settings.

```
\newcommand\babeladjust[1]{%
  \bbl@forkv{#1}{%
    \bbl@ifunset{bbl@ADJ@##1@##2}%
      {\bbl@cs{ADJ@##1}{##2}}%
      {\bbl@cs{ADJ@##1@##2}}}}
%
\def\bbl@adjust@lua#1#2{%
  \ifvmode
    \ifnum\currentgrouplevel=\z@
      \directlua{ Babel.#2 }%
      \expandafter\expandafter\expandafter\@gobble
    \fi
  \fi
  {\bbl@error{adjust-only-vertical}{#1}{}{}}% Gobbled if everything went ok.
\@namedef{bbl@ADJ@bidi.mirroring@on}{%
```

```
  \bbl@adjust@lua{bidi}{mirroring_enabled=true}}
\@namedef{bbl@ADJ@bidi.mirroring@off}{%
  \bbl@adjust@lua{bidi}{mirroring_enabled=false}}
\@namedef{bbl@ADJ@bidi.text@on}{%
  \bbl@adjust@lua{bidi}{bidi_enabled=true}}
\@namedef{bbl@ADJ@bidi.text@off}{%
  \bbl@adjust@lua{bidi}{bidi_enabled=false}}
\@namedef{bbl@ADJ@bidi.math@on}{%
  \let\bbl@noamsmath\@empty}
\@namedef{bbl@ADJ@bidi.math@off}{%
  \let\bbl@noamsmath\relax}
%
\@namedef{bbl@ADJ@bidi.mapdigits@on}{%
  \bbl@adjust@lua{bidi}{digits_mapped=true}}
\@namedef{bbl@ADJ@bidi.mapdigits@off}{%
  \bbl@adjust@lua{bidi}{digits_mapped=false}}
%
\@namedef{bbl@ADJ@linebreak.sea@on}{%
  \bbl@adjust@lua{linebreak}{sea_enabled=true}}
\@namedef{bbl@ADJ@linebreak.sea@off}{%
  \bbl@adjust@lua{linebreak}{sea_enabled=false}}
\@namedef{bbl@ADJ@linebreak.cjk@on}{%
  \bbl@adjust@lua{linebreak}{cjk_enabled=true}}
\@namedef{bbl@ADJ@linebreak.cjk@off}{%
  \bbl@adjust@lua{linebreak}{cjk_enabled=false}}
\@namedef{bbl@ADJ@justify.arabic@on}{%
  \bbl@adjust@lua{linebreak}{arabic.justify_enabled=true}}
\@namedef{bbl@ADJ@justify.arabic@off}{%
  \bbl@adjust@lua{linebreak}{arabic.justify_enabled=false}}
%
\def\bbl@adjust@layout#1{%
  \ifvmode
    #1%
    \expandafter\@gobble
  \fi
  {\bbl@error{layout-only-vertical}{}{}{}}% Gobbled if everything went ok.
\@namedef{bbl@ADJ@layout.tabular@on}{%
  \ifnum\bbl@tabular@mode=\tw@
    \bbl@adjust@layout{\let\@tabular\bbl@NL@@tabular}%
  \else
    \chardef\bbl@tabular@mode\@ne
  \fi}
\@namedef{bbl@ADJ@layout.tabular@off}{%
  \ifnum\bbl@tabular@mode=\tw@
    \bbl@adjust@layout{\let\@tabular\bbl@OL@@tabular}%
  \else
    \chardef\bbl@tabular@mode\z@
  \fi}
\@namedef{bbl@ADJ@layout.lists@on}{%
  \bbl@adjust@layout{\let\list\bbl@NL@list}}
\@namedef{bbl@ADJ@layout.lists@off}{%
  \bbl@adjust@layout{\let\list\bbl@OL@list}}
%
\@namedef{bbl@ADJ@autoload.bcp47@on}{%
  \bbl@bcpallowedtrue}
\@namedef{bbl@ADJ@autoload.bcp47@off}{%
  \bbl@bcpallowedfalse}
\@namedef{bbl@ADJ@autoload.bcp47.prefix}#1{%
  \def\bbl@bcp@prefix{#1}}
\def\bbl@bcp@prefix{bcp47-}
\@namedef{bbl@ADJ@autoload.options}#1{%
  \def\bbl@autoload@options{#1}}
\def\bbl@autoload@bcpoptions{import}
```

```
\@namedef{bbl@ADJ@autoload.bcp47.options}#1{%
  \def\bbl@autoload@bcpoptions{#1}}
\newif\ifbbl@bcptoname
%
\@namedef{bbl@ADJ@bcp47.toname@on}{%
  \bbl@bcptonametrue}
\@namedef{bbl@ADJ@bcp47.toname@off}{%
  \bbl@bcptonamefalse}
%
\@namedef{bbl@ADJ@prehyphenation.disable@nohyphenation}{%
  \directlua{ Babel.ignore_pre_char = function(node)
      return (node.lang == \the\csname l@nohyphenation\endcsname)
    end }}
\@namedef{bbl@ADJ@prehyphenation.disable@off}{%
  \directlua{ Babel.ignore_pre_char = function(node)
      return false
    end }}
%
\@namedef{bbl@ADJ@interchar.disable@nohyphenation}{%
  \def\bbl@ignoreinterchar{%
    \ifnum\language=\l@nohyphenation
      \expandafter\@gobble
    \else
      \expandafter\@firstofone
    \fi}}
\@namedef{bbl@ADJ@interchar.disable@off}{%
  \let\bbl@ignoreinterchar\@firstofone}
%
\@namedef{bbl@ADJ@select.write@shift}{%
  \let\bbl@restorelastskip\relax
  \def\bbl@savelastskip{%
    \let\bbl@restorelastskip\relax
    \ifvmode
      \ifdim\lastskip=\z@
        \let\bbl@restorelastskip\nobreak
      \else
        \bbl@exp{%
          \def\\\bbl@restorelastskip{%
            \skip@=\the\lastskip
            \\\nobreak \vskip-\skip@ \vskip\skip@}}%
      \fi
    \fi}}
\@namedef{bbl@ADJ@select.write@keep}{%
  \let\bbl@restorelastskip\relax
  \let\bbl@savelastskip\relax}
\@namedef{bbl@ADJ@select.write@omit}{%
  \AddBabelHook{babel-select}{beforestart}{%
    \expandafter\babel@aux\expandafter{\bbl@main@language}{}}%
  \let\bbl@restorelastskip\relax
  \def\bbl@savelastskip##1\bbl@restorelastskip{}}
\@namedef{bbl@ADJ@select.encoding@off}{%
  \let\bbl@encoding@select@off\@empty}
```

4.1. Cross referencing macros

The LaTeX book states:

> The *key* argument is any sequence of letters, digits, and punctuation symbols; upper- and lowercase letters are regarded as different.

When the above quote should still be true when a document is typeset in a language that has active characters, special care has to be taken of the category codes of these characters when they appear in an argument of the cross referencing macros.

When a cross referencing command processes its argument, all tokens in this argument should be character tokens with category 'letter' or 'other'.

The following package options control which macros are to be redefined.

```
⟨⟨*More package options⟩⟩ ▸
\DeclareOption{safe=none}{\let\bbl@opt@safe\@empty}
\DeclareOption{safe=bib}{\def\bbl@opt@safe{B}}
\DeclareOption{safe=ref}{\def\bbl@opt@safe{R}}
\DeclareOption{safe=refbib}{\def\bbl@opt@safe{BR}}
\DeclareOption{safe=bibref}{\def\bbl@opt@safe{BR}}
⟨⟨/More package options⟩⟩
```

\@newl@bel First we open a new group to keep the changed setting of `\protect` local and then we set the `@safe@actives` switch to true to make sure that any shorthand that appears in any of the arguments immediately expands to its non-active self.

```
\bbl@trace{Cross referencing macros}
\ifx\bbl@opt@safe\@empty\else % i.e., if 'ref' and/or 'bib'
  \def\@newl@bel#1#2#3{%
   {\@safe@activestrue
    \bbl@ifunset{#1@#2}%
       \relax
       {\gdef\@multiplelabels{%
          \@latex@warning@no@line{There were multiply-defined labels}}%
        \@latex@warning@no@line{Label `#2' multiply defined}}%
    \global\@namedef{#1@#2}{#3}}}
```

\@testdef An internal LaTeX macro used to test if the labels that have been written on the aux file have changed. It is called by the `\enddocument` macro.

```
  \CheckCommand*\@testdef[3]{%
    \def\reserved@a{#3}%
    \expandafter\ifx\csname#1@#2\endcsname\reserved@a
    \else
      \@tempswatrue
    \fi}
```

Now that we made sure that `\@testdef` still has the same definition we can rewrite it. First we make the shorthands 'safe'. Then we use `\bbl@tempa` as an 'alias' for the macro that contains the label which is being checked. Then we define `\bbl@tempb` just as `\@newl@bel` does it. When the label is defined we replace the definition of `\bbl@tempa` by its meaning. If the label didn't change, `\bbl@tempa` and `\bbl@tempb` should be identical macros.

```
  \def\@testdef#1#2#3{%
    \@safe@activestrue
    \expandafter\let\expandafter\bbl@tempa\csname #1@#2\endcsname
    \def\bbl@tempb{#3}%
    \@safe@activesfalse
    \ifx\bbl@tempa\relax
    \else
      \edef\bbl@tempa{\expandafter\strip@prefix\meaning\bbl@tempa}%
    \fi
    \edef\bbl@tempb{\expandafter\strip@prefix\meaning\bbl@tempb}%
    \ifx\bbl@tempa\bbl@tempb
    \else
      \@tempswatrue
    \fi}
\fi
```

\ref
\pageref The same holds for the macro `\ref` that references a label and `\pageref` to reference a page. We make them robust as well (if they weren't already) to prevent problems if they should become expanded at the wrong moment.

```
\bbl@xin@{R}\bbl@opt@safe
\ifin@
  \edef\bbl@tempc{\expandafter\string\csname ref code\endcsname}%
  \bbl@xin@{\expandafter\strip@prefix\meaning\bbl@tempc}%
```

```
    {\expandafter\strip@prefix\meaning\ref}%
  \ifin@
    \bbl@redefine\@kernel@ref#1{%
      \@safe@activestrue\org@@kernel@ref{#1}\@safe@activesfalse}
    \bbl@redefine\@kernel@pageref#1{%
      \@safe@activestrue\org@@kernel@pageref{#1}\@safe@activesfalse}
    \bbl@redefine\@kernel@sref#1{%
      \@safe@activestrue\org@@kernel@sref{#1}\@safe@activesfalse}
    \bbl@redefine\@kernel@spageref#1{%
      \@safe@activestrue\org@@kernel@spageref{#1}\@safe@activesfalse}
  \else
    \bbl@redefinerobust\ref#1{%
      \@safe@activestrue\org@ref{#1}\@safe@activesfalse}
    \bbl@redefinerobust\pageref#1{%
      \@safe@activestrue\org@pageref{#1}\@safe@activesfalse}
  \fi
\else
  \let\org@ref\ref
  \let\org@pageref\pageref
\fi
```

\@citex The macro used to cite from a bibliography, `\cite`, uses an internal macro, `\@citex`. It is this internal macro that picks up the argument(s), so we redefine this internal macro and leave `\cite` alone. The first argument is used for typesetting, so the shorthands need only be deactivated in the second argument.

```
\bbl@xin@{B}\bbl@opt@safe
\ifin@
  \bbl@redefine\@citex[#1]#2{%
    \@safe@activestrue\edef\bbl@tempa{#2}\@safe@activesfalse
    \org@@citex[#1]{\bbl@tempa}}
```

Unfortunately, the packages `natbib` and `cite` need a different definition of `\@citex`... To begin with, `natbib` has a definition for `\@citex` with *three* arguments... We only know that a package is loaded when `\begin{document}` is executed, so we need to postpone the different redefinition.

Notice that we use `\def` here instead of `\bbl@redefine` because `\org@@citex` is already defined and we don't want to overwrite that definition (it would result in parameter stack overflow because of a circular definition).

(Recent versions of `natbib` change dynamically `\@citex`, so PR4087 doesn't seem fixable in a simple way. Just load `natbib` before.)

```
  \AtBeginDocument{%
    \@ifpackageloaded{natbib}{%
    \def\@citex[#1][#2]#3{%
      \@safe@activestrue\edef\bbl@tempa{#3}\@safe@activesfalse
      \org@@citex[#1][#2]{\bbl@tempa}}%
    }{}}
```

The package `cite` has a definition of `\@citex` where the shorthands need to be turned off in both arguments.

```
  \AtBeginDocument{%
    \@ifpackageloaded{cite}{%
      \def\@citex[#1]#2{%
        \@safe@activestrue\org@@citex[#1]{#2}\@safe@activesfalse}%
      }{}}
```

\nocite The macro `\nocite` which is used to instruct BiBTEX to extract uncited references from the database.

```
  \bbl@redefine\nocite#1{%
    \@safe@activestrue\org@nocite{#1}\@safe@activesfalse}
```

\bibcite The macro that is used in the `aux` file to define citation labels. When packages such as `natbib` or `cite` are not loaded its second argument is used to typeset the citation label. In that case, this second argument can contain active characters but is used in an environment where

\@safe@activestrue is in effect. This switch needs to be reset inside the \hbox which contains the citation label. In order to determine during aux file processing which definition of \bibcite is needed we define \bibcite in such a way that it redefines itself with the proper definition. We call \bbl@cite@choice to select the proper definition for \bibcite. This new definition is then activated.

```
\bbl@redefine\bibcite{%
  \bbl@cite@choice
  \bibcite}
```

\bbl@bibcite The macro \bbl@bibcite holds the definition of \bibcite needed when neither natbib nor cite is loaded.

```
\def\bbl@bibcite#1#2{%
  \org@bibcite{#1}{\@safe@activesfalse#2}}
```

\bbl@cite@choice The macro \bbl@cite@choice determines which definition of \bibcite is needed. First we give \bibcite its default definition.

```
\def\bbl@cite@choice{%
  \global\let\bibcite\bbl@bibcite
  \@ifpackageloaded{natbib}{\global\let\bibcite\org@bibcite}{}%
  \@ifpackageloaded{cite}{\global\let\bibcite\org@bibcite}{}%
  \global\let\bbl@cite@choice\relax}
```

When a document is run for the first time, no aux file is available, and \bibcite will not yet be properly defined. In this case, this has to happen before the document starts.

```
\AtBeginDocument{\bbl@cite@choice}
```

\@bibitem One of the two internal LaTeX macros called by \bibitem that write the citation label on the aux file.

```
\bbl@redefine\@bibitem#1{%
  \@safe@activestrue\org@@bibitem{#1}\@safe@activesfalse}
\else
  \let\org@nocite\nocite
  \let\org@@citex\@citex
  \let\org@bibcite\bibcite
  \let\org@@bibitem\@bibitem
\fi
```

4.2. Layout

```
\newcommand\BabelPatchSection[1]{%
  \@ifundefined{#1}{}{%
    \bbl@exp{\let\<bbl@ss@#1>\<#1>}%
    \@namedef{#1}{%
      \@ifstar{\bbl@presec@s{#1}}%
              {\@dblarg{\bbl@presec@x{#1}}}}}
\def\bbl@presec@x#1[#2]#3{%
  \bbl@exp{%
    \\\select@language@x{\bbl@main@language}%
    \\\bbl@cs{sspre@#1}%
    \\\bbl@cs{ss@#1}%
      [\\\foreignlanguage{\languagename}{\unexpanded{#2}}]%
      {\\\foreignlanguage{\languagename}{\unexpanded{#3}}%
       \ifcase\bbl@bidimode\else\\\babelsublr{}\fi}%
    \\\select@language@x{\languagename}}}
\def\bbl@presec@s#1#2{%
  \bbl@exp{%
    \\\select@language@x{\bbl@main@language}%
    \\\bbl@cs{sspre@#1}%
    \\\bbl@cs{ss@#1}*%
      {\\\foreignlanguage{\languagename}{\unexpanded{#2}}%
       \ifcase\bbl@bidimode\else\\\babelsublr{}\fi}%
    \\\select@language@x{\languagename}}}
```

```
%
\IfBabelLayout{sectioning}%
  {\BabelPatchSection{part}%
   \BabelPatchSection{chapter}%
   \BabelPatchSection{section}%
   \BabelPatchSection{subsection}%
   \BabelPatchSection{subsubsection}%
   \BabelPatchSection{paragraph}%
   \BabelPatchSection{subparagraph}%
   \def\babel@toc#1{%
     \select@language@x{\bbl@main@language}}}{}
\IfBabelLayout{captions}%
  {\BabelPatchSection{caption}}{}
```

\BabelFootnote Footnotes.

```
\bbl@trace{Footnotes}
\def\bbl@footnote#1#2#3{%
  \@ifnextchar[%
    {\bbl@footnote@o{#1}{#2}{#3}}%
    {\bbl@footnote@x{#1}{#2}{#3}}}
\long\def\bbl@footnote@x#1#2#3#4{%
  \begingroup
    \select@language@x{\bbl@main@language}%
    \bbl@fn@footnote{#2#1{\ignorespaces#4}#3}%
  \endgroup}
\long\def\bbl@footnote@o#1#2#3[#4]#5{%
  \begingroup
    \select@language@x{\bbl@main@language}%
    \bbl@fn@footnote[#4]{#2#1{\ignorespaces#5}#3}%
  \endgroup}
\def\bbl@footnotetext#1#2#3{%
  \@ifnextchar[%
    {\bbl@footnotetext@o{#1}{#2}{#3}}%
    {\bbl@footnotetext@x{#1}{#2}{#3}}}
\long\def\bbl@footnotetext@x#1#2#3#4{%
  \begingroup
    \select@language@x{\bbl@main@language}%
    \bbl@fn@footnotetext{#2#1{\ignorespaces#4}#3}%
  \endgroup}
\long\def\bbl@footnotetext@o#1#2#3[#4]#5{%
  \begingroup
    \select@language@x{\bbl@main@language}%
    \bbl@fn@footnotetext[#4]{#2#1{\ignorespaces#5}#3}%
  \endgroup}
\def\BabelFootnote#1#2#3#4{%
  \ifx\bbl@fn@footnote\@undefined
    \let\bbl@fn@footnote\footnote
  \fi
  \ifx\bbl@fn@footnotetext\@undefined
    \let\bbl@fn@footnotetext\footnotetext
  \fi
  \bbl@ifblank{#2}%
    {\def#1{\bbl@footnote{\@firstofone}{#3}{#4}}
     \@namedef{\bbl@stripslash#1text}%
       {\bbl@footnotetext{\@firstofone}{#3}{#4}}}%
    {\def#1{\bbl@exp{\\\bbl@footnote{\\\foreignlanguage{#2}}}{#3}{#4}}%
     \@namedef{\bbl@stripslash#1text}%
       {\bbl@exp{\\\bbl@footnotetext{\\\foreignlanguage{#2}}}{#3}{#4}}}}
\IfBabelLayout{footnotes}%
  {\ifcase\bbl@engine\or
     \AddToHook{begindocument/end}{%
       \ExplSyntaxOn
       \bbl@sreplace\@footnotetext{\color@begingroup}%
```

```
        {\color@begingroup\ifnum\bbl@insidemath>\z@\localerestoredirs\fi}%
      \ExplSyntaxOff}%
  \fi
  \let\bbl@OL@footnote\footnote
  \BabelFootnote\footnote\languagename{}{}%
  \BabelFootnote\localfootnote\languagename{}{}%
  \BabelFootnote\mainfootnote{}{}{}}
 {}
```

4.3. Marks

\markright Because the output routine is asynchronous, we must pass the current language attribute to the head lines. To achieve this we need to adapt the definition of `\markright` and `\markboth` somewhat. However, headlines and footlines can contain text outside marks; for that we must take some actions in the output routine if the 'headfoot' options is used.

We need to make some redefinitions to the output routine to avoid an endless loop and to correctly handle the page number in bidi documents.

```
\bbl@trace{Marks}
\IfBabelLayout{sectioning}
  {\ifx\bbl@opt@headfoot\@nnil
     \g@addto@macro\@resetactivechars{%
       \set@typeset@protect
       \expandafter\select@language@x\expandafter{\bbl@main@language}%
       \let\protect\noexpand
       \ifcase\bbl@bidimode\else % Only with bidi. See also above
         \edef\thepage{%
           \noexpand\babelsublr{\unexpanded\expandafter{\thepage}}}%
       \fi}%
   \fi}
  {\ifbbl@single\else
     \bbl@ifunset{markright }\bbl@redefine\bbl@redefinerobust
     \markright#1{%
       \bbl@ifblank{#1}%
         {\org@markright{}}%
         {\toks@{#1}%
          \bbl@exp{%
            \\\org@markright{\\\protect\\\foreignlanguage{\languagename}%
              {\\\protect\\\bbl@restore@actives\the\toks@}}}}%
```

\markboth
\@mkboth The definition of `\markboth` is equivalent to that of `\markright`, except that we need two token registers. The documentclasses `report` and `book` define and set the headings for the page. While doing so they also store a copy of `\markboth` in `\@mkboth`. Therefore we need to check whether `\@mkboth` has already been set. If so we need to do that again with the new definition of `\markboth`. (As of Oct 2019, LaTeX stores the definition in an intermediate macro, so it's not necessary anymore, but it's preserved for older versions.)

```
     \ifx\@mkboth\markboth
       \def\bbl@tempc{\let\@mkboth\markboth}%
     \else
       \def\bbl@tempc{}%
     \fi
     \bbl@ifunset{markboth }\bbl@redefine\bbl@redefinerobust
     \markboth#1#2{%
       \protected@edef\bbl@tempb##1{%
         \protect\foreignlanguage
         {\languagename}{\protect\bbl@restore@actives##1}}%
       \bbl@ifblank{#1}%
         {\toks@{}}%
         {\toks@\expandafter{\bbl@tempb{#1}}}%
       \bbl@ifblank{#2}%
         {\@temptokena{}}%
         {\@temptokena\expandafter{\bbl@tempb{#2}}}%
```

```
      \bbl@exp{\\\org@markboth{\the\toks@}{\the\@temptokena}}%
      \bbl@tempc
    \fi}  % end ifbbl@single, end \IfBabelLayout
```

4.4. Other packages

4.4.1. ifthen

\ifthenelse Sometimes a document writer wants to create a special effect depending on the page a certain fragment of text appears on. This can be achieved by the following piece of code:

```
% \ifthenelse{\isodd{\pageref{some-label}}}
%            {code for odd pages}
%            {code for even pages}
%
```

In order for this to work the argument of `\isodd` needs to be fully expandable. With the above redefinition of `\pageref` it is not in the case of this example. To overcome that, we add some code to the definition of `\ifthenelse` to make things work.

We want to revert the definition of `\pageref` and `\ref` to their original definition for the first argument of `\ifthenelse`, so we first need to store their current meanings.

Then we can set the `\@safe@actives` switch and call the original `\ifthenelse`. In order to be able to use shorthands in the second and third arguments of `\ifthenelse` the resetting of the switch *and* the definition of `\pageref` happens inside those arguments.

```
\bbl@trace{Preventing clashes with other packages}
\ifx\org@ref\@undefined\else
  \bbl@xin@{R}\bbl@opt@safe
  \ifin@
    \AtBeginDocument{%
      \@ifpackageloaded{ifthen}{%
        \bbl@redefine@long\ifthenelse#1#2#3{%
          \let\bbl@temp@pref\pageref
          \let\pageref\org@pageref
          \let\bbl@temp@ref\ref
          \let\ref\org@ref
          \@safe@activestrue
          \org@ifthenelse{#1}%
            {\let\pageref\bbl@temp@pref
             \let\ref\bbl@temp@ref
             \@safe@activesfalse
             #2}%
            {\let\pageref\bbl@temp@pref
             \let\ref\bbl@temp@ref
             \@safe@activesfalse
             #3}%
          }%
        }{}%
      }
\fi
```

4.4.2. varioref

\@@vpageref
\vrefpagenum
\Ref When the package `varioref` is in use we need to modify its internal command `\@@vpageref` in order to prevent problems when an active character ends up in the argument of `\vref`. The same needs to happen for `\vrefpagenum`.

```
  \AtBeginDocument{%
    \@ifpackageloaded{varioref}{%
      \bbl@redefine\@@vpageref#1[#2]#3{%
        \@safe@activestrue
        \org@@@vpageref{#1}[#2]{#3}%
        \@safe@activesfalse}%
```

```
      \bbl@redefine\vrefpagenum#1#2{%
        \@safe@activestrue
        \org@vrefpagenum{#1}{#2}%
        \@safe@activesfalse}%
```

The package `varioref` defines `\Ref` to be a robust command which uppercases the first character of the reference text. In order to be able to do that it needs to access the expandable form of `\ref`. So we employ a little trick here. We redefine the (internal) command `\Ref␣` to call `\org@ref` instead of `\ref`. The disadvantage of this solution is that whenever the definition of `\Ref` changes, this definition needs to be updated as well.

```
      \expandafter\def\csname Ref \endcsname#1{%
        \protected@edef\@tempa{\org@ref{#1}}\expandafter\MakeUppercase\@tempa}
      }{}%
    }
\fi
```

4.4.3. hhline

\hhline Delaying the activation of the shorthand characters has introduced a problem with the `hhline` package. The reason is that it uses the ':' character which is made active by the french support in babel. Therefore we need to *reload* the package when the ':' is an active character. Note that this happens *after* the category code of the @-sign has been changed to other, so we need to temporarily change it to letter again.

```
\AtEndOfPackage{%
  \AtBeginDocument{%
    \@ifpackageloaded{hhline}%
      {\expandafter\ifx\csname normal@char\string:\endcsname\relax
       \else
         \makeatletter
         \def\@currname{hhline}\input{hhline.sty}\makeatother
       \fi}%
      {}}}
```

\substitutefontfamily *Deprecated.* It creates an `fd` file on the fly. The first argument is an encoding mnemonic, the second and third arguments are font family names. Use the tools provided by LaTeX (`\DeclareFontFamilySubstitution`).

```
\def\substitutefontfamily#1#2#3{%
  \lowercase{\immediate\openout15=#1#2.fd\relax}%
  \immediate\write15{%
    \string\ProvidesFile{#1#2.fd}%
    [\the\year/\two@digits{\the\month}/\two@digits{\the\day}
     \space generated font description file]^^J
    \string\DeclareFontFamily{#1}{#2}{}^^J
    \string\DeclareFontShape{#1}{#2}{m}{n}{<->ssub * #3/m/n}{}^^J
    \string\DeclareFontShape{#1}{#2}{m}{it}{<->ssub * #3/m/it}{}^^J
    \string\DeclareFontShape{#1}{#2}{m}{sl}{<->ssub * #3/m/sl}{}^^J
    \string\DeclareFontShape{#1}{#2}{m}{sc}{<->ssub * #3/m/sc}{}^^J
    \string\DeclareFontShape{#1}{#2}{b}{n}{<->ssub * #3/bx/n}{}^^J
    \string\DeclareFontShape{#1}{#2}{b}{it}{<->ssub * #3/bx/it}{}^^J
    \string\DeclareFontShape{#1}{#2}{b}{sl}{<->ssub * #3/bx/sl}{}^^J
    \string\DeclareFontShape{#1}{#2}{b}{sc}{<->ssub * #3/bx/sc}{}^^J
    }%
  \closeout15
  }
\@onlypreamble\substitutefontfamily
```

4.5. Encoding and fonts

Because documents may use non-ASCII font encodings, we make sure that the logos of TeX and LaTeX always come out in the right encoding. There is a list of non-ASCII encodings. Requested encodings are currently stored in `\@fontenc@load@list`. If a non-ASCII has been loaded, we define versions of `\TeX` and `\LaTeX` for them using `\ensureascii`. The default ASCII encoding is set, too (in reverse order): the "main" encoding (when the document begins), the last loaded, or `OT1`.

\ensureascii

```
\bbl@trace{Encoding and fonts}
\newcommand\BabelNonASCII{LGR,LGI,X2,OT2,OT3,OT6,LHE,LWN,LMA,LMC,LMS,LMU}
\newcommand\BabelNonText{TS1,T3,TS3}
\let\org@TeX\TeX
\let\org@LaTeX\LaTeX
\let\ensureascii\@firstofone
\let\asciiencoding\@empty
\AtBeginDocument{%
  \def\@elt#1{,#1,}%
  \edef\bbl@tempa{\expandafter\@gobbletwo\@fontenc@load@list}%
  \let\@elt\relax
  \let\bbl@tempb\@empty
  \def\bbl@tempc{OT1}%
  \bbl@foreach\BabelNonASCII{% LGR loaded in a non-standard way
    \bbl@ifunset{T@#1}{}{\def\bbl@tempb{#1}}}%
  \bbl@foreach\bbl@tempa{%
    \bbl@xin@{,#1,}{,\BabelNonASCII,}%
    \ifin@
      \def\bbl@tempb{#1}% Store last non-ascii
    \else\bbl@xin@{,#1,}{,\BabelNonText,}% Pass
      \ifin@\else
        \def\bbl@tempc{#1}% Store last ascii
      \fi
    \fi}%
  \ifx\bbl@tempb\@empty\else
    \bbl@xin@{,\cf@encoding,}{,\BabelNonASCII,\BabelNonText,}%
    \ifin@\else
      \edef\bbl@tempc{\cf@encoding}% The default if ascii wins
    \fi
    \let\asciiencoding\bbl@tempc
    \renewcommand\ensureascii[1]{%
      {\fontencoding{\asciiencoding}\selectfont#1}}%
    \DeclareTextCommandDefault{\TeX}{\ensureascii{\org@TeX}}%
    \DeclareTextCommandDefault{\LaTeX}{\ensureascii{\org@LaTeX}}%
  \fi}
```

Now comes the old deprecated stuff (with a little change in 3.9l, for fontspec). The first thing we need to do is to determine, at `\begin{document}`, which latin fontencoding to use.

\latinencoding When text is being typeset in an encoding other than 'latin' (`OT1` or `T1`), it would be nice to still have Roman numerals come out in the Latin encoding. So we first assume that the current encoding at the end of processing the package is the Latin encoding.

```
\AtEndOfPackage{\edef\latinencoding{\cf@encoding}}
```

But this might be overruled with a later loading of the package `fontenc`. Therefore we check at the execution of `\begin{document}` whether it was loaded with the `T1` option. The normal way to do this (using `\@ifpackageloaded`) is disabled for this package. Now we have to revert to parsing the internal macro `\@filelist` which contains all the filenames loaded.

```
\AtBeginDocument{%
  \@ifpackageloaded{fontspec}%
    {\xdef\latinencoding{%
       \ifx\UTFencname\@undefined
         EU\ifcase\bbl@engine\or2\or1\fi
       \else
         \UTFencname
       \fi}}%
    {\gdef\latinencoding{OT1}%
     \ifx\cf@encoding\bbl@t@one
       \xdef\latinencoding{\bbl@t@one}%
     \else
       \def\@elt#1{,#1,}%
       \edef\bbl@tempa{\expandafter\@gobbletwo\@fontenc@load@list}%
```

```
      \let\@elt\relax
      \bbl@xin@{,T1,}\bbl@tempa
      \ifin@
        \xdef\latinencoding{\bbl@t@one}%
      \fi
    \fi}}
```

\latintext Then we can define the command `\latintext` which is a declarative switch to a latin font-encoding. Usage of this macro is deprecated.

```
\DeclareRobustCommand{\latintext}{%
  \fontencoding{\latinencoding}\selectfont
  \def\encodingdefault{\latinencoding}}
```

\textlatin This command takes an argument which is then typeset using the requested font encoding. In order to avoid many encoding switches it operates in a local scope.

```
\ifx\@undefined\DeclareTextFontCommand
  \DeclareRobustCommand{\textlatin}[1]{\leavevmode{\latintext #1}}
\else
  \DeclareTextFontCommand{\textlatin}{\latintext}
\fi
```

For several functions, we need to execute some code with `\selectfont`. With LaTeX 2021-06-01, there is a hook for this purpose.

```
\def\bbl@patchfont#1{\AddToHook{selectfont}{#1}}
```

4.6. Basic bidi support

This code is currently placed here for practical reasons. It will be moved to the correct place soon, I hope.

It is loosely based on `rlbabel.def`, but most of it has been developed from scratch. This babel module (by Johannes Braams and Boris Lavva) has served the purpose of typesetting R documents for two decades, and despite its flaws I think it is still a good starting point (some parts have been copied here almost verbatim), partly thanks to its simplicity. I've also looked at ARABI (by Youssef Jabri), which is compatible with babel.

There are two ways of modifying macros to make them "bidi", namely, by patching the internal low-level macros (which is what I have done with lists, columns, counters, tocs, much like `rlbabel` did), and by introducing a "middle layer" just below the user interface (sectioning, footnotes).

- pdftex provides a minimal support for bidi text, and it must be done by hand. Vertical typesetting is not possible.
- xetex is somewhat better, thanks to its font engine (even if not always reliable) and a few additional tools. However, very little is done at the paragraph level. Another challenging problem is text direction does not honour TeX grouping.
- luatex can provide the most complete solution, as we can manipulate almost freely the node list, the generated lines, and so on, but bidi text does not work out of the box and some development is necessary. It also provides tools to properly set left-to-right and right-to-left page layouts. As LuaTeX-ja shows, vertical typesetting is possible, too.

```
\bbl@trace{Loading basic (internal) bidi support}
\ifodd\bbl@engine
\else % Any xe+lua bidi
  \ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200
    \bbl@error{bidi-only-lua}{}{}{}%
    \let\bbl@beforeforeign\leavevmode
    \AtEndOfPackage{%
      \EnableBabelHook{babel-bidi}%
      \bbl@xebidipar}
  \fi\fi
  \def\bbl@loadxebidi#1{%
    \ifx\RTLfootnotetext\@undefined
      \AtEndOfPackage{%
        \EnableBabelHook{babel-bidi}%
```

```
        \ifx\fontspec\@undefined
          \usepackage{fontspec}% bidi needs fontspec
        \fi
        \usepackage#1{bidi}%
        \let\bbl@digitsdotdash\DigitsDotDashInterCharToks
        \def\DigitsDotDashInterCharToks{% See the 'bidi' package
          \ifnum\@nameuse{bbl@wdir@\languagename}=\tw@ % 'AL' bidi
            \bbl@digitsdotdash % So ignore in 'R' bidi
          \fi}}%
    \fi}
  \ifnum\bbl@bidimode>200 % Any xe bidi=
    \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
      \bbl@tentative{bidi=bidi}
      \bbl@loadxebidi{}
    \or
      \bbl@loadxebidi{[rldocument]}
    \or
      \bbl@loadxebidi{}
    \fi
  \fi
\fi
\ifnum\bbl@bidimode=\@ne % bidi=default
  \let\bbl@beforeforeign\leavevmode
  \ifodd\bbl@engine % lua
    \newattribute\bbl@attr@dir
    \directlua{ Babel.attr_dir = luatexbase.registernumber'bbl@attr@dir' }
    \bbl@exp{\output{\bodydir\pagedir\the\output}}
  \fi
  \AtEndOfPackage{%
    \EnableBabelHook{babel-bidi}% pdf/lua/xe
    \ifodd\bbl@engine\else % pdf/xe
      \bbl@xebidipar
    \fi}
\fi
```

Now come the macros used to set the direction when a language is switched. Testing are based on script names, because it's the user interface (including `language` and `script` in `\babelprovide`. First the (mostly) common macros.

```
\bbl@trace{Macros to switch the text direction}
\def\bbl@alscripts{%
  ,Arabic,Syriac,Thaana,Hanifi Rohingya,Hanifi,Sogdian,}
\def\bbl@rscripts{%
  Adlam,Avestan,Chorasmian,Cypriot,Elymaic,Garay,%
  Hatran,Hebrew,Imperial Aramaic,Inscriptional Pahlavi,%
  Inscriptional Parthian,Kharoshthi,Lydian,Mandaic,Manichaean,%
  Mende Kikakui,Meroitic Cursive,Meroitic Hieroglyphs,Nabataean,%
  Nko,Old Hungarian,Old North Arabian,Old Sogdian,%
  Old South Arabian,Old Turkic,Old Uyghur,Palmyrene,Phoenician,%
  Psalter Pahlavi,Samaritan,Yezidi,Mandaean,%
  Meroitic,N'Ko,Orkhon,Todhri}
%
\def\bbl@provide@dirs#1{%
  \bbl@xin@{\csname bbl@sname@#1\endcsname}{\bbl@alscripts\bbl@rscripts}%
  \ifin@
    \global\bbl@csarg\chardef{wdir@#1}\@ne
    \bbl@xin@{\csname bbl@sname@#1\endcsname}{\bbl@alscripts}%
    \ifin@
      \global\bbl@csarg\chardef{wdir@#1}\tw@
    \fi
  \else
    \global\bbl@csarg\chardef{wdir@#1}\z@
  \fi
  \ifodd\bbl@engine
```

```
    \bbl@csarg\ifcase{wdir@#1}%
      \directlua{ Babel.locale_props[\the\localeid].textdir = 'l' }%
    \or
      \directlua{ Babel.locale_props[\the\localeid].textdir = 'r' }%
    \or
      \directlua{ Babel.locale_props[\the\localeid].textdir = 'al' }%
    \fi
  \fi}
%
\def\bbl@switchdir{%
  \bbl@ifunset{bbl@lsys@\languagename}{\bbl@provide@lsys{\languagename}}{}%
  \bbl@ifunset{bbl@wdir@\languagename}{\bbl@provide@dirs{\languagename}}{}%
  \bbl@exp{\\\bbl@setdirs\bbl@cl{wdir}}}
\def\bbl@setdirs#1{%
  \ifcase\bbl@select@type
    \bbl@bodydir{#1}%
    \bbl@pardir{#1}% <- Must precede \bbl@textdir
  \fi
  \bbl@textdir{#1}}
\ifnum\bbl@bidimode>\z@
  \AddBabelHook{babel-bidi}{afterextras}{\bbl@switchdir}
  \DisableBabelHook{babel-bidi}
\fi
```

Now the engine-dependent macros.

```
\ifodd\bbl@engine  % luatex=1
\else % pdftex=0, xetex=2
  \newcount\bbl@dirlevel
  \chardef\bbl@thetextdir\z@
  \chardef\bbl@thepardir\z@
  \def\bbl@textdir#1{%
    \ifcase#1\relax
       \chardef\bbl@thetextdir\z@
       \@nameuse{setlatin}%
       \bbl@textdir@i\beginL\endL
     \else
       \chardef\bbl@thetextdir\@ne
       \@nameuse{setnonlatin}%
       \bbl@textdir@i\beginR\endR
    \fi}
  \def\bbl@textdir@i#1#2{%
    \ifhmode
      \ifnum\currentgrouplevel>\z@
        \ifnum\currentgrouplevel=\bbl@dirlevel
          \bbl@error{multiple-bidi}{}{}{}%
          \bgroup\aftergroup#2\aftergroup\egroup
        \else
          \ifcase\currentgrouptype\or % 0 bottom
            \aftergroup#2% 1 simple {}
          \or
            \bgroup\aftergroup#2\aftergroup\egroup % 2 hbox
          \or
            \bgroup\aftergroup#2\aftergroup\egroup % 3 adj hbox
          \or\or\or % vbox vtop align
          \or
            \bgroup\aftergroup#2\aftergroup\egroup % 7 noalign
          \or\or\or\or\or\or % output math disc insert vcent mathchoice
          \or
            \aftergroup#2% 14 \begingroup
          \else
            \bgroup\aftergroup#2\aftergroup\egroup % 15 adj
          \fi
        \fi
```

```
        \bbl@dirlevel\currentgrouplevel
      \fi
      #1%
    \fi}
\def\bbl@pardir#1{\chardef\bbl@thepardir#1\relax}
\let\bbl@bodydir\@gobble
\def\bbl@dirparastext{\chardef\bbl@thepardir\bbl@thetextdir}
```

The following command is executed only if there is a right-to-left script (once). It activates the `\everypar` hack for xetex, to properly handle the par direction. Note text and par dirs are decoupled to some extent (although not completely).

```
\def\bbl@xebidipar{%
  \let\bbl@xebidipar\relax
  \TeXXeTstate\@ne
  \def\bbl@xeeverypar{%
    \ifcase\bbl@thepardir
      \ifcase\bbl@thetextdir\else\beginR\fi
    \else
      {\setbox\z@\lastbox\beginR\box\z@}%
    \fi}%
  \AddToHook{para/begin}{\bbl@xeeverypar}}
\ifnum\bbl@bidimode>200 % Any xe bidi=
  \let\bbl@textdir@i\@gobbletwo
  \let\bbl@xebidipar\@empty
  \AddBabelHook{bidi}{foreign}{%
    \ifcase\bbl@thetextdir
      \BabelWrapText{\LR{##1}}%
    \else
      \BabelWrapText{\RL{##1}}%
    \fi}
  \def\bbl@pardir#1{\ifcase#1\relax\setLR\else\setRL\fi}
\fi
\fi
```

A tool for weak L (mainly digits). We also disable warnings with hyperref. There is a variant for `bidi=unibidi`, but using formatting characters is discouraged by Unicode UAX9, so it must be revised.

```
\providecommand\bbl@sublr[1]{\bbl@textdir\z@#1}
\DeclareRobustCommand\babelsublr[1]{\leavevmode{\bbl@sublr{#1}}}
\AtBeginDocument{%
  \ifx\pdfstringdefDisableCommands\@undefined\else
    \ifx\pdfstringdefDisableCommands\relax\else
      \pdfstringdefDisableCommands{\let\babelsublr\@firstofone}%
    \fi
  \fi}
```

4.7. Local Language Configuration

\loadlocalcfg At some sites it may be necessary to add site-specific actions to a language definition file. This can be done by creating a file with the same name as the language definition file, but with the extension `.cfg`. For instance the file `norsk.cfg` will be loaded when the language definition file `norsk.ldf` is loaded.

For plain-based formats we don't want to override the definition of `\loadlocalcfg` from `plain.def`.

```
\bbl@trace{Local Language Configuration}
\ifx\loadlocalcfg\@undefined
  \@ifpackagewith{babel}{noconfigs}%
    {\let\loadlocalcfg\@gobble}%
    {\def\loadlocalcfg#1{%
      \InputIfFileExists{#1.cfg}%
        {\typeout{**********************************^^J%
                        * Local config file #1.cfg used^^J%
                        *}}%
```

```
        \@empty}}
\fi
```

4.8. Language options

Languages are loaded when processing the corresponding option *except* if a `main` language has been set. In such a case, it is not loaded until all options has been processed. The following macro inputs the ldf file and does some additional checks (`\input` works, too, but possible errors are not caught).

```
\bbl@trace{Language options}
\def\BabelDefinitionFile#1#2#3{}
\let\bbl@afterlang\relax
\let\BabelModifiers\relax
\let\bbl@loaded\@empty
\def\bbl@load@language#1{%
  \InputIfFileExists{#1.ldf}%
    {\edef\bbl@loaded{\CurrentOption
       \ifx\bbl@loaded\@empty\else,\bbl@loaded\fi}%
     \expandafter\let\expandafter\bbl@afterlang
        \csname\CurrentOption.ldf-h@@k\endcsname
     \expandafter\let\expandafter\BabelModifiers
        \csname bbl@mod@\CurrentOption\endcsname
     \bbl@exp{\\\AtBeginDocument{%
       \\\bbl@usehooks@lang{\CurrentOption}{begindocument}{{\CurrentOption}}}}}%
    {\bbl@error{unknown-package-option}{}{}{}}}
```

Another way to extend the list of 'known' options for babel was to create the file `bblopts.cfg` in which one can add option declarations. However, this mechanism is deprecated – if you want an alternative name for a language, just create a new `ldf` file loading the actual one. You can also set the name of the file with the package option `config=`⟨*name*⟩, which will load ⟨*name*⟩`.cfg` instead.

If the language as been set as metadata, read the info from the corresponding `ini` file and extract the babel name. Then added it as a package option at the end, so that it becomes the main language. The behavior of a metatag with a global language option is not well defined, so if there is not a `main` option we set here explicitly.

Tagging PDF Span elements requires horizontal mode. With `DocumentMetada` we also force it with `\foreignlanguage` (this is also done in bidi texts).

```
\ifx\GetDocumentProperties\@undefined\else
  \let\bbl@beforeforeign\leavevmode
  \edef\bbl@tempa{\GetDocumentProperties{document/other-languages}}%
  \let\bbl@collect@other\@empty
  \bbl@foreach\bbl@tempa{%
    \edef\bbl@metalang{#1}%
    \ifx\bbl@metalang\@empty\else
      \begingroup
        \expandafter
        \bbl@bcplookup{\bbl@metalang}%
        \ifx\bbl@bcp\relax
          \ifx\bbl@opt@main\@nnil
            \bbl@error{no-locale-for-meta}{\bbl@metalang}{}{}%
          \fi
        \else
          \bbl@read@ini{\bbl@bcp}\m@ne
          \xdef\bbl@collect@other{\bbl@collect@other,\languagename}%
          \GenericInfo{}{(babel) \@spaces\@spaces\@spaces
             Passing '\languagename' to babel\@gobble}%
        \fi
      \endgroup
    \fi}
  \ifx\bbl@collect@other\@empty\else
    \xdef\bbl@language@opts{\bbl@collect@other,\bbl@language@opts}%
  \fi
  \edef\bbl@metalang{\GetDocumentProperties{document/language}}%
  \ifx\bbl@metalang\@empty\else
    \begingroup
```

```
      \expandafter
      \bbl@bcplookup{\bbl@metalang}%
      \ifx\bbl@bcp\relax
        \ifx\bbl@opt@main\@nnil
          \bbl@error{no-locale-for-meta}{\bbl@metalang}{}{}%
        \fi
      \else
        \bbl@read@ini{\bbl@bcp}\m@ne
        \xdef\bbl@language@opts{\bbl@language@opts,\languagename}%
        \ifx\bbl@opt@main\@nnil
          \global\let\bbl@opt@main\languagename
        \fi
        \GenericInfo{}{(babel) \@spaces\@spaces\@spaces
             Passing '\languagename' to babel\@gobble}%
      \fi
    \endgroup
  \fi
\fi
\ifx\bbl@opt@config\@nnil
  \@ifpackagewith{babel}{noconfigs}{}%
    {\InputIfFileExists{bblopts.cfg}%
      {\bbl@info{Configuration files are deprecated, as\\%
                    they can break document portability.\\%
                    Reported}%
       \typeout{**************************************^^J%
               * Local config file bblopts.cfg used^^J%
               *}}%
      {}}%
\else
  \InputIfFileExists{\bbl@opt@config.cfg}%
    {\bbl@info{Configuration files are deprecated, as\\%
                  they can break document portability.\\%
                  Reported}%
     \typeout{**************************************^^J%
             * Local config file \bbl@opt@config.cfg used^^J%
             *}}%
    {\bbl@error{config-not-found}{}{}{}}%
\fi
```

Recognizing global options in packages not having a closed set of them is not trivial, as for them to be processed they must be defined explicitly. So, package options not yet taken into account and stored in `bbl@language@opts` are assumed to be languages. If not declared above, the names of the option and the file are the same. We first pre-process the class and package options to determine the available locales, and which version (`ldf` or `ini` will be loaded. This is done by first loading the corresponding `babel-`⟨*name*⟩`.tex` file.

The second argument of `\BabelBeforeIni` may content a `\BabelDefinitionFile` which defines `\bbl@tempa` and `\bbl@tempb` and saves the third argument for the moment of the actual loading. If there is no `\BabelDefinitionFile` the last element is usually empty, and the `ini` file is loaded. The values are used to build a list in the form 'main-or-not' `/` 'ldf-or-ldfini-flag' `//` 'option-name' `//` 'bcp-tag' `/` 'ldf-name-or-none'. The 'main-or-not' element is `0` by default and set to `10` later if necessary (by prepending `1`). The 'bcp-tag' is stored here so that the corresponding `ini` file can be be loaded directly (with `@import`).

```
\def\BabelBeforeIni#1#2{%
  \def\bbl@tempa{\@m}% <- Default if no \BDefFile
  \let\bbl@tempb\@empty
  #2%
  \edef\bbl@toload{%
    \ifx\bbl@toload\@empty\else\bbl@toload,\fi
    \bbl@toload@last}%
  \edef\bbl@toload@last{0/\bbl@tempa//\CurrentOption//#1/\bbl@tempb}}
\def\BabelDefinitionFile#1#2#3{%
  \def\bbl@tempa{#1}\def\bbl@tempb{#2}%
  \@namedef{bbl@preldf@\CurrentOption}{#3}%
```

```
  \endinput}%
```

For efficiency, first preprocess the class options to remove those with =, which are becoming increasingly frequent (no language should contain this character). Here we use the more robust macro to traverse a clist from the LaTeX3 layer.

```
\def\bbl@tempf{,}
\@nameuse{clist_map_inline:Nn}\@raw@classoptionslist{%
  \in@{=}{#1}%
  \ifin@\else
    \edef\bbl@tempf{\bbl@tempf\zap@space#1 \@empty,}%
  \fi}
```

Store the class/package options in a list. If there is an explicit `main`, it's placed as the last option. Then loop it to read the `tex` files, which can have a `\BabelDefinitionFile`. If there is no `tex` file, we attempt loading the ldf for the option name; if it fails, an error is raised. Note the option name is surrounded by `//.../`. Class and package options are separated with `@@`, because errors and info are dealt with in different ways. Consecutive identical languages count as one.

```
\let\bbl@toload\@empty
\let\bbl@toload@last\@empty
\let\bbl@unkopt\@gobble  %% <- Ugly
\edef\bbl@tempc{%
 \bbl@tempf,@@,\bbl@language@opts
 \ifx\bbl@opt@main\@nnil\else,\bbl@opt@main\fi}
\let\BabelLocalesTentative\bbl@tempc
%
\bbl@foreach\bbl@tempc{%
  \in@{@@}{#1}%  <- Ugly
  \ifin@
    \def\bbl@unkopt##1{%
      \DeclareOption{##1}{\bbl@error{unknown-package-option}{}{}{}}}%
  \else
    \def\CurrentOption{#1}%
    \bbl@xin@{//#1//}{\bbl@toload@last}% Collapse consecutive
    \ifin@\else
    \lowercase{\InputIfFileExists{babel-#1.tex}}{}{%
      \IfFileExists{#1.ldf}%
        {\edef\bbl@toload{%
           \ifx\bbl@toload\@empty\else\bbl@toload,\fi
           \bbl@toload@last}%
         \edef\bbl@toload@last{0/0//\CurrentOption//und/#1}}%
        {\bbl@unkopt{#1}}}%
     \fi
  \fi}
```

We have to determine (1) if no language has be loaded (in which case we fallback to 'nil', with a special tag), and (2) the main language. With an explicit 'main' language, remove repeated elements. The number `1` flags it as the main language (relevant in *ini* locales), because with `0` becomes `10`.

```
\ifx\bbl@opt@main\@nnil
  \ifx\bbl@toload@last\@empty
    \def\bbl@toload@last{0/0//nil//und-x-nil/nil}
    \bbl@info{%
      You haven't specified a language as a class or package\\%
      option. I'll load 'nil'. Reported}
  \fi
\else
  \let\bbl@tempc\@empty
  \bbl@foreach\bbl@toload{%
    \bbl@xin@{//\bbl@opt@main//}{#1}%
    \ifin@\else
      \bbl@add@list\bbl@tempc{#1}%
    \fi}
  \let\bbl@toload\bbl@tempc
\fi
\edef\bbl@toload{\bbl@toload,1\bbl@toload@last}
```

Finally, load the ‘ini‘ file or the pair ‘ini‘/‘ldf‘ file. Babel resorts to its own mechanism, not the default one based on `\ProcessOptions` (which is still present to make some internal clean-up). First, handle `provide=!` and friends (with a recursive call if they are present), and then `provide=*` and friend. `\count@` is used as flag: 0 if ‘ini’, 1 if ‘ldf’.

```
\def\AfterBabelLanguage#1{%
  \bbl@ifsamestring\CurrentOption{#1}{\global\bbl@add\bbl@afterlang}{}}
\NewHook{babel/presets}
\UseHook{babel/presets}
%
\let\bbl@tempb\@empty
\def\bbl@tempc#1/#2//#3//#4/#5\@@{%
  \count@\z@
  \ifnum#2=\@m % if no \BabelDefinitionFile
    \ifnum#1=\z@ % not main. -- % if provide+=!, provide*=!
      \ifnum\bbl@ldfflag>\@ne\bbl@tempc 0/0//#3//#4/#3\@@
      \else\bbl@tempd{#1}{#2}{#3}{#4}{#5}%
      \fi
    \else % 10 = main --  % if provide=!, provide*=!
      \ifodd\bbl@ldfflag\bbl@tempc 10/0//#3//#4/#3\@@
      \else\bbl@tempd{#1}{#2}{#3}{#4}{#5}%
      \fi
    \fi
  \else
    \ifnum#1=\z@ % not main
      \ifnum\bbl@iniflag>\@ne\else % if ø, provide
        \ifcase#2\count@\@ne\else\ifcase\bbl@engine\count@\@ne\fi\fi
      \fi
    \else % 10 = main
      \ifodd\bbl@iniflag\else % if provide+, provide*
        \ifcase#2\count@\@ne\else\ifcase\bbl@engine\count@\@ne\fi\fi
      \fi
    \fi
    \bbl@tempd{#1}{#2}{#3}{#4}{#5}%
  \fi}
```

Based on the value of `\count@`, do the actual loading. If ‘ldf’, we load the basic info from the ‘ini’ file before.

```
\def\bbl@tempd#1#2#3#4#5{%
  \DeclareOption{#3}{}%
  \ifcase\count@
    \bbl@exp{\\\bbl@add\\\bbl@tempb{%
      \global\let\\\bbl@afterload\\\@empty
      \\\@nameuse{bbl@preini@#3}%
      \\\bbl@ldfinit
      \def\\\CurrentOption{#3}%
      \\\babelprovide[@import=#4,\ifnum#1=\z@\else\bbl@opt@provide,main\fi]{#3}%
      \\\bbl@afterldf
      \\\bbl@afterload}}%
  \else
    \bbl@add\bbl@tempb{%
      \global\let\bbl@afterload\@empty
      \def\CurrentOption{#3}%
      \let\localename\CurrentOption
      \let\languagename\localename
      \def\BabelIniTag{#4}%
      \@nameuse{bbl@preldf@#3}%
      \begingroup
        \bbl@id@assign
        \bbl@read@ini{\BabelIniTag}0%
      \endgroup
      \bbl@load@language{#5}%
      \bbl@afterload}%
  \fi}
```

```
%
\bbl@foreach\bbl@toload{\bbl@tempc#1\@@}
\bbl@tempb
\DeclareOption*{}
\ProcessOptions
%
\bbl@exp{%
  \\\AtBeginDocument{\\\bbl@usehooks@lang{/}{begindocument}{{}}}}%
\def\AfterBabelLanguage{\bbl@error{late-after-babel}{}{}{}}
\AddToHook{begindocument/end}{%
  \bbl@info{Main language set to '\mainlocalename'\@gobble}}
⟨/package⟩
```

5. Tagging

Preliminary and experimental. Only `\foreignlanguage`, for the moment. Requires the package option `babel-metadata=tagging`. Also changes for `\DocumentMetadata`. Option `babel-metadata=on` makes these changes without activating the changes for tagging.

```
⟨*tagging⟩
\ifx\bbl@chfmt\@undefined\else
  \EditInstance{heading}{chapter}{%
    prefix = ,
    number-format = \unskip\bbl@chfmt
   }
\fi
\ifx\bbl@partformat\@undefined\else
  \EditInstance{heading}{part}{%
    prefix = ,
    number-format = \unskip\bbl@partformat
   }
\fi
\@ifpackagewith{babel}{babel-metadata=tagging}{}{\endinput}
% Still only foreign and document. Select is pending:
\let\bbl@ifmetadata\IfDocumentMetadataT
\ExplSyntaxOn
\tagpdfsetup{
  role/new-attribute = {babel-dir-rl}{/O/Layout/WritingMode/RlTb},
  role/new-attribute = {babel-dir-lr}{/O/Layout/WritingMode/LrTb} }
%
\AddToHook{begindocument/end}{%
  \ifcase\bbl@thepardir\else
    \tag_struct_gput:nnn{\tag_get:n{struct_num}}{attribute}{/O/Layout/WritingMode/RlTb}%
  \fi}
%
\NewTaggingSocket{babel/foreign/begin}{0}
\NewTaggingSocket{babel/foreign/end}{0}
\NewTaggingSocketPlug{babel/foreign/begin}{default}{
  \tag_mc_end_push:
  \bbl@array@get\bbl@select@opts{phoneme}\bbl@tempa
  \ifx\bbl@tempa\relax\let\bbl@tempa\@empty\fi
  \bbl@array@get\bbl@select@opts{actualtext}\bbl@tempb
  \ifx\bbl@tempb\relax\let\bbl@tempb\@empty\fi
  \bbl@exp{%
    \\\tagstructbegin{tag=Span, lang=\BCPdata{tag},
      \ifnum\bbl@bidimode>\z@
        attribute=babel-dir-\ifcase\bbl@thetextdir lr\else rl\fi,
      \fi
      phoneme={\bbl@tempa}, actualtext={\bbl@tempb}}}%
  \tagmcbegin {} }
\NewTaggingSocketPlug{babel/foreign/end}{default}{
  \tagmcend
  \tagstructend
```

```
  \tag_mc_begin_pop:n {}}
\AssignTaggingSocketPlug{babel/foreign/begin}{default}
\AssignTaggingSocketPlug{babel/foreign/end}{default}
\ExplSyntaxOff
%
\AddBabelHook{babel-pdftagging}{afterextras}{%
  \IfBabelSelectorTF{select}%
    {\ifvmode
       \bbl@ifsamestring{\BCPdata{tag}}{\BCPdata{main.tag}}%
         {\tagpdfsetup{text/lang=}}
         {\tagpdfsetup{text/lang=\BCPdata{tag}}}%
     \else
       \bbl@once{select-tag-vmode}{%
         \bbl@warning{%
           PDF language tagging with \string\selectlanguage\\%
           requires vertical mode. Reported}}%
     \fi}%
    {}}
⟨/tagging⟩
```

6. Error messages

They are loaded when `\bll@error` is first called. To save space, the main code just identifies them with a tag, and messages are stored in a separate file. Since it can be loaded anywhere, you make sure some catcodes have the right value, although those for `\`, `` ` ``, `^^M`, `%` and `=` are reset before loading the file.

```
⟨*errors⟩
\catcode`\{=1  \catcode`\}=2  \catcode`\#=6
\catcode`\:=12 \catcode`\,=12 \catcode`\.=12 \catcode`\-=12
\catcode`\'=12 \catcode`\(=12 \catcode`\)=12
\catcode`\@=11 \catcode`\^=7
%
\ifx\MessageBreak\@undefined
  \gdef\bbl@error@i#1#2{%
    \begingroup
      \newlinechar=`\^^J
      \def\\{^^J(babel) }%
      \errhelp{#2}\errmessage{\\#1}%
    \endgroup}
\else
  \gdef\bbl@error@i#1#2{%
    \begingroup
      \def\\{\MessageBreak}%
      \PackageError{babel}{#1}{#2}%
    \endgroup}
\fi
\def\bbl@errmessage#1#2#3{%
  \expandafter\gdef\csname bbl@err@#1\endcsname##1##2##3{%
    \bbl@error@i{#2}{#3}}}
% Implicit #2#3#4:
\gdef\bbl@error#1{\csname bbl@err@#1\endcsname}
%
\bbl@errmessage{not-yet-available}
    {Not yet available}%
    {Find an armchair, sit down and wait}
\bbl@errmessage{bad-package-option}%
   {Bad option '#1=#2'. Either you have misspelled the\\%
    key or there is a previous setting of '#1'. Valid\\%
    keys are, among others, 'shorthands', 'main', 'bidi',\\%
    'strings', 'config', 'headfoot', 'safe', 'math'.}%
   {See the manual for further details.}
\bbl@errmessage{base-on-the-fly}
```

```
   {For a language to be defined on the fly 'base'\\%
    is not enough, and the whole package must be\\%
    loaded. Either delete the 'base' option or\\%
    request the languages explicitly}%
   {See the manual for further details.}
\bbl@errmessage{undefined-language}
   {You haven't defined the language '#1' yet.\\%
    Perhaps you misspelled it or your installation\\%
    is not complete}%
   {Your command will be ignored, type <return> to proceed}
\bbl@errmessage{invalid-ini-name}
     {'#1' not valid with the 'ini' mechanism.\\%
      I think you want '#2' instead. You may continue,\\%
      but you should fix the name. See the babel manual\\%
      for the available locales with 'provide'}%
     {See the manual for further details.}
\bbl@errmessage{shorthand-is-off}
   {I can't declare a shorthand turned off (\string#2)}
   {Sorry, but you can't use shorthands which have been\\%
    turned off in the package options}
\bbl@errmessage{not-a-shorthand}
   {The character '\string #1' should be made a shorthand character;\\%
    add the command \string\useshorthands\string{#1\string} to
    the preamble.\\%
    I will ignore your instruction}%
   {You may proceed, but expect unexpected results}
\bbl@errmessage{not-a-shorthand-b}
   {I can't switch '\string#2' on or off--not a shorthand\\%
    This character is not a shorthand. Maybe you made\\%
    a typing mistake?}%
   {I will ignore your instruction.}
\bbl@errmessage{unknown-attribute}
   {The attribute #2 is unknown for language #1.}%
   {Your command will be ignored, type <return> to proceed}
\bbl@errmessage{missing-group}
   {Missing group for string \string#1}%
   {You must assign strings to some category, typically\\%
    captions or extras, but you set none}
\bbl@errmessage{only-lua-xe}
   {This macro is available only in LuaLaTeX and XeLaTeX.}%
   {Consider switching to these engines.}
\bbl@errmessage{only-lua}
   {This macro is available only in LuaLaTeX}%
   {Consider switching to that engine.}
\bbl@errmessage{unknown-provide-key}
   {Unknown key '#1' in \string\babelprovide}%
   {See the manual for valid keys}%
\bbl@errmessage{unknown-mapfont}
   {Option '\bbl@KVP@mapfont' unknown for\\%
    mapfont. Use 'direction'}%
   {See the manual for details.}
\bbl@errmessage{no-ini-file}
   {There is no ini file for the requested language\\%
    (#1: \languagename). Perhaps you misspelled it or your\\%
    installation is not complete}%
   {Fix the name or reinstall babel.}
\bbl@errmessage{digits-is-reserved}
   {The counter name 'digits' is reserved for mapping\\%
    decimal digits}%
   {Use another name.}
\bbl@errmessage{limit-two-digits}
   {Currently two-digit years are restricted to the\\5
    range 0-9999}%
```

```
   {There is little you can do. Sorry.}
\bbl@errmessage{counter-too-large}
 {Counter too large (#1)}%
 {Currently this is the limit.}
\bbl@errmessage{no-ini-info}
   {I've found no info for the current locale.\\%
    The corresponding ini file has not been loaded\\%
    Perhaps it doesn't exist}%
   {See the manual for details.}
\bbl@errmessage{unknown-ini-field}
   {Unknown field '#1' in \string\BCPdata.\\%
    Perhaps you misspelled it}%
   {See the manual for details.}
\bbl@errmessage{unknown-locale-key}
   {Unknown key for locale '#2':\\%
    #3\\%
    \string#1 will be set to \string\relax}%
   {Perhaps you misspelled it.}%
\bbl@errmessage{adjust-only-vertical}
   {Currently, #1 related features can be adjusted only\\%
    in the main vertical list}%
   {Maybe things change in the future, but this is what it is.}
\bbl@errmessage{layout-only-vertical}
   {Currently, layout related features can be adjusted only\\%
    in vertical mode}%
   {Maybe things change in the future, but this is what it is.}
\bbl@errmessage{bidi-only-lua}
   {The bidi method 'basic' is available only in\\%
    luatex. I'll continue with 'bidi=default', so\\%
    expect wrong results.\\%
    Suggested actions:\\%
    * If possible, switch to luatex, as xetex is not\\%
      recommend anymore.\\%
    * If you can't, try 'bidi=bidi' with xetex.\\%
    * With pdftex, only 'bidi=default' is available.}%
   {See the manual for further details.}
\bbl@errmessage{multiple-bidi}
   {Multiple bidi settings inside a group\\%
    I'll insert a new group, but expect wrong results.\\%
    Suggested action:\\%
    * Add a new group where appropriate.}
   {See the manual for further details.}
\bbl@errmessage{unknown-package-option}
   {Unknown option '\CurrentOption'.\\%
    Suggested actions:\\%
    * Make sure you haven't misspelled it\\%
    * Check in the babel manual that it's supported\\%
    * If supported and it's a language, you may\\%
    \space\space  need in some distributions a separate\\%
    \space\space  installation\\%
    * If installed, check there isn't an old\\%
    \space\space version of the required files in your system\\%
    * If it's an unsupported language, create it with\\%
    \space\space \string\babelprovide\space (see the manual)}
   {Valid options are, among others: shorthands=, KeepShorthandsActive,\\%
    activeacute, activegrave, noconfigs, safe=, main=, math=\\%
    headfoot=, strings=, config=, hyphenmap=, or a language name.}
\bbl@errmessage{config-not-found}
   {Local config file '\bbl@opt@config.cfg' not found.\\%
    Suggested actions:\\%
    * Make sure you haven't misspelled it in config=\\%
    * Check it exists and it's in the correct path}%
   {Perhaps you misspelled it.}
```

```
\bbl@errmessage{late-after-babel}
   {Too late for \string\AfterBabelLanguage}%
   {Languages have been loaded, so I can do nothing}
\bbl@errmessage{double-hyphens-class}
   {Double hyphens aren't allowed in \string\babelcharclass\\%
    because it's potentially ambiguous}%
   {See the manual for further info}
\bbl@errmessage{unknown-interchar}
   {'#1' for '\languagename' cannot be enabled.\\%
    Maybe there is a typo}%
   {See the manual for further details.}
\bbl@errmessage{unknown-interchar-b}
   {'#1' for '\languagename' cannot be disabled.\\%
    Maybe there is a typo}%
   {See the manual for further details.}
\bbl@errmessage{charproperty-only-vertical}
   {\string\babelcharproperty\space can be used only in\\%
    vertical mode (preamble or between paragraphs)}%
   {See the manual for further info}
\bbl@errmessage{unknown-char-property}
   {No property named '#2'. Allowed values are\\%
    direction (bc), mirror (bmg), and linebreak (lb)}%
   {See the manual for further info}
\bbl@errmessage{bad-transform-option}
   {Bad option '#1' in a transform.\\%
    I'll ignore it but expect more errors}%
   {See the manual for further info.}
\bbl@errmessage{font-conflict-transforms}
   {Transforms cannot be re-assigned to different\\%
    fonts. The conflict is in '\bbl@kv@label'.\\%
    Apply the same fonts or use a different label}%
   {See the manual for further details.}
\bbl@errmessage{transform-not-available}
   {'#1' for '\languagename' cannot be enabled.\\%
    Maybe there is a typo or it's a font-dependent transform}%
   {See the manual for further details.}
\bbl@errmessage{transform-not-available-b}
   {'#1' for '\languagename' cannot be disabled.\\%
    Maybe there is a typo or it's a font-dependent transform}%
   {See the manual for further details.}
\bbl@errmessage{year-out-range}
   {Year out of range.\\%
    The allowed range is #1}%
   {See the manual for further details.}
\bbl@errmessage{only-pdftex-lang}
   {The '#1' ldf style doesn't work with #2,\\%
    but you can use the ini locale instead.\\%
    Try adding 'provide=*' to the option list. You may\\%
    also want to set 'bidi=' to some value}%
   {See the manual for further details.}
\bbl@errmessage{hyphenmins-args}
   {\string\babelhyphenmins\ accepts either the optional\\%
    argument or the star, but not both at the same time}%
   {See the manual for further details.}
\bbl@errmessage{no-locale-for-meta}
   {There isn't currently a locale for the 'lang' requested\\%
    in the PDF metadata ('#1'). To fix it, you can\\%
    set explicitly a similar language (using the same\\%
    script) with the key main= when loading babel. If you\\%
    continue, I'll fallback to the 'nil' language, with\\%
    tag 'und' and script 'Latn', but expect a bad font\\%
    rendering with other scripts. You may also need set\\%
    explicitly captions and date, too}%
```

```
4807    {See the manual for further details.}
4808 ⟨/errors⟩
4809 ⟨*patterns⟩
```

7. Loading hyphenation patterns

The following code is meant to be read by iniTEX because it should instruct TEX to read hyphenation patterns. To this end the `docstrip` option `patterns` is used to include this code in the file `hyphen.cfg`. Code is written with lower level macros.

```
4810 <@Make sure ProvidesFile is defined@>
4811 \ProvidesFile{hyphen.cfg}[<@date@> v<@version@> Babel hyphens]
4812 \xdef\bbl@format{\jobname}
4813 \def\bbl@version{<@version@>}
4814 \def\bbl@date{<@date@>}
4815 \ifx\AtBeginDocument\@undefined
4816   \def\@empty{}
4817 \fi
4818 <@Define core switching macros@>
```

\process@line Each line in the file `language.dat` is processed by `\process@line` after it is read. The first thing this macro does is to check whether the line starts with =. When the first token of a line is an =, the macro `\process@synonym` is called; otherwise the macro `\process@language` will continue.

```
4819 \def\process@line#1#2 #3 #4 {%
4820   \ifx=#1%
4821     \process@synonym{#2}%
4822   \else
4823     \process@language{#1#2}{#3}{#4}%
4824   \fi
4825   \ignorespaces}
```

\process@synonym This macro takes care of the lines which start with an =. It needs an empty token register to begin with. `\bbl@languages` is also set to empty.

```
4826 \toks@{}
4827 \def\bbl@languages{}
```

When no languages have been loaded yet, the name following the = will be a synonym for hyphenation register 0. So, it is stored in a token register and executed when the first pattern file has been processed. (The `\relax` just helps to the `\if` below catching synonyms without a language.)

Otherwise the name will be a synonym for the language loaded last.

We also need to copy the hyphenmin parameters for the synonym.

```
4828 \def\process@synonym#1{%
4829   \ifnum\last@language=\m@ne
4830     \toks@\expandafter{\the\toks@\relax\process@synonym{#1}}%
4831   \else
4832     \expandafter\chardef\csname l@#1\endcsname\last@language
4833     \wlog{\string\l@#1=\string\language\the\last@language}%
4834     \expandafter\let\csname #1hyphenmins\expandafter\endcsname
4835       \csname\languagename hyphenmins\endcsname
4836     \let\bbl@elt\relax
4837     \edef\bbl@languages{\bbl@languages\bbl@elt{#1}{\the\last@language}{}{}}%
4838   \fi}
```

\process@language The macro `\process@language` is used to process a non-empty line from the 'configuration file'. It has three arguments, each delimited by white space. The first argument is the 'name' of a language; the second is the name of the file that contains the patterns. The optional third argument is the name of a file containing hyphenation exceptions.

The first thing to do is call `\addlanguage` to allocate a pattern register and to make that register 'active'. Then the pattern file is read.

For some hyphenation patterns it is needed to load them with a specific font encoding selected. This can be specified in the file `language.dat` by adding for instance '`:T1`' to the name of the

language. The macro \bbl@get@enc extracts the font encoding from the language name and stores it in \bbl@hyph@enc. The latter can be used in hyphenation files if you need to set a behavior depending on the given encoding (it is set to empty if no encoding is given).

Pattern files may contain assignments to \lefthyphenmin and \righthyphenmin. TEX does not keep track of these assignments. Therefore we try to detect such assignments and store them in the \⟨*language*⟩hyphenmins macro. When no assignments were made we provide a default setting.

Some pattern files contain changes to the \lccode en \uccode arrays. Such changes should remain local to the language; therefore we process the pattern file in a group; the \patterns command acts globally so its effect will be remembered.

Then we globally store the settings of \lefthyphenmin and \righthyphenmin and close the group.

When the hyphenation patterns have been processed we need to see if a file with hyphenation exceptions needs to be read. This is the case when the third argument is not empty and when it does not contain a space token. (Note however there is no need to save hyphenation exceptions into the format.)

\bbl@languages saves a snapshot of the loaded languages in the form \bbl@elt{⟨*language-name*⟩}{⟨*number*⟩}{⟨*patterns-file*⟩}{⟨*exceptions-file*⟩}. Note the last 2 arguments are empty in 'dialects' defined in language.dat with =. Note also the language name can have encoding info.

Finally, if the counter \language is equal to zero we execute the synonyms stored.

```
\def\process@language#1#2#3{%
  \expandafter\addlanguage\csname l@#1\endcsname
  \expandafter\language\csname l@#1\endcsname
  \edef\languagename{#1}%
  \bbl@hook@everylanguage{#1}%
  %  > luatex
  \bbl@get@enc#1::\@@@
  \begingroup
    \lefthyphenmin\m@ne
    \bbl@hook@loadpatterns{#2}%
    %  > luatex
    \ifnum\lefthyphenmin=\m@ne
    \else
      \expandafter\xdef\csname #1hyphenmins\endcsname{%
        \the\lefthyphenmin\the\righthyphenmin}%
    \fi
  \endgroup
  \def\bbl@tempa{#3}%
  \ifx\bbl@tempa\@empty\else
    \bbl@hook@loadexceptions{#3}%
    %  > luatex
  \fi
  \let\bbl@elt\relax
  \edef\bbl@languages{%
    \bbl@languages\bbl@elt{#1}{\the\language}{#2}{\bbl@tempa}}%
  \ifnum\the\language=\z@
    \expandafter\ifx\csname #1hyphenmins\endcsname\relax
      \set@hyphenmins\tw@\thr@@\relax
    \else
      \expandafter\expandafter\expandafter\set@hyphenmins
        \csname #1hyphenmins\endcsname
    \fi
    \the\toks@
    \toks@{}%
  \fi}
```

\bbl@get@enc
\bbl@hyph@enc The macro \bbl@get@enc extracts the font encoding from the language name and stores it in \bbl@hyph@enc. It uses delimited arguments to achieve this.

```
\def\bbl@get@enc#1:#2:#3\@@@{\def\bbl@hyph@enc{#2}}
```

Now, hooks are defined. For efficiency reasons, they are dealt here in a special way. Besides luatex, format-specific configuration files are taken into account. \bbl@hook@loadkernel currently loads nothing, but define some basic macros instead.

```
\def\bbl@hook@everylanguage#1{}
\def\bbl@hook@loadpatterns#1{\input #1\relax}
\let\bbl@hook@loadexceptions\bbl@hook@loadpatterns
\def\bbl@hook@loadkernel#1{%
  \def\addlanguage{\csname newlanguage\endcsname}%
  \def\adddialect##1##2{%
    \global\chardef##1##2\relax
    \wlog{\string##1 = a dialect from \string\language##2}}%
  \def\iflanguage##1{%
    \expandafter\ifx\csname l@##1\endcsname\relax
      \@nolanerr{##1}%
    \else
      \ifnum\csname l@##1\endcsname=\language
        \expandafter\expandafter\expandafter\@firstoftwo
      \else
        \expandafter\expandafter\expandafter\@secondoftwo
      \fi
    \fi}%
  \def\providehyphenmins##1##2{%
    \expandafter\ifx\csname ##1hyphenmins\endcsname\relax
      \@namedef{##1hyphenmins}{##2}%
    \fi}%
  \def\set@hyphenmins##1##2{%
    \lefthyphenmin##1\relax
    \righthyphenmin##2\relax}%
  \def\selectlanguage{%
    \errhelp{Selecting a language requires a package supporting it}%
    \errmessage{No multilingual package has been loaded}}%
  \let\foreignlanguage\selectlanguage
  \let\otherlanguage\selectlanguage
  \expandafter\let\csname otherlanguage*\endcsname\selectlanguage
  \def\bbl@usehooks##1##2{}%
  \def\setlocale{%
    \errhelp{Find an armchair, sit down and wait}%
    \errmessage{(babel) Not yet available}}%
  \let\uselocale\setlocale
  \let\locale\setlocale
  \let\selectlocale\setlocale
  \let\localename\setlocale
  \let\textlocale\setlocale
  \let\textlanguage\setlocale
  \let\languagetext\setlocale}
\begingroup
  \def\AddBabelHook#1#2{%
    \expandafter\ifx\csname bbl@hook@#2\endcsname\relax
      \def\next{\toks1}%
    \else
      \def\next{\expandafter\gdef\csname bbl@hook@#2\endcsname####1}%
    \fi
    \next}
  \ifx\directlua\@undefined
    \ifx\XeTeXinputencoding\@undefined\else
      \input xebabel.def
    \fi
  \else
    \input luababel.def
  \fi
  \openin1 = babel-\bbl@format.cfg
  \ifeof1
  \else
    \input babel-\bbl@format.cfg\relax
  \fi
  \closein1
```

```
\endgroup
\bbl@hook@loadkernel{switch.def} % Dummy argument
```

\readconfigfile The configuration file can now be opened for reading.

```
\openin1 = language.dat
```

See if the file exists, if not, use the default hyphenation file `hyphen.tex`. The user will be informed about this.

```
\def\languagename{english}%
\ifeof1
  \message{I couldn't find the file language.dat,\space
           I will try the file hyphen.tex}
  \input hyphen.tex\relax
  \chardef\l@english\z@
\else
```

Pattern registers are allocated using count register `\last@language`. Its initial value is 0. The definition of the macro `\newlanguage` is such that it first increments the count register and then defines the language. In order to have the first patterns loaded in pattern register number 0 we initialize `\last@language` with the value -1.

```
  \last@language\m@ne
```

We now read lines from the file until the end is found. While reading from the input, it is useful to switch off recognition of the end-of-line character. This saves us stripping off spaces from the contents of the control sequence.

```
  \loop
    \endlinechar\m@ne
    \read1 to \bbl@line
    \endlinechar`\^^M
```

If the file has reached its end, exit from the loop here. If not, empty lines are skipped. Add 3 space characters to the end of `\bbl@line`. This is needed to be able to recognize the arguments of `\process@line` later on. The default language should be the very first one.

```
    \if T\ifeof1F\fi T\relax
      \ifx\bbl@line\@empty\else
        \edef\bbl@line{\bbl@line\space\space\space}%
        \expandafter\process@line\bbl@line\relax
      \fi
  \repeat
```

Check for the end of the file. We must reverse the test for `\ifeof` without `\else`. Then reactivate the default patterns, and close the configuration file.

```
  \begingroup
    \def\bbl@elt#1#2#3#4{%
      \global\language=#2\relax
      \gdef\languagename{#1}%
      \def\bbl@elt##1##2##3##4{}}%
    \bbl@languages
  \endgroup
\fi
\closein1
```

We add a message about the fact that babel is loaded in the format and with which language patterns to the `\everyjob` register.

```
\if/\the\toks@/\else
  \errhelp{language.dat loads no language, only synonyms}
  \errmessage{Orphan language synonym}
\fi
```

Also remove some macros from memory and raise an error if `\toks@` is not empty.

```
\let\bbl@line\@undefined
\let\process@line\@undefined
\let\process@synonym\@undefined
```

```
\let\process@language\@undefined
\let\bbl@get@enc\@undefined
\let\bbl@hyph@enc\@undefined
\let\bbl@tempa\@undefined
\let\bbl@hook@loadkernel\@undefined
\let\bbl@hook@everylanguage\@undefined
\let\bbl@hook@loadpatterns\@undefined
\let\bbl@hook@loadexceptions\@undefined
⟨/patterns⟩
```

Here the code for iniTEX ends.

8. luatex + xetex: common stuff

Add the bidi handler just before luaotfload, which is loaded by default by LaTeX. Just in case, consider the possibility it has not been loaded. First, a couple of definitions related to bidi (although `default` also applies to pdftex).

```
⟨⟨*More package options⟩⟩ ▸
\chardef\bbl@bidimode\z@
\DeclareOption{bidi=default}{\chardef\bbl@bidimode=\@ne}
\DeclareOption{bidi=basic}{\chardef\bbl@bidimode=101 }
\DeclareOption{bidi=basic-r}{\chardef\bbl@bidimode=102 }
\DeclareOption{bidi=bidi}{\chardef\bbl@bidimode=201 }
\DeclareOption{bidi=bidi-r}{\chardef\bbl@bidimode=202 }
\DeclareOption{bidi=bidi-l}{\chardef\bbl@bidimode=203 }
\DeclareOption{bidi=unibidi}{\chardef\bbl@bidimode=301 }
⟨⟨/More package options⟩⟩
```

\babelfont With explicit languages, we could define the font at once, but we don't. Just wait and see if the language is actually activated. `bbl@font` replaces hardcoded font names inside `\..family` by the corresponding macro `\..default`.

```
⟨⟨*Font selection⟩⟩ ▸
\bbl@trace{Font handling with fontspec}
\AddBabelHook{babel-fontspec}{afterextras}{\bbl@switchfont}
\AddBabelHook{babel-fontspec}{beforestart}{\bbl@ckeckstdfonts}
\DisableBabelHook{babel-fontspec}
\@onlypreamble\babelfont
\ifx\NewDocumentCommand\@undefined\else % Not plain
  \NewDocumentCommand\babelfont{O{}mO{}mO{}}{%
    \bbl@bblfont@o[#1]{#2}[#3,#5]{#4}}
\fi
\newcommand\bbl@bblfont@o[2][]{%  1=langs/scripts 2=fam
  \ifx\fontspec\@undefined
    \usepackage{fontspec}%
  \fi
  \EnableBabelHook{babel-fontspec}%
  \edef\bbl@tempa{#1}%
  \def\bbl@tempb{#2}%  Used by \bbl@bblfont
  \bbl@bblfont}
\newcommand\bbl@bblfont[2][]{% 1=features 2=fontname, @font=rm|sf|tt
  \bbl@ifunset{\bbl@tempb family}%
    {\bbl@providefam{\bbl@tempb}}%
    {}%
  % For the default font, just in case:
  \bbl@ifunset{bbl@lsys@\languagename}{\bbl@provide@lsys{\languagename}}{}%
  \expandafter\bbl@ifblank\expandafter{\bbl@tempa}%
    {\bbl@csarg\edef{\bbl@tempb dflt@}{<>{#1}{#2}}% save bbl@rmdflt@
     \bbl@exp{%
       \let\<bbl@\bbl@tempb dflt@\languagename>\<bbl@\bbl@tempb dflt@>%
       \\\bbl@font@set\<bbl@\bbl@tempb dflt@\languagename>%
                      \<\bbl@tempb default>\<\bbl@tempb family>}}%
    {\bbl@foreach\bbl@tempa{% i.e., bbl@rmdflt@lang / *scrt
```

```
      \bbl@csarg\def{\bbl@tempb dflt@##1}{<>{#1}{#2}}}}}%
```

If the family in the previous command does not exist, it must be defined. Here is how:

```
\def\bbl@providefam#1{%
  \bbl@exp{%
    \\\newcommand\<#1default>{}% Just define it
    \\\bbl@add@list\\\bbl@font@fams{#1}%
    \\\NewHook{#1family}%
    \\\DeclareRobustCommand\<#1family>{%
      \\\not@math@alphabet\<#1family>\relax
      % \\\prepare@family@series@update{#1}\<#1default>% TODO. Fails
      \\\fontfamily\<#1default>%
      \\\UseHook{#1family}%
      \\\selectfont}%
    \\\DeclareTextFontCommand{\<text#1>}{\<#1family>}}}
```

The following macro is activated when the hook `babel-fontspec` is enabled. But before, we define a macro for a warning, which sets a flag to avoid duplicate them.

```
\def\bbl@nostdfont#1{%
  \bbl@once{nostdfam-\f@family}%
    {\bbl@infowarn{The current font is not a babel standard family:\\%
       #1%
       \fontname\font\\%
       There is nothing intrinsically wrong, and you can\\%,
       ignore this message altogether if you do not need\\%
       this font. If they are used in the document, be aware\\%
       'babel' will not set Script and Language for it, so\\%
       you may consider defining a new family with \string\babelfont.\\%
       See the manual for further details about \string\babelfont.
       Reported}}%
   {}}%
\gdef\bbl@switchfont{%
  \bbl@ifunset{bbl@lsys@\languagename}{\bbl@provide@lsys{\languagename}}{}%
  \bbl@exp{%  e.g., Arabic -> arabic
    \lowercase{\edef\\\bbl@tempa{\bbl@cl{sname}}}}%
  \bbl@foreach\bbl@font@fams{%
    \bbl@ifunset{bbl@##1dflt@\languagename}%    (1) language?
      {\bbl@ifunset{bbl@##1dflt@*\bbl@tempa}%   (2) from script?
         {\bbl@ifunset{bbl@##1dflt@}%           2=F - (3) from generic?
           {}%                                  123=F - nothing!
           {\bbl@exp{%                          3=T - from generic
              \global\let\<bbl@##1dflt@\languagename>%
                        \<bbl@##1dflt@>}}}%
         {\bbl@exp{%                            2=T - from script
            \global\let\<bbl@##1dflt@\languagename>%
                       \<bbl@##1dflt@*\bbl@tempa>}}}%
      {}}%                                 1=T - language, already defined
  \def\bbl@tempa{\bbl@nostdfont{}}%
  \bbl@foreach\bbl@font@fams{%     don't gather with prev for
    \bbl@ifunset{bbl@##1dflt@\languagename}%
      {\bbl@cs{famrst@##1}%
       \global\bbl@csarg\let{famrst@##1}\relax}%
      {\bbl@exp{% order is relevant.
         \\\bbl@add\\\originalTeX{%
           \\\bbl@font@rst{\bbl@cl{##1dflt}}%
                          \<##1default>\<##1family>{##1}}%
         \\\bbl@font@set\<bbl@##1dflt@\languagename>% the main part!
                        \<##1default>\<##1family>}}}%
  \bbl@ifrestoring{}{\bbl@tempa}}%
```

The following is executed at the beginning of the aux file or the document to warn about fonts not defined with `\babelfont`.

```
\ifx\f@family\@undefined\else   % if latex
  \ifcase\bbl@engine            % if pdftex
```

```
    \let\bbl@ckeckstdfonts\relax
  \else
    \def\bbl@ckeckstdfonts{%
      \begingroup
        \global\let\bbl@ckeckstdfonts\relax
        \let\bbl@tempa\@empty
        \bbl@foreach\bbl@font@fams{%
          \bbl@ifunset{bbl@##1dflt@}%
            {\@nameuse{##1family}%
             \bbl@csarg\gdef{WFF@\f@family}{}% Flag
             \bbl@exp{\\\bbl@add\\\bbl@tempa{* \<##1family>= \f@family\\\\%
                \space\space\fontname\font\\\\}}%
             \bbl@csarg\xdef{##1dflt@}{\f@family}%
             \expandafter\xdef\csname ##1default\endcsname{\f@family}}%
            {}}%
        \ifx\bbl@tempa\@empty\else
          \bbl@infowarn{The following font families will use the default\\%
            settings for all or some languages:\\%
            \bbl@tempa
            There is nothing intrinsically wrong with it, but\\%
            'babel' will no set Script and Language, which could\\%
             be relevant in some languages. If your document uses\\%
             these families, consider redefining them with \string\babelfont.\\%
            Reported}%
        \fi
      \endgroup}
  \fi
\fi
```

Now the macros defining the font with fontspec.

When there are repeated keys in fontspec, the last value wins. So, we just place the ini settings at the beginning, and user settings will take precedence. We must deactivate temporarily `\bbl@mapselect` because `\selectfont` is called internally when a font is defined.

For historical reasons, LaTeX can select two different series (`bx` and `b`), for what is conceptually a single one. This can lead to problems when a single family requires several fonts, depending on the language, mainly because 'substitutions' with some combinations are not done consistently – sometimes `bx/sc` is the correct font, but sometimes points to `b/n`, even if `b/sc` exists. So, some substitutions are redefined (in a somewhat hackish way, by inspecting if the variant declaration contains `>ssub*`).

```
\def\bbl@font@set#1#2#3{% e.g., \bbl@rmdflt@lang \rmdefault \rmfamily
  \bbl@xin@{<>}{#1}%
  \ifin@
    \bbl@exp{\\\bbl@fontspec@set\\#1\expandafter\@gobbletwo#1\\#3}%
  \fi
  \bbl@exp{%              'Unprotected' macros return prev values
    \def\\#2{#1}%         e.g., \rmdefault{\bbl@rmdflt@lang}
    \\\bbl@ifsamestring{#2}{\f@family}%
      {\\#3%
       \\\bbl@ifsamestring{\f@series}{\bfdefault}{\\\bfseries}{}%
       \let\\\bbl@tempa\relax}%
      {}}}
```

Loaded locally, which does its job, but very must be global. The problem is how. This actually defines a font predeclared with `\babelfont`, making sure `Script` and `Language` names are defined. If they are not, the corresponding data in the ini file is used. The font is actually set temporarily to get the family name (`\f@family`). There is also a hack because by default some replacements related to the bold series are sometimes assigned to the wrong font (see issue #92).

```
\def\bbl@fontspec@lsys{%
  \ifx\newfontscript\@undefined\else\bbl@exp{%
    \<keys_if_exist:nnF>{fontspec-opentype}{Script/\bbl@cl{sname}}%
      {\\\newfontscript{\bbl@cl{sname}}{\bbl@cl{sotf}}}%
    \<keys_if_exist:nnF>{fontspec-opentype}{Language/\bbl@cl{lname}}%
       {\\\newfontlanguage{\bbl@cl{lname}}{\bbl@cl{lotf}}}}%
  \fi}
```

```
\ifx\AddToHook\@undefined
  \let\bbl@fontspec@lsys\relax
\else
  \AddToHook{selectfont}{\bbl@fontspec@lsys}
\fi
\def\bbl@fontspec@set#1#2#3#4{% eg \bbl@rmdflt@lang fnt-opt fnt-nme \xxfamily
  \let\bbl@tempe\bbl@mapselect
  \edef\bbl@tempb{\bbl@stripslash#4/}% Catcodes hack (better pass it).
  \bbl@exp{\\\bbl@replace\\\bbl@tempb{\bbl@stripslash\family/}{}}%
  \let\bbl@mapselect\relax
  \let\bbl@temp@fam#4%       e.g., '\rmfamily', to be restored below
  \let#4\@empty      %       Make sure \renewfontfamily is valid
  \bbl@set@renderer
  \bbl@fontspec@lsys
  \bbl@exp{%
    \let\\\bbl@temp@pfam\<\bbl@stripslash#4\space>% e.g., '\rmfamily '
    \\\renewfontfamily\\#4%
      [\bbl@cl{lsys},% xetex removes unknown features :-(
       \ifcase\bbl@engine\or RawFeature={family=\bbl@tempb},\fi
       #2]}{#3}% i.e., \bbl@exp{..}{#3}
  \bbl@unset@renderer
  \begingroup
     #4%
     \xdef#1{\f@family}%     e.g., \bbl@rmdflt@lang{FreeSerif(0)}
  \endgroup
  \bbl@xin@{\detokenize{>ssub*}}%
    {\expandafter\meaning\csname TU/#1/bx/sc\endcsname}%
  \ifin@
    \global\bbl@ccarg\let{TU/#1/bx/sc}{TU/#1/b/sc}%
  \fi
  \bbl@xin@{\detokenize{>ssub*}}%
    {\expandafter\meaning\csname TU/#1/bx/scit\endcsname}%
  \ifin@
    \global\bbl@ccarg\let{TU/#1/bx/scit}{TU/#1/b/scit}%
  \fi
  \let#4\bbl@temp@fam
  \bbl@exp{\let\<\bbl@stripslash#4\space>}\bbl@temp@pfam
  \let\bbl@mapselect\bbl@tempe}%
```

`font@rst` and `famrst` are only used when there is no global settings, to save and restore de previous families. Not really necessary, but done for optimization.

```
\def\bbl@font@rst#1#2#3#4{%
  \bbl@csarg\def{famrst@#4}{\bbl@font@set{#1}#2#3}}
```

The default font families. They are eurocentric, but the list can be expanded easily with `\babelfont`.

```
\def\bbl@font@fams{rm,sf,tt}
```

⟨⟨/Font selection⟩⟩

9. Hooks for XeTeX and LuaTeX

9.1. XeTeX

Unfortunately, the current encoding cannot be retrieved and therefore it is reset always to `utf8`, which seems a sensible default.

Now, the code.

```
⟨*xetex⟩
\def\BabelStringsDefault{unicode}
\let\xebbl@stop\relax
\AddBabelHook{xetex}{encodedcommands}{%
  \def\bbl@tempa{#1}%
  \ifx\bbl@tempa\@empty
```

```
    \XeTeXinputencoding"bytes"%
  \else
    \XeTeXinputencoding"#1"%
  \fi
  \def\xebbl@stop{\XeTeXinputencoding"utf8"}}
\AddBabelHook{xetex}{stopcommands}{%
  \xebbl@stop
  \let\xebbl@stop\relax}
\def\bbl@input@classes{% Used in CJK intraspaces
  \input{load-unicode-xetex-classes.tex}%
  \let\bbl@input@classes\relax}
\def\bbl@intraspace#1 #2 #3\@@{%
  \bbl@csarg\gdef{xeisp@\languagename}%
    {\XeTeXlinebreakskip #1em plus #2em minus #3em\relax}}
\def\bbl@intrapenalty#1\@@{%
  \bbl@csarg\gdef{xeipn@\languagename}%
    {\XeTeXlinebreakpenalty #1\relax}}
\def\bbl@provide@intraspace{%
  \bbl@xin@{/s}{/\bbl@cl{lnbrk}}%
  \ifin@\else\bbl@xin@{/c}{/\bbl@cl{lnbrk}}\fi
  \ifin@
    \bbl@ifunset{bbl@intsp@\languagename}{}%
      {\expandafter\ifx\csname bbl@intsp@\languagename\endcsname\@empty\else
        \ifx\bbl@KVP@intraspace\@nnil
           \bbl@exp{%
             \\\bbl@intraspace\bbl@cl{intsp}\\\@@}%
        \fi
        \ifx\bbl@KVP@intrapenalty\@nnil
          \bbl@intrapenalty0\@@
        \fi
      \fi
      \ifx\bbl@KVP@intraspace\@nnil\else % We may override the ini
        \expandafter\bbl@intraspace\bbl@KVP@intraspace\@@
      \fi
      \ifx\bbl@KVP@intrapenalty\@nnil\else
        \expandafter\bbl@intrapenalty\bbl@KVP@intrapenalty\@@
      \fi
      \bbl@exp{%
        \\\bbl@add\<extras\languagename>{%
          \XeTeXlinebreaklocale "\bbl@cl{tbcp}"%
          \<bbl@xeisp@\languagename>%
          \<bbl@xeipn@\languagename>}%
        \\\bbl@toglobal\<extras\languagename>%
        \\\bbl@add\<noextras\languagename>{%
          \XeTeXlinebreaklocale ""}%
        \\\bbl@toglobal\<noextras\languagename>}%
      \ifx\bbl@ispacesize\@undefined
        \gdef\bbl@ispacesize{\bbl@cl{xeisp}}%
        \ifx\AtBeginDocument\@notprerr
          \expandafter\@secondoftwo  % to execute right now
        \fi
        \AtBeginDocument{\bbl@patchfont{\bbl@ispacesize}}%
      \fi}%
  \fi}
\ifx\DisableBabelHook\@undefined\endinput\fi
\let\bbl@set@renderer\relax
\let\bbl@unset@renderer\relax
<@Font selection@>
\def\bbl@provide@extra#1{}
```

Hack for unhyphenated line breaking. See `\bbl@provide@lsys` in the common code.

```
\def\bbl@xenohyph@d{%
  \bbl@ifset{bbl@prehc@\languagename}%
```

```
    {\ifnum\hyphenchar\font=\defaulthyphenchar
       \iffontchar\font\bbl@cl{prehc}\relax
         \hyphenchar\font\bbl@cl{prehc}\relax
       \else\iffontchar\font"200B
         \hyphenchar\font"200B
       \else
         \bbl@warning
           {Neither 0 nor ZERO WIDTH SPACE are available\\%
            in the current font, and therefore the hyphen\\%
            will be printed. Try changing the fontspec's\\%
            'HyphenChar' to another value, but be aware\\%
            this setting is not safe (see the manual).\\%
            Reported}%
         \hyphenchar\font\defaulthyphenchar
       \fi\fi
     \fi}%
    {\hyphenchar\font\defaulthyphenchar}}
```

9.2. Support for interchar

xetex reserves some values for CJK (although they are not set in XELATEX), so we make sure they are skipped. Define some user names for the global classes, too.

```
\ifnum\xe@alloc@intercharclass<\thr@@
  \xe@alloc@intercharclass\thr@@
\fi
\chardef\bbl@xeclass@default@=\z@
\chardef\bbl@xeclass@cjkideogram@=\@ne
\chardef\bbl@xeclass@cjkleftpunctuation@=\tw@
\chardef\bbl@xeclass@cjkrightpunctuation@=\thr@@
\chardef\bbl@xeclass@boundary@=4095
\chardef\bbl@xeclass@ignore@=4096
```

The machinery is activated with a hook (enabled only if actually used). Here `\bbl@tempc` is pre-set with `\bbl@usingxeclass`, defined below. The standard mechanism based on `\originalTeX` to save, set and restore values is used. `\count@` stores the previous char to be set, except at the beginning (0) and after `\bbl@upto`, which is the previous char negated, as a flag to mark a range.

```
\AddBabelHook{babel-interchar}{beforeextras}{%
  \@nameuse{bbl@xechars@\languagename}}
\DisableBabelHook{babel-interchar}
\protected\def\bbl@charclass#1{%
  \ifnum\count@<\z@
    \count@-\count@
    \loop
      \bbl@exp{%
        \\\babel@savevariable{\XeTeXcharclass`\Uchar\count@}}%
      \XeTeXcharclass\count@ \bbl@tempc
      \ifnum\count@<`#1\relax
      \advance\count@\@ne
    \repeat
  \else
    \babel@savevariable{\XeTeXcharclass`#1}%
    \XeTeXcharclass`#1 \bbl@tempc
  \fi
  \count@`#1\relax}
```

Now the two user macros. Char classes are declared implicitly, and then the macro to be executed at the `babel-interchar` hook is created. The list of chars to be handled by the hook defined above has internally the form `\bbl@usingxeclass\bbl@xeclass@punct@english\bbl@charclass{.}` `\bbl@charclass{,}` (etc.), where `\bbl@usingxeclass` stores the class to be applied to the subsequent characters. The `\ifcat` part deals with the alternative way to enter characters as macros (e.g., `\}`). As a special case, hyphens are stored as `\bbl@upto`, to deal with ranges.

```
\newcommand\bbl@ifinterchar[1]{%
  \let\bbl@tempa\@gobble        % Assume to ignore
```

```
  \edef\bbl@tempb{\zap@space#1 \@empty}%
  \ifx\bbl@KVP@interchar\@nnil\else
      \bbl@replace\bbl@KVP@interchar{ }{,}%
      \bbl@foreach\bbl@tempb{%
        \bbl@xin@{,##1,}{,\bbl@KVP@interchar,}%
        \ifin@
          \let\bbl@tempa\@firstofone
        \fi}%
  \fi
  \bbl@tempa}
\newcommand\IfBabelIntercharT[2]{%
  \bbl@carg\bbl@add{bbl@icsave@\CurrentOption}{\bbl@ifinterchar{#1}{#2}}}%
\newcommand\babelcharclass[3]{%
  \EnableBabelHook{babel-interchar}%
  \bbl@csarg\newXeTeXintercharclass{xeclass@#2@#1}%
  \def\bbl@tempb##1{%
    \ifx##1\@empty\else
      \ifx##1-%
        \bbl@upto
      \else
        \bbl@charclass{%
          \ifcat\noexpand##1\relax\bbl@stripslash##1\else\string##1\fi}%
      \fi
      \expandafter\bbl@tempb
    \fi}%
  \bbl@ifunset{bbl@xechars@#1}%
    {\toks@{%
       \babel@savevariable\XeTeXinterchartokenstate
       \XeTeXinterchartokenstate\@ne
      }}%
    {\toks@\expandafter\expandafter\expandafter{%
       \csname bbl@xechars@#1\endcsname}}%
  \bbl@csarg\edef{xechars@#1}{%
    \the\toks@
    \bbl@usingxeclass\csname bbl@xeclass@#2@#1\endcsname
    \bbl@tempb#3\@empty}}
\protected\def\bbl@usingxeclass#1{\count@\z@ \let\bbl@tempc#1}
\protected\def\bbl@upto{%
  \ifnum\count@>\z@
    \advance\count@\@ne
    \count@-\count@
  \else\ifnum\count@=\z@
    \bbl@charclass{-}%
  \else
    \bbl@error{double-hyphens-class}{}{}{}%
  \fi\fi}
```

And finally, the command with the code to be inserted. If the language doesn't define a class, then use the global one, as defined above. For the definition there is a intermediate macro, which can be 'disabled' with `\bbl@ic@`⟨*label*⟩`@`⟨*language*⟩.

```
\def\bbl@ignoreinterchar{%
  \ifnum\language=\l@nohyphenation
    \expandafter\@gobble
  \else
    \expandafter\@firstofone
  \fi}
\newcommand\babelinterchar[5][]{%
  \let\bbl@kv@label\@empty
  \bbl@forkv{#1}{\bbl@csarg\edef{kv@##1}{##2}}%
  \@namedef{\zap@space bbl@xeinter@\bbl@kv@label @#3@#4@#2 \@empty}%
    {\bbl@ignoreinterchar{#5}}%
  \bbl@csarg\let{ic@\bbl@kv@label @#2}\@firstofone
  \bbl@exp{\\\bbl@for\\\bbl@tempa{\zap@space#3 \@empty}}{%
```

```
    \bbl@exp{\\\bbl@for\\\bbl@tempb{\zap@space#4 \@empty}}{%
      \XeTeXinterchartoks
        \@nameuse{bbl@xeclass@\bbl@tempa @%
          \bbl@ifunset{bbl@xeclass@\bbl@tempa @#2}{}{#2}} %
        \@nameuse{bbl@xeclass@\bbl@tempb @%
          \bbl@ifunset{bbl@xeclass@\bbl@tempb @#2}{}{#2}} %
        = \expandafter{%
           \csname bbl@ic@\bbl@kv@label @#2\expandafter\endcsname
           \csname\zap@space bbl@xeinter@\bbl@kv@label
              @#3@#4@#2 \@empty\endcsname}}}
\DeclareRobustCommand\enablelocaleinterchar[1]{%
  \bbl@ifunset{bbl@ic@#1@\languagename}%
    {\bbl@error{unknown-interchar}{#1}{}{}}%
    {\bbl@csarg\let{ic@#1@\languagename}\@firstofone}}
\DeclareRobustCommand\disablelocaleinterchar[1]{%
  \bbl@ifunset{bbl@ic@#1@\languagename}%
    {\bbl@error{unknown-interchar-b}{#1}{}{}}%
    {\bbl@csarg\let{ic@#1@\languagename}\@gobble}}
⟨/xetex⟩
```

9.3. Layout

Note elements like headlines and margins can be modified easily with packages like fancyhdr, typearea or titleps, and geometry.

`\bbl@startskip` and `\bbl@endskip` are available to package authors. Thanks to the TEX expansion mechanism the following constructs are valid: `\adim\bbl@startskip`, `\advance\bbl@startskip\adim`, `\bbl@startskip\adim`.

Consider `txtbabel` as a shorthand for *tex–xet babel*, which is the bidi model in both pdftex and xetex.

```
⟨*xetex|texxet⟩
\providecommand\bbl@provide@intraspace{}
\bbl@trace{Redefinitions for bidi layout}
```

Finish here if there in no `layout`.

```
\ifx\bbl@opt@layout\@nnil\else % if layout=..
  \ifx\bbl@opt@layout\@undefined\else % Plain
    \IfBabelLayout{nopars}
      {}
     {\edef\bbl@opt@layout{\bbl@opt@layout.pars.}}%
  \fi
\def\bbl@startskip{\ifcase\bbl@thepardir\leftskip\else\rightskip\fi}
\def\bbl@endskip{\ifcase\bbl@thepardir\rightskip\else\leftskip\fi}
\ifnum\bbl@bidimode>\z@
\IfBabelLayout{pars}
  {\def\@hangfrom#1{%
     \setbox\@tempboxa\hbox{{#1}}%
     \hangindent\ifcase\bbl@thepardir\wd\@tempboxa\else-\wd\@tempboxa\fi
     \noindent\box\@tempboxa}
   \def\raggedright{%
     \let\\\@centercr
     \bbl@startskip\z@skip
     \@rightskip\@flushglue
     \bbl@endskip\@rightskip
     \parindent\z@
     \parfillskip\bbl@startskip}
   \def\raggedleft{%
     \let\\\@centercr
     \bbl@startskip\@flushglue
     \bbl@endskip\z@skip
     \parindent\z@
     \parfillskip\bbl@endskip}}
  {}
\fi
```

```
\IfBabelLayout{lists}
  {\bbl@sreplace\list
     {\@totalleftmargin\leftmargin}{\@totalleftmargin\bbl@listleftmargin}%
   \def\bbl@listleftmargin{%
     \ifcase\bbl@thepardir\leftmargin\else\rightmargin\fi}%
   \ifcase\bbl@engine
     \def\labelenumii{)\theenumii(}% pdftex doesn't reverse ()
     \def\p@enumiii{\p@enumii)\theenumii(}%
   \fi
   \bbl@sreplace\@verbatim
     {\leftskip\@totalleftmargin}%
     {\bbl@startskip\textwidth
      \advance\bbl@startskip-\linewidth}%
   \bbl@sreplace\@verbatim
     {\rightskip\z@skip}%
     {\bbl@endskip\z@skip}}%
  {}
\IfBabelLayout{contents}
  {\bbl@sreplace\@dottedtocline{\leftskip}{\bbl@startskip}%
   \bbl@sreplace\@dottedtocline{\rightskip}{\bbl@endskip}}
  {}
\IfBabelLayout{columns}
  {\bbl@sreplace\@outputdblcol{\hb@xt@\textwidth}{\bbl@outputhbox}%
   \def\bbl@outputhbox#1{%
     \hb@xt@\textwidth{%
       \hskip\columnwidth
       \hfil
       {\normalcolor\vrule \@width\columnseprule}%
       \hfil
       \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
       \hskip-\textwidth
       \hb@xt@\columnwidth{\box\@outputbox \hss}%
       \hskip\columnsep
       \hskip\columnwidth}}%
  {}
```

Implicitly reverses sectioning labels in `bidi=basic`, because the full stop is not in contact with L numbers any more. I think there must be a better way.

```
\IfBabelLayout{counters*}%
  {\bbl@add\bbl@opt@layout{.counters.}%
   \AddToHook{shipout/before}{%
     \let\bbl@tempa\babelsublr
     \let\babelsublr\@firstofone
     \let\bbl@save@thepage\thepage
     \protected@edef\thepage{\thepage}%
     \let\babelsublr\bbl@tempa}%
   \AddToHook{shipout/after}{%
     \let\thepage\bbl@save@thepage}}{}
\IfBabelLayout{counters}%
  {\let\bbl@latinarabic=\@arabic
   \def\@arabic#1{\babelsublr{\bbl@latinarabic#1}}%
   \let\bbl@asciiroman=\@roman
   \def\@roman#1{\babelsublr{\ensureascii{\bbl@asciiroman#1}}}%
   \let\bbl@asciiRoman=\@Roman
   \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asciiRoman#1}}}}{}
\fi % end if layout
```

⟨/xetex | texxet⟩

9.4. 8-bit TeX

Which start just above, because some code is shared with xetex. Now, 8-bit specific stuff. If just one encoding has been declared, then assume no switching is necessary (1).

⟨*texxet⟩

```
\def\bbl@provide@extra#1{%
  % == auto-select encoding ==
  \ifx\bbl@encoding@select@off\@empty\else
    \bbl@ifunset{bbl@encoding@#1}%
      {\def\@elt##1{,##1,}%
       \edef\bbl@tempe{\expandafter\@gobbletwo\@fontenc@load@list}%
       \count@\z@
       \bbl@foreach\bbl@tempe{%
         \def\bbl@tempd{##1}%  Save last declared
         \advance\count@\@ne}%
       \ifnum\count@>\@ne    % (1)
         \getlocaleproperty*\bbl@tempa{#1}{identification/encodings}%
         \ifx\bbl@tempa\relax \let\bbl@tempa\@empty \fi
         \bbl@replace\bbl@tempa{ }{,}%
         \global\bbl@csarg\let{encoding@#1}\@empty
         \bbl@xin@{,\bbl@tempd,}{,\bbl@tempa,}%
         \ifin@\else % if main encoding included in ini, do nothing
           \let\bbl@tempb\relax
           \bbl@foreach\bbl@tempa{%
             \ifx\bbl@tempb\relax
               \bbl@xin@{,##1,}{,\bbl@tempe,}%
               \ifin@\def\bbl@tempb{##1}\fi
             \fi}%
           \ifx\bbl@tempb\relax\else
             \bbl@exp{%
               \global\<bbl@add>\<bbl@preextras@#1>{\<bbl@encoding@#1>}%
             \gdef\<bbl@encoding@#1>{%
               \\\babel@save\\\f@encoding
               \\\bbl@add\\\originalTeX{\\\selectfont}%
               \\\fontencoding{\bbl@tempb}%
               \\\selectfont}}%
           \fi
         \fi
       \fi}%
      {}%
  \fi}
```
⟨/texxet⟩

9.5. LuaTeX

The loader for luatex is based solely on `language.dat`, which is read on the fly. The code shouldn't be executed when the format is build, so we check if `\AddBabelHook` is defined. Then comes a modified version of the loader in `hyphen.cfg` (without the hyphenmins stuff, which is under the direct control of babel).

The names `\l@`⟨*language*⟩ are defined and take some value from the beginning because all `ldf` files assume this for the corresponding language to be considered valid, but patterns are not loaded (except the first one). This is done later, when the language is first selected (which usually means when the `ldf` finishes). If a language has been loaded, `\bbl@hyphendata@`⟨*num*⟩ exists (with the names of the files read).

The default setup preloads the first language into the format. This is intended mainly for 'english', so that it's available without further intervention from the user. To avoid duplicating it, the following rule applies: if the "0th" language and the first language in `language.dat` have the same name then just ignore the latter. If there are new synonymous, the are added, but note if the language patterns have not been preloaded they won't at run time.

Other preloaded languages could be read twice, if they have been preloaded into the format. This is not optimal, but it shouldn't happen very often – with luatex patterns are best loaded when the document is typeset, and the "0th" language is preloaded just for backwards compatibility.

As of 1.1b, lua(e)tex is taken into account. Formerly, loading of patterns on the fly didn't work in this format, but with the new loader it does. Unfortunately, the format is not based on babel, and data could be duplicated, because languages are reassigned above those in the format (nothing serious, anyway). Note even with this format `language.dat` is used (under the principle of a single source), instead of `language.def`.

Of course, there is room for improvements, like tools to read and reassign languages, which would require modifying the language list, and better error handling.

We need catcode tables, but no format (targeted by babel) provide a command to allocate them (although there are packages like ctablestack). FIX - This isn't true anymore. For the moment, a dangerous approach is used - just allocate a high random number and cross the fingers. To complicate things, etex.sty changes the way languages are allocated.

This files is read at three places: (1) when `plain.def`, `babel.sty` starts, to read the list of available languages from `language.dat` (for the `base` option); (2) at hyphen.cfg, to modify some macros; (3) in the middle of `plain.def` and `babel.sty`, by `babel.def`, with the commands and other definitions for `luatex` (e.g., `\babelpatterns`).

```
⟨*luatex⟩
\directlua{ Babel = Babel or {} } % DL2
\ifx\AddBabelHook\@undefined % When plain.def, babel.sty starts
\bbl@trace{Read language.dat}
\ifx\bbl@readstream\@undefined
  \csname newread\endcsname\bbl@readstream
\fi
\begingroup
  \toks@{}
  \count@\z@ % 0=start, 1=0th, 2=normal
  \def\bbl@process@line#1#2 #3 #4 {%
    \ifx=#1%
      \bbl@process@synonym{#2}%
    \else
      \bbl@process@language{#1#2}{#3}{#4}%
    \fi
    \ignorespaces}
  \def\bbl@manylang{%
    \ifnum\bbl@last>\@ne
      \bbl@info{Non-standard hyphenation setup}%
    \fi
    \let\bbl@manylang\relax}
  \def\bbl@process@language#1#2#3{%
    \ifcase\count@
      \@ifundefined{zth@#1}{\count@\tw@}{\count@\@ne}%
    \or
      \count@\tw@
    \fi
    \ifnum\count@=\tw@
      \expandafter\addlanguage\csname l@#1\endcsname
      \language\allocationnumber
      \chardef\bbl@last\allocationnumber
      \bbl@manylang
      \let\bbl@elt\relax
      \xdef\bbl@languages{%
        \bbl@languages\bbl@elt{#1}{\the\language}{#2}{#3}}%
    \fi
    \the\toks@
    \toks@{}}
  \def\bbl@process@synonym@aux#1#2{%
    \global\expandafter\chardef\csname l@#1\endcsname#2\relax
    \let\bbl@elt\relax
    \xdef\bbl@languages{%
      \bbl@languages\bbl@elt{#1}{#2}{}{}}}%
  \def\bbl@process@synonym#1{%
    \ifcase\count@
      \toks@\expandafter{\the\toks@\relax\bbl@process@synonym{#1}}%
    \or
      \@ifundefined{zth@#1}{\bbl@process@synonym@aux{#1}{0}}{}%
    \else
      \bbl@process@synonym@aux{#1}{\the\bbl@last}%
    \fi}
  \ifx\bbl@languages\@undefined % Just a (sensible?) guess
```

```
    \chardef\l@english\z@
    \chardef\l@USenglish\z@
    \chardef\bbl@last\z@
    \global\@namedef{bbl@hyphendata@0}{{hyphen.tex}{}}
    \gdef\bbl@languages{%
      \bbl@elt{english}{0}{hyphen.tex}{}%
      \bbl@elt{USenglish}{0}{}{}}
  \else
    \global\let\bbl@languages@format\bbl@languages
    \def\bbl@elt#1#2#3#4{% Remove all except language 0
      \ifnum#2>\z@\else
        \noexpand\bbl@elt{#1}{#2}{#3}{#4}%
      \fi}%
    \xdef\bbl@languages{\bbl@languages}%
  \fi
  \def\bbl@elt#1#2#3#4{\@namedef{zth@#1}{}} % Define flags
  \bbl@languages
  \openin\bbl@readstream=language.dat
  \ifeof\bbl@readstream
    \bbl@warning{I couldn't find language.dat. No additional\\%
                 patterns loaded. Reported}%
  \else
    \loop
      \endlinechar\m@ne
      \read\bbl@readstream to \bbl@line
      \endlinechar`\^^M
      \if T\ifeof\bbl@readstream F\fi T\relax
        \ifx\bbl@line\@empty\else
          \edef\bbl@line{\bbl@line\space\space\space}%
          \expandafter\bbl@process@line\bbl@line\relax
        \fi
    \repeat
  \fi
  \closein\bbl@readstream
\endgroup
\bbl@trace{Macros for reading patterns files}
\def\bbl@get@enc#1:#2:#3\@@@{\def\bbl@hyph@enc{#2}}
\ifx\babelcatcodetablenum\@undefined
  \ifx\newcatcodetable\@undefined
    \def\babelcatcodetablenum{5211}
    \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
  \else
    \newcatcodetable\babelcatcodetablenum
    \newcatcodetable\bbl@pattcodes
  \fi
\else
  \def\bbl@pattcodes{\numexpr\babelcatcodetablenum+1\relax}
\fi
\def\bbl@luapatterns#1#2{%
  \bbl@get@enc#1::\@@@
  \setbox\z@\hbox\bgroup
    \begingroup
      \savecatcodetable\babelcatcodetablenum\relax
      \initcatcodetable\bbl@pattcodes\relax
      \catcodetable\bbl@pattcodes\relax
        \catcode`\#=6  \catcode`\$=3 \catcode`\&=4 \catcode`\^=7
        \catcode`\_=8  \catcode`\{=1 \catcode`\}=2 \catcode`\~=13
        \catcode`\@=11 \catcode`\^^I=10 \catcode`\^^J=12
        \catcode`\<=12 \catcode`\>=12 \catcode`\*=12 \catcode`\.=12
        \catcode`\-=12 \catcode`\/=12 \catcode`\[=12 \catcode`\]=12
        \catcode`\`=12 \catcode`\'=12 \catcode`\"=12
        \input #1\relax
      \catcodetable\babelcatcodetablenum\relax
```

```
    \endgroup
    \def\bbl@tempa{#2}%
    \ifx\bbl@tempa\@empty\else
      \input #2\relax
    \fi
  \egroup}%
\def\bbl@patterns@lua#1{%
  \language=\expandafter\ifx\csname l@#1:\f@encoding\endcsname\relax
    \csname l@#1\endcsname
    \edef\bbl@tempa{#1}%
  \else
    \csname l@#1:\f@encoding\endcsname
    \edef\bbl@tempa{#1:\f@encoding}%
  \fi\relax
  \@namedef{lu@texhyphen@loaded@\the\language}{}% Temp
  \@ifundefined{bbl@hyphendata@\the\language}%
    {\def\bbl@elt##1##2##3##4{%
       \ifnum##2=\csname l@\bbl@tempa\endcsname % #2=spanish, dutch:OT1...
         \def\bbl@tempb{##3}%
         \ifx\bbl@tempb\@empty\else % if not a synonymous
           \def\bbl@tempc{{##3}{##4}}%
         \fi
         \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
       \fi}%
     \bbl@languages
     \@ifundefined{bbl@hyphendata@\the\language}%
       {\bbl@info{No hyphenation patterns were set for\\%
                  language '\bbl@tempa'. Reported}}%
       {\expandafter\expandafter\expandafter\bbl@luapatterns
          \csname bbl@hyphendata@\the\language\endcsname}}{}}
\endinput\fi
```

Here ends `\ifx\AddBabelHook\@undefined`. A few lines are only read by HYPHEN.CFG.

```
\ifx\DisableBabelHook\@undefined
  \AddBabelHook{luatex}{everylanguage}{%
    \def\process@language##1##2##3{%
      \def\process@line####1####2 ####3 ####4 {}}}
  \AddBabelHook{luatex}{loadpatterns}{%
     \input #1\relax
     \expandafter\gdef\csname bbl@hyphendata@\the\language\endcsname
       {{#1}{}}}
  \AddBabelHook{luatex}{loadexceptions}{%
     \input #1\relax
     \def\bbl@tempb##1##2{{##1}{#1}}%
     \expandafter\xdef\csname bbl@hyphendata@\the\language\endcsname
       {\expandafter\expandafter\expandafter\bbl@tempb
        \csname bbl@hyphendata@\the\language\endcsname}}
\endinput\fi
```

Here stops reading code for HYPHEN.CFG. The following is read the 2nd time it's loaded. First, global declarations for lua.

```
\begingroup
\catcode`\%=12
\catcode`\'=12
\catcode`\"=12
\catcode`\:=12
\directlua{
  Babel.locale_props = Babel.locale_props or {}

  function Babel.lua_error(e, a)
    tex.print([[\noexpand\csname bbl@error\endcsname{]] ..
      e .. '}{' .. (a or '') .. '}{}{}')
  end

```

```
function Babel.bytes(line)
  return line:gsub("(.)",
    function (chr) return unicode.utf8.char(string.byte(chr)) end)
end

function Babel.priority_in_callback(name,description)
  for i,v in ipairs(luatexbase.callback_descriptions(name)) do
    if v == description then return i end
  end
  return false
end

function Babel.begin_process_input()
  if luatexbase and luatexbase.add_to_callback then
    luatexbase.add_to_callback('process_input_buffer',
                               Babel.bytes,'Babel.bytes')
  else
    Babel.callback = callback.find('process_input_buffer')
    callback.register('process_input_buffer',Babel.bytes)
  end
end
function Babel.end_process_input ()
  if luatexbase and luatexbase.remove_from_callback then
    luatexbase.remove_from_callback('process_input_buffer','Babel.bytes')
  else
    callback.register('process_input_buffer',Babel.callback)
  end
end

function Babel.str_to_nodes(fn, matches, base)
  local n, head, last
  if fn == nil then return nil end
  for s in string.utfvalues(fn(matches)) do
    if base.id == 7 then
      base = base.replace
    end
    n = node.copy(base)
    n.char    = s
    if not head then
      head = n
    else
      last.next = n
    end
    last = n
  end
  return head
end

Babel.linebreaking = Babel.linebreaking or {}
Babel.linebreaking.before = {}
Babel.linebreaking.after = {}
Babel.locale = {}
function Babel.linebreaking.add_before(func, pos)
  tex.print([[\noexpand\csname bbl@luahyphenate\endcsname]])
  if pos == nil then
    table.insert(Babel.linebreaking.before, func)
  else
    table.insert(Babel.linebreaking.before, pos, func)
  end
end
function Babel.linebreaking.add_after(func)
  tex.print([[\noexpand\csname bbl@luahyphenate\endcsname]])
  table.insert(Babel.linebreaking.after, func)
```

```
end

function Babel.addpatterns(pp, lg)
  local lg = lang.new(lg)
  local pats = lang.patterns(lg) or ''
  lang.clear_patterns(lg)
  for p in pp:gmatch('[^%s]+') do
    ss = ''
    for i in string.utfcharacters(p:gsub('%d', '')) do
       ss = ss .. '%d?' .. i
    end
    ss = ss:gsub('^%%d%?%.', '%%.') .. '%d?'
    ss = ss:gsub('%.%%d%?$', '%%.')
    pats, n = pats:gsub('%s' .. ss .. '%s', ' ' .. p .. ' ')
    if n == 0 then
      tex.sprint(
        [[\string\csname\space bbl@info\endcsname{New pattern: ]]
        .. p .. [[}]])
      pats = pats .. ' ' .. p
    else
      tex.sprint(
        [[\string\csname\space bbl@info\endcsname{Renew pattern: ]]
        .. p .. [[}]])
    end
  end
  lang.patterns(lg, pats)
end

Babel.characters = Babel.characters or {}
Babel.ranges = Babel.ranges or {}
function Babel.hlist_has_bidi(head)
  local has_bidi = false
  local ranges = Babel.ranges
  for item in node.traverse(head) do
    if item.id == node.id'glyph' then
      local itemchar = item.char
      local chardata = Babel.characters[itemchar]
      local dir = chardata and chardata.d or nil
      if not dir then
        for nn, et in ipairs(ranges) do
          if itemchar < et[1] then
            break
          elseif itemchar <= et[2] then
            dir = et[3]
            break
          end
        end
      end
      if dir and (dir == 'al' or dir == 'r') then
        has_bidi = true
      end
    end
  end
  return has_bidi
end
function Babel.set_chranges_b (script, chrng)
  if chrng == '' then return end
  texio.write('Package babel Info: Replacing ' .. script .. ' script ranges')
  Babel.script_blocks[script] = {}
  for s, e in string.gmatch(chrng..' ', '(.-)%.%.(.-)%s') do
    table.insert(
      Babel.script_blocks[script], {tonumber(s,16), tonumber(e,16)})
  end
```

```
  end

  function Babel.discard_sublr(str)
    if str:find( [[\string\indexentry]] ) and
         str:find( [[\string\babelsublr]] ) then
     str = str:gsub( [[\string\babelsublr%s*(%b{})]],
                     function(m) return m:sub(2,-2) end )
     end
     return str
  end
}
\endgroup
\ifx\newattribute\@undefined\else % Test for plain
  \newattribute\bbl@attr@locale % DL4
  \directlua{ Babel.attr_locale = luatexbase.registernumber'bbl@attr@locale' }
  \AddBabelHook{luatex}{beforeextras}{%
    \setattribute\bbl@attr@locale\localeid}
\fi
%
\def\BabelStringsDefault{unicode}
\let\luabbl@stop\relax
\AddBabelHook{luatex}{encodedcommands}{%
  \def\bbl@tempa{utf8}\def\bbl@tempb{#1}%
  \ifx\bbl@tempa\bbl@tempb\else
    \directlua{Babel.begin_process_input()}%
    \def\luabbl@stop{%
      \directlua{Babel.end_process_input()}}%
  \fi}%
\AddBabelHook{luatex}{stopcommands}{%
  \luabbl@stop
  \let\luabbl@stop\relax}
%
\AddBabelHook{luatex}{patterns}{%
  \@ifundefined{bbl@hyphendata@\the\language}%
    {\def\bbl@elt##1##2##3##4{%
       \ifnum##2=\csname l@#2\endcsname % #2=spanish, dutch:OT1...
         \def\bbl@tempb{##3}%
         \ifx\bbl@tempb\@empty\else % if not a synonymous
           \def\bbl@tempc{{##3}{##4}}%
         \fi
         \bbl@csarg\xdef{hyphendata@##2}{\bbl@tempc}%
       \fi}%
     \bbl@languages
     \@ifundefined{bbl@hyphendata@\the\language}%
       {\bbl@info{No hyphenation patterns were set for\\%
                  language '#2'. Reported}}%
       {\expandafter\expandafter\expandafter\bbl@luapatterns
          \csname bbl@hyphendata@\the\language\endcsname}}{}%
  \@ifundefined{bbl@patterns@}{}{%
    \begingroup
      \bbl@xin@{,\number\language,}{,\bbl@pttnlist}%
      \ifin@\else
        \ifx\bbl@patterns@\@empty\else
           \directlua{ Babel.addpatterns(
             [[\bbl@patterns@]], \number\language) }%
        \fi
        \@ifundefined{bbl@patterns@#1}%
          \@empty
          {\directlua{ Babel.addpatterns(
               [[\space\csname bbl@patterns@#1\endcsname]],
               \number\language) }}%
        \xdef\bbl@pttnlist{\bbl@pttnlist\number\language,}%
      \fi
```

```
    \endgroup}%
  \bbl@exp{%
    \bbl@ifunset{bbl@prehc@\languagename}{}%
      {\\\bbl@ifblank{\bbl@cs{prehc@\languagename}}{}%
        {\prehyphenchar=\bbl@cl{prehc}\relax}}}}
```

\babelpatterns This macro adds patterns. Two macros are used to store them: `\bbl@patterns@` for the global ones and `\bbl@patterns@`⟨*language*⟩ for language ones. We make sure there is a space between words when multiple commands are used.

```
\@onlypreamble\babelpatterns
\AtEndOfPackage{%
  \newcommand\babelpatterns[2][\@empty]{%
    \ifx\bbl@patterns@\relax
      \let\bbl@patterns@\@empty
    \fi
    \ifx\bbl@pttnlist\@empty\else
      \bbl@warning{%
        You must not intermingle \string\selectlanguage\space and\\%
        \string\babelpatterns\space or some patterns will not\\%
        be taken into account. Reported}%
    \fi
    \ifx\@empty#1%
      \protected@edef\bbl@patterns@{\bbl@patterns@\space#2}%
    \else
      \edef\bbl@tempb{\zap@space#1 \@empty}%
      \bbl@for\bbl@tempa\bbl@tempb{%
        \bbl@fixname\bbl@tempa
        \bbl@iflanguage\bbl@tempa{%
          \bbl@csarg\protected@edef{patterns@\bbl@tempa}{%
            \@ifundefined{bbl@patterns@\bbl@tempa}%
              \@empty
              {\csname bbl@patterns@\bbl@tempa\endcsname\space}%
            #2}}}%
    \fi}}
```

9.6. Southeast Asian scripts

First, some general code for line breaking, used by `\babelposthyphenation`.

Replace regular (i.e., implicit) discretionaries by spaceskips, based on the previous glyph (which I think makes sense, because the hyphen and the previous char go always together). Other discretionaries are not touched. See Unicode UAX 14.

```
\def\bbl@intraspace#1 #2 #3\@@{%
  \directlua{
    Babel.intraspaces = Babel.intraspaces or {}
    Babel.intraspaces['\csname bbl@sbcp@\languagename\endcsname'] = %
       {b = #1, p = #2, m = #3}
    Babel.locale_props[\the\localeid].intraspace = %
       {b = #1, p = #2, m = #3}
  }}
\def\bbl@intrapenalty#1\@@{%
  \directlua{
    Babel.intrapenalties = Babel.intrapenalties or {}
    Babel.intrapenalties['\csname bbl@sbcp@\languagename\endcsname'] = #1
    Babel.locale_props[\the\localeid].intrapenalty = #1
  }}
\begingroup
\catcode`\%=12
\catcode`\&=14
\catcode`\'=12
\catcode`\~=12
\gdef\bbl@seaintraspace{&
  \let\bbl@seaintraspace\relax
```

```
\directlua{
  Babel.sea_enabled = true
  Babel.sea_ranges = Babel.sea_ranges or {}
  function Babel.set_chranges (script, chrng)
    local c = 0
    for s, e in string.gmatch(chrng..' ', '(.-)%.%.(.-)%s') do
      Babel.sea_ranges[script..c]={tonumber(s,16), tonumber(e,16)}
      c = c + 1
    end
  end
  function Babel.sea_disc_to_space (head)
    local sea_ranges = Babel.sea_ranges
    local last_char = nil
    local quad = 655360      &% 10 pt = 655360 = 10 * 65536
    local item, next_item = head
    while item do
      next_item = item.next
      local i = item.id
      if i == node.id'glyph' then
        last_char = item
      elseif i == 7 and item.subtype == 3 and last_char
          and last_char.char > 0x0C99 then
        quad = font.getfont(last_char.font).size
        for lg, rg in pairs(sea_ranges) do
          if last_char.char > rg[1] and last_char.char < rg[2] then
            lg = lg:sub(1, 4)  &% Remove trailing number of, e.g., Cyrl1
            local intraspace = Babel.intraspaces[lg]
            local intrapenalty = Babel.intrapenalties[lg]
            local n
            if intrapenalty ~= 0 then
              n = node.new(14, 0)     &% penalty
              n.penalty = intrapenalty
              node.insert_before(head, item, n)
            end
            n = node.new(12, 13)      &% (glue, spaceskip)
            node.setglue(n, intraspace.b * quad,
                            intraspace.p * quad,
                            intraspace.m * quad)
            node.insert_before(head, item, n)
            node.remove(head, item)
            node.free(item)
            break
          end
        end
      end
      item = next_item
    end
  end
}&
\bbl@luahyphenate}
```

9.7. CJK line breaking

Minimal line breaking for CJK scripts, mainly intended for simple documents and short texts as a secondary language. Only line breaking, with a little stretching for justification, without any attempt to adjust the spacing. It is based on (but does not strictly follow) the Unicode algorithm.

We first need a little table with the corresponding line breaking properties. A few characters have an additional key for the width (fullwidth *vs.* halfwidth), not yet used. There is a separate file, defined below.

```
\catcode`\%=14
\gdef\bbl@cjkintraspace{%
  \let\bbl@cjkintraspace\relax
  \directlua{
```

```
    require('babel-data-cjk.lua')
    Babel.cjk_enabled = true
    function Babel.cjk_linebreak(head)
      local GLYPH = node.id'glyph'
      local last_char = nil
      local quad = 655360      % 10 pt = 655360 = 10 * 65536
      local last_class = nil
      local last_lang = nil
      for item in node.traverse(head) do
        if item.id == GLYPH then
          local lang = item.lang
          local LOCALE = node.get_attribute(item,
                Babel.attr_locale)
          local props = Babel.locale_props[LOCALE] or {}
          local class = Babel.cjk_class[item.char].c
          if props.cjk_quotes and props.cjk_quotes[item.char] then
            class = props.cjk_quotes[item.char]
          end
          if class == 'cp' then class = 'cl' % )] as CL
          elseif class == 'id' then class = 'I'
          elseif class == 'cj' then class = 'I' % loose
          end
          local br = 0
          if class and last_class and Babel.cjk_breaks[last_class][class] then
            br = Babel.cjk_breaks[last_class][class]
          end
          if br == 1 and props.linebreak == 'c' and
              lang ~= \the\l@nohyphenation\space and
              last_lang ~= \the\l@nohyphenation then
            local intrapenalty = props.intrapenalty
            if intrapenalty ~= 0 then
              local n = node.new(14, 0)     % penalty
              n.penalty = intrapenalty
              node.insert_before(head, item, n)
            end
            local intraspace = props.intraspace
            local n = node.new(12, 13)      % (glue, spaceskip)
            node.setglue(n, intraspace.b * quad,
                            intraspace.p * quad,
                            intraspace.m * quad)
            node.insert_before(head, item, n)
          end
          if font.getfont(item.font) then
            quad = font.getfont(item.font).size
          end
          last_class = class
          last_lang = lang
        else % if penalty, glue or anything else
          last_class = nil
        end
      end
      lang.hyphenate(head)
    end
  }%
  \bbl@luahyphenate}
\gdef\bbl@luahyphenate{%
  \let\bbl@luahyphenate\relax
  \directlua{
    luatexbase.add_to_callback('hyphenate',
    function (head, tail)
      if Babel.protect_tail then
        Babel.protect_tail(head, tail)
      end
```

```
      if Babel.linebreaking.before then
        for k, func in ipairs(Babel.linebreaking.before)  do
          func(head)
        end
      end
      lang.hyphenate(head)
      if Babel.cjk_enabled then
        Babel.cjk_linebreak(head)
      end
      if Babel.linebreaking.after then
        for k, func in ipairs(Babel.linebreaking.after)  do
          func(head)
        end
      end
      if Babel.set_hboxed then
        Babel.set_hboxed(head)
      end
      if Babel.sea_enabled then
        Babel.sea_disc_to_space(head)
      end
    end,
    'Babel.hyphenate')
  }}
\endgroup
%
\def\bbl@provide@intraspace{%
  \bbl@ifunset{bbl@intsp@\languagename}{}%
    {\expandafter\ifx\csname bbl@intsp@\languagename\endcsname\@empty\else
       \bbl@xin@{/c}{/\bbl@cl{lnbrk}}%
       \ifin@           % cjk
         \bbl@cjkintraspace
         \directlua{
             Babel.locale_props = Babel.locale_props or {}
             Babel.locale_props[\the\localeid].linebreak = 'c'
         }%
         \bbl@exp{\\\bbl@intraspace\bbl@cl{intsp}\\\@@}%
         \ifx\bbl@KVP@intrapenalty\@nnil
           \bbl@intrapenalty0\@@
         \fi
       \else            % sea
         \bbl@seaintraspace
         \bbl@exp{\\\bbl@intraspace\bbl@cl{intsp}\\\@@}%
         \directlua{
            Babel.sea_ranges = Babel.sea_ranges or {}
            Babel.set_chranges('\bbl@cl{sbcp}',
                               '\bbl@cl{chrng}')
         }%
         \ifx\bbl@KVP@intrapenalty\@nnil
           \bbl@intrapenalty0\@@
         \fi
       \fi
     \fi
     \ifx\bbl@KVP@intrapenalty\@nnil\else
       \expandafter\bbl@intrapenalty\bbl@KVP@intrapenalty\@@
     \fi}}
```

9.8. Arabic justification

WIP. `\bbl@arabicjust` is executed with both elongated an kashida. This must be fine tuned. The attribute kashida is set by transforms with `kashida`.

```
\ifnum\bbl@bidimode>100 \ifnum\bbl@bidimode<200
\def\bblar@chars{%
  0628,0629,062A,062B,062C,062D,062E,062F,0630,0631,0632,0633,%
```

```
  0634,0635,0636,0637,0638,0639,063A,063B,063C,063D,063E,063F,%
  0640,0641,0642,0643,0644,0645,0646,0647,0649}
\def\bblar@elongated{%
  0626,0628,062A,062B,0633,0634,0635,0636,063B,%
  063C,063D,063E,063F,0641,0642,0643,0644,0646,%
  0649,064A}
\begingroup
  \catcode`_=11 \catcode`:=11
  \gdef\bblar@nofswarn{\gdef\msg_warning:nnx##1##2##3{}}
\endgroup
\gdef\bbl@arabicjust{%
  \let\bbl@arabicjust\relax
  \newattribute\bblar@kashida
  \directlua{ Babel.attr_kashida = luatexbase.registernumber'bblar@kashida' }%
  \bblar@kashida=\z@
  \bbl@patchfont{{\bbl@parsejalt}}%
  \directlua{
    Babel.arabic.elong_map   = Babel.arabic.elong_map or {}
    Babel.arabic.elong_map[\the\localeid]   = {}
    luatexbase.add_to_callback('post_linebreak_filter',
      Babel.arabic.justify, 'Babel.arabic.justify')
    luatexbase.add_to_callback('hpack_filter',
      Babel.arabic.justify_hbox, 'Babel.arabic.justify_hbox')
  }}%
```

Save both node lists to make replacement.

```
\def\bblar@fetchjalt#1#2#3#4{%
  \bbl@exp{\\\bbl@foreach{#1}}{%
    \bbl@ifunset{bblar@JE@##1}%
      {\setbox\z@\hbox{\textdir TRT ^^^^200d\char"##1#2}}%
      {\setbox\z@\hbox{\textdir TRT ^^^^200d\char"\@nameuse{bblar@JE@##1}#2}}%
    \directlua{%
      local last = nil
      for item in node.traverse(tex.box[0].head) do
        if item.id == node.id'glyph' and item.char > 0x600 and
            not (item.char == 0x200D) then
          last = item
        end
      end
      Babel.arabic.#3['##1#4'] = last.char
    }}}
```

Elongated forms. Brute force. No rules at all, yet. The ideal: look at jalt table. And perhaps other tables (falt?, cswh?). What about kaf? And diacritic positioning?

```
\gdef\bbl@parsejalt{%
  \ifx\addfontfeature\@undefined\else
    \bbl@xin@{/e}{/\bbl@cl{lnbrk}}%
    \ifin@
      \directlua{%
        if Babel.arabic.elong_map[\the\localeid][\fontid\font] == nil then
          Babel.arabic.elong_map[\the\localeid][\fontid\font] = {}
          tex.print([[\string\csname\space bbl@parsejalti\endcsname]])
        end
      }%
    \fi
  \fi}
\gdef\bbl@parsejalti{%
  \begingroup
    \let\bbl@parsejalt\relax     % To avoid infinite loop
    \edef\bbl@tempb{\fontid\font}%
    \bblar@nofswarn
    \@nameuse{tracinglostchars}\z@
    \bblar@fetchjalt\bblar@elongated{}{from}{}%
    \bblar@fetchjalt\bblar@chars{^^^^064a}{from}{a}% Alef maksura
```

```
    \bblar@fetchjalt\bblar@chars{^^^^0649}{from}{y}% Yeh
    \addfontfeature{RawFeature=+jalt}%
    % \@namedef{bblar@JE@0643}{06AA}% todo: catch medial kaf
    \bblar@fetchjalt\bblar@elongated{}{dest}{}%
    \bblar@fetchjalt\bblar@chars{^^^^064a}{dest}{a}%
    \bblar@fetchjalt\bblar@chars{^^^^0649}{dest}{y}%
      \directlua{%
        for k, v in pairs(Babel.arabic.from) do
          if Babel.arabic.dest[k] and
              not (Babel.arabic.from[k] == Babel.arabic.dest[k]) then
            Babel.arabic.elong_map[\the\localeid][\bbl@tempb]
               [Babel.arabic.from[k]] = Babel.arabic.dest[k]
          end
        end
      }%
  \endgroup}
```

The actual justification (inspired by CHICKENIZE).

```
\begingroup
\catcode`#=11
\catcode`~=11
\directlua{

Babel.arabic = Babel.arabic or {}
Babel.arabic.from = {}
Babel.arabic.dest = {}
Babel.arabic.justify_factor = 0.95
Babel.arabic.justify_enabled = true
Babel.arabic.kashida_limit = -1

function Babel.arabic.justify(head)
  if not Babel.arabic.justify_enabled then return head end
  local HLIST = node.id'hlist'
  local line, next_line = head
  while line do
    next_line = line.next
    if line.id == HLIST then
      % The line may be replaced (and freed), even the first one (eg,
      % in \vbox), so the head is returned.
      head = Babel.arabic.justify_hlist(head, line)
    end
    line = next_line
  end
  return head
end

function Babel.arabic.justify_hbox(head, gc, size, pack)
  local has_inf = false
  if Babel.arabic.justify_enabled and pack == 'exactly' then
    for n in node.traverse_id(12, head) do
      if n.stretch_order > 0 then has_inf = true end
    end
    if not has_inf then
      head = Babel.arabic.justify_hlist(head, nil, gc, size, pack)
    end
  end
  return head
end

function Babel.arabic.justify_hlist(head, line, gc, size, pack)
  local d, new
  local k_list, k_item, pos_inline
  local width, width_new, full, k_curr, wt_pos, goal, shift
```

```
6195  local subst_done = false
6196  local elong_map = Babel.arabic.elong_map
6197  local cnt
6198  local last_line
6199  local GLYPH = node.id'glyph'
6200  local KASHIDA = Babel.attr_kashida
6201  local LOCALE = Babel.attr_locale
6202
6203  if line == nil then
6204    line = {}
6205    line.glue_sign = 1
6206    line.glue_order = 0
6207    line.head = head
6208    line.shift = 0
6209    line.width = size
6210  end
6211
6212  % Exclude last line.
6213  if ((line.next ~= nil or line.glue_sign == 1) and line.glue_order == 0) then
6214    elongs = {}     % Stores elongated candidates of each line
6215    k_list = {}     % And all letters with kashida
6216    pos_inline = 0  % Not yet used
6217
6218    for n in node.traverse_id(GLYPH, line.head) do
6219      pos_inline = pos_inline + 1 % To find where it is. Not used.
6220
6221      % Elongated glyphs
6222      if elong_map then
6223        local locale = node.get_attribute(n, LOCALE)
6224        if elong_map[locale] and elong_map[locale][n.font] and
6225            elong_map[locale][n.font][n.char] then
6226          table.insert(elongs, {node = n, locale = locale} )
6227          node.set_attribute(n.prev, KASHIDA, 0)
6228        end
6229      end
6230
6231      % Tatwil. First create a list of nodes marked with kashida. The
6232      % rest of nodes can be ignored. The list of used weigths is build
6233      % when transforms with the key kashida= are declared.
6234      if Babel.kashida_wts then
6235        local k_wt = node.get_attribute(n, KASHIDA)
6236        if k_wt > 0 then % todo. parameter for multi inserts
6237          table.insert(k_list, {node = n, weight = k_wt, pos = pos_inline})
6238        end
6239      end
6240
6241    end % of node.traverse_id
6242
6243    if #elongs == 0 and #k_list == 0 then goto next_line end
6244    full  = line.width
6245    shift = line.shift
6246    goal  = full * Babel.arabic.justify_factor % A bit crude
6247    width = node.dimensions(line.head)    % The 'natural' width
6248
6249    % == Elongated ==
6250    % Original idea taken from 'chikenize'
6251    while (#elongs > 0 and width < goal) do
6252      subst_done = true
6253      local x = #elongs
6254      local curr = elongs[x].node
6255      local oldchar = curr.char
6256      curr.char = elong_map[elongs[x].locale][curr.font][curr.char]
6257      width = node.dimensions(line.head)  % Check if the line is too wide
```

```
6258      % Substitute back if the line would be too wide and break:
6259      if width > goal then
6260        curr.char = oldchar
6261        break
6262      end
6263      % If continue, pop the just substituted node from the list:
6264      table.remove(elongs, x)
6265    end
6266
6267    % == Tatwil ==
6268    % Traverse the kashida node list so many times as required, until
6269    % the line if filled. The first pass adds a tatweel after each
6270    % node with kashida in the line, the second pass adds another one,
6271    % and so on. In each pass, add first the kashida with the highest
6272    % weight, then with lower weight and so on.
6273    if #k_list == 0 then goto next_line end
6274
6275    width = node.dimensions(line.head)    % The 'natural' width
6276    k_curr = #k_list % Traverse backwards, from the end
6277    wt_pos = 1
6278
6279    while width < goal do
6280      subst_done = true
6281      k_item = k_list[k_curr].node
6282      if k_list[k_curr].weight == Babel.kashida_wts[wt_pos] then
6283        d = node.copy(k_item)
6284        d.char = 0x0640
6285        d.yoffset = 0 % TODO. From the prev char. But 0 seems safe.
6286        d.xoffset = 0
6287        line.head, new = node.insert_after(line.head, k_item, d)
6288        width_new = node.dimensions(line.head)
6289        if width > goal or width == width_new then
6290          node.remove(line.head, new) % Better compute before
6291          node.free(new)
6292          break
6293        end
6294        if Babel.fix_diacr then
6295          Babel.fix_diacr(k_item.next)
6296        end
6297        width = width_new
6298      end
6299      if k_curr == 1 then
6300        k_curr = #k_list
6301        wt_pos = (wt_pos >= table.getn(Babel.kashida_wts)) and 1 or wt_pos+1
6302      else
6303        k_curr = k_curr - 1
6304      end
6305    end
6306
6307    % Limit the number of tatweel by removing them. Not very efficient,
6308    % but it does the job in a quite predictable way.
6309    if Babel.arabic.kashida_limit > -1 then
6310      cnt = 0
6311      local n, next_n = line.head
6312      while n do
6313        next_n = n.next
6314        if n.id == GLYPH and n.char == 0x0640 then
6315          cnt = cnt + 1
6316          if cnt > Babel.arabic.kashida_limit then
6317            line.head = node.remove(line.head, n)
6318            node.free(n)
6319          end
6320        elseif n.id == GLYPH then
```

```
          cnt = 0
        end
        n = next_n
      end
    end

    ::next_line::

    % Must take into account marks and ins, see luatex manual.
    % Have to be executed only if there are changes. Investigate
    % what's going on exactly.
    if subst_done and not gc then
      d = node.hpack(line.head, full, 'exactly')
      d.shift = shift
      head = node.insert_before(head, line, d)
      head = node.remove(head, line)
      line.head = nil  % Now in d
      node.free(line)
    end
  end % if process line
  % The list of a box (line is a table) may start with a removed tatweel
  return (line.id and head) or line.head
end
}
\endgroup
\fi\fi % ends Arabic just block: \ifnum\bbl@bidimode>100...
```

9.9. Common stuff

First, a couple of auxiliary macros to set the renderer according to the script. This is done by patching temporarily the low-level fontspec macro containing the current features set with `\defaultfontfeatures`. Admittedly this is somewhat dangerous, but that way the latter command still works as expected, because the renderer is set just before other settings. In xetex they are set to `\relax`.

```
\def\bbl@scr@node@list{%
 ,Armenian,Coptic,Cyrillic,Georgian,,Glagolitic,Gothic,%
 ,Greek,Latin,Old Church Slavonic Cyrillic,}
\ifnum\bbl@bidimode=102 % bidi-r
   \bbl@add\bbl@scr@node@list{Arabic,Hebrew,Syriac}
\fi
\def\bbl@set@renderer{%
  \bbl@xin@{\bbl@cl{sname}}{\bbl@scr@node@list}%
  \ifin@
    \let\bbl@unset@renderer\relax
  \else
    \bbl@exp{%
       \def\\\bbl@unset@renderer{%
         \def\<g__fontspec_default_fontopts_clist>{%
           \[g__fontspec_default_fontopts_clist]}}%
       \def\<g__fontspec_default_fontopts_clist>{%
         Renderer=Harfbuzz,\[g__fontspec_default_fontopts_clist]}}%
  \fi}
<@Font selection@>
```

9.10. Automatic fonts and ids switching

After defining the blocks for a number of scripts (must be extended and very likely fine tuned), we define a the function `Babel.locale_map`, which just traverse the node list to carry out the replacements. The table `loc_to_scr` stores the script range for each locale (whose id is the key), copied from this table (so that it can be modified on a locale basis); there is an intermediate table named `chr_to_loc` built on the fly for optimization, which maps a char to the locale. This locale is then used to get the `\language` as stored in `locale_props`, as well as the font (as requested). In the

latter table a key starting with / maps the font from the global one (the key) to the local one (the value). Maths are skipped and discretionaries are handled in a special way.

There are two situations where the replacement is not carried out: either the `letters` option has been set and the character is not a letter (in the TEX sense), or the current script is the same as the new one.

```
\directlua{% DL6
Babel.script_blocks = {
  ['dflt'] = {},
  ['Arab'] = {{0x0600, 0x06FF}, {0x08A0, 0x08FF}, {0x0750, 0x077F},
              {0xFE70, 0xFEFF}, {0xFB50, 0xFDFF}, {0x1EE00, 0x1EEFF}},
  ['Armn'] = {{0x0530, 0x058F}},
  ['Beng'] = {{0x0980, 0x09FF}},
  ['Cher'] = {{0x13A0, 0x13FF}, {0xAB70, 0xABBF}},
  ['Copt'] = {{0x03E2, 0x03EF}, {0x2C80, 0x2CFF}, {0x102E0, 0x102FF}},
  ['Cyrl'] = {{0x0400, 0x04FF}, {0x0500, 0x052F}, {0x1C80, 0x1C8F},
              {0x2DE0, 0x2DFF}, {0xA640, 0xA69F}},
  ['Deva'] = {{0x0900, 0x097F}, {0xA8E0, 0xA8FF}},
  ['Ethi'] = {{0x1200, 0x137F}, {0x1380, 0x139F}, {0x2D80, 0x2DDF},
              {0xAB00, 0xAB2F}},
  ['Geor'] = {{0x10A0, 0x10FF}, {0x2D00, 0x2D2F}},
  % Don't follow strictly Unicode, which places some Coptic letters in
  % the 'Greek and Coptic' block
  ['Grek'] = {{0x0370, 0x03E1}, {0x03F0, 0x03FF}, {0x1F00, 0x1FFF}},
  ['Hans'] = {{0x2E80, 0x2EFF}, {0x3000, 0x303F}, {0x31C0, 0x31EF},
              {0x3300, 0x33FF}, {0x3400, 0x4DBF}, {0x4E00, 0x9FFF},
              {0xF900, 0xFAFF}, {0xFE30, 0xFE4F}, {0xFF00, 0xFFEF},
              {0x20000, 0x2A6DF}, {0x2A700, 0x2B73F},
              {0x2B740, 0x2B81F}, {0x2B820, 0x2CEAF},
              {0x2CEB0, 0x2EBEF}, {0x2F800, 0x2FA1F}},
  ['Hebr'] = {{0x0590, 0x05FF},
              {0xFB1F, 0xFB4E}}, % <- Includes some <reserved>
  ['Jpan'] = {{0x3000, 0x303F}, {0x3040, 0x309F}, {0x30A0, 0x30FF},
              {0x4E00, 0x9FAF}, {0xFF00, 0xFFEF}},
  ['Khmr'] = {{0x1780, 0x17FF}, {0x19E0, 0x19FF}},
  ['Knda'] = {{0x0C80, 0x0CFF}},
  ['Kore'] = {{0x1100, 0x11FF}, {0x3000, 0x303F}, {0x3130, 0x318F},
              {0x4E00, 0x9FAF}, {0xA960, 0xA97F}, {0xAC00, 0xD7AF},
              {0xD7B0, 0xD7FF}, {0xFF00, 0xFFEF}},
  ['Laoo'] = {{0x0E80, 0x0EFF}},
  ['Latn'] = {{0x0000, 0x007F}, {0x0080, 0x00FF}, {0x0100, 0x017F},
              {0x0180, 0x024F}, {0x1E00, 0x1EFF}, {0x2C60, 0x2C7F},
              {0xA720, 0xA7FF}, {0xAB30, 0xAB6F}},
  ['Mahj'] = {{0x11150, 0x1117F}},
  ['Mlym'] = {{0x0D00, 0x0D7F}},
  ['Mymr'] = {{0x1000, 0x109F}, {0xAA60, 0xAA7F}, {0xA9E0, 0xA9FF}},
  ['Orya'] = {{0x0B00, 0x0B7F}},
  ['Sinh'] = {{0x0D80, 0x0DFF}, {0x111E0, 0x111FF}},
  ['Syrc'] = {{0x0700, 0x074F}, {0x0860, 0x086F}},
  ['Taml'] = {{0x0B80, 0x0BFF}},
  ['Telu'] = {{0x0C00, 0x0C7F}},
  ['Tfng'] = {{0x2D30, 0x2D7F}},
  ['Thai'] = {{0x0E00, 0x0E7F}},
  ['Tibt'] = {{0x0F00, 0x0FFF}},
  ['Vaii'] = {{0xA500, 0xA63F}},
  ['Yiii'] = {{0xA000, 0xA48F}, {0xA490, 0xA4CF}}
}

Babel.script_blocks.Cyrs = Babel.script_blocks.Cyrl
Babel.script_blocks.Hant = Babel.script_blocks.Hans
Babel.script_blocks.Kana = Babel.script_blocks.Jpan

function Babel.locale_map(head)
  if not Babel.locale_mapped then return head end
```

```
6424
6425  local LOCALE = Babel.attr_locale
6426  local GLYPH = node.id('glyph')
6427  local inmath = false
6428  local toloc_save
6429  for item in node.traverse(head) do
6430    local toloc
6431    if not inmath and item.id == GLYPH then
6432      % Optimization: build a table with the chars found
6433      if Babel.chr_to_loc[item.char] then
6434        toloc = Babel.chr_to_loc[item.char]
6435      else
6436        for lc, maps in pairs(Babel.loc_to_scr) do
6437          for _, rg in pairs(maps) do
6438            if item.char >= rg[1] and item.char <= rg[2] then
6439              Babel.chr_to_loc[item.char] = lc
6440              toloc = lc
6441              break
6442            end
6443          end
6444        end
6445        % Treat composite chars in a different fashion, because they
6446        % 'inherit' the previous locale.
6447        if (item.char >= 0x0300 and item.char <= 0x036F) or
6448           (item.char >= 0x1AB0 and item.char <= 0x1AFF) or
6449           (item.char >= 0x1DC0 and item.char <= 0x1DFF) then
6450            Babel.chr_to_loc[item.char] = -2000
6451            toloc = -2000
6452        end
6453        if not toloc then
6454          Babel.chr_to_loc[item.char] = -1000
6455        end
6456      end
6457      if toloc == -2000 then
6458        toloc = toloc_save
6459      elseif toloc == -1000 then
6460        toloc = nil
6461      end
6462      if toloc and Babel.locale_props[toloc] and
6463          Babel.locale_props[toloc].letters and
6464          tex.getcatcode(item.char) \string~= 11 then
6465        toloc = nil
6466      end
6467      if toloc and Babel.locale_props[toloc].script
6468          and Babel.locale_props[node.get_attribute(item, LOCALE)].script
6469          and Babel.locale_props[toloc].script ==
6470            Babel.locale_props[node.get_attribute(item, LOCALE)].script then
6471        toloc = nil
6472      end
6473      if toloc then
6474        if Babel.locale_props[toloc].lg then
6475          item.lang = Babel.locale_props[toloc].lg
6476          node.set_attribute(item, LOCALE, toloc)
6477        end
6478        if Babel.locale_props[toloc]['/'..item.font] then
6479          item.font = Babel.locale_props[toloc]['/'..item.font]
6480        end
6481      end
6482      toloc_save = toloc
6483    elseif not inmath and item.id == 7 then % Apply recursively
6484      item.replace = item.replace and Babel.locale_map(item.replace)
6485      item.pre     = item.pre and Babel.locale_map(item.pre)
6486      item.post    = item.post and Babel.locale_map(item.post)
```

```
    elseif item.id == node.id'math' then
      inmath = (item.subtype == 0)
    end
  end
  return head
end
}
```

The code for `\babelcharproperty` is straightforward. Just note the modified lua table can be different.

```
\newcommand\babelcharproperty[1]{%
  \count@=#1\relax
  \ifvmode
    \expandafter\bbl@chprop
  \else
    \bbl@error{charproperty-only-vertical}{}{}{}%
  \fi}
\newcommand\bbl@chprop[3][\the\count@]{%
  \@tempcnta=#1\relax
  \bbl@ifunset{bbl@chprop@#2}% {unknown-char-property}
    {\bbl@error{unknown-char-property}{}{#2}{}}%
    {}%
  \loop
    \bbl@cs{chprop@#2}{#3}%
  \ifnum\count@<\@tempcnta
    \advance\count@\@ne
  \repeat}
%
\def\bbl@chprop@direction#1{%
  \directlua{
    Babel.characters[\the\count@] =  Babel.characters[\the\count@] or {}
    Babel.characters[\the\count@]['d'] = '#1'
  }}
\let\bbl@chprop@bc\bbl@chprop@direction
%
\def\bbl@chprop@mirror#1{%
  \directlua{
    Babel.characters[\the\count@] =  Babel.characters[\the\count@] or {}
    Babel.characters[\the\count@]['m'] = '\number#1'
  }}
\let\bbl@chprop@bmg\bbl@chprop@mirror
%
\def\bbl@chprop@linebreak#1{%
  \directlua{
    Babel.cjk_characters[\the\count@] = Babel.cjk_characters[\the\count@] or {}
    Babel.cjk_characters[\the\count@]['c'] = '#1'
  }}
\let\bbl@chprop@lb\bbl@chprop@linebreak
%
\def\bbl@chprop@locale#1{%
  \directlua{
    Babel.chr_to_loc = Babel.chr_to_loc or {}
    Babel.chr_to_loc[\the\count@] =
      \bbl@ifblank{#1}{-1000}{\the\bbl@cs{id@@#1}}\space
  }}
```

Post-handling hyphenation patterns for non-standard rules, like `ff` to `ff-f`. There are still some issues with speed (not very slow, but still slow). The Lua code is below.

```
\directlua{% DL7
  Babel.nohyphenation = \the\l@nohyphenation
}
```

Now the TEX high level interface, which requires the function defined above for converting strings to functions returning a string. These functions handle the {*n*} syntax. For example, `pre={1}{1}-`

becomes `function(m) return m[1]..m[1]..'-' end`, where `m` are the matches returned after applying the pattern. With a mapped capture the functions are similar to `function(m) return Babel.capt_map(m[1],1) end`, where the last argument identifies the mapping to be applied to `m[1]`. The way it is carried out is somewhat tricky, but the effect in not dissimilar to lua `load` – save the code as string in a TeX macro, and expand this macro at the appropriate place. As `\directlua` does not take into account the current catcode of `@`, we just avoid this character in macro names (which explains the internal group, too).

```
\begingroup
\catcode`\~=12
\catcode`\%=12
\catcode`\&=14
\catcode`\|=12
\gdef\babelprehyphenation{&%
  \@ifnextchar[{\bbl@settransform{0}}{\bbl@settransform{0}[]}}
\gdef\babelposthyphenation{&%
  \@ifnextchar[{\bbl@settransform{1}}{\bbl@settransform{1}[]}}
%
\gdef\bbl@settransform#1[#2]#3#4#5{&%
  \ifcase#1
    \bbl@activateprehyphen
  \or
    \bbl@activateposthyphen
  \fi
  \begingroup
    \def\babeltempa{\bbl@add@list\babeltempb}&%
    \let\babeltempb\@empty
    \def\bbl@tempa{#5}&%
    \bbl@replace\bbl@tempa{,}{ ,}&% TODO. Ugly trick to preserve {}
    \expandafter\bbl@foreach\expandafter{\bbl@tempa}{&%
      \bbl@ifsamestring{##1}{remove}&%
        {\bbl@add@list\babeltempb{nil}}&%
        {\directlua{
           local rep = [=[##1]=]
           local three_args = '%s*=%s*([%-%d%.%a{}|]+)%s+([%-%d%.%a{}|]+)%s+([%-%d%.%a{}|]+)'
           &% Numeric passes directly: kern, penalty...
           rep = rep:gsub('^%s*(remove)%s*$', 'remove = true')
           rep = rep:gsub('^%s*(insert)%s*,', 'insert = true, ')
           rep = rep:gsub('^%s*(after)%s*,', 'after = true, ')
           rep = rep:gsub('(string)%s*=%s*([^%s,]*)', Babel.capture_func)
           rep = rep:gsub('node%s*=%s*(%a+)%s*(%a*)', Babel.capture_node)
           rep = rep:gsub( '(norule)' .. three_args,
               'norule = {' .. '%2, %3, %4' .. '}')
           if #1 == 0 or #1 == 2 then
             rep = rep:gsub( '(space)' .. three_args,
               'space = {' .. '%2, %3, %4' .. '}')
             rep = rep:gsub( '(spacefactor)' .. three_args,
               'spacefactor = {' .. '%2, %3, %4' .. '}')
             rep = rep:gsub('(kashida)%s*=%s*([^%s,]*)', Babel.capture_kashida)
             &% Transform values
             rep, n = rep:gsub( '{([%a%-%.]+)|([%a%_%.]+)}',
               function(v,d)
                 return string.format (
                   '{\the\csname bbl@id@@#3\endcsname,"%s",%s}',
                   v,
                   load( 'return Babel.locale_props'..
                         '[\the\csname bbl@id@@#3\endcsname].' .. d)() )
               end )
             rep, n = rep:gsub( '{([%a%-%.]+)|([%-%d%.]+)}',
              '{\the\csname bbl@id@@#3\endcsname,"%1",%2}')
           end
           if #1 == 1 then
             rep = rep:gsub(    '(no)%s*=%s*([^%s,]*)', Babel.capture_func)
             rep = rep:gsub(   '(pre)%s*=%s*([^%s,]*)', Babel.capture_func)
```

```
            rep = rep:gsub(  '(post)%s*=%s*([^%s,]*)', Babel.capture_func)
          end
          tex.print([[\string\babeltempa{{]] .. rep .. [[}}]])
       }}}&%
  \bbl@foreach\babeltempb{&%
    \bbl@forkv{{##1}}{&%
      \in@{,####1,}{,nil,step,data,remove,insert,string,no,pre,no,&%
        post,penalty,kashida,space,spacefactor,kern,node,after,norule,}&%
      \ifin@\else
        \bbl@error{bad-transform-option}{####1}{}{}&%
      \fi}}&%
  \let\bbl@kv@attribute\relax
  \let\bbl@kv@label\relax
  \let\bbl@kv@fonts\@empty
  \let\bbl@kv@prepend\relax
  \bbl@forkv{#2}{\bbl@csarg\edef{kv@##1}{##2}}&%
  \ifx\bbl@kv@fonts\@empty\else\bbl@settransfont\fi
  \ifx\bbl@kv@attribute\relax
    \ifx\bbl@kv@label\relax\else
      \bbl@exp{\\\bbl@trim@def\\\bbl@kv@fonts{\bbl@kv@fonts}}&%
      \bbl@replace\bbl@kv@fonts{ }{,}&%
      \edef\bbl@kv@attribute{bbl@ATR@\bbl@kv@label @#3@\bbl@kv@fonts}&%
      \count@\z@
      \def\bbl@elt##1##2##3{&%
        \bbl@ifsamestring{#3,\bbl@kv@label}{##1,##2}&%
          {\bbl@ifsamestring{\bbl@kv@fonts}{##3}&%
             {\count@\@ne}&%
             {\bbl@error{font-conflict-transforms}{}{}{}}}&%
          {}}&%
      \bbl@transfont@list
      \ifnum\count@=\z@
        \bbl@exp{\global\\\bbl@add\\\bbl@transfont@list
          {\\\bbl@elt{#3}{\bbl@kv@label}{\bbl@kv@fonts}}}&%
      \fi
      \bbl@ifunset{\bbl@kv@attribute}&%
        {\global\bbl@carg\newattribute{\bbl@kv@attribute}}&%
        {}&%
      \global\bbl@carg\setattribute{\bbl@kv@attribute}\@ne
    \fi
  \else
    \edef\bbl@kv@attribute{\expandafter\bbl@stripslash\bbl@kv@attribute}&%
  \fi
  \directlua{
    local lbkr = Babel.linebreaking.replacements[#1]
    local u = unicode.utf8
    local id, attr, label
    if #1 == 0 then
      id = \the\csname bbl@id@@#3\endcsname\space
    else
      id = \the\csname l@#3\endcsname\space
    end
    \ifx\bbl@kv@attribute\relax
      attr = -1
    \else
      attr = luatexbase.registernumber'\bbl@kv@attribute'
    \fi
    \ifx\bbl@kv@label\relax\else  &% Same refs:
      label = [==[\bbl@kv@label]==]
    \fi
    &% Convert pattern:
    local patt = string.gsub([==[#4]==], '%s', '')
    if #1 == 0 then
      patt = string.gsub(patt, '|', ' ')
```

```
      end
      if not u.find(patt, '()', nil, true) then
        patt = '()' .. patt .. '()'
      end
      patt = string.gsub(patt, '%(%)%^', '^()')
      patt = string.gsub(patt, '%$%(%)', '()$')
      patt = u.gsub(patt, '{(.)}',
             function (n)
               return '%' .. (tonumber(n) and (tonumber(n)+1) or n)
             end)
      patt = u.gsub(patt, '{(%x%x%x%x+)}',
             function (n)
               return u.gsub(u.char(tonumber(n, 16)), '(%p)', '%%%1')
             end)
      lbkr[id] = lbkr[id] or {}
      table.insert(lbkr[id], \ifx\bbl@kv@prepend\relax\else 1,\fi
        { label=label, attr=attr, pattern=patt, replace={\babeltempb} })
    }&%
  \endgroup}
\endgroup
%
\let\bbl@transfont@list\@empty
\def\bbl@settransfont{%
  \global\let\bbl@settransfont\relax % Execute only once
  \gdef\bbl@transfont{%
    \def\bbl@elt####1####2####3{%
      \bbl@ifblank{####3}%
         {\count@\tw@}% Do nothing if no fonts
         {\count@\z@
          \bbl@vforeach{####3}{%
            \def\bbl@tempd{########1}%
            \edef\bbl@tempe{\bbl@transfam/\f@series/\f@shape}%
            \ifx\bbl@tempd\bbl@tempe
              \count@\@ne
            \else\ifx\bbl@tempd\bbl@transfam
              \count@\@ne
            \fi\fi}%
         \ifcase\count@
           \bbl@csarg\unsetattribute{ATR@####2@####1@####3}%
         \or
           \bbl@csarg\setattribute{ATR@####2@####1@####3}\@ne
         \fi}}%
      \bbl@transfont@list}%
  \AddToHook{selectfont}{\bbl@transfont}% Hooks are global.
  \gdef\bbl@transfam{-unknown-}%
  \bbl@foreach\bbl@font@fams{%
    \AddToHook{##1family}{\def\bbl@transfam{##1}}%
    \bbl@ifsamestring{\@nameuse{##1default}}\familydefault
      {\xdef\bbl@transfam{##1}}%
      {}}}
%
\DeclareRobustCommand\enablelocaletransform[1]{%
  \bbl@ifunset{bbl@ATR@#1@\languagename @}%
    {\bbl@error{transform-not-available}{#1}{}{}}%
    {\bbl@csarg\setattribute{ATR@#1@\languagename @}\@ne}}
\DeclareRobustCommand\disablelocaletransform[1]{%
  \bbl@ifunset{bbl@ATR@#1@\languagename @}%
    {\bbl@error{transform-not-available-b}{#1}{}{}}%
    {\bbl@csarg\unsetattribute{ATR@#1@\languagename @}}}
```

The following two macros load the Lua code for transforms, but only once. The only difference is in `add_after` and `add_before`.

```
\def\bbl@activateposthyphen{%
```

```
  \let\bbl@activateposthyphen\relax
  \ifx\bbl@attr@hboxed\@undefined
    \newattribute\bbl@attr@hboxed
  \fi
  \directlua{
    require('babel-transforms.lua')
    Babel.linebreaking.add_after(Babel.post_hyphenate_replace)
  }}
\def\bbl@activateprehyphen{%
  \let\bbl@activateprehyphen\relax
  \ifx\bbl@attr@hboxed\@undefined
    \newattribute\bbl@attr@hboxed
  \fi
  \directlua{
    require('babel-transforms.lua')
    Babel.linebreaking.add_before(Babel.pre_hyphenate_replace)
  }}
\newcommand\SetTransformValue[3]{%
  \directlua{
    Babel.locale_props[\the\csname bbl@id@@#1\endcsname].vars["#2"] = #3
  }}
```

The code in `babel-transforms.lua` prints at some points the current string being transformed. This macro first make sure this file is loaded. Then, activates temporarily this feature and typeset inside a box the text in the argument.

```
\newcommand\ShowBabelTransforms[1]{%
  \bbl@activateprehyphen
  \bbl@activateposthyphen
  \begingroup
    \directlua{ Babel.show_transforms = true }%
    \setbox\z@\vbox{#1}%
    \directlua{ Babel.show_transforms = false }%
  \endgroup}
```

The following experimental (and unfinished) macro applies the prehyphenation transforms for the current locale to a string (characters and spaces) and processes it in a fully expandable way (among other limitations, the string can't contain `]==]`). The way it operates is admittedly rather cumbersome: it converts the string to a node list, processes it, and converts it back to a string. The lua code is in the lua file below.

```
\newcommand\localeprehyphenation[1]{%
  \directlua{ Babel.string_prehyphenation([==[#1]==], \the\localeid) }}
```

9.11. Bidi

Make sure the `\pagedir` is always the same as the `\bodydir` when the document starts. At this point the main language has been selected, and therefore its `\bodydir` has been set.

```
\AtBeginDocument{\pagedir\bodydir}
```

As a first step, add a handler for bidi and digits (and potentially other processes) just before luaoftload is applied, which is loaded by default by LaTeX. Just in case, consider the possibility it has not been loaded.

```
\def\bbl@activate@preotf{%
  \let\bbl@activate@preotf\relax  % only once
  \directlua{
    function Babel.pre_otfload_v(head)
      if Babel.numbers and Babel.digits_mapped then
        head = Babel.numbers(head)
      end
      if Babel.bidi_enabled then
        head = Babel.bidi(head, false, dir)
      end
      return head
    end
```

```
    %
    function Babel.pre_otfload_h(head, gc, sz, pt, dir)
      if Babel.numbers and Babel.digits_mapped then
        head = Babel.numbers(head)
      end
      if Babel.bidi_enabled then
        head = Babel.bidi(head, false, dir)
      end
      return head
    end
    %
    luatexbase.add_to_callback('pre_linebreak_filter',
      Babel.pre_otfload_v,
      'Babel.pre_otfload_v',
      Babel.priority_in_callback('pre_linebreak_filter',
        'luaotfload.node_processor') or nil)
    %
    luatexbase.add_to_callback('hpack_filter',
      Babel.pre_otfload_h,
      'Babel.pre_otfload_h',
      Babel.priority_in_callback('hpack_filter',
        'luaotfload.node_processor') or nil)
  }}
```

The basic setup. The output is modified at a very low level to set the `\bodydir` to the `\pagedir`. Sadly, we have to deal with boxes in math with basic, so the `\bbl@insidemath` hack is activated (set to 1) every math with the package option bidi=. The hack for the PUA is no longer necessary with `basic` (24.8), but it's kept in `basic-r`.

```
\ifnum\bbl@bidimode>\@ne % Any bidi= except default (=1)
  \let\bbl@beforeforeign\leavevmode
  \AtEndOfPackage{\EnableBabelHook{babel-bidi}}
  \ifnum\bbl@bidimode>300
    \RequirePackage{unibidi-lua}
  \else
    \RequirePackage{luatexbase}
    \bbl@activate@preotf
    \directlua{
      require('babel-data-bidi.lua')
      \ifcase\expandafter\@gobbletwo\the\bbl@bidimode\or
        require('babel-bidi-basic.lua')
      \or
        require('babel-bidi-basic-r.lua')
        table.insert(Babel.ranges, {0xE000,   0xF8FF, 'on'})
        table.insert(Babel.ranges, {0xF0000,  0xFFFFD, 'on'})
        table.insert(Babel.ranges, {0x100000, 0x10FFFD, 'on'})
      \fi}
  \fi
  \newattribute\bbl@attr@dir
  \directlua{ Babel.attr_dir = luatexbase.registernumber'bbl@attr@dir' }
  \bbl@exp{\output{\bodydir\pagedir\the\output}}
\fi
%
\chardef\bbl@thetextdir\z@
\chardef\bbl@thepardir\z@
\def\bbl@setluadir#1#2{% 1=\text/pardirection  2= 0:l 1:r 2:al
  \ifcase#2\relax
    \ifcase#1\else#1=\z@\fi
  \else
    \ifcase#1#1=\@ne\fi
  \fi}
```

`\bbl@attr@dir` stores the directions with a mask: `..00PPTT`, with masks 0xC (`PP` is the par dir) and 0x3 (`TT` is the text dir). These macro names are shared by the 3 engines, with different definitions.

```
\def\bbl@thedir{0}
```

```
\def\bbl@textdir#1{%
  \bbl@setluadir\textdirection{#1}%
  \chardef\bbl@thetextdir#1\relax
  \edef\bbl@thedir{\the\numexpr\bbl@thepardir*4+#1}%
  \setattribute\bbl@attr@dir{\numexpr\bbl@thepardir*4+#1}}
\def\bbl@pardir#1{%  Used twice
  \bbl@setluadir\pardirection{#1}%
  \chardef\bbl@thepardir#1\relax}
\def\bbl@bodydir{\bbl@setluadir\bodydirection}%   Used once
\def\bbl@dirparastext{\pardirection=\textdirection\relax}% Used once
```

RTL text inside math needs special attention. It affects not only to actual math stuff, but also to 'tabular', which is based on a fake math.

```
\ifnum\bbl@bidimode>\z@ % Any bidi=
  \def\bbl@insidemath{0}%
  \def\bbl@everymath{\def\bbl@insidemath{1}}
  \def\bbl@everydisplay{\def\bbl@insidemath{2}}
  \frozen@everymath\expandafter{%
    \expandafter\bbl@everymath\the\frozen@everymath}
  \frozen@everydisplay\expandafter{%
    \expandafter\bbl@everydisplay\the\frozen@everydisplay}
  \AtBeginDocument{
    \directlua{
      function Babel.math_box_dir(head)
        if not (token.get_macro('bbl@insidemath') == '0') then
          if Babel.hlist_has_bidi(head) then
            local d = node.new(node.id'dir')
            d.dir = '+TRT'
            for item in node.traverse(head) do
              if item.id == 11 or item.id == node.id'glyph' then
                head = node.insert_before(head, item, d)
                break
              end
            end
            local inmath = false
            for item in node.traverse(head) do
              if item.id == 11 then
                inmath = (item.subtype == 0)
              elseif not inmath then
                node.set_attribute(item,
                  Babel.attr_dir, token.get_macro('bbl@thedir'))
              end
            end
          end
        end
        return head
      end
      luatexbase.add_to_callback("hpack_filter", Babel.math_box_dir,
        "Babel.math_box_dir", 0)
      if Babel.unset_atdir then
        luatexbase.add_to_callback("pre_linebreak_filter", Babel.unset_atdir,
          "Babel.unset_atdir")
         luatexbase.add_to_callback("hpack_filter", Babel.unset_atdir,
           "Babel.unset_atdir")
       end
    luatexbase.add_to_callback("post_mlist_to_hlist_filter", function(head)
        local dir = tex.mathdirection
        local n = node.new("dir")
        n.direction = dir
        head = node.insert_before(head,head,n)
        n = node.new("dir",1)
        n.direction = dir
        head = node.insert_after(head,node.tail(head),n)
```

```
        return head
    end,"Babel.ensure_math_dir")
  }}%
\fi
\ifnum\bbl@bidimode>300
  \def\bbl@sublr#1{^^^^2066#1^^^^2069}
\fi
```

Experimental. Tentative name.

```
\DeclareRobustCommand\localebox[1]{%
  {\def\bbl@insidemath{0}%
   \mbox{\foreignlanguage{\languagename}{#1}}}}
```

9.12. Layout

Unlike xetex, luatex requires only minimal changes for right-to-left layouts, particularly in monolingual documents (the engine itself reverses boxes – including column order or headings –, margins, etc.) with `bidi=basic`, without having to patch almost any macro where text direction is relevant.

Still, there are three areas deserving special attention, namely, tabular, math, and graphics, text and intrinsically left-to-right elements are intermingled. I've made some progress in graphics, but they're essentially hacks; I've also made some progress in 'tabular', but when I decided to tackle math (both standard math and 'amsmath') the nightmare began. I'm still not sure how 'amsmath' should be modified, but the main problem is that, boxes are "generic" containers that can hold text, math, and graphics (even at the same time; remember that inline math is included in the list of text nodes marked with 'math' (11) nodes too).

`\@hangfrom` is useful in many contexts and it is redefined always with the `layout` option.

There are, however, a number of issues when the text direction is not the same as the box direction (as set by `\bodydir`), and when `\parbox` and `\hangindent` are involved. Fortunately, latest releases of luatex simplify a lot the solution with `\shapemode`.

With the issue #15 I realized commands are best patched, instead of redefined. With a few lines, a modification could be applied to several classes and packages. Now, `tabular` seems to work (at least in simple cases) with array, tabularx, hhline, colortbl, longtable, booktabs, etc. However, dcolumn still fails.

```
\bbl@trace{Redefinitions for bidi layout}
%
⟨⟨*More package options⟩⟩ ▸
\chardef\bbl@eqnpos\z@
\DeclareOption{leqno}{\chardef\bbl@eqnpos\@ne}
\DeclareOption{fleqn}{\chardef\bbl@eqnpos\tw@}
⟨⟨/More package options⟩⟩
```

Fixes in luatex are sometimes done with flags. We first activate all all them.

```
\ifnum\bbl@bidimode>\z@ % Any bidi=
  \matheqdirmode\@ne
  \mathemptydisplaymode\@ne
  \breakafterdirmode\@ne
  \fixupboxesmode\@ne
  \let\bbl@eqnodir\relax
  \def\bbl@eqdel{()}
  \def\bbl@eqnum{%
    {\normalfont\normalcolor
     \expandafter\@firstoftwo\bbl@eqdel
     \theequation
     \expandafter\@secondoftwo\bbl@eqdel}}
  \def\bbl@puteqno#1{\eqno\hbox{#1}}
  \def\bbl@putleqno#1{\leqno\hbox{#1}}
  \def\bbl@eqno@flip#1{% So
    \ifdim\predisplaysize=-\maxdimen % For consecutive displays
      \eqno
      \hb@xt@.01pt{%
        \hb@xt@\displaywidth{\hss{#1\glet\bbl@upset\@currentlabel}}\hss}%
    \else
```

```
      \leqno\hbox{#1\glet\bbl@upset\@currentlabel}%
    \fi
    \bbl@exp{\def\\\@currentlabel{\[bbl@upset]}}}
  \def\bbl@leqno@flip#1{%
    \ifdim\predisplaysize=-\maxdimen % For consecutive displays
      \leqno
      \hb@xt@.01pt{%
        \hss\hb@xt@\displaywidth{{#1\glet\bbl@upset\@currentlabel}\hss}}%
    \else
      \eqno\hbox{#1\glet\bbl@upset\@currentlabel}%
    \fi
    \bbl@exp{\def\\\@currentlabel{\[bbl@upset]}}}
%
  \AtBeginDocument{%
    \ifx\bbl@noamsmath\relax\else
    \ifx\maketag@@@\@undefined % Normal equation, eqnarray
      \ifnum\bbl@eqnpos=\tw@
        \bbl@replace\equation{\hb@xt@\linewidth}%
          {\hbox bdir\mathdirection to\linewidth}%
        \bbl@carg\bbl@sreplace{[ }{\hb@xt@\linewidth}%
          {\hbox bdir\mathdirection to\linewidth}%
      \fi
      \AddToHook{env/equation/begin}{%
        \ifnum\bbl@thetextdir>\z@
          \let\@eqnnum\bbl@eqnum
          \edef\bbl@eqnodir{\noexpand\bbl@textdir{\the\bbl@thetextdir}}%
          \chardef\bbl@thetextdir\z@
          \bbl@add\normalfont{\bbl@eqnodir}%
          \ifcase\bbl@eqnpos
            \let\bbl@puteqno\bbl@eqno@flip
          \or
            \let\bbl@puteqno\bbl@leqno@flip
          \fi
        \fi}%
      \ifnum\bbl@eqnpos=\tw@\else
        \def\endequation{\bbl@puteqno{\@eqnnum}$$\@ignoretrue}%
      \fi
      \AddToHook{env/eqnarray/begin}{%
        \ifnum\bbl@thetextdir>\z@
          \edef\bbl@eqnodir{\noexpand\bbl@textdir{\the\bbl@thetextdir}}%
          \chardef\bbl@thetextdir\z@
          \bbl@add\normalfont{\bbl@eqnodir}%
          \ifnum\bbl@eqnpos=\@ne
            \def\@eqnnum{%
              \setbox\z@\hbox{\bbl@eqnum}%
              \hbox to0.01pt{\hss\hbox to\displaywidth{\box\z@\hss}}}%
          \else
            \let\@eqnnum\bbl@eqnum
          \fi
        \fi}
    \else % amstex
      \bbl@exp{% Hack to hide maybe undefined conditionals:
        \chardef\bbl@eqnpos=0\<iftagsleft@>1\<else>\<if@fleqn>2\<fi>\<fi>\relax}%
      \ifnum\bbl@eqnpos=\@ne
        \let\bbl@ams@lap\hbox
      \else
        \let\bbl@ams@lap\llap
      \fi
      \ExplSyntaxOn % Required by \bbl@sreplace with \intertext@
      \bbl@sreplace\intertext@{\normalbaselines}%
        {\normalbaselines
         \ifx\bbl@eqnodir\relax\else\bbl@pardir\@ne\bbl@eqnodir\fi}%
      \ExplSyntaxOff
```

```
      \def\bbl@ams@tagbox#1#2{#1{\bbl@eqnodir#2}}% #1=hbox|@lap|flip
      \ifx\bbl@ams@lap\hbox % leqno
        \def\bbl@ams@flip#1{%
          \hbox to 0.01pt{\hss\hbox to\displaywidth{{#1}\hss}}}%
      \else % eqno
        \def\bbl@ams@flip#1{%
          \hbox to 0.01pt{\hbox to\displaywidth{\hss{#1}}\hss}}%
      \fi
     \def\bbl@ams@preset#1{%
        \ifnum\bbl@thetextdir>\z@
          \edef\bbl@eqnodir{\noexpand\bbl@textdir{\the\bbl@thetextdir}}%
          \bbl@sreplace\textdef@{\hbox}{\bbl@ams@tagbox\hbox}%
          \bbl@sreplace\maketag@@@{\hbox}{\bbl@ams@tagbox#1}%
        \fi}%
      \def\bbl@ams@equation{%
        \ifnum\bbl@thetextdir>\z@
          \bbl@ams@preset\hbox
          \chardef\bbl@thetextdir\z@
          \bbl@add\normalfont{\bbl@eqnodir}%
          \ifcase\bbl@eqnpos
            \def\veqno##1##2{\bbl@eqno@flip{##1##2}}%
          \or
            \def\veqno##1##2{\bbl@leqno@flip{##1##2}}%
          \fi
        \fi}%
      \AddToHook{env/equation/begin}{\bbl@ams@equation}%
      \AddToHook{env/equation*/begin}{\bbl@ams@equation}%
      \AddToHook{env/cases/begin}{\bbl@ams@preset\bbl@ams@lap}%
      \AddToHook{env/multline/begin}{\bbl@ams@preset\hbox}%
      \AddToHook{env/gather/begin}{\bbl@ams@preset\bbl@ams@lap}%
      \AddToHook{env/gather*/begin}{\bbl@ams@preset\bbl@ams@lap}%
      \AddToHook{env/align/begin}{\bbl@ams@preset\bbl@ams@lap}%
      \AddToHook{env/align*/begin}{\bbl@ams@preset\bbl@ams@lap}%
      \AddToHook{env/alignat/begin}{\bbl@ams@preset\bbl@ams@lap}%
      \AddToHook{env/alignat*/begin}{\bbl@ams@preset\bbl@ams@lap}%
      \AddToHook{env/eqnalign/begin}{\bbl@ams@preset\hbox}%
      % Hackish, for proper alignment. Don't ask me why it works!:
      \bbl@exp{% Avoid a 'visible' conditional
        \\\AddToHook{env/align*/end}{\<iftag@>\<else>\\\tag*{}\<fi>}%
        \\\AddToHook{env/alignat*/end}{\<iftag@>\<else>\\\tag*{}\<fi>}}%
      \AddToHook{env/flalign/begin}{\bbl@ams@preset\hbox}%
      \AddToHook{env/split/before}{%
        \ifnum\bbl@thetextdir>\z@
          \bbl@ifsamestring\@currenvir{equation}%
            {\ifx\bbl@ams@lap\hbox % leqno
               \def\bbl@ams@flip#1{%
                 \hbox to 0.01pt{\hbox to\displaywidth{{#1}\hss}\hss}}%
             \else
               \def\bbl@ams@flip#1{%
                 \hbox to 0.01pt{\hss\hbox to\displaywidth{\hss{#1}}}}%
             \fi}%
            {}%
        \fi}%
    \fi\fi}
\fi
```

Declarations specific to lua, called by `\babelprovide`.

```
\def\bbl@provide@extra#1{%
  % == onchar ==
  \ifx\bbl@KVP@onchar\@nnil\else
    \bbl@luahyphenate
    \bbl@exp{%
      \\\AddToHook{env/document/before}{%
```

```
      {\let\\\bbl@ifrestoring\\\@firstoftwo
       \\\select@language{#1}{}}}}%
  \directlua{
    if Babel.locale_mapped == nil then
      Babel.locale_mapped = true
      Babel.linebreaking.add_before(Babel.locale_map, 1)
      Babel.loc_to_scr = {}
      Babel.chr_to_loc = Babel.chr_to_loc or {}
    end
    Babel.locale_props[\the\localeid].letters = false
  }%
  \bbl@xin@{ letters }{ \bbl@KVP@onchar\space}%
  \ifin@
    \directlua{
      Babel.locale_props[\the\localeid].letters = true
    }%
  \fi
  \bbl@xin@{ ids }{ \bbl@KVP@onchar\space}%
  \ifin@
    \ifx\bbl@starthyphens\@undefined % Needed if no explicit selection
      \AddBabelHook{babel-onchar}{beforestart}{{\bbl@starthyphens}}%
    \fi
    \bbl@exp{\\\bbl@add\\\bbl@starthyphens
      {\\\bbl@patterns@lua{\languagename}}}%
    \directlua{
      if Babel.script_blocks['\bbl@cl{sbcp}'] then
        Babel.loc_to_scr[\the\localeid] = Babel.script_blocks['\bbl@cl{sbcp}']
        Babel.locale_props[\the\localeid].lg = \the\@nameuse{l@\languagename}\space
      end
    }%
  \fi
  \bbl@xin@{ fonts }{ \bbl@KVP@onchar\space}%
  \ifin@
    \bbl@ifunset{bbl@lsys@\languagename}{\bbl@provide@lsys{\languagename}}{}%
    \bbl@ifunset{bbl@wdir@\languagename}{\bbl@provide@dirs{\languagename}}{}%
    \directlua{
      if Babel.script_blocks['\bbl@cl{sbcp}'] then
        Babel.loc_to_scr[\the\localeid] =
          Babel.script_blocks['\bbl@cl{sbcp}']
      end}%
    \ifx\bbl@mapselect\@undefined
      \AtBeginDocument{%
        \bbl@patchfont{{\bbl@mapselect}}%
        {\selectfont}}%
      \def\bbl@mapselect{%
        \let\bbl@mapselect\relax
        \edef\bbl@prefontid{\fontid\font}}%
      \def\bbl@mapdir##1{%
        \begingroup
          \setbox\z@\hbox{% Force text mode
            \def\languagename{##1}%
            \let\bbl@ifrestoring\@firstoftwo % To avoid font warning
            \bbl@switchfont
            \ifnum\fontid\font>\z@ % A hack, for the pgf nullfont hack
              \directlua{
                Babel.locale_props[\the\csname bbl@id@@##1\endcsname]%
                        ['/\bbl@prefontid'] = \fontid\font\space}%
            \fi}%
        \endgroup}%
    \fi
    \bbl@exp{\\\bbl@add\\\bbl@mapselect{\\\bbl@mapdir{\languagename}}}%
  \fi
\fi
```

```
% == mapfont ==
% For bidi texts, to switch the font based on direction. Deprecated
\ifx\bbl@KVP@mapfont\@nnil\else
  \bbl@ifsamestring{\bbl@KVP@mapfont}{direction}{}%
    {\bbl@error{unknown-mapfont}{}{}{}}%
  \bbl@ifunset{bbl@lsys@\languagename}{\bbl@provide@lsys{\languagename}}{}%
  \bbl@ifunset{bbl@wdir@\languagename}{\bbl@provide@dirs{\languagename}}{}%
  \ifx\bbl@mapselect\@undefined
    \AtBeginDocument{%
      \bbl@patchfont{{\bbl@mapselect}}%
      {\selectfont}}%
    \def\bbl@mapselect{%
      \let\bbl@mapselect\relax
      \edef\bbl@prefontid{\fontid\font}}%
    \def\bbl@mapdir##1{%
      {\def\languagename{##1}%
       \let\bbl@ifrestoring\@firstoftwo % avoid font warning
       \bbl@switchfont
       \directlua{Babel.fontmap
         [\the\csname bbl@wdir@##1\endcsname]%
         [\bbl@prefontid]=\fontid\font}}}%
  \fi
  \bbl@exp{\\\bbl@add\\\bbl@mapselect{\\\bbl@mapdir{\languagename}}}%
\fi
% == Line breaking: CJK quotes ==
\ifcase\bbl@engine\or
  \bbl@xin@{/c}{/\bbl@cl{lnbrk}}%
  \ifin@
    \bbl@ifunset{bbl@quote@\languagename}{}%
      {\directlua{
         Babel.locale_props[\the\localeid].cjk_quotes = {}
         local cs = 'op'
         for c in string.utfvalues(%
             [[\csname bbl@quote@\languagename\endcsname]]) do
           if Babel.cjk_characters[c].c == 'qu' then
             Babel.locale_props[\the\localeid].cjk_quotes[c] = cs
           end
           cs = ( cs == 'op') and 'cl' or 'op'
         end
      }}%
  \fi
\fi
% == Counters: mapdigits ==
% Native digits
\ifx\bbl@KVP@mapdigits\@nnil\else
  \bbl@ifunset{bbl@dgnat@\languagename}{}%
    {\bbl@activate@preotf
     \directlua{
       Babel.digits_mapped = true
       Babel.digits = Babel.digits or {}
       Babel.digits[\the\localeid] =
         table.pack(string.utfvalue('\bbl@cl{dgnat}'))
       if not Babel.numbers then
         function Babel.numbers(head)
           local LOCALE = Babel.attr_locale
           local GLYPH = node.id'glyph'
           local inmath = false
           for item in node.traverse(head) do
             if not inmath and item.id == GLYPH then
               local temp = node.get_attribute(item, LOCALE)
               if Babel.digits[temp] then
                 local chr = item.char
                 if chr > 47 and chr < 58 then
```

```
                    item.char = Babel.digits[temp][chr-47]
                  end
                end
              elseif item.id == node.id'math' then
                inmath = (item.subtype == 0)
              end
            end
            return head
          end
        end
    }}%
\fi
% == transforms ==
\ifx\bbl@KVP@transforms\@nnil\else
  \def\bbl@elt##1##2##3{%
    \in@{$transforms.}{$##1}%
    \ifin@
      \def\bbl@tempa{##1}%
      \bbl@replace\bbl@tempa{transforms.}{}%
      \bbl@carg\bbl@transforms{babel\bbl@tempa}{##2}{##3}%
    \fi}%
  \bbl@exp{%
    \\\bbl@ifblank{\bbl@cl{dgnat}}%
     {\let\\\bbl@tempa\relax}%
     {\def\\\bbl@tempa{%
       \\\bbl@elt{transforms.prehyphenation}%
        {digits.native.1.0}{([0-9])}%
       \\\bbl@elt{transforms.prehyphenation}%
        {digits.native.1.1}{string={1\string|0123456789\string|\bbl@cl{dgnat}}}}}}%
  \ifx\bbl@tempa\relax\else
    \toks@\expandafter\expandafter\expandafter{%
      \csname bbl@inidata@\languagename\endcsname}%
    \bbl@csarg\edef{inidata@\languagename}{%
      \unexpanded\expandafter{\bbl@tempa}%
      \the\toks@}%
  \fi
  \csname bbl@inidata@\languagename\endcsname
  \bbl@release@transforms\relax % \relax closes the last item.
\fi}
```

Start tabular here:

```
\def\localerestoredirs{%
  \ifcase\bbl@thetextdir
    \ifnum\textdirection=\z@\else\textdirection=\z@\fi
  \else
    \ifnum\textdirection=\@ne\else\textdirection=\@ne\fi
  \fi
  \ifcase\bbl@thepardir
    \ifnum\pardirection=\z@\else\pardirection=\z@\bodydirection=\z@\fi
  \else
    \ifnum\pardirection=\@ne\else\pardirection=\@ne\bodydirection=\@ne\fi
  \fi}
%
\IfBabelLayout{tabular}%
  {\chardef\bbl@tabular@mode\z@}% All RTL
  {\IfBabelLayout{lrtabular}%
    {\chardef\bbl@tabular@mode\@ne}%
    {\chardef\bbl@tabular@mode\z@}}% Mixed, with LTR cols
%
\ifnum\bbl@bidimode>\@ne % Any lua bidi= except default=1
  % Redefine: vrules mess up dirs (why?).
  \AtBeginDocument{\def\@arstrut{\relax\copy\@arstrutbox}}%
  \ifcase\bbl@tabular@mode\else % 1 = Mixed
```

```
    \let\bbl@parabefore\relax
    \AddToHook{para/before}{\bbl@parabefore}
    \AtBeginDocument{%
      \bbl@replace\@tabular{\hbox\bgroup}{\hbox bdir\z@\bgroup}%
      \ifnum\bbl@tabular@mode=\@ne
        \bbl@ifunset{@tabclassz}{}{%
          \bbl@exp{% Hide conditionals
            \\\bbl@sreplace\\\@tabclassz
              {\<ifcase>\\\@chnum}%
              {\\\localerestoredirs\<ifcase>\\\@chnum}}}%
        \@ifpackageloaded{colortbl}%
          {\bbl@sreplace\@classz
            {\hbox\bgroup\bgroup}{\hbox\bgroup\bgroup\localerestoredirs}}%
          {\@ifpackageloaded{array}%
             {\bbl@exp{% Hide conditionals
                \\\bbl@sreplace\\\@classz
                  {\<ifcase>\\\@chnum}%
                  {\bgroup\\\localerestoredirs\<ifcase>\\\@chnum}%
                \\\bbl@sreplace\\\@classz
                  {\\\do@row@strut\<fi>}{\\\do@row@strut\<fi>\egroup}}}%
             {}}%
    \fi}%
  \fi
```

Very likely the `\output` routine must be patched in a quite general way to make sure the `\bodydir` is set to `\pagedir`. Note outside `\output` they can be different (and often are). For the moment, two *ad hoc* changes.

```
  \AtBeginDocument{%
    \@ifpackageloaded{multicol}%
      {\toks@\expandafter{\multi@column@out}%
       \edef\multi@column@out{\bodydir\pagedir\the\toks@}}%
      {}%
    \@ifpackageloaded{paracol}%
      {\edef\pcol@output{%
        \bodydir\pagedir\unexpanded\expandafter{\pcol@output}}}%
      {}}%
\fi
```

Finish here if there in no `layout`.

```
\ifx\bbl@opt@layout\@nnil\endinput\fi
```

`\hangindent` does not honour direction changes by default, so we need to redefine `\@hangfrom`.

```
\chardef\bbl@trace@vboxdir\z@
\ifnum\bbl@bidimode>\z@ % Any bidi=
  \IfBabelLayout{nopars}{}
    {\edef\bbl@opt@layout{\bbl@opt@layout.pars.}}%
  \IfBabelLayout{pars}
    {\chardef\bbl@trace@vboxdir\@ne
     \def\@hangfrom#1{%
      \setbox\@tempboxa\hbox{{#1}}%
      \hangindent\wd\@tempboxa
      \ifnum\bbl@vbox@bodydir=\pardirection\else
        \shapemode\@ne
      \fi
      \noindent\box\@tempboxa}}
    {}
\fi
```

We need to patch lists in documents with both LTR and RTL paragraphs. See issue #395 in GitHub. There was a partial solution, but a better one has been devised by Udi Fogiel (in 26.4).

```
\IfBabelLayout{lists}
  {\chardef\bbl@trace@vboxdir\@ne
   \let\bbl@OL@list\list
   \bbl@sreplace\list{\parshape}{\bbl@listparshape}%
```

```
  \let\bbl@NL@list\list
  \def\bbl@listparshape#1#2#3{%
    \parshape #1 #2 #3 %
    \ifnum\bbl@vbox@bodydir=\pardirection\else
      \shapemode\tw@
    \fi}}
 {}
%
\ifcase\bbl@trace@vboxdir\else
  \AtBeginDocument{\chardef\bbl@vbox@bodydir\pagedirection}%
  \def\bbl@vbox@lists{\chardef\bbl@vbox@bodydir\bodydirection}%
  \let\bbl@bidi@vbox\everyvbox
  \@nameuse{newtoks}\everyvbox   % \outer in Plain
  \everyvbox\expandafter{\the\bbl@bidi@vbox}%
  \bbl@bidi@vbox{\bbl@vbox@lists\the\everyvbox}%
\fi
%
\IfBabelLayout{graphics}
  {\let\bbl@pictresetdir\relax
   \def\bbl@pictsetdir#1{%
     \ifcase\bbl@thetextdir
       \let\bbl@pictresetdir\relax
     \else
       \ifcase#1\bodydir TLT  % Remember this sets the inner boxes
         \or\textdir TLT
         \else\bodydir TLT \textdir TLT
       \fi
       % \(text|par)dir required in pgf:
       \def\bbl@pictresetdir{\bodydir TRT\pardir TRT\textdir TRT\relax}%
     \fi}%
   \AddToHook{env/picture/begin}{\bbl@pictsetdir\tw@}%
   \directlua{
     Babel.get_picture_dir = true
     Babel.picture_has_bidi = 0
     %
     function Babel.picture_dir (head)
       if not Babel.get_picture_dir then return head end
       if Babel.hlist_has_bidi(head) then
         Babel.picture_has_bidi = 1
       end
       return head
     end
     luatexbase.add_to_callback("hpack_filter", Babel.picture_dir,
       "Babel.picture_dir")
   }%
   \AddToHook{package/graphics/after}{%
     \bbl@exp{%
       \\\bbl@sreplace\\\rotatebox{\hbox{{\string#2}}}
         {\hbox bdir\z@{\hbox bdir\<ifcase>\bbl@thetextdir\z@\<else>\@ne\<fi>{{\string#2}}}}}}
   \AddToHook{package/graphicx/after}{%
     \bbl@exp{%
       \\\bbl@sreplace\\\Grot@box@std{\hbox{{\string#2}}}
         {\hbox bdir\z@{\hbox bdir\<ifcase>\bbl@thetextdir\z@\<else>\@ne\<fi>{{\string#2}}}}%
       \\\bbl@sreplace\\\Grot@box@kv{\hbox{\string#3}}
         {{\hbox bdir\z@}{\hbox bdir\<ifcase>\bbl@thetextdir\z@\<else>\@ne\<fi>{{\string#3}}}}%
       \\\bbl@sreplace\\\Grot@box{\hbox}{\hbox bdir\z@}}}
   \AtBeginDocument{%
     \long\def\put(#1,#2)#3{%
       \@killglue
       % Try:
       \ifx\bbl@pictresetdir\relax
         \def\bbl@tempc{0}%
       \else
```

```
        \directlua{
          Babel.get_picture_dir = true
          Babel.picture_has_bidi = 0
        }%
        \setbox\z@\hb@xt@\z@{%
          \@defaultunitsset\@tempdimc{#1}\unitlength
          \kern\@tempdimc
          #3\hss}%
        \edef\bbl@tempc{\directlua{tex.print(Babel.picture_has_bidi)}}%
      \fi
      % Do:
      \@defaultunitsset\@tempdimc{#2}\unitlength
      \raise\@tempdimc\hb@xt@\z@{%
        \@defaultunitsset\@tempdimc{#1}\unitlength
        \kern\@tempdimc
        {\ifnum\bbl@tempc>\z@\bbl@pictresetdir\fi#3}\hss}%
      \ignorespaces}%
    \MakeRobust\put}%
  \AtBeginDocument
    {\AddToHook{cmd/diagbox@pict/before}{\let\bbl@pictsetdir\@gobble}%
     \ifx\pgfpicture\@undefined\else
       \AddToHook{env/pgfpicture/begin}{\bbl@pictsetdir\@ne}%
       \bbl@add\pgfinterruptpicture{\bbl@pictresetdir}%
       \bbl@add\pgfsys@beginpicture{\bbl@pictsetdir\z@}%
     \fi
     \ifx\tikzpicture\@undefined\else
       \AddToHook{env/tikzpicture/begin}{\bbl@pictsetdir\tw@}%
       \bbl@add\tikz@atbegin@node{\bbl@pictresetdir}%
       \bbl@sreplace\tikz{\begingroup}{\begingroup\bbl@pictsetdir\tw@}%
       \bbl@sreplace\tikzpicture{\begingroup}{\begingroup\bbl@pictsetdir\tw@}%
     \fi
    }}
  {}
```

Implicitly reverses sectioning labels in bidi=basic-r, because the full stop is not in contact with L numbers any more. I think there must be a better way. Assumes `bidi=basic`, but there are some additional readjustments for `bidi=default`.

```
\IfBabelLayout{counters*}%
  {\bbl@add\bbl@opt@layout{.counters.}%
   \directlua{
     luatexbase.add_to_callback("process_output_buffer",
       Babel.discard_sublr , "Babel.discard_sublr") }%
  }{}
\IfBabelLayout{counters}%
  {\let\bbl@latinarabic=\@arabic
   \let\bbl@OL@@arabic\@arabic
   \def\@arabic#1{\babelsublr{\bbl@latinarabic#1}}%
   \@ifpackagewith{babel}{bidi=default}%
     {\let\bbl@asciiroman=\@roman
      \let\bbl@OL@@roman\@roman
      \def\@roman#1{\babelsublr{\ensureascii{\bbl@asciiroman#1}}}%
      \let\bbl@asciiRoman=\@Roman
      \let\bbl@OL@@roman\@Roman
      \def\@Roman#1{\babelsublr{\ensureascii{\bbl@asciiRoman#1}}}%
      \let\bbl@OL@labelenumii\labelenumii
      \def\labelenumii{)\theenumii(}%
      \let\bbl@OL@p@enumiii\p@enumiii
      \def\p@enumiii{\p@enumii)\theenumii(}}{}}{}
```

Some LaTeX macros use internally the math mode for text formatting. They have very little in common and are grouped here, as a single option.

```
\IfBabelLayout{extras}%
  {\bbl@ncarg\let\bbl@OL@underline{underline }%
   \bbl@carg\bbl@sreplace{underline }{\hbox}%
```

```
    {\def\bbl@insidemath{0}\hbox bdir\ifcase\bbl@thetextdir\z@\else\@ne\fi}%
  \let\bbl@OL@LaTeXe\LaTeXe
  \DeclareRobustCommand{\LaTeXe}{\mbox{\m@th
    \if b\expandafter\@car\f@series\@nil\boldmath\fi
    \babelsublr{\LaTeX\kern.15em2$_{\textstyle\varepsilon}$}}}}
 {}
⟨/luatex⟩
```

9.13. Lua: transforms

After declaring the table containing the patterns with their replacements, we define some auxiliary functions: `str_to_nodes` converts the string returned by a function to a node list, taking the node at `base` as a model (font, language, etc.); `fetch_word` fetches a series of glyphs and discretionaries, which `pattern` is matched against (if there is a match, it is called again before trying other patterns, and this is very likely the main bottleneck).

`post_hyphenate_replace` is the callback applied after `lang.hyphenate`. This means the automatic hyphenation points are known. As empty captures return a byte position (as explained in the luatex manual), we must convert it to a utf8 position. With `first`, the last byte can be the leading byte in a utf8 sequence, so we just remove it and add 1 to the resulting length. With `last` we must take into account the capture position points to the next character. Here `word_head` points to the starting node of the text to be matched.

```
⟨*transforms⟩
Babel.linebreaking.replacements = {}
Babel.linebreaking.replacements[0] = {}  -- pre
Babel.linebreaking.replacements[1] = {}  -- post

function Babel.tovalue(v)
  if type(v) == 'table' then
    return Babel.locale_props[v[1]].vars[v[2]] or v[3]
  else
    return v
  end
end

Babel.attr_hboxed = luatexbase.registernumber'bbl@attr@hboxed'

function Babel.set_hboxed(head, gc)
  for item in node.traverse(head) do
    node.set_attribute(item, Babel.attr_hboxed, 1)
  end
  return head
end

Babel.fetch_subtext = {}

Babel.ignore_pre_char = function(node)
  return (node.lang == Babel.nohyphenation)
end

Babel.show_transforms = false

-- Merging both functions doesn't seen feasible, because there are too
-- many differences.
Babel.fetch_subtext[0] = function(head)
  local word_string = ''
  local word_nodes = {}
  local lang
  local item = head
  local inmath = false

  while item do

    if item.id == 11 then
```

```
      inmath = (item.subtype == 0)
    end

    if inmath then
      -- pass

    elseif item.id == 29 then
      local locale = node.get_attribute(item, Babel.attr_locale)

      if lang == locale or lang == nil then
        lang = lang or locale
        if Babel.ignore_pre_char(item) then
          word_string = word_string .. Babel.us_char
        else
          if node.has_attribute(item, Babel.attr_hboxed) then
            word_string = word_string .. Babel.us_char
          else
            word_string = word_string .. unicode.utf8.char(item.char)
          end
        end
        word_nodes[#word_nodes+1] = item
      else
        break
      end

    elseif item.id == 12 and item.subtype == 13 then
      if node.has_attribute(item, Babel.attr_hboxed) then
        word_string = word_string .. Babel.us_char
      else
        word_string = word_string .. ' '
      end
      word_nodes[#word_nodes+1] = item

    -- Ignore leading unrecognized nodes, too.
    elseif word_string ~= '' then
      word_string = word_string .. Babel.us_char
      word_nodes[#word_nodes+1] = item  -- Will be ignored
    end

    item = item.next
  end

  -- Here and above we remove some trailing chars but not the
  -- corresponding nodes. But they aren't accessed.
  if word_string:sub(-1) == ' ' then
    word_string = word_string:sub(1,-2)
  end
  if Babel.show_transforms then texio.write_nl(word_string) end
  word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
  return word_string, word_nodes, item, lang
end

Babel.fetch_subtext[1] = function(head)
  local word_string = ''
  local word_nodes = {}
  local lang
  local item = head
  local inmath = false

  while item do

    if item.id == 11 then
      inmath = (item.subtype == 0)
```

```
    end

    if inmath then
      -- pass

    elseif item.id == 29 then
      if item.lang == lang or lang == nil then
        lang = lang or item.lang
        if node.has_attribute(item, Babel.attr_hboxed) then
          word_string = word_string .. Babel.us_char
        elseif (item.char == 124) or (item.char == 61) then -- not =, not |
          word_string = word_string .. Babel.us_char
        else
          word_string = word_string .. unicode.utf8.char(item.char)
        end
        word_nodes[#word_nodes+1] = item
      else
        break
      end

    elseif item.id == 7 and item.subtype == 2 then
      if node.has_attribute(item, Babel.attr_hboxed) then
        word_string = word_string .. Babel.us_char
      else
        word_string = word_string .. '='
      end
      word_nodes[#word_nodes+1] = item

    elseif item.id == 7 and item.subtype == 3 then
      if node.has_attribute(item, Babel.attr_hboxed) then
        word_string = word_string .. Babel.us_char
      else
        word_string = word_string .. '|'
      end
      word_nodes[#word_nodes+1] = item

    -- (1) Go to next word if nothing was found, and (2) implicitly
    -- remove leading USs.
    elseif word_string == '' then
      -- pass

    -- This is the responsible for splitting by words.
    elseif (item.id == 12 and item.subtype == 13) then
      break

    else
      word_string = word_string .. Babel.us_char
      word_nodes[#word_nodes+1] = item  -- Will be ignored
    end

    item = item.next
  end
  if Babel.show_transforms then texio.write_nl(word_string) end
  word_string = unicode.utf8.gsub(word_string, Babel.us_char .. '+$', '')
  return word_string, word_nodes, item, lang
end

-- LuaTeX keeps its own pointer to the last node of the list passed to
-- the hyphenate callback and uses it afterwards (line_break and
-- filtered_hpack), so a transform freeing that node makes TeX use
-- freed memory. Before transforming, the last node is replaced with a
-- copy, and the original is kept out of the list, alive and with no
-- links, and freed at the next call (new_ligkern walks from such a
```

```
-- node to the actual end of the list).

do
  local stale_tail

  function Babel.protect_tail(head, tail)
    if stale_tail then
      node.free(stale_tail)
      stale_tail = nil
    end
    if not tail or tail == head then return end
    local prev = tail.prev
    if not prev or prev.next ~= tail then
      prev = head
      while prev.next ~= tail do prev = prev.next end
    end
    local copy = node.copy(tail)
    prev.next = copy
    copy.prev = prev
    copy.next = nil
    tail.prev = nil
    tail.next = nil
    stale_tail = tail
  end
end

function Babel.pre_hyphenate_replace(head)
  Babel.hyphenate_replace(head, 0)
end

function Babel.post_hyphenate_replace(head)
  Babel.hyphenate_replace(head, 1)
end

Babel.us_char = string.char(31)

function Babel.hyphenate_replace(head, mode)
  local u = unicode.utf8
  local lbkr = Babel.linebreaking.replacements[mode]
  local tovalue = Babel.tovalue

  local word_head = head

  -- Removed nodes are freed at the end of each match, because 'data'
  -- may still refer to them. Keyed by the direct node, so none is
  -- freed twice.
  local removed = {}
  local function remove_node(n)
    if n then
      node.remove(head, n)
      removed[node.direct.todirect(n)] = true
    end
  end

  if Babel.show_transforms then
    texio.write_nl('\n==== Showing ' .. (mode == 0 and 'pre' or 'post') .. 'hyphenation ====')
  end

  while true do  -- for each subtext block

    local w, w_nodes, nw, lang = Babel.fetch_subtext[mode](word_head)

    if Babel.debug then
```

```
      print()
      print((mode == 0) and '@@@@<' or '@@@@>', w)
    end

    if nw == nil and w == '' then break end

    if not lang then goto next end
    if not lbkr[lang] then goto next end

    -- For each saved (pre|post)hyphenation. TODO. Reconsider how
    -- loops are nested.
    for k=1, #lbkr[lang] do
      local p = lbkr[lang][k].pattern
      local r = lbkr[lang][k].replace
      local attr = lbkr[lang][k].attr or -1

      if Babel.debug then
        print('*****', p, mode)
      end

      -- This variable is set in some cases below to the first *byte*
      -- after the match, either as found by u.match (faster) or the
      -- computed position based on sc if w has changed.
      local last_match = 0
      local step = 0

      -- For every match.
      while true do
        if Babel.debug then
          print('=====')
        end
        local new  -- used when inserting and removing nodes
        local dummy_node -- used by after

        local matches = { u.match(w, p, last_match) }

        if #matches < 2 then break end

        -- Get and remove empty captures (with ()'s, which return a
        -- number with the position), and keep actual captures
        -- (from (...)), if any, in matches.
        local first = table.remove(matches, 1)
        local last  = table.remove(matches, #matches)
        -- Non re-fetched substrings may contain \31, which separates
        -- subsubstrings.
        if string.find(w:sub(first, last-1), Babel.us_char) then break end

        local save_last = last -- with A()BC()D, points to D

        -- Fix offsets, from bytes to unicode. Explained above.
        first = u.len(w:sub(1, first-1)) + 1
        last  = u.len(w:sub(1, last-1)) -- now last points to C

        -- This loop stores in a small table the nodes
        -- corresponding to the pattern. Used by 'data' to provide a
        -- predictable behavior with 'insert' (w_nodes is modified on
        -- the fly), and also access to 'remove'd nodes.
        local sc = first-1           -- Used below, too
        local data_nodes = {}

        local enabled = true
        for q = 1, last-first+1 do
          data_nodes[q] = w_nodes[sc+q]
```

```
          if enabled
              and attr > -1
              and not node.has_attribute(data_nodes[q], attr)
            then
            enabled = false
          end
        end

        -- This loop traverses the matched substring and takes the
        -- corresponding action stored in the replacement list.
        -- sc = the position in substr nodes / string
        -- rc = the replacement table index
        local rc = 0

------- TODO. dummy_node?
        while rc < last-first+1 or dummy_node do -- for each replacement
          if Babel.debug then
            print('.....', rc + 1)
          end
          sc = sc + 1
          rc = rc + 1

          if Babel.debug then
            Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
            local ss = ''
            for itt in node.traverse(head) do
             if itt.id == 29 then
               ss = ss .. unicode.utf8.char(itt.char)
             else
               ss = ss .. '{' .. itt.id .. '}'
             end
            end
            print('*****************', ss)

          end

          local crep = r[rc]
          local item = w_nodes[sc]
          local item_base = item
          local placeholder = Babel.us_char
          local d

          if crep and crep.data then
            item_base = data_nodes[crep.data]
          end

          if crep then
            step = crep.step or step
          end

          if crep and crep.after then
            crep.insert = true
            if dummy_node then
              item = dummy_node
            else -- TODO. if there is a node after?
              d = node.copy(item_base)
              head, item = node.insert_after(head, item, d)
              dummy_node = item
            end
          end

          if crep and not crep.after and dummy_node then
            remove_node(dummy_node)
```

```
7766            dummy_node = nil
7767          end
7768
7769          if not enabled then
7770            last_match = save_last
7771            goto next
7772
7773          elseif crep and next(crep) == nil then -- = {}
7774            if step == 0 then
7775              last_match = save_last    -- Optimization
7776            else
7777              last_match = utf8.offset(w, sc+step)
7778            end
7779            goto next
7780
7781          elseif crep == nil or crep.remove then
7782            remove_node(item)
7783            table.remove(w_nodes, sc)
7784            w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
7785            sc = sc - 1  -- Nothing has been inserted.
7786            last_match = utf8.offset(w, sc+1+step)
7787            goto next
7788
7789          elseif crep and crep.kashida then
7790            node.set_attribute(item,
7791               Babel.attr_kashida,
7792               crep.kashida)
7793            last_match = utf8.offset(w, sc+1+step)
7794            goto next
7795
7796          elseif crep and crep.string then
7797            local str = crep.string(matches)
7798            if str == '' then  -- Gather with nil
7799              remove_node(item)
7800              table.remove(w_nodes, sc)
7801              w = u.sub(w, 1, sc-1) .. u.sub(w, sc+1)
7802              sc = sc - 1  -- Nothing has been inserted.
7803            else
7804              local loop_first = true
7805              for s in string.utfvalues(str) do
7806                d = node.copy(item_base)
7807                d.char = s
7808                if loop_first then
7809                  loop_first = false
7810                  head, new = node.insert_before(head, item, d)
7811                  if sc == 1 then
7812                    word_head = head
7813                  end
7814                  w_nodes[sc] = d
7815                  w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc+1)
7816                else
7817                  sc = sc + 1
7818                  head, new = node.insert_before(head, item, d)
7819                  table.insert(w_nodes, sc, new)
7820                  w = u.sub(w, 1, sc-1) .. u.char(s) .. u.sub(w, sc)
7821                end
7822                if Babel.debug then
7823                  print('.....', 'str')
7824                  Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
7825                end
7826              end  -- for
7827              remove_node(item)
7828            end  -- if ''
```

```
7829            last_match = utf8.offset(w, sc+1+step)
7830            goto next
7831
7832          elseif mode == 1 and crep and (crep.pre or crep.no or crep.post) then
7833            d = node.new(7, 3)   -- (disc, regular)
7834            d.pre     = Babel.str_to_nodes(crep.pre, matches, item_base)
7835            d.post    = Babel.str_to_nodes(crep.post, matches, item_base)
7836            d.replace = Babel.str_to_nodes(crep.no, matches, item_base)
7837            d.attr = item_base.attr
7838            if crep.pre == nil then  -- TeXbook p96
7839              d.penalty = tovalue(crep.penalty) or tex.hyphenpenalty
7840            else
7841              d.penalty = tovalue(crep.penalty) or tex.exhyphenpenalty
7842            end
7843            placeholder = '|'
7844            head, new = node.insert_before(head, item, d)
7845
7846          elseif mode == 0 and crep and (crep.pre or crep.no or crep.post) then
7847            -- ERROR
7848
7849          elseif crep and crep.penalty then
7850            d = node.new(14, 0)   -- (penalty, userpenalty)
7851            d.attr = item_base.attr
7852            d.penalty = tovalue(crep.penalty)
7853            head, new = node.insert_before(head, item, d)
7854
7855          elseif crep and crep.space then
7856            -- 655360 = 10 pt = 10 * 65536 sp
7857            d = node.new(12, 13)      -- (glue, spaceskip)
7858            local quad = font.getfont(item_base.font).size or 655360
7859            node.setglue(d, tovalue(crep.space[1]) * quad,
7860                            tovalue(crep.space[2]) * quad,
7861                            tovalue(crep.space[3]) * quad)
7862            if mode == 0 then
7863              placeholder = ' '
7864            end
7865            head, new = node.insert_before(head, item, d)
7866
7867          elseif crep and crep.norule then
7868            -- 655360 = 10 pt = 10 * 65536 sp
7869            d = node.new(2, 3)      -- (rule, empty) = \no*rule
7870            local quad = font.getfont(item_base.font).size or 655360
7871            d.width   = tovalue(crep.norule[1]) * quad
7872            d.height  = tovalue(crep.norule[2]) * quad
7873            d.depth   = tovalue(crep.norule[3]) * quad
7874            head, new = node.insert_before(head, item, d)
7875
7876          elseif crep and crep.spacefactor then
7877            d = node.new(12, 13)      -- (glue, spaceskip)
7878            local base_font = font.getfont(item_base.font)
7879            node.setglue(d,
7880              tovalue(crep.spacefactor[1]) * base_font.parameters['space'],
7881              tovalue(crep.spacefactor[2]) * base_font.parameters['space_stretch'],
7882              tovalue(crep.spacefactor[3]) * base_font.parameters['space_shrink'])
7883            if mode == 0 then
7884              placeholder = ' '
7885            end
7886            head, new = node.insert_before(head, item, d)
7887
7888          elseif mode == 0 and crep and crep.space then
7889            -- ERROR
7890
7891          elseif crep and crep.kern then
```

```
            d = node.new(13, 1)      -- (kern, user)
            local quad = font.getfont(item_base.font).size or 655360
            d.attr = item_base.attr
            d.kern = tovalue(crep.kern) * quad
            head, new = node.insert_before(head, item, d)

          elseif crep and crep.node then
            d = node.new(crep.node[1], crep.node[2])
            d.attr = item_base.attr
            head, new = node.insert_before(head, item, d)

          end  -- i.e., replacement cases

          -- Shared by disc, space(factor), kern, node and penalty.
          if sc == 1 then
            word_head = head
          end
          if crep.insert then
            w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc)
            table.insert(w_nodes, sc, new)
            last = last + 1
          else
            w_nodes[sc] = d
            remove_node(item)
            w = u.sub(w, 1, sc-1) .. placeholder .. u.sub(w, sc+1)
          end

          last_match = utf8.offset(w, sc+1+step)

          ::next::

        end  -- for each replacement

        if Babel.show_transforms then texio.write_nl('>  ' .. w) end
        if Babel.debug then
            print('.....', '/')
            Babel.debug_hyph(w, w_nodes, sc, first, last, last_match)
        end

      if dummy_node then
        remove_node(dummy_node)
        dummy_node = nil
      end

      for n in pairs(removed) do
        node.direct.free(n)
      end
      removed = {}

      end  -- for match

    end  -- for patterns

    ::next::
    word_head = nw
  end  -- for substring

  if Babel.show_transforms then texio.write_nl(string.rep('-', 32) .. '\n') end
  return head
end

-- This table stores capture maps, numbered consecutively
Babel.capture_maps = {}
```

```
function Babel.esc_hex_to_char(h)
  if tex.getcatcode(tonumber(h, 16)) ~= 11 and
     tex.getcatcode(tonumber(h, 16)) ~= 12 then
    return string.format([[\Uchar"%X ]], tonumber(h,16))
  else
    return unicode.utf8.char(tonumber(h, 16))
  end
end

-- The following functions belong to the next macro
function Babel.capture_func(key, cap)
  local ret = "[[" .. cap:gsub('{([0-9])}', "]]..m[%1]..[[") .. "]]"
  local cnt
  local u = unicode.utf8
  ret = u.gsub(ret, '{(%x%x%x%x+)}', '\x01%1\x04')
  ret, cnt = ret:gsub('{([0-9])|([^|]+)|(.-)}', Babel.capture_func_map)
  ret = u.gsub(ret, '\x01(%x%x%x%x+)\x04', Babel.esc_hex_to_char)
  ret = ret:gsub("%[%[%]%]%.%.", '')
  ret = ret:gsub("%.%.%[%[%]%]", '')
  return key .. [[=function(m) return ]] .. ret .. [[ end]]
end

function Babel.capt_map(from, mapno)
  return Babel.capture_maps[mapno][from] or from
end

-- Handle the {n|abc|ABC} syntax in captures
function Babel.capture_func_map(capno, from, to)
  local u = unicode.utf8
  from = u.gsub(from, '\x01(%x%x%x%x+)\x04',
       function (n)
         return u.char(tonumber(n, 16))
       end)
  to = u.gsub(to, '\x01(%x%x%x%x+)\x04',
       function (n)
         return u.char(tonumber(n, 16))
       end)
  local froms = {}
  for s in string.utfcharacters(from) do
    table.insert(froms, s)
  end
  local cnt = 1
  table.insert(Babel.capture_maps, {})
  local mlen = table.getn(Babel.capture_maps)
  for s in string.utfcharacters(to) do
    Babel.capture_maps[mlen][froms[cnt]] = s
    cnt = cnt + 1
  end
  return "]]..Babel.capt_map(m[" .. capno .. "]," ..
         (mlen) .. ")..." .. "[["
end

-- Create/Extend reversed sorted list of kashida weights:
function Babel.capture_kashida(key, wt)
  wt = tonumber(wt)
  if Babel.kashida_wts then
    for p, q in ipairs(Babel.kashida_wts) do
      if wt  == q then
        break
      elseif wt > q then
        table.insert(Babel.kashida_wts, p, wt)
        break
```

```
      elseif table.getn(Babel.kashida_wts) == p then
        table.insert(Babel.kashida_wts, wt)
      end
    end
  else
    Babel.kashida_wts = { wt }
  end
  return 'kashida = ' .. wt
end

function Babel.capture_node(id, subtype)
  local sbt = 0
  for k, v in pairs(node.subtypes(id)) do
    if v == subtype then sbt = k end
  end
  return 'node = {' .. node.id(id) .. ', ' .. sbt .. '}'
end

-- Experimental: applies prehyphenation transforms to a string (letters
-- and spaces).
function Babel.string_prehyphenation(str, locale)
  local n, head, last, res
  head = node.new(8, 0) -- dummy (hack just to start)
  last = head
  for s in string.utfvalues(str) do
    if s == 20 then
      n = node.new(12, 0)
    else
      n = node.new(29, 0)
      n.char = s
    end
    node.set_attribute(n, Babel.attr_locale, locale)
    last.next = n
    last = n
  end
  head = Babel.hyphenate_replace(head, 0)
  res = ''
  for n in node.traverse(head) do
    if n.id == 12 then
      res = res .. ' '
    elseif n.id == 29 then
      res = res .. unicode.utf8.char(n.char)
    end
  end
  node.flush_list(head)
  tex.print(res)
end
⟨/transforms⟩
```

9.14. Lua: Auto bidi with `basic` and `basic-r`

The file babel-data-bidi.lua currently only contains data. It is a large and boring file and it is not shown here (see the generated file), but here is a sample:

```
% [0x25]={d='et'},
% [0x26]={d='on'},
% [0x27]={d='on'},
% [0x28]={d='on', m=0x29},
% [0x29]={d='on', m=0x28},
% [0x2A]={d='on'},
% [0x2B]={d='es'},
% [0x2C]={d='cs'},
```

```
%
```

For the meaning of these codes, see the Unicode standard.

Now the `basic-r` bidi mode. One of the aims is to implement a fast and simple bidi algorithm, with a single loop. I managed to do it for R texts, with a second smaller loop for a special case. The code is still somewhat chaotic, but its behavior is essentially correct. I cannot resist copying the following text from Emacs `bidi.c` (which also attempts to implement the bidi algorithm with a single loop):

> Arrrgh!! The UAX#9 algorithm is too deeply entrenched in the assumption of batch-style processing [...]. May the fleas of a thousand camels infest the armpits of those who design supposedly general-purpose algorithms by looking at their own implementations, and fail to consider other possible implementations!

Well, it took me some time to guess what the batch rules in UAX#9 actually mean (in other word, *what* they do and *why*, and not only *how*), but I think (or I hope) I've managed to understand them.

In some sense, there are two bidi modes, one for numbers, and the other for text. Furthermore, setting just the direction in R text is not enough, because there are actually *two* R modes (set explicitly in Unicode with RLM and ALM). In babel the dir is set by a higher protocol based on the language/script, which in turn sets the correct dir (<l>, <r> or <al>).

From UAX#9: "Where available, markup should be used instead of the explicit formatting characters". So, this simple version just ignores formatting characters. Actually, most of that annex is devoted to how to handle them.

BD14-BD16 are not implemented. Unicode (and the W3C) are making a great effort to deal with some special problematic cases in "streamed" plain text. I don't think this is the way to go – particular issues should be fixed by a high level interface taking into account the needs of the document. And here is where luatex excels, because everything related to bidi writing is under our control.

```
⟨*basic-r⟩
Babel.bidi_enabled = true

require('babel-data-bidi.lua')

local characters = Babel.characters
local ranges = Babel.ranges

local DIR = node.id("dir")

local function dir_mark(head, from, to, outer)
  dir = (outer == 'r') and 'TLT' or 'TRT' -- i.e., reverse
  local d = node.new(DIR)
  d.dir = '+' .. dir
  node.insert_before(head, from, d)
  d = node.new(DIR)
  d.dir = '-' .. dir
  node.insert_after(head, to, d)
end

function Babel.bidi(head, ispar)
  local first_n, last_n            -- first and last char with nums
  local last_es                    -- an auxiliary 'last' used with nums
  local first_d, last_d            -- first and last char in L/R block
  local dir, dir_real
```

Next also depends on script/lang (<al>/<r>). To be set by babel. `tex.pardir` is dangerous, could be (re)set but it should be changed only in vmode. There are two strong's – `strong` = l/al/r and `strong_lr` = l/r (there must be a better way):

```
  local strong = ('TRT' == tex.pardir) and 'r' or 'l'
  local strong_lr = (strong == 'l') and 'l' or 'r'
  local outer = strong

  local new_dir = false
  local first_dir = false
  local inmath = false

  local last_lr
```

```
8100
8101  local type_n = ''
8102
8103  for item in node.traverse(head) do
8104
8105    -- three cases: glyph, dir, otherwise
8106    if item.id == node.id'glyph'
8107      or (item.id == 7 and item.subtype == 2) then
8108
8109      local itemchar
8110      if item.id == 7 and item.subtype == 2 then
8111        itemchar = item.replace.char
8112      else
8113        itemchar = item.char
8114      end
8115      local chardata = characters[itemchar]
8116      dir = chardata and chardata.d or nil
8117      if not dir then
8118        for nn, et in ipairs(ranges) do
8119          if itemchar < et[1] then
8120            break
8121          elseif itemchar <= et[2] then
8122            dir = et[3]
8123            break
8124          end
8125        end
8126      end
8127      dir = dir or 'l'
8128      if inmath then dir = ('TRT' == tex.mathdir) and 'r' or 'l' end
```

Next is based on the assumption babel sets the language *and* switches the script with its dir. We treat a language block as a separate Unicode sequence. The following piece of code is executed at the first glyph after a 'dir' node. We don't know the current language until then. This is not exactly true, as the math mode may insert explicit dirs in the node list, so, for the moment there is a hack by brute force (just above).

```
8129      if new_dir then
8130        attr_dir = 0
8131        for at in node.traverse(item.attr) do
8132          if at.number == Babel.attr_dir then
8133            attr_dir = at.value & 0x3
8134          end
8135        end
8136        if attr_dir == 1 then
8137          strong = 'r'
8138        elseif attr_dir == 2 then
8139          strong = 'al'
8140        else
8141          strong = 'l'
8142        end
8143        strong_lr = (strong == 'l') and 'l' or 'r'
8144        outer = strong_lr
8145        new_dir = false
8146      end
8147
8148      if dir == 'nsm' then dir = strong end             -- W1
```

Numbers. The dual <al>/<r> system for R is somewhat cumbersome.

```
8149      dir_real = dir               -- We need dir_real to set strong below
8150      if dir == 'al' then dir = 'r' end -- W3
```

By W2, there are no <en> <et> <es> if `strong` == ⟨*al*⟩, only <an>. Therefore, there are not <et en> nor <en et>, W5 can be ignored, and W6 applied:

```
8151      if strong == 'al' then
8152        if dir == 'en' then dir = 'an' end               -- W2
```

```
        if dir == 'et' or dir == 'es' then dir = 'on' end -- W6
        strong_lr = 'r'                                   -- W3
      end
```

Once finished the basic setup for glyphs, consider the two other cases: dir node and the rest.

```
    elseif item.id == node.id'dir' and not inmath then
      new_dir = true
      dir = nil
    elseif item.id == node.id'math' then
      inmath = (item.subtype == 0)
    else
      dir = nil          -- Not a char
    end
```

Numbers in R mode. A sequence of <en>, <et>, <an>, <es> and <cs> is typeset (with some rules) in L mode. We store the starting and ending points, and only when anything different is found (including nil, i.e., a non-char), the textdir is set. This means you cannot insert, say, a whatsit, but this is what I would expect (with luacolor you may colorize some digits). Anyway, this behavior could be changed with a switch in the future. Note in the first branch only <an> is relevant if <al>.

```
    if dir == 'en' or dir == 'an' or dir == 'et' then
      if dir ~= 'et' then
        type_n = dir
      end
      first_n = first_n or item
      last_n = last_es or item
      last_es = nil
    elseif dir == 'es' and last_n then -- W3+W6
      last_es = item
    elseif dir == 'cs' then            -- it's right - do nothing
    elseif first_n then -- & if dir = any but en, et, an, es, cs, inc nil
      if strong_lr == 'r' and type_n ~= '' then
        dir_mark(head, first_n, last_n, 'r')
      elseif strong_lr == 'l' and first_d and type_n == 'an' then
        dir_mark(head, first_n, last_n, 'r')
        dir_mark(head, first_d, last_d, outer)
        first_d, last_d = nil, nil
      elseif strong_lr == 'l' and type_n ~= '' then
        last_d = last_n
      end
      type_n = ''
      first_n, last_n = nil, nil
    end
```

R text in L, or L text in R. Order of `dir_ mark`'s are relevant: d goes outside n, and therefore it's emitted after. See `dir_mark` to understand why (but is the nesting actually necessary or is a flat dir structure enough?). Only L, R (and AL) chars are taken into account – everything else, including spaces, whatsits, etc., are ignored:

```
    if dir == 'l' or dir == 'r' then
      if dir ~= outer then
        first_d = first_d or item
        last_d = item
      elseif first_d and dir ~= strong_lr then
        dir_mark(head, first_d, last_d, outer)
        first_d, last_d = nil, nil
      end
    end
```

Mirroring. Each chunk of text in a certain language is considered a "closed" sequence. If <r on r> and <l on l>, it's clearly <r> and <l>, resptly, but with other combinations depends on outer. From all these, we select only those resolving <on> $\rightarrow$ <r>. At the beginning (when `last_lr` is nil) of an R text, they are mirrored directly. Numbers in R mode are processed. It should not be done, but it doesn't hurt.

```
    if dir and not last_lr and dir ~= 'l' and outer == 'r' then
      item.char = characters[item.char] and
```

```
                  characters[item.char].m or item.char
    elseif (dir or new_dir) and last_lr ~= item then
      local mir = outer .. strong_lr .. (dir or outer)
      if mir == 'rrr' or mir == 'lrr' or mir == 'rrl' or mir == 'rlr' then
        for ch in node.traverse(node.next(last_lr)) do
          if ch == item then break end
          if ch.id == node.id'glyph' and characters[ch.char] then
            ch.char = characters[ch.char].m or ch.char
          end
        end
      end
    end
```

Save some values for the next iteration. If the current node is 'dir', open a new sequence. Since dir could be changed, strong is set with its real value (`dir_real`).

```
    if dir == 'l' or dir == 'r' then
      last_lr = item
      strong = dir_real            -- Don't search back - best save now
      strong_lr = (strong == 'l') and 'l' or 'r'
    elseif new_dir then
      last_lr = nil
    end
  end
```

Mirror the last chars if they are no directed. And make sure any open block is closed, too.

```
  if last_lr and outer == 'r' then
    for ch in node.traverse_id(node.id'glyph', node.next(last_lr)) do
      if characters[ch.char] then
        ch.char = characters[ch.char].m or ch.char
      end
    end
  end
  if first_n then
    dir_mark(head, first_n, last_n, outer)
  end
  if first_d then
    dir_mark(head, first_d, last_d, outer)
  end
```

In boxes, the dir node could be added before the original head, so the actual head is the previous node.

```
  return node.prev(head) or head
end
```
⟨/basic-r⟩

And here the Lua code for `bidi=basic`:

```
⟨*basic⟩
-- e.g., Babel.fontmap[1][<prefontid>]=<dirfontid>

Babel.fontmap = Babel.fontmap or {}
Babel.fontmap[0] = {}      -- l
Babel.fontmap[1] = {}      -- r
Babel.fontmap[2] = {}      -- al/an

-- To cancel mirroring. Also OML, OMS, U?
Babel.symbol_fonts = Babel.symbol_fonts or {}
Babel.symbol_fonts[font.id('tenln')] = true
Babel.symbol_fonts[font.id('tenlnw')] = true
Babel.symbol_fonts[font.id('tencirc')] = true
Babel.symbol_fonts[font.id('tencircw')] = true

Babel.bidi_enabled = true
Babel.mirroring_enabled = true

```

```
require('babel-data-bidi.lua')

local characters = Babel.characters
local ranges = Babel.ranges

local DIR = node.id('dir')
local GLYPH = node.id('glyph')

local function insert_implicit(head, state, outer)
  local new_state = state
  if state.sim and state.eim and state.sim ~= state.eim then
    dir = ((outer == 'r') and 'TLT' or 'TRT') -- i.e., reverse
    local d = node.new(DIR)
    d.dir = '+' .. dir
    node.insert_before(head, state.sim, d)
    local d = node.new(DIR)
    d.dir = '-' .. dir
    node.insert_after(head, state.eim, d)
  end
  new_state.sim, new_state.eim = nil, nil
  return head, new_state
end

local function insert_numeric(head, state)
  local new
  local new_state = state
  if state.san and state.ean and state.san ~= state.ean then
    local d = node.new(DIR)
    d.dir = '+TLT'
    _, new = node.insert_before(head, state.san, d)
    if state.san == state.sim then state.sim = new end
    local d = node.new(DIR)
    d.dir = '-TLT'
    _, new = node.insert_after(head, state.ean, d)
    if state.ean == state.eim then state.eim = new end
  end
  new_state.san, new_state.ean = nil, nil
  return head, new_state
end

local function glyph_not_symbol_font(node)
  if node.id == GLYPH then
    return not Babel.symbol_fonts[node.font]
  else
    return false
  end
end

-- TODO - \hbox with an explicit dir can lead to wrong results
-- <R \hbox dir TLT{<R>}> and <L \hbox dir TRT{<L>}>. A small attempt
-- was made to improve the situation, but the problem is the 3-dir
-- model in babel/Unicode and the 2-dir model in LuaTeX don't fit
-- well.

function Babel.bidi(head, ispar, hdir)
  local d   -- d is used mainly for computations in a loop
  local prev_d = ''
  local new_d = false

  local nodes = {}
  local outer_first = nil
  local inmath = false

```

```
local glue_d = nil
local glue_i = nil

local has_en = false
local first_et = nil

local has_hyperlink = false

local ATDIR = Babel.attr_dir
local attr_d, temp
local locale_d

local save_outer
local locale_d = node.get_attribute(head, ATDIR)
if locale_d then
  locale_d = locale_d & 0x3
  save_outer = (locale_d == 0 and 'l') or
               (locale_d == 1 and 'r') or
               (locale_d == 2 and 'al')
elseif ispar then       -- Or error? Shouldn't happen
  -- when the callback is called, we are just _after_ the box,
  -- and the textdir is that of the surrounding text
  save_outer = ('TRT' == tex.pardir) and 'r' or 'l'
else                    -- Empty box
  save_outer = ('TRT' == hdir) and 'r' or 'l'
end
local outer = save_outer
local last = outer
-- 'al' is only taken into account in the first, current loop
if save_outer == 'al' then save_outer = 'r' end

local fontmap = Babel.fontmap

for item in node.traverse(head) do

  -- Mask: DxxxPPTT (Done, Pardir [0-2], Textdir [0-2])
  locale_d = node.get_attribute(item, ATDIR)
  node.set_attribute(item, ATDIR, 0x80)

  -- In what follows, #node is the last (previous) node, because the
  -- current one is not added until we start processing the neutrals.
  -- three cases: glyph, dir, otherwise
  if glyph_not_symbol_font(item)
     or (item.id == 7 and item.subtype == 2) then

    if inmath then goto nextnode end

     if locale_d == 0x80 then goto nextnode end
    locale_d = locale_d or ((save_outer=='l') and 0 or 1)

    local d_font = nil
    local item_r
    if item.id == 7 and item.subtype == 2 then
      item_r = item.replace    -- automatic discs have just 1 glyph
    else
      item_r = item
    end

    local chardata = characters[item_r.char]
    d = chardata and chardata.d or nil
    if not d or d == 'nsm' then
      for nn, et in ipairs(ranges) do
        if item_r.char < et[1] then
```

```
8378            break
8379          elseif item_r.char <= et[2] then
8380            if not d then d = et[3]
8381            elseif d == 'nsm' then d_font = et[3]
8382            end
8383            break
8384          end
8385        end
8386      end
8387      d = d or 'l'
8388
8389      -- A short 'pause' in bidi for mapfont
8390      -- %%%% TODO. move if fontmap here
8391      d_font = d_font or d
8392      d_font = (d_font == 'l' and 0) or
8393               (d_font == 'nsm' and 0) or
8394               (d_font == 'r' and 1) or
8395               (d_font == 'al' and 2) or
8396               (d_font == 'an' and 2) or nil
8397      if d_font and fontmap and fontmap[d_font][item_r.font] then
8398        item_r.font = fontmap[d_font][item_r.font]
8399      end
8400
8401      if new_d then
8402        table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})
8403        if inmath then
8404          attr_d = 0
8405        else
8406          attr_d = locale_d & 0x3
8407        end
8408        if attr_d == 1 then
8409          outer_first = 'r'
8410          last = 'r'
8411        elseif attr_d == 2 then
8412          outer_first = 'r'
8413          last = 'al'
8414        else
8415          outer_first = 'l'
8416          last = 'l'
8417        end
8418        outer = last
8419        has_en = false
8420        first_et = nil
8421        new_d = false
8422      end
8423
8424      if glue_d then
8425        if (d == 'l' and 'l' or 'r') ~= glue_d then
8426           table.insert(nodes, {glue_i, 'on', nil})
8427        end
8428        glue_d = nil
8429        glue_i = nil
8430      end
8431
8432     elseif item.id == DIR then
8433       if inmath then goto nextnode end
8434       d = nil
8435       new_d = true
8436
8437     elseif item.id == node.id'glue' and item.subtype == 13 then
8438       if inmath then goto nextnode end
8439       glue_d = d
8440       glue_i = item
```

```
      d = nil

    elseif item.id == node.id'math' then
      if item.subtype == 0 then  -- mathon
        inmath = true
        d = 'on'
        table.insert(nodes, {item, 'on', outer_first})
        outer_first = nil
        goto nextnode
      else  -- mathoff
        inmath = false
      end

    elseif item.id == 8 and item.subtype == 19 then
      has_hyperlink = true

    else
      d = nil
    end

    -- AL <= EN/ET/ES     -- W2 + W3 + W6
    if last == 'al' and d == 'en' then
      d = 'an'           -- W3
    elseif last == 'al' and (d == 'et' or d == 'es') then
      d = 'on'           -- W6
    end

    -- EN + CS/ES + EN     -- W4
    if d == 'en' and #nodes >= 2 then
      if (nodes[#nodes][2] == 'es' or nodes[#nodes][2] == 'cs')
          and nodes[#nodes-1][2] == 'en' then
        nodes[#nodes][2] = 'en'
      end
    end

    -- AN + CS + AN        -- W4 too, because uax9 mixes both cases
    if d == 'an' and #nodes >= 2 then
      if (nodes[#nodes][2] == 'cs')
          and nodes[#nodes-1][2] == 'an' then
        nodes[#nodes][2] = 'an'
      end
    end

    -- ET/EN               -- W5 + W7->l / W6->on
    if d == 'et' then
      first_et = first_et or (#nodes + 1)
    elseif d == 'en' then
      has_en = true
      first_et = first_et or (#nodes + 1)
    elseif first_et then       -- d may be nil here !
      if has_en then
        if last == 'l' then
          temp = 'l'    -- W7
        else
          temp = 'en'   -- W5
        end
      else
        temp = 'on'     -- W6
      end
      for e = first_et, #nodes do
        if glyph_not_symbol_font(nodes[e][1]) then nodes[e][2] = temp end
      end
      first_et = nil
```

```
      has_en = false
    end

    -- Force mathdir in math if ON (currently works as expected only
    -- with 'l')

    if inmath and d == 'on' then
      d = ('TRT' == tex.mathdir) and 'r' or 'l'
    end

    if d then
      if d == 'al' then
        d = 'r'
        last = 'al'
      elseif d == 'l' or d == 'r' then
        last = d
      end
      prev_d = d
      table.insert(nodes, {item, d, outer_first})
    end

    outer_first = nil

    ::nextnode::

  end -- for each node

  -- TODO -- repeated here in case EN/ET is the last node. Find a
  -- better way of doing things:
  if first_et then       -- dir may be nil here !
    if has_en then
      if last == 'l' then
        temp = 'l'    -- W7
      else
        temp = 'en'   -- W5
      end
    else
      temp = 'on'     -- W6
    end
    for e = first_et, #nodes do
      if glyph_not_symbol_font(nodes[e][1]) then nodes[e][2] = temp end
    end
  end

  -- dummy node, to close things
  table.insert(nodes, {nil, (outer == 'l') and 'l' or 'r', nil})

  ---------------  NEUTRAL -----------------

  outer = save_outer
  last = outer

  local first_on = nil

  for q = 1, #nodes do
    local item

    local outer_first = nodes[q][3]
    outer = outer_first or outer
    last = outer_first or last

    local d = nodes[q][2]
    if d == 'an' or d == 'en' then d = 'r' end
```

```
  if d == 'cs' or d == 'et' or d == 'es' then d = 'on' end --- W6

  if d == 'on' then
    first_on = first_on or q
  elseif first_on then
    if last == d then
      temp = d
    else
      temp = outer
    end
    for r = first_on, q - 1 do
      nodes[r][2] = temp
      item = nodes[r][1]    -- MIRRORING
      if Babel.mirroring_enabled and glyph_not_symbol_font(item)
           and temp == 'r' and characters[item.char] then
        local font_mode = ''
        if item.font > 0 and font.fonts[item.font].properties then
          font_mode = font.fonts[item.font].properties.mode
        end
        if font_mode ~= 'harf' and font_mode ~= 'plug' then
          item.char = characters[item.char].m or item.char
        end
      end
    end
    first_on = nil
  end

  if d == 'r' or d == 'l' then last = d end
end

--------------  IMPLICIT, REORDER ----------------

outer = save_outer
last = outer

local state = {}
state.has_r = false

for q = 1, #nodes do

  local item = nodes[q][1]

  outer = nodes[q][3] or outer

  local d = nodes[q][2]

  if d == 'nsm' then d = last end             -- W1
  if d == 'en' then d = 'an' end
  local isdir = (d == 'r' or d == 'l')

  if outer == 'l' and d == 'an' then
    state.san = state.san or item
    state.ean = item
  elseif state.san then
    head, state = insert_numeric(head, state)
  end

  if outer == 'l' then
    if d == 'an' or d == 'r' then     -- im -> implicit
      if d == 'r' then state.has_r = true end
      state.sim = state.sim or item
      state.eim = item
    elseif d == 'l' and state.sim and state.has_r then
```

```
        head, state = insert_implicit(head, state, outer)
      elseif d == 'l' then
        state.sim, state.eim, state.has_r = nil, nil, false
      end
    else
      if d == 'an' or d == 'l' then
        if nodes[q][3] then -- nil except after an explicit dir
          state.sim = item  -- so we move sim 'inside' the group
        else
          state.sim = state.sim or item
        end
        state.eim = item
      elseif d == 'r' and state.sim then
        head, state = insert_implicit(head, state, outer)
      elseif d == 'r' then
        state.sim, state.eim = nil, nil
      end
    end

    if isdir then
      last = d           -- Don't search back - best save now
    elseif d == 'on' and state.san  then
      state.san = state.san or item
      state.ean = item
    end

  end

  head = node.prev(head) or head
% \end{macrocode}
%
% Now direction nodes has been distributed with relation to characters
% and spaces, we need to take into account \TeX\-specific elements in
% the node list, to move them at an appropriate place. Firstly, with
% hyperlinks. Secondly, we avoid them between penalties and spaces, so
% that the latter are still discardable.
%
% \begin{macrocode}
  --- FIXES ---
  if has_hyperlink then
    local flag, linking = 0, 0
    for item in node.traverse(head) do
      if item.id == DIR then
        if item.dir == '+TRT' or item.dir == '+TLT' then
          flag = flag + 1
        elseif item.dir == '-TRT' or item.dir == '-TLT' then
          flag = flag - 1
        end
      elseif item.id == 8 and item.subtype == 19 then
        linking = flag
      elseif item.id == 8 and item.subtype == 20 then
        if linking > 0 then
          if item.prev.id == DIR and
              (item.prev.dir == '-TRT' or item.prev.dir == '-TLT') then
            local old = item.prev
            d = node.new(DIR)
            d.dir = old.dir
            head = node.remove(head, old)
            node.free(old)
            node.insert_after(head, item, d)
          end
        end
        linking = 0
```

```
      end
    end
  end

  local item, next_item = head
  while item do
    next_item = item.next
    if item.id == 10 then
      local p = item
      while p.prev and p.prev.id == 14 do
        p = p.prev
      end
      if p ~= item then
        head = node.remove(head, item)
        head = node.insert_before(head, p, item)
      end
    end
    item = next_item
  end

  return head
end
function Babel.unset_atdir(head)
  local ATDIR = Babel.attr_dir
  for item in node.traverse(head) do
    node.set_attribute(item, ATDIR, 0x80)
  end
  return head
end
```

The following code has been contributed by Udi Fogiel. It fixes misplaced glues when combined with penalties at line breaks.

```
local GLUE    = node.id'glue'
local PENALTY = node.id'penalty'
local HLIST   = node.id'hlist'
local LINE    = table.swapped(node.subtypes("hlist")).line

local characters = Babel.characters
local ranges     = Babel.ranges

-- L1's whitespace set: WS + isolate formats + (per the UBA reference) the
-- explicit embedding/override formats + BN.
-- Babel does not use embedding/override/isolates. In fact, their use
-- is discouraged by the UAX#9. To be removed.
local l1_whitespace = {
  ws  = true, bn  = true,
  lre = true, rle = true, lro = true, rlo = true, pdf = true,
  lri = true, rli = true, fsi = true, pdi = true,
}

local function bidi_class(c)
  local cd = characters[c]
  local d  = cd and cd.d
  if not d then
    for _, et in ipairs(ranges) do
      if c < et[1] then
        break
      elseif c <= et[2] then
        d = et[3]
        break
      end
    end
  end
```

```
  return d or 'l'
end

-- Nodes we step over as part of a trailing-whitespace run: glue,
-- penalties, and a whitespace glyph.
local function skippable(n)
  local id = n.id
  if id == GLUE or id == PENALTY then
    return true
  elseif id == GLYPH then
    return l1_whitespace[bidi_class(n.char)] == true
  end
  return false
end

local function is_enddir(n)
  return n.id == DIR and n.subtype == 1
end

-- Rule L1, clause 4, for one line: pull its trailing whitespace out past the
-- closing dir run so it renders in the box (base) direction.
local function reset_line(head)
  local last = node.slide(head)           -- tail, fixes prev links
  -- 1. skip the tail that follows the closing dir run (rightskip/parfillskip/...)
  local q = last
  while q and skippable(q) do q = q.prev end
  if not (q and is_enddir(q)) then return head end
  local d_last = q
  -- 2. step back over the whole closing dir run
  while q and q.id == DIR do q = q.prev end
  -- 3. what precedes the dirs must be the trailing whitespace run
  if not (q and skippable(q)) then return head end
  local w_last = q
  while q and skippable(q) do q = q.prev end
  local before_w = q
  if not before_w then return head end     -- whole line is whitespace; leave it
  local w_first = before_w.next
  local d_first = w_last.next
  local after_d = d_last.next
  -- detach W = [w_first .. w_last]
  before_w.next = d_first
  if d_first then d_first.prev = before_w end
  -- reinsert W after the dir run (outside every dir => box/base direction)
  d_last.next  = w_first
  w_first.prev = d_last
  w_last.next  = after_d
  if after_d then after_d.prev = w_last end
  return head
end

function Babel.reset_lines(head)
  for line, subtype in node.traverse_id(HLIST, head) do
    if subtype == LINE then
      line.list = reset_line(line.list)
    end
  end
  return head
end

luatexbase.add_to_callback('post_linebreak_filter',
  function(head, gc)
    if Babel.bidi_enabled then head = Babel.reset_lines(head) end
    return head
```

```
  end,
  'Babel.reset_lines')
</basic>
```

10. Data for CJK

It is a boring file and it is not shown here (see the generated file), but here is a sample:

```
% [0x0021]={c='ex'},
% [0x0024]={c='pr'},
% [0x0025]={c='po'},
% [0x0028]={c='op'},
% [0x0029]={c='cp'},
% [0x002B]={c='pr'},
%
```

For the meaning of these codes, see the Unicode standard.

11. The 'nil' language

This 'language' does nothing, except setting the hyphenation patterns to nohyphenation. For this language currently no special definitions are needed or available.

The macro `\LdfInit` takes care of preventing that this file is loaded more than once, checking the category code of the `@` sign, etc.

```
<*nil>
\ProvidesLanguage{nil}[<@date@> v<@version@> Nil language]
\LdfInit{nil}{datenil}
```

When this file is read as an option, i.e., by the `\usepackage` command, `nil` could be an 'unknown' language in which case we have to make it known.

```
\ifx\l@nil\@undefined
  \newlanguage\l@nil
  \@namedef{bbl@hyphendata@\the\l@nil}{{}{}}% Remove warning
  \let\bbl@elt\relax
  \edef\bbl@languages{%  Add it to the list of languages
    \bbl@languages\bbl@elt{nil}{\the\l@nil}{}{}}
\fi
```

This macro is used to store the values of the hyphenation parameters `\lefthyphenmin` and `\righthyphenmin`.

```
\providehyphenmins{\CurrentOption}{\m@ne\m@ne}
```

The next step consists of defining commands to switch to (and from) the 'nil' language.

\captionnil
\datenil

```
\let\captionsnil\@empty
\let\datenil\@empty
```

There is no locale file for this pseudo-language, so the corresponding fields are defined here.

```
\def\bbl@inidata@nil{%
  \bbl@elt{identification}{tag.ini}{und}%
  \bbl@elt{identification}{load.level}{0}%
  \bbl@elt{identification}{charset}{utf8}%
  \bbl@elt{identification}{version}{1.0}%
  \bbl@elt{identification}{date}{2022-05-16}%
  \bbl@elt{identification}{name.local}{nil}%
  \bbl@elt{identification}{name.english}{nil}%
  \bbl@elt{identification}{name.babel}{nil}%
  \bbl@elt{identification}{tag.bcp47}{und}%
  \bbl@elt{identification}{language.tag.bcp47}{und}%
  \bbl@elt{identification}{tag.opentype}{dflt}%
```

```
  \bbl@elt{identification}{script.name}{Latin}%
  \bbl@elt{identification}{script.tag.bcp47}{Latn}%
  \bbl@elt{identification}{script.tag.opentype}{DFLT}%
  \bbl@elt{identification}{level}{1}%
  \bbl@elt{identification}{encodings}{}%
  \bbl@elt{identification}{derivate}{no}}
\@namedef{bbl@tbcp@nil}{und}
\@namedef{bbl@lbcp@nil}{und}
\@namedef{bbl@casing@nil}{und}
\@namedef{bbl@lotf@nil}{dflt}
\@namedef{bbl@elname@nil}{nil}
\@namedef{bbl@lname@nil}{nil}
\@namedef{bbl@esname@nil}{Latin}
\@namedef{bbl@sname@nil}{Latin}
\@namedef{bbl@sbcp@nil}{Latn}
\@namedef{bbl@sotf@nil}{latn}
```

The macro `\ldf@finish` takes care of looking for a configuration file, setting the main language to be switched on at `\begin{document}` and resetting the category code of `@` to its original value.

```
\ldf@finish{nil}
⟨/nil⟩
```

12. Calendars

The code for specific calendars are placed in the specific files, loaded when requested by an `ini` file in the `identification` section with `require.calendars`.

Start with function to compute the Julian day. It's based on the little library `calendar.js`, by John Walker, in the public domain.

```
⟨⟨*Compute Julian day⟩⟩  ▸
\def\bbl@fpmod#1#2{(#1-#2*floor((#1)/(#2)))}
\def\bbl@cs@gregleap#1{%
  (\bbl@fpmod{#1}{4} == 0) &&
    (!((\bbl@fpmod{#1}{100} == 0) && (\bbl@fpmod{#1}{400} != 0)))}
\def\bbl@cs@jd#1#2#3{% year, month, day
  \fpeval{ 1721424.5   + (365 * (#1 - 1)) +
    floor((#1 - 1) / 4)   + (-floor((#1 - 1) / 100)) +
    floor((#1 - 1) / 400) + floor((((367 * #2) - 362) / 12) +
    ((#2 <= 2) ? 0 : (\bbl@cs@gregleap{#1} ? -1 : -2)) + #3) }}
⟨⟨/Compute Julian day⟩⟩
```

12.1. Islamic

The code for the Civil calendar is based on it, too.

```
⟨*ca-islamic⟩
<@Compute Julian day@>
% == islamic (default)
% Not yet implemented
\def\bbl@ca@islamic#1-#2-#3\@@#4#5#6{}
```

The Civil calendar.

```
\def\bbl@cs@isltojd#1#2#3{ % year, month, day
  ((#3 + ceil(29.5 * (#2 - 1)) +
  (#1 - 1) * 354 + floor((3 + (11 * #1)) / 30) +
  1948439.5) - 1) }
\@namedef{bbl@ca@islamic-civil++}{\bbl@ca@islamicvl@x{+2}}
\@namedef{bbl@ca@islamic-civil+}{\bbl@ca@islamicvl@x{+1}}
\@namedef{bbl@ca@islamic-civil}{\bbl@ca@islamicvl@x{}}
\@namedef{bbl@ca@islamic-civil-}{\bbl@ca@islamicvl@x{-1}}
\@namedef{bbl@ca@islamic-civil--}{\bbl@ca@islamicvl@x{-2}}
\def\bbl@ca@islamicvl@x#1#2-#3-#4\@@#5#6#7{%
  \edef\bbl@tempa{%
    \fpeval{ floor(\bbl@cs@jd{#2}{#3}{#4})+0.5 #1}}%
```

```
  \edef#5{%
    \fpeval{ floor(((30*(\bbl@tempa-1948439.5)) + 10646)/10631) }}%
  \edef#6{\fpeval{
    min(12,ceil((\bbl@tempa-(29+\bbl@cs@isltojd{#5}{1}{1}))/29.5)+1) }}%
  \edef#7{\fpeval{ \bbl@tempa - \bbl@cs@isltojd{#5}{#6}{1} + 1} }}
```

The Umm al-Qura calendar, used mainly in Saudi Arabia, is based on moment-hijri, by Abdullah Alsigar (license MIT).

Since the main aim is to provide a suitable `\today`, and maybe some close dates, data just covers Hijri ∼1435/∼1460 (Gregorian ∼2014/∼2038).

```
\def\bbl@cs@umalqura@data{56660, 56690,56719,56749,56778,56808,%
  56837,56867,56897,56926,56956,56985,57015,57044,57074,57103,%
  57133,57162,57192,57221,57251,57280,57310,57340,57369,57399,%
  57429,57458,57487,57517,57546,57576,57605,57634,57664,57694,%
  57723,57753,57783,57813,57842,57871,57901,57930,57959,57989,%
  58018,58048,58077,58107,58137,58167,58196,58226,58255,58285,%
  58314,58343,58373,58402,58432,58461,58491,58521,58551,58580,%
  58610,58639,58669,58698,58727,58757,58786,58816,58845,58875,%
  58905,58934,58964,58994,59023,59053,59082,59111,59141,59170,%
  59200,59229,59259,59288,59318,59348,59377,59407,59436,59466,%
  59495,59525,59554,59584,59613,59643,59672,59702,59731,59761,%
  59791,59820,59850,59879,59909,59939,59968,59997,60027,60056,%
  60086,60115,60145,60174,60204,60234,60264,60293,60323,60352,%
  60381,60411,60440,60469,60499,60528,60558,60588,60618,60648,%
  60677,60707,60736,60765,60795,60824,60853,60883,60912,60942,%
  60972,61002,61031,61061,61090,61120,61149,61179,61208,61237,%
  61267,61296,61326,61356,61385,61415,61445,61474,61504,61533,%
  61563,61592,61621,61651,61680,61710,61739,61769,61799,61828,%
  61858,61888,61917,61947,61976,62006,62035,62064,62094,62123,%
  62153,62182,62212,62242,62271,62301,62331,62360,62390,62419,%
  62448,62478,62507,62537,62566,62596,62625,62655,62685,62715,%
  62744,62774,62803,62832,62862,62891,62921,62950,62980,63009,%
  63039,63069,63099,63128,63157,63187,63216,63246,63275,63305,%
  63334,63363,63393,63423,63453,63482,63512,63541,63571,63600,%
  63630,63659,63689,63718,63747,63777,63807,63836,63866,63895,%
  63925,63955,63984,64014,64043,64073,64102,64131,64161,64190,%
  64220,64249,64279,64309,64339,64368,64398,64427,64457,64486,%
  64515,64545,64574,64603,64633,64663,64692,64722,64752,64782,%
  64811,64841,64870,64899,64929,64958,64987,65017,65047,65076,%
  65106,65136,65166,65195,65225,65254,65283,65313,65342,65371,%
  65401,65431,65460,65490,65520}
\@namedef{bbl@ca@islamic-umalqura+}{\bbl@ca@islamcuqr@x{+1}}
\@namedef{bbl@ca@islamic-umalqura}{\bbl@ca@islamcuqr@x{}}
\@namedef{bbl@ca@islamic-umalqura-}{\bbl@ca@islamcuqr@x{-1}}
\def\bbl@ca@islamcuqr@x#1#2-#3-#4\@@#5#6#7{%
  \ifnum#2>2014 \ifnum#2<2038
    \bbl@afterfi\expandafter\@gobble
  \fi\fi
    {\bbl@error{year-out-range}{2014-2038}{}{}}%
  \edef\bbl@tempd{\fpeval{ % (Julian) day
    \bbl@cs@jd{#2}{#3}{#4} + 0.5 - 2400000 #1}}%
  \count@\@ne
  \bbl@foreach\bbl@cs@umalqura@data{%
    \advance\count@\@ne
    \ifnum##1>\bbl@tempd\else
      \edef\bbl@tempe{\the\count@}%
      \edef\bbl@tempb{##1}%
    \fi}%
  \edef\bbl@templ{\fpeval{ \bbl@tempe + 16260 + 949 }}% month~lunar
  \edef\bbl@tempa{\fpeval{ floor((\bbl@templ - 1 ) / 12) }}% annus
  \edef#5{\fpeval{ \bbl@tempa + 1  }}%
  \edef#6{\fpeval{ \bbl@templ - (12 * \bbl@tempa) }}%
  \edef#7{\fpeval{ \bbl@tempd - \bbl@tempb + 1 }}}
```

```
\bbl@add\bbl@precalendar{%
  \bbl@replace\bbl@ld@calendar{-civil}{}%
  \bbl@replace\bbl@ld@calendar{-umalqura}{}%
  \bbl@replace\bbl@ld@calendar{+}{}%
  \bbl@replace\bbl@ld@calendar{-}{}}
</ca-islamic>
```

12.2. Hebrew

This is basically the set of macros written by Michail Rozman in 1991, with corrections and adaptions by Rama Porrat, Misha, Dan Haran and Boris Lavva. This must be eventually replaced by computations with l3fp. An explanation of what's going on can be found in `hebcal.sty`

```
<*ca-hebrew>
\newcount\bbl@cntcommon
\def\bbl@remainder#1#2#3{%
  #3=#1\relax
  \divide #3 by #2\relax
  \multiply #3 by -#2\relax
  \advance #3 by #1\relax}%
\newif\ifbbl@divisible
\def\bbl@checkifdivisible#1#2{%
  {\countdef\tmp=0
   \bbl@remainder{#1}{#2}{\tmp}%
   \ifnum \tmp=0
       \global\bbl@divisibletrue
   \else
       \global\bbl@divisiblefalse
   \fi}}
\newif\ifbbl@gregleap
\def\bbl@ifgregleap#1{%
  \bbl@checkifdivisible{#1}{4}%
  \ifbbl@divisible
      \bbl@checkifdivisible{#1}{100}%
      \ifbbl@divisible
          \bbl@checkifdivisible{#1}{400}%
          \ifbbl@divisible
              \bbl@gregleaptrue
          \else
              \bbl@gregleapfalse
          \fi
      \else
          \bbl@gregleaptrue
      \fi
  \else
      \bbl@gregleapfalse
  \fi
  \ifbbl@gregleap}
\def\bbl@gregdayspriormonths#1#2#3{%
    {#3=\ifcase #1 0 \or 0 \or 31 \or 59 \or 90 \or 120 \or 151 \or
          181 \or 212 \or 243 \or 273 \or 304 \or 334 \fi
     \bbl@ifgregleap{#2}%
         \ifnum #1 > 2
             \advance #3 by 1
         \fi
     \fi
     \global\bbl@cntcommon=#3}%
    #3=\bbl@cntcommon}
\def\bbl@gregdaysprioryears#1#2{%
  {\countdef\tmpc=4
   \countdef\tmpb=2
   \tmpb=#1\relax
   \advance \tmpb by -1
   \tmpc=\tmpb
```

```
  \multiply \tmpc by 365
  #2=\tmpc
  \tmpc=\tmpb
  \divide \tmpc by 4
  \advance #2 by \tmpc
  \tmpc=\tmpb
  \divide \tmpc by 100
  \advance #2 by -\tmpc
  \tmpc=\tmpb
  \divide \tmpc by 400
  \advance #2 by \tmpc
  \global\bbl@cntcommon=#2\relax}%
 #2=\bbl@cntcommon}
\def\bbl@absfromgreg#1#2#3#4{%
 {\countdef\tmpd=0
  #4=#1\relax
  \bbl@gregdayspriormonths{#2}{#3}{\tmpd}%
  \advance #4 by \tmpd
  \bbl@gregdaysprioryears{#3}{\tmpd}%
  \advance #4 by \tmpd
  \global\bbl@cntcommon=#4\relax}%
 #4=\bbl@cntcommon}
\newif\ifbbl@hebrleap
\def\bbl@checkleaphebryear#1{%
 {\countdef\tmpa=0
  \countdef\tmpb=1
  \tmpa=#1\relax
  \multiply \tmpa by 7
  \advance \tmpa by 1
  \bbl@remainder{\tmpa}{19}{\tmpb}%
  \ifnum \tmpb < 7
      \global\bbl@hebrleaptrue
  \else
      \global\bbl@hebrleapfalse
  \fi}}
\def\bbl@hebrelapsedmonths#1#2{%
 {\countdef\tmpa=0
  \countdef\tmpb=1
  \countdef\tmpc=2
  \tmpa=#1\relax
  \advance \tmpa by -1
  #2=\tmpa
  \divide #2 by 19
  \multiply #2 by 235
  \bbl@remainder{\tmpa}{19}{\tmpb}% \tmpa=years%19-years this cycle
  \tmpc=\tmpb
  \multiply \tmpb by 12
  \advance #2 by \tmpb
  \multiply \tmpc by 7
  \advance \tmpc by 1
  \divide \tmpc by 19
  \advance #2 by \tmpc
  \global\bbl@cntcommon=#2}%
 #2=\bbl@cntcommon}
\def\bbl@hebrelapseddays#1#2{%
 {\countdef\tmpa=0
  \countdef\tmpb=1
  \countdef\tmpc=2
  \bbl@hebrelapsedmonths{#1}{#2}%
  \tmpa=#2\relax
  \multiply \tmpa by 13753
  \advance \tmpa by 5604
  \bbl@remainder{\tmpa}{25920}{\tmpc}% \tmpc == ConjunctionParts
```

```
  \divide \tmpa by 25920
  \multiply #2 by 29
  \advance #2 by 1
  \advance #2 by \tmpa
  \bbl@remainder{#2}{7}{\tmpa}%
  \ifnum \tmpc < 19440
      \ifnum \tmpc < 9924
      \else
          \ifnum \tmpa=2
              \bbl@checkleaphebryear{#1}% of a common year
              \ifbbl@hebrleap
              \else
                  \advance #2 by 1
              \fi
          \fi
      \fi
      \ifnum \tmpc < 16789
      \else
          \ifnum \tmpa=1
              \advance #1 by -1
              \bbl@checkleaphebryear{#1}% at the end of leap year
              \ifbbl@hebrleap
                  \advance #2 by 1
              \fi
          \fi
      \fi
  \else
      \advance #2 by 1
  \fi
  \bbl@remainder{#2}{7}{\tmpa}%
  \ifnum \tmpa=0
      \advance #2 by 1
  \else
      \ifnum \tmpa=3
          \advance #2 by 1
      \else
          \ifnum \tmpa=5
               \advance #2 by 1
          \fi
      \fi
  \fi
  \global\bbl@cntcommon=#2\relax}%
 #2=\bbl@cntcommon}
\def\bbl@daysinhebryear#1#2{%
 {\countdef\tmpe=12
  \bbl@hebrelapseddays{#1}{\tmpe}%
  \advance #1 by 1
  \bbl@hebrelapseddays{#1}{#2}%
  \advance #2 by -\tmpe
  \global\bbl@cntcommon=#2}%
 #2=\bbl@cntcommon}
\def\bbl@hebrdayspriormonths#1#2#3{%
 {\countdef\tmpf= 14
  #3=\ifcase #1
          0 \or
          0 \or
         30 \or
         59 \or
         89 \or
        118 \or
        148 \or
        148 \or
        177 \or
```

```
        207 \or
        236 \or
        266 \or
        295 \or
        325 \or
        400
  \fi
  \bbl@checkleaphebryear{#2}%
  \ifbbl@hebrleap
      \ifnum #1 > 6
          \advance #3 by 30
      \fi
  \fi
  \bbl@daysinhebryear{#2}{\tmpf}%
  \ifnum #1 > 3
      \ifnum \tmpf=353
          \advance #3 by -1
      \fi
      \ifnum \tmpf=383
          \advance #3 by -1
      \fi
  \fi
  \ifnum #1 > 2
      \ifnum \tmpf=355
          \advance #3 by 1
      \fi
      \ifnum \tmpf=385
          \advance #3 by 1
      \fi
  \fi
  \global\bbl@cntcommon=#3\relax}%
 #3=\bbl@cntcommon}
\def\bbl@absfromhebr#1#2#3#4{%
 {#4=#1\relax
  \bbl@hebrdayspriormonths{#2}{#3}{#1}%
  \advance #4 by #1\relax
  \bbl@hebrelapseddays{#3}{#1}%
  \advance #4 by #1\relax
  \advance #4 by -1373429
  \global\bbl@cntcommon=#4\relax}%
 #4=\bbl@cntcommon}
\def\bbl@hebrfromgreg#1#2#3#4#5#6{%
 {\countdef\tmpx= 17
  \countdef\tmpy= 18
  \countdef\tmpz= 19
  #6=#3\relax
  \global\advance #6 by 3761
  \bbl@absfromgreg{#1}{#2}{#3}{#4}%
  \tmpz=1  \tmpy=1
  \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
  \ifnum \tmpx > #4\relax
      \global\advance #6 by -1
      \bbl@absfromhebr{\tmpz}{\tmpy}{#6}{\tmpx}%
  \fi
  \advance #4 by -\tmpx
  \advance #4 by 1
  #5=#4\relax
  \divide #5 by 30
  \loop
      \bbl@hebrdayspriormonths{#5}{#6}{\tmpx}%
      \ifnum \tmpx < #4\relax
          \advance #5 by 1
          \tmpy=\tmpx
```

```
  \repeat
  \global\advance #5 by -1
  \global\advance #4 by -\tmpy}}
\newcount\bbl@hebrday \newcount\bbl@hebrmonth \newcount\bbl@hebryear
\newcount\bbl@gregday \newcount\bbl@gregmonth \newcount\bbl@gregyear
\def\bbl@ca@hebrew#1-#2-#3\@@#4#5#6{%
  \bbl@gregday=#3\relax \bbl@gregmonth=#2\relax \bbl@gregyear=#1\relax
  \bbl@hebrfromgreg
    {\bbl@gregday}{\bbl@gregmonth}{\bbl@gregyear}%
    {\bbl@hebrday}{\bbl@hebrmonth}{\bbl@hebryear}%
  \edef#4{\the\bbl@hebryear}%
  \edef#5{\the\bbl@hebrmonth}%
  \edef#6{\the\bbl@hebrday}}
⟨/ca-hebrew⟩
```

12.3. Persian

There is an algorithm written in TeX by Jabri, Abolhassani, Pournader and Esfahbod, created for the first versions of the FarsiTeX system (no longer available), but the original license is GPL, so its use with LPPL is problematic. The code here follows loosely that by John Walker, which is free and accurate, but sadly very complex, so the relevant data for the years 2013-2050 have been pre-calculated and stored. Actually, all we need is the first day (either March 20 or March 21).

```
⟨*ca-persian⟩
<@Compute Julian day@>
\def\bbl@cs@firstjal@xx{2012,2016,2020,2024,2028,2029,% March 20
  2032,2033,2036,2037,2040,2041,2044,2045,2048,2049}
\def\bbl@ca@persian#1-#2-#3\@@#4#5#6{%
  \edef\bbl@tempa{#1}%  20XX-03-\bbl@tempe = 1 farvardin:
  \ifnum\bbl@tempa>2012 \ifnum\bbl@tempa<2051
    \bbl@afterfi\expandafter\@gobble
  \fi\fi
    {\bbl@error{year-out-range}{2013-2050}{}{}}%
  \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%
  \ifin@\def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
  \edef\bbl@tempc{\fpeval{\bbl@cs@jd{\bbl@tempa}{#2}{#3}+.5}}% current
  \edef\bbl@tempb{\fpeval{\bbl@cs@jd{\bbl@tempa}{03}{\bbl@tempe}+.5}}% begin
  \ifnum\bbl@tempc<\bbl@tempb
    \edef\bbl@tempa{\fpeval{\bbl@tempa-1}}% go back 1 year and redo
    \bbl@xin@{\bbl@tempa}{\bbl@cs@firstjal@xx}%
    \ifin@\def\bbl@tempe{20}\else\def\bbl@tempe{21}\fi
    \edef\bbl@tempb{\fpeval{\bbl@cs@jd{\bbl@tempa}{03}{\bbl@tempe}+.5}}%
  \fi
  \edef#4{\fpeval{\bbl@tempa-621}}% set Jalali year
  \edef#6{\fpeval{\bbl@tempc-\bbl@tempb+1}}% days from 1 farvardin
  \edef#5{\fpeval{% set Jalali month
    (#6 <= 186) ? ceil(#6 / 31) : ceil((#6 - 6) / 30)}}
  \edef#6{\fpeval{% set Jalali day
    (#6 - ((#5 <= 7) ? ((#5 - 1) * 31) : (((#5 - 1) * 30) + 6)))}}}
⟨/ca-persian⟩
```

12.4. Coptic and Ethiopic

Adapted from `jquery.calendars.package-1.1.4`, written by Keith Wood, 2010. Dual license: GPL and MIT. The only difference is the epoch.

```
⟨*ca-coptic⟩
<@Compute Julian day@>
\def\bbl@ca@coptic#1-#2-#3\@@#4#5#6{%
  \edef\bbl@tempd{\fpeval{floor(\bbl@cs@jd{#1}{#2}{#3}) + 0.5}}%
  \edef\bbl@tempc{\fpeval{\bbl@tempd - 1825029.5}}%
  \edef#4{\fpeval{%
    floor((\bbl@tempc - floor((\bbl@tempc+366) / 1461)) / 365) + 1}}%
  \edef\bbl@tempc{\fpeval{%
```

```
    \bbl@tempd - (#4-1) * 365 - floor(#4/4) - 1825029.5}}%
  \edef#5{\fpeval{floor(\bbl@tempc / 30) + 1}}%
  \edef#6{\fpeval{\bbl@tempc - (#5 - 1) * 30 + 1}}}
⟨/ca-coptic⟩
⟨*ca-ethiopic⟩
<@Compute Julian day@>
\def\bbl@ca@ethiopic#1-#2-#3\@@#4#5#6{%
  \edef\bbl@tempd{\fpeval{floor(\bbl@cs@jd{#1}{#2}{#3}) + 0.5}}%
  \edef\bbl@tempc{\fpeval{\bbl@tempd - 1724220.5}}%
  \edef#4{\fpeval{%
    floor((\bbl@tempc - floor((\bbl@tempc+366) / 1461)) / 365) + 1}}%
  \edef\bbl@tempc{\fpeval{%
    \bbl@tempd - (#4-1) * 365 - floor(#4/4) - 1724220.5}}%
  \edef#5{\fpeval{floor(\bbl@tempc / 30) + 1}}%
  \edef#6{\fpeval{\bbl@tempc - (#5 - 1) * 30 + 1}}}
⟨/ca-ethiopic⟩
```

12.5. Julian

Based on [ReinDersh].

```
⟨*ca-julian⟩
<@Compute Julian day@>
\def\bbl@ca@julian#1-#2-#3\@@#4#5#6{%
  \edef\bbl@tempj{\fpeval{floor(\bbl@cs@jd{#1}{#2}{#3}) + .5}}%
  \edef\bbl@tempa{\fpeval{\bbl@tempj + 32082.5}}%
  \edef\bbl@tempb{\fpeval{floor((4 * \bbl@tempa + 3) / 1461)}}%
  \edef\bbl@tempc{\fpeval{\bbl@tempa - floor(1461*\bbl@tempb/4)}}%
  \edef\bbl@tempd{\fpeval{floor((5 * \bbl@tempc + 2) / 153)}}%
  \edef#6{\fpeval{\bbl@tempc - floor((153*\bbl@tempd+2) / 5) + 1}}%
  \edef#5{\fpeval{\bbl@tempd + 3 - 12 * floor(\bbl@tempd / 10)}}%
  \edef#4{\fpeval{\bbl@tempb - 4800 + floor(\bbl@tempd / 10)}}}
⟨/ca-julian⟩
```

The Indian National Calendar, Saka era.

```
⟨*ca-indian⟩
<@Compute Julian day@>
\def\bbl@sakachaitra#1{%
  \bbl@cs@jd{#1}{3}{%
    \fpeval{ ((\bbl@fpmod{#1}{4}==0 && \bbl@fpmod{#1}{100}!=0)
    ||\bbl@fpmod{#1}{400}==0) ? 21 : 22 }}}
\def\bbl@ca@indian#1-#2-#3\@@#4#5#6{%
  \edef\bbl@tempa{\fpeval{\bbl@cs@jd{#1}{#2}{#3}}}%
  \edef\bbl@tempb{\fpeval{\bbl@sakachaitra{#1}}}%
  \edef\bbl@tempc{\fpeval{\bbl@tempa < \bbl@tempb ? #1-1 : #1}}%
  \edef\bbl@tempd{\fpeval{\bbl@tempa-\bbl@sakachaitra{\bbl@tempc}}}%
  \edef\bbl@tempe{\fpeval{ ((\bbl@fpmod{\bbl@tempc}{4}==0 &&
    \bbl@fpmod{\bbl@tempc}{100}!=0) || \bbl@fpmod{\bbl@tempc}{400}==0)?31:30}}%
  \edef#4{\fpeval{\bbl@tempc-78}}%
  \edef#5{\fpeval{\bbl@tempd<\bbl@tempe ? 1 :
    (\bbl@tempd-\bbl@tempe < 155 ?
      2+trunc((\bbl@tempd-\bbl@tempe)/31,0) :
      7+trunc((\bbl@tempd-\bbl@tempe-155)/30,0))}}%
  \edef#6{\fpeval{\bbl@tempd<\bbl@tempe ? \bbl@tempd+1 :
    (\bbl@tempd-\bbl@tempe < 155 ?
      \bbl@fpmod{\bbl@tempd-\bbl@tempe}{31}+1 :
      \bbl@fpmod{\bbl@tempd-\bbl@tempe-155}{30}+1)}}}
⟨/ca-indian⟩
%
```

12.6. Buddhist

That's very simple.

```
⟨*ca-buddhist⟩
\def\bbl@ca@buddhist#1-#2-#3\@@#4#5#6{%
  \edef#4{\number\numexpr#1+543\relax}%
  \edef#5{#2}%
  \edef#6{#3}}
⟨/ca-buddhist⟩
%
% \subsection{Chinese}
%
% Brute force, with the Julian day of first day of each month. The
% table has been computed with the help of \textsf{python-lunardate} by
% Ricky Yeung, GPLv2 (but the code itself has not been used). The range
% is 2015-2044.
%
%    \begin{macrocode}
⟨*ca-chinese⟩
\ExplSyntaxOn
<@Compute Julian day@>
\def\bbl@ca@chinese#1-#2-#3\@@#4#5#6{%
  \edef\bbl@tempd{\fpeval{%
    \bbl@cs@jd{#1}{#2}{#3} - 2457072.5 }}%
  \count@\z@
  \@tempcnta=2015
  \bbl@foreach\bbl@cs@chinese@data{%
    \ifnum##1>\bbl@tempd\else
      \advance\count@\@ne
      \ifnum\count@>12
        \count@\@ne
        \advance\@tempcnta\@ne\fi
      \bbl@xin@{,##1,}{,\bbl@cs@chinese@leap,}%
      \ifin@
        \advance\count@\m@ne
        \edef\bbl@tempe{\the\numexpr\count@+12\relax}%
      \else
        \edef\bbl@tempe{\the\count@}%
      \fi
      \edef\bbl@tempb{##1}%
    \fi}%
  \edef#4{\the\@tempcnta}%
  \edef#5{\bbl@tempe}%
  \edef#6{\the\numexpr\bbl@tempd-\bbl@tempb+1\relax}}
\def\bbl@cs@chinese@leap{%
  885,1920,2953,3809,4873,5906,6881,7825,8889,9893,10778}
\def\bbl@cs@chinese@data{0,29,59,88,117,147,176,206,236,266,295,325,
  354,384,413,443,472,501,531,560,590,620,649,679,709,738,%
  768,797,827,856,885,915,944,974,1003,1033,1063,1093,1122,%
  1152,1181,1211,1240,1269,1299,1328,1358,1387,1417,1447,1477,%
  1506,1536,1565,1595,1624,1653,1683,1712,1741,1771,1801,1830,%
  1860,1890,1920,1949,1979,2008,2037,2067,2096,2126,2155,2185,%
  2214,2244,2274,2303,2333,2362,2392,2421,2451,2480,2510,2539,%
  2569,2598,2628,2657,2687,2717,2746,2776,2805,2835,2864,2894,%
  2923,2953,2982,3011,3041,3071,3100,3130,3160,3189,3219,3248,%
  3278,3307,3337,3366,3395,3425,3454,3484,3514,3543,3573,3603,%
  3632,3662,3691,3721,3750,3779,3809,3838,3868,3897,3927,3957,%
  3987,4016,4046,4075,4105,4134,4163,4193,4222,4251,4281,4311,%
  4341,4370,4400,4430,4459,4489,4518,4547,4577,4606,4635,4665,%
  4695,4724,4754,4784,4814,4843,4873,4902,4931,4961,4990,5019,%
  5049,5079,5108,5138,5168,5197,5227,5256,5286,5315,5345,5374,%
  5403,5433,5463,5492,5522,5551,5581,5611,5640,5670,5699,5729,%
  5758,5788,5817,5846,5876,5906,5935,5965,5994,6024,6054,6083,%
  6113,6142,6172,6201,6231,6260,6289,6319,6348,6378,6408,6437,%
  6467,6497,6526,6556,6585,6615,6644,6673,6703,6732,6762,6791,%
  6821,6851,6881,6910,6940,6969,6999,7028,7057,7087,7116,7146,%
```

```
  7175,7205,7235,7264,7294,7324,7353,7383,7412,7441,7471,7500,%
  7529,7559,7589,7618,7648,7678,7708,7737,7767,7796,7825,7855,%
  7884,7913,7943,7972,8002,8032,8062,8092,8121,8151,8180,8209,%
  8239,8268,8297,8327,8356,8386,8416,8446,8475,8505,8534,8564,%
  8593,8623,8652,8681,8711,8740,8770,8800,8829,8859,8889,8918,%
  8948,8977,9007,9036,9066,9095,9124,9154,9183,9213,9243,9272,%
  9302,9331,9361,9391,9420,9450,9479,9508,9538,9567,9597,9626,%
  9656,9686,9715,9745,9775,9804,9834,9863,9893,9922,9951,9981,%
  10010,10040,10069,10099,10129,10158,10188,10218,10247,10277,%
  10306,10335,10365,10394,10423,10453,10483,10512,10542,10572,%
  10602,10631,10661,10690,10719,10749,10778,10807,10837,10866,%
  10896,10926,10956,10986,11015,11045,11074,11103}
\ExplSyntaxOff
⟨/ca-chinese⟩
```

13. Acknowledgements

In the initial stages of the development of babel, Bernd Raichle provided many helpful suggestions and Michel Goossens supplied contributions for many languages. Ideas from Nico Poppelier, Piet van Oostrum and many others have been used. Paul Wackers and Werenfried Spit helped find and repair bugs.

More recently, there are significant contributions by Salim Bou, Ulrike Fischer, Loren Davis and Udi Fogiel.

Barbara Beeton has helped in improving the manual.

There are also many contributors for specific languages, which are mentioned in the respective files. Without them, babel just wouldn't exist.

References

[1] Huda Smitshuijzen Abifares, *Arabic Typography*, Saqi, 2001.

[2] Johannes Braams, Victor Eijkhout and Nico Poppelier, *The development of national LaTeX styles*, *TUGboat* 10 (1989) #3, pp. 401–406.

[3] Yannis Haralambous, *Fonts & Encodings*, O'Reilly, 2007.

[4] Donald E. Knuth, *The TeXbook*, Addison-Wesley, 1986.

[5] Jukka K. Korpela, *Unicode Explained*, O'Reilly, 2006.

[6] Leslie Lamport, *LaTeX, A document preparation System*, Addison-Wesley, 1986.

[7] Leslie Lamport, in: TeXhax Digest, Volume 89, #13, 17 February 1989.

[8] Ken Lunde, *CJKV Information Processing*, O'Reilly, 2nd ed., 2009.

[9] Edward M. Reingold and Nachum Dershowitz, *Calendrical Calculations: The Ultimate Edition*, Cambridge University Press, 2018

[10] Hubert Partl, *German TeX*, *TUGboat* 9 (1988) #1, pp. 70–72.

[11] Joachim Schrod, *International LaTeX is ready to use*, *TUGboat* 11 (1990) #1, pp. 87–90.

[12] Apostolos Syropoulos, Antonis Tsolomitis and Nick Sofroniu, *Digital typography using LaTeX*, Springer, 2002, pp. 301–373.

[13] K.F. Treebus. *Tekstwijzer, een gids voor het grafisch verwerken van tekst*, SDU Uitgeverij ('s-Gravenhage, 1988).