The LaTeX 2_ε Sources

Johannes Braams
David Carlisle
Alan Jeffrey
Leslie Lamport
Frank Mittelbach
Chris Rowley
Rainer Schöpf

2022-06-01

This file is maintained by the LaTeX Project team.
Bug reports can be opened (category `latex`) at
https://latex-project.org/bugs.html.

Contents

a ltdirchk.dtx **1**

1 LaTeX System Dependent Initializations **1**

2 Initialization **2**
2.1 INITEX . . . 3
2.2 Some bits of 2e . . . 4

3 texsys.cfg **5**
3.1 texsys.cfg . . . 6
3.2 UNIX (web2c) . . . 7
3.3 UNIX (other) . . . 7
3.4 MSDOS (emtex) . . . 7
3.5 MSDOS (other) . . . 7
3.6 VMS (DECUS TeX, PD VMS 3.6) . . . 7
3.7 VMS (???) . . . 8
3.8 MACINTOSH (OzTeX 1.6) . . . 8
3.9 MACINTOSH (other) . . . 8
3.10 FAKE EXAMPLE . . . 8

4 Setting `\@currdir` **9**

5 Setting `\input@path` **11**

6 Filename Parsing 11

7 TEX Versions 13

8 ltxcheck.tex 14

b ltplain.dtx 15

1 Plain TEX 15

c ltvers.dtx 39

1 Version Identification 39
1.1 Declaring an all-new module 42

d ltluatex.dtx 44

1 Overview 44

2 Core TEX functionality 44

3 Plain TEX interface 45

4 Lua functionality 45
4.1 Allocators in Lua 45
4.2 Lua access to TEX register numbers 46
4.3 Module utilities 47
4.4 Callback management 47

5 Implementation 48
5.1 Minimum LuaTEX version 48
5.2 Older LATEX/Plain TEX setup 48
5.2.1 Fixes to `etex.src/etex.sty` 49
5.2.2 luatex specific settings 49
5.3 Attributes 50
5.4 Category code tables 51
5.5 Named Lua functions 52
5.6 Custom whatsits 53
5.7 Lua bytecode registers 53
5.8 Lua chunk registers 54
5.9 Lua loader 54
5.10 Lua module preliminaries 55
5.11 Lua module utilities 56
5.11.1 Module tracking 56
5.11.2 Module messages 57
5.12 Accessing register numbers from Lua 58
5.13 Attribute allocation 59
5.14 Custom whatsit allocation 59

5.15 Bytecode register allocation . . . 60
5.16 Lua chunk name allocation . . . 60
5.17 Lua function allocation . . . 61
5.18 Lua callback management . . . 61
5.18.1 Housekeeping . . . 61
5.18.2 Handlers . . . 64
5.18.3 Public functions for callback management . . . 66

e ltexpl.dtx 72

1 expl3-dependent code 72
1.1 Loader . . . 72
1.2 Using expl3 code . . . 75

2 Document-level command names for expl3 functions 76

f ltdefns.dtx 78

1 Definitions 78
1.1 Initex initializations . . . 78
1.2 Saved versions of TEX primitives . . . 78
1.3 Command definitions . . . 79
1.4 Robust commands and protect . . . 88
1.5 Acting on robust commands . . . 94
1.5.1 Copying robust commands . . . 96
1.5.2 Showing robust commands . . . 97
1.5.3 Commands defined with `\DeclareRobustCommand` . . . 98
1.5.4 Commands defined with `\newcommand` (with optional argument) . . . 100
1.6 Internal defining commands . . . 101

2 Discretionary Hyphenation 105

g ltcmd.dtx 108

1 Creating document commands 108
1.1 Variables and constants . . . 108
1.2 Declaring commands and environments . . . 111
1.3 Structure of xparse commands . . . 115
1.4 Normalizing the argument specifications . . . 120
1.5 Preparing the signature: general mechanism . . . 128
1.6 Setting up a standard signature . . . 129
1.7 Setting up expandable types . . . 134
1.7.1 Copying a command and its internal structure . . . 137
1.7.2 Showing the definition of a command . . . 142
1.8 Grabbing arguments . . . 146
1.9 Grabbing arguments expandably . . . 158
1.10 Argument processors . . . 163
1.11 Access to the argument specification . . . 165

1.12 Utilities . . . 167
1.13 Messages . . . 171
1.14 User functions . . . 176

h lthooks.dtx **181**

1 Introduction **181**

2 Package writer interface **181**
2.1 LaTeX 2_ε interfaces . . . 181
2.1.1 Declaring hooks . . . 181
2.1.2 Special declarations for generic hooks . . . 182
2.1.3 Using hooks in code . . . 182
2.1.4 Updating code for hooks . . . 183
2.1.5 Hook names and default labels . . . 185
2.1.6 The `top-level` label . . . 187
2.1.7 Defining relations between hook code . . . 188
2.1.8 Querying hooks . . . 189
2.1.9 Displaying hook code . . . 190
2.1.10 Debugging hook code . . . 191
2.2 L3 programming layer (`expl3`) interfaces . . . 191
2.3 On the order of hook code execution . . . 193
2.4 The use of "reversed" hooks . . . 195
2.5 Difference between "normal" and "one-time" hooks . . . 196
2.6 Generic hooks provided by packages . . . 197
2.7 Private LaTeX kernel hooks . . . 197
2.8 Legacy LaTeX 2_ε interfaces . . . 198

3 LaTeX 2_ε commands and environments augmented by hooks **199**
3.1 Generic hooks . . . 199
3.1.1 Generic hooks for all environments . . . 199
3.1.2 Generic hooks for commands . . . 200
3.1.3 Generic hooks provided by file loading operations . . . 201
3.2 Hooks provided by `\begin{document}` . . . 201
3.3 Hooks provided by `\end{document}` . . . 201
3.4 Hooks provided by `\shipout` operations . . . 203
3.5 Hooks provided for paragraphs . . . 203
3.6 Hooks provided in NFSS commands . . . 203
3.7 Hook provided by the mark mechanism . . . 204

4 The Implementation **204**
4.1 Debugging . . . 204
4.2 Borrowing from internals of other kernel modules . . . 205
4.3 Declarations . . . 205
4.4 Providing new hooks . . . 207
4.4.1 The data structures of a hook . . . 207
4.4.2 On the existence of hooks . . . 208
4.4.3 Setting hooks up . . . 209
4.4.4 Disabling and providing hooks . . . 212
4.5 Parsing a label . . . 213
4.6 Adding or removing hook code . . . 217
4.7 Setting rules for hooks code . . . 226
4.8 Specifying code for next invocation . . . 241
4.9 Using the hook . . . 242
4.10 Querying a hook . . . 245
4.11 Messages . . . 247
4.12 LaTeX 2_ε package interface commands . . . 249
4.13 Deprecated that needs cleanup at some point . . . 252
4.14 Internal commands needed elsewhere . . . 254

i ltcmdhooks.dtx **256**

1 Introduction **256**

2 Restrictions and Operational details **256**
2.1 Patching . . . 257
2.1.1 Timing . . . 257
2.2 Commands that look ahead . . . 257

3 Package Author Interface **258**

4 The Implementation **259**
4.1 Execution plan . . . 259
4.2 Variables . . . 259
4.3 Variants . . . 260
4.4 Patching or delaying . . . 261
4.5 Patching commands . . . 262
4.5.1 Patching by expansion and redefinition . . . 263
4.5.2 Patching by retokenization . . . 269
4.6 Messages . . . 273

j ltalloc.dtx **275**

1 Counters **275**

k ltcntrl.dtx **277**

1 Program control structure **277**

l lterror.dtx **281**

1 Error handling and tracing **281**
1.1 General commands . . . 281
1.2 Specific errors . . . 287
1.3 Tracing . . . 291

m ltpar.dtx **292**

1 Paragraphs **292**
1.1 Implementation . . . 292

n ltpara.dtx **294**

1 Introduction **294**
1.1 The default processing done by the engine . . . 294

2 The new mechanism implemented for LaTeX **296**
2.1 The provided hooks . . . 297
2.2 Altered and newly provided commands . . . 298
2.3 Examples . . . 299
2.3.1 Testing the mechanism . . . 299
2.3.2 Mark the first paragraph of each `itemize` . . . 301
2.4 Some technical notes . . . 301
2.4.1 Glue items between paragraphs (found with fancypar) . . . 301

3 The Implementation **302**
3.1 Providing hooks for paragraphs . . . 302
3.2 The error messages . . . 308

o ltmeta.dtx **310**

1 Introduction **310**
1.1 `\DocumentMetadata` . . . 310

2 The Implementation **310**

p ltspace.dtx **312**

1 Spacing **312**
1.1 User Commands . . . 312
1.2 Chris' comments . . . 312
1.3 Some immediate actions . . . 314
1.4 The code . . . 315
1.5 Vertical spacing . . . 322
1.6 Horizontal space (and breaks) . . . 327

q ltlogos.dtx 331

1 Logos 331

r ltfiles.dtx 332

1 File Handling 332
1.1 Safe Input Macros . . . 345
1.2 Listing files . . . 352

s ltoutenc.dtx 354

1 Font encodings 354
1.1 Removing encoding-specific commands . . . 356
1.2 The order of declarations . . . 357
1.3 Docstrip modules . . . 357
1.4 Definitions for the kernel . . . 358
1.4.1 Declaration commands . . . 358
1.4.2 Hyphenation . . . 366
1.4.3 Miscellania . . . 366
1.4.4 Default encodings . . . 366
1.4.5 Math material . . . 369
1.5 Definitions for the OT1 encoding . . . 370
1.6 Definitions for the T1 encoding . . . 372
1.7 Definitions for the OMS encoding . . . 378
1.8 Definitions for the OML encoding . . . 379
1.9 Definitions for the OT4 encoding . . . 379
1.10 Definitions for the TS1 encoding . . . 381
1.11 Definitions for the TU encoding . . . 386

2 Package files 397
2.1 The fontenc package . . . 397

t ltcounts.dtx 400

1 Counters and Lengths 400
1.1 Environment Counter Macros . . . 400

u ltlength.dtx 408

1 Lengths 408

v ltfssbas.dtx 410

1 Preliminary macros 410

2 Macros for setting up the tables **411**

3 Selecting a new font **418**
3.1 Macros for the user 418
3.2 Macros for loading fonts 422

4 Assigning math fonts to *versions* **430**

w ltfssaxes.dtx **437**

1 Changing the font series **437**
1.1 The series lookup table 437
1.2 Mapping rules for series changes 438
1.3 Changing to a new series 446

2 Changing the shape **451**
2.1 Mapping rules for shape combinations 452
2.2 Changing to a new shape 454

3 Make sure we win . . . **456**

x ltfsstrc.dtx **458**

1 Introduction **458**

2 A driver for this document **458**

3 The Implementation **459**

4 Handling Options **459**

5 Macros common to `fam.tex` and `tracefnt.sty` **461**
5.1 General font loading 461
5.2 Math fonts setup 467
5.2.1 Outline of algorithm for math font sizes 467
5.2.2 Code for math font size setting 468
5.2.3 Other code for math 469

6 Scaled font extraction **471**
6.1 Sizefunctions 479

y ltfsscmp.dtx **483**

z ltfssdcl.dtx **488**

1 Interface Commands **488**

A ltfssini.dtx **518**

1 NFSS Initialization **518**
1.1 Providing math *versions* . . . 518

2 Custom series settings for main document families **519**

3 Supporting nested emphasis **536**
3.1 Legacy . . . 540
3.2 Miscellaneous . . . 540

B fontdef.dtx **546**

1 Introduction **546**

2 Customization **546**

3 The `docstrip` modules **547**

4 A driver for this document **547**

5 The `fonttext.ltx` file **547**
5.1 Encodings . . . 548
5.2 Defaults . . . 550

6 The `fontmath.ltx` file **552**
6.1 The font encodings used . . . 552
6.1.1 Symbolfont and Alphabet declarations . . . 552
6.2 Math font sizes . . . 553
6.3 The math symbol assignments . . . 554
6.3.1 The letters . . . 554
6.3.2 The digits . . . 555
6.3.3 Punctuation, brace, etc. keys . . . 555
6.3.4 Delimitercodes for characters . . . 555
6.4 Symbols accessed via control sequences . . . 556
6.4.1 Greek letters . . . 556
6.4.2 Ordinary symbols . . . 557
6.4.3 Large Operators . . . 557
6.4.4 Binary symbols . . . 558
6.4.5 Relations . . . 559
6.4.6 Arrows . . . 560
6.4.7 Punctuation symbols . . . 561
6.4.8 Math accents . . . 562
6.4.9 Radicals . . . 562
6.4.10 Over and under something, etc . . . 562
6.4.11 Delimiters . . . 563
6.5 Math versions of text commands . . . 564
6.6 Other special functions and parameters . . . 564
6.6.1 Biggggg . . . 564
6.6.2 The log-like functions . . . 565

6.6.3 Parameters 565

7 Default cfg files **565**

C preload.dtx **567**

1 Overview **567**

2 Customization **567**

3 Module switches for the DOCSTRIP program **567**

4 A driver for this document **568**

5 The code **568**

D ltfntcmd.dtx **570**

1 Introduction **570**

2 The implementation **572**

3 Initialization **578**

E lttextcomp.dtx **579**

1 Sub-encodings **583**

1.1 Unavailable in sub-encoding 1 and higher (drop symbols not working in Latin Modern) 584

1.2 Unavailable in sub-encoding 2 (majority of new OTF fonts via autoinst) and higher 584

1.3 Unavailable in sub-encoding 3 and higher 588

1.4 Unavailable in sub-encoding 4 and higher 588

1.5 Unavailable in sub-encoding 5 (most older PS fonts) and higher 588

1.6 Unavailable in sub-encoding 6 and higher 589

1.7 Unavailable in sub-encoding 7 and higher 589

1.8 Unavailable in sub-encoding 8 and higher 589

1.9 Unavailable in Sub-encoding 9 (most missing) 589

2 Unicode engine specials **589**

3 Font family sub-encodings setup **590**

4 Legacy symbol support for lists and footnote symbols **594**

5 The textcomp package **599**

5.1 The old textcomp package code 600

5.1.1 Supporting oldstyle digits 608

5.1.2 Subset encoding defaults 609

F ltpageno.dtx 611

1 Page Numbering 611

G ltxref.dtx 612

1 Cross Referencing 612
1.1 Cross Referencing . . . 612

H ltmiscen.dtx 618

1 Miscellaneous Environments 618
1.1 Environments . . . 618
1.2 Center, Flushright, Flushleft . . . 630
1.3 Verbatim . . . 633

I ltmath.dtx 639

1 Math setup 639
1.1 Math commands based on plain TEX . . . 639
1.1.1 The log-like functions . . . 639
1.1.2 Biggggg . . . 640
1.1.3 The UNSORTED Rest . . . 640
1.2 Math Environments . . . 646
1.3 External options to the standard document classes . . . 651
1.3.1 Left equation numbering . . . 651
1.3.2 Flush left equations . . . 651

J ltlists.dtx 654

1 List, and related environments 654
1.1 List and Trivlist . . . 655
1.2 Vertical Spacing (skips) . . . 656
1.3 Penalties . . . 656
1.4 Horizontal Spacing (dimens) . . . 656
1.5 Default Values . . . 656
1.6 Itemize and Enumerate . . . 667

K ltboxes.dtx 670

1 LATEX Box commands 670
1.1 Some low-level constructs . . . 685

L lttab.dtx 686

1 Tabbing, Tabular and Array Environments 686
1.1 tabbing . . . 686
1.2 array and tabular environments . . . 695

M ltpictur.dtx 711

1 Picture Mode 711
1.1 Curves . . . 738

N ltthm.dtx 743

1 Theorem Environments 743

O ltsect.dtx 747

1 Sectioning Commands 747
1.1 The Title . . . 747
1.2 Sectioning . . . 748
1.2.1 Initializations . . . 755
1.3 Table of Contents etc. . . . 755
1.3.1 Convention . . . 755
1.3.2 Commands . . . 755

P ltfloat.dtx 760

1 Floats 760
1.1 Floating Environments . . . 760
1.2 Footnotes . . . 774

Q ltidxglo.dtx 783

1 Index and Glossary Generation 783

R ltbibl.dtx 786

1 Bibliography Generation 786
1.1 Default definitions . . . 790

S ltmarks.dtx 791

1 Introduction 791

2 Design-level and code-level interfaces 792
2.1 Debugging mark code . . . 795

3 Application examples **795**

4 Legacy LaTeX 2_ε interface **795**
4.1 Legacy design-level and document-level interfaces . . . 795
4.2 Legacy interface extensions . . . 796

5 Notes on the mechanism **796**

6 Internal output routine functions **798**

7 The Implementation **799**
7.1 Allocating new mark classes . . . 799
7.2 Updating mark structures . . . 800
7.3 Placing and retrieving marks . . . 804
7.4 Comparing mark values . . . 805
7.5 Messages . . . 806
7.6 Debugging the mark structures . . . 807
7.7 Designer-level interfaces . . . 808

8 LaTeX 2_ε integration **809**
8.1 Core LaTeX 2_ε integration . . . 809
8.2 Other LaTeX 2_ε output routines . . . 811

T ltpage.dtx **813**

1 Page styles and related commands **813**
1.1 Page Style Commands . . . 813
1.2 How a page style makes running heads and feet . . . 813
1.3 marking conventions . . . 813

U ltclass.dtx **818**

1 Introduction **818**

2 User interface **818**
2.1 Option processing . . . 819

3 Class and Package interface **820**
3.1 Class name and version . . . 820
3.2 Package name and version . . . 820
3.3 Requiring other packages . . . 820
3.4 Declaring new options . . . 821
3.5 Safe Input Macros . . . 822

4 Implementation **822**
4.1 Hooks . . . 849
4.2 Providing shipment . . . 851

5 Package/class rollback mechanism **859**

6 After Preamble 867

V ltkeys.dtx 868

1 Creating and using keyval options 868
1.1 Implementation of ltkeys . . . 869
1.2 Key properties . . . 869
1.3 Main mechanism . . . 869
1.4 The document interfaces . . . 872
1.5 Option usage scope . . . 873
1.6 General key setting . . . 874

W ltfilehook.dtx 875

1 Introduction 875
1.1 Provided hooks . . . 875
1.2 General hooks for file reading . . . 875
1.3 Hooks for package and class files . . . 876
1.4 Hooks for \include files . . . 877
1.5 High-level interfaces for LaTeX . . . 878
1.6 Internal interfaces for LaTeX . . . 879
1.7 A sample package for structuring the log output . . . 879

2 The Implementation 880
2.1 Document and package-level commands . . . 880
2.2 expl3 helpers . . . 881
2.3 Declaring the file-related hooks . . . 884
2.4 Patching LaTeX's \InputIfFileExists command . . . 884
2.5 Declaring a file substitution . . . 886
2.6 Selecting a file (\set@curr@file) . . . 888
2.7 Replacing a file and detecting loops . . . 891
2.7.1 The Tortoise and Hare algorithm . . . 892
2.8 Preventing a package from loading . . . 894
2.9 High-level interfaces for LaTeX . . . 894
2.10 Internal commands needed elsewhere . . . 895

3 A sample package for structuring the log output 896

4 Package emulations 897
4.1 Package atveryend emulation . . . 897

X ltshipout.dtx 898

1 Introduction **898**
1.1 Overloading the \shipout primitive . . . 898
1.2 Provided hooks . . . 899
1.3 Legacy LaTeX commands . . . 901
1.4 Special commands for use inside the hooks . . . 901
1.5 Provided LuaTeX callbacks . . . 902
1.6 Information counters . . . 902
1.7 Debugging shipout code . . . 903

2 Emulating commands from other packages **903**
2.1 Emulating atbegshi . . . 903
2.2 Emulating everyshi . . . 904
2.3 Emulating atenddvi . . . 904
2.4 Emulating everypage . . . 905

3 The Implementation **905**
3.1 Debugging . . . 905
3.2 Handling the end of job hook . . . 918

4 Legacy LaTeX 2_ε interfaces **921**

5 Internal commands needed elsewhere **921**

6 Package emulation for compatibility **923**
6.1 Package atenddvi emulation . . . 923
6.2 Package atbegshi emulation . . . 923
6.3 Package everyshi emulation . . . 925

Y ltoutput.dtx **926**

1 Output Routine **926**
1.1 Floats . . . 926
1.1.1 Kludgeins . . . 982
1.1.2 Float control . . . 984
1.1.3 Float placement parameters . . . 997

Z lthyphen.dtx **1001**

aa ltfinal.dtx **1003**

1 Final settings **1003**
1.1 Debugging . . . 1003
1.2 Typesetting parameters . . . 1003
1.3 Lccodes for hyphenation . . . 1007
1.4 Hyphenation . . . 1009
1.5 Font loading . . . 1010
1.6 Input encoding . . . 1011
1.7 Lccodes and uccodes . . . 1016
1.8 Applying Patch files . . . 1018
1.9 Freeing Memory . . . 1018
1.10 Initialise file list . . . 1019
1.11 Preparation for supporting PDF in backends . . . 1019
1.12 Do some temporary work for pre-release . . . 1020
1.13 Some last minute initializations 1020
1.14 Dumping the format . . . 1020

Change History **1021**

Index **1091**

File a
ltdirchk.dtx

1 LaTeX System Dependent Initializations

This file implements the semi-automatic determination of various system dependent parts of the initialization. The actual definitions may be placed in a file `texsys.cfg`. Thus for operating systems for which the tests here do not result in acceptable settings, a 'hand written' `texsys.cfg` may be produced.

The macros that must be defined are:

`\@currdir` `\@currdir`⟨*filename*⟩⟨*space*⟩ should expand to a form of the filename that uniquely refers to the 'current directory' if this is possible. (The expansion should also end with a space.) on UNIX, this is `\def\@currdir{./}`. For more exotic operating systems you may want to make `\@currdir` a macro with arguments delimited by `.` and/or ⟨*space*⟩. If the operating system has no concept of directory structure, this macro should be defined to be empty.

`\input@path` If the primitive `\openin` searches the same directories as the primitive `\input`, then it is possible to tell (using `\ifeof`) whether a file exists before trying to input it. For systems like this, `\input@path` should be left undefined.

If `\openin` does not 'follow' `\input` then `\input@path` must be defined to be a list of directories to search for input files. The format for each directory is as for `\@currdir`, normally just a prefix is required, but it may be a macro with space-delimited argument. That is, if ⟨*dir*⟩ is an entry in the input path, TeX will try to load the expansion of ⟨*dir*⟩⟨*filename*⟩⟨*space*⟩

So either ⟨*dir*⟩ should be defined as a macro with argument delimited by space, or it should just expand to a directory name, including the final directory separator, so that it may be concatenated with the ⟨*filename*⟩. This means that for UNIX-like syntax, each ⟨*dir*⟩ should end with a slash, `/`.

`\input@path` should expand to a list of such directories, each in a `{}` group.

`\filename@parse` After a call of the form: `\filename@parse{`⟨*filename*⟩`}`, the three macros `\filename@area`, `\filename@base` and `\filename@ext` should be defined to be the 'area' (or directory), basename and extension respectively. If there was no extension specified in ⟨*filename*⟩, `\filename@ext` should be `\let` to `\relax` (so this case may be tested with `\@ifundefined{filename@ext}` and, perhaps a default extension substituted).

Normally one would not need to define this macro in `texsys.cfg` as the automatic tests can supply parsers that work with UNIX and VMS and Macintosh syntax, as well as a basic parser that will cover many other cases. However some operating systems may need a 'hand produced' parser in which case it should be defined in this file.

The UNIX parser also works for most MSDOS TeX versions. Currently if the UNIX, VMS or Macintosh parser is not used, `\filename@parse` is defined to always return an empty area, and to split the argument into basename and extension at the first '`.`' that occurs in the name. Parsers for other formats may be defined in `texsys.cfg`, in which case they will be used in preference to the default definitions.

`\@TeXversion` `\@TeXversion` is now set automatically by the initialization tests in this file. You should not need to set it in `texsys.cfg`, however the following documentation is left for information. LaTeX does not set this variable exactly, the automatic tests set it to:

`2` for any version, v, $v < 3.0$

`3` for any version, v, $3.0 \leq v \leq 3.14$

⟨*undefined*⟩ otherwise.
However these values are accurate enough for LaTeX to take appropriate action for these old TeXs.

If your TeX is older than version 3.141, then you should define `\@TeXversion` (using `\def`) to be the version number. If you do not do this[1] , LaTeX will not work around a bug in old TeX versions, and so error messages will appear in a very strange format, with `^^J` appearing instead of line breaks:

```
 LaTeX Error: \rubbish undefined.^^J^^JSee the LaTeX manual or LaTeX=
Companion
for explanation.^^JType  H <return>  for immediate help.
...

.3 \renewcommand{\rubbish}
                          {}
```

However if you put `\def\@TeXversion{3.14}` in `texsys.cfg` the following format will be used:

```
 LaTeX Error: \rubbish undefined.

ee the LaTeX manual or LaTeX Companion for explanation.
ype  H <return>  for immediate help.
 .
...

.3 \renewcommand{\rubbish}
                          {}
```

Note that this has an extra line `! .` which does not appear in error messages that use the default settings with a current version of TeX, but this should not cause any confusion we hope.

2 Initialization

As this file is read at a very early stage, some definitions that are normally considered to be part of the format must be made here.

Most such definitions are repeated later in the "right" place, usually (but not always) with different implementations. To be able to spot this more easily if you look into the file `latex.ltx` (which is stripped of comments) we add some comment lines to that effect that survive the stripping process by `docstrip`.

```
⟨*dircheck⟩
%% ---- START temporary definitions for bootstrapping; later overwritten ----
⟨/dircheck⟩
```

[1] Actually if your TeX is really old, version 2, LaTeX can detect this, and sets `\@TeXversion` to 2 if it is not set in the `cfg` file.

2.1 INITEX

```
⟨*dircheck⟩
⟨*initex⟩
⟨initex⟩\ifnum\catcode`\{=1
⟨initex⟩  \errmessage
⟨initex⟩  {LaTeX must be made using an initex with no format preloaded}
⟨initex⟩\fi
\catcode`\{=1
\catcode`\}=2
```

If LuaTEX is in use the extensions and other new primitives have to be activated: this is done as early as possible. Older versions of LuaTEX do not hide the primitives: a version check is not needed as the version itself will be missing in the case where action is needed!

```
\ifx\directlua\undefined
\else
  \ifx\luatexversion\undefined
```

Enable e-TeX/pdfTeX/Umath primitives with their natural names

```
    \directlua{tex.enableprimitives("",%
                tex.extraprimitives('etex', 'pdftex', 'umath'))}
```

In current formats enable primitives with unprefixed names. the latexrelease guards allow the primitives to be defined with a `\luatex` prefix if older formats are specified.

```
⟨/initex⟩
⟨/dircheck⟩
⟨*initex, latexrelease⟩
⟨latexrelease⟩\ifx\directlua\undefined\else
⟨latexrelease⟩\IncludeInRelease{2015/10/01}{\luatexluafunction}
⟨latexrelease⟩                              {LuaTeX (prefixed names)}%
    \directlua{tex.enableprimitives("",%
                tex.extraprimitives("omega", "aleph", "luatex"))}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\luatexluafunction}
⟨latexrelease⟩                              {LuaTeX (prefixed names)}%
⟨latexrelease⟩\directlua{
⟨latexrelease⟩  tex.enableprimitives(
⟨latexrelease⟩    "luatex",
⟨latexrelease⟩    tex.extraprimitives("core","omega", "aleph", "luatex")
⟨latexrelease⟩  )
⟨latexrelease⟩  local i
⟨latexrelease⟩  local t = { }
⟨latexrelease⟩  for _,i in pairs(tex.extraprimitives("luatex")) do
⟨latexrelease⟩    if not string.match(i,"^U") then
⟨latexrelease⟩      if not string.match(i, "^luatex") then
⟨latexrelease⟩        table.insert(t,i)
⟨latexrelease⟩      end
⟨latexrelease⟩    else
⟨latexrelease⟩      if string.match(i,"^Uchar$") then
⟨latexrelease⟩        table.insert(t,i)
⟨latexrelease⟩      end
⟨latexrelease⟩    end
⟨latexrelease⟩  end
⟨latexrelease⟩  for _,i in pairs(t) do
⟨latexrelease⟩    tex.print(
⟨latexrelease⟩      "\noexpand\\let\noexpand\\" .. i
```

```
⟨latexrelease⟩          .. "\noexpand\\undefined"
⟨latexrelease⟩     )
⟨latexrelease⟩   end
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\fi
⟨/initex, latexrelease⟩
⟨*dircheck⟩
⟨*initex⟩
  \fi
\fi
```

A test can now be made for eTEX.

```
⟨initex⟩\ifx\eTeXversion\undefined
⟨initex⟩   \errmessage
⟨initex⟩     {LaTeX requires e-TeX}
⟨initex⟩   \expandafter\endinput
⟨initex⟩\fi
```

That distraction over, back to the basics of a format.

```
\catcode`\#=6
\catcode`\^=7
\chardef\active=13
\catcode`\@=11
\countdef\count@=255
\let\bgroup={ \let\egroup=}
\ifx\@@input\@undefined\let\@@input\input\fi
\ifx\@@end\@undefined\let\@@end\end\fi
\chardef\@inputcheck0
\chardef\sixt@@n=16
\newlinechar`\^^J
\def\typeout{\immediate\write17}
\def\dospecials{\do\ \do\\\do\{\do\}\do\$\do\&%
  \do\#\do\^\do\_\do\%\do\~}
\def\@makeother#1{\catcode`#1=12\relax}
\def\space{ }
\def\@tempswafalse{\let\if@tempswa\iffalse}
\def\@tempswatrue{\let\if@tempswa\iftrue}
\let\if@tempswa\iffalse
\def\loop#1\repeat{\def\iterate{#1\relax\expandafter\iterate\fi}%
  \iterate \let\iterate\relax}
\let\repeat\fi
⟨/initex⟩
```

2.2 Some bits of 2e

```
⟨*2ekernel⟩
\def\two@digits#1{\ifnum#1<10 0\fi\number#1}
\long\def\@firstoftwo#1#2{#1}
\long\def\@secondoftwo#1#2{#2}
```

This is a special version of `\ProvidesFile` for initex use.

```
\def\ProvidesFile#1{%
  \begingroup
    \catcode`\ 10 %
    \ifnum \endlinechar<256 %
```

```
      \ifnum \endlinechar>\m@ne
        \catcode\endlinechar 10 %
      \fi
    \fi
    \@makeother\/%
    \@ifnextchar[{\@providesfile{#1}}{\@providesfile{#1}[]}}
\def\@providesfile#1[#2]{%
    \wlog{File: #1 #2}%
    \@addtofilelist{ #2}%
    \endgroup}
\long\def\@addtofilelist#1{}
\def\@empty{}
\catcode`\%=12
\def\@percentchar{%}
\catcode`\%=14
\let\@currdir\@undefined
\let\input@path\@undefined
\let\filename@parse\@undefined
```

`\strip@prefix`

```
\def\strip@prefix#1>{}
⟨/2ekernel⟩
```

(*End definition for* `\strip@prefix`.)

3 texsys.cfg

As mentioned above, any site specific definitions required to describe the filename handling must be entered into a file `texsys.cfg`. If `texsys.cfg` can not be located by `\openin`, we write a default version out. The default version only contains comments, so we do not actually input the file in that case. The automatic tests later will, hopefully, correctly define the required macros.

The tricky code below checks to see if `texsys.cfg` exists. If it does not, all the text in this file between START and END is copied verbatim to a new file `texsys,cfg`. If `texsys.cfg` is found, then it is simply input. This is only done when this file is being used unstripped.

```
⟨*docstrip⟩
\openin15=texsys.cfg
\ifeof15
\typeout{** Writing a default texsys.cfg}
\immediate\openout15=texsys.cfg
\begingroup
\catcode`\^^M\active%
\let^^M\par%
\def\reserved@a#1^^M{%
 \def\reserved@b{#1}%
 \ifx\reserved@b\reserved@c\endgroup\else%
     \immediate\write15{#1}%
     \expandafter\reserved@a\fi}%
\def\reserved@d#1START^^M{\let\do\@makeother\dospecials\reserved@a}%
\catcode`\%=12
\def\reserved@c{%END}
\reserved@d
```

START

3.1 texsys.cfg

This file contains the site specific definitions of the four macros `\@currdir`, `\input@path`, `\filename@parse` and `\@TeXversion`.

As distributed it only contains comments, however this 'empty' file will work on many systems because of the automatic tests built into `ltdirchk.dtx`. You *are* allowed to edit this file to add definitions of these macros appropriate to your system.

The macros that must be defined are:

`\@currdir` `\@currdir`⟨*filename*⟩⟨*space*⟩ should expand to a form of the filename that uniquely refers to the 'current directory' if this is possible. (The expansion should also end with a space.) on UNIX, this is `\def\@currdir{./}`. For more exotic operating systems you may want to make `\@currdir` a macro with arguments delimited by `.` and/or ⟨*space*⟩. If the operating system has no concept of directory structure, this macro should be defined to be empty.

`\input@path` If the primitive `\openin` searches the same directories as the primitive `\input`, then it is possible to tell (using `\ifeof`) whether a file exists before trying to input it. For systems like this, `\input@path` should be left undefined.

If `\openin` does not 'follow' `\input` then `\input@path` must be defined to be a list of directories to search for input files. The format for each directory is as for `\@currdir`, normally just a prefix is required, but it may be a macro with space-delimited argument. That is, if ⟨*dir*⟩ is an entry in the input path, TEXwill try to load the expansion of

⟨*dir*⟩⟨*filename*⟩⟨*space*⟩

So either ⟨*dir*⟩ should be defined as a macro with argument delimited by space, or it should just expand to a directory name, including the final directory separator, so that it may be concatenated with the ⟨*filename*⟩. This means that for UNIX-like syntax, each ⟨*dir*⟩ should end with a slash, `/`. One exception to this rule is that the input path should *always* contain the empty directory `{}` as this will allow 'full pathnames' to be used, and the 'current directory' to be searched.

`\input@path` should expand to a list of such directories, each in a `{}` group.

`\filename@parse` After a call of the form: `\filename@parse{`⟨*filename*⟩`}`, the three macros `\filename@area`, `\filename@base`, `\filename@ext` should be defined to be the 'area' (or directory), basename and extension respectively. If there was no extension specified in ⟨*filename*⟩, `\filename@ext` should be `\let` to `\relax` (so this case may be tested with `\@ifundefined{filename@ext}` and, perhaps a default extension substituted).

Normally one would not need to define this macro in `texsys.cfg` as the automatic tests can supply parsers that work with UNIX and VMS syntax, as well as a basic parser that will cover many other cases. However some operating systems may need a 'hand produced' parser in which case it should be defined in this file.

The UNIX parser also works for most MSDOS TEX versions. Currently if the UNIX or VMS parser is not used, `\filename@parse` is defined to always return an empty area, and to split the argument into basename and extension at the first '`.`' that occurs in the name. Parsers for other formats may be defined in `texsys.cfg`, in which case they will be used in preference to the default definitions.

`\@TeXversion` You should not need to set this macro in `texsys.cfg`. LATEX tests to set this automatically. See the comments in the opening section of `ltdirchk.dtx`.

The following sections give examples of definitions which might work on various systems. These are currently mainly untested as I only have access to a few systems, all

of which do not need this file as the automatic tests work. All the code is commented out.

3.2 UNIX (web2c)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
%\def\@currdir{./}
%\let\input@path\@undefined
```

3.3 UNIX (other)

Apparently some commercial UNIX implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever directories are used at your site): note that the directory names should end with `/`.

```
% \def\@currdir{./}
% \def\input@path{%
%   {/usr/local/lib/tex/inputs/distrib/}%
%   {/usr/local/lib/tex/inputs/contrib/}%
%   {/usr/local/lib/tex/inputs/local/}%
% }
```

3.4 MSDOS (emtex)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
% \def\@currdir{./}
% \let\input@path\@undefined
```

3.5 MSDOS (other)

Some PC implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever directories are used at your site): note that the directory names should end with `/`. This assumes the implementation uses UNIX style `/` as the directory separator.

```
% \def\@currdir{./}
% \def\input@path{%
%   {c:/tex/inputs/distrib/}%
%   {c:/tex/inputs/contrib/}%
%   {c:/tex/inputs/local/}%
% }
```

3.6 VMS (DECUS TEX, PD VMS 3.6)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
% \def\@currdir{[]}
% \let\input@path\@undefined
```

3.7 VMS (???)

Some VMS implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following:

```
% \def\@currdir{[]}
% \def\input@path{%
%   {tex_inputs:}%
%   {SOMEDISK:[SOME.TEX.DIRECTORY]}%
% }
```

3.8 MACINTOSH (OzTeX 1.6)

This implementation does make `\openin` and `\input` look in the same places. Acceptable settings are made by `ltdirchk.dtx`, and so this file may be empty. The definitions below are therefore just for information.

```
% \def\@currdir{:}
% \let\input@path\@undefined
```

3.9 MACINTOSH (other)

Some Macintosh implementations have different paths for `\openin` and `\input`. For these one could use definitions like the following (with whatever folders are used on your machine): note that the directory names should end with `:`, and they should contain *no* spaces.

```
% \def\@currdir{:}
% \def\input@path{%
%   {Hard-Disk:Applications:TeX:TeX-inputs:}%
%   {Hard-Disk:Applications:TeX:My-inputs:}%
% }
```

3.10 FAKE EXAMPLE

This example is for an operating system that has filenames of the form `<area>name` For maximum compatibility with macro sets, you want `name.ext` to be mapped to `<ext>name`. and `<area>name.ext` to be mapped to `<area.ext>name`. `\input` does this mapping automatically, but `\openin` does not, and does not look in the same places as `\input`. `<>name` is the desired 'current directory' syntax.

the following code would possibly work:

```
% \def\@dir#1#2 {%
%   \@d@r{#1}#2..\@nil}
% \def\@d@r#1#2.#3.#4\@nil{%
%   <\ifx\@dir#1\@dir\else#1\ifx\@dir#3\@dir\else.\fi\fi#3>#2 }
%
% \def\@currdir{\@dir{}}
% \def\input@path{%
%   {\@dir{area.one}}%
%   {\@dir{area.two}}%
% }
```

END

```
\immediate\closeout15
```

If texsys.cfg did exist, then input it.

```
\else
\typeout{** Using the existing texsys.cfg}
\closein15
\input texsys.cfg
\fi
⟨/docstrip⟩
```

If the stripped version of this file is being used (in latex2e.ltx) then texsys.cfg should be there, so just input it.

```
⟨dircheck⟩\input texsys.cfg
```

4 Setting \@currdir

\@currdir
\IfFileExists

This is a local definition of \IfFileExists. It tries to relocate texsxys.aux. If it succeeds, then the \@currdir syntax has been determined. If all the tests fail then \@currdir will be set to \@empty, and ltxcheck will warn of this when it checks the format.

```
\begingroup
\count@\time
\divide\count@ 60
\count2=-\count@
\multiply\count2 60
\advance\count2 \time
```

The current date and time stamp.

\today

```
\edef\today{%
  \the\year/\two@digits{\the\month}/\two@digits{\the\day}:%
    \two@digits{\the\count@}:\two@digits{\the\count2}}
```

Create a file texsys.aux (hopefully in the current directory), then try to locate it again.

```
\immediate\openout15=texsys.aux
\immediate\write15{\today^^J}
\immediate\closeout15 %
```

#1 is the file to try, #2 is what to do on success, #3 on failure. Note that this definition is overwritten later on again!

```
\def\IfFileExists#1#2#3{%
  \openin\@inputcheck#1 %
  \ifeof\@inputcheck
     #3\relax
  \else
    \read\@inputcheck to \reserved@a
    \ifx\reserved@a\today
      \typeout{#1 found}#2\relax
    \else
      \typeout{BAD: old file \reserved@a (should be \today)}%
      #3\relax
    \fi
  \fi
  \closein\@inputcheck}
```

```
\endlinechar=-1
```

If `\@currdir` has not been pre-defined in `texsys.cfg` then test for UNIX, VMS and Oz-TEX-Mac. syntax.

```
\ifx\@currdir\@undefined
  \IfFileExists{./texsys.aux}{\gdef\@currdir{./}}%
    {\IfFileExists{[]texsys.aux}{\gdef\@currdir{[]}}%
      {\IfFileExists{:texsys.aux}{\gdef\@currdir{:}}{}}}
```

If it is still undefined at this point, all the above tests failed. Earlier versions interactively prompted for a definition at this point, but it seems impossible to reliably obtain information from users at this point in the installation. This version of the file produces a format with no user-interaction. Later if the format is not suitable for the system, `texsys.cfg` may be edited and the format re-made.

```
  \ifx\@currdir\@undefined
    \global\let\@currdir\@empty
    \typeout{^^J^^J%
      !! No syntax for the current directory could be found^^J%
      }%
  \fi
```

Otherwise `\@currdir` was defined in `texsys.cfg`. In this case check that the syntax specified works on this system. (In case a complete LATEX system has been copied from one system to another.) If the test fails, give up. The installer should remove or correct the offending `texsys.cfg` and try again.

```
\else
  \IfFileExists{\@currdir texsys.aux}{}{%
    \edef\reserved@a{\errhelp{%
      texsys.cfg specifies the current directory syntax to be^^J%
      \meaning\@currdir^^J%
      but this does not work on this system.^^J%
      Remove texsys.cfg and restart.}}\reserved@a
    \errmessage{Bad texsys.cfg file: \noexpand\@currdir}\@@end}
```

The version of `\@currdir` in `texsys.cfg` looks OK.

```
\fi
```

```
\immediate\closeout15 %
\endgroup
```

```
\typeout{^^J^^J%
         \noexpand\@currdir set to:
           \expandafter\strip@prefix\meaning\@currdir.^^J%
         }
```

(*End definition for* `\@currdir`, `\IfFileExists`, *and* `\today`.)

Stop here if the file is being used unstripped.

```
⟨*docstrip⟩
\relax\endinput
⟨/docstrip⟩
```

5 Setting \input@path

Earlier versions of this file attempted to automatically test whether \input@path was required, and interactively prompt for a path if necessary. This was not found to be very reliable The first-time installer of LaTeX 2_ε can not be expected to have enough information to supply the correct information to the prompts. Now the interaction is omitted. After the format is made the installer can attempt to run the test document ltxcheck.tex through LaTeX 2_ε. This will check, among other things, whether texsys.cfg will need to be edited and the format remade.

\input@path Now set up the \input@path.

\input@path should either be undefined, or a list of directories as described in the introduction.

```
\typeout{^^J%
  Assuming \noexpand\openin and \noexpand\input^^J%
  \ifx\input@path\@undefined
```

\input@path has not been pre-defined.

```
    have the same search path.^^J%
  \else
```

\input@path has been defined in texsys.cfg.

```
    have different  search paths.^^J%
    LaTeX will use the path specified by \noexpand\input@path:^^J%
  \fi
  }
```

(*End definition for* \input@path.)

6 Filename Parsing

\filename@parse Split a filename into its components.

```
\ifx\filename@parse\@undefined
  \def\reserved@a{./}\ifx\@currdir\reserved@a
```

\filename@parse was not specified in texsys.cfg, but \@currdir looks like UNIX...

```
  \typeout{^^JDefining UNIX/DOS style filename parser.^^J}
  \def\filename@parse#1{%
    \let\filename@area\@empty
    \expandafter\filename@path#1/\\}
```

Search for the last /.

```
  \def\filename@path#1/#2\\{%
    \ifx\\#2\\%
       \def\reserved@a{\filename@simple#1.\\}%
    \else
       \edef\filename@area{\filename@area#1/}%
       \def\reserved@a{\filename@path#2\\}%
    \fi
    \reserved@a}
\else\def\reserved@a{[]}\ifx\@currdir\reserved@a
```

`\filename@parse` was not specified in `texsys.cfg`, but `\@currdir` looks like VMS...

```
    \typeout{^^JDefining VMS style filename parser.^^J}
    \def\filename@parse#1{%
      \let\filename@area\@empty
      \expandafter\filename@path#1]\\}
```

Search for the last `]`.

```
    \def\filename@path#1]#2\\{%
      \ifx\\#2\\%
         \def\reserved@a{\filename@simple#1.\\}%
      \else
         \edef\filename@area{\filename@area#1]}%
         \def\reserved@a{\filename@path#2\\}%
      \fi
      \reserved@a}
  \else\def\reserved@a{:}\ifx\@currdir\reserved@a
```

`\filename@parse` was not specified in `texsys.cfg`, but `\@currdir` looks like Macintosh...

```
    \typeout{^^JDefining Mac style filename parser.^^J}
    \def\filename@parse#1{%
      \let\filename@area\@empty
      \expandafter\filename@path#1:\\}
```

Search for the last `:`.

```
    \def\filename@path#1:#2\\{%
      \ifx\\#2\\%
         \def\reserved@a{\filename@simple#1.\\}%
      \else
         \edef\filename@area{\filename@area#1:}%
         \def\reserved@a{\filename@path#2\\}%
      \fi
      \reserved@a}
  \else
```

`\filename@parse` was not specified in `texsys.cfg`. So just make a simple parser that always sets `\filename@area` to empty.

```
    \typeout{^^JDefining generic filename parser.^^J}
    \def\filename@parse#1{%
      \let\filename@area\@empty
      \expandafter\filename@simple#1.\\}
  \fi\fi\fi
```

`\filename@simple` is used by all three versions. Finally we can split off the extension.

```
⟨/dircheck⟩
⟨*dircheck, latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}{\filename@simple}
⟨latexrelease⟩                                {Final dot for extension}%
\def\filename@simple#1.#2\\{%
  \ifx\\#2\\%
    \let\filename@ext\relax
    \edef\filename@base{#1}%
  \else
```

```
    \filename@dots{#1}#2\\%
  \fi}
\def\filename@dots#1#2.#3\\{%
  \ifx\\#3\\%
    \def\filename@ext{#2}%
    \edef\filename@base{#1}%
  \else
    \filename@dots{#1.#2}#3\\%
  \fi}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\filename@simple}
⟨latexrelease⟩                              {Final dot for extension}%
⟨latexrelease⟩  \def\filename@simple#1.#2\\{%
⟨latexrelease⟩    \ifx\\#2\\%
⟨latexrelease⟩       \let\filename@ext\relax
⟨latexrelease⟩    \else
⟨latexrelease⟩       \edef\filename@ext{\filename@dot#2\\}%
⟨latexrelease⟩    \fi
⟨latexrelease⟩    \edef\filename@base{#1}}
⟨latexrelease⟩\EndIncludeInRelease
⟨/dircheck, latexrelease⟩
⟨*dircheck⟩
```

Remove a final dot, added earlier.

```
  \def\filename@dot#1.\\{#1}
\else
```

Otherwise, `\filename@parse` was specified in `texsys.cfg`.

```
  \typeout{^^J^^J%
    \noexpand\filename@parse was defined in texsys.cfg:^^J%
    \expandafter\strip@prefix\meaning\filename@parse.^^J%
    }
\fi
```

(*End definition for* `\filename@parse`.)

7 TEX Versions

`\@TeXversion` TEX versions older than 3.141 require `\@TeXversion` to be set. This can be determined automatically due to a trick suggested by Bernd Raichle. (Actually this will not always get the correct version number, eg TEX3.14 would be detected as TEX3, but LATEX only needs to take account of TEX's older than 3, or between 3 and 3.14.

```
\ifx\@TeXversion\@undefined
  \ifx\@undefined\inputlineno
    \def\@TeXversion{2}
  \else
   {\catcode`\^^J=\active
     \def\reserved@a#1#2\@@{\if#1\string^3\fi}
     \edef\reserved@a{\expandafter\reserved@a\string^^J\@@}
     \ifx\reserved@a\@empty\else\gdef\@TeXversion{3}\fi}
  \fi
\fi
```

(*End definition for* `\@TeXversion`.)

```
%% ---- END temporary definitions for bootstrapping ----
⟨/dircheck⟩
```

8 ltxcheck.tex

After the format has been made, and article.cls moved with the other files to the 'standard input directory' as specified in `install.txt`, the format may be checked by running the file `ltxcheck.tex`.

File b
ltplain.dtx

1 Plain TEX

LATEX includes almost all of the functionality of Knuth's original 'Basic Macros' That is, the plain TEX format described in Appendix B of the TEXBook. However, some of the user commands are not much use so, in order to save memory, we may remove them from the kernel into a package. Here is a list of the commands that may be removed (PROBABLY NOT COMPLETE).

```
\magstep     \magstephalf
\mathhexbox
\vglue       \vgl@
\hglue       \hgl@
```

This file is by now very small as most of it has been moved to more appropriate kernel files: it may disappear completely one day.

LATEX font definitions are done using NFSS2 so none of PLAIN's font definitions are in LATEX.

LATEX has its own tabbing environment, so PLAIN's is disabled.

LATEX uses its own output routine, so most of the plain one was removed.

```
⟨*2ekernel⟩
\catcode`\{=1 % left brace is begin-group character
\catcode`\}=2 % right brace is end-group character
\catcode`\$=3 % dollar sign is math shift
\catcode`\&=4 % ampersand is alignment tab
\catcode`\#=6 % hash mark is macro parameter character
\catcode`\^=7 % circumflex and uparrow are for superscripts
\catcode`\_=8 % underline and downarrow are for subscripts
\catcode`\^^I=10 % ascii tab is a blank space
\chardef\active=13 \catcode`\~=\active % tilde is active
\catcode`\^^L=\active \def^^L{\par}% ascii form-feed is \par
\message{catcodes,}
```

We had to define the `\catcodes` right away, before the message line, since `\message` uses the `{` and `}` characters. When INITEX (the TEX initializer) starts up, it has defined the following `\catcode` values:

`\catcode`\^^@=9 %` ascii null is ignored
`\catcode`\^^M=5 %` ascii return is end-line
`\catcode`\\=0 %` backslash is TeX escape character
`\catcode`\%=14 %` percent sign is comment character
`\catcode`\ =10 %` ascii space is blank space
`\catcode`\^^?=15 %` ascii delete is invalid
`\catcode`\A=11 ... \catcode`\Z=11 %` uppercase letters
`\catcode`\a=11 ... \catcode`\z=11 %` lowercase letters
all others are type 12 (other)

Here is a list of the characters that have been specially catcoded:

```
\def\dospecials{\do\ \do\\\do\{\do\}\do\$\do\&%
  \do\#\do\^\do\_\do\%\do\~}
```

(not counting ascii null, tab, linefeed, formfeed, return, delete) Each symbol in the list is preceded by , which can be defined if you want to do something to every item in the list.

We make `@` signs act like letters, temporarily, to avoid conflict between user names and internal control sequences of plain format.

```
\catcode`@=11
```

To make the plain macros more efficient in time and space, several constant values are declared here as control sequences. If they were changed, anything could happen; so they are private symbols.

`\@ne` `\tw@` `\thr@@` `\sixt@@n` `\@cclv`

Small constants are defined using `\chardef`.

```
\chardef\@ne=1
\chardef\tw@=2
\chardef\thr@@=3
\chardef\sixt@@n=16
\chardef\@cclv=255
```

(*End definition for* `\@ne` *and others.*)

`\@cclvi` `\@m` `\@M` `\@MM`

Constants above 255 defined using `\mathchardef`.

```
\mathchardef\@cclvi=256
\mathchardef\@m=1000
\mathchardef\@M=10000
\mathchardef\@MM=20000
```

(*End definition for* `\@cclvi` *and others.*)

Allocation of registers

Here are macros for the automatic allocation of `\count`, `\box`, `\dimen`, `\skip`, `\muskip`, and `\toks` registers, as well as `\read` and `\write` stream numbers, `\fam` codes, `\language` codes, and `\insert` numbers.

```
\message{registers,}
```

When a register is used only temporarily, it need not be allocated; grouping can be used, making the value previously in the register return after the close of the group. The main use of these macros is for registers that are defined by one macro and used by others, possibly at different nesting levels. All such registers should be defined through these macros; otherwise conflicts may occur, especially when two or more macro packages are being used at the same time.

Historical LaTeX 2.09 comments (not necessarily accurate any more):

The following counters are reserved:

0 to 9	page numbering
10	count allocation
11	dimen allocation
12	skip allocation
13	muskip allocation
14	box allocation
15	toks allocation
16	read file allocation
17	write file allocation
18	math family allocation
19	language allocation
20	insert allocation
21	the most recently allocated number

22 constant -1

End of historical LaTeX 2.09 comments.

New counters are allocated starting with 23, 24, etc. Other registers are allocated starting with 10. This leaves 0 through 9 for the user to play with safely, except that counts 0 to 9 are considered to be the page and subpage numbers (since they are displayed during output). In this scheme, `\count` 10 always contains the number of the highest-numbered counter that has been allocated, `\count` 14 the highest-numbered box, etc. Inserts are given numbers 254, 253, etc., since they require a `\count`, `\dimen`, `\skip`, and `\box` all with the same number; `\count` 20 contains the lowest-numbered insert that has been allocated. Of course, `\box`255 is reserved for `\output`; `\count`255, `\dimen`255, and `\skip`255 can be used freely.

It is recommended that macro designers always use `\global` assignments with respect to registers numbered
1, 3, 5, 7, 9,
and always non-`\global` assignments with respect to registers
0, 2, 4, 6, 8, 255.
This will prevent "save stack buildup" that might otherwise occur.

```
\count10=22 % allocates \count registers 23, 24, ...
\count11=9 % allocates \dimen registers 10, 11, ...
\count12=9 % allocates \skip registers 10, 11, ...
\count13=9 % allocates \muskip registers 10, 11, ...
\count14=9 % allocates \box registers 10, 11, ...
\count15=9 % allocates \toks registers 10, 11, ...
\count16=-1 % allocates input streams 0, 1, ...
\count17=-1 % allocates output streams 0, 1, ...
\count18=3 % allocates math families 4, 5, ...
\count19=0 % allocates \language codes 1, 2, ...
\count20=255 % allocates insertions 254, 253, ...
```

`\insc@unt` `\allocationnumber`

The insertion counter and most recent allocation.

```
\countdef\insc@unt=20
\countdef\allocationnumber=21
```

(*End definition for* `\insc@unt` *and* `\allocationnumber`.)

`\m@ne`

The constant −1.

```
\countdef\m@ne=22 \m@ne=-1
```

(*End definition for* `\m@ne`.)

`\wlog`

Write on log file (only)

```
\def\wlog{\immediate\write\m@ne}
```

(*End definition for* `\wlog`.)

`\count@` `\dimen@` `\dimen@i` `\dimen@ii` `\skip@` `\toks@`

Here are abbreviations for the names of scratch registers that don't need to be allocated.

```
\countdef\count@=255
\dimendef\dimen@=0
\dimendef\dimen@i=1 % global only
\dimendef\dimen@ii=2
\skipdef\skip@=0
\toksdef\toks@=0
```

(*End definition for* `\count@` *and others.*)

`\newcount` `\newdimen` `\newskip` `\newmuskip` `\newbox` `\newtoks` `\newread` `\newwrite` `\newfam` `\newlanguage`

Now, we define `\newcount`, `\newbox`, etc. so that you can say `\newcount\foo` and `\foo` will be defined (with `\countdef`) to be the next counter.

To find out which counter `\foo` is, you can look at `\allocationnumber`.

Since there's no `\boxdef` command, `\chardef` is used to define a `\newbox`, `\newinsert`, `\newfam`, and so on.

LaTeX change: remove `\outer` from `\newcount` and `\newdimen` (FMi) This is necessary to use `\newcount` inside `\if...` later on. Also remove from `\newskip`, `\newbox` `\newwrite` and `\newfam` (DPC) to save later redefinition.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\newcount}{Extended Allocation}%
```

```
\def\newcount {\e@alloc\count \countdef {\count10}\insc@unt\float@count}
\def\newdimen {\e@alloc\dimen \dimendef {\count11}\insc@unt\float@count}
\def\newskip  {\e@alloc\skip  \skipdef  {\count12}\insc@unt\float@count}
\def\newmuskip
           {\e@alloc\muskip\muskipdef{\count13}\m@ne\e@alloc@top}
```

For compatibility use `\chardef` in the classical range.

```
\def\newbox   {\e@alloc\box
                  {\ifnum\allocationnumber<\@cclvi
                     \expandafter\chardef
                   \else
                     \expandafter\e@alloc@chardef
                   \fi}
                                          {\count14}\insc@unt\float@count}
\def\newtoks  {\e@alloc\toks \toksdef{\count15}\m@ne\e@alloc@top}
\def\newread  {\e@alloc\read \chardef{\count16}\m@ne\sixt@@n}
```

Skip `\write18` due to its traditional use as a shell-escape.

```
\ifx\directlua\@undefined
  \def\newwrite   {\e@alloc\write \chardef{\count17}\m@ne\sixt@@n}
\else
  \def\newwrite   {\e@alloc\write
                   {\ifnum\allocationnumber=18
                     \advance\count17\@ne
                     \allocationnumber\count17 %
                    \fi
                    \global\chardef}%
                   {\count17}%
                   \m@ne
                   {128}}
\fi
```

```
\def\new@mathgroup
  {\e@alloc\mathgroup\chardef{\count18}\m@ne\e@mathgroup@top}
\let\newfam\new@mathgroup
```

```
\ifx\directlua\@undefined
  \def\newlanguage  {\e@alloc\language \chardef{\count19}\m@ne\@cclvi}
\else
  \def\newlanguage  {\e@alloc\language \chardef{\count19}\m@ne{16384}}
```

```
\fi
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\newcount}{Extended Allocation}%
⟨latexrelease⟩\def\newcount{\alloc@0\count\countdef\insc@unt}
⟨latexrelease⟩\def\newdimen{\alloc@1\dimen\dimendef\insc@unt}
⟨latexrelease⟩\def\newskip{\alloc@2\skip\skipdef\insc@unt}
⟨latexrelease⟩\def\newmuskip{\alloc@3\muskip\muskipdef\@cclvi}
⟨latexrelease⟩\def\newbox{\alloc@4\box\chardef\insc@unt}
⟨latexrelease⟩\def\newtoks{\alloc@5\toks\toksdef\@cclvi}
⟨latexrelease⟩\def\newread{\alloc@6\read\chardef\sixt@@n}
⟨latexrelease⟩\def\newwrite{\alloc@7\write\chardef\sixt@@n}
⟨latexrelease⟩\def\new@mathgroup{\alloc@8\fam\chardef\sixt@@n}
⟨latexrelease⟩\def\newlanguage{\alloc@9\language\chardef\@cclvi}
⟨latexrelease⟩\let\newfam\new@mathgroup
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\newcount` *and others.*)

`\e@alloc@chardef`
`\e@alloc@top`

The upper limit of extended registers, which leaves this number (eg `\dimen32767`) always unallocated by these macros. cf traditional `\dimen255`.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\e@alloc@chardef}{Extended Allocation}%
```

```
\ifx\directlua\@undefined
  \ifx\widowpenalties\@undefined
```

classic tex has 2^8 registers.

```
    \mathchardef\e@alloc@top=255
    \let\e@alloc@chardef\chardef
  \else
```

etex and xetex have 2^{15} registers.

```
    \mathchardef\e@alloc@top=32767
    \let\e@alloc@chardef\mathchardef
  \fi
\else
```

luatex has 2^{16} registers.

```
  \chardef\e@alloc@top=65535
  \let\e@alloc@chardef\chardef
\fi
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\e@alloc@chardef}{Extended Allocation}%
⟨latexrelease⟩\let\e@alloc@top\@undefined
⟨latexrelease⟩\let\e@alloc@chardef\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\e@alloc@chardef` *and* `\e@alloc@top`.)

`\e@mathgroup@top` The upper limit of extended math groups (`\fam`) 16 in classic TEX and e-TEX, but 256 in Unicode TeX variants.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\e@mathgroup@top}{Extended Allocation}%
```

```
\ifx\Umathcode\@undefined
```

classic and e tex have 16 fam (0–15).

```
  \chardef\e@mathgroup@top=16
\else
```

xetex and luatex have 256 fam (0–255).

```
  \chardef\e@mathgroup@top=256
\fi
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\e@mathgroup@top}{Extended Allocation}%
⟨latexrelease⟩\let\e@mathgroup@top\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\e@mathgroup@top`.)

`\e@alloc` A modified version of `\alloc@` that takes the count register rather than just the final digit of its number (assuming `\count`1x). It also has an extra argument to give the top of the extended range.

```
                #1  #2      #3     #4    #5          #6
  \e@alloc type defcmd current top extended-top newname
```

Note that if just a single allocation range is required (not omitting a range up to 255 for inserts) then −1 should be used for the first upper bound argument, `#4`.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\e@alloc}{Extended Allocation}%
```

```
\def\e@alloc#1#2#3#4#5#6{%
  \global\advance#3\@ne
  \e@ch@ck{#3}{#4}{#5}#1%
  \allocationnumber#3\relax
  \global#2#6\allocationnumber
  \wlog{\string#6=\string#1\the\allocationnumber}}%
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\e@alloc}{Extended Allocation}%
⟨latexrelease⟩\let\e@alloc\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\e@alloc`.)

`\e@ch@ck` Extended check command. If the first range is exceeded, bump to 256 (or 266 for counts) and try again, testing the extended range.

Allocate matching registers from the top of the extended range and add to `\@freelist`.

`\extrafloats`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/10/01}
⟨latexrelease⟩                  {\e@ch@ck}{Extended Allocation (checking)}%
\gdef\e@ch@ck#1#2#3#4{%
  \ifnum#1<#2\else
```

If we've reached the classical top limit, bump to 256 or 266 for counts (count 256–265 are reserved by the allocation system).

```
    \ifnum#1=#2\relax
      \global#1\@cclvi
      \ifx\count#4\global\advance#1 10 \fi
    \fi
```

Check we are below the extended limit.

```
    \ifnum#1<#3\relax
    \else
      \errmessage{No room for a new \string#4}%
    \fi
  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\e@ch@ck}{Extended Allocation (checking)}%
⟨latexrelease⟩\gdef\e@ch@ck#1#2#3#4{%
⟨latexrelease⟩  \ifnum#1<#2\else
⟨latexrelease⟩    \ifnum#1=#2\relax
⟨latexrelease⟩      #1\@cclvi
⟨latexrelease⟩      \ifx\count#4\advance#1 10 \fi
⟨latexrelease⟩    \fi
⟨latexrelease⟩    \ifnum#1<#3\relax
⟨latexrelease⟩    \else
⟨latexrelease⟩      \errmessage{No room for a new #4}%
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\e@ch@ck}{Extended Allocation (checking)}%
⟨latexrelease⟩\let\e@ch@ck\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\extrafloats}{Extra floats}%
\let\float@count\e@alloc@top
```

`\extrafloats`

```
\ifx\numexpr\@undefined
```

In classic TeX use `\newinsert` to allocate float boxes.

```
\def\extrafloats#1{%
\count@#1\relax
\ifnum\count@>\z@
\newinsert\reserved@a
\global\expandafter\chardef
```

```
            \csname bx@\the\allocationnumber\endcsname\allocationnumber
\@cons\@freelist{\csname bx@\the\allocationnumber\endcsname}%
\advance\count@\m@ne
\expandafter\extrafloats
\expandafter\count@
\fi
}%
\else
```

In e-tex take float boxes from the top of the extended range.

```
\def\extrafloats#1{%
\ifnum#1>\z@
\count@\numexpr\float@count-1\relax
  \ch@ck0\count@\count
  \ch@ck1\count@\dimen
  \ch@ck2\count@\skip
  \ch@ck4\count@\box
\global\e@alloc@chardef\float@count\count@
\global\expandafter\e@alloc@chardef
            \csname bx@\the\float@count\endcsname\float@count
\@cons\@freelist{\csname bx@\the\float@count\endcsname}%
\expandafter
\extrafloats\expandafter{\numexpr#1-1\relax}%
\fi}%
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\extrafloats}{Extra floats}%
⟨latexrelease⟩\let\float@count\@undefined
⟨latexrelease⟩\let\extrafloats\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\e@ch@ck`, `\extrafloats`, *and* `\extrafloats`.)

`\alloc@` Since `\e@alloc` was added in 2015, `\@alloc` has not been used, but was left as some legacy code calls it. However the original definition gives spurious errors once the "classic" registers run out, so it is now defined to call `\e@alloc` internally.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}
⟨latexrelease⟩                 {\alloc@}{emulate alloc@}%
\def\alloc@#1#2#3#4{\e@alloc#2#3{\count1#1}#4\float@count}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\alloc@}{emulate alloc@}%
⟨latexrelease⟩\def\alloc@#1#2#3#4#5{\global\advance\count1#1\@ne
⟨latexrelease⟩  \ch@ck#1#4#2%
⟨latexrelease⟩  \allocationnumber\count1#1%
⟨latexrelease⟩  \global#3#5\allocationnumber
⟨latexrelease⟩  \wlog{\string#5=\string#2\the\allocationnumber}}
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\alloc@`.)

`\newinsert`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/10/01}
⟨latexrelease⟩                  {\newinsert}{Extended \newinsert}%
\ifx\numexpr\@undefined
```

If e-TEX is not available use the original plain TEX definition of `\newinsert`.

```
\def\newinsert#1{\global\advance\insc@unt \m@ne
  \ch@ck0\insc@unt\count
  \ch@ck1\insc@unt\dimen
  \ch@ck2\insc@unt\skip
  \ch@ck4\insc@unt\box
  \allocationnumber\insc@unt
  \global\chardef#1\allocationnumber
  \wlog{\string#1=\string\insert\the\allocationnumber}}
\else
```

The highest register allowed with `\insert`.

```
\ifx\directlua\@undefined
  \chardef\e@insert@top255
\else
  \chardef\e@insert@top\e@alloc@top
\fi
```

If the classic registers are exhausted, take an insert from the free float list and use `\extrafloats` to add a new float to that list.

```
\def\newinsert#1{%
\@tempswafalse
\global\advance\insc@unt\m@ne
\ifnum\count10<\insc@unt
\ifnum\count11<\insc@unt
\ifnum\count12<\insc@unt
\ifnum\count14<\insc@unt
  \@tempswatrue
\fi\fi\fi\fi
\if@tempswa
\allocationnumber\insc@unt
\else
\global\advance\insc@unt\@ne
  \extrafloats\@ne
  \@next\@currbox\@freelist
    {\ifnum\@currbox<\e@insert@top
      \allocationnumber\@currbox
     \else
     \ch@ck0\m@ne\insert
     \fi}%
     {\ch@ck0\m@ne\insert}%
\fi
```

```
\global\chardef#1\allocationnumber
\wlog{\string#1=\string\insert\the\allocationnumber}%
}
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\newinsert}{Extended \newinsert}%
⟨latexrelease⟩\let\e@insert@top\@undefined
⟨latexrelease⟩\def\newinsert#1{\global\advance\insc@unt \m@ne
⟨latexrelease⟩  \ch@ck0\insc@unt\count
⟨latexrelease⟩  \ch@ck1\insc@unt\dimen
⟨latexrelease⟩  \ch@ck2\insc@unt\skip
⟨latexrelease⟩  \ch@ck4\insc@unt\box
⟨latexrelease⟩  \allocationnumber\insc@unt
⟨latexrelease⟩  \global\chardef#1\allocationnumber
⟨latexrelease⟩  \wlog{\string#1=\string\insert\the\allocationnumber}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\newinsert`.)

`\ch@ck`

```
\gdef\ch@ck#1#2#3{%
  \ifnum\count1#1<#2\else
    \errmessage{No room for a new #3}%
  \fi}
```

(*End definition for* `\ch@ck`.)

`\newhelp`

```
\def\newhelp#1#2{\newtoks#1#1\expandafter{\csname#2\endcsname}}
```

(*End definition for* `\newhelp`.)

`\@inputcheck` `\@unused`

Allocate read stream for testing and output stream that is never open an thus writes to the terminal.

```
\newread\@inputcheck
\newwrite\@unused
```

(*End definition for* `\@inputcheck` *and* `\@unused`.)

`\maxdimen` `\hideskip`

Here are some examples of allocation.

```
\newdimen\maxdimen \maxdimen=16383.99999pt % the largest legal <dimen>
\newskip\hideskip \hideskip=-1000pt plus 1fill % negative but can grow
```

(*End definition for* `\maxdimen` *and* `\hideskip`.)

`\p@` `\z@` `\z@skip` `\voidb@x`

```
\newdimen\p@ \p@=1pt % this saves macro space and time
\newdimen\z@ \z@=0pt % can be used both for 0pt and 0
\newskip\z@skip \z@skip=0pt plus0pt minus0pt
\newbox\voidb@x % permanently void box register
```

(*End definition for* `\p@` *and others.*)

Assign initial values to TEX's parameters

```
\message{parameters,}
```

All of TEX's numeric parameters are listed here, but the code is commented out if no special value needs to be set. INITEX makes all parameters zero except where noted. *Historical LATEX 2.09 comments (not necessarily accurate any more):*

```
\pretolerance=100
\tolerance=200 % INITEX sets this to 10000
\hbadness=1000
\vbadness=1000
\linepenalty=10
\hyphenpenalty=50
\exhyphenpenalty=50
\binoppenalty=700
\relpenalty=500
\clubpenalty=150
\widowpenalty=150
\displaywidowpenalty=50
\brokenpenalty=100
\predisplaypenalty=10000
```

`\postdisplaypenalty=`0
`\interlinepenalty=`0
`\floatingpenalty=`0, set during `\insert`
`\outputpenalty=`0, set before TeX enters `\output`

```
\doublehyphendemerits=10000
\finalhyphendemerits=5000
\adjdemerits=10000
```

```
% \looseness=0, cleared by TeX after each paragraph
% \pausing=0
% \holdinginserts=0
% \tracingonline=0
% \tracingmacros=0
% \tracingstats=0
% \tracingparagraphs=0
% \tracingpages=0
% \tracingoutput=0
```

In the past `\LaTeX{}` used the default value of `\texttt{1}` for `\cs{tracinglostchars}` because this was the best it could do. This way one would at least get a warning in the `\texttt{.log}` file. e-`\TeX{}` improved on that and supported a value of `\texttt{2}` to show the warning on the terminal, so we could have changed the default when we made the e-`\TeX{}` extensions required—however, we overlooked that oportunity.
In 2021 this parameter was improved on again and now also accepts the value `\texttt{3}`
(error on the terminal). This made us realize that we should change the default. Using `\texttt{3}` would really be the best, but for compatibility reasons we only use `\texttt{2}`.

`\changes{v2.3g}{2021/07/16}{Use 2 as default value for \cs{tracinglostchars}}`

```
\tracinglostchars=2
```

```
% \tracingcommands=0
% \tracingrestores=0
```

\begin{macro}{\tracingstacklevels}

For Lua\TeX, the \cs{tracingstacklevels} functionality was implemented as a callback, so here we just define the count register to hold the value of the parameter.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}{\tracingstacklevels}%
⟨latexrelease⟩                  {tracingstacklevels}%
\ifx\directlua\@undefined
  % \tracingstacklevels=0 % added in 2021
\else
  \newcount\tracingstacklevels
  % Code for \tracingstacklevels defined in ltfinal.dtx
\fi
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\tracingstacklevels}%
⟨latexrelease⟩                  {tracingstacklevels}%
⟨latexrelease⟩\ifx\directlua\@undefined
⟨latexrelease⟩\else
⟨latexrelease⟩   \let\tracingstacklevels\@undefined
⟨latexrelease⟩\fi
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
```

\end{macro}

\language=0

```
\uchyph=1
```

\lefthyphenmin=2 \righthyphenmin=3 set below
\globaldefs=0
\maxdeadcycles=25 % INITEX does this
\hangafter=1 % INITEX does this, also TeX after each paragraph
\fam=0
\mag=1000 % INITEX does this
\escapechar=`\\ % INITEX does this

```
\defaulthyphenchar=`\-
\defaultskewchar=-1
```

\endlinechar=`\^^M % INITEX does this
\newlinechar=-1 \LaTeX\ sets this in ltdefns.dtx.

```
\delimiterfactor=901
```

\time=now % TeX does this at beginning of job
\day=now % TeX does this at beginning of job
\month=now % TeX does this at beginning of job
\year=now % TeX does this at beginning of job

End of historical LaTeX 2.09 comments.

In LaTeX we don't want box information in the transcript unless we do a full tracing.

```
\showboxbreadth=-1
\showboxdepth=-1
\errorcontextlines=-1
```

```
\hfuzz=0.1pt
\vfuzz=0.1pt
\overfullrule=5pt
\maxdepth=4pt
\splitmaxdepth=\maxdimen
\boxmaxdepth=\maxdimen
```

Historical LaTeX 2.09 comments (not necessarily accurate any more):
\lineskiplimit=0pt, changed by \normalbaselines

```
\delimitershortfall=5pt
\nulldelimiterspace=1.2pt
\scriptspace=0.5pt
```

\mathsurround=0pt
\predisplaysize=0pt, set before TeX enters $$
\displaywidth=0pt, set before TeX enters $$
\displayindent=0pt, set before TeX enters $$

```
\parindent=20pt
```

\hangindent=0pt, zeroed by TeX after each paragraph
\hoffset=0pt
\voffset=0pt

\baselineskip=0pt, changed by \normalbaselines
\lineskip=0pt, changed by \normalbaselines

```
\parskip=0pt plus 1pt
\abovedisplayskip=12pt plus 3pt minus 9pt
\abovedisplayshortskip=0pt plus 3pt
\belowdisplayskip=12pt plus 3pt minus 9pt
\belowdisplayshortskip=7pt plus 3pt minus 4pt
```

\leftskip=0pt
\rightskip=0pt

```
\topskip=10pt
\splittopskip=10pt
```

\tabskip=0pt
\spaceskip=0pt
\xspaceskip=0pt

```
\parfillskip=0pt plus 1fil
```

End of historical LaTeX 2.09 comments.

\normalbaselineskip
\normallineskip
\normallineskiplimit

We also define special registers that function like parameters:

```
\newskip\normalbaselineskip \normalbaselineskip=12pt
\newskip\normallineskip \normallineskip=1pt
\newdimen\normallineskiplimit \normallineskiplimit=0pt
```

(*End definition for* \normalbaselineskip*,* \normallineskip*, and* \normallineskiplimit*.*)

\interfootlinepenalty

```
\newcount\interfootnotelinepenalty \interfootnotelinepenalty=100
```

(*End definition for* \interfootlinepenalty*.*)

Definitions for preloaded fonts

\magstephalf
\magstep

```
\def\magstephalf{1095 }
\def\magstep#1{\ifcase#1 \@m\or 1200\or 1440\or 1728\or
                2074\or 2488\fi\relax}
```

(*End definition for* \magstephalf *and* \magstep*.*)

Macros for setting ordinary text

\frenchspacing
\nonfrenchspacing

```
\def\frenchspacing{\sfcode`\.\@m \sfcode`\?\@m \sfcode`\!\@m
  \sfcode`\:\@m \sfcode`\;\@m \sfcode`\,\@m}
\def\nonfrenchspacing{\sfcode`\.3000\sfcode`\?3000\sfcode`\!3000%
  \sfcode`\:2000\sfcode`\;1500\sfcode`\,1250 }
```

(*End definition for* \frenchspacing *and* \nonfrenchspacing*.*)

\normalbaselines

```
\def\normalbaselines{\lineskip\normallineskip
  \baselineskip\normalbaselineskip \lineskiplimit\normallineskiplimit}
```

(*End definition for* \normalbaselines*.*)

\M
\I

Save a bit of space by using \let here.

```
\def\^^M{\ } % control <return> = control <space>
\let\^^I\^^M % same for <tab>
```

(*End definition for* \M *and* \I*.*)

\lq
\rq

```
\def\lq{`}
\def\rq{'}
```

(*End definition for* \lq *and* \rq*.*)

\lbrack
\rbrack

```
\def\lbrack{[}
\def\rbrack{]}
```

(*End definition for* \lbrack *and* \rbrack*.*)

\aa
\AA

These are not from plain.tex but they are similar to other commands found here and nowhere else, being alternate input forms for characters.

```
\def \aa {\r a}
\def \AA {\r A}
```

(*End definition for* `\aa` *and* `\AA`.)

\endgraf
\endline

```
\let\endgraf=\par
\let\endline=\cr
```

(*End definition for* `\endgraf` *and* `\endline`. *These functions are documented on page 298.*)

\space

```
\def\space{ }
```

(*End definition for* `\space`.)

\empty

This probably ought to go altogether, but let it to the LaTeX version to save space.

```
\let\empty\@empty
```

(*End definition for* `\empty`.)

\null

```
\def\null{\hbox{}}
```

(*End definition for* `\null`.)

\bgroup
\egroup

```
\let\bgroup={
\let\egroup=}
```

(*End definition for* `\bgroup` *and* `\egroup`.)

\obeylines
\obeyspaces

In `\obeylines`, we say `\let^^M=\obeyedline` instead of `\def^^M{\obeyedline}` since this allows, for example, `\let\obeyedline=\cr \obeylines \halign{....`

This is essentially a plain TeX trick and in its original version where you had to use to use `\let\par=\cr` not really a safe idea in LaTeX. If anybody used this trick this now breaks (and one needs to use `\obeyedline` instead).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}{\obeylines}%
⟨latexrelease⟩     {Add a redirection to obeylines and obeyspaces}%
```

If the active `^^M` escapes, e.g. into a `\write` (which is effectively in a different context) we don't want the definition from `\obeylines` but rather a simple `\par` (in fact even the primitive one, not the LaTeX version `\para_end:` which is only defined later.

```
\begingroup
\catcode`\^^M=\active % these lines must end with %
  \gdef\obeylines{\catcode`\^^M\active%
    \let^^M\obeyedline%
```

The next line ending the definition is rather curious and it took me awhile to understand why rollback fails. The problem is the following: if `latexrelease` is used, then blocks of `\IncludeInRelease` ... `\EndIncludeInRelease` are bypassed at high speed by grabbing each as a delimited argument. However, in that case `^^M` is seen not as code but as line ending characters and in that mode TEX discards everything from that point onwards to the real end of the line so it works like a comment — pretty strange really (and I think due to the fact the the original pascal compiler could have some garbage showing up after the normal line ending character. Thus we really have to make sure that any closing braces is not one the same line as an `^^M`, because otherwise it would get dropped and we end with unbalanced braces and never see the `\EndIncludeInRelease` — weird. In other places it doesn't matter because we aren't using the incomplete result.

```
  }%
  \global\let^^M\par % this is in case ^^M appears in a \write
\endgroup
```

The `\obeyedline` expands by default to `\par` with whatever definition `\par` has when it is executed. It can, however, be redefined (before calling `\obeylines`!) to achieve some special effects. If you want to alter is definition when already in the scope of `\obeylines`, it has no effect (because `\let` is used above). In that case simply make another call to `\obeylines` immediately. As you are in a restricted scope all that happens is that your redefinition is applied.

`\obeyedline`

For the default definition we have to use `\def` not `\let` because the meaning of `\par` can change and we want to use the one that is current when `\obeylines` act.

There is a small subtlety here: in an `\edef` the active `^^M` stayed put (because it was equal to to the primitive `\par`), now `\obeyedline` expands and you get what it contains, i.e., in that case `\par`, into the `\edef` or `\mark` unless we use `\protected` on it.

```
\protected\gdef\obeyedline{\par}
```

The definition of `\obeyspaces` is changed in the same way and now executes `\obeyedspace` for each active space.

`\obeyedspace`

```
\global\let\obeyedspace\space
```

```
\begingroup
\catcode`\ =\active%
\gdef\obeyspaces{\catcode`\ \active\let =\obeyedspace}%
```

An active space elsewhere generates `\space` by default (for example in a `\write`).

```
\global\let =\space%
\endgroup
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\obeylines}%
⟨latexrelease⟩    {Add a redirection to obeylines and obeyspaces}%
⟨latexrelease⟩
```

From 2019 onwards the commands are made robust (somewhat later in the kernel sources). So if we roll back they are robust, so when redefining them we have get rid of the robust payload first. Otherwise that is seen by the later rollback below, which then installs a fragile version of the new definition on top of the one we roll back to here, sigh. `\kernel@make@fragile` also changes its definition (later own) so this is done directly.

```
⟨latexrelease⟩\expandafter\let\csname obeylines \endcsname\@undefined
```

```
⟨latexrelease⟩\expandafter\let\csname obeyspace \endcsname\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\begingroup
⟨latexrelease⟩\catcode`\^^M=\active % these lines must end with %
⟨latexrelease⟩  \gdef\obeylines{\catcode`\^^M\active \let^^M\par %
```

Closing brace on a separate line (see comment above).

```
⟨latexrelease⟩                    }%
```

Another pitfall: if we do a rollback `\par` is no longer the primitive, so the roll back definition needs `\let` to what is new the primitive.

```
⟨latexrelease⟩  \global\let^^M\RawParEnd % this is in case ^^M appears in a \write
⟨latexrelease⟩\endgroup
⟨latexrelease⟩\def\obeyspaces{\catcode`\ \active}
⟨latexrelease⟩
⟨latexrelease⟩\let\obeyedline\@undefined
⟨latexrelease⟩\let\obeyedspace\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\obeylines` *and others.*)

`\loop`
`\iterate`
`\repeat`

We use Kabelschacht's method of doing loops, see TUB 8#2 (1987). (unless that breaks something :-). It turned out to need an extra `\relax`: see pr/642 (`\loop` could do one iteration too much in certain cases).

```
\long\def \loop #1\repeat{%
  \def\iterate{#1\relax  % Extra \relax
               \expandafter\iterate\fi
               }%
  \iterate
  \let\iterate\relax
}
```

This setting of `\repeat` is needed to make `\loop...\if...\repeat` skippable within another `\if...`.

```
\let\repeat=\fi
```

(*End definition for* `\loop`*,* `\iterate`*, and* `\repeat`*.*)

LaTeX defines `\smallskip`, etc. in `ltspace.dtx`.

`\nointerlineskip`
`\offinterlineskip`

```
\def\nointerlineskip{\prevdepth-\@m\p@}
\def\offinterlineskip{\baselineskip-\@m\p@
  \lineskip\z@ \lineskiplimit\maxdimen}
```

(*End definition for* `\nointerlineskip` *and* `\offinterlineskip`*.*)

`\vglue`
`\hglue`

```
\def\vglue{\afterassignment\vgl@\skip@=}
\def\vgl@{\par \dimen@\prevdepth \hrule \@height\z@
  \nobreak\vskip\skip@ \prevdepth\dimen@}
\def\hglue{\afterassignment\hgl@\skip@=}
\def\hgl@{\leavevmode \count@\spacefactor \vrule \@width\z@
  \nobreak\hskip\skip@ \spacefactor\count@}
```

(*End definition for* `\vglue` *and* `\hglue`.)

LaTeX defines ~ in `ltdefns.dtx`.

`\slash` This generates a / acting a bit like - but still allows hyphenation in the word part preceding it (but not after).

```
\def\slash{/\penalty\exhyphenpenalty}
```

(*End definition for* `\slash`.)

`\break`
`\nobreak`
`\allowbreak`

```
\def\break{\penalty-\@M}
\def\nobreak{\penalty \@M}
\def\allowbreak{\penalty \z@}
```

(*End definition for* `\break`, `\nobreak`, *and* `\allowbreak`.)

`\filbreak`
`\goodbreak`

```
\def\filbreak{\par\vfil\penalty-200\vfilneg}
\def\goodbreak{\par\penalty-500 }
```

(*End definition for* `\filbreak` *and* `\goodbreak`.)

`\eject` Define `\eject` as in plain TeX but define `\supereject` only in the compatibility file.

```
\def\eject{\par\break}
```

(*End definition for* `\eject`.)

`\removelastskip`

```
\def\removelastskip{\ifdim\lastskip=\z@\else\vskip-\lastskip\fi}
```

(*End definition for* `\removelastskip`.)

`\smallbreak`
`\medbreak`
`\bigbreak`

```
\def\smallbreak{\par\ifdim\lastskip<\smallskipamount
  \removelastskip\penalty-50\smallskip\fi}
\def\medbreak{\par\ifdim\lastskip<\medskipamount
  \removelastskip\penalty-100\medskip\fi}
\def\bigbreak{\par\ifdim\lastskip<\bigskipamount
  \removelastskip\penalty-200\bigskip\fi}
```

(*End definition for* `\smallbreak`, `\medbreak`, *and* `\bigbreak`.)

`\m@th`

```
\def\m@th{\mathsurround\z@}
```

(*End definition for* `\m@th`.)

`\underbar` Due to LaTeX's redefinition of `\underline` plain TeX's `\underbar` can be done in a simpler fashion (but do we need it at all?).

```
\def\underbar#1{\underline{\sbox\tw@{#1}\dp\tw@\z@\box\tw@}}
```

(*End definition for* `\underbar`.)

`\strutbox` LaTeX sets `\strutbox` in `\set@fontsize`.
`\strut`

```
\newbox\strutbox
\def\strut{\relax\ifmmode\copy\strutbox\else\unhcopy\strutbox\fi}
```

(*End definition for* `\strutbox` *and* `\strut`.)

`\hidewidth` For alignment entries that can stick out.

```
\def\hidewidth{\hskip\hideskip}
```

(*End definition for* `\hidewidth`.)

`\narrower`

```
\def\narrower{%
  \advance\leftskip\parindent
  \advance\rightskip\parindent}
```

(*End definition for* `\narrower`.)

LaTeX defines `\ae` and similar commands elsewhere.

```
\chardef\%=`\%
\chardef\&=`\&
\chardef\#=`\#
```

Most text commands are actually encoding specific and therefore defined later, so commented out or removed from this file.

`\leavevmode` begins a paragraph, if necessary

```
\def\leavevmode{\unhbox\voidb@x}
```

(*End definition for* `\leavevmode`.)

`\mathhexbox`

```
\def\mathhexbox#1#2#3{\mbox{$\m@th \mathchar"#1#2#3$}}
```

(*End definition for* `\mathhexbox`.)

`\ialign`

```
\def\ialign{\everycr{}\tabskip\z@skip\halign} % initialized \halign
```

(*End definition for* `\ialign`.)

`\oalign` `\o@lign` `\ooalign`

```
\def\oalign#1{\leavevmode\vtop{\baselineskip\z@skip \lineskip.25ex%
  \ialign{##\crcr#1\crcr}}}
\def\o@lign{\lineskiplimit\z@ \oalign}
\def\ooalign{\lineskiplimit-\maxdimen \oalign}
```

(*End definition for* `\oalign`, `\o@lign`, *and* `\ooalign`.)

`\sh@ft` The definition of this macro in plain.tex was improved in about 1997; but as a result its usage was changed and its new definition is not appropriate for LaTeX.

Since the version given here has been in use by LaTeX for many years it does not seem prudent to remove it now. As far as we can tell it has only been used to define `\b` and `\d` but this cannot be certain.

```
\def\sh@ft#1{\dimen@.00#1ex\multiply\dimen@\fontdimen1\font
  \kern-.0156\dimen@} % compensate for slant in lowered accents
```

(*End definition for* `\sh@ft`.)

\ltx@sh@ft This is the LaTeX version of the second incarnation of the plain macro \sh@ft, which takes a dimension as its argument. It shifts a pseudo-accent horizontally by an amount proportional to the product of its argument and the slant-per-point (fontdimen 1).

```
\def\ltx@sh@ft #1{%
  \dimen@ #1%
  \kern \strip@pt
    \fontdimen1\font \dimen@
  } % kern by #1 times the current slant
```

(*End definition for* \ltx@sh@ft.)

LaTeX change: the text commands such as \d, \b, \c, \copyright, \TeX are now defined elsewhere.

LaTeX change: Make \t work in a moving argument. Now defined elsewhere.

\hrulefill \dotfill LaTeX change: \kern\z@ added to end of \hrulefill and \dotfill to make them work in 'tabular' and 'array' environments. (Change made 24 July 1987). LaTeX change: \leavevmode added at beginning of \dotfill and \hrulefill so that they work as expected in vertical mode.

```
\def\hrulefill{\leavevmode\leaders\hrule\hfill\kern\z@}
```

The box in \dotfill originally contained (in plain.tex):
\mkern 1.5mu .\mkern 1.5mu;
the width of .44em differs from this by .04pt which is probably an acceptable difference within leaders.

```
\def\dotfill{%
  \leavevmode
  \cleaders \hb@xt@ .44em{\hss.\hss}\hfill
  \kern\z@}
```

(*End definition for* \hrulefill *and* \dotfill.)

INITEX sets \sfcode x=1000 for all x, except that \sfcode‘X=999 for uppercase letters. The following changes are needed:

```
\sfcode‘\)=0 \sfcode‘\’=0 \sfcode‘\]=0
```

The \nonfrenchspacing macro will make further changes to \sfcode values.

Definitions related to output

\magnification doesn't work in LaTeX.

```
def\magnification{\afterassignment\m@g\count@}
def\m@g{\mag\count@
 \hsize6.5truein\vsize8.9truein\dimen\footins8truein}
```

\showoverfull The following commands are used in debugging:

```
\def\showoverfull{\tracingonline\@ne}
```

(*End definition for* \showoverfull.)

\showoutput \loggingoutput

```
\gdef\loggingoutput{\tracingoutput\@ne
    \showboxbreadth\maxdimen\showboxdepth\maxdimen\errorstopmode}
\gdef\showoutput{\loggingoutput\showoverfull}
⟨/2ekernel⟩
```

(*End definition for* \showoutput *and* \loggingoutput.)

\tracingall
\loggingall

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}{\loggingall}
⟨latexrelease⟩                  {\tracingstacklevels and \tracinglostchars=3}%
⟨*2ekernel | latexrelease⟩
\edef\loggingall{%
  \tracingstats\tw@
  \tracingpages\@ne
  \tracinglostchars\thr@@
  \tracingparagraphs\@ne
  \tracinggroups\@ne
  \tracingifs\@ne
  \tracingscantokens\@ne
  \tracingnesting\@ne
  \errorcontextlines\maxdimen
  \ifdefined\tracingstacklevels \tracingstacklevels\maxdimen \fi
  \noexpand \loggingoutput
  \tracingmacros\tw@
  \tracingcommands\thr@@
  \tracingrestores\@ne
  \tracingassigns\@ne
}%
\def\tracingall{\showoverfull\loggingall}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\loggingall}{etex tracing}%
⟨latexrelease⟩\ifx\tracingscantokens\@undefined
⟨latexrelease⟩\gdef\loggingall{%
⟨latexrelease⟩  \tracingstats\tw@
⟨latexrelease⟩  \tracingpages\@ne
⟨latexrelease⟩  \tracinglostchars\@ne
⟨latexrelease⟩  \tracingparagraphs\@ne
⟨latexrelease⟩  \errorcontextlines\maxdimen
⟨latexrelease⟩  \loggingoutput
⟨latexrelease⟩  \tracingmacros\tw@
⟨latexrelease⟩  \tracingcommands\tw@
⟨latexrelease⟩  \tracingrestores\@ne
⟨latexrelease⟩  }%
⟨latexrelease⟩\else
⟨latexrelease⟩\gdef\loggingall{%
⟨latexrelease⟩  \tracingstats\tw@
⟨latexrelease⟩  \tracingpages\@ne
⟨latexrelease⟩  \tracinglostchars\tw@
⟨latexrelease⟩  \tracingparagraphs\@ne
⟨latexrelease⟩  \tracinggroups\@ne
⟨latexrelease⟩  \tracingifs\@ne
⟨latexrelease⟩  \tracingscantokens\@ne
⟨latexrelease⟩  \tracingnesting\@ne
⟨latexrelease⟩  \errorcontextlines\maxdimen
⟨latexrelease⟩  \loggingoutput
⟨latexrelease⟩  \tracingmacros\tw@
⟨latexrelease⟩  \tracingcommands\thr@@
⟨latexrelease⟩  \tracingrestores\@ne
⟨latexrelease⟩  \tracingassigns\@ne
```

```
⟨latexrelease⟩}%
⟨latexrelease⟩\fi
⟨latexrelease⟩\gdef\tracingall{\showoverfull\loggingall}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\loggingall}{etex tracing}%
⟨latexrelease⟩\gdef\loggingall{\tracingcommands\tw@\tracingstats\tw@
⟨latexrelease⟩   \tracingpages\@ne\tracinglostchars\@ne
⟨latexrelease⟩   \tracingmacros\tw@\tracingparagraphs\@ne\tracingrestores\@ne
⟨latexrelease⟩   \errorcontextlines\maxdimen\loggingoutput}
⟨latexrelease⟩   \gdef\tracingall{\loggingall\showoverfull}
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\tracingall` *and* `\loggingall`.)

`\tracingnone`

```
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\tracingnone}%
⟨latexrelease⟩                              {turn off etex tracing}%
⟨*2ekernel | latexrelease⟩
\edef\tracingnone{%
  \tracingassigns\z@
  \tracingrestores\z@
  \tracingonline\z@
  \tracingcommands\z@
  \showboxdepth\m@ne
  \showboxbreadth\m@ne
  \tracingoutput\z@
  \errorcontextlines\m@ne
  \ifdefined\tracingstacklevels \tracingstacklevels\z@ \fi
  \tracingnesting\z@
  \tracingscantokens\z@
  \tracingifs\z@
  \tracinggroups\z@
  \tracingparagraphs\z@
  \tracingmacros\z@
  \tracinglostchars\@ne
  \tracingpages\z@
  \tracingstats\z@
}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\tracingnone}%
⟨latexrelease⟩                              {turn off etex tracing}%
⟨latexrelease⟩\ifx\tracingscantokens\@undefined
⟨latexrelease⟩\def\tracingnone{%
⟨latexrelease⟩   \tracingonline\z@
⟨latexrelease⟩   \tracingcommands\z@
⟨latexrelease⟩   \showboxdepth\m@ne
⟨latexrelease⟩   \showboxbreadth\m@ne
⟨latexrelease⟩   \tracingoutput\z@
⟨latexrelease⟩   \errorcontextlines\m@ne
⟨latexrelease⟩   \tracingrestores\z@
⟨latexrelease⟩   \tracingparagraphs\z@
```

```
⟨latexrelease⟩  \tracingmacros\z@
⟨latexrelease⟩  \tracinglostchars\@ne
⟨latexrelease⟩  \tracingpages\z@
⟨latexrelease⟩  \tracingstats\z@
⟨latexrelease⟩}%
⟨latexrelease⟩\else
⟨latexrelease⟩\def\tracingnone{%
⟨latexrelease⟩  \tracingassigns\z@
⟨latexrelease⟩  \tracingrestores\z@
⟨latexrelease⟩  \tracingonline\z@
⟨latexrelease⟩  \tracingcommands\z@
⟨latexrelease⟩  \showboxdepth\m@ne
⟨latexrelease⟩  \showboxbreadth\m@ne
⟨latexrelease⟩  \tracingoutput\z@
⟨latexrelease⟩  \errorcontextlines\m@ne
⟨latexrelease⟩  \tracingnesting\z@
⟨latexrelease⟩  \tracingscantokens\z@
⟨latexrelease⟩  \tracingifs\z@
⟨latexrelease⟩  \tracinggroups\z@
⟨latexrelease⟩  \tracingparagraphs\z@
⟨latexrelease⟩  \tracingmacros\z@
⟨latexrelease⟩  \tracinglostchars\@ne
⟨latexrelease⟩  \tracingpages\z@
⟨latexrelease⟩  \tracingstats\z@
⟨latexrelease⟩}%
⟨latexrelease⟩\fi
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\tracingnone}%
⟨latexrelease⟩                              {turn off etex tracing}%
⟨latexrelease⟩\let\tracingnone\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\tracingnone`.)

`\hideoutput`

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\hideoutput}%
⟨latexrelease⟩                              {hide output from tracing}%
\def\hideoutput{%
  \tracingoutput\z@
  \showboxbreadth\m@ne
  \showboxdepth\m@ne
  \tracingonline\m@ne
}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\hideoutput}%
⟨latexrelease⟩                              {hide output from tracing}%
⟨latexrelease⟩\let\hideoutput\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
```

(*End definition for* `\hideoutput`.)

LaTeX change: `\showhyphens` Defined later.

Punctuation affects the spacing.

```
⟨*2ekernel⟩
\nonfrenchspacing
⟨/2ekernel⟩
```

File c
ltvers.dtx

1 Version Identification

First we identify the date and version number of this release of LaTeX, and set `\everyjob` so that it is printed at the start of every LaTeX run.

`\fmtname`
`\fmtversion`
`\latexreleaseversion`
`\patch@level`

A `\patch@level` of `0` or higher denotes an official public release. A negative value indicates a candidate release that is not distributed.

If we put code updates into the kernel that are supposed to go into the next release we set the `\patch@level` to `-1` and the `\fmtversion` / `\latexreleaseversion` to the dated of the next release (guessed, the real value is not so important and will get corrected when we make the release official).

If the `\patch@level` is already at `-1` we do nothing here and use the `\fmtversion` date for any new`\IncludeInRelease` line when we add further code.

Finally, if we do make a public release we either just set the `\patch@level` to zero (if our initial guess was good) or we also change the date and then have to additionally change to that date on all the `\IncludeInRelease` statements that used the "guessed" date.

```
⟨*2ekernel⟩
\def\fmtname{LaTeX2e}
\edef\fmtversion
⟨/2ekernel⟩
⟨latexrelease⟩\edef\latexreleaseversion
⟨*2ekernel | latexrelease⟩
    {2022-06-01}
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
\def\patch@level{0}
```

For more fine grain control there is the possibility to name the current development branch. This is only used when the `\patch@level` is negative (i.e., a pre-release format) and is intended to help us internally when we locally install a format out of some development branch.

`\development@branch@name`

```
\edef\development@branch@name{}
```

(*End definition for* `\fmtname` *and others.*)

Check that the format being made is not too old. The error message complains about 'more than 5 years' but in fact the error is not triggered until 65 months.

This code is currently not activated as we don't know if we already got to the last official 2e version (due to staff shortage or due to a successor (think positive:-)).

```
\iffalse
\def\reserved@a#1/#2/#3\@nil{%
  \count@\year
  \advance\count@-#1\relax
  \multiply\count@ by 12\relax
  \advance\count@\month
  \advance\count@-#2\relax}
\expandafter\reserved@a\fmtversion\@nil
```

\count@ is now the age of this file in months. Take a generous definition of 'year' so this message is not generated too often.

```
\ifnum\count@>65
  \typeout{^^J%
!!!
```

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\newif\if@includeinrelease
⟨latexrelease⟩\@includeinreleasefalse
```

```
\def\IncludeInRelease#1{%
 \if@includeinrelease
   \PackageError{latexrelease}{mis-matched IncludeInRelease}%
                 {There is an \string\EndIncludeRelease\space missing}%
  \@includeinreleasefalse
  \fi
  \ifnum0%
      \ifx\new@moduledate\@empty\else 1\fi
      \ifnum \expandafter\@parse@version#1//00\@nil=0 1\fi
      =11
    \expandafter\@firstoftwo
  \else
    \expandafter\@secondoftwo
  \fi
    {\finish@module@release{#1}}%
    {\kernel@ifnextchar[%
      {\@IncludeInRelease{#1}}
      {\@IncludeInRelease{#1}[#1]}}}
\def\finish@module@release#1#2#3{%
  \toks@{[#1] #3}%
  \begingroup
    \edef\x{\detokenize\expandafter{\new@modulename}}%
    \edef\y{\detokenize{#2}}%
  \expandafter\endgroup
  \ifx\x\y \else
    \@latex@error{\noexpand\IncludeInRelease dated #1 in a module is not
      allowed.\MessageBreak Use a date at least equal to \new@moduledate
      \space for complete rollback}\@ehd
  \fi
  \ifnum\expandafter\@parse@version\new@moduledate//00\@nil
       >\expandafter\@parse@version\fmtversion//00\@nil
    \GenericInfo{}{Applying: \the\toks@}%
  \else
    \GenericInfo{}{Skipping: \the\toks@}%
    \expandafter\gobble@finish@module@release
  \fi}
\long\def\gobble@finish@module@release#1\EndModuleRelease{%
  \EndModuleRelease}
```

If a specific date has not been specified in `latexrelease` use '`#1`'.

```
\def\@IncludeInRelease#1[#2]{\@IncludeInRele@se{#2}}
```

```
\def\@IncludeInRele@se#1#2#3{%
  \toks@{[#1] #3}%
  \expandafter\ifx\csname\string#2+\@currname+IIR\endcsname\relax
```

If we roll back and the first patch already match then applying that is actually reapplying what is already in the format, i.e., it is useless and possibly allocating new registers. However, it makes the logic simpler so this is the way it is for now. In theory we could always jump over the first patch because that is only really needed for rolling forward. So maybe one day ...

```
    \ifnum\expandafter\@parse@version#1//00\@nil
         >\expandafter\@parse@version\fmtversion//00\@nil
      \GenericInfo{}{Skipping: \the\toks@}%
      \expandafter\expandafter\expandafter\@gobble@IncludeInRelease
    \else
      \GenericInfo{}{Applying: \the\toks@}%
      \@includeinreleasetrue
      \expandafter\let\csname\string#2+\@currname+IIR\endcsname\@empty
    \fi
  \else
    \GenericInfo{}{Already applied: \the\toks@}%
    \expandafter\@gobble@IncludeInRelease
  \fi
}
```

```
\def\EndIncludeInRelease{%
\if@includeinrelease
  \@includeinreleasefalse
\else
  \PackageError{latexrelease}{mis-matched EndIncludeInRelease}{}%
\fi
\if@skipping@module
  \expandafter\new@module@skip
\fi}
```

```
\long\def\@gobble@IncludeInRelease#1\EndIncludeInRelease{%
  \@includeinreleasefalse
  \@check@IncludeInRelease#1\IncludeInRelease\@check@IncludeInRelease
  \@end@check@IncludeInRelease}
```

```
\long\def\@check@IncludeInRelease#1\IncludeInRelease
                                  #2#3\@end@check@IncludeInRelease{%
  \ifx\@check@IncludeInRelease#2\else
    \PackageError{latexrelease}{skipped IncludeInRelease for tag \string#2}{}%
  \fi
  \if@skipping@module
    \expandafter\new@module@skip
  \fi}
```

(*End definition for* `\IncludeInRelease` *and others.*)

1.1 Declaring an all-new module

`\if@skipping@module`
`\NewModuleRelease`
`\EndModuleRelease`
`\new@module@skip`
`\new@modulename`
`\new@moduledate`

When we have a whole new module, we can't roll back to a date where such module exists, otherwise hundreds of "command already defined" errors will pop up. But we can't skip it altogether either, because the module might have changes we still want applied, so a more detailed cherry-picking of code chunks have to be done.

```
\let\if@skipping@module\iffalse
\def\@skipping@moduletrue{\let\if@skipping@module\iftrue}
\def\@skipping@modulefalse{\let\if@skipping@module\iffalse}
\let\new@modulename\@empty
\let\new@moduledate\@empty
\def\NewModuleRelease#1#2#3{%
  \ifx\new@modulename\@empty \else
    \@latex@error{Nested \noexpand\NewModuleRelease forbidden.}\@ehd \fi
```

```
  \edef\new@moduledate{#1}%
  \edef\new@modulename{#2}%
  \GenericInfo{}{BEGIN module: \new@modulename\space (\new@moduledate)}%
  \GenericInfo{}{ \@spaces\@spaces\@spaces\space#3\@gobble}%
  \ifnum\sourceLaTeXdate<%
        \expandafter\@parse@version\new@moduledate//00\@nil\relax
    \ifnum\expandafter\@parse@version\fmtversion//00\@nil<%
          \expandafter\@parse@version\new@moduledate//00\@nil\relax
      \GenericInfo{}{Skipping module \new@modulename}%
      \expandafter\expandafter
      \expandafter\gobble@finish@module@release
    \else
      \GenericInfo{}{Applying module \new@modulename}
      \@skipping@modulefalse
    \fi
  \else
    \GenericInfo{}{Skipping module \new@modulename}
    \@skipping@moduletrue
    \expandafter\new@module@skip
  \fi}
\long\def\new@module@skip#1\IncludeInRelease{%
  \long\def\reserved@a##1\EndModuleRelease{}%
  \if\relax\detokenize\expandafter{\reserved@a#1{}{}\EndModuleRelease}\relax
  \else
    \@latex@error{Missing mandatory \string\IncludeInRelease{0000/00/00}}\@ehc
    \expandafter\@secondoftwo
  \fi
  \@gobble
    {\@expandtwoargs\IncludeInRelease
         {0000/00/00}{\new@modulename}%
         {ERROR! Emergency recovery}%
     #1}%
  \IncludeInRelease}
\def\EndModuleRelease{%
  \ifx\new@modulename\@empty
    \@latex@error{Extra \string\EndModuleRelease.}\@eha
  \else
    \GenericInfo{}{END module: \new@modulename\space (\new@moduledate)}%
    \let\new@modulename\@empty
    \let\new@moduledate\@empty
    \@skipping@modulefalse
  \fi}
```

(*End definition for* `\if@skipping@module` *and others.*)

```
⟨/2ekernel | latexrelease⟩
```

File d
ltluatex.dtx

1 Overview

LuaTEX adds a number of engine-specific functions to TEX. Several of these require set up that is best done in the kernel or need related support functions. This file provides *basic* support for LuaTEX at the LATEX 2_ε kernel level plus as a loadable file which can be used with plain TEX and LATEX.

This file contains code for both TEX (to be stored as part of the format) and Lua (to be loaded at the start of each job). In the Lua code, the kernel uses the namespace `luatexbase`.

The following `\count` registers are used here for register allocation:

`\e@alloc@attribute@count` Attributes (default 258)

`\e@alloc@ccodetable@count` Category code tables (default 259)

`\e@alloc@luafunction@count` Lua functions (default 260)

`\e@alloc@whatsit@count` User whatsits (default 261)

`\e@alloc@bytecode@count` Lua bytecodes (default 262)

`\e@alloc@luachunk@count` Lua chunks (default 263)

(`\count 256` is used for `\newmarks` allocation and `\count 257` is used for `\newXeTeXintercharclass` with XeTEX, with code defined in `ltfinal.dtx`). With any LATEX 2_ε kernel from 2015 onward these registers are part of the block in the extended area reserved by the kernel (prior to 2015 the LATEX 2_ε kernel did not provide any functionality for the extended allocation area).

2 Core TEX functionality

The commands defined here are defined for possible inclusion in a future LATEX format, however also extracted to the file `ltluatex.tex` which may be used with older LATEX formats, and with plain TEX.

`\newattribute` `\newattribute{`⟨*attribute*⟩`}`
Defines a named `\attribute`, indexed from 1 (*i.e.* `\attribute0` is never defined). Attributes initially have the marker value `-"7FFFFFFF` ('unset') set by the engine.

`\newcatcodetable` `\newcatcodetable{`⟨*catcodetable*⟩`}`
Defines a named `\catcodetable`, indexed from 1 (`\catcodetable0` is never assigned). A new catcode table will be populated with exactly those values assigned by IniTEX (as described in the LuaTEX manual).

`\newluafunction` `\newluafunction{`⟨*function*⟩`}`
Defines a named `\luafunction`, indexed from 1. (Lua indexes tables from 1 so `\luafunction0` is not available).

`\newluacmd` `\newluadef{`⟨*function*⟩`}`
Like `\newluafunction`, but defines the command using `\luadef` instead of just assigning an integer.

\newprotectedluacmd `\newluadef{⟨function⟩}`
Like `\newluacmd`, but the defined command is not expandable.

\newwhatsit `\newwhatsit{⟨whatsit⟩}`
Defines a custom `\whatsit`, indexed from 1.

\newluabytecode `\newluabytecode{⟨bytecode⟩}`
Allocates a number for Lua bytecode register, indexed from 1.

\newluachunkname `newluachunkname{⟨chunkname⟩}`
Allocates a number for Lua chunk register, indexed from 1. Also enters the name of the register (without backslash) into the `lua.name` table to be used in stack traces.

\catcodetable@initex
\catcodetable@string
\catcodetable@latex
\catcodetable@atletter
Predefined category code tables with the obvious assignments. Note that the `latex` and `atletter` tables set the full Unicode range to the codes predefined by the kernel.

\setattribute `\setattribute{⟨attribute⟩}{⟨value⟩}`
\unsetattribute `\unsetattribute{⟨attribute⟩}`
Set and unset attributes in a manner analogous to `\setlength`. Note that attributes take a marker value when unset so this operation is distinct from setting the value to zero.

3 Plain TEX interface

The ltluatex interface may be used with plain TEX using `\input{ltluatex}`. This inputs `ltluatex.tex` which inputs `etex.src` (or `etex.sty` if used with LATEX) if it is not already input, and then defines some internal commands to allow the ltluatex interface to be defined.

The luatexbase package interface may also be used in plain TEX, as before, by inputting the package `\input luatexbase.sty`. The new version of luatexbase is based on this ltluatex code but implements a compatibility layer providing the interface of the original package.

4 Lua functionality

4.1 Allocators in Lua

new_attribute `luatexbase.new_attribute(⟨attribute⟩)`
Returns an allocation number for the ⟨*attribute*⟩, indexed from 1. The attribute will be initialised with the marker value `-"7FFFFFFF` ('unset'). The attribute allocation sequence is shared with the TEX code but this function does *not* define a token using `\attributedef`. The attribute name is recorded in the `attributes` table. A metatable is provided so that the table syntax can be used consistently for attributes declared in TEX or Lua.

new_whatsit `luatexbase.new_whatsit(⟨whatsit⟩)`
Returns an allocation number for the custom ⟨*whatsit*⟩, indexed from 1.

new_bytecode `luatexbase.new_bytecode(⟨bytecode⟩)`
Returns an allocation number for a bytecode register, indexed from 1. The optional ⟨*name*⟩ argument is just used for logging.

new_chunkname `luatexbase.new_chunkname(⟨chunkname⟩)`
Returns an allocation number for a Lua chunk name for use with `\directlua` and `\latelua`, indexed from 1. The number is returned and also ⟨*name*⟩ argument is added to the `lua.name` array at that index.

new_luafunction `luatexbase.new_luafunction(⟨functionname⟩)`

Returns an allocation number for a lua function for use with `\luafunction`, `\lateluafunction`, and `\luadef`, indexed from 1. The optional ⟨*functionname*⟩ argument is just used for logging.

These functions all require access to a named TEX count register to manage their allocations. The standard names are those defined above for access from TEX, *e.g.* \e@alloc@attribute@count, but these can be adjusted by defining the variable ⟨*type*⟩`_count_name` before loading `ltluatex.lua`, for example

```
local attribute_count_name = "attributetracker"
require("ltluatex")
```

would use a TEX `\count` (`\countdef`'d token) called `attributetracker` in place of \e@alloc@attribute@count.

4.2 Lua access to TEX register numbers

registernumber `luatexbase.registernumer(`⟨*name*⟩`)`

Sometimes (notably in the case of Lua attributes) it is necessary to access a register *by number* that has been allocated by TEX. This package provides a function to look up the relevant number using LuaTEX's internal tables. After for example `\newattribute\myattrib`, `\myattrib` would be defined by (say) `\myattrib=\attribute15`. `luatexbase.registernumer("myattrib")` would then return the register number, 15 in this case. If the string passed as argument does not correspond to a token defined by `\attributedef`, `\countdef` or similar commands, the Lua value `false` is returned.

As an example, consider the input:

```
\newcommand\test[1]{%
\typeout{#1: \expandafter\meaning\csname#1\endcsname^^J
\space\space\space\space
\directlua{tex.write(luatexbase.registernumber("#1") or "bad input")}%
}}

\test{undefinedrubbish}

\test{space}

\test{hbox}

\test{@MM}

\test{@tempdima}
\test{@tempdimb}

\test{strutbox}

\test{sixt@@n}

\attrbutedef\myattr=12
\myattr=200
\test{myattr}
```

If the demonstration code is processed with LuaLaTeX then the following would be produced in the log and terminal output.

```
undefinedrubbish: \relax
     bad input
space: macro:->
     bad input
hbox: \hbox
     bad input
@MM: \mathchar"4E20
     20000
@tempdima: \dimen14
     14
@tempdimb: \dimen15
     15
strutbox: \char"B
     11
sixt@@n: \char"10
     16
myattr: \attribute12
     12
```

Notice how undefined commands, or commands unrelated to registers do not produce an error, just return `false` and so print `bad input` here. Note also that commands defined by `\newbox` work and return the number of the box register even though the actual command holding this number is a `\chardef` defined token (there is no `\boxdef`).

4.3 Module utilities

`provides_module` `luatexbase.provides_module(`⟨*info*⟩`)`
This function is used by modules to identify themselves; the `info` should be a table containing information about the module. The required field `name` must contain the name of the module. It is recommended to provide a field `date` in the usual LaTeX format `yyyy/mm/dd`. Optional fields `version` (a string) and `description` may be used if present. This information will be recorded in the log. Other fields are ignored.

`module_info` `luatexbase.module_info(`⟨*module*⟩, ⟨*text*⟩`)`
`module_warning` `luatexbase.module_warning(`⟨*module*⟩, ⟨*text*⟩`)`
`module_error` `luatexbase.module_error(`⟨*module*⟩, ⟨*text*⟩`)`
These functions are similar to LaTeX's `\PackageError`, `\PackageWarning` and `\PackageInfo` in the way they format the output. No automatic line breaking is done, you may still use `\n` as usual for that, and the name of the package will be prepended to each output line.

Note that `luatexbase.module_error` raises an actual Lua error with `error()`, which currently means a call stack will be dumped. While this may not look pretty, at least it provides useful information for tracking the error down.

4.4 Callback management

`add_to_callback` `luatexbase.add_to_callback(`⟨*callback*⟩, ⟨*function*⟩, ⟨*description*⟩`)` Registers the ⟨*function*⟩ into the ⟨*callback*⟩ with a textual ⟨*description*⟩ of the function. Functions are inserted into the callback in the order loaded.

`remove_from_callback` `luatexbase.remove_from_callback(`⟨*callback*⟩, ⟨*description*⟩`)` Removes the callback

function with ⟨*description*⟩ from the ⟨*callback*⟩. The removed function and its description are returned as the results of this function.

`in_callback` `luatexbase.in_callback(`⟨*callback*⟩, ⟨*description*⟩`)` Checks if the ⟨*description*⟩ matches one of the functions added to the list for the ⟨*callback*⟩, returning a boolean value.

`disable_callback` `luatexbase.disable_callback(`⟨*callback*⟩`)` Sets the ⟨*callback*⟩ to `false` as described in the LuaTEX manual for the underlying `callback.register` built-in. Callbacks will only be set to false (and thus be skipped entirely) if there are no functions registered using the callback.

`callback_descriptions` A list of the descriptions of functions registered to the specified callback is returned. `{}` is returned if there are no functions registered.

`create_callback` `luatexbase.create_callback(`⟨*name*⟩,metatype,⟨*default*⟩`)` Defines a user defined callback. The last argument is a default function or `false`.

`call_callback` `luatexbase.call_callback(`⟨*name*⟩,...`)` Calls a user defined callback with the supplied arguments.

5 Implementation

```
⟨*2ekernel | tex | latexrelease⟩
⟨2ekernel | latexrelease⟩\ifx\directlua\@undefined\else
```

5.1 Minimum LuaTEX version

LuaTEX has changed a lot over time. In the kernel support for ancient versions is not provided: trying to build a format with a very old binary therefore gives some information in the log and loading stops. The cut-off selected here relates to the tree-searching behaviour of `require()`: from version 0.60, LuaTEX will correctly find Lua files in the `texmf` tree without 'help'.

```
⟨latexrelease⟩\IncludeInRelease{2015/10/01}
⟨latexrelease⟩                  {\newluafunction}{LuaTeX}%
\ifnum\luatexversion<60 %
  \wlog{****************************************************}
  \wlog{* LuaTeX version too old for ltluatex support *}
  \wlog{****************************************************}
  \expandafter\endinput
\fi
```

Two simple LaTeX macros from `ltdefns.dtx` have to be defined here because ltdefns.dtx is not loaded yet when ltluatex.dtx is executed.

```
\long\def\@gobble#1{}
\long\def\@firstofone#1{#1}
```

5.2 Older LaTeX/Plain TeX setup

```
⟨*tex⟩
```

Older LaTeX formats don't have the primitives with 'native' names: sort that out. If they already exist this will still be safe.

```
\directlua{tex.enableprimitives("",tex.extraprimitives("luatex"))}
\ifx\e@alloc\@undefined
```

In pre-2014 LaTeX, or plain TeX, load `etex.{sty,src}`.

```
  \ifx\documentclass\@undefined
    \ifx\loccount\@undefined
```

```
      \input{etex.src}%
    \fi
    \catcode`\@=11 %
    \outer\expandafter\def\csname newfam\endcsname
                          {\alloc@8\fam\chardef\et@xmaxfam}
  \else
    \RequirePackage{etex}
    \expandafter\def\csname newfam\endcsname
                    {\alloc@8\fam\chardef\et@xmaxfam}
    \expandafter\let\expandafter\new@mathgroup\csname newfam\endcsname
  \fi
```

5.2.1 Fixes to etex.src/etex.sty

These could and probably should be made directly in an update to `etex.src` which already has some LuaTEX-specific code, but does not define the correct range for LuaTEX.

2015-07-13 higher range in luatex.

```
\edef \et@xmaxregs {\ifx\directlua\@undefined 32768\else 65536\fi}
```

luatex/xetex also allow more math fam.

```
\edef \et@xmaxfam {\ifx\Umathcode\@undefined\sixt@@n\else\@cclvi\fi}
```

```
\count 270=\et@xmaxregs % locally allocates \count registers
\count 271=\et@xmaxregs % ditto for \dimen registers
\count 272=\et@xmaxregs % ditto for \skip registers
\count 273=\et@xmaxregs % ditto for \muskip registers
\count 274=\et@xmaxregs % ditto for \box registers
\count 275=\et@xmaxregs % ditto for \toks registers
\count 276=\et@xmaxregs % ditto for \marks classes
```

and 256 or 16 fam. (Done above due to plain/LATEX differences in ltluatex.)

```
% \outer\def\newfam{\alloc@8\fam\chardef\et@xmaxfam}
```

End of proposed changes to `etex.src`

5.2.2 luatex specific settings

Switch to global cf `luatex.sty` to leave room for inserts not really needed for luatex but possibly most compatible with existing use.

```
\expandafter\let\csname newcount\expandafter\expandafter\endcsname
                \csname globcount\endcsname
\expandafter\let\csname newdimen\expandafter\expandafter\endcsname
                \csname globdimen\endcsname
\expandafter\let\csname newskip\expandafter\expandafter\endcsname
                \csname globskip\endcsname
\expandafter\let\csname newbox\expandafter\expandafter\endcsname
                \csname globbox\endcsname
```

Define`\e@alloc` as in latex (the existing macros in `etex.src` hard to extend to further register types as they assume specific 26x and 27x count range. For compatibility the existing register allocation is not changed.

```
\chardef\e@alloc@top=65535
\let\e@alloc@chardef\chardef
```

```
\def\e@alloc#1#2#3#4#5#6{%
  \global\advance#3\@ne
  \e@ch@ck{#3}{#4}{#5}#1%
  \allocationnumber#3\relax
  \global#2#6\allocationnumber
  \wlog{\string#6=\string#1\the\allocationnumber}}%
\gdef\e@ch@ck#1#2#3#4{%
  \ifnum#1<#2\else
    \ifnum#1=#2\relax
      #1\@cclvi
      \ifx\count#4\advance#1 10 \fi
    \fi
    \ifnum#1<#3\relax
    \else
      \errmessage{No room for a new \string#4}%
    \fi
  \fi}%
```

Fix up allocations not to clash with `etex.src`.

```
\expandafter\csname newcount\endcsname\e@alloc@attribute@count
\expandafter\csname newcount\endcsname\e@alloc@ccodetable@count
\expandafter\csname newcount\endcsname\e@alloc@luafunction@count
\expandafter\csname newcount\endcsname\e@alloc@whatsit@count
\expandafter\csname newcount\endcsname\e@alloc@bytecode@count
\expandafter\csname newcount\endcsname\e@alloc@luachunk@count
```

End of conditional setup for plain TEX / old LATEX.

```
\fi
⟨/tex⟩
```

5.3 Attributes

`\newattribute`

As is generally the case for the LuaTEX registers we start here from 1. Notably, some code assumes that `\attribute0` is never used so this is important in this case.

```
\ifx\e@alloc@attribute@count\@undefined
  \countdef\e@alloc@attribute@count=258
  \e@alloc@attribute@count=\z@
\fi
\def\newattribute#1{%
  \e@alloc\attribute\attributedef
    \e@alloc@attribute@count\m@ne\e@alloc@top#1%
}
```

(*End definition for* `\newattribute`.)

`\setattribute`
`\unsetattribute`

Handy utilities.

```
\def\setattribute#1#2{#1=\numexpr#2\relax}
\def\unsetattribute#1{#1=-"7FFFFFFF\relax}
```

(*End definition for* `\setattribute` *and* `\unsetattribute`.)

5.4 Category code tables

\newcatcodetable

Category code tables are allocated with a limit half of that used by LuaTEX for everything else. At the end of allocation there needs to be an initialization step. Table 0 is already taken (it's the global one for current use) so the allocation starts at 1.

```
\ifx\e@alloc@ccodetable@count\@undefined
  \countdef\e@alloc@ccodetable@count=259
  \e@alloc@ccodetable@count=\z@
\fi
\def\newcatcodetable#1{%
  \e@alloc\catcodetable\chardef
    \e@alloc@ccodetable@count\m@ne{"8000}#1%
  \initcatcodetable\allocationnumber
}
```

(*End definition for* `\newcatcodetable`.)

\catcodetable@initex
\catcodetable@string
\catcodetable@latex
\catcodetable@atletter

Save a small set of standard tables. The Unicode data is read here in using a parser simplified from that in `load-unicode-data`: only the nature of letters needs to be detected.

```
\newcatcodetable\catcodetable@initex
\newcatcodetable\catcodetable@string
\begingroup
  \def\setrangecatcode#1#2#3{%
    \ifnum#1>#2 %
      \expandafter\@gobble
    \else
      \expandafter\@firstofone
    \fi
      {%
        \catcode#1=#3 %
        \expandafter\setrangecatcode\expandafter
          {\number\numexpr#1 + 1\relax}{#2}{#3}
      }%
  }
  \@firstofone{%
    \catcodetable\catcodetable@initex
      \catcode0=12 %
      \catcode13=12 %
      \catcode37=12 %
      \setrangecatcode{65}{90}{12}%
      \setrangecatcode{97}{122}{12}%
      \catcode92=12 %
      \catcode127=12 %
      \savecatcodetable\catcodetable@string
    \endgroup
  }%
\newcatcodetable\catcodetable@latex
\newcatcodetable\catcodetable@atletter
\begingroup
  \def\parseunicodedataI#1;#2;#3;#4\relax{%
    \parseunicodedataII#1;#3;#2 First>\relax
  }%
  \def\parseunicodedataII#1;#2;#3 First>#4\relax{%
    \ifx\relax#4\relax
```

```
      \expandafter\parseunicodedataIII
    \else
      \expandafter\parseunicodedataIV
    \fi
      {#1}#2\relax%
  }%
  \def\parseunicodedataIII#1#2#3\relax{%
    \ifnum 0%
      \if L#21\fi
      \if M#21\fi
      >0 %
      \catcode"#1=11 %
    \fi
  }%
  \def\parseunicodedataIV#1#2#3\relax{%
    \read\unicoderead to \unicodedataline
    \if L#2%
      \count0="#1 %
      \expandafter\parseunicodedataV\unicodedataline\relax
    \fi
  }%
  \def\parseunicodedataV#1;#2\relax{%
    \loop
      \unless\ifnum\count0>"#1 %
        \catcode\count0=11 %
        \advance\count0 by 1 %
    \repeat
  }%
  \def\storedpar{\par}%
  \chardef\unicoderead=\numexpr\count16 + 1\relax
  \openin\unicoderead=UnicodeData.txt %
  \loop\unless\ifeof\unicoderead %
    \read\unicoderead to \unicodedataline
    \unless\ifx\unicodedataline\storedpar
      \expandafter\parseunicodedataI\unicodedataline\relax
    \fi
  \repeat
  \closein\unicoderead
  \@firstofone{%
    \catcode64=12 %
    \savecatcodetable\catcodetable@latex
    \catcode64=11 %
    \savecatcodetable\catcodetable@atletter
   }
\endgroup
```

(*End definition for* `\catcodetable@initex` *and others.*)

5.5 Named Lua functions

`\newluafunction` Much the same story for allocating LuaTEX functions except here they are just numbers so they are allocated in the same way as boxes. Lua indexes from 1 so once again slot 0 is skipped.

```
\ifx\e@alloc@luafunction@count\@undefined
```

```
  \countdef\e@alloc@luafunction@count=260
  \e@alloc@luafunction@count=\z@
\fi
\def\newluafunction{%
  \e@alloc\luafunction\e@alloc@chardef
    \e@alloc@luafunction@count\m@ne\e@alloc@top
}
```

(*End definition for* `\newluafunction`.)

`\newluacmd` `\newprotectedluacmd` Additionally two variants are provided to make the passed control sequence call the function directly.

```
\def\newluacmd{%
  \e@alloc\luafunction\luadef
    \e@alloc@luafunction@count\m@ne\e@alloc@top
}
\def\newprotectedluacmd{%
  \e@alloc\luafunction{\protected\luadef}
    \e@alloc@luafunction@count\m@ne\e@alloc@top
}
```

(*End definition for* `\newluacmd` *and* `\newprotectedluacmd`.)

5.6 Custom whatsits

`\newwhatsit` These are only settable from Lua but for consistency are definable here.

```
\ifx\e@alloc@whatsit@count\@undefined
  \countdef\e@alloc@whatsit@count=261
  \e@alloc@whatsit@count=\z@
\fi
\def\newwhatsit#1{%
  \e@alloc\whatsit\e@alloc@chardef
    \e@alloc@whatsit@count\m@ne\e@alloc@top#1%
}
```

(*End definition for* `\newwhatsit`.)

5.7 Lua bytecode registers

`\newluabytecode` These are only settable from Lua but for consistency are definable here.

```
\ifx\e@alloc@bytecode@count\@undefined
  \countdef\e@alloc@bytecode@count=262
  \e@alloc@bytecode@count=\z@
\fi
\def\newluabytecode#1{%
  \e@alloc\luabytecode\e@alloc@chardef
    \e@alloc@bytecode@count\m@ne\e@alloc@top#1%
}
```

(*End definition for* `\newluabytecode`.)

5.8 Lua chunk registers

\newluachunkname

As for bytecode registers, but in addition we need to add a string to the `lua.name` table to use in stack tracing. We use the name of the command passed to the allocator, with no backslash.

```
\ifx\e@alloc@luachunk@count\@undefined
  \countdef\e@alloc@luachunk@count=263
  \e@alloc@luachunk@count=\z@
\fi
\def\newluachunkname#1{%
  \e@alloc\luachunk\e@alloc@chardef
    \e@alloc@luachunk@count\m@ne\e@alloc@top#1%
    {\escapechar\m@ne
    \directlua{lua.name[\the\allocationnumber]="\string#1"}}%
}
```

(*End definition for* `\newluachunkname`.)

5.9 Lua loader

Lua code loaded in the format often has to be loaded again at the beginning of every job, so we define a helper which allows us to avoid duplicated code:

```
\def\now@and@everyjob#1{%
  \everyjob\expandafter{\the\everyjob
    #1%
  }%
  #1%
}
```

Load the Lua code at the start of every job. For the conversion of TEX into numbers at the Lua side we need some known registers: for convenience we use a set of systematic names, which means using a group around the Lua loader.

```
⟨2ekernel⟩\now@and@everyjob{%
  \begingroup
    \attributedef\attributezero=0 %
    \chardef     \charzero     =0 %
```

Note name change required on older luatex, for hash table access.

```
    \countdef    \CountZero    =0 %
    \dimendef    \dimenzero    =0 %
    \mathchardef \mathcharzero =0 %
    \muskipdef   \muskipzero   =0 %
    \skipdef     \skipzero     =0 %
    \toksdef     \tokszero     =0 %
    \directlua{require("ltluatex")}
  \endgroup
⟨2ekernel⟩}
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}
⟨latexrelease⟩                  {\newluafunction}{LuaTeX}%
⟨latexrelease⟩\let\e@alloc@attribute@count\@undefined
⟨latexrelease⟩\let\newattribute\@undefined
⟨latexrelease⟩\let\setattribute\@undefined
```

```
⟨latexrelease⟩\let\unsetattribute\@undefined
⟨latexrelease⟩\let\e@alloc@ccodetable@count\@undefined
⟨latexrelease⟩\let\newcatcodetable\@undefined
⟨latexrelease⟩\let\catcodetable@initex\@undefined
⟨latexrelease⟩\let\catcodetable@string\@undefined
⟨latexrelease⟩\let\catcodetable@latex\@undefined
⟨latexrelease⟩\let\catcodetable@atletter\@undefined
⟨latexrelease⟩\let\e@alloc@luafunction@count\@undefined
⟨latexrelease⟩\let\newluafunction\@undefined
⟨latexrelease⟩\let\e@alloc@luafunction@count\@undefined
⟨latexrelease⟩\let\newwhatsit\@undefined
⟨latexrelease⟩\let\e@alloc@whatsit@count\@undefined
⟨latexrelease⟩\let\newluabytecode\@undefined
⟨latexrelease⟩\let\e@alloc@bytecode@count\@undefined
⟨latexrelease⟩\let\newluachunkname\@undefined
⟨latexrelease⟩\let\e@alloc@luachunk@count\@undefined
⟨latexrelease⟩\directlua{luatexbase.uninstall()}
⟨latexrelease⟩\EndIncludeInRelease
```

In `\everyjob`, if luaotfload is available, load it and switch to TU.

```
⟨latexrelease⟩\IncludeInRelease{2017/01/01}%
⟨latexrelease⟩                  {\fontencoding}{TU in everyjob}%
⟨latexrelease⟩\fontencoding{TU}\let\encodingdefault\f@encoding
⟨latexrelease⟩\ifx\directlua\@undefined\else
⟨2ekernel⟩\everyjob\expandafter{%
⟨2ekernel⟩   \the\everyjob
⟨*2ekernel, latexrelease⟩
  \directlua{%
  if xpcall(function ()%
             require('luaotfload-main')%
            end,texio.write_nl) then %
  local _void = luaotfload.main ()%
  else %
  texio.write_nl('Error in luaotfload: reverting to OT1')%
  tex.print('\string\\def\string\\encodingdefault{OT1}')%
  end %
  }%
  \let\f@encoding\encodingdefault
  \expandafter\let\csname ver@luaotfload.sty\endcsname\fmtversion
⟨/2ekernel, latexrelease⟩
⟨latexrelease⟩\fi
⟨2ekernel⟩   }
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\fontencoding}{TU in everyjob}%
⟨latexrelease⟩\fontencoding{OT1}\let\encodingdefault\f@encoding
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨2ekernel | latexrelease⟩\fi
⟨/2ekernel | tex | latexrelease⟩
```

5.10 Lua module preliminaries

```
⟨*lua⟩
```

Some set up for the Lua module which is needed for all of the Lua functionality added here.

`luatexbase` Set up the table for the returned functions. This is used to expose all of the public functions.

```
luatexbase       = luatexbase or { }
local luatexbase = luatexbase
```

(*End definition for* `luatexbase`.)

Some Lua best practice: use local versions of functions where possible.

```
local string_gsub      = string.gsub
local tex_count        = tex.count
local tex_setattribute = tex.setattribute
local tex_setcount     = tex.setcount
local texio_write_nl   = texio.write_nl
local flush_list       = node.flush_list

local luatexbase_warning
local luatexbase_error
```

5.11 Lua module utilities

5.11.1 Module tracking

`modules` To allow tracking of module usage, a structure is provided to store information and to return it.

```
local modules = modules or { }
```

(*End definition for* `modules`.)

`provides_module` Local function to write to the log.

```
local function luatexbase_log(text)
  texio_write_nl("log", text)
end
```

Modelled on `\ProvidesPackage`, we store much the same information but with a little more structure.

```
local function provides_module(info)
  if not (info and info.name) then
    luatexbase_error("Missing module name for provides_module")
  end
  local function spaced(text)
    return text and (" " .. text) or ""
  end
  luatexbase_log(
    "Lua module: " .. info.name
      .. spaced(info.date)
      .. spaced(info.version)
      .. spaced(info.description)
  )
  modules[info.name] = info
end
luatexbase.provides_module = provides_module
```

(*End definition for* `provides_module`.)

5.11.2 Module messages

There are various warnings and errors that need to be given. For warnings we can get exactly the same formatting as from TEX. For errors we have to make some changes. Here we give the text of the error in the LATEX format then force an error from Lua to halt the run. Splitting the message text is done using `\n` which takes the place of `\MessageBreak`.

First an auxiliary for the formatting: this measures up the message leader so we always get the correct indent.

```
local function msg_format(mod, msg_type, text)
  local leader = ""
  local cont
  local first_head
  if mod == "LaTeX" then
    cont = string_gsub(leader, ".", " ")
    first_head = leader .. "LaTeX: "
  else
    first_head = leader .. "Module "  .. msg_type
    cont = "(" .. mod .. ")"
      .. string_gsub(first_head, ".", " ")
    first_head =  leader .. "Module "  .. mod .. " " .. msg_type  .. ":"
  end
  if msg_type == "Error" then
    first_head = "\n" .. first_head
  end
  if string.sub(text,-1) ~= "\n" then
    text = text .. " "
  end
  return first_head .. " "
    .. string_gsub(
         text
 .. "on input line "
         .. tex.inputlineno, "\n", "\n" .. cont .. " "
      )
   .. "\n"
end
```

`module_info`
`module_warning`
`module_error`

Write messages.

```
local function module_info(mod, text)
  texio_write_nl("log", msg_format(mod, "Info", text))
end
luatexbase.module_info = module_info
local function module_warning(mod, text)
  texio_write_nl("term and log",msg_format(mod, "Warning", text))
end
luatexbase.module_warning = module_warning
local function module_error(mod, text)
  error(msg_format(mod, "Error", text))
end
luatexbase.module_error = module_error
```

(*End definition for* `module_info`, `module_warning`, *and* `module_error`.)

Dedicated versions for the rest of the code here.

```
function luatexbase_warning(text)
  module_warning("luatexbase", text)
end
function luatexbase_error(text)
  module_error("luatexbase", text)
end
```

5.12 Accessing register numbers from Lua

Collect up the data from the TEX level into a Lua table: from version 0.80, LuaTEX makes that easy.

```
local luaregisterbasetable = { }
local registermap = {
  attributezero = "assign_attr"    ,
  charzero      = "char_given"     ,
  CountZero     = "assign_int"     ,
  dimenzero     = "assign_dimen"   ,
  mathcharzero  = "math_given"     ,
  muskipzero    = "assign_mu_skip" ,
  skipzero      = "assign_skip"    ,
  tokszero      = "assign_toks"    ,
}
local createtoken
if tex.luatexversion > 81 then
  createtoken = token.create
elseif tex.luatexversion > 79 then
  createtoken = newtoken.create
end
local hashtokens    = tex.hashtokens()
local luatexversion = tex.luatexversion
for i,j in pairs (registermap) do
  if luatexversion < 80 then
    luaregisterbasetable[hashtokens[i][1]] =
      hashtokens[i][2]
  else
    luaregisterbasetable[j] = createtoken(i).mode
  end
end
```

`registernumber` Working out the correct return value can be done in two ways. For older LuaTEX releases it has to be extracted from the `hashtokens`. On the other hand, newer LuaTEX's have `newtoken`, and whilst `.mode` isn't currently documented, Hans Hagen pointed to this approach so we should be OK.

```
local registernumber
if luatexversion < 80 then
  function registernumber(name)
    local nt = hashtokens[name]
    if(nt and luaregisterbasetable[nt[1]]) then
      return nt[2] - luaregisterbasetable[nt[1]]
    else
      return false
    end
  end
```

```
else
  function registernumber(name)
    local nt = createtoken(name)
    if(luaregisterbasetable[nt.cmdname]) then
      return nt.mode - luaregisterbasetable[nt.cmdname]
    else
      return false
    end
  end
end
luatexbase.registernumber = registernumber
```

(*End definition for* `registernumber`.)

5.13 Attribute allocation

`new_attribute` As attributes are used for Lua manipulations its useful to be able to assign from this end.

```
local attributes=setmetatable(
{},
{
__index = function(t,key)
return registernumber(key) or nil
end}
)
luatexbase.attributes = attributes
```

```
local attribute_count_name =
                      attribute_count_name or "e@alloc@attribute@count"
local function new_attribute(name)
  tex_setcount("global", attribute_count_name,
                          tex_count[attribute_count_name] + 1)
  if tex_count[attribute_count_name] > 65534 then
    luatexbase_error("No room for a new \\attribute")
  end
  attributes[name]= tex_count[attribute_count_name]
  luatexbase_log("Lua-only attribute " .. name .. " = " ..
                 tex_count[attribute_count_name])
  return tex_count[attribute_count_name]
end
luatexbase.new_attribute = new_attribute
```

(*End definition for* `new_attribute`.)

5.14 Custom whatsit allocation

`new_whatsit` Much the same as for attribute allocation in Lua.

```
local whatsit_count_name = whatsit_count_name or "e@alloc@whatsit@count"
local function new_whatsit(name)
  tex_setcount("global", whatsit_count_name,
                          tex_count[whatsit_count_name] + 1)
  if tex_count[whatsit_count_name] > 65534 then
    luatexbase_error("No room for a new custom whatsit")
  end
  luatexbase_log("Custom whatsit " .. (name or "") .. " = " ..
```

```
                  tex_count[whatsit_count_name])
  return tex_count[whatsit_count_name]
end
luatexbase.new_whatsit = new_whatsit
```

(*End definition for* `new_whatsit`.)

5.15 Bytecode register allocation

`new_bytecode` Much the same as for attribute allocation in Lua. The optional ⟨*name*⟩ argument is used in the log if given.

```
local bytecode_count_name =
                          bytecode_count_name or "e@alloc@bytecode@count"
local function new_bytecode(name)
  tex_setcount("global", bytecode_count_name,
                          tex_count[bytecode_count_name] + 1)
  if tex_count[bytecode_count_name] > 65534 then
    luatexbase_error("No room for a new bytecode register")
  end
  luatexbase_log("Lua bytecode " .. (name or "") .. " = " ..
                  tex_count[bytecode_count_name])
  return tex_count[bytecode_count_name]
end
luatexbase.new_bytecode = new_bytecode
```

(*End definition for* `new_bytecode`.)

5.16 Lua chunk name allocation

`new_chunkname` As for bytecode registers but also store the name in the `lua.name` table.

```
local chunkname_count_name =
                         chunkname_count_name or "e@alloc@luachunk@count"
local function new_chunkname(name)
  tex_setcount("global", chunkname_count_name,
                          tex_count[chunkname_count_name] + 1)
  local chunkname_count = tex_count[chunkname_count_name]
  chunkname_count = chunkname_count + 1
  if chunkname_count > 65534 then
    luatexbase_error("No room for a new chunkname")
  end
  lua.name[chunkname_count]=name
  luatexbase_log("Lua chunkname " .. (name or "") .. " = " ..
                  chunkname_count .. "\n")
  return chunkname_count
end
luatexbase.new_chunkname = new_chunkname
```

(*End definition for* `new_chunkname`.)

5.17 Lua function allocation

`new_luafunction` Much the same as for attribute allocation in Lua. The optional ⟨*name*⟩ argument is used in the log if given.

```
local luafunction_count_name =
                        luafunction_count_name or "e@alloc@luafunction@count"
local function new_luafunction(name)
  tex_setcount("global", luafunction_count_name,
                        tex_count[luafunction_count_name] + 1)
  if tex_count[luafunction_count_name] > 65534 then
    luatexbase_error("No room for a new luafunction register")
  end
  luatexbase_log("Lua function " .. (name or "") .. " = " ..
                 tex_count[luafunction_count_name])
  return tex_count[luafunction_count_name]
end
luatexbase.new_luafunction = new_luafunction
```

(*End definition for* `new_luafunction`.)

5.18 Lua callback management

The native mechanism for callbacks in LuaTEX allows only one per function. That is extremely restrictive and so a mechanism is needed to add and remove callbacks from the appropriate hooks.

5.18.1 Housekeeping

The main table: keys are callback names, and values are the associated lists of functions. More precisely, the entries in the list are tables holding the actual function as `func` and the identifying description as `description`. Only callbacks with a non-empty list of functions have an entry in this list.

```
local callbacklist = callbacklist or { }
```

Numerical codes for callback types, and name-to-value association (the table keys are strings, the values are numbers).

```
local list, data, exclusive, simple, reverselist = 1, 2, 3, 4, 5
local types   = {
  list        = list,
  data        = data,
  exclusive   = exclusive,
  simple      = simple,
  reverselist = reverselist,
}
```

Now, list all predefined callbacks with their current type, based on the LuaTEX manual version 1.01. A full list of the currently-available callbacks can be obtained using

```
\directlua{
  for i,_ in pairs(callback.list()) do
    texio.write_nl("- " .. i)
  end
}
\bye
```

in plain LuaTEX. (Some undocumented callbacks are omitted as they are to be removed.)

```
local callbacktypes = callbacktypes or {
```

Section 8.2: file discovery callbacks.

```
  find_read_file     = exclusive,
  find_write_file    = exclusive,
  find_font_file     = data,
  find_output_file   = data,
  find_format_file   = data,
  find_vf_file       = data,
  find_map_file      = data,
  find_enc_file      = data,
  find_pk_file       = data,
  find_data_file     = data,
  find_opentype_file = data,
  find_truetype_file = data,
  find_type1_file    = data,
  find_image_file    = data,

  open_read_file     = exclusive,
  read_font_file     = exclusive,
  read_vf_file       = exclusive,
  read_map_file      = exclusive,
  read_enc_file      = exclusive,
  read_pk_file       = exclusive,
  read_data_file     = exclusive,
  read_truetype_file = exclusive,
  read_type1_file    = exclusive,
  read_opentype_file = exclusive,
```

Not currently used by luatex but included for completeness. may be used by a font handler.

```
  find_cidmap_file   = data,
  read_cidmap_file   = exclusive,
```

Section 8.3: data processing callbacks.

```
  process_input_buffer  = data,
  process_output_buffer = data,
  process_jobname       = data,
```

Section 8.4: node list processing callbacks.

```
  contribute_filter      = simple,
  buildpage_filter       = simple,
  build_page_insert      = exclusive,
  pre_linebreak_filter   = list,
  linebreak_filter       = exclusive,
  append_to_vlist_filter = exclusive,
  post_linebreak_filter  = reverselist,
  hpack_filter           = list,
  vpack_filter           = list,
  hpack_quality          = exclusive,
  vpack_quality          = exclusive,
  pre_output_filter      = list,
  process_rule           = exclusive,
  hyphenate              = simple,
```

```
  ligaturing             = simple,
  kerning                = simple,
  insert_local_par       = simple,
  pre_mlist_to_hlist_filter = list,
  mlist_to_hlist         = exclusive,
  post_mlist_to_hlist_filter = reverselist,
  new_graf               = exclusive,
```

Section 8.5: information reporting callbacks.

```
  pre_dump             = simple,
  start_run            = simple,
  stop_run             = simple,
  start_page_number    = simple,
  stop_page_number     = simple,
  show_error_hook      = simple,
  show_warning_message = simple,
  show_error_message   = simple,
  show_lua_error_hook  = simple,
  start_file           = simple,
  stop_file            = simple,
  call_edit            = simple,
  finish_synctex       = simple,
  wrapup_run           = simple,
```

Section 8.6: PDF-related callbacks.

```
  finish_pdffile            = data,
  finish_pdfpage            = data,
  page_objnum_provider      = data,
  page_order_index          = data,
  process_pdf_image_content = data,
```

Section 8.7: font-related callbacks.

```
  define_font                     = exclusive,
  glyph_info                      = exclusive,
  glyph_not_found                 = exclusive,
  glyph_stream_provider           = exclusive,
  make_extensible                 = exclusive,
  font_descriptor_objnum_provider = exclusive,
  input_level_string              = exclusive,
  provide_charproc_data           = exclusive,

}
luatexbase.callbacktypes=callbacktypes
```

`callback.register` Save the original function for registering callbacks and prevent the original being used. The original is saved in a place that remains available so other more sophisticated code can override the approach taken by the kernel if desired.

```
local callback_register = callback_register or callback.register
function callback.register()
  luatexbase_error("Attempt to use callback.register() directly\n")
end
```

(*End definition for* `callback.register`.)

5.18.2 Handlers

The handler function is registered into the callback when the first function is added to this callback's list. Then, when the callback is called, the handler takes care of running all functions in the list. When the last function is removed from the callback's list, the handler is unregistered.

More precisely, the functions below are used to generate a specialized function (closure) for a given callback, which is the actual handler.

The way the functions are combined together depends on the type of the callback. There are currently 4 types of callback, depending on the calling convention of the functions the callback can hold:

simple is for functions that don't return anything: they are called in order, all with the same argument;

data is for functions receiving a piece of data of any type except node list head (and possibly other arguments) and returning it (possibly modified): the functions are called in order, and each is passed the return value of the previous (and the other arguments untouched, if any). The return value is that of the last function;

list is a specialized variant of *data* for functions filtering node lists. Such functions may return either the head of a modified node list, or the boolean values `true` or `false`. The functions are chained the same way as for *data* except that for the following. If one function returns `false`, then `false` is immediately returned and the following functions are *not* called. If one function returns `true`, then the same head is passed to the next function. If all functions return `true`, then `true` is returned, otherwise the return value of the last function not returning `true` is used.

reverselist is a specialized variant of *list* which executes functions in inverse order.

exclusive is for functions with more complex signatures; functions in this type of callback are *not* combined: An error is raised if a second callback is registered.

Handler for `data` callbacks.

```
local function data_handler(name)
  return function(data, ...)
    for _,i in ipairs(callbacklist[name]) do
      data = i.func(data,...)
    end
    return data
  end
end
```

Default for user-defined `data` callbacks without explicit default.

```
local function data_handler_default(value)
  return value
end
```

Handler for `exclusive` callbacks. We can assume `callbacklist[name]` is not empty: otherwise, the function wouldn't be registered in the callback any more.

```
local function exclusive_handler(name)
  return function(...)
    return callbacklist[name][1].func(...)
  end
end
```

Handler for `list` callbacks.

```
local function list_handler(name)
  return function(head, ...)
    local ret
    for _,i in ipairs(callbacklist[name]) do
      ret = i.func(head, ...)
      if ret == false then
        luatexbase_warning(
          "Function ‘" .. i.description .. "’ returned false\n"
            .. "in callback ‘" .. name .."’"
         )
        return false
      end
      if ret ~= true then
        head = ret
      end
    end
    return head
  end
end
```

Default for user-defined `list` and `reverselist` callbacks without explicit default.

```
local function list_handler_default(head)
return head
end
```

Handler for `reverselist` callbacks.

```
local function reverselist_handler(name)
  return function(head, ...)
    local ret
    local callbacks = callbacklist[name]
    for i = #callbacks, 1, -1 do
      local cb = callbacks[i]
      ret = cb.func(head, ...)
      if ret == false then
        luatexbase_warning(
          "Function ‘" .. cb.description .. "’ returned false\n"
            .. "in callback ‘" .. name .."’"
         )
        return false
      end
      if ret ~= true then
        head = ret
      end
    end
    return head
  end
end
```

Handler for `simple` callbacks.

```
local function simple_handler(name)
  return function(...)
    for _,i in ipairs(callbacklist[name]) do
      i.func(...)
    end
```

```
  end
end
```

Default for user-defined `simple` callbacks without explicit default.

```
local function simple_handler_default()
end
```

Keep a handlers table for indexed access and a table with the corresponding default functions.

```
local handlers  = {
  [data]        = data_handler,
  [exclusive]   = exclusive_handler,
  [list]        = list_handler,
  [reverselist] = reverselist_handler,
  [simple]      = simple_handler,
}
local defaults = {
  [data]        = data_handler_default,
  [exclusive]   = nil,
  [list]        = list_handler_default,
  [reverselist] = list_handler_default,
  [simple]      = simple_handler_default,
}
```

5.18.3 Public functions for callback management

Defining user callbacks perhaps should be in package code, but impacts on `add_to_callback`. If a default function is not required, it may be declared as `false`. First we need a list of user callbacks.

```
local user_callbacks_defaults = {
  pre_mlist_to_hlist_filter = list_handler_default,
  mlist_to_hlist = node.mlist_to_hlist,
  post_mlist_to_hlist_filter = list_handler_default,
}
```

`create_callback` The allocator itself.

```
local function create_callback(name, ctype, default)
  local ctype_id = types[ctype]
  if not name  or name  == ""
  or not ctype_id
  then
    luatexbase_error("Unable to create callback:\n" ..
                     "valid callback name and type required")
  end
  if callbacktypes[name] then
    luatexbase_error("Unable to create callback ‘" .. name ..
                     "’:\ncallback is already defined")
  end
  default = default or defaults[ctype_id]
  if not default then
    luatexbase_error("Unable to create callback ‘" .. name ..
                     "’:\ndefault is required for ‘" .. ctype ..
                     "’ callbacks")
  elseif type (default) ~= "function" then
```

```
    luatexbase_error("Unable to create callback ‘" .. name ..
                     "’:\ndefault is not a function")
  end
  user_callbacks_defaults[name] = default
  callbacktypes[name] = ctype_id
end
luatexbase.create_callback = create_callback
```

(*End definition for* `create_callback`.)

`call_callback` Call a user defined callback. First check arguments.

```
local function call_callback(name,...)
  if not name or name == "" then
    luatexbase_error("Unable to create callback:\n" ..
                     "valid callback name required")
  end
  if user_callbacks_defaults[name] == nil then
    luatexbase_error("Unable to call callback ‘" .. name
                     .. "’:\nunknown or empty")
   end
  local l = callbacklist[name]
  local f
  if not l then
    f = user_callbacks_defaults[name]
  else
    f = handlers[callbacktypes[name]](name)
  end
  return f(...)
end
luatexbase.call_callback=call_callback
```

(*End definition for* `call_callback`.)

`add_to_callback` Add a function to a callback. First check arguments.

```
local function add_to_callback(name, func, description)
  if not name or name == "" then
    luatexbase_error("Unable to register callback:\n" ..
                     "valid callback name required")
  end
  if not callbacktypes[name] or
    type(func) ~= "function" or
    not description or
    description == "" then
    luatexbase_error(
      "Unable to register callback.\n\n"
        .. "Correct usage:\n"
        .. "add_to_callback(<callback>, <function>, <description>)"
    )
  end
```

Then test if this callback is already in use. If not, initialise its list and register the proper handler.

```
  local l = callbacklist[name]
  if l == nil then
    l = { }
    callbacklist[name] = l
```

If it is not a user defined callback use the primitive callback register.

```
    if user_callbacks_defaults[name] == nil then
      callback_register(name, handlers[callbacktypes[name]](name))
    end
  end
```

Actually register the function and give an error if more than one `exclusive` one is registered.

```
  local f = {
    func        = func,
    description = description,
  }
  local priority = #l + 1
  if callbacktypes[name] == exclusive then
    if #l == 1 then
      luatexbase_error(
        "Cannot add second callback to exclusive function\n‘" ..
        name .. "’")
    end
  end
  table.insert(l, priority, f)
```

Keep user informed.

```
  luatexbase_log(
    "Inserting ‘" .. description .. "’ at position "
      .. priority .. " in ‘" .. name .. "’."
  )
end
luatexbase.add_to_callback = add_to_callback
```

(*End definition for* `add_to_callback`.)

`remove_from_callback` Remove a function from a callback. First check arguments.

```
local function remove_from_callback(name, description)
  if not name or name == "" then
    luatexbase_error("Unable to remove function from callback:\n" ..
                     "valid callback name required")
  end
  if not callbacktypes[name] or
    not description or
    description == "" then
    luatexbase_error(
      "Unable to remove function from callback.\n\n"
        .. "Correct usage:\n"
        .. "remove_from_callback(<callback>, <description>)"
    )
  end
  local l = callbacklist[name]
  if not l then
    luatexbase_error(
      "No callback list for ‘" .. name .. "’\n")
  end
```

Loop over the callback's function list until we find a matching entry. Remove it and check if the list is empty: if so, unregister the callback handler.

```
  local index = false
  for i,j in ipairs(l) do
    if j.description == description then
      index = i
      break
    end
  end
  if not index then
    luatexbase_error(
      "No callback ‘" .. description .. "’ registered for ‘" ..
      name .. "’\n")
  end
  local cb = l[index]
  table.remove(l, index)
  luatexbase_log(
    "Removing  ‘" .. description .. "’ from ‘" .. name .. "’."
  )
  if #l == 0 then
    callbacklist[name] = nil
    if user_callbacks_defaults[name] == nil then
      callback_register(name, nil)
    end
  end
  return cb.func,cb.description
end
luatexbase.remove_from_callback = remove_from_callback
```

(*End definition for* `remove_from_callback`.)

`in_callback` Look for a function description in a callback.

```
local function in_callback(name, description)
  if not name
    or name == ""
    or not callbacklist[name]
    or not callbacktypes[name]
    or not description then
      return false
  end
  for _, i in pairs(callbacklist[name]) do
    if i.description == description then
      return true
    end
  end
  return false
end
luatexbase.in_callback = in_callback
```

(*End definition for* `in_callback`.)

`disable_callback` As we subvert the engine interface we need to provide a way to access this functionality.

```
local function disable_callback(name)
  if(callbacklist[name] == nil) then
    callback_register(name, false)
  else
    luatexbase_error("Callback list for " .. name .. " not empty")
```

```
  end
end
luatexbase.disable_callback = disable_callback
```

(*End definition for* `disable_callback`.)

`callback_descriptions` List the descriptions of functions registered for the given callback.

```
local function callback_descriptions (name)
  local d = {}
  if not name
    or name == ""
    or not callbacklist[name]
    or not callbacktypes[name]
    then
    return d
  else
  for k, i in pairs(callbacklist[name]) do
    d[k]= i.description
    end
  end
  return d
end
luatexbase.callback_descriptions =callback_descriptions
```

(*End definition for* `callback_descriptions`.)

`uninstall` Unlike at the TEX level, we have to provide a back-out mechanism here at the same time as the rest of the code. This is not meant for use by anything other than latexrelease: as such this is *deliberately* not documented for users!

```
local function uninstall()
  module_info(
    "luatexbase",
    "Uninstalling kernel luatexbase code"
  )
  callback.register = callback_register
  luatexbase = nil
end
luatexbase.uninstall = uninstall
```

(*End definition for* `uninstall`.)

`mlist_to_hlist` To emulate these callbacks, the "real" `mlist_to_hlist` is replaced by a wrapper calling the wrappers before and after.

```
callback_register("mlist_to_hlist", function(head, display_type, need_penalties)
  local current = call_callback("pre_mlist_to_hlist_filter", head, display_type, need_penalti
  if current == false then
    flush_list(head)
    return nil
  end
  current = call_callback("mlist_to_hlist", current, display_type, need_penalties)
  local post = call_callback("post_mlist_to_hlist_filter", current, display_type, need_penalt
  if post == false then
    flush_list(current)
    return nil
```

```
  end
  return post
end)
```

(*End definition for* `mlist_to_hlist`.)

```
⟨/lua⟩
```

Reset the catcode of `@`.

```
⟨tex⟩\catcode`\@=\etatcatcode\relax
```

File e
ltexpl.dtx

1 expl3-dependent code

1.1 Loader

\@kernel@after@enddocument
\@kernel@after@enddocument@afterlastpage

These two kernel hooks are used by the shipout code. They are defined earlier here because the lthooks code adds material to them.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩  {kernel@enddocument hooks}{Define several kernel hooks}
```

We only initialize these kernel hooks if they are not already existing. Otherwise they would be set to \@empty on rollback which would be wrong because code that has been added to them may still have to be executed in the rollback situation . Instead code that writes to them needs to handle the rollback as needed. It is likely that we have to change that approach in the future, but for now it should do. (It is enough to test only for the existence of one hook, as all got added at the same time.)

```
\ifx\@kernel@after@enddocument\@undefined
  \let \@kernel@after@enddocument               \@empty
  \let \@kernel@after@enddocument@afterlastpage \@empty
```

For the similar reasons we also define those that are used in \document because they too get material added to in early modules.

\@kernel@before@begindocument
\@kernel@after@begindocument

```
  \let \@kernel@before@begindocument \@empty
  \let \@kernel@after@begindocument  \@empty
\fi
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩  {kernel@enddocument hooks}{Define several kernel hooks}
⟨latexrelease⟩\let\@kernel@after@enddocument\@undefined
⟨latexrelease⟩\let\@kernel@after@enddocument@afterlastpage\@undefined
⟨latexrelease⟩\let\@kernel@before@begindocument\@undefined
⟨latexrelease⟩\let\@kernel@after@begindocument\@undefined
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* \@kernel@after@enddocument *and others.*)

First define some blank commands, so that in case something goes wrong while loading expl3, we won't get strange Undefined control sequence errors.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩            {\@expl@sys@load@backend@@}{Roll forward support}%
\def\reserved@a#1{\ifdefined#1\else\def#1{}\fi}
\reserved@a\@expl@sys@load@backend@@
\reserved@a\@expl@push@filename@@
\reserved@a\@expl@push@filename@aux@@
\reserved@a\@expl@pop@filename@@
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
```

Create a hook for last-minute expl3 material.

```
⟨*2ekernel⟩
\def\@expl@finalise@setup@@{}
⟨/2ekernel⟩
```

Now define some basics to support loading expl3. These macros can be defined here safely, because they are redefined later on by the kernel, so we define simpler versions just to suit our needs.

```
⟨*2ekernel⟩
\long\def\@gobble#1{}
\long\def\@firstofone#1{#1}
\long\def\@firstoftwo#1#2{#1}
\long\def\@secondoftwo#1#2{#2}
\long\def\IfFileExists#1{%
  \openin\@inputcheck"#1" %
  \ifeof\@inputcheck
    \expandafter\@secondoftwo
  \else
    \closein\@inputcheck
    \expandafter\@firstoftwo
  \fi}
\long\def\@ifnextchar#1#2#3{%
  \let\reserved@d=#1%
  \def\reserved@a{#2}%
  \def\reserved@b{#3}%
  \futurelet\@let@token\@ifnch}
\def\@ifnch{%
  \ifx\@let@token\reserved@d
    \expandafter\reserved@a
  \else
    \expandafter\reserved@b
  \fi}
⟨/2ekernel⟩
```

If we are doing a rollback with a format containing expl3 we aren't reloading it as that creates havoc. This may need a refined version!

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {expl3}{Pre-load expl3}%
\expandafter\ifx\csname tex\string _let:D\endcsname\relax
  \expandafter\@firstofone
\else
  \GenericInfo{}{Skipping: expl3 code already part of the format}%
⟨2ekernel⟩   \expandafter\endinput
⟨latexrelease⟩   \expandafter\@gobble
\fi
```

Check for the required primitive/engine support and the existence of a loader.

```
 {%
   \IfFileExists{expl3.ltx}
     {%
       \ifnum0%
         \ifdefined\pdffilesize 1\fi
         \ifdefined\filesize 1\fi
         \ifdefined\luatexversion\ifnum\luatexversion>94 1\fi\fi
```

```
          \ifdefined\kanjiskip 1\fi
            >0 %
          \expandafter\@firstofone
        \else
```

In 2ekernel mode, an error is fatal and building the format is aborted. Use `\batchmode \read -1 to \tokenlist`, which errors with

```
! Emergency stop. (cannot \read from terminal in nonstop modes)
```

and aborts the TEX run. In latexrelease mode, raise an error and do nothing. Both ways, the error message shows the minimum expl3 engine requirements.

```
⟨2ekernel⟩          \def~{ }\def\MessageBreak{^^J~~~~~~~~~~~~~~~}%
⟨2ekernel⟩          \errmessage{LaTeX Error:
⟨latexrelease⟩         \@latex@error{%
            LaTeX requires the e-TeX primitives and additional\MessageBreak
            functionality available in the engines:\MessageBreak
              - pdfTeX v1.40\MessageBreak
              - XeTeX v0.99992\MessageBreak
              - LuaTeX v0.95\MessageBreak
              - e-(u)pTeX mid-2012\MessageBreak
            or later%
⟨latexrelease⟩         }\@ehd \expandafter\@gobble
⟨2ekernel⟩          }\batchmode \read -1 to \reserved@a
        \fi
      }
      {%
⟨*2ekernel⟩
        \errmessage{LaTeX requires expl3}%
        \batchmode \read -1 to \reserved@a
⟨/2ekernel⟩
```

We do not support a roll forward across 2019. You need to start with 2019 if you want to get to 2020 or beyond.

```
⟨*latexrelease⟩
        \@latex@warning@no@line
          {You need a format that already contains a recent\MessageBreak
           expl3 as part of the kernel, e.g. at least a kernel\MessageBreak
           from 2019 to roll forward to that date!\MessageBreak
           --- I'm giving up!\MessageBreak\MessageBreak
           Note that manually loading the expl3 package\MessageBreak
           from your distribution is not enough}%
        \batchmode \read -1 to \reserved@a
⟨/latexrelease⟩
      }%
      {\input expl3.ltx }%
  }
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
```

To support roll-forward for the case where xparse is fully integrated into the kernel, we do not need to repeat the complex test above as we can simply look for the marker command.

```
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {expl3}{Pre-load expl3}%
```

```
⟨latexrelease⟩\IfFileExists{expl3.ltx}
⟨latexrelease⟩  {%
⟨latexrelease⟩    \ifnum0%
⟨latexrelease⟩      \ifdefined\pdffilesize 1\fi
⟨latexrelease⟩      \ifdefined\filesize 1\fi
⟨latexrelease⟩      \ifdefined\luatexversion\ifnum\luatexversion>94 1\fi\fi
⟨latexrelease⟩      >0 %
⟨latexrelease⟩    \else
⟨latexrelease⟩      \message{Skipping expl3-dependent extensions}
⟨latexrelease⟩      \expandafter\@gobbletwo
⟨latexrelease⟩    \fi
⟨latexrelease⟩  }
⟨latexrelease⟩  {%
⟨latexrelease⟩    \message{Skipping expl3-dependent extensions}%
⟨latexrelease⟩    \@gobbletwo
⟨latexrelease⟩  }%
⟨latexrelease⟩\input{expl3.ltx}
⟨latexrelease⟩\EndIncludeInRelease
```

Now in `latexrelease` mode, redefine a few commands to avoid "already defined" errors.

```
⟨latexrelease⟩\@ifundefined{ExplSyntaxOff}{}{\latexrelease@postltexpl}
```

1.2 Using expl3 code

In order to ease the implementation of some new features in LaTeX 2_ε we may (temporarily) use some coding based on the expl3-code. Such macros will eventually vanish and may be changed unannounced. They are there for internal use in the LaTeX 2_ε kernel and are not meant to be used in third-party packages. These macros will always have the `@expl@` prefix in their name.

The rest of the name matches the expl3 name but with all underscores replaced by `@`s and the `:` replaced by `@@`, e.g.,

```
\cs_new_eq:NN \@expl@tl@trim@spaces@apply@@nN \tl_trim_spaces_apply:nN
```

if that expl3 command is needed in places that are others coded in LaTeX 2_ε conventions.

In this file, each release of LaTeX adds an `\IncludeInRelease` block, in which the macros copied for that release were defined. In case a rollback is requested, the entire block is changed.

Each macro copied has a `\changes` entry to explain when and why it was copied, so that further to that may spot it easily.

Here `\cs_gset_eq:NN` is used, instead of the `new` variant because if different releases use that same name for different purposes, each can copy the macro without worrying about redefinitions.

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\@expl@cs@to@str@@N}%
⟨latexrelease⟩        {expl3 macros added for the 2020-10-01 release}%
```

The expl3 activation needs to be inside the release guards as otherwise rolling forward is broken in old kernels that do not have expl3 loaded.

```
\ExplSyntaxOn
```

```
\cs_gset_eq:NN \@expl@cs@to@str@@N \cs_to_str:N
\cs_gset_eq:NN \@expl@str@if@eq@@nnTF \str_if_eq:nnTF
```

```
\cs_gset_eq:NN \@expl@cs@prefix@spec@@N \cs_prefix_spec:N
\cs_gset_eq:NN \@expl@cs@argument@spec@@N \cs_argument_spec:N
\cs_gset_eq:NN \@expl@cs@replacement@spec@@N \cs_replacement_spec:N

\cs_gset_eq:NN \@expl@str@map@function@@NN \str_map_function:NN
\cs_gset_eq:NN \@expl@char@generate@@nn \char_generate:nn

\ExplSyntaxOff
```

Here we can't assume that expl3 is available. It will be if we roll back but if this code is executed rolling forward it needs to be pure 2e.

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@expl@cs@to@str@@N}%
⟨latexrelease⟩        {expl3 macros added for the 2020-10-01 release}%
⟨latexrelease⟩\let \@expl@cs@to@str@@N \@undefined
⟨latexrelease⟩\let \@expl@str@if@eq@@nnTF \@undefined
⟨latexrelease⟩\let \@expl@cs@prefix@spec@@N \@undefined
⟨latexrelease⟩\let \@expl@cs@argument@spec@@N \@undefined
⟨latexrelease⟩\let \@expl@cs@replacement@spec@@N \@undefined
⟨latexrelease⟩\let \@expl@str@map@function@@NN \@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
```

2 Document-level command names for expl3 functions

Current home for L3 programing layer functions that we make directly available at the document level. This section may need to be moved later (after `\NewDocumentCommand` is defined in case we want to use that in the setup).

`\fpeval` The expandable command `\fpeval` takes as its argument a floating point expression and produces a result using the normal rules of mathematics. As this command is expandable it can be used where TEX requires a number and for example within a low-level `\edef` operation to give a purely numerical result. See `usrguide3` for further explanation.

`\inteval` `\dimeval` `\skipeval` The expandable command `\inteval` takes as its argument an integer expression and produces a result using the normal rules of mathematics. The operations recognised are `+`, `-`, `*` and `/` plus parentheses. Division occurs with *rounding*, and ties are rounded away from zero. As this command is expandable it can be used where TEX requires a number and for example within a low-level `\edef` operation to give a purely numerical result. See `usrguide3` for further explanation. `\dimeval` and `\skipeval` are similar, but generate fixed and rubber length values, respectively.

`\fpeval` `\inteval` `\dimeval` `\skipeval` A document level wrapper around the code level function for floating point calculations.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                    {\fpeval}{fp and int calculations}%
\ExplSyntaxOn
\cs_new_eq:NN \fpeval \fp_eval:n
```

And a few more, this time wrappers around the eTEX primitives.

```
\cs_new_eq:NN \inteval \int_eval:n
```

```
\cs_new_eq:NN \dimeval  \dim_eval:n
\cs_new_eq:NN \skipeval \skip_eval:n
\ExplSyntaxOff
```

(*End definition for* `\fpeval` *and others.*)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\fpeval}{fp and int calculations}%
⟨latexrelease⟩
⟨latexrelease⟩\let\fpeval\@undefined
⟨latexrelease⟩\let\inteval\@undefined
⟨latexrelease⟩\let\dimeval\@undefined
⟨latexrelease⟩\let\skipeval\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

`\UseName` `\ExpandArgs` When declaring new commands with `\NewDocumentCommand` or `\NewCommandCopy` or similar, it is sometimes necessary to "construct" the csname. As a general mechanism the L3 programming layer has `\exp_args:N...` for this, but there is no mechanism for it if `\ExplSyntaxOn` is not active. We therefore offer a few of these commands also with CamelCase names.

`\UseName` `\ExpandArgs` A document wrapper for changing arguments to cs names for use with `\NewDocumentCommand` and similar functions.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                 {\ExpandArgs}{Some pre-expansion commands}%
\ExplSyntaxOn
\cs_new_eq:NN \UseName \use:c
```

```
\cs_new:Npn \ExpandArgs #1
  {
    \cs_if_exist_use:cF { exp_args:N #1 }
      { \msg_expandable_error:nnn { kernel } { unknown-arg-expansion } {#1} }
  }
\msg_new:nnn { kernel } { unknown-arg-expansion }
  { Unknown~arg~expansion~"#1" }
\ExplSyntaxOff
```

(*End definition for* `\UseName` *and* `\ExpandArgs`*.*)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\ExpandArgs}{Some pre-expansion commands}%
⟨latexrelease⟩
⟨latexrelease⟩\let\UseName\@undefined
⟨latexrelease⟩\let\ExpandArgs\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

File f
ltdefns.dtx

1 Definitions

This section contains commands used in defining other macros.

```
⟨*2ekernel⟩
```

1.1 Initex initializations

`\two@digits` Prefix a number less than 10 with '0'.

```
\def\two@digits#1{\ifnum#1<10 0\fi\number#1}
```

(*End definition for* `\two@digits`.)

`\typeout` Display something on the terminal.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\typeout}{Allow "par" in \typeout}%
\protected\long\def\typeout#1{\begingroup
  \set@display@protect
  \def\par{^^J^^J}%
  \immediate\write\@unused{#1}\endgroup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\typeout}{Allow "par" in \typeout}%
⟨latexrelease⟩
⟨latexrelease⟩\def\typeout#1{\begingroup\set@display@protect
⟨latexrelease⟩    \immediate\write\@unused{#1}\endgroup}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\typeout`.)

`\newlinechar` A char to be used as new-line in output to files.

```
\newlinechar`\^^J
```

(*End definition for* `\newlinechar`.)

1.2 Saved versions of TEX primitives

The TeX primitive `\foo` is saved as `\@@foo`. The following primitives are handled in this way:

`\@@par`

```
\let\@@par=\par
%\let\@@input=\input    %%% moved earlier
%\let\@@end=\end        %%%
```

(*End definition for* `\@@par`.)

\@@hyph Save original primitive definition.

```
\let\@@hyph=\-
```

(*End definition for* `\@@hyph`.)

\@@italiccorr Save the original italic correction.

```
\let\@@italiccorr=\/
```

(*End definition for* `\@@italiccorr`.)

\@height
\@depth
\@width
\@minus
\@plus

The following definitions save token space. E.g., using `\@height` instead of height saves 5 tokens at the cost in time of one macro expansion.

```
\def\@height{height} \def\@depth{depth} \def\@width{width}
\def\@minus{minus}
\def\@plus{plus}
```

The next one is another 100 tokens worth.

```
\def\hb@xt@{\hbox to}
```

(*End definition for* `\@height` *and others.*)

```
\message{hacks,}
```

\hb@xt@

1.3 Command definitions

This section defines the following commands:

\@namedef `{`⟨*NAME*⟩`}`
Expands to `\def\{`⟨*NAME*⟩`}`, except name can contain any characters.

\@nameuse `{`⟨*NAME*⟩`}`
Expands to `\{`⟨*NAME*⟩`}`.

\@ifnextchar X`{`⟨*YES*⟩`}{`⟨*NO*⟩`}`
Expands to ⟨*YES*⟩ if next character is an 'X', and to ⟨*NO*⟩ otherwise. (Uses `\reserved@a`–`\reserved@c`.) NOTE: GOBBLES ANY SPACE FOLLOWING IT.

\@ifstar `{`⟨*YES*⟩`}{`⟨*NO*⟩`}`
Gobbles following spaces and then tests if next the character is a '*'. If it is, then it gobbles the '*' and expands to ⟨*YES*⟩, otherwise it expands to ⟨*NO*⟩.

\@dblarg `{`⟨*CMD*⟩`}{`⟨*ARG*⟩`}`
Expands to `\{`⟨*CMD*⟩`}[`⟨*ARG*⟩`]{`⟨*ARG*⟩`}`. Use `\@dblarg\CS` when `\CS` takes arguments `[ARG1]{ARG2}`, where default is `ARG1` = `ARG2`.

\@ifundefined `{`⟨*NAME*⟩`}{`⟨*YES*⟩`}{`⟨*NO*⟩`}`
: If `\NAME` is undefined then it executes ⟨*YES*⟩, otherwise it executes ⟨*NO*⟩. More precisely, true if `\NAME` either undefined or = `\relax`.

\@ifdefinable `\NAME{`⟨*YES*⟩`}` Executes ⟨*YES*⟩ if the user is allowed to define `\NAME`, otherwise it gives an error. The user can define `\NAME` if `\@ifundefined{NAME}` is true, '`NAME`' ≠ '`relax`' and the first three letters of '`NAME`' are not '`end`', and if `\endNAME` is not defined.

\newcommand `*{`⟨`\FOO`⟩`}[`⟨*i*⟩`]{`⟨*TEXT*⟩`}`
User command to define `\FOO` to be a macro with i arguments (i = 0 if missing) having the definition ⟨*TEXT*⟩. Produces an error if `\FOO` already defined.

Normally the command is defined to be `\long` (ie it may take multiple paragraphs in its argument). In the star-form, the command is not defined as `\long` and a blank line in any argument to the command would generate an error.

\renewcommand `*{`⟨`\FOO`⟩`}[`⟨*i*⟩`]{`⟨*TEXT*⟩`}`

Same as \newcommand, except it checks if \FOO already defined.

\newenvironment *{⟨*FOO*⟩}[⟨*i*⟩]{⟨*DEF1*⟩}{⟨*DEF2*⟩}

equivalent to:

\newcommand{\FOO}[i]{DEF1} \def{\endFOO}{DEF2}

(or the appropriate star forms).

\renewenvironment

Obvious companion to \newenvironment.

\@cons : See description of \output routine.

\@car \@car T1 T2 ... Tn\@nil == T1 (unexpanded)

\@cdr \@cdr T1 T2 ... Tn\@nil == T2 ... Tn (unexpanded)

\typeout {⟨*message*⟩}

Produces a warning message on the terminal.

\typein {⟨*message*⟩}

Types message, asks the user to type in a command, then executes it

\typein [⟨\CS⟩]{⟨*MSG*⟩}

Same as above, except defines \CS to be the input instead of executing it.

\typein

```
\def\typein{%
  \let\@typein\relax
  \@testopt\@xtypein\@typein}
```

```
\ifx\directlua\@undefined
```

```
\def\@xtypein[#1]#2{%
 \typeout{#2}%
 \advance\endlinechar\@M
 \read\@inputcheck to#1%
 \advance\endlinechar-\@M
 \@typein}%
```

```
\else
```

```
\def\@xtypein[#1]#2{%
  \typeout{#2}%
  \begingroup \endlinechar\m@ne
  \read\@inputcheck to#1%
  \expandafter\endgroup
  \expandafter\def\expandafter#1\expandafter{#1}%
  \@typein}%
```

```
\fi
```

(*End definition for* \typein.)

\@namedef

```
\def\@namedef#1{\expandafter\def\csname #1\endcsname}
```

(*End definition for* \@namedef.)

\@nameuse

```
\def\@nameuse#1{\csname #1\endcsname}
```

(*End definition for* \@nameuse.)

\@cons

```
\def\@cons#1#2{\begingroup\let\@elt\relax\xdef#1{#1\@elt #2}\endgroup}
```

(*End definition for* `\@cons`.)

\@car
\@cdr

```
\def\@car#1#2\@nil{#1}
\def\@cdr#1#2\@nil{#2}
```

(*End definition for* `\@car` *and* `\@cdr`.)

\@carcube

`\@carcube T1 ... Tn\@nil` = `T1 T2 T3` , $n > 3$

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\@carcube}{Make \@carcube long}%
⟨*2ekernel | latexrelease⟩
\long\def\@carcube#1#2#3#4\@nil{#1#2#3}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@carcube}{Undo: Make \@carcube long}%
⟨latexrelease⟩\def\@carcube#1#2#3#4\@nil{#1#2#3}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@carcube`.)

\@onlypreamble
\@preamblecmds

This macro adds its argument to the list of commands stored in `\@preamblecmds` to be disabled after `\begin{document}`. These commands are redefined to generate `\@notprerr` at this point.

```
\def\@preamblecmds{}
\def\@onlypreamble#1{%
  \expandafter\gdef\expandafter\@preamblecmds\expandafter{%
       \@preamblecmds\do#1}}
\@onlypreamble\@onlypreamble
\@onlypreamble\@preamblecmds
```

(*End definition for* `\@onlypreamble` *and* `\@preamblecmds`.)

\@star@or@long

Look ahead for a `*`. If present reset `\l@ngrel@x` so that the next definition, `#1`, will be non-long.

```
\def\@star@or@long#1{%
  \@ifstar
   {\let\l@ngrel@x\relax#1}%
   {\let\l@ngrel@x\long#1}}
```

(*End definition for* `\@star@or@long`.)

\l@ngrel@x

This is either `\relax` or `\long` depending on whether the `*`-form of a definition command is being executed.

```
\let\l@ngrel@x\relax
```

(*End definition for* `\l@ngrel@x`.)

\newcommand

User level `\newcommand`.

```
\def\newcommand{\@star@or@long\new@command}
```

\new@command

```
\def\new@command#1{%
  \@testopt{\@newcommand#1}0}
```

(*End definition for* \newcommand *and* \new@command.)

\@newcommand
\@argdef
\@xargdef

Handling arguments for \newcommand.

```
\def\@newcommand#1[#2]{%
  \kernel@ifnextchar [{\@xargdef#1[#2]}%
                {\@argdef#1[#2]}}
```

Define #1 if it is definable.

Both here and in \@xargdef the replacement text is absorbed as an argument because if we are not allowed to make the definition we have to get rid of it completely.

```
\long\def\@argdef#1[#2]#3{%
   \@ifdefinable #1{\@yargdef#1\@ne{#2}{#3}}}
```

Handle the second optional argument.

```
\long\def\@xargdef#1[#2][#3]#4{%
  \@ifdefinable#1{%
```

Define the actual command to be:
\def\foo{\@protected@testopt\foo\\foo{default}}
where \\foo is a csname generated from applying \csname and \string to \foo, ie the actual name contains a backslash and therefore can't clash easily with existing command names. "Default" is the contents of the second optional argument of (re)newcommand.

```
     \expandafter\def\expandafter#1\expandafter{%
          \expandafter
          \@protected@testopt
          \expandafter
          #1%
          \csname\string#1\endcsname
          {#3}}%
```

Now we define the internal macro ie \\foo which is supposed to pick up all arguments (optional and mandatory).

```
        \expandafter\@yargdef
          \csname\string#1\endcsname
           \tw@
           {#2}%
           {#4}}}
```

(*End definition for* \@newcommand*,* \@argdef*, and* \@xargdef.)

\@testopt

This macro encapsulates the most common call to \@ifnextchar, saving several tokens each time it is used in the definition of a command with an optional argument. #1 The code to execute in the case that there is a [need not be a single token but can be any sequence of commands that 'expects' to be followed by [. If this command were only used in \newcommand definitions then #1 would be a single token and the braces could be omitted from {#1} in the definition below, saving a bit of memory.

```
\long\def\@testopt#1#2{%
  \kernel@ifnextchar[{#1}{#1[{#2}]}}
```

(*End definition for* \@testopt.)

\@protected@testopt Robust version of \@testopt. The extra argument (#1) must be a single token. If protection is needed the call expands to \protect applied to this token, and the 2nd and 3rd arguments are discarded (by \@x@protect). Otherwise \@testopt is called on the 2nd and 3rd arguments.

This method of making commands robust avoids the need for using up two csnames per command, the price is the extra expansion time for the \ifx test.

```
\def\@protected@testopt#1{%
  \ifx\protect\@typeset@protect
    \expandafter\@testopt
  \else
    \@x@protect#1%
  \fi}
```

(*End definition for* \@protected@testopt.)

\@yargdef \@yargd@f These generate a primitive argument specification, from a LaTeX [⟨*digit*⟩] form; in fact ⟨*digit*⟩ can be anything such that \number ⟨*digit*⟩ is single digit.

Reorganised slightly so that \renewcommand{\reserved@a}[1]{foo} works. I am not sure this is worth it, as a following \newcommand would over-write the definition of \reserved@a.

Recall that LaTeX2.09 goes into an infinite loop with
\renewcommand[1]{\@tempa}{foo}
(DPC 6 October 93).

Reorganised again (DPC 1999). Rather than make a loop to construct the argument spec by counting, just extract the required argument spec by using a delimited argument (delimited by the digit). This is faster and uses less tokens. The coding is slightly odd to preserve the old interface (using #2 = \tw@ as the flag to surround the first argument with []. But the new method did not allow for the number of arguments #3 not being given as an explicit digit; hence (further expansion of this argument and use of) \number was added later in 1999.

It is not clear why these are still \long.

```
\long \def \@yargdef #1#2#3{%
  \ifx#2\tw@
    \def\reserved@b##11{[####1]}%
  \else
    \let\reserved@b\@gobble
  \fi
  \expandafter
    \@yargd@f \expandafter{\number #3}#1%
}
```

```
\long \def \@yargd@f#1#2{%
  \def \reserved@a ##1#1##2##{%
    \expandafter\def\expandafter#2\reserved@b ##1#1%
    }%
  \l@ngrel@x \reserved@a 0##1##2##3##4##5##6##7##8##9###1%
}
```

(*End definition for* \@yargdef *and* \@yargd@f.)

\@reargdef

```
\long\def\@reargdef#1[#2]{%
  \@yargdef#1\@ne{#2}}
```

(*End definition for* `\@reargdef`.)

`\renewcommand` Check the command name is already used. If not give an error message. Then temporarily disable `\@ifdefinable` then call `\newcommand`. (Previous version `\let#1=\relax` but this does not work too well if `#1` is `\@temp`*a–e*.)

```
\def\renewcommand{\@star@or@long\renew@command}
```

`\renew@command`

```
\def\renew@command#1{%
  \begingroup \escapechar\m@ne\xdef\@gtempa{{\string#1}}\endgroup
  \expandafter\@ifundefined\@gtempa
     {\@latex@error{Command \string#1 undefined}\@ehc}%
     \relax
  \let\@ifdefinable\@rc@ifdefinable
  \new@command#1}
```

(*End definition for* `\renewcommand` *and* `\renew@command`.)

`\@ifdefinable` `\@@ifdefinable` `\@rc@ifdefinable` Test if user is allowed to define a command.

```
\long\def\@ifdefinable #1#2{%
      \edef\reserved@a{\expandafter\@gobble\string #1}%
     \@ifundefined\reserved@a
         {\edef\reserved@b{\expandafter\@carcube \reserved@a xxx\@nil}%
          \ifx \reserved@b\@qend \@notdefinable\else
            \ifx \reserved@a\@qrelax \@notdefinable\else
              #2%
            \fi
          \fi}%
         \@notdefinable}
```

Saved definition of `\@ifdefinable`.

```
\let\@@ifdefinable\@ifdefinable
```

Version of `\@ifdefinable` for use with `\renewcommand`. Does not do the check this time, but restores the normal definition.

```
\long\def\@rc@ifdefinable#1#2{%
  \let\@ifdefinable\@@ifdefinable
  #2}
```

(*End definition for* `\@ifdefinable`, `\@@ifdefinable`, *and* `\@rc@ifdefinable`.)

`\newenvironment` Define a new user environment. `#1` is the environment name. `#2#` Grabs all the tokens up to the first `{`. These will be any optional arguments. They are not parsed at this point, but are just passed to `\@newenv` which will eventually call `\newcommand`. Any optional arguments will then be parsed by `\newcommand` as it defines the command that executes the 'begin code' of the environment.

This `#2#` trick removed with version 1.2i as it fails if a `{` occurs in the optional argument. Now use `\@ifnextchar` directly.

```
\def\newenvironment{\@star@or@long\new@environment}
```

`\new@environment`

```
\def\new@environment#1{%
  \@testopt{\@newenva#1}0}
```

\@newenva

```
\def\@newenva#1[#2]{%
   \kernel@ifnextchar [{\@newenvb#1[#2]}{\@newenv{#1}{[#2]}}}
```

\@newenvb

```
\def\@newenvb#1[#2][#3]{\@newenv{#1}{[#2][{#3}]}}
```

(*End definition for* `\newenvironment` *and others.*)

\renewenvironment

Redefine an environment. For `\renewenvironment` disable `\@ifdefinable` and then call `\newenvironment`. It is OK to `\let` the argument to `\relax` here as there should not be a `@temp`... environment.

```
\def\renewenvironment{\@star@or@long\renew@environment}
```

\renew@environment

```
\def\renew@environment#1{%
  \@ifundefined{#1}%
     {\@latex@error{Environment #1 undefined}\@ehc
     }\relax
  \expandafter\let\csname#1\endcsname\relax
  \expandafter\let\csname end#1\endcsname\relax
  \new@environment{#1}}
```

(*End definition for* `\renewenvironment` *and* `\renew@environment`.)

\@newenv

The internal version of `\newenvironment`.

Call `\newcommand` to define the ⟨*begin-code*⟩ for the environment. `\def` is used for the ⟨*end-code*⟩ as it does not take arguments. (but may contain `\pars`)

Make sure that an attempt to define a 'graf' or 'group' environment fails.

```
\long\def\@newenv#1#2#3#4{%
  \@ifundefined{#1}%
    {\expandafter\let\csname#1\expandafter\endcsname
                          \csname end#1\endcsname}%
    \relax
  \expandafter\new@command
     \csname #1\endcsname#2{#3}%
     \l@ngrel@x\expandafter\def\csname end#1\endcsname{#4}}
```

(*End definition for* `\@newenv`.)

\newif

And here's a different sort of allocation: For example, `\newif\iffoo` creates `\footrue`, `\foofalse` to go with `\iffoo`.

```
\def\newif#1{%
  \count@\escapechar \escapechar\m@ne
    \let#1\iffalse
    \@if#1\iftrue
    \@if#1\iffalse
  \escapechar\count@}
```

\@if

```
\def\@if#1#2{%
  \expandafter\def\csname\expandafter\@gobbletwo\string#1%
                     \expandafter\@gobbletwo\string#2\endcsname
                        {\let#1#2}}
```

(*End definition for* `\newif` *and* `\@if`.)

`\providecommand` `\providecommand` takes the same arguments as `\newcommand`, but discards them if `#1` is already defined, Otherwise it just acts like `\newcommand`. This implementation currently leaves any discarded definition in `\reserved@a` (and possibly `\\reserved@a`) this wastes a bit of space, but it will be reclaimed as soon as these scratch macros are redefined.

```
\def\providecommand{\@star@or@long\provide@command}
```

`\provide@command`

```
\def\provide@command#1{%
  \begingroup
    \escapechar\m@ne\xdef\@gtempa{{\string#1}}%
  \endgroup
  \expandafter\@ifundefined\@gtempa
    {\def\reserved@a{\new@command#1}}%
    {\def\reserved@a{\renew@command\reserved@a}}%
   \reserved@a}%
```

(*End definition for* `\providecommand` *and* `\provide@command`.)

`\CheckCommand` `\CheckCommand` takes the same arguments as `\newcommand`. If the command already exists, with the same definition, then nothing happens, otherwise a warning is issued. Useful for checking the current state before a macro package starts redefining things. Currently two macros are considered to have the same definition if they are the same except for different default arguments. That is, if the old definition was: `\newcommand\xxx[2][a]{(#1)(#2)}` then `\CheckCommand\xxx[2][b]{(#1)(#2)}` would *not* generate a warning, but, for instance `\CheckCommand\xxx[2]{(#1)(#2)}` would.

```
\def\CheckCommand{\@star@or@long\check@command}
```

`\CheckCommand` is only available in the preamble part of the document.

```
\@onlypreamble\CheckCommand
```

`\check@command`

```
\def\check@command#1#2#{\@check@c#1{#2}}
\@onlypreamble\check@command
```

(*End definition for* `\CheckCommand` *and* `\check@command`.)

`\@check@c` `\CheckCommand` itself just grabs all the arguments we need, without actually looking for `[` optional argument forms. Now define `\reserved@a`. If `\\reserved@a` is then defined, compare it with the "`\#1`' otherwise compare `\reserved@a` with `#1`.

```
\long\def\@check@c#1#2#3{%
  \expandafter\let\csname\string\reserved@a\endcsname\relax
  \renew@command\reserved@a#2{#3}%
  \@ifundefined{\string\reserved@a}%
   {\@check@eq#1\reserved@a}%
   {\expandafter\@check@eq
           \csname\string#1\expandafter\endcsname
           \csname\string\reserved@a\endcsname}}
\@onlypreamble\@check@c
```

(*End definition for* `\@check@c`.)

\@check@eq Complain if #1 and #2 are not \ifx equal.

```
\def\@check@eq#1#2{%
  \ifx#1#2\else
     \@latex@warning@no@line
                {Command \noexpand#1 has
                 changed.\MessageBreak
                 Check if current package is valid}%
  \fi}
\@onlypreamble\@check@eq
```

(*End definition for* \@check@eq.)

\@gobble The \@gobble macro is used to get rid of its argument.
\@gobbletwo
\@gobblethree
\@gobblefour

```
\long\def \@gobble #1{}
\long\def \@gobbletwo #1#2{}
\long\def \@gobblethree #1#2#3{}
\long\def \@gobblefour #1#2#3#4{}
```

(*End definition for* \@gobble *and others.*)

\@firstofone Some argument-grabbers.
\@firstoftwo
\@secondoftwo

```
\long\def\@firstofone#1{#1}
\long\def\@firstoftwo#1#2{#1}
\long\def\@secondoftwo#1#2{#2}
```

\@iden is another name for \@firstofone for compatibility reasons.

```
\let\@iden\@firstofone
```

\@iden (*End definition for* \@firstofone *and others.*)

\@thirdofthree Another grabber now used in the encoding specific section.

```
\long\def\@thirdofthree#1#2#3{#3}
```

(*End definition for* \@thirdofthree.)

\@expandtwoargs A macro to totally expand two arguments to another macro

```
\def\@expandtwoargs#1#2#3{%
\edef\reserved@a{\noexpand#1{#2}{#3}}\reserved@a}
```

(*End definition for* \@expandtwoargs.)

\@backslashchar A category code 12 backslash.

```
\edef\@backslashchar{\expandafter\@gobble\string\\}
```

(*End definition for* \@backslashchar.)

1.4 Robust commands and protect

Fragile and robust commands are one of the thornier issues in LaTeX's commands. Whilst typesetting documents, LaTeX makes use of many of TeX's features, such as arithmetic, defining macros, and setting variables. However, there are (at least) three different occasions when these commands are not safe. These are called 'moving arguments' by LaTeX, and consist of:

- writing information to a file, such as indexes or tables of contents.
- writing information to the screen.
- inside an `\edef`, `\message`, `\mark`, or other command which evaluates its argument fully.

The method LaTeX uses for making fragile commands robust is to precede them with `\protect`. This can have one of four possible values:

- `\relax`, for normal typesetting. So `\protect\foo` will execute `\foo`.
- `\string`, for writing to the screen. So `\protect\foo` will write `\foo`.
- `\noexpand`, for writing to a file. So `\protect\foo` will write `\foo` followed by a space.
- `\@unexpandable@protect`, for writing a moving argument to a file. So `\protect\foo` will write `\protect\foo` followed by a space. This value is also used inside `\edef`s, `\mark`s and other commands which evaluate their arguments fully. More precisely, whenever the content of an `\edef` or `\xdef` etc. can contain arbitrary user input not under the direct control of the programmer, one should use `\proetected@edef` instead of `\edef`, etc., so that `\protect` has a suitable definition and the user input will not break if it contains fragile commands.

`\@unexpandable@protect`

```
\def\@unexpandable@protect{\noexpand\protect\noexpand}
```

(*End definition for* `\@unexpandable@protect`.)

`\DeclareRobustCommand`
`\declare@robustcommand`

This is a package-writers command, which has the same syntax as `\newcommand`, but which declares a protected command. It does this by having
`\DeclareRobustCommand\foo`
define `\foo` to be `\protect\foo<space>`,
and then use `\newcommand\foo<space>`.
Since the internal command is `\foo<space>`, when it is written to an auxiliary file, it will appear as `\foo`.

We have to be a bit cleverer if we're defining a short command, such as `\_`, in order to make sure that the auxiliary file does not include a space after the command, since `\_ a` and `\_a` aren't the same. In this case we define `\_` to be:

```
\x@protect\_\protect\_<space>
```

which expands to:

```
\ifx\protect\@typeset@protect\else
   \@x@protect@\_
\fi
\protect\_<space>
```

Then if \protect is \@typeset@protect (normally \relax) then we just perform _<space>, and otherwise \@x@protect@ gobbles everything up and expands to \protect_.

Note: setting \protect to any value other than \relax whilst in 'typesetting' mode will cause commands to go into an infinite loop! In particular, setting \protect to \@empty will cause _ to loop forever. It will also break lots of other things, such as protected \ifmmodes inside \halignes. If you really have to do such a thing, then please set \@typeset@protect to be \@empty as well. (This is what the code for \patterns does, for example.)

More fun with \expandafter and \csname.

```
\def\DeclareRobustCommand{\@star@or@long\declare@robustcommand}
\def\declare@robustcommand#1{%
   \ifx#1\@undefined\else\ifx#1\relax\else
      \@latex@info{Redefining \string#1}%
   \fi\fi
   \edef\reserved@a{\string#1}%
   \def\reserved@b{#1}%
   \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
   \edef#1{%
      \ifx\reserved@a\reserved@b
         \noexpand\x@protect
         \noexpand#1%
      \fi
      \noexpand\protect
      \expandafter\noexpand\csname
         \expandafter\@gobble\string#1 \endcsname
   }%
   \let\@ifdefinable\@rc@ifdefinable
   \expandafter\new@command\csname
      \expandafter\@gobble\string#1 \endcsname
}
```

(*End definition for* \DeclareRobustCommand *and* \declare@robustcommand.)

\@x@protect
\x@protect

```
\def\x@protect#1{%
   \ifx\protect\@typeset@protect\else
      \@x@protect#1%
   \fi
}
\def\@x@protect#1\fi#2#3{%
   \fi\protect#1%
}
```

(*End definition for* \@x@protect *and* \x@protect.)

\@typeset@protect

We set \@typeset@protect to \relax rather than \@empty to make sure that the protection mechanism stops the look-ahead and expansion performed at the start of \halign cells.

```
\let\@typeset@protect\relax
```

(*End definition for* `\@typeset@protect`.)

`\set@display@protect`
`\set@typeset@protect`

These macros set `\protect` appropriately for typesetting or displaying.

```
\def\set@display@protect{\let\protect\string}
\def\set@typeset@protect{\let\protect\@typeset@protect}
```

(*End definition for* `\set@display@protect` *and* `\set@typeset@protect`.)

`\protected@edef`
`\protected@xdef`
`\unrestored@protected@xdef`
`\restore@protect`

The commands `\protected@edef` and `\protected@xdef` perform 'safe' `\edef`s and `\xdef`s, saving and restoring `\protect` appropriately. For cases where restoring `\protect` doesn't matter, there's an 'unsafe' `\unrestored@protected@xdef`, useful if you know what you're doing!

```
\def\protected@edef{%
   \let\@@protect\protect
   \let\protect\@unexpandable@protect
   \afterassignment\restore@protect
   \edef
}
\def\protected@xdef{%
   \let\@@protect\protect
   \let\protect\@unexpandable@protect
   \afterassignment\restore@protect
   \xdef
}
\def\unrestored@protected@xdef{%
   \let\protect\@unexpandable@protect
   \xdef
}
\def\restore@protect{\let\protect\@@protect}
```

(*End definition for* `\protected@edef` *and others*.)

`\protect`

The normal meaning of `\protect`

```
\set@typeset@protect
```

(*End definition for* `\protect`.)

`\MakeRobust`

This macro makes an existing fragile macro robust, but only if it hasn't been robust in the past, i.e., it checks for the existence of the macro `\<name>␣` and if that exists it assumes that `\<name>` is already robust. In that case either undefine the inner macro first or use `\DeclareRobustCommand` to define it in a robust way directly. We could probably test the top-level definition to have the right kind of structure, but this is somewhat problematical as we then have to distinguish between `\long` macros and others and also take into account that sometimes the top-level is deliberately done manually (like with `\begin`).

The macro firstly checks if the control sequence in question exists at all.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\MakeRobust}{\MakeRobust}%
⟨*2ekernel | latexrelease⟩
\def\MakeRobust#1{%
  \count@=\escapechar
  \escapechar=`\\
  \@ifundefined{\expandafter\@gobble\string#1}{%
    \@latex@error{Command `\string#1' undefined.%
```

```
      \MessageBreak There is nothing here to make robust}%
    \@eha
  }%
```

Then we check if the macro is already robust. We do this by testing if the internal name for a robust macro is defined, namely `\foo␣`. If it is already defined do nothing, otherwise set `\foo␣` equal to `\foo` and redefine `\foo` so that it acts like a macro defined with `\DeclareRobustCommand`. We use `\@kernel@rename@newcommand` to copy `\foo` over to `\foo␣`, including a possible default optional argument.

```
  {%
    \@ifundefined{\expandafter\@gobble\string#1\space}%
    {%
      \expandafter\@kernel@rename@newcommand
        \csname\expandafter\@gobble\string#1\space\endcsname
        #1%
      \edef\reserved@a{\string#1}%
      \def\reserved@b{#1}%
      \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
      \xdef#1{%
        \ifx\reserved@a\reserved@b
          \noexpand\x@protect\noexpand#1%
        \fi
        \noexpand\protect\expandafter\noexpand
        \csname\expandafter\@gobble\string#1\space\endcsname}%
    }%
    {\@latex@info{Command `\string#1' is already robust}}%
  }%
  \escapechar=\count@
}%
```

`\@kernel@rename@newcommand`

This macro renames a command, possibly with an optional argument (defined with `\newcommand`) from `#2` to `#1`, by renaming the internal macro `\\#2` to `\\#1` and defining `\#1` appropriately, then undefining `\#2` and `\\#2`. The `\afterassignment` trick is to make both definitions in `\@copy@newcommand` global (which are local by default).

In case the macro was defined with `\newcommand` and an optional argument, to replicate exactly the behaviour of `\DeclareRobustCommand` we have to move also the internal `\\foo` to `\\foo␣`. In that case, `#1` will be a parameterless macro (`\robust@command@chk@safe` checks that), and `\@if@newcommand` will return true (both defined below in this file). If so, we can use `\@copy@newcommand` rather than plain `\let` to copy the command over. `\@kernel@rename@newcommand` does this test and carries out the renaming.

```
\def\@kernel@rename@newcommand#1#2{%
  \robust@command@chk@safe#2%
    {\@if@newcommand#2%
      {\afterassignment\global
       \global\@copy@newcommand#1#2%
       \global\let#2\@undefined
       \global\expandafter\let\csname\string#2\endcsname\@undefined}%
      {\global\let#1=#2}}%
    {\global\let#1=#2}}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
%
⟨latexrelease⟩\IncludeInRelease{2019/10/01}{\MakeRobust}{\MakeRobust}%
⟨latexrelease⟩\def\MakeRobust#1{%
⟨latexrelease⟩  \@ifundefined{\expandafter\@gobble\string#1}{%
⟨latexrelease⟩    \@latex@error{The control sequence ‘\string#1’ is undefined!%
⟨latexrelease⟩      \MessageBreak There is nothing here to make robust}%
⟨latexrelease⟩    \@eha
⟨latexrelease⟩  }%
⟨latexrelease⟩  {%
⟨latexrelease⟩    \@ifundefined{\expandafter\@gobble\string#1\space}%
⟨latexrelease⟩    {%
⟨latexrelease⟩      \global\expandafter\let\csname
⟨latexrelease⟩      \expandafter\@gobble\string#1\space\endcsname=#1%
⟨latexrelease⟩      \edef\reserved@a{\string#1}%
⟨latexrelease⟩      \def\reserved@b{#1}%
⟨latexrelease⟩      \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
⟨latexrelease⟩      \xdef#1{%
⟨latexrelease⟩        \ifx\reserved@a\reserved@b
⟨latexrelease⟩          \noexpand\x@protect\noexpand#1%
⟨latexrelease⟩        \fi
⟨latexrelease⟩        \noexpand\protect\expandafter\noexpand
⟨latexrelease⟩        \csname\expandafter\@gobble\string#1\space\endcsname}%
⟨latexrelease⟩    }%
⟨latexrelease⟩    {\@latex@info{The control sequence ‘\string#1’ is already robust}}%
⟨latexrelease⟩   }%
⟨latexrelease⟩}%
⟨latexrelease⟩\let\@kernel@rename@newcommand\@undefined
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\MakeRobust}{\MakeRobust}%
⟨latexrelease⟩\def\MakeRobust#1{%
⟨latexrelease⟩  \@ifundefined{\expandafter\@gobble\string#1}{%
⟨latexrelease⟩    \@latex@error{The control sequence ‘\string#1’ is undefined!%
⟨latexrelease⟩      \MessageBreak There is nothing here to make robust}%
⟨latexrelease⟩    \@eha
⟨latexrelease⟩  }%
⟨latexrelease⟩  {%
⟨latexrelease⟩    \@ifundefined{\expandafter\@gobble\string#1\space}%
⟨latexrelease⟩    {%
⟨latexrelease⟩      \expandafter\let\csname
⟨latexrelease⟩      \expandafter\@gobble\string#1\space\endcsname=#1%
⟨latexrelease⟩      \edef\reserved@a{\string#1}%
⟨latexrelease⟩      \def\reserved@b{#1}%
⟨latexrelease⟩      \edef\reserved@b{\expandafter\strip@prefix\meaning\reserved@b}%
⟨latexrelease⟩      \edef#1{%
⟨latexrelease⟩        \ifx\reserved@a\reserved@b
⟨latexrelease⟩          \noexpand\x@protect\noexpand#1%
⟨latexrelease⟩        \fi
⟨latexrelease⟩        \noexpand\protect\expandafter\noexpand
⟨latexrelease⟩        \csname\expandafter\@gobble\string#1\space\endcsname}%
⟨latexrelease⟩    }%
⟨latexrelease⟩    {\@latex@info{The control sequence ‘\string#1’ is already robust}}%
⟨latexrelease⟩   }%
⟨latexrelease⟩}%
```

```
⟨latexrelease⟩\let\@kernel@rename@newcommand\@undefined
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\MakeRobust}{\MakeRobust}%
⟨latexrelease⟩\let\MakeRobust\@undefined
⟨latexrelease⟩\let\@kernel@rename@newcommand\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\MakeRobust` *and* `\@kernel@rename@newcommand`.)

`\kernel@make@fragile` The opposite of `\MakeRobust` except that it doesn't do many checks as it is internal to the kernel. Why does one want such a thing? Only for compatibility reasons if `latexrelease` requests a rollback of the kernel. For this reason we pretend that this command existed in all earlier versions of LaTeX i.e., we are not rolling it back since we need it precisely then. But we have to get it into the `latexrelease` file so that a roll forward is possible too.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\kernel@make@fragile}{Undo robustness}%
\def\kernel@make@fragile#1{%
  \@ifundefined{\expandafter\@gobble\string#1\space}%
```

If not robust do nothing.

```
      {}%
```

Otherwise copy `\foo␣` back to `\foo`. Then use `\@kernel@rename@newcommand` to check and copy `\\foo␣` back to `\\foo` in case the command has an optional argument. If so, also undefine `\\foo␣`, and at the end undefine `\foo␣`.

```
      {%
       \global\expandafter\let\expandafter #1\csname
         \expandafter\@gobble\string#1\space\endcsname
       \expandafter\@kernel@rename@newcommand
         \csname\expandafter\@gobble\string#1\expandafter\endcsname
         \csname\expandafter\@gobble\string#1\space\endcsname
       \global\expandafter\let\csname
         \expandafter\@gobble\string#1\space\endcsname\@undefined
      }%
}
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\kernel@make@fragile}{Undo robustness}%
⟨latexrelease⟩\def\kernel@make@fragile#1{%
⟨latexrelease⟩   \@ifundefined{\expandafter\@gobble\string#1\space}%
⟨latexrelease⟩      {}%
⟨latexrelease⟩      {%
⟨latexrelease⟩       \global\expandafter\let\expandafter #1\csname
⟨latexrelease⟩       \expandafter\@gobble\string#1\space\endcsname
⟨latexrelease⟩       \global\expandafter\let\csname
⟨latexrelease⟩       \expandafter\@gobble\string#1\space\endcsname\@undefined
⟨latexrelease⟩      }%
⟨latexrelease⟩}
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
```

(*End definition for* `\kernel@make@fragile`.)

1.5 Acting on robust commands

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020-10-01}{\robust@command@act}
⟨latexrelease⟩   {Add \robust@command@act}%
⟨*2ekernel | latexrelease⟩
```

With most document level commands being robust now there is more of a requirement to have a standard way of aliasing (or copying) a command to a new name, for example to save an original definition before changing a command. `\DeclareCommandCopy` is analogous to TEX's `\let`, except that it copes with the different types of robust commands defined by LATEX's mechanisms.

A couple of "types of robustness" are defined by the LATEX 2_ε kernel, namely robust commands defined with `\DeclareRobustCommand` and commands with optional arguments defined with `\newcommand`. However there are other types of robust commands that are frequently used, which are not defined in the LATEX 2_ε kernel, like commands defined with xparse's `\NewDocumentCommand` and etoolbox's `\newrobustcmd`.

In this section we will define a generic extensible machinery to act on robust commands. This code will then be used to test if a command is robust, considered the different types of robustness, and then either copy that definition, if `\DeclareCommandCopy` (or similar) is used, or show the definition of the command, if `\ShowCommand` is used.

`\robust@command@act` The looping machinery is generic and knows nothing about what is to be done for each case. The syntax of the main macro `\robust@command@act` is:

> `\robust@command@act`⟨*action-list*⟩⟨*robust-cmd*⟩
> ⟨*fallback-action*⟩⟨*act-arg*⟩

⟨*action-list*⟩ is a token list of the form:

> `{`⟨*if-type-1*⟩ ⟨*act-type-1*⟩`}`
> `{`⟨*if-type-2*⟩ ⟨*act-type-2*⟩`}`
> ...

`\robust@command@act` will iterate over the ⟨*action-list*⟩, evaluating each ⟨*if-type-n*⟩ ⟨*robust-cmd*⟩ `{`⟨*true*⟩`}{`⟨*false*⟩`}`. If the ⟨*if-type-n*⟩ conditional returns ⟨*true*⟩, then ⟨*act-type-n*⟩⟨*act-arg*⟩ is executed, and the loop ends. If the conditional returns ⟨*false*⟩, then ⟨*if-type-n* + 1⟩ is executed in the same way, until either one of the conditionals return ⟨*true*⟩, or the end of the ⟨*action-list*⟩ is reached. If the end is reached, then ⟨*fallback-action*⟩⟨*act-arg*⟩ is executed before `\robust@command@act` exits.

`\robust@command@act` will start by using `\robust@command@act@chk@args` to check if the ⟨*robust-cmd*⟩ (`#2`) is a parameterless (possibly `\protected`) macro. If it is not, the command is not a robust command: these always start with a parameterless user-level macro; in that case, `\robust@command@act@end` is used to short-circuit the process and do the ⟨*fallback-action*⟩ (`#3`). This first test is necessary because later on we need to be able to expand the ⟨*robust-cmd*⟩ without the risk of it Breaking Badly, and as a bonus, this speeds up the process in case we used `\NewCommandCopy` in a "normal" macro.

```
\long\def\robust@command@act#1#2#3#4{%
```

```
  \robust@command@chk@safe#2%
    {\expandafter\robust@command@act@loop
       \expandafter#2%
         #1{\@nnil\@nnil}%
     \robust@command@act@end}%
    {\robust@command@act@end}%
      {#3}{#4}}%
```

If `\robust@command@act@chk@args` branched to false, then `\robust@command@act@loop` will loop over the list of items in the ⟨*action-list*⟩ (`#1`), and process each item as described earlier. If the ⟨*if-type-n*⟩ command expands to ⟨*true*⟩ then `\robust@command@act@do` is used to execute ⟨*act-type-n*⟩ on the ⟨*act-arg*⟩, otherwise the loop resumes with the next item.

`\robust@command@act@loop`
`\robust@command@act@loop@aux`
`\robust@command@act@do`

```
\long\def\robust@command@act@loop#1#2{\robust@command@act@loop@aux#1#2}
\long\def\robust@command@act@loop@aux#1#2#3{%
  \ifx\@nnil#2%
  \else
    #2{#1}%
      {\robust@command@act@do{#3}}%
      {\expandafter\robust@command@act@loop\expandafter#1}%
  \fi}
\long\def\robust@command@act@do#1%
  \fi#2%
  \robust@command@act@end#3#4{%
  \fi
  #1#4}
```

If the end is reached and no action was taken, then do ⟨*fallback-action*⟩⟨*act-arg*⟩.

`\robust@command@act@end`

```
\long\def\robust@command@act@end#1#2{#1#2}
```

`\robust@command@chk@safe`
`\robust@command@act@chk@args`

```
\long\def\robust@command@chk@safe#1{%
  \begingroup
    \escapechar=`\\
  \expandafter\endgroup\expandafter
  \robust@command@act@chk@args\meaning#1:->\@nil}
\def\robust@command@act@chk@args#1:->#2\@nil{%
  \@expl@str@if@eq@@nnTF{#1}{macro}%
    {\@firstoftwo}%
    {\@expl@str@if@eq@@nnTF{#1}{\protected macro}%
      {\@firstoftwo}%
      {\@secondoftwo}}}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}{\robust@command@act}
⟨latexrelease⟩   {Add \robust@command@act}%
⟨latexrelease⟩\let\robust@command@act\@undefined
⟨latexrelease⟩\let\robust@command@act@loop\@undefined
⟨latexrelease⟩\let\robust@command@act@loop@aux\@undefined
⟨latexrelease⟩\let\robust@command@act@do\@undefined
⟨latexrelease⟩\let\robust@command@act@end\@undefined
⟨latexrelease⟩\let\robust@command@chk@safe\@undefined
⟨latexrelease⟩\let\robust@command@act@chk@args\@undefined
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\robust@command@act` *and others.*)

1.5.1 Copying robust commands

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020-10-01}{\DeclareCommandCopy}
⟨latexrelease⟩  {Add \NewCommandCopy, \RenewCommandCopy, and \DeclareCommandCopy}%
⟨*2ekernel | latexrelease⟩
```

`\NewCommandCopy`
`\RenewCommandCopy`
`\DeclareCommandCopy`

`\NewCommandCopy` starts by checking if `#1` is already defined, and raises an error if so, otherwise the definition is carried out. `\RenewCommandCopy` does (almost) the opposite. If the command is *not* defined, then an error is raised. But the definition is carried out anyhow, so the behaviour is consistent with `\renewcommand`.

A `\ProvideCommandCopy` isn't defined because it's not reasonably useful. `\provide...` commands mean "define this if there's no other definition", but copying a command (usually) implies that the command being copied is defined, so `\ProvideCommandCopy` doesn't make a lot of sense. But more importantly, the most common use case of copying a command is to redefine it later, while preserving the old definition, as in:

```
\ProvideCommandCopy \A \B
\renewcommand \B { ... \A ... }
```

then, if `\A` is already defined the first line is skipped, an in this case `\B` won't work as expected.

The three versions call the internal `\declare@commandcopy` with the proper action. `\@firstofone` will carry out the copy. The only case when the copy is not made is the ⟨*false*⟩ case for `\NewCommandCopy`, in which the command already exists and the definition is aborted.

```
\def\NewCommandCopy{%
  \declare@commandcopy
    {\@firstofone}%
    {\@firstoftwo\@notdefinable}}
\def\RenewCommandCopy{%
  \declare@commandcopy
    {\@latex@error{Command \@backslashchar\reserved@a\space undefined}\@ehc
     \@firstofone}%
    {\@firstofone}}
\def\DeclareCommandCopy{%
  \declare@commandcopy
    {\@firstofone}%
    {\@firstofone}}
```

Start by checking if the command is already defined. The proper action is taken by each specific command above. If all's good, then `\robust@command@act` is called with the proper arguments as described earlier, with `\@declarecommandcopylisthook` as the ⟨*action-list*⟩ and `\declare@commandcopy@let` as the ⟨*fallback-action*⟩.

`\declare@commandcopy`

```
\long\def\declare@commandcopy#1#2#3#4{%
  \edef\reserved@a{\@expl@cs@to@str@@N#3}%
  \@ifundefined\reserved@a{#1}{#2}%
    {\robust@command@act
       \@declarecommandcopylisthook#4%
       \declare@commandcopy@let{#3#4}}}
```

The initial definition of \@declarecommandcopylisthook contains the tests for the two types of robust command in the kernel.

\@declarecommandcopylisthook

```
\def\@declarecommandcopylisthook{%
  {\@if@DeclareRobustCommand \@copy@DeclareRobustCommand}%
  {\@if@newcommand \@copy@newcommand}}
```

The initial definition of \@declarecommandcopylisthook contains the tests for the two types of robust command in the kernel.

\declare@commandcopy@let

```
\long\def\declare@commandcopy@let#1#2{\let#1=#2\relax}
```

Now the rollback code.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}{\DeclareCommandCopy}
⟨latexrelease⟩  {Undefine \NewCommandCopy, \RenewCommandCopy, and \DeclareCommandCopy}%
⟨latexrelease⟩\let\NewCommandCopy\@undefined
⟨latexrelease⟩\let\RenewCommandCopy\@undefined
⟨latexrelease⟩\let\DeclareCommandCopy\@undefined
⟨latexrelease⟩\let\declare@commandcopy\@undefined
⟨latexrelease⟩\let\@declarecommandcopylisthook\@undefined
⟨latexrelease⟩\let\declare@commandcopy@let\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \NewCommandCopy *and others.*)

1.5.2 Showing robust commands

\ShowCommand

Most of the machinery defined for \NewCommandCopy can be used to show the definition of a robust command, in a similar fashion to texdef. The difference is that after the command's is detected to has a given type of robustness, rather than making a copy, we use a separate routine to show its definition.

With all the machinery in place, \ShowCommand itself is quite simple: use \robust@command@act to iterate through the \@showcommandlisthook list, and if nothing is found, fallback to \show.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020-10-01}{\ShowCommand}%
⟨latexrelease⟩  {Add \ShowCommand}%
⟨*2ekernel | latexrelease⟩
```

```
\long\def\ShowCommand#1{%
  \robust@command@act
    \@showcommandlisthook#1%
    \show#1}
```

\@showcommandlisthook

The initial definition of \@showcommandlisthook contains the same tests as used for copying, but \@show@... commands instead of \@copy@.... Same as before, it is initialized to cope with \DeclareRobustCommand and \newcommand with optional arguments.

```
\def\@showcommandlisthook{%
  {\@if@DeclareRobustCommand \@show@DeclareRobustCommand}%
  {\@if@newcommand \@show@newcommand}}
```

Now the rollback code.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}{\ShowCommand}
⟨latexrelease⟩  {Undefine \ShowCommand}%
⟨latexrelease⟩\let\ShowCommand\@undefined
⟨latexrelease⟩\let\@showcommandlisthook\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\ShowCommand` *and* `\@showcommandlisthook`.)

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020-10-01}{\@if@DeclareRobustCommand}
⟨latexrelease⟩  {Add \@if@DeclareRobustCommand, \@if@newcommand,
⟨latexrelease⟩       \@copy@DeclareRobustCommand, \@copy@newcommand,
⟨latexrelease⟩       \@show@DeclareRobustCommand, \@show@newcommand}%
⟨*2ekernel | latexrelease⟩
```

1.5.3 Commands defined with `\DeclareRobustCommand`

`\@if@DeclareRobustCommand`

Now that we provided a generic way to copy one macro to another, we need to define a way to check if a command is one of LaTeX 2_ε's robust types. These tests are heavily based on Heiko's `\LetLtxMacro`, but chopped into separate macros.

`\@if@DeclareRobustCommand` checks if a command `\cmd` was defined by `\DeclareRobustCommand`. The test returns true if the expansion of `\cmd` is exactly `\protect\cmd␣`.

```
\long\def\@if@DeclareRobustCommand#1{%
  \begingroup
    \escapechar=`\\
    \edef\reserved@a{\string#1}%
    \edef\reserved@b{\detokenize{#1}}%
    \xdef\@gtempa{%
      \ifx\reserved@a\reserved@b
         \noexpand\x@protect
         \noexpand#1%
      \fi
      \noexpand\protect
      \expandafter\noexpand\csname\@expl@cs@to@str@@N#1 \endcsname}%
  \endgroup
  \ifx\@gtempa#1\relax
    \expandafter\@firstoftwo
  \else
    \expandafter\@secondoftwo
  \fi}
```

`\@copy@DeclareRobustCommand`
`\copy@kernel@robust@command`

If a command was defined by `\DeclareRobustCommand` (that is, `\@if@DeclareRobustCommand` returns true), then to make a copy of `\cmd` into `\foo` we define the latter such that it expands to `\protect\foo␣`, then make `\foo␣` equal to `\cmd␣`.

There is one detail we need to take care of: if a command was defined with `\DeclareRobustCommand` it may still have an optional argument, in which case there is one more macro layer before the actual definition of the command. We use `\@if@newcommand` to check that and `\@copy@newcommand` to do the copying.

```
\long\def\@copy@DeclareRobustCommand#1#2{%
```

```
  \begingroup
    \escapechar=`\\
    \edef\reserved@a{\string#1}%
    \edef\reserved@b{\detokenize{#1}}%
    \edef\reserved@a{%
  \endgroup
  \def\noexpand#1{%
    \ifx\reserved@a\reserved@b
       \noexpand\x@protect
       \noexpand#1%
    \fi
    \noexpand\protect
    \expandafter\noexpand\csname\@expl@cs@to@str@@N#1 \endcsname}%
  \noexpand\copy@kernel@robust@command
    \expandafter\noexpand\csname\@expl@cs@to@str@@N#1 \endcsname
    \expandafter\noexpand\csname\@expl@cs@to@str@@N#2 \endcsname}%
  \reserved@a}
\long\def\copy@kernel@robust@command#1#2{%
  \robust@command@chk@safe#2%
    {\@if@newcommand#2%
       {\@copy@newcommand}%
       {\declare@commandcopy@let}}
    {\declare@commandcopy@let}%
  #1#2}
```

`\@show@DeclareRobustCommand`
`\show@kernel@robust@command`

Showing the command is pretty simple. This command prints the top-level expansion as TEX's `\show` would, but with `robust macro:` rather than just `macro:`, then a blank line and then `\show` the inner command. For a macro defined with, say, `\DeclareRobustCommand\foo[1]{bar}`, it will print:

```
> \foo=robust macro:
->\protect \foo  .

> \foo =\long macro:
#1->bar.
```

If the inner command is defined with an optional argument, then `\@show@newcommand` is also used.

The value of `\escapechar` is deliberately not enforced, so `\ShowCommand` behaves more like `\show`.

```
\long\def\@show@DeclareRobustCommand#1{%
  \typeout{> \string#1=robust macro:}%
  \typeout{->\@expl@cs@replacement@spec@@N#1.^^J}%
  \expandafter\show@kernel@robust@command
    \csname\@expl@cs@to@str@@N#1 \endcsname}
\long\def\show@kernel@robust@command#1{%
  \robust@command@chk@safe#1%
    {\@if@newcommand#1%
       {\@show@newcommand}%
       {\show}}%
    {\show}%
  #1}
```

(*End definition for* `\@if@DeclareRobustCommand` *and others.*)

1.5.4 Commands defined with \newcommand (with optional argument)

\@if@newcommand

A command \cmd (or \cmd␣, if it was defined with \DeclareRobustCommand) with an optional argument will expand to \@protected@testopt\cmd\\cmd{<opt>}. To check that we look at the first three tokens in the expansion of \cmd, and return true or false accordingly.

This test *requires* that the command be a parameterless macro, otherwise it will not work (and probably break). This is ensured with \robust@command@chk@safe before calling \@if@newcommand.

```
\long\def\@if@newcommand#1{%
  \edef\reserved@a{%
    \noexpand\@protected@testopt
    \noexpand#1%
    \expandafter\noexpand\csname\@backslashchar\@expl@cs@to@str@@N#1\endcsname}%
  \edef\reserved@b{%
    \unexpanded\expandafter\expandafter\expandafter
      {\expandafter\@carcube#1{}{}{}\@nil}}%
  \ifx\reserved@a\reserved@b
    \expandafter\@firstoftwo
  \else
    \expandafter\@secondoftwo
  \fi}
```

\@copy@newcommand

Then, if a command \cmd takes an optional argument, we copy it to \foo by defining the latter to expand to \@protected@testopt\foo\\foo{<opt>}.

```
\long\def\@copy@newcommand#1#2{%
  \edef#1{\noexpand\@protected@testopt
    \noexpand#1%
    \expandafter\noexpand\csname\@backslashchar\@expl@cs@to@str@@N#1\endcsname
    \unexpanded\expandafter\expandafter\expandafter
      {\expandafter\@gobblethree#2}}%
  \expandafter
  \let\csname\@backslashchar\@expl@cs@to@str@@N#1\expandafter\endcsname
      \csname\@backslashchar\@expl@cs@to@str@@N#2\endcsname}
```

\@show@newcommand
\@show@newcommand@aux

A command being \shown here is guaranteed to have an optional argument. Start by showing the top-level expansion of the command (using \typeout to avoid TeX asking for interaction and extra context lines), then call \@show@newcommand@aux with the internal command, which contains the actual definition, and with the expansion of the command to extract the default value of the optional argument.

```
\long\def\@show@newcommand#1{%
  \typeout{> \string#1=robust macro:}%
  \typeout{->\@expl@cs@replacement@spec@@N#1.^^J}%
  \expandafter\@show@newcommand@aux
    \csname\@backslashchar\@expl@cs@to@str@@N#1\expandafter\endcsname
    \expandafter{#1}}
```

For a macro defined with, say, \newcommand\foo[1][opt]{bar}, it will print:

```
> \foo=robust macro:
->\@protected@testopt \foo \\foo {opt}.

> \\foo=\long macro:
```

```
> default #1=opt.
[#1]->bar.
```

If the command was defined with `\DeclareRobustCommand`, then another pair of lines show the top-level expansion `\protect␣\foo␣␣`.

The extra gymnastics with `\showtokens` ensures that `\showtokens` itself, and the internals of this macro aren't showed in the context lines.

```
\long\def\@show@newcommand@aux#1#2{%
  \typeout{> \string#1=\@expl@cs@prefix@spec@@N#1macro:}%
  \edef\reserved@a{%
    default \string##1=\expandafter\detokenize\@gobblethree#2.^^J%
    \@expl@cs@argument@spec@@N#1->\@expl@cs@replacement@spec@@N#1}%
  \showtokens\expandafter\expandafter\expandafter{\expandafter\reserved@a}}
```

Now the rollback code.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}{\@if@DeclareRobustCommand}
⟨latexrelease⟩  {Undefine \@if@DeclareRobustCommand, \@if@newcommand,
⟨latexrelease⟩            \@copy@DeclareRobustCommand, \@copy@newcommand,
⟨latexrelease⟩            \@show@DeclareRobustCommand, \@show@newcommand}%
⟨latexrelease⟩\let\@if@DeclareRobustCommand\@undefined
⟨latexrelease⟩\let\@copy@DeclareRobustCommand\@undefined
⟨latexrelease⟩\let\@show@DeclareRobustCommand\@undefined
⟨latexrelease⟩\let\@if@newcommand\@undefined
⟨latexrelease⟩\let\@copy@newcommand\@undefined
⟨latexrelease⟩\let\@show@newcommand\@undefined
%
⟨latexrelease⟩\let\copy@kernel@robust@command\@undefined
⟨latexrelease⟩\let\show@kernel@robust@command\@undefined
⟨latexrelease⟩\let\@show@newcommand@aux\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@if@newcommand` *and others.*)

1.6 Internal defining commands

These commands are used internally to define other LaTeX commands.

`\@ifundefined` Check if first arg is undefined or `\relax` and execute second or third arg depending,

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2018-04-01}{\@ifundefined}
⟨latexrelease⟩{Leave commands undefined in \@ifundefined}%
⟨*2ekernel | latexrelease⟩
```

Version using `\ifcsname` to avoid defining undefined tokens to `\relax`. Defined here to simplify using unmatched `\fi`.

```
\def\@ifundefined#1{%
  \ifcsname#1\endcsname\@ifundefin@d@i\else\@ifundefin@d@ii\fi{#1}}
```

```
\long\def\@ifundefin@d@i#1\fi#2{\fi
  \expandafter\ifx\csname #2\endcsname\relax
    \@ifundefin@d@ii
  \fi
  \@secondoftwo}
```

```
\long\def\@ifundefin@d@ii\fi#1#2#3{\fi #2}
```

Now test of engine.

```
\ifx\numexpr\@undefined
```

Classic version (should not be needed as etex is assumed).

```
\def\@ifundefined#1{%
  \expandafter\ifx\csname#1\endcsname\relax
    \expandafter\@firstoftwo
  \else
    \expandafter\@secondoftwo
  \fi}
\else\ifx\directlua\@undefined
```

Use the `\ifcsname` defined above.

```
\else
```

Optimised version for LuaTEX, using `\lastnamedcs`

```
\def\@ifundefined#1{%
  \ifcsname#1\endcsname
    \expandafter\ifx\lastnamedcs\relax\else\@ifundefin@d@i\fi
  \fi
  \@firstoftwo}
```

```
\long\def\@ifundefin@d@i#1#2#3#4#5{#1#2#5}
```

```
\fi
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}{\@ifundefined}
⟨latexrelease⟩{Leave commands undefined in \@ifundefined}%
⟨latexrelease⟩\def\@ifundefined#1{%
⟨latexrelease⟩  \expandafter\ifx\csname#1\endcsname\relax
⟨latexrelease⟩    \expandafter\@firstoftwo
⟨latexrelease⟩  \else
⟨latexrelease⟩    \expandafter\@secondoftwo
⟨latexrelease⟩  \fi}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@ifundefined`.)

`\@qend` `\@qrelax`

The following define `\@qend` and `\@qrelax` to be the strings '`end`' and '`relax`' with the characters `\catcode`d 12.

```
\edef\@qend{\expandafter\@cdr\string\end\@nil}
\edef\@qrelax{\expandafter\@cdr\string\relax\@nil}
```

(*End definition for* `\@qend` *and* `\@qrelax`.)

`\@ifnextchar`

`\@ifnextchar` peeks at the following character and compares it with its first argument. If both are the same it executes its second argument, otherwise its third.

```
\long\def\@ifnextchar#1#2#3{%
  \let\reserved@d=#1%
  \def\reserved@a{#2}%
  \def\reserved@b{#3}%
  \futurelet\@let@token\@ifnch}
```

(*End definition for* `\@ifnextchar`.)

`\kernel@ifnextchar` This macro is the kernel version of `\@ifnextchar` which is used in a couple of places to prevent the AMS variant from being used since in some places this produced chaos (for example if an `fd` file is loaded in a random place then the optional argument to `\ProvidesFile` could get printed there instead of being written only in the log file. This happened when there was a space or a newline between the mandatory and optional arguments! It should really be fixed in the `amsmath` package one day, but...

Note that there may be other places in the kernel where this version should be used rather than the original, but variable, version.

```
\let\kernel@ifnextchar\@ifnextchar
```

(*End definition for* `\kernel@ifnextchar`.)

`\@ifnch` `\@ifnch` is a tricky macro to skip any space tokens that may appear before the character in question. If it encounters a space token, it calls xifnch.

```
\def\@ifnch{%
  \ifx\@let@token\@sptoken
    \let\reserved@c\@xifnch
  \else
    \ifx\@let@token\reserved@d
      \let\reserved@c\reserved@a
    \else
      \let\reserved@c\reserved@b
    \fi
  \fi
  \reserved@c}
```

(*End definition for* `\@ifnch`.)

`\@sptoken` The following code makes `\@sptoken` a space token. It is important here that the control sequence `\:` consists of a non-letter only, so that the following whitespace is significant. Together with the fact that the equal sign in a `\let` may be followed by only one optional space the desired effect is achieved. NOTE: the following hacking must precede the definition of `\:` as math medium space.

```
\def\:{\let\@sptoken= } \:  % this makes \@sptoken a space token
```

(*End definition for* `\@sptoken`.)

`\@xifnch` In the following definition of `\@xifnch`, `\:` is again used to get a space token as delimiter into the definition.

```
\def\:{\@xifnch} \expandafter\def\: {\futurelet\@let@token\@ifnch}
```

(*End definition for* `\@xifnch`.)

`\@ifstar` The new implementation below avoids passing the ⟨*true code*⟩ Through one more `\def` than the ⟨*false code*⟩, which previously meant that `#` had to be written as `####` in one argument, but `##` in the other. The `*` is gobbled by `\@firstoftwo`.

```
\def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}
```

(*End definition for* `\@ifstar`.)

\@dblarg
\@xdblarg

```
\long\def\@dblarg#1{\kernel@ifnextchar[{#1}{\@xdblarg{#1}}}
\long\def\@xdblarg#1#2{#1[{#2}]{#2}}
```

(*End definition for* `\@dblarg` *and* `\@xdblarg`.)

\@sanitize

The command `\@sanitize` changes the catcode of all special characters except for braces to 'other'. It can be used for commands like `\index` that want to write their arguments verbatim. Needless to say, this command should only be executed within a group, or chaos will ensue.

```
\def\@sanitize{\@makeother\ \@makeother\\\@makeother\$\@makeother\&%
\@makeother\#\@makeother\^\@makeother\_\@makeother\%\@makeother\~}
```

(*End definition for* `\@sanitize`.)

\@onelevel@sanitize

This makes the whole "meaning" of `#1` (its one-level expansion) into catcode 12 tokens: it could be used in `\DeclareRobustCommand`.

If it is to be used on default float specifiers, this should be done when they are defined.

```
\def \@onelevel@sanitize #1{%
  \edef #1{\expandafter\strip@prefix
           \meaning #1}%
}
```

(*End definition for* `\@onelevel@sanitize`.)

\string@makeletter
\@string@makeletter
\char@if@alph

Iterates through a string, turning each alphabetic character into a catcode-11 token (partly undoes a `\detokenize`). Useful for `\ifx`-based string comparisons where `\detokenize`-ing the other string would break too much code.

The macro uses expl3's `\@expl@str@map@function@@NN` to iterate on the string (without losing spaces) and applies `\@string@makeletter` on each character. The latter checks if character is between a–z or A–Z, and uses `\@alph` or `\@Alph` to get the corresponding catcode-11 token. Other tokens are passed through unchanged.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\string@makeletter}
⟨latexrelease⟩  {Add \string@makeletter}%
⟨*2ekernel | latexrelease⟩
\def\string@makeletter#1{%
  \@expl@str@map@function@@NN#1\@string@makeletter}
\def\@string@makeletter#1{%
  \char@if@alph{#1}%
    {\@expl@char@generate@@nn{`#1}{11}}%
    {#1}}
\def\char@if@alph#1{%
  \ifnum0\ifnum`#1<`A 1\fi\ifnum`#1>`z 1\fi
      \if\ifnum`#1>`Z @\fi\ifnum`#1<`a @\fi01\fi>0
    \expandafter\@secondoftwo
  \else
    \expandafter\@firstoftwo
  \fi}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
%
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\string@makeletter}
⟨latexrelease⟩  {Undefine \string@makeletter}%
⟨latexrelease⟩\let\string@makeletter\@undefined
⟨latexrelease⟩\let\@string@makeletter\@undefined
⟨latexrelease⟩\let\char@if@alph\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\string@makeletter`, `\@string@makeletter`, *and* `\char@if@alph`.)

`\makeatletter` `\makeatother`

Make internal control sequences accessible or inaccessible.

```
\DeclareRobustCommand\makeatletter{\catcode`\@11\relax}
\DeclareRobustCommand\makeatother{\catcode`\@12\relax}
```

(*End definition for* `\makeatletter` *and* `\makeatother`.)

2 Discretionary Hyphenation

`\-` `\@dischyph`

Moved here to be after the definition of `\DeclareRobustCommand`.

The primitive `\-` command adds a discretionary hyphen using the current font's `\hyphenchar`. Monospace fonts are usually declared with `\hyphenchar` set to -1 to suppress hyphenation.

LaTeX, from LaTeX2.09 in 1986 defined `\-` by

```
\def\-{\discretionary{-}{}{}}
```

The following comment was added when these commands were first set up, 19 April 1986:

> the `\-` command is redefined to allow it to work in the `\ttfamily` type style, where automatic hyphenation is suppressed by setting `\hyphenchar` to -1. The original primitive TeX definition is saved as `\@@hyph` just in case anyone needs it.

LaTeX 2_ε, between 1993 and 2017, had a comment at this point saying that the definition "would probably change" because the definition always uses `-`. The definition used below was given in comments at this point during time.

In 2017 we finally enabled this definition by default, with the older LaTeX definition accessible via latexrelease as usual.

In LuaLaTeX the primitive definition of `\-` is used directly because it's use of extended hyphenation parameters means that `\-` works correctly even with `\hyphenchar` set to -1. This change makes `\-` under LuaLaTeX compatible with language specific hyphenation characters.

Temporary definition of `\@latex@info`, final definition is later.

```
\def\@latex@info#1{}
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\-}{Use primitive \- in Lua\LaTeX}%
⟨*2ekernel | latexrelease⟩
\ifx\directlua\@undefined
  \DeclareRobustCommand{\-}{%
    \discretionary{%
      \char \ifnum\hyphenchar\font<\z@
```

```
              \defaulthyphenchar
            \else
              \hyphenchar\font
            \fi
                 }{}{}%
  }
\else
  \let\-\@@hyph
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2017/04/15}{\-}{Use \hyphenchar in \-}%
⟨latexrelease⟩\DeclareRobustCommand{\-}{%
⟨latexrelease⟩  \discretionary{%
⟨latexrelease⟩    \char \ifnum\hyphenchar\font<\z@
⟨latexrelease⟩              \defaulthyphenchar
⟨latexrelease⟩           \else
⟨latexrelease⟩              \hyphenchar\font
⟨latexrelease⟩           \fi
⟨latexrelease⟩                 }{}{}%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\-}{Use \hyphenchar in \-}%
⟨latexrelease⟩\def\-{\discretionary{-}{}{}}
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨*2ekernel | latexrelease⟩
\let\@dischyph=\-
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
```

(*End definition for* `\-` *and* `\@dischyph`.)

Delayed from `ltvers.dtx`

```
\newif\if@includeinrelease
\@includeinreleasefalse
```

Delayed from `ltplain.dtx`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                 {\allowbreak}{Make various commands robust}%
\MakeRobust\allowbreak
\MakeRobust\bigbreak
\MakeRobust\break
\MakeRobust\dotfill
\MakeRobust\frenchspacing
\MakeRobust\goodbreak
\MakeRobust\hrulefill
\MakeRobust\medbreak
\MakeRobust\nobreak
\MakeRobust\nonfrenchspacing
\MakeRobust\obeylines
\MakeRobust\obeyspaces
\MakeRobust\slash
\MakeRobust\smallbreak
```

```
\MakeRobust\strut
\MakeRobust\underbar
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\allowbreak}{Make various commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\allowbreak
⟨latexrelease⟩\kernel@make@fragile\bigbreak
⟨latexrelease⟩\kernel@make@fragile\break
⟨latexrelease⟩\kernel@make@fragile\dotfill
⟨latexrelease⟩\kernel@make@fragile\frenchspacing
⟨latexrelease⟩\kernel@make@fragile\goodbreak
⟨latexrelease⟩\kernel@make@fragile\hrulefill
⟨latexrelease⟩\kernel@make@fragile\medbreak
⟨latexrelease⟩\kernel@make@fragile\nobreak
⟨latexrelease⟩\kernel@make@fragile\nonfrenchspacing
⟨latexrelease⟩\kernel@make@fragile\obeylines
⟨latexrelease⟩\kernel@make@fragile\obeyspaces
⟨latexrelease⟩\kernel@make@fragile\slash
⟨latexrelease⟩\kernel@make@fragile\smallbreak
⟨latexrelease⟩\kernel@make@fragile\strut
⟨latexrelease⟩\kernel@make@fragile\underbar
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\g@addto@macro` Globally add to the end of a macro. This macro is used by the kernel to add to its internal hooks.

```
\long\def\g@addto@macro#1#2{%
  \begingroup
    \toks@\expandafter{#1#2}%
    \xdef#1{\the\toks@}%
  \endgroup}
```

(*End definition for* `\g@addto@macro`.)

```
⟨/2ekernel⟩
```

File g
ltcmd.dtx

1 Creating document commands

Document commands should be created using the tools provided by this module: `\NewDocumentCommand`, etc., in almost all cases. This allows clean separation of document-level syntax from code-level interfaces. Users have a need to create new document commands, and as such a significant amount of documentation for ltcmd is provided as part of `usrguide3`. Here, additional material aimed at programmers is provided

```
⟨@@=cmd⟩
```

```
⟨*2ekernel⟩
\message{document commands,}
⟨/2ekernel⟩
```

ltcmd code contains an `^^@` character, which usually has catcode 15, so `\IncludeInRelease` will break when this code is being skipped, so we'll save the catcode of `^^@` to restore later:

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\edef\@latexrelease@catcode@null{\the\catcode`\^^@ }
⟨latexrelease⟩\catcode`\^^@=12
\ExplSyntaxOn
⟨latexrelease⟩\NewModuleRelease{2020/10/01}{ltcmd}
⟨latexrelease⟩                    {Document~command~parser}%
```

1.1 Variables and constants

`\l__cmd_arg_spec_tl` Holds the argument specification after normalization of shorthands.

```
\tl_new:N \l__cmd_arg_spec_tl
```

`\l__cmd_args_tl` Token list variable for grabbed arguments.

```
\tl_new:N \l__cmd_args_tl
```

`\l__cmd_args_i_tl` `\l__cmd_args_ii_tl` Hold the modified arguments when dealing with default values or processors.

```
\tl_new:N \l__cmd_args_i_tl
\tl_new:N \l__cmd_args_ii_tl
```

`\l__cmd_current_arg_int` The number of the current argument being set up: this is used to make sure there are at most 9 arguments, then for creating the expandable auxiliary functions and knowing how many arguments the code function should take.

```
\int_new:N \l__cmd_current_arg_int
```

`\l__cmd_defaults_bool`
`\l__cmd_defaults_tl`

The boolean indicates whether there are any argument with default value other than `-NoValue-`; the token list holds the code to determine these default values in terms of other arguments.

```
\bool_new:N \l__cmd_defaults_bool
\tl_new:N \l__cmd_defaults_tl
```

`\l__cmd_environment_bool`

Generating environments uses the same mechanism as generating functions. However, full processing of arguments is always needed for environments, and so the function-generating code needs to know this. This variable is also used at run time to give correct error messages.

```
\bool_new:N \l__cmd_environment_bool
```

`\l__cmd_environment_str`

Name of the environment, used at definition time and at run time.

```
\str_new:N \l__cmd_environment_str
```

`\l__cmd_expandable_bool`

Used to indicate if an expandable command is begin generated, as this affects both the acceptable argument types and how they are implemented.

```
\bool_new:N \l__cmd_expandable_bool
```

`\l__cmd_expandable_aux_name_tl`

Used to create pretty-printing names for the auxiliaries: although the immediate definition does not vary, the full expansion does and so it does not count as a constant.

```
\tl_new:N \l__cmd_expandable_aux_name_tl
\tl_set:Nn \l__cmd_expandable_aux_name_tl
  {
    \l__cmd_function_tl \c_space_tl
    ( arg~ \int_use:N \l__cmd_current_arg_int )
  }
```

`\g__cmd_grabber_int`

Used (in exceptional cases) to get unique names for grabbers used by expandable commands.

```
\int_new:N \g__cmd_grabber_int
```

`\l__cmd_fn_tl`

For passing the pre-formed name of the auxiliary to be used as the parsing function.

```
\tl_new:N \l__cmd_fn_tl
```

`\l__cmd_fn_code_tl`

For passing the pre-formed name of the auxiliary that contains the actual code.

```
\tl_new:N \l__cmd_fn_code_tl
```

`\l__cmd_function_tl` Holds the control sequence name of the function currently being defined: used to avoid passing this as an argument and to avoid repeated use of `\cs_to_str:N`.

```
\tl_new:N \l__cmd_function_tl
```

`\l__cmd_grab_expandably_bool`

When defining a non-expandable command, indicates whether the arguments can all safely be grabbed by expandable grabbers. This is to support abuses of xparse that use protected functions inside csname constructions.

```
\bool_new:N \l__cmd_grab_expandably_bool
```

`\l__cmd_obey_spaces_bool` For trailing optionals.

```
\bool_new:N \l__cmd_obey_spaces_bool
```

`\l__cmd_last_delimiters_tl` Holds the delimiters (first tokens) of all optional arguments since the previous mandatory argument, to warn about cases where it would be impossible to omit optional arguments completely because the following mandatory argument has the same delimiter as one of the optional arguments.

```
\tl_new:N \l__cmd_last_delimiters_tl
```

`\l__cmd_long_bool` Used to indicate that an argument is long, on a per-argument basis.

```
\bool_new:N \l__cmd_long_bool
```

`\l__cmd_m_args_int` The number of `m` arguments: if this is the same as the total number of arguments, then a short-cut can be taken in the creation of the grabber code.

```
\int_new:N \l__cmd_m_args_int
```

`\l__cmd_prefixed_bool` When preparing the signature of non-expandable commands, indicates that the current argument is affected by a processor or by `+` (namely is long).

```
\bool_new:N \l__cmd_prefixed_bool
```

`\l__cmd_process_all_tl`
`\l__cmd_process_one_tl`
`\l__cmd_process_some_bool`

When preparing the signature, the processors that will be applied to a given argument are collected in `\l__cmd_process_one_tl`, while `\l__cmd_process_all_tl` contains processors for all arguments. The boolean indicates whether there are any processors (to bypass the whole endeavour otherwise).

```
\tl_new:N \l__cmd_process_all_tl
\tl_new:N \l__cmd_process_one_tl
\bool_new:N \l__cmd_process_some_bool
```

\l__cmd_saved_args_tl

Stores \l__cmd_args_tl to deal with space-trimming of b-type arguments.

```
\tl_new:N \l__cmd_saved_args_tl
```

\l__cmd_signature_tl

Used when constructing the signature (code for argument grabbing) to hold what will become the implementation of the main function. When arguments are grabbed (at point of use of the command/environment), it also stores the code for grabbing the remaining arguments.

```
\tl_new:N \l__cmd_signature_tl
```

\l__cmd_some_obey_spaces_bool
\l__cmd_some_long_bool
\l__cmd_some_short_bool

These flags are set while normalizing the argument specification. The obey_spaces one is used to detect when ! is used on an argument that is not a trailing optional argument. The other two are used to check whether all short arguments appear before long arguments: this is needed to grab arguments expandably. As soon as the first long argument is seen (other than t-type, whose long status is ignored) the some_long flag is set. The some_short flag is used for expandable commands, to know whether to define a short auxiliary too.

```
\bool_new:N \l__cmd_some_obey_spaces_bool
\bool_new:N \l__cmd_some_long_bool
\bool_new:N \l__cmd_some_short_bool
```

\l__cmd_tmp_prop
\l__cmd_tmpa_tl
\l__cmd_tmpb_tl

Scratch space.

```
\prop_new:N \l__cmd_tmp_prop
\tl_new:N \l__cmd_tmpa_tl
\tl_new:N \l__cmd_tmpb_tl
\cs_new_eq:NN \__cmd_tmp:w ?
```

(*End definition for* __cmd_tmp:w.)

With xparse, information about commands being (re)defined was switched off by default, unless the log-declarations package option was used, so here we'll switch that off as well.

```
\msg_redirect_module:nnn { cmd } { info } { none }
```

Also add cmd to the LaTeX messages.

```
\prop_gput:Nnn \g_msg_module_type_prop { cmd } { LaTeX }
```

1.2 Declaring commands and environments

__cmd_declare_cmd:Nnn
__cmd_declare_expandable_cmd:Nnn
__cmd_declare_cmd_aux:Nnn
__cmd_declare_cmd_internal:Nnnn

The main functions for creating commands set the appropriate flag then use the same internal code to do the definition.

```
\cs_new_protected:Npn \__cmd_declare_cmd:Nnn
  {
    \bool_set_false:N \l__cmd_expandable_bool
```

```
    \__cmd_declare_cmd_aux:Nnn
  }
\cs_new_protected:Npn \__cmd_declare_expandable_cmd:Nnn
  {
    \bool_set_true:N \l__cmd_expandable_bool
    \__cmd_declare_cmd_aux:Nnn
  }
```

The first stage is to log information, both for the user in the log and for programmatic use in a property list of all declared commands.

```
\cs_new_protected:Npn \__cmd_declare_cmd_aux:Nnn #1#2#3
  {
    \cs_if_exist:NTF #1
      {
        \msg_info:nnxx { cmd } { redefine }
          { \token_to_str:N #1 } { \tl_to_str:n {#2} }
      }
      {
        \bool_lazy_or:nnT
          { \cs_if_exist_p:c { \cs_to_str:N #1 ~ code } }
          { \cs_if_exist_p:c { \cs_to_str:N #1 ~ defaults } }
          {
            \msg_warning:nnx { cmd } { unsupported-let }
              { \token_to_str:N #1 }
          }
        \msg_info:nnxx { cmd } { define-command }
          { \token_to_str:N #1 } { \tl_to_str:n {#2} }
      }
    \bool_set_false:N \l__cmd_environment_bool
    \__cmd_declare_cmd_internal:Nnnn #1 {#2} {#3} { }
  }
```

At definition time, the variable `\l__cmd_fn_tl` is only used for error messages. The real business of defining a document command starts with setting up the appropriate name, then normalizing the argument specification to get rid of shorthands.

```
\cs_new_protected:Npn \__cmd_declare_cmd_internal:Nnnn #1#2#3#4
  {
    \tl_set:Nx \l__cmd_function_tl { \cs_to_str:N #1 }
    \tl_set:Nx \l__cmd_fn_tl
      { \exp_not:c { \l__cmd_function_tl \c_space_tl } }
    \__cmd_normalize_arg_spec:n {#2}
    \exp_args:No \__cmd_prepare_signature:n \l__cmd_arg_spec_tl
    \__cmd_declare_cmd_code:Nnn #1 {#2} {#3}
    #4
    \__cmd_break_point:n {#2}
  }
```

(*End definition for* `\__cmd_declare_cmd:Nnn` *and others.*)

`\__cmd_break_point:n` A marker used to escape from creating a definition if necessary.

```
\cs_new_eq:NN \__cmd_break_point:n \use_none:n
```

(*End definition for* `\__cmd_break_point:n`.)

__cmd_declare_cmd_code:Nnn
__cmd_declare_cmd_code_aux:Nnn
__cmd_declare_cmd_code_expandable:Nnn

The appropriate auxiliary is called.

```
\cs_new_protected:Npn \__cmd_declare_cmd_code:Nnn
  {
    \bool_if:NTF \l__cmd_grab_expandably_bool
      { \__cmd_declare_cmd_code_expandable:Nnn }
      { \__cmd_declare_cmd_code_aux:Nnn }
   }
```

Standard functions call `\__cmd_start:nNNnnn`, which receives the argument specification, an auxiliary used for grabbing arguments, an auxiliary containing the code, and then the signature, default arguments, and processors.

```
\cs_new_protected:Npn \__cmd_declare_cmd_code_aux:Nnn #1#2#3
  {
    \cs_generate_from_arg_count:cNnn
      { \l__cmd_function_tl \c_space_tl code }
      \cs_set_protected:Npn \l__cmd_current_arg_int {#3}
    \cs_set_protected_nopar:Npx #1
      {
        \bool_if:NTF \l__cmd_environment_bool
          {
            \__cmd_start_env:nnnnn { \exp_not:n {#2} }
              { \l__cmd_environment_str }
          }
          {
            \__cmd_start:nNNnnn { \exp_not:n {#2} }
              \exp_not:c { \l__cmd_function_tl \c_space_tl }
              \exp_not:c { \l__cmd_function_tl \c_space_tl code }
          }
          { \exp_not:o \l__cmd_signature_tl }
          {
            \bool_if:NT \l__cmd_defaults_bool
              { \exp_not:o \l__cmd_defaults_tl }
          }
          {
            \bool_if:NT \l__cmd_process_some_bool
              { \exp_not:o \l__cmd_process_all_tl }
          }
      }
  }
```

Expandable functions and functions whose arguments can be grabbed expandably call `\__cmd_start_expandable:nNNNNn`, which receives the argument specification, four auxiliaries (two for grabbing arguments, one for the code, and one for default arguments), and finally the signature. Non-expandable functions that take this branch should nevertheless be protected, as well as their `code` function. They will only be expanded in contexts such as constructing a csname. The two grabbers (named after the function with one or two spaces) are needed when there are both short and long arguments; otherwise the same grabber is included twice in the definition. If all arguments are long or all are short the (only) grabber is defined correspondingly to be long/short. Otherwise two grabbers are defined, one long, one short.

```
\cs_new_protected:Npn \__cmd_declare_cmd_code_expandable:Nnn #1#2#3
  {
    \exp_args:Ncc \cs_generate_from_arg_count:NNnn
      { \l__cmd_function_tl \c_space_tl code }
```

```
      { cs_set \bool_if:NF \l__cmd_expandable_bool { _protected } :Npn }
      \l__cmd_current_arg_int {#3}
    \bool_if:NT \l__cmd_defaults_bool
      {
        \use:x
          {
            \cs_generate_from_arg_count:cNnn
              { \l__cmd_function_tl \c_space_tl defaults }
              \cs_set:Npn \l__cmd_current_arg_int
              { \exp_not:o \l__cmd_defaults_tl }
          }
      }
    \bool_if:NTF \l__cmd_expandable_bool
      { \cs_set_nopar:Npx } { \cs_set_protected_nopar:Npx } #1
      {
        \exp_not:N \__cmd_start_expandable:nNNNNn
          { \exp_not:n {#2} }
          \exp_not:c { \l__cmd_function_tl \c_space_tl }
          \exp_not:c
            {
              \l__cmd_function_tl \c_space_tl
              \bool_if:NT \l__cmd_some_short_bool
                { \bool_if:NT \l__cmd_some_long_bool { \c_space_tl } }
            }
          \exp_not:c { \l__cmd_function_tl \c_space_tl code }
          \bool_if:NTF \l__cmd_defaults_bool
            { \exp_not:c { \l__cmd_function_tl \c_space_tl defaults } }
            { ? }
          { \exp_not:o \l__cmd_signature_tl }
      }
    \bool_if:NTF \l__cmd_some_long_bool
      {
        \bool_if:NT \l__cmd_some_short_bool
          {
            \cs_set_nopar:cpx { \l__cmd_function_tl \c_space_tl \c_space_tl }
              ##1##2 { ##1 {##2} }
          }
        \cs_set:cpx
      }
      { \cs_set_nopar:cpx }
          { \l__cmd_function_tl \c_space_tl } ##1##2 { ##1 {##2} }
  }
```

(*End definition for* `\__cmd_declare_cmd_code:Nnn`, `\__cmd_declare_cmd_code_aux:Nnn`, *and* `\__cmd_declare_cmd_code_expandable:Nnn`.)

`\__cmd_declare_env:nnnn`
`\__cmd_declare_env_internal:nnnn`

The lead-off to creating an environment is much the same as that for creating a command: issue the appropriate message, store the argument specification then hand off to an internal function.

```
\cs_new_protected:Npn \__cmd_declare_env:nnnn #1#2
  {
    \str_set:Nx \l__cmd_environment_str {#1}
    \str_set:Nx \l__cmd_environment_str
      { \tl_trim_spaces:o { \l__cmd_environment_str } }
```

```
    \cs_if_exist:cTF { \l__cmd_environment_str }
      {
        \msg_info:nnxx { cmd } { redefine-env }
          { \l__cmd_environment_str } { \tl_to_str:n {#2} }
      }
      {
        \msg_info:nnxx { cmd } { define-env }
          { \l__cmd_environment_str } { \tl_to_str:n {#2} }
      }
    \bool_set_false:N \l__cmd_expandable_bool
    \bool_set_true:N \l__cmd_environment_bool
    \exp_args:NV \__cmd_declare_env_internal:nnnn
      \l__cmd_environment_str {#2}
  }
```

Creating a document environment requires a few more steps than creating a single command. In order to pass the arguments of the command to the end of the function, it is necessary to store the grabbed arguments. To do that, the function used at the end of the environment has to be redefined to contain the appropriate information. To minimize the amount of expansion at point of use, the code here is expanded now as well as when used. The last argument of `\__cmd_declare_cmd_internal:Nnnn` is only run if the definition succeeded. In package mode this ensures that the original definition of the environment is not changed if the definition fails for any reason. This also avoids an error when defining the `end␣aux␣` function when the user asks for more than 9 arguments.

```
\cs_new_protected:Npn \__cmd_declare_env_internal:nnnn #1#2#3#4
  {
    \exp_args:Nc \__cmd_declare_cmd_internal:Nnnn { environment~ #1 } {#2}
      {#3}
      {
        \cs_set_nopar:cpx { environment~ #1 ~end }
          { \exp_not:c { environment~ #1 ~end~aux } }
        \cs_generate_from_arg_count:cNnn
          { environment~ #1 ~end~aux~ } \cs_set:Npn
          \l__cmd_current_arg_int {#4}
        \cs_set_eq:cc {#1}       { environment~ #1 }
        \cs_set_eq:cc { end #1 } { environment~ #1 ~end }
      }
  }
\cs_new_protected:Npn \__cmd_set_environment_end:n #1
  {
    \cs_set_nopar:cpx { environment~ #1 ~end~aux }
      {
        \exp_not:c { environment~ #1 ~end~aux~ }
        \exp_not:o \l__cmd_args_tl
      }
  }
```

(*End definition for* `\__cmd_declare_env:nnnn` *and* `\__cmd_declare_env_internal:nnnn`.)

1.3 Structure of xparse commands

`\__cmd_start_env:nnnnn`
`\__cmd_start:nNNnnn`

For error messages that occur during run-time when getting arguments of environments it is necessary to keep track of the environment name. We begin non-expandable commands with a token equal to `\scan_stop:`, whose name gives a reasonable error message

if the command is used inside a csname and protects against f-expansion. This is useless for environments since \begin is already not expandable. Both the command and environment codes start with \group_align_safe_begin:, then __cmd_run_code: (used by both) does \group_align_safe_end:, so that delimited arguments may be grabbed in alignments if they contain and alignment tab token (see latex3/latex3/issues/839).

```
\cs_new_protected:Npn \__cmd_start_env:nnnnn #1#2
  {
    \conditionally@traceoff
    \group_align_safe_begin:
    \str_set:Nn \l__cmd_environment_str {#2}
    \bool_set_true:N \l__cmd_environment_bool
    \__cmd_start_aux:ccnnnn
      { environment~ \l__cmd_environment_str \c_space_tl }
      { environment~ \l__cmd_environment_str \c_space_tl code }
      {#1}
  }
\cs_new_protected:Npx \__cmd_start:nNNnnn #1#2#3
  {
    \exp_not:c { xparse~function~is~not~expandable }
    \exp_not:N \conditionally@traceoff
    \exp_not:N \group_align_safe_begin:
    \exp_not:n { \bool_set_false:N \l__cmd_environment_bool }
    \exp_not:N \__cmd_start_aux:NNnnnn
    #2 #3 {#1}
  }
```

(*End definition for* __cmd_start_env:nnnnn *and* __cmd_start:nNNnnn.)

__cmd_start_aux:NNnnnn
__cmd_start_aux:ccnnnn

This sets up a few variables to minimize the boilerplate code included in all xparse-defined commands. It then runs the grabbers #4. Again, the argument specification #1 is only for diagnostics.

```
\cs_new_protected:Npn \__cmd_start_aux:NNnnnn #1#2#3#4#5#6
  {
    \tl_clear:N \l__cmd_args_tl
    \tl_set:Nn \l__cmd_fn_tl {#1}
    \tl_set:Nn \l__cmd_fn_code_tl {#2}
    \tl_set:Nn \l__cmd_defaults_tl {#5}
    \tl_set:Nn \l__cmd_process_all_tl {#6}
    #4
    \__cmd_run_code:
  }
\cs_generate_variant:Nn \__cmd_start_aux:NNnnnn { cc }
```

(*End definition for* __cmd_start_aux:NNnnnn.)

__cmd_run_code:

After arguments are grabbed, this function is responsible for inserting default values, running processors, and finally doing \group_align_safe_end: as promised, and running the code.

```
\cs_new_protected:Npn \__cmd_run_code:
  {
    \tl_if_empty:NF \l__cmd_defaults_tl { \__cmd_defaults: }
    \tl_if_empty:NF \l__cmd_process_all_tl { \__cmd_args_process: }
    \bool_if:NT \l__cmd_environment_bool
      { \exp_args:No \__cmd_set_environment_end:n \l__cmd_environment_str }
```

```
    \group_align_safe_end:
    \conditionally@traceon
    \exp_after:wN \l__cmd_fn_code_tl \l__cmd_args_tl
  }
```

(*End definition for* `\__cmd_run_code:`.)

`\__cmd_defaults:`
`\__cmd_defaults_def:`
`\__cmd_defaults_def:nn`
`\__cmd_defaults_def:nnn`
`\__cmd_defaults_aux:`
`\__cmd_defaults_error:w`

First construct `\__cmd_tmp:w` (see below) that will receive the arguments found so far and determine default values for any missing argument. Then call it repeatedly until the set of arguments stabilizes. Since that could lead to an infinite loop we only call it up to nine times, the maximal number needed for stabilization if there is a chain of arguments that depend on each other. If that fails to stabilize raise an error.

```
\cs_new_protected:Npn \__cmd_defaults:
  {
    \__cmd_defaults_def:
    \tl_set_eq:NN \l__cmd_args_i_tl \l__cmd_args_tl
    \__cmd_defaults_aux: \__cmd_defaults_aux: \__cmd_defaults_aux:
    \__cmd_defaults_aux: \__cmd_defaults_aux: \__cmd_defaults_aux:
    \__cmd_defaults_aux: \__cmd_defaults_aux: \__cmd_defaults_aux:
    \__cmd_defaults_error:w
    \q_recursion_stop
    \tl_set_eq:NN \l__cmd_args_tl \l__cmd_args_i_tl
  }
\cs_new_protected:Npn \__cmd_defaults_aux:
  {
    \tl_set:Nx \l__cmd_args_ii_tl
      { \exp_after:wN \__cmd_tmp:w \l__cmd_args_i_tl }
    \tl_if_eq:NNT \l__cmd_args_ii_tl \l__cmd_args_i_tl
      { \use_none_delimit_by_q_recursion_stop:w }
    \tl_set_eq:NN \l__cmd_args_i_tl \l__cmd_args_ii_tl
  }
\cs_new_protected:Npn \__cmd_defaults_error:w \q_recursion_stop
  {
    \msg_error:nnx { cmd } { default-loop }
      { \__cmd_environment_or_command: }
  }
```

To construct `\__cmd_tmp:w`, first go through the arguments found and the corresponding defaults, building a token list with `{#`⟨*arg number*⟩`}` for arguments found in the input (whose default will not be used) and otherwise `{\exp_not:n{`⟨*default*⟩`}}` for arguments whose default will be used.

```
\cs_new_protected:Npn \__cmd_defaults_def:
  {
    \tl_clear:N \l__cmd_tmpa_tl
    \int_zero:N \l__cmd_current_arg_int
    \__cmd_tl_mapthread_function:NNN \l__cmd_args_tl \l__cmd_defaults_tl
      \__cmd_defaults_def:nn
    \cs_generate_from_arg_count:NNVo \__cmd_tmp:w \cs_set:Npn
      \l__cmd_current_arg_int \l__cmd_tmpa_tl
  }
\cs_generate_variant:Nn \cs_generate_from_arg_count:NNnn { NNVo }
\cs_new_protected:Npn \__cmd_defaults_def:nn
  {
    \int_incr:N \l__cmd_current_arg_int
```

```
    \exp_args:NV \__cmd_defaults_def:nnn \l__cmd_current_arg_int
  }
\cs_new_protected:Npn \__cmd_defaults_def:nnn #1#2#3
  {
    \tl_put_right:Nx \l__cmd_tmpa_tl
      {
        {
          \exp_not:N \exp_not:n
            {
              \tl_if_novalue:nTF {#2}
                { \exp_not:o {#3} }
                { \exp_not:n { ## #1 } }
            }
        }
      }
  }
```

(*End definition for* `\__cmd_defaults:` *and others.*)

`\__cmd_args_process:`
`\__cmd_args_process_loop:nn`
`\__cmd_args_process_aux:n`

Loop through arguments (stored in `\l__cmd_args_tl`) and the corresponding processors (in `\l__cmd_process_all_tl`) simultaneously, apply all processors for each argument and store the result back into `\l__cmd_args_tl`. To allow processors to depend on other arguments, for every processor define a temporary auxiliary that receives all arguments `\l__cmd_args_tl`.

```
\cs_new_protected:Npn \__cmd_args_process:
  {
    \tl_clear:N \l__cmd_args_ii_tl
    \__cmd_tl_mapthread_function:NNN
      \l__cmd_args_tl
      \l__cmd_process_all_tl
      \__cmd_args_process_loop:nn
    \tl_set_eq:NN \l__cmd_args_tl \l__cmd_args_ii_tl
  }
\cs_new_protected:Npn \__cmd_args_process_loop:nn #1#2
  {
    \tl_set:Nn \ProcessedArgument {#1}
    \tl_if_novalue:nF {#1}
      { \tl_map_function:nN {#2} \__cmd_args_process_aux:n }
    \tl_put_right:No \l__cmd_args_ii_tl
      { \exp_after:wN { \ProcessedArgument } }
  }
\cs_new_protected:Npn \__cmd_args_process_aux:n #1
  {
    \cs_generate_from_arg_count:NNnn \__cmd_tmp:w \cs_set:Npn
      { \tl_count:N \l__cmd_args_tl } {#1}
    \exp_args:NNNo \exp_after:wN \__cmd_tmp:w \l__cmd_args_tl
      { \ProcessedArgument }
  }
```

(*End definition for* `\__cmd_args_process:`, `\__cmd_args_process_loop:nn`, *and* `\__cmd_args_process_aux:n`.)

`\__cmd_start_expandable:nNNNNn`

This is called for all expandable commands. `#6` is the signature, responsible for grabbing arguments. `#5` is used to determine default values (or is `?` if there are none). `#4` is

the code to run. #2 and #3 are functions (named after the command) that grab a single argument in the input stream (#3 is short). The argument specification #1 is only used by diagnostic functions. Same as for the non-expandable version, this starts with \group_-align_safe_begin:, which expands to nothing, so may be safely used in an expandable context.

```
\cs_new:Npn \__cmd_start_expandable:nNNNNn #1#2#3#4#5#6
  {
    \group_align_safe_begin:
    #6 \__cmd_end_expandable:NNw #5 #4 \q__cmd #2#3
  }
```

(*End definition for* __cmd_start_expandable:nNNNNn.)

__cmd_end_expandable:NNw
__cmd_end_expandable_aux:w
__cmd_end_expandable_aux:nNNNN
__cmd_end_expandable_defaults:nnnNNn
__cmd_end_expandable_defaults:nnw
__cmd_end_expandable_defaults:nw

Followed by a function #1 to determine default values (or ? if there are no defaults), the code #2, arguments that have been grabbed, then \q__cmd and two generic grabbers. The idea to find default values is similar to the non-expandable case but we cannot define an auxiliary function, so at every step in the loop we need to go through all arguments searching for which ones started out as -NoValue- and replacing these by the newly computed values. In fact we need to keep track of three versions of all arguments: the original version, the previous version with default values, and the currently built version (first argument of __cmd_end_expandable_defaults:nnnNNn).

```
\cs_new:Npn \__cmd_end_expandable:NNw #1#2
  { \__cmd_end_expandable_aux:w #1#2 \prg_do_nothing: }
\cs_new:Npn \__cmd_end_expandable_aux:w #1#2#3 \q__cmd
  { \exp_args:No \__cmd_end_expandable_aux:nNNNN {#3} #1 #2 }
\cs_new:Npn \__cmd_end_expandable_aux:nNNNN #1#2#3#4#5
  {
    \token_if_eq_charcode:NNT ? #2 { \exp_after:wN \use_iv:nnnn }
    \__cmd_end_expandable_defaults:nnnNNn {#1} { } {#1} #2#3
      { } { } { } { } { } { } { } { } { } { }
      {
        \msg_expandable_error:nnf { cmd } { default-loop }
          { \exp_args:Nf \tl_trim_spaces:n { \token_to_str:N #4 } }
        \use_iv:nnnn
      }
    \q_stop
  }
\cs_new:Npn \__cmd_end_expandable_defaults:nnnNNn #1#2#3#4#5#6
  {
    #6
    \str_if_eq:nnTF {#1} {#2}
      { \use_i_delimit_by_q_stop:nw { \group_align_safe_end: #5 #1 } }
      {
        \exp_args:No \__cmd_tl_mapthread_function:nnN
          { #4 #1 } {#3}
          \__cmd_end_expandable_defaults:nnw
        \__cmd_end_expandable_defaults:nnnNNn { } {#1} {#3} #4 #5
      }
  }
\cs_new:Npn \__cmd_end_expandable_defaults:nnw #1#2
  {
    \tl_if_novalue:nTF {#2}
      { \exp_args:No \__cmd_end_expandable_defaults:nw {#1} }
```

```
      { \__cmd_end_expandable_defaults:nw {#2} }
  }
\cs_new:Npn \__cmd_end_expandable_defaults:nw
    #1#2 \__cmd_end_expandable_defaults:nnnNNn #3
  { #2 \__cmd_end_expandable_defaults:nnnNNn { #3 {#1} } }
```

(*End definition for* `\__cmd_end_expandable:NNw` *and others.*)

1.4 Normalizing the argument specifications

The goal here is to expand aliases and check that the argument specification is valid before the main parsing run. If it is not valid the entire set up is abandoned to avoid any strange internal errors. A function is provided for each argument type that will grab any extra data items and call the loop function after performing the following checks and tasks.

- Check that each argument has the correct number of data items associated with it, and that where a single character is required, one has actually been supplied.
- Check that processors and the markers `+` and `!` are followed by an argument for which they make sense, and are not redundant.
- Check the absence of forbidden types for expandable commands, namely `G`/`v` always, and `l`/`u` after optional arguments (xparse may have inserted braces due to a failed search for an optional argument).
- Check that no optional argument is followed by a mandatory argument with the same delimiter, as otherwise the optional argument could never be omitted.
- Keep track in `\l__cmd_some_long_bool` and `\l__cmd_some_short_bool` of whether the command has some long/short arguments.
- Keep track in `\l__cmd_grab_expandably_bool` of whether all arguments are `m`/`l`/`u` type and short arguments appear before long ones, in which case they can be grabbed expandably just as safely as they could be grabbed nonexpandably. Regardless of that, arguments of expandable commands will be grabbed expandably and arguments of environments will not (because the list of arguments built by non-expandable grabbing is used to pass them to the end-environment code).

Further checks happen at the end of the loop:

- that there are at most 9 arguments;
- that an expandable command does not end with an optional argument (this case is detected by using the fact that `\l__cmd_last_delimiters_tl` is cleared by every mandatory argument and filled by every optional argument).

`\__cmd_normalize_arg_spec:n`
`\__cmd_normalize_arg_spec_loop:n`

Loop through the argument specification, calling an auxiliary specific to each argument type. If any argument is unknown stop the definition.

```
\cs_new_protected:Npn \__cmd_normalize_arg_spec:n #1
  {
    \int_zero:N \l__cmd_current_arg_int
    \tl_clear:N \l__cmd_last_delimiters_tl
    \tl_clear:N \l__cmd_arg_spec_tl
```

```
    \bool_set_true:N \l__cmd_grab_expandably_bool
    \bool_set_false:N \l__cmd_obey_spaces_bool
    \bool_set_false:N \l__cmd_long_bool
    \bool_set_false:N \l__cmd_some_obey_spaces_bool
    \bool_set_false:N \l__cmd_some_long_bool
    \bool_set_false:N \l__cmd_some_short_bool
    \__cmd_normalize_arg_spec_loop:n #1
      \q_recursion_tail \q_recursion_tail \q_recursion_tail \q_recursion_stop
    \int_compare:nNnT \l__cmd_current_arg_int > 9
      {
        \msg_error:nnxx { cmd } { too-many-args }
          { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
        \__cmd_bad_def:wn
      }
    \bool_if:NT \l__cmd_expandable_bool
      {
        \tl_if_empty:NF \l__cmd_last_delimiters_tl
          {
            \msg_error:nnxx { cmd } { expandable-ending-optional }
              { \iow_char:N \\ \l__cmd_function_tl } { \tl_to_str:n {#1} }
            \__cmd_bad_def:wn
          }
      }
    \bool_if:NT \l__cmd_expandable_bool
      { \bool_set_true:N \l__cmd_grab_expandably_bool }
    \bool_if:NT \l__cmd_environment_bool
      { \bool_set_false:N \l__cmd_grab_expandably_bool }
  }
\cs_new_protected:Npn \__cmd_normalize_arg_spec_loop:n #1
  {
    \quark_if_recursion_tail_stop:n {#1}
    \int_incr:N \l__cmd_current_arg_int
    \cs_if_exist_use:cF { __cmd_normalize_type_ \tl_to_str:n {#1} :w }
      {
        \bool_lazy_any:nTF
          {
            { \str_if_eq_p:nn {#1} { G } }
            { \str_if_eq_p:nn {#1} { g } }
            { \str_if_eq_p:nn {#1} { l } }
            { \str_if_eq_p:nn {#1} { u } }
          }
          {
            \msg_error:nnxx { cmd } { xparse-arg-type }
              { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
          }
          {
            \msg_error:nnxx { cmd } { unknown-argument-type }
              { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
          }
        \__cmd_bad_def:wn
      }
  }
```

(*End definition for* `\__cmd_normalize_arg_spec:n` *and* `\__cmd_normalize_arg_spec_loop:n`.)

__cmd_normalize_type_d:w
__cmd_normalize_type_e:w
__cmd_normalize_type_o:w
__cmd_normalize_type_O:w
__cmd_normalize_type_r:w
__cmd_normalize_type_s:w

These argument types are aliases of more general ones, for example with the default argument `-NoValue-`. To easily insert that marker expanded in the definitions we call `\__cmd_tmp:w` with the argument `-NoValue-`. For argument types that need additional data, check that the data is present (not `\q_recursion_tail`) before proceeding.

```
\cs_set_protected:Npn \__cmd_tmp:w #1
  {
    \cs_new_protected:Npn \__cmd_normalize_type_d:w ##1##2
      {
        \quark_if_recursion_tail_stop_do:nn {##2} { \__cmd_bad_arg_spec:wn }
        \__cmd_normalize_type_D:w {##1} {##2} {#1}
      }
    \cs_new_protected:Npn \__cmd_normalize_type_e:w ##1
      {
        \quark_if_recursion_tail_stop_do:nn {##1} { \__cmd_bad_arg_spec:wn }
        \__cmd_normalize_type_E:w {##1} { }
      }
    \cs_new_protected:Npn \__cmd_normalize_type_o:w
      { \__cmd_normalize_type_D:w [ ] {#1} }
    \cs_new_protected:Npn \__cmd_normalize_type_O:w
      { \__cmd_normalize_type_D:w [ ] }
    \cs_new_protected:Npn \__cmd_normalize_type_r:w ##1##2
      {
        \quark_if_recursion_tail_stop_do:nn {##2} { \__cmd_bad_arg_spec:wn }
        \__cmd_normalize_type_R:w {##1} {##2} {#1}
      }
    \cs_new_protected:Npn \__cmd_normalize_type_s:w
      { \__cmd_normalize_type_t:w * }
  }
\exp_args:No \__cmd_tmp:w { \c_novalue_tl }
```

(*End definition for* `\__cmd_normalize_type_d:w` *and others.*)

__cmd_normalize_type_>:w
__cmd_normalize_type_+:w
__cmd_normalize_type_!:w

Check that these prefixes have arguments, namely that the next token is not `\q_recursion_tail`, and remember to leave it after the looping macro. Processors are forbidden in expandable commands. If all is good, store the prefix in the cleaned up `\l__cmd_arg_spec_tl`, and decrement the argument number as prefixes do not correspond to arguments.

```
\cs_new_protected:cpn { __cmd_normalize_type_>:w } #1#2
  {
    \quark_if_recursion_tail_stop_do:nn {#2} { \__cmd_bad_arg_spec:wn }
    \bool_if:NT \l__cmd_expandable_bool
      {
        \msg_error:nnxx { cmd } { processor-in-expandable }
          { \iow_char:N \\ \l__cmd_function_tl } { \tl_to_str:n {#1} }
        \__cmd_bad_def:wn
      }
    \tl_put_right:Nx \l__cmd_arg_spec_tl { > { \tl_trim_spaces:n {#1} } }
    \int_decr:N \l__cmd_current_arg_int
    \bool_set_false:N \l__cmd_grab_expandably_bool
    \__cmd_normalize_arg_spec_loop:n {#2}
  }
\cs_new_protected:cpn { __cmd_normalize_type_+:w } #1
  {
```

```
    \quark_if_recursion_tail_stop_do:nn {#1} { \__cmd_bad_arg_spec:wn }
    \bool_if:NT \l__cmd_long_bool
      {
        \msg_error:nnxx { cmd } { two-markers }
          { \__cmd_environment_or_command: } { + }
        \__cmd_bad_def:wn
      }
    \bool_set_true:N \l__cmd_long_bool
    \int_decr:N \l__cmd_current_arg_int
    \__cmd_normalize_arg_spec_loop:n {#1}
  }
\cs_new_protected:cpn { __cmd_normalize_type_!:w } #1
  {
    \quark_if_recursion_tail_stop_do:nn {#1} { \__cmd_bad_arg_spec:wn }
    \bool_if:NT \l__cmd_obey_spaces_bool
      {
        \msg_error:nnxx { cmd } { two-markers }
          { \__cmd_environment_or_command: } { ! }
        \__cmd_bad_def:wn
      }
    \bool_set_true:N \l__cmd_obey_spaces_bool
    \bool_set_true:N \l__cmd_some_obey_spaces_bool
    \int_decr:N \l__cmd_current_arg_int
    \__cmd_normalize_arg_spec_loop:n {#1}
  }
```

(*End definition for* `\__cmd_normalize_type_>:w`, `\__cmd_normalize_type_+:w`, *and* `\__cmd_normalize_type_!:w`.)

`\__cmd_normalize_type_D:w`
`\__cmd_normalize_type_E:w`
`\__cmd_normalize_type_t:w`
`\__cmd_normalize_E_unique_check:w`

Optional argument types. Check that all required data is present (and consists of single characters if applicable) and check for forbidden types for expandable commands. For E-type require that there is at least one embellishment, that each one is a single character, and that there aren't more optional arguments than embellishments; also remember that each embellishment counts as one argument for `\l__cmd_current_arg_int`. Then in each case store the data in `\l__cmd_arg_spec_tl`, and for later checks store in `\l__cmd_last_delimiters_tl` the tokens whose presence determines whether there is an optional argument (for braces store `{}`, seen later as an empty delimiter).

```
\cs_new_protected:Npn \__cmd_normalize_type_D:w #1#2#3
  {
    \quark_if_recursion_tail_stop_do:nn {#3} { \__cmd_bad_arg_spec:wn }
    \__cmd_single_token_check:n {#1} \__cmd_allowed_token_check:N #1
    \__cmd_single_token_check:n {#2}
    \__cmd_add_arg_spec:n { D #1 #2 {#3} }
    \tl_put_right:Nn \l__cmd_last_delimiters_tl {#1}
    \bool_set_false:N \l__cmd_grab_expandably_bool
    \__cmd_normalize_arg_spec_loop:n
  }
\cs_new_protected:Npn \__cmd_normalize_type_E:w #1#2
  {
    \quark_if_recursion_tail_stop_do:nn {#2} { \__cmd_bad_arg_spec:wn }
    \tl_if_blank:nT {#1} { \__cmd_bad_arg_spec:wn }
    \tl_map_function:nN {#1} \__cmd_single_token_check:n
    \tl_map_function:nN {#1} \__cmd_allowed_token_check:N
    \__cmd_normalize_E_unique_check:w #1 \q_nil \q_stop
```

```
    \int_compare:nNnT { \tl_count:n {#2} } > { \tl_count:n {#1} }
      { \__cmd_bad_arg_spec:wn }
    \__cmd_add_arg_spec:n { E {#1} {#2} }
    \tl_put_right:Nn \l__cmd_last_delimiters_tl {#1}
    \bool_set_false:N \l__cmd_grab_expandably_bool
    \int_add:Nn \l__cmd_current_arg_int { \tl_count:n {#1} - 1 }
    \__cmd_normalize_arg_spec_loop:n
  }
\cs_new_protected:Npn \__cmd_normalize_E_unique_check:w #1#2 \q_stop
  {
    \quark_if_nil:NF #1
      {
        \tl_if_in:nnT {#2} {#1} { \__cmd_bad_arg_spec:wn }
        \__cmd_normalize_E_unique_check:w #2 \q_stop
      }
  }
\cs_new_protected:Npn \__cmd_normalize_type_t:w #1
  {
    \quark_if_recursion_tail_stop_do:Nn #1 { \__cmd_bad_arg_spec:wn }
    \__cmd_single_token_check:n {#1} \__cmd_allowed_token_check:N #1
    \tl_put_right:Nx \l__cmd_arg_spec_tl
      {
        \bool_if:NT \l__cmd_obey_spaces_bool { ! }
        t \exp_not:n {#1}
      }
    \tl_put_right:Nn \l__cmd_last_delimiters_tl {#1}
    \bool_set_false:N \l__cmd_grab_expandably_bool
    \bool_set_false:N \l__cmd_obey_spaces_bool
    \bool_set_false:N \l__cmd_long_bool
    \__cmd_normalize_arg_spec_loop:n
  }
```

(*End definition for* `\__cmd_normalize_type_D:w` *and others.*)

`\__cmd_normalize_type_m:w`
`\__cmd_normalize_type_R:w`
`\__cmd_normalize_type_v:w`

Mandatory arguments. First check the required data is present, consists of single characters where applicable, and that the argument type is allowed for expandable commands if applicable. For the `m` and `R` argument types check that they do not follow some optional argument with that delimiter as otherwise the optional argument could not be omitted. Then save data in `\l__cmd_arg_spec_tl`, count the mandatory argument, and empty the list of last delimiters.

```
\cs_new_protected:Npn \__cmd_normalize_type_m:w
  {
    \__cmd_delimiter_check:nnn { } { m } { \iow_char:N \{ }
    \__cmd_add_arg_spec_mandatory:n { m }
    \__cmd_normalize_arg_spec_loop:n
  }
\cs_new_protected:Npn \__cmd_normalize_type_R:w #1#2#3
  {
    \quark_if_recursion_tail_stop_do:nn {#3} { \__cmd_bad_arg_spec:wn }
    \__cmd_single_token_check:n {#1} \__cmd_allowed_token_check:N #1
    \__cmd_single_token_check:n {#2}
    \__cmd_delimiter_check:nnn {#1} { R/r } { \tl_to_str:n {#1} }
    \bool_set_false:N \l__cmd_grab_expandably_bool
    \__cmd_add_arg_spec_mandatory:n { R #1 #2 {#3} }
```

```
    \__cmd_normalize_arg_spec_loop:n
  }
\cs_new_protected:Npn \__cmd_normalize_type_v:w
  {
    \__cmd_normalize_check_gv:N v
    \__cmd_add_arg_spec_mandatory:n { v }
    \__cmd_normalize_arg_spec_loop:n
  }
```

(*End definition for* `\__cmd_normalize_type_m:w`, `\__cmd_normalize_type_R:w`, *and* `\__cmd_normalize_type_v:w`.)

`\__cmd_normalize_type_b:w` This argument type is not allowed for commands. This is only allowed at the end of the argument specification, hence we check that `#1` is the end.

```
\cs_new_protected:Npn \__cmd_normalize_type_b:w #1
  {
    \bool_if:NF \l__cmd_environment_bool
      {
        \msg_error:nnxx { cmd } { invalid-command-arg }
          { \__cmd_environment_or_command: } { b }
        \__cmd_bad_def:wn
      }
    \tl_clear:N \l__cmd_last_delimiters_tl
    \__cmd_add_arg_spec:n { b }
    \quark_if_recursion_tail_stop:n {#1}
    \msg_error:nnxx { cmd } { arg-after-body }
      { \__cmd_environment_or_command: }
      { \tl_to_str:n {#1} }
    \__cmd_bad_def:wn
  }
```

(*End definition for* `\__cmd_normalize_type_b:w`.)

`\__cmd_single_token_check:n` Checks that the argument is a single (non-space) token (possibly surrounded by spaces), and aborts the definition otherwise.

```
\cs_new_protected:Npn \__cmd_single_token_check:n #1
  {
    \tl_trim_spaces_apply:nN {#1} \tl_if_single_token:nF
      {
        \msg_error:nnxx { cmd } { not-single-token }
          { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
        \__cmd_bad_def:wn
      }
  }
```

(*End definition for* `\__cmd_single_token_check:n`.)

`\__cmd_allowed_token_check:N` Some tokens are now allowed as delimiters for some argument types, notably implicit begin/end-group tokens (`\bgroup`/`\egroup`). The major problem with these tokens is that for `\peek_...` functions, a literal $\texttt{\{}_1$. is virtually indistinguishable from a `\bgroup` or other token which was `\let` to a $\texttt{\{}_1$, and the same goes for $\texttt{\}}_2$. All other tokens can be easily distingushed from their implicit counterparts by grabbing them and looking at the string length (see `\__cmd_token_if_cs:NTF`), but for begin/end group tokens

that is not possible without the risk of mistakenly grabbing the entire brace group (potentially leading to a `! Runaway argument` error) or trying to grab a $\}_2$, leading to an `! Argument of \dots has an extra }` error.

```
\cs_new_protected:Npn \__cmd_allowed_token_check:N #1
  {
    \token_if_eq_meaning:NNTF #1 \c_group_begin_token
        { \use:n }
        {
          \token_if_eq_meaning:NNTF #1 \c_group_end_token
            { \use:n }
            { \use_none:n }
        }
      {
        \msg_error:nnxxx { cmd } { forbidden-group-token }
          { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
          {
            \token_if_eq_meaning:NNTF #1 \c_group_begin_token
              { begin } { end }
          }
        \__cmd_bad_def:wn
      }
  }
```

(*End definition for* `\__cmd_allowed_token_check:N`.)

`\__cmd_normalize_check_gv:N`
`\__cmd_normalize_check_lu:N`

Called for arguments that are always forbidden, or forbidden after an optional argument, for expandable commands.

```
\cs_new_protected:Npn \__cmd_normalize_check_gv:N #1
  {
    \bool_if:NT \l__cmd_expandable_bool
      {
        \msg_error:nnxx { cmd } { invalid-expandable-arg }
          { \iow_char:N \\ \l__cmd_function_tl } { \tl_to_str:n {#1} }
        \__cmd_bad_def:wn
      }
    \bool_set_false:N \l__cmd_grab_expandably_bool
  }
\cs_new_protected:Npn \__cmd_normalize_check_lu:N #1
  {
    \bool_if:NT \l__cmd_expandable_bool
      {
        \tl_if_empty:NF \l__cmd_last_delimiters_tl
          {
            \msg_error:nnxx { cmd } { invalid-after-optional-expandably }
              { \iow_char:N \\ \l__cmd_function_tl } { \tl_to_str:n {#1} }
            \__cmd_bad_def:wn
          }
      }
  }
```

(*End definition for* `\__cmd_normalize_check_gv:N` *and* `\__cmd_normalize_check_lu:N`.)

`\__cmd_delimiter_check:nnn`

Called for `m` and `R` arguments. Checks that the leading token does not coincide with the token denoting the presence of a previous optional argument. Instead of dealing with braces for the `m`-type we use an empty delimiter to denote that case.

```
\cs_new_protected:Npn \__cmd_delimiter_check:nnn #1#2#3
  {
    \tl_map_inline:Nn \l__cmd_last_delimiters_tl
      {
        \tl_if_eq:nnT {##1} {#1}
          {
            \msg_warning:nnxx { cmd } { optional-mandatory }
              {#2} {#3}
          }
      }
  }
```

(*End definition for* `\__cmd_delimiter_check:nnn`.)

`\__cmd_bad_arg_spec:wn`
`\__cmd_bad_def:wn`

If the argument specification is wrong, this provides an escape from the entire definition process.

```
\cs_new_protected:Npn \__cmd_bad_arg_spec:wn #1 \__cmd_break_point:n #2
  {
    \msg_error:nnxx { cmd } { bad-arg-spec }
      { \__cmd_environment_or_command: } { \tl_to_str:n {#2} }
  }
\cs_new_protected:Npn \__cmd_bad_def:wn #1 \__cmd_break_point:n #2 { }
```

(*End definition for* `\__cmd_bad_arg_spec:wn` *and* `\__cmd_bad_def:wn`.)

`\__cmd_add_arg_spec:n`
`\__cmd_add_arg_spec_mandatory:n`

When adding an argument to the argument specification, set the `some_long` or `some_short` booleans as appropriate and clear the booleans keeping track of `+` and `!` markers. Before that, test for a short argument following some long arguments: this is forbidden for expandable commands and prevents grabbing arguments expandably.

For mandatory arguments do some more work, in particular complain if they were preceeded by `!`.

```
\cs_new_protected:Npn \__cmd_add_arg_spec:n #1
  {
    \bool_lazy_and:nnT
      { ! \l__cmd_long_bool }
      { \l__cmd_some_long_bool }
      {
        \bool_if:NT \l__cmd_expandable_bool
          {
            \msg_error:nnx { cmd } { long-short-mix }
              { \iow_char:N \\ \l__cmd_function_tl }
            \__cmd_bad_def:wn
          }
        \bool_set_false:N \l__cmd_grab_expandably_bool
      }
    \bool_if:NTF \l__cmd_long_bool
      { \bool_set_true:N \l__cmd_some_long_bool }
      { \bool_set_true:N \l__cmd_some_short_bool }
    \tl_put_right:Nx \l__cmd_arg_spec_tl
      {
        \bool_if:NT \l__cmd_long_bool { + }
        \bool_if:NT \l__cmd_obey_spaces_bool { ! }
        \exp_not:n {#1}
      }
```

```
    \bool_set_false:N \l__cmd_long_bool
    \bool_set_false:N \l__cmd_obey_spaces_bool
  }
\cs_new_protected:Npn \__cmd_add_arg_spec_mandatory:n #1
  {
    \bool_if:NT \l__cmd_some_obey_spaces_bool
      {
        \msg_error:nnxx { cmd } { invalid-bang }
          { \__cmd_environment_or_command: } { \tl_to_str:n {#1} }
        \__cmd_bad_def:wn
      }
    \tl_clear:N \l__cmd_last_delimiters_tl
    \__cmd_add_arg_spec:n {#1}
  }
```

(*End definition for* `\__cmd_add_arg_spec:n` *and* `\__cmd_add_arg_spec_mandatory:n`.)

1.5 Preparing the signature: general mechanism

`\__cmd_prepare_signature:n`
`\__cmd_prepare_signature:N`
`\__cmd_prepare_signature_bypass:N`

Actually creating the signature uses the same loop approach as normalizing the signature. There are first a number of variables which need to be set to track what is going on. Many of these variables are unused when defining expandable commands.

```
\cs_new_protected:Npn \__cmd_prepare_signature:n #1
  {
    \int_zero:N \l__cmd_current_arg_int
    \bool_set_false:N \l__cmd_long_bool
    \bool_set_false:N \l__cmd_obey_spaces_bool
    \int_zero:N \l__cmd_m_args_int
    \bool_set_false:N \l__cmd_defaults_bool
    \tl_clear:N \l__cmd_defaults_tl
    \tl_clear:N \l__cmd_process_all_tl
    \tl_clear:N \l__cmd_process_one_tl
    \bool_set_false:N \l__cmd_process_some_bool
    \tl_clear:N \l__cmd_signature_tl
    \__cmd_prepare_signature:N #1 \q_recursion_tail \q_recursion_stop
    \bool_if:NF \l__cmd_expandable_bool { \__cmd_flush_m_args: }
  }
```

The main looping function does not take an argument, but carries out the reset on the processor boolean. This is split off from the rest of the process so that when actually setting up processors the flag-reset can be bypassed.

For each known argument type there is an appropriate function to actually do the addition to the signature. These are separate for expandable and standard functions, as the approaches are different.

```
\cs_new_protected:Npn \__cmd_prepare_signature:N
  {
    \bool_set_false:N \l__cmd_prefixed_bool
    \__cmd_prepare_signature_bypass:N
  }
\cs_new_protected:Npn \__cmd_prepare_signature_bypass:N #1
  {
    \quark_if_recursion_tail_stop:N #1
    \use:c
      {
```

```
        __cmd_add
        \bool_if:NT \l__cmd_grab_expandably_bool { _expandable }
        _type_  \token_to_str:N #1 :w
      }
  }
```

(*End definition for* `\__cmd_prepare_signature:n`, `\__cmd_prepare_signature:N`, *and* `\__cmd_prepare_signature_bypass:N`.)

1.6 Setting up a standard signature

Each argument-adding function appends to the signature a grabber (and for some types, the delimiters or default value), except the one for `m` arguments. These are collected and added to the signature all at once by `\__cmd_flush_m_args:`, called for every other argument type. All of the functions then call the loop function `\__cmd_prepare_signature:N`. Default values of arguments are collected by `\__cmd_add_default:n` rather than being stored with the argument; this function and `\__cmd_add_default:` are also responsible for keeping track of `\l__cmd_current_arg_int`.

`\__cmd_add_type_+:w` Making the next argument long means setting the flag. The `m` arguments are recorded here as this has to be done for every case where there is then a long argument.

```
\cs_new_protected:cpn { __cmd_add_type_+:w }
  {
    \__cmd_flush_m_args:
    \bool_set_true:N \l__cmd_long_bool
    \bool_set_true:N \l__cmd_prefixed_bool
    \__cmd_prepare_signature_bypass:N
  }
```

(*End definition for* `\__cmd_add_type_+:w`.)

`\__cmd_add_type_!:w` Much the same for controlling trailing optional arguments.

```
\cs_new_protected:cpn { __cmd_add_type_!:w }
  {
    \__cmd_flush_m_args:
    \bool_set_true:N \l__cmd_obey_spaces_bool
    \bool_set_true:N \l__cmd_prefixed_bool
    \__cmd_prepare_signature_bypass:N
  }
```

(*End definition for* `\__cmd_add_type_!:w`.)

`\__cmd_add_type_>:w` When a processor is found, the processor code is stored. It will be used by `\__cmd_args_process:` once arguments are all found. Here too the loop calls `\__cmd_prepare_signature_bypass:N` rather than `\__cmd_prepare_signature:N` so that the flag is not reset.

```
\cs_new_protected:cpn { __cmd_add_type_>:w } #1
  {
    \__cmd_flush_m_args:
    \bool_set_true:N \l__cmd_prefixed_bool
    \bool_set_true:N \l__cmd_process_some_bool
    \tl_put_left:Nn \l__cmd_process_one_tl { {#1} }
    \__cmd_prepare_signature_bypass:N
  }
```

(*End definition for* `\__cmd_add_type_>:w`.)

`\__cmd_add_type_b:w`

```
\cs_new_protected:Npn \__cmd_add_type_b:w
  {
    \__cmd_flush_m_args:
    \__cmd_add_default:
    \__cmd_add_grabber:N b
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_type_b:w`.)

`\__cmd_add_type_D:w`

```
\cs_new_protected:Npn \__cmd_add_type_D:w #1#2#3
  {
    \__cmd_flush_m_args:
    \__cmd_add_default:n {#3}
    \__cmd_add_grabber:N D
    \tl_put_right:Nn \l__cmd_signature_tl { #1 #2 }
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_type_D:w`.)

`\__cmd_add_type_E:w` The `E`-type argument needs a special handling of default values. Since each embellishment is a separate argument, it also needs to replicate the argument processors for each embellishment argument so that the numbers of arguments and processors remain in sync.

```
\cs_new_protected:Npn \__cmd_add_type_E:w #1#2
  {
    \__cmd_flush_m_args:
    \__cmd_add_default_E:nn {#1} {#2}
    \use:x
      {
        \__cmd_replicate_processor:nn { \tl_count:n {#1} }
          { \exp_not:o \l__cmd_process_one_tl }
      }
    \__cmd_add_grabber:N E
    \tl_put_right:Nn \l__cmd_signature_tl { {#1} }
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_type_E:w`.)

`\__cmd_replicate_processor:nn` In the command's argument processor signature (the final argument of `\__cmd_start:nNNnnn`) there is one braced item for each formal argument (up to nine), and in each of these items there is one braced item for each processor (as many as there were processors declared for a given argument). Something like this:

```
{ % argument processors
  { % argument 1
    { processor 1 } { processor 2 } ... { processor n }
```

```
    } % end argument 1
    { ... } % argument 2
       ⋮
    { ... } % argument n
  } % end argument processors
```

The function `\__cmd_add_grabber:N` adds one single grabber for an argument, and adds the braced item for that one argument. However, in an `E`-type argument each embellishment requires its own formal argument, so we need to break out of one layer of braces in `\l__cmd_process_one_tl`, add copies of the processor as necessary, and then return the removed brace. The function below does just that: it defines `\l__cmd_process_one_tl` starting with a $\}_2$ and ending with a $\{_1$, so that it adds as many processors as needed when `x`-expanded.

```
\cs_new_protected:Npn \__cmd_replicate_processor:nn #1 #2
  {
    \int_compare:nNnF {#1} > { 1 } { \use_none:nnn }
    \tl_set:Nx \l__cmd_process_one_tl
      {
        \exp_not:n { \exp_not:n {#2} \if_false: { \fi: } }
        \prg_replicate:nn { #1 - 2 }
          { \exp_not:n { \exp_not:n { {#2} } } }
        \exp_not:n { { \if_false: } \fi: \exp_not:n {#2} }
      }
  }
```

(*End definition for* `\__cmd_replicate_processor:nn`.)

`\__cmd_add_type_m:w` The `m` type is special as short arguments which are not post-processed are simply counted at this stage. Thus there is a check to see if either of these cases apply. If so, a one-argument grabber is added to the signature. On the other hand, if a standard short argument is required it is simply counted at this stage, to be added later using `\__cmd_flush_m_args:`.

```
\cs_new_protected:Npn \__cmd_add_type_m:w
  {
    \__cmd_add_default:
    \bool_if:NTF \l__cmd_prefixed_bool
      { \__cmd_add_grabber:N m }
      { \int_incr:N \l__cmd_m_args_int }
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_type_m:w`.)

`\__cmd_add_type_R:w` The `R`-type argument is very similar to the `D`-type.

```
\cs_new_protected:Npn \__cmd_add_type_R:w #1#2#3
  {
    \__cmd_flush_m_args:
    \__cmd_add_default:n {#3}
    \__cmd_add_grabber:N R
    \tl_put_right:Nn \l__cmd_signature_tl { #1 #2 }
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_type_R:w`.)

`\__cmd_add_type_t:w` Setting up a `t` argument means collecting one token for the test, and adding it along with the grabber to the signature.

```
\cs_new_protected:Npn \__cmd_add_type_t:w #1
  {
    \__cmd_flush_m_args:
    \__cmd_add_default:
    \__cmd_add_grabber:N t
    \tl_put_right:Nn \l__cmd_signature_tl {#1}
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_type_t:w`.)

`\__cmd_add_type_v:w` At this stage, the `v` argument is identical to `l` except that since the grabber may fail to read a verbatim argument we need a default value.

```
\cs_new_protected:Npn \__cmd_add_type_v:w
  {
    \__cmd_flush_m_args:
    \exp_args:No \__cmd_add_default:n \c_novalue_tl
    \__cmd_add_grabber:N v
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_type_v:w`.)

`\__cmd_flush_m_args:` As `m` arguments are simply counted, there is a need to add them to the token register in a block. As this function can only be called if something other than `m` turns up, the flag can be switched here.

```
\cs_new_protected:Npn \__cmd_flush_m_args:
  {
    \int_compare:nNnT \l__cmd_m_args_int > 0
      {
        \tl_put_right:Nx \l__cmd_signature_tl
          { \exp_not:c { __cmd_grab_m_ \int_use:N \l__cmd_m_args_int :w } }
        \tl_put_right:Nx \l__cmd_process_all_tl
          { \prg_replicate:nn { \l__cmd_m_args_int } { { } } }
      }
    \int_zero:N \l__cmd_m_args_int
  }
```

(*End definition for* `\__cmd_flush_m_args:`.)

`\__cmd_add_grabber:N` To keep the various checks needed in one place, adding the grabber to the signature is done here. The only questions are whether the grabber should be long or not, and whether to obey spaces. The `\l__cmd_obey_spaces_bool` boolean can only be `true` for trailing optional arguments. In that case spaces will not be ignored when looking for that optional argument.

```
\cs_new_protected:Npn \__cmd_add_grabber:N #1
  {
    \tl_put_right:Nx \l__cmd_signature_tl
      {
        \exp_not:c
```

```
          {
            __cmd_grab_ #1
            \bool_if:NT \l__cmd_long_bool { _long }
            \bool_if:NT \l__cmd_obey_spaces_bool { _obey_spaces }
            :w
          }
      }
    \bool_set_false:N \l__cmd_long_bool
    \bool_set_false:N \l__cmd_obey_spaces_bool
    \tl_put_right:Nx \l__cmd_process_all_tl
      {
        {
          \if_charcode:w E #1 \use_i:nn \fi:
          \exp_not:o \l__cmd_process_one_tl
        }
      }
    \tl_clear:N \l__cmd_process_one_tl
  }
```

(*End definition for* `\__cmd_add_grabber:N`.)

`\__cmd_add_default:n`
`\__cmd_add_default:`
`\__cmd_add_default_E:nn`

Store the default value of an argument, or rather code that gives that default value (it may involve other arguments). This is `\c_novalue_tl` for arguments with no actual default or with default `-NoValue-`; and (in a brace group) `\prg_do_nothing:` followed by a default value for others. For `E`-type arguments, pad the defaults `#2` with some `\c_novalue_tl` until there are as many as embellishments `#1`. These functions are also used when defining expandable commands.

```
\cs_new_protected:Npn \__cmd_add_default:n #1
  {
    \tl_if_novalue:nTF {#1}
      { \__cmd_add_default: }
      {
        \int_incr:N \l__cmd_current_arg_int
        \bool_set_true:N \l__cmd_defaults_bool
        \tl_put_right:Nn \l__cmd_defaults_tl { { \prg_do_nothing: #1 } }
      }
  }
\cs_new_protected:Npn \__cmd_add_default:
  {
    \int_incr:N \l__cmd_current_arg_int
    \tl_put_right:Nn \l__cmd_defaults_tl { \c_novalue_tl }
  }
\cs_new_protected:Npn \__cmd_add_default_E:nn #1#2
  {
    \tl_map_function:nN {#2} \__cmd_add_default:n
    \prg_replicate:nn
      { \tl_count:n {#1} - \tl_count:n {#2} }
      { \__cmd_add_default: }
  }
```

(*End definition for* `\__cmd_add_default:n`, `\__cmd_add_default:`, *and* `\__cmd_add_default_E:nn`.)

1.7 Setting up expandable types

The approach here is not dissimilar to that for standard types, but fewer types are supported. There is also a need to define the per-function auxiliaries: this is done here, while the general grabbers are dealt with later.

__cmd_add_expandable_type_+:w

We have already checked that short arguments are before long arguments, so `\l__cmd_long_bool` only changes from `false` to `true` once (and there is no need to reset it after each argument). Continue the loop.

```
\cs_new_protected:cpn { __cmd_add_expandable_type_+:w }
  {
    \bool_set_true:N \l__cmd_long_bool
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_expandable_type_+:w`.)

__cmd_add_expandable_type_D:w
__cmd_add_expandable_type_D_aux:NNNn
__cmd_add_expandable_type_D_aux:NNN
__cmd_add_expandable_type_D_aux:NN

The set up for `D`-type arguments involves constructing a rather complex auxiliary which is used repeatedly when grabbing. There is an auxiliary here so that the `R`-type can share code readily: `#1` is `D` or `R`. The `_aux:NN` auxiliary is needed if the two delimiting tokens are identical: in contrast to the non-expandable route, the grabber here has to act differently for this case.

```
\cs_new_protected:Npn \__cmd_add_expandable_type_D:w
  { \__cmd_add_expandable_type_D_aux:NNNn D }
\cs_new_protected:Npn \__cmd_add_expandable_type_D_aux:NNNn #1#2#3#4
  {
    \__cmd_add_default:n {#4}
    \tl_if_eq:nnTF {#2} {#3}
      { \__cmd_add_expandable_type_D_aux:NN #1 #2 }
      { \__cmd_add_expandable_type_D_aux:NNN #1 #2 #3 }
    \__cmd_prepare_signature:N
  }
\cs_new_protected:Npn \__cmd_add_expandable_type_D_aux:NNN #1#2#3
  {
    \bool_if:NTF \l__cmd_long_bool
      { \cs_set:cpx }
      { \cs_set_nopar:cpx }
      { \l__cmd_expandable_aux_name_tl } ##1 ##2 #2 ##3 \q__cmd ##4 #3
      { ##1 {##2} {##3} {##4} }
    \__cmd_add_expandable_grabber:nn {#1}
      {
        \exp_not:c  { \l__cmd_expandable_aux_name_tl }
        \exp_not:n { #2 #3 }
      }
  }
\cs_new_protected:Npn \__cmd_add_expandable_type_D_aux:NN #1#2
  {
    \bool_if:NTF \l__cmd_long_bool
      { \cs_set:cpx }
      { \cs_set_nopar:cpx }
      { \l__cmd_expandable_aux_name_tl } ##1 #2 ##2 #2
      { ##1 {##2} }
    \__cmd_add_expandable_grabber:nn { #1_alt }
      {
```

```
        \exp_not:c  { \l__cmd_expandable_aux_name_tl }
        \exp_not:n {#2}
      }
  }
```

(*End definition for* `\__cmd_add_expandable_type_D:w` *and others.*)

`\__cmd_add_expandable_type_E:w`
`\__cmd_add_expandable_type_E_aux:n`

For each embellishment, use `\__cmd_get_grabber:NN` to obtain an auxiliary delimited by that token and store a pair constituted of the auxiliary and the token in `\l__cmd_tmpb_tl`, before appending the whole set of these pairs to the signature, and an equal number of `-NoValue-` markers (regardless of the default values of arguments). Set the current argument appropriately.

```
\cs_new_protected:Npn \__cmd_add_expandable_type_E:w #1#2
  {
    \__cmd_add_default_E:nn {#1} {#2}
    \tl_clear:N \l__cmd_tmpb_tl
    \tl_map_function:nN {#1} \__cmd_add_expandable_type_E_aux:n
    \__cmd_add_expandable_grabber:nn
      { E \bool_if:NT \l__cmd_long_bool { _long } }
      {
        { \exp_not:o \l__cmd_tmpb_tl }
        {
          \prg_replicate:nn { \tl_count:n {#1} }
            { { \c_novalue_tl } }
        }
      }
    \__cmd_prepare_signature:N
  }
\cs_new_protected:Npn \__cmd_add_expandable_type_E_aux:n #1
  {
    \__cmd_get_grabber:NN #1 \l__cmd_tmpa_tl
    \tl_put_right:Nx \l__cmd_tmpb_tl
      { \exp_not:o \l__cmd_tmpa_tl \exp_not:N #1 }
  }
```

(*End definition for* `\__cmd_add_expandable_type_E:w` *and* `\__cmd_add_expandable_type_E_aux:n`.)

`\__cmd_add_expandable_type_m:w`

Unlike the standard case, when working expandably each argument is always grabbed separately.

```
\cs_new_protected:Npn \__cmd_add_expandable_type_m:w
  {
    \__cmd_add_default:
    \__cmd_add_expandable_grabber:nn
      { m \bool_if:NT \l__cmd_long_bool { _long } } { }
    \__cmd_prepare_signature:N
  }
```

(*End definition for* `\__cmd_add_expandable_type_m:w`.)

`\__cmd_add_expandable_type_R:w`

The `R`-type is very similar to the `D`-type argument, and so the same internals are used.

```
\cs_new_protected:Npn \__cmd_add_expandable_type_R:w
  { \__cmd_add_expandable_type_D_aux:NNNn R }
```

(*End definition for* `\__cmd_add_expandable_type_R:w`.)

__cmd_add_expandable_type_t:w

An auxiliary delimited by #1 is built now. It will be used to test for the presence of that token.

```
\cs_new_protected:Npn \__cmd_add_expandable_type_t:w #1
  {
    \__cmd_add_default:
    \__cmd_get_grabber:NN #1 \l__cmd_tmpa_tl
    \__cmd_add_expandable_grabber:nn { t }
      {
        \exp_not:o \l__cmd_tmpa_tl
        \exp_not:N #1
      }
    \__cmd_prepare_signature:N
  }
```

(*End definition for* __cmd_add_expandable_type_t:w.)

__cmd_add_expandable_grabber:nn

This is called for all arguments to place the right grabber in the signature.

```
\cs_new_protected:Npn \__cmd_add_expandable_grabber:nn #1#2
  {
    \tl_put_right:Nx \l__cmd_signature_tl
      { \exp_not:c { __cmd_expandable_grab_ #1 :w } #2 }
  }
```

(*End definition for* __cmd_add_expandable_grabber:nn.)

__cmd_get_grabber:NN
__cmd_get_grabber_auxi:NN
__cmd_get_grabber_auxii:NN

Given a token #1, defines an expandable function delimited by that token and stores it in the token list #2. The function is named after the token, unless that function name is already taken by some other grabber (this can happen in the rare case where delimiters with different category codes are used in the same document): in that case use a global counter to get a unique name. Since the grabbers are not named after xparse commands they should not be used to get material from the input stream.

```
\cs_new_protected:Npn \__cmd_get_grabber:NN #1#2
  {
    \cs_set:Npn \__cmd_tmp:w ##1 #1 {##1}
    \exp_args:Nc \__cmd_get_grabber_auxi:NN
      { __cmd_grabber_ \token_to_str:N #1 :w } #2
  }
\cs_new_protected:Npn \__cmd_get_grabber_auxi:NN #1#2
  {
    \cs_if_eq:NNTF \__cmd_tmp:w #1
      { \tl_set:Nn #2 {#1} }
      {
        \cs_if_exist:NTF #1
          {
            \int_gincr:N \g__cmd_grabber_int
            \exp_args:Nc \__cmd_get_grabber_auxi:NN
              {
                __cmd_grabber_
                - \int_use:N \g__cmd_grabber_int :w
              }
              #2
          }
          { \__cmd_get_grabber_auxii:NN #1 #2 }
      }
```

```
  }
\cs_new_protected:Npn \__cmd_get_grabber_auxii:NN #1#2
  {
    \cs_set_eq:NN #1 \__cmd_tmp:w
    \tl_set:Nn #2 {#1}
  }
```

(*End definition for* `\__cmd_get_grabber:NN`, `\__cmd_get_grabber_auxi:NN`, *and* `\__cmd_get_grabber_auxii:NN`.)

1.7.1 Copying a command and its internal structure

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__cmd_copy:NN}%
⟨latexrelease⟩   {Support~\NewCommandCopy~in~ltcmd}
```

Since the 2020-10-01 LaTeX 2_ε release, support for copying, and showing the definition of, robust commands has been available, but the specifics of each command are implemented separately. Here we'll add support for copying and showing ltcmd definitions.

To fully support copying, we need two commands: a conditional to test if a command is in fact a ltcmd command, and another command to actually copy the command. The conditional is defined later as `\__kernel_cmd_if_xparse:NTF`, so now to the copying:

`\__cmd_copy:NN`
`\__cmd_set_eq_if_exist:NN`
`\__cmd_set_eq_if_exist:cc`

This macro just branches to the proper copying command by using `\__cmd_cmd_type_cases:NnnnnF`. The copying command takes the names of the commands to be copied to and from, and the actual commands as its four arguments.

```
\cs_new_protected:Npn \__cmd_copy:NN #1 #2
  {
    \use:x
      {
        \int_set:Nn \tex_escapechar:D { 92 }
        \exp_not:N \__cmd_cmd_type_cases:NnnnnF \exp_not:N #2
          { \__cmd_copy_command:nnNN }
          { \__cmd_copy_expandable:nnNN }
          { \__cmd_copy_environment:nnNN }
          { \__cmd_copy_environment_end:nnNN }
          { \__cmd_cant_copy:nwn { non-ltcmd } }
            { \cs_to_str:N #1 } { \cs_to_str:N #2 }
            \exp_not:N #1 \exp_not:N #2
        \exp_not:N \__cmd_break_point:n { \cs_to_str:N #2 }
        \int_set:Nn \tex_escapechar:D { \int_use:N \tex_escapechar:D }
      }
  }
\cs_new_protected:Npn \__cmd_set_eq_if_exist:NN #1 #2
  { \cs_if_exist:NTF #2 { \cs_set_eq:NN } { \use_none:nn } #1 #2 }
\cs_generate_variant:Nn \__cmd_set_eq_if_exist:NN { cc }
```

`\__cmd_cant_copy:nwn`

An utility macro similar to `\__cmd_bad_def:wn` to abort a command copy. Contrary to `\__cmd_bad_def:wn` though, when this happens the issue is most likely internal, because the command was already (supposedly) correcly defined so it should be copyable. Hopefully this macro will never be used ever, but if it does, apologise and give the reason for the failure so the user can report.

```
\cs_new_protected:Npn \__cmd_cant_copy:nwn #1 #2 \__cmd_break_point:n #3
  { \msg_error:nnnn { cmd } { copy-bug } {#1} {#3} }
\msg_new:nnn { cmd } { copy-bug }
```

```
  {
    Error~while~copying~command~\iow_char:N\\#2:\\
    \str_case:nn {#1}
      {
        { non-ltcmd } { Command~is~not~a~valid~ltcmd~command. }
        { unknown-type } { Found~an~unknown~argument~type. }
        { invalid-end }
          { Target~command~is~not~named~\iow_char:N \\end<name>. }
      }
  }
```

And, of course, add `\__kernel_cmd_if_xparse:NTF` and `\__cmd_copy:NN` to `\@declarecommandcopylisthook`:

```
\tl_gput_right:Nn \@declarecommandcopylisthook
  { { \__kernel_cmd_if_xparse:NTF \__cmd_copy:NN } }
```

(*End definition for* `\__cmd_copy:NN`, `\__cmd_set_eq_if_exist:NN`, *and* `\__cmd_cant_copy:nwn`.)

`\__cmd_copy_command:nnNN`
`\__cmd_copy_command:NnNNnnnn`

A normal (non-expandable) command has a pretty straightforward structure. Its definition is stored in `\`⟨*cmd*⟩`␣code`, its defaults (if any) are stored in `\`⟨*cmd*⟩`␣defaults`, and its top-level definition contains its signature, which can just be copied over. `\__cmd_copy_command:nnNN` copies the command code and defaults, and then defines the top-level command using the auxiliary `\__cmd_copy_command:NnNNnnnn`. This macro takes the signature of the command being copied from its top-level definition, and replaces the named bits with the new name.

```
\cs_new_protected:Npn \__cmd_copy_command:nnNN #1 #2 #3 #4
  {
    \cs_set_eq:cc { #1 ~ code } { #2 ~ code }
    \__cmd_set_eq_if_exist:cc { #1 ~ defaults } { #2 ~ defaults }
    \cs_set_protected_nopar:Npx #3
      { \exp_after:wN \__cmd_copy_command:NnNNnnnn #4 {#1} }
  }
\cs_new:Npn \__cmd_copy_command:NnNNnnnn #1 #2 #3 #4 #5 #6 #7 #8
  {
    #1 \exp_not:n { {#2} }
    \exp_not:c { #8 ~ } \exp_not:c { #8 ~ code }
    \exp_not:n { {#5} {#6} {#7} }
  }
```

(*End definition for* `\__cmd_copy_command:nnNN` *and* `\__cmd_copy_command:NnNNnnnn`.)

`\__cmd_copy_expandable:nnNN`
`\__cmd_copy_expandable:NnNNNNnnn`

An expandable command is slightly more complicated. Besides the `\`⟨*cmd*⟩`␣code`, and `\`⟨*cmd*⟩`␣defaults`, it also has an auxiliary `\`⟨*cmd*⟩`␣` for grabbing delimited arguments, and possibly another auxiliary `\`⟨*cmd*⟩`␣␣`, if the command has both long and short arguments. Then, its signature also has several specific bits that are unique to that command; this is in contrast to non-expandable commands, which use a common set of parsing functions.

We start by copying the basics, then call `\__cmd_copy_expandable_signature:NnNNNNnnn` to parse the signature of the command and build up the modified copy in a temporary token list, then we call `\__cmd_copy_expandable:NnNNNNnnn` that will copy the top-level definition of the command, with the proper internal renames.

```
\cs_new_protected:Npn \__cmd_copy_expandable:nnNN #1 #2 #3 #4
  {
    \cs_set_eq:cc { #1 ~ code } { #2 ~ code }
```

```
    \__cmd_set_eq_if_exist:cc { #1 ~ } { #2 ~ }
    \__cmd_set_eq_if_exist:cc { #1 ~ \c_space_tl } { #2 ~ \c_space_tl }
    \__cmd_set_eq_if_exist:cc { #1 ~ defaults } { #2 ~ defaults }
    \exp_after:wN \__cmd_copy_expandable_signature:NnNNNNnnn #4 {#1} {#2}
    \cs_set_nopar:Npx #3
      { \exp_after:wN \__cmd_copy_expandable:NnNNNNnnn #4 {#1} {#2} }
  }
\cs_new:Npn \__cmd_copy_expandable:NnNNNNnnn #1 #2 #3 #4 #5 #6 #7 #8 #9
  {
    \exp_not:N #1 \exp_not:n { {#2} }
    \exp_not:c { #8 ~ }
    \exp_not:c
      {
        #8 ~
        \str_if_eq:eeT
            { \exp_not:c { #9 ~ \c_space_tl } } { \exp_not:N #4 }
          { \c_space_tl }
      }
    \exp_not:c { #8 ~ code }
    \str_if_eq:eeTF { \exp_not:N #6 } { ? }
      { ? }
      { \exp_not:c { #8 ~ defaults } }
    { \exp_not:V \l__cmd_tmpa_tl }
  }
```

A signature for an expandable command contains as many `\expandable_grab_`⟨*type*⟩`:w` as there are arguments, and what follows this macro depends on the ⟨*type*⟩. We'll start a loop through the signature, and at each argument grabber, we'll step the argument count, and look for the ⟨*type*⟩ with `\__cmd_copy_parse_grabber:w` so that we know which `\__cmd_copy_grabber_`⟨*type*⟩`:w` to call next.

`\__cmd_copy_expandable_signature:NnNNNNnnn`
`\__cmd_copy_expandable:nnN`
`\__cmd_copy_parse_grabber:w`

```
\cs_new_protected:Npn \__cmd_copy_expandable_signature:NnNNNNnnn
    #1 #2 #3 #4 #5 #6 #7 #8 #9
  {
    \int_zero:N \l__cmd_current_arg_int
    \tl_clear:N \l__cmd_tmpa_tl
    \__cmd_copy_expandable:nnN {#8} {#9} #7
      \q_recursion_tail \q_recursion_stop
  }
\cs_new_protected:Npn \__cmd_copy_expandable:nnN #1 #2 #3
  {
    \quark_if_recursion_tail_stop:n {#3}
    \int_incr:N \l__cmd_current_arg_int
    \exp_after:wN \__cmd_copy_parse_grabber:w \token_to_str:N #3 {#1} {#2}
  }
\use:x
  {
    \cs_new_protected:Npn \exp_not:N \__cmd_copy_parse_grabber:w ##1
        \tl_to_str:n { expandable_grab_ } ##2 \tl_to_str:n { :w }
      {
        \tl_put_right:Nx \exp_not:N \l__cmd_tmpa_tl
          { \exp_not:N \exp_not:c { __cmd_expandable_grab_##2:w } }
        \exp_not:N \cs_if_exist_use:cF { __cmd_copy_grabber_##2:w }
          { \__cmd_cant_copy:nwn { unknown-type } }
      }
```

```
}
```

The most complicated is the Delimited argument: each argument has a dedicated grabbing function named after the command that has to be copied over (of the form \⟨*cmd*⟩␣(arg␣⟨*num*⟩)).

```
\cs_new_protected:Npn \__cmd_copy_grabber_D:w #1 #2 #3 #4 #5
  {
    \tl_put_right:Nx \l__cmd_tmpa_tl
      {
        \exp_not:c { #1 ~ (arg ~ \int_use:N \l__cmd_current_arg_int ) }
        \exp_not:n { #4 #5 }
      }
    \cs_set_eq:cc
      { #1 ~ (arg ~ \int_use:N \l__cmd_current_arg_int ) }
      { #2 ~ (arg ~ \int_use:N \l__cmd_current_arg_int ) }
    \__cmd_copy_expandable:nnN {#1} {#2}
  }
```

__cmd_copy_grabber_D:w
__cmd_copy_grabber_D_alt:w
__cmd_copy_grabber_R:w
__cmd_copy_grabber_R_alt:w
__cmd_copy_grabber_E:w
__cmd_copy_grabber_E_long:w
__cmd_copy_grabber_t:w
__cmd_copy_grabber_m:w
__cmd_copy_grabber_m_long:w

D_alt is just a special case of D that uses a single delimiter (used when both delimiters of the argument are identical):

```
\cs_new_protected:Npn \__cmd_copy_grabber_D_alt:w #1 #2 #3 #4
  { \__cmd_copy_grabber_D:w {#1} {#2} {#3} {#4} { } }
```

As far as copying is concerned, R is identical to D:

```
\cs_new_eq:NN \__cmd_copy_grabber_R:w \__cmd_copy_grabber_D:w
\cs_new_eq:NN \__cmd_copy_grabber_R_alt:w \__cmd_copy_grabber_D_alt:w
```

E is straightforward: we just copy the embellishments over, and increase the current argument number \l__cmd_current_arg_int by the number of embellishments (minus one because there is a \int_incr:N down the line).

```
\cs_new_protected:Npn \__cmd_copy_grabber_E:w #1 #2 #3 #4
  {
    \tl_put_right:Nn \l__cmd_tmpa_tl { {#3} {#4} }
    \int_add:Nn \l__cmd_current_arg_int { \tl_count:n {#4} - 1 }
    \__cmd_copy_expandable:nnN {#1} {#2}
  }
\cs_new_eq:NN \__cmd_copy_grabber_E_long:w \__cmd_copy_grabber_E:w
```

t just needs copying the token to be tested for:

```
\cs_new_protected:Npn \__cmd_copy_grabber_t:w #1 #2 #3 #4
  {
    \tl_put_right:Nn \l__cmd_tmpa_tl { #3 #4 }
    \__cmd_copy_expandable:nnN {#1} {#2}
  }
```

And last but not least, m is the simplest; the grabber is just __cmd_expandable_grab_m:w, which is already added to the new command so here we just resume the loop:

```
\cs_new_protected:Npn \__cmd_copy_grabber_m:w { \__cmd_copy_expandable:nnN }
\cs_new_eq:NN \__cmd_copy_grabber_m_long:w \__cmd_copy_grabber_m:w
```

(*End definition for* __cmd_copy_expandable:nnNN *and others.*)

__cmd_copy_environment:nnNN
__cmd_copy_environment:Nnnnnnn

Copying an environment's \begin part is pretty much like copying a command, except it has a longer name, and at the end we have to copy \environment ⟨*name*⟩ into \⟨*name*⟩.

```
\cs_new_protected:Npn \__cmd_copy_environment:nnNN #1 #2 #3 #4
```

```
  {
    \cs_set_eq:cc { environment~ #1 ~ code } { environment~ #2 ~ code }
    \__cmd_set_eq_if_exist:cc
      { environment~ #1 ~ defaults } { environment~ #2 ~ defaults }
    \cs_set_protected_nopar:cpx { environment~ #1 }
      { \exp_after:wN \__cmd_copy_environment:Nnnnnnn #4 {#1} }
    \cs_set_eq:cc {#1} { environment~ #1 }
  }
\cs_new:Npn \__cmd_copy_environment:Nnnnnnn #1 #2 #3 #4 #5 #6 #7
  { #1 \exp_not:n { {#2} } {#7} \exp_not:n { {#4} {#5} {#6} } }
```

(*End definition for* `\__cmd_copy_environment:nnNN` *and* `\__cmd_copy_environment:Nnnnnnn`.)

`\__cmd_copy_environment_end:nnNN`
`\__cmd_copy_environment_end_aux:nnNN`

Copying an environment's `\end` part is a bit trickier. We first have to make sure that both parts are named `\end`⟨*name*⟩ (that's actually not a hard requirement, but an environment `\end` command makes no sense without the `end` in its name), and strip the leading `end` from the strings. After that, copying is straightforward.

```
\cs_new_protected:Npn \__cmd_copy_environment_end:nnNN #1 #2
  {
    \__cmd_check_end:Nn \l__cmd_tmpa_tl {#1}
    \__cmd_check_end:Nn \l__cmd_tmpb_tl {#2}
    \exp_args:Noo \__cmd_copy_environment_end_aux:nnNN
      { \l__cmd_tmpa_tl } { \l__cmd_tmpb_tl }
  }
\cs_new_protected:Npn \__cmd_copy_environment_end_aux:nnNN #1 #2 #3 #4
  {
    \cs_set_nopar:cpx { environment~ #1 ~end }
      { \exp_not:c { environment~ #1 ~end~aux } }
    \cs_set_eq:cc
      { environment~ #1 ~end~aux~ } { environment~ #2 ~end~aux~ }
    \cs_set_eq:cc { end #1 } { environment~ #1 ~end }
  }
```

To check whether an `\end` command is valid, we look for the string `end` at the beginning of the command name, and if not found, raise an error:

`\__cmd_check_end:Nn`
`\__cmd_check_end:n`
`\__cmd_check_end:w`

```
\cs_new_protected:Npn \__cmd_check_end:Nn #1 #2
  {
    \tl_set:Nx #1 { \__cmd_check_end:n {#2} }
    \token_if_eq_meaning:NNT #1 \q_nil
      { \__cmd_cant_copy:nwn { invalid-end } }
  }
\cs_set_protected:Npn \__cmd_tmp:w #1
  {
    \cs_new:Npn \__cmd_check_end:n ##1
      {
        \exp_after:wN \__cmd_check_end:w \tl_to_str:n {##1}
          #1 \q_mark #1 \q_stop
      }
    \cs_new:Npn \__cmd_check_end:w ##1 #1 ##2 #1 ##3 \q_stop
      { \if_meaning:w ##2 \q_mark \exp_not:N \q_nil \else: ##2 \fi: }
  }
\exp_args:No \__cmd_tmp:w { \tl_to_str:n { end } }
```

(*End definition for* `\__cmd_copy_environment_end:nnNN` *and others.*)

Not much to do regarding latexrelease: we could remove the entries from `\@declarecommandcopylist` but it doesn't seem worth it.

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__cmd_copy:NN}%
⟨latexrelease⟩   {Support~\NewCommandCopy~in~ltcmd}
⟨latexrelease⟩\EndIncludeInRelease
```

1.7.2 Showing the definition of a command

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__cmd_show:N}%
⟨latexrelease⟩   {Support~\ShowCommand~in~ltcmd}
```

To show the definition of a command we need more or less the same building blocks as for copying, except that instead of making a copy, we'll just print stuff to the terminal.

`\__cmd_show:N` This macro just branches to the proper showing command by using `\__cmd_cmd_type_cases:NnnnnF`. The showing command takes the command to be shown as argument.

```
\cs_new_protected:Npn \__cmd_show:N #1
  {
    \use:x
      {
        \int_set:Nn \tex_escapechar:D { 92 }
        \exp_not:N \__cmd_cmd_type_cases:NnnnnF \exp_not:N #1
          { \__cmd_show_command:N }
          { \__cmd_show_expandable:N }
          { \__cmd_show_environment:N }
          { \__cmd_show_environment_end:N }
          { \__cmd_cant_copy:nwn { non-ltcmd } }
            \exp_not:N #1
        \exp_not:N \__cmd_break_point:n { \cs_to_str:N #1 }
        \int_set:Nn \tex_escapechar:D { \int_use:N \tex_escapechar:D }
      }
  }
```

(*End definition for* `\__cmd_show:N`.)

`\__cmd_show_command:N`
`\__cmd_show_command:NnNNwN`
`\__cmd_show_expandable:N`
`\__cmd_show_expandable:NnNNNNnN`
`\__cmd_show_command_aux:nNNn`
`\__cmd_show_environment:N`

These commands just expand the command once to reveal its innards, then pass the type of command, the control sequence, the signature, and the code macro to `\__cmd_show_command_aux:nNNn`.

```
\cs_new_protected:Npn \__cmd_show_command:N #1
  { \exp_after:wN \__cmd_show_command:NnNNwN #1 \q__cmd #1 }
\cs_new_protected:Npn \__cmd_show_command:NnNNwN #1 #2 #3 #4 #5 \q__cmd #6
  { \__cmd_show_command_aux:nNNn { document~command } #6 #4 {#2} }
\cs_new_protected:Npn \__cmd_show_expandable:N #1
  { \exp_after:wN \__cmd_show_expandable:NnNNNNnN #1 #1 }
\cs_new_protected:Npn \__cmd_show_expandable:NnNNNNnN #1 #2 #3 #4 #5 #6 #7 #8
  { \__cmd_show_command_aux:nNNn { expandable~document~command } #8 #5 {#2} }
```

Now just print everything in the required format. The auxiliary `\__cmd_split_signature:n` stores a ready-to-print token list in `\l__cmd_tmpa_tl`, so we ust use that here:

```
\cs_new_protected:Npn \__cmd_show_command_aux:nNNn #1 #2 #3 #4
  {
    \__cmd_split_signature:n {#4}
```

```
    \tl_show:x
      {
        \token_to_str:N #2 = #1: \iow_newline:
        \tl_use:N \l__cmd_tmpa_tl
        -> \cs_replacement_spec:N #3
      }
  }
```

We can reuse most of the above to show an environment, except that we need to ensure that the proper `\environment ...` are passed to `\__cmd_show_command_aux:nNNn`. Additionally, when `\ShowCommand\foo` is used (if `foo` is an environment), we show `\endfoo` as well, and when `\ShowCommand\endfoo` is used, change that to `\ShowCommand\foo` and do the same.

```
\cs_new_protected:Npn \__cmd_show_environment:N #1
  {
    \exp_after:wN \__cmd_show_environment:Nnnw #1 \q__cmd
    \tl_show:x
      {
        \token_to_str:N \end { \cs_to_str:N #1 } : \iow_newline:
        -> \exp_args:Nc \cs_replacement_spec:N
          { environment~ \cs_to_str:N #1 ~end~aux~ }
      }
  }
\cs_new_protected:Npn \__cmd_show_environment:Nnnw #1 #2 #3 #4 \q__cmd
  {
    \use:x
      {
        \__cmd_show_command_aux:nNNn { document~environment }
          { \exp_not:N \begin {#3} }
          \exp_not:c { environment~ #3 ~ code }
          {#2}
      }
  }
\cs_new_protected:Npn \__cmd_show_environment_end:N #1
  {
    \exp_args:NNx \__cmd_check_end:Nn \l__cmd_tmpa_tl { \cs_to_str:N #1 }
    \exp_args:Nc \__cmd_show_environment:N { \l__cmd_tmpa_tl }
  }
```

And, of course, add `\__kernel_cmd_if_xparse:NTF` and `\__cmd_show:N` to `\@showcommandlisthoo

```
\tl_gput_right:Nn \@showcommandlisthook
  { { \__kernel_cmd_if_xparse:NTF \__cmd_show:N } }
```

(*End definition for* `\__cmd_show_command:N` *and others.*)

`\__cmd_split_signature:n` Now we'll try a least-effort adventure into splitting the symbolic user-provided signature for a command into individual parameters for pretty-printing. A counter is used to keep track of the current argument number, and two token lists are used: `\l__cmd_tmpa_tl` holds the final token list to be printed, and `\l__cmd_tmpb_tl` holds just the current item, so that we can make changes to an individual item without having to dissect the whole thing (this is used for `e`- and `E`-types).

```
\cs_new_protected:Npn \__cmd_split_signature:n #1
  {
    \int_set:Nn \l__cmd_current_arg_int { 1 }
```

```
    \tl_clear:N \l__cmd_tmpa_tl
    \tl_clear:N \l__cmd_tmpb_tl
    \__cmd_split_signature_loop:Nw #1 \q_recursion_tail \q_recursion_stop
  }
```

__cmd_split_signature_loop:Nw

This is the main chunk of the loop: it starts an item with `\__cmd_split_start_item:` (this adds indentation and the argument number to `\l__cmd_tmpb_tl`), then checks if a special token list `\c__cmd_show_type_`⟨*type*⟩`_tl` exists. If it doesn't, the current argument is a "simple" type which needs no extra processing. Otherwise, call a specific function depending on the value of said token list.

```
\cs_new_protected:Npn \__cmd_split_signature_loop:Nw #1
  {
    \quark_if_recursion_tail_stop:N #1
    \tl_if_empty:NT \l__cmd_tmpb_tl { \__cmd_split_start_item: }
    \tl_if_exist:cTF { c__cmd_show_type_#1_tl }
      {
        \use:c
          {
            __cmd_show_
            \if_case:w \tl_use:c { c__cmd_show_type_#1_tl } \exp_stop_f:
            delim \or: delims \or: delims_opt \or: opt \or:
            e \or: E \or: prefix \or: processor \fi: :Nw
          } #1
      }
      { \__cmd_split_end_item:n {#1} \__cmd_split_signature_loop:Nw }
  }
```

\c__cmd_show_type_t_tl
\c__cmd_show_type_r_tl
\c__cmd_show_type_d_tl
\c__cmd_show_type_R_tl
\c__cmd_show_type_D_tl
\c__cmd_show_type_O_tl
\c__cmd_show_type_e_tl
\c__cmd_show_type_E_tl
\c__cmd_show_type_+_tl
\c__cmd_show_type_!_tl
\c__cmd_show_type_>_tl

The token lists `\c__cmd_show_type_`⟨*type*⟩`_tl` exist for nontrivial (for printing) ⟨*types*⟩ that require special parsing (like delimiters or optional arguments). Values from 0 to 7 are assigned to each type:

1. a single delimiter token;
2. two delimiter tokens;
3. two delimiter tokens plus a default value;
4. a default value;
5. a list of embellishments (exclusive for `e`-type);
6. embellishments plus defaults (exclusive for `E`-type);
7. simple prefixes;
8. prefixes with arguments (argument processors);

```
\cs_set_protected:Npn \__cmd_tmp:w #1 #2
  {
    \quark_if_nil:nF {#1}
      { \tl_const:cn { c__cmd_show_type_#1_tl } {#2} \__cmd_tmp:w }
  }
\__cmd_tmp:w t0 r1 d1 R2 D2 O3 e4 E5 +6 !6 >7 \q_nil \q_nil
```

Now, based on each type we know how to act. In most cases it is just a matter of feeding in the grabbed arguments and resuming the loop. The embellishments require a bit more attention: the e-type loops through the list of embellishments and adds each to the token list as a separate argument. The E-type does more or less the same, but uses __cmd_tl_mapthread_function:nnN to map over two lists simultaneously, adding each token and default to the token list for printing.

__cmd_show_delim:Nw
__cmd_show_delims:Nw
__cmd_show_delims_opt:Nw
__cmd_show_opt:Nw
__cmd_show_e:Nw
__cmd_show_E:Nw
__cmd_show_prefix:Nw
__cmd_show_processor:Nw

```
\cs_new_protected:Npn \__cmd_show_delim:Nw #1 #2
  { \__cmd_split_end_item:n { #1 #2 } \__cmd_split_signature_loop:Nw }
\cs_new_protected:Npn \__cmd_show_delims:Nw #1 #2 #3
  { \__cmd_split_end_item:n { #1 #2 #3 } \__cmd_split_signature_loop:Nw }
\cs_new_protected:Npn \__cmd_show_delims_opt:Nw #1 #2 #3 #4
  { \__cmd_split_end_item:n { #1 #2 #3 {#4} } \__cmd_split_signature_loop:Nw }
\cs_new_protected:Npn \__cmd_show_opt:Nw #1 #2
  { \__cmd_split_end_item:n { #1 {#2} } \__cmd_split_signature_loop:Nw }
\cs_new_protected:Npn \__cmd_show_e:Nw #1 #2
  {
    \tl_map_inline:nn {#2}
      {
        \__cmd_split_start_item:
        \__cmd_split_end_item:n { #1 ##1 }
      }
    \__cmd_split_signature_loop:Nw
  }
\cs_set_protected:Npn \__cmd_tmp:w #1
  {
    \cs_new_protected:Npn \__cmd_show_E:Nw ##1 ##2 ##3
      {
        \cs_set_protected:Npn \__cmd_tmp:w ####1 ####2
          {
            \__cmd_split_start_item:
            \__cmd_split_end_item:n { ##1 ####1 {####2} }
          }
        \__cmd_tl_mapthread_function:nnN {##2}
          { ##3 {#1} {#1} {#1} {#1} {#1} {#1} {#1} {#1} {#1} } \__cmd_tmp:w
        \__cmd_split_signature_loop:Nw
      }
  }
\exp_args:NV \__cmd_tmp:w \c_novalue_tl
```

Minor wrinkle with the prefixes: they use __cmd_split_add_item:n instead of __cmd_split_end_item:n (add *vs.* end) because they are followed by an argument, so they can't end the item.

```
\cs_new_protected:Npn \__cmd_show_prefix:Nw #1
  { \__cmd_split_add_item:n {#1} \__cmd_split_signature_loop:Nw }
\cs_new_protected:Npn \__cmd_show_processor:Nw #1 #2
  { \__cmd_split_add_item:n { #1 {#2} } \__cmd_split_signature_loop:Nw }
```

And now the auxiliaries that store the strings to be printed. __cmd_split_start_item: starts an item from scratch, __cmd_split_add_item:n adds tokens to an item without adding a newline, and __cmd_split_end_item:n adds tokens, terminates the item with a newline, and steps the argument count.

```
\cs_new_protected:Npn \__cmd_split_start_item:
  {
```

```
    \tl_set:Nx \l__cmd_tmpb_tl
      { ~ \c_space_tl \c_hash_str \int_use:N \l__cmd_current_arg_int : }
  }
\cs_new_protected:Npn \__cmd_split_add_item:n #1
  { \tl_put_right:Nx \l__cmd_tmpb_tl { \tl_to_str:n {#1} } }
\cs_new_protected:Npn \__cmd_split_end_item:n #1
  {
    \tl_put_right:Nx \l__cmd_tmpa_tl
      { \l__cmd_tmpb_tl \tl_to_str:n {#1} \iow_newline: }
    \tl_clear:N \l__cmd_tmpb_tl
    \int_incr:N \l__cmd_current_arg_int
  }
```

(*End definition for* `\__cmd_split_signature:n` *and others.*)

Not much to do regarding latexrelease: we could remove the entries from `\@showcommandlisthook`, but it doesn't seem worth it.

```
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__cmd_show:N}%
⟨latexrelease⟩   {Support~\ShowCommand~in~ltcmd}
⟨latexrelease⟩\EndIncludeInRelease
```

1.8 Grabbing arguments

All of the grabbers follow the same basic pattern. The initial function stores in `\l__cmd_signature_tl` the code to grab further arguments, defines (the function in) `\l__cmd_fn_tl` that will grab the argument, and calls it.

Defining `\l__cmd_fn_tl` means determining whether to use `\cs_set:Npn` or `\cs_set_nopar:Npn`, and for optional arguments whether to skip spaces. Once the argument is found, `\l__cmd_fn_tl` calls `\__cmd_add_arg:n`, responsible for calling processors and grabbing further arguments.

`\__cmd_grab_b:w`
`\__cmd_grab_b_long:w`
`\__cmd_grab_b_obey_spaces:w`
`\__cmd_grab_b_long_obey_spaces:w`
`\__cmd_grab_b_aux:NNw`
`\__cmd_grab_b_end:Nw`

This uses the well-tested code of `D`-type arguments, skipping the peeking step because the `b`-type argument is always present, and adding a cleanup stage at the end by hijacking the signature. The clean-up consists of properly dealing with `\l__cmd_args_tl` and also putting back the `\end` that served as an end-delimiter: this `\end` receives the environment name as its argument and is run normally. The `D`-type code stores the argument found (body of the environment) as a brace group in `\l__cmd_args_tl` and depending on the presence of a prefix `!` we trim spaces or not before adding this braced argument into the saved `\l__cmd_args_tl`. The strange `\begin␣` control sequence is there for display purposes only: it has to look like `\begin` in the terminal but not to delimited arguments.

```
\cs_new_protected:Npn \__cmd_grab_b:w
  { \__cmd_grab_b_aux:NNw \cs_set_protected_nopar:Npn \tl_trim_spaces:n }
\cs_new_protected:Npn \__cmd_grab_b_long:w
  { \__cmd_grab_b_aux:NNw \cs_set_protected:Npn \tl_trim_spaces:n }
\cs_new_protected:Npn \__cmd_grab_b_obey_spaces:w
  { \__cmd_grab_b_aux:NNw \cs_set_protected_nopar:Npn \exp_not:n }
\cs_new_protected:Npn \__cmd_grab_b_long_obey_spaces:w
  { \__cmd_grab_b_aux:NNw \cs_set_protected:Npn \exp_not:n }
\cs_new_protected:Npn \__cmd_grab_b_aux:NNw #1#2#3 \__cmd_run_code:
  {
    \__cmd_grab_D_aux:NNnN \begin \end {#3} #1
```

```
    \tl_put_left:Nn \l__cmd_signature_tl { \__cmd_grab_b_end:Nw #2 }
    \tl_set_eq:NN \l__cmd_saved_args_tl \l__cmd_args_tl
    \tl_clear:N \l__cmd_args_tl
    \exp_args:Nc \l__cmd_fn_tl { begin ~ }
  }
\cs_new_protected:Npn \__cmd_grab_b_end:Nw #1#2 \__cmd_run_code:
  {
    \tl_set:Nx \l__cmd_args_tl
      {
        \exp_not:V \l__cmd_saved_args_tl
        { \exp_after:wN #1 \l__cmd_args_tl }
      }
    #2
    \__cmd_run_code:
    \end
  }
```

(*End definition for* `\__cmd_grab_b:w` *and others.*)

`\__cmd_grab_D:w`
`\__cmd_grab_D_long:w`
`\__cmd_grab_D_obey_spaces:w`
`\__cmd_grab_D_long_obey_spaces:w`

The generic delimited argument grabber. The auxiliary function does a peek test before calling `\__cmd_grab_D_call:Nw`, so that the optional nature of the argument works as expected.

```
\cs_new_protected:Npn \__cmd_grab_D:w #1#2#3 \__cmd_run_code:
  {
    \__cmd_grab_D_aux:NNnNN #1 #2 {#3} \cs_set_protected_nopar:Npn
      \__cmd_peek_nonspace_remove:NTF
  }
\cs_new_protected:Npn \__cmd_grab_D_long:w #1#2#3 \__cmd_run_code:
  {
    \__cmd_grab_D_aux:NNnNN #1 #2 {#3} \cs_set_protected:Npn
      \__cmd_peek_nonspace_remove:NTF
  }
\cs_new_protected:Npn \__cmd_grab_D_obey_spaces:w #1#2#3 \__cmd_run_code:
  {
    \__cmd_grab_D_aux:NNnNN #1 #2 {#3} \cs_set_protected_nopar:Npn
      \__cmd_peek_meaning_remove:NTF
  }
\cs_new_protected:Npn \__cmd_grab_D_long_obey_spaces:w #1#2#3 \__cmd_run_code:
  {
    \__cmd_grab_D_aux:NNnNN #1 #2 {#3} \cs_set_protected:Npn
      \__cmd_peek_meaning_remove:NTF
  }
```

`\__cmd_grab_D_aux:NNnNN`
`\__cmd_grab_D_aux:NNnN`

This is a bit complicated. The idea is that, in order to check for nested optional argument tokens (`[[...]]` and so on) the argument needs to be grabbed without removing any braces at all. If this is not done, then cases like `[{[}]` fail. So after testing for an optional argument, it is collected piece-wise. Inserting a quark prevents loss of braces, and there is then a test to see if there are nested delimiters to handle.

```
\cs_new_protected:Npn \__cmd_grab_D_aux:NNnNN #1#2#3#4#5
  {
    \__cmd_grab_D_aux:NNnN #1#2 {#3} #4
    #5 #1
      { \__cmd_grab_D_call:Nw #1 }
      { \__cmd_add_arg:o \c_novalue_tl }
```

```
  }
```

Inside the "standard" grabber, there is a test to see if the grabbed argument is entirely enclosed by braces. There are a couple of extra factors to allow for: the argument might be entirely empty, and spaces at the start and end of the input must be retained around a brace group. Also notice that a *blank* argument might still contain spaces.

```
\cs_new_protected:Npn \__cmd_grab_D_aux:NNnN #1#2#3#4
  {
    \tl_set:Nn \l__cmd_signature_tl {#3}
    \exp_after:wN #4 \l__cmd_fn_tl ##1 #2
      {
        \tl_if_in:nnTF {##1} {#1}
          { \__cmd_grab_D_nested:NNnN #1 #2 {##1} #4 }
          {
            \tl_if_blank:oTF { \use_none:n ##1 }
              { \__cmd_add_arg:o { \use_none:n ##1 } }
              {
                \str_if_eq:eeTF
                  { \exp_not:o { \use_none:n ##1 } }
                  { { \exp_not:o { \use_ii:nnn ##1 \q_nil } } }
                  { \__cmd_add_arg:o { \use_ii:nn ##1 } }
                  { \__cmd_add_arg:o { \use_none:n ##1 } }
              }
          }
      }
  }
```

(*End definition for* `\__cmd_grab_D:w` *and others.*)

`\__cmd_grab_D_nested:NNnN`
`\__cmd_grab_D_nested:w`
`\l__cmd_nesting_a_tl`
`\l__cmd_nesting_b_tl`
`\q__cmd`

Catching nested optional arguments means more work. The aim here is to collect up each pair of optional tokens without TEX helping out, and without counting anything. The code above will already have removed the leading opening token and a closing token, but the wrong one. The aim is then to work through the material grabbed so far and divide it up on each opening token, grabbing a closing token to match (thus working in pairs). Once there are no opening tokens, then there is a second check to see if there are any opening tokens in the second part of the argument (for things like `[][]`). Once everything has been found, the entire collected material is added to the output as a single argument. The only tricky part here is ensuring that any grabbing function that might run away is named after the function currently being parsed and not after xparse. That leads to some rather complex nesting! There is also a need to prevent the loss of any braces, hence the insertion and removal of quarks along the way.

```
\tl_new:N \l__cmd_nesting_a_tl
\tl_new:N \l__cmd_nesting_b_tl
\quark_new:N \q__cmd
\cs_new_protected:Npn \__cmd_grab_D_nested:NNnN #1#2#3#4
  {
    \tl_clear:N \l__cmd_nesting_a_tl
    \tl_clear:N \l__cmd_nesting_b_tl
    \exp_after:wN #4 \l__cmd_fn_tl ##1 #1 ##2 \q__cmd ##3 #2
      {
        \tl_put_right:No \l__cmd_nesting_a_tl { \use_none:n ##1 #1 }
        \tl_put_right:No \l__cmd_nesting_b_tl { \use_i:nn #2 ##3 }
        \tl_if_in:nnTF {##2} {#1}
```

```
          {
            \l__cmd_fn_tl
              \q_nil ##2 \q__cmd \ERROR
          }
          {
            \tl_put_right:Nx \l__cmd_nesting_a_tl
              { \__cmd_grab_D_nested:w \q_nil ##2 \q_stop }
            \tl_if_in:NnTF \l__cmd_nesting_b_tl {#1}
              {
                \tl_set_eq:NN \l__cmd_tmpa_tl \l__cmd_nesting_b_tl
                \tl_clear:N \l__cmd_nesting_b_tl
                \exp_after:wN \l__cmd_fn_tl \exp_after:wN
                  \q_nil \l__cmd_tmpa_tl \q_nil \q__cmd \ERROR
              }
              {
                \tl_put_right:No \l__cmd_nesting_a_tl
                  \l__cmd_nesting_b_tl
                \__cmd_add_arg:V \l__cmd_nesting_a_tl
              }
          }
      }
    \l__cmd_fn_tl #3 \q_nil \q__cmd \ERROR
  }
\cs_new:Npn \__cmd_grab_D_nested:w #1 \q_nil \q_stop
  { \exp_not:o { \use_none:n #1 } }
```

(*End definition for* `\__cmd_grab_D_nested:NNnN` *and others.*)

`\__cmd_grab_D_call:Nw` For `D` and `R`-type arguments, to avoid losing any braces, a token needs to be inserted before the argument to be grabbed. If the argument runs away because the closing token is missing then this inserted token shows up in the terminal. Ideally, `#1` would therefore be used directly, but that is no good as it will mess up the rest of the grabber. Instead, a copy of `#1` with an altered category code is used, as this will look right in the terminal but will not mess up the grabber. The only issue then is that the category code of `#1` is unknown. So there is a quick test to ensure that the inserted token can never be matched by the grabber. (This assumes that the open and close delimiters are not the same character with different category codes, but that really should not happen in any sensible document-level syntax.) An exception is when `#1` is a control sequence token, in which case the character-token treatment is no good because if hit with `\token_to_str:N` it would add sputios tokens to the argument. In this case a different branch is taken. The token inserted is then the same ⟨*csname*⟩ as `#1`, but with a space appended, so that the grabber don't see it as another of the same delimiter.

```
\cs_new_protected_nopar:Npn \__cmd_grab_D_call:Nw #1
  {
    \token_if_eq_catcode:NNTF + #1
      {
        \exp_after:wN \exp_after:wN \exp_after:wN
          \l__cmd_fn_tl \char_generate:nn { `#1 } { 11 }
      }
      {
        \__cmd_token_if_cs:NTF #1
          {
            \exp_after:wN \l__cmd_fn_tl
```

```
            \cs:w \cs_to_str:N #1 ~ \cs_end:
          }
          {
            \exp_after:wN \l__cmd_fn_tl
            \token_to_str:N #1
          }
      }
  }
```

(*End definition for* `\__cmd_grab_D_call:Nw`.)

`\__cmd_grab_E:w`
`\__cmd_grab_E_long:w`
`\__cmd_grab_E_obey_spaces:w`
`\__cmd_grab_E_long_obey_spaces:w`
`\__cmd_grab_E:nnNN`
`\__cmd_grab_E_loop:NnN`
`\__cmd_grab_E_finalise:`

Everything here needs to point to a loop.

```
\cs_new_protected:Npn \__cmd_grab_E:w #1#2 \__cmd_run_code:
  {
    \__cmd_grab_E:nnNN {#1} {#2}
      \cs_set_protected_nopar:Npn
      \__cmd_peek_nonspace_remove:NTF
  }
\cs_new_protected:Npn \__cmd_grab_E_long:w #1#2 \__cmd_run_code:
  {
    \__cmd_grab_E:nnNN {#1} {#2}
      \cs_set_protected:Npn
      \__cmd_peek_nonspace_remove:NTF
  }
\cs_new_protected:Npn \__cmd_grab_E_obey_spaces:w #1#2 \__cmd_run_code:
  {
    \__cmd_grab_E:nnNN {#1} {#2}
      \cs_set_protected_nopar:Npn
      \__cmd_peek_meaning_remove:NTF
  }
\cs_new_protected:Npn \__cmd_grab_E_long_obey_spaces:w #1#2 \__cmd_run_code:
  {
    \__cmd_grab_E:nnNN {#1} {#2}
      \cs_set_protected:Npn
      \__cmd_peek_meaning_remove:NTF
  }
```

A loop is needed here to allow a random ordering of keys. These are searched for one at a time, with any not found needing to be tracked: they can appear later. The grabbed values are held in a property list which is then turned into an ordered list to be passed back to the user.

```
\cs_new_protected:Npn \__cmd_grab_E:nnNN #1#2#3#4
  {
    \exp_after:wN #3 \l__cmd_fn_tl ##1##2##3
      {
        \prop_put:Nnn \l__cmd_tmp_prop {##1} {##3}
        \__cmd_grab_E_loop:NnN #4 { } ##2 \q_recursion_stop
      }
    \prop_clear:N \l__cmd_tmp_prop
    \tl_set:Nn \l__cmd_signature_tl {#2}
    \cs_set_protected:Npn \__cmd_grab_E_finalise:
      {
        \tl_map_inline:nn {#1}
          {
```

```
            \prop_get:NnNF \l__cmd_tmp_prop {####1} \l__cmd_tmpb_tl
              { \tl_set_eq:NN \l__cmd_tmpb_tl \c_novalue_tl }
            \tl_put_right:Nx \l__cmd_args_tl
              { { \exp_not:V \l__cmd_tmpb_tl } }
          }
        \l__cmd_signature_tl \__cmd_run_code:
      }
    \__cmd_grab_E_loop:NnN #4 { } #1 \q_recursion_tail \q_recursion_stop
  }
\cs_new_protected:Npn \__cmd_grab_E_loop:NnN #1#2#3#4 \q_recursion_stop
  {
    \cs_if_eq:NNTF #3 \q_recursion_tail
      { \__cmd_grab_E_finalise: }
      {
        #1 #3
          { \l__cmd_fn_tl #3 {#2#4} }
          { \__cmd_grab_E_loop:NnN #1 {#2#3} #4 \q_recursion_stop }
      }
  }
\cs_new_protected:Npn \__cmd_grab_E_finalise: { }
```

(*End definition for* `\__cmd_grab_E:w` *and others.*)

`\__cmd_grab_m:w`
`\__cmd_grab_m_long:w`

Collecting a single mandatory argument is quite easy.

```
\cs_new_protected:Npn \__cmd_grab_m:w #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_protected_nopar:Npn \l__cmd_fn_tl ##1
      { \__cmd_add_arg:n {##1} }
    \l__cmd_fn_tl
  }
\cs_new_protected:Npn \__cmd_grab_m_long:w #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_protected:Npn \l__cmd_fn_tl ##1
      { \__cmd_add_arg:n {##1} }
    \l__cmd_fn_tl
  }
```

(*End definition for* `\__cmd_grab_m:w` *and* `\__cmd_grab_m_long:w`.)

`\__cmd_grab_m_1:w`
`\__cmd_grab_m_2:w`
`\__cmd_grab_m_3:w`
`\__cmd_grab_m_4:w`
`\__cmd_grab_m_5:w`
`\__cmd_grab_m_6:w`
`\__cmd_grab_m_7:w`
`\__cmd_grab_m_8:w`
`\__cmd_grab_m_9:w`
`\__cmd_grab_m_aux:Nnnnnnnnn`

Grabbing 1–8 mandatory arguments is done by giving 8–1 known arguments to a 9-argument function that stores them in `\l__cmd_args_tl`. For simplicity, grabbing 9 mandatory arguments is done by grabbing 5 then 4 arguments.

```
\cs_new_protected_nopar:Npn \__cmd_grab_m_aux:Nnnnnnnnn #1#2#3#4#5#6#7#8#9
  {
    \tl_put_right:No \l__cmd_args_tl
      { #1 {#2} {#3} {#4} {#5} {#6} {#7} {#8} {#9} }
    \l__cmd_signature_tl \__cmd_run_code:
  }
\cs_new_protected:cpn { __cmd_grab_m_1:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
```

```
    \l__cmd_fn_tl \use_none:nnnnnnn { } { } { } { } { } { } { }
  }
\cs_new_protected:cpn { __cmd_grab_m_2:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
    \l__cmd_fn_tl \use_none:nnnnnn { } { } { } { } { } { }
  }
\cs_new_protected:cpn { __cmd_grab_m_3:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
    \l__cmd_fn_tl \use_none:nnnnn { } { } { } { } { }
  }
\cs_new_protected:cpn { __cmd_grab_m_4:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
    \l__cmd_fn_tl \use_none:nnnn { } { } { } { }
  }
\cs_new_protected:cpn { __cmd_grab_m_5:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
    \l__cmd_fn_tl \use_none:nnn { } { } { }
  }
\cs_new_protected:cpn { __cmd_grab_m_6:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
    \l__cmd_fn_tl \use_none:nn { } { }
  }
\cs_new_protected:cpn { __cmd_grab_m_7:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
    \l__cmd_fn_tl \use_none:n { }
  }
\cs_new_protected:cpn { __cmd_grab_m_8:w } #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \exp_after:wN \cs_set_eq:NN \l__cmd_fn_tl \__cmd_grab_m_aux:Nnnnnnnnn
    \l__cmd_fn_tl \prg_do_nothing:
  }
\cs_new_protected:cpx { __cmd_grab_m_9:w }
  {
    \exp_not:c { __cmd_grab_m_5:w }
    \exp_not:c { __cmd_grab_m_4:w }
  }
```

(*End definition for* `\__cmd_grab_m_1:w` *and others.*)

`\__cmd_grab_R:w`
`\__cmd_grab_R_long:w`
`\__cmd_grab_R_aux:NNnN`

The grabber for `R`-type arguments is basically the same as that for `D`-type ones, but always skips spaces (as it is mandatory) and has a hard-coded error message.

```
\cs_new_protected:Npn \__cmd_grab_R:w #1#2#3 \__cmd_run_code:
  { \__cmd_grab_R_aux:NNnN #1 #2 {#3} \cs_set_protected_nopar:Npn }
\cs_new_protected:Npn \__cmd_grab_R_long:w #1#2#3 \__cmd_run_code:
  { \__cmd_grab_R_aux:NNnN #1 #2 {#3} \cs_set_protected:Npn }
\cs_new_protected:Npn \__cmd_grab_R_aux:NNnN #1#2#3#4
  {
    \__cmd_grab_D_aux:NNnN #1 #2 {#3} #4
    \__cmd_peek_nonspace_remove:NTF #1
      { \__cmd_grab_D_call:Nw #1 }
      {
        \msg_error:nnxx { cmd } { missing-required }
          { \__cmd_environment_or_command: }
          { \token_to_str:N #1 }
        \__cmd_add_arg:o \c_novalue_tl
      }
  }
```

(*End definition for* `\__cmd_grab_R:w`, `\__cmd_grab_R_long:w`, *and* `\__cmd_grab_R_aux:NNnN`.)

`\__cmd_grab_t:w`
`\__cmd_grab_t_obey_spaces:w`
`\__cmd_grab_t_aux:NNw`

Dealing with a token is quite easy. Check the match, remove the token if needed and add a flag to the output.

```
\cs_new_protected:Npn \__cmd_grab_t:w
  { \__cmd_grab_t_aux:NNw \__cmd_peek_nonspace_remove:NTF }
\cs_new_protected:Npn \__cmd_grab_t_obey_spaces:w
  { \__cmd_grab_t_aux:NNw \__cmd_peek_meaning_remove:NTF }
\cs_new_protected:Npn \__cmd_grab_t_aux:NNw #1#2#3 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#3}
    \exp_after:wN \cs_set_protected:Npn \l__cmd_fn_tl
      {
        #1 #2
          { \__cmd_add_arg:n { \BooleanTrue } }
          { \__cmd_add_arg:n { \BooleanFalse } }
      }
    \l__cmd_fn_tl
  }
```

(*End definition for* `\__cmd_grab_t:w`, `\__cmd_grab_t_obey_spaces:w`, *and* `\__cmd_grab_t_aux:NNw`.)

`\l__cmd_v_arg_tl`

```
\tl_new:N \l__cmd_v_arg_tl
```

`\__cmd_grab_v:w`
`\__cmd_grab_v_long:w`
`\__cmd_grab_v_aux:w`
`\__cmd_grab_v_group_end:`

The opening delimiter is the first non-space token, and is never read verbatim. This is required by consistency with the case where the preceding argument was optional and absent: then TEX has already read and tokenized that token when looking for the optional argument. The first thing is thus to check is that this delimiter is a character, and to distinguish the case of a left brace (in that case, `\group_align_safe_end:` is needed to compensate for the begin-group character that was just seen). Then set verbatim catcodes with `\__cmd_grab_v_aux_catcodes:`.

The group keep catcode changes local, and `\group_align_safe_begin/end:` allow to use a character with category code 4 (normally `&`) as the delimiter (all commands do `\group_align_safe_begin/end:`, so there's no need to do that again here). It is

ended by `\__cmd_grab_v_group_end:`, which smuggles the collected argument out of the group.

```
\cs_new_protected:Npn \__cmd_grab_v:w
  {
    \bool_set_false:N \l__cmd_long_bool
    \__cmd_grab_v_aux:w
  }
\cs_new_protected:Npn \__cmd_grab_v_long:w
  {
    \bool_set_true:N \l__cmd_long_bool
    \__cmd_grab_v_aux:w
  }
\cs_new_protected:Npn \__cmd_grab_v_aux:w #1 \__cmd_run_code:
  {
    \tl_set:Nn \l__cmd_signature_tl {#1}
    \group_begin:
      \tex_escapechar:D = 92 \scan_stop:
      \tl_clear:N \l__cmd_v_arg_tl
      \peek_remove_spaces:n
        {
          \peek_meaning_remove:NTF \c_group_begin_token
            {
              \group_align_safe_end:
              \__cmd_grab_v_bgroup:
            }
            {
              \peek_N_type:TF
                { \__cmd_grab_v_aux_test:N }
                { \__cmd_grab_v_aux_abort:n { } }
            }
        }
  }
\cs_new_protected:Npn \__cmd_grab_v_group_end:
  {
        \exp_args:NNNo
      \group_end:
    \tl_set:Nn \l__cmd_v_arg_tl { \l__cmd_v_arg_tl }
  }
```

(*End definition for* `\__cmd_grab_v:w` *and others.*)

`\__cmd_grab_v_aux_test:N`
`\__cmd_grab_v_aux_loop:N`
`\__cmd_grab_v_aux_loop:NN`
`\__cmd_grab_v_aux_loop_end:`

Check that the opening delimiter is a character, setup category codes, then start reading tokens one by one, keeping the delimiter as an argument. If the verbatim was not nested, we will be grabbing one character at each step. Unfortunately, it can happen that what follows the verbatim argument is already tokenized. Thus, we check at each step that the next token is indeed a "nice" character, *i.e.*, is not a character with category code 1 (begin-group), 2 (end-group) or 6 (macro parameter), nor the space character, with category code 10 and character code 32, nor a control sequence. The partially built argument is stored in `\l__cmd_v_arg_tl`. If we ever meet a token which we cannot grab (non-N-type), or which is not a character according to `\__cmd_grab_v_token_if_char:NTF`, then we bail out with `\__cmd_grab_v_aux_abort:n`. Otherwise, we stop at the first character matching the delimiter.

```
\cs_new_protected:Npn \__cmd_grab_v_aux_test:N #1
```

```
  {
    \__cmd_grab_v_token_if_char:NTF #1
      {
        \__cmd_grab_v_aux_put:N #1
        \__cmd_grab_v_aux_catcodes:
        \__cmd_grab_v_aux_loop:N #1
      }
      { \__cmd_grab_v_aux_abort:n {#1} #1 }
  }
\cs_new_protected:Npn \__cmd_grab_v_aux_loop:N #1
  {
    \peek_N_type:TF
      { \__cmd_grab_v_aux_loop:NN #1 }
      { \__cmd_grab_v_aux_abort:n { } }
  }
\cs_new_protected:Npn \__cmd_grab_v_aux_loop:NN #1#2
  {
    \__cmd_grab_v_token_if_char:NTF #2
      {
        \token_if_eq_charcode:NNTF #1 #2
          { \__cmd_grab_v_aux_loop_end: }
          {
            \__cmd_grab_v_aux_put:N #2
            \__cmd_grab_v_aux_loop:N #1
          }
      }
      { \__cmd_grab_v_aux_abort:n {#2} #2 }
  }
\cs_new_protected:Npn \__cmd_grab_v_aux_loop_end:
  {
    \__cmd_grab_v_group_end:
    \__cmd_add_arg:x { \tl_tail:N \l__cmd_v_arg_tl }
  }
```

(*End definition for* `\__cmd_grab_v_aux_test:N` *and others.*)

`\l__cmd_v_nesting_int`

```
\int_new:N \l__cmd_v_nesting_int
```

`\__cmd_grab_v_bgroup:`
`\__cmd_grab_v_bgroup_loop:`
`\__cmd_grab_v_bgroup_loop:N`

If the opening delimiter is a left brace, we keep track of how many left and right braces were encountered so far in `\l__cmd_v_nesting_int` (the methods used for optional arguments cannot apply here), and stop as soon as it reaches 0.

Some care was needed when removing the opening delimiter, which has already been assigned category code 1: using `\peek_meaning_remove:NTF` in the `\__cmd_grab_v_aux:w` function would break within alignments. Instead, we first convert that token to a string, and remove the result as a normal undelimited argument.

```
\cs_new_protected:Npx \__cmd_grab_v_bgroup:
  {
    \exp_not:N \__cmd_grab_v_aux_catcodes:
    \exp_not:n { \int_set:Nn \l__cmd_v_nesting_int { 1 } }
    \exp_not:N \__cmd_grab_v_aux_put:N \iow_char:N \{
    \exp_not:N \__cmd_grab_v_bgroup_loop:
  }
```

```
\cs_new_protected:Npn \__cmd_grab_v_bgroup_loop:
  {
    \peek_N_type:TF
      { \__cmd_grab_v_bgroup_loop:N }
      { \__cmd_grab_v_aux_abort:n { } }
  }
\cs_new_protected:Npn \__cmd_grab_v_bgroup_loop:N #1
  {
    \__cmd_grab_v_token_if_char:NTF #1
      {
        \token_if_eq_charcode:NNTF \c_group_end_token #1
          {
            \int_decr:N \l__cmd_v_nesting_int
            \int_compare:nNnTF \l__cmd_v_nesting_int > 0
              {
                \__cmd_grab_v_aux_put:N #1
                \__cmd_grab_v_bgroup_loop:
              }
              { \__cmd_grab_v_aux_loop_end: }
          }
          {
            \token_if_eq_charcode:NNT \c_group_begin_token #1
              { \int_incr:N \l__cmd_v_nesting_int }
            \__cmd_grab_v_aux_put:N #1
            \__cmd_grab_v_bgroup_loop:
          }
      }
      { \__cmd_grab_v_aux_abort:n {#1} #1 }
  }
```

(*End definition for* `\__cmd_grab_v_bgroup:`, `\__cmd_grab_v_bgroup_loop:`, *and* `\__cmd_grab_v_bgroup_loop:N`.)

`\__cmd_grab_v_aux_catcodes:`
`\__cmd_grab_v_aux_abort:n`

The approach for short verbatim arguments is to make the end-line character a macro parameter character: this is forbidden by the rest of the code. Then the error branch can check what caused the bail out and give the appropriate error message.

```
\cs_new_protected:Npn \__cmd_grab_v_aux_catcodes:
  {
    \cs_set_eq:NN \do \char_set_catcode_other:N
    \dospecials
    \tex_endlinechar:D = `\^^M \scan_stop:
    \bool_if:NTF \l__cmd_long_bool
      { \char_set_catcode_other:n { \tex_endlinechar:D } }
      { \char_set_catcode_parameter:n { \tex_endlinechar:D } }
  }
\cs_new_protected:Npn \__cmd_grab_v_aux_abort:n #1
  {
    \__cmd_grab_v_group_end:
    \exp_after:wN \exp_after:wN \exp_after:wN
      \peek_meaning_remove:NTF \char_generate:nn { \tex_endlinechar:D } { 6 }
      {
        \msg_error:nnxxx { cmd } { verbatim-nl }
          { \__cmd_environment_or_command: }
          { \tl_to_str:N \l__cmd_v_arg_tl }
```

```
          { \tl_to_str:n {#1} }
        \__cmd_add_arg:o \c_novalue_tl
      }
      {
        \msg_error:nnxxx { cmd } { verbatim-tokenized }
          { \__cmd_environment_or_command: }
          { \tl_to_str:N \l__cmd_v_arg_tl }
          { \tl_to_str:n {#1} }
        \__cmd_add_arg:o \c_novalue_tl
      }
  }
```

(*End definition for* `\__cmd_grab_v_aux_catcodes:` *and* `\__cmd_grab_v_aux_abort:n`.)

`\__cmd_grab_v_aux_put:N` Storing one token in the collected argument. Most tokens are converted to category code 12, with the exception of active characters, and spaces (not sure what should be done for those).

```
\cs_new_protected:Npn \__cmd_grab_v_aux_put:N #1
  {
    \tl_put_right:Nx \l__cmd_v_arg_tl
      {
        \token_if_active:NTF #1
          { \exp_not:N #1 } { \token_to_str:N #1 }
      }
  }
```

(*End definition for* `\__cmd_grab_v_aux_put:N`.)

`\__cmd_grab_v_token_if_char:NTF` This function assumes that the escape character is printable. Then the string representation of control sequences is at least two characters, and `\str_tail:n` only removes the escape character. Macro parameter characters are doubled by `\tl_to_str:n`, and will also yield a non-empty result, hence are not considered as characters.

```
\cs_new_protected:Npn \__cmd_grab_v_token_if_char:NTF #1
  { \str_if_eq:eeTF { } { \str_tail:n {#1} } }
```

(*End definition for* `\__cmd_grab_v_token_if_char:NTF`.)

`\__cmd_add_arg:n` `\__cmd_add_arg:V` `\__cmd_add_arg:o` `\__cmd_add_arg:x` When an argument is found it is stored, then further arguments are grabbed by calling `\l__cmd_signature_tl`.

```
\cs_new_protected:Npn \__cmd_add_arg:n #1
  {
    \tl_put_right:Nn \l__cmd_args_tl { {#1} }
    \l__cmd_signature_tl \__cmd_run_code:
  }
\cs_generate_variant:Nn \__cmd_add_arg:n { V , o , x }
```

(*End definition for* `\__cmd_add_arg:n`.)

1.9 Grabbing arguments expandably

__cmd_expandable_grab_D:w
__cmd_expandable_grab_D:NNNwNNn
__cmd_expandable_grab_D:NNNwNNnnn
__cmd_expandable_grab_D:Nw
__cmd_expandable_grab_D:nnNNNwNN

The first step is to grab the first token or group. The generic grabbers \⟨*function*⟩␣ and \⟨*function*⟩␣ are just after \q__cmd, we go and find them (and use the long one).

```
\cs_new:Npn \__cmd_expandable_grab_D:w #1 \q__cmd #2#3
  { #2 { \__cmd_expandable_grab_D:NNNwNNn #1 \q__cmd #2 #3 } }
```

We then wish to test whether #7, which we just grabbed, is exactly #2. A preliminary test is whether their string representations coincide, then expand the only grabber function we have, #1, once: the two strings below are equal if and only if #7 matches #2 exactly.[2] The preliminary test is needed as #7 could validly contain \par (because a later mandatory argument could be long) and our grabber may be short. If #7 does not match #2, then the optional argument is missing, we use the default -NoValue-, and put back the argument #7 in the input stream.

If it does match, then interesting things need to be done. We will grab the argument piece by piece, with the following pattern:

⟨*grabber*⟩ {⟨*tokens*⟩}
\q_nil {⟨*piece 1*⟩} ⟨*piece 2*⟩ \ERROR \q__cmd
\q_nil ⟨*input stream*⟩

The ⟨*grabber*⟩ will find an opening delimiter in ⟨*piece 2*⟩, take the \q__cmd as a second delimiter, and find more material delimited by the closing delimiter in the ⟨*input stream*⟩. We then move the part before the opening delimiter from ⟨*piece 2*⟩ to ⟨*piece 1*⟩, and the material taken from the ⟨*input stream*⟩ to the ⟨*piece 2*⟩. Thus, the argument moves gradually from the ⟨*input stream*⟩ to the ⟨*piece 2*⟩, then to the ⟨*piece 1*⟩ when we have made sure to find all opening and closing delimiters. This two-step process ensures that nesting works: the number of opening delimiters minus closing delimiters in ⟨*piece 1*⟩ is always equal to the number of closing delimiters in ⟨*piece 2*⟩. We stop grabbing arguments once the ⟨*piece 2*⟩ contains no opening delimiter any more, hence the balance is reached, and the final argument is ⟨*piece 1*⟩ ⟨*piece 2*⟩. The indirection via __cmd_tmp:w allows to insert -NoValue- expanded.

```
\cs_set_protected:Npn \__cmd_tmp:w #1
  {
    \cs_new:Npn \__cmd_expandable_grab_D:NNNwNNn ##1##2##3##4 \q__cmd ##5##6##7
      {
        \str_if_eq:nnTF {##2} {##7}
          {
            \str_if_eq:onTF
              { ##1 { } { } ##7 ##2 \q__cmd ##3 }
              { { } {##2} { } }
          }
          { \use_ii:nn }
          {
            ##1
              { \__cmd_expandable_grab_D:NNNwNNnnn ##1##2##3##4 \q__cmd ##5##6 }
```

[2] It is obvious that if #7 matches #2 then the strings are equal. We must check the converse. The right-hand-side of \str_if_eq:onTF does not end with #3, implying that the grabber function took everything as its arguments. The first brace group can only be empty if #7 starts with #2, otherwise the brace group preceding #7 would not vanish. The third brace group is empty, thus the \q__cmd that was used by our grabber #1 must be the one that we inserted (not some token in #7), hence the second brace group contains the end of #7 followed by #2. Since this is #2 on the right-hand-side, and no brace can be lost there, #7 must contain nothing else than its leading #2.

```
            \q_nil { } ##2 \ERROR \q__cmd \ERROR
        }
        { ##4 {#1} \q__cmd ##5 ##6 {##7} }
    }
  }
\exp_args:No \__cmd_tmp:w { \c_novalue_tl }
```

At this stage, #7 is `\q_nil {`⟨*piece 1*⟩`}` ⟨*more for piece 1*⟩, and we want to concatenate all that, removing `\q_nil`, and keeping the opening delimiter #2. Simply use `\use_ii:nn`. Also, #8 is ⟨*remainder of piece 2*⟩ `\ERROR`, and #9 is `\ERROR` ⟨*more for piece 2*⟩. We concatenate those, replacing the two `\ERROR` by the closing delimiter #3.

```
\cs_new:Npn \__cmd_expandable_grab_D:NNNwNNnnn #1#2#3#4 \q__cmd #5#6#7#8#9
  {
    \exp_args:Nof \__cmd_expandable_grab_D:nnNNNwNN
      { \use_ii:nn #7 #2 }
      { \__cmd_expandable_grab_D:Nw #3 \exp_stop_f: #8 #9 }
    #1#2#3 #4 \q__cmd #5 #6
  }
\cs_new:Npn \__cmd_expandable_grab_D:Nw #1#2 \ERROR \ERROR { #2 #1 }
```

Armed with our two new ⟨*pieces*⟩, we are ready to loop. However, we must first see if ⟨*piece 2*⟩ (here #2) contains any opening delimiter #4. Again, we expand #3, this time removing its whole output with `\use_none:nnn`. The test is similar to `\tl_if_in:nnTF`. The token list is empty if and only if #2 does not contain the opening delimiter. In that case, we are done, and put the argument (from which we remove a spurious pair of delimiters coming from how we started the loop). Otherwise, we go back to looping with `\__cmd_expandable_grab_D:NNNwNNnnn`. The code to deal with brace stripping is much the same as for the non-expandable case.

```
\cs_new:Npn \__cmd_expandable_grab_D:nnNNNwNN #1#2#3#4#5#6 \q__cmd #7#8
  {
    \exp_args:No \tl_if_empty:oTF
      { #3 { \use_none:nnn } #2 \q__cmd #5 #4 \q__cmd #5 }
      {
        \tl_if_blank:oTF { \use_none:nn #1#2 }
          { \__cmd_put_arg_expandable:ow { \use_none:nn #1#2 } }
          {
            \str_if_eq:eeTF
              { \exp_not:o { \use_none:nn #1#2 } }
              { { \exp_not:o { \use_iii:nnnn #1#2 \q_nil } } }
              { \__cmd_put_arg_expandable:ow { \use_iii:nnn #1#2 } }
              { \__cmd_put_arg_expandable:ow { \use_none:nn #1#2 } }
          }
            #6 \q__cmd #7 #8
      }
      {
        #3
          { \__cmd_expandable_grab_D:NNNwNNnnn #3#4#5#6 \q__cmd #7 #8 }
          \q_nil {#1} #2 \ERROR \q__cmd \ERROR
      }
  }
```

(*End definition for* `\__cmd_expandable_grab_D:w` *and others.*)

__cmd_expandable_grab_D_alt:w
__cmd_expandable_grab_D_alt:NNwNNn
__cmd_expandable_grab_D_alt:Nwn

When the delimiters are identical, nesting is not possible and a simplified approach is used. The test concept here is the same as for the case where the delimiters are different but there cannot be any nesting.

```
\cs_new:Npn \__cmd_expandable_grab_D_alt:w #1 \q__cmd #2#3
  { #2 { \__cmd_expandable_grab_D_alt:NNwNNn #1 \q__cmd #2 #3 } }
\cs_set_protected:Npn \__cmd_tmp:w #1
  {
    \cs_new:Npn \__cmd_expandable_grab_D_alt:NNwNNn ##1##2##3 \q__cmd ##4##5##6
      {
        \str_if_eq:nnTF {##6} {##2}
          {
            \str_if_eq:onTF
              { ##1 { } ##6 ##2 ##2 }
              { { } ##2 }
          }
          { \use_ii:nn }
          {
            ##1
              { \__cmd_expandable_grab_D_alt:NNwn ##4 ##5 ##3 \q__cmd }
              ##6 \ERROR
          }
          { ##3 {#1} \q__cmd ##4 ##5 {##6} }
      }
  }
\exp_args:No \__cmd_tmp:w { \c_novalue_tl }
\cs_new:Npn \__cmd_expandable_grab_D_alt:NNwn #1#2#3 \q__cmd #4
  {
    \tl_if_blank:oTF { \use_none:n #4 }
      { \__cmd_put_arg_expandable:ow { \use_none:n #4 } }
      {
        \str_if_eq:eeTF
          { \exp_not:o { \use_none:n #4 } }
          { { \exp_not:o { \use_ii:nnn #4 \q_nil } } }
          { \__cmd_put_arg_expandable:ow { \use_ii:nn #4 } }
          { \__cmd_put_arg_expandable:ow { \use_none:n #4 } }
      }
        #3 \q__cmd #1 #2
  }
```

(*End definition for* `\__cmd_expandable_grab_D_alt:w`, `\__cmd_expandable_grab_D_alt:NNwNNn`, *and* `\__cmd_expandable_grab_D_alt:Nwn`.)

__cmd_expandable_grab_E:w
__cmd_expandable_grab_E_long:w
__cmd_expandable_grab_E_aux:w
__cmd_expandable_grab_E_test:nnw
__cmd_expandable_grab_E_loop:nnnNNw
__cmd_expandable_grab_E_find:w
__cmd_expandable_grab_E_find:nnw
__cmd_expandable_grab_E_end:nnw

We keep track of long/short by placing the appropriate grabber as the third token after `\q__cmd`; it is eventually removed by the `end:nnw` auxiliary. The `aux:w` auxiliary will be called repeatedly with two arguments: the set of pairs ⟨*parser*⟩ ⟨*token*⟩, and the set of arguments found so far (initially all `{-NoValue-}`). At each step, grab what follows in the input stream then call the `loop:nnnNNw` auxiliary to compare it with each possible embellishment in turn. This auxiliary's `#1` is what was found in the input, `#2` collects ⟨*parser*⟩ ⟨*token*⟩ pairs that did not match, `#3` collects the corresponding arguments found previously, `#4` and `#5` is the current pair, `#6` is the remaining pairs, `#7` is empty or two `\q_nil`, and `#8` is the current argument. If none of the pairs matched (determined by `\quark_if_nil:NTF`) then call the `end` auxiliary to stop looking for embellishments, remembering to put what was grabbed in the input back where it belongs, and storing

the arguments found just before \q__cmd. If the current argument #8 is not -NoValue- or if the input #1 does not match #5 (see t-type arguments below for a similar \str_if_eq:onTF test) then carry on the loop. Otherwise, we found a new embellishment: grab the corresponding argument in the input using the find:w auxiliary. To avoid losing braces around that auxiliary's argument we include a space, which will be eliminated in the next loop through embellishments.

```
\cs_new:Npn \__cmd_expandable_grab_E:w #1 \q__cmd #2#3
  { \__cmd_expandable_grab_E_aux:w #1 \q__cmd #2 #3 #3 }
\cs_new:Npn \__cmd_expandable_grab_E_long:w #1 \q__cmd #2#3
  { \__cmd_expandable_grab_E_aux:w #1 \q__cmd #2 #3 #2 }
\cs_new:Npn \__cmd_expandable_grab_E_aux:w #1 \q__cmd #2#3#4
  { #2 { \__cmd_expandable_grab_E_test:nnw #1 \q__cmd #2 #3 #4 } }
\cs_new:Npn \__cmd_expandable_grab_E_test:nnw #1#2#3 \q__cmd #4#5#6#7
  {
    \__cmd_expandable_grab_E_loop:nnnNNw {#7} { } { }
      #1 \q_nil \q_nil \q_nil \q_mark #2 \q_nil
    #3 \q__cmd #4 #5 #6
  }
\cs_new:Npn \__cmd_expandable_grab_E_loop:nnnNNw
    #1#2#3#4#5#6 \q_nil #7 \q_mark #8
  {
    \quark_if_nil:NTF #4
      { \__cmd_expandable_grab_E_end:nnw {#1} {#3} }
      {
        \tl_if_novalue:nTF {#8}
          { \str_if_eq:onTF { #4 { } #1 #5 } {#5} }
          { \use_ii:nn }
            { \__cmd_expandable_grab_E_find:w { #2 #4 #5 #6 } {#3} ~ }
            {
              \__cmd_expandable_grab_E_loop:nnnNNw
                {#1} { #2 #4 #5 } { #3 {#8} }
                #6 \q_nil #7 \q_mark
            }
      }
  }
\cs_new:Npn \__cmd_expandable_grab_E_find:w #1 \q__cmd #2#3#4
  { #4 { \__cmd_expandable_grab_E_find:nnw #1 \q__cmd #2 #3 #4 } }
\cs_new:Npn \__cmd_expandable_grab_E_find:nnw #1#2#3 \q_nil #4 \q__cmd #5#6#7#8
  { \__cmd_expandable_grab_E_aux:w {#1} { #2 {#8} #3 } #4 \q__cmd #5 #6 #7 }
\cs_new:Npn \__cmd_expandable_grab_E_end:nnw #1#2#3 \q__cmd #4#5#6
  { #3 #2 \q__cmd #4 #5 {#1} }
```

(*End definition for* __cmd_expandable_grab_E:w *and others.*)

__cmd_expandable_grab_m:w
__cmd_expandable_grab_m_long:w
__cmd_expandable_grab_m_aux:wNn

The mandatory case is easy: find the auxiliary after the \q__cmd, and use it directly to grab the argument, then correctly position the argument before \q__cmd.

```
\cs_new:Npn \__cmd_expandable_grab_m:w #1 \q__cmd #2#3
  { #3 { \__cmd_expandable_grab_m_aux:wNn #1 \q__cmd #2 #3 } }
\cs_new:Npn \__cmd_expandable_grab_m_long:w #1 \q__cmd #2#3
  { #2 { \__cmd_expandable_grab_m_aux:wNn #1 \q__cmd #2 #3 } }
\cs_new:Npn \__cmd_expandable_grab_m_aux:wNn #1 \q__cmd #2#3#4
  { #1 {#4} \q__cmd #2 #3 }
```

(*End definition for* __cmd_expandable_grab_m:w, __cmd_expandable_grab_m_long:w, *and* __cmd_expandable_grab_m_aux:wNn.)

__cmd_expandable_grab_R:w
__cmd_expandable_grab_R_aux:NNNwNNn

Much the same as for the D-type argument, with only the lead-off function varying.

```
\cs_new:Npn \__cmd_expandable_grab_R:w #1 \q__cmd #2#3
  { #2 { \__cmd_expandable_grab_R_aux:NNNwNNn #1 \q__cmd #2#3 } }
\cs_set_protected:Npn \__cmd_tmp:w #1
  {
    \cs_new:Npn \__cmd_expandable_grab_R_aux:NNNwNNn ##1##2##3##4 \q__cmd ##5##6##7
      {
        \str_if_eq:nnTF {##7} {##2}
          {
            \str_if_eq:onTF
              { ##1 { } { } ##7 ##2 \q__cmd ##3 }
              { { } {##2} { } }
          }
          { \use_ii:nn }
          {
            ##1
              { \__cmd_expandable_grab_D:NNNwNNnnn ##1##2##3##4 \q__cmd ##5##6 }
              \q_nil { } ##2 \ERROR \q__cmd \ERROR
          }
          {
            \msg_expandable_error:nnff { cmd } { missing-required }
              { \exp_args:Nf \tl_trim_spaces:n { \token_to_str:N ##5 } }
              { \tl_to_str:n {##2} }
            ##4 {#1} \q__cmd ##5 ##6 {##7}
          }
      }
  }
\exp_args:No \__cmd_tmp:w { \c_novalue_tl }
```

(*End definition for* `\__cmd_expandable_grab_R:w` *and* `\__cmd_expandable_grab_R_aux:NNNwNNn`.)

__cmd_expandable_grab_R_alt:w
__cmd_expandable_grab_R_alt_aux:NNwNNn

When the delimiters are identical, nesting is not possible and a simplified approach is used. The test concept here is the same as for the case where the delimiters are different.

```
\cs_new:Npn \__cmd_expandable_grab_R_alt:w #1 \q__cmd #2#3
  { #2 { \__cmd_expandable_grab_R_alt_aux:NNwNNn #1 \q__cmd #2#3 } }
\cs_set_protected:Npn \__cmd_tmp:w #1
  {
    \cs_new:Npn \__cmd_expandable_grab_R_alt_aux:NNwNNn ##1##2##3 \q__cmd ##4##5##6
      {
        \str_if_eq:nnTF {##6} {##2}
          {
            \str_if_eq:onTF
              { ##1 { } ##6 ##2 ##2 }
              { { } ##2 }
          }
          { \use_ii:nn }
          {
            ##1
              { \__cmd_expandable_grab_D_alt:NNwn ##4 ##5 ##3 \q__cmd }
              ##6 \ERROR
          }
          {
            \msg_expandable_error:nnff { cmd } { missing-required }
              { \exp_args:Nf \tl_trim_spaces:n { \token_to_str:N ##4 } }
```

```
              { \tl_to_str:n {##2} }
            ##3 {#1} \q__cmd ##4 ##5 {##6}
          }
      }
  }
\exp_args:No \__cmd_tmp:w { \c_novalue_tl }
```

(*End definition for* `\__cmd_expandable_grab_R_alt:w` *and* `\__cmd_expandable_grab_R_alt_aux:NNwNNn`.)

`\__cmd_expandable_grab_t:w`
`\__cmd_expandable_grab_t_aux:NNwn`

As for a D-type argument, here we compare the grabbed tokens using the only parser we have in order to work out if #2 is exactly equal to the output of the grabber.

```
\cs_new:Npn \__cmd_expandable_grab_t:w #1 \q__cmd #2#3
  { #2 { \__cmd_expandable_grab_t_aux:NNwn #1 \q__cmd #2 #3 } }
\cs_new:Npn \__cmd_expandable_grab_t_aux:NNwn #1#2#3 \q__cmd #4#5#6
  {
    \str_if_eq:onTF { #1 { } #6 #2 } {#2}
      { #3 { \BooleanTrue } \q__cmd #4 #5 }
      { #3 { \BooleanFalse } \q__cmd #4 #5 {#6} }
  }
```

(*End definition for* `\__cmd_expandable_grab_t:w` *and* `\__cmd_expandable_grab_t_aux:NNwn`.)

`\__cmd_put_arg_expandable:nw`
`\__cmd_put_arg_expandable:ow`

A useful helper, to store arguments when they are ready.

```
\cs_new:Npn \__cmd_put_arg_expandable:nw #1#2 \q__cmd { #2 {#1} \q__cmd }
\cs_generate_variant:Nn \__cmd_put_arg_expandable:nw { o }
```

(*End definition for* `\__cmd_put_arg_expandable:nw`.)

1.10 Argument processors

`\__cmd_bool_reverse:N`

A simple reversal.

```
\cs_new_protected:Npn \__cmd_bool_reverse:N #1
  {
    \bool_if:NTF #1
      { \tl_set:Nn \ProcessedArgument { \c_false_bool } }
      { \tl_set:Nn \ProcessedArgument { \c_true_bool } }
  }
```

(*End definition for* `\__cmd_bool_reverse:N`.)

\l__cmd_split_list_seq
\l__cmd_split_list_tl
__cmd_split_list:nn
__cmd_split_list_multi:nn
__cmd_split_list_multi:nV
__cmd_split_list_single:Nn

Splitting can take place either at a single token or at a longer identifier. To deal with single active tokens, a two-part procedure is needed.

```
\seq_new:N \l__cmd_split_list_seq
\tl_new:N \l__cmd_split_list_tl
\cs_new_protected:Npn \__cmd_split_list:nn #1#2
  {
    \tl_if_single:nTF {#1}
      {
        \token_if_cs:NTF #1
          { \__cmd_split_list_multi:nn {#1} {#2} }
          { \__cmd_split_list_single:Nn #1 {#2} }
      }
      { \__cmd_split_list_multi:nn {#1} {#2} }
  }
\cs_new_protected:Npn \__cmd_split_list_multi:nn #1#2
  {
    \seq_set_split:Nnn \l__cmd_split_list_seq {#1} {#2}
    \tl_clear:N \ProcessedArgument
    \seq_map_inline:Nn \l__cmd_split_list_seq
      { \tl_put_right:Nn \ProcessedArgument { {##1} } }
  }
\cs_generate_variant:Nn \__cmd_split_list_multi:nn { nV }
\group_begin:
\char_set_catcode_active:N \^^@
\cs_new_protected:Npn \__cmd_split_list_single:Nn #1#2
  {
    \tl_set:Nn \l__cmd_split_list_tl {#2}
    \group_begin:
    \char_set_lccode:nn { `\^^@ } { `#1 }
    \tex_lowercase:D
      {
        \group_end:
        \tl_replace_all:Nnn \l__cmd_split_list_tl { ^^@ }
      }   {#1}
     \__cmd_split_list_multi:nV {#1} \l__cmd_split_list_tl
   }
\group_end:
```

(*End definition for* `\__cmd_split_list:nn`*,* `\__cmd_split_list_multi:nn`*, and* `\__cmd_split_list_single:Nn`*.*)

__cmd_split_argument:nnn
__cmd_split_argument_aux:nnnn
__cmd_split_argument_aux:n
__cmd_split_argument_aux:wn

Splitting to a known number of items is a special version of splitting a list, in which the limit is hard-coded and where there will always be exactly the correct number of output items. An auxiliary function is used to save on working out the token list length several times.

```
\cs_new_protected:Npn \__cmd_split_argument:nnn #1#2#3
  {
    \__cmd_split_list:nn {#2} {#3}
    \exp_args:Nf \__cmd_split_argument_aux:nnnn
      { \tl_count:N \ProcessedArgument }
      {#1} {#2} {#3}
  }
```

```
\cs_new_protected:Npn \__cmd_split_argument_aux:nnnn #1#2#3#4
  {
    \int_compare:nNnF {#1} = { #2 + 1 }
      {
        \int_compare:nNnTF {#1} > { #2 + 1 }
          {
            \tl_set:Nx \ProcessedArgument
              {
                \exp_last_unbraced:NnNo
                  \__cmd_split_argument_aux:n
                  { #2 + 1 }
                  \use_none_delimit_by_q_stop:w
                  \ProcessedArgument
                  \q_stop
              }
            \msg_error:nnxxx { cmd } { arg-split }
              { \tl_to_str:n {#3} } { \int_eval:n { #2 + 1 } }
              { \tl_to_str:n {#4} }
          }
          {
            \tl_put_right:Nx \ProcessedArgument
              {
                \prg_replicate:nn { #2 + 1 - (#1) }
                  { { \exp_not:V \c_novalue_tl } }
              }
          }
      }
  }
```

Auxiliaries to leave exactly the correct number of arguments in `\ProcessedArgument`.

```
\cs_new:Npn \__cmd_split_argument_aux:n #1
  { \prg_replicate:nn {#1} { \__cmd_split_argument_aux:wn } }
\cs_new:Npn \__cmd_split_argument_aux:wn #1 \use_none_delimit_by_q_stop:w #2
  {
    \exp_not:n { {#2} }
    #1
    \use_none_delimit_by_q_stop:w
  }
```

(*End definition for* `\__cmd_split_argument:nnn` *and others.*)

`\__cmd_trim_spaces:n` This one is almost trivial.

```
\cs_new_protected:Npn \__cmd_trim_spaces:n #1
  { \tl_set:Nx \ProcessedArgument { \tl_trim_spaces:n {#1} } }
```

(*End definition for* `\__cmd_trim_spaces:n`.)

1.11 Access to the argument specification

`\__cmd_get_arg_spec_error:N`
`\__cmd_get_arg_spec_error:n`
`\__cmd_get_arg_spec_error_aux:n`

Provide an informative error when trying to get the argument specification of a non-xparse command or environment.

```
\cs_new_protected:Npn \__cmd_get_arg_spec_error:N #1
  {
    \bool_set_false:N \l__cmd_environment_bool
```

```
    \tl_set:Nn \l__cmd_fn_tl {#1}
    \__cmd_get_arg_spec_error_aux:n { \cs_if_exist:NTF #1 }
  }
\cs_new_protected:Npn \__cmd_get_arg_spec_error:n #1
  {
    \bool_set_true:N \l__cmd_environment_bool
    \str_set:Nx \l__cmd_environment_str {#1}
    \__cmd_get_arg_spec_error_aux:n
      { \cs_if_exist:cTF { \l__cmd_environment_str } }
  }
\cs_new_protected:Npn \__cmd_get_arg_spec_error_aux:n #1
  {
    #1
      {
        \msg_error:nnx { cmd } { non-xparse }
          { \__cmd_environment_or_command: }
      }
      {
        \msg_error:nnx { cmd } { unknown }
          { \__cmd_environment_or_command: }
      }
  }
```

(*End definition for* `\__cmd_get_arg_spec_error:N`, `\__cmd_get_arg_spec_error:n`, *and* `\__cmd_get_arg_spec_error_aux:n`.)

`\__cmd_get_arg_spec:NTF` If the command is not an xparse command, complain. If it is, its second "item" is the argument specification.

```
\cs_new_protected:Npn \__cmd_get_arg_spec:NTF #1#2#3
  {
    \__kernel_cmd_if_xparse:NTF #1
      {
        \tl_set:Nx \ArgumentSpecification { \tl_item:Nn #1 { 2 } }
        #2
      }
      {#3}
  }
```

(*End definition for* `\__cmd_get_arg_spec:NTF`.)

Rolling forward from 2020-10-01 is tricky because the entire `ltcmd` module is new, but the user-level commands have the same name, so only these will clash. To work around that, in `latexrelease` mode we will (temporarily) disable `\__kernel_chk_if_free_cs:N` for this final part of the code, then restore at the end.

```
⟨latexrelease⟩\cs_new_eq:NN \__cmd_chk_if_free_cs:N \__kernel_chk_if_free_cs:N
⟨latexrelease⟩\cs_gset_eq:NN \__kernel_chk_if_free_cs:N \use_none:n
```

`\ArgumentSpecification`

```
\tl_new:N \ArgumentSpecification
```

`\__cmd_get_arg_spec:N` `\__cmd_get_arg_spec:n` Recovering the argument specification is now trivial.

```
\cs_new_protected:Npn \__cmd_get_arg_spec:N #1
  {
    \__cmd_get_arg_spec:NTF #1 { }
```

```
      { \__cmd_get_arg_spec_error:N #1 }
  }
\cs_new_protected:Npn \__cmd_get_arg_spec:n #1
  {
    \exp_args:Nc \__cmd_get_arg_spec:NTF
      { environment~ \tl_to_str:n {#1} }
      { }
      { \__cmd_get_arg_spec_error:n {#1} }
  }
```

(*End definition for* `\__cmd_get_arg_spec:N` *and* `\__cmd_get_arg_spec:n`.)

`\__cmd_show_arg_spec:N`
`\__cmd_show_arg_spec:n`

Showing the argument specification simply means finding it and then calling the `\tl_show:N` function.

```
\cs_new_protected:Npn \__cmd_show_arg_spec:N #1
  {
    \__cmd_get_arg_spec:NTF #1
      { \tl_show:N \ArgumentSpecification }
      { \__cmd_get_arg_spec_error:N #1 }
  }
\cs_new_protected:Npn \__cmd_show_arg_spec:n #1
  {
    \exp_args:Nc \__cmd_get_arg_spec:NTF
      { environment~ \tl_to_str:n {#1} }
      { \tl_show:N \ArgumentSpecification }
      { \__cmd_get_arg_spec_error:n {#1} }
  }
```

(*End definition for* `\__cmd_show_arg_spec:N` *and* `\__cmd_show_arg_spec:n`.)

1.12 Utilities

`\__cmd_check_definable:nNT`
`\__cmd_check_definable_aux:nN`

Check that a token list is appropriate as a first argument of `\NewDocumentCommand` and similar functions and otherwise produce an error. First trim whitespace to allow for spaces around the actual command to be defined. If the result has multiple tokens, it is not a valid argument. The single token is a control sequence exactly if its string representation has more than one character (using `\token_to_str:N` rather than `\tl_to_str:n` to avoid problems with macro parameter characters, and setting `\tex_escapechar:D` to prevent it from being non-printable). Finally, check for an active character: this is done by lowercasing the token to fix its character code (arbitrarily to that of `?`) and comparing the result to an active `?`. Both control sequences and active characters are valid arguments, and non-active character tokens are not. In all cases, the group opened to keep assignments local must be closed.

```
\cs_new_protected:Npn \__cmd_check_definable:nNT #1
  { \tl_trim_spaces_apply:nN {#1} \__cmd_check_definable_aux:nN }
\group_begin:
  \char_set_catcode_active:n { `? }
  \cs_new_protected:Npn \__cmd_check_definable_aux:nN #1#2
    {
      \group_begin:
      \tl_if_single_token:nTF {#1}
        {
          \int_set:Nn \tex_escapechar:D { 92 }
```

```
          \exp_args:Nx \tl_if_empty:nTF
            { \exp_args:No \str_tail:n { \token_to_str:N #1 } }
            {
              \exp_args:Nx \char_set_lccode:nn
                { ‘ \str_head:n {#1} } { ‘? }
              \tex_lowercase:D { \tl_if_eq:nnTF {#1} } { ? }
                { \group_end: \use_iii:nnn }
                { \group_end: \use_i:nnn }
            }
            { \group_end: \use_iii:nnn }
        }
        { \group_end: \use_ii:nnn }
      {
        \msg_error:nnxx { cmd } { not-definable }
          { \tl_to_str:n {#1} } { \token_to_str:N #2 }
      }
      {
        \msg_error:nnxx { cmd } { not-one-token }
          { \tl_to_str:n {#1} } { \token_to_str:N #2 }
      }
    }
\group_end:
```

(*End definition for* `\__cmd_check_definable:nNT` *and* `\__cmd_check_definable_aux:nN`.)

`\__cmd_token_if_cs:NTF` Based on the definition of `\__cmd_check_definable_aux:nN` above, but only checks for an actual control sequence (*i.e.*, `\`⟨*anything*⟩). `\tex_escapechar:D` is temporarily changed to a known value and then it checks if `\string#1` contains more than one character: if it does, it's a control sequence. This test differs from `\token_if_cs:NTF` for example in `\token_if_cs:NTF \c_group_begin_token {T}{F}`, where `\token_if_cs:NTF` returns false.

```
\cs_new_protected:Npn \__cmd_token_if_cs:NTF #1
  {
    \group_begin:
      \int_set:Nn \tex_escapechar:D { 92 }
      \exp_args:Nx \tl_if_empty:nTF
          { \exp_args:No \str_tail:n { \token_to_str:N #1 } }
        { \group_end: \use_ii:nn }
        { \group_end: \use_i:nn }
  }
```

(*End definition for* `\__cmd_token_if_cs:NTF`.)

`\__cmd_tl_mapthread_function:NNN` `\__cmd_tl_mapthread_function:nnN` `\__cmd_tl_mapthread_loop:w` Analogue of `\seq_mapthread_function:NNN` for token lists.

```
\cs_new:Npn \__cmd_tl_mapthread_function:NNN #1#2#3
  {
    \exp_after:wN \exp_after:wN
    \exp_after:wN \__cmd_tl_mapthread_loop:w
    \exp_after:wN \exp_after:wN
    \exp_after:wN #3
    \exp_after:wN #1
    \exp_after:wN \q_recursion_tail
    \exp_after:wN \q_mark
    #2
```

```
    \q_recursion_tail
    \q_recursion_stop
  }
\cs_new:Npn \__cmd_tl_mapthread_function:nnN #1#2#3
  {
    \__cmd_tl_mapthread_loop:w #3
      #1 \q_recursion_tail \q_mark
      #2 \q_recursion_tail \q_recursion_stop
  }
\cs_new:Npn \__cmd_tl_mapthread_loop:w #1#2#3 \q_mark #4
  {
    \quark_if_recursion_tail_stop:n {#2}
    \quark_if_recursion_tail_stop:n {#4}
    #1 {#2} {#4}
    \__cmd_tl_mapthread_loop:w #1#3 \q_mark
  }
```

(*End definition for* `\__cmd_tl_mapthread_function:NNN`*,* `\__cmd_tl_mapthread_function:nnN`*, and* `\__cmd_tl_mapthread_loop:w`*.*)

`\__kernel_cmd_if_xparse:NTF`
`\__cmd_cmd_type_cases:Nnnnn`
`\__cmd_cmd_if_xparse_aux:N`

To determine whether the command is an xparse command check that its `arg_spec` is empty (this also excludes non-macros) and that its `replacement_spec` starts with either `\__cmd_start:nNNnnn` (non-expandable command) or `\__cmd_start_expandable:nNNNNn` (expandable command) or `\__cmd_start_env:nnnnn` (environment) or `\environment #1 end aux` (environment end).

This conditional is needed in several kernel modules and is therefore has a kernel-internal name.

```
\cs_new_protected:Npn \__cmd_cmd_type_cases:NnnnnF #1 #2 #3 #4 #5 #6
  {
    \exp_args:Ne \str_case_e:nnF
      {
        \exp_args:Nf \tl_if_empty:nT { \cs_argument_spec:N #1 }
          { \exp_not:N \exp_not:n { \exp_not:e { \tl_head:N #1 } } }
      }
      {
        { \exp_not:N \__cmd_start:nNNnnn } {#2}
        { \exp_not:N \__cmd_start_expandable:nNNNNn } {#3}
        { \exp_not:N \__cmd_start_env:nnnnn } {#4}
        {
          \exp_after:wN \exp_not:N
            \cs:w environment~
              \exp_last_unbraced:Ne \use_none:nnn
                { \cs_to_str:N #1 } ~end~aux \cs_end:
        } {#5}
      }
      {#6}
  }
\cs_new_protected:Npn \__kernel_cmd_if_xparse:NTF #1
  {
    \__cmd_cmd_type_cases:NnnnnF #1
      { } { } { } { } { \use_iii:nnn }
    \use_i:nn
  }
```

(*End definition for* `\__kernel_cmd_if_xparse:NTF`, `\__cmd_cmd_type_cases:Nnnnn`, *and* `\__cmd_cmd_if_xparse_aux:N`.)

`\__cmd_peek_nonspace:NTF`
`\__cmd_peek_nonspace_remove:NTF`
`\__cmd_peek_nonspace_aux:nNNTF`

Collect spaces in a loop, and put the collected spaces back in the false branch of a call to `\peek_meaning:NTF` or `\peek_meaning_remove:NTF`.

```
\cs_new_protected:Npn \__cmd_peek_nonspace:NTF
  { \__cmd_peek_nonspace_aux:nNNTF { } \__cmd_peek_meaning:NTF }
\cs_new_protected:Npn \__cmd_peek_nonspace_remove:NTF
  { \__cmd_peek_nonspace_aux:nNNTF { } \__cmd_peek_meaning_remove:NTF }
\cs_new_protected:Npn \__cmd_peek_nonspace_aux:nNNTF #1#2#3#4#5
  {
    \peek_meaning_remove:NTF \c_space_token
      { \__cmd_peek_nonspace_aux:nNNTF { #1 ~ } #2 #3 {#4} {#5} }
      { #2 #3 { #4 } { #5 #1 } }
  }
```

(*End definition for* `\__cmd_peek_nonspace:NTF`, `\__cmd_peek_nonspace_remove:NTF`, *and* `\__cmd_peek_nonspace_aux:nNNTF`.)

`\__cmd_peek_meaning:NTF`
`\__cmd_peek_meaning_remove:NTF`
`\__cmd_peek_cs_check_equal:NNN`
`\__cmd_peek_meaning_aux:NNTF`
`\__cmd_peek_true_remove:NNw`

Peek ahead for a token with a given meaning. In case the search token is a control sequence, also check that the ⟨*csname*⟩ is the same as the control sequence peeked at. This extra verification is necessary when the command is delimited by control sequence tokens (as opposed to character tokens), and we want the exact same control sequence to match.

```
\cs_new_protected:Npn \__cmd_peek_meaning:NTF
  { \__cmd_peek_meaning_aux:NNTF \c_false_bool }
\cs_new_protected:Npn \__cmd_peek_meaning_remove:NTF
  { \__cmd_peek_meaning_aux:NNTF \c_true_bool }
\cs_new_protected:Npn \__cmd_peek_meaning_aux:NNTF #1#2#3#4
  {
    \tl_set:Nn \l__cmd_tmpa_tl {#3}
    \tl_set:Nn \l__cmd_tmpb_tl {#4}
    \peek_meaning:NTF #2
      {
        \token_if_eq_meaning:NNTF #2 \c_group_begin_token
          { \__cmd_peek_true_remove:Nw #1 }
          {
            \__cmd_token_if_cs:NTF #2
              { \__cmd_peek_cs_check_equal:NNN #1 #2 }
              { \__cmd_peek_true_remove:Nw #1 }
          }
      }
      { \l__cmd_tmpb_tl }
  }
\cs_new_protected:Npn \__cmd_peek_cs_check_equal:NNN #1#2#3
  {
    \str_if_eq:nnTF {#2} {#3}
      { \__cmd_peek_true_remove:Nw #1 }
      { \l__cmd_tmpb_tl }
    #3
  }
\cs_new_protected:Npn \__cmd_peek_true_remove:Nw #1
  {
    \bool_if:NTF #1
```

```
      {
        \tex_afterassignment:D \l__cmd_tmpa_tl
        \cs_set_eq:NN \__cmd_tmp:w
      }
      { \l__cmd_tmpa_tl }
  }
```

(*End definition for* `\__cmd_peek_meaning:NTF` *and others.*)

1.13 Messages

`\c__cmd_ignore_def_tl`

```
\tl_const:Nn \c__cmd_ignore_def_tl
  { \\ \\ LaTeX~will~ignore~this~entire~definition. }
```

`\__cmd_environment_or_command:` Two texts used in several messages.

```
\cs_new:Npn \__cmd_environment_or_command:
  {
    \bool_if:NTF \l__cmd_environment_bool
      { environment ~ ' \l__cmd_environment_str ' }
      {
        command ~ '
        \exp_args:Nf \tl_trim_spaces:n
          { \exp_after:wN \token_to_str:N \l__cmd_fn_tl }
        '
      }
  }
```

(*End definition for* `\__cmd_environment_or_command:`.)

Some messages intended as errors when defining commands/environments.

```
\msg_new:nnnn { cmd } { arg-after-body }
  { Argument~type~'b'~must~be~last~in~#1. }
  {
    The~'b'~argument~type~must~come~last~but~it~is~followed~
    by~'#2'~in~the~argument~specification.~This~is~not~allowed.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { bad-arg-spec }
  { Bad~argument~specification~'#2'~for~#1. }
  {
    The~argument~specification~provided~is~not~valid:~
    one~or~more~mandatory~parts~are~missing.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { already-defined }
  { Command~'#1'~already~defined. }
  {
    You~have~used~#2~
    with~a~command~that~already~has~a~definition. \\ \\
    The~existing~definition~of~'#1'~will~not~be~altered.
  }
\msg_new:nnnn { cmd } { undefined }
```

```
  { Command ~'#1'~undefined. }
  {
    You~have~used~#2~
    with~a~command~that~was~never~defined.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { env-already-defined }
  { Environment~'#1'~already~defined. }
  {
    You~have~used~\NewDocumentEnvironment
    with~an~environment~that~already~has~a~definition. \\ \\
    The~existing~definition~of~'#1'~will~not~be~altered.
  }
\msg_new:nnnn { cmd } { env-end-already-defined }
  { End~of~environment~'#1'~already~defined. }
  {
    You~have~used~\NewDocumentEnvironment
    with~an~environment~that~already~has~a~definition~for~'end#1'. \\ \\
    The~existing~definition~of~'#1'~will~not~be~altered.
  }
\msg_new:nnnn { cmd } { env-undefined }
  { Environment~'#1'~undefined. }
  {
    You~have~used~\RenewDocumentEnvironment
    with~an~environment~that~was~never~defined.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { expandable-ending-optional }
  { Bad~argument~specification~'#2'~for~#1. }
  {
    Expandable~commands~must~have~a~final~mandatory~argument~
    (or~no~arguments~at~all).~You~cannot~have~a~terminal~optional~
    argument~with~expandable~commands.
  }
\msg_new:nnnn { cmd } { long-short-mix }
  { Invalid~argument~prefix~'+'~in~command~'#1'. }
  {
    The~arguments~for~an~expandable~command~must~not~involve~short~
    arguments~after~long~arguments.~You~have~tried~to~mix~the~two~types~
    when~defining~'#1'.
  }
\msg_new:nnnn { cmd } { invalid-command-arg }
  { Invalid~argument~type~'#2'~in~#1. }
  {
    The~letter~'#2'~can~only~be~used~in~environment~argument~
    specifications,~but~not~for~commands.
    \\ \\
    LaTeX~will~ignore~the~entire~definition.
  }
\msg_new:nnnn { cmd } { invalid-expandable-arg }
  { Invalid~argument~type~'#2'~in~#1. }
  {
    The~letter~'#2'~specifies~an~argument~type~which~cannot~be~used~
    in~an~expandable~command.
```

```
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { invalid-after-optional-expandably }
  { Argument~'#2'~invalid~after~optional~arg~in~#1. }
  {
    The~letter~'#2'~specifies~an~argument~type~which~cannot~be~used~
    in~an~expandable~command~after~an~optional~argument.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { invalid-bang }
  { Invalid~argument~prefix~'!'~in~#1. }
  {
    The~prefix~'!'~is~only~allowed~for~trailing~optional~arguments.~
    You~tried~to~apply~it~to~'#2'.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { not-definable }
  { First~argument~of~'#2'~must~be~a~command. }
  {
    The~first~argument~of~'#2'~should~be~the~document~command~that~will~
    be~defined.~The~provided~argument~'#1'~is~a~character.~Perhaps~a~
    backslash~is~missing?
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { not-one-token }
  { First~argument~of~'#2'~must~be~a~command. }
  {
    The~first~argument~of~'#2'~should~be~the~document~command~that~will~
    be~defined.~The~provided~argument~'#1'~contains~more~than~one~
    token.~Perhaps~a~backslash~is~missing?
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { not-single-token }
  { Argument~delimiter~'#2'~invalid~in~#1. }
  {
    The~argument~specification~contains~
    \tl_if_empty:nTF{#2}{nothing}{'#2'}~
    in~a~place~
    where~a~single~token~is~required.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { forbidden-group-token }
  { Argument~delimiter~'#2'~invalid~in~#1. }
  {
    The~argument~specification~contains~the~implicit~
    #3-group~token~'#2'~which~is~not~allowed~as~an~argument~delimiter.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { processor-in-expandable }
  { Invalid~argument~prefix~'>'~in~command~'#1'. }
  {
    The~argument~specification~for~'#1'~contains~the~processor~function~'>{#2}'.~
    This~is~only~supported~for~robust~commands,~but~not~for~expandable~ones.
    \c__cmd_ignore_def_tl
```

```
  }
\msg_new:nnnn { cmd } { too-many-args }
  { Too~many~arguments~for~#1. }
  {
    The~argument~specification~'#2'~asks~for~more~than~9~arguments.~
    This~cannot~be~implemented.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { two-markers }
  { Invalid~argument~prefix~'#2'~in~#1. }
  {
    The~argument~specification~provided~for~#1~has~two~'#2'~markers~applied~
    to~the~same~argument;~one~is~redundant.
  }
\msg_new:nnnn { cmd } { unknown-argument-type } % should be unkown-arg-type but dep in xparse
  { Invalid~argument~type~'#2'~in~#1. }
  {
    The~letter~'#2'~does~not~specify~a~known~argument~type.
    \c__cmd_ignore_def_tl
  }
\msg_new:nnnn { cmd } { xparse-arg-type }
  { Invalid~argument~type~'#2'~in~#1~(requires~xparse). }
  {
    The~letter~'#2'~specifies~a~known~but~deprecated~argument~type.~
    If~you~really~need~it~you~have~to~load~the~xparse~package.
    \c__cmd_ignore_def_tl
  }
```

Errors when using commands/environments. The `if-boolean` message is always used in expandable errors. The `default-loop` and `missing-required` messages can be expandable or not expandable.

```
\msg_new:nnn { cmd } { if-boolean }
  { Invalid~argument~{#1}~to~\iow_char:N\\IfBoolean... }
\msg_new:nnnn { cmd } { default-loop }
  { Circular~dependency~in~defaults~of~#1. }
  {
    The~default~values~of~two~or~more~arguments~of~the~#1~
    depend~on~each~other~in~a~way~that~cannot~be~resolved.
  }
\msg_new:nnnn { cmd } { missing-required }
  { Required~argument~missing~for~#1. }
  {
    The~#1~expects~one~of~its~arguments~to~start~with~'#2'.~
    LaTeX~did~not~find~this~argument~and~will~insert~a~default~value~
    for~further~processing.
  }
\msg_new:nnnn { cmd } { non-xparse }
  { \str_uppercase:n #1~not~defined~using~xparse. }
  {
    You~have~asked~for~the~argument~specification~for~the~#1,~
    but~this~was~not~defined~using~xparse.
  }
\msg_new:nnnn { cmd } { arg-split }
  { Too~many~'#1'~separators~in~argument. }
```

```
  {
    LaTeX~was~asked~to~split~the~input~'#3'~
    at~each~occurrence~of~the~separator~'#1'~into~#2~parts.~
    Too~many~separators~were~found.
  }
\msg_new:nnnn { cmd } { unknown }
  { Unknown~document~#1. }
  {
    You~have~asked~for~the~argument~specification~for~the~#1,~
    but~it~is~not~defined.
  }
\msg_new:nnnn { cmd } { verbatim-nl }
  { Verbatim-like~#1~ended~by~end~of~line. }
  {
    The~verbatim~argument~of~the~#1~cannot~contain~more~than~one~line,~
    but~the~end~
    of~the~current~line~has~been~reached.~You~may~have~forgotten~the~
    closing~delimiter.
    \\ \\
    LaTeX~will~ignore~'#2'~and~you~may~get~some~additional~
    (low-level)~errors.
  }
\msg_new:nnnn { cmd } { verbatim-tokenized }
  { Verbatim-like~#1~illegal~in~argument. }
  {
    The~#1~takes~a~verbatim~argument~and~should~therefore~normally~
    not~be~used~in~arguments~of~other~commands~or~environments.~
    LaTeX~found~an~illegal~token~ \tl_if_empty:nF {#3} { (#3)~ }
    after~'#2'~and~will~drop~everything~up~to~this~point.
    \\ \\
    Expect~further~(low-level)~errors.
  }
```

Intended more for information.

```
\msg_new:nnn { cmd } { define-command }    % should be just ``define'' but dep in xparse
  {
    Defining~command~#1~
    with~sig.~'#2'~\msg_line_context:.
  }
\msg_new:nnn { cmd } { define-env }
  {
    Defining~environment~'#1'~
    with~sig.~'#2'~\msg_line_context:.
  }
\msg_new:nnn { cmd } { redefine }
  {
    Redefining~command~#1~
    with~sig.~'#2'~\msg_line_context:.
  }
\msg_new:nnn { cmd } { redefine-env }
  {
    Redefining~environment~'#1'~
    with~sig.~'#2'~\msg_line_context:.
  }
\msg_new:nnn { cmd } { optional-mandatory }
```

```
  {
    Optional~and~mandatory~argument~with~same~delimiter~'#2'.
    \\ \\
    The~mandatory~argument~specified~with~
    '\str_case:nnF{#1}{ {R/r}{r'~or~'R} }{#1}'~has~the~
    same~delimiter~'#2'~as~an~earlier~optional~argument.~
    It~will~therefore~not~be~possible~to~omit~all~the~earlier~
    optional~arguments~when~calling~this~command.
    \\ \\
    This~may~be~intentional,~but~then~it~might~be~a~mistake.
  }
\msg_new:nnn { cmd } { unsupported-let }
  {
    The~command~'#1'~was~undefined~but~not~the~associated~commands~
    '#1~code'~and/or~'#1~defaults'.~Maybe~you~tried~using~
    \iow_char:N\\let.~This~may~lead~to~an~infinite~loop.
  }
```

1.14 User functions

The user functions are more or less just the internal functions renamed.

`\BooleanFalse` `\BooleanTrue`

Design-space names for the Boolean values.

```
\cs_new_eq:NN \BooleanFalse \c_false_bool
\cs_new_eq:NN \BooleanTrue  \c_true_bool
```

(*End definition for* `\BooleanFalse` *and* `\BooleanTrue`.)

`\NewDocumentCommand` `\RenewDocumentCommand` `\ProvideDocumentCommand` `\DeclareDocumentCommand`

The user macros are pretty simple wrappers around the internal ones. There is however a check that the first argument is a single token, possibly surrounded by spaces (hence the strange `\use:nnn`), and is definable.

```
\cs_new_protected:Npn \NewDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \NewDocumentCommand
      {
        \cs_if_exist:NTF #1
          {
            \msg_error:nnxx { cmd } { already-defined }
              { \use:nnn \token_to_str:N #1 { } }
              { \token_to_str:N \NewDocumentCommand }
          }
          { \__cmd_declare_cmd:Nnn #1 {#2} {#3} }
      }
  }
\cs_new_protected:Npn \RenewDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \RenewDocumentCommand
      {
        \cs_if_exist:NTF #1
          { \__cmd_declare_cmd:Nnn #1 {#2} {#3} }
          {
            \msg_error:nnxx { cmd } { undefined }
              { \use:nnn \token_to_str:N #1 { } }
              { \token_to_str:N \RenewDocumentCommand }
```

```
          }
      }
  }
\cs_new_protected:Npn \ProvideDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \ProvideDocumentCommand
      { \cs_if_exist:NF #1 { \__cmd_declare_cmd:Nnn #1 {#2} {#3} } }
 }
\cs_new_protected:Npn \DeclareDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \DeclareDocumentCommand
      { \__cmd_declare_cmd:Nnn #1 {#2} {#3} }
  }
```

(*End definition for* `\NewDocumentCommand` *and others.*)

`\NewDocumentEnvironment`
`\RenewDocumentEnvironment`
`\ProvideDocumentEnvironment`
`\DeclareDocumentEnvironment`

Very similar for environments.

```
\cs_new_protected:Npn \NewDocumentEnvironment #1#2#3#4
  {
    \cs_if_exist:cTF {#1}
      { \msg_error:nnx { cmd } { env-already-defined } {#1} }
      {
        \cs_if_exist:cTF { end #1 }
          { \msg_error:nnx { cmd } { env-end-already-defined } {#1} }
          { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} }
      }
  }
\cs_new_protected:Npn \RenewDocumentEnvironment #1#2#3#4
  {
    \cs_if_exist:cTF {#1}
      { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} }
      { \msg_error:nnx { cmd } { env-undefined } {#1} }
  }
\cs_new_protected:Npn \ProvideDocumentEnvironment #1#2#3#4
  { \cs_if_exist:cF {#1} { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} } }
\cs_new_protected:Npn \DeclareDocumentEnvironment #1#2#3#4
  { \__cmd_declare_env:nnnn {#1} {#2} {#3} {#4} }
```

(*End definition for* `\NewDocumentEnvironment` *and others.*)

`\NewExpandableDocumentCommand`
`\RenewExpandableDocumentCommand`
`\ProvideExpandableDocumentCommand`
`\DeclareExpandableDocumentCommand`

The expandable versions are essentially the same as the basic functions. The strange `\use:nnn` is there in case `#1` is surrounded with spaces, as can happen with usual document catcodes in `\RenewExpandableDocumentCommand { \! }` ...

```
\cs_new_protected:Npn \NewExpandableDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \NewExpandableDocumentCommand
      {
        \cs_if_exist:NTF #1
          {
            \msg_error:nnxx { cmd } { already-defined }
              { \use:nnn \token_to_str:N #1 { } }
              { \token_to_str:N \NewExpandableDocumentCommand }
          }
          { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }
```

```
      }
  }
\cs_new_protected:Npn \RenewExpandableDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \RenewExpandableDocumentCommand
      {
        \cs_if_exist:NTF #1
          { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }
          {
            \msg_error:nnxx { cmd } { undefined }
              { \use:nnn \token_to_str:N #1 { } }
              { \token_to_str:N \RenewExpandableDocumentCommand }
          }
      }
  }
\cs_new_protected:Npn \ProvideExpandableDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \ProvideExpandableDocumentCommand
      {
        \cs_if_exist:NF #1
          { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }
      }
 }
\cs_new_protected:Npn \DeclareExpandableDocumentCommand #1#2#3
  {
    \__cmd_check_definable:nNT {#1} \DeclareExpandableDocumentCommand
      { \__cmd_declare_expandable_cmd:Nnn #1 {#2} {#3} }
  }
```

(*End definition for* `\NewExpandableDocumentCommand` *and others.*)

`\IfBooleanT` `\IfBooleanF` `\IfBooleanTF`

The logical ⟨*true*⟩ and ⟨*false*⟩ statements are just the normal `\c_true_bool` and `\c_false_bool` so `\bool_if:NTF` is almost enough. However, this code-level function blows up badly when passed invalid input. We want `\IfBooleanTF` to accept a single (non-space) token equal to `\c_true_bool` or `\c_false_bool`, possibly surrounded by spaces. If the input is blank or multiple items, jump to the error and pick the false branch. If the input, ignoring spaces (we do this by omitting braces in the `\tl_if_single_token:nF` test), is not a single token then jump to the error as well. It is then safe to compare the token to the two booleans, picking the appropriate branch. If neither matches, we jump to the error as well.

```
\cs_new:Npn \IfBooleanTF #1
  {
    \tl_if_single:nF {#1}
      { \prg_break:n { \use:n } }
    \tl_if_single_token:nF #1
      { \prg_break:n { \use:n } }
    \token_if_eq_meaning:NNT #1 \c_true_bool
      { \prg_break:n { \use_ii:nnn } }
    \token_if_eq_meaning:NNT #1 \c_false_bool
      { \prg_break:n { \use_iii:nnn } }
    \prg_break:n { \use:n }
    \prg_break_point:
    {
      \msg_expandable_error:nnn { cmd } { if-boolean } {#1}
```

```
      \use_ii:nn
    }
  }
\cs_new:Npn \IfBooleanT #1#2 { \IfBooleanTF {#1} {#2} { } }
\cs_new:Npn \IfBooleanF #1 { \IfBooleanTF {#1} { } }
```

(*End definition for* `\IfBooleanT`, `\IfBooleanF`, *and* `\IfBooleanTF`.)

`\IfNoValueT` `\IfNoValueF` `\IfNoValueTF`

Simple re-naming.

```
\cs_new_eq:NN \IfNoValueF  \tl_if_novalue:nF
\cs_new_eq:NN \IfNoValueT  \tl_if_novalue:nT
\cs_new_eq:NN \IfNoValueTF \tl_if_novalue:nTF
```

(*End definition for* `\IfNoValueT`, `\IfNoValueF`, *and* `\IfNoValueTF`.)

`\IfValueT` `\IfValueF` `\IfValueTF`

Inverted logic.

```
\cs_new:Npn \IfValueF { \tl_if_novalue:nT }
\cs_new:Npn \IfValueT { \tl_if_novalue:nF }
\cs_new:Npn \IfValueTF #1#2#3 { \tl_if_novalue:nTF {#1} {#3} {#2} }
```

(*End definition for* `\IfValueT`, `\IfValueF`, *and* `\IfValueTF`.)

`\IfBlankT` `\IfBlankF` `\IfBlankTF`

Another simple re-naming.

```
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                 {\IfBlankTF}{Testing~for~empty~or~blank}%
\cs_new_eq:NN \IfBlankF  \tl_if_blank:nF
\cs_new_eq:NN \IfBlankT  \tl_if_blank:nT
\cs_new_eq:NN \IfBlankTF \tl_if_blank:nTF
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                 {\IfBlankTF}{Testing~for~empty~or~blank}%
⟨latexrelease⟩\cs_undefine:N \IfBlankF
⟨latexrelease⟩\cs_undefine:N \IfBlankT
⟨latexrelease⟩\cs_undefine:N \IfBlankTF
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\IfBlankT`, `\IfBlankF`, *and* `\IfBlankTF`.)

`\ProcessedArgument`

Processed arguments are returned using this name, which is reserved here although the definition will change.

```
\tl_new:N \ProcessedArgument
```

(*End definition for* `\ProcessedArgument`.)

`\ReverseBoolean` `\SplitArgument` `\SplitList` `\TrimSpaces`

Simple copies.

```
\cs_new_eq:NN \ReverseBoolean \__cmd_bool_reverse:N
\cs_new_eq:NN \SplitArgument  \__cmd_split_argument:nnn
\cs_new_eq:NN \SplitList      \__cmd_split_list:nn
\cs_new_eq:NN \TrimSpaces     \__cmd_trim_spaces:n
```

(*End definition for* `\ReverseBoolean` *and others.*)

`\ProcessList`

To support `\SplitList`.

```
\cs_new_eq:NN \ProcessList \tl_map_function:nN
```

(*End definition for* `\ProcessList`.)

`\GetDocumentCommandArgSpec` `\GetDocumentEnvironmentArgSpec` `\ShowDocumentCommandArgSpec` `\ShowDocumentEnvironmentArgSpec`

More simple mappings, with a check that the argument is a single control sequence or active character.

```
\cs_new_protected:Npn \GetDocumentCommandArgSpec #1
  {
    \__cmd_check_definable:nNT {#1} \GetDocumentCommandArgSpec
      { \__cmd_get_arg_spec:N #1 }
  }
\cs_new_eq:NN \GetDocumentEnvironmentArgSpec \__cmd_get_arg_spec:n
\cs_new_protected:Npn \ShowDocumentCommandArgSpec #1
  {
    \__cmd_check_definable:nNT {#1} \ShowDocumentCommandArgSpec
      { \__cmd_show_arg_spec:N #1 }
  }
\cs_new_eq:NN \ShowDocumentEnvironmentArgSpec \__cmd_show_arg_spec:n
```

(*End definition for* `\GetDocumentCommandArgSpec` *and others.*)

Finally as promised, restore `\__kernel_chk_if_free_cs:N`:

```
⟨latexrelease⟩\cs_gset_eq:NN \__kernel_chk_if_free_cs:N \__cmd_chk_if_free_cs:N
⟨latexrelease⟩\cs_undefine:N \__cmd_chk_if_free_cs:N
```

```
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{ltcmd}%
⟨latexrelease⟩                  {Document~command~parser}%
⟨latexrelease⟩
⟨latexrelease⟩\EndModuleRelease
\ExplSyntaxOff
```

Now in `latexrelease` mode, redefine `\NewDocumentCommand` to not complain on commands already defined.

```
⟨latexrelease⟩\@ifundefined{ExplSyntaxOff}{}{\latexrelease@postltcmd}
⟨latexrelease⟩\catcode`\^^@=\@latexrelease@catcode@null\relax
⟨/2ekernel | latexrelease⟩
```

We need to stop DocStrip treating `@@` in a special way at this point.

```
⟨@@=⟩
```

File h
lthooks.dtx

1 Introduction

Hooks are points in the code of commands or environments where it is possible to add processing code into existing commands. This can be done by different packages that do not know about each other and to allow for hopefully safe processing it is necessary to sort different chunks of code added by different packages into a suitable processing order.

This is done by the packages adding chunks of code (via `\AddToHook`) and labeling their code with some label by default using the package name as a label.

At `\begin{document}` all code for a hook is then sorted according to some rules (given by `\DeclareHookRule`) for fast execution without processing overhead. If the hook code is modified afterwards (or the rules are changed), a new version for fast processing is generated.

Some hooks are used already in the preamble of the document. If that happens then the hook is prepared for execution (and sorted) already at that point.

2 Package writer interface

The hook management system is offered as a set of CamelCase commands for traditional LaTeX 2_ε packages (and for use in the document preamble if needed) as well as `expl3` commands for modern packages, that use the L3 programming layer of LaTeX. Behind the scenes, a single set of data structures is accessed so that packages from both worlds can coexist and access hooks in other packages.

2.1 LaTeX 2_ε interfaces

2.1.1 Declaring hooks

With a few exceptions, hooks have to be declared before they can be used. The exceptions are the generic hooks for commands and environments (executed at `\begin` and `\end`), and the hooks run when loading files (see section 3.1).

`\NewHook` `\NewHook {⟨hook⟩}`

Creates a new ⟨*hook*⟩. If this hook is declared within a package it is suggested that its name is always structured as follows: ⟨*package-name*⟩`/`⟨*hook-name*⟩. If necessary you can further subdivide the name by adding more `/` parts. If a hook name is already taken, an error is raised and the hook is not created.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

`\NewReversedHook` `\NewReversedHook {⟨hook⟩}`

Like `\NewHook` declares a new ⟨*hook*⟩. the difference is that the code chunks for this hook are in reverse order by default (those added last are executed first). Any rules for the hook are applied after the default ordering. See sections 2.3 and 2.4 for further details.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

\NewMirroredHookPair `\NewMirroredHookPair {⟨hook-1⟩} {⟨hook-2⟩}`

A shorthand for `\NewHook{⟨hook-1⟩}\NewReversedHook{⟨hook-2⟩}`.

The ⟨*hooks*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

2.1.2 Special declarations for generic hooks

The declarations here should normally not be used. They are available to provide support for special use cases mainly involving generic command hooks.

\DisableGenericHook `\DisableGenericHook {⟨hook⟩}`

After this declaration[3] the ⟨*hook*⟩ is no longer usable: Any attempt to add further code to it will result in an error and any use, e.g., via `\UseHook`, will simply do nothing.

This is intended to be used with generic command hooks (see `ltcmdhooks-doc`) as depending on the definition of the command such generic hooks may be unusable. If that is known, a package developer can disable such hooks up front.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

\ActivateGenericHook `\ActivateGenericHook {⟨hook⟩}`

This declaration activates a generic hook provided by a package/class (e.g., one used in code with `\UseHook` or `\UseOneTimeHook`) without it being explicitly declared with `\NewHook`). This command undoes the effect of `\DisableGenericHook`. If the hook is already activated, this command does nothing.

See section 2.6 for a discussion of when this declaration is appropriate.

2.1.3 Using hooks in code

\UseHook `\UseHook {⟨hook⟩}`

Execute the hook code inside a command or environment.

Before `\begin{document}` the fast execution code for a hook is not set up, so in order to use a hook there it is explicitly initialized first. As that involves assignments using a hook at those times is not 100% the same as using it after `\begin{document}`.

The ⟨*hook*⟩ *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

[3] In the 2020/06 release this command was called `\DisableHook`, but that name was misleading as it shouldn't be used to disable non-generic hooks.

\UseOneTimeHook `\UseOneTimeHook {⟨hook⟩}`

Some hooks are only used (and can be only used) in one place, for example, those in `\begin{document}` or `\end{document}`. Once we have passed that point adding to the hook through a defined `\⟨addto-cmd⟩` command (e.g., `\AddToHook` or `\AtBeginDocument`, etc.) would have no effect (as would the use of such a command inside the hook code itself). It is therefore customary to redefine `\⟨addto-cmd⟩` to simply process its argument, i.e., essentially make it behave like `\@firstofone`.

`\UseOneTimeHook` does that: it records that the hook has been consumed and any further attempt to add to it will result in executing the code to be added immediately.

The ⟨*hook*⟩ *cannot* be specified using the dot-syntax. A leading `.` is treated literally. See section 2.1.5 for details.

Using `\UseOneTimeHook` several times with the same `{⟨hook⟩}` means that it only executes the first time it is used. For example, if it is used in a command that can be called several times then the hook executes during only the *first* invocation of that command; this allows its use as an "initialization hook".

Mixing `\UseHook` and `\UseOneTimeHook` for the same `{⟨hook⟩}` should be avoided, but if this is done then neither will execute after the first `\UseOneTimeHook`.

2.1.4 Updating code for hooks

\AddToHook `\AddToHook {⟨hook⟩}[⟨label⟩]{⟨code⟩}`

Adds ⟨*code*⟩ to the ⟨*hook*⟩ labeled by ⟨*label*⟩. When the optional argument ⟨*label*⟩ is not provided, the ⟨*default label*⟩ is used (see section 2.1.5). If `\AddToHook` is used in a package/class, the ⟨*default label*⟩ is the package/class name, otherwise it is `top-level` (the `top-level` label is treated differently: see section 2.1.6).

If there already exists code under the ⟨*label*⟩ then the new ⟨*code*⟩ is appended to the existing one (even if this is a reversed hook). If you want to replace existing code under the ⟨*label*⟩, first apply `\RemoveFromHook`.

The hook doesn't have to exist for code to be added to it. However, if it is not declared, then obviously the added ⟨*code*⟩ will never be executed. This allows for hooks to work regardless of package loading order and enables packages to add to hooks from other packages without worrying whether they are actually used in the current document. See section 2.1.8.

The ⟨*hook*⟩ and ⟨*label*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

\RemoveFromHook

\RemoveFromHook {⟨*hook*⟩}[⟨*label*⟩]

Removes any code labeled by ⟨*label*⟩ from the ⟨*hook*⟩. When the optional argument ⟨*label*⟩ is not provided, the ⟨*default label*⟩ is used (see section 2.1.5).

If there is no code under the ⟨*label*⟩ in the ⟨*hook*⟩, or if the ⟨*hook*⟩ does not exist, a warning is issued when you attempt to `\RemoveFromHook`, and the command is ignored. `\RemoveFromHook` should be used only when you know exactly what labels are in a hook. Typically this will be when some code gets added to a hook by a package, then later this code is removed by that same package. If you want to prevent the execution of code from another package, use the `voids` rule instead (see section 2.1.7).

If the optional ⟨*label*⟩ argument is `*`, then all code chunks are removed. This is rather dangerous as it may well drop code from other packages (that one may not know about); it should therefore not be used in packages but only in document preambles!

The ⟨*hook*⟩ and ⟨*label*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

In contrast to the `voids` relationship between two labels in a `\DeclareHookRule` this is a destructive operation as the labeled code is removed from the hook data structure, whereas the relationship setting can be undone by providing a different relationship later.

A useful application for this declaration inside the document body is when one wants to temporarily add code to hooks and later remove it again, e.g.,

```
\AddToHook{env/quote/before}{\small}
\begin{quote}
  A quote set in a smaller typeface
\end{quote}
...
\RemoveFromHook{env/quote/before}
... now back to normal for further quotes
```

Note that you can't cancel the setting with

```
\AddToHook{env/quote/before}{}
```

because that only "adds" a further empty chunk of code to the hook. Adding `\normalsize` would work but that means the hook then contained `\small\normalsize` which means two font size changes for no good reason.

The above is only needed if one wants to typeset several quotes in a smaller typeface. If the hook is only needed once then `\AddToHookNext` is simpler, because it resets itself after one use.

\AddToHookNext `\AddToHookNext {⟨hook⟩}{⟨code⟩}`

Adds ⟨*code*⟩ to the next invocation of the ⟨*hook*⟩. The code is executed after the normal hook code has finished and it is executed only once, i.e. it is deleted after it was used.

Using this declaration is a global operation, i.e., the code is not lost even if the declaration is used inside a group and the next invocation of the hook happens after the end of that group. If the declaration is used several times before the hook is executed then all code is executed in the order in which it was declared.[4]

If this declaration is used with a one-time hook then the code is only ever used if the declaration comes before the hook's invocation. This is because, in contrast to `\AddToHook`, the code in this declaration is not executed immediately in the case when the invocation of the hook has already happened—in other words, this code will truly execute only on the next invocation of the hook (and in the case of a one-time hook there is no such "next invocation"). This gives you a choice: should my code execute always, or should it execute only at the point where the one-time hook is used (and not at all if this is impossible)? For both of these possibilities there are use cases.

It is possible to nest this declaration using the same hook (or different hooks): e.g.,

`\AddToHookNext{`⟨*hook*⟩`}{`⟨*code-1*⟩`\AddToHookNext{`⟨*hook*⟩`}{`⟨*code-2*⟩`}}`

will execute ⟨*code-1*⟩ next time the ⟨*hook*⟩ is used and at that point puts ⟨*code-2*⟩ into the ⟨*hook*⟩ so that it gets executed on following time the hook is run.

A hook doesn't have to exist for code to be added to it. This allows for hooks to work regardless of package loading order. See section 2.1.8.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

\ClearHookNext `\ClearHookNext{⟨hook⟩}`

Normally `\AddToHookNext` is only used when you know precisely where it will apply and why you want some extra code at that point. However, there are a few use cases in which such a declaration needs to be canceled, for example, when discarding a page with `\DiscardShipoutBox` (but even then not always), and in such situations `\ClearHookNext` can be used.

2.1.5 Hook names and default labels

It is best practice to use `\AddToHook` in packages or classes *without specifying a* ⟨*label*⟩ because then the package or class name is automatically used, which is helpful if rules are needed, and avoids mistyping the ⟨*label*⟩.

Using an explicit ⟨*label*⟩ is only necessary in very specific situations, e.g., if you want to add several chunks of code into a single hook and have them placed in different parts of the hook (by providing some rules).

The other case is when you develop a larger package with several sub-packages. In that case you may want to use the same ⟨*label*⟩ throughout the sub-packages in order to avoid that the labels change if you internally reorganize your code.

Except for `\UseHook`, `\UseOneTimeHook` and `\IfHookEmptyTF` (and their expl3 interfaces `\hook_use:n`, `\hook_use_once:n` and `\hook_if_empty:nTF`), all ⟨*hook*⟩ and ⟨*label*⟩ arguments are processed in the same way: first, spaces are trimmed around the argument, then it is fully expanded until only character tokens remain. If the full expansion

[4] There is no mechanism to reorder such code chunks (or delete them).

of the ⟨*hook*⟩ or ⟨*label*⟩ contains a non-expandable non-character token, a low-level TEX error is raised (namely, the ⟨*hook*⟩ is expanded using TEX's `\csname`...`\endcsname`, as such, Unicode characters are allowed in ⟨*hook*⟩ and ⟨*label*⟩ arguments). The arguments of `\UseHook`, `\UseOneTimeHook`, and `\IfHookEmptyTF` are processed much in the same way except that spaces are not trimmed around the argument, for better performance.

It is not enforced, but highly recommended that the hooks defined by a package, and the ⟨*labels*⟩ used to add code to other hooks contain the package name to easily identify the source of the code chunk and to prevent clashes. This should be the standard practice, so this hook management code provides a shortcut to refer to the current package in the name of a ⟨*hook*⟩ and in a ⟨*label*⟩. If the ⟨*hook*⟩ name or the ⟨*label*⟩ consist just of a single dot (`.`), or starts with a dot followed by a slash (`./`) then the dot denotes the ⟨*default label*⟩ (usually the current package or class name—see `\SetDefaultHookLabel`). A "`.`" or "`./`" anywhere else in a ⟨*hook*⟩ or in ⟨*label*⟩ is treated literally and is not replaced.

For example, inside the package `mypackage.sty`, the default label is `mypackage`, so the instructions:

```
\NewHook   {./hook}
\AddToHook {./hook}[.]{code}     % Same as \AddToHook{./hook}{code}
\AddToHook {./hook}[./sub]{code}
\DeclareHookRule{begindocument}{.}{before}{babel}
\AddToHook {file/foo.tex/after}{code}
```

are equivalent to:

```
\NewHook   {mypackage/hook}
\AddToHook {mypackage/hook}[mypackage]{code}
\AddToHook {mypackage/hook}[mypackage/sub]{code}
\DeclareHookRule{begindocument}{mypackage}{before}{babel}
\AddToHook {file/foo.tex/after}{code}                  % unchanged
```

The ⟨*default label*⟩ is automatically set equal to the name of the current package or class at the time the package is loaded. If the hook command is used outside of a package, or the current file wasn't loaded with `\usepackage` or `\documentclass`, then the `top-level` is used as the ⟨*default label*⟩. This may have exceptions—see `\PushDefaultHookLabel`.

This syntax is available in all ⟨*label*⟩ arguments and most ⟨*hook*⟩ arguments, both in the LaTeX 2_ε interface, and the LaTeX3 interface described in section 2.2.

Note, however, that the replacement of `.` by the ⟨*default label*⟩ takes place when the hook command is executed, so actions that are somehow executed after the package ends will have the wrong ⟨*default label*⟩ if the dot-syntax is used. For that reason, this syntax is not available in `\UseHook` (and `\hook_use:n`) because the hook is most of the time used outside of the package file in which it was defined. This syntax is also not available in the hook conditionals `\IfHookEmptyTF` (and `\hook_if_empty:nTF`), because these conditionals are used in some performance-critical parts of the hook management code, and because they are usually used to refer to other package's hooks, so the dot-syntax doesn't make much sense.

In some cases, for example in large packages, one may want to separate it in logical parts, but still use the main package name as ⟨*label*⟩, then the ⟨*default label*⟩ can be set using `\SetDefaultHookLabel` or `\PushDefaultHookLabel{..}`...`\PopDefaultHookLabel`.

\PushDefaultHookLabel
\PopDefaultHookLabel

\PushDefaultHookLabel {⟨*default label*⟩}
  ⟨*code*⟩
\PopDefaultHookLabel

\PushDefaultHookLabel sets the current ⟨*default label*⟩ to be used in ⟨*label*⟩ arguments, or when replacing a leading "." (see above). \PopDefaultHookLabel reverts the ⟨*default label*⟩ to its previous value.

Inside a package or class, the ⟨*default label*⟩ is equal to the package or class name, unless explicitly changed. Everywhere else, the ⟨*default label*⟩ is top-level (see section 2.1.6) unless explicitly changed.

The effect of \PushDefaultHookLabel holds until the next \PopDefaultHookLabel. \usepackage (and \RequirePackage and \documentclass) internally use

```
\PushDefaultHookLabel{⟨package name⟩}
  ⟨package code⟩
\PopDefaultHookLabel
```

to set the ⟨*default label*⟩ for the package or class file. Inside the ⟨*package code*⟩ the ⟨*default label*⟩ can also be changed with \SetDefaultHookLabel. \input and other file input-related commands from the LaTeX kernel do not use \PushDefaultHookLabel, so code within files loaded by these commands does *not* get a dedicated ⟨*label*⟩! (that is, the ⟨*default label*⟩ is the current active one when the file was loaded.)

Packages that provide their own package-like interfaces (TikZ's \usetikzlibrary, for example) can use \PushDefaultHookLabel and \PopDefaultHookLabel to set dedicated labels and to emulate \usepackage-like hook behavior within those contexts.

The top-level label is treated differently, and is reserved to the user document, so it is not allowed to change the ⟨*default label*⟩ to top-level.

\SetDefaultHookLabel

\SetDefaultHookLabel {⟨*default label*⟩}

Similarly to \PushDefaultHookLabel, sets the current ⟨*default label*⟩ to be used in ⟨*label*⟩ arguments, or when replacing a leading ".". The effect holds until the label is changed again or until the next \PopDefaultHookLabel. The difference between \PushDefaultHookLabel and \SetDefaultHookLabel is that the latter does not save the current ⟨*default label*⟩.

This command is useful when a large package is composed of several smaller packages, but all should have the same ⟨*label*⟩, so \SetDefaultHookLabel can be used at the beginning of each package file to set the correct label.

\SetDefaultHookLabel is not allowed in the main document, where the ⟨*default label*⟩ is top-level and there is no \PopDefaultHookLabel to end its effect. It is also not allowed to change the ⟨*default label*⟩ to top-level.

2.1.6 The top-level label

The top-level label, assigned to code added from the main document, is different from other labels. Code added to hooks (usually \AtBeginDocument) in the preamble is almost always to change something defined by a package, so it should go at the very end of the hook.

Therefore, code added in the top-level is always executed at the end of the hook, regardless of where it was declared. If the hook is reversed (see \NewReversedHook), the top-level chunk is executed at the very beginning instead.

Rules regarding `top-level` have no effect: if a user wants to have a specific set of rules for a code chunk, they should use a different label to said code chunk, and provide a rule for that label instead.

The `top-level` label is exclusive for the user, so trying to add code with that label from a package results in an error.

2.1.7 Defining relations between hook code

The default assumption is that code added to hooks by different packages are independent and the order in which they are executed is irrelevant. While this is true in many cases it is obviously false in others.

Before the hook management system was introduced packages had to take elaborate precaution to determine of some other package got loaded as well (before or after) and find some ways to alter its behavior accordingly. In addition is was often the user's responsibility to load packages in the right order so that code added to hooks got added in the right order and some cases even altering the loading order wouldn't resolve the conflicts.

With the new hook management system it is now possible to define rules (i.e., relationships) between code chunks added by different packages and explicitly describe in which order they should be processed.

`\DeclareHookRule` `\DeclareHookRule {⟨hook⟩}{⟨label1⟩}{⟨relation⟩}{⟨label2⟩}`

Defines a relation between ⟨*label1*⟩ and ⟨*label2*⟩ for a given ⟨*hook*⟩. If ⟨*hook*⟩ is `??` this defines a default relation for all hooks that use the two labels, i.e., that have chunks of code labeled with ⟨*label1*⟩ and ⟨*label2*⟩. Rules specific to a given hook take precedence over default rules that use `??` as the ⟨*hook*⟩.

Currently, the supported relations are the following:

`before` or `<` Code for ⟨*label1*⟩ comes before code for ⟨*label2*⟩.

`after` or `>` Code for ⟨*label1*⟩ comes after code for ⟨*label2*⟩.

`incompatible-warning` Only code for either ⟨*label1*⟩ or ⟨*label2*⟩ can appear for that hook (a way to say that two packages—or parts of them—are incompatible). A warning is raised if both labels appear in the same hook.

`incompatible-error` Like `incompatible-error` but instead of a warning a LaTeX error is raised, and the code for both labels are dropped from that hook until the conflict is resolved.

`voids` Code for ⟨*label1*⟩ overwrites code for ⟨*label2*⟩. More precisely, code for ⟨*label2*⟩ is dropped for that hook. This can be used, for example if one package is a superset in functionality of another one and therefore wants to undo code in some hook and replace it with its own version.

`unrelated` The order of code for ⟨*label1*⟩ and ⟨*label2*⟩ is irrelevant. This rule is there to undo an incorrect rule specified earlier.

There can only be a single relation between two labels for a given hook, i.e., a later `\DeclareHookrule` overwrites any previous declaration.

The ⟨*hook*⟩ and ⟨*label*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

\ClearHookRule `\ClearHookRule{⟨hook⟩}{⟨label1⟩}{⟨label2⟩}`

Syntactic sugar for saying that ⟨*label1*⟩ and ⟨*label2*⟩ are unrelated for the given ⟨*hook*⟩.

\DeclareDefaultHookRule `\DeclareDefaultHookRule{⟨label1⟩}{⟨relation⟩}{⟨label2⟩}`

This sets up a relation between ⟨*label1*⟩ and ⟨*label2*⟩ for all hooks unless overwritten by a specific rule for a hook. Useful for cases where one package has a specific relation to some other package, e.g., is `incompatible` or always needs a special ordering `before` or `after`. (Technically it is just a shorthand for using `\DeclareHookRule` with `??` as the hook name.)

Declaring default rules is only supported in the document preamble.[5]

The ⟨*label*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

2.1.8 Querying hooks

Simpler data types, like token lists, have three possible states; they can:

- exist and be empty;
- exist and be non-empty; and
- not exist (in which case emptiness doesn't apply);

Hooks are a bit more complicated: a hook may exist or not, and independently it may or may not be empty. This means that even a hook that doesn't exist may be non-empty and it can also be disabled.

This seemingly strange state may happen when, for example, package *A* defines hook `A/foo`, and package *B* adds some code to that hook. However, a document may load package *B* before package *A*, or may not load package *A* at all. In both cases some code is added to hook `A/foo` without that hook being defined yet, thus that hook is said to be non-empty, whereas it doesn't exist. Therefore, querying the existence of a hook doesn't imply its emptiness, neither does the other way around.

Given that code or rules can be added to a hook even if it doesn't physically exist yet, means that a querying its existence has no real use case (in contrast to other variables that can only be update if they have already been declared). For that reason only the test for emptiness has a public interface.

A hook is said to be empty when no code was added to it, either to its permanent code pool, or to its "next" token list. The hook doesn't need to be declared to have code added to its code pool. A hook is said to exist when it was declared with `\NewHook` or some variant thereof. Generic hooks such as `file` and `env` hooks are automatically declared when code is added to them.

\IfHookEmptyTF ⋆ `\IfHookEmptyTF {⟨hook⟩} {⟨true code⟩} {⟨false code⟩}`

Tests if the ⟨*hook*⟩ is empty (*i.e.*, no code was added to it using either `\AddToHook` or `\AddToHookNext`) or such code was removed again (via `\RemoveFromHook`), and branches to either ⟨*true code*⟩ or ⟨*false code*⟩ depending on the result.

The ⟨*hook*⟩ *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

[5] Trying to do so, e.g., via `\DeclareHookRule` with `??` has bad side-effects and is not supported (though not explicitly caught for performance reasons).

2.1.9 Displaying hook code

If one has to adjust the code execution in a hook using a hook rule it is helpful to get some information about the code associated with a hook, its current order and the existing rules.

`\ShowHook` `\ShowHook {⟨hook⟩}`
`\LogHook` `\LogHook {⟨hook⟩}`

Displays information about the ⟨*hook*⟩ such as

- the code chunks (and their labels) added to it,
- any rules set up to order them,
- the computed order in which the chunks are executed,
- any code executed on the next invocation only.

`\LogHook` prints the information to the `.log` file, and `\ShowHook` prints them to the terminal/command window and starts TEX's prompt (only in `\errorstopmode`) to wait for user action.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

Suppose a hook `example-hook` whose output of `\ShowHook{example-hook}` is:

```
1  -> The hook 'example-hook':
2  > Code chunks:
3  >     foo -> [code from package 'foo']
4  >     bar -> [from package 'bar']
5  >     baz -> [package 'baz' is here]
6  > Document-level (top-level) code (executed last):
7  >     -> [code from 'top-level']
8  > Extra code for next invocation:
9  >     -> [one-time code]
10 > Rules:
11 >     foo|baz with relation >
12 >     baz|bar with default relation <
13 > Execution order (after applying rules):
14 >     baz, foo, bar.
```

In the listing above, lines 3 to 5 show the three code chunks added to the hook and their respective labels in the format

⟨*label*⟩ `->` ⟨*code*⟩

Line 7 shows the code chunk added by the user in the main document (labeled `top-level`) in the format

`Document-level (top-level) code (executed` ⟨*first*|*last*⟩`):`
`->` ⟨*top-level code*⟩

This code will be either the first or last code executed by the hook (`last` if the hook is normal, `first` if it is reversed). This chunk is not affected by rules and does not take part in sorting.

Line 9 shows the code chunk for the next execution of the hook in the format

`->` ⟨*next-code*⟩

This code will be used and disappear at the next `\UseHook{example-hook}`, in contrast to the chunks mentioned earlier, which can only be removed from that hook by doing `\RemoveFromHook{`⟨*label*⟩`}[example-hook]`.

Lines 11 and 12 show the rules declared that affect this hook in the format

⟨*label-1*⟩`|`⟨*label-2*⟩ `with` ⟨*default?*⟩ `relation` ⟨*relation*⟩

which means that the ⟨*relation*⟩ applies to ⟨*label-1*⟩ and ⟨*label-2*⟩, in that order, as detailed in `\DeclareHookRule`. If the relation is `default` it means that this rule applies to ⟨*label-1*⟩ and ⟨*label-2*⟩ in *all* hooks, (unless overridden by a non-default relation).

Finally, line 14 lists the labels in the hook after sorting; that is, in the order they will be executed when the hook is used.

2.1.10 Debugging hook code

`\DebugHooksOn`
`\DebugHooksOff`

`\DebugHooksOn`

Turn the debugging of hook code on or off. This displays most changes made to the hook data structures. The output is rather coarse and not really intended for normal use.

2.2 L3 programming layer (`expl3`) interfaces

This is a quick summary of the LaTeX3 programming interfaces for use with packages written in `expl3`. In contrast to the LaTeX 2ε interfaces they always use mandatory arguments only, e.g., you always have to specify the ⟨*label*⟩ for a code chunk. We therefore suggest to use the declarations discussed in the previous section even in `expl3` packages, but the choice is yours.

`\hook_new:n`
`\hook_new_reversed:n`
`\hook_new_pair:nn`

`\hook_new:n {`⟨*hook*⟩`}`
`\hook_new_reversed:n {`⟨*hook*⟩`}`
`\hook_new_pair:nn {`⟨*hook-1*⟩`} {`⟨*hook-2*⟩`}`

Creates a new ⟨*hook*⟩ with normal or reverse ordering of code chunks. `\hook_new_pair:nn` creates a pair of such hooks with `{`⟨*hook-2*⟩`}` being a reversed hook. If a hook name is already taken, an error is raised and the hook is not created.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

`\hook_disable_generic:n`

`\hook_disable_generic:n {`⟨*hook*⟩`}`

Marks `{`⟨*hook*⟩`}` as disabled. Any further attempt to add code to it or declare it, will result in an error and any call to `\hook_use:n` will simply do nothing.

This declaration is intended for use with generic hooks that are known not to work (see `ltcmdhooks-doc`) if they receive code.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

`\hook_activate_generic:n` `\hook_activate_generic:n {⟨hook⟩}`

This is like `\hook_new:n` but it does nothing if the hook was previously declared with `\hook_new:n`. This declaration should be used only in special situations, e.g., when a command from another package needs to be altered and it is not clear whether a generic `cmd` hook (for that command) has been previously explicitly declared.

Normally `\hook_new:n` should be used instead of this.

`\hook_use:n` `\hook_use:n {⟨hook⟩}`

Executes the `{⟨hook⟩}` code followed (if set up) by the code for next invocation only, then empties that next invocation code.

The ⟨*hook*⟩ *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

`\hook_use_once:n` `\hook_use_once:n {⟨hook⟩}`

Changes the `{⟨hook⟩}` status so that from now on any addition to the hook code is executed immediately. Then execute any `{⟨hook⟩}` code already set up.

The ⟨*hook*⟩ *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

`\hook_gput_code:nnn` `\hook_gput_code:nnn {⟨hook⟩} {⟨label⟩} {⟨code⟩}`

Adds a chunk of ⟨*code*⟩ to the ⟨*hook*⟩ labeled ⟨*label*⟩. If the label already exists the ⟨*code*⟩ is appended to the already existing code.

If code is added to an external ⟨*hook*⟩ (of the kernel or another package) then the convention is to use the package name as the ⟨*label*⟩ not some internal module name or some other arbitrary string.

The ⟨*hook*⟩ and ⟨*label*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

`\hook_gput_next_code:nn` `\hook_gput_next_code:nn {⟨hook⟩} {⟨code⟩}`

Adds a chunk of ⟨*code*⟩ for use only in the next invocation of the ⟨*hook*⟩. Once used it is gone.

This is simpler than `\hook_gput_code:nnn`, the code is simply appended to the hook in the order of declaration at the very end, i.e., after all standard code for the hook got executed.

Thus if one needs to undo what the standard does one has to do that as part of ⟨*code*⟩.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

`\hook_gclear_next_code:n` `\hook_gclear_next_code:n {⟨hook⟩}`

Undo any earlier `\hook_gput_next_code:nn`.

`\hook_gremove_code:nn` `\hook_gremove_code:nn {⟨hook⟩} {⟨label⟩}`

Removes any code for ⟨*hook*⟩ labeled ⟨*label*⟩.

If there is no code under the ⟨*label*⟩ in the ⟨*hook*⟩, or if the ⟨*hook*⟩ does not exist, a warning is issued when you attempt to use `\hook_gremove_code:nn`, and the command is ignored.

If the second argument is `*`, then all code chunks are removed. This is rather dangerous as it drops code from other packages one may not know about, so think twice before using that!

The ⟨*hook*⟩ and ⟨*label*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

`\hook_gset_rule:nnnn` `\hook_gset_rule:nnnn {⟨hook⟩} {⟨label1⟩} {⟨relation⟩} {⟨label2⟩}`

Relate ⟨*label1*⟩ with ⟨*label2*⟩ when used in ⟨*hook*⟩. See `\DeclareHookRule` for the allowed ⟨*relation*⟩s. If ⟨*hook*⟩ is `??` a default rule is specified.

The ⟨*hook*⟩ and ⟨*label*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5. The dot-syntax is parsed in both ⟨*label*⟩ arguments, but it usually makes sense to be used in only one of them.

`\hook_if_empty_p:n` ⋆ `\hook_if_empty:nTF` ⋆ `\hook_if_empty:nTF {⟨hook⟩} {⟨true code⟩} {⟨false code⟩}`

Tests if the ⟨*hook*⟩ is empty (*i.e.*, no code was added to it using either `\AddToHook` or `\AddToHookNext`), and branches to either ⟨*true code*⟩ or ⟨*false code*⟩ depending on the result.

The ⟨*hook*⟩ *cannot* be specified using the dot-syntax. A leading `.` is treated literally.

`\hook_show:n` `\hook_show:n {⟨hook⟩}`
`\hook_log:n` `\hook_log:n {⟨hook⟩}`

Displays information about the ⟨*hook*⟩ such as

- the code chunks (and their labels) added to it,
- any rules set up to order them,
- the computed order in which the chunks are executed,
- any code executed on the next invocation only.

`\hook_log:n` prints the information to the `.log` file, and `\hook_show:n` prints them to the terminal/command window and starts TEX's prompt (only if `\errorstopmode`) to wait for user action.

The ⟨*hook*⟩ can be specified using the dot-syntax to denote the current package name. See section 2.1.5.

`\hook_debug_on:` `\hook_debug_on:`
`\hook_debug_off:`

Turns the debugging of hook code on or off. This displays changes to the hook data.

2.3 On the order of hook code execution

Chunks of code for a ⟨*hook*⟩ under different labels are supposed to be independent if there are no special rules set up that define a relation between the chunks. This means that you can't make assumptions about the order of execution!

Suppose you have the following declarations:

```
\NewHook{myhook}
\AddToHook{myhook}[packageA]{\typeout{A}}
\AddToHook{myhook}[packageB]{\typeout{B}}
\AddToHook{myhook}[packageC]{\typeout{C}}
```

then executing the hook with `\UseHook` will produce the typeout `A B C` in that order. In other words, the execution order is computed to be `packageA`, `packageB`, `packageC` which you can verify with `\ShowHook{myhook}`:

```
-> The hook 'myhook':
> Code chunks:
>     packageA -> \typeout {A}
>     packageB -> \typeout {B}
>     packageC -> \typeout {C}
> Document-level (top-level) code (executed last):
>     ---
> Extra code for next invocation:
>     ---
> Rules:
>     ---
> Execution order:
>     packageA, packageB, packageC.
```

The reason is that the code chunks are internally saved in a property list and the initial order of such a property list is the order in which key-value pairs got added. However, that is only true if nothing other than adding happens!

Suppose, for example, you want to replace the code chunk for `packageA`, e.g.,

```
\RemoveFromHook{myhook}[packageA]
\AddToHook{myhook}[packageA]{\typeout{A alt}}
```

then your order becomes `packageB`, `packageC`, `packageA` because the label got removed from the property list and then re-added (at its end).

While that may not be too surprising, the execution order is also sometimes altered if you add a redundant rule, e.g. if you specify

```
\DeclareHookRule{myhook}{packageA}{before}{packageB}
```

instead of the previous lines we get

```
-> The hook 'myhook':
> Code chunks:
>     packageA -> \typeout {A}
>     packageB -> \typeout {B}
>     packageC -> \typeout {C}
> Document-level (top-level) code (executed last):
>     ---
> Extra code for next invocation:
>     ---
> Rules:
>     packageB|packageA with relation >
> Execution order (after applying rules):
>     packageA, packageC, packageB.
```

As you can see the code chunks are still in the same order, but in the execution order for the labels `packageB` and `packageC` have swapped places. The reason is that, with the rule there are two orders that satisfy it, and the algorithm for sorting happened to pick a different one compared to the case without rules (where it doesn't run at all as there is nothing to resolve). Incidentally, if we had instead specified the redundant rule

```
\DeclareHookRule{myhook}{packageB}{before}{packageC}
```

the execution order would not have changed.

In summary: it is not possible to rely on the order of execution unless there are rules that partially or fully define the order (in which you can rely on them being fulfilled).

2.4 The use of "reversed" hooks

You may have wondered why you can declare a "reversed" hook with `\NewReversedHook` and what that does exactly.

In short: the execution order of a reversed hook (without any rules!) is exactly reversed to the order you would have gotten for a hook declared with `\NewHook`.

This is helpful if you have a pair of hooks where you expect to see code added that involves grouping, e.g., starting an environment in the first and closing that environment in the second hook. To give a somewhat contrived example[6], suppose there is a package adding the following:

```
\AddToHook{env/quote/before}[package-1]{\begin{itshape}}
\AddToHook{env/quote/after} [package-1]{\end{itshape}}
```

As a result, all quotes will be in italics. Now suppose further that another `package-too` makes the quotes also in blue and therefore adds:

```
\usepackage{color}
\AddToHook{env/quote/before}[package-too]{\begin{color}{blue}}
\AddToHook{env/quote/after} [package-too]{\end{color}}
```

Now if the `env/quote/after` hook would be a normal hook we would get the same execution order in both hooks, namely:

```
package-1, package-too
```

(or vice versa) and as a result, would get:

```
\begin{itshape}\begin{color}{blue} ...
\end{itshape}\end{color}
```

and an error message that `\begin{color}` ended by `\end{itshape}`. With `env/quote/after` declared as a reversed hook the execution order is reversed and so all environments are closed in the correct sequence and `\ShowHook` would give us the following output:

```
-> The hook 'env/quote/after':
> Code chunks:
>     package-1 -> \end {itshape}
>     package-too -> \end {color}
> Document-level (top-level) code (executed first):
```

[6] there are simpler ways to achieve the same effect.

```
>     ---
> Extra code for next invocation:
>     ---
> Rules:
>     ---
> Execution order (after reversal):
>     package-too, package-1.
```

The reversal of the execution order happens before applying any rules, so if you alter the order you will probably have to alter it in both hooks, not just in one, but that depends on the use case.

2.5 Difference between "normal" and "one-time" hooks

When executing a hook a developer has the choice of using either `\UseHook` or `\UseOneTimeHook` (or their expl3 equivalents `\hook_use:n` and `\hook_use_once:n`). This choice affects how `\AddToHook` is handled after the hook has been executed for the first time.

With normal hooks adding code via `\AddToHook` means that the code chunk is added to the hook data structure and then used each time `\UseHook` is called.

With one-time hooks it this is handled slightly differently: After `\UseOneTimeHook` has been called, any further attempts to add code to the hook via `\AddToHook` will simply execute the ⟨*code*⟩ immediately.

This has some consequences one needs to be aware of:

- If ⟨*code*⟩ is added to a normal hook after the hook was executed and it is never executed again for one or the other reason, then this new ⟨*code*⟩ will never be executed.
- In contrast if that happens with a one-time hook the ⟨*code*⟩ is executed immediately.

In particular this means that construct such as

```
\AddToHook{myhook}
          { ⟨code-1⟩ \AddToHook{myhook}{⟨code-2⟩} ⟨code-3⟩ }
```

works for one-time hooks[7] (all three code chunks are executed one after another), but it makes little sense with a normal hook, because with a normal hook the first time `\UseHook{myhook}` is executed it would

- execute ⟨*code-1*⟩,
- then execute `\AddToHook{myhook}{code-2}` which adds the code chunk ⟨*code-2*⟩ to the hook for use on the next invocation,
- and finally execute ⟨*code-3*⟩.

The second time `\UseHook` is called it would execute the above and in addition ⟨*code-2*⟩ as that was added as a code chunk to the hook in the meantime. So each time the hook is used another copy of ⟨*code-2*⟩ is added and so that code chunk is executed ⟨*# of invocations*⟩ − 1 times.

[7] This is sometimes used with `\AtBeginDocument` which is why it is supported.

2.6 Generic hooks provided by packages

The hook management system also implements a category of hooks that are called "Generic Hooks". Normally a hook has to be explicitly declared before it can be used in code. This ensures that different packages are not using the same hook name for unrelated purposes—something that would result in absolute chaos. However, there are a number of "standard" hooks where it is unreasonable to declare them beforehand, e.g, each and every command has (in theory) an associated `before` and `after` hook. In such cases, i.e., for command, environment or file hooks, they can be used simply by adding code to them with `\AddToHook`. For more specialized generic hooks, e.g., those provided by babel, you have to additionally enable them with `\ActivateGenericHook` as explained below.

The generic hooks provided by LaTeX are those for `cmd`, `env`, `file`, `include package`, and `class`, and all these are available out of the box: you only have to use `\AddToHook` to add code to them, but you don't have to add `\UseHook` or `\UseOneTimeHook` to your code, because this is already done for you (or, in the case of `cmd` hooks, the command's code is patched at `\begin{document}`, if necessary).

However, if you want to provide further generic hooks in your own code, the situation is slightly different. To do this you should use `\UseHook` or `\UseOneTimeHook`, but *without declaring the hook* with `\NewHook`. As mentioned earlier, a call to `\UseHook` with an undeclared hook name does nothing. So as an additional setup step, you need to explicitly activate your generic hook. Note that a generic hook produced in this way is always a normal hook.

For a truly generic hook, with a variable part in the hook name, such upfront activation would be difficult or impossible, because you typically do not know what kind of variable parts may come up in real documents.

For example, babel may want to provide hooks such as `babel/`⟨*language*⟩`/afterextras`. Language support in babel is often done through external language packages. Thus doing the activation for all languages inside the core babel code is not a viable approach. Instead it needs to be done by each language package (or by the user who wants to use a particular hook).

Because the hooks are not declared with `\NewHook` their names should be carefully chosen to ensure that they are (likely to be) unique. Best practice is to include the package or command name, as was done in the babel example above.

Generic hooks defined in this way are always normal hooks (i.e., you can't implement reversed hooks this way). This is a deliberate limitation, because it speeds up the processessing conciderably.

2.7 Private LaTeX kernel hooks

There are a few places where it is absolutely essential for LaTeX to function correctly that code is executed in a precisely defined order. Even that could have been implemented with the hook management (by adding various rules to ensure the appropriate ordering with respect to other code added by packages). However, this makes every document unnecessary slow, because there has to be sorting even though the result is predetermined. Furthermore it forces package writers to unnecessarily add such rules if they add further code to the hook (or break LaTeX).

For that reason such code is not using the hook management, but instead private kernel commands directly before or after a public hook with the following naming convention:

`\@kernel@before@⟨hook⟩` or `\@kernel@after@⟨hook⟩`. For example, in `\enddocument` you find

```
\UseHook{enddocument}%
\@kernel@after@enddocument
```

which means first the user/package-accessible `enddocument` hook is executed and then the internal kernel hook. As their name indicates these kernel commands should not be altered by third-party packages, so please refrain from that in the interest of stability and instead use the public hook next to it.[8]

2.8 Legacy LaTeX 2ε interfaces

LaTeX 2ε offered a small number of hooks together with commands to add to them. They are listed here and are retained for backwards compatibility.

With the new hook management, several additional hooks have been added to LaTeX and more will follow. See the next section for what is already available.

`\AtBeginDocument`

`\AtBeginDocument [⟨label⟩] {⟨code⟩}`

If used without the optional argument ⟨*label*⟩, it works essentially like before, i.e., it is adding ⟨*code*⟩ to the hook `begindocument` (which is executed inside `\begin{document}`). However, all code added this way is labeled with the label `top-level` (see section 2.1.6) if done outside of a package or class or with the package/class name if called inside such a file (see section 2.1.5).

This way one can add further code to the hook using `\AddToHook` or `\AtBeginDocument` using a different label and explicitly order the code chunks as necessary, e.g., run some code before or after another package's code. When using the optional argument the call is equivalent to running `\AddToHook {begindocument} [⟨label⟩] {⟨code⟩}`.

`\AtBeginDocument` is a wrapper around the `begindocument` hook (see section 3.2), which is a one-time hook. As such, after the `begindocument` hook is executed at `\begin{document}` any attempt to add ⟨*code*⟩ to this hook with `\AtBeginDocument` or with `\AddToHook` will cause that ⟨*code*⟩ to execute immediately instead. See section 2.5 for more on one-time hooks.

For important packages with known order requirement we may over time add rules to the kernel (or to those packages) so that they work regardless of the loading-order in the document.

`\AtEndDocument`

`\AtEndDocument [⟨label⟩] {⟨code⟩}`

Like `\AtBeginDocument` but for the `enddocument` hook.

The few hooks that existed previously in LaTeX 2ε used internally commands such as `\@begindocumenthook` and packages sometimes augmented them directly rather than working through `\AtBeginDocument`. For that reason there is currently support for this, that is, if the system detects that such an internal legacy hook command contains code it adds it to the new hook system under the label `legacy` so that it doesn't get lost.

However, over time the remaining cases of direct usage need updating because in one of the future release of LaTeX we will turn this legacy support off, as it does unnecessary slow down the processing.

[8] As with everything in TeX there is not enforcement of this rule, and by looking at the code it is easy to find out how the kernel adds to them. The main reason of this section is therefore to say "please don't do that, this is unconfigurable code!"

3 LaTeX 2ε commands and environments augmented by hooks

In this section we describe the standard hooks that are now offered by LaTeX, or give pointers to other documents in which they are described. This section will grow over time (and perhaps eventually move to usrguide3).

3.1 Generic hooks

As stated earlier, with the exception of generic hooks, all hooks must be declared with `\NewHook` before they can be used. All generic hooks have names of the form "⟨*type*⟩/⟨*name*⟩/⟨*position*⟩", where ⟨*type*⟩ is from the predefined list shown below, and ⟨*name*⟩ is the variable part whose meaning will depend on the ⟨*type*⟩. The last component, ⟨*position*⟩, has more complex possibilities: it can always be `before` or `after`; for `env` hooks, it can also be `begin` or `end`; and for `include` hooks it can also be `end`. Each specific hook is documented below, or in `ltcmdhooks-doc.pdf` or `ltfilehook-doc.pdf`.

The generic hooks provided by LaTeX belong to one of the six types:

env Hooks executed before and after environments – ⟨*name*⟩ is the name of the environment, and available values for ⟨*position*⟩ are `before`, `begin`, `end`, and `after`;

cmd Hooks added to and executed before and after commands – ⟨*name*⟩ is the name of the command, and available values for ⟨*position*⟩ are `before` and `after`;

file Hooks executed before and after reading a file – ⟨*name*⟩ is the name of the file (with extension), and available values for ⟨*position*⟩ are `before` and `after`;

package Hooks executed before and after loading packages – ⟨*name*⟩ is the name of the package, and available values for ⟨*position*⟩ are `before` and `after`;

class Hooks executed before and after loading classes – ⟨*name*⟩ is the name of the class, and available values for ⟨*position*⟩ are `before` and `after`;

include Hooks executed before and after `\included` files – ⟨*name*⟩ is the name of the included file (without the `.tex` extension), and available values for ⟨*position*⟩ are `before`, `end`, and `after`.

Each of the hooks above are detailed in the following sections and in linked documentation.

3.1.1 Generic hooks for all environments

Every environment ⟨*env*⟩ has now four associated hooks coming with it:

`env/`⟨*env*⟩`/before` This hook is executed as part of `\begin` as the very first action, in particular prior to starting the environment group. Its scope is therefore not restricted by the environment.

`env/`⟨*env*⟩`/begin` This hook is executed as part of `\begin` directly in front of the code specific to the environment start (e.g., the second argument of `\newenvironment`). Its scope is the environment body.

`env/`⟨*env*⟩`/end` This hook is executed as part of `\end` directly in front of the code specific to the end of the environment (e.g., the third argument of `\newenvironment`).

env/⟨*env*⟩/after This hook is executed as part of `\end` after the code specific to the environment end and after the environment group has ended. Its scope is therefore not restricted by the environment.

The hook is implemented as a reversed hook so if two packages add code to `env/⟨env⟩/before` and to `env/⟨env⟩/after` they can add surrounding environments and the order of closing them happens in the right sequence.

Generic environment hooks are never one-time hooks even with environments that are supposed to appear only once in a document.[9] In contrast to other hooks there is also no need to declare them using `\NewHook`.

The hooks are only executed if `\begin{⟨env⟩}` and `\end{⟨env⟩}` is used. If the environment code is executed via low-level calls to `\⟨env⟩` and `\end⟨env⟩` (e.g., to avoid the environment grouping) they are not available. If you want them available in code using this method, you would need to add them yourself, i.e., write something like

```
\UseHook{env/quote/before}\quote
    ...
\endquote\UseHook{env/quote/after}
```

to add the outer hooks, etc.

Largely for compatibility with existing packages, the following four commands are also available to set the environment hooks; but for new packages we recommend directly using the hook names and `\AddToHook`.

`\BeforeBeginEnvironment` `\BeforeBeginEnvironment [⟨label⟩] {⟨env⟩} {⟨code⟩}`

This declaration adds to the `env/⟨env⟩/before` hook using the ⟨*label*⟩. If ⟨*label*⟩ is not given, the ⟨*default label*⟩ is used (see section 2.1.5).

`\AtBeginEnvironment` `\AtBeginEnvironment [⟨label⟩] {⟨env⟩} {⟨code⟩}`

This is like `\BeforeBeginEnvironment` but it adds to the `env/⟨env⟩/begin` hook.

`\AtEndEnvironment` `\AtEndEnvironment [⟨label⟩] {⟨env⟩} {⟨code⟩}`

This is like `\BeforeBeginEnvironment` but it adds to the `env/⟨env⟩/end` hook.

`\AfterEndEnvironment` `\AfterEndEnvironment [⟨label⟩] {⟨env⟩} {⟨code⟩}`

This is like `\BeforeBeginEnvironment` but it adds to the `env/⟨env⟩/after` hook.

3.1.2 Generic hooks for commands

Similar to environments there are now (at least in theory) two generic hooks available for any LaTeX command. These are

cmd/⟨*name*⟩/before This hook is executed at the very start of the command execution.

cmd/⟨*name*⟩/after This hook is executed at the very end of the command body. It is implemented as a reversed hook.

In practice there are restrictions and especially the `after` hook works only with a subset of commands. Details about these restrictions are documented in `ltcmdhooks-doc.pdf` or with code in `ltcmdhooks-code.pdf`.

[9] Thus if one adds code to such hooks after the environment has been processed, it will only be executed if the environment appears again and if that doesn't happen the code will never get executed.

3.1.3 Generic hooks provided by file loading operations

There are several hooks added to LaTeX's process of loading file via its high-level interfaces such as `\input`, `\include`, `\usepackage`, `\RequirePackage`, etc. These are documented in `ltfilehook-doc.pdf` or with code in `ltfilehook-code.pdf`.

3.2 Hooks provided by `\begin{document}`

Until 2020 `\begin{document}` offered exactly one hook that one could add to using `\AtBeginDocument`. Experiences over the years have shown that this single hook in one place was not enough and as part of adding the general hook management system a number of additional hooks have been added at this point. The places for these hooks have been chosen to provide the same support as offered by external packages, such as etoolbox and others that augmented `\document` to gain better control.

Supported are now the following hooks (all of them one-time hooks):

`begindocument/before` This hook is executed at the very start of `\document`, one can think of it as a hook for code at the end of the preamble section and this is how it is used by etoolbox's `\AtEndPreamble`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

`begindocument` This hook is added to when using `\AtBeginDocument` and it is executed after the `.aux` file as be read in and most initialization are done, so they can be altered and inspected by the hook code. It is followed by a small number of further initializations that shouldn't be altered and are therefore coming later.

The hook should not be used to add material for typesetting as we are still in LaTeX's initialization phase and not in the document body. If such material needs to be added to the document body use the next hook instead.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

`begindocument/end` This hook is executed at the end of the `\document` code in other words at the beginning of the document body. The only command that follows it is `\ignorespaces`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

The generic hooks executed by `\begin` also exist, i.e., `env/document/before` and `env/document/begin`, but with this special environment it is better use the dedicated one-time hooks above.

3.3 Hooks provided by `\end{document}`

LaTeX 2_ε always provided `\AtEndDocument` to add code to the execution of `\end{document}` just in front of the code that is normally executed there. While this was a big improvement over the situation in LaTeX 2.09 it was not flexible enough for a number of use cases and so packages, such as etoolbox, atveryend and others patched `\enddocument` to add additional points where code could be hooked into.

Patching using packages is always problematical as leads to conflicts (code availability, ordering of patches, incompatible patches, etc.). For this reason a number of

additional hooks have been added to the `\enddocument` code to allow packages to add code in various places in a controlled way without the need for overwriting or patching the core code.

Supported are now the following hooks (all of them one-time hooks):

`enddocument` The hook associated with `\AtEndDocument`. It is immediately called at the beginning of `\enddocument`.

When this hook is executed there may be still unprocessed material (e.g., floats on the deferlist) and the hook may add further material to be typeset. After it, `\clearpage` is called to ensure that all such material gets typeset. If there is nothing waiting the `\clearpage` has no effect.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

`enddocument/afterlastpage` As the name indicates this hook should not receive code that generates material for further pages. It is the right place to do some final housekeeping and possibly write out some information to the `.aux` file (which is still open at this point to receive data, but since there will be no more pages you need to write to it using `\immediate\write`). It is also the correct place to set up any testing code to be run when the `.aux` file is re-read in the next step.

After this hook has been executed the `.aux` file is closed for writing and then read back in to do some tests (e.g., looking for missing references or duplicated labels, etc.).

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

`enddocument/afteraux` At this point, the `.aux` file has been reprocessed and so this is a possible place for final checks and display of information to the user. However, for the latter you might prefer the next hook, so that your information is displayed after the (possibly longish) list of files if that got requested via `\listfiles`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

`enddocument/info` This hook is meant to receive code that write final information messages to the terminal. It follows immediately after the previous hook (so both could have been combined, but then packages adding further code would always need to also supply an explicit rule to specify where it should go.

This hook already contains some code added by the kernel (under the labels `kernel/filelist` and `kernel/warnings`), namely the list of files when `\listfiles` has been used and the warnings for duplicate labels, missing references, font substitutions etc.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).

`enddocument/end` Finally, this hook is executed just in front of the final call to `\@@end`.

This is a one-time hook, so after it is executed, all further attempts to add code to it will execute such code immediately (see section 2.5).is it even possible to add code after this one?

There is also the hook `shipout/lastpage`. This hook is executed as part of the last `\shipout` in the document to allow package to add final `\special`'s to that page. Where this hook is executed in relation to those from the above list can vary from document to document. Furthermore to determine correctly which of the `\shipout`s is the last one, LaTeX needs to be run several times, so initially it might get executed on the wrong page. See section 3.4 for where to find the details.

It is in also possible to use the generic `env/document/end` hook which is executed by `\end`, i.e., just in front of the first hook above. Note however that the other generic `\end` environment hook, i.e., `env/document/after` will never get executed, because by that time LaTeX has finished the document processing.

3.4 Hooks provided by `\shipout` operations

There are several hooks and mechanisms added to LaTeX's process of generating pages. These are documented in `ltshipout-doc.pdf` or with code in `ltshipout-code.pdf`.

3.5 Hooks provided for paragraphs

The paragraph processing has been augmented to include a number of internal and public hooks. These are documented in `ltpara-doc.pdf` or with code in `ltpara-code.pdf`.

3.6 Hooks provided in NFSS commands

In languages that need to support for more than one script in parallel (and thus several sets of fonts, e.g., supporting both Latin and Japanese fonts), NFSS font commands such as `\sffamily` need to switch both the Latin family to "Sans Serif" and in addition alter a second set of fonts.

To support this, several NFSS commands have hooks to which such support can be added.

`rmfamily` After `\rmfamily` has done its initial checks and prepared a font series update, this hook is executed before `\selectfont`.

`sffamily` This is like the `rmfamily` hook, but for the `\sffamily` command.

`ttfamily` This is like the `rmfamily` hook, but for the `\ttfamily` command.

`normalfont` The `\normalfont` command resets the font encoding, family, series and shape to their document defaults. It then executes this hook and finally calls `\selectfont`.

`expand@font@defaults` The internal `\expand@font@defaults` command expands and saves the current defaults for the meta families (rm/sf/tt) and the meta series (bf/md). If the NFSS machinery has been augmented, e.g., for Chinese or Japanese fonts, then further defaults may need to be set at this point. This can be done in this hook which is executed at the end of this macro.

`bfseries/defaults, bfseries` If the `\bfdefault` was explicitly changed by the user, its new value is used to set the bf series defaults for the meta families (rm/sf/tt) when `\bfseries` is called. The `bfseries/defaults` hook allows further adjustments to be made in this case. This hook is only executed if such a change is detected. In contrast, the `bfseries` hook is always executed just before `\selectfont` is called to change to the new series.

mdseries/defaults, mdseries These two hooks are like the previous ones but they are in the `\mdseries` command.

selectfont This hook is executed inside `\selectfont`, after the current values for *encoding*, *family*, *series*, *shape*, and *size* are evaluated and the new font is selected (and if necessary loaded). After the hook has executed, NFSS will still do any updates necessary for a new *size* (such as changing the size of `\strut`) and any updates necessary to a change in *encoding*.

This hook is intended for use cases where, in parallel to a change in the main font, some other fonts need to be altered (e.g., in CJK processing where you may need to deal with several different alphabets).

3.7 Hook provided by the mark mechanism

See `ltmarks-doc.pdf` for details.

insertmark This hook allows for a special setup while `\InsertMark` inserts a mark. It is executed in group so local changes only apply to the mark being inserted.

4 The Implementation

```
⟨@@=hook⟩
⟨*2ekernel | latexrelease⟩
\ExplSyntaxOn
⟨latexrelease⟩\NewModuleRelease{2020/10/01}{lthooks}
⟨latexrelease⟩                    {The~hook~management~system}
```

4.1 Debugging

`\g__hook_debug_bool` Holds the current debugging state.

```
\bool_new:N \g__hook_debug_bool
```

(*End definition for* `\g__hook_debug_bool`.)

`\hook_debug_on:` `\hook_debug_off:` `\__hook_debug:n` `\__hook_debug_gset:` Turns debugging on and off by redefining `\__hook_debug:n`.

```
\cs_new_eq:NN \__hook_debug:n \use_none:n
\cs_new_protected:Npn \hook_debug_on:
  {
    \bool_gset_true:N \g__hook_debug_bool
    \__hook_debug_gset:
  }
\cs_new_protected:Npn \hook_debug_off:
  {
    \bool_gset_false:N \g__hook_debug_bool
    \__hook_debug_gset:
  }
\cs_new_protected:Npn \__hook_debug_gset:
  {
    \cs_gset_protected:Npx \__hook_debug:n ##1
      { \bool_if:NT \g__hook_debug_bool {##1} }
  }
```

(*End definition for* `\hook_debug_on:` *and others. These functions are documented on page* 193.)

4.2 Borrowing from internals of other kernel modules

__hook_str_compare:nn

Private copy of __str_if_eq:nn

```
\cs_new_eq:NN \__hook_str_compare:nn \__str_if_eq:nn
```

(*End definition for* __hook_str_compare:nn.)

4.3 Declarations

\l__hook_tmpa_bool

Scratch boolean used throughout the package.

```
\bool_new:N \l__hook_tmpa_bool
```

(*End definition for* \l__hook_tmpa_bool.)

\l__hook_return_tl
\l__hook_tmpa_tl
\l__hook_tmpb_tl

Scratch variables used throughout the package.

```
\tl_new:N \l__hook_return_tl
\tl_new:N \l__hook_tmpa_tl
\tl_new:N \l__hook_tmpb_tl
```

(*End definition for* \l__hook_return_tl, \l__hook_tmpa_tl, *and* \l__hook_tmpb_tl.)

\g__hook_all_seq

In a few places we need a list of all hook names ever defined so we keep track if them in this sequence.

```
\seq_new:N \g__hook_all_seq
```

(*End definition for* \g__hook_all_seq.)

\l__hook_cur_hook_tl

Stores the name of the hook currently being sorted.

```
\tl_new:N \l__hook_cur_hook_tl
```

(*End definition for* \l__hook_cur_hook_tl.)

\l__hook_work_prop

A property list holding a copy of the \g__hook_⟨*hook*⟩_code_prop of the hook being sorted to work on, so that changes don't act destructively on the hook data structure.

```
\prop_new:N \l__hook_work_prop
```

(*End definition for* \l__hook_work_prop.)

\g__hook_used_prop

All hooks that receive code (for use in debugging display).

```
\prop_new:N \g__hook_used_prop
```

(*End definition for* \g__hook_used_prop.)

\g__hook_hook_curr_name_tl
\g__hook_name_stack_seq

Default label used for hook commands, and a stack to keep track of packages within packages.

```
\tl_new:N \g__hook_hook_curr_name_tl
\seq_new:N \g__hook_name_stack_seq
```

(*End definition for* \g__hook_hook_curr_name_tl *and* \g__hook_name_stack_seq.)

__hook_tmp:w

Temporary macro for generic usage.

```
\cs_new_eq:NN \__hook_tmp:w ?
```

(*End definition for* __hook_tmp:w.)

\tl_gremove_once:Nx
\tl_show:x
\tl_log:x

Some variants of expl3 functions.

FMi: should probably be moved to expl3

```
\cs_generate_variant:Nn \tl_gremove_once:Nn { Nx }
\cs_generate_variant:Nn \tl_show:n { x }
\cs_generate_variant:Nn \tl_log:n { x }
```

(*End definition for* `\tl_gremove_once:Nx`, `\tl_show:x`, *and* `\tl_log:x`.)

`\s__hook_mark` Scan mark used for delimited arguments.

```
\scan_new:N \s__hook_mark
```

(*End definition for* `\s__hook_mark`.)

`\__hook_clean_to_scan:w` Removes tokens until the next `\s__hook_mark`.

```
\cs_new:Npn \__hook_clean_to_scan:w #1 \s__hook_mark { }
```

(*End definition for* `\__hook_clean_to_scan:w`.)

`\__hook_tl_set:Nn` `\__hook_tl_set:Nx` `\__hook_tl_set:cn` `\__hook_tl_set:cx` Private copies of a few expl3 functions. l3debug will only add debugging to the public names, not to these copies, so we don't have to use `\debug_suspend:` and `\debug_resume:` everywhere.

Functions like `\__hook_tl_set:Nn` have to be redefined, rather than copied because in expl3 they use `\__kernel_tl_(g)set:Nx`, which is also patched by l3debug.

```
\cs_new_protected:Npn \__hook_tl_set:Nn #1#2
  { \cs_set_nopar:Npx #1 { \__kernel_exp_not:w {#2} } }
\cs_new_protected:Npn \__hook_tl_set:Nx #1#2
  { \cs_set_nopar:Npx #1 {#2} }
\cs_generate_variant:Nn \__hook_tl_set:Nn { c }
\cs_generate_variant:Nn \__hook_tl_set:Nx { c }
```

(*End definition for* `\__hook_tl_set:Nn`.)

`\__hook_tl_gset:Nn` `\__hook_tl_gset:No` `\__hook_tl_gset:Nx` `\__hook_tl_gset:cn` `\__hook_tl_gset:co` `\__hook_tl_gset:cx` Same as above.

```
\cs_new_protected:Npn \__hook_tl_gset:Nn #1#2
  { \cs_gset_nopar:Npx #1 { \__kernel_exp_not:w {#2} } }
\cs_new_protected:Npn \__hook_tl_gset:No #1#2
  { \cs_gset_nopar:Npx #1 { \__kernel_exp_not:w \exp_after:wN {#2} } }
\cs_new_protected:Npn \__hook_tl_gset:Nx #1#2
  { \cs_gset_nopar:Npx #1 {#2} }
\cs_generate_variant:Nn \__hook_tl_gset:Nn { c }
\cs_generate_variant:Nn \__hook_tl_gset:No { c }
\cs_generate_variant:Nn \__hook_tl_gset:Nx { c }
```

(*End definition for* `\__hook_tl_gset:Nn`.)

`\__hook_tl_gput_right:Nn` `\__hook_tl_gput_right:No` `\__hook_tl_gput_right:cn` Same as above.

```
\cs_new_protected:Npn \__hook_tl_gput_right:Nn #1#2
  { \__hook_tl_gset:Nx #1 { \__kernel_exp_not:w \exp_after:wN { #1 #2 } } }
\cs_generate_variant:Nn \__hook_tl_gput_right:Nn { No, cn }
```

(*End definition for* `\__hook_tl_gput_right:Nn`.)

__hook_tl_gput_left:Nn
__hook_tl_gput_left:No

Same as above.

```
\cs_new_protected:Npn \__hook_tl_gput_left:Nn #1#2
  {
    \__hook_tl_gset:Nx #1
      { \__kernel_exp_not:w {#2} \__kernel_exp_not:w \exp_after:wN {#1} }
  }
\cs_generate_variant:Nn \__hook_tl_gput_left:Nn { No }
```

(*End definition for* __hook_tl_gput_left:Nn.)

__hook_tl_gset_eq:NN

Same as above.

```
\cs_new_eq:NN \__hook_tl_gset_eq:NN \tl_gset_eq:NN
```

(*End definition for* __hook_tl_gset_eq:NN.)

__hook_tl_gclear:N
__hook_tl_gclear:c

Same as above.

```
\cs_new_protected:Npn \__hook_tl_gclear:N #1
  { \__hook_tl_gset_eq:NN #1 \c_empty_tl }
\cs_generate_variant:Nn \__hook_tl_gclear:N { c }
```

(*End definition for* __hook_tl_gclear:N.)

4.4 Providing new hooks

4.4.1 The data structures of a hook

\g_@@_⟨*hook*⟩_code_prop
\@@␣⟨*hook*⟩
\@@_next␣⟨*hook*⟩

Hooks have a name (called ⟨*hook*⟩ in the description below) and for each hook we have to provide a number of data structures. These are

\g__hook_⟨*hook*⟩_code_prop A property list holding the code for the hook in separate chunks. The keys are by default the package names that add code to the hook, but it is possible for packages to define other keys.

\g__hook_⟨*hook*⟩_rule_⟨*label1*⟩|⟨*label2*⟩_tl A token list holding the relation between ⟨*label1*⟩ and ⟨*label2*⟩ in the ⟨*hook*⟩. The ⟨*labels*⟩ are lexically (reverse) sorted to ensure that two labels always point to the same token list. For global rules, the ⟨*hook*⟩ name is ??.

__hook␣⟨*hook*⟩ The code that is actually executed when the hook is called in the document is stored in this token list. It is constructed from the code chunks applying the information. This token list is named like that so that in case of an error inside the hook, the reported token list in the error is shorter, and to make it simpler to normalize hook names in __hook_make_name:n.

\g__hook_⟨*hook*⟩_reversed_tl Some hooks are "reversed". This token list stores a - for such hook so that it can be identified. The - character is used because ⟨*reversed*⟩1 is +1 for normal hooks and −1 for reversed ones.

\g__hook_⟨*hook*⟩_declared_tl This token list serves as marker for the hook being officially declared. Its existence is tested to raise an error in case another declaration is attempted.

`\__hook_toplevel␣⟨hook⟩` This token list stores the code inserted in the hook from the user's document, in the `top-level` label. This label is special, and doesn't participate in sorting. Instead, all code is appended to it and executed after (or before, if the hook is reversed) the normal hook code, but before the `next` code chunk.

`\__hook_next␣⟨hook⟩` Finally there is extra code (normally empty) that is used on the next invocation of the hook (and then deleted). This can be used to define some special behavior for a single occasion from within the document. This token list follows the same naming scheme than the main `\__hook␣⟨hook⟩` token list. It is called `\__hook_next␣⟨hook⟩` rather than `\__hook␣next_⟨hook⟩` because otherwise a hook whose name is `next_⟨hook⟩` would clash with the next code-token list of the hook called ⟨*hook*⟩.

4.4.2 On the existence of hooks

A hook may be in different states of existence. Here we give an overview of the internal commands to set up hooks and explain how the different states are distinguished. The actual implementation then follows in subsequent sections.

One problem we have to solve is that we need to be able to add code to hooks (e.g., with `\AddToHook`) even if that code has not yet been declared. For example, one package needs to write into a hook of another package, but that package may not get loaded, or is loaded only later. Another problem is that most hooks, but not the generic hooks, require a declaration.

We therefore distinguish the following states for a hook, which are managed by four different tests: structure existence (`\__hook_if_structure_exist:nTF`), creation (`\__hook_if_usable:nTF`), declaration (`\__hook_if_declared:nTF`) and disabled or not (`\__hook_if_disabled:nTF`)

not existing Nothing is known about the hook so far. This state can be detected with `\__hook_if_structure_exist:nTF` (which uses the false branch).

In this state the hook can be declared, disabled, rules can be defined or code could be added to it, but it is not possible to use the hook (with `\UseHook`).

basic data structure set up A hook is this state when its basic data structure has been set up (using `\__hook_init_structure:n`). The data structure setup happens automatically when commands such as `\AddToHook` are used and the hook is at that point in state "not existing".

In this state the four tests give the following results:

`\__hook_if_structure_exist:nTF` returns `true`.

`\__hook_if_usable:nTF` returns `false`.

`\__hook_if_declared:nTF` returns `false`.

`\__hook_if_disabled:nTF` returns `false`.

The allowed actions are the same as in the "not existing" state.

declared A hook is in this state it is not disabled and was explicitly declared (e.g., with `\NewHook`). In this case the four tests give the following results:

`\__hook_if_structure_exist:nTF` returns `true`.

__hook_if_usable:nTF returns true.

__hook_if_declared:nTF returns true.

__hook_if_disabled:nTF returns false.

usable A hook is in this state if it is not disabled, was not explicitly declared but nevertheless is allowed to be used (with \UseHook or \hook_use:n). This state is only possible for generic hooks as they do not need to be declared. Therefore such hooks move directly from state "not existing" to "usable" the moment a declaration such as \AddToHook wants to add to the hook data structure. In this state the tests give the following results:

__hook_if_structure_exist:nTF returns true.

__hook_if_usable:nTF returns true.

__hook_if_declared:nTF returns false.

__hook_if_disabled:nTF returns false.

disabled A generic hook in any state is moved to this state when \DisableGenericHook is used. This changes the tests to give the following results:

__hook_if_structure_exist:nTF *unchanged.*

__hook_if_usable:nTF returns false.

__hook_if_declared:nTF returns true.

__hook_if_disabled:nTF returns true.

The structure test is unchanged (if the hook was unknown before it is false, otherwise true). The usable test returns false so that any \UseHook will bypass the hook from now on. The declared test returns true so that any further \NewHook generates an error and the disabled test returns true so that \AddToHook can return an error.

FMi: maybe it should do this only after begin document?

4.4.3 Setting hooks up

\hook_new:n
__hook_new:n

The \hook_new:n declaration declares a new hook and expects the hook ⟨*name*⟩ as its argument, e.g., begindocument.

```
\cs_new_protected:Npn \hook_new:n #1
  { \__hook_normalize_hook_args:Nn \__hook_new:n {#1} }
```

```
\cs_new_protected:Npn \__hook_new:n #1
  {
```

We check if the hook was already *explicitly* declared with \hook_new:n, and if it already exists we complain, otherwise set the "created" flag for the hook so that it errors next time \hook_new:n is used.

```
    \__hook_if_declared:nTF {#1}
      { \msg_error:nnn { hooks } { exists } {#1} }
      {
        \tl_new:c { g__hook_#1_declared_tl }
        \__hook_make_usable:n {#1}
      }
  }
```

(*End definition for* `\hook_new:n` *and* `\__hook_new:n`*. This function is documented on page* 191.)

`\__hook_make_usable:n` This initializes all hook data structures for the hook but if used on its own doesn't mark the hook as declared (as `\hook_new:n` does, so a later `\hook_new:n` on that hook will not result in an error. This command is internally used by `\hook_gput_code:n` when adding code to a generic hook.

```
\cs_new_protected:Npn \__hook_make_usable:n #1
  {
```

Now we check if the hook's data structure can be safely created without expl3 raising errors, then we add the hook name to the list of all hooks and allocate the necessary data structures for the new hook, otherwise just do nothing.

```
    \tl_if_exist:cF { __hook~#1 }
      {
        \seq_gput_right:Nn \g__hook_all_seq {#1}
```

This is only used by the actual code of the current hook, so declare it normally:

```
        \tl_new:c { __hook~#1 }
```

Now ensure that the base data structure for the hook exists:

```
        \__hook_init_structure:n {#1}
```

The `\g__hook_`⟨*hook*⟩`_labels_clist` holds the sorted list of labels (once it got sorted). This is used only for debugging.

```
        \clist_new:c { g__hook_#1_labels_clist }
```

Some hooks should reverse the default order of code chunks. To signal this we have a token list which is empty for normal hooks and contains a `-` for reversed hooks.

```
        \tl_new:c { g__hook_#1_reversed_tl }
```

The above is all in L3 convention, but we also provide an interface to legacy LaTeX 2ε hooks of the form `\@...hook`, e.g., `\@begindocumenthook`. there have been a few of them and they have been added to using `\g@addto@macro`. If there exists such a macro matching the name of the new hook, i.e., `\@`⟨*hook-name*⟩`hook` and it is not empty then we add its contents as a code chunk under the label `legacy`.

Warning: this support will vanish in future releases!

```
        \__hook_include_legacy_code_chunk:n {#1}
      }
  }
```

(*End definition for* `\__hook_make_usable:n`*.*)

`\__hook_init_structure:n` This function declares the basic data structures for a hook without explicit declaring the hook itself. This is needed to allow adding to undeclared hooks. Here it is unnecessary to check whether all variables exist, since all three are declared at the same time (either all of them exist, or none).

It creates the hook code pool (`\g__hook_`⟨*hook*⟩`_code_prop`) and the `top-level` and `next` token lists. A hook is initialized with `\__hook_init_structure:n` the first time anything is added to it. Initializing a hook just with `\__hook_init_structure:n` will not make it usable with `\hook_use:n`.

```
\cs_new_protected:Npn \__hook_init_structure:n #1
  {
    \__hook_if_structure_exist:nF {#1}
      {
```

```
      \prop_new:c { g__hook_#1_code_prop }
      \tl_new:c { __hook_toplevel~#1 }
      \tl_new:c { __hook_next~#1 }
    }
}
```

(*End definition for* `\__hook_init_structure:n`.)

`\hook_new_reversed:n` `\__hook_new_reversed:n`

Declare a new hook. The default ordering of code chunks is reversed, signaled by setting the token list to a minus sign.

```
\cs_new_protected:Npn \hook_new_reversed:n #1
  { \__hook_normalize_hook_args:Nn \__hook_new_reversed:n {#1} }
\cs_new_protected:Npn \__hook_new_reversed:n #1
  {
    \__hook_new:n {#1}
```

If the hook already exists the above will generate an error message, so the next line should be executed (but it is — too bad).

```
    \tl_gset:cn { g__hook_#1_reversed_tl } { - }
  }
```

(*End definition for* `\hook_new_reversed:n` *and* `\__hook_new_reversed:n`. *This function is documented on page* 191.)

`\hook_new_pair:nn`

A shorthand for declaring a normal and a (matching) reversed hook in one go.

```
\cs_new_protected:Npn \hook_new_pair:nn #1#2
  { \hook_new:n {#1} \hook_new_reversed:n {#2} }
```

(*End definition for* `\hook_new_pair:nn`. *This function is documented on page* 191.)

`\__hook_include_legacy_code_chunk:n`

The LaTeX legacy concept for hooks uses with hooks the following naming scheme in the code: `\@...hook`.

If this macro is not empty we add it under the label `legacy` to the current hook and then empty it globally. This way packages or classes directly manipulating commands such as `\@begindocumenthook` still get their hook data added.

Warning: this support will vanish in future releases!

```
\cs_new_protected:Npn \__hook_include_legacy_code_chunk:n #1
  {
```

If the macro doesn't exist (which is the usual case) then nothing needs to be done.

```
    \tl_if_exist:cT { @#1hook }
```

Of course if the legacy hook exists but is empty, there is no need to add anything under `legacy` the legacy label.

```
      {
        \tl_if_empty:cF { @#1hook }
          {
            \exp_args:Nnnv \__hook_hook_gput_code_do:nnn {#1}
                                    { legacy } { @#1hook }
```

Once added to the hook, we need to clear it otherwise it might get added again later if the hook data gets updated.

```
            \__hook_tl_gclear:c { @#1hook }
          }
      }
  }
```

(*End definition for* `\__hook_include_legacy_code_chunk:n`.)

4.4.4 Disabling and providing hooks

\hook_disable_generic:n
__hook_disable:n
__hook_if_disabled_p:n
__hook_if_disabled:nTF

Disables a hook by creating its \g__hook_⟨hook⟩_declared_tl so that the hook errors when used with \hook_new:n, then it undefines __hook␣⟨hook⟩ so that it may not be executed.

This does not clear any code that may be already stored in the hook's structure, but doesn't allow adding more code. __hook_if_disabled:nTF uses that specific combination to check if the hook is disabled.

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩          {\hook_disable_generic:n}{Disable~hooks}
```

```
\cs_new_protected:Npn \hook_disable_generic:n #1
  { \__hook_normalize_hook_args:Nn \__hook_disable:n {#1} }
\cs_new_protected:Npn \__hook_disable:n #1
  {
    \tl_gclear_new:c { g__hook_#1_declared_tl }
    \cs_undefine:c { __hook~#1 }
  }
\prg_new_conditional:Npnn \__hook_if_disabled:n #1 { p, T, F, TF }
  {
    \bool_lazy_and:nnTF
        { \tl_if_exist_p:c { g__hook_#1_declared_tl } }
        { ! \tl_if_exist_p:c { __hook~#1 } }
      { \prg_return_true: }
      { \prg_return_false: }
  }
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}
⟨latexrelease⟩                  {\hook_disable_generic:n}{Disable~hooks}
⟨latexrelease⟩
⟨latexrelease⟩\cs_new_protected:Npn \hook_disable_generic:n #1 {}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* \hook_disable_generic:n, __hook_disable:n, *and* __hook_if_disabled:nTF. *This function is documented on page* 191.)

\hook_activate_generic:n
__hook_activate_generic:n

The \hook_activate_generic:n declaration declares a new hook if it wasn't declared already, in which case it only checks that the already existing hook is not a reversed hook.

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩          {\hook_activate_generic:n}{Providing~hooks}
```

```
\cs_new_protected:Npn \hook_activate_generic:n #1
  { \__hook_normalize_hook_args:Nn \__hook_activate_generic:nn {#1} {   } }
```

```
\cs_new_protected:Npn \__hook_activate_generic:nn #1 #2
  {
```

If the hook to be activated was disabled we warn (for now — this may change).

```
    \__hook_if_disabled:nTF {#1}
      { \msg_warning:nnn { hooks } { activate-disabled } {#1} }
```

Otherwise we check if the hook is not declared, and if it isn't, figure out if it's reversed or not, then declare it accordingly.

```
      {
        \__hook_if_declared:nF {#1}
```

```
          {
            \tl_new:c { g__hook_#1_declared_tl }
            \__hook_make_usable:n {#1}
            \tl_gset:cx { g__hook_#1_reversed_tl }
              { \__hook_if_generic_reversed:nT {#1} { - } }
          }
      }
  }
```

(*End definition for* `\hook_activate_generic:n` *and* `\__hook_activate_generic:n`*. This function is documented on page* 192.)

```
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}
⟨latexrelease⟩                  {\hook_activate_generic:n}{Providing~hooks}
⟨latexrelease⟩
⟨latexrelease⟩\cs_new_protected:Npn \hook_activate_generic:n #1 {}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

4.5 Parsing a label

`\__hook_parse_label_default:n`

This macro checks if a label was given (not `\c_novalue_tl`), and if so, tries to parse the label looking for a leading `.` to replace by `\__hook_currname_or_default:`.

```
\cs_new:Npn \__hook_parse_label_default:n #1
  {
    \tl_if_novalue:nTF {#1}
      { \__hook_currname_or_default: }
      { \tl_trim_spaces_apply:nN {#1} \__hook_parse_dot_label:n }
  }
```

(*End definition for* `\__hook_parse_label_default:n`.)

`\__hook_parse_dot_label:n`
`\__hook_parse_dot_label:w`
`\__hook_parse_dot_label_cleanup:w`
`\__hook_parse_dot_label_aux:w`

Start by checking if the label is empty, which raises an error, and uses the fallback value. If not, split the label at a `./`, if any, and check if no tokens are before the `./`, or if the only character is a `.`. If these requirements are fulfilled, the leading `.` is replaced with `\__hook_currname_or_default:`. Otherwise the label is returned unchanged.

```
\cs_new:Npn \__hook_parse_dot_label:n #1
  {
    \tl_if_empty:nTF {#1}
      {
        \msg_expandable_error:nn { hooks } { empty-label }
        \__hook_currname_or_default:
      }
      {
        \str_if_eq:nnTF {#1} { . }
          { \__hook_currname_or_default: }
          { \__hook_parse_dot_label:w #1 ./ \s__hook_mark }
      }
  }
\cs_new:Npn \__hook_parse_dot_label:w #1 ./ #2 \s__hook_mark
  {
    \tl_if_empty:nTF {#1}
      { \__hook_parse_dot_label_aux:w #2 \s__hook_mark }
```

```
      {
        \tl_if_empty:nTF {#2}
          { \__hook_make_name:n {#1} }
          { \__hook_parse_dot_label_cleanup:w #1 ./ #2 \s__hook_mark }
      }
  }
\cs_new:Npn \__hook_parse_dot_label_cleanup:w #1 ./ \s__hook_mark {#1}
\cs_new:Npn \__hook_parse_dot_label_aux:w #1 ./ \s__hook_mark
  { \__hook_currname_or_default: / \__hook_make_name:n {#1} }
```

(*End definition for* `\__hook_parse_dot_label:n` *and others.*)

`\__hook_currname_or_default:` This uses `\g__hook_hook_curr_name_tl` if it is set, otherwise it tries `\@currname`. If neither is set, it raises an error and uses the fallback value `label-missing`.

```
\cs_new:Npn \__hook_currname_or_default:
  {
    \tl_if_empty:NTF \g__hook_hook_curr_name_tl
      {
        \tl_if_empty:NTF \@currname
          {
            \msg_expandable_error:nnn { latex2e } { should-not-happen }
              { Empty~default~label. }
            \__hook_make_name:n { label-missing }
          }
          { \@currname }
      }
      { \g__hook_hook_curr_name_tl }
  }
```

(*End definition for* `\__hook_currname_or_default:`.)

`\__hook_make_name:n` `\__hook_make_name:w` This provides a standard sanitization of a hook's name. It uses `\cs:w` to build a control sequence out of the hook name, then uses `\cs_to_str:N` to get the string representation of that, without the escape character. `\cs:w`-based expansion is used instead of `e`-based because Unicode characters don't behave well inside `\expanded`. The macro adds the `\__hook␣` prefix to the hook name to reuse the hook's code token list to build the csname and avoid leaving "public" control sequences defined (as `\relax`) in TeX's memory.

```
\cs_new:Npn \__hook_make_name:n #1
  {
    \exp_after:wN \exp_after:wN \exp_after:wN \__hook_make_name:w
    \exp_after:wN \token_to_str:N \cs:w __hook~ #1 \cs_end:
  }
\exp_last_unbraced:NNNNo
\cs_new:Npn \__hook_make_name:w #1 \tl_to_str:n { __hook~ } { }
```

(*End definition for* `\__hook_make_name:n` *and* `\__hook_make_name:w`.)

`\__hook_normalize_hook_args:Nn` `\__hook_normalize_hook_args:Nnn` `\__hook_normalize_hook_rule_args:Nnnnn` `\__hook_normalize_hook_args_aux:Nn` This is the standard route for normalizing hook and label arguments. The main macro does the entire operation within a group so that csnames made by `\__hook_make_name:n` are wiped off before continuing. This means that this function cannot be used for `\hook_use:n`!

```
\cs_new_protected:Npn \__hook_normalize_hook_args_aux:Nn #1 #2
  {
    \group_begin:
```

```
    \use:e
      {
        \group_end:
        \exp_not:N #1 #2
      }
  }
\cs_new_protected:Npn \__hook_normalize_hook_args:Nn #1 #2
  {
    \__hook_normalize_hook_args_aux:Nn #1
      { { \__hook_parse_label_default:n {#2} } }
  }
\cs_new_protected:Npn \__hook_normalize_hook_args:Nnn #1 #2 #3
  {
    \__hook_normalize_hook_args_aux:Nn #1
      {
        { \__hook_parse_label_default:n {#2} }
        { \__hook_parse_label_default:n {#3} }
      }
  }
\cs_new_protected:Npn \__hook_normalize_hook_rule_args:Nnnnn #1 #2 #3 #4 #5
  {
    \__hook_normalize_hook_args_aux:Nn #1
      {
        { \__hook_parse_label_default:n {#2} }
        { \__hook_parse_label_default:n {#3} }
        { \tl_trim_spaces:n {#4} }
        { \__hook_parse_label_default:n {#5} }
      }
  }
```

(*End definition for* `\__hook_normalize_hook_args:Nn` *and others.*)

`\__hook_curr_name_push:n`
`\__hook_curr_name_push_aux:n`
`\__hook_curr_name_pop:`
`\__hook_end_document_label_check:`

The token list `\g__hook_hook_curr_name_tl` stores the name of the current package/file to be used as the default label in hooks. Providing a consistent interface is tricky because packages can be loaded within packages, and some packages may not use `\SetDefaultHookLabel` to change the default label (in which case `\@currname` is used).

To pull that one off, we keep a stack that contains the default label for each level of input. The bottom of the stack contains the default label for the `top-level` (this stack should never go empty). If we're building the format, set the default label to be `top-level`:

```
\tl_gset:Nn \g__hook_hook_curr_name_tl { top-level }
```

Then, in case we're in latexrelease we push something on the stack to support roll forward. But in some rare cases, latexrelease may be loaded inside another package (notably platexrelease), so we'll first push the `top-level` entry:

```
⟨latexrelease⟩\seq_if_empty:NT \g__hook_name_stack_seq
⟨latexrelease⟩  { \seq_gput_right:Nn \g__hook_name_stack_seq { top-level } }
```

then we dissect the `\@currnamestack`, adding `\@currname` to the stack:

```
⟨latexrelease⟩\cs_set_protected:Npn \__hook_tmp:w #1 #2 #3
⟨latexrelease⟩  {
⟨latexrelease⟩    \quark_if_recursion_tail_stop:n {#1}
⟨latexrelease⟩    \seq_gput_right:Nn \g__hook_name_stack_seq {#1}
⟨latexrelease⟩    \__hook_tmp:w
```

```
⟨latexrelease⟩   }
⟨latexrelease⟩\exp_after:wN \__hook_tmp:w \@currnamestack
⟨latexrelease⟩   \q_recursion_tail \q_recursion_tail
⟨latexrelease⟩   \q_recursion_tail \q_recursion_stop
```

and finally set the default label to be the `\@currname`:

```
⟨latexrelease⟩\tl_gset:Nx \g__hook_hook_curr_name_tl { \@currname }
⟨latexrelease⟩\seq_gpop_right:NN \g__hook_name_stack_seq \l__hook_tmpa_tl
```

Two commands keep track of the stack: when a file is input, `\__hook_curr_name_push:n` pushes the current default label onto the stack and sets the new default label (all in one go):

```
\cs_new_protected:Npn \__hook_curr_name_push:n #1
  { \exp_args:Nx \__hook_curr_name_push_aux:n { \__hook_make_name:n {#1} } }
\cs_new_protected:Npn \__hook_curr_name_push_aux:n #1
  {
    \tl_if_blank:nTF {#1}
      { \msg_error:nn { hooks } { no-default-label } }
      {
        \str_if_eq:nnTF {#1} { top-level }
          {
            \msg_error:nnnnn { hooks } { set-top-level }
              { to } { PushDefaultHookLabel } {#1}
          }
          {
            \seq_gpush:NV \g__hook_name_stack_seq \g__hook_hook_curr_name_tl
            \tl_gset:Nn \g__hook_hook_curr_name_tl {#1}
          }
      }
  }
```

and when an input is over, the topmost item of the stack is popped, since that label will not be used again, and `\g__hook_hook_curr_name_tl` is updated to equal the now topmost item of the stack:

```
\cs_new_protected:Npn \__hook_curr_name_pop:
  {
    \seq_gpop:NNTF \g__hook_name_stack_seq \l__hook_return_tl
      { \tl_gset_eq:NN \g__hook_hook_curr_name_tl \l__hook_return_tl }
      { \msg_error:nn { hooks } { extra-pop-label } }
  }
```

At the end of the document we want to check if there was no `\__hook_curr_name_push:n` without a matching `\__hook_curr_name_pop:` (not a critical error, but it might indicate that something else is not quite right):

```
\tl_gput_right:Nn \@kernel@after@enddocument@afterlastpage
  { \__hook_end_document_label_check: }
\cs_new_protected:Npn \__hook_end_document_label_check:
  {
    \seq_gpop:NNT \g__hook_name_stack_seq \l__hook_return_tl
      {
        \msg_error:nnx { hooks } { missing-pop-label }
          { \g__hook_hook_curr_name_tl }
        \tl_gset_eq:NN \g__hook_hook_curr_name_tl \l__hook_return_tl
        \__hook_end_document_label_check:
      }
```

```
}
```

The token list \g__hook_hook_curr_name_tl is but a mirror of the top of the stack.

Now define a wrapper that replaces the top of the stack with the argument, and updates \g__hook_hook_curr_name_tl accordingly.

__hook_set_default_hook_label:n
__hook_set_default_label:n

```
\cs_new_protected:Npn \__hook_set_default_hook_label:n #1
  {
    \seq_if_empty:NTF \g__hook_name_stack_seq
      {
        \msg_error:nnnnn { hooks } { set-top-level }
          { for } { SetDefaultHookLabel } {#1}
      }
      { \exp_args:Nx \__hook_set_default_label:n { \__hook_make_name:n {#1} } }
  }
\cs_new_protected:Npn \__hook_set_default_label:n #1
  {
    \str_if_eq:nnTF {#1} { top-level }
      {
        \msg_error:nnnnn { hooks } { set-top-level }
          { to } { SetDefaultHookLabel } {#1}
      }
      { \tl_gset:Nn \g__hook_hook_curr_name_tl {#1} }
  }
```

(*End definition for* __hook_curr_name_push:n *and others.*)

4.6 Adding or removing hook code

\hook_gput_code:nnn
__hook_gput_code:nnn
__hook_hook_gput_code_do:nnn

With \hook_gput_code:nnn{⟨*hook*⟩}{⟨*label*⟩}{⟨*code*⟩} a chunk of ⟨*code*⟩ is added to an existing ⟨*hook*⟩ labeled with ⟨*label*⟩.

```
\cs_new_protected:Npn \hook_gput_code:nnn #1 #2
  { \__hook_normalize_hook_args:Nnn \__hook_gput_code:nnn {#1} {#2} }
```

```
\cs_new_protected:Npn \__hook_gput_code:nnn #1 #2 #3
  {
```

First check if the code should be executed immediately, rather than stored:

```
    \__hook_if_execute_immediately:nTF {#1}
      {#3}
      {
```

Then check if the hook is usable.

```
        \__hook_if_usable:nTF {#1}
```

If so we simply add (or append) the new code to the property list holding different chunks for the hook. At \begin{document} this is then sorted into a token list for fast execution.

```
          {
            \__hook_hook_gput_code_do:nnn {#1} {#2} {#3}
```

However, if there is an update within the document we need to alter this execution code which is done by __hook_update_hook_code:n. In the preamble this does nothing.

```
            \__hook_update_hook_code:n {#1}
          }
```

If the hook is not usable, before giving up, check if it's not disabled and otherwise try to declare it as a generic hook, if its name matches one of the valid patterns.

```
          {
            \__hook_if_disabled:nTF {#1}
              { \msg_error:nnn { hooks } { hook-disabled } {#1} }
              { \__hook_try_declaring_generic_hook:nnn {#1} {#2} {#3} }
          }
      }
  }
```

This macro will unconditionally add a chunk of code to the given hook.

```
\cs_new_protected:Npn \__hook_hook_gput_code_do:nnn #1 #2 #3
  {
```

However, first some debugging info if debugging is enabled:

```
    \__hook_debug:n{\iow_term:x{****~ Add~ to~
                        \__hook_if_usable:nF {#1} { undeclared~ }
                        hook~ #1~ (#2)
                        \on@line\space <-~ \tl_to_str:n{#3}} }
```

Then try to get the code chunk labeled #2 from the hook. If there's code already there, then append #3 to that, otherwise just put #3. If the current label is top-level, the code is added to a dedicated token list __hook_toplevel␣⟨*hook*⟩ that goes at the end of the hook (or at the beginning, for a reversed hook), just before __hook_next␣⟨*hook*⟩.

```
    \str_if_eq:nnTF {#2} { top-level }
      {
        \str_if_eq:eeTF { top-level } { \__hook_currname_or_default: }
          {
```

If the hook's basic structure does not exist, we need to declare it with __hook_init_structure:n.

```
            \__hook_init_structure:n {#1}
            \__hook_tl_gput_right:cn { __hook_toplevel~#1 } {#3}
          }
          { \msg_error:nnn { hooks } { misused-top-level } {#1} }
      }
      {
        \prop_get:cnNTF { g__hook_#1_code_prop } {#2} \l__hook_return_tl
          {
            \prop_gput:cno { g__hook_#1_code_prop } {#2}
              { \l__hook_return_tl #3 }
          }
          { \prop_gput:cnn { g__hook_#1_code_prop } {#2} {#3} }
      }
  }
```

(*End definition for* \hook_gput_code:nnn*,* __hook_gput_code:nnn*, and* __hook_hook_gput_code_do:nnn*. This function is documented on page 192.*)

__hook_gput_undeclared_hook:nnn

Often it may happen that a package A defines a hook foo, but package B, that adds code to that hook, is loaded before A. In such case we need to add code to the hook before its declared.

```
\cs_new_protected:Npn \__hook_gput_undeclared_hook:nnn #1 #2 #3
  {
    \__hook_init_structure:n {#1}
```

```
    \__hook_hook_gput_code_do:nnn {#1} {#2} {#3}
  }
```

(*End definition for* `\__hook_gput_undeclared_hook:nnn`.)

`\__hook_try_declaring_generic_hook:nnn`
`\__hook_try_declaring_generic_next_hook:nn`

These entry-level macros just pass the arguments along to the common `\__hook_try_declaring_generic_hook:nNNnn` with the right functions to execute when some action is to be taken.

The wrapper `\__hook_try_declaring_generic_hook:nnn` then defers `\hook_gput_code:nnn` if the generic hook was declared, or to `\__hook_gput_undeclared_hook:nnn` otherwise (the hook was tested for existence before, so at this point if it isn't generic, it doesn't exist).

The wrapper `\__hook_try_declaring_generic_next_hook:nn` for next-execution hooks does the same: it defers the code to `\hook_gput_next_code:nn` if the generic hook was declared, or to `\__hook_gput_next_do:nn` otherwise.

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__hook_try_declaring_generic_hook:nnn}
⟨latexrelease⟩                  {Standardise~generic~hook~names}
\cs_new_protected:Npn \__hook_try_declaring_generic_hook:nnn #1
  {
    \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop: {#1}
      \hook_gput_code:nnn
      \__hook_gput_undeclared_hook:nnn
        {#1}
  }
\cs_new_protected:Npn \__hook_try_declaring_generic_next_hook:nn #1
  {
    \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop: {#1}
      \hook_gput_next_code:nn
      \__hook_gput_next_do:nn
        {#1}
  }
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__hook_try_declaring_generic_hook:nnn}
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\cs_new_protected:Npn \__hook_try_declaring_generic_hook:nnn #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \__hook_try_declaring_generic_hook:nNNnn {#1}
⟨latexrelease⟩      \hook_gput_code:nnn \__hook_gput_undeclared_hook:nnn
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new_protected:Npn \__hook_try_declaring_generic_next_hook:nn #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \__hook_try_declaring_generic_hook:nNNnn {#1}
⟨latexrelease⟩      \hook_gput_next_code:nn \__hook_gput_next_do:nn
⟨latexrelease⟩  }
```

(*End definition for* `\__hook_try_declaring_generic_hook:nnn` *and* `\__hook_try_declaring_generic_next_hook:nn`.)

`\__hook_try_declaring_generic_hook:nNNnn`
`hook_try_declaring_generic_hook_split:nNNnn`

`\__hook_try_declaring_generic_hook:nNNnn` now splits the hook name at the first `/` (if any) and first checks if it is a file-specific hook (they require some normalization) using `\__hook_if_file_hook:wTF`. If not then check it is one of a predefined set for generic names. We also split off the second component to see if we have to make a reversed hook. In either case the function returns ⟨*true*⟩ for a generic hook and ⟨*false*⟩ in other cases.

```
⟨latexrelease⟩\cs_new_protected:Npn \__hook_try_declaring_generic_hook:nNNnn #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \__hook_if_file_hook:wTF #1 / \s__hook_mark
⟨latexrelease⟩      {
⟨latexrelease⟩        \exp_args:Ne \__hook_try_declaring_generic_hook_split:nNNnn
⟨latexrelease⟩          { \exp_args:Ne \__hook_file_hook_normalize:n {#1} }
⟨latexrelease⟩      }
⟨latexrelease⟩      { \__hook_try_declaring_generic_hook_split:nNNnn {#1} }
⟨latexrelease⟩  }
```

```
⟨latexrelease⟩\cs_new_protected:Npn \__hook_try_declaring_generic_hook_split:nNNnn #1 #2 #3
⟨latexrelease⟩  {
⟨latexrelease⟩    \__hook_try_declaring_generic_hook:wnTF #1 / / / \scan_stop: {#1}
⟨latexrelease⟩      { #2 }
⟨latexrelease⟩      { #3 } {#1}
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\__hook_try_declaring_generic_hook:nNNnn` *and* `\__hook_try_declaring_generic_hook_split:nNNnn`.)

`\__hook_try_declaring_generic_hook:wnTF`

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__hook_try_declaring_generic_hook:wn}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
\prg_new_protected_conditional:Npnn \__hook_try_declaring_generic_hook:wn
    #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
  {
    \__hook_if_generic:nTF {#5}
      {
        \__hook_if_usable:nF {#5}
          {
```

If the hook doesn't exist yet we check if it is a `cmd` hook and if so we attempt patching the command in addition to declaring the hook.

For some commands this will not be possible, in which case `\__hook_patch_cmd_-or_delay:Nnn` (defined in `ltcmdhooks`) will generate an appropriate error message.

```
            \str_if_eq:nnT {#1} { cmd }
              { \__hook_try_put_cmd_hook:n {#5} }
```

Declare the hook always even if it can't really be used (error message generated elsewhere).

Here we use `\__hook_make_usable:n`, so that a `\hook_new:n` is still possible later.

```
            \__hook_make_usable:n {#5}
          }
        \__hook_if_generic_reversed:nT {#5}
          { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
        \prg_return_true:
      }
      {
```

Generic hooks are all named ⟨*type*⟩/⟨*name*⟩/⟨*place*⟩, where ⟨*type*⟩ and ⟨*place*⟩ are predefined (`\c__hook_generic_`⟨*type*⟩`/./`⟨*place*⟩`_tl`), and ⟨*name*⟩ is the variable component. Older releases had some hooks with the ⟨*name*⟩ in the third part, so the code below supports that syntax for a while, with a warning.

The \exp_after:wN ... \exp:w trick is there to remove the conditional structure inserted by __hook_try_declaring_generic_hook:wnTF and thus allow access to the tokens that follow it, as is needed to keep things going.

When the deprecation cycle ends, the lines below should all be replaced by \prg_return_false:.

```
        \__hook_if_deprecated_generic:nTF {#5}
          {
            \__hook_deprecated_generic_warn:n {#5}
            \exp_after:wN \__hook_declare_deprecated_generic:NNn
            \exp:w % \exp_end:
          }
          { \prg_return_false: }
      }
  }
```

__hook_deprecated_generic_warn:n will issue a deprecation warning for a given hook, and mark that hook such that the warning will not be issued again (multiple warnings can be issued, but only once per hook).

__hook_deprecated_generic_warn:Nn
__hook_deprecated_generic_warn:Nw

```
\cs_new_protected:Npn \__hook_deprecated_generic_warn:n #1
  { \__hook_deprecated_generic_warn:w #1 \s__hook_mark }
\cs_new_protected:Npn \__hook_deprecated_generic_warn:w
    #1 / #2 / #3 \s__hook_mark
  {
    \if_cs_exist:w __hook~#1/#2/#3 \cs_end: \else:
      \msg_warning:nnnnn { hooks } { generic-deprecated } {#1} {#2} {#3}
    \fi:
    \cs_gset_eq:cN { __hook~#1/#2/#3 } \scan_stop:
  }
```

Now that the user has been told about the deprecation, we proceed by swapping ⟨*name*⟩ and ⟨*place*⟩ and adding the code to the correct hook.

__hook_do_deprecated_generic:Nn
__hook_do_deprecated_generic:Nw
__hook_declare_deprecated_generic:NNw
__hook_declare_deprecated_generic:NNw

```
\cs_new_protected:Npn \__hook_do_deprecated_generic:Nn #1 #2
  { \__hook_do_deprecated_generic:Nw #1 #2 \s__hook_mark }
\cs_new_protected:Npn \__hook_do_deprecated_generic:Nw #1
         #2 / #3 / #4 \s__hook_mark
  { #1 { #2 / #4 / #3 } }
\cs_new_protected:Npn \__hook_declare_deprecated_generic:NNn #1 #2 #3
  { \__hook_declare_deprecated_generic:NNw #1 #2 #3 \s__hook_mark }
\cs_new_protected:Npn \__hook_declare_deprecated_generic:NNw #1 #2
    #3 / #4 / #5 \s__hook_mark
  {
    \__hook_try_declaring_generic_hook:wnTF #3 / #5 / #4 / \scan_stop:
        { #3 / #5 / #4 }
      #1 #2 { #3 / #5 / #4 }
  }
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}{\__hook_try_declaring_generic_hook:wn}
⟨latexrelease⟩                  {Support~cmd~hooks}
⟨latexrelease⟩\prg_new_protected_conditional:Npnn \__hook_try_declaring_generic_hook:wn
⟨latexrelease⟩    #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
⟨latexrelease⟩  {
⟨latexrelease⟩    \tl_if_empty:nTF {#2}
```

```
⟨latexrelease⟩      { \prg_return_false: }
⟨latexrelease⟩      {
⟨latexrelease⟩        \prop_if_in:NnTF \c__hook_generics_prop {#1}
⟨latexrelease⟩          {
⟨latexrelease⟩            \__hook_if_usable:nF {#5}
⟨latexrelease⟩              {
⟨latexrelease⟩                \str_if_eq:nnT {#1} { cmd }
⟨latexrelease⟩                  { \__hook_try_put_cmd_hook:n {#5} }
⟨latexrelease⟩                \__hook_make_usable:n {#5}
⟨latexrelease⟩              }
⟨latexrelease⟩            \prop_if_in:NnTF \c__hook_generics_reversed_ii_prop {#2}
⟨latexrelease⟩              { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
⟨latexrelease⟩              {
⟨latexrelease⟩                \prop_if_in:NnT \c__hook_generics_reversed_iii_prop {#3}
⟨latexrelease⟩                  { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
⟨latexrelease⟩              }
⟨latexrelease⟩            \prg_return_true:
⟨latexrelease⟩          }
⟨latexrelease⟩          { \prg_return_false: }
⟨latexrelease⟩      }
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__hook_try_declaring_generic_hook:wn}%
⟨latexrelease⟩                  {Support~cmd~hooks}
⟨latexrelease⟩\prg_new_protected_conditional:Npnn \__hook_try_declaring_generic_hook:wn
⟨latexrelease⟩    #1 / #2 / #3 / #4 \scan_stop: #5 { TF }
⟨latexrelease⟩  {
⟨latexrelease⟩    \tl_if_empty:nTF {#2}
⟨latexrelease⟩      { \prg_return_false: }
⟨latexrelease⟩      {
⟨latexrelease⟩        \prop_if_in:NnTF \c__hook_generics_prop {#1}
⟨latexrelease⟩          {
⟨latexrelease⟩            \__hook_if_declared:nF {#5} { \hook_new:n {#5} }
⟨latexrelease⟩            \prop_if_in:NnTF \c__hook_generics_reversed_ii_prop {#2}
⟨latexrelease⟩              { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
⟨latexrelease⟩              {
⟨latexrelease⟩                \prop_if_in:NnT \c__hook_generics_reversed_iii_prop {#3}
⟨latexrelease⟩                  { \tl_gset:cn { g__hook_#5_reversed_tl } { - } }
⟨latexrelease⟩              }
⟨latexrelease⟩            \prg_return_true:
⟨latexrelease⟩          }
⟨latexrelease⟩          { \prg_return_false: }
⟨latexrelease⟩      }
⟨latexrelease⟩  }
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\__hook_try_declaring_generic_hook:wnTF` *and others.*)

`\__hook_if_file_hook_p:w`
`\__hook_if_file_hook:wTF`

`\__hook_if_file_hook:wTF` checks if the argument is a valid file-specific hook (not, for example, `file/before`, but `file/foo.tex/before`). If it is a file-specific hook, then it executes the ⟨*true*⟩ branch, otherwise ⟨*false*⟩.

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__hook_if_file_hook:w}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
```

```
\prg_new_conditional:Npnn \__hook_if_file_hook:w
    #1 / #2 \s__hook_mark #3 { TF }
  {
    \__hook_if_generic:nTF {#3}
      {
        \str_if_eq:nnTF {#1} { file }
          { \prg_return_true: }
          { \prg_return_false: }
      }
      { \prg_return_false: }
  }
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__hook_if_file_hook:w}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\prg_new_conditional:Npnn \__hook_if_file_hook:w
⟨latexrelease⟩    #1 / #2 / #3 \s__hook_mark { TF }
⟨latexrelease⟩  {
⟨latexrelease⟩    \str_if_eq:nnTF {#1} { file }
⟨latexrelease⟩      {
⟨latexrelease⟩        \bool_lazy_or:nnTF
⟨latexrelease⟩            { \tl_if_empty_p:n {#3} }
⟨latexrelease⟩            { \str_if_eq_p:nn {#3} { / } }
⟨latexrelease⟩          { \prg_return_false: }
⟨latexrelease⟩          {
⟨latexrelease⟩            \prop_if_in:NnTF \c__hook_generics_file_prop {#2}
⟨latexrelease⟩              { \prg_return_true: }
⟨latexrelease⟩              { \prg_return_false: }
⟨latexrelease⟩          }
⟨latexrelease⟩      }
⟨latexrelease⟩      { \prg_return_false: }
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\__hook_if_file_hook:wTF`.)

`\__hook_file_hook_normalize:n`
`\__hook_strip_double_slash:n`
`\__hook_strip_double_slash:w`

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__hook_file_hook_normalize:n}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\EndIncludeInRelease
```

When a file-specific hook is found, before being declared it is lightly normalized by `\__hook_file_hook_normalize:n`. The current implementation just replaces two consecutive slashes (`//`) by a single one, to cope with simple cases where the user did something like `\def\input@path{{./mypath/}}`, in which case a hook would have to be `\AddToHook{file/./mypath//file.tex/after}`.

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__hook_file_hook_normalize:n}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\cs_new:Npn \__hook_file_hook_normalize:n #1
⟨latexrelease⟩  { \__hook_strip_double_slash:n {#1} }
⟨latexrelease⟩\cs_new:Npn \__hook_strip_double_slash:n #1
⟨latexrelease⟩  { \__hook_strip_double_slash:w #1 // \s__hook_mark }
```

This function is always called after testing if the argument is a file hook with `\__hook_if_file_hook:wTF`, so we can assume it has three parts (it is either `file/.../before`

or `file/.../after`), so we use `#1/#2/#3 //` instead of just `#1 //` to prevent losing a slash if the file name is empty.

```
⟨latexrelease⟩\cs_new:Npn \__hook_strip_double_slash:w #1/#2/#3 // #4 \s__hook_mark
⟨latexrelease⟩  {
⟨latexrelease⟩    \tl_if_empty:nTF {#4}
⟨latexrelease⟩      { #1/#2/#3 }
⟨latexrelease⟩      { \__hook_strip_double_slash:w #1/#2/#3 / #4 \s__hook_mark }
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\__hook_file_hook_normalize:n`, `\__hook_strip_double_slash:n`, *and* `\__hook_strip_double_slash:w`.)

\c__hook_generic_cmd/./before_tl
\c__hook_generic_cmd/./after_tl
\c__hook_generic_env/./before_tl
\c__hook_generic_env/./after_tl
\c__hook_generic_file/./before_tl
\c__hook_generic_file/./after_tl
\c__hook_generic_package/./before_tl
\c__hook_generic_package/./after_tl
\c__hook_generic_class/./before_tl
\c__hook_generic_class/./after_tl
\c__hook_generic_include/./before_tl
\c__hook_generic_include/./after_tl
\c__hook_generic_env/./begin_tl
\c__hook_generic_env/./end_tl
\c__hook_generic_include/./end_tl

Token lists defining the possible generic hooks. We don't provide any user interface to this as this is meant to be static.

cmd The generic hooks used for commands.

env The generic hooks used in `\begin` and `\end`.

file, package, class, include The generic hooks used when loading a file

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\c__hook_generics_prop}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
\clist_map_inline:nn { cmd , env , file , package , class , include }
  {
    \tl_const:cn { c__hook_generic_#1/./before_tl } { + }
    \tl_const:cn { c__hook_generic_#1/./after_tl  } { - }
  }
\tl_const:cn { c__hook_generic_env/./begin_tl } { + }
\tl_const:cn { c__hook_generic_env/./end_tl   } { + }

\tl_const:cn { c__hook_generic_include/./end_tl } { - }
\tl_const:cn { c__hook_generic_include/./excluded_tl } { + }
```

Deprecated generic hooks:

```
\clist_map_inline:nn { file , package , class , include }
  {
    \tl_const:cn { c__hook_deprecated_#1/./before_tl } { }
    \tl_const:cn { c__hook_deprecated_#1/./after_tl  } { }
  }
\tl_const:cn { c__hook_deprecated_include/./end_tl } { }
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\c__hook_generics_prop}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\prop_const_from_keyval:Nn \c__hook_generics_prop
⟨latexrelease⟩     {cmd=,env=,file=,package=,class=,include=}
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\c__hook_generic_cmd/./before_tl` *and others.*)

\c__hook_generics_reversed_ii_prop
\c__hook_generics_reversed_iii_prop
\c__hook_generics_file_prop

The following generic hooks are supposed to use reverse ordering (the `ii` and `iii` names are kept for the deprecation cycle):

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\c__hook_generics_reversed_ii_prop}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\c__hook_generics_reversed_ii_prop}%
⟨latexrelease⟩                    {Standardise~generic~hook~names}
⟨latexrelease⟩\prop_const_from_keyval:Nn \c__hook_generics_reversed_ii_prop {after=,end=}
⟨latexrelease⟩\prop_const_from_keyval:Nn \c__hook_generics_reversed_iii_prop {after=}
⟨latexrelease⟩\prop_const_from_keyval:Nn \c__hook_generics_file_prop {before=,after=}
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\c__hook_generics_reversed_ii_prop`, `\c__hook_generics_reversed_iii_prop`, *and* `\c__hook_generics_file_prop`.)

`\hook_gremove_code:nn`
`\__hook_gremove_code:nn`

With `\hook_gremove_code:nn{⟨hook⟩}{⟨label⟩}` any code for ⟨*hook*⟩ stored under ⟨*label*⟩ is removed.

```
\cs_new_protected:Npn \hook_gremove_code:nn #1 #2
  { \__hook_normalize_hook_args:Nnn \__hook_gremove_code:nn {#1} {#2} }
\cs_new_protected:Npn \__hook_gremove_code:nn #1 #2
  {
```

First check that the hook code pool exists. `\__hook_if_usable:nTF` isn't used here because it should be possible to remove code from a hook before its defined (see section 2.1.8).

```
    \__hook_if_structure_exist:nTF {#1}
      {
```

Then remove the chunk and run `\__hook_update_hook_code:n` so that the execution token list reflects the change if we are after `\begin{document}`.

If all code is to be removed, clear the code pool `\g__hook_`⟨*hook*⟩`_code_prop`, the top-level code `\__hook_toplevel␣`⟨*hook*⟩, and the next-execution code `\__hook_next␣`⟨*hook*⟩.

```
        \str_if_eq:nnTF {#2} {*}
          {
            \prop_gclear:c { g__hook_#1_code_prop }
            \__hook_tl_gclear:c { __hook_toplevel~#1 }
            \__hook_tl_gclear:c { __hook_next~#1 }
          }
          {
```

If the label is `top-level` then clear the token list, as all code there is under the same label.

```
            \str_if_eq:nnTF {#2} { top-level }
              { \__hook_tl_gclear:c { __hook_toplevel~#1 } }
              {
                \prop_gpop:cnNF { g__hook_#1_code_prop } {#2} \l__hook_return_tl
                  { \msg_warning:nnnn { hooks } { cannot-remove } {#1} {#2} }
              }
          }
```

Finally update the code, if the hook exists.

```
        \__hook_if_usable:nT {#1}
          { \__hook_update_hook_code:n {#1} }
      }
```

If the code pool for this hook doesn't exist, show a warning:

```
      {
        \__hook_if_deprecated_generic:nTF {#1}
          {
            \__hook_deprecated_generic_warn:n {#1}
```

```
            \__hook_do_deprecated_generic:Nn \__hook_gremove_code:nn {#1} {#2}
          }
          { \msg_warning:nnnn { hooks } { cannot-remove } {#1} {#2} }
      }
  }
```

(*End definition for* `\hook_gremove_code:nn` *and* `\__hook_gremove_code:nn`*. This function is documented on page 193.*)

`\g__hook_??_code_prop`
`\__hook~??`
`\g__hook_??_reversed_tl`

Initially these variables simply used an empty "label" name (not two question marks). This was a bit unfortunate, because then `l3doc` complains about `__` in the middle of a command name when trying to typeset the documentation. However using a "normal" name such as `default` has the disadvantage of that being not really distinguishable from a real hook name. I now have settled for `??` which needs some gymnastics to get it into the csname, but since this is used a lot, the code should be fast, so this is not done with `c` expansion in the code later on.

`\__hook␣??` isn't used, but it has to be defined to trick the code into thinking that `??` is actually a hook.

```
\prop_new:c {g__hook_??_code_prop}
\prop_new:c {__hook~??}
```

Default rules are always given in normal ordering (never in reversed ordering). If such a rule is applied to a reversed hook it behaves as if the rule is reversed (e.g., `after` becomes `before`) because those rules are applied first and then the order is reversed.

```
\tl_new:c {g__hook_??_reversed_tl}
```

(*End definition for* `\g__hook_??_code_prop`*,* `\__hook~??`*, and* `\g__hook_??_reversed_tl`*.*)

4.7 Setting rules for hooks code

`\hook_gset_rule:nnnn`
`\__hook_gset_rule:nnnn`

With `\hook_gset_rule:nnnn{`⟨*hook*⟩`}{`⟨*label1*⟩`}{`⟨*relation*⟩`}{`⟨*label2*⟩`}` a relation is defined between the two code labels for the given ⟨*hook*⟩. The special hook `??` stands for *any* hook, which sets a default rule (to be used if no other relation between the two hooks exist).

```
\cs_new_protected:Npn \hook_gset_rule:nnnn #1#2#3#4
  {
    \__hook_normalize_hook_rule_args:Nnnnn \__hook_gset_rule:nnnn
      {#1} {#2} {#3} {#4}
  }
⟨latexrelease⟩\IncludeInRelease{2022/06/01}{\__hook_gset_rule:nnnn}
⟨latexrelease⟩                  {Refuse~setting~rule~for~one-time~hooks}
\cs_new_protected:Npn \__hook_gset_rule:nnnn #1#2#3#4
  {
    \__hook_if_deprecated_generic:nT {#1}
      {
        \__hook_deprecated_generic_warn:n {#1}
        \__hook_do_deprecated_generic:Nn \__hook_gset_rule:nnnn {#1}
          {#2} {#3} {#4}
        \__hook_clean_to_scan:w
      }
    \__hook_if_execute_immediately:nT {#1}
      {
        \msg_error:nnnnnn { hooks } { rule-too-late }
```

```
          {#1} {#2} {#3} {#4}
        \__hook_clean_to_scan:w
      }
```

First we ensure the basic data structure of the hook exists:

```
    \__hook_init_structure:n {#1}
```

Then we clear any previous relationship between both labels.

```
    \__hook_rule_gclear:nnn {#1} {#2} {#4}
```

Then we call the function to handle the given rule. Throw an error if the rule is invalid.

```
    \cs_if_exist_use:cTF { __hook_rule_#3_gset:nnn }
      {
          {#1} {#2} {#4}
        \__hook_update_hook_code:n {#1}
      }
      {
        \msg_error:nnnnnn { hooks } { unknown-rule }
          {#1} {#2} {#3} {#4}
      }
    \s__hook_mark
  }
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__hook_gset_rule:nnnn}
⟨latexrelease⟩                  {Refuse~setting~rule~for~one-time~hooks}
⟨latexrelease⟩\cs_new_protected:Npn \__hook_gset_rule:nnnn #1#2#3#4
⟨latexrelease⟩  {
⟨latexrelease⟩    \__hook_if_deprecated_generic:nT {#1}
⟨latexrelease⟩      {
⟨latexrelease⟩        \__hook_deprecated_generic_warn:n {#1}
⟨latexrelease⟩        \__hook_do_deprecated_generic:Nn \__hook_gset_rule:nnnn {#1}
⟨latexrelease⟩          {#2} {#3} {#4}
⟨latexrelease⟩        \exp_after:wN \use_none:nnnnnnnnn \use_none:n
⟨latexrelease⟩      }
⟨latexrelease⟩    \__hook_init_structure:n {#1}
⟨latexrelease⟩    \__hook_rule_gclear:nnn {#1} {#2} {#4}
⟨latexrelease⟩    \cs_if_exist_use:cTF { __hook_rule_#3_gset:nnn }
⟨latexrelease⟩      {
⟨latexrelease⟩          {#1} {#2} {#4}
⟨latexrelease⟩        \__hook_update_hook_code:n {#1}
⟨latexrelease⟩      }
⟨latexrelease⟩      {
⟨latexrelease⟩        \msg_error:nnnnnn { hooks } { unknown-rule }
⟨latexrelease⟩          {#1} {#2} {#3} {#4}
⟨latexrelease⟩      }
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\hook_gset_rule:nnnn` *and* `\__hook_gset_rule:nnnn`*. This function is documented on page* 193.)

`\__hook_rule_before_gset:nnn`
`\__hook_rule_after_gset:nnn`
`\__hook_rule_<_gset:nnn`
`\__hook_rule_>_gset:nnn`

Then we add the new rule. We need to normalize the rules here to allow for faster processing later. Given a pair of labels l_A and l_B, the rule $l_A > l_B$ is the same as $l_B < l_A$ only presented differently. But by normalizing the forms of the rule to a single representation, say, $l_B < l_A$, reduces the time spent looking for the rules later considerably.

Here we do that normalization by using `\(pdf)strcmp` to lexically sort labels l_A and l_B to a fixed order. This order is then enforced every time these two labels are used together.

Here we use `\__hook_label_pair:nn` {⟨*hook*⟩} {⟨l_A⟩} {⟨l_B⟩} to build a string $l_B|l_A$ with a fixed order, and use `\__hook_label_ordered:nnTF` to apply the correct rule to the pair of labels, depending if it was sorted or not.

```
\cs_new_protected:Npn \__hook_rule_before_gset:nnn #1#2#3
  {
    \__hook_tl_gset:cx { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl }
      { \__hook_label_ordered:nnTF {#2} {#3} { < } { > } }
  }
\cs_new_eq:cN { __hook_rule_<_gset:nnn } \__hook_rule_before_gset:nnn
```

```
\cs_new_protected:Npn \__hook_rule_after_gset:nnn #1#2#3
  {
    \__hook_tl_gset:cx { g__hook_#1_rule_ \__hook_label_pair:nn {#3} {#2} _tl }
      { \__hook_label_ordered:nnTF {#3} {#2} { < } { > } }
  }
\cs_new_eq:cN { __hook_rule_>_gset:nnn } \__hook_rule_after_gset:nnn
```

(*End definition for* `\__hook_rule_before_gset:nnn` *and others.*)

`\__hook_rule_voids_gset:nnn` This rule removes (clears, actually) the code from label `#3` if label `#2` is in the hook `#1`.

```
\cs_new_protected:Npn \__hook_rule_voids_gset:nnn #1#2#3
  {
    \__hook_tl_gset:cx { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl }
      { \__hook_label_ordered:nnTF {#2} {#3} { -> } { <- } }
  }
```

(*End definition for* `\__hook_rule_voids_gset:nnn`.)

`\__hook_rule_incompatible-error_gset:nnn` `\__hook_rule_incompatible-warning_gset:nnn` These relations make an error/warning if labels `#2` and `#3` appear together in hook `#1`.

```
\cs_new_protected:cpn { __hook_rule_incompatible-error_gset:nnn } #1#2#3
  { \__hook_tl_gset:cn { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl }
                   { xE } }
\cs_new_protected:cpn { __hook_rule_incompatible-warning_gset:nnn } #1#2#3
  { \__hook_tl_gset:cn { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl }
                   { xW } }
```

(*End definition for* `\__hook_rule_incompatible-error_gset:nnn` *and* `\__hook_rule_incompatible-warning_gset:nnn`.)

`\__hook_rule_unrelated_gset:nnn` `\__hook_rule_gclear:nnn` Undo a setting. `\__hook_rule_unrelated_gset:nnn` doesn't need to do anything, since we use `\__hook_rule_gclear:nnn` before setting any rule.

```
\cs_new_protected:Npn \__hook_rule_unrelated_gset:nnn #1#2#3 { }
\cs_new_protected:Npn \__hook_rule_gclear:nnn #1#2#3
  { \cs_undefine:c { g__hook_#1_rule_ \__hook_label_pair:nn {#2} {#3} _tl } }
```

(*End definition for* `\__hook_rule_unrelated_gset:nnn` *and* `\__hook_rule_gclear:nnn`.)

`\__hook_label_pair:nn` Ensure that the lexically greater label comes first.

```
\cs_new:Npn \__hook_label_pair:nn #1#2
  {
    \if_case:w \__hook_str_compare:nn {#1} {#2} \exp_stop_f:
          #1 | #1 %  0
```

```
    \or:   #1 | #2 % +1
    \else: #2 | #1 % -1
    \fi:
  }
```

(*End definition for* `\__hook_label_pair:nn`.)

`\__hook_label_ordered_p:nn`
`\__hook_label_ordered:nnTF`

Check that labels `#1` and `#2` are in the correct order (as returned by `\__hook_label_pair:nn`) and if so return true, else return false.

```
\prg_new_conditional:Npnn \__hook_label_ordered:nn #1#2 { TF }
  {
    \if_int_compare:w \__hook_str_compare:nn {#1} {#2} > 0 \exp_stop_f:
      \prg_return_true:
    \else:
      \prg_return_false:
    \fi:
  }
```

(*End definition for* `\__hook_label_ordered:nnTF`.)

`\__hook_if_label_case:nnnnn`

To avoid doing the string comparison twice in `\__hook_initialize_single:NNn` (once with `\str_if_eq:nn` and again with `\__hook_label_ordered:nn`), we use a three-way branching macro that will compare `#1` and `#2` and expand to `\use_i:nnn` if they are equal, `\use_ii:nn` if `#1` is lexically greater, and `\use_iii:nn` otherwise.

```
\cs_new:Npn \__hook_if_label_case:nnnnn #1#2
  {
    \cs:w use_
      \if_case:w \__hook_str_compare:nn {#1} {#2}
         i \or: ii \else: iii \fi: :nnn
    \cs_end:
  }
```

(*End definition for* `\__hook_if_label_case:nnnnn`.)

`\__hook_update_hook_code:n`

Before `\begin{document}` this does nothing, in the body it reinitializes the hook code using the altered data.

```
\cs_new_eq:NN \__hook_update_hook_code:n \use_none:n
```

(*End definition for* `\__hook_update_hook_code:n`.)

`\__hook_initialize_all:`

Initialize all known hooks (at `\begin{document}`), i.e., update the fast execution token lists to hold the necessary code in the right order.

```
\cs_new_protected:Npn \__hook_initialize_all: {
```

First we change `\__hook_update_hook_code:n` which so far was a no-op to now initialize one hook. This way any later updates to the hook will run that code and also update the execution token list.

```
  \cs_gset_eq:NN \__hook_update_hook_code:n \__hook_initialize_hook_code:n
```

Now we loop over all hooks that have been defined and update each of them.

```
  \__hook_debug:n { \prop_gclear:N \g__hook_used_prop }
  \seq_map_inline:Nn \g__hook_all_seq
      {
        \__hook_update_hook_code:n {##1}
      }
```

If we are debugging we show results hook by hook for all hooks that have data.

```
  \__hook_debug:n
     { \iow_term:x{^^JAll~ initialized~ (non-empty)~ hooks:}
       \prop_map_inline:Nn \g__hook_used_prop
           { \iow_term:x{^^J~ ##1~ ->~
               \exp_not:v {__hook~##1}~ }
           }
     }
```

After all hooks are initialized we change the "use" to just call the hook code and not initialize it (as it was done in the preamble.

```
  \cs_gset_eq:NN \hook_use:n \__hook_use_initialized:n
  \cs_gset_eq:NN \__hook_preamble_hook:n \use_none:n
}
```

(*End definition for* `\__hook_initialize_all:`.)

`\__hook_initialize_hook_code:n` Initializing or reinitializing the fast execution hook code. In the preamble this is selectively done in case a hook gets used and at `\begin{document}` this is done for all hooks and afterwards only if the hook code changes.

```
\cs_new_protected:Npn \__hook_initialize_hook_code:n #1
  {
    \__hook_debug:n
      { \iow_term:x { ^^J Update~code~for~hook~'#1' \on@line :^^J } }
```

This does the sorting and the updates. First thing we do is to check if a legacy hook macro exists and if so we add it to the hook under the label `legacy`. This might make the hook non-empty so we have to do this before the then following test.

```
    \__hook_include_legacy_code_chunk:n {#1}
```

If there aren't any code chunks for the current hook, there is no point in even starting the sorting routine so we make a quick test for that and in that case just update `\__hook␣`⟨*hook*⟩ to hold the `top-level` and `next` code chunks. If there are code chunks we call `\__hook_initialize_single:NNn` and pass to it ready made csnames as they are needed several times inside. This way we save a bit on processing time if we do that up front.

```
    \__hook_if_usable:nT {#1}
      {
        \prop_if_empty:cTF { g__hook_#1_code_prop }
          {
            \__hook_tl_gset:co { __hook~#1 }
              {
                \cs:w __hook_toplevel~#1 \exp_after:wN \cs_end:
                \cs:w __hook_next~#1 \cs_end:
              }
          }
          {
```

By default the algorithm sorts the code chunks and then saves the result in a token list for fast execution; this is done by adding the code chunks one after another, using `\tl_gput_right:NV`. When we sort code for a reversed hook, all we have to do is to add the code chunks in the opposite order into the token list. So all we have to do in preparation is to change two definitions that are used later on.

```
            \__hook_if_reversed:nTF {#1}
```

```
              { \cs_set_eq:NN \__hook_tl_gput:Nn    \__hook_tl_gput_left:Nn
                \cs_set_eq:NN \__hook_clist_gput:NV \clist_gput_left:NV  }
              { \cs_set_eq:NN \__hook_tl_gput:Nn    \__hook_tl_gput_right:Nn
                \cs_set_eq:NN \__hook_clist_gput:NV \clist_gput_right:NV }
```

When sorting, some relations (namely `voids`) need to act destructively on the code property lists to remove code that shouldn't appear in the sorted hook token list, so we make a copy of the code property list that we can safely work on without changing the main one.

```
            \prop_set_eq:Nc \l__hook_work_prop { g__hook_#1_code_prop }
            \__hook_initialize_single:ccn
              { __hook~#1 } { g__hook_#1_labels_clist } {#1}
```

For debug display we want to keep track of those hooks that actually got code added to them, so we record that in plist. We use a plist to ensure that we record each hook name only once, i.e., we are only interested in storing the keys and the value is arbitrary.

```
            \__hook_debug:n
              { \exp_args:NNx \prop_gput:Nnn \g__hook_used_prop {#1} { } }
          }
      }
  }
```

(*End definition for* `\__hook_initialize_hook_code:n`.)

`\__hook_tl_csname:n`
`\__hook_seq_csname:n`

It is faster to pass a single token and expand it when necessary than to pass a bunch of character tokens around.

FMi: note to myself: verify

```
\cs_new:Npn \__hook_tl_csname:n #1 { l__hook_label_#1_tl }
\cs_new:Npn \__hook_seq_csname:n #1 { l__hook_label_#1_seq }
```

(*End definition for* `\__hook_tl_csname:n` *and* `\__hook_seq_csname:n`.)

`\l__hook_labels_seq`
`\l__hook_labels_int`
`\l__hook_front_tl`
`\l__hook_rear_tl`
`\l__hook_label_0_tl`

For the sorting I am basically implementing Knuth's algorithm for topological sorting as given in TAOCP volume 1 pages 263–266. For this algorithm we need a number of local variables:

- List of labels used in the current hook to label code chunks:

```
    \seq_new:N \l__hook_labels_seq
```

- Number of labels used in the current hook. In Knuth's algorithm this is called N:

```
    \int_new:N \l__hook_labels_int
```

- The sorted code list to be build is managed using two pointers one to the front of the queue and one to the rear. We model this using token list pointers. Knuth calls them F and R:

```
    \tl_new:N \l__hook_front_tl
    \tl_new:N \l__hook_rear_tl
```

- The data for the start of the queue is kept in this token list, it corresponds to what Don calls `QLINK[0]` but since we aren't manipulating individual words in memory it is slightly differently done:

```
\tl_new:c { \__hook_tl_csname:n { 0 } }
```

(*End definition for* `\l__hook_labels_seq` *and others.*)

__hook_initialize_single:NNn
__hook_initialize_single:ccn

`\__hook_initialize_single:NNn` implements the sorting of the code chunks for a hook and saves the result in the token list for fast execution (`#4`). The arguments are ⟨*hook-code-plist*⟩, ⟨*hook-code-tl*⟩, ⟨*hook-top-level-code-tl*⟩, ⟨*hook-next-code-tl*⟩, ⟨*hook-ordered-labels-clist*⟩ and ⟨*hook-name*⟩ (the latter is only used for debugging—the ⟨*hook-rule-plist*⟩ is accessed using the ⟨*hook-name*⟩).

The additional complexity compared to Don's algorithm is that we do not use simple positive integers but have arbitrary alphanumeric labels. As usual Don's data structures are chosen in a way that one can omit a lot of tests and I have mimicked that as far as possible. The result is a restriction I do not test for at the moment: a label can't be equal to the number 0!

FMi: Needs checking for, just in case ... maybe

```
\cs_new_protected:Npn \__hook_initialize_single:NNn #1#2#3
  {
```

Step T1: Initialize the data structure ...

```
    \seq_clear:N \l__hook_labels_seq
    \int_zero:N  \l__hook_labels_int
```

Store the name of the hook:

```
    \tl_set:Nn \l__hook_cur_hook_tl {#3}
```

We loop over the property list holding the code and record all the labels listed there. Only the rules for those labels are of interest to us. While we are at it we count them (which gives us the N in Knuth's algorithm). The prefix `label_` is added to the variables to ensure that labels named `front`, `rear`, `labels`, or `return` don't interact with our code.

```
    \prop_map_inline:Nn \l__hook_work_prop
       {
         \int_incr:N \l__hook_labels_int
         \seq_put_right:Nn \l__hook_labels_seq {##1}
         \__hook_tl_set:cn { \__hook_tl_csname:n {##1} } { 0 }
         \seq_clear_new:c { \__hook_seq_csname:n {##1} }
       }
```

Steps T2 and T3: Here we sort the relevant rules into the data structure...

This loop constitutes a square matrix of the labels in `\l__hook_work_prop` in the vertical and the horizontal directions. However, since the rule $l_A\langle rel\rangle l_B$ is the same as $l_B\langle rel\rangle^{-1}l_A$ we can cut the loop short at the diagonal of the matrix (*i.e.*, when both labels are equal), saving a good amount of time. The way the rules were set up (see the implementation of `\__hook_rule_before_gset:nnn` above) ensures that we have no rule in the ignored side of the matrix, and all rules are seen. The rules are applied in `\__hook_apply_label_pair:nnn`, which takes the properly-ordered pair of labels as argument.

```
    \prop_map_inline:Nn \l__hook_work_prop
      {
```

```
        \prop_map_inline:Nn \l__hook_work_prop
          {
            \__hook_if_label_case:nnnnn {##1} {####1}
              { \prop_map_break: }
              { \__hook_apply_label_pair:nnn {##1} {####1} }
              { \__hook_apply_label_pair:nnn {####1} {##1} }
                  {#3}
          }
      }
```

Now take a breath, and look at the data structures that have been set up:

```
    \__hook_debug:n { \__hook_debug_label_data:N \l__hook_work_prop }
```

Step T4:

```
    \tl_set:Nn \l__hook_rear_tl { 0 }
    \tl_set:cn { \__hook_tl_csname:n { 0 } } { 0 }
    \seq_map_inline:Nn \l__hook_labels_seq
      {
        \int_compare:nNnT { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
            {
              \tl_set:cn { \__hook_tl_csname:n { \l__hook_rear_tl } }{##1}
              \tl_set:Nn \l__hook_rear_tl {##1}
            }
      }
    \tl_set_eq:Nc \l__hook_front_tl { \__hook_tl_csname:n { 0 } }
    \__hook_tl_gclear:N #1
    \clist_gclear:N #2
```

The whole loop gets combined in steps T5–T7:

```
    \bool_while_do:nn { ! \str_if_eq_p:Vn \l__hook_front_tl { 0 } }
      {
```

This part is step T5:

```
        \int_decr:N \l__hook_labels_int
        \prop_get:NVN \l__hook_work_prop \l__hook_front_tl \l__hook_return_tl
        \exp_args:NNV \__hook_tl_gput:Nn #1 \l__hook_return_tl
        \__hook_clist_gput:NV #2 \l__hook_front_tl
        \__hook_debug:n{ \iow_term:x{Handled~ code~ for~ \l__hook_front_tl} }
```

This is step T6, except that we don't use a pointer P to move through the successors, but instead use `##1` of the mapping function.

```
        \seq_map_inline:cn { \__hook_seq_csname:n { \l__hook_front_tl } }
          {
            \tl_set:cx { \__hook_tl_csname:n {##1} }
                       { \int_eval:n
                           { \cs:w \__hook_tl_csname:n {##1} \cs_end: - 1 }
                       }
            \int_compare:nNnT
                { \cs:w \__hook_tl_csname:n {##1} \cs_end: } = 0
                {
                  \tl_set:cn { \__hook_tl_csname:n { \l__hook_rear_tl } } {##1}
                  \tl_set:Nn \l__hook_rear_tl            {##1}
                }
          }
```

and here is step T7:

```
        \tl_set_eq:Nc \l__hook_front_tl
                      { \__hook_tl_csname:n { \l__hook_front_tl } }
```

This is step T8: If we haven't moved the code for all labels (i.e., if `\l__hook_labels_int` is still greater than zero) we have a loop and our partial order can't be flattened out.

```
      }
    \int_compare:nNnF \l__hook_labels_int = 0
      {
        \iow_term:x{====================}
        \iow_term:x{Error:~ label~ rules~ are~ incompatible:}
```

This is not really the information one needs in the error case but it will do for now ...

FMi: improve output on a rainy day

```
        \__hook_debug_label_data:N \l__hook_work_prop
        \iow_term:x{====================}
      }
```

After we have added all hook code to `#1`, we finish it off by adding extra code for the `top-level` (`#2`) and for one time execution (`#3`). These should normally be empty. The `top-level` code is added with `\__hook_tl_gput:Nn` as that might change for a reversed hook (then `top-level` is the very first code chunk added). The `next` code is always added last.

```
    \exp_args:NNo \__hook_tl_gput:Nn #1 { \cs:w __hook_toplevel~#3 \cs_end: }
    \__hook_tl_gput_right:No #1 { \cs:w __hook_next~#3 \cs_end: }
  }
\cs_generate_variant:Nn \__hook_initialize_single:NNn { cc }
```

(*End definition for* `\__hook_initialize_single:NNn`.)

`\__hook_tl_gput:Nn`
`\__hook_clist_gput:NV`

These append either on the right (normal hook) or on the left (reversed hook). This is setup up in `\__hook_initialize_hook_code:n`, elsewhere their behavior is undefined.

```
\cs_new:Npn \__hook_tl_gput:Nn    { \ERROR }
\cs_new:Npn \__hook_clist_gput:NV { \ERROR }
```

(*End definition for* `\__hook_tl_gput:Nn` *and* `\__hook_clist_gput:NV`.)

`\__hook_apply_label_pair:nnn`
`\__hook_label_if_exist_apply:nnnF`

This is the payload of steps T2 and T3 executed in the loop described above. This macro assumes `#1` and `#2` are ordered, which means that any rule pertaining the pair `#1` and `#2` is `\g__hook_`⟨*hook*⟩`_rule_#1|#2_tl`, and not `\g__hook_`⟨*hook*⟩`_rule_#2|#1_tl`. This also saves a great deal of time since we only need to check the order of the labels once.

The arguments here are ⟨*label1*⟩, ⟨*label2*⟩, ⟨*hook*⟩, and ⟨*hook-code-plist*⟩. We are about to apply the next rule and enter it into the data structure. `\__hook_apply_label_pair:nnn` will just call `\__hook_label_if_exist_apply:nnnF` for the ⟨*hook*⟩, and if no rule is found, also try the ⟨*hook*⟩ name `??` denoting a default hook rule.

`\__hook_label_if_exist_apply:nnnF` will check if the rule exists for the given hook, and if so call `\__hook_apply_rule:nnn`.

```
\cs_new_protected:Npn \__hook_apply_label_pair:nnn #1#2#3
  {
```

Extra complication: as we use default rules and local hook specific rules we first have to check if there is a local rule and if that exist use it. Otherwise check if there is a default rule and use that.

```
    \__hook_label_if_exist_apply:nnnF {#1} {#2} {#3}
      {
```

If there is no hook-specific rule we check for a default one and use that if it exists.

```
        \__hook_label_if_exist_apply:nnnF {#1} {#2} { ?? } { }
      }
  }
\cs_new_protected:Npn \__hook_label_if_exist_apply:nnnF #1#2#3
  {
    \if_cs_exist:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end:
```

What to do precisely depends on the type of rule we have encountered. If it is a `before` rule it will be handled by the algorithm but other types need to be managed differently. All this is done in `\__hook_apply_rule:nnnN`.

```
      \__hook_apply_rule:nnn {#1} {#2} {#3}
      \exp_after:wN \use_none:n
    \else:
      \use:nn
    \fi:
  }
```

(*End definition for* `\__hook_apply_label_pair:nnn` *and* `\__hook_label_if_exist_apply:nnnF`.)

`\__hook_apply_rule:nnn` This is the code executed in steps T2 and T3 while looping through the matrix This is part of step T3. We are about to apply the next rule and enter it into the data structure. The arguments are ⟨*label1*⟩, ⟨*label2*⟩, ⟨*hook-name*⟩, and ⟨*hook-code-plist*⟩.

```
\cs_new_protected:Npn \__hook_apply_rule:nnn #1#2#3
  {
    \cs:w __hook_apply_
      \cs:w g__hook_#3_reversed_tl \cs_end: rule_
        \cs:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end: :nnn \cs_end:
      {#1} {#2} {#3}
  }
```

(*End definition for* `\__hook_apply_rule:nnn`.)

`\__hook_apply_rule_<:nnn` `\__hook_apply_rule_>:nnn` The most common cases are `<` and `>` so we handle that first. They are relations $\prec$ and $\succ$ in TAOCP, and they dictate sorting.

```
\cs_new_protected:cpn { __hook_apply_rule_<:nnn } #1#2#3
  {
    \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
    \tl_set:cx { \__hook_tl_csname:n {#2} }
       { \int_eval:n{ \cs:w \__hook_tl_csname:n {#2} \cs_end: + 1 } }
    \seq_put_right:cn{ \__hook_seq_csname:n {#1} }{#2}
  }
\cs_new_protected:cpn { __hook_apply_rule_>:nnn } #1#2#3
  {
    \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
    \tl_set:cx { \__hook_tl_csname:n {#1} }
       { \int_eval:n{ \cs:w \__hook_tl_csname:n {#1} \cs_end: + 1 } }
    \seq_put_right:cn{ \__hook_seq_csname:n {#2} }{#1}
  }
```

(*End definition for* `\__hook_apply_rule_<:nnn` *and* `\__hook_apply_rule_>:nnn`.)

`\__hook_apply_rule_xE:nnn`
`\__hook_apply_rule_xW:nnn`

These relations make two labels incompatible within a hook. `xE` makes raises an error if the labels are found in the same hook, and `xW` makes it a warning.

```
\cs_new_protected:cpn { __hook_apply_rule_xE:nnn } #1#2#3
  {
    \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
    \msg_error:nnnnnn { hooks } { labels-incompatible }
      {#1} {#2} {#3} { 1 }
    \use:c { __hook_apply_rule_->:nnn } {#1} {#2} {#3}
    \use:c { __hook_apply_rule_<-:nnn } {#1} {#2} {#3}
  }
\cs_new_protected:cpn { __hook_apply_rule_xW:nnn } #1#2#3
  {
    \__hook_debug:n { \__hook_msg_pair_found:nnn {#1} {#2} {#3} }
    \msg_warning:nnnnnn { hooks } { labels-incompatible }
      {#1} {#2} {#3} { 0 }
  }
```

(*End definition for* `\__hook_apply_rule_xE:nnn` *and* `\__hook_apply_rule_xW:nnn`.)

`\__hook_apply_rule_->:nnn`
`\__hook_apply_rule_<-:nnn`

If we see `->` we have to drop code for label `#3` and carry on. We could do a little better and drop everything for that label since it doesn't matter where we put such empty code. However that would complicate the algorithm a lot with little gain.[10] So we still unnecessarily try to sort it in and depending on the rules that might result in a loop that is otherwise resolved. If that turns out to be a real issue, we can improve the code.

Here the code is removed from `\l__hook_cur_hook_tl` rather than `#3` because the latter may be `??`, and the default hook doesn't store any code. Removing it instead from `\l__hook_cur_hook_tl` makes the default rules `->` and `<-` work properly.

```
\cs_new_protected:cpn { __hook_apply_rule_->:nnn } #1#2#3
  {
    \__hook_debug:n
      {
        \__hook_msg_pair_found:nnn {#1} {#2} {#3}
        \iow_term:x{--->~ Drop~ '#2'~ code~ from~
          \iow_char:N \\ g__hook_ \l__hook_cur_hook_tl _code_prop ~
          because~ of~ '#1' }
      }
    \prop_put:Nnn \l__hook_work_prop {#2} { }
  }
\cs_new_protected:cpn { __hook_apply_rule_<-:nnn } #1#2#3
  {
    \__hook_debug:n
      {
        \__hook_msg_pair_found:nnn {#1} {#2} {#3}
        \iow_term:x{--->~ Drop~ '#1'~ code~ from~
          \iow_char:N \\ g__hook_ \l__hook_cur_hook_tl _code_prop ~
          because~ of~ '#2' }
      }
    \prop_put:Nnn \l__hook_work_prop {#1} { }
  }
```

[10] This also has the advantage that the result of the sorting doesn't change, as it might otherwise do (for unrelated chunks) if we aren't careful.

(*End definition for* `\__hook_apply_rule_->:nnn` *and* `\__hook_apply_rule_<-:nnn`.)

`\__hook_apply_-rule_<:nnn`
`\__hook_apply_-rule_>:nnn`
`\__hook_apply_-rule_<-:nnn`
`\__hook_apply_-rule_->:nnn`
`\__hook_apply_-rule_xW:nnn`
`\__hook_apply_-rule_xE:nnn`

Reversed rules.

```
\cs_new_eq:cc { __hook_apply_-rule_<:nnn } { __hook_apply_rule_>:nnn }
\cs_new_eq:cc { __hook_apply_-rule_>:nnn } { __hook_apply_rule_<:nnn }
\cs_new_eq:cc { __hook_apply_-rule_<-:nnn } { __hook_apply_rule_<-:nnn }
\cs_new_eq:cc { __hook_apply_-rule_->:nnn } { __hook_apply_rule_->:nnn }
\cs_new_eq:cc { __hook_apply_-rule_xE:nnn } { __hook_apply_rule_xE:nnn }
\cs_new_eq:cc { __hook_apply_-rule_xW:nnn } { __hook_apply_rule_xW:nnn }
```

(*End definition for* `\__hook_apply_-rule_<:nnn` *and others.*)

`\__hook_msg_pair_found:nnn`

A macro to avoid moving this many tokens around.

```
\cs_new_protected:Npn \__hook_msg_pair_found:nnn #1#2#3
  {
    \iow_term:x{~ \str_if_eq:nnTF {#3} {??} {default} {~normal} ~
        rule~ \__hook_label_pair:nn {#1} {#2}:~
        \use:c { g__hook_#3_rule_ \__hook_label_pair:nn {#1} {#2} _tl } ~
        found}
  }
```

(*End definition for* `\__hook_msg_pair_found:nnn`.)

`\__hook_debug_label_data:N`

```
\cs_new_protected:Npn \__hook_debug_label_data:N #1 {
  \iow_term:x{Code~ labels~ for~ sorting:}
  \iow_term:x{~ \seq_use:Nnnn\l__hook_labels_seq {~and~}{,~}{~and~} }
  \iow_term:x{^^J Data~ structure~ for~ label~ rules:}
  \prop_map_inline:Nn #1
      {
        \iow_term:x{~ ##1~ =~ \tl_use:c{ \__hook_tl_csname:n {##1} }~ ->~
          \seq_use:cnnn{ \__hook_seq_csname:n {##1} }{~->~}{~->~}{~->~}
        }
      }
  \iow_term:x{}
}
```

(*End definition for* `\__hook_debug_label_data:N`.)

`\hook_show:n`
`\hook_log:n`
`\__hook_log_line:x`
`\__hook_log_line_indent:x`
`\__hook_log:nN`

This writes out information about the hook given in its argument onto the `.log` file and the terminal, if `\show_hook:n` is used. Internally both share the same structure, except that at the end, `\hook_show:n` triggers TEX's prompt.

```
\cs_new_protected:Npn \hook_log:n #1
  {
    \cs_set_eq:NN \__hook_log_cmd:x \iow_log:x
    \__hook_normalize_hook_args:Nn \__hook_log:nN {#1} \tl_log:x
  }
\cs_new_protected:Npn \hook_show:n #1
  {
    \cs_set_eq:NN \__hook_log_cmd:x \iow_term:x
    \__hook_normalize_hook_args:Nn \__hook_log:nN {#1} \tl_show:x
  }
\cs_new_protected:Npn \__hook_log_line:x #1
  { \__hook_log_cmd:x { >~#1 } }
\cs_new_protected:Npn \__hook_log_line_indent:x #1
  { \__hook_log_cmd:x { >~\@spaces #1 } }
```

```
\cs_new_protected:Npn \__hook_log:nN #1 #2
  {
    \__hook_if_deprecated_generic:nT {#1}
      {
        \__hook_deprecated_generic_warn:n {#1}
        \__hook_do_deprecated_generic:Nn \__hook_log:nN {#1} #2
        \exp_after:wN \use_none:nnnnnnnnn \use_none:nnnnn
      }
    \__hook_preamble_hook:n {#1}
    \__hook_log_cmd:x
      { ^^J ->~The~ \__hook_if_generic:nT {#1} { generic~ } hook~'#1': }
    \__hook_if_usable:nF {#1}
      { \__hook_log_line:x { The~hook~is~not~declared. } }
    \__hook_if_disabled:nT {#1}
      { \__hook_log_line:x { The~hook~is~disabled. } }
    \hook_if_empty:nTF {#1}
      { #2 { The~hook~is~empty } }
      {
        \__hook_log_line:x { Code~chunks: }
        \prop_if_empty:cTF { g__hook_#1_code_prop }
          { \__hook_log_line_indent:x { --- } }
          {
            \prop_map_inline:cn { g__hook_#1_code_prop }
              { \__hook_log_line_indent:x { ##1~->~\tl_to_str:n {##2} } }
          }
```

If there is code in the `top-level` token list, print it:

```
        \__hook_log_line:x
          {
            Document-level~(top-level)~code
            \__hook_if_usable:nT {#1}
              { ~(executed~\__hook_if_reversed:nTF {#1} {first} {last} ) } :
          }
        \__hook_log_line_indent:x
          {
            \tl_if_empty:cTF { __hook_toplevel~#1 }
              { --- }
              { -> ~ \exp_args:Nv \tl_to_str:n { __hook_toplevel~#1 } }
          }
        \__hook_log_line:x { Extra~code~for~next~invocation: }
        \__hook_log_line_indent:x
          {
            \tl_if_empty:cTF { __hook_next~#1 }
              { --- }
```

If the token list is not empty we want to display it but without the first tokens (the code to clear itself) so we call a helper command to get rid of them.

```
              { ->~ \exp_args:Nv \__hook_log_next_code:n { __hook_next~#1 } }
          }
```

Loop through the rules in a hook and for every rule found, print it. If no rule is there, print `---`. The boolean `\l__hook_tmpa_bool` here indicates if the hook has no rules.

```
        \__hook_log_line:x { Rules: }
```

```
        \bool_set_true:N \l__hook_tmpa_bool
        \__hook_list_rules:nn {#1}
          {
            \bool_set_false:N \l__hook_tmpa_bool
            \__hook_log_line_indent:x
              {
                ##2~ with~
                \str_if_eq:nnT {##3} {??} { default~ }
                relation~ ##1
              }
          }
        \bool_if:NT \l__hook_tmpa_bool
          { \__hook_log_line_indent:x { --- } }
```

When the hook is declared (that is, the sorting algorithm is applied to that hook) and not empty

```
        \bool_lazy_and:nnTF
            { \__hook_if_usable_p:n {#1} }
            { ! \hook_if_empty_p:n {#1} }
          {
            \__hook_log_line:x
              {
                Execution~order
                \bool_if:NTF \l__hook_tmpa_bool
                  { \__hook_if_reversed:nT {#1} { ~(after~reversal) } }
                  { ~(after~
                    \__hook_if_reversed:nT {#1} { reversal~and~ }
                    applying~rules)
                  } :
              }
            #2 % \tl_show:n
              {
                \@spaces
                \clist_if_empty:cTF { g__hook_#1_labels_clist }
                  { --- }
                  { \clist_use:cn {g__hook_#1_labels_clist} { ,~ } }
              }
          }
          {
            \__hook_log_line:x { Execution~order: }
            #2
              {
                \@spaces Not~set~because~the~hook~ \__hook_if_usable:nTF {#1}
                  { code~pool~is~empty }
                  { is~\__hook_if_disabled:nTF {#1} {disabled} {undeclared} }
              }
          }
      }
  }
```

To display the code for next invocation only (i.e., from `\AddToHookNext` we have to remove the first two tokens at the front which are `\tl_gclear:N` and the token list to clear.

```
\cs_new:Npn \__hook_log_next_code:n #1
```

`\__hook_log_next_code:n`

```
  { \exp_args:No \tl_to_str:n { \use_none:nn #1 } }
```

(*End definition for* `\hook_show:n` *and others. These functions are documented on page* 193.)

`\__hook_list_rules:nn`
`\__hook_list_one_rule:nnn`
`\__hook_list_if_rule_exists:nnnF`

This macro takes a ⟨*hook*⟩ and an ⟨*inline function*⟩ and loops through each pair of ⟨*labels*⟩ in the ⟨*hook*⟩, and if there is a relation between this pair of ⟨*labels*⟩, the ⟨*inline function*⟩ is executed with `#1` = ⟨*relation*⟩, `#2` = ⟨*label*$_1$⟩ | ⟨*label*$_2$⟩, and `#3` = ⟨*hook*⟩ (the latter may be the argument `#1` to `\__hook_list_rules:nn`, or `??` if it is a default rule).

```
\cs_new_protected:Npn \__hook_list_rules:nn #1 #2
  {
    \cs_set_protected:Npn \__hook_tmp:w ##1 ##2 ##3 {#2}
    \prop_map_inline:cn { g__hook_#1_code_prop }
      {
        \prop_map_inline:cn { g__hook_#1_code_prop }
          {
            \__hook_if_label_case:nnnnn {##1} {####1}
              { \prop_map_break: }
              { \__hook_list_one_rule:nnn {##1} {####1} }
              { \__hook_list_one_rule:nnn {####1} {##1} }
                  {#1}
          }
      }
  }
```

These two are quite similar to `\__hook_apply_label_pair:nnn` and `\__hook_label_if_exist_apply:nnnF`, respectively, but rather than applying the rule, they pass it to the ⟨*inline function*⟩.

```
\cs_new_protected:Npn \__hook_list_one_rule:nnn #1#2#3
  {
    \__hook_list_if_rule_exists:nnnF {#1} {#2} {#3}
      { \__hook_list_if_rule_exists:nnnF {#1} {#2} { ?? } { } }
  }
\cs_new_protected:Npn \__hook_list_if_rule_exists:nnnF #1#2#3
  {
    \if_cs_exist:w g__hook_ #3 _rule_ #1 | #2 _tl \cs_end:
      \exp_args:Nv \__hook_tmp:w
        { g__hook_ #3 _rule_ #1 | #2 _tl } { #1 | #2 } {#3}
      \exp_after:wN \use_none:nn
    \fi:
    \use:n
  }
```

(*End definition for* `\__hook_list_rules:nn`, `\__hook_list_one_rule:nnn`, *and* `\__hook_list_if_rule_exists:nnnF`.)

`\__hook_debug_print_rules:n`

A shorthand for debugging that prints similar to `\prop_show:N`.

```
\cs_new_protected:Npn \__hook_debug_print_rules:n #1
  {
    \iow_term:n { The~hook~#1~contains~the~rules: }
    \cs_set_protected:Npn \__hook_tmp:w ##1
      {
        \__hook_list_rules:nn {#1}
          {
            \iow_term:x
              {
```

```
                > ##1 {####2} ##1 => ##1 {####1}
                \str_if_eq:nnT {####3} {??} { ~(default) }
              }
          }
      }
    \exp_args:No \__hook_tmp:w { \use:nn { ~ } { ~ } }
  }
```

(*End definition for* `\__hook_debug_print_rules:n`.)

4.8 Specifying code for next invocation

`\hook_gput_next_code:nn`

```
\cs_new_protected:Npn \hook_gput_next_code:nn #1
  { \__hook_normalize_hook_args:Nn \__hook_gput_next_code:nn {#1} }
```

(*End definition for* `\hook_gput_next_code:nn`. *This function is documented on page* 192.)

`\__hook_gput_next_code:nn`
`\__hook_gput_next_do:nn`
`\__hook_gput_next_do:Nnn`

```
\cs_new_protected:Npn \__hook_gput_next_code:nn #1 #2
  {
    \__hook_if_disabled:nTF {#1}
      { \msg_error:nnn { hooks } { hook-disabled } {#1} }
      {
        \__hook_if_structure_exist:nTF {#1}
          { \__hook_gput_next_do:nn {#1} {#2} }
          { \__hook_try_declaring_generic_next_hook:nn {#1} {#2} }
      }
  }
```

```
\cs_new_protected:Npn \__hook_gput_next_do:nn #1
  {
    \exp_args:Nc \__hook_gput_next_do:Nnn
      { __hook_next~#1 } {#1}
  }
```

First check if the "next code" token list is empty: if so we need to add a `\tl_gclear:c` to clear it, so the code lasts for one usage only. The token list is cleared early so that nested usages don't get lost. `\tl_gclear:c` is used instead of `\tl_gclear:N` in case the hook is used in an expansion-only context, so the token list doesn't expand before `\tl_gclear:N`: that would make an infinite loop. Also in case the main code token list is empty, the hook code has to be updated to add the next execution token list.

```
\cs_new_protected:Npn \__hook_gput_next_do:Nnn #1 #2
  {
    \tl_if_empty:cT { __hook~#2 }
      { \__hook_update_hook_code:n {#2} }
    \tl_if_empty:NT #1
      { \__hook_tl_gset:Nn #1 { \__hook_clear_next:n {#2} } }
    \__hook_tl_gput_right:Nn #1
  }
```

(*End definition for* `\__hook_gput_next_code:nn`, `\__hook_gput_next_do:nn`, *and* `\__hook_gput_next_do:Nnn`.)

\hook_gclear_next_code:n
__hook_clear_next:n

Discard anything set up for next invocation of the hook.

```
\cs_new_protected:Npn \hook_gclear_next_code:n #1
  { \__hook_normalize_hook_args:Nn \__hook_clear_next:n {#1} }
\cs_new_protected:Npn \__hook_clear_next:n #1
  { \cs_gset_eq:cN { __hook_next~#1 } \c_empty_tl }
```

(*End definition for* `\hook_gclear_next_code:n` *and* `\__hook_clear_next:n`*. This function is documented on page* 192.)

4.9 Using the hook

\hook_use:n
__hook_use_initialized:n
__hook_use_undefined:w
__hook_use_end:
__hook_preamble_hook:n

`\hook_use:n` as defined here is used in the preamble, where hooks aren't initialized by default. `\__hook_use_initialized:n` is also defined, which is the non-`\protected` version for use within the document. Their definition is identical, except for the `\__hook_preamble_hook:n` (which wouldn't hurt in the expandable version, but it would be an unnecessary extra expansion).

`\__hook_use_initialized:n` holds the expandable definition while in the preamble. `\__hook_preamble_hook:n` initializes the hook in the preamble, and is redefined to `\use_none:n` at `\begin{document}`.

Both versions do the same thing internally: they check that the hook exists as given, and if so they use it as quickly as possible.

At `\begin{document}`, all hooks are initialized, and any change in them causes an update, so `\hook_use:n` can be made expandable. This one is better not protected so that it can expand into nothing if containing no code. Also important in case of generic hooks that we do not generate a `\relax` as a side effect of checking for a csname. In contrast to the TEX low-level `\csname ...\endcsname` construct `\tl_if_exist:c` is careful to avoid this.

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\hook_use:n}
⟨latexrelease⟩                    {Standardise~generic~hook~names}
\cs_new_protected:Npn \hook_use:n #1
  {
    \tl_if_exist:cT { __hook~#1 }
      {
        \__hook_preamble_hook:n {#1}
        \cs:w __hook~#1 \cs_end:
      }
  }
\cs_new:Npn \__hook_use_initialized:n #1
  {
    \if_cs_exist:w __hook~#1 \cs_end:
      \cs:w __hook~#1 \exp_after:wN \cs_end:
    \fi:
  }
\cs_new_protected:Npn \__hook_preamble_hook:n #1
  { \__hook_initialize_hook_code:n {#1} }
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\hook_use:n}
⟨latexrelease⟩                    {Standardise~generic~hook~names}
⟨latexrelease⟩\cs_new_protected:Npn \hook_use:n #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \tl_if_exist:cTF { __hook~#1 }
⟨latexrelease⟩      {
```

```
⟨latexrelease⟩        \__hook_preamble_hook:n {#1}
⟨latexrelease⟩        \cs:w __hook~#1 \cs_end:
⟨latexrelease⟩      }
⟨latexrelease⟩      { \__hook_use:wn #1 / \s__hook_mark {#1} }
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new:Npn \__hook_use_initialized:n #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \if_cs_exist:w __hook~#1 \cs_end:
⟨latexrelease⟩    \else:
⟨latexrelease⟩      \__hook_use_undefined:w
⟨latexrelease⟩    \fi:
⟨latexrelease⟩    \cs:w __hook~#1 \__hook_use_end:
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new:Npn \__hook_use_undefined:w #1 #2 __hook~#3 \__hook_use_end:
⟨latexrelease⟩  {
⟨latexrelease⟩    #1 % fi
⟨latexrelease⟩    \__hook_use:wn #3 / \s__hook_mark {#3}
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new_protected:Npn \__hook_preamble_hook:n #1
⟨latexrelease⟩  { \__hook_initialize_hook_code:n {#1} }
⟨latexrelease⟩\cs_new_eq:NN \__hook_use_end: \cs_end:
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\hook_use:n` *and others. This function is documented on page* 192.)

`\__hook_use:wn`
`\__hook_try_file_hook:n`
`\__hook_if_usable_use:n`

`\__hook_use:wn` does a quick check to test if the current hook is a file hook: those need a special treatment. If it is not, the hook does not exist. If it is, then `\__hook_try_file_hook:n` is called, and checks that the current hook is a file-specific hook using `\__hook_if_file_hook:wTF`. If it's not, then it's a generic `file/` hook and is used if it exist.

If it is a file-specific hook, it passes through the same normalization as during declaration, and then it is used if defined. `\__hook_if_usable_use:n` checks if the hook exist, and calls `\__hook_preamble_hook:n` if so, then uses the hook.

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__hook_use:wn}
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\__hook_use:wn}
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\cs_new:Npn \__hook_use:wn #1 / #2 \s__hook_mark #3
⟨latexrelease⟩  {
⟨latexrelease⟩    \str_if_eq:nnTF {#1} { file }
⟨latexrelease⟩      { \__hook_try_file_hook:n {#3} }
⟨latexrelease⟩      { } % Hook doesn't exist
⟨latexrelease⟩  }
```

```
⟨latexrelease⟩\cs_new_protected:Npn \__hook_try_file_hook:n #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \__hook_if_file_hook:wTF #1 / \s__hook_mark
⟨latexrelease⟩      {
⟨latexrelease⟩        \exp_args:Ne \__hook_if_usable_use:n
⟨latexrelease⟩          { \exp_args:Ne \__hook_file_hook_normalize:n {#1} }
⟨latexrelease⟩      }
⟨latexrelease⟩      { \__hook_if_usable_use:n {#1} } % file/ generic hook (e.g. file/before)
⟨latexrelease⟩  }
```

```
⟨latexrelease⟩\cs_new_protected:Npn \__hook_if_usable_use:n #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \tl_if_exist:cT { __hook~#1 }
⟨latexrelease⟩      {
⟨latexrelease⟩        \__hook_preamble_hook:n {#1}
⟨latexrelease⟩        \cs:w __hook~#1 \cs_end:
⟨latexrelease⟩      }
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\__hook_use:wn`, `\__hook_try_file_hook:n`, *and* `\__hook_if_usable_use:n`.)

`\hook_use_once:n`
`\__hook_use_once:n`

For hooks that can and should be used only once we have a special use command that further inhibits the hook from getting more code added to it. This has the effect that any further code added to the hook is executed immediately rather than stored in the hook.

The code needs some gymnastics to prevent space trimming from the hook name, since `\hook_use:n` and `\hook_use_once:n` are documented to not trim spaces.

```
\cs_new_protected:Npn \hook_use_once:n #1
  {
    \__hook_if_execute_immediately:nF {#1}
      { \__hook_normalize_hook_args:Nn \__hook_use_once:n { \use:n {#1} } }
  }
\cs_new_protected:Npn \__hook_use_once:n #1
  {
    \__hook_preamble_hook:n {#1}
    \__hook_use_once_set:n {#1}
    \__hook_use_initialized:n {#1}
    \__hook_use_once_clear:n {#1}
  }
```

`\__hook_use_once_set:n`
`\__hook_use_once_clear:n`

`\__hook_use_once_set:n` is used before the actual hook code is executed so that any usage of `\AddToHook` inside the hook causes the code to execute immediately. Setting `\g__hook_`⟨*hook*⟩`_reversed_tl` to `I` prevents further code from being added to the hook. `\__hook_use_once_clear:n` then clears the hook so that any further call to `\hook_use:n` or `\hook_use_once:n` will expand to nothing.

```
\cs_new_protected:Npn \__hook_use_once_set:n #1
  { \__hook_tl_gset:cn { g__hook_#1_reversed_tl } { I } }
\cs_new_protected:Npn \__hook_use_once_clear:n #1
  {
    \__hook_tl_gclear:c { __hook~#1 }
    \__hook_tl_gclear:c { __hook_next~#1 }
    \__hook_tl_gclear:c { __hook_toplevel~#1 }
    \prop_gclear_new:c { g__hook_#1_code_prop }
  }
```

(*End definition for* `\hook_use_once:n` *and others. This function is documented on page* 192.)

`\__hook_if_execute_immediately_p:n`
`\__hook_if_execute_immediately:nTF`

To check whether the code being added should be executed immediately (that is, if the hook is a one-time hook), we check if it's usable (it can't be one-time if it was not already usable), then we check that `\g__hook_`⟨*hook*⟩`_reversed_tl` is `I`. The gymnastics around `\if:w` is there to allow the `reversed` token list to be empty.

```
\prg_new_conditional:Npnn \__hook_if_execute_immediately:n #1 { T, F, TF }
```

```
{
  \__hook_if_usable:nTF {#1}
    {
      \exp_after:wN \__hook_clean_to_scan:w
      \if:w I \cs:w g__hook_#1_reversed_tl \cs_end:
        \s__hook_mark \prg_return_true:
      \else:
        \s__hook_mark \prg_return_false:
      \fi:
    }
    { \prg_return_false: }
}
```

(*End definition for* `\__hook_if_execute_immediately:nTF`.)

4.10 Querying a hook

Simpler data types, like token lists, have three possible states; they can exist and be empty, exist and be non-empty, and they may not exist, in which case emptiness doesn't apply (though `\tl_if_empty:N` returns false in this case).

Hooks are a bit more complicated: they have several other states as discussed in 4.4.2. A hook may exist or not, and either way it may or may not be empty (even a hook that doesn't exist may be non-empty) or may be disabled.

A hook is said to be empty when no code was added to it, either to its permanent code pool, or to its "next" token list. The hook doesn't need to be declared to have code added to its code pool (it may happen that a package A defines a hook `foo`, but it's loaded after package B, which adds some code to that hook. In this case it is important that the code added by package B is remembered until package A is loaded).

All other states can only be queried with internal tests as the different states are irrelevant for package code.

`\hook_if_empty_p:n`
`\hook_if_empty:nTF`

Test if a hook is empty (that is, no code was added to that hook). A ⟨*hook*⟩ being empty means that all three of its `\g__hook_`⟨*hook*⟩`_code_prop`, its `\__hook_toplevel␣`⟨*hook*⟩ and its `\__hook_next␣`⟨*hook*⟩ are empty.

```
\prg_new_conditional:Npnn \hook_if_empty:n #1 { p , T , F , TF }
  {
    \__hook_if_structure_exist:nTF {#1}
      {
        \bool_lazy_and:nnTF
            { \prop_if_empty_p:c { g__hook_#1_code_prop } }
            {
              \bool_lazy_and_p:nn
                { \tl_if_empty_p:c { __hook_toplevel~#1 } }
                { \tl_if_empty_p:c { __hook_next~#1 } }
            }
          { \prg_return_true: }
          { \prg_return_false: }
      }
      { \prg_return_true: }
  }
```

(*End definition for* `\hook_if_empty:nTF`. *This function is documented on page* 193.)

__hook_if_usable_p:n
__hook_if_usable:nTF

A hook is usable if the token list that stores the sorted code for that hook, __hook ⟨hook⟩, exists. The property list \g__hook_⟨hook⟩_code_prop cannot be used here because often it is necessary to add code to a hook without knowing if such hook was already declared, or even if it will ever be (for example, in case the package that defines it isn't loaded).

```
\prg_new_conditional:Npnn \__hook_if_usable:n #1 { p , T , F , TF }
  {
    \tl_if_exist:cTF { __hook~#1 }
      { \prg_return_true: }
      { \prg_return_false: }
  }
```

(*End definition for* __hook_if_usable:nTF.)

__hook_if_structure_exist_p:n
__hook_if_structure_exist:nTF

An internal check if the hook has already its basic internal structure set up with __hook_init_structure:n. This means that the hook was already used somehow (a code chunk or rule was added to it), but it still wasn't declared with \hook_new:n.

```
\prg_new_conditional:Npnn \__hook_if_structure_exist:n #1 { p , T , F , TF }
  {
    \prop_if_exist:cTF { g__hook_#1_code_prop }
      { \prg_return_true: }
      { \prg_return_false: }
  }
```

(*End definition for* __hook_if_structure_exist:nTF.)

__hook_if_declared_p:n
__hook_if_declared:nTF

Internal test to check if the hook was officially declared with \hook_new:n or a variant.

```
\prg_new_conditional:Npnn \__hook_if_declared:n #1 { p, T, F, TF }
  {
    \tl_if_exist:cTF { g__hook_#1_declared_tl }
      { \prg_return_true: }
      { \prg_return_false: }
  }
```

(*End definition for* __hook_if_declared:nTF.)

__hook_if_reversed_p:n
__hook_if_reversed:nTF

An internal conditional that checks if a hook is reversed.

```
\prg_new_conditional:Npnn \__hook_if_reversed:n #1 { p , T , F , TF }
  {
    \exp_after:wN \__hook_clean_to_scan:w
    \if:w - \cs:w g__hook_#1_reversed_tl \cs_end:
      \s__hook_mark \prg_return_true:
    \else:
      \s__hook_mark \prg_return_false:
    \fi:
  }
```

(*End definition for* __hook_if_reversed:nTF.)

__hook_if_generic_p:n
__hook_if_generic:nTF
__hook_if_deprecated_generic_p:n
__hook_if_deprecated_generic:nTF

An internal conditional that checks if a name belongs to a generic hook. The deprecated version needs to check if #3 is empty to avoid returning true on file/before, for example.

```
\prg_new_conditional:Npnn \__hook_if_generic:n #1 { T, TF }
  { \__hook_if_generic:w #1 / / / \s__hook_mark }
\cs_new:Npn \__hook_if_generic:w #1 / #2 / #3 / #4 \s__hook_mark
```

```
  {
    \cs_if_exist:cTF { c__hook_generic_#1/./#3_tl }
      { \prg_return_true: }
      { \prg_return_false: }
  }
\prg_new_conditional:Npnn \__hook_if_deprecated_generic:n #1 { T, TF }
  { \__hook_if_deprecated_generic:w #1 / / / \s__hook_mark }
\cs_new:Npn \__hook_if_deprecated_generic:w #1 / #2 / #3 / #4 \s__hook_mark
  {
    \cs_if_exist:cTF { c__hook_deprecated_#1/./#2_tl }
      {
        \tl_if_empty:nTF {#3}
          { \prg_return_false: }
          { \prg_return_true: }
      }
      { \prg_return_false: }
  }
```

(*End definition for* `\__hook_if_generic:nTF` *and* `\__hook_if_deprecated_generic:nTF`.)

`\__hook_if_generic_reversed_p:n`
`\__hook_if_generic_reversed:nTF`

An internal conditional that checks if a name belongs to a generic reversed hook.

```
\prg_new_conditional:Npnn \__hook_if_generic_reversed:n #1 { T }
  { \__hook_if_generic_reversed:w #1 / / / \scan_stop: }
\cs_new:Npn \__hook_if_generic_reversed:w #1 / #2 / #3 / #4 \scan_stop:
  {
    \if_charcode:w - \cs:w c__hook_generic_#1/./#3_tl \cs_end:
      \prg_return_true:
    \else:
      \prg_return_false:
    \fi:
  }
```

(*End definition for* `\__hook_if_generic_reversed:nTF`.)

4.11 Messages

Hook errors are LaTeX kernel errors:

```
\prop_gput:Nnn \g_msg_module_type_prop { hooks } { LaTeX }
```

And so are kernel errors (this should move elsewhere eventually).

```
\prop_gput:Nnn \g_msg_module_type_prop { latex2e } { LaTeX }
\prop_gput:Nnn \g_msg_module_name_prop { latex2e } { kernel }
```

```
\msg_new:nnnn { hooks } { labels-incompatible }
  {
    Labels~'#1'~and~'#2'~are~incompatible
    \str_if_eq:nnF {#3} {??} { ~in~hook~'#3' } .~
    \int_compare:nNnTF {#4} = { 1 }
      { The~ code~ for~ both~ labels~ will~ be~ dropped. }
      { You~ may~ see~ errors~ later. }
  }
  { LaTeX~found~two~incompatible~labels~in~the~same~hook.~
    This~indicates~an~incompatibility~between~packages.  }
```

```
\msg_new:nnnn { hooks } { exists }
    { Hook~'#1'~ has~ already~ been~ declared. }
    { There~ already~ exists~ a~ hook~ declaration~ with~ this~
      name.\\
      Please~ use~ a~ different~ name~ for~ your~ hook.}
\msg_new:nnnn { hooks } { hook-disabled }
  { Cannot~add~code~to~disabled~hook~'#1'. }
  {
    The~hook~'#1'~you~tried~to~add~code~to~was~previously~disabled~
    with~\iow_char:N\\hook_disable_generic:n~or~\iow_char:N\\DisableGenericHook,~so~
    it~cannot~have~code~added~to~it.
  }
\msg_new:nnn { hooks } { empty-label }
  {
    Empty~code~label~\msg_line_context:.~
    Using~'\__hook_currname_or_default:'~instead.
  }
\msg_new:nnn { hooks } { no-default-label }
  {
    Missing~(empty)~default~label~\msg_line_context:. \\
    This~command~was~ignored.
  }
\msg_new:nnnn { hooks } { unknown-rule }
  {
    Unknown~ relationship~ '#3'~
    between~ labels~ '#2'~ and~ '#4'~
    \str_if_eq:nnF {#1} {??} { ~in~hook~'#1' }. ~
    Perhaps~ a~ misspelling?
  }
  {
    The~ relation~ used~ not~ known~ to~ the~ system.~ Allowed~ values~ are~
    'before'~ or~ '<',~
    'after'~ or~ '>',~
    'incompatible-warning',~
    'incompatible-error',~
    'voids'~ or~
    'unrelated'.
  }
\msg_new:nnnn { hooks } { rule-too-late }
  {
    Sorting~rule~for~'#1'~hook~applied~too~late.\\
    Try~setting~this~rule~earlier.
  }
  {
    You~tried~to~set~the~ordering~of~hook~'#1'~using\\
    \ \ \iow_char:N\\DeclareHookRule{#1}{#2}{#3}{#4}\\
    but~hook~'#1'~was~already~used~as~a~one-time~hook,~
    thus~sorting~is\\
    no~longer~possible.~Declare~the~rule~
    before~the~hook~is~used.
  }
\msg_new:nnnn { hooks } { misused-top-level }
```

```
  {
    Illegal~use~of~\iow_char:N \\AddToHook{#1}[top-level]{...}.\\
    'top-level'~is~reserved~for~the~user's~document.
  }
  {
    The~'top-level'~label~is~meant~for~user~code~only,~and~should~only~
    be~used~(sparingly)~in~the~main~document.~Use~the~default~label~
    '\__hook_currname_or_default:'~for~this~\@cls@pkg,~or~another~
    suitable~label.
  }
\msg_new:nnn { hooks } { set-top-level }
  {
    You~cannot~change~the~default~label~#1~'top-level'.~Illegal \\
    \use:nn { ~ } { ~ } \iow_char:N \\#2{#3} \\
    \msg_line_context:.
  }
\msg_new:nnn { hooks } { extra-pop-label }
  {
    Extra~\iow_char:N \\PopDefaultHookLabel. \\
    This~command~will~be~ignored.
  }
\msg_new:nnn { hooks } { missing-pop-label }
  {
    Missing~\iow_char:N \\PopDefaultHookLabel. \\
    The~label~'#1'~was~pushed~but~never~popped.~Something~is~wrong.
  }
\msg_new:nnn { latex2e } { should-not-happen }
  {
    This~should~not~happen.~#1 \\
    Please~report~at~https://github.com/latex3/latex2e.
  }
\msg_new:nnn { hooks } { activate-disabled }
  {
    Cannot~ activate~ hook~ '#1'~ because~ it~ is~ disabled!
  }
\msg_new:nnn { hooks } { cannot-remove }
  {
    Cannot~remove~chunk~'#2'~from~hook~'#1'~because~
    \__hook_if_structure_exist:nTF {#1}
      { it~does~not~exist~in~that~hook. }
      { the~hook~does~not~exist. }
  }
\msg_new:nnn { hooks } { generic-deprecated }
  {
    Generic~hook~'#1/#2/#3'~is~deprecated. \\
    Use~hook~'#1/#3/#2'~instead.
  }
```

4.12 LaTeX 2_ε package interface commands

\NewHook
\NewReversedHook
\NewMirroredHookPair

Declaring new hooks ...

```
\NewDocumentCommand \NewHook             { m }{ \hook_new:n {#1} }
\NewDocumentCommand \NewReversedHook     { m }{ \hook_new_reversed:n {#1} }
\NewDocumentCommand \NewMirroredHookPair { mm }{ \hook_new_pair:nn {#1}{#2} }
```

(*End definition for* `\NewHook`, `\NewReversedHook`, *and* `\NewMirroredHookPair`. *These functions are documented on page* 181.)

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩          {\hook_activate_generic:n}{Providing~hooks}
```

`\ActivateGenericHook` Providing new hooks . . .

```
\NewDocumentCommand \ActivateGenericHook { m }{ \hook_activate_generic:n {#1} }
```

(*End definition for* `\ActivateGenericHook`. *This function is documented on page* 182.)

`\DisableGenericHook` Disabling a generic hook.

```
\NewDocumentCommand \DisableGenericHook { m }{ \hook_disable_generic:n {#1} }
```

(*End definition for* `\DisableGenericHook`. *This function is documented on page* 182.)

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}
⟨latexrelease⟩                  {\hook_activate_generic:n}{Providing~hooks}
⟨latexrelease⟩
⟨latexrelease⟩\def \ActivateGenericHook#1{}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

`\AddToHook`

```
\NewDocumentCommand \AddToHook { m o +m }
  { \hook_gput_code:nnn {#1} {#2} {#3} }
```

(*End definition for* `\AddToHook`. *This function is documented on page* 183.)

`\AddToHookNext`

```
\NewDocumentCommand \AddToHookNext { m +m }
  { \hook_gput_next_code:nn {#1} {#2} }
```

(*End definition for* `\AddToHookNext`. *This function is documented on page* 185.)

`\ClearHookNext`

```
\NewDocumentCommand \ClearHookNext { m }
  { \hook_gclear_next_code:n {#1} }
```

(*End definition for* `\ClearHookNext`. *This function is documented on page* 185.)

`\RemoveFromHook`

```
\NewDocumentCommand \RemoveFromHook { m o }
  { \hook_gremove_code:nn {#1} {#2} }
```

(*End definition for* `\RemoveFromHook`. *This function is documented on page* 184.)

\SetDefaultHookLabel
\PushDefaultHookLabel
\PopDefaultHookLabel

Now define a wrapper that replaces the top of the stack with the argument, and updates \g__hook_hook_curr_name_tl accordingly.

```
\NewDocumentCommand \SetDefaultHookLabel { m }
  { \__hook_set_default_hook_label:n {#1} }
%
%   The label is only automatically updated with \cs{@onefilewithoptions}
%   (\cs{usepackage} and \cs{documentclass}), but some packages, like
%   Ti\emph{k}Z, define package-like interfaces, like
%   \cs{usetikzlibrary} that are wrappers around \cs{input}, so they
%   inherit the default label currently in force (usually |top-level|,
%   but it may change if loaded in another package).  To provide a
%   package-like behavior also for hooks in these files, we provide
%   high-level access to the default label stack.
%    \begin{macrocode}
\NewDocumentCommand \PushDefaultHookLabel { m }
  { \__hook_curr_name_push:n {#1} }
\NewDocumentCommand \PopDefaultHookLabel { }
  { \__hook_curr_name_pop: }
```

The current label stack holds the labels for all files but the current one (more or less like \@currnamestack), and the current label token list, \g__hook_hook_curr_name_tl, holds the label for the current file. However \@pushfilename happens before \@currname is set, so we need to look ahead to get the \@currname for the label. expl3 also requires the current file in \@pushfilename, so here we abuse \@expl@push@filename@aux@@ to do __hook_curr_name_push:n.

```
\cs_gset_protected:Npn \@expl@push@filename@aux@@ #1#2#3
  {
    \__hook_curr_name_push:n {#3}
    \str_gset:Nx \g_file_curr_name_str {#3}
    #1 #2 {#3}
  }
```

(*End definition for* \SetDefaultHookLabel*,* \PushDefaultHookLabel*, and* \PopDefaultHookLabel*. These functions are documented on page* 187.)

\UseHook
\UseOneTimeHook

Avoid the overhead of xparse and its protection that we don't want here (since the hook should vanish without trace if empty)!

```
\cs_new:Npn \UseHook        { \hook_use:n }
\cs_new:Npn \UseOneTimeHook { \hook_use_once:n }
```

(*End definition for* \UseHook *and* \UseOneTimeHook*. These functions are documented on page* 182.)

\ShowHook
\LogHook

```
\cs_new_protected:Npn \ShowHook { \hook_show:n }
\cs_new_protected:Npn \LogHook { \hook_log:n }
```

(*End definition for* \ShowHook *and* \LogHook*. These functions are documented on page* 190.)

\DebugHooksOn
\DebugHooksOff

```
\cs_new_protected:Npn \DebugHooksOn  { \hook_debug_on:  }
\cs_new_protected:Npn \DebugHooksOff { \hook_debug_off: }
```

(*End definition for* \DebugHooksOn *and* \DebugHooksOff*. These functions are documented on page* 191.)

\DeclareHookRule

```
\NewDocumentCommand \DeclareHookRule { m m m m }
                    { \hook_gset_rule:nnnn {#1}{#2}{#3}{#4} }
```

(*End definition for* `\DeclareHookRule`. *This function is documented on page* 188.)

\DeclareDefaultHookRule

This declaration is only supported before `\begin{document}`.

```
\NewDocumentCommand \DeclareDefaultHookRule { m m m }
                    { \hook_gset_rule:nnnn {??}{#1}{#2}{#3} }
\@onlypreamble\DeclareDefaultHookRule
```

(*End definition for* `\DeclareDefaultHookRule`. *This function is documented on page* 189.)

\ClearHookRule

A special setup rule that removes an existing relation. Basically @@_rule_gclear:nnn plus fixing the property list for debugging.

FMi: Needs perhaps an L3 interface, or maybe it should get dropped?

```
\NewDocumentCommand \ClearHookRule { m m m }
{ \hook_gset_rule:nnnn {#1}{#2}{unrelated}{#3} }
```

(*End definition for* `\ClearHookRule`. *This function is documented on page* 189.)

\IfHookEmptyTF

Here we avoid the overhead of xparse, since `\IfHookEmptyTF` is used in `\end` (that is, every LaTeX environment). As a further optimization, use `\let` rather than `\def` to avoid one expansion step.

```
\cs_new_eq:NN \IfHookEmptyTF \hook_if_empty:nTF
```

(*End definition for* `\IfHookEmptyTF`. *This function is documented on page* 189.)

\IfHookExistsTF

Marked for removal and no longer documented in the doc section!

PhO: `\IfHookExistsTF` *is used in* `jlreq.cls`, `pxatbegshi.sty`, `pxeverysel.sty`, `pxeveryshi.sty`, *so the public name may be an alias of the internal conditional for a while. Regardless, those packages' use for* `\IfHookExistsTF` *is not really correct and can be changed.*

```
\cs_new_eq:NN \IfHookExistsTF \__hook_if_usable:nTF
```

(*End definition for* `\IfHookExistsTF`.)

4.13 Deprecated that needs cleanup at some point

\hook_disable:n
\hook_provide:n
\hook_provide_reversed:n
\hook_provide_pair:nn
__hook_activate_generic_reversed:n
__hook_activate_generic_pair:nn

Deprecated.

```
\cs_new_protected:Npn \hook_disable:n
  {
    \__hook_deprecated_warn:nn
      { hook_disable:n }
      { hook_disable_generic:n }
    \hook_disable_generic:n
  }
\cs_new_protected:Npn \hook_provide:n
  {
    \__hook_deprecated_warn:nn
      { hook_provide:n }
      { hook_activate_generic:n }
    \hook_activate_generic:n
  }
```

```
\cs_new_protected:Npn \hook_provide_reversed:n
  {
    \__hook_deprecated_warn:nn
      { hook_provide_reversed:n }
      { hook_activate_generic:n }
    \__hook_activate_generic_reversed:n
  }
\cs_new_protected:Npn \hook_provide_pair:nn
  {
    \__hook_deprecated_warn:nn
      { hook_provide_pair:nn }
      { hook_activate_generic:n }
    \__hook_activate_generic_pair:nn
  }
\cs_new_protected:Npn \__hook_activate_generic_reversed:n #1
  { \__hook_normalize_hook_args:Nn \__hook_activate_generic:nn {#1} { - } }
\cs_new_protected:Npn \__hook_activate_generic_pair:nn #1#2
  { \hook_activate_generic:n {#1} \__hook_activate_generic_reversed:n {#2} }
```

(*End definition for* `\hook_disable:n` *and others.*)

`\DisableHook`
`\ProvideHook`
`\ProvideReversedHook`
`\ProvideMirroredHookPair`

Deprecated.

```
\cs_new_protected:Npn \DisableHook
  {
    \__hook_deprecated_warn:nn
      { DisableHook }
      { DisableGenericHook }
    \hook_disable_generic:n
  }
\cs_new_protected:Npn \ProvideHook
  {
    \__hook_deprecated_warn:nn
      { ProvideHook }
      { ActivateGenericHook }
    \hook_activate_generic:n
  }
\cs_new_protected:Npn \ProvideReversedHook
  {
    \__hook_deprecated_warn:nn
      { ProvideReversedHook }
      { ActivateGenericHook }
    \__hook_activate_generic_reversed:n
  }
\cs_new_protected:Npn \ProvideMirroredHookPair
  {
    \__hook_deprecated_warn:nn
      { ProvideMirroredHookPair }
      { ActivateGenericHook }
    \__hook_activate_generic_pair:nn
  }
```

(*End definition for* `\DisableHook` *and others.*)

`\__hook_deprecated_warn:nn`

Warns about a deprecation, telling what should be used instead.

```
\cs_new_protected:Npn \__hook_deprecated_warn:nn #1 #2
  { \msg_warning:nnnn { hooks } { deprecated } {#1} {#2} }
\msg_new:nnn { hooks } { deprecated }
  {
    Command~\iow_char:N\\#1~is~deprecated~and~will~be~removed~in~a~
    future~release. \\ \\
    Use~\iow_char:N\\#2~instead.
  }
```

(*End definition for* `\__hook_deprecated_warn:nn`.)

4.14 Internal commands needed elsewhere

Here we set up a few horrible (but consistent) LaTeX 2_ε names to allow for internal commands to be used outside this module. We have to unset the `@@` since we want double "at" sign in place of double underscores.

```
⟨@@=⟩
```

`\@expl@@@initialize@all@@`
`\@expl@@@hook@curr@name@pop@@`

```
\cs_new_eq:NN \@expl@@@initialize@all@@
              \__hook_initialize_all:
\cs_new_eq:NN \@expl@@@hook@curr@name@pop@@
              \__hook_curr_name_pop:
```

(*End definition for* `\@expl@@@initialize@all@@` *and* `\@expl@@@hook@curr@name@pop@@`.)

Rolling back here doesn't undefine the interface commands as they may be used in packages without rollback functionality. So we just make them do nothing which may or may not work depending on the code usage.

```
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {lthooks}{The~hook~management}%
⟨latexrelease⟩
⟨latexrelease⟩\def \NewHook#1{}
⟨latexrelease⟩\def \NewReversedHook#1{}
⟨latexrelease⟩\def \NewMirroredHookPair#1#2{}
⟨latexrelease⟩
⟨latexrelease⟩\def \DisableGenericHook #1{}
⟨latexrelease⟩
⟨latexrelease⟩\long\def\AddToHookNext#1#2{}
⟨latexrelease⟩
⟨latexrelease⟩\def\AddToHook#1{\@gobble@AddToHook@args}
⟨latexrelease⟩\providecommand\@gobble@AddToHook@args[2][]{}
⟨latexrelease⟩
⟨latexrelease⟩\def\RemoveFromHook#1{\@gobble@RemoveFromHook@arg}
⟨latexrelease⟩\providecommand\@gobble@RemoveFromHook@arg[1][]{}
⟨latexrelease⟩
⟨latexrelease⟩\def \UseHook        #1{}
⟨latexrelease⟩\def \UseOneTimeHook #1{}
⟨latexrelease⟩\def \ShowHook #1{}
⟨latexrelease⟩\let \DebugHooksOn \@empty
⟨latexrelease⟩\let \DebugHooksOff\@empty
⟨latexrelease⟩
⟨latexrelease⟩\def \DeclareHookRule #1#2#3#4{}
```

```
⟨latexrelease⟩\def \DeclareDefaultHookRule #1#2#3{}
⟨latexrelease⟩\def \ClearHookRule #1#2#3{}
```

If the hook management is not provided we make the test for existence false and the test for empty true in the hope that this is most of the time reasonable. If not a package would need to guard against running in an old kernel.

```
⟨latexrelease⟩\long\def \IfHookExistsTF #1#2#3{#3}
⟨latexrelease⟩\long\def \IfHookEmptyTF #1#2#3{#2}
⟨latexrelease⟩
⟨latexrelease⟩\EndModuleRelease
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
```

File i
ltcmdhooks.dtx

1 Introduction

This file implements generic hooks for (arbitrary) commands. In theory every command \⟨*name*⟩ offers now two associated hooks to which code can be added using `\AddToHook` or `\AddToHookNext`.[11] These are

`cmd/`⟨*name*⟩`/before` This hook is executed at the very start of the command execution after its arguments (if any) are parsed. The hook ⟨*code*⟩ is wrapped in the command inside a call to `\UseHook{cmd/`⟨*name*⟩`/before}`, so the arguments passed to the command are *not* available in the hook ⟨*code*⟩.

`cmd/`⟨*name*⟩`/after` This hook is similar to `cmd/`⟨*name*⟩`/before`, but it is executed at the very end of the command body. This hook is implemented as a reversed hook.

The hooks are not physically present before `\begin{document}` (i.e., using a command in the preamble will never execute them) and if nobody has declared any code for them, then they are not added to the command code ever. For example, if we have the following definition

```
\newcommand\foo[2]{Code #1 for #2!}
```

then executing `\foo{A}{B}` will simply run `Code␣A␣for␣B!` as it was always the case. However, if somebody, somewhere (e.g., in a package) adds

```
\AddToHook{cmd/foo/before}{<before code>}
```

then, after `\begin{document}` the definition of `\foo` will be:

```
\renewcommand\foo[2]{\UseHook{cmd/foo/before}Code #1 for #2!}
```

and similarly `\AddToHook{cmd/foo/after}{<after code>}` alters the definition to

```
\renewcommand\foo[2]{Code #1 for #2!\UseHook{cmd/foo/after}}
```

In other words, the mechanism is similar to what `etoolbox` offers with `\pretocmd` and `\apptocmd` with the important differences

- that code can be prepended or appended (i.e., added to the hooks) even if the command itself is not defined, because the defining package has not yet been loaded
- and that by using the hook management interface it is now possible to define how the code chunks added in these places are ordered, if different packages want to add code at these points.

2 Restrictions and Operational details

Adding arbitrary material to commands is tricky because most of the time we do not know what the macro expects as arguments when expanding and TEX doesn't have a reliable way to see that, so some guesswork has to be employed.

[11] In practice this is not supported for all types of commands, see section 2.2 for the restrictions that apply and what happens if one tries to use this with commands for which this is not supported.

2.1 Patching

The code here tries to find out if a command was defined with `\newcommand` or `\DeclareRobustCommand` or `\NewDocumentCommand`, and if so it *assumes* that the argument specification of the command is as expected (which is not fail-proof, if someone redefines the internals of these commands in devious ways, but is a reasonable assumption).

If the command is one of the defined types, the code here does a sandboxed expansion of the command such that it can be redefined again exactly as before, but with the hook code added.

If however the command is not a known type (it was defined with `\def`, for example), then the code uses an approach similar to etoolbox's `\patchcmd` to retokenize the command with the hook code in place. This procedure, however, is more likely to fail if the catcode settings are not the same as the ones at the time of command's definition, so not always adding a hook to a command will work.

2.1.1 Timing

When `\AddToHook` (or its expl3 equivalent) is called with a generic `cmd` hook, say, `cmd/foo/before`, for the first time (that is, no code was added to that same hook before), in the preamble of a document, it will store a patch instruction for that command until `\begin{document}`, and only then all the commands which had hooks added will be patched in one go. That means that no command in the preamble will have hooks patched into them.

At `\begin{document}` all the delayed patches will be executed, and if the command doesn't exist the code is still added to the hook, but it will not be executed. After `\begin{document}`, when `\AddToHook` is called with a generic `cmd` hook the first time, the command will be immediately patched to include the hook, and if it doesn't exist or if it can't be patched for any reason, an error is thrown; if `\AddToHook` was already used in the preamble no new patching is attempted.

This has the consequence that a command defined or redefined after `\begin{document}` only uses generic `cmd` hook code if `\AddToHook` is called for the first time after the definition is made, or if the command explicitly uses the generic hook in its definition by declaring it with `\NewHookPair` adding `\UseHook` as part of the code.[12]

2.2 Commands that look ahead

Some commands are defined in different "steps" and they look ahead in the input stream to find more arguments. If you try to add some code to the `cmd/`⟨*name*⟩`/after` hook of such command, it will not work, and it is not possible to detect that programmatically, so the user has to know (or find out) which commands can or cannot have hooks attached to them.

One good example is the `\section` command. You can add something to the `cmd/section/before` hook, but if you try to add something to the `cmd/section/after` hook, `\section` will no longer work. That happens because the `\section` macro takes no argument, but instead calls a few internal LaTeX macros to look for the optional and mandatory arguments. By adding code to the `cmd/section/after` hook, you get in the way of that scanning.

[12] We might change this behavior in the main document slightly after gaining some usage experience.

3 Package Author Interface

The `cmd` hooks are, by default, available for all commands that can be patched to add the hooks. For some commands, however, the very beginning or the very end of the code is not the best place to put the hooks, for example, if the command looks ahead for arguments (see section 2.2).

If you are a package author and you want to add the hooks to your own commands in the proper position you can define the command and manually add the `\UseHook` calls inside the command in the proper positions, and manually define the hooks with `\NewHook` or `\NewReversedHook`. When the hooks are explicitly defined, patching is not attempted so you can make sure your command works properly. For example, an (admittedly not really useful) command that typesets its contents in a framed box with width optionally given in parentheses:

```
\newcommand\fancybox{\@ifnextchar({\@fancybox}{\@fancybox(5cm)}}
\def\@fancybox(#1)#2{\fbox{\parbox{#1}{#2}}}
```

If you try that definition, then add some code after it with

```
\AddToHook{cmd/fancybox/after}{<code>}
```

and then use the `\fancybox` command you will see that it will be completely broken, because the hook will get executed in the middle of parsing for optional `(...)` argument.

If, on the other hand, you want to add hooks to your command you can do something like:

```
\newcommand\fancybox{\@ifnextchar({\@fancybox}{\@fancybox(5cm)}}
\def\@fancybox(#1)#2{\fbox{%
                      \UseHook{cmd/fancybox/before}%
                      \parbox{#1}{#2}%
                      \UseHook{cmd/fancybox/after}}}
\NewHook{cmd/fancybox/before}
\NewReversedHook{cmd/fancybox/after}
```

then the hooks will be executed where they should and no patching will be attempted. It is important that the hooks are declared with `\NewHook` or `\NewReversedHook`, otherwise the command hook code will try to patch the command. Note also that the call to `\UseHook{cmd/fancybox/before}` does not need to be in the definition of `\fancybox`, but anywhere it makes sense to insert it (in this case in the internal `\@fancybox`).

Alternatively, if for whatever reason your command does not support the generic hooks provided here, you can disable a hook with `\DisableHook`[13], so that when someone tries to add code to it they will get an error. Or if you don't want the error, you can simply declare the hook with `\NewHook` and never use it.

The above approach is useful for really complex commands where for one or the other reason the hooks can't be placed at the very beginning and end of the command body and some hand-crafting is needed. However, in the example above the real (and in fact only) issue is the cascading argument parsing in the style developed long ago in LaTeX 2.09. Thus, a much simpler solution for this case is to replace it with the modern `\NewDocumentCommand` syntax and define the command as follows:

```
\DeclareDocumentCommand\fancybox{D(){5cm}m}{\fbox{\parbox{#1}{#2}}}
```

If you do that then both hooks automatically work and are patched into the right places.

[13] Please use `\DisableHook` if at all, only on hooks that you "own", i.e., for commands that your package or class defines and not second guess whether or not hooks of other packages should get disabled!

4 The Implementation

4.1 Execution plan

To add `before` and `after` hooks to a command we will need to peek into the definition of a command, which is always a tricky thing to do. Some cases are easy because we know how the command was defined, so we can assume how its ⟨*parameter text*⟩ looks like (for example a command defined with `\newcommand` may have an optional argument followed by a run of mandatory arguments), so we can just expand that command and make it grab `#1`, `#2`, etc. as arguments and define it all back with the hooks added.

Life's usually not that easy, so with some commands we can't do that (a `#1` might as well be $\#_{12}1_{12}$ instead of the expected $\#_{6}1_{12}$, for example) so we need to resort to "patching" the command: read its `\meaning`, and tokenize it again with `\scantokens` and hope for the best.

So the overall plan is:

1. Check if a command is of a known type (that is, defined with `\newcommand`[14], `\DeclareRobustCommand`, or `\New(Expandable)DocumentCommand`), and if is, take appropriate action.

2. If the command is not a known type, we'll check if the command can be patched. Two things will prevent a command from being patched: if it was defined in a nonstandard catcode setting, or if it is an internal expl3 command with `__`⟨*module*⟩ in its name, in which case we refuse to patch.

3. If the command was defined in nonstandard catcode settings, we will try a few standard ones to try our best to carry out the pathing. If this doesn't help either, the code will give up and throw an error.

```
⟨@@=hook⟩
```

```
⟨*2ekernel | latexrelease⟩
\ExplSyntaxOn
⟨latexrelease⟩\NewModuleRelease{2021/06/01}{ltcmdhooks}
⟨latexrelease⟩                    {The~hook~management~system~for~commands}
```

4.2 Variables

`\g_hook_patch_action_list_tl`

Pairs of `\if<cmd>..\patch<cmd>` to be used with `\robust@command@act` when looking for a known patching rule. This token list is exposed because we see some future applications (with very specialized packages, such as etoolbox that may want to extend the pairs processed. It is not meant for general use which is why it is not documented in the interface documentation above.

```
\tl_new:N \g_hook_patch_action_list_tl
```

(*End definition for* `\g_hook_patch_action_list_tl`.)

`\l__hook_patch_num_args_int`

The number of arguments in a macro being patched.

```
\int_new:N \l__hook_patch_num_args_int
```

(*End definition for* `\l__hook_patch_num_args_int`.)

[14] It's not always possible to reliably detect this case because a command defined with no optional argument is indistinguishable from a `\def`ed command.

\l__hook_patch_prefixes_tl
\l__hook_param_text_tl
\l__hook_replace_text_tl

The prefixes and parameters of the definition for the macro being patched.

```
\tl_new:N \l__hook_patch_prefixes_tl
\tl_new:N \l__hook_param_text_tl
\tl_new:N \l__hook_replace_text_tl
```

(*End definition for* `\l__hook_patch_prefixes_tl`, `\l__hook_param_text_tl`, *and* `\l__hook_replace_text_tl`.)

\c__hook_hash_tl

A constant token list that contains two parameter tokens.

```
\tl_const:Nn \c__hook_hash_tl { # # }
```

(*End definition for* `\c__hook_hash_tl`.)

__hook_exp_not:NN
__hook_def_cmd:w

Two temporary macros that change depending on the macro being patched.

```
\cs_new_eq:NN \__hook_exp_not:NN ?
\cs_new_eq:NN \__hook_def_cmd:w ?
```

(*End definition for* `\__hook_exp_not:NN` *and* `\__hook_def_cmd:w`.)

\q__hook_recursion_tail
\q__hook_recursion_stop

Internal quarks for recursion: they can't appear in any macro being patched.

```
\quark_new:N \q__hook_recursion_tail
\quark_new:N \q__hook_recursion_stop
```

(*End definition for* `\q__hook_recursion_tail` *and* `\q__hook_recursion_stop`.)

\g__hook_delayed_patches_prop

A list containing the patches delayed to `\begin{document}`, so that patching is not attempted twice.

```
\prop_new:N \g__hook_delayed_patches_prop
```

(*End definition for* `\g__hook_delayed_patches_prop`.)

__hook_patch_debug:x

A helper for patching debug info.

```
\cs_new_protected:Npn \__hook_patch_debug:x #1
  { \__hook_debug:n { \iow_term:x { [lthooks]~#1 } } }
```

(*End definition for* `\__hook_patch_debug:x`.)

4.3 Variants

\tl_rescan:nV

expl3 function variants used throughout the code.

```
\cs_generate_variant:Nn \tl_rescan:nn { nV }
```

(*End definition for* `\tl_rescan:nV`.)

4.4 Patching or delaying

Before \begin{document} all patching is delayed.

__hook_try_put_cmd_hook:n
__hook_try_put_cmd_hook:w

This function is called from within \AddToHook, when code is first added to a generic cmd hook. If it is called within in the preamble, it delays the action until \begin{document}; otherwise it tries to update the hook.

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{\__hook_try_put_cmd_hook:n}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
\cs_new_protected:Npn \__hook_try_put_cmd_hook:n #1
  { \__hook_try_put_cmd_hook:w #1 / / / \s__hook_mark {#1} }
\cs_new_protected:Npn \__hook_try_put_cmd_hook:w
    #1 / #2 / #3 / #4 \s__hook_mark #5
  {
    \__hook_debug:n { \iow_term:n { ->~Adding~cmd~hook~to~'#2'~(#3): } }
    \exp_args:Nc \__hook_patch_cmd_or_delay:Nnn {#2} {#2} {#3}
  }
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}{\__hook_try_put_cmd_hook:n}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\cs_new_protected:Npn \__hook_try_put_cmd_hook:n #1
⟨latexrelease⟩  { \__hook_try_put_cmd_hook:w #1 / / / \s__hook_mark {#1} }
⟨latexrelease⟩\cs_new_protected:Npn \__hook_try_put_cmd_hook:w
⟨latexrelease⟩    #1 / #2 / #3 / #4 \s__hook_mark #5
⟨latexrelease⟩  {
⟨latexrelease⟩    \__hook_debug:n { \iow_term:n { ->~Adding~cmd~hook~to~'#2'~(#3): } }
⟨latexrelease⟩    \str_case:nnTF {#3}
⟨latexrelease⟩        { { before } { } { after } { } }
⟨latexrelease⟩      { \exp_args:Nc \__hook_patch_cmd_or_delay:Nnn {#2} {#2} {#3} }
⟨latexrelease⟩      { \msg_error:nnnn { hooks } { wrong-cmd-hook } {#2} {#3} }
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* __hook_try_put_cmd_hook:n *and* __hook_try_put_cmd_hook:w.)

__hook_patch_cmd_or_delay:Nnn
__hook_cmd_begindocument_code:

In the preamble, __hook_patch_cmd_or_delay:Nnn just adds the patch instruction to a property list to be executed later.

```
\cs_new_protected:Npn \__hook_patch_cmd_or_delay:Nnn #1 #2 #3
  {
    \__hook_debug:n { \iow_term:n { ->~Add~generic~cmd~hook~for~#2~(#3). } }
    \__hook_debug:n
      { \iow_term:n { !~In~the~preamble:~delaying. } }
    \prop_gput:Nnn \g__hook_delayed_patches_prop { #2 / #3 }
      { \__hook_cmd_try_patch:nn {#2} {#3} }
  }
```

The delayed patches are added to a property list to prevent duplication, and the code stored in the property list for each key is executed. The function __hook_patch_cmd_-or_delay:Nnn is also redefined to be __hook_patch_command:Nnn so that no further delaying is attempted.

```
\cs_new_protected:Npn \__hook_cmd_begindocument_code:
  {
    \cs_gset_eq:NN \__hook_patch_cmd_or_delay:Nnn \__hook_patch_command:Nnn
    \prop_map_function:NN \g__hook_delayed_patches_prop { \use_ii:nn }
```

```
    \prop_gclear:N \g__hook_delayed_patches_prop
    \cs_undefine:N \__hook_cmd_begindocument_code:
  }
\g@addto@macro \@kernel@after@begindocument
  { \__hook_cmd_begindocument_code: }
```

(*End definition for* `\__hook_patch_cmd_or_delay:Nnn` *and* `\__hook_cmd_begindocument_code:`.)

`\__hook_cmd_try_patch:nn`

At `\begin{document}` tries patching the command if the hook was not manually created in the meantime. If the document does not exist, no error is raised here as it may hook into a package that wasn't loaded. Hooks added to commands in the document body still raise an error if the command is not defined.

```
\cs_new_protected:Npn \__hook_cmd_try_patch:nn #1 #2
  {
    \__hook_debug:n
      { \iow_term:x { ->~\string\begin{document}~try~cmd / #1 / #2. } }
    \__hook_if_declared:nTF { cmd / #1 / #2 }
      {
        \__hook_debug:n
          { \iow_term:n { .->~Giving~up:~hook~already~created. } }
      }
      {
        \cs_if_exist:cT {#1}
          { \exp_args:Nc \__hook_patch_command:Nnn {#1} {#1} {#2} }
      }
  }
```

(*End definition for* `\__hook_cmd_try_patch:nn`.)

4.5 Patching commands

`\__hook_patch_command:Nnn`
`\__hook_patch_check:NNnn`
`\__hook_if_public_command:NTF`
`\__hook_if_public_command:w`

`\__hook_patch_command:Nnn` will do some sanity checks on the argument to detect if it is possible to add hooks to the command, and raises an error otherwise. If the command can contain hooks, then it uses `\robust@command@act` to find out what type is the command, and patch it accordingly.

```
\cs_new_protected:Npn \__hook_patch_command:Nnn #1 #2 #3
  {
    \__hook_patch_debug:x { analyzing~'\token_to_str:N #1' }
    \__hook_patch_debug:x { \token_to_str:N #1 = \token_to_meaning:N #1 }
    \__hook_patch_check:NNnn \cs_if_exist:NTF #1 { undef }
      {
        \__hook_patch_debug:x { ++~control~sequence~is~defined }
        \__hook_patch_check:NNnn \token_if_macro:NTF #1 { macro }
          {
            \__hook_patch_debug:x { ++~control~sequence~is~a~macro }
            \__hook_patch_check:NNnn \__hook_if_public_command:NTF #1 { expl3 }
              {
                \__hook_patch_debug:x { ++~macro~is~not~private }
                \robust@command@act
                  \g_hook_patch_action_list_tl #1
                  \__hook_retokenize_patch:Nnn { #1 {#2} {#3} }
              }
          }
      }
```

```
  }
```

And here's the auxiliary used above:

```
\cs_new_protected:Npn \__hook_patch_check:NNnn #1 #2 #3 #4
  {
    #1 #2 {#4}
      {
        \msg_error:nnxx { hooks } { cant-patch }
          { \token_to_str:N #2 } {#3}
      }
  }
```

and a conditional `\__hook_if_public_command:N` to check if a command has `__` in its name (no other checking is performed). Primitives with `:D` in their name could be included here, but they are already discarded in the `\token_if_macro:NTF` test above.

```
\use:x
  {
    \prg_new_protected_conditional:Npnn
        \exp_not:N \__hook_if_public_command:N ##1 { TF }
      {
        \exp_not:N \exp_last_unbraced:Nf
          \exp_not:N \__hook_if_public_command:w
            { \exp_not:N \cs_to_str:N ##1 }
          \tl_to_str:n { _ _ } \s__hook_mark
      }
  }
\exp_last_unbraced:NNNNo
\cs_new_protected:Npn \__hook_if_public_command:w
    #1 \tl_to_str:n { _ _ } #2 \s__hook_mark
  {
    \tl_if_empty:nTF {#2}
      { \prg_return_true: }
      { \prg_return_false: }
  }
```

(*End definition for* `\__hook_patch_command:Nnn` *and others.*)

4.5.1 Patching by expansion and redefinition

`\g_hook_patch_action_list_tl`

This is the list of known command types and the function that patches the command hooks into them. The conditionals are taken from `\ShowCommand`, `\NewCommandCopy` and `\__kernel_cmd_if_xparse:NTF` defined in `ltcmd`.

```
\tl_gset:Nn \g_hook_patch_action_list_tl
  {
    { \@if@DeclareRobustCommand \__hook_patch_DeclareRobustCommand:Nnn }
    { \@if@newcommand \__hook_patch_newcommand:Nnn }
    { \__kernel_cmd_if_xparse:NTF \__hook_cmd_patch_xparse:Nnn }
  }
```

(*End definition for* `\g_hook_patch_action_list_tl`.)

`\__hook_patch_DeclareRobustCommand:Nnn`

At this point we know that the commands can be patched by expanding then redefining. These are the cases of commands defined with `\newcommand` with an optional argument or with `\DeclareRobustCommand`.

With `\__hook_patch_DeclareRobustCommand:Nnn` we check if the command has an optional argument (with a test counter-intuitively called `\@if@newcommand`; also make sure the command doesn't take args by calling `\robust@command@chk@safe`). If so, we pass the patching action to `\__hook_patch_newcommand:Nnn`, otherwise we call the patching engine `\__hook_patch_expand_redefine:NNnn` with a `\c_false_bool` to indicate that there is no optional argument.

```
\cs_new_protected:Npn \__hook_patch_DeclareRobustCommand:Nnn #1
  {
    \exp_args:Nc \__hook_patch_DeclareRobustCommand_aux:Nnn
      { \cs_to_str:N #1 ~ }
  }
\cs_new_protected:Npn \__hook_patch_DeclareRobustCommand_aux:Nnn #1
  {
    \robust@command@chk@safe #1
      { \@if@newcommand #1 }
      { \use_ii:nn }
        { \__hook_patch_newcommand:Nnn }
        { \__hook_patch_expand_redefine:NNnn \c_false_bool }
          #1
  }
```

(*End definition for* `\__hook_patch_DeclareRobustCommand:Nnn`.)

`\__hook_patch_newcommand:Nnn`

If the command was defined with `\newcommand` and an optional argument, call the patching engine with a `\c_true_bool` to flag the presence of an optional argument, and with `\\command` to patch the actual code for `\command`.

```
\cs_new_protected:Npn \__hook_patch_newcommand:Nnn #1
  {
    \exp_args:NNc \__hook_patch_expand_redefine:NNnn \c_true_bool
      { \c_backslash_str \cs_to_str:N #1 }
  }
```

(*End definition for* `\__hook_patch_newcommand:Nnn`.)

`\__hook_cmd_patch_xparse:Nnn`

And for commands defined by the xparse commands use this for patching:

```
\cs_new_protected:Npn \__hook_cmd_patch_xparse:Nnn #1
  {
    \exp_args:NNc \__hook_patch_expand_redefine:NNnn \c_false_bool
      { \cs_to_str:N #1 ~ code }
  }
```

(*End definition for* `\__hook_cmd_patch_xparse:Nnn`.)

`\__hook_patch_expand_redefine:NNnn`
`\__hook_redefine_with_hooks:Nnnn`
`\__hook_make_prefixes:w`

Now the real action begins. Here we have in `#1` a boolean indicating if the command has a leading `[...]`-delimited argument, in `#2` the command control sequence, in `#3` the name of the command (note that `#1` ≠ `\csname#2\endcsname` at this point!), and in `#4` the hook position, either `before` or `after`.

Patching with expansion+redefinition is trickier than it looks like at first glance. Suppose the simple definition:

```
\def\foo#1{#1##2}
```

When defined, its ⟨*replacement text*⟩ will be a token list containing:

out_param `1`, *mac_param* `#`, *character* `2`

Then, after expanding `\foo{##1}` (here `##` denotes a single $\#_6$) we end up with a token list with *out_param* `1` replaced:

mac_param `#`, *character* `1`, *mac_param* `#`, *character* `2`

that is, the definition would be:

```
\def\foo#1{#1#2}
```

which obviously fails, because the original input in the definition was `##` but TEX reduced that to a single parameter token $\#_6$ when carrying out the definition. That leaves no room for a clever solution with (say) `\unexpanded`, because anything that would double the second $\#_6$, would also (incorrectly) double the first, so there's not much to do other than a manual solution.

There are three cases we can distinguish to make things hopefully faster on simpler cases:

1. a macro with no parameters;
2. a macro with no parameter tokens in its definition;
3. a macro with parameters *and* parameter tokens.

The first case is trivial: if the macro has no parameters, we can just use `\unexpanded` around it, and if there is a parameter token in it, it is handled correctly (the macro can be treated as a `tl` variable).

The second case requires looking at the ⟨*replacement text*⟩ of the macro to see if it has a parameter token in there. If it does not, then there is no worry, and the macro can be redefined normally (without `\unexpanded`).

The third case, as usual, is the devious one. Here we'll have to loop through the definition token by token, and double every parameter token, so that this case can be handled like the previous one.

```
\cs_new_protected:Npn \__hook_patch_expand_redefine:NNnn #1 #2 #3 #4
  {
    \__hook_patch_debug:x { ++~command~can~be~patched~without~rescanning }
```

We'll start by counting the number of arguments in the command by counting the number of characters in the `\cs_argument_spec:N` of the macro, divided by two, and subtracting one if the command has an optional argument (that is, an extra `[]` in its ⟨*parameter text*⟩).

```
    \int_set:Nn \l__hook_patch_num_args_int
      {
        \exp_args:Nf \str_count:n { \cs_argument_spec:N #2 } / 2
        \bool_if:NT #1 { -1 }
      }
```

Now build two token lists:

`\l__hook_param_text_tl` will contain the ⟨*parameter text*⟩ to be used when redefining the macro. It should be identical to the ⟨*parameter text*⟩ used when originally defining that macro.

`\l__hook_replace_text_tl` will contain braced pairs of `\c__hook_hash_tl`⟨*num*⟩ to feed to the macro when expanded. This token list as well as the previous will have the first item surrounded by `[...]` in the case of an optional argument.

The use of \c__hook_hash_tl here is to differentiate actual parameters in the macro from parameter tokens in the original definition of the macro. Later on, \c__hook_hash_tl is either replaced by actual parameter tokens, or expanded into them.

```
    \int_compare:nNnTF { \l__hook_patch_num_args_int } > { \c_zero_int }
      {
```

We'll first check if the command has any parameter token in its definition (feeding it empty arguments), and set __hook_exp_not:n accordingly. __hook_exp_not:n will be used later to either leave \c__hook_hash_tl or expand it, and also to remember the result of __hook_if_has_hash:nTF to avoid testing twice (the test can be rather slow).

```
        \tl_set:Nx \l__hook_tmpa_tl { \bool_if:NTF #1 { [ ] } { { } } }
        \int_step_inline:nnn { 2 } { \l__hook_patch_num_args_int }
          { \tl_put_right:Nn \l__hook_tmpa_tl { { } } }
        \exp_args:NNo \exp_args:No \__hook_if_has_hash:nTF
            { \exp_after:wN #2 \l__hook_tmpa_tl }
          { \cs_set_eq:NN \__hook_exp_not:n \exp_not:n }
          { \cs_set_eq:NN \__hook_exp_not:n \use:n }
        \cs_set_protected:Npn \__hook_tmp:w ##1 ##2
          {
            ##1 \l__hook_param_text_tl   { \use:n ##2 }
            ##1 \l__hook_replace_text_tl { \__hook_exp_not:n {##2} }
          }
```

Here we'll conditionally add [...] around the first parameter:

```
        \bool_if:NTF #1
          { \__hook_tmp:w \tl_set:Nx { [ \c__hook_hash_tl 1 ] } }
          { \__hook_tmp:w \tl_set:Nx { { \c__hook_hash_tl 1 } } }
```

Then, for every parameter from the second, just add it normally:

```
        \int_step_inline:nnn { 2 } { \l__hook_patch_num_args_int }
          { \__hook_tmp:w \tl_put_right:Nx { { \c__hook_hash_tl ##1 } } }
```

Now, if the command has any parameter token in its definition (then __hook_exp_not:n is \exp_not:n), call __hook_double_hashes:n to double them, and replace every \c__hook_hash_tl by #:

```
        \tl_set:Nx \l__hook_replace_text_tl
          { \exp_not:N #2 \exp_not:V \l__hook_replace_text_tl }
        \tl_set:Nx \l__hook_replace_text_tl
          {
            \token_if_eq_meaning:NNTF \__hook_exp_not:n \exp_not:n
              { \exp_args:NNV \exp_args:No \__hook_double_hashes:n }
              { \exp_args:NV \exp_not:o }
                  \l__hook_replace_text_tl
          }
```

And now, set a few auxiliaries for the case that the macro has parameters, so it won't be passed through \unexpanded (twice):

```
        \cs_set_eq:NN \__hook_def_cmd:w \tex_gdef:D
        \cs_set_eq:NN \__hook_exp_not:NN \prg_do_nothing:
      }
      {
```

In the case the macro has no parameters, we'll treat it as a token list and things are much simpler (expansion control looks a bit complicated, but it's just a pair of \exp_not:N preventing another \exp_not:n from expanding):

```
        \tl_clear:N \l__hook_param_text_tl
        \tl_set_eq:NN \l__hook_replace_text_tl #2
        \cs_set_eq:NN \__hook_def_cmd:w \tex_xdef:D
        \cs_set:Npn \__hook_exp_not:NN ##1 { \exp_not:N ##1 \exp_not:N }
      }
```

Before redefining, we need to also get the prefixes used when defining the command. Here we ensure that the `\escapechar` is printable, otherwise a macro defined with prefixes `\protected \long` will have it `\meaning` printed as `protectedlong`, making life unnecessarily complicated. Here the `\escapechar` is changed to `/`, then we loop between pairs of `/.../` extracting the prefixes.

```
    \group_begin:
      \int_set:Nn \tex_escapechar:D { `\/ }
      \use:x
        {
    \group_end:
    \tl_set:Nx \exp_not:N \l__hook_patch_prefixes_tl
      { \exp_not:N \__hook_make_prefixes:w \cs_prefix_spec:N #2 / / }
        }
```

Finally, call `\__hook_redefine_with_hooks:Nnnn` with the macro being redefined in `#1`, then `\UseHook{cmd/<name>/before}` in `#2` or `\UseHook{cmd/<name>/after}` in `#3` (one is always empty), and in `#4` the ⟨*replacement text*⟩ of the macro.

```
    \use:x
      {
        \__hook_redefine_with_hooks:Nnnn \exp_not:N #2
        \str_if_eq:nnTF {#4} { after }
          { \use_ii_i:nn }
          { \use:nn }
            { { \__hook_exp_not:NN \exp_not:N \UseHook { cmd / #3 / #4 } } }
            { { } }
            { \__hook_exp_not:NN \exp_not:V \l__hook_replace_text_tl }
      }
  }
```

Now that all the needed tools are ready, without further ado we'll redefine the command. The definition uses the prefixes gathered in `\l__hook_patch_prefixes_tl`, a primitive `\__hook_def_cmd:w` (which is `\tex_gdef:D` or `\tex_xdef:D`) to avoid adding extra prefixes, and the ⟨*parameter text*⟩ from `\l__hook_param_text_tl`.

Then finally, in the body of the definition, we insert `#2`, which is `cmd/#1/before` or empty, `#4` which is the ⟨*replacement text*⟩, and `#3` which is `cmd/#1/after` or empty.

```
\cs_new_protected:Npn \__hook_redefine_with_hooks:Nnnn #1 #2 #3 #4
  {
    \l__hook_patch_prefixes_tl
      \exp_after:wN \__hook_def_cmd:w
        \exp_after:wN #1 \l__hook_param_text_tl
      { #2  #4  #3 }
  }
```

Here's the auxiliary that makes the prefix control sequences for the redefinition. Each item has to be `\tl_trim_spaces:n`'d because the last item (and not any other) has a trailing space.

```
\cs_new:Npn \__hook_make_prefixes:w / #1 /
  {
```

```
    \tl_if_empty:nF {#1}
      {
        \exp_not:c { tex_ \tl_trim_spaces:n {#1} :D }
        \__hook_make_prefixes:w /
      }
  }
```

(*End definition for* `\__hook_patch_expand_redefine:NNnn`, `\__hook_redefine_with_hooks:Nnnn`, *and* `\__hook_make_prefixes:w`.)

Here are some auxiliaries for the contraption above.

`\__hook_if_has_hash_p:n`
`\__hook_if_has_hash:nTF`
`\__hook_if_has_hash:w`
`\__hook_if_has_hash_check:w`

`\__hook_if_has_hash:nTF` searches the token list `#1` for a catcode 6 token, and if any is found, it returns `true`, and `false` otherwise. The searching doesn't care about preserving groups or spaces: we can ignore those safely (braces are removed) so that searching is as fast as possible.

```
\prg_new_conditional:Npnn \__hook_if_has_hash:n #1 { TF }
  { \__hook_if_has_hash:w #1 ## \s__hook_mark }
\cs_new:Npn \__hook_if_has_hash:w #1
  {
    \tl_if_single_token:nTF {#1}
      {
        \token_if_eq_catcode:NNTF ## #1
          { \__hook_if_has_hash_check:w }
          { \__hook_if_has_hash:w }
      }
      { \__hook_if_has_hash:w #1 }
  }
\cs_new:Npn \__hook_if_has_hash_check:w #1 \s__hook_mark
  { \tl_if_empty:nTF {#1} { \prg_return_false: } { \prg_return_true: } }
```

(*End definition for* `\__hook_if_has_hash:nTF`, `\__hook_if_has_hash:w`, *and* `\__hook_if_has_hash_check:w`.)

`\__hook_double_hashes:n`
`\__hook_double_hashes:w`
`\__hook_double_hashes_output:N`
`\__hook_double_hashes_stop:w`
`\__hook_double_hashes_group:n`
`\__hook_double_hashes_space:w`

`\__hook_double_hashes:n` loops through the token list `#1` and duplicates any catcode 6 token, and expands tokens `\ifx`-equal to `\c__hook_hash_tl`, and leaves all other tokens `\notexpanded` with `\exp_not:N`. Unfortunately pairs of explicit catcode 1 and catcode 2 character tokens are normalised to $\{_1$ and $\}_1$ because it's not feasible to expandably detect the character code (*maybe* it could be done using something along the lines of https://tex.stackexchange.com/a/527538, but it's far too much work for close to zero benefit).

`\__hook_double_hashes:w` is the tail-recursive loop macro, that tests which of the three types of item is in the head of the token list.

```
\cs_new:Npn \__hook_double_hashes:n #1
  { \__hook_double_hashes:w #1 \q__hook_recursion_tail \q__hook_recursion_stop }
\cs_new:Npn \__hook_double_hashes:w #1 \q__hook_recursion_stop
  {
    \tl_if_head_is_N_type:nTF {#1}
      { \__hook_double_hashes_output:N }
      {
        \tl_if_head_is_group:nTF {#1}
          { \__hook_double_hashes_group:n }
          { \__hook_double_hashes_space:w }
      }
    #1 \q__hook_recursion_stop
```

```
  }
```

`\__hook_double_hashes_output:N` checks for the end of the token list, then checks if the token is `\c__hook_hash_tl`, and if so just leaves it.

```
\cs_new:Npn \__hook_double_hashes_output:N #1
  {
    \if_meaning:w \q__hook_recursion_tail #1
      \__hook_double_hashes_stop:w
    \fi:
    \if_meaning:w \c__hook_hash_tl #1
```

(this `\use_i:nnnn` uses `\fi:` and consumes `\use:n`, the whole `\if_catcode:w` block, and the `\exp_not:N`, leaving just `#1` which is `\c__hook_hash_tl`.)

```
      \use_i:nnnn
    \fi:
    \use:n
      {
```

If `#1` is not `\c__hook_hash_tl`, then check if its catcode is 6, and if so, leave it doubled in `\exp_not:n` and consume the following `\exp_not:N #1`.

```
        \if_catcode:w ## \exp_not:N #1
          \exp_after:wN \use_ii:nnnn
        \fi:
        \use_none:n
          { \exp_not:n { #1 #1 } }
      }
```

If both previous tests returned `false`, then leave the token unexpanded and resume the loop.

```
    \exp_not:N #1
    \__hook_double_hashes:w
  }
\cs_new:Npn \__hook_double_hashes_stop:w #1 \q__hook_recursion_stop { \fi: }
```

Dealing with spaces and grouped tokens is trivial:

```
\cs_new:Npn \__hook_double_hashes_group:n #1
  { { \__hook_double_hashes:n {#1} } \__hook_double_hashes:w }
\exp_last_unbraced:NNo
\cs_new:Npn \__hook_double_hashes_space:w \c_space_tl
  { ~ \__hook_double_hashes:w }
```

(*End definition for* `\__hook_double_hashes:n` *and others.*)

4.5.2 Patching by retokenization

At this point we've drained the possibilities of patching a command by expansion-and-redefinition, so we have to resort to patching by retokenizing the command. Patching by retokenization is done by getting the `\meaning` of the command, doing the necessary manipulations on the generated string, and the retokenizing that again by using `\scantokens`.

Patching by retokenization is definitely a riskier business, because it relies that the tokens printed by `\meaning` produce the exact same tokens as the ones in the original definition. That is, the catcode régime must be exactly(ish) the same, and there is no way of telling except by trial and error.

__hook_retokenize_patch:Nnn

This is the macro that will control the whole process. First we'll try out one final, rather trivial case, of a command with no arguments; that is, a token list. This case can be patched with the expand-and-redefine routine but it has to be the very last case tested for, because most (all?) robust commands start with a top-level macro with no arguments, so testing this first would short-circuit `\robust@command@act` and the top-level macros would be incorrectly patched. In that case, we just check if the `\cs_argument_spec:N` is empty, and call `\__hook_patch_expand_redefine:NNnn`.

```
\cs_new_protected:Npn \__hook_retokenize_patch:Nnn #1 #2 #3
  {
    \__hook_patch_debug:x { ..~command~can~only~be~patched~by~rescanning }
    \str_if_eq:eeTF { \cs_argument_spec:N #1 } { }
      { \__hook_patch_expand_redefine:NNnn \c_false_bool #1 {#2} {#3} }
      {
```

Otherwise, we start the actual patching by retokenization job. The code calls `\__hook_try_patch_with_catcodes:Nnnnw` with a different catcode setting:

- The current catcode setting;
- Switching the catcode of `@`;
- Switching the expl3 syntax on or off;
- Both of the above.

If patching succeeds, `\__hook_try_patch_with_catcodes:Nnnnw` has the side-effect of patching the macro `#1` (which may be an internal from the command whose name is `#2`).

```
        \tl_set:Nx \l__hook_tmpa_tl
          {
            \int_compare:nNnTF { \char_value_catcode:n {`\@ } } = { 12 }
              { \exp_not:N \makeatletter } { \exp_not:N \makeatother }
          }
        \tl_set:Nx \l__hook_tmpb_tl
          {
            \bool_if:NTF \l__kernel_expl_bool
              { \ExplSyntaxOff } { \ExplSyntaxOn }
          }
        \use:x
          {
            \exp_not:N \__hook_try_patch_with_catcodes:Nnnnw
                \exp_not:n { #1 {#2} {#3} }
              { \prg_do_nothing: }
              { \exp_not:V \l__hook_tmpa_tl } % @
              { \exp_not:V \l__hook_tmpb_tl } % _:
              {
                \exp_not:V \l__hook_tmpa_tl   % @
                \exp_not:V \l__hook_tmpb_tl   % _:
              }
          }
              \q_recursion_tail \q_recursion_stop
```

If no catcode setting succeeds, give up and raise an error. The command isn't changed in any way in that case.

```
          {
            \msg_error:nnxx { hooks } { cant-patch }
```

```
                { \c_backslash_str #2 } { retok }
            }
        }
    }
```

(*End definition for* `\__hook_retokenize_patch:Nnn`.)

`\__hook_try_patch_with_catcodes:Nnnnw` This function is a simple wrapper around `\__hook_cmd_if_scanable:NnTF` and `\__hook_patch_retokenize:Nnnn` if the former returns ⟨*true*⟩, plus some debug messages.

```
\cs_new_protected:Npn \__hook_try_patch_with_catcodes:Nnnnw #1 #2 #3 #4
  {
    \quark_if_recursion_tail_stop_do:nn {#4} { \use:n }
    \__hook_patch_debug:x { ++~trying~to~patch~by~retokenization }
    \__hook_cmd_if_scanable:NnTF {#1} {#4}
      {
        \__hook_patch_debug:x { ++~macro~can~be~retokenized~cleanly }
        \__hook_patch_debug:x { ==~retokenizing~macro~now }
        \__hook_patch_retokenize:Nnnn #1 {#2} {#3} {#4}
        \use_i_delimit_by_q_recursion_stop:nw \use_none:n
      }
      {
        \__hook_patch_debug:x { --~macro~cannot~be~retokenized~cleanly }
        \__hook_try_patch_with_catcodes:Nnnnw #1 {#2} {#3}
      }
  }
```

(*End definition for* `\__hook_try_patch_with_catcodes:Nnnnw`.)

`\kerneltmpDoNotUse` This is an oddity required to be safe (as safe as reasonably possible) when patching the command. The entirety of

⟨*prefixes*⟩ `\def` ⟨*cs*⟩ ⟨*parameter text*⟩ `{`⟨*replacement text*⟩`}`

will go through `\scantokens`. The ⟨*parameter text*⟩ and ⟨*replacement text*⟩ are what we are trying to retokenize, so not much worry there. The other items, however, should "just work", so some care is needed to not use too fancy catcode settings. Therefore we can't use an expl3-named macro for ⟨*cs*⟩, nor the expl3 versions of `\def` or the ⟨*prefixes*⟩. That is why the definitions that will eventually go into `\scantokens` will use the oddly (but hopefully clearly)-named `\kerneltmpDoNotUse`:

```
\cs_new_eq:NN \kerneltmpDoNotUse !
```

> *PhO: Maybe this can be avoided by running the ⟨parameter text⟩ and the ⟨replacement text⟩ separately through* `\scantokens` *and then putting everything together at the end.*

(*End definition for* `\kerneltmpDoNotUse`.)

`\__hook_patch_required_catcodes:` Here are the catcode settings that are *mandatory* when retokenizing commands. These are the minimum necessary settings to perform the definitions: they identify control sequences, which must be escaped with $\backslash_0$, delimit the definition with $\{_1$ and $\}_2$, and mark parameters with $\#_6$. Everything else may be changed, but not these.

```
\cs_new_protected:Npn \__hook_patch_required_catcodes:
  {
    \char_set_catcode_escape:N \\
    \char_set_catcode_group_begin:N \{
    \char_set_catcode_group_end:N \}
```

```
    \char_set_catcode_parameter:N \#
    % \int_set:Nn \tex_endlinechar:D { -1 }
    % \int_set:Nn \tex_newlinechar:D { -1 }
  }
```

PhO: etoolbox sets the `\endlinechar` *and* `\newlinechar` *when patching, but as far as I tested these didn't make much of a difference, so I left them out for now. Maybe* `\newlinechar=-1` *avoids a space token being added after the definition.*

PhO: If the patching is split by ⟨parameter text⟩ and ⟨replacement text⟩, then only # will have to stay in that list.

PhO: Actually now that we patch `\UseHook{cmd/foo/before}`*, all the tokens there need to have the right catcodes, so this list now includes all lowercase letters, U and H, the slash, and whatever characters in the command name... sigh...*

(*End definition for* `\__hook_patch_required_catcodes:`.)

`\__hook_cmd_if_scanable:NnTF` Here we'll do a quick test if the command being patched can in fact be retokenized with the specific catcode setting without changing in meaning. The test is straightforward:

1. apply `\meaning` to the command;
2. split the ⟨*prefixes*⟩, ⟨*parameter text*⟩ and ⟨*replacement text*⟩ and arrange them as

   ⟨*prefixes*⟩`\def\kerneltmpDoNotUse`⟨*parameter text*⟩`{`⟨*replacement text*⟩`}`

3. rescan that with the given catcode settings, and do the definition; then finally
4. compare `\kerneltmpDoNotUse` with the original command.

If both are `\ifx`-equal, the command can be safely patched.

```
\prg_new_protected_conditional:Npnn \__hook_cmd_if_scanable:Nn #1 #2 { TF }
  {
    \cs_set_eq:NN \kerneltmpDoNotUse \scan_stop:
    \cs_set_eq:NN \__hook_tmp:w \scan_stop:
    \use:x
      {
        \cs_set:Npn \__hook_tmp:w
            ####1 \tl_to_str:n { macro: } ####2 -> ####3 \s__hook_mark
          { ####1 \def \kerneltmpDoNotUse ####2   {####3} }
        \tl_set:Nx \exp_not:N \l__hook_tmpa_tl
          { \exp_not:N \__hook_tmp:w \token_to_meaning:N #1 \s__hook_mark }
      }
    \tl_rescan:nV { #2 \__hook_patch_required_catcodes: } \l__hook_tmpa_tl
    \token_if_eq_meaning:NNTF #1 \kerneltmpDoNotUse
      { \prg_return_true: }
      { \prg_return_false: }
  }
```

(*End definition for* `\__hook_cmd_if_scanable:NnTF`.)

`\__hook_patch_retokenize:Nnnn` Then, if `\__hook_cmd_if_scanable:NnTF` returned true, we can go on and patch the command.

```
\cs_new_protected:Npn \__hook_patch_retokenize:Nnnn #1 #2 #3 #4
  {
```

Start off by making some things `\relax` to avoid lots of `\noexpand` below.

```
    \cs_set_eq:NN \kerneltmpDoNotUse \scan_stop:
    \cs_set_eq:NN \__hook_tmp:w \scan_stop:
    \use:x
      {
```

Now we'll define `\__hook_tmp:w` such that it splits the `\meaning` of the macro (`#1`) into its three parts:

`####1.` ⟨*prefixes*⟩

`####2.` ⟨*parameter text*⟩

`####3.` ⟨*replacement text*⟩

and arrange that a complete definition, then place the `before` or `after` hooks around the ⟨*replacement text*⟩: accordingly.

```
        \cs_set:Npn \__hook_tmp:w
            ####1 \tl_to_str:n { macro: } ####2 -> ####3 \s__hook_mark
          {
            ####1 \def \kerneltmpDoNotUse ####2
              {
                \str_if_eq:nnT {#3} { before }
                  { \token_to_str:N \UseHook { cmd / #2 / #3 } }
                ####3
                \str_if_eq:nnT {#3} { after }
                  { \token_to_str:N \UseHook { cmd / #2 / #3 } }
              }
          }
```

Now we just have to get the `\meaning` of the command being patched and pass it through the meat grinder above.

```
        \tl_set:Nx \exp_not:N \l__hook_tmpa_tl
          { \exp_not:N \__hook_tmp:w \token_to_meaning:N #1 \s__hook_mark }
      }
```

Now rescan with the given catcode settings (overridden by the `\__hook_patch_required_catcodes:`), and implicitly (by using the rescanned token list) carry out the definition from above.

```
    \tl_rescan:nV { #4 \__hook_patch_required_catcodes: } \l__hook_tmpa_tl
```

And to close, copy the newly-defined command into the old name and the patching is finally completed:

```
    \cs_gset_eq:NN #1 \kerneltmpDoNotUse
  }
```

(*End definition for* `\__hook_patch_retokenize:Nnnn`.)

4.6 Messages

```
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{wrong-cmd-hook}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2021/11/15}{wrong-cmd-hook}%
⟨latexrelease⟩                  {Standardise~generic~hook~names}
⟨latexrelease⟩\msg_new:nnnn { hooks } { wrong-cmd-hook }
```

```
⟨latexrelease⟩  {
⟨latexrelease⟩    Generic~hook~‘cmd/#1/#2’~is~invalid.
⟨latexrelease⟩%    The~hook~should~be~‘cmd/#1/before’~or~‘cmd/#1/after’.
⟨latexrelease⟩  }
⟨latexrelease⟩  {
⟨latexrelease⟩    You~tried~to~add~a~generic~hook~to~command~\iow_char:N \\#1,~but~‘#2’~
⟨latexrelease⟩    is~an~invalid~component.~Only~‘before’~or~‘after’~are~allowed.
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
\msg_new:nnnn { hooks } { cant-patch }
  {
    Generic~hooks~cannot~be~added~to~’#1’.
  }
  {
    You~tried~to~add~a~hook~to~’#1’,~but~LaTeX~was~unable~to~
    patch~the~command~because~it~\__hook_unpatchable_cases:n {#2}.
  }
\cs_new:Npn \__hook_unpatchable_cases:n #1
  {
    \str_case:nn {#1}
      {
        { undef } { doesn’t~exist }
        { macro } { is~not~a~macro }
        { expl3 } { is~a~private~expl3~macro }
        { retok } { can’t~be~retokenized~cleanly }
      }
  }
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{ltcmdhooks}%
⟨latexrelease⟩                  {The~hook~management~system~for~commands}
⟨latexrelease⟩
```

The command `\__hook_cmd_begindocument_code:` is used in an internal hook, so we need to make sure it has a harmless definition after rollback as that will not remove it from the kernel hook.

```
⟨latexrelease⟩\cs_set_eq:NN \__hook_cmd_begindocument_code: \prg_do_nothing:
⟨latexrelease⟩
⟨latexrelease⟩\EndModuleRelease
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨@@=⟩
```

File j
ltalloc.dtx

1 Counters

This section deals with counter and other variable allocation.

```
⟨*2ekernel⟩
```

The following are from plain TEX:

`\z@` A zero dimen or number. It's more efficient to write `\parindent\z@` than `\parindent 0pt`.

`\@ne` The number 1.

`\m@ne` The number −1.

`\tw@` The number 2.

`\sixt@@n` The number 16.

`\@m` The number 1000.

`\@MM` The number 20000.

`\@xxxii` The constant 32.

```
\chardef\@xxxii=32
```

(*End definition for* `\@xxxii`.)

`\@Mi` `\@Mii` `\@Miii` `\@Miv` Constants 10001–10004.

```
\mathchardef\@Mi=10001
\mathchardef\@Mii=10002
\mathchardef\@Miii=10003
\mathchardef\@Miv=10004
```

(*End definition for* `\@Mi` *and others.*)

`\@tempcnta` `\@tempcntb` Scratch count registers used by LATEX kernel commands.

```
\newcount\@tempcnta
\newcount\@tempcntb
```

(*End definition for* `\@tempcnta` *and* `\@tempcntb`.)

`\if@tempswa` General boolean switch used by LATEX kernel commands.

```
\newif\if@tempswa
```

(*End definition for* `\if@tempswa`.)

`\@tempdima` `\@tempdimb` `\@tempdimc` Scratch dimen registers used by LATEX kernel commands.

```
\newdimen\@tempdima
\newdimen\@tempdimb
\newdimen\@tempdimc
```

(*End definition for* `\@tempdima`, `\@tempdimb`, *and* `\@tempdimc`.)

`\@tempboxa` Scratch box register used by LaTeX kernel commands.

```
\newbox\@tempboxa
```

(*End definition for* `\@tempboxa`.)

`\@tempskipa` `\@tempskipb` Scratch skip registers used by LaTeX kernel commands.

```
\newskip\@tempskipa
\newskip\@tempskipb
```

(*End definition for* `\@tempskipa` *and* `\@tempskipb`.)

`\@temptokena` Scratch token register used by LaTeX kernel commands.

```
\newtoks\@temptokena
```

(*End definition for* `\@temptokena`.)

`\@flushglue` Glue used for `\right-` & `\leftskip` = 0pt plus 1fil

```
\newskip\@flushglue \@flushglue = 0pt plus 1fil
```

(*End definition for* `\@flushglue`.)

⟨/2ekernel⟩

File k
ltcntrl.dtx

1 Program control structure

This section defines a number of control structure macros, such as while-loops and for-loops.
Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
⟨*2ekernel⟩
\message{control,}
```

```
\@whilenum TEST \do {BODY}
\@whiledim TEST \do {BODY}  : These implement the loop
          while  TEST  do  BODY  od
    where  TEST  is a TeX \ifnum or \ifdim test, respectively.
    They are optimized for the normal case of TEST initially false.

\@whilesw SWITCH \fi {BODY} : Implements the loop
               while SWITCH do BODY od
    Optimized for normal case of SWITCH initially false.

\@for NAME := LIST \do {BODY} : Assumes that LIST expands to A1,A2,
     ... ,An .
     Executes  BODY  n  times, with  NAME = Ai  on the i-th iteration.
     Optimized for the normal case of n = 1.  Works for n=0.

\@tfor NAME := LIST \do {BODY}
     if, before expansion, LIST = T1 ... Tn  where each Ti is a
     token or {...}, then executes  BODY  n  times, with  NAME = Ti
     on the i-th iteration.  Works for n=0.

 NOTES: 1. These macros use no \@temp sequences.
        2. These macros do not work if the body contains anything that
        looks syntactically to TeX like an improperly balanced \if
        \else \fi.

\@whilenum TEST \do {BODY} ==
 BEGIN
   if  TEST
     then  BODY
           \@iwhilenum{TEST \relax BODY}
 END

\@iwhilenum {TEST BODY} ==
 BEGIN
   if  TEST
     then  BODY
```

```
            \@nextwhile = def(\@iwhilenum)
      else  \@nextwhile = def(\@whilenoop)
    fi
    \@nextwhile {TEST BODY}
  END

 \@whilesw SWITCH \fi {BODY} ==
  BEGIN
    if SWITCH
      then BODY
           \@iwhilesw {SWITCH BODY}\fi
    fi
  END

 \@iwhilesw {SWITCH BODY} \fi ==
  BEGIN
    if SWITCH
      then BODY
           \@nextwhile = def(\@iwhilesw)
      else \@nextwhile = def(\@whileswnoop)
    fi
    \@nextwhile {SWITCH BODY} \fi
  END
```

End of historical LaTeX 2.09 comments.

\@whilenoop
\@whilenum
\@iwhilenum

```
\long\def\@whilenum#1\do #2{\ifnum #1\relax #2\relax\@iwhilenum{#1\relax
     #2\relax}\fi}
\long\def\@iwhilenum#1{\ifnum #1\expandafter\@iwhilenum
         \else\expandafter\@gobble\fi{#1}}
```

(*End definition for* `\@whilenoop`, `\@whilenum`, *and* `\@iwhilenum`.)

\@whiledim
\@iwhiledim

```
\long\def\@whiledim#1\do #2{\ifdim #1\relax#2\@iwhiledim{#1\relax#2}\fi}
\long\def\@iwhiledim#1{\ifdim #1\expandafter\@iwhiledim
        \else\expandafter\@gobble\fi{#1}}
```

(*End definition for* `\@whiledim` *and* `\@iwhiledim`.)

\@whileswnoop
\@whilesw
\@iwhilesw

```
\long\def\@whilesw#1\fi#2{#1#2\@iwhilesw{#1#2}\fi\fi}
\long\def\@iwhilesw#1\fi{#1\expandafter\@iwhilesw
         \else\@gobbletwo\fi{#1}\fi}
```

(*End definition for* `\@whileswnoop`, `\@whilesw`, *and* `\@iwhilesw`.)

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\@for NAME := LIST \do {BODY} ==
   BEGIN \@forloop expand(LIST),\@nil,\@nil \@@ NAME {BODY} END

\@forloop CAR, CARCDR, CDRCDR \@@ NAME {BODY} ==
  BEGIN
    NAME = CAR
    if def(NAME) = def(\@nnil)
      else BODY;
            NAME = CARCDR
            if def(NAME) = def(\@nnil)
              else BODY
                   \@iforloop CDRCDR \@@ NAME \do {BODY}
            fi
    fi
  END

\@iforloop CAR, CDR \@@ NAME {BODY} =
    NAME = CAR
    if def(NAME) = def(\@nnil)
       then  \@nextwhile = def(\@fornoop)
       else  BODY ;
             \@nextwhile = def(\@iforloop)
    fi
    \@nextwhile name cdr {body}

\@tfor NAME := LIST \do {BODY}
   =  \@tforloop LIST \@nil \@@ NAME {BODY}

\@tforloop car cdr \@@ name {body} =
    name = car
    if def(name) = def(\@nnil)
       then  \@nextwhile == \@fornoop
       else  body ;
             \@nextwhile == \@forloop
    fi
    \@nextwhile name cdr {body}
```

End of historical LaTeX 2.09 comments.

`\@nnil`

```
\def\@nnil{\@nil}
```

(*End definition for* `\@nnil`.)

`\@empty`

```
\def\@empty{}
```

(*End definition for* `\@empty`.)

\@fornoop

```
\long\def\@fornoop#1\@@#2#3{}
```

(*End definition for* `\@fornoop`.)

\@for

```
\long\def\@for#1:=#2\do#3{%
  \expandafter\def\expandafter\@fortmp\expandafter{#2}%
  \ifx\@fortmp\@empty \else
    \expandafter\@forloop#2,\@nil,\@nil\@@#1{#3}\fi}
```

(*End definition for* `\@for`.)

\@forloop

```
\long\def\@forloop#1,#2,#3\@@#4#5{\def#4{#1}\ifx #4\@nnil \else
       #5\def#4{#2}\ifx #4\@nnil \else#5\@iforloop #3\@@#4{#5}\fi\fi}
```

(*End definition for* `\@forloop`.)

\@iforloop

```
\long\def\@iforloop#1,#2\@@#3#4{\def#3{#1}\ifx #3\@nnil
       \expandafter\@fornoop \else
      #4\relax\expandafter\@iforloop\fi#2\@@#3{#4}}
```

(*End definition for* `\@iforloop`.)

\@tfor

```
\def\@tfor#1:={\@tf@r#1 }
\long\def\@tf@r#1#2\do#3{\def\@fortmp{#2}\ifx\@fortmp\space\else
    \@tforloop#2\@nil\@nil\@@#1{#3}\fi}
\long\def\@tforloop#1#2\@@#3#4{\def#3{#1}\ifx #3\@nnil
       \expandafter\@fornoop \else
      #4\relax\expandafter\@tforloop\fi#2\@@#3{#4}}
```

(*End definition for* `\@tfor`.)

\@break@tfor Break out of a `\@tfor` loop. This should be called *inside* the scope of an `\if`. See `\@iffileonpath` for an example.

```
\long\def\@break@tfor#1\@@#2#3{\fi\fi}
```

(*End definition for* `\@break@tfor`.)

\@removeelement Removes an element from a comma-separated list and puts it into a control sequence, called as `\@removeelement{`⟨*element*⟩`}{`⟨*list*⟩`}{`⟨*cs*⟩`}`. Due to the implementation method the ⟨*element*⟩ is not allowed to contain braces.

```
\def\@removeelement#1#2#3{%
  \def\reserved@a##1,#1,##2\reserved@a{##1,##2\reserved@b}%
  \def\reserved@b##1,\reserved@b##2\reserved@b{%
    \ifx,##1\@empty\else##1\fi}%
  \edef#3{%
    \expandafter\reserved@b\reserved@a,#2,\reserved@b,#1,\reserved@a}}
```

(*End definition for* `\@removeelement`.)

⟨/2ekernel⟩

File l
lterror.dtx

1 Error handling and tracing

This section defines LaTeX's error commands.

```
⟨*2ekernel⟩
```

The '2ekernel' code ensures that a `\usepackage{autoerr}` is essentially ignored if a 'full' format is being used that has the error messages already in the format.

These days we don't support autoloading approach any longer, but this part bit is kept in case it is used in old documents.

```
\expandafter\let\csname ver@autoerr.sty\endcsname\fmtversion
```

1.1 General commands

`\MessageBreak` This command prints a new-line inside a message, followed by a continuation line begun with `\@msg@continuation`. Normally it is defined to be `\relax`, but inside messages, it is let to `\@message@break`.

```
\let\MessageBreak\relax
```

(*End definition for* `\MessageBreak`.)

`\GenericInfo` This takes two arguments: a continuation and a message, and sends the result to the log file.

```
\DeclareRobustCommand{\GenericInfo}[2]{%
   \begingroup
      \def\MessageBreak{^^J#1}%
      \set@display@protect
      \immediate\write\m@ne{#2\on@line.}%
   \endgroup
}
```

(*End definition for* `\GenericInfo`.)

`\GenericWarning` This takes two arguments: a continuation and a message, and sends the result to the screen.

```
\DeclareRobustCommand{\GenericWarning}[2]{%
   \begingroup
      \def\MessageBreak{^^J#1}%
      \set@display@protect
      \immediate\write\@unused{^^J#2\on@line.^^J}%
   \endgroup
}
```

(*End definition for* `\GenericWarning`.)

`\GenericError` This macro takes four arguments: a continuation, an error message, where to go for further information, and the help information. It displays the error message, and sets the error help (the result of typing `h` to the prompt), and does a horrible hack to turn the last context line (which by default is the only context line) into just three dots. This could be made more efficient.

```
\bgroup
\lccode`\@=`\ %
\lccode`\~=`\ %
\lccode`\}=`\ %
\lccode`\{=`\ %
\lccode`\T=`\T%
\lccode`\H=`\H%
\catcode`\ =11\relax%
\lowercase{%
\egroup%
```

Unfortunately TEX versions older than 3.141 have a bug which means that `^^J` does not force a linebreak in `\message` and `\errmessage` commands. So for these old TEX's we use `\typeout` to produce the message, and then have an empty `\errmessage` command. This causes an extra line of the form

.

To appear on the terminal, but if you do not like it, you can always upgrade your TEX! In order for your format to use this version, you must define the macro `\@TeXversion` to be the version number, e.g., 3.14 of the underlying TEX. See the comments in `ltdircheck.dtx`.

```
\dimen@\ifx\@TeXversion\@undefined4\else\@TeXversion\fi\p@%
\ifdim\dimen@>3.14\p@%
```

First the 'standard case'.

```
\DeclareRobustCommand{\GenericError}[4]{%
\begingroup%
\immediate\write\@unused{}%
\def\MessageBreak{^^J}%
\set@display@protect%
\edef%
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
{{#4}}%
\errhelp
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
\let
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
\@empty
\def\MessageBreak{^^J#1}%
\def~{\errmessage{%
#2.^^J^^J%
#3^^J%
Type  H <return>  for immediate help%
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
```

```
}}%
~%
\endgroup}%
\else%
```

Secondly the version for old TEX's.

```
\DeclareRobustCommand{\GenericError}[4]{%
\begingroup%
\immediate\write\@unused{}%
\def\MessageBreak{^^J}%
\set@display@protect%
\edef%
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
{{#4}}%
\errhelp
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
\let
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
\errmessage
\def\MessageBreak{^^J#1}%
\def~{\typeout{! %
#2.^^J^^J%
#3^^J%
Type  H <return>  for immediate help.}%
%    %<-------------------do not delete this space!------------------->%
\@err@                                                                  %
{}}%
~%
\endgroup}%
\fi}%
```

(*End definition for* `\GenericError`.)

`\PackageError`
`\PackageWarning`
`\PackageWarningNoLine`
`\PackageInfo`
`\ClassError`
`\ClassWarning`
`\ClassWarningNoLine`
`\ClassInfo`

These commands are intended for use by package and class writers, to give information to authors. The syntax is:

`\PackageError`{⟨*package*⟩}{⟨*error*⟩}{⟨*help*⟩}
`\PackageWarning`{⟨*package*⟩}{⟨*warning*⟩}
`\PackageWarningNoLine`{⟨*package*⟩}{⟨*warning*⟩}
`\PackageInfo`{⟨*package*⟩}{⟨*info*⟩}

and similarly for classes. The `Error` commands print the ⟨*error*⟩ message, and present the interactive prompt; if the author types `h`, then the ⟨*help*⟩ information is displayed. The `Warning` commands produce a warning but do not present the interactive prompt. The `WarningNoLine` commands do the same, but don't print the input line number. The `Info` commands write the message to the `log` file. Within the messages, the command `\MessageBreak` can be used to break a line, `\protect` can be used to protect command names, and `\space` is a space, for example:

```
\newcommand{\foo}{FOO}
\PackageWarning{ethel}{%
   Your hovercraft is full of eels,\MessageBreak
   and \protect\foo\space is \foo}
```

produces:

```
Package ethel warning: Your hovercraft is full of eels,
(ethel)                and \foo is FOO on input line 54.
```

```
\gdef\PackageError#1#2#3{%
   \GenericError{%
      (#1)\@spaces\@spaces\@spaces\@spaces
   }{%
      Package #1 Error: #2%
   }{%
      See the #1 package documentation for explanation.%
   }{#3}%
}
\def\PackageWarning#1#2{%
   \GenericWarning{%
      (#1)\@spaces\@spaces\@spaces\@spaces
   }{%
      Package #1 Warning: #2%
   }%
}
\def\PackageWarningNoLine#1#2{%
   \PackageWarning{#1}{#2\@gobble}%
}
\def\PackageInfo#1#2{%
   \GenericInfo{%
      (#1) \@spaces\@spaces\@spaces
   }{%
      Package #1 Info: #2%
   }%
}
\gdef\ClassError#1#2#3{%
   \GenericError{%
      (#1) \space\@spaces\@spaces\@spaces
   }{%
      Class #1 Error: #2%
   }{%
      See the #1 class documentation for explanation.%
   }{#3}%
}
\def\ClassWarning#1#2{%
   \GenericWarning{%
      (#1) \space\@spaces\@spaces\@spaces
   }{%
      Class #1 Warning: #2%
   }%
}
\def\ClassWarningNoLine#1#2{%
```

```
   \ClassWarning{#1}{#2\@gobble}%
}
\def\ClassInfo#1#2{%
   \GenericInfo{%
      (#1) \space\space\@spaces\@spaces
   }{%
      Class #1 Info: #2%
   }%
}
```

(*End definition for* `\PackageError` *and others.*)

\ClassNote
\ClassNoteNoLine
\PackageNote
\PackageNoteNoLine

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                  {\ClassNote}{Notes for classes/packages}%
\def\ClassNote#1#2{%
   \GenericWarning{%
      (#1) \space\space\@spaces\@spaces
   }{%
      Class #1 Info: #2%
   }%
}
\def\ClassNoteNoLine#1#2{\ClassNote{#1}{#2\@gobble}}
\def\PackageNote#1#2{%
   \GenericWarning{%
      (#1) \@spaces\@spaces\@spaces
   }{%
      Package #1 Info: #2%
   }%
}
\def\PackageNoteNoLine#1#2{\PackageNote{#1}{#2\@gobble}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

We don't roll back, because if this code is used by packages then most often they will not have rollback code implemented, so they would immediately break even if they otherwise would work fine.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\ClassNote}{Notes for classes/packages}%
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\ClassNote` *and others.*)

\@latex@error
\@latex@warning
\@latex@warning@no@line
\@latex@info
\@latex@info@no@line

Errors and other info, for use in the LaTeX core.

```
\gdef\@latex@error#1#2{%
   \GenericError{%
      \space\space\space\@spaces\@spaces\@spaces
   }{%
      LaTeX Error: #1%
   }{%
```

```
      See the LaTeX manual or LaTeX Companion for explanation.%
   }{#2}%
}
\def\@latex@warning#1{%
   \GenericWarning{%
      \space\space\space\@spaces\@spaces\@spaces
   }{%
      LaTeX Warning: #1%
   }%
}
\def\@latex@warning@no@line#1{%
   \@latex@warning{#1\@gobble}}
\def\@latex@info#1{%
   \GenericInfo{%
      \@spaces\@spaces\@spaces
   }{%
      LaTeX Info: #1%
   }%
}
\def\@latex@info@no@line#1{%
  \@latex@info{#1\@gobble}}
```

`\@font@warning` and `\@font@info` are defined later since they have to be redefined by the `tracefnt` package.

```
def\@font@warning#1{%
  \GenericWarning{%
     {(font)\@spaces\@spaces}%
     {Font Warning: #1}%
}
def\@font@info#1{%
  \GenericInfo{%
     (font)\space\@spaces
  }{%
     Font Info: #1%
  }%
}
```

(*End definition for* `\@latex@error` *and others.*)

`\@latex@note`
`\@latex@note@no@line`

These are "info" messages that display on the terminal not just in the transcript.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                    {\@latex@note}{Display notes}%
\def\@latex@note#1{%
   \GenericWarning{%
      \@spaces\@spaces\@spaces
   }{%
      LaTeX Info: #1%
   }%
}
```

```
\def\@latex@note@no@line#1{%
  \@latex@note{#1\@gobble}}
```

We don't make them undefined but rather point to `\@latex@info` because that's what they replace. This way we can change `\@latex@info` elsewhere without the need to further rollback sections.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@latex@note}{Display notes}%
⟨latexrelease⟩
⟨latexrelease⟩\let\@latex@note\@latex@info
⟨latexrelease⟩\let\@latex@note@no@line\@latex@info@no@line
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@latex@note` *and* `\@latex@note@no@line`.)

`\c@errorcontextlines` `\errorcontextlines` as a LaTeX counter, so that it may be manipulated with `\setcounter` (once it is defined :-)

```
\let\c@errorcontextlines\errorcontextlines
\c@errorcontextlines=-1
```

(*End definition for* `\c@errorcontextlines`.)

`\on@line` The message ' on input line n'.

```
\def\on@line{ on input line \the\inputlineno}
```

(*End definition for* `\on@line`.)

`\@warning` `\@@warning` `\@latexerr` Older LaTeX messages. For the moment, these `\let` to the new message commands. They may be changed later, once only obsolete packages and classes contain them.

```
\let\@warning\@latex@warning
\let\@@warning\@latex@warning@no@line
\global\let\@latexerr\@latex@error
```

(*End definition for* `\@warning`, `\@@warning`, *and* `\@latexerr`.)

`\@spaces` Four spaces.

```
\def\@spaces{\space\space\space\space}
```

(*End definition for* `\@spaces`.)

1.2 Specific errors

`\@eha` `\@ehb` `\@ehc` `\@ehd` The more common error help messages.

```
\gdef\@eha{%
  Your command was ignored.\MessageBreak
  Type \space I <command> <return> \space to replace it %
  with another command,\MessageBreak
  or \space <return> \space to continue without it.}
\gdef\@ehb{%
  You've lost some text. \space \@ehc}
\gdef\@ehc{%
  Try typing \space <return> %
```

```
  \space to proceed.\MessageBreak
  If that doesn't work, type \space X <return> \space to quit.}
\gdef\@ehd{%
  You're in trouble here.  \space\@ehc}
```

(*End definition for* `\@eha` *and others.*)

`\@notdefinable` Error message generated in `\@ifdefinable` from calls to one of the commands `\newcommand`, `\newlength` or `\newtheorem` specifying an already-defined command name or one that begins `\end`....

```
\gdef\@notdefinable{%
 \@latex@error{%
   Command \@backslashchar\reserved@a\space
   already defined.\MessageBreak
   Or name \@backslashchar\@qend... illegal,
   see p.192 of the manual}\@eha}
```

(*End definition for* `\@notdefinable`.)

`\@nolnerr` Generated by `\newline` and `\\` when called in vertical mode.

```
\gdef\@nolnerr{%
  \@latex@error{There's no line here to end}\@eha}
```

(*End definition for* `\@nolnerr`.)

`\@nocounterr` Generated by `\setcounter`, `\addtocounter` or `\newcounter` if applied to an undefined counter ⟨*cnt*⟩.

`\@nocnterr` Obsolete error message generated in LaTeX2.09 by `\setcounter`, `\addtocounter` or `\newcounter` for undefined counter. DO NOT use for LaTeX 2ε it MIGHT vanish! Use `\@nocounterr{`⟨*cnt*⟩`}` instead.

```
\gdef\@nocounterr#1{%
  \@latex@error{No counter '#1' defined}\@eha}
\gdef\@nocnterr{\@nocounterr?}
```

(*End definition for* `\@nocounterr` *and* `\@nocnterr`.)

`\@ctrerr` Called when trying to print the value of a counter numbered by letters that's greater than 26.

```
\gdef\@ctrerr{%
  \@latex@error{Counter too large}\@ehb}
```

(*End definition for* `\@ctrerr`.)

`\@nodocument` Error produced if paragraphs are typeset in the preamble.

```
\gdef\@nodocument{%
  \@latex@error{Missing \protect\begin{document}}\@ehd}
```

(*End definition for* `\@nodocument`.)

`\@badend` Called by `\end` that doesn't match its `\begin`. RmS 1992/08/24: added code to `\@badend` to display position of non-matching `\begin`. FMi 1993/01/14: missing space added.

The environment name has to literally match, i.e., what is stored in `\@currenvir` (after one expansion) must match what is passed to `\end` (without expansion). If not we complain. Not the absolute best solution but at least it avoids getting `\begin{foo} ended by \end{foo}` which was possible in the past.

```
\gdef\@badend#1{%
  \@latex@error{\protect\begin
     {\detokenize\expandafter{\@currenvir}}\@currenvline
     \space ended by \protect\end{\detokenize{#1}}}\@eha}
```

(*End definition for* `\@badend`.)

`\@badmath` Called by `\[`, `\]`, `\(` or `\)` when used in wrong mode.

```
\gdef\@badmath{%
  \@latex@error{Bad math environment delimiter}\@eha}
```

(*End definition for* `\@badmath`.)

`\@toodeep` Called by a list environment nested more than six levels deep, or an enumerate or itemize nested more than four levels.

```
\gdef\@toodeep{%
  \@latex@error{Too deeply nested}\@ehd}
```

(*End definition for* `\@toodeep`.)

`\@badpoptabs` Called by `\endtabbing` when not enough `\poptabs` have occurred, or by `\poptabs` when too many have occurred.

```
\gdef\@badpoptabs{%
  \@latex@error{\protect\pushtabs\space and \protect\poptabs
      \space don't match}\@ehd}
```

(*End definition for* `\@badpoptabs`.)

`\@badtab` Called by `\>`, `\+` , `\-` or `\<` when stepping to an undefined tab.

```
\gdef\@badtab{%
 \@latex@error{Undefined tab position}\@ehd}
```

(*End definition for* `\@badtab`.)

`\@preamerr` This error is special: it appears in places where we normally have to `\protect` expansions. However, to prevent a protection of the error message itself (which would result in the message getting printed not issued on the terminal) we need to locally reset `\protect` to `\relax`.

```
\gdef\@preamerr#1{%
  \begingroup
    \let\protect\relax
    \@latex@error{\ifcase #1 Illegal character\or
     Missing @-exp\or Missing p-arg\fi\space
     in array arg}\@ehd
  \endgroup}
```

(*End definition for* `\@preamerr`.)

\@badlinearg Occurs in \line and \vector command when a bad slope argument is encountered.

```
\gdef\@badlinearg{%
  \@latex@error{%
       Bad \protect\line\space or \protect\vector
       \space argument}\@ehb}
```

(*End definition for* \@badlinearg.)

\@parmoderr Occurs in a float environment or a \marginpar when encountered in inner vertical mode.

```
\gdef\@parmoderr{%
  \@latex@error{Not in outer par mode}\@ehb}
```

(*End definition for* \@parmoderr.)

\@fltovf Occurs in float environment or \marginpar when there are no more free boxes for storing floats.

```
\gdef\@fltovf{%
  \@latex@error{Too many unprocessed floats}\@ehb}
```

(*End definition for* \@fltovf.)

\@latexbug Occurs in output routine. This is bad news.

```
\gdef\@latexbug{%
  \@latex@error{This may be a LaTeX bug}{Call for help}}
```

(*End definition for* \@latexbug.)

\@badcrerr This error was removed and replaced by \@nolnerr.

```
%\def\@badcrerr {\@latex@error{Bad use of \protect\\}\@ehc}
```

(*End definition for* \@badcrerr.)

\@noitemerr \addvspace or \addpenalty was called when not in vmode. Probably caused by a missing \item.

```
\gdef\@noitemerr{%
  \@latex@error{Something's wrong--perhaps a missing %
      \protect\item}\@ehc}
```

(*End definition for* \@noitemerr.)

\@notprerr A command that can be used only in the preamble appears after the command \begin{document}.

```
\gdef\@notprerr{%
  \@latex@error{Can be used only in preamble}\@eha}
```

(*End definition for* \@notprerr.)

\@inmatherr Issued by commands that don't work correctly within math (like \item). There is no real error recovery happening, e.g., the user might get additional errors afterwards.

```
\gdef\@inmatherr#1{%
   \relax
   \ifmmode
    \@latex@error{Command \protect#1 invalid in math mode}\@ehc
   \fi}
```

(*End definition for* `\@inmatherr`.)

`\@invalidchar` An error for use with invalid characters. This is commented out, since we decided to use catcode 15 instead.

```
%\def\@invalidchar{\@latex@error{Invalid character in input}\@ehc}
```

(*End definition for* `\@invalidchar`.)

As well as the above error commands some error messages are directly coded to save space. The messages already present in LaTeX2.09 include:

`Environment --- undefined`

Issued by `\begin` for undefined environment.

`Tab overflow`

Occurs in `\=` when maximum number of tabs exceeded.

`\< in mid line`

Occurs in `\<` when it appears in middle of line.

`Float(s) lost`

In output routine, caused by a float environment or `\marginpar` occurring in inner vertical mode.

1.3 Tracing

The `trace` package implements the commands `\traceon` and `\traceoff` that work similar to `\tracingall` but skip certain code blocks that produce a lot of tracing output being of no interest during debugging (for example loading a font). Code blocks that should be hidden during tracing need to be surrounded by the macros `\conditionally@traceoff` and `\contionally@traceon`.

For the kernel code the `trace` package then redefines a number of macros to include this tracing support.

However, in order to allow any macro package to react to `\traceon` we also provide dummy definitions for the two commands in the kernel so that they can be used by external packages without the need to distinguish between `trace` being loaded or not.

`\conditionally@traceon`
`\conditionally@traceoff` These are only dummy definitions. For details see the `trace` package.

```
\let\conditionally@traceon\@empty
\let\conditionally@traceoff\@empty
```

(*End definition for* `\conditionally@traceon` *and* `\conditionally@traceoff`.)

⟨/2ekernel⟩

File m
ltpar.dtx

1 Paragraphs

This section of the kernel declares the commands used to set `\par` and `\everypar` when ever their function needs to be changed for a long time.

This file here describes the interfaces that have been in the kernel forever, used to implement the scenarios described below. They remain valid but are now augmented in the next file (`ltpara.dtx`) to add hooks to paragraphs. At some point we will consolidate the two files further.

There are two situations in which `\par` may be changed:

- Long-term changes, in which the new value is to remain in effect until the current environment is left. The environments that change `\par` in this way are the following:
  - All list environments (itemize, quote, etc.)
  - Environments that turn `\par` into a noop: tabbing, array and tabular.
- Temporary changes, in which `\par` is restored to its previous value the next time it is executed. The following are all such uses.
  - `\end` when preceded by `\@endparenv`, which is called by `\endtrivlist`
  - The mechanism for avoiding page breaks and getting the spacing right after section heads.

1.1 Implementation

`\@setpar` To permit the proper interaction of these two situations, long-term changes are made by the `\@setpar{`⟨*VAL*⟩`}` command. It's function is:

To set `\par`. It `\def`'s `\par` and `\@par` to ⟨*VAL*⟩.

`\@restorepar` Short-term changes are made by the usual `\def\par` commands. The original values are restored after a short-term change by the `\@restorepar` commands.

`\@@par` `\@@par` always is defined to be the original TEX `\par`.

`\everypar` `\everypar` is changed only for the short term. Whenever `\everypar` is set non-null, it should restore itself to null when executed.

The following commands change `\everypar` in this way:

- `\item`
- `\end` when preceded by `\@endparenv`, which is called by `endtrivlist`
- `\minipage`

When dealing with `\par` and `\everypar` remember the following two warnings:

1. Commands that make short-term changes to \par and \everypar must take account of the possibility that the new commands and the ones that do the restoration may be executed inside a group. In particular, \everypar is executed inside a group whenever a new paragraph begins with a left brace. The \everypar command that restores its definition should be local to the current group (in case the command is inside a minipage used inside someplace where \everypar has been redefined). Thus, if \everypar is redefined to do an \everypar{} it could take several executions of \everypar before the restoration "holds". This usually causes no problem. However, to prevent the extra executions from doing harm, use a global switch to keep anything harmful in the new \everypar from being done twice.

2. Commands that change \everypar should remember that \everypar might be supposed to set the following switches false:

   - @nobreak
   - @minipage

   they should do the setting if necessary.

```
⟨*2ekernel⟩
\message{par,}
```

\@setpar
\@par

Initiate a long-term change to \par.

```
\def\@setpar#1{\def\par{#1}\def\@par{#1}}
```

The default definition of \@par will ensure that if \@restorepar defines \par to execute \@par it will redefine itself to the primitive \@@par after one iteration.

```
\def\@par{\let\par\@@par\par}
```

(*End definition for* \@setpar *and* \@par.)

\@restorepar

Restore from a short-term change to \par.

```
\def\@restorepar{\def\par{\@par}}
⟨/2ekernel⟩
```

(*End definition for* \@restorepar.)

File n
ltpara.dtx

Abstract

This code defines four special kernel hooks to support paragraph tagging as well as four public hooks which can be occasionally useful.

1 Introduction

The building of paragraphs in the TEX engine(s) has a number of peculiarities that makes it on one hand fairly flexible but on the other hand somewhat awkward to control or reliably to extend. Thus to better understand the code below we start with a brief introduction of the mechanism; for more details refer to the TEXbook [**?**, chap. 14] (for the full truth you may even have to study the program code).

1.1 The default processing done by the engine

TEX automatically starts building a paragraph when it is currently in vertical mode and encounters anything that can only live in horizontal mode. Most often this is a character, but there are also many commands that can be used only in horizontal mode. If any of them is encountered, TEX will immediately back up (i.e., the character or command is read later again), adds a `\parskip` glue to the current vertical list unless the list is empty, switches to horizontal mode, starts its special "start of paragraph processing" and only then rereads the character or command that caused the mode change.[15]

This "start of paragraph processing" first adds an empty box at the start of the horizontal list of width `\parindent` (which represents the paragraph indentation) unless the paragraph was started with `\noindent` in which case no such box is added[16]. It then reads and processes all tokens stored in the special engine token register `\everypar`. After that it reads and processes whatever has caused the paragraph to start.

Thus out of the box, TEX offers the possibility to put some special code into `\everypar` to gain control at (more or less) the start of the paragraph. For example, in LaTeX and a number of packages, special code like the following is sometimes used:

```
\everypar{{\setbox\z@\lastbox}\everypar{} ...}
```

This removes the paragraph indentation box again (that was already placed by TEX), then resets `\everypar` so that it doesn't do anything on the next paragraph start and then does whatever it wants to do, e.g., in an `\item` of a list it will typeset the label in front of the paragraph text. However, there is only one such `\everypar` token register and if different packages and/or the kernel all attempt to add their own code here, coordination is very difficult if not impossible.

The process when the paragraph ends has different mechanisms and interfaces. A paragraph ends when the engine primitive `\par` is called while TEX is in unrestricted horizontal mode, i.e., is building a paragraph. At other times this primitive does nothing or generates as an error depending on the mode TEX is in, e.g., the `\par` in `\hbox{a\par b}` is ignored, but `$a\par b$` would complain.

[15] Already not quite true: the command `\noindent` starts the paragraph but influences the special processing by suppressing the paragraph indentation box normally inserted by it.

[16] That's a bit different from placing a zero-sized box!

If this primitive ends the paragraph it does some special "end of horizontal list" processing, then calls TEX's paragraph builder; this breaks the horizontal list into lines and then these lines are added as boxes to the enclosing vertical list and TEX returns to vertical mode.

This `\par` command can be given explicitly, but there are also situations in which TEX is generating it on the fly. Most often this happens when TEX encounters a blank line which is automatically changed to a `\par` command which is then executed. The other possibility is that TEX encounters a command which is incompatible with horizontal processing, e.g., `\vskip` (a request for adding vertical space). In such cases it silently backs up, and inserts a `\par` in the hope that this gets it out of horizontal mode and makes the vertical command acceptable.

The important point to note here is that TEX really inserts the command with the name `\par`, which can be redefined. Thus, it may not have its original "primitive" meaning and therefore may not end the horizontal list and call the paragraph builder. This approach offers some flexibility but also allows you to easily produce a TEX document that loops forever, for example, the simple line

```
A \let\par\relax \vskip
```

will start a horizontal list at `A`, redefines `\par`, then sees `\vskip` and inserts `\par` to end the paragraph. But this now only runs `\relax` so nothing changes and `\vskip` is read again, issues a `\par` which .... In short, it only takes a plain TEX document with five tokens to run forever (since no memory is consumed and therefore eventually exhausted).

There is no way other than changing `\par` to gain control at the end of a paragraph, i.e., there is no token list like `\everypar` that is inserted. Hence the only way to change the default behavior is to modify the action that `\par` executes, with similar issues as outlined before: different processes need to ensure that they do not overwrite their modifications or worse, think that the `\par` in front of them is the engine primitive while in fact it has already been changed by other code.

To make matters slightly worse there are a few places where TEX handles the situation differently (most likely for speed reasons back when computers were much slower). If TEX finds itself in unrestricted horizontal mode at the end of building a vertical box (for an `\insert`, `\vadjust` or executing the output routine code), it will finish the horizontal list not by issuing a `\par` command (which would be consistent with all other places) but by simply executing the primitive meaning of `\par`, regardless of the actual definition that `\par` has at the time.

Thus, if you have carefully crafted a redefined `\par` to execute some special actions at the end of a paragraph and you write something like

```
\vbox{Some paragraph ... text.}
```

you will find that your code does not get run for the last paragraph in that box. LATEX avoids this problem, by making sure that its boxes (such as `\parbox` or the `minipage` environment, etc.) all internally add an explicit `\par` at the end so that such code is run and TEX finds itself in vertical mode already without the need to start up the paragraph builder internally. But, of course, this only works for boxes under direct control of the LATEX kernel; if some package uses low-level `\vbox`es without adding this precaution the TEX optimization kicks in and no special `\par` code is executed.

And there is another optimization that is painful: if a paragraph is interrupted by a mathematical display, e.g., `\[...\]` in LATEX or `$$...$$` in plain TEX, then TEX will resume horizontal mode afterward, i.e., it will start to build a new horizontal list

without inserting an indentation box or \everypar at that point. However, if that list immediately ends with an explicit or implicit \par then TEX will simply throw away this "null" paragraph and not do its usual "end of horizontal list" processing, so this special case also needs to be accounted for when introducing any extended processing.

2 The new mechanism implemented for LATEX

To improve the situation (and also to support automatic tagging of PDF documents) we now offer public as well as private hooks at the start and end of the paragraph processing. The public hooks can be used by packages (or by the user in the preamble or within the document) and using the hook mechanisms it is possible to reorder or arrange code from different packages in such a way that these can safely coexist.

To make that happen we have to make use of the basic functionality that is offered by TEX, e.g., we install special code inside \everypar to provide hooks at the beginning and we redefine \par to do some special processing when appropriate to install hooks at the end of the paragraph.

In order to make this work, we have to ensure that package use of \everypar is not overwriting our code. This is done through a trick: we basically hide the real \everypar from the packages and offer them a new token register (with the same name). So if they install their own code it doesn't overwrite ours. Our code then inserts the new \everypar at the right place inside the process so that it looks as if it was the primitive \everypar.[17]

At the end of the paragraph it would be great if we could use a similar trick. However, due to the fact that TEX inserts the token \par (that doesn't have a defined meaning) we can't hide "the real thing™" and offer the package an indistinguishable alternate.

Fortunately, LATEX has already redefined \par for its own purposes. As a result there aren't many packages that attempt to change \par, because without a lot of extra care that would fail miserably. But the bottom line is that, if you load a package that alters \par then the end of paragraph hooks are most likely not executing while that redefinition is active.[18]

[17] Ideally, \everypar wouldn't be used at all by packages and instead they would simply write their code into the hooks now offered by the kernel. However, while this is the longterm goal and clearly an improvement (because then the packages do no longer need to worry about getting their code overwritten or needing to account for already existing code in \everypar), this will not happen overnight. For that reason support for this legacy method is retained.

[18] Similarly to the \everypar situation, the remedy is that such packages stop doing this and instead add their alterations into the paragraph hooks now provided.

2.1 The provided hooks

para/before
para/begin
para/end
para/after

The following four public hooks are defined and executed for each paragraph:

para/before This hook is executed after the kernel hook `\@kernel@before@para@before` (discussed below) in vertical mode immediately after TEX has contributed `\parskip` to the vertical list and before the actual paragraph processing in horizontal mode starts.

This hook should either not produce any typeset material or add only vertical material. If it starts a paragraph an error is generated. The reason is that we are in the starting process of processing a paragraph and so this would lead to endless recursion.[19]

para/begin This hook is executed after the kernel hook `\@kernel@before@para@begin` (discussed below) in horizontal mode immediately before the indentation box is placed (if there is any, i.e., if the paragraph hasn't been started with `\noindent`).

The indentation box to be typeset is available to the hook as `\IndentBox` and its automatic placement (after the hook is executed) can be prevented through `\OmitIndent`. More precisely `\OmitIndent` voids the box.

The indentation box is then typeset directly after the hook execution by something equivalent to `\box\IndentBox` followed by the current content of the token register `\everypar` that it is available to the kernel or to packages (that run some legacy code).

One has to be careful not to add any code to the hook that starts its own paragraph (e.g., by adding a `\parbox` or a `\marginpar` inside) because that would call the hook inside again (as a new paragraph is started there) and thus lead to an endless recursion ending only after exhausting the available memory. This can only be done by making sure that is not executed for the inner paragraphs (or at least not recursively forever).

para/end This hook is executed at the end of a paragraph when TEX is ready to return to vertical mode and after it has removed the last horizontal glue (but not any kerns) placed on the horizontal list. The code is still executed in horizontal mode so it is possible to add further horizontal material at this point, but it should not alter the mode (even a temporary exit from horizontal mode would create chaos—any attempt will cause an error message)! After the hook has ended the kernel hook `\@kernel@after@para@end` is executed and then TEX returns to vertical mode.

The hook is offered as public hook, but because of the requirement to stay within horizontal mode one needs to be careful in what is placed into the hook.[20]

This hook is implemented as a reversed hook.

para/after This hook is executed directly after TEX has returned to vertical mode and after any material that migrated out of the horizontal list (e.g., from a `\vadjust`) has processed.

[20] Maybe we should guard against that, but it would be rather tricky to implement as mode changes can happen across group boundaries so one would need to keep a private stack just for that. Well, something to ponder.

This hook should either not produce any typeset material or add only vertical material. However, for this hook starting a new paragraph is not a disaster so that it isn't prevented.

This hook is implemented as a reversed hook.

Once that hook code has been processed the kernel hook `\@kernel@after@para@after` is executed as the final action of the paragraph processing.

`\@kernel@before@para@before`
`\@kernel@after@para@after`
`\@kernel@before@para@begin`
`\@kernel@after@para@end`

As already mentioned above there are also four kernel hooks that are executed at the start and end of the processing.

`\@kernel@before@para@before` For future extensions, not currently used by the kernel.

`\@kernel@after@para@after` For future extensions, not currently used by the kernel.

`\@kernel@before@para@begin` Used by the kernel to implement tagging. This hook is executed at the very beginning of a paragraph after TEX has switched to horizontal mode but before any indentation box got added or any `\everypar` was run.

It should not generate typeset material that could alter the position. Note that it should never leave hmode, otherwise you will end with a loop! We could guard against this, but since it is an internal kernel hook that shouldn't be touched this isn't checked.

`\@kernel@after@para@end` Used by the kernel to implement tagging. It is executed directly after the public `para/end` hook. After it there is a quick check that we are still in horizontal mode, i.e., that the public hook has not mistakenly ended horizontal mode prematurely (this is an incomplete check just testing the mode and could perhaps be improved (at the cost of speed)).

2.2 Altered and newly provided commands

`\par`
`\endgraf`
`\para_end:`

An explicit request for ending a paragraph is provided in plain TEX under the name `\endgraf`, which simply uses the primitive meaning (regardless of what `\par` may have as its current definition). In LATEX `\endgraf` (with that behavior) was originally also available.

With the new paragraph handling in LATEX, ending a paragraph means a bit more than just calling the engine's paragraph builder: the process also has to add any hook code for the end of a paragraph. Thus `\endgraf` was changed to provide this additional functionality (along with `\par` remaining subject to its current meaning).

The expl3 name for this functionality is `\para_end:`.

> **Note:** *The next two commands are still under discussion and may slightly change their semantics (as described in the document) and/or their names between now and the 2021 Spring release!*

\OmitIndent
\para_omit_indent:

Inside the para/begin hook one can use this command to suppress the indentation box at the start of the paragraph. (Technically it is possible to use this command outside the hook as well, but this should not be relied upon.) The box itself remains available for use.

The expl3 name for the function is \para_omit_indent:.

\IndentBox
\g_para_indent_box

The box register holding the indentation box for the paragraph is available for inspection (or changes) inside hooks. It remains available even if the \OmitIndent command was used; in that case it will just not be automatically placed.

The expl3 name for the box register is \g_para_indent_box.

\RawIndent
\para_raw_indent:
\RawNoindent
\para_raw_noindent:
\RawParEnd
\para_raw_end:

\RawIndent *hmode material* \RawParEnd
\RawNoindent *hmode material* \RawParEnd

The commands \RawIndent and \RawNoindent are not meant for normal paragraph building (where the result is a textual paragraph in the traditional meaning of the word), but for special cases where TEX's low-level algorithm is used to achieve special effects, but where the result is not a "paragraph".

They are called "raw", because they bypass LATEX's hook mechanism for paragraphs and simply invoke the low-level TEX algorithm. I.e., they are like the original TEX primitives \indent and \noindent (that is they execute no hooks other than \everypar) except that they can only be used in vertical mode and generate an error if found elsewhere.

To avoid issues a paragraph started by them should always be ended by \RawParEnd[21] and not by \par (or a blank line), because the latter will execute hooks which then have no counterpart at the beginning of the paragraph. It is the responsibility of the programmer to make sure that they are properly paired. This also means that one should not put arbitrary user content between these commands if that content could contain stray \pars.

The expl3 names for the functions are \para_raw_indent:, \para_raw_indent: and \para_raw_end:.

2.3 Examples

None of the examples in this section are meant for real use as they are far too simple-minded but they should give some ideas of what could be possible if a bit more care is applied.

2.3.1 Testing the mechanism

The idea is to output for each paragraph encountered some information: a paragraph sequence number, a level number in roman numerals, the environment in which this paragraph appears, and the line number where the start or end of the paragraph is, e.g., something like

```
PARA: 1-i start (document env. on input line 38)
PARA: 1-i end   (document env. on input line 38)
PARA: 2-i start (document env. on input line 40)
PARA: 3-ii start (minipage env. on input line 40)
```

```
PARA: 3-ii end   (minipage env. on input line 40)
PARA: 2-i end   (document env. on input line 41)
```

As you can see paragraph 2 starts on line 40 and ends on 41 and inside a minipage started paragraph 3 (start and end on line 40). If you run this on some document you will find that LaTeX considers more things "a paragraph" than you have probably thought.

This was generated by the following hook code:

```
\newcounter{paracnt}         % sequence counter
\newcounter{paralevel}       % level counter
```

To support paragraph nesting we need to maintain a stack of the sequence numbers. This is most easily done using expl3 functions, so we switch over. This is not a very general implementation, just enough for what we need and a bit of LaTeX 2_ε thrown in as well. When popping, the result gets stored in `\paracntvalue` and the `\ERROR` should never happen because it means we have tried to pop from an empty stack.

```
\ExplSyntaxOn
\seq_new:N \g_para_seq
\cs_new:Npn \ParaPush
  {\seq_gpush:No  \g_para_seq {\the\value{paracnt}}}
\cs_new:Npn \ParaPop  {\seq_gpop:NNF  \g_para_seq \paracntvalue \ERROR }
\ExplSyntaxOff
```

At the start of the paragraph increment both sequence counter and level and also save the then current sequence number on our stack.

```
\AddToHook{para/begin}{%
  \stepcounter{paracnt}\stepcounter{paralevel}%
  \ParaPush
```

To display the sequence number we `\typeout` the current sequence and level number. The command `\@currenvir` gives us the current environment and `\on@line` produces a space and the current input line number.

```
  \typeout{PARA: \arabic{paracnt}-\roman{paralevel} start
    (\@currenvir\space env.\on@line)}%
```

We also typeset the sequence number as a tiny red number in a box that takes up no horizontal space. This helps us seeing where LaTeX sees the start and end of the paragraphs in the document.

```
  \llap{\color{red}\tiny\arabic{paracnt}\ }%
}
```

At the end of the paragraph we display sequence number and level again. The level counter has the correct value but we need to retrieve the right sequence value by popping it off the stack after which it is available in `\paracntvalue` the way we have set this up above.

```
\AddToHook{para/end}{%
  \ParaPop
  \typeout{PARA: \paracntvalue-\roman{paralevel} end \space\space
    (\@currenvir\space env.\on@line)}%
```

We also typeset again a tiny red number with that value, this time sticking out to the right.[22] We also decrement the level counter since our level has finished.

```
  \rlap{\color{red}\tiny\ \paracntvalue}%
  \addtocounter{paralevel}{-1}%
}
\makeatother
```

2.3.2 Mark the first paragraph of each `itemize`

The code for this is rather simple. We supply some code that is executed only once inside a hook at the start of each `itemize`. We explicitly change the color back and forth so that we don't introduce grouping around the paragraph.

```
\AddToHook{env/itemize/begin}{%
  \AddToHookNext{para/begin}{\color{blue}}%
  \AddToHookNext{para/end}{\color{black}}%
}
```

As a result the first paragraph of each `itemize` will appear in blue.

2.4 Some technical notes

The code tries hard to be transparent for package code, but of course any change means that there is a potential for breaking other code. So in section we collect a few cases that may be of importance if low-level code is dealing with paragraphs that are now behaving slightly differently. The notes are from issues we observed and will probably grow over time.

2.4.1 Glue items between paragraphs (found with fancypar)

In the past LaTeX placed two glue items between two consecutive paragraphs, e.g.,

```
text1 \par text2 \par
```

would show something like

```
\glue(\parskip) 0.0 plus 1.0
\glue(\baselineskip) 5.16669
```

but now there is anothe `\parskip` glue (that is always 0pt):

```
\glue(\parskip) 0.0 plus 1.0
\glue(\parskip) 0.0
\glue(\baselineskip) 5.16669
```

The reason is that we generate a "fake" paragraph to gain control and safely add the early hooks, but this generates an additional glue item. That item doesn't contribute anything vertically but if somebody writes code that unravels a constructed list using `\lastbox`, `\unskip` and `\unpenalty` then the code has to remove one additional glue item or else it will fail.

[22] Note that this can alter the document pagination, because a paragraph ending in a display (e.g., an equation) will get an extra line—in that case our tiny number has an effect even though it doesn't take up any space, because it paragraph is no longer empty and thus isn't dropped!

3 The Implementation

```
⟨@@=para⟩
⟨*2ekernel | latexrelease⟩
\ExplSyntaxOn
⟨latexrelease⟩\NewModuleRelease{2021/06/01}{ltpara}
⟨latexrelease⟩                    {Paragraph~handling~and~hooks}
```

3.1 Providing hooks for paragraphs

para/before
para/after
para/begin
para/end

The public hooks. They are implemented as a paired set of hooks.

```
\hook_new_pair:nn{para/before}{para/after}
\hook_new_pair:nn{para/begin}{para/end}
```

(*End definition for* `para/before` *and others. These functions are documented on page 297.*)

\@kernel@before@para@before
\@kernel@after@para@after
\@kernel@before@para@begin
\@kernel@after@para@end

The corresponding kernel hooks (for tagging and future extensions).

```
\let \@kernel@before@para@before \@empty
\let \@kernel@before@para@begin  \@empty
\let \@kernel@after@para@end     \@empty
\let \@kernel@after@para@after   \@empty
```

(*End definition for* `\@kernel@before@para@before` *and others. These functions are documented on page 298.*)

\g__para_standard_everypar_tl

Whenever TEX starts a paragraph it inserts first an indentation box and then executes the tokens stored in `\tex_everypar:D` (known to LATEX as `\everypar`). We alter this behavior slightly here, so that hooks are added into the right place. Otherwise the process change remains transparent to any legacy code for this space.

We keep the standard code to be used by `\tex_everypar:D` in a separate token list because we have to switch back and forth for error recovery and so altering `\tex_everypar:D` all the time should be a tiny bit faster.

```
\tl_new:N \g__para_standard_everypar_tl
```

Here is now its definition:

```
\tl_gset:Nn \g__para_standard_everypar_tl {
```

First we remove the indentation box and store it in `\g_para_indent_box`. If there was none because the paragraph was started by `\noindent` the box register will be void.

```
  \box_gset_to_last:N \g_para_indent_box
```

This will make the newly started horizontal list empty, so if we stop it now and return to vertical mode it will be dropped by TEX. We do that but inside a group so that any `\parshape` settings will not get lost as we need them for later.

```
  \group_begin:
    \tex_par:D
  \group_end:
```

We then change `\tex_everypar:D` to generate an error so that we can detect and report if the `para/before` hook illegally changed out of vmode.

```
  \tex_everypar:D { \msg_error:nnnn { hooks }{ para-mode }{before}{vertical} }
  \@kernel@before@para@before
  \hook_use:n {para/before}
```

Assuming the hooks have been well behaved it is time to return to horizontal mode and start the paragraph in earnest. We already have the indentation box saved away so we now have to restart the paragraph with an empty `\tex_everypar:D` and with `\tex_noindent:D`. And we need to make sure not to get another `\parskip` or rather (since we can't prevent that) that it is of zero size.

```
\group_begin:
  \tex_everypar:D {}
  \skip_zero:N \tex_parskip:D
  \tex_noindent:D
\group_end:
```

That brings us back to the start of the horizontal list but we need to change `\tex_everypar:D` back to its normal content in case there are nested paragraphs coming up.

```
\tex_everypar:D{\g__para_standard_everypar_tl}
```

This is followed by executing the kernel and the public hook. The kernel hook is there to enable tagging.

```
\@kernel@before@para@begin
\hook_use:n {para/begin}
```

If we aren't in horizontal mode any longer the hooks above misbehaved.

```
\if_mode_horizontal: \else:
  \msg_error:nnnn { hooks }{ para-mode }{begin}{vertical} \fi:
```

Finally we reinsert the indentation box (unless suppressed) and then call `\everypar` the way legacy LaTeX code expects it.

However, adding the public `\everypar` is a bit tricky (see below) so we add that later, and indirectly.

```
\__para_handle_indent:
% \the \everypar           % <--- done differently below
}
```

(*End definition for* `\g__para_standard_everypar_tl`.)

`\tex_everypar:D` `\tex_everypar:D` then only has to execute `\g__para_standard_everypar_tl` by default.

```
\tex_everypar:D{\g__para_standard_everypar_tl}
```

(*End definition for* `\tex_everypar:D`.)

`\everypar` Tokens inserted at the beginning of the paragraph are placed into `\everypar` inside legacy LaTeX code, e.g., by the list environments or by headings to handle `\clubpenalty`, etc. Now this isn't any longer the primitive but simply a toks register used in the code above but to legacy LaTeX code that is transparent.

There is, however, a problem: a handful packages use exactly the same trick and replace the primitive with a token register and call the token register inside the renamed primitive. That is they assume that `\everypar` is the primitive and that it will still be called at the start of the paragraph even if renamed.

But if we have already replaced it by a token register then all they do is to give that token register a new name. Thus our code in `\tex_everypar:D` would call `\everypar` (which is now their token register) and the code that they added ends up in our token register which is then never used at all. A bit mind boggling I guess.

So what we have to do is not to call the token register `\everypar` by its name inside `\tex_everypar:D` but by using its actual register number.

```
\newtoks \everypar
```

After we have allocated a new toks register with the name \everypar the actual register number is available (briefly) inside \allocationnumber. So instead of \the\everypar we have to put \the\toks⟨*allocated number*⟩ at the end of \tex_everypar:D.

So what remains doing is to append a few tokens to the token list \g__para_standard_everypar_tl which we do now. We use x expansion here to get the value of \allocationnumber in, all the other tokens should not be expanded at this point.

One important point here is to terminate the register allocation number with a real space. This space will get swallowed up when the number is read. Anything else, such as \scan_stop: would remain in the input and that would mean that it would interfere with \everypar code that attempts to scan ahead to see how the paragraph text starts.

```
\tl_gput_right:Nx \g__para_standard_everypar_tl {
    \exp_not:N \the
    \exp_not:N \toks
    \the \allocationnumber
    \c_space_tl
}
```

(*End definition for* \everypar.)

\g_para_indent_box

For managing the indentation we need to provide a public accessible box register

```
\box_new:N \g_para_indent_box
```

(*End definition for* \g_para_indent_box. *This function is documented on page 299.*)

__para_handle_indent:

Adding (typesetting) the indent box is straight forward. If it was emptied before it does nothing.

```
\cs_new:Npn \__para_handle_indent: {
  \box_use_drop:N \g_para_indent_box
}
```

The declaration \para_omit_indent: (or \OmitIndent) changes that to do nothing.

```
\cs_new:Npn \para_omit_indent: {
  \box_gclear:N \g_para_indent_box
}
```

(*End definition for* __para_handle_indent:.)

\IndentBox
\OmitIndent

The LaTeX 2ε names for the indentation box and for suppressing it for use in the para/begin hook.

```
\cs_set_eq:NN \IndentBox \g_para_indent_box
\cs_set_eq:NN \OmitIndent \para_omit_indent:
```

(*End definition for* \IndentBox *and* \OmitIndent. *These functions are documented on page 299.*)

\para_end:

Adding hooks to the end of a paragraph is similar but here we need to alter the command that is used by TeX to end horizontal mode and return to vertical mode, i.e., \par.

This is a bit more complicated as this command can appear anywhere either explicitly or implicitly added by TeX in certain situations:

- when using \par in the code or the document
- when using a blank line (which is converted to \par)
- when TeX finds any commands incompatible with horizontal mode it issues a \par and then rereads the command.

Unfortunately, TEX has some (these days) unnecessary optimizations: if a \vbox ends and TEX is still in horizontal mode it simply exercises the paragraph builder instead of issuing a \par. It is therefore necessary for LATEX to ensure that this case doesn't happen and all boxes internally have a \par command at their end.

This \par may or may not run the "par primitive" (which is always available as \tex_par:D in expl3); it is permissible to have a changed meaning and it is in fact changed by LATEX in various ways at various points inside latex.ltx. For this LATEX 2_ε code has the following conventions: \@@par and \endgraf both refer to the default meaning (in the past this was the initex primitive) while \par is the current meaning which maybe does something else.

We are now going to change this default meaning to instead run \para_end:, which ultimately executes the initex primitive but additionally adds our hooks when appropriate. This way the change is again transparent to the legacy LATEX 2_ε code.

In most cases \para_end: should behave exactly like the primitive and we achieve this by simply expanding it to the primitive which is available to us as \tex_par:D. This way we don't have to care about whether TEX just does nothing (e.g., if in vertical mode already) or generates an error, etc.

```
\cs_new_protected:Npn \para_end: {
```

CCC Maybe needs more explanation. TEMP NOTE: What should happen if in outer hmode with an empty hlist?

The only case we care about is when we are in horizontal mode (i.e., doing typesetting) and not also in inner mode (i.e., making paragraphs and not building an \hbox.

```
\bool_lazy_and:nnT
      { \mode_if_horizontal_p: }
      { \bool_not_p:n { \mode_if_inner_p: } }
      { ...
```

Since this is executed for each and every paragraph in a document we try to stay as fast as possible, so we do not use the above construct but two conditionals instead. Using low-level \if_mode... conditions would be even faster but has the danger to conflict with conditionals in the user hooks.

If \para_end: is executed while TEX is currently doing a low-level assignment the test for horizontal mode may get executed as part of the assignment. That is normally not an issue but we just found one case where it is:

```
\afterassignment\lst@vskip\@tempskipa \z@ \par
```

If TEX is in hmode while that assignment happens then the \par is seen in hmode because in the above case the assignment may not be finished (one should have used \z@skip) and the \lst@vskip will get inserted into the middle of the conditional. The \lst@vskip then changes to vmode and you get a surprising error about the para/end hook having changed modes even if you don't have any hook code(!): it is the inserted \lst@vskip that is actually causing the change of mode.This is what happened when the output routines got started while a lstlisting environment (that redefines \vskip in this way) was active. This is really faulty coding, but we try to be proactive and guard the conditional so that any scanning is first stopped, thus:

```
  \scan_stop:
  \mode_if_horizontal:TF {
    \mode_if_inner:F {
```

In that case the action of the primitive would be to remove the last glue (but no kerns) from the horizontal list (constructed to form a paragraph) and then to append a penalty of 10000 and the `\parfillskip`; it then passes the whole list to the paragraph builder, which breaks it into lines and TEX then returns to vertical mode.

What we want to do is to add this hook code at the end of the horizontal list before any of the above happens. If there was a glue item at the end of the list then it should get removed before the hook code gets added so we have to arrange for this removal.

As in other simular cases, it maybe best to add here a `\nobreak` in case the hook itself adds glue and thus creates a non-explicit and unwanted potential breakpoont. On the other hand (as has been argued) the code in the hook should perhaps have the responsibility for adding such a guard penalty in this casse. This needs further analysis and decisions (as in emails).

In either case, good documentation of these hooks is essential, covering what the hook may or should provide and all such related considerations convernimg the content.

There is not much point in checking if there was really a glue item at the end of the horizontal list, instead we simply try to remove one using `\tex_unskip:D`: if there wasn't one this will do nothing.

```
\tex_unskip:D
```

We then execute the public hook (which may add some final typeset material) followed by the kernel hook that we need for adding tagging support. None of this is supposed to change the mode—at the moment we make only a very simple test for this, more devious changes go unnoticed, but too bad as they will then probably backfire badly.

```
\hook_use:n{para/end}
\@kernel@after@para@end
\mode_if_horizontal:TF {
```

The final action (before getting to the point where `\tex_par:D` is called) is to add an extra glue item so that the primitive is prevented from removing intended glue (if there was some). If we don't do this and the horizontal list ends in several glue items we would end up removing two glue items instead of just the last one, which would be wrong. We use glue (rather than a kern) as that will be removed by the primitive.

There is however one other TEX optimization that hurts: in a sequence like this `$$ ... $$ \par` (with `\par` being the primitive) TEX will be in horizontal mode after the display, ready to receive further paragraph text, but since the `\par` follows immediately there is a "null" paragraph at the end and TEX simply throws that away. The space between `$$` and `\par` got already dropped during the display processing so the `\par` is not removing any space and appending `\parfillskip`, instead it simply goes silently to vmode.

Now if we would have added something (to prevent glue removal) that would look to TEX like material after the display and so we would end up with an empty paragraph just containing a penalty and `\parfillskip`.

We therefore check if the current hlist does end in glue (`\tex_lastnodetype:D` has the value `11`) and if so we add a zero-length guard skip which will be removed by the following `\tex_par:D`.

```
\if_int_compare:w 11 = \tex_lastnodetype:D
  \tex_hskip:D \c_zero_dim
\fi:
```

To run the `para/after` hook we first end the paragraph. This means that the `\tex_par:D` at the very end is unnecessary but executing it there unnecessarily is better than having code that tests for all the different mode possibilities.

```
            \tex_par:D
            \hook_use:n{para/after}
            \@kernel@after@para@after
          }
```

If we were not horizontal mode (the F case from above) then the earlier hook `para/end` must have been at fault, so we report that.

```
          { \msg_error:nnnn { hooks }{ para-mode }{end}{horizontal} }
```

Finally close out the nested conditionals.

```
      }
    }
```

And then we can use the primitive to truly end the paragraph.

```
    \tex_par:D
}
```

(*End definition for* `\para_end:`. *This function is documented on page 298.*)

`\para_raw_indent:`
`\para_raw_noindent:`
`\para_raw_end:`

The commands `\para_raw_indent:` and `\para_raw_noindent:` are like the primitives `\indent` and `\noindent` except that they can only be used in vertical mode.

To avoid issues a paragraph started by them should always be ended by `\para_raw_end:` and not by `\para_end:` or `\par` as the latter will execute hooks which then have no counterpart at the beginning of the paragraph. It is the responsibility of the programmer to make sure that they are properly paired.

```
\cs_new:Npn \para_raw_indent: {
  \mode_if_vertical:TF
      {
        \tex_everypar:D {
          \box_gset_to_last:N \g_para_indent_box
          \tex_everypar:D { \g__para_standard_everypar_tl }
          \__para_handle_indent:
          \the\everypar }
      }
      { \msg_error:nn { latex2e }{ raw-para } }
  \tex_indent:D
}
```

```
\cs_new:Npn \para_raw_noindent: {
  \mode_if_vertical:TF
      {
        \tex_everypar:D {
          \tex_everypar:D { \g__para_standard_everypar_tl }
          \the\everypar }
      }
      { \msg_error:nn { latex2e }{ raw-para } }
  \tex_noindent:D
}
```

```
\cs_new_eq:NN \para_raw_end: \tex_par:D
```

(*End definition for* `\para_raw_indent:`, `\para_raw_noindent:`, *and* `\para_raw_end:`. *These functions are documented on page 299.*)

\RawIndent
\RawNoIndent
\RawParEnd

The LaTeX 2ε names for starting and ending a paragraph without adding any hooks.

```
\cs_set_eq:NN \RawIndent   \para_raw_indent:
\cs_set_eq:NN \RawNoindent \para_raw_noindent:
\cs_set_eq:NN \RawParEnd   \para_raw_end:
```

(*End definition for* \RawIndent, \RawNoIndent, *and* \RawParEnd. *These functions are documented on page 299.*)

This ends the para module code.

```
⟨@@=⟩
```

\par
\endgraf
\@@par

Having the new default definition for \par we also have to set it up so that it gets used. This involves three commands: \par, \@@par (to which LaTeX resets \par occasionally) and \endgraf, which is another name for the "default" action of \par.

```
\cs_set_eq:NN \par     \para_end:
\cs_set_eq:NN \@@par   \para_end:
\cs_set_eq:NN \endgraf \para_end:
```

(*End definition for* \par, \endgraf, *and* \@@par. *These functions are documented on page 298.*)

While this is not integrated properly into the format we have to redo the \everypar setting from the kernel, otherwise that gets lost (as it happens before that file is loaded).

```
\everypar{\@nodocument} %% To get an error if text appears before the
```

3.2 The error messages

This one is used when we detect that some hook code has changed the mode where it shouldn't, e.g., by starting or ending a paragraph. The first argument is the hook name second the mode it should have stayed in but didn't.

```
\msg_new:nnnn { hooks } { para-mode }
  {
    Illegal~mode~ change~ in~ hook~ 'para/#1'.\\
    Hook~ code~ did~ not~ remain~ in~ #2~ mode.
  }
  {
    Paragraph~ hooks~ cannot~ change~ the~ TeX~ mode~ without~ causing~
    endless~ recursion.~ The~ hook~ code~ in~ 'para/#1'~ needs~ to~ stay~
    in~ #2~ mode,~ but~ it~ didn't.~ Examine~ the~ hook~
    code~ with~ \iow_char:N \\ShowHook~ to~ find~ the~ issue.
  }
```

And here is one used in the "raw" commands when they are used outside of vertical mode.

```
\msg_new:nnnn { latex2e } { raw-para }
  {
     Not~ in~ vertical~ mode.
  }
  {
    Starting~ a~ paragraph~ with~ \iow_char:N \\RawIndent~ or~
    \iow_char:N \\RawNoindent \\
    (or~ \iow_char:N \\para_raw_indent:~ or~
    \iow_char:N \\para_raw_noindent:)~ is~ only~ allowed \\
    if~ LaTeX~ is~ in~ vertical~ mode.
  }
```

```
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {ltpara}{Undo~hooks~for~paragraphs}
⟨latexrelease⟩
⟨latexrelease⟩\let \OmitIndent  \@undefined
⟨latexrelease⟩\let \IndentBox   \@undefined
⟨latexrelease⟩\let \RawIndent   \@undefined
⟨latexrelease⟩\let \RawNoindent \@undefined
⟨latexrelease⟩\let \RawParEnd   \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\cs_set_eq:NN \par     \tex_par:D
⟨latexrelease⟩\cs_set_eq:NN \@@par   \tex_par:D
⟨latexrelease⟩\cs_set_eq:NN \endgraf \tex_par:D
⟨latexrelease⟩
```

We also need to clean up the primitive "everypar" as that should no longer execute any code by default. And, of course, make `\everypar` become the primitive again.

```
⟨latexrelease⟩\tex_everypar:D {}
⟨latexrelease⟩\cs_set_eq:NN \everypar \tex_everypar:D
⟨latexrelease⟩
⟨latexrelease⟩\EndModuleRelease
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
```

File o
ltmeta.dtx

Abstract

This code defines the `\DocumentMetadata` interface.

1 Introduction

In the past there was no dedicated location to declare settings concerning a document as a whole. Settings are placed somewhere in the preamble or with the class options or even with some package options. For some settings this can be too late, for example the pdf version can no longer be changed if a package has used code which already opened the PDF.

`\DocumentMetadata` as a new command unifies such settings in one place. It must be used before `\documentclass` but can be issued more than once there.

At the moment most of the code run by `\DocumentMetadata` is external to the format and subject to change. This includes the supported key/values.

For that reason all that happens right now in the format is to look for suitable support files and if found, to redirect the processing to them.

1.1 `\DocumentMetadata`

`\DocumentMetadata` `\DocumentMetadata{`⟨*key-value list*⟩`}`

The keys defined for `\DocumentMetadata` currently allow to set the PDF version, to set the PDF `/Lang`, to uncompress a PDF, to set the language and to declare a few PDF standards and some color profiles.

`\DocumentMetadata` is also used to activate the new PDF management code and it loads a number of required files for the PDF management code. As this forces the loading of the backend files, a backend which can't be detected automatically like `dvipdfmx`, must be set in the first `\DocumentMetadata` call (if there is more than one).

The full set of keys currently supported is documented in `documentmetadata-support.pdf` for now.

2 The Implementation

```
⟨*2ekernel | latexrelease⟩
```

Not needed yet but ...

```
%\ExplSyntaxOn
⟨latexrelease⟩\NewModuleRelease{2022/06/01}{ltmeta}
⟨latexrelease⟩                  {Document Metadata handling}
\let \IfDocumentMetadataTF \@secondoftwo
\protected\def\DocumentMetadata{%
  \InputIfFileExists{documentmetadata-support.ltx}%
     {}%
```

The above file is changing \DocumentMetadata to a suitable definition (or so we hope), so that we can try again — if not tough.

If the file can't be found we say so and carry on without it.

```
    {%
      \@latex@error{No support files for
                    \noexpand\DocumentMetadata found}
        {Is the 'LaTeX-lab' bundle installed?%
        \MessageBreak
        Without it, the declaration is ignored.}%
```

No point in trying this more than once if there are several calls in the document.

```
     \let\DocumentMetadata\@gobble
    }%
  \let \IfDocumentMetadataTF \@firstoftwo
  \DocumentMetadata
}
```

To allow package and class author to support for document links we provide also the new interface commands of the hyperref package for the creation of targets.

\MakeLinkTarget
\LinkTargetOn
\LinkTargetOff
\NextLinkTarget

```
\NewDocumentCommand\MakeLinkTarget{sO{}m}{%
  \ifvmode
    \special{}%
  \else
    \@savsf\spacefactor
    \smash{}%
    \spacefactor\@savsf
  \fi}
\NewDocumentCommand\LinkTargetOn{}{}
\NewDocumentCommand\LinkTargetOff{}{}
\NewDocumentCommand\NextLinkTarget{m}{}
```

(*End definition for* \MakeLinkTarget *and others.*)

We do not undo \MakeLinkTarget and friends if we roll back, in case they are used in packages that themselves do not offer rollback. This way a roll forward adds them, but the dummies remain if you roll back and you don't get missing csname errors if they are used.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{ltmeta}%
⟨latexrelease⟩                  {Undo Document Metadata handling}
⟨latexrelease⟩
⟨latexrelease⟩\let\DocumentMetadata\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndModuleRelease
```

Again for the future . . .

```
%\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
```

Restore module prefix (if any):

```
⟨@@=⟩
```

File p
ltspace.dtx

1 Spacing

This section deals with spacing, and line- and page-breaking.

1.1 User Commands

`\nopagebreak` `[`⟨*i*⟩`]` : ⟨*i*⟩ = 0,...,4.

Default argument = 4. Puts a penalty into the vertical list output as follows:

0 : penalty = 0
1 : penalty = `\@lowpenalty`
2 : penalty = `\@medpenalty`
3 : penalty = `\@highpenalty`
4 : penalty = 10000

`\pagebreak` `[`⟨*i*⟩`]` : same as except negatives of its penalty

`\linebreak` `[`⟨*i*⟩`]` : analog of the above

`\nolinebreak` `[`⟨*i*⟩`]` : analog of the above

`\samepage` : inhibits page breaking most places by setting the following penalties to 10000:

```
\interlinepenalty
\postdisplaypenalty
\interdisplaylinepenalty
\@beginparpenalty
\@endparpenalty
\@itempenalty
\@secpenalty
\interfootnotelinepenalty
```

`\\` : initially defined to be `\newline`

`\\[`⟨*length*⟩`]` : initially defined to be `\vspace{`⟨*length*⟩`}\newline`

Note: `\\*` adds a `\vadjust{\penalty 10000}`

OBSOLETE COMMANDS (which never made it into the manual):

`\obeycr` : defines <CR> == `\\\relax`

`\restorecr` : restores <CR> to its usual meaning.

1.2 Chris' comments

There are several aspects of the handling of space in horizontal mode that are inconsistent or do not work well in some cases. These are largely concerned with ignoring the effect of space tokens that would otherwise typeset an inter-word space.

Negating the effect of such space tokens is achieved by two mechanisms:

- `\unskip` is used to remove the glue just added by a space that has already had its effect; it is sometimes invoked after an `\ifdim` test on `\lastskip` (see below);
- `\ignorespaces` is used to ignore space-tokens yet to come.

The test done on \lastskip is sometimes for equality with zero and sometimes for being positive. Recall also that the test is only on the natural length of the glue and that no glue cannot be distinguished from glue whose natural length is zero: to summarise, a pretty awful test. It is not clear why these tests are not all the same; I think that they should all be for equality. One place where \unskip is often used is just before a \par (which itself internally does an \unskip) and one bit of code (in \@item) even has two \unskips before a \par. These uses may be fossil code but if they are necessary, maybe \@killglue would be even safer.

Such removal of glue by \unskip may sometimes have the wrong result, removing not the glue from a space-token but other explicit glue; this is sometimes not what is intended.

A common way to prevent such removal is to add an \hskip\z@ after the glue that should not be removed. This protects that glue against one \unskip with no test but not against more than one. It does work for 'tested \unskips'. This is used by \hspace* but not by \hspace; this is inconsistent as the star is supposed to prevent removal only at the beginning of a line, not at the end, or in a tabular, etc.

If this reason for removing glue were the only consideration then a tested-\unskip and protection by \hskip\z@ would suffice but would need to be consistently implemented.

However, the class of invisibles, commands and environments tries to be even cleverer: one of these tries to leave only one inter-word space whenever there is one before it and one after it; and it does this quite well.

But problems can arise when there is not a space-token on both sides of it; in particular, when an invisible appears at the beginning or end of a piece of text the method still leaves one space token whereas usually in these cases it should leave none.

Also, the current rules do not work well when more than one such command appears consecutively, separated by space-tokens; it leaves glue between every other invisible.

There is also a question about what these commands should do when they occur next to spaces that do not come from space tokens but, for example, from \hspace. Should they still produce 'just one space'? If so, which one? It is good to note that the manual is sufficiently cautious about invisibles that we are not obliged to make anything work.

Another interesting side-road to explore is whether the space-tokens either side of an \hspace{...} should be ignored.

One alternative to the current algorithm that is often suggested is that all glue around the invisible should be consolidated into a space after it (usually without stating how much glue should be put there). The command \nolinebreak is implemented this way (and \linebreak should also be). This does not work correctly for the following common case:

```
... some text
\index{some-word}
some-word and more text.
```

This is optimal coding since it is normal to index a word that gets split across a page-break on its starting page. This would, on the other hand, fix another common (and documented) failure of the current system: when the invisible is the last thing in a paragraph the space before it is not removed and, worse, it is also hidden from the paragraph-ending mechanism so that an 'empty' line can be created at the end of the paragraph.

Another deficiency (I think) of the current system is that the following is treated as having the `\index` command between the paragraphs, which is probably not what the author intended (since there is no empty line after it).

```
\index{beginnings}
Beginnings of paragraphs ...
```

I know of no algorithm that will handle satisfactorily even all the most common cases; note that it could be that the best algorithm may be different for different invisibles since, for example, the common uses and expected behaviour of `\index`, `\marginpar`, `\linebreak`, `\pagebreak` and `\vspace` are somewhat different. [For example, is `\vspace` ever used in the middle of a paragraph?]

One method that can (and is) used to make invisible commands produce no space when used at the beginning of text is to put in some glue that is nearly enough the same as no glue or glue of zero length in all respects except for the precise test for not being exactly equal to zero; examples of such glue are `\hskip 1sp` and, possibly better but more complex, `\hskip -1sp \hskip 1sp`. However, this only works when it is known that user-supplied text is about to start.

Some similar concerns apply to the handling of space and penalties in vertical mode; there is an extra hurdle here as `\unskip` does not work on the main vertical list. The complexity of the tests done by `\addvspace` have never been explained.

The implementation of space hacks etc for vertical mode is another major area that needs further attention; my earlier experiments did not produce much improvement over the current unsatisfactory situation.

One particular problem is what happens when the following very natural coding is used (part of the problem here is that this looks like an hmode problem, but it is not):

```
... end of text.

\begin{enumerate}
  \item \label{item:xxx} Item text.
\end{enumerate}
```

1.3 Some immediate actions

- Fix bug in `\linebreak`.
- Fix bug in `\\*`.
- Reimplement `\\`, etc, removing extra `\vadjust`s and getting better error trapping (this seems to involve a lot more tokens).
- Investigate whether `\\`, etc need to be errors in vmode; I think that they could be noops (maybe with a warning).
- Make all(?) `\unskips` include test for zero skip (rather than other tests or no test).
- Consider replacing `\hskip 1sp` by something better (here called an 'infinitesimal' skip).
- Look at all `\hskip\z@` (or similar) to see if they should be changed to an 'infinitesimal' skip.

- Resolve the inconsistency between `\hspace` and `\hspace*`.
- Remove unnecessary `\unskips`.
- Investigate and rationalise the 'newline' code.
- Find better algorithms for all sorts of things or, easier(?), fix TEX itself.

1.4 The code

```
⟨*2ekernel⟩
\message{spacing,}
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\pagebreak}{Make commands robust}%
```

`\pagebreak`
`\nopagebreak`

```
\DeclareRobustCommand\pagebreak{\@testopt{\@no@pgbk-}4}
\DeclareRobustCommand\nopagebreak{\@testopt\@no@pgbk4}
```

(*End definition for* `\pagebreak` *and* `\nopagebreak`.)

`\linebreak`
`\nolinebreak`

```
\DeclareRobustCommand\linebreak{\@testopt{\@no@lnbk-}4}
\DeclareRobustCommand\nolinebreak{\@testopt\@no@lnbk4}
```

(*End definition for* `\linebreak` *and* `\nolinebreak`.)

`\samepage`

```
\DeclareRobustCommand\samepage{\interlinepenalty\@M
   \postdisplaypenalty\@M
   \interdisplaylinepenalty\@M
   \@beginparpenalty\@M
   \@endparpenalty\@M
   \@itempenalty\@M
   \@secpenalty\@M
   \interfootnotelinepenalty\@M}
```

(*End definition for* `\samepage`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\pagebreak}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\pagebreak
⟨latexrelease⟩\kernel@make@fragile\nopagebreak
⟨latexrelease⟩\kernel@make@fragile\linebreak
⟨latexrelease⟩\kernel@make@fragile\nolinebreak
⟨latexrelease⟩\kernel@make@fragile\samepage
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\@no@pgbk

```
\def\@no@pgbk #1[#2]{%
  \ifvmode
    \penalty #1\@getpen{#2}%
  \else
    \@bsphack
    \vadjust{\penalty #1\@getpen{#2}}%
    \@esphack
  \fi}
```

(*End definition for* `\@no@pgbk`.)

\@no@lnbk

```
\def\@no@lnbk #1[#2]{%
  \ifvmode
    \@nolnerr
  \else
    \@tempskipa\lastskip
    \unskip
    \penalty #1\@getpen{#2}%
    \ifdim\@tempskipa>\z@
      \hskip\@tempskipa
      \ignorespaces
    \fi
  \fi}
```

(*End definition for* `\@no@lnbk`.)

\\ The purpose of the new code is to fix a few bugs; however, it also attempts to optimize the following, in order of priority:

1. efficient execution of plain `\\`;
2. efficient execution of `\\[...]`;
3. memory use;
4. name-space use.

The changes should make no difference to the typeset output. It appears to be safe to use `\reserved@e` and `\reserved@f` here (other reserved macros are somewhat disastrous).

These changes made `\newline` even less robust than it had been, so now it is explicitly robust, like `\\`.

The internal definition of the 'normal' definition of `\\`.

\@normalcr

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\@normalcr}{Make robust}%
\protected\def\@normalcr{%
  \let \reserved@e \relax
  \let \reserved@f \relax
  \@ifstar{\let \reserved@e \vadjust \let \reserved@f \nobreak
             \@xnewline}%
  \@xnewline}
```

```
\let\\\@normalcr
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@normalcr}{Make robust}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\\{%
⟨latexrelease⟩   \let \reserved@e \relax
⟨latexrelease⟩   \let \reserved@f \relax
⟨latexrelease⟩   \@ifstar{\let \reserved@e \vadjust \let \reserved@f \nobreak
⟨latexrelease⟩             \@xnewline}%
⟨latexrelease⟩  \@xnewline}
⟨latexrelease⟩\expandafter\let\expandafter\@normalcr
⟨latexrelease⟩     \csname\expandafter\@gobble\string\\ \endcsname
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\\` *and* `\@normalcr`.)

`\@vspace@calcify` Helper command to produce a `\vskip` that is first run through `\setlength`. This way the `calc` package can operate on the argument value.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@vspace@calcify}{Add calc support}%
\def\@vspace@calcify#1{\begingroup\setlength\skip@{#1}\vskip\skip@\endgroup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@vspace@calcify}{Add calc support}%
⟨latexrelease⟩
⟨latexrelease⟩\let\@vspace@calcify\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@vspace@calcify`.)

`\newline` A simple form of the 'normal' definition of `\\`.

```
\DeclareRobustCommand\newline{\@normalcr\relax}
```

(*End definition for* `\newline`.)

`\@xnewline`

```
\def\@xnewline{\@ifnextchar[% ] bracket matching
                   \@newline
                  {\@gnewline\relax}}
```

(*End definition for* `\@xnewline`.)

`\@newline`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
```

```
⟨latexrelease⟩                  {\@newline}{\newline calc support}%
\def\@newline[#1]{\let \reserved@e \vadjust
                    \@gnewline {\@vspace@calcify{#1}}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@newline}{\newline calc support}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@newline[#1]{\let \reserved@e \vadjust
⟨latexrelease⟩                    \@gnewline {\vskip #1}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@newline`.)

`\@gnewline` The `\nobreak` added to prevent null lines when `\\` ends an overfull line. Change made 24 May 89 as suggested by Frank Mittelbach and Rainer Schöpf

```
\def\@gnewline #1{%
  \ifvmode
    \@nolnerr
  \else
    \unskip \reserved@e {\reserved@f#1}\nobreak \hfil \break
  \fi}
```

(*End definition for* `\@gnewline`.)

`\@getpen`

```
\def\@getpen#1{\ifcase #1 \z@ \or \@lowpenalty\or
         \@medpenalty \or \@highpenalty
         \else \@M \fi}
```

(*End definition for* `\@getpen`.)

`\if@nobreak` Switch used to avoid page breaks caused by `\label` after a section heading, etc. It should be **GLOBALLY** set true after the `\nobreak` and **globally** set false by the next invocation of `\everypar`.

Commands that reset `\everypar` should globally set it false if appropriate.

```
\def\@nobreakfalse{\global\let\if@nobreak\iffalse}
\def\@nobreaktrue {\global\let\if@nobreak\iftrue}
\@nobreakfalse
```

(*End definition for* `\if@nobreak`.)

`\@savsk` `\@savsf` Registers used to save the space factor and last skip.

```
\newdimen\@savsk
\newcount\@savsf
```

(*End definition for* `\@savsk` *and* `\@savsf`.)

\@bsphack

\@bsphack and \@esphack used by macros such as \index and \begin{@float} ... \end{@float} that want to be invisible — i.e., not leave any extra space when used in the middle of text. Such a macro should begin with \@bsphack and end with \@esphack. The macro in question should not create any text, nor change the mode.

Before giving the current definition we give an extended definition that is currently not used (because it doesn't work as advertised:-)

These are generalised hacks which attempt to do sensible things when 'invisible commands' appear in vmode too.

They need to cope with space in both hmode (plus spacefactor) and vmode, and also cope with breaks etc. In vmode this means ensuring that any following \addvspace, etc sees the correct glue in \lastskip.

In fact, these improved versions should be used for other cases of 'whatsits, thingies etc' which should be invisible. They are only for commands, not environments (see notes on \@Esphack).

BTW, anyone know why the standard hacks are surrounded by \ifmmode\else rather than simply \ifhmode?

And are there any cases where saving the spacefactor is essential? I have some extensions where it is, but it does not appear to be so in the standard uses.

```
def \@bsphack{%
 \relax \ifvmode
   \@savsk \lastskip
   \ifdim \lastskip=\z@
   \else
     \vskip -\lastskip
   \fi
 \else
   \ifhmode
     \@savsk \lastskip
     \@savsf \spacefactor
   \fi
 \fi
```

I think that, in vmode, it is the safest to put in a \nobreak immediately after such things since writes, inserts etc followed by glue give valid breakpoints and, in general, it is possible to create breaks but impossible to destroy them.

```
def \@esphack{%
  \relax \ifvmode
    \nobreak
    \ifdim \@savsk=\z@
    \else
      \vskip\@savsk
    \fi
  \else
    \ifhmode
      \spacefactor \@savsf
      \ifdim \@savsk>\z@
        \ignorespaces
      \fi
```

```
    \fi
  \fi
```

For the moment we are going to ignore the vertical versions until they are correct.

```
\def\@bsphack{%
  \relax
  \ifhmode
    \@savsk\lastskip
    \@savsf\spacefactor
  \fi}
```

(*End definition for* `\@bsphack`.)

`\@esphack` Companion to `\@bsphack`. If this command is not properly paired with `\@bsphack` one might end up with a low-level TEX error: "BAD spacefactor". One possible cause is calling `\@bsphack` in vertical mode, then doing something that gets you (sometimes) into horizontal mode and finally calling `\@esphack`. Even if no error is generated that is wrong, because `\@esphack` will then use the saved values for `\@savsk` and `\@savsf` from some earlier invocation of `\@bsphack` which will have nothing to do with the current situation.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2018/10/10}%
⟨latexrelease⟩                  {\@esphack}{hyphenation and nobreak after space hack}%
⟨*2ekernel | latexrelease⟩
\def\@esphack{%
  \relax
  \ifhmode
    \spacefactor\@savsf
    \ifdim\@savsk>\z@

      \ifdim\lastskip=\z@
        \nobreak \hskip\z@skip
      \fi
      \ignorespaces
    \fi

  \else
    \ifvmode
      \if@nobreak\nobreak\else\if@noskipsec\nobreak\fi\fi
    \fi

  \fi}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2015/10/01}%
⟨latexrelease⟩                  {\@esphack}{hyphenation and nobreak after space hack}%
⟨latexrelease⟩\def\@esphack{%
⟨latexrelease⟩  \relax
⟨latexrelease⟩  \ifhmode
⟨latexrelease⟩    \spacefactor\@savsf
⟨latexrelease⟩    \ifdim\@savsk>\z@
⟨latexrelease⟩      \ifdim\lastskip=\z@
⟨latexrelease⟩        \nobreak \hskip\z@skip
⟨latexrelease⟩      \fi
```

```
⟨latexrelease⟩      \ignorespaces
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                 {\@esphack}{hyphenation and nobreak after space hack}%
⟨latexrelease⟩\def\@esphack{%
⟨latexrelease⟩  \relax
⟨latexrelease⟩  \ifhmode
⟨latexrelease⟩    \spacefactor\@savsf
⟨latexrelease⟩    \ifdim\@savsk>\z@
⟨latexrelease⟩      \nobreak \hskip\z@skip
⟨latexrelease⟩      \ignorespaces
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@esphack}{hyphenation and nobreak after space hack}%
⟨latexrelease⟩\def\@esphack{%
⟨latexrelease⟩  \relax
⟨latexrelease⟩  \ifhmode
⟨latexrelease⟩    \spacefactor\@savsf
⟨latexrelease⟩    \ifdim\@savsk>\z@
⟨latexrelease⟩      \ignorespaces
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@esphack`.)

`\@Esphack` A variant of `\@esphack` that sets the `@ignore` switch to true (as `\@esphack` used to do previously). This is currently used only for floats and similar environments. w

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                 {\@Esphack}{hyphenation after space hack}%
⟨*2ekernel | latexrelease⟩
\def\@Esphack{%
  \relax
  \ifhmode
    \spacefactor\@savsf
    \ifdim\@savsk>\z@
      \nobreak \hskip\z@skip
      \@ignoretrue
      \ignorespaces
    \fi
   \fi}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@Esphack}{hyphenation after space hack}%
⟨latexrelease⟩\def\@Esphack{%
⟨latexrelease⟩  \relax
⟨latexrelease⟩  \ifhmode
```

```
⟨latexrelease⟩     \spacefactor\@savsf
⟨latexrelease⟩     \ifdim\@savsk>\z@
⟨latexrelease⟩       \@ignoretrue
⟨latexrelease⟩       \ignorespaces
⟨latexrelease⟩     \fi
⟨latexrelease⟩    \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@Esphack`.)

`\@vbsphack` Another variant which is useful for invisible things which should not live in vmode (this is how some people feel about marginals).

If it occurs in vmode then it enters hmode and ensures that `\@savsk` is nonzero so that the `\ignorespaces` is put in later. It is not used at present.

```
\def \@vbsphack{ %
   \relax \ifvmode
     \leavevmode
     \@savsk 1sp
     \@savsf \spacefactor
   \else
     \ifhmode
       \@savsk \lastskip
       \@savsf \spacefactor
     \fi
   \fi
}
```

(*End definition for* `\@vbsphack`.)

1.5 Vertical spacing

LaTeX supports the plain TeX commands `\smallskip`, `\medskip` and `\bigskip`. However, it redefines them using `\vspace` instead of `\vskip`.

Extra vertical space is added by the command `\addvspace{`⟨*skip*⟩`}`, which adds a vertical skip of ⟨*skip*⟩ to the document. The sequence
`\addvspace{`⟨*s1*⟩`}` `\addvspace{`⟨*s2*⟩`}` is equivalent to
`\addvspace{`⟨*maximum of s1, s2*⟩`}`.

`\addvspace` should be used only in vertical mode, and gives an error if it's not. The `\addvspace` command does *not* add vertical space if `@minipage` is true. The minipage environment uses this to inhibit the addition of extra vertical space at the beginning.

Penalties are put into the vertical list with the `\addpenalty{`⟨*penalty*⟩`}` command. It works properly when `\addpenalty` and `\addvspace` commands are mixed.

The `@nobreak` switch is set true used when in vertical mode and no page break should occur. (Right now, it is used only by the section heading commands to inhibit page breaking after a heading.)

```
\addvspace{SKIP} ==
 BEGIN
  if vmode
    then if @minipage
```

```
          else if \lastskip =0
                  then  \vskip SKIP
                  else  if \lastskip < SKIP
                           then  \vskip -\lastskip
                                 \vskip SKIP
                           else if SKIP < 0 and \lastskip >= 0
                                  then \vskip -\lastskip
                                       \vskip \lastskip + SKIP
        fi      fi       fi      fi
   else useful error message (CAR).
 fi
END
```

`\@xaddvskip` Internal macro for `\vspace` handling the case that space has previously been added.

```
\def\@xaddvskip{%
  \ifdim\lastskip<\@tempskipb
    \vskip-\lastskip
    \vskip\@tempskipb
  \else
    \ifdim\@tempskipb<\z@
      \ifdim\lastskip<\z@
      \else
        \advance\@tempskipb\lastskip
        \vskip-\lastskip
        \vskip \@tempskipb
      \fi
    \fi
  \fi}
```

(*End definition for* `\@xaddvskip`.)

`\addvspace` Add vertical space taking into account space already added, as described above.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\addvspace}{\addvspace calc support}%
\def\addvspace#1{%
  \ifvmode
     \if@minipage\else
       \ifdim \lastskip =\z@
         \@vspace@calcify{#1}%
       \else
       \setlength\@tempskipb{#1}%
         \@xaddvskip
       \fi
     \fi
  \else
    \@noitemerr
  \fi}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\addvspace}{\addvspace calc support}%
```

```
⟨latexrelease⟩
⟨latexrelease⟩\def\addvspace#1{%
⟨latexrelease⟩  \ifvmode
⟨latexrelease⟩     \if@minipage\else
⟨latexrelease⟩       \ifdim \lastskip =\z@
⟨latexrelease⟩         \vskip #1\relax
⟨latexrelease⟩       \else
⟨latexrelease⟩       \@tempskipb#1\relax
⟨latexrelease⟩         \@xaddvskip
⟨latexrelease⟩       \fi
⟨latexrelease⟩     \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@noitemerr
⟨latexrelease⟩  \fi}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\addvspace`.)

`\addpenalty`

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\addpenalty}{\addpenalty}%
⟨*2ekernel | latexrelease⟩
```

Fix provided by Donald (though the original fix was not good enough). In 2005 Plamen Tanovski discovered that this fix wasn't good enough either as the `\vskip` kept getting bigger if several `\addpenalty` commands followed each other. Donald kindly send a new fix.

```
\def\addpenalty#1{%
  \ifvmode
    \if@minipage
    \else
      \if@nobreak
      \else
        \ifdim\lastskip=\z@
          \penalty#1\relax
        \else
          \@tempskipb\lastskip
```

We have to make sure the final `\vskip` seen by TEX is the correct one, namely `\@tempskipb`. However we may have to adjust for `\prevdepth` when placing the penalty but that should not affect the skip we pass on to TEX.

```
          \begingroup
            \@tempskipa\@tempskipb
            \advance \@tempskipb
              \ifdim\prevdepth>\maxdepth\maxdepth\else
```

If `\prevdepth` is -1000pt due to `\nointerlineskip` we better not add it!

```
                \ifdim \prevdepth = -\@m\p@ \z@ \else \prevdepth \fi
              \fi
            \vskip -\@tempskipb
            \penalty#1%
            \ifdim\@tempskipa=\@tempskipb
```

Do nothing if the `\prevdepth` check made no adjustment.

```
            \else
```

Combine the prevdepth adjustment into a single skip.

```
              \advance\@tempskipb -\@tempskipa
              \vskip \@tempskipb
            \fi
```

The final skip is always the specified length.

```
            \vskip \@tempskipa
          \endgroup
        \fi
      \fi
    \fi
  \else
    \@noitemerr
  \fi}%
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\addpenalty}{\addpenalty}%
⟨latexrelease⟩\def\addpenalty#1{%
⟨latexrelease⟩  \ifvmode
⟨latexrelease⟩    \if@minipage
⟨latexrelease⟩    \else
⟨latexrelease⟩      \if@nobreak
⟨latexrelease⟩      \else
⟨latexrelease⟩        \ifdim\lastskip=\z@
⟨latexrelease⟩          \penalty#1\relax
⟨latexrelease⟩        \else
⟨latexrelease⟩          \@tempskipb\lastskip
⟨latexrelease⟩          \vskip -\lastskip
⟨latexrelease⟩          \penalty#1%
⟨latexrelease⟩          \vskip\@tempskipb
⟨latexrelease⟩        \fi
⟨latexrelease⟩      \fi
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@noitemerr
⟨latexrelease⟩  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\addpenalty`.)

`\vspace`
`\@vspace`
`\@vspacer`

The new code for these commands depends on the following facts:

- The value of prevdepth is changed only when a box or rule is created and added to a vertical list;
- The value of prevdepth is used only when a box is created and added to a vertical list;
- The value of prevdepth is always local to the building of one vertical list.

```
\DeclareRobustCommand\vspace{\@ifstar\@vspacer\@vspace}
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@vspace}{Support calc in \vspace}%
```

We support calc syntax in the argument and therefore use `\setlength`.

```
\def\@vspace #1{%
  \ifvmode
    \@vspace@calcify{#1}%
    \vskip\z@skip
   \else
     \@bsphack
     \vadjust{\@restorepar
              \@vspace@calcify{#1}%
              \vskip\z@skip
              }%
     \@esphack
   \fi}
```

```
\def\@vspacer#1{%
  \ifvmode
    \dimen@\prevdepth
    \hrule \@height\z@
    \nobreak
    \@vspace@calcify{#1}%
    \vskip\z@skip
    \prevdepth\dimen@
  \else
    \@bsphack
    \vadjust{\@restorepar
             \hrule \@height\z@
             \nobreak
             \@vspace@calcify{#1}%
             \vskip\z@skip}%
    \@esphack
  \fi}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@vspace}{Support calc in \vspace}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@vspace #1{%
⟨latexrelease⟩  \ifvmode
⟨latexrelease⟩    \vskip #1
⟨latexrelease⟩    \vskip\z@skip
⟨latexrelease⟩   \else
⟨latexrelease⟩     \@bsphack
⟨latexrelease⟩     \vadjust{\@restorepar
⟨latexrelease⟩              \vskip #1
⟨latexrelease⟩              \vskip\z@skip
⟨latexrelease⟩              }%
⟨latexrelease⟩     \@esphack
⟨latexrelease⟩   \fi}
⟨latexrelease⟩\def\@vspacer#1{%
⟨latexrelease⟩  \ifvmode
```

```
⟨latexrelease⟩    \dimen@\prevdepth
⟨latexrelease⟩    \hrule \@height\z@
⟨latexrelease⟩    \nobreak
⟨latexrelease⟩    \vskip #1
⟨latexrelease⟩    \vskip\z@skip
⟨latexrelease⟩    \prevdepth\dimen@
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@bsphack
⟨latexrelease⟩    \vadjust{\@restorepar
⟨latexrelease⟩             \hrule \@height\z@
⟨latexrelease⟩             \nobreak
⟨latexrelease⟩             \vskip #1
⟨latexrelease⟩             \vskip\z@skip}%
⟨latexrelease⟩    \@esphack
⟨latexrelease⟩  \fi}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\vspace`, `\@vspace`, *and* `\@vspacer`.)

`\smallskip`
`\medskip`
`\bigskip`

```
\def\smallskip{\vspace\smallskipamount}
\def\medskip{\vspace\medskipamount}
\def\bigskip{\vspace\bigskipamount}
```

(*End definition for* `\smallskip`, `\medskip`, *and* `\bigskip`.)

`\smallskipamount`
`\medskipamount`
`\bigskipamount`

```
\newskip\smallskipamount \smallskipamount=3pt plus 1pt minus 1pt
\newskip\medskipamount   \medskipamount  =6pt plus 2pt minus 2pt
\newskip\bigskipamount   \bigskipamount =12pt plus 4pt minus 4pt
```

(*End definition for* `\smallskipamount`, `\medskipamount`, *and* `\bigskipamount`.)

1.6 Horizontal space (and breaks)

`\nobreakdashes` This idea is borrowed from the amsmath package but here we define a robust command.

This command is a low-level command designed for use only before hyphens or dashes (such as `-`, `--`, or `---`).

It could probably be better implemented: it may need its own private token register and temporary command.

Setting the hyphen in a box and then unboxing it means that the normal penalty will not be added after it—and if the penalty is not there a break will not be taken (unless an explicit penalty or glue follows, thus the final `\nobreak`).

Note that even if it is not followed by a '-', it still leaves vmode and sets the space-factor; so use it carefully!

```
\DeclareRobustCommand{\nobreakdashes}{%
  \leavevmode
  \toks@{}%
  \def\reserved@a##1{\toks@\expandafter{\the\toks@-}%
                     \futurelet\@let@token \reserved@b}%
  \def\reserved@b   {\ifx\@let@token -%
                         \expandafter\reserved@a
```

```
                      \else
                        \setbox\z@ \hbox{\the\toks@\nobreak}%
                        \unhbox\z@
                        \spacefactor\sfcode`\-
                      \fi}%
  \futurelet\@let@token \reserved@b
}
```

(*End definition for* `\nobreakdashes`.)

`\nobreakspace` `\@xobeysp` This is a robust command that produces a horizontal space at which, in paragraph-mode, a line-break is not possible. We then define an active `~` to expand to it since this is the documented behaviour of `~`. One reason for introducing this is that some 8-bit input encodings have a slot for such a space and we do not want to use active characters as the LaTeX internal commands.

The braces in the definition of `~` are needed to ensure that a following space is preserved when reading to/from internal files.

We need to keep `\@xobeysp` as it is widely used; so here it is let to the non-robust command `\nobreakspace` .

```
\DeclareRobustCommand{\nobreakspace}{%
   \leavevmode\nobreak\ }
\catcode `\~=13
\def~{\nobreakspace{}}
\expandafter\let\expandafter\@xobeysp\csname nobreakspace \endcsname
```

(*End definition for* `\nobreakspace` *and* `\@xobeysp`.)

`\@` Placed before a '.', makes it a sentence-ending period. Does the right thing for other punctuation marks as well. Does this by setting spacefactor to 1000.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\@}{Space after \@}%
⟨*2ekernel | latexrelease⟩
\def\@{\spacefactor\@m{}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@}{Space after \@}%
⟨latexrelease⟩\def\@{\spacefactor\@m}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@`.)

`\hspace`

```
\DeclareRobustCommand\hspace{\@ifstar\@hspacer\@hspace}
```

(*End definition for* `\hspace`.)

\@hspace

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@hspace}{Support calc with \hspace}%
\def\@hspace#1{\begingroup\setlength\skip@{#1}\hskip\skip@\endgroup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@hspace}{Support calc with \hspace}%

⟨latexrelease⟩
⟨latexrelease⟩\def\@hspace#1{\hskip #1\relax}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \@hspace.)

\@hspacer Extra \hskip 0pt added 1985/17/12 to guard against a following \unskip \relax added 13 Oct 88 for usual TEX lossage replaced both changes by \hskip\z@skip 27 Nov 91

```
\def\@hspacer#1{\vrule \@width\z@\nobreak
                \@hspace{#1}\hskip \z@skip}
```

(*End definition for* \@hspacer.)

\fill

```
\newskip\fill
\fill = 0pt plus 1fill
```

(*End definition for* \fill.)

\stretch

```
\def\stretch#1{\z@ \@plus #1fill\relax}
```

(*End definition for* \stretch.)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                  {\thinspace}{Start LR-mode}%
```

\enspace

```
\DeclareRobustCommand\enspace{\leavevmode@ifvmode\kern.5em }
```

(*End definition for* \enspace.)

\leavevmode@ifvmode Leave vmode but only if we are really in vmode, otherwise the expansion is empty (which is not the case with the default definition).

```
\protected\def\leavevmode@ifvmode{\ifvmode\expandafter\indent\fi}
```

(*End definition for* `\leavevmode@ifvmode`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\thinspace}{Start LR-mode}%
⟨latexrelease⟩\def\thinspace{\kern .16667em }
⟨latexrelease⟩\def\negthinspace{\kern-.16667em }
⟨latexrelease⟩\def\enspace{\kern.5em }
⟨latexrelease⟩\let\leavevmode@ifvmode\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\enskip` `\quad` `\qquad`

```
\def\enskip{\hskip.5em\relax}
\def\quad{\hskip1em\relax}
\def\qquad{\hskip2em\relax}
```

(*End definition for* `\enskip`, `\quad`, *and* `\qquad`.)

For Unicode engines, make the Unicode soft hyphen an active character defined as `\-`.

```
\ifx\Umathcode\@undefined\else
  \catcode "AD=13
  \def^^ad{\-}
\fi
```

`\obeycr` `\restorecr`

The following definitions will probably get deleted or moved to compatibility mode soon.

```
{\catcode`\^^M=13 \gdef\obeycr{\catcode`\^^M13 \def^^M{\\\relax}%
    \@gobblecr}%
{\catcode`\^^M=13 \gdef\@gobblecr{\@ifnextchar
\@gobble\ignorespaces}}
\gdef\restorecr{\catcode`\^^M5 }}
```

(*End definition for* `\obeycr` *and* `\restorecr`.)

```
⟨/2ekernel⟩
```

File q
ltlogos.dtx

1 Logos

Various logos are defined here.

\TeX The TEX logo, adjusted so that a full stop after the logo counts as ending a sentence.

```
⟨*2ekernel⟩
\DeclareRobustCommand\TeX{T\kern-.1667em\lower.5ex\hbox{E}\kern-.125emX\@}
```

(*End definition for* \TeX.)

\LaTeX The LATEX logo.

```
\DeclareRobustCommand{\LaTeX}{L\kern-.36em%
        {\sbox\z@ T%
         \vbox to\ht\z@{\hbox{\check@mathfonts
                              \fontsize\sf@size\z@
                              \math@fontsfalse\selectfont
                              A}%
                         \vss}%
        }%
        \kern-.15em%
        \TeX}
```

(*End definition for* \LaTeX.)

\LaTeXe The LATEX 2_ε logo as proposed by A-W designers.

```
\DeclareRobustCommand{\LaTeXe}{\mbox{\m@th
  \if b\expandafter\@car\f@series\@nil\boldmath\fi
  \LaTeX\kern.15em2$_{\textstyle\varepsilon}$}}
⟨/2ekernel⟩
```

(*End definition for* \LaTeXe.)

File r
ltfiles.dtx

1 File Handling

The following user commands are defined in this part:

`\document` (ie `\begin{document}`)
Reads in the .AUX files and `\catcode`'s `@` to 12.

`\nofiles`
Suppresses all file output by setting `\@filesw` false.

`\includeonly` `{`⟨*NAME1, ... ,NAMEn*⟩`}`
Causes only parts NAME1, ... ,NAMEn to be read by their `\include` commands. Works by setting partsw true and setting `\@partlist` to NAME1, ... ,NAMEn.

`\include` `{`⟨*NAME*⟩`}`
Does an `\input` NAME unless `\@partsw` is true and NAME is not in `\@partlist`. If `\@filesw` is true, then it directs .AUX output to NAME.AUX, including a checkpoint at the end.

`\input` `{`⟨*NAME*⟩`}`
The same as TeX's `\input`, except it allows optional braces around the file name. In LaTeX 2_ε, it also avoids the primitive 'missing file' error, if the file can not be found.

`\IfFileExists` `{`⟨*NAME*⟩`}{`⟨*then*⟩`}{`⟨*else*⟩`}`
If the file exists on the system, execute *then* otherwise execute *else*.

`\InputIfFileExists` `{`⟨*NAME*⟩`}{`⟨*then*⟩`}{`⟨*else*⟩`}`
If the file exists on the system, execute *then* and input *NAME* otherwise execute *else*.
Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
⟨*2ekernel⟩
\message{files,}
```

```
VARIABLES, SWITCHES AND INTERNAL COMMANDS:
  \@mainaux     : Output file number for main .AUX file.
  \@partaux     : Output file number for current part's .AUX file.
  \@auxout      : Either \@mainout or \@partout, depending on
                  which .AUX file output goes to.
  \@input{foo} : If file foo exists, then \input's it,
                  otherwise types a warning message.
  @filesw       : Switch – set false if no .AUX, .TOC, .IDX etc
                    files are to be written
  @partsw       : Set true by a \includeonly command.
  \@partlist    : Set to the argument of the \includeonly command.

  \cp@FOO       : The checkpoint for \include'd file FOO.TEX, written
                  by \@writeckpt at the end of file FOO.AUX


\includeonly{FILELIST} ==
 BEGIN
```

```
  \@partsw   := T
  \@partlist := FILELIST
 END

\include{FILE} ==
 BEGIN
  \clearpage
  if \@filesw = T
    then  \immediate\write\@mainaux{\string\@input{FILE.AUX}}
  fi
  if  \@partsw = T
    then \@tempswa := F
         \reserved@b == FILE
         for \reserved@a := \@partlist
             do if eval(\reserved@a) = eval(\reserved@b)
                   then \@tempswa := T          fi
             od
  fi

  if \@tempswa = T
     then \@auxout := \@partaux
          if \@filesw = T
            then  \immediate\openout\@partaux{FILE.AUX}
                  \immediate\write\@partaux{\relax}
          fi
          \@input{FILE.TEX}
          \clearpage
          \@writeckpt{FILE}
          if @filesw then \closeout \@partaux fi
          \@auxout := \@mainaux
     else \cp@FILE
  fi
 END

\@writeckpt{FILE} ==
 BEGIN
   if \@filesw = T
       \immediate\write on file \@partaux:
                 \@setckpt{FILE}{                  %% }
       for \reserved@a := \cl@@ckpt
          do  \immediate\write on file \@partaux:
                  \global\string\setcounter
                      {eval(\reserved@a)}{eval(\c@eval(\reserved@a))}
          od                                     %% {
       \immediate\write on file \@partaux:  }
   fi
 END

\@setckpt{FILE}{LIST} ==
 BEGIN
```

```
    G \cp@FILE := LIST
  END

  INITIALIZATION
    \@tempswa := T
```

End of historical LaTeX 2.09 comments.

\@mainaux
\@partaux

```
\newwrite\@mainaux
\newwrite\@partaux
```

(*End definition for* \@mainaux *and* \@partaux.)

\if@filesw
\if@partsw

```
\newif\if@filesw \@fileswtrue
\newif\if@partsw \@partswfalse
```

(*End definition for* \if@filesw *and* \if@partsw.)

\@clubpenalty

This stores the current normal (non-infinite) value of \clubpenalty; it should therefore be reset whenever the normal value is changed (as in the bibliography in the standard styles).

```
\newcount\@clubpenalty
\@clubpenalty \clubpenalty
```

(*End definition for* \@clubpenalty.)

\document

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩  {\document}{Added hook to load l3backend code}%
⟨*2ekernel | latexrelease⟩
\def\document{%
```

We do cancel the grouping as part of the \begin handling (this is now done inside \begin instead) so that the env/⟨*env*⟩/begin hook is not hidden inside \begingroup ... \endgroup.

```
%  \endgroup
  \UseOneTimeHook{begindocument/before}%
  \@kernel@after@begindocument@before
```

Added hook to load l3backend code:

```
  \@expl@sys@load@backend@@
  \ifx\@unusedoptionlist\@empty\else
    \@latex@warning@no@line{Unused global option(s):^^J%
            \@spaces[\@unusedoptionlist]}%
  \fi
  \@colht\textheight
  \@colroom\textheight \vsize\textheight
  \columnwidth\textwidth
  \@clubpenalty\clubpenalty
  \if@twocolumn
    \advance\columnwidth -\columnsep
```

```
    \divide\columnwidth\tw@ \hsize\columnwidth \@firstcolumntrue
  \fi
  \hsize\columnwidth \linewidth\hsize
  \begingroup\@floatplacement\@dblfloatplacement
    \makeatletter\let\@writefile\@gobbletwo
    \global \let \@multiplelabels \relax
    \@input{\jobname.aux}%
  \endgroup
  \if@filesw
    \immediate\openout\@mainaux\jobname.aux
    \immediate\write\@mainaux{\relax}%
  \fi
```

Dateline 1991/03/26: FMi added `\process@table` to support NFSS; This will also work with old lfonts if no other style defines `\process@table`. The following line forces the initialization of the math fonts.

```
  \process@table
  \let\glb@currsize\@empty  % Force math initialization.
  \normalsize
  \everypar{}%
```

So that punctuation in headings is not disturbed by verbatim or other local changes to the space factor codes, save the document default here. This will be locally reset by the output routine. For special cases a class may want to define `\normalsfcodes` directly, in case that definition will be used. (This is an old bug, problem existed in LaTeX2.0x and plain TeX.)

```
  \ifx\normalsfcodes\@empty
    \ifnum\sfcode`\.=\@m
      \let\normalsfcodes\frenchspacing
    \else
      \let\normalsfcodes\nonfrenchspacing
    \fi
  \fi
```

For similar reasons also save the default language, this will be reset locally in the output routine. In particular it allows hyphenation in the page head even if the page break happens in verbatim. If this has already been set by a package, set to the value of `\language` at this point.

```
  \ifx\document@default@language\m@ne
    \chardef\document@default@language\language
  \fi
```

Way back in 1991 (08/26) FMi & RmS set the `\@noskipsec` switch to true in the preamble and to false here. This was done to trap lists and related text in the preamble but it does not catch everything; hence Change 1.1g was introduced.

```
  \@noskipsecfalse
  \let \@refundefined \relax
```

Just before disabling the preamble commands we execute the begin document hook which contains any code contributed by `\AtBeginDocument`. Also disable the gathering of the file list, if no `\listfiles` has been issued. `\AtBeginDocument` is redefined at this point so that and such commands that get into the hook do not chase their tail...

```
\@kernel@before@begindocument
\UseOneTimeHook{begindocument}%
\@kernel@after@begindocument
```

Most of the following assignments will be done globally in case the user adds something like `\begin{multicols}` to the document hook, i.e. starts are group in `\begin{document}`.

Since a value of exactly 0pt for `\topskip` causes `\twocolumn[]` to misbehave, we add this check, hoping that it will not cause any problems elsewhere.

```
\ifdim\topskip<1sp\global\topskip 1sp\relax\fi
\global\@maxdepth\maxdepth
\global\let\@begindocumenthook\@undefined
\ifx\@listfiles\@undefined
  \global\let\@filelist\relax
  \global\let\@addtofilelist\@gobble
\fi
```

At the very end we disable all preamble commands. This has to happen after the begin document hooks was executed so that this hook can still use such commands.

```
\gdef\do##1{\global\let ##1\@notprerr}%
\@preamblecmds
```

The next line saves tokens and also allows `\@nodocument` to be used directly to trap preamble errors.

```
\global\let \@nodocument \relax
```

The next line is a pure safety measure in case a do list is ever expanded at the wrong place. In addition it will save a few tokens to get rid of the above definition.

```
\global\let\do\noexpand
```

```
\UseOneTimeHook{begindocument/end}%
```

Use of the hook might mean that we are already in horizontal mode, so ignore the space after `\begin{document}`.

```
\ignorespaces}
```

The `begindocument` hook already existed in the kernel since 1994 under the name `\atbegindocumenthook` the additional ones are originally from the etoolbox package under the names `\@endpreamblehook` `\afterpreamble`.

```
\NewHook{begindocument}
\NewHook{begindocument/before}
\NewHook{begindocument/end}
```

Above we used two kernel only hooks to be run after the public `begindocument/before` and after `begindocument` hooks.

\@kernel@after@begindocument@before
\@kernel@before@begindocument
\@kernel@after@begindocument

In `\@kernel@after@begindocument@before` we already place one action: drop the fast execution code for the `env/document/begin` hook. That hook marks the end of the preamble and should therefore only be run once. In a normal document that is anyway the case (so the code would just sit there taking up space afterwards, which these days is rather harmless), however, in more complicated scenarios where several full documents are combined to a single document it might get applied several times with harmful effects. We therefore explicitly drop it at this point. the coding is somewhat obscure due to the name of the macro which requires constructing.

```
\edef \@kernel@after@begindocument@before {%
  \let\expandafter\noexpand\csname
```

```
      __hook env/document/begin\endcsname
 \noexpand\@empty}
```

These internal hooks are already declared earlier (in `ltexpl`) so that other modules could write to them.

```
%\let \@kernel@before@begindocument \@empty
%\let \@kernel@after@begindocument  \@empty
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2017/04/15}%
⟨latexrelease⟩  {\document}{Save language for hyphenation}%
⟨latexrelease⟩
⟨latexrelease⟩\def\document{\endgroup
⟨latexrelease⟩  \ifx\@unusedoptionlist\@empty\else
⟨latexrelease⟩    \@latex@warning@no@line{Unused global option(s):^^J%
⟨latexrelease⟩            \@spaces[\@unusedoptionlist]}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@colht\textheight
⟨latexrelease⟩  \@colroom\textheight \vsize\textheight
⟨latexrelease⟩  \columnwidth\textwidth
⟨latexrelease⟩  \@clubpenalty\clubpenalty
⟨latexrelease⟩  \if@twocolumn
⟨latexrelease⟩    \advance\columnwidth -\columnsep
⟨latexrelease⟩    \divide\columnwidth\tw@ \hsize\columnwidth \@firstcolumntrue
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \hsize\columnwidth \linewidth\hsize
⟨latexrelease⟩  \begingroup\@floatplacement\@dblfloatplacement
⟨latexrelease⟩    \makeatletter\let\@writefile\@gobbletwo
⟨latexrelease⟩    \global \let \@multiplelabels \relax
⟨latexrelease⟩    \@input{\jobname.aux}%
⟨latexrelease⟩  \endgroup
⟨latexrelease⟩  \if@filesw
⟨latexrelease⟩    \immediate\openout\@mainaux\jobname.aux
⟨latexrelease⟩    \immediate\write\@mainaux{\relax}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \process@table
⟨latexrelease⟩  \let\glb@currsize\@empty  % Force math initialization.
⟨latexrelease⟩  \normalsize
⟨latexrelease⟩  \everypar{}%
⟨latexrelease⟩  \ifx\normalsfcodes\@empty
⟨latexrelease⟩    \ifnum\sfcode`\.=\@m
⟨latexrelease⟩      \let\normalsfcodes\frenchspacing
⟨latexrelease⟩    \else
⟨latexrelease⟩      \let\normalsfcodes\nonfrenchspacing
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \ifx\document@default@language\m@ne
⟨latexrelease⟩    \chardef\document@default@language\language
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@noskipsecfalse
⟨latexrelease⟩  \let \@refundefined \relax
⟨latexrelease⟩  \let\AtBeginDocument\@firstofone
⟨latexrelease⟩  \@begindocumenthook
```

```
⟨latexrelease⟩  \ifdim\topskip<1sp\global\topskip 1sp\relax\fi
⟨latexrelease⟩  \global\@maxdepth\maxdepth
⟨latexrelease⟩  \global\let\@begindocumenthook\@undefined
⟨latexrelease⟩  \ifx\@listfiles\@undefined
⟨latexrelease⟩    \global\let\@filelist\relax
⟨latexrelease⟩    \global\let\@addtofilelist\@gobble
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \gdef\do##1{\global\let ##1\@notprerr}%
⟨latexrelease⟩  \@preamblecmds
⟨latexrelease⟩  \global\let \@nodocument \relax
⟨latexrelease⟩  \global\let\do\noexpand
⟨latexrelease⟩  \ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩  {\document}{Save language for hyphenation}
⟨latexrelease⟩\def\document{\endgroup
⟨latexrelease⟩  \ifx\@unusedoptionlist\@empty\else
⟨latexrelease⟩    \@latex@warning@no@line{Unused global option(s):^^J%
⟨latexrelease⟩            \@spaces[\@unusedoptionlist]}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@colht\textheight
⟨latexrelease⟩  \@colroom\textheight \vsize\textheight
⟨latexrelease⟩  \columnwidth\textwidth
⟨latexrelease⟩  \@clubpenalty\clubpenalty
⟨latexrelease⟩  \if@twocolumn
⟨latexrelease⟩    \advance\columnwidth -\columnsep
⟨latexrelease⟩    \divide\columnwidth\tw@ \hsize\columnwidth
⟨latexrelease⟩    \@firstcolumntrue
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \hsize\columnwidth \linewidth\hsize
⟨latexrelease⟩  \begingroup\@floatplacement\@dblfloatplacement
⟨latexrelease⟩    \makeatletter\let\@writefile\@gobbletwo
⟨latexrelease⟩    \global \let \@multiplelabels \relax
⟨latexrelease⟩    \@input{\jobname.aux}%
⟨latexrelease⟩  \endgroup
⟨latexrelease⟩  \if@filesw
⟨latexrelease⟩    \immediate\openout\@mainaux\jobname.aux
⟨latexrelease⟩    \immediate\write\@mainaux{\relax}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \process@table
⟨latexrelease⟩  \let\glb@currsize\@empty
⟨latexrelease⟩  \normalsize
⟨latexrelease⟩  \everypar{}%
⟨latexrelease⟩  \ifx\normalsfcodes\@empty
⟨latexrelease⟩    \ifnum\sfcode`\.=\@m
⟨latexrelease⟩      \let\normalsfcodes\frenchspacing
⟨latexrelease⟩    \else
⟨latexrelease⟩      \let\normalsfcodes\nonfrenchspacing
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@noskipsecfalse
⟨latexrelease⟩  \let \@refundefined \relax
⟨latexrelease⟩  \let\AtBeginDocument\@firstofone
```

```
⟨latexrelease⟩  \@begindocumenthook
⟨latexrelease⟩  \ifdim\topskip<1sp\global\topskip 1sp\relax\fi
⟨latexrelease⟩  \global\@maxdepth\maxdepth
⟨latexrelease⟩  \global\let\@begindocumenthook\@undefined
⟨latexrelease⟩  \ifx\@listfiles\@undefined
⟨latexrelease⟩    \global\let\@filelist\relax
⟨latexrelease⟩    \global\let\@addtofilelist\@gobble
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \gdef\do##1{\global\let ##1\@notprerr}%
⟨latexrelease⟩  \@preamblecmds
⟨latexrelease⟩  \global\let \@nodocument \relax
⟨latexrelease⟩  \global\let\do\noexpand
⟨latexrelease⟩  \ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
\@onlypreamble\document
```

(*End definition for* `\document` *and others.*)

`\normalsfcodes` The setting of `\@empty` is just a flag. This command may be defined in a class or package file. If it is still `\@empty` at `\begin{document}` it will be defined to be `\frenchspacing` or `\nonfrenchspacing`, depending on which of those appears to be in effect at that point.

```
\let\normalsfcodes\@empty
```

(*End definition for* `\normalsfcodes`.)

`\nofiles` Set `\@fileswfalse` which suppresses the places where LaTeX makes `\immediate` writes. The `\makeindex` and `\makeglossary` are disabled. `\protected@write` is redefined not to write to the file specified, but rather to write a blank line to the log file. This ensures that a ⟨*whatsit*⟩ node is still created, and so spacing is not affected by the `\nofiles` command; to ensure this more generally, the `\if@nobreak` test is needed.

```
\def\nofiles{%
  \@fileswfalse
  \typeout{No auxiliary output files.^^J}%
  \long\def\protected@write##1##2##3%
    {\write\m@ne{}\if@nobreak\ifvmode\nobreak\fi\fi}%
  \let\makeindex\relax
  \let\makeglossary\relax}
\@onlypreamble\nofiles
```

(*End definition for* `\nofiles`.)

`\protected@write` This takes three arguments: an output stream, some initialization code, and some text to write. It then writes this, with appropriate handling of `\protect` and `\thepage`.

```
\long\def \protected@write#1#2#3{%
      \begingroup
       \let\thepage\relax
       #2%
       \let\protect\@unexpandable@protect
       \edef\reserved@a{\write#1{#3}}%
       \reserved@a
      \endgroup
      \if@nobreak\ifvmode\nobreak\fi\fi
}
```

(*End definition for* `\protected@write`.)

```
\let\@auxout=\@mainaux
```

`\include` `\includeonly`

In the definition of `\include`, `\def\reserved@b` changed to `\edef\reserved@b` to be consistent with the `\edef` in `\includeonly`. (Suggested by Rainer Schöpf & Frank Mittelbach. Change made 20 Jul 88.)

Changed definition of `\include` to allow space at end of file name — otherwise, typing `\include{foo }` would cause LaTeX to overwrite `foo.tex`. Change made 24 May 89, suggested by Rainer Schöpf and Frank Mittelbach

Made `\include` check for being used inside an `\include`'d file, as this will not work and cause surprising results.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\includeonly}{Spaces in file names}%
```

```
\def\include#1{\relax
  \ifnum\@auxout=\@partaux
    \@latex@error{\string\include\space cannot be nested}\@eha
  \else
```

Here the normalization will add `.tex` for all files, (it uses the same normalization as the hooks), so we need to remove that manually. `\@strip@tex@ext` does that.

```
    \set@curr@file{#1}%
    \edef\@curr@file{\@strip@tex@ext\@curr@file}%
```

For historical reasons `\@include` expects an argument delimited by a space. This is kept (though unnecessary now) to avoid errors in other packages that use `\@include` directly.

```
    \expandafter\@include\expandafter{\@curr@file} % deliberate space
  \fi}
```

Here in `\includeonly` we also need to strip `.tex` after normalization:

```
\def\includeonly#1{%
  \@partswtrue
```

Because the argument to `\includeonly` is a comma-separated list of filenames where there may be comma's preceding some of the filenames or trailing them. Therefore we need to take the list apart, remove the unwanted spaces while leaving the spaces *in* the filenames intact.

```
  \let\@partlist\@empty
  \@for\reserved@a:=#1 \do
    {%
      \expandafter\set@curr@file\expandafter{\reserved@a}%
      \ifx\@partlist\@empty
        \edef\@partlist{\@strip@tex@ext\@curr@file}%
      \else
        \edef\@partlist{\@partlist,\@strip@tex@ext\@curr@file}%
      \fi
    }%
  }
\@onlypreamble\includeonly
```

(*End definition for* `\include` *and* `\includeonly`.)

`\@strip@tex@ext`
`\@strip@tex@ext@aux`

These macros take a (`\detokenize`d file name and remove any `.tex` extension). Extra care is taken to not remove the string `.tex` from the middle of a file name: it is only removed if it's the very last thing in the file name.

```
\def\reserved@a#1{%
\def\@strip@tex@ext##1{%
  \expandafter\@strip@tex@ext@aux
    ##1\@nil\@nil
     #1\@nil\relax\@nnil}
\def\@strip@tex@ext@aux##1#1\@nil##2\@nnil{%
  \ifx\relax##2\@empty
    \expandafter\@cdr\expandafter\@empty\@cdr{}##1%
  \else##1\fi}}%
\expandafter\reserved@a
\expandafter{\detokenize{.tex}}
⟨/2ekernel | latexrelease⟩
```

(*End definition for* `\@strip@tex@ext` *and* `\@strip@tex@ext@aux`.)

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                 {\includeonly}{Spaces in file names}%
⟨latexrelease⟩
⟨latexrelease⟩\def\includeonly#1{%
⟨latexrelease⟩  \@partswtrue
⟨latexrelease⟩  \set@curr@file{\zap@space#1 \@empty}%
⟨latexrelease⟩  \let\@partlist\@curr@file
⟨latexrelease⟩  }
⟨latexrelease⟩
⟨latexrelease⟩\def\include#1{\relax
⟨latexrelease⟩  \ifnum\@auxout=\@partaux
⟨latexrelease⟩    \@latex@error{\string\include\space cannot be nested}\@eha
⟨latexrelease⟩  \else
⟨latexrelease⟩    \set@curr@file{#1 }%
⟨latexrelease⟩    \expandafter\@include\@curr@file
⟨latexrelease⟩  \fi}
⟨latexrelease⟩
⟨latexrelease⟩\let\@strip@tex@ext\@undefined
⟨latexrelease⟩\let\@strip@tex@ext@aux\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\includeonly}{Spaces in file names}%
⟨latexrelease⟩\def\includeonly#1{%
⟨latexrelease⟩  \@partswtrue
⟨latexrelease⟩  \edef\@partlist{\zap@space#1 \@empty}}
⟨latexrelease⟩
⟨latexrelease⟩\def\include#1{\relax
⟨latexrelease⟩  \ifnum\@auxout=\@partaux
⟨latexrelease⟩    \@latex@error{\string\include\space cannot be nested}\@eha
⟨latexrelease⟩  \else \@include#1 \fi}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\@include

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                    {\@include}{Spaces in file names and hooks}%
```

```
\def\@include#1 {%
\ifx\@nodocument\relax
  \clearpage
  \if@filesw
    \immediate\write\@mainaux{\string\@input{#1.aux}}%
  \fi
  \@tempswatrue
  \if@partsw
    \@tempswafalse
    \edef\reserved@b{#1}%
    \@for\reserved@a:=\@partlist\do
      {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
  \fi
  \if@tempswa
    \let\@auxout\@partaux
    \if@filesw
      \immediate\openout\@partaux "#1.aux"
      \immediate\write\@partaux{\relax}%
    \fi
```

Now before going to the hooks we need to set `\CurrentFile`:

```
%-----------------------------------------
    \@filehook@set@CurrentFile
```

Execute the `before` hooks just after we switched the `.aux` file ...

```
    \UseHook{include/before}%
    \UseOneTimeHook{include/#1/before}%
%-----------------------------------------
    \@input@{#1.tex}%
%-----------------------------------------
```

... then `end` hooks ...

```
    \UseOneTimeHook{include/#1/end}%
    \UseHook{include/end}%
%-----------------------------------------
    \clearpage
%-----------------------------------------
```

... and after the `\clearpage` the `after` hooks followed by another `\clearpage` just in case new material got added (after all we need to be in well defined state after the `\include`).

```
    \UseOneTimeHook{include/#1/after}%
    \UseHook{include/after}%
    \clearpage
%-----------------------------------------
    \@writeckpt{#1}%
    \if@filesw
      \immediate\closeout\@partaux
```

```
    \fi
  \else
```

If the file is not included, reset `\deadcycles`, so that a long list of non-included files does not generate an 'Output loop' error.

```
    \deadcycles\z@
    \@nameuse{cp@#1}%
```

We also execute a hook in this case, first a general used for every include file that is exclude and then a specific one that contains the name of the include file.

```
%----------------------------------------
    \UseHook{include/excluded}%
    \UseOneTimeHook{include/#1/excluded}%
%----------------------------------------
  \fi
  \let\@auxout\@mainaux
```

```
\else
\@latex@warning{%
  \noexpand\include should only be used after \string\begin{document}}%
\@input@{#1}%
\fi}
```

Now declare the non-generic `include` hooks used above:

```
\NewHook{include/before}
\NewReversedHook{include/end}
\NewReversedHook{include/after}
\NewHook{include/excluded}
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\@include}{Spaces in file names and hooks}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\def\@include#1 {%
⟨latexrelease⟩\ifx\@nodocument\relax
⟨latexrelease⟩  \clearpage
⟨latexrelease⟩  \if@filesw
⟨latexrelease⟩    \immediate\write\@mainaux{\string\@input{#1.aux}}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@tempswatrue
⟨latexrelease⟩  \if@partsw
⟨latexrelease⟩    \@tempswafalse
⟨latexrelease⟩    \edef\reserved@b{#1}%
⟨latexrelease⟩    \@for\reserved@a:=\@partlist\do
⟨latexrelease⟩      {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \if@tempswa
⟨latexrelease⟩    \let\@auxout\@partaux
⟨latexrelease⟩    \if@filesw
⟨latexrelease⟩      \immediate\openout\@partaux "#1.aux"
⟨latexrelease⟩      \immediate\write\@partaux{\relax}%
⟨latexrelease⟩    \fi
⟨latexrelease⟩    \@filehook@set@CurrentFile
⟨latexrelease⟩    \UseHook{include/before}%
⟨latexrelease⟩    \UseOneTimeHook{include/#1/before}%
```

```
⟨latexrelease⟩    \@input@{#1.tex}%
⟨latexrelease⟩    \UseOneTimeHook{include/#1/end}%
⟨latexrelease⟩    \UseHook{include/end}%
⟨latexrelease⟩    \clearpage
⟨latexrelease⟩    \UseOneTimeHook{include/#1/after}%
⟨latexrelease⟩    \UseHook{include/after}%
⟨latexrelease⟩    \clearpage
⟨latexrelease⟩    \@writeckpt{#1}%
⟨latexrelease⟩    \if@filesw
⟨latexrelease⟩      \immediate\closeout\@partaux
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \deadcycles\z@
⟨latexrelease⟩    \@nameuse{cp@#1}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \let\@auxout\@mainaux
⟨latexrelease⟩\else
⟨latexrelease⟩\@latex@warning{%
⟨latexrelease⟩  \noexpand\include should only be used after \string\begin{document}}%
⟨latexrelease⟩\@input@{#1}%
⟨latexrelease⟩\fi}
⟨latexrelease⟩\NewHook{include/before}
⟨latexrelease⟩\NewReversedHook{include/end}
⟨latexrelease⟩\NewReversedHook{include/after}

⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@include}{Spaces in file names and hooks}%
⟨latexrelease⟩\def\@include#1 {%
⟨latexrelease⟩  \clearpage
⟨latexrelease⟩  \if@filesw
⟨latexrelease⟩    \immediate\write\@mainaux{\string\@input{#1.aux}}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@tempswatrue
⟨latexrelease⟩  \if@partsw
⟨latexrelease⟩    \@tempswafalse
⟨latexrelease⟩    \edef\reserved@b{#1}%
⟨latexrelease⟩    \@for\reserved@a:=\@partlist\do
⟨latexrelease⟩      {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \if@tempswa
⟨latexrelease⟩    \let\@auxout\@partaux
⟨latexrelease⟩    \if@filesw
⟨latexrelease⟩      \immediate\openout\@partaux #1.aux
⟨latexrelease⟩      \immediate\write\@partaux{\relax}%
⟨latexrelease⟩    \fi
⟨latexrelease⟩    \@input@{#1.tex}%
⟨latexrelease⟩    \clearpage
⟨latexrelease⟩    \@writeckpt{#1}%
⟨latexrelease⟩    \if@filesw
⟨latexrelease⟩      \immediate\closeout\@partaux
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \deadcycles\z@
⟨latexrelease⟩    \@nameuse{cp@#1}%
⟨latexrelease⟩  \fi
```

```
⟨latexrelease⟩   \let\@auxout\@mainaux}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@include`.)

`\@writeckpt`

```
\def\@writeckpt#1{%
  \if@filesw
    \immediate\write\@partaux{\string\@setckpt{#1}\@charlb}%
    {\let\@elt\@wckptelt \cl@@ckpt}%
    \immediate\write\@partaux{\@charrb}%
  \fi}
```

(*End definition for* `\@writeckpt`.)

`\@wckptelt`

```
\def\@wckptelt#1{%
  \immediate\write\@partaux{%
    \string\setcounter{#1}{\the\@nameuse{c@#1}}}}
```

(*End definition for* `\@wckptelt`.)

`\@setckpt` RmS 93/08/31: introduced `\@setckpt`

```
\def\@setckpt#1{\global\@namedef{cp@#1}}
```

(*End definition for* `\@setckpt`.)

`\@charlb` `\@charrb` The following defines `\@charlb` and `\@charrb` to be `{` and `}`, respectively with `\catcode` 11.

```
{\catcode`[=1 \catcode`]=2
\catcode`{=11 \catcode`}=11
\gdef\@charlb[{]
\gdef\@charrb[}]
]% }brace matching
```

(*End definition for* `\@charlb` *and* `\@charrb`.)

1.1 Safe Input Macros

`\@curr@file` `\set@curr@file` File name handling is done by generating a csname from the provided file name (which means that UTF-8 octets gets turned into strings as this is what happens if they appear in a csname due to the code in `utf8.def`). By setting `\escapchar` to `-1` we ensure that we don't get a backslash in front. As a result we end up with all characters as catcode 12 (plus spaces). We then sometimes add quotes around the construct (removing any existing inner quotes. Sometimes we only remove the quotes if they have been supplied by the user. There is clearly some room for improvement.

A side effect of the new code is that we will see quotes around file name displays where there haven't been any before.

For compatibility with existing code using `{abc}.tex` or `{one.two}.png`, an initial brace group is discarded before expansion and `\string` is applied. The content of the brace group is discarded. This means that a leading space will be lost unless protected (by `{ }` or `" "` or `\space`) but filenames with a space are hopefully rare.

The definition below is from 2019 and only used during kernel bootstrapping, later on in `ltfilehook.dtx` it will get overwritten.

```
\def\set@curr@file#1{%
  \begingroup
    \escapechar\m@ne
    \xdef\@curr@file{%
      \expandafter\expandafter\expandafter\unquote@name
      \expandafter\expandafter\expandafter{%
      \expandafter\string
        \csname\@firstofone#1\@empty\endcsname}}%
  \endgroup
}
```

(*End definition for* `\@curr@file` *and* `\set@curr@file`.)

`\quote@name`
`\quote@@name`
`\unquote@name`

Quoting spaces

```
a b c     -> "a b c"
"a b c"   -> "a b c"
a" "b" "c -> "a b c"
          -> ""
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\quote@name}{Quote file names}%
\def\quote@name#1{"\quote@@name#1\@gobble""}
\def\quote@@name#1"{#1\quote@@name}
```

and removing quotes ...

```
\def\unquote@name#1{\quote@@name#1\@gobble"}
```

(*End definition for* `\quote@name`, `\quote@@name`, *and* `\unquote@name`.)

`\IfFileExists`

```
\DeclareRobustCommand\IfFileExists[1]{%
  \set@curr@file{#1}%
  \expandafter\IfFileExists@\expandafter{\@curr@file}}
```

(*End definition for* `\IfFileExists`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\quote@name}{Quote file names}%
⟨latexrelease⟩
⟨latexrelease⟩\let\quote@name\@undefined
⟨latexrelease⟩\let\quote@@name\@undefined
⟨latexrelease⟩\let\unquote@name\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\long\def \IfFileExists#1#2#3{%
⟨latexrelease⟩  \openin\@inputcheck#1 %
⟨latexrelease⟩  \ifeof\@inputcheck
⟨latexrelease⟩    \ifx\input@path\@undefined
⟨latexrelease⟩      \def\reserved@a{#3}%
⟨latexrelease⟩    \else
```

```
⟨latexrelease⟩      \def\reserved@a{\@iffileonpath{#1}{#2}{#3}}%
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \closein\@inputcheck
⟨latexrelease⟩    \edef\@filef@und{#1 }%
⟨latexrelease⟩    \def\reserved@a{#2}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \reserved@a}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\IfFileExists@` Argument `#1` is `\@curr@file` so catcode 12 string with no quotes.

The original definition picked up arguments `#2` and `#3` in a way that they couldn't contain unbalanced conditionals. A better implementation would have been not to pick up the arguments at all but instead use the usual `\@firstoftwo` and `\secondoftwo`. However, that changes how `#` is interpreted and so we can't do that nowaways without invalidating a lot of code. Therefore the somewhat curious construction near the end.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                 {\IfFileExists@}{manage unbalanced conditionals}
\long\def \IfFileExists@#1#2#3{%
  \openin\@inputcheck"#1" %
  \ifeof\@inputcheck
    \ifx\input@path\@undefined
      \let\reserved@a\@secondoftwo
    \else
      \def\reserved@a{\@iffileonpath{#1}}%
    \fi
  \else
    \closein\@inputcheck
    \edef\@filef@und{"#1" }%
    \let\reserved@a\@firstoftwo
  \fi
```

This is just there so that any `#` inside `#2` or `#3` needs doubling (as that was the case in the past).

```
  \expandafter\def\expandafter\reserved@a
    \expandafter{\reserved@a{#2}{#3}}%
\reserved@a}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                 {\IfFileExists@}{manage unbalanced conditionals}
⟨latexrelease⟩
⟨latexrelease⟩\long\def \IfFileExists@#1#2#3{%
⟨latexrelease⟩  \openin\@inputcheck"#1" %
⟨latexrelease⟩  \ifeof\@inputcheck
⟨latexrelease⟩    \ifx\input@path\@undefined
⟨latexrelease⟩      \def\reserved@a{#3}%
⟨latexrelease⟩    \else
⟨latexrelease⟩      \def\reserved@a{\@iffileonpath{#1}{#2}{#3}}%
⟨latexrelease⟩    \fi
```

```
⟨latexrelease⟩  \else
⟨latexrelease⟩    \closein\@inputcheck
⟨latexrelease⟩    \edef\@filef@und{"#1" }%
⟨latexrelease⟩    \def\reserved@a{#2}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \reserved@a}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\IfFileExists@}{manage unbalanced conditionals}
⟨latexrelease⟩
⟨latexrelease⟩\let\IfFileExists@\@undefined
⟨latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\IfFileExists@`.)

`\@iffileonpath` If the file is not found by `\openin`, and `\input@path` is defined, look in all the directories specified in `\input@path`.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                 {\@iffileonpath}{Quote file names}
\long\def\@iffileonpath#1{%
  \let\reserved@a\@secondoftwo
  \expandafter\@tfor\expandafter\reserved@b\expandafter
             :\expandafter=\input@path\do{%
    \openin\@inputcheck\expandafter\quote@name\expandafter{\reserved@b#1} %
    \ifeof\@inputcheck\else
      \edef\@filef@und{\expandafter\quote@name\expandafter{\reserved@b#1} }%
      \let\reserved@a\@firstoftwo%
      \closein\@inputcheck
      \@break@tfor
    \fi}%
  \reserved@a}
```

(*End definition for* `\@iffileonpath`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\quote@name}{Quote file names}
⟨latexrelease⟩
⟨latexrelease⟩\long\def\@iffileonpath#1{%
⟨latexrelease⟩  \let\reserved@a\@secondoftwo
⟨latexrelease⟩  \expandafter\@tfor\expandafter\reserved@b\expandafter
⟨latexrelease⟩             :\expandafter=\input@path\do{%
⟨latexrelease⟩    \openin\@inputcheck\reserved@b#1 %
⟨latexrelease⟩    \ifeof\@inputcheck\else
⟨latexrelease⟩      \edef\@filef@und{\reserved@b#1 }%
⟨latexrelease⟩      \let\reserved@a\@firstoftwo%
⟨latexrelease⟩      \closein\@inputcheck
⟨latexrelease⟩      \@break@tfor
⟨latexrelease⟩    \fi}%
```

```
⟨latexrelease⟩   \reserved@a}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\InputIfFileExists Now define \InputIfFileExists to input #1 if it seems to exist. Immediately prior to the input, #2 is executed. If the file #1 does not exist, execute '#3'.

This here is a temporary definition for the kernel. The real one comes somewhat later in the file ltfilehook.dtx.

```
\DeclareRobustCommand \InputIfFileExists[2]{%
  \IfFileExists{#1}%
    {%
  \expandafter\@swaptwoargs\expandafter
      {\@filef@und}{#2\@addtofilelist{#1}\@@input}}}
```

(*End definition for* \InputIfFileExists.)

\@swaptwoargs Swap two arguments and return them unbraced (like \@firstoftwo etc).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩   {\@swaptwoargs}{Don't lose the file name}%
\long\def\@swaptwoargs#1#2{#2#1}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩   {\@swaptwoargs}{Don't lose the file name}%
⟨latexrelease⟩\let\@swaptwoargs\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \@swaptwoargs.)

\input Input a file: if the argument is given in braces use safe input macros, otherwise use TEX's primitive \input command (which is called \@@input in LATEX).

```
\def\input{\@ifnextchar\bgroup\@iinput\@@input}
```

(*End definition for* \input.)

\@iinput Define \@iinput (i.e., \input) in terms of \InputIfIfileExists.

Changes to \@iinput: adapt to the changes to \@missingfileerror.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@iinput}{Change in file error handling}%
\def\@iinput#1{%
  \InputIfFileExists{#1}{}%
  {\filename@parse\@curr@file
   \edef\reserved@a{\noexpand\@missingfileerror
     {\filename@area\filename@base}%
     {\ifx\filename@ext\relax tex\else\filename@ext\fi}}%
```

This line now just sets \@missingfile@⟨*part*⟩:

```
    \reserved@a
```

Now here we have to use it. The file here is guaranteed to exist, because `\@missingfileerror` ensures so, but we have to use `\InputIfFileExists` because it executes the file hooks.

```
  \edef\reserved@a{\noexpand\@iinput{%
    \@missingfile@area\@missingfile@base.\@missingfile@ext}}%
  \reserved@a}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                 {\@iinput}{Quote file names}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@iinput#1{%
⟨latexrelease⟩  \InputIfFileExists{#1}{}%
⟨latexrelease⟩  {\filename@parse\@curr@file
⟨latexrelease⟩   \edef\reserved@a{\noexpand\@missingfileerror
⟨latexrelease⟩     {\filename@area\filename@base}%
⟨latexrelease⟩     {\ifx\filename@ext\relax tex\else\filename@ext\fi}}%
⟨latexrelease⟩   \reserved@a}}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@iinput}{Quote file names}%
⟨latexrelease⟩\def\@iinput#1{%
⟨latexrelease⟩  \InputIfFileExists{#1}{}%
⟨latexrelease⟩  {\filename@parse{#1}%
⟨latexrelease⟩   \edef\reserved@a{\noexpand\@missingfileerror
⟨latexrelease⟩     {\filename@area\filename@base}%
⟨latexrelease⟩     {\ifx\filename@ext\relax tex\else\filename@ext\fi}}%
⟨latexrelease⟩   \reserved@a}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@iinput`.)

`\@input` Define `\@input` in terms of `\IfIfileExists`. So this is a 'safe input' command, but the files input are not listed by `\listfiles`.

We don't want `.aux`, `.toc` files etc be listed by `\listfiles`. However, something like `.bbl` probably should be listed and thus should be implemented not by `\@input`.

```
\def\@input#1{%
  \IfFileExists{#1}{\@@input\@filef@und}{\typeout{No file #1.}}}
```

(*End definition for* `\@input`.)

`\@input@` Version of `\@input` that does add the file to `\@filelist`.

```
\def\@input@#1{\InputIfFileExists{#1}{}{\typeout{No file #1.}}}
```

(*End definition for* `\@input@`.)

`\@missingfileerror` This 'error' command avoids TEX's primitive missing file loop.

Missing file error. Prompt for a new filename, offering a default extension.

Changes to `\@missingfileerror`: rather than trying to input the file by force, now `\@missingfileerror` just returns three `\@missingfile@`⟨*part*⟩ and the caller macro is responsible for doing the right thing with it.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩        {\@missingfileerror}{Do not load missing file immediately}%
\gdef\@missingfileerror#1#2{%
     \typeout{^^J! LaTeX Error: File ‘#1.#2’ not found.^^J^^J%
      Type X to quit or <RETURN> to proceed,^^J%
      or enter new name. (Default extension: #2)^^J}%
     \message{Enter file name: }%
      {\endlinechar\m@ne
       \global\read\m@ne to\@gtempa}%
    \ifx\@gtempa\@empty
```

If the user answers with ⟨*return*⟩, fallback to the `.tex` file (previously it did nothing).

```
      \let\@missingfile@area\@empty
      \let\@missingfile@base\@empty
      \def\@missingfile@ext{tex}%
    \else
```

Use `\batchmode\read-1 to` ⟨*tl*⟩ to end the TEX run, same as expl3 does (it was `\batchmode\@@end` before).

```
      \def\reserved@b{\batchmode\read-1 to \reserved@a}%
      \def\reserved@a{x}\ifx\reserved@a\@gtempa\reserved@b\fi
      \def\reserved@a{X}\ifx\reserved@a\@gtempa\reserved@b\fi
      \filename@parse\@gtempa
      \edef\filename@ext{%
        \ifx\filename@ext\relax#2\else\filename@ext\fi}%
     \edef\reserved@a{%
```

Only check `\IfFileExists` (it was `\InputIfFileExists`).

```
       \noexpand\IfFileExists
         {\filename@area\filename@base.\filename@ext}%
```

If the file exists, define `\@missingfile@`⟨*part*⟩.

```
         {\def\noexpand\@missingfile@area{\filename@area}%
          \def\noexpand\@missingfile@base{\filename@base}%
          \def\noexpand\@missingfile@ext {\filename@ext}}%
         {\noexpand\@missingfileerror
            {\filename@area\filename@base}{\filename@ext}}}%
      \reserved@a
    \fi
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩        {\@missingfileerror}{Do not load missing file immediately}%
⟨latexrelease⟩
⟨latexrelease⟩\gdef\@missingfileerror#1#2{%
⟨latexrelease⟩     \typeout{^^J! LaTeX Error: File ‘#1.#2’ not found.^^J^^J%
⟨latexrelease⟩      Type X to quit or <RETURN> to proceed,^^J%
⟨latexrelease⟩      or enter new name. (Default extension: #2)^^J}%
⟨latexrelease⟩     \message{Enter file name: }%
⟨latexrelease⟩      {\endlinechar\m@ne
⟨latexrelease⟩       \global\read\m@ne to\@gtempa}%
⟨latexrelease⟩    \ifx\@gtempa\@empty
⟨latexrelease⟩    \else
⟨latexrelease⟩      \def\reserved@a{x}\ifx\reserved@a\@gtempa\batchmode\@@end\fi
```

```
⟨latexrelease⟩      \def\reserved@a{X}\ifx\reserved@a\@gtempa\batchmode\@@end\fi
⟨latexrelease⟩      \filename@parse\@gtempa
⟨latexrelease⟩      \edef\filename@ext{%
⟨latexrelease⟩        \ifx\filename@ext\relax#2\else\filename@ext\fi}%
⟨latexrelease⟩     \edef\reserved@a{%
⟨latexrelease⟩       \noexpand\InputIfFileExists
⟨latexrelease⟩         {\filename@area\filename@base.\filename@ext}%
⟨latexrelease⟩         {}%
⟨latexrelease⟩         {\noexpand\@missingfileerror
⟨latexrelease⟩            {\filename@area\filename@base}{\filename@ext}}}%
⟨latexrelease⟩      \reserved@a
⟨latexrelease⟩    \fi}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@missingfileerror`.)

`\@obsoletefile` For compatibility with LaTeX 2.09 document styles, we distribute files called `article.sty`, `book.sty`, `report.sty`, `slides.sty` and `letter.sty`. These use the command `\@obsoletefile`, which produces a warning message.

```
\def\@obsoletefile#1#2{%
   \@latex@warning@no@line{inputting ‘#1’ instead of obsolete ‘#2’}}
\@onlypreamble\@obsoletefile
```

1.2 Listing files

`\@filelist` A list of files input so far. The initial value of `\@gobble` eats the comma before the first file name.

```
\let\@filelist\@gobble
```

`\@addtofilelist` Add to the list of files input so far. This ‘real’ definition is only used for ‘cfg’ files during initex. An initial definition of `\@gobble` has already been set.

```
%\def\@addtofilelist#1{\xdef\@filelist{\@filelist,#1}}
```

`\listfiles` A preamble command to cause `\end{document}` to list files input from the main file.

```
\def\listfiles{%
  \let\listfiles\relax
  \def\@listfiles##1##2##3##4##5##6##7##8##9\@@{%
     \def\reserved@d{\\}%
     \@tfor\reserved@c:=##1##2##3##4##5##6##7##8\do{%
       \ifx\reserved@c\reserved@d
         \edef\filename@area{ \filename@area}%
       \fi}}%

  \def\@dofilelist{%
     \typeout{^^J *File List*}%
     \@for\@currname:=\@filelist\do{%
       \filename@parse\@currname
       \edef\reserved@a{%
          \filename@base.%
          \ifx\filename@ext\relax tex\else\filename@ext\fi}%
       \expandafter\let\expandafter\reserved@b
                                 \csname ver@\reserved@a\endcsname
```

Packages that \relax their \ver@... string to allow for multiple loading (e.g., fontenc) can use \ver@@... to store the version information instead.

```
      \ifx\reserved@b\relax
        \expandafter\let\expandafter\reserved@b
                        \csname ver@@\reserved@a\endcsname
      \fi
      \expandafter\expandafter\expandafter\@listfiles\expandafter
            \filename@area\filename@base\\\\\\\\\\\\\\\\\\\\@@
      \typeout{%
        \filename@area\reserved@a
        \ifx\reserved@b\relax\else\@spaces\reserved@b\fi}}%
    \typeout{ ***********^^J}}}
```

The \@filelist will be de-activated if \listfiles does not appear in the preamble. \begin{document} contains code equivalent to the following:

```
\AtBeginDocument{%
  \ifx\@listfiles\@undefined
    \let\@filelist\relax
    \let\@addtofilelist\@gobble
  \fi}
```

```
\@onlypreamble\listfiles
```

\@dofilelist

```
\let\@dofilelist\relax
```

⟨/2ekernel⟩

(*End definition for* \@obsoletefile *and others.*)

File s
ltoutenc.dtx

1 Font encodings

This section of the kernel contains commands for declaring encoding-specific commands, such as accents. It also contains the code for some of the encoding files, including `omlenc.def`, `omsenc.def`, `t1enc.def` and `ot1enc.def` files, which define the `OML`, `OMS`, `T1` and `OT1` encodings, and the `fontenc` package for selecting encodings.

The `fontenc` package has options for encodings, of which the last option is the default encoding. For example, to use the `OT2`, `OT3` and `T1` encodings, with `T1` as the default, you say:

```
\usepackage[OT2,OT3,T1]{fontenc}
```

The standard kernel set-up loads font encoding files and selects an encoding as follows.

```
\input {omlenc.def}
\input  {t1enc.def}
\input {ot1enc.def}
\input {omsenc.def}
\fontencoding{OT1}
```

Note that the files in the standard `inputenc` package depend on this behaviour of the kernel.

The syntax for declaring encoding-specific commands is:

`\DeclareTextCommand{`⟨*command*⟩`}{`⟨*encoding*⟩`}`
`[`⟨*number*⟩`][`⟨*default*⟩`]{`⟨*commands*⟩`}`

This command is like `\newcommand`, except that it defines a command which is specific to one encoding. The resulting command is always robust, even if its definition is fragile. For example, the definition of `\l` in the `OT1` encoding is:

```
\DeclareTextCommand{\l}{OT1}{{\@xxxii l}}
```

`\DeclareTextCommand` takes the same optional arguments as `\newcommand`.

`\ProvideTextCommand{`⟨*command*⟩`}{`⟨*encoding*⟩`}`
`[`⟨*number*⟩`][`⟨*default*⟩`]{`⟨*commands*⟩`}`

This acts like `\DeclareTextCommand`, but does nothing if the command is already defined.

`\DeclareTextSymbol{`⟨*command*⟩`}{`⟨*encoding*⟩`}{`⟨*slot*⟩`}`

This command defines a text symbol, with a particular slot in that encoding. The commands:

```
\DeclareTextSymbol{\ss}{OT1}{25}
\DeclareTextCommand{\ss}{OT1}{\char25 }
```

have the same effect, but the `\DeclareTextSymbol` is faster.

`\DeclareTextAccent{`⟨*command*⟩`}{`⟨*encoding*⟩`}{`⟨*slot*⟩`}`

This command declares a text accent. The commands:

```
\DeclareTextAccent{\"}{OT1}{127}
\DeclareTextCommand{\"}{OT1}{\add@accent {127}}
```

have the same effect.

\DeclareTextComposite{⟨*command*⟩}
{⟨*encoding*⟩}{⟨*argument*⟩}{⟨*slot*⟩}

This command declares a composite letter, for example in the T1 encoding \'{a} is slot 225, which is declared by:

```
\DeclareTextComposite{\'}{T1}{a}{225}
```

The *command* will normally have been declared with \DeclareTextAccent, or as a one-argument \DeclareTextCommand.

\DeclareTextComposite is the most common example of using the more general declaration \DeclareTextCompositeCommand, which can define a composite to be an arbitrary piece of text.

\DeclareTextCompositeCommand{⟨*command*⟩}
{⟨*encoding*⟩}{⟨*argument*⟩}{⟨*text*⟩}

For example, in the OT1 encoding Å has a hand-crafted definition this is declared as follows

```
\DeclareTextCompositeCommand{\r}{OT1}{A}
 {\leavevmode\setbox\z@\hbox{!}\dimen@\ht\z@\advance\dimen@-1ex%
  \rlap{\raise.67\dimen@\hbox{\char23}}A}
```

The *command* will normally have been declared with \DeclareTextAccent, or as a one-argument \DeclareTextCommand.

The commands defined using the above declarations can be used in two ways. Normally they are used by just calling the command in the appropriate encoding, for example \ss. However, sometimes you may wish to use a command in an encoding where it is not defined. If the command has no arguments, then you can use it in another encoding by calling \UseTextSymbol:

\UseTextSymbol{⟨*encoding*⟩}{⟨*command*⟩}

For example, \UseTextSymbol{OT1}{\ss} has the same effect as:

```
{\fontencoding{OT1}\selectfont\ss}
```

If the command has one argument then you can use it in another encoding by calling \UseTextAccent:

\UseTextAccent{⟨*encoding*⟩}{⟨*command*⟩}{⟨*text*⟩}

For example, if the current encoding is OT2 then \UseTextAccent{OT1}{\'}{a} has the same effect as:

```
{\fontencoding{OT1}\selectfont\'{\fontencoding{OT2}\selectfont a}}
```

You can also declare a default definition for a text command, which will be used if the current encoding has no appropriate definition. Such use will also set the definition for this command in the current encoding to equal this default definition; this makes subsequent uses of the command much faster.

`\DeclareTextCommandDefault{`⟨*command*⟩`}{`⟨*definition*⟩`}`

For example, the default definition of the command `\textonequarter` (which produces the fraction $\frac{1}{4}$) could be built using math mode:

```
\DeclareTextCommandDefault{\textonequarter}{\ensuremath {\frac14}}
```

There is a matching `\Provide` command which will not override an existing default definition:

`\ProvideTextCommandDefault{`⟨*command*⟩`}{`⟨*definition*⟩`}`

The most common use for these commands is to use symbols from other encodings, so there are some optimizations provided:

`\DeclareTextSymbolDefault{`⟨*command*⟩`}`⟨*encoding*⟩`}`
`\DeclareTextAccentDefault{`⟨*command*⟩`}`⟨*encoding*⟩`}`

are short for:

`\DeclareTextCommandDefault{`⟨*command*⟩`}`
`{\UseTextSymbol{`⟨*encoding*⟩`}{`⟨*command*⟩`}}`
`\DeclareTextCommandDefault[1]{`⟨*command*⟩`}`
`{\UseTextAccent{`⟨*encoding*⟩`}{`⟨*command*⟩`}{#1}}`

For example, to make `OT1` the default encoding for `\ss` and `\'` you say:

```
\DeclareTextSymbolDefault{\ss}{OT1}
\DeclareTextAccentDefault{\'}{OT1}
```

Note that you can use these commands on any zero- or one-argument commands declared with `\DeclareText*` or `\ProvideText*`, not just those defined using `\DeclareTextSymbol` or `\DeclareTextAccent`.

1.1 Removing encoding-specific commands

In some cases encoding definitions are given to provide some limited support since nothing better is available, for example, the definition for `\textdollar` in `OT1` is a hack since $ and £ actually share the same slot in this encoding. Thus if such a glyph becomes available in a different encoding (e.g., `TS1`) one would like to get rid of the flaky one and make the default definition point to the new encoding. In such a case defining

```
\DeclareTextSymbol{\textdollar}{TS1}{36}
\DeclareTextSymbolDefault{\textdollar}{TS1}
```

is not enough since if typesetting in `OT1` LaTeX will still find the encoding specific-definition for `OT1` and therefore ignore the new default. Therefore to ensure that in this case the `TS1` version is used we have to remove the `OT1` declaration:

```
\UndeclareTextCommand{\textdollar}{OT1}
```

Since the $ sign is a proper glyph in the T1 encoding there is no point removing its definition and forcing LaTeX to pick up the TS1 version if typesetting in this encoding. However, assume you want to use the variant dollar sign, i.e., $ for your dollars. In that case you have to get rid of the T1 declaration as well, e.g., the following would do that for you:

```
\UndeclareTextCommand{\textdollar}{OT1}
\UndeclareTextCommand{\textdollar} {T1}
\DeclareTextCommandDefault{\textdollar}
                          {\UseTextSymbol{TS1}\textdollaroldstyle}
```

1.2 The order of declarations

If an encoding-specific command is defined for more than one encoding, then it will execute fastest in the encoding in which it was defined last since its top-level definition will be set up to execute in that encoding without any overhead.

For this reason the file fonttext.ltx currently first loads the definitions for the T1 encoding and then those for the OT1 encoding so that typesetting in OT1 is optimized since that is (still) the default. However, when T1 is explicitly requested (via \usepackage[T1]{fontenc}) the top-level definitions are automatically changed to favour T1 since its declarations are reloaded in the process.

For the same reason default declarations should never come last since they are implemented as a special encoding themselves (with the name ?). Specifying them last would simply mean to make those encoding-specific commands equally inefficient in all encodings. Therefore the textcomp package, for example, first sets up all defaults to point to TS1 and then declares the commands in the TS1 encoding.

1.3 Docstrip modules

This .dtx file is be used to generate several related files containing font encoding definitions. The mutually exclusive docstrip options are listed here.

T1	generates t1enc.def for the Cork encoding.
TS1	generates ts1enc.def for the Text Companion encoding.
TS1sty	generates textcomp.sty, package that sets up use of the Text Companion encoding.
OT1	generates ot1enc.def for Knuth's CM encoding.
OMS	generates omsenc.def for Knuth's math symbol encoding.
OML	generates omlenc.def for Knuth's math letters encoding.
OT4	generates ot4enc.def for the Polish extension to the OT1 encoding, created by B. Jackowski and M. Ryćko for use with the Polish version of Computer Modern and Computer Concrete.
TU	generates tuenc.def for Unicode font encoding.
package	generates fontenc.sty for selecting encodings.
2ekernel	for the kernel commands.

1.4 Definitions for the kernel

1.4.1 Declaration commands

This section contains definitions for commands such as accents which depend on the current encoding. These commands will usually be kept in `.def` files, for example `ot1enc.def` contains the definitions for the `OT1` encoding.

```
⟨*2ekernel⟩
\message{font encodings,}
```

Far too many macros in one block here!

\DeclareTextCommand
\ProvideTextCommand
\DeclareTextSymbol
\@dec@text@cmd
\chardef@text@cmd
\@changed@cmd
\@changed@x
\TextSymbolUnavailable
\@inmathwarn

If you say:

```
\DeclareTextCommand{\foo}{T1}...
```

then `\foo` is defined to be `\T1-cmd \foo \T1\foo`, where `\T1\foo` is *one* control sequence, not two! We then call `\newcommand` to define `\T1\foo`.

```
\def\DeclareTextCommand{%
   \@dec@text@cmd\newcommand}
\def\ProvideTextCommand{%
   \@dec@text@cmd\providecommand}
\def\@dec@text@cmd#1#2#3{%
   \expandafter\def\expandafter#2%
      \expandafter{%
         \csname#3-cmd\expandafter\endcsname
         \expandafter#2%
         \csname#3\string#2\endcsname
      }%
   \let\@ifdefinable\@rc@ifdefinable
   \expandafter#1\csname#3\string#2\endcsname}
```

This command was introduced to fix a major bug in `\@dec@text@cmd` without changing that command itself. This was thought to be necessary because it is defined in more than one package. (Perhaps the more serious bug is to put complex low-level commands like this in packages?)

The problem it solves is that whereas both `\newcommand` and `\providecommand` (used just above) both handle the resetting of `\@ifdefinable` (following its disabling in `\@dec@text@cmd`), the primitive `\chardef` neither needs the disabling, nor does the resetting.

```
\def\chardef@text@cmd{%
   \let\@ifdefinable\@@ifdefinable
   \chardef
  }
\def\DeclareTextSymbol#1#2#3{%
   \@dec@text@cmd\chardef@text@cmd#1{#2}#3\relax
  }
```

The declarations are only available before `\begin{document}`.

```
\@onlypreamble\DeclareTextCommand
\@onlypreamble\DeclareTextSymbol
```

The sneaky bit in all this is what `\T1-cmd \foo \T1\foo` does. There are five possibilities, depending on the current values of `\protect`, `\cf@encoding` and `\ifmmode`:

- If \protect is \@typeset@protect and \cf@encoding is T1, then we execute \T1\foo. This should be the normal behaviour, and is optimized for speed.
- If \protect is \@typeset@protect, \cf@encoding is (say) OT1, and \OT1\foo is defined, then we execute \OT1\foo.
- If \protect is \@typeset@protect, \cf@encoding is (say) OT1, we're in text mode, and \OT1\foo is undefined, then we define \OT1\foo to be the default value of \foo, and execute \OT1\foo.
- If \protect is \@typeset@protect, \cf@encoding is (say) OT1, we're in math mode, and \OT1\foo is undefined, then we execute the default value of \foo. (This is necessary so that things like $X_\copyright$ work properly.)
- If \protect is not \@typeset@protect then we execute \noexpand\foo. For example, if we are writing to a file, then this results in \foo being written. If we are in a \mark, then \foo will be put in the mark—since \foo is robust, it will then survive all the things which may happen to it whilst it's a \mark.

So after all that, we will either execute the appropriate definition of \foo for the current encoding, or we will execute \noexpand\foo.

The default value of \foo is \?\foo if it is defined, and an error message otherwise.

When the encoding is changed from T1 to OT1, \T1-cmd is defined to be \@changed@cmd and \OT1-cmd is defined to be \@current@cmd. This means that the test for what the current encoding is can be performed quickly.

```
\def\@current@cmd#1{%
   \ifx\protect\@typeset@protect
      \@inmathwarn#1%
   \else
      \noexpand#1\expandafter\@gobble
   \fi}
```

```
\def\@changed@cmd#1#2{%
   \ifx\protect\@typeset@protect
      \@inmathwarn#1%
      \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
         \expandafter\ifx\csname ?\string#1\endcsname\relax
            \expandafter\def\csname ?\string#1\endcsname{%
               \TextSymbolUnavailable#1%
            }%
         \fi
         \global\expandafter\let
               \csname\cf@encoding \string#1\expandafter\endcsname
               \csname ?\string#1\endcsname
      \fi
      \csname\cf@encoding\string#1%
         \expandafter\endcsname
   \else
      \noexpand#1%
   \fi}
```

```
\gdef\TextSymbolUnavailable#1{%
   \@latex@error{%
      Command \protect#1 unavailable in encoding \cf@encoding%
   }\@eha}
```

The command \@inmathwarn produces a warning message if we are currently in math mode. Note that since this command is used inside text commands, it can't call \relax before the \ifmmode. This means that it is possible for the warning to fail to be issued at the beginning of a row of an halign whose template enters math mode. This is probably a bad feature, but there's not much that can be done about it, since adding a \relax would break ligatures and kerning between text symbols.

A more efficient solution would be to make \@inmathwarn and \@inmatherr equal to \@empty and \relax by default, and to have \everymath reset them to their usual definitions. This is left for future investigation (for example it may break some third party code).

```
\def\@inmathwarn#1{%
   \ifmmode
      \@latex@warning{Command \protect#1 invalid in math mode}%
   \fi}
```

(*End definition for* \DeclareTextCommand *and others.*)

\DeclareTextCommandDefault
\ProvideTextCommandDefault

These define commands with encoding ?.

Note that \DeclareTextCommandDefault can only be used in the preamble, but that the \Provide version is allowed in inputenc .def files, so is allowed anywhere.

```
\def\DeclareTextCommandDefault#1{%
   \DeclareTextCommand#1?}
```

```
\def\ProvideTextCommandDefault#1{%
   \ProvideTextCommand#1?}
```

```
\@onlypreamble\DeclareTextCommandDefault
%\@onlypreamble\ProvideTextCommandDefault
```

They require \?-cmd to be initialized as \@changed@cmd.

```
\expandafter\let\csname?-cmd\endcsname\@changed@cmd
```

(*End definition for* \DeclareTextCommandDefault *and* \ProvideTextCommandDefault.)

\DeclareTextAccent

This is just a disguise for defining a TEX \accent command.

```
\def\DeclareTextAccent#1#2#3{%
   \DeclareTextCommand#1{#2}{\add@accent{#3}}}
```

```
\@onlypreamble\DeclareTextAccent
```

(*End definition for* \DeclareTextAccent.)

\add@accent

To save space this code is shared between all text accents that are set using the \accent primitive. The argument is pre-set in a box so that any font loading that is needed is already done within the box. This is needed because font-loading involves grouping and that would prevent the accent mechanism from working so that the accent would not be positioned over the argument. Declarations that change the font should be allowed (only low-level ones are at present) inside the argument of an accent command, but not size changes, as they involve \setbox operations which also inhibit the mechanism of the \accent primitive.

Note that the whole process is within a group. For a detailed discussion of this reimplementation and its deficiencies, see pr/3160.

```
\def\add@accent#1#2{\hmode@bgroup
```

Turn off the group in \UseTextSymbol in case this is used inside the argument of \add@accent.

```
\let\hmode@start@before@group\@firstofone
\setbox\@tempboxa\hbox{#2%
```

When presetting the argument in a box we record its \spacefactor for later use after the accent got typeset. This way something like \`A gets the spacefactor of A (i.e., 999) rather than the default value of 1000.

```
    \global\mathchardef\accent@spacefactor\spacefactor}%
```

The accent primitive doesn't allow things \begingroup to interfere between accent and base character. Therefore we need to avoid that (they are some hidden inside \maybe@load@fontshape). As we don't have to load the fontshape in this case (as that happened in the box above if necessary, we simply disable that part of the code temporarily. We also ignore \ignorespaces which has the same issue and may show up as part of \normalfont if that is used.

```
\let\maybe@load@fontshape\relax
\let\ignorespaces\relax
\accent#1 #2\egroup\ifmmode\else\spacefactor\accent@spacefactor\fi}
```

Default definition for \accent@spacefactor prevents a horrible death of the above macro inside an unprotected \edef.

```
\let\accent@spacefactor\relax
```

(*End definition for* \add@accent.)

\hmode@bgroup

```
\def\hmode@bgroup{\leavevmode\bgroup}
```

(*End definition for* \hmode@bgroup.)

\DeclareTextCompositeCommand
\DeclareTextComposite
\@text@composite
\@text@composite@x
\@strip@args

Another amusing game to play with \expandafter, \csname, and \string. When you say \DeclareTextCompositeCommand{\foo}{T1}{a}{bar}, we look to see if the expansion of \T1\foo begins with \@text@composite, and if it doesn't, we redefine \T1\foo to be:

```
#1 -> \@text@composite \T1\foo #1\@empty \@text@composite {...}
```

where ... is the previous definition of \T1\foo. Finally, we define \\T1\foo-a to expand to bar.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2017/04/15}{\DeclareTextCompositeCommand}
⟨latexrelease⟩                              {test for undeclared accent}%
⟨*2ekernel | latexrelease⟩
\def\DeclareTextCompositeCommand#1#2#3#4{%
  \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
  \ifx\reserved@a\relax
   \DeclareTextCommand#1{#2}{%
     \@latex@error{\string#1 undeclared in encoding #2}\@eha}%
   \@latex@info{Composite with undeclared \string#1 in encoding #2}%
   \expandafter\let\expandafter\reserved@a\csname#2\string#1\endcsname
  \fi
  \expandafter\expandafter\expandafter\ifx
  \expandafter\@car\reserved@a\relax\relax\@nil \@text@composite \else
      \edef\reserved@b##1{%
```

```
        \def\expandafter\noexpand
           \csname#2\string#1\endcsname####1{%
           \noexpand\@text@composite
              \expandafter\noexpand\csname#2\string#1\endcsname
              ####1\noexpand\@empty\noexpand\@text@composite
              {##1}}}%
      \expandafter\reserved@b\expandafter{\reserved@a{##1}}%
   \fi
   \expandafter\def\csname\expandafter\string\csname
      #2\endcsname\string#1-\string#3\@empty\endcsname{#4}%
  }
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\DeclareTextCompositeCommand}
⟨latexrelease⟩                              {test for undeclared accent}%
⟨latexrelease⟩\def\DeclareTextCompositeCommand#1#2#3#4{%
⟨latexrelease⟩  \expandafter\let\expandafter\reserved@a
⟨latexrelease⟩                       \csname#2\string#1\endcsname
⟨latexrelease⟩  \expandafter\expandafter\expandafter\ifx
⟨latexrelease⟩  \expandafter\@car\reserved@a\relax\relax\@nil
⟨latexrelease⟩                                \@text@composite \else
⟨latexrelease⟩      \edef\reserved@b##1{%
⟨latexrelease⟩         \def\expandafter\noexpand
⟨latexrelease⟩           \csname#2\string#1\endcsname####1{%
⟨latexrelease⟩           \noexpand\@text@composite
⟨latexrelease⟩             \expandafter\noexpand\csname#2\string#1\endcsname
⟨latexrelease⟩             ####1\noexpand\@empty\noexpand\@text@composite
⟨latexrelease⟩             {##1}}}%
⟨latexrelease⟩      \expandafter\reserved@b\expandafter{\reserved@a{##1}}%
⟨latexrelease⟩   \fi
⟨latexrelease⟩   \expandafter\def\csname\expandafter\string\csname
⟨latexrelease⟩      #2\endcsname\string#1-\string#3\@empty\endcsname{#4}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
\@onlypreamble\DeclareTextCompositeCommand
```

This all works because:

```
\@text@composite \T1\foo A\@empty \@text@composite {...}
```

expands to `\\T1\foo-A` if `\\T1\foo-A` has been defined, and `{...}` otherwise.

Note that `\@text@composite` grabs the first token of the argument and puts just that in the csname. This is so that `\'{\textit{e}}` will work—it checks whether `\\T1\'-\textit` is defined (which presumably it isn't) and so expands to `{\accent 1 \textit{e}}`.

This trick won't always work, for example `\'{{\itshape e}}` will expand to (with spaces added for clarity):

```
\csname \string \T1\' - \string {\itshape e} \@empty \endcsname
```

which will die pretty horribly. Unfortunately there's not much can be done about this if we're going to use `\csname` lookups as a fast way of accessing composites.

This has an unfortunate 'misfeature' though, which is that in the T1 encoding, `\'{aa}` produces á. This is not the expected behaviour, and should perhaps be fixed if the fix doesn't affect performance too badly.

Finally, it's worth noting that the `\@empty` is used in `\@text@composite` so that accents will work even when the argument is empty. If you say `\'{}` then this looks up `\\T1\'-\@empty`, which ought to be `\relax`, and so all is well. If we didn't include the `\@empty`, then `\'{}` would expand to:

```
\csname \string \T1\' - \string \endcsname
```

so the `\endcsname` would be `\string`'ed and the whole of the rest of the document would be put inside the `\csname`. This would not be good.

```
\def\@text@composite#1#2#3\@text@composite{%
   \expandafter\@text@composite@x
      \csname\string#1-\string#2\endcsname}
```

Originally the `\@text@composite@x` macro had two arguments and if `#1` was not `\relax` it was executed, otherwise `#2` was executed. All this happened within the `\ifx` code so that neither `#1` nor `#2` could have picked up any additional arguments form the input stream. This has now being changed using the typical `\@firstoftwo` / `\@secondoftwo` coding. This way the final expansion will happen without any `\else` or `\fi` intervening in the case that we need to get a further token from the input stream.

```
\def\@text@composite@x#1{%
   \ifx#1\relax
      \expandafter\@secondoftwo
   \else
      \expandafter\@firstoftwo
   \fi
   #1}
```

The command `\DeclareTextComposite` uses `\DeclareTextCompositeCommand` to declare a command which expands out to a single glyph.

```
\catcode\z@=11\relax
\def\DeclareTextComposite#1#2#3#4{%
   \def\reserved@a{\DeclareTextCompositeCommand#1{#2}{#3}}%
   \bgroup
      \lccode\z@#4%
      \lowercase{%
   \egroup
      \reserved@a ^^@}}
\catcode\z@=15\relax
\@onlypreamble\DeclareTextComposite
```

(*End definition for* `\DeclareTextCompositeCommand` *and others.*)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                    {\UseTextAccent}{Make commands robust}%
```

`\UseTextAccent`
`\UseTextSymbol`
`\@use@text@encoding`

These fragile commands access glyphs from different encodings. They use grotty low-level calls to the font selection scheme for speed, and in order to make sure that `\UseTextSymbol` doesn't do anything which you're not allowed to do between an `\accent` and its glyph.

For a detailed discussion of this reimplementation and its deficiencies, see pr/3160.

```
\DeclareRobustCommand*\UseTextAccent[3]{%
  \hmode@start@before@group
   {%
```

Turn off the group in \UseTextSymbol in case this is used inside the arguments of \UseTextAccent.

```
    \let\hmode@start@before@group\@firstofone
    \let\@curr@enc\cf@encoding
    \@use@text@encoding{#1}%
    #2{\@use@text@encoding\@curr@enc#3}%
   }}
```

```
\DeclareRobustCommand*\UseTextSymbol[2]{%
       \hmode@start@before@group
       {%
          \def\@wrong@font@char{\MessageBreak
             for \noexpand\symbol`\string#2'}%
          \@use@text@encoding{#1}%
          #2%
       }%
    }
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\UseTextAccent}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\UseTextAccent
⟨latexrelease⟩\kernel@make@fragile\UseTextSymbol
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

Switch to a different text encoding without any grouping for use in \UseTextAccent or \UseTextSymbol (and for \oldstylenums).

```
\def\@use@text@encoding#1{%
   \edef\f@encoding{#1}%
   \xdef\font@name{%
      \csname\curr@fontshape/\f@size\endcsname}%
   \pickup@font
   \font@name
   \@@enc@update}
```

(*End definition for* \UseTextAccent*,* \UseTextSymbol*, and* \@use@text@encoding*.*)

\hmode@start@before@group

The \hmode@start@before@group starts hmode and should be immediately followed by an explicit {...}. Its purpose is to ensure that hmode is started before this group is opened. Inside \add@accent and \UseTextAccent it is redefined to remove this group so that it doesn't conflict with the \accent primitive.

For a detailed discussion see pr/3160.

```
\let\hmode@start@before@group\leavevmode
```

(*End definition for* \hmode@start@before@group*.*)

\DeclareTextSymbolDefault
\DeclareTextAccentDefault

Some syntactic sugar. Again, these should probably be optimized for speed.

```
\def\DeclareTextSymbolDefault#1#2{%
   \DeclareTextCommandDefault#1{\UseTextSymbol{#2}#1}}
\def\DeclareTextAccentDefault#1#2{%
   \DeclareTextCommandDefault#1{\UseTextAccent{#2}#1}}
\@onlypreamble\DeclareTextSymbolDefault
\@onlypreamble\DeclareTextAccentDefault
```

(*End definition for* `\DeclareTextSymbolDefault` *and* `\DeclareTextAccentDefault`.)

\UndeclareTextCommand

This command safely removes an encoding specific declaration for a given encoding. It is helpful if one intends to use the default definition always and therefore wants to get rid of a declaration for some specific encoding.

```
\def\UndeclareTextCommand#1#2{%
```

If there is no declaration for the current encoding do nothing. (This makes a hash table entry but without eTEX we can't do anything about that).

```
  \expandafter\ifx\csname#2\string#1\endcsname\relax
  \else
```

Else: throw away that declaration.

```
     \global\expandafter\let\csname#2\string#1\endcsname
            \@undefined
```

But this is unfortunately not enough, we have to take a look at the top-level definition of the encoding specific command which for a command `\foo` would look similar to `\T1-cmd \foo \T1\foo` (three tokens).

Of course, instead of `T1` one could see a different encoding name; which one depends the encoding for which `\foo` was declared last.

Now assume we have just removed the declaration for `\foo` in `T1` and the top-level of `\foo` expands to the above. Then we better change that pretty fast otherwise we do get an "undefined csname error" when we try to typeset `\foo` within `T1` instead of getting the default definition for `\foo`. And what is the best way to change that top-level definition? Well, the only "encoding" we know for sure will still be around is the default encoding denoted by `?`.

Thus in case the last token of the top-level expansion is now undefined we change the declaration to look like `\?-cmd \foo \?\foo` which is done by the following (readable?) code:

```
     \expandafter\expandafter\expandafter
     \ifx\expandafter\@thirdofthree#1\@undefined
       \expandafter\gdef\expandafter#1\expandafter
          {\csname ?-cmd\expandafter\endcsname\expandafter
           #1\csname?\string#1\endcsname}%
     \fi
 \fi
}
\@onlypreamble\UndeclareTextCommand
```

(*End definition for* `\UndeclareTextCommand`.)

1.4.2 Hyphenation

\patterns
\@@patterns
\hyphenation
\@@hyphenation

We redefine \patterns and \hyphenation to allow the use of commands declared with \DeclareText* to be used inside them.

```
%\let\@@patterns\patterns
%\let\@@hyphenation\hyphenation
%\def\patterns{%
%   \bgroup
%      \let\protect\@empty
%      \let\@typeset@protect\@empty
%      \let\@changed@x\@changed@x@mouth
%   \afterassignment\egroup
%   \@@patterns
%}
%\def\hyphenation{%
%   \bgroup
%      \let\protect\@empty
%      \let\@typeset@protect\@empty
%      \let\@changed@x\@changed@x@mouth
%   \afterassignment\egroup
%   \@@hyphenation
%}
```

(*End definition for* \patterns *and others.*)

1.4.3 Miscellania

\a

The \a command is used to access the accent commands even when they have been redefined (for example by the tabbing environment). Its internal name is \@tabacckludge.

The \string within the \csname guards against something like ' being active at the point of use.

```
\def\@tabacckludge#1{\expandafter\@changed@cmd
                                  \csname\string#1\endcsname\relax}
\let\a=\@tabacckludge
```

(*End definition for* \a.)

1.4.4 Default encodings

We define the default encodings for most commands to be either OT1, OML or OMS. These defaults are in the kernel and therefore fonts with these encodings must be available unless these defaults are redefined elsewhere. Recall that the standard kernel loads the encoding files for these encodings, and also that for the T1 encoding.

The naming conventions in the kernel are not what we would use if we were starting from scratch... Those defined by DEK (like \ae and \ss) or by the TEX Users Group Technical Working Group on multi-lingual typesetting (like \th and \ng) have short names. Those which were added to the kernel in 1993 and early 1994 are named after their Adobe glyph names (like \guillemotleft and \quotedblbase). Unfortunately, this naming scheme won't work for all glyphs, since some names (like \space) are already used, and some (like \endash) are very likely to be defined by users. So we're now using the naming scheme of \text followed by the Adobe name, (like \textendash and \textsterling). Except that some glyphs don't have Adobe names, so we're using the names used by fontinst for those (like \textcompwordmark). Sigh.

Some accents from OT1:

```
\DeclareTextAccentDefault{\"}{OT1}
\DeclareTextAccentDefault{\'}{OT1}
\DeclareTextAccentDefault{\.}{OT1}
\DeclareTextAccentDefault{\=}{OT1}
\DeclareTextAccentDefault{\H}{OT1}
\DeclareTextAccentDefault{\^}{OT1}
\DeclareTextAccentDefault{\`}{OT1}
\DeclareTextAccentDefault{\b}{OT1}
\DeclareTextAccentDefault{\c}{OT1}
\DeclareTextAccentDefault{\d}{OT1}
\DeclareTextAccentDefault{\r}{OT1}
\DeclareTextAccentDefault{\u}{OT1}
\DeclareTextAccentDefault{\v}{OT1}
\DeclareTextAccentDefault{\~}{OT1}
```

Some symbols from OT1:

```
%\DeclareTextSymbolDefault{\AA}{OT1}
\DeclareTextSymbolDefault{\AE}{OT1}
\DeclareTextSymbolDefault{\L}{OT1}
\DeclareTextSymbolDefault{\OE}{OT1}
\DeclareTextSymbolDefault{\O}{OT1}
%\DeclareTextSymbolDefault{\aa}{OT1}
\DeclareTextSymbolDefault{\ae}{OT1}
\DeclareTextSymbolDefault{\i}{OT1}
\DeclareTextSymbolDefault{\j}{OT1}
```

```
\DeclareTextSymbolDefault{\ij}{OT1}
\DeclareTextSymbolDefault{\IJ}{OT1}
```

```
\DeclareTextSymbolDefault{\l}{OT1}
\DeclareTextSymbolDefault{\oe}{OT1}
\DeclareTextSymbolDefault{\o}{OT1}
\DeclareTextSymbolDefault{\ss}{OT1}
\DeclareTextSymbolDefault{\textdollar}{OT1}
\DeclareTextSymbolDefault{\textemdash}{OT1}
\DeclareTextSymbolDefault{\textendash}{OT1}
\DeclareTextSymbolDefault{\textexclamdown}{OT1}
%\DeclareTextSymbolDefault{\texthyphenchar}{OT1}
%\DeclareTextSymbolDefault{\texthyphen}{OT1}
\DeclareTextSymbolDefault{\textquestiondown}{OT1}
\DeclareTextSymbolDefault{\textquotedblleft}{OT1}
\DeclareTextSymbolDefault{\textquotedblright}{OT1}
\DeclareTextSymbolDefault{\textquoteleft}{OT1}
\DeclareTextSymbolDefault{\textquoteright}{OT1}
\DeclareTextSymbolDefault{\textsterling}{OT1}
```

Some symbols from OMS:

```
\DeclareTextSymbolDefault{\textasteriskcentered}{OMS}
\DeclareTextSymbolDefault{\textbackslash}{OMS}
\DeclareTextSymbolDefault{\textbar}{OMS}
\DeclareTextSymbolDefault{\textbardbl}{OMS}
\DeclareTextSymbolDefault{\textbraceleft}{OMS}
\DeclareTextSymbolDefault{\textbraceright}{OMS}
\DeclareTextSymbolDefault{\textbullet}{OMS}
```

```
\DeclareTextSymbolDefault{\textdaggerdbl}{OMS}
\DeclareTextSymbolDefault{\textdagger}{OMS}
\DeclareTextSymbolDefault{\textparagraph}{OMS}
\DeclareTextSymbolDefault{\textperiodcentered}{OMS}
\DeclareTextSymbolDefault{\textsection}{OMS}
\DeclareTextAccentDefault{\textcircled}{OMS}
```

Some symbols from OML:

```
\DeclareTextSymbolDefault{\textless}{OML}
\DeclareTextSymbolDefault{\textgreater}{OML}
\DeclareTextAccentDefault{\t}{OML}
```

Some defaults we can fake.

The interface for defining `\copyright` changed, it used to use `\expandafter` to add braces at the appropriate points.

```
\DeclareTextCommandDefault{\textcopyright}{\textcircled{c}}
% \expandafter\def\expandafter
%                 \copyright\expandafter{\expandafter{\copyright}}
```

```
\DeclareTextCommandDefault{\textasciicircum}{\^{}}
\DeclareTextCommandDefault{\textasciitilde}{\~{}}
\DeclareTextCommandDefault{\textunderscore}{%
  \leavevmode \kern.06em\vbox{\hrule\@width.3em}}
```

There is no good reason anymore to fake `\textcompwordmark`.

```
%\DeclareTextCommandDefault{\textcompwordmark}{\leavevmode\kern\z@}
\DeclareTextSymbolDefault{\textcompwordmark}{T1}
```

```
\DeclareTextCommandDefault{\textvisiblespace}{%
   \mbox{\kern.06em\vrule \@height.3ex}%
   \vbox{\hrule \@width.3em}%
   \hbox{\vrule \@height.3ex}}
```

Using `\fontdimen3` in the next definition is some sort of a kludge (since it is the interword stretch) but it makes the ellipsis come out right in mono-spaced fonts too (since there it is zero).

```
\DeclareTextCommandDefault{\textellipsis}{%
   .\kern\fontdimen3\font
   .\kern\fontdimen3\font
   .\kern\fontdimen3\font}
```

```
%\DeclareTextCommandDefault{\textregistered}{\textcircled{\scshape r}}
\DeclareTextCommandDefault{\textregistered}{\textcircled{%
     \check@mathfonts\fontsize\sf@size\z@\math@fontsfalse\selectfont R}}
\DeclareTextCommandDefault{\texttrademark}{\textsuperscript{TM}}
\DeclareTextCommandDefault{\SS}{SS}
```

```
\DeclareTextCommandDefault{\textordfeminine}{\textsuperscript{a}}
\DeclareTextCommandDefault{\textordmasculine}{\textsuperscript{o}}
```

1.4.5 Math material

Some commands can be used in both text and math mode:

```
\DeclareRobustCommand{\$}{\ifmmode\mathdollar\else\textdollar\fi}
```

We use `\protected` not `\DeclareRobustCommand` so that `\bigl\{` etc. works inside `\protected@edef`.

```
\protected\def\{{\ifmmode\lbrace\else\textbraceleft\fi}
\protected\def\}{\ifmmode\rbrace\else\textbraceright\fi}
```

```
\DeclareRobustCommand{\P}{\ifmmode\mathparagraph\else\textparagraph\fi}
\DeclareRobustCommand{\S}{\ifmmode\mathsection\else\textsection\fi}
\DeclareRobustCommand{\dag}{\ifmmode{\dagger}\else\textdagger\fi}
\DeclareRobustCommand{\ddag}{\ifmmode{\ddagger}\else\textdaggerdbl\fi}
```

For historical reasons `\copyright` needs `{}` around the definition in maths.

```
\DeclareRobustCommand{\_}{%
   \ifmmode\nfss@text{\textunderscore}\else\textunderscore\fi}
\DeclareRobustCommand{\copyright}{%
   \ifmmode{\nfss@text{\textcopyright}}\else\textcopyright\fi}
\DeclareRobustCommand{\pounds}{%
   \ifmmode\mathsterling\else\textsterling\fi}
```

```
\DeclareRobustCommand{\dots}{%
   \ifmmode\mathellipsis\else\textellipsis\fi}
```

```
\let\ldots\dots
```

Default definition of the commabelow accent.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/10/01}{\textcommabelow}{comma accent}%
⟨*2ekernel | latexrelease⟩
\DeclareTextCommandDefault\textcommabelow[1]
  {\hmode@bgroup\ooalign{\null#1\crcr\hidewidth\raise-.31ex
   \hbox{\check@mathfonts\fontsize\ssf@size\z@
   \math@fontsfalse\selectfont,}\hidewidth}\egroup}
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\textcommabelow}{comma accent}%
⟨latexrelease⟩\let\textcommabelow\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-G\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-K\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-k\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-L\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-l\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-N\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-n\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩  \let\csname\string\T1\string\c-R\endcsname\@undefined
```

```
⟨latexrelease⟩\expandafter
⟨latexrelease⟩   \let\csname\string\T1\string\c-r\endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

Default definition of the commaabove accent(E.G.).

```
⟨latexrelease⟩\IncludeInRelease{2016/02/01}{\textcommaabove}{comma above}%
⟨*2ekernel | latexrelease⟩
\DeclareTextCommandDefault\textcommaabove[1]{%
  \hmode@bgroup
  \ooalign{%
    \hidewidth
    \raise.7ex\hbox{%
      \check@mathfonts\fontsize\ssf@size\z@\math@fontsfalse\selectfont‘%
    }%
   \hidewidth\crcr
   \null#1\crcr
  }%
  \egroup
}
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\textcommaabove}{comma above}%
⟨latexrelease⟩\let\textcommaabove\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩   \let\csname\string\OT1\string\c-g\endcsname\@undefined
⟨latexrelease⟩\expandafter
⟨latexrelease⟩   \let\csname\string\T1\string\c-g\endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

1.5 Definitions for the OT1 encoding

The definitions for the ‘TEX text’ (OT1) encoding.

Declare the encoding.

```
⟨*OT1⟩
\DeclareFontEncoding{OT1}{}{}
```

Declare the accents.

```
\DeclareTextAccent{\"}{OT1}{127}
\DeclareTextAccent{\’}{OT1}{19}
\DeclareTextAccent{\.}{OT1}{95}
\DeclareTextAccent{\=}{OT1}{22}
\DeclareTextAccent{\^}{OT1}{94}
\DeclareTextAccent{\‘}{OT1}{18}
\DeclareTextAccent{\~}{OT1}{126}
\DeclareTextAccent{\H}{OT1}{125}
\DeclareTextAccent{\u}{OT1}{21}
\DeclareTextAccent{\v}{OT1}{20}
\DeclareTextAccent{\r}{OT1}{23}
```

Some accents have to be built by hand: Note that `\ooalign` and `\o@lign` must be inside a group. In these definitions we no longer use the helper function `\sh@ft` from plain.tex since that now has two incompatible definitions.

```
\DeclareTextCommand{\b}{OT1}[1]
   {\hmode@bgroup\o@lign{\relax#1\crcr\hidewidth\ltx@sh@ft{-3ex}%
```

```
     \vbox to.2ex{\hbox{\char22}\vss}\hidewidth}\egroup}
\DeclareTextCommand{\c}{OT1}[1]
   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent24 #1%
    \else{\ooalign{\unhbox\z@\crcr\hidewidth\char24\hidewidth}}\fi}
\DeclareTextCommand{\d}{OT1}[1]
   {\hmode@bgroup
    \o@lign{\relax#1\crcr\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}
```

Declare the text symbols.

```
\DeclareTextSymbol{\AE}{OT1}{29}
\DeclareTextSymbol{\OE}{OT1}{30}
\DeclareTextSymbol{\O}{OT1}{31}
\DeclareTextSymbol{\ae}{OT1}{26}
\DeclareTextSymbol{\i}{OT1}{16}
\DeclareTextSymbol{\j}{OT1}{17}
\DeclareTextSymbol{\oe}{OT1}{27}
\DeclareTextSymbol{\o}{OT1}{28}
\DeclareTextSymbol{\ss}{OT1}{25}
\DeclareTextSymbol{\textemdash}{OT1}{124}
\DeclareTextSymbol{\textendash}{OT1}{123}
```

The `\nobreak\hskip\z@` is there to prevent a break after the hyphen but allow later breaks in the remainder of the word.

```
\DeclareTextCommand{\textnonbreakinghyphen}{OT1}{\mbox{-}\nobreak\hskip\z@}
\DeclareTextCommand{\textfiguredash}       {OT1}{\textendash}
\DeclareTextCommand{\texthorizontalbar}    {OT1}{\textemdash}
```

Using the ligatures helps with OT1 fonts that have `\textexclamdown` and `\textquestiondown` in unusual positions.

```
%\DeclareTextSymbol{\textexclamdown}{OT1}{60}
%\DeclareTextSymbol{\textquestiondown}{OT1}{62}
\DeclareTextCommand{\textexclamdown}{OT1}{!`}
\DeclareTextCommand{\textquestiondown}{OT1}{?`}
%\DeclareTextSymbol{\texthyphenchar}{OT1}{`\-}
%\DeclareTextSymbol{\texthyphen}{OT1}{`\-}
\DeclareTextSymbol{\textquotedblleft}{OT1}{92}
\DeclareTextSymbol{\textquotedblright}{OT1}{`\"}
\DeclareTextSymbol{\textquoteleft}{OT1}{`\`}
\DeclareTextSymbol{\textquoteright}{OT1}{`\'}
```

Some symbols which are faked from others:

```
% \DeclareTextCommand{\aa}{OT1}
%    {{\accent23a}}
\DeclareTextCommand{\L}{OT1}
   {\leavevmode\setbox\z@\hbox{L}\hb@xt@\wd\z@{\hss\@xxxii L}}
\DeclareTextCommand{\l}{OT1}
   {\hmode@bgroup\@xxxii l\egroup}
% \DeclareTextCommand{\AA}{OT1}
%    {\leavevmode\setbox\z@\hbox{h}\dimen@\ht\z@\advance\dimen@-1ex%
%     \rlap{\raise.67\dimen@\hbox{\char23}}A}
```

In the OT1 encoding Å has a hand-crafted definition, so we have here the first recorded explicit use of `\DeclareTextCompositeCommand`.

```
\DeclareTextCompositeCommand{\r}{OT1}{A}
   {\leavevmode\setbox\z@\hbox{!}\dimen@\ht\z@\advance\dimen@-1ex%
    \rlap{\raise.67\dimen@\hbox{\char23}}A}
```

The dutch language uses the letter 'ij'. It is available in T1 encoded fonts, but not in the OT1 encoded fonts. Therefore we fake it for the OT1 encoding.

```
\DeclareTextCommand{\ij}{OT1}{%
  \nobreak\hskip\z@skip i\kern-0.02em\nobreak\hskip\z@skip j}
\DeclareTextCommand{\IJ}{OT1}{%
  \nobreak\hskip\z@skip I\kern-0.02em\nobreak\hskip\z@skip J}
```

In the OT1 encoding, £ and $ share a slot.

```
\DeclareTextCommand{\textdollar}{OT1}{\hmode@bgroup
   \ifdim \fontdimen\@ne\font >\z@
      \slshape
   \else
      \upshape
   \fi
   \char`\$\egroup}
```

```
\DeclareTextCommand{\textsterling}{OT1}{\hmode@bgroup
   \ifdim \fontdimen\@ne\font >\z@
      \itshape
   \else
      \fontshape{ui}\selectfont
   \fi
   \char`\$\egroup}
```

Here we are adding some more composite commands to the OT1 encoding. This makes the use of certain accents with i compatible with their use with the T1 encoding; this enables them to become true LaTeX internal representations. However, it will make these accents work a little less fast since a check will always be made for the existence of a composite.

```
\DeclareTextComposite{\.}{OT1}{i}{`\i}
\DeclareTextComposite{\.}{OT1}{\i}{`\i}
\DeclareTextCompositeCommand{\`}{OT1}{i}{\@tabacckludge`\i}
\DeclareTextCompositeCommand{\'}{OT1}{i}{\@tabacckludge'\i}
\DeclareTextCompositeCommand{\^}{OT1}{i}{\^\i}
\DeclareTextCompositeCommand{\"}{OT1}{i}{\"\i}
```

T1 encoding is given more extensive set of overloads for \c But here we just adjust \c{g}.

```
\ifx\textcommaabove\@undefined\else
\DeclareTextCompositeCommand{\c}{OT1}{g}{\textcommaabove{g}}
\fi
```

⟨/OT1⟩

1.6 Definitions for the T1 encoding

The definitions for the 'Extended TeX text' (T1) encoding.

Declare the encoding.

```
⟨*T1⟩
\DeclareFontEncoding{T1}{}{}
```

Declare the accents.

```
\DeclareTextAccent{\`}{T1}{0}
\DeclareTextAccent{\'}{T1}{1}
\DeclareTextAccent{\^}{T1}{2}
```

```
\DeclareTextAccent{\~}{T1}{3}
\DeclareTextAccent{\"}{T1}{4}
\DeclareTextAccent{\H}{T1}{5}
\DeclareTextAccent{\r}{T1}{6}
\DeclareTextAccent{\v}{T1}{7}
\DeclareTextAccent{\u}{T1}{8}
\DeclareTextAccent{\=}{T1}{9}
\DeclareTextAccent{\.}{T1}{10}
```

Some accents have to be built by hand. Note that `\ooalign` and `\o@lign` must be inside a group. In these definitions we no longer use the helper function `\sh@ft` from plain.tex since that now has two incompatible definitions.

```
\DeclareTextCommand{\b}{T1}[1]
   {\hmode@bgroup\o@lign{\relax#1\crcr\hidewidth\ltx@sh@ft{-3ex}%
     \vbox to.2ex{\hbox{\char9}\vss}\hidewidth}\egroup}
\DeclareTextCommand{\c}{T1}[1]
   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent11 #1%
     \else{\ooalign{\unhbox\z@\crcr
        \hidewidth\char11\hidewidth}}\fi}
\DeclareTextCommand{\d}{T1}[1]
   {\hmode@bgroup
    \o@lign{\relax#1\crcr\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}
\DeclareTextCommand{\k}{T1}[1]
   {\hmode@bgroup\ooalign{\null#1\crcr\hidewidth\char12}\egroup}
\DeclareTextCommand{\textogonekcentered}{T1}[1]
   {\hmode@bgroup\ooalign{%
                 \null#1\crcr\hidewidth\char12\hidewidth}\egroup}
```

Some symbols are constructed.

Slot 24 contains a small circle intended for construction of these two glyphs.

```
\DeclareTextCommand{\textperthousand}{T1}
   {\%\char 24 }          % space or ‘relax as delimiter?
\DeclareTextCommand{\textpertenthousand}{T1}
   {\%\char 24\char 24 }  % space or ‘relax as delimiter?
```

For Maltese, `\Hwithstroke` and `\hwithstroke` are needed.

```
\DeclareTextCommand{\Hwithstroke}{T1}
   {%
    \hmode@bgroup
    \vphantom{H}%
    \sbox\z@{H}%
    \ooalign{%
      H\cr
      \hidewidth
      \vrule
        height \dimexpr 0.7\ht\z@+0.1ex\relax
        depth  -0.7\ht\z@
        width  0.8\wd\z@
      \hidewidth\cr
    }%
    \egroup
   }
\DeclareTextCommand{\hwithstroke}{T1}
   {%
```

```
    \hmode@bgroup
    \vphantom{h}%
    \sbox\z@{h}%
    \ooalign{%
      h\cr
      \kern0.075\wd\z@
      \vrule
        height \dimexpr 0.7\ht\z@+0.1ex\relax
        depth  -0.7\ht\z@
        width  0.4\wd\z@
      \hidewidth\cr
    }%
    \egroup
  }
```

Declare the text symbols.

```
%\DeclareTextSymbol{\AA}{T1}{197}
\DeclareTextSymbol{\AE}{T1}{198}
\DeclareTextSymbol{\DH}{T1}{208}
\DeclareTextSymbol{\DJ}{T1}{208}
\DeclareTextSymbol{\L}{T1}{138}
\DeclareTextSymbol{\NG}{T1}{141}
\DeclareTextSymbol{\OE}{T1}{215}
\DeclareTextSymbol{\O}{T1}{216}
\DeclareTextSymbol{\SS}{T1}{223}
\DeclareTextSymbol{\TH}{T1}{222}
%\DeclareTextSymbol{\aa}{T1}{229}
\DeclareTextSymbol{\ae}{T1}{230}
\DeclareTextSymbol{\dh}{T1}{240}
\DeclareTextSymbol{\dj}{T1}{158}

\DeclareTextSymbol{\guillemetleft}{T1}{19}
\DeclareTextSymbol{\guillemetright}{T1}{20}
% old Adobe names
\DeclareTextSymbol{\guillemotleft}{T1}{19}
\DeclareTextSymbol{\guillemotright}{T1}{20}

\DeclareTextSymbol{\guilsinglleft}{T1}{14}
\DeclareTextSymbol{\guilsinglright}{T1}{15}
\DeclareTextSymbol{\i}{T1}{25}
\DeclareTextSymbol{\j}{T1}{26}
\DeclareTextSymbol{\ij}{T1}{188}
\DeclareTextSymbol{\IJ}{T1}{156}
\DeclareTextSymbol{\l}{T1}{170}
\DeclareTextSymbol{\ng}{T1}{173}
\DeclareTextSymbol{\oe}{T1}{247}
\DeclareTextSymbol{\o}{T1}{248}
\DeclareTextSymbol{\quotedblbase}{T1}{18}
\DeclareTextSymbol{\quotesinglbase}{T1}{13}
\DeclareTextSymbol{\ss}{T1}{255}
\DeclareTextSymbol{\textasciicircum}{T1}{`\^}
\DeclareTextSymbol{\textasciitilde}{T1}{`\~}
\DeclareTextSymbol{\textbackslash}{T1}{`\\}
\DeclareTextSymbol{\textbar}{T1}{`\|}
\DeclareTextSymbol{\textbraceleft}{T1}{`\{}
```

```
\DeclareTextSymbol{\textbraceright}{T1}{`\}}
\DeclareTextSymbol{\textcompwordmark}{T1}{23}
\DeclareTextSymbol{\textdollar}{T1}{`\$}
\DeclareTextSymbol{\textemdash}{T1}{22}
\DeclareTextSymbol{\textendash}{T1}{21}
```

The `\nobreak\hskip\z@` is there to prevent a break after the hyphen but allow later breaks in the remainder of the word.

```
\DeclareTextCommand{\textnonbreakinghyphen}{T1}{\mbox{-}\nobreak\hskip\z@}
\DeclareTextCommand{\textfiguredash}       {T1}{\textendash}
\DeclareTextCommand{\texthorizontalbar}    {T1}{\textemdash}
```

```
\DeclareTextSymbol{\textexclamdown}{T1}{189}
\DeclareTextSymbol{\textgreater}{T1}{`\>}
%\DeclareTextSymbol{\texthyphenchar}{T1}{127}
%\DeclareTextSymbol{\texthyphen}{T1}{`\-}
\DeclareTextSymbol{\textless}{T1}{`\<}
\DeclareTextSymbol{\textquestiondown}{T1}{190}
\DeclareTextSymbol{\textquotedblleft}{T1}{16}
\DeclareTextSymbol{\textquotedblright}{T1}{17}
\DeclareTextSymbol{\textquotedbl}{T1}{`\"}
\DeclareTextSymbol{\textquoteleft}{T1}{`\`}
\DeclareTextSymbol{\textquoteright}{T1}{`\'}
\DeclareTextSymbol{\textsection}{T1}{159}
\DeclareTextSymbol{\textsterling}{T1}{191}
\DeclareTextSymbol{\textunderscore}{T1}{95}
\DeclareTextSymbol{\textvisiblespace}{T1}{32}
\DeclareTextSymbol{\th}{T1}{254}
```

Declare the composites.

```
\DeclareTextComposite{\.}{T1}{i}{`\i}
\DeclareTextComposite{\.}{T1}{\i}{`\i}
```

"80 = 128

```
\DeclareTextComposite{\u}{T1}{A}{128}
\DeclareTextComposite{\k}{T1}{A}{129}
\DeclareTextComposite{\'}{T1}{C}{130}
\DeclareTextComposite{\v}{T1}{C}{131}
\DeclareTextComposite{\v}{T1}{D}{132}
\DeclareTextComposite{\v}{T1}{E}{133}
\DeclareTextComposite{\k}{T1}{E}{134}
\DeclareTextComposite{\u}{T1}{G}{135}
```

"88 = 136

```
\DeclareTextComposite{\'}{T1}{L}{136}
\DeclareTextComposite{\v}{T1}{L}{137}
\DeclareTextComposite{\'}{T1}{N}{139}
\DeclareTextComposite{\v}{T1}{N}{140}
\DeclareTextComposite{\H}{T1}{O}{142}
\DeclareTextComposite{\'}{T1}{R}{143}
```

"90 = 144

```
\DeclareTextComposite{\v}{T1}{R}{144}
\DeclareTextComposite{\'}{T1}{S}{145}
\DeclareTextComposite{\v}{T1}{S}{146}
\DeclareTextComposite{\c}{T1}{S}{147}
```

```
\DeclareTextComposite{\v}{T1}{T}{148}
\DeclareTextComposite{\c}{T1}{T}{149}
\DeclareTextComposite{\H}{T1}{U}{150}
\DeclareTextComposite{\r}{T1}{U}{151}
```

"98 = 152

```
\DeclareTextComposite{\"}{T1}{Y}{152}
\DeclareTextComposite{\'}{T1}{Z}{153}
\DeclareTextComposite{\v}{T1}{Z}{154}
\DeclareTextComposite{\.}{T1}{Z}{155}
\DeclareTextComposite{\.}{T1}{I}{157}
```

"A0 = 160

```
\DeclareTextComposite{\u}{T1}{a}{160}
\DeclareTextComposite{\k}{T1}{a}{161}
\DeclareTextComposite{\'}{T1}{c}{162}
\DeclareTextComposite{\v}{T1}{c}{163}
\DeclareTextComposite{\v}{T1}{d}{164}
\DeclareTextComposite{\v}{T1}{e}{165}
\DeclareTextComposite{\k}{T1}{e}{166}
\DeclareTextComposite{\u}{T1}{g}{167}
```

"A8 = 168

```
\DeclareTextComposite{\'}{T1}{l}{168}
\DeclareTextComposite{\v}{T1}{l}{169}
\DeclareTextComposite{\'}{T1}{n}{171}
\DeclareTextComposite{\v}{T1}{n}{172}
\DeclareTextComposite{\H}{T1}{o}{174}
\DeclareTextComposite{\'}{T1}{r}{175}
```

"B0 = 176

```
\DeclareTextComposite{\v}{T1}{r}{176}
\DeclareTextComposite{\'}{T1}{s}{177}
\DeclareTextComposite{\v}{T1}{s}{178}
\DeclareTextComposite{\c}{T1}{s}{179}
\DeclareTextComposite{\v}{T1}{t}{180}
\DeclareTextComposite{\c}{T1}{t}{181}
\DeclareTextComposite{\H}{T1}{u}{182}
\DeclareTextComposite{\r}{T1}{u}{183}
```

"B8 = 184

```
\DeclareTextComposite{\"}{T1}{y}{184}
\DeclareTextComposite{\'}{T1}{z}{185}
\DeclareTextComposite{\v}{T1}{z}{186}
\DeclareTextComposite{\.}{T1}{z}{187}
```

"C0 = 192

```
\DeclareTextComposite{\`}{T1}{A}{192}
\DeclareTextComposite{\'}{T1}{A}{193}
\DeclareTextComposite{\^}{T1}{A}{194}
\DeclareTextComposite{\~}{T1}{A}{195}
\DeclareTextComposite{\"}{T1}{A}{196}
\DeclareTextComposite{\r}{T1}{A}{197}
\DeclareTextComposite{\c}{T1}{C}{199}
```

"C8 = 200

```
\DeclareTextComposite{\`}{T1}{E}{200}
\DeclareTextComposite{\'}{T1}{E}{201}
\DeclareTextComposite{\^}{T1}{E}{202}
\DeclareTextComposite{\"}{T1}{E}{203}
\DeclareTextComposite{\`}{T1}{I}{204}
\DeclareTextComposite{\'}{T1}{I}{205}
\DeclareTextComposite{\^}{T1}{I}{206}
\DeclareTextComposite{\"}{T1}{I}{207}
```

"D0 = 208

```
\DeclareTextComposite{\~}{T1}{N}{209}
\DeclareTextComposite{\`}{T1}{O}{210}
\DeclareTextComposite{\'}{T1}{O}{211}
\DeclareTextComposite{\^}{T1}{O}{212}
\DeclareTextComposite{\~}{T1}{O}{213}
\DeclareTextComposite{\"}{T1}{O}{214}
```

"D8 = 216

```
\DeclareTextComposite{\`}{T1}{U}{217}
\DeclareTextComposite{\'}{T1}{U}{218}
\DeclareTextComposite{\^}{T1}{U}{219}
\DeclareTextComposite{\"}{T1}{U}{220}
\DeclareTextComposite{\'}{T1}{Y}{221}
```

"E0 = 224

```
\DeclareTextComposite{\`}{T1}{a}{224}
\DeclareTextComposite{\'}{T1}{a}{225}
\DeclareTextComposite{\^}{T1}{a}{226}
\DeclareTextComposite{\~}{T1}{a}{227}
\DeclareTextComposite{\"}{T1}{a}{228}
\DeclareTextComposite{\r}{T1}{a}{229}
\DeclareTextComposite{\c}{T1}{c}{231}
```

"E8 = 232

```
\DeclareTextComposite{\`}{T1}{e}{232}
\DeclareTextComposite{\'}{T1}{e}{233}
\DeclareTextComposite{\^}{T1}{e}{234}
\DeclareTextComposite{\"}{T1}{e}{235}
\DeclareTextComposite{\`}{T1}{i}{236}
\DeclareTextComposite{\`}{T1}{\i}{236}
\DeclareTextComposite{\'}{T1}{i}{237}
\DeclareTextComposite{\'}{T1}{\i}{237}
\DeclareTextComposite{\^}{T1}{i}{238}
\DeclareTextComposite{\^}{T1}{\i}{238}
\DeclareTextComposite{\"}{T1}{i}{239}
\DeclareTextComposite{\"}{T1}{\i}{239}
```

"F0 = 240

```
\DeclareTextComposite{\~}{T1}{n}{241}
\DeclareTextComposite{\`}{T1}{o}{242}
\DeclareTextComposite{\'}{T1}{o}{243}
\DeclareTextComposite{\^}{T1}{o}{244}
\DeclareTextComposite{\~}{T1}{o}{245}
\DeclareTextComposite{\"}{T1}{o}{246}
```

"F8 = 248

```
\DeclareTextComposite{\`}{T1}{u}{249}
\DeclareTextComposite{\'}{T1}{u}{250}
\DeclareTextComposite{\^}{T1}{u}{251}
\DeclareTextComposite{\"}{T1}{u}{252}
\DeclareTextComposite{\'}{T1}{y}{253}
```

```
\DeclareTextCompositeCommand{\k}{T1}{o}{\textogonekcentered{o}}
\DeclareTextCompositeCommand{\k}{T1}{O}{\textogonekcentered{O}}
```

```
\ifx\textcommaabove\@undefined\else
\DeclareTextCompositeCommand{\c}{T1}{g}{\textcommaabove{g}}
\fi
\ifx\textcommabelow\@undefined\else
\DeclareTextCompositeCommand{\c}{T1}{G}{\textcommabelow{G}}
\DeclareTextCompositeCommand{\c}{T1}{K}{\textcommabelow{K}}
\DeclareTextCompositeCommand{\c}{T1}{k}{\textcommabelow{k}}
\DeclareTextCompositeCommand{\c}{T1}{L}{\textcommabelow{L}}
\DeclareTextCompositeCommand{\c}{T1}{l}{\textcommabelow{l}}
\DeclareTextCompositeCommand{\c}{T1}{N}{\textcommabelow{N}}
\DeclareTextCompositeCommand{\c}{T1}{n}{\textcommabelow{n}}
\DeclareTextCompositeCommand{\c}{T1}{R}{\textcommabelow{R}}
\DeclareTextCompositeCommand{\c}{T1}{r}{\textcommabelow{r}}
\fi
```

⟨/T1⟩

1.7 Definitions for the OMS encoding

The definitions for the 'TEX math symbol' (OMS) encoding. Even though this is meant to be a math font, it includes some of the standard LATEX text symbols.

Declare the encoding.

⟨*OMS⟩

```
\DeclareFontEncoding{OMS}{}{}
```

Declare the symbols. Note that slot 13 has in places been named `\Orb`: please root out and destroy this impolity wherever you find it!

```
\DeclareTextSymbol{\textasteriskcentered}{OMS}{3}   % "03
\DeclareTextSymbol{\textbackslash}{OMS}{110}        % "6E
\DeclareTextSymbol{\textbar}{OMS}{106}              % "6A
\DeclareTextSymbol{\textbardbl}{OMS}{107}           % "6B
\DeclareTextSymbol{\textbraceleft}{OMS}{102}        % "66
\DeclareTextSymbol{\textbraceright}{OMS}{103}       % "67
\DeclareTextSymbol{\textbullet}{OMS}{15}            % "0F
\DeclareTextSymbol{\textdaggerdbl}{OMS}{122}        % "7A
\DeclareTextSymbol{\textdagger}{OMS}{121}           % "79
\DeclareTextSymbol{\textparagraph}{OMS}{123}        % "7B
\DeclareTextSymbol{\textperiodcentered}{OMS}{1}     % "01
\DeclareTextSymbol{\textsection}{OMS}{120}          % "78
\DeclareTextSymbol{\textbigcircle}{OMS}{13}         % "0D
\DeclareTextCommand{\textcircled}{OMS}[1]{\hmode@bgroup
   \ooalign{%
      \hfil \raise .07ex\hbox {\upshape#1}\hfil \crcr
      \char 13 % "0D
```

```
  }%
 \egroup}
⟨/OMS⟩
```

1.8 Definitions for the OML encoding

The definitions for the 'TEX math italic' (OML) encoding. Even though this is meant to be a math font, it includes some of the standard LATEX text symbols.

Declare the encoding.

```
⟨*OML⟩
\DeclareFontEncoding{OML}{}{}
```

Declare the symbols.

```
\DeclareTextSymbol{\textless}{OML}{`\<}
\DeclareTextSymbol{\textgreater}{OML}{`\>}
\DeclareTextAccent{\t}{OML}{127}  % "7F
⟨/OML⟩
```

1.9 Definitions for the OT4 encoding

These definitions are for the Polish extension to the 'TEX text' (OT1) encoding. This encoding was created by B. Jackowski and M. Ryćko for use with the Polish version of Computer Modern and Computer Concrete. In positions 0–127 it is identical to OT1 but it contains some additional characters in the upper half. The LATEX support was developed by Mariusz Olko.

The PL fonts that use it are available as follows:
Metafont sources `ftp://ftp.gust.org.pl/TeX/language/polish/pl-mf.zip`;
Font files `ftp://ftp.gust.org.pl/TeX/language/polish/pl-tfm.zip`.

Declare the encoding.

```
⟨*OT4⟩
\DeclareFontEncoding{OT4}{}{}
\DeclareFontSubstitution{OT4}{cmr}{m}{n}
```

Declare the accents.

```
\DeclareTextAccent{\"}{OT4}{127}
\DeclareTextAccent{\'}{OT4}{19}
\DeclareTextAccent{\.}{OT4}{95}
\DeclareTextAccent{\=}{OT4}{22}
\DeclareTextAccent{\^}{OT4}{94}
\DeclareTextAccent{\`}{OT4}{18}
\DeclareTextAccent{\~}{OT4}{126}
\DeclareTextAccent{\H}{OT4}{125}
\DeclareTextAccent{\u}{OT4}{21}
\DeclareTextAccent{\v}{OT4}{20}
\DeclareTextAccent{\r}{OT4}{23}
```

The ogonek accent is available only under a e A & E. But we have to provide some definition for `\k`. Some other accents have to be built by hand as in OT1:

```
\DeclareTextCommand{\k}{OT4}[1]{%
    \TextSymbolUnavailable{\k{#1}}#1}
```

In these definitions we no longer use the helper function `\sh@ft` from plain.tex since that now has two incompatible definitions.

```
\DeclareTextCommand{\b}{OT4}[1]
   {\hmode@bgroup\o@lign{\relax#1\crcr\hidewidth\ltx@sh@ft{-3ex}%
     \vbox to.2ex{\hbox{\char22}\vss}\hidewidth}\egroup}
\DeclareTextCommand{\c}{OT4}[1]
   {\leavevmode\setbox\z@\hbox{#1}\ifdim\ht\z@=1ex\accent24 #1%
    \else{\ooalign{\unhbox\z@\crcr\hidewidth\char24\hidewidth}}\fi}
\DeclareTextCommand{\d}{OT4}[1]
   {\hmode@bgroup
    \o@lign{\relax#1\crcr\hidewidth\ltx@sh@ft{-1ex}.\hidewidth}\egroup}
```

Declare the text symbols.

```
\DeclareTextSymbol{\AE}{OT4}{29}
\DeclareTextSymbol{\OE}{OT4}{30}
\DeclareTextSymbol{\O}{OT4}{31}
\DeclareTextSymbol{\L}{OT4}{138}
\DeclareTextSymbol{\ae}{OT4}{26}

\DeclareTextSymbol{\guillemetleft}{OT4}{174}
\DeclareTextSymbol{\guillemetright}{OT4}{175}
% old Adobe names
\DeclareTextSymbol{\guillemotleft}{OT4}{174}
\DeclareTextSymbol{\guillemotright}{OT4}{175}

\DeclareTextSymbol{\i}{OT4}{16}
\DeclareTextSymbol{\j}{OT4}{17}
\DeclareTextSymbol{\l}{OT4}{170}
\DeclareTextSymbol{\o}{OT4}{28}
\DeclareTextSymbol{\oe}{OT4}{27}
\DeclareTextSymbol{\quotedblbase}{OT4}{255}
\DeclareTextSymbol{\ss}{OT4}{25}
\DeclareTextSymbol{\textemdash}{OT4}{124}
\DeclareTextSymbol{\textendash}{OT4}{123}
\DeclareTextSymbol{\textexclamdown}{OT4}{60}
%\DeclareTextSymbol{\texthyphenchar}{OT4}{`\-}
%\DeclareTextSymbol{\texthyphen}{OT4}{`\-}
\DeclareTextSymbol{\textquestiondown}{OT4}{62}
\DeclareTextSymbol{\textquotedblleft}{OT4}{92}
\DeclareTextSymbol{\textquotedblright}{OT4}{`\"}
\DeclareTextSymbol{\textquoteleft}{OT4}{`\`}
\DeclareTextSymbol{\textquoteright}{OT4}{`\'}
```

Definition for Å as in OT1:

```
\DeclareTextCompositeCommand{\r}{OT4}{A}
   {\leavevmode\setbox\z@\hbox{!}\dimen@\ht\z@\advance\dimen@-1ex%
    \rlap{\raise.67\dimen@\hbox{\char23}}A}
```

In the OT4 encoding, £ and $ share a slot.

```
\DeclareTextCommand{\textdollar}{OT4}{\hmode@bgroup
   \ifdim \fontdimen\@ne\font >\z@
      \slshape
   \else
      \upshape
   \fi
   \char`\$\egroup}
```

```
\DeclareTextCommand{\textsterling}{OT4}{\hmode@bgroup
   \ifdim \fontdimen\@ne\font >\z@
      \itshape
   \else
      \fontshape{ui}\selectfont
   \fi
   \char`\$\egroup}
```

Declare the composites.

```
\DeclareTextComposite{\k}{OT4}{A}{129}
\DeclareTextComposite{\'}{OT4}{C}{130}
\DeclareTextComposite{\k}{OT4}{E}{134}
\DeclareTextComposite{\'}{OT4}{N}{139}
\DeclareTextComposite{\'}{OT4}{S}{145}
\DeclareTextComposite{\'}{OT4}{Z}{153}
\DeclareTextComposite{\.}{OT4}{Z}{155}
\DeclareTextComposite{\k}{OT4}{a}{161}
\DeclareTextComposite{\'}{OT4}{c}{162}
\DeclareTextComposite{\k}{OT4}{e}{166}
\DeclareTextComposite{\'}{OT4}{n}{171}
\DeclareTextComposite{\'}{OT4}{s}{177}
\DeclareTextComposite{\'}{OT4}{z}{185}
\DeclareTextComposite{\.}{OT4}{z}{187}
\DeclareTextComposite{\'}{OT4}{O}{211}
\DeclareTextComposite{\'}{OT4}{o}{243}
```

⟨/OT4⟩

1.10 Definitions for the TS1 encoding

⟨∗TS1⟩

```
\DeclareFontEncoding{TS1}{}{}
\DeclareFontSubstitution{TS1}{cmr}{m}{n}
```

Some accents have to be built by hand. Note that `\ooalign` and `\o@lign` must be inside a group.

```
\DeclareTextCommand{\capitalcedilla}{TS1}[1]
   {\hmode@bgroup
    \ooalign{\null#1\crcr\hidewidth\char11\hidewidth}\egroup}
\DeclareTextCommand{\capitalogonek}{TS1}[1]
   {\hmode@bgroup
    \ooalign{\null#1\crcr\hidewidth\char12\hidewidth}\egroup}
```

Accents for capital letters.

These commands can be used by the end user either directly or through definitions of the type
`\DeclareTextCompositeCommand{\'}{T1}{X}{\capitalacute X}`

None of the latter definitions are provided by default, since they are probably rarely used.

"00 = 0

```
\DeclareTextAccent{\capitalgrave}{TS1}{0}
\DeclareTextAccent{\capitalacute}{TS1}{1}
\DeclareTextAccent{\capitalcircumflex}{TS1}{2}
\DeclareTextAccent{\capitaltilde}{TS1}{3}
\DeclareTextAccent{\capitaldieresis}{TS1}{4}
\DeclareTextAccent{\capitalhungarumlaut}{TS1}{5}
```

```
\DeclareTextAccent{\capitalring}{TS1}{6}
\DeclareTextAccent{\capitalcaron}{TS1}{7}
```

"08 = 8

```
\DeclareTextAccent{\capitalbreve}{TS1}{8}
\DeclareTextAccent{\capitalmacron}{TS1}{9}
\DeclareTextAccent{\capitaldotaccent}{TS1}{10}
```

Tie accents.

The tie accent was borrowed from the `cmmi` font. The tc fonts now provide four tie accents, the first two are done in the classical way with asymmetric glyphs hanging out of their boxes; the new ties are centered in their boxes like all other accents. They need a name: please tell us if you know what to call them.

" =

```
\DeclareTextAccent{\t}{TS1}{26}
\DeclareTextAccent{\capitaltie}{TS1}{27}
\DeclareTextAccent{\newtie}{TS1}{28}
\DeclareTextAccent{\capitalnewtie}{TS1}{29}
```

Compound word marks.

The text companion fonts contain two compound word marks of different heights, one has `cap_height`, the other `asc_height`.

```
\DeclareTextSymbol{\textcapitalcompwordmark}{TS1}{23}
\DeclareTextSymbol{\textascendercompwordmark}{TS1}{31}
```

The text companion symbols.

```
\DeclareTextSymbol{\textquotestraightbase}{TS1}{13}
```

"10 = 16

```
\DeclareTextSymbol{\textquotestraightdblbase}{TS1}{18}
\DeclareTextSymbol{\texttwelveudash}{TS1}{21}
\DeclareTextSymbol{\textthreequartersemdash}{TS1}{22}
```

"18 = 24

```
\DeclareTextSymbol{\textleftarrow}{TS1}{24}
\DeclareTextSymbol{\textrightarrow}{TS1}{25}
```

"20 = 32

```
\DeclareTextSymbol{\textblank}{TS1}{32}
\DeclareTextSymbol{\textdollar}{TS1}{36}
\DeclareTextSymbol{\textquotesingle}{TS1}{39}
```

"28 = 40

The symbol `\textasteriskcentered` "$*$" is supposed to be always available in `TS1` and that is important as it is used in footnote symbols. However, in a few fonts it is missing even though they are otherwise fairly complete. We therefore use a rather elaborate method and check if the slot has a glyph and if not produce a poor man's version by using a normal "*" slightly enlarged and somewhat lowered. The main application for this symbol is in footnote symbols and there it should produce a comparable size and show a similar placement.

```
%\DeclareTextSymbol{\textasteriskcentered}{TS1}{42} % that's wanted
\DeclareTextCommand \textasteriskcentered{TS1}{%    % and that's needed
  \iffontchar\font 42 \char42 \else
   \begingroup\fontencoding{T1}%
       \fontsize
```

```
        {\the\dimexpr1.3\dimexpr\f@size pt\relax}%
        {\f@baselineskip}%
      \selectfont
      \raisebox{-0.7ex}[\dimexpr\height-0.7ex][0pt]{*}%
    \endgroup
    \fi
}
```

Note that '054 is a comma and '056 is a full stop: these make numbers using oldstyle digits easier to input.

```
\DeclareTextSymbol{\textdblhyphen}{TS1}{45}
\DeclareTextSymbol{\textfractionsolidus}{TS1}{47}
```

Oldstyle digits.

"30 = 48

```
\DeclareTextSymbol{\textzerooldstyle}{TS1}{48}
\DeclareTextSymbol{\textoneoldstyle}{TS1}{49}
\DeclareTextSymbol{\texttwooldstyle}{TS1}{50}
\DeclareTextSymbol{\textthreeoldstyle}{TS1}{51}
\DeclareTextSymbol{\textfouroldstyle}{TS1}{52}
\DeclareTextSymbol{\textfiveoldstyle}{TS1}{53}
\DeclareTextSymbol{\textsixoldstyle}{TS1}{54}
\DeclareTextSymbol{\textsevenoldstyle}{TS1}{55}
```

"38 = 56

```
\DeclareTextSymbol{\texteightoldstyle}{TS1}{56}
\DeclareTextSymbol{\textnineoldstyle}{TS1}{57}
```

More text companion symbols.

```
\DeclareTextSymbol{\textlangle}{TS1}{60}
\DeclareTextSymbol{\textminus}{TS1}{61}
\DeclareTextSymbol{\textrangle}{TS1}{62}
```

"48 = 72

```
\DeclareTextSymbol{\textmho}{TS1}{77}
```

The big circle is here to define the command `\textcircled`. Formerly it was taken from the `cmsy` font.

```
\DeclareTextSymbol{\textbigcircle}{TS1}{79}
\DeclareTextCommand{\textcircled}{TS1}[1]{\hmode@bgroup
   \ooalign{%
      \hfil \raise .07ex\hbox {\upshape#1}\hfil \crcr
      \char 79   % '117 = "4F
   }%
 \egroup}
```

More text companion symbols.

"50 = 80

```
\DeclareTextSymbol{\textohm}{TS1}{87}
```

"58 = 88

```
\DeclareTextSymbol{\textlbrackdbl}{TS1}{91}
\DeclareTextSymbol{\textrbrackdbl}{TS1}{93}
\DeclareTextSymbol{\textuparrow}{TS1}{94}
\DeclareTextSymbol{\textdownarrow}{TS1}{95}
```

"60 = 96

```
\DeclareTextSymbol{\textasciigrave}{TS1}{96}
\DeclareTextSymbol{\textborn}{TS1}{98}
\DeclareTextSymbol{\textdivorced}{TS1}{99}
\DeclareTextSymbol{\textdied}{TS1}{100}
```

"68 = 104

```
\DeclareTextSymbol{\textleaf}{TS1}{108}
\DeclareTextSymbol{\textmarried}{TS1}{109}
\DeclareTextSymbol{\textmusicalnote}{TS1}{110}
```

"78 = 120

```
\DeclareTextSymbol{\texttildelow}{TS1}{126}
```

This glyph, `\textdblhyphenchar` is hanging, like the hyphenchar of the ec fonts.

```
\DeclareTextSymbol{\textdblhyphenchar}{TS1}{127}
```

"80 = 128

```
\DeclareTextSymbol{\textasciibreve}{TS1}{128}
\DeclareTextSymbol{\textasciicaron}{TS1}{129}
```

This next glyph is *not* the same as `\textquotedbl`.

```
\DeclareTextSymbol{\textacutedbl}{TS1}{130}
\DeclareTextSymbol{\textgravedbl}{TS1}{131}
\DeclareTextSymbol{\textdagger}{TS1}{132}
\DeclareTextSymbol{\textdaggerdbl}{TS1}{133}
\DeclareTextSymbol{\textbardbl}{TS1}{134}
\DeclareTextSymbol{\textperthousand}{TS1}{135}
```

"88 = 136

```
\DeclareTextSymbol{\textbullet}{TS1}{136}
\DeclareTextSymbol{\textcelsius}{TS1}{137}
\DeclareTextSymbol{\textdollaroldstyle}{TS1}{138}
\DeclareTextSymbol{\textcentoldstyle}{TS1}{139}
\DeclareTextSymbol{\textflorin}{TS1}{140}
\DeclareTextSymbol{\textcolonmonetary}{TS1}{141}
\DeclareTextSymbol{\textwon}{TS1}{142}
\DeclareTextSymbol{\textnaira}{TS1}{143}
```

"90 = 144

```
\DeclareTextSymbol{\textguarani}{TS1}{144}
\DeclareTextSymbol{\textpeso}{TS1}{145}
\DeclareTextSymbol{\textlira}{TS1}{146}
\DeclareTextSymbol{\textrecipe}{TS1}{147}
\DeclareTextSymbol{\textinterrobang}{TS1}{148}
\DeclareTextSymbol{\textinterrobangdown}{TS1}{149}
\DeclareTextSymbol{\textdong}{TS1}{150}
\DeclareTextSymbol{\texttrademark}{TS1}{151}
```

"98 = 152

```
\DeclareTextSymbol{\textpertenthousand}{TS1}{152}
\DeclareTextSymbol{\textpilcrow}{TS1}{153}
\DeclareTextSymbol{\textbaht}{TS1}{154}
\DeclareTextSymbol{\textnumero}{TS1}{155}
```

This next name may change. For the following sign we know only a german name, which is abzüglich. The meaning is something like "commercial minus". An ASCII ersatz is ./. (dot slash dot). The temporary English name is `\textdiscount`.

```
\DeclareTextSymbol{\textdiscount}{TS1}{156}
\DeclareTextSymbol{\textestimated}{TS1}{157}
\DeclareTextSymbol{\textopenbullet}{TS1}{158}
\DeclareTextSymbol{\textservicemark}{TS1}{159}
```

"A0 = 160

```
\DeclareTextSymbol{\textlquill}{TS1}{160}
\DeclareTextSymbol{\textrquill}{TS1}{161}
\DeclareTextSymbol{\textcent}{TS1}{162}
\DeclareTextSymbol{\textsterling}{TS1}{163}
\DeclareTextSymbol{\textcurrency}{TS1}{164}
\DeclareTextSymbol{\textyen}{TS1}{165}
\DeclareTextSymbol{\textbrokenbar}{TS1}{166}
\DeclareTextSymbol{\textsection}{TS1}{167}
```

"A8 = 168

```
\DeclareTextSymbol{\textasciidieresis}{TS1}{168}
\DeclareTextSymbol{\textcopyright}{TS1}{169}
\DeclareTextSymbol{\textordfeminine}{TS1}{170}
\DeclareTextSymbol{\textcopyleft}{TS1}{171}
\DeclareTextSymbol{\textlnot}{TS1}{172}
```

The meaning of the circled-P is "sound recording copyright".

```
\DeclareTextSymbol{\textcircledP}{TS1}{173}
\DeclareTextSymbol{\textregistered}{TS1}{174}
\DeclareTextSymbol{\textasciimacron}{TS1}{175}
```

"B0 = 176

```
\DeclareTextSymbol{\textdegree}{TS1}{176}
\DeclareTextSymbol{\textpm}{TS1}{177}
\DeclareTextSymbol{\texttwosuperior}{TS1}{178}
\DeclareTextSymbol{\textthreesuperior}{TS1}{179}
\DeclareTextSymbol{\textasciiacute}{TS1}{180}
\DeclareTextSymbol{\textmu}{TS1}{181} % micro sign
\DeclareTextSymbol{\textparagraph}{TS1}{182}
\DeclareTextSymbol{\textperiodcentered}{TS1}{183}
```

"B8 = 184

```
\DeclareTextSymbol{\textreferencemark}{TS1}{184}
\DeclareTextSymbol{\textonesuperior}{TS1}{185}
\DeclareTextSymbol{\textordmasculine}{TS1}{186}
\DeclareTextSymbol{\textsurd}{TS1}{187}
\DeclareTextSymbol{\textonequarter}{TS1}{188}
\DeclareTextSymbol{\textonehalf}{TS1}{189}
\DeclareTextSymbol{\textthreequarters}{TS1}{190}
\DeclareTextSymbol{\texteuro}{TS1}{191}
```

"E0 = 208

```
\DeclareTextSymbol{\texttimes}{TS1}{214}
```

"F0 = 240

```
\DeclareTextSymbol{\textdiv}{TS1}{246}
```

⟨/TS1⟩

1.11 Definitions for the TU encoding

The TU encoding was originally introduced in the contributed package `fontspec` as a Unicode encoding for XeTeX and LuaTeX.

Normally for these engines, the input consists of Unicode characters encoded in UTF-8. There is therefore little need to use the traditional (ASCII) encoding-specific commands

However, sometimes (e.g. for backwards compatibility) it can be useful to access these Unicode characters via such ASCII-based markup. The commands provided here Cover the characters in the T1 and TS1 encodings, but specified in Unicode position. Almost all the command names have been mechanically extracted form the `inputenc` UTF-8 support, which is essentially doing a reverse mapping from UTF-8 data to LaTeX LICR commands.

A few additional names for character which were supported in the original `fontspec` version of this file have also been added, even though they are not currently in the default `inputenc` UTF-8 declarations.

```
⟨*TU⟩
```

In the base interface the Unicode encoding is always known as TU But we parameterize the encoding name to allow for modelling differences in Unicode support by different fonts.

```
\providecommand\UnicodeEncodingName{TU}
```

As the Unicode encoding, TU, is only currently available with XeTeX or LuaTeX, we detect these engines first, and make adjustments for the differing font loading syntax. For other engines, we issue a warning then abort this file, switching back to T1 encoding.

```
\begingroup\expandafter\expandafter\expandafter\endgroup
\expandafter\ifx\csname XeTeXrevision\endcsname\relax
 \begingroup\expandafter\expandafter\expandafter\endgroup
 \expandafter\ifx\csname directlua\endcsname\relax
```

Not LuaTeX or XeTeX, abort with a warning.

```
   \PackageWarningNoLine{fontenc}
     {\UnicodeEncodingName\space
      encoding is only available with XeTeX and LuaTeX.\MessageBreak
      Defaulting to T1 encoding}
     \def\encodingdefault{T1}
   \expandafter\expandafter\expandafter\endinput
 \else
```

LuaTeX. For LuaTeX 1.10+, define a Lua function to disable any handing by the font code. Otherwise we reload the font without TeX ligatures.

```
   \def\UnicodeFontTeXLigatures{+tlig;}
   \ifnum\luatexversion<110
     \def\reserved@a#1{%
       \def\@remove@tlig@##1{\@remove@tlig@##1\@nil#1\@nil\relax}
       \def\@remove@tlig@##1#1{\@remove@tlig@@##1}}
     \edef\reserved@b{\detokenize{+tlig;}}
     \expandafter\reserved@a\expandafter{\reserved@b}
     \def\@remove@tlig@@#1\@nil#2\relax{#1}
```

```
      \def\remove@tlig#1{%
        \begingroup
        \font\remove@tlig
        \expandafter\@remove@tlig\expandafter{\fontname\font}%
        \remove@tlig
        \char#1\relax
        \endgroup
      }
    \else
      \newprotectedluacmd\@remove@tlig@@@
```

Now we can define the function. Mostly we just have to insert a protected glyph node, which is a glyph node with subtype 256. But we have to keep track of the current mode to avoid inserting the glyph into a vlist.

```
      \now@and@everyjob{\directlua{
        local rawchar_func = token.create'@remove@tlig@@@'.index
        local forcehmode = tex.forcehmode
        local put_next = token.put_next
        local glyph_id = node.id'glyph'
        local rawchar_token = token.new(rawchar_func, token.command_id'lua_call')
        lua.get_functions_table()[rawchar_func] = function()
          local mode = tex.nest.top.mode
          if mode == 1 or mode == -1 then
            put_next(rawchar_token)
            return forcehmode(true)
          end
          local n = node.new(glyph_id, 256)
          n.font = font.current()
          n.char = token.scan_int()
          return node.write(n)
        end
      }}
```

Now `\remove@tlig` can be implemented almost as in XeTeX.

```
      \def\remove@tlig#1{\@remove@tlig@@@#1\relax}
    \fi
  \fi
\else
```

XeTeX

```
  \def\UnicodeFontTeXLigatures{mapping=tex-text;}
  \def\remove@tlig#1{\XeTeXglyph\numexpr\XeTeXcharglyph#1\relax}
\fi
\def\UnicodeFontFile#1#2{"[#1]:#2"}
\def\UnicodeFontName#1#2{"#1:#2"}
```

Declare the encoding

```
\DeclareFontEncoding\UnicodeEncodingName{}{}
```

Declare accent command to use a postpended combining character rather than the TeX `\accent` primitive

```
\def\add@unicode@accent#1#2{%
  \if\relax\detokenize{#2}\relax^^a0\else#2\fi
  \char#1\relax}
```

In its original implementation \DeclareUnicodeAccent was given 3 arguments (with second the "Unicode encoding" a.k.a., \UnicodeEncodingName) while in other places, e.g., \DeclareUnicodeComposite, we always made encoding implicit. So we now change it here to implicit too so that the interfaces become a bit more consistent. To avoid making that a breaking change (even though it only affects two packages on CTAN) we test for #2 being \UnicodeEncodingName. This would not catch if somebody used \DeclareUnicodeAccent{\=}{TU-sub}{"0304} but that fortunately hasn't happened. With the implicit argument you would need to change \UnicodeEncodingName instead, as you have to do anyway for the other interface commands.

```
\def\DeclareUnicodeAccent#1#2{%
  \edef\reserved@a{#2}%
  \edef\reserved@b{\UnicodeEncodingName}%
  \ifx\reserved@a\reserved@b
    \def\reserved@a{\DeclareUnicodeAccent@{#1}}%
  \else
    \def\reserved@a{\DeclareUnicodeAccent@{#1}\UnicodeEncodingName}%
  \fi
  \reserved@a{#2}%
}
\def\DeclareUnicodeAccent@#1#2#3{%
  \DeclareTextCommand{#1}{#2}{\add@unicode@accent{#3}}%
}
```

Wrapper around \DeclareTextCompositeCommand that uses the declared composite if it exists in the current font or falls back to the default definition for the TU accent if not.

```
{
\catcode\z@=11\relax
\gdef\DeclareUnicodeComposite#1#2#3{%
   \def\reserved@a##1##2{%
     \DeclareTextCompositeCommand#1\UnicodeEncodingName{#2}{%
   \iffontchar\font#3 ##2%
      \else ##1\fi}}%
    \expandafter\expandafter\expandafter\extract@default@composite
    \csname\UnicodeEncodingName\string#1\endcsname{#2}\@nil
   \bgroup
      \lccode\z@#3 %
      \lowercase{\egroup
      \expandafter\reserved@a\expandafter{\reserved@b}{^^@}}}%
}
```

```
\def\extract@default@composite#1{%
 \ifx\@text@composite#1%
   \expandafter\extract@default@composite@a
 \else
   \expandafter\extract@default@composite@b\expandafter#1%
 \fi}
```

```
\def\extract@default@composite@a#1\@text@composite#2\@nil{%
  \def\reserved@b{#2}}
\def\extract@default@composite@b#1#2\@nil{%
  \def\reserved@b{#1#2}}
```

Next two commands are simply syntactic sugar to go with the other \DeclareUnicode... declarations.

```
\def\DeclareUnicodeSymbol#1{\DeclareTextSymbol{#1}{\UnicodeEncodingName}}
\def\DeclareUnicodeCommand#1{\DeclareTextCommand{#1}{\UnicodeEncodingName}}

\DeclareUnicodeCommand\textquotesingle {\remove@tlig{"0027}}
\DeclareUnicodeCommand\textasciigrave  {\remove@tlig{"0060}}
\DeclareUnicodeCommand\textquotedbl    {\remove@tlig{"0022}}

\DeclareUnicodeSymbol{\textdollar}          {"0024}
\DeclareUnicodeSymbol{\textless}            {"003C}
\DeclareUnicodeSymbol{\textgreater}         {"003E}
\DeclareUnicodeSymbol{\textbackslash}       {"005C}
\DeclareUnicodeSymbol{\textasciicircum}     {"005E}
\DeclareUnicodeSymbol{\textunderscore}      {"005F}
\DeclareUnicodeSymbol{\textbraceleft}       {"007B}
\DeclareUnicodeSymbol{\textbar}             {"007C}
\DeclareUnicodeSymbol{\textbraceright}      {"007D}
\DeclareUnicodeSymbol{\textasciitilde}      {"007E}
\DeclareUnicodeSymbol{\textexclamdown}      {"00A1}
\DeclareUnicodeSymbol{\textcent}            {"00A2}
\DeclareUnicodeSymbol{\textsterling}        {"00A3}
\DeclareUnicodeSymbol{\textcurrency}        {"00A4}
\DeclareUnicodeSymbol{\textyen}             {"00A5}
\DeclareUnicodeSymbol{\textbrokenbar}       {"00A6}
\DeclareUnicodeSymbol{\textsection}         {"00A7}
\DeclareUnicodeSymbol{\textasciidieresis}   {"00A8}
\DeclareUnicodeSymbol{\textcopyright}       {"00A9}
\DeclareUnicodeSymbol{\textordfeminine}     {"00AA}

\DeclareUnicodeSymbol{\guillemetleft}       {"00AB}
% old Adobe name
\DeclareUnicodeSymbol{\guillemotleft}       {"00AB}

\DeclareUnicodeSymbol{\textlnot}            {"00AC}
\DeclareUnicodeSymbol{\textregistered}      {"00AE}
\DeclareUnicodeSymbol{\textasciimacron}     {"00AF}
\DeclareUnicodeSymbol{\textdegree}          {"00B0}
\DeclareUnicodeSymbol{\textpm}              {"00B1}
\DeclareUnicodeSymbol{\texttwosuperior}     {"00B2}
\DeclareUnicodeSymbol{\textthreesuperior}   {"00B3}
\DeclareUnicodeSymbol{\textasciiacute}      {"00B4}
\DeclareUnicodeSymbol{\textmu}              {"00B5}
\DeclareUnicodeSymbol{\textparagraph}       {"00B6}
\DeclareUnicodeSymbol{\textperiodcentered}  {"00B7}
\DeclareUnicodeSymbol{\textonesuperior}     {"00B9}
\DeclareUnicodeSymbol{\textordmasculine}    {"00BA}

\DeclareUnicodeSymbol{\guillemetright}      {"00BB}
% old Adobe name
\DeclareUnicodeSymbol{\guillemotright}      {"00BB}

\DeclareUnicodeSymbol{\textonequarter}      {"00BC}
\DeclareUnicodeSymbol{\textonehalf}         {"00BD}
\DeclareUnicodeSymbol{\textthreequarters}   {"00BE}
\DeclareUnicodeSymbol{\textquestiondown}    {"00BF}
\DeclareUnicodeSymbol{\AE}                  {"00C6}
\DeclareUnicodeSymbol{\DH}                  {"00D0}
\DeclareUnicodeSymbol{\texttimes}           {"00D7}
```

```
\DeclareUnicodeSymbol{\O}                    {"00D8}
\DeclareUnicodeSymbol{\TH}                   {"00DE}
\DeclareUnicodeSymbol{\ss}                   {"00DF}
\DeclareUnicodeSymbol{\ae}                   {"00E6}
\DeclareUnicodeSymbol{\dh}                   {"00F0}
\DeclareUnicodeSymbol{\textdiv}              {"00F7}
\DeclareUnicodeSymbol{\o}                    {"00F8}
\DeclareUnicodeSymbol{\th}                   {"00FE}
\DeclareUnicodeSymbol{\DJ}                   {"0110}
\DeclareUnicodeSymbol{\dj}                   {"0111}
\DeclareUnicodeSymbol{\i}                    {"0131}
\DeclareUnicodeSymbol{\IJ}                   {"0132}
\DeclareUnicodeSymbol{\ij}                   {"0133}
\DeclareUnicodeSymbol{\L}                    {"0141}
\DeclareUnicodeSymbol{\l}                    {"0142}
\DeclareUnicodeSymbol{\NG}                   {"014A}
\DeclareUnicodeSymbol{\ng}                   {"014B}
\DeclareUnicodeSymbol{\OE}                   {"0152}
\DeclareUnicodeSymbol{\oe}                   {"0153}
\DeclareUnicodeSymbol{\textflorin}           {"0192}
\DeclareUnicodeSymbol{\j}                    {"0237}
\DeclareUnicodeSymbol{\textasciicaron}       {"02C7}
\DeclareUnicodeSymbol{\textasciibreve}       {"02D8}
\DeclareUnicodeSymbol{\textacutedbl}         {"02DD}
\DeclareUnicodeSymbol{\textgravedbl}         {"02F5}
\DeclareUnicodeSymbol{\texttildelow}         {"02F7}
\DeclareUnicodeSymbol{\textbaht}             {"0E3F}
\DeclareUnicodeSymbol{\SS}                   {"1E9E}
\DeclareUnicodeSymbol{\textcompwordmark}     {"200C}
```

```
%\DeclareUnicodeSymbol{\textnonbreakinghyphen} {"2011}
%\DeclareUnicodeSymbol{\textfiguredash}        {"2012}
\DeclareUnicodeSymbol{\textendash}           {"2013}
\DeclareUnicodeSymbol{\textemdash}           {"2014}
%\DeclareUnicodeSymbol{\texthorizontalbar}   {"2015}
```

Unfortunately some fonts do not implement `"2011`, `"2012` and/or `"2015` (including the LaTeX default fonts for Unicode engines) so we provide some approximations if the glyph is missing, like we do for `OT1` and `T1`.

The `\nobreak\hskip\z@` is there to prevent a break after the hyphen but allow later breaks in the remainder of the word.

```
\DeclareUnicodeCommand{\textnonbreakinghyphen}
     {\iffontchar\font "2011 \char "2011 \else \mbox{-}\nobreak\hskip\z@ \fi}
\DeclareUnicodeCommand{\textfiguredash}
     {\iffontchar\font "2012 \char "2012 \else \char "2013 \fi}
\DeclareUnicodeCommand{\texthorizontalbar}
     {\iffontchar\font "2015 \char "2015 \else \char "2014 \fi}
```

```
\DeclareUnicodeSymbol{\textbardbl}           {"2016}
\DeclareUnicodeSymbol{\textquoteleft}        {"2018}
\DeclareUnicodeSymbol{\textquoteright}       {"2019}
\DeclareUnicodeSymbol{\quotesinglbase}       {"201A}
\DeclareUnicodeSymbol{\textquotedblleft}     {"201C}
\DeclareUnicodeSymbol{\textquotedblright}    {"201D}
\DeclareUnicodeSymbol{\quotedblbase}         {"201E}
```

```
\DeclareUnicodeSymbol{\textdagger}          {"2020}
\DeclareUnicodeSymbol{\textdaggerdbl}       {"2021}
\DeclareUnicodeSymbol{\textbullet}          {"2022}
\DeclareUnicodeSymbol{\textellipsis}        {"2026}
\DeclareUnicodeSymbol{\textperthousand}     {"2030}
\DeclareUnicodeSymbol{\textpertenthousand}  {"2031}
\DeclareUnicodeSymbol{\guilsinglleft}       {"2039}
\DeclareUnicodeSymbol{\guilsinglright}      {"203A}
\DeclareUnicodeSymbol{\textreferencemark}   {"203B}
\DeclareUnicodeSymbol{\textinterrobang}     {"203D}
\DeclareUnicodeSymbol{\textfractionsolidus} {"2044}
\DeclareUnicodeSymbol{\textlquill}          {"2045}
\DeclareUnicodeSymbol{\textrquill}          {"2046}
\DeclareUnicodeSymbol{\textdiscount}        {"2052}
\DeclareUnicodeSymbol{\textcolonmonetary}   {"20A1}
\DeclareUnicodeSymbol{\textlira}            {"20A4}
\DeclareUnicodeSymbol{\textnaira}           {"20A6}
\DeclareUnicodeSymbol{\textwon}             {"20A9}
\DeclareUnicodeSymbol{\textdong}            {"20AB}
\DeclareUnicodeSymbol{\texteuro}            {"20AC}
\DeclareUnicodeSymbol{\textpeso}            {"20B1}
\DeclareUnicodeSymbol{\textcelsius}         {"2103}
\DeclareUnicodeSymbol{\textnumero}          {"2116}
\DeclareUnicodeSymbol{\textcircledP}        {"2117}
\DeclareUnicodeSymbol{\textrecipe}          {"211E}
\DeclareUnicodeSymbol{\textservicemark}     {"2120}
\DeclareUnicodeSymbol{\texttrademark}       {"2122}
\DeclareUnicodeSymbol{\textohm}             {"2126}
\DeclareUnicodeSymbol{\textmho}             {"2127}
\DeclareUnicodeSymbol{\textestimated}       {"212E}
\DeclareUnicodeSymbol{\textleftarrow}       {"2190}
\DeclareUnicodeSymbol{\textuparrow}         {"2191}
\DeclareUnicodeSymbol{\textrightarrow}      {"2192}
\DeclareUnicodeSymbol{\textdownarrow}       {"2193}
\DeclareUnicodeSymbol{\textminus}           {"2212}

\DeclareUnicodeSymbol{\Hwithstroke}         {"0126}
\DeclareUnicodeSymbol{\hwithstroke}         {"0127}
```

Not all fonts have U+2217 but using U+002A requires some adjustment.

```
\DeclareUnicodeCommand{\textasteriskcentered}{%
  \iffontchar\font"2217 \char"2217 \else
    \begingroup
      \fontsize
       {\the\dimexpr1.3\dimexpr\f@size pt\relax}%
       {\f@baselineskip}%
      \selectfont
      \raisebox{-0.7ex}[\dimexpr\height-0.7ex][0pt]{*}%
    \endgroup
  \fi
}
```

```
\DeclareUnicodeSymbol{\textsurd}            {"221A}
\DeclareUnicodeSymbol{\textlangle}          {"2329}
```

```
\DeclareUnicodeSymbol{\textrangle}          {"232A}
\DeclareUnicodeSymbol{\textblank}           {"2422}
\DeclareUnicodeSymbol{\textvisiblespace}    {"2423}
\DeclareUnicodeSymbol{\textopenbullet}      {"25E6}
\DeclareUnicodeSymbol{\textbigcircle}       {"25EF}
\DeclareUnicodeSymbol{\textmusicalnote}     {"266A}
\DeclareUnicodeSymbol{\textmarried}         {"26AD}
\DeclareUnicodeSymbol{\textdivorced}        {"26AE}
\DeclareUnicodeSymbol{\textinterrobangdown} {"2E18}
```

Accents must be declared before the composites that use them.

```
\DeclareUnicodeAccent{\`}{"0300}
\DeclareUnicodeAccent{\'}{"0301}
\DeclareUnicodeAccent{\^}{"0302}
\DeclareUnicodeAccent{\~}{"0303}
\DeclareUnicodeAccent{\=}{"0304}
\DeclareUnicodeAccent{\u}{"0306}
\DeclareUnicodeAccent{\.}{"0307}
\DeclareUnicodeAccent{\"}{"0308}
\DeclareUnicodeAccent{\r}{"030A}
\DeclareUnicodeAccent{\H}{"030B}
\DeclareUnicodeAccent{\v}{"030C}
\DeclareUnicodeAccent{\b}{"0332}
\DeclareUnicodeAccent{\d}{"0323}
\DeclareUnicodeAccent{\c}{"0327}
\DeclareUnicodeAccent{\k}{"0328}
```

The odd one out:

```
\DeclareUnicodeCommand\textcommabelow[1]
  {\hmode@bgroup\ooalign{\null#1\crcr\hidewidth\raise-.31ex
   \hbox{\check@mathfonts\fontsize\ssf@size\z@
   \math@fontsfalse\selectfont,}\hidewidth}\egroup}
```

```
\DeclareUnicodeComposite{\^}              {}{"005E}
\DeclareUnicodeComposite{\~}              {}{"007E}
```

```
\DeclareUnicodeComposite{\`}             {A}{"00C0}
\DeclareUnicodeComposite{\'}             {A}{"00C1}
\DeclareUnicodeComposite{\^}             {A}{"00C2}
\DeclareUnicodeComposite{\~}             {A}{"00C3}
\DeclareUnicodeComposite{\"}             {A}{"00C4}
\DeclareUnicodeComposite{\r}             {A}{"00C5}
\DeclareUnicodeComposite{\c}             {C}{"00C7}
\DeclareUnicodeComposite{\`}             {E}{"00C8}
\DeclareUnicodeComposite{\'}             {E}{"00C9}
\DeclareUnicodeComposite{\^}             {E}{"00CA}
\DeclareUnicodeComposite{\"}             {E}{"00CB}
\DeclareUnicodeComposite{\`}             {I}{"00CC}
\DeclareUnicodeComposite{\'}             {I}{"00CD}
\DeclareUnicodeComposite{\^}             {I}{"00CE}
\DeclareUnicodeComposite{\"}             {I}{"00CF}
\DeclareUnicodeComposite{\~}             {N}{"00D1}
\DeclareUnicodeComposite{\`}             {O}{"00D2}
\DeclareUnicodeComposite{\'}             {O}{"00D3}
\DeclareUnicodeComposite{\^}             {O}{"00D4}
\DeclareUnicodeComposite{\~}             {O}{"00D5}
```

```
\DeclareUnicodeComposite{\"}            {O}{"00D6}
\DeclareUnicodeComposite{\`}            {U}{"00D9}
\DeclareUnicodeComposite{\'}            {U}{"00DA}
\DeclareUnicodeComposite{\^}            {U}{"00DB}
\DeclareUnicodeComposite{\"}            {U}{"00DC}
\DeclareUnicodeComposite{\'}            {Y}{"00DD}
\DeclareUnicodeComposite{\`}            {a}{"00E0}
\DeclareUnicodeComposite{\'}            {a}{"00E1}
\DeclareUnicodeComposite{\^}            {a}{"00E2}
\DeclareUnicodeComposite{\~}            {a}{"00E3}
\DeclareUnicodeComposite{\"}            {a}{"00E4}
\DeclareUnicodeComposite{\r}            {a}{"00E5}
\DeclareUnicodeComposite{\c}            {c}{"00E7}
\DeclareUnicodeComposite{\`}            {e}{"00E8}
\DeclareUnicodeComposite{\'}            {e}{"00E9}
\DeclareUnicodeComposite{\^}            {e}{"00EA}
\DeclareUnicodeComposite{\"}            {e}{"00EB}
\DeclareUnicodeComposite{\`}            \i {"00EC}
\DeclareUnicodeComposite{\`}            {i}{"00EC}
\DeclareUnicodeComposite{\'}            \i {"00ED}
\DeclareUnicodeComposite{\'}            {i}{"00ED}
\DeclareUnicodeComposite{\^}            \i {"00EE}
\DeclareUnicodeComposite{\^}            {i}{"00EE}
\DeclareUnicodeComposite{\"}            \i {"00EF}
\DeclareUnicodeComposite{\"}            {i}{"00EF}
\DeclareUnicodeComposite{\~}            {n}{"00F1}
\DeclareUnicodeComposite{\`}            {o}{"00F2}
\DeclareUnicodeComposite{\'}            {o}{"00F3}
\DeclareUnicodeComposite{\^}            {o}{"00F4}
\DeclareUnicodeComposite{\~}            {o}{"00F5}
\DeclareUnicodeComposite{\"}            {o}{"00F6}
\DeclareUnicodeComposite{\`}            {u}{"00F9}
\DeclareUnicodeComposite{\'}            {u}{"00FA}
\DeclareUnicodeComposite{\^}            {u}{"00FB}
\DeclareUnicodeComposite{\"}            {u}{"00FC}
\DeclareUnicodeComposite{\'}            {y}{"00FD}
\DeclareUnicodeComposite{\"}            {y}{"00FF}
\DeclareUnicodeComposite{\=}            {A}{"0100}
\DeclareUnicodeComposite{\=}            {a}{"0101}
\DeclareUnicodeComposite{\u}            {A}{"0102}
\DeclareUnicodeComposite{\u}            {a}{"0103}
\DeclareUnicodeComposite{\k}            {A}{"0104}
\DeclareUnicodeComposite{\k}            {a}{"0105}
\DeclareUnicodeComposite{\'}            {C}{"0106}
\DeclareUnicodeComposite{\'}            {c}{"0107}
\DeclareUnicodeComposite{\^}            {C}{"0108}
\DeclareUnicodeComposite{\^}            {c}{"0109}
\DeclareUnicodeComposite{\.}            {C}{"010A}
\DeclareUnicodeComposite{\.}            {c}{"010B}
\DeclareUnicodeComposite{\v}            {C}{"010C}
\DeclareUnicodeComposite{\v}            {c}{"010D}
\DeclareUnicodeComposite{\v}            {D}{"010E}
\DeclareUnicodeComposite{\v}            {d}{"010F}
\DeclareUnicodeComposite{\=}            {E}{"0112}
```

```
\DeclareUnicodeComposite{\=}            {e}{"0113}
\DeclareUnicodeComposite{\u}            {E}{"0114}
\DeclareUnicodeComposite{\u}            {e}{"0115}
\DeclareUnicodeComposite{\.}            {E}{"0116}
\DeclareUnicodeComposite{\.}            {e}{"0117}
\DeclareUnicodeComposite{\k}            {E}{"0118}
\DeclareUnicodeComposite{\k}            {e}{"0119}
\DeclareUnicodeComposite{\v}            {E}{"011A}
\DeclareUnicodeComposite{\v}            {e}{"011B}
\DeclareUnicodeComposite{\^}            {G}{"011C}
\DeclareUnicodeComposite{\^}            {g}{"011D}
\DeclareUnicodeComposite{\u}            {G}{"011E}
\DeclareUnicodeComposite{\u}            {g}{"011F}
\DeclareUnicodeComposite{\.}            {G}{"0120}
\DeclareUnicodeComposite{\.}            {g}{"0121}
\DeclareUnicodeComposite{\c}            {G}{"0122}
\DeclareUnicodeComposite{\c}            {g}{"0123}
\DeclareUnicodeComposite{\^}            {H}{"0124}
\DeclareUnicodeComposite{\^}            {h}{"0125}
\DeclareUnicodeComposite{\~}            {I}{"0128}
\DeclareUnicodeComposite{\~}            \i {"0129}
\DeclareUnicodeComposite{\~}            {i}{"0129}
\DeclareUnicodeComposite{\=}            {I}{"012A}
\DeclareUnicodeComposite{\=}            \i {"012B}
\DeclareUnicodeComposite{\=}            {i}{"012B}
\DeclareUnicodeComposite{\u}            {I}{"012C}
\DeclareUnicodeComposite{\u}            \i {"012D}
\DeclareUnicodeComposite{\u}            {i}{"012D}
\DeclareUnicodeComposite{\k}            {I}{"012E}
\DeclareUnicodeComposite{\k}            \i {"012F}
\DeclareUnicodeComposite{\k}            {i}{"012F}
\DeclareUnicodeComposite{\.}            {I}{"0130}
\DeclareUnicodeComposite{\^}            {J}{"0134}
\DeclareUnicodeComposite{\^}            \j {"0135}
\DeclareUnicodeComposite{\^}            {j}{"0135}
\DeclareUnicodeComposite{\c}            {K}{"0136}
\DeclareUnicodeComposite{\c}            {k}{"0137}
\DeclareUnicodeComposite{\'}            {L}{"0139}
\DeclareUnicodeComposite{\'}            {l}{"013A}
\DeclareUnicodeComposite{\c}            {L}{"013B}
\DeclareUnicodeComposite{\c}            {l}{"013C}
\DeclareUnicodeComposite{\v}            {L}{"013D}
\DeclareUnicodeComposite{\v}            {l}{"013E}
\DeclareUnicodeComposite{\'}            {N}{"0143}
\DeclareUnicodeComposite{\'}            {n}{"0144}
\DeclareUnicodeComposite{\c}            {N}{"0145}
\DeclareUnicodeComposite{\c}            {n}{"0146}
\DeclareUnicodeComposite{\v}            {N}{"0147}
\DeclareUnicodeComposite{\v}            {n}{"0148}
\DeclareUnicodeComposite{\=}            {O}{"014C}
\DeclareUnicodeComposite{\=}            {o}{"014D}
\DeclareUnicodeComposite{\u}            {O}{"014E}
\DeclareUnicodeComposite{\u}            {o}{"014F}
\DeclareUnicodeComposite{\H}            {O}{"0150}
```

```
\DeclareUnicodeComposite{\H}            {o}{"0151}
\DeclareUnicodeComposite{\'}            {R}{"0154}
\DeclareUnicodeComposite{\'}            {r}{"0155}
\DeclareUnicodeComposite{\c}            {R}{"0156}
\DeclareUnicodeComposite{\c}            {r}{"0157}
\DeclareUnicodeComposite{\v}            {R}{"0158}
\DeclareUnicodeComposite{\v}            {r}{"0159}
\DeclareUnicodeComposite{\'}            {S}{"015A}
\DeclareUnicodeComposite{\'}            {s}{"015B}
\DeclareUnicodeComposite{\^}            {S}{"015C}
\DeclareUnicodeComposite{\^}            {s}{"015D}
\DeclareUnicodeComposite{\c}            {S}{"015E}
\DeclareUnicodeComposite{\c}            {s}{"015F}
\DeclareUnicodeComposite{\v}            {S}{"0160}
\DeclareUnicodeComposite{\v}            {s}{"0161}
\DeclareUnicodeComposite{\c}            {T}{"0162}
\DeclareUnicodeComposite{\c}            {t}{"0163}
\DeclareUnicodeComposite{\v}            {T}{"0164}
\DeclareUnicodeComposite{\v}            {t}{"0165}
\DeclareUnicodeComposite{\~}            {U}{"0168}
\DeclareUnicodeComposite{\~}            {u}{"0169}
\DeclareUnicodeComposite{\=}            {U}{"016A}
\DeclareUnicodeComposite{\=}            {u}{"016B}
\DeclareUnicodeComposite{\u}            {U}{"016C}
\DeclareUnicodeComposite{\u}            {u}{"016D}
\DeclareUnicodeComposite{\r}            {U}{"016E}
\DeclareUnicodeComposite{\r}            {u}{"016F}
\DeclareUnicodeComposite{\H}            {U}{"0170}
\DeclareUnicodeComposite{\H}            {u}{"0171}
\DeclareUnicodeComposite{\k}            {U}{"0172}
\DeclareUnicodeComposite{\k}            {u}{"0173}
\DeclareUnicodeComposite{\^}            {W}{"0174}
\DeclareUnicodeComposite{\^}            {w}{"0175}
\DeclareUnicodeComposite{\^}            {Y}{"0176}
\DeclareUnicodeComposite{\^}            {y}{"0177}
\DeclareUnicodeComposite{\"}            {Y}{"0178}
\DeclareUnicodeComposite{\'}            {Z}{"0179}
\DeclareUnicodeComposite{\'}            {z}{"017A}
\DeclareUnicodeComposite{\.}            {Z}{"017B}
\DeclareUnicodeComposite{\.}            {z}{"017C}
\DeclareUnicodeComposite{\v}            {Z}{"017D}
\DeclareUnicodeComposite{\v}            {z}{"017E}
\DeclareUnicodeComposite{\v}            {A}{"01CD}
\DeclareUnicodeComposite{\v}            {a}{"01CE}
\DeclareUnicodeComposite{\v}            {I}{"01CF}
\DeclareUnicodeComposite{\v}            \i {"01D0}
\DeclareUnicodeComposite{\v}            {i}{"01D0}
\DeclareUnicodeComposite{\v}            {O}{"01D1}
\DeclareUnicodeComposite{\v}            {o}{"01D2}
\DeclareUnicodeComposite{\v}            {U}{"01D3}
\DeclareUnicodeComposite{\v}            {u}{"01D4}

\DeclareUnicodeComposite{\'}            \AE{"01FC}
\DeclareUnicodeComposite{\'}            {Æ}{"01FC}
```

```
\DeclareUnicodeComposite{\'}            \ae{"01FD}
\DeclareUnicodeComposite{\'}            {æ}{"01FD}
\DeclareUnicodeComposite{\=}            \AE{"01E2}
\DeclareUnicodeComposite{\=}            {Æ}{"01E2}
\DeclareUnicodeComposite{\=}            \ae{"01E3}
\DeclareUnicodeComposite{\=}            {æ}{"01E3}
\DeclareUnicodeComposite{\v}            {G}{"01E6}
\DeclareUnicodeComposite{\v}            {g}{"01E7}
\DeclareUnicodeComposite{\v}            {K}{"01E8}
\DeclareUnicodeComposite{\v}            {k}{"01E9}
\DeclareUnicodeComposite{\k}            {O}{"01EA}
\DeclareUnicodeComposite{\k}            {o}{"01EB}
\DeclareUnicodeComposite{\v}            \j {"01F0}
\DeclareUnicodeComposite{\v}            {j}{"01F0}
\DeclareUnicodeComposite{\'}            {G}{"01F4}
\DeclareUnicodeComposite{\'}            {g}{"01F5}
\DeclareUnicodeComposite{\textcommabelow}{S}{"0218}
\DeclareUnicodeComposite{\textcommabelow}{s}{"0219}
\DeclareUnicodeComposite{\textcommabelow}{T}{"021A}
\DeclareUnicodeComposite{\textcommabelow}{t}{"021B}
\DeclareUnicodeComposite{\=}            {Y}{"0232}
\DeclareUnicodeComposite{\=}            {y}{"0233}
\DeclareUnicodeComposite{\.}            {B}{"1E02}
\DeclareUnicodeComposite{\.}            {b}{"1E03}
\DeclareUnicodeComposite{\d}            {B}{"1E04}
\DeclareUnicodeComposite{\d}            {b}{"1E05}
\DeclareUnicodeComposite{\d}            {D}{"1E0C}
\DeclareUnicodeComposite{\d}            {d}{"1E0D}
\DeclareUnicodeComposite{\=}            {G}{"1E20}
\DeclareUnicodeComposite{\=}            {g}{"1E21}
\DeclareUnicodeComposite{\d}            {H}{"1E24}
\DeclareUnicodeComposite{\d}            {h}{"1E25}
\DeclareUnicodeComposite{\d}            {K}{"1E32}
\DeclareUnicodeComposite{\d}            {k}{"1E33}
\DeclareUnicodeComposite{\d}            {L}{"1E36}
\DeclareUnicodeComposite{\d}            {l}{"1E37}
\DeclareUnicodeComposite{\d}            {M}{"1E42}
\DeclareUnicodeComposite{\d}            {m}{"1E43}
\DeclareUnicodeComposite{\d}            {N}{"1E46}
\DeclareUnicodeComposite{\d}            {n}{"1E47}
\DeclareUnicodeComposite{\d}            {R}{"1E5A}
\DeclareUnicodeComposite{\d}            {r}{"1E5B}
\DeclareUnicodeComposite{\d}            {S}{"1E62}
\DeclareUnicodeComposite{\d}            {s}{"1E63}
\DeclareUnicodeComposite{\d}            {T}{"1E6C}
\DeclareUnicodeComposite{\d}            {t}{"1E6D}
\DeclareUnicodeComposite{\d}            {V}{"1E7E}
\DeclareUnicodeComposite{\d}            {v}{"1E7F}
\DeclareUnicodeComposite{\d}            {W}{"1E88}
\DeclareUnicodeComposite{\d}            {w}{"1E89}
\DeclareUnicodeComposite{\d}            {Z}{"1E92}
\DeclareUnicodeComposite{\d}            {z}{"1E93}
\DeclareUnicodeComposite{\d}            {A}{"1EA0}
\DeclareUnicodeComposite{\d}            {a}{"1EA1}
```

```
\DeclareUnicodeComposite{\d}            {E}{"1EB8}
\DeclareUnicodeComposite{\d}            {e}{"1EB9}
\DeclareUnicodeComposite{\d}            {I}{"1ECA}
\DeclareUnicodeComposite{\d}            {i}{"1ECB}
\DeclareUnicodeComposite{\d}            {O}{"1ECC}
\DeclareUnicodeComposite{\d}            {o}{"1ECD}
\DeclareUnicodeComposite{\d}            {U}{"1EE4}
\DeclareUnicodeComposite{\d}            {u}{"1EE5}
\DeclareUnicodeComposite{\d}            {Y}{"1EF4}
\DeclareUnicodeComposite{\d}            {y}{"1EF5}
```

⟨/TU⟩

2 Package files

This file now also contains some packages that provide access to the more specialised encodings.

2.1 The fontenc package

This package allows authors to specify which encodings they will use. For each encoding `FOO`, the package looks to see if the encoding `FOO` has already been declared. If it has not, the file `fooenc.def` is loaded. The default encoding is set to be `FOO`.

In addition the package at the moment contains extra code to extend the `\@uclclist` (list of upper/lower case pairs) for encodings that involve cyrillic characters. THIS IS A TEMPORARY SOLUTION and will not stay this way forever (or so we hope) but right now we are missing a proper interface for this and didn't wanted to rush it.

⟨∗package⟩

Here we define a macro that extends the `\@uclclist` if needed and afterwards turns itself in a noop.

```
\def\update@uclc@with@cyrillic{%
 \expandafter\def\expandafter\@uclclist\expandafter
  {\@uclclist
  \cyra\CYRA\cyrabhch\CYRABHCH\cyrabhchdsc\CYRABHCHDSC\cyrabhdze
  \CYRABHDZE\cyrabhha\CYRABHHA\cyrae\CYRAE\cyrb\CYRB\cyrbyus
  \CYRBYUS\cyrc\CYRC\cyrch\CYRCH\cyrchldsc\CYRCHLDSC\cyrchrdsc
  \CYRCHRDSC\cyrchvcrs\CYRCHVCRS\cyrd\CYRD\cyrdelta\CYRDELTA
  \cyrdje\CYRDJE\cyrdze\CYRDZE\cyrdzhe\CYRDZHE\cyre\CYRE\cyreps
  \CYREPS\cyrerev\CYREREV\cyrery\CYRERY\cyrf\CYRF\cyrfita
  \CYRFITA\cyrg\CYRG\cyrgdsc\CYRGDSC\cyrgdschcrs\CYRGDSCHCRS
  \cyrghcrs\CYRGHCRS\cyrghk\CYRGHK\cyrgup\CYRGUP\cyrh\CYRH
  \cyrhdsc\CYRHDSC\cyrhhcrs\CYRHHCRS\cyrhhk\CYRHHK\cyrhrdsn
  \CYRHRDSN\cyri\CYRI\cyrie\CYRIE\cyrii\CYRII\cyrishrt\CYRISHRT
  \cyrishrtdsc\CYRISHRTDSC\cyrizh\CYRIZH\cyrje\CYRJE\cyrk\CYRK
  \cyrkbeak\CYRKBEAK\cyrkdsc\CYRKDSC\cyrkhcrs\CYRKHCRS\cyrkhk
  \CYRKHK\cyrkvcrs\CYRKVCRS\cyrl\CYRL\cyrldsc\CYRLDSC\cyrlhk
  \CYRLHK\cyrlje\CYRLJE\cyrm\CYRM\cyrmdsc\CYRMDSC\cyrmhk\CYRMHK
  \cyrn\CYRN\cyrndsc\CYRNDSC\cyrng\CYRNG\cyrnhk\CYRNHK\cyrnje
  \CYRNJE\cyrnlhk\CYRNLHK\cyro\CYRO\cyrotld\CYROTLD\cyrp\CYRP
  \cyrphk\CYRPHK\cyrq\CYRQ\cyrr\CYRR\cyrrdsc\CYRRDSC\cyrrhk
  \CYRRHK\cyrrtick\CYRRTICK\cyrs\CYRS\cyrsacrs\CYRSACRS
  \cyrschwa\CYRSCHWA\cyrsdsc\CYRSDSC\cyrsemisftsn\CYRSEMISFTSN
```

```
  \cyrsftsn\CYRSFTSN\cyrsh\CYRSH\cyrshch\CYRSHCH\cyrshha\CYRSHHA
  \cyrt\CYRT\cyrtdsc\CYRTDSC\cyrtetse\CYRTETSE\cyrtshe\CYRTSHE
  \cyru\CYRU\cyrushrt\CYRUSHRT\cyrv\CYRV\cyrw\CYRW\cyry\CYRY
  \cyrya\CYRYA\cyryat\CYRYAT\cyryhcrs\CYRYHCRS\cyryi\CYRYI\cyryo
  \CYRYO\cyryu\CYRYU\cyrz\CYRZ\cyrzdsc\CYRZDSC\cyrzh\CYRZH
  \cyrzhdsc\CYRZHDSC}%
 \let\update@uclc@with@cyrillic\relax
}
```

Here we process each option:

```
\DeclareOption*{%
  \let\encodingdefault\CurrentOption
```

From 2020/02/02 release onward we only load the encoding files if they haven't be loaded already. To check this we look if `\T@`*encoding* is already defined. If not we load (indicated by setting the switch `@tempswa` to true and we always load if we run in an older format (or rather in a rollback situation).

```
  \@tempswafalse
  \@ifl@t@r\fmtversion{2020/02/02}%
      {\expandafter\ifx\csname T@\CurrentOption\endcsname\relax
        \@tempswatrue\fi}%
      {\@tempswatrue}%
```

Load if necessary:

```
  \if@tempswa
    \edef\reserved@f{%
      \lowercase{\def\noexpand\reserved@f{\CurrentOption enc.def}}}%
    \reserved@f
    \InputIfFileExists\reserved@f
         {}{\PackageError{fontenc}%
          {Encoding file `\reserved@f' not found.%
           \MessageBreak
            You might have misspelt the name of the encoding}%
          {Necessary code for this encoding was not
           loaded.\MessageBreak
           Thus calling the encoding later on will
           produce further error messages.}}%
   \let\reserved@f\relax
```

In case the current encoding is one of a list of known cyrillic ones we extend the `\@uclclist`:

```
   \expandafter\in@\expandafter{\CurrentOption}%
                               {T2A,T2B,T2C,X2,LCY,OT2}%
   \ifin@
```

But only if it hasn't already been extended. This might happen if there are several calls to fontenc loading one of the above encodings. If we don't do this check the `\@uclclist` gets unnecessarily big, slowing down the processing at runtime.

```
      \expandafter\in@\expandafter\cyra\expandafter
                               {\@uclclist}%
      \ifin@
      \else
        \update@uclc@with@cyrillic
      \fi
   \fi
```

```
  \fi
}
\ProcessOptions*
```

We select the new font encoding default (i.e., the last encoding specified in the option list. But this encoding may not work with the current `\f@shape`, e.g., `LY1` is not defined for `cmr` and therefore packages switching to `LY1` usually also change `\rmdefault`. But that only applies at `\begin{document}` so we get a spurious warning if we use what LaTeX previously used:

```
%\fontencoding\encodingdefault\selectfont
```

So instead we do this here:

```
\usefont\encodingdefault\familydefault\seriesdefault\shapedefault
```

To save some space we get rid of the macro extending the `\@uclclist` (might have happened already).

```
\let\update@uclc@with@cyrillic\relax
```

Finally we pretend that the fontenc package wasn't read in. This allows for using it several times, e.g., in a class file and in the preamble (at the cost of not getting any version info). That kind of hackery shows that using a general purpose package just for loading an encoding is not the right kind of interface for setting up encodings — it will get replaced at some point in the future.

```
\let\@elt\relax
\xdef\@fontenc@load@list{\@fontenc@load@list
  \@elt{\csname opt@fontenc.sty\endcsname}}

\global\expandafter\let\csname ver@@fontenc.sty\expandafter\endcsname
                        \csname ver@fontenc.sty\endcsname
\global\expandafter\let\csname ver@fontenc.sty\endcsname\relax
\global\expandafter\let\csname opt@fontenc.sty\endcsname\relax
\global\let\@ifl@ter@@\@ifl@ter
\def\@ifl@ter#1#2#3#4#5{\global\let\@ifl@ter\@ifl@ter@@}
⟨/package⟩
```

File t
ltcounts.dtx

1 Counters and Lengths

Commands for defining and using counters. This file defines:

`\newcounter` To define a new counter.

`\setcounter` To set the value of counters.

`\addtocounter` Increase the counter `#1` by the number `#2`.

`\stepcounter` Increase a counter by one.

`\refstepcounter` Increase a counter by one, also setting the value used by `\label`.

`\value` For accessing the value of the counter as a TEX number (as opposed to `\the`⟨*counter*⟩ which expands to the *printed* representation of ⟨*counter*⟩)

`\arabic` `\arabic{`⟨*counter*⟩`}`: 1, 2, 3, ...

`\roman` `\roman{`⟨*counter*⟩`}`: i, ii, iii, ...

`\Roman` `\Roman{`⟨*counter*⟩`}`: I, II, III, ...

`\alph` `\alph{`⟨*counter*⟩`}`: a, b, c, ...

`\Alph` `\Alph{`⟨*counter*⟩`}`: A, B, C, ...

`\fnsymbol` `\fnsymbol{`⟨*counter*⟩`}`: ∗, †, ‡, ...

`\counterwithin` `\counterwithin[`⟨*format*⟩`]{`⟨*counter*⟩`}{`⟨*within-counter*⟩`}`: Resets ⟨*counter*⟩ whenever ⟨*within-counter*⟩ is stepped. Also redefines `\the`⟨*counter*⟩ command to produce `\the`⟨*within-counter*⟩.⟨*format*⟩`{`⟨*counter*⟩`}` with `\arabic` as the default for ⟨*format*⟩. Star form omits redefining the print representation.

`\counterwithout` `\counterwithout[`⟨*format*⟩`]{`⟨*counter*⟩`}{`⟨*within-counter*⟩`}`: Removes ⟨*counter*⟩ from the reset list of ⟨*within-counter*⟩. Also redefines `\the`⟨*counter*⟩ command to produce ⟨*format*⟩`{`⟨*counter*⟩`}` with `\arabic` as the default for ⟨*format*⟩. Star form omits redefining the print representation.

```
⟨*2ekernel⟩
```

1.1 Environment Counter Macros

An environment foo has an associated counter defined by the following control sequences:

`\c@foo` Contains the counter's numerical value. It is defined by `\newcount\foocounter`.

`\thefoo` Macro that expands to the printed value of `\foocounter`. For example, if sections are numbered within chapters, and section headings look like
Section II-3. The Nature of Counters
then `\thesection` might be defined by:

```
\def\thesection
    {\@Roman{\c@chapter}-\@arabic{\c@section}}
```

`\p@foo` Macro that expands to a printed 'reference prefix' of counter foo. Any `\ref` to a value created by counter foo will produce the expansion of `\p@foo\thefoo` when the `\label` command is executed. See file `ltxref.dtx` for an extension of this mechanism.

`\cl@foo` List of counters to be reset when foo stepped. Has format `\@elt{countera}\@elt{counterb}\@elt{counterc}`.

NOTE:
`\thefoo` and `\p@foo` *must* be defined in such a way that `\edef\bar{\thefoo}` or `\edef\bar{\p@foo}` defines `\bar` so that it will evaluate to the counter value at the time of the `\edef`, even after `\foocounter` and any other counters have been changed. This will happen if you use the standard commands `\@arabic`, `\@Roman`, etc.

The following commands are used to define and modify counters.

`\refstepcounter{`⟨*foo*⟩`}`
Same as `\stepcounter`, but it also defines `\@currentreference` so that a subsequent `\label{`⟨*bar*⟩`}` command causes `\ref{`⟨*bar*⟩`}` to generate the current value of counter ⟨*foo*⟩.

`\@definecounter{`⟨*foo*⟩`}`
Initializes counter `{`⟨*foo*⟩`}` (with empty reset list), defines `\p@foo` and `\thefoo` to be null. Also adds ⟨*foo*⟩ to `\cl@@ckpt` – the reset list of a dummy counter `@ckpt` used for taking checkpoints for the `\include` system.

`\@addtoreset{`⟨*foo*⟩`}{`⟨*bar*⟩`}` : Adds counter ⟨*foo*⟩ to the list of counters `\cl@bar` to be reset when counter ⟨*bar*⟩ is stepped.

`\@removefromreset{`⟨*foo*⟩`}{`⟨*bar*⟩`}` : Removes counter ⟨*foo*⟩ to the list of counters `\cl@bar` to be reset when counter ⟨*bar*⟩ is stepped.

`\setcounter` `\setcounter{`⟨*foo*⟩`}{`⟨*val*⟩`}` : Globally sets `\foocounter` equal to ⟨*val*⟩.

```
\def\setcounter#1#2{%
  \@ifundefined{c@#1}%
    {\@nocounterr{#1}}%
    {\global\csname c@#1\endcsname#2\relax}}
```

(*End definition for* `\setcounter`.)

`\addtocounter` `\addtocounter{`⟨*foo*⟩`}{`⟨*val*⟩`}` Globally increments `\foocounter` by ⟨*val*⟩.

```
\def\addtocounter#1#2{%
  \@ifundefined{c@#1}%
    {\@nocounterr{#1}}%
    {\global\advance\csname c@#1\endcsname #2\relax}}
```

(*End definition for* `\addtocounter`.)

`\newcounter` `\newcounter{`⟨*newctr*⟩`}[`⟨*oldctr*⟩`]` Defines ⟨*newctr*⟩ to be a counter, which is reset when counter ⟨*oldctr*⟩ is stepped. If ⟨*newctr*⟩ already defined produces '`c@newctr  already defined`' error.

```
\def\newcounter#1{%
  \expandafter\@ifdefinable \csname c@#1\endcsname
    {\@definecounter{#1}}%
  \@ifnextchar[{\@newctr{#1}}{}}
```

(*End definition for* `\newcounter`.)

`\value` `\value{`⟨*ctr*⟩`}` produces the value of counter ⟨*ctr*⟩, for use with a `\setcounter` or `\addtocounter` command.

```
\def\value#1{\csname c@#1\endcsname}
```

(*End definition for* `\value`.)

`\@newctr`

```
\def\@newctr#1[#2]{%
  \@ifundefined{c@#2}{\@nocounterr{#2}}{\@addtoreset{#1}{#2}}}
```

(*End definition for* `\@newctr`.)

`\stepcounter` `\stepcounter`foo Globally increments counter `\c@FOO` and resets all subsidiary counters.

```
\def\stepcounter#1{%
  \addtocounter{#1}\@ne
  \begingroup
    \let\@elt\@stpelt
    \csname cl@#1\endcsname
  \endgroup}
```

(*End definition for* `\stepcounter`.)

`\@stpelt` Rather than resetting the "within" counter to zero we set it to −1 and then run `\stepcounter` that moves it to 0 and also initiates resetting the next level down.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\@stpelt}
⟨latexrelease⟩                              {Reset nested counters}%
⟨*2ekernel | latexrelease⟩
\def\@stpelt#1{\global\csname c@#1\endcsname \m@ne\stepcounter{#1}}%
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@stpelt}
⟨latexrelease⟩                              {Reset nested counters}%%
⟨latexrelease⟩\def\@stpelt#1{\global\csname c@#1\endcsname \z@}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@stpelt`.)

`\cl@@ckpt`

```
\def\cl@@ckpt{\@elt{page}}
```

(*End definition for* `\cl@@ckpt`.)

`\@definecounter`

```
\def\@definecounter#1{\expandafter\newcount\csname c@#1\endcsname
     \setcounter{#1}\z@
     \global\expandafter\let\csname cl@#1\endcsname\@empty
     \@addtoreset{#1}{@ckpt}%
     \global\expandafter\let\csname p@#1\endcsname\@empty
     \expandafter
     \gdef\csname the#1\expandafter\endcsname\expandafter
          {\expandafter\@arabic\csname c@#1\endcsname}}
```

(*End definition for* `\@definecounter`.)

`\@addtoreset`

```
\def\@addtoreset#1#2{\expandafter\@cons\csname cl@#2\endcsname {{#1}}}
```

(*End definition for* `\@addtoreset`.)

```
⟨/2ekernel⟩
```

\@removefromreset

```
⟨latexrelease⟩\IncludeInRelease{2018-04-01}
⟨latexrelease⟩                  {\@removefromreset}{Add interfaces}%
⟨*2ekernel | latexrelease⟩
```

```
\def\@removefromreset#1#2{%
```

Even through this is internal and the programmer should know what he/she is doing we test here if counter #2 is defined. If not, the execution would run into a tight loop.

```
  \@ifundefined{c@#2}\relax
  {\begingroup
     \expandafter\let\csname c@#1\endcsname\@removefromreset
     \def\@elt##1{%
       \expandafter\ifx\csname c@##1\endcsname\@removefromreset
       \else
         \noexpand\@elt{##1}%
       \fi}%
     \expandafter\xdef\csname cl@#2\endcsname
      {\csname cl@#2\endcsname}%
    \endgroup}}
```

(*End definition for* `\@removefromreset`.)

\@ifbothcounters

Test if arg #1 and #2 are counters and if so execute #3.

```
\def\@ifbothcounters#1#2#3{%
  \@ifundefined{c@#1}{\@nocounterr{#1}}%
    {% else counter is defined
     \@ifundefined{c@#2}{\@nocounterr{#2}}%
       {% else both counter and within  are defined
        #3}}}
```

(*End definition for* `\@ifbothcounters`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}
⟨latexrelease⟩                  {\@removefromreset}{Add interfaces}%
⟨latexrelease⟩\let \@removefromreset \undefined
⟨latexrelease⟩\let \@ifbothcounters  \undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\counterwithout
\counterwithin

New implementation using xparse and supporting an optional format argument.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                  {\counterwithout}{counter without/within}%
```

```
\NewDocumentCommand \counterwithout {sO{\arabic}mm}{%
  \@ifbothcounters{#3}{#4}{%
    \@removefromreset{#3}{#4}%
    \IfBooleanF #1%
        {\expandafter
         \gdef\csname the#3\endcsname {#2{#3}}}%
  }%
}
```

```
\NewDocumentCommand \counterwithin {sO{\arabic}mm}{%
  \@ifbothcounters{#3}{#4}{%
    \@addtoreset{#3}{#4}%
    \IfBooleanF #1%
       {\expandafter
         \gdef\csname the#3\expandafter\endcsname
         \expandafter
             {\csname the#4\endcsname .#2{#3}}}%
  }%
}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2018-04-01}
⟨latexrelease⟩                 {\counterwithout}{counter without/within}%
⟨latexrelease⟩
⟨latexrelease⟩\def\counterwithout {\@ifstar\counterwithout@s\counterwithout@x}
⟨latexrelease⟩\def\counterwithout@s#1#2{%
⟨latexrelease⟩  \@ifbothcounters{#1}{#2}{\@removefromreset{#1}{#2}}}
⟨latexrelease⟩\def\counterwithout@x#1#2{%
⟨latexrelease⟩  \@ifbothcounters{#1}{#2}%
⟨latexrelease⟩      {\@removefromreset{#1}{#2}%
⟨latexrelease⟩       \expandafter
⟨latexrelease⟩       \gdef\csname the#1\expandafter\endcsname\expandafter
⟨latexrelease⟩            {\expandafter
⟨latexrelease⟩             \@arabic\csname c@#1\endcsname}}}
⟨latexrelease⟩
⟨latexrelease⟩\def\counterwithin{\@ifstar\counterwithin@s\counterwithin@x}
⟨latexrelease⟩\def\counterwithin@s#1#2{%
⟨latexrelease⟩  \@ifbothcounters{#1}{#2}{\@addtoreset{#1}{#2}}}
```

```
⟨latexrelease⟩\def\counterwithin@x#1#2{%
⟨latexrelease⟩  \@ifbothcounters{#1}{#2}%
⟨latexrelease⟩      {\@addtoreset{#1}{#2}%
⟨latexrelease⟩       \expandafter
⟨latexrelease⟩       \gdef\csname the#1\expandafter\endcsname\expandafter
⟨latexrelease⟩            {\csname the#2\expandafter\endcsname\expandafter
⟨latexrelease⟩             .\expandafter
⟨latexrelease⟩             \@arabic\csname c@#1\endcsname}}}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}
⟨latexrelease⟩                 {\counterwithout}{counter without/within}%
⟨latexrelease⟩\let \counterwithout   \undefined
⟨latexrelease⟩\let \counterwithout@s \undefined
⟨latexrelease⟩\let \counterwithout@x \undefined
⟨latexrelease⟩\let \counterwithin    \undefined
⟨latexrelease⟩\let \counterwithin@s  \undefined
⟨latexrelease⟩\let \counterwithin@x  \undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\counterwithout` *and* `\counterwithin`.)

Numbering commands for definitions of `\theCOUNTER` and `\list` arguments. All commands can now be used in text and math mode.

`\arabic` Representation of⟨*counter*⟩ as arabic numerals. Changed 29 Apr 86 to make it print the obvious thing it COUNTER not positive.

```
\def\arabic#1{\expandafter\@arabic\csname c@#1\endcsname}
```

(*End definition for* `\arabic`.)

`\roman` Representation of ⟨*counter*⟩ as lower-case Roman numerals.

```
\def\roman#1{\expandafter\@roman\csname c@#1\endcsname}
```

(*End definition for* `\roman`.)

`\Roman` Representation of ⟨*counter*⟩ as upper-case Roman numerals.

```
\def\Roman#1{\expandafter\@Roman\csname c@#1\endcsname}
```

(*End definition for* `\Roman`.)

`\alph` Representation of ⟨*counter*⟩ as a lower-case letter: 1 = a, 2 = b, etc.

```
\def\alph#1{\expandafter\@alph\csname c@#1\endcsname}
```

(*End definition for* `\alph`.)

`\Alph` Representation of ⟨*counter*⟩ as an upper-case letter: 1 = A, 2 = B, etc.

```
\def\Alph#1{\expandafter\@Alph\csname c@#1\endcsname}
```

(*End definition for* `\Alph`.)

`\fnsymbol` Representation of ⟨*COUNTER*⟩ as a footnote symbol: 1 = ∗, 2 = †, etc.

```
\def\fnsymbol#1{\expandafter\@fnsymbol\csname c@#1\endcsname}
```

(*End definition for* `\fnsymbol`.)

`\@arabic` `\@arabic\FOOcounter` Representation of `\FOOcounter` as arabic numerals.

```
\def\@arabic#1{\number #1}  %% changed 29 Apr 86
```

(*End definition for* `\@arabic`.)

`\@roman` `\@roman\FOOcounter` Representation of `\FOOcounter` as lower-case Roman numerals.

```
\def\@roman#1{\romannumeral #1}
```

(*End definition for* `\@roman`.)

`\@Roman` `\@Roman\FOOcounter` Representation of `\FOOcounter` as upper-case Roman numerals.

```
\def\@Roman#1{\expandafter\@slowromancap\romannumeral #1@}
```

(*End definition for* `\@Roman`.)

`\@slowromancap` Fully expandable macro to change a roman number to uppercase.

```
\def\@slowromancap#1{\ifx @#1% then terminate
     \else
       \if i#1I\else\if v#1V\else\if x#1X\else\if l#1L\else\if
       c#1C\else\if d#1D\else \if m#1M\else#1\fi\fi\fi\fi\fi\fi\fi
       \expandafter\@slowromancap
     \fi
}
```

(*End definition for* `\@slowromancap`.)

\@alph \@alph\FOOcounter Representation of \FOOcounter as a lower-case letter: 1 = a, 2 = b, etc.

```
\def\@alph#1{%
  \ifcase#1\or a\or b\or c\or d\or e\or f\or g\or h\or i\or j\or
   k\or l\or m\or n\or o\or p\or q\or r\or s\or t\or u\or v\or w\or x\or
    y\or z\else\@ctrerr\fi}
```

(*End definition for* \@alph.)

\@Alph \@Alph\FOOcounter Representation of \FOOcounter as an upper-case letter: 1 = A, 2 = B, etc.

```
\def\@Alph#1{%
  \ifcase#1\or A\or B\or C\or D\or E\or F\or G\or H\or I\or J\or
   K\or L\or M\or N\or O\or P\or Q\or R\or S\or T\or U\or V\or W\or X\or
    Y\or Z\else\@ctrerr\fi}
```

(*End definition for* \@Alph.)

\@fnsymbol Typesetting old fashioned footnote symbols. This can be done both in text or math mode now.

This macro is another example of an ever recurring problem in TEX: Determining if something is text-mode or math-mode. It is imperative for the decision between text and math to be delayed until the actual typesetting is done as the code in question may go through an \edef or \write where an \ifmmode test would be executed prematurely. Hence in the implementation below, \@fnsymbol is not robust in itself but the parts doing the actual typesetting are.

In the case of \@fnsymbol we make use of the robust command \TextOrMath which takes two arguments and typesets the first if in text-mode and the second if in math-mode. Note that in order for this command to make the correct decision, it must insert a \relax token if run under regular TEX, which ruins any kerning between the preceding characters and whatever awaits typesetting. If you use eTEX as engine for LATEX (as recommended) this unfortunate side effect is not present.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\@fnsymbol}{Use \TextOrMath}%
⟨*2ekernel | latexrelease⟩
\def\@fnsymbol#1{%
   \ifcase#1\or \TextOrMath\textasteriskcentered *\or
   \TextOrMath \textdagger \dagger\or
   \TextOrMath \textdaggerdbl \ddagger \or
   \TextOrMath \textsection  \mathsection\or
   \TextOrMath \textparagraph \mathparagraph\or
   \TextOrMath \textbardbl \|\or
   \TextOrMath {\textasteriskcentered\textasteriskcentered}{**}\or
   \TextOrMath {\textdagger\textdagger}{\dagger\dagger}\or
   \TextOrMath {\textdaggerdbl\textdaggerdbl}{\ddagger\ddagger}\else
   \@ctrerr \fi
}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@fnsymbol}{Use \TextOrMath}%
⟨latexrelease⟩\def\@fnsymbol#1{\ensuremath{%
⟨latexrelease⟩   \ifcase#1\or *\or \dagger\or \ddagger\or \mathsection\or
⟨latexrelease⟩      \mathparagraph\or \|\or **\or \dagger\dagger
```

```
⟨latexrelease⟩      \or \ddagger\ddagger \else\@ctrerr\fi}}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@fnsymbol`.)

`\TextOrMath` When using regular TEX, we make this command robust so that it always selects the correct branch in an `\ifmmode` switch with the usual disadvantage of ruining kerning. For the application we use it for here that shouldn't matter. The alternative would be to mimic `\IeC` from inputenc but then it will have the disadvantage of choosing the wrong branch if appearing at the beginning of an alignment cell. However, users of eTEX will be pleasantly surprised to get the best of both worlds and no bad side effects.

First some code for checking if we are running eTEX but making sure not to permanently turn `\protected` into `\relax`.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\TextOrMath}{\TextOrMath}%
⟨*2ekernel | latexrelease⟩
\begingroup\expandafter\expandafter\expandafter\endgroup
\expandafter\ifx\csname protected\endcsname\relax
```

In case of ordinary TEX we define `\TextOrMath` as a robust command but make sure it always grabs its arguments. If we didn't do this it might very well gobble spaces in the input stream.

```
\DeclareRobustCommand\TextOrMath{%
  \ifmmode  \expandafter\@secondoftwo
  \else     \expandafter\@firstoftwo  \fi}
\protected@edef\TextOrMath#1#2{\TextOrMath{#1}{#2}}
\else
```

For eTEX the situation is similar. The robust macro is a hidden one so that we again avoid problems of gobbling spaces in the input.

```
\protected\expandafter\def\csname TextOrMath\space\endcsname{%
  \ifmmode  \expandafter\@secondoftwo
  \else     \expandafter\@firstoftwo  \fi}
\edef\TextOrMath#1#2{%
  \expandafter\noexpand\csname TextOrMath\space\endcsname
  {#1}{#2}}
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\TextOrMath}{\TextOrMath}%
⟨latexrelease⟩\let\TextOrMath\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\TextOrMath`.)

```
⟨/2ekernel⟩
```

File u
ltlength.dtx

1 Lengths

\newlength Declare #1 to be a new length command.
\setlength Set the length command, #1, to the value #2.
\addtolength Increase the value of the length command, #1, by the value #2.
\settowidth Set the length, #1 to the width of a box containing #2.
\settoheight Set the length, #1 to the height of a box containing #2.
\settodepth Set the length, #1 to the depth of a box containing #2.

```
⟨*2ekernel⟩
\message{lengths,}
```

\newlength

```
\def\newlength#1{\@ifdefinable#1{\newskip#1}}
```

(*End definition for* \newlength.)

\setlength

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\setlength}{Using \setlength with \dimen0}%
⟨*2ekernel | latexrelease⟩
\def\setlength#1#2{#1 #2\relax}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\setlength}{Using \setlength with \dimen0}%
⟨latexrelease⟩\def\setlength#1#2{#1#2\relax}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \setlength.)

\addtolength \relax added 24 Mar 86

```
\def\addtolength#1#2{\advance#1 #2\relax}
```

(*End definition for* \addtolength.)

\settoheight The obvious analogs of \settowidth.
\settodepth
\settowidth
\@settodim

```
\def\@settodim#1#2#3{\setbox\@tempboxa\hbox{{#3}}#2#1\@tempboxa
```

Clear the memory afterwards (which might be a lot).

```
        \setbox\@tempboxa\box\voidb@x}
\DeclareRobustCommand\settoheight{\@settodim\ht}
\DeclareRobustCommand\settodepth {\@settodim\dp}
\DeclareRobustCommand\settowidth {\@settodim\wd}
```

(*End definition for* \settoheight *and others.*)

`\@settopoint` This macro takes the contents of the skip register that is supplied as its argument and removes the fractional part to make it a whole number of points. This can be used in class files to avoid values like `345.4666666pt` when calculating a dimension.

```
\def\@settopoint#1{\divide#1\p@\multiply#1\p@}
```

⟨/2ekernel⟩

(*End definition for* `\@settopoint`.)

File v
ltfssbas.dtx

This file contains the main implementation of the 'low level' font selection commands. See other parts of the LaTeX distribution, or *The LaTeX Companion* for higher level documentation of the LaTeX 'New' Font Selection Scheme.

> **Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

1 Preliminary macros

We define a number of macros that will be used later.

`\@nomath` `\@nomath` is used by most macros that will have no effect in math mode. It issues a warning message.

```
⟨*2ekernel⟩
\def\@nomath#1{\relax\ifmmode
   \@font@warning{Command \noexpand#1invalid in math mode}\fi}
```

(*End definition for* `\@nomath`.)

`\no@alphabet@error` The macro `\no@alphabet@error` is called whenever the user requests a math *alphabet* that is not available in the current *version*. In math mode an error message is produced otherwise the command keeps silent. The argument is the name of the control sequence that identifies the math *alphabet*. The `\relax` at the beginning is necessary to prevent TeX from scanning too far in certain situations.

```
\gdef\no@alphabet@error#1{\relax \ifmmode
    \@latex@error{Math\space alphabet\space identifier\space
          \noexpand#1is\space undefined\space in\space math\space
           version\space `\math@version'}%
        {Your\space requested\space math\space alphabet\space
         is\space undefined\space in\space the\space current\space
          math\space version.^^JCheck\space the\space spelling\space
          or\space use\space the\space \noexpand\SetMathAlphabet\space
          command.}
     \fi}
```

(*End definition for* `\no@alphabet@error`.)

`\new@mathgroup` `\mathgroup` We also give a new name to `\newfam` and `\fam` to avoid verbal confusion (see the introduction).[23]

```
%\def\new@mathgroup{\alloc@8\mathgroup\chardef\sixt@@n}
\let\mathgroup\fam
%\let\newfam\new@mathgroup
\@onlypreamble\new@mathgroup
```

(*End definition for* `\new@mathgroup` *and* `\mathgroup`.)

[23] For the same reason it seems advisable to `\let\fam` and `\newfam` equal to `\relax`, but this is commented out to retain compatibility to existing style files.

2 Macros for setting up the tables

\DeclareFontShape

The macro \DeclareFontShape takes 6 arguments:

```
\def\DeclareFontShape{\begingroup
```

First we restore the catcodes of all characters used in the syntax.

```
   \nfss@catcodes
```

We use \expandafter \endgroup to restore catcode in case something goes wrong with the argument parsing (suggested by Tim Van Zandt)

```
   \expandafter\endgroup
   \DeclareFontShape@}
```

(*End definition for* \DeclareFontShape.)

\DeclareFontShape@

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                    {\DeclareFontShape@}{Maybe drop one m}%
\def\DeclareFontShape@#1#2#3#4#5#6{%
   \expandafter\ifx\csname #1+#2\endcsname\relax
     \@latex@error{Font family ‘#1+#2’ unknown}\@eha
   \else
```

If the series value is incorrectly specified with an extra “m”, e.g., “mc” instead of just “c”, drop the surplus “m” but keep the “m” if it is by its own. In that case also issue a warning that the declaration needs correction.

For this we compare the given value #3 with one where we may have dropped an “m”. If nothing has changes, fine. Otherwise there was a wrong value which is now corrected in \reservedb so we use that and also issue a warning.

```
     \edef\reserved@a{#3}%
     \series@maybe@drop@one@m\reserved@a\reserved@b
     \ifx\reserved@a\reserved@b\else
       \@latex@note{Font shape #1/#2/#3/#4 has incorrect series
         value ‘#3’.\MessageBreak It should not contain an ‘m’!
         Please correct it.\MessageBreak Found}%
     \fi
     \expandafter
       \xdef\csname#1/#2/\reserved@b/#4\endcsname
                 {\expandafter\noexpand\csname #5\endcsname}%
%
```

Most of the time #6 is empty so using \let to \@empty saves on space compared to using \def. That’s really one of the old space saving techniques and probably not necessary these days.

```
     \def\reserved@a{#6}%
     \global
     \expandafter\let\csname#5\expandafter\endcsname
        \ifx\reserved@a\@empty
          \@empty
        \else
          \reserved@a
        \fi
   \fi
  }
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\DeclareFontShape@}{Maybe drop one m}%
⟨latexrelease⟩
⟨latexrelease⟩\def\DeclareFontShape@#1#2#3#4#5#6{%
⟨latexrelease⟩   \expandafter\ifx\csname #1+#2\endcsname\relax
⟨latexrelease⟩     \@latex@error{Font family ‘#1+#2’ unknown}\@eha
⟨latexrelease⟩   \else
⟨latexrelease⟩     \expandafter
⟨latexrelease⟩       \xdef\csname#1/#2/#3/#4\endcsname{\expandafter\noexpand
⟨latexrelease⟩                                 \csname #5\endcsname}%
⟨latexrelease⟩     \def\reserved@a{#6}%
⟨latexrelease⟩     \global
⟨latexrelease⟩     \expandafter\let\csname#5\expandafter\endcsname
⟨latexrelease⟩        \ifx\reserved@a\@empty
⟨latexrelease⟩          \@empty
⟨latexrelease⟩        \else
⟨latexrelease⟩          \reserved@a
⟨latexrelease⟩        \fi
⟨latexrelease⟩   \fi
⟨latexrelease⟩  }
⟨latexrelease⟩\EndIncludeInRelease
⟨∗2ekernel⟩
```

(*End definition for* `\DeclareFontShape@`.)

`\DeclareFixedFont` Define a direct font switch that avoids all overhead.

```
\def\DeclareFixedFont#1#2#3#4#5#6{%
   \begingroup
      \math@fontsfalse
      \every@math@size{}%
      \fontsize{#6}\z@
      \usefont{#2}{#3}{#4}{#5}%
      \global\expandafter\let\expandafter#1\the\font
   \endgroup
  }
```

(*End definition for* `\DeclareFixedFont`.)

`\do@subst@correction`

```
\def\do@subst@correction{%
       \xdef\subst@correction{%
          \font@name
          \global\expandafter\font
            \csname \curr@fontshape/\f@size\endcsname
            \noexpand\fontname\font
           \relax}%
```

Calling `\subst@correction` after the current group means calling it after we have loaded the substitution font which is done inside a group.

```
       \aftergroup\subst@correction
}
```

(*End definition for* `\do@subst@correction`.)

\DeclareFontFamily

```
\def\DeclareFontFamily#1#2#3{%
```

If we want fast checking for the encoding scheme we can just check for \T@.. being defined.

```
% \@tempswafalse
% \def\reserved@b{#1}%
% \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
%      \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
% \cdp@list
% \if@tempswa
 \@ifundefined{T@#1}%
    {%
     \@latex@error{Encoding scheme  `#1' unknown}\@eha
    }%
    {%
```

Now we have to define the macro \⟨#1⟩+⟨#2⟩ to contain #3. But since most of the time #3 will be empty we use \let in a tricky way rather than a simple \def since this will save internal memory. We store the argument #3 in a temporary macro \reserved@a.

```
     \def\reserved@a{#3}%
```

We compare \reserved@a with \@empty If these two are the same we \let the 'extra' macro equal to \@empty which is not the same a doing a \let to \reserved@a — the latter would blow one extra memory location rather then reusing the one from \@empty.

```
     \global
     \expandafter\let\csname #1+#2\expandafter\endcsname
            \ifx \reserved@a\@empty
              \@empty
            \else \reserved@a
            \fi
    }%
}
```

(*End definition for* \DeclareFontFamily.)

\cdp@list We initialize the code page list to be empty.

```
\let\cdp@list\@empty
\@onlypreamble\cdp@list
```

(*End definition for* \cdp@list.)

\cdp@elt

```
\let\cdp@elt\relax
\@onlypreamble\cdp@elt
```

(*End definition for* \cdp@elt.)

\DeclareFontEncoding

```
\def\DeclareFontEncoding{%
```

First we start with ignoring all blanks and newlines since every surplus space in the second or third argument will come out in a weird place in the document.

```
  \begingroup
  \nfss@catcodes
  \expandafter\endgroup
  \DeclareFontEncoding@}
\@onlypreamble\DeclareFontEncoding
```

```
\def\DeclareFontEncoding@#1#2#3{%
  \expandafter
  \ifx\csname T@#1\endcsname\relax
     \def\cdp@elt{\noexpand\cdp@elt}%
     \xdef\cdp@list{\cdp@list\cdp@elt{#1}%
                    {\default@family}{\default@series}%
                    {\default@shape}}%
```

To support encoding dependent commands (like accents) we initialise the command \⟨*encoding*⟩-cmd to be `\@changed@cmd`. (See `ltoutenc.dtx` for details.)

```
     \expandafter\let\csname#1-cmd\endcsname\@changed@cmd
  \else
     \@font@info{Redeclaring font encoding #1}%
  \fi
```

```
  \global\@namedef{T@#1}{#2}%
  \global\@namedef{M@#1}{\default@M#3}%
```

Keep a record of the last encoding being declared:

```
  \xdef\LastDeclaredEncoding{#1}%
  }
\@onlypreamble\DeclareFontEncoding@
```

(*End definition for* `\DeclareFontEncoding`.)

`\LastDeclaredEncoding` The last encoding being declared by `\DeclareFontEncoding`.

```
\def\LastDeclaredEncoding{}
```

(*End definition for* `\LastDeclaredEncoding`.)

`\DeclareFontSubstitution`

```
\def\DeclareFontSubstitution#1#2#3#4{%
  \expandafter
  \ifx\csname T@#1\endcsname\relax
    \@latex@error{Encoding scheme  `#1' unknown}\@eha
  \else
    \begingroup
```

We loop through the `\cdp@list` and rebuild it anew in `\toks@` thereby replacing the defaults for the encoding in question with the new defaults. It is important to store the encoding to test against expanded in `\reserved@a` since it might just be `\LastDeclaredEncoding` that is passed as `#1`.

```
        \edef\reserved@a{#1}%
        \toks@{}%
        \def\cdp@elt##1##2##3##4{%
           \def\reserved@b{##1}%
           \ifx\reserved@a\reserved@b
```

Here we use the new defaults but we use `##1` (i.e., the encoding name already stored previously) since we know that it is expanded.

```
            \addto@hook\toks@{\cdp@elt{##1}{#2}{#3}{#4}}%
          \else
```

If `\reserved@a` and `\reserved@b` differ then we simply copy from the old list to the new.

```
            \addto@hook\toks@{\cdp@elt{##1}{##2}{##3}{##4}}%
          \fi}%
        \cdp@list
        \xdef\cdp@list{\the\toks@}%
    \endgroup
    \global
    \@namedef{D@#1}{%
           \def\default@family{#2}%
           \def\default@series{#3}%
           \def\default@shape{#4}%
           }%
  \fi
 }
\@onlypreamble\DeclareFontSubstitution
```

(*End definition for* `\DeclareFontSubstitution`.)

`\DeclareFontEncodingDefaults`

```
\def\DeclareFontEncodingDefaults#1#2{%
  \ifx\relax#1\else
    \ifx\default@T\@empty\else
      \@font@info{Overwriting encoding scheme text defaults}%
    \fi
    \gdef\default@T{#1}%
  \fi
  \ifx\relax#2\else
    \ifx\default@M\@empty\else
      \@font@info{Overwriting encoding scheme math defaults}%
    \fi
    \gdef\default@M{#2}%
  \fi
}
\@onlypreamble\DeclareFontEncodingDefaults
```

(*End definition for* `\DeclareFontEncodingDefaults`.)

`\default@T`
`\default@M`

```
\let\default@T\@empty
\let\default@M\@empty
```

(*End definition for* `\default@T` *and* `\default@M`.)

`\DeclarePreloadSizes`

```
\def\DeclarePreloadSizes#1#2#3#4#5{%
 \@ifundefined{T@#1}%
   {\@latex@error{Encoding scheme  `#1' unknown}\@eha}%
   {%
```

Don't know at the moment what this group here does!

```
    \begingroup
```

We define a macro \reserved@f[24] that grabs the next *size* and loads the corresponding font. This is done by delimiting \reserved@f's only argument by the token , (comma).

```
    \def\reserved@f##1,{%
```

The end of the list will be detected when there are no more elements, i.e. when \reserved@f's argument is empty. The trick used here is explained in Appendix D of the TEXbook: if the argument is empty the \if will select the first clause and \let \reserved@f equal to \relax. (We use the > character here since it cannot appear in font file names.)

```
        \if>##1>%
          \let\reserved@f\relax
        \else
```

Otherwise, we define \font@name appropriately and call \pickup@font to do the work. Note that the requested \curr@fontshape combination must have been defined, or you will get an error. The definition of \font@name is carried out globally to be consistent with the rest of the code in this file.

```
          \xdef\font@name{\csname#1/#2/#3/#4/##1\endcsname}%
          \pickup@font
```

Now we forget the name of the font just loaded. More precisely, we set the corresponding control sequence to \relax. This means that later on, when the font is first used, the macro \define@newfont is called again to execute the 'extra' macro for this font.

```
          \global\expandafter\let\font@name\relax
        \fi
```

Finally we call \reserved@f again to process the next *size*. If \reserved@f was \let equal to \relax this will end the macro.

```
        \reserved@f}%
```

We finish with reinserting the list of sizes after the \reserved@f macro and appending an empty element so that the end of the list is recognized properly.

```
    \reserved@f#5,,%
  \endgroup
  }%
}
\@onlypreamble\DeclarePreloadSizes
```

(*End definition for* \DeclarePreloadSizes.)

\ifmath@fonts We need a switch to decide if we have to switch math fonts. For this purpose we provide \ifmath@fonts that can be set to true or false by the \S@... macros depending on if math fonts are provided for this size or not. The default is of course to switch all fonts.

```
\newif\ifmath@fonts \math@fontstrue
```

(*End definition for* \ifmath@fonts.)

[24] We cannot use \@tempa since it is needed in \pickup@font.

\DeclareMathSizes
\DeclareMathSizes*

\DeclareMathSizes takes the text size, math text size, math script size, and math scriptscript size as arguments and defines the right \S@... macro.

```
\def\DeclareMathSizes{%
  \@ifstar{\@DeclareMathSizes\math@fontsfalse}%
          {\@DeclareMathSizes{}}}
\@onlypreamble\DeclareMathSizes
```

(*End definition for* \DeclareMathSizes *and* \DeclareMathSizes*.)

\@DeclareMathSizes

This modification by Michael J. Downes on comp.text.tex on 2002/10/17 allows the user to have settings such as
\DeclareMathSizes{9.5dd}{9.5dd}{7.4dd}{6.6dd}.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\@DeclareMathSizes}%
⟨latexrelease⟩                 {Arbitrary units in \DeclareMathSizes}%
⟨*2ekernel | latexrelease⟩
\def\@DeclareMathSizes #1#2#3#4#5{%
  \@defaultunits\dimen@ #2pt\relax\@nnil
  \if $#3$%
    \expandafter\let\csname S@\strip@pt\dimen@\endcsname\math@fontsfalse
  \else
    \@defaultunits\dimen@ii #3pt\relax\@nnil
    \@defaultunits\@tempdima #4pt\relax\@nnil
    \@defaultunits\@tempdimb #5pt\relax\@nnil
    \toks@{#1}%
    \expandafter\xdef\csname S@\strip@pt\dimen@\endcsname{%
      \gdef\noexpand\tf@size{\strip@pt\dimen@ii}%
      \gdef\noexpand\sf@size{\strip@pt\@tempdima}%
      \gdef\noexpand\ssf@size{\strip@pt\@tempdimb}%
      \the\toks@
    }%
  \fi
}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@DeclareMathSizes}%
⟨latexrelease⟩                 {Arbitrary units in \DeclareMathSizes}%
⟨latexrelease⟩\def\@DeclareMathSizes#1#2#3#4#5{%
⟨latexrelease⟩    \@defaultunits\dimen@#2pt\relax\@nnil
⟨latexrelease⟩    \if$#3$%
⟨latexrelease⟩      \expandafter \let
⟨latexrelease⟩        \csname S@\strip@pt\dimen@\endcsname
⟨latexrelease⟩        \math@fontsfalse
⟨latexrelease⟩    \else
⟨latexrelease⟩      \expandafter \gdef
⟨latexrelease⟩      \csname S@\strip@pt\dimen@\endcsname
⟨latexrelease⟩            {\gdef\tf@size{#3}\gdef\sf@size{#4}%
⟨latexrelease⟩                              \gdef\ssf@size{#5}%
⟨latexrelease⟩             #1%
⟨latexrelease⟩                              }%
⟨latexrelease⟩    \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\@DeclareMathSizes
```

(*End definition for* `\@DeclareMathSizes`.)

3 Selecting a new font

3.1 Macros for the user

`\fontencoding` `\f@encoding`

As we said in the introduction a font is described by four parameters. We first define macros to specify the wanted *family*, *series*, or *shape*. These are simply recorded in internal macros `\f@family`, `\f@series`, and `\f@shape`, resp. We use `\edef`'s so that the arguments can also be macros.

```
\DeclareRobustCommand\fontencoding[1]{%
    \expandafter\ifx\csname T@#1\endcsname\relax
      \@latex@error{Encoding scheme `#1' unknown}\@eha
    \else
      \edef\f@encoding{#1}%
      \ifx\cf@encoding\f@encoding
```

If the new encoding is the same as the old encoding we have nothing to do. However, in case we had a sequence of several encoding changes without a `\selectfont` in-between we can save processing by making sure that `\enc@update` is `\relax`.

```
        \let\enc@update\relax
      \else
```

If current and new encoding differ we define the macro `\enc@update` to contain all updates necessary at `\selectfont` time.

```
        \let\enc@update\@@enc@update
      \fi
    \fi
}
```

(*End definition for* `\fontencoding` *and* `\f@encoding`.)

`\@@enc@update`

```
\def\@@enc@update{%
```

When `\@@enc@update` is executed `\f@encoding` holds the encoding name for the new encoding and `\cf@encoding` the name of the last active encoding.

We start by setting the init command for encoding dependent macros to `\@changed@cmd`.

```
          \expandafter
          \let
            \csname\cf@encoding -cmd\endcsname
            \@changed@cmd
```

Then we turn the one for the new encoding to `\@current@cmd` (see `ltoutenc.dtx` for further explanations).

```
          \expandafter
          \let
            \csname\f@encoding-cmd\endcsname
            \@current@cmd
```

We execute the default settings `\default@T`, followed by the one for the new encoding.

```
        \default@T
        \csname T@\f@encoding\endcsname
```

Finally we change the default substitution values, disable `\enc@update` and make `\f@encoding` officially the current encoding.

```
        \csname D@\f@encoding\endcsname
        \let\enc@update\relax
        \let\cf@encoding\f@encoding
}
```

(*End definition for* `\@@enc@update`.)

`\enc@update` The default action in `\selectfont` is to do nothing.

```
\let\enc@update\relax
```

(*End definition for* `\enc@update`.)

`\fontfamily` `\f@family` `\fontseries` `\f@series` `\fontshape` `\f@shape`

```
\DeclareRobustCommand\fontfamily[1]{\edef\f@family{#1}}
```

There are now defined later (and differently).

```
%\DeclareRobustCommand\fontseries[1]{\edef\f@series{#1}}
%\DeclareRobustCommand\fontshape [1]{\edef\f@shape{#1}}
```

(*End definition for* `\fontfamily` *and others.*)

`\usefont` Some handy abbreviation if you want to get some particular font in the current size. If also the size should change one has to issue a `\fontsize` command first.

`\fontencoding` needs to do some setup work so we call that, but instead of calling `\fontfamily`, `\fontseries` and `\fontshape` it earlier versions of this code did, we now set `\f@family`, etc. directly. If we would call `\fontseries` or `\fontshape` as it was done in the past, they would now interact with the existing series and shape which is not desired if we intend to use an explicit font shape!

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\usefont}{Force font face}%
\DeclareRobustCommand\usefont[4]{\fontencoding{#1}%
    \edef\f@family{#2}%
    \set@target@series{#3}%
    \edef\f@shape{#4}%
```

Any earlier `\fontseries`, etc. should be canceled and we should switch unconditionally to the requested font face so we drop any code that may have been stored in `\delayed@f@adjustment`.

```
    \let\delayed@f@adjustment\@empty
    \selectfont
    \ignorespaces}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\usefont}{Drop m in usefont}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\usefont[4]{\fontencoding{#1}%
⟨latexrelease⟩    \edef\f@family{#2}%
⟨latexrelease⟩    \set@target@series{#3}%
⟨latexrelease⟩    \edef\f@shape{#4}\selectfont
```

```
⟨latexrelease⟩   \ignorespaces}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\usefont}{Drop m in usefont}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\usefont[4]{\fontencoding{#1}%
⟨latexrelease⟩   \edef\f@family{#2}%
⟨latexrelease⟩   \edef\f@series{#3}%
⟨latexrelease⟩   \edef\f@shape{#4}\selectfont
⟨latexrelease⟩   \ignorespaces}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\usefont`.)

`\linespread` The command `\linespread` changes the current `\baselinestretch` by calling `\set@fontsize`. The values for `\f@size` and `\f@baselineskip` will be left unchanged.

```
\DeclareRobustCommand\linespread[1]
   {\set@fontsize{#1}\f@size\f@baselineskip}
```

(*End definition for* `\linespread`.)

`\fontsize` We also define a macro that allows to specify a size. In this case, however, we also need the value of `\baselineskip`. As the first argument to `\set@fontsize` we pass the current value of `\baselinestretch`. This will either match the internal value (in which case nothing changes, or it will be an updated value due to a user change of that macro using `\renewcommand`. If we would pass the internal `\f@linespread` such a change would be effectively overwritten by a size change.

```
\DeclareRobustCommand\fontsize[2]
   {\set@fontsize\baselinestretch{#1}{#2}}
```

(*End definition for* `\fontsize`.)

`\f@linespread` This macro holds the current internal value for `\baselinestretch`.

```
\let\f@family\@empty
\let\f@series\@empty
\let\f@shape\@empty
\let\f@size\@empty
\let\f@baselineskip\@empty
\let\f@linespread\@empty
```

(*End definition for* `\f@linespread`.)

`\cf@encoding`

```
\let\f@encoding\@empty
\let\cf@encoding\@empty
```

(*End definition for* `\cf@encoding`.)

\@defaultunits The function \@defaultunits when wrapped around a dimen or skip assignment supplies default units. Usage:

```
\@defaultunits\dimen@=#1pt\relax\@nnil
```

Note: the \relax is *important*. Other units can be substituted for the 'pt' if desired.

We use \remove@to@nnil as an auxiliary macros for \@defaultunits. It just has to gobble the supplied default unit 'pt' or whatever, if it wasn't used in the assignment.

```
\def\@defaultunits{\afterassignment\remove@to@nnil}
```

(*End definition for* \@defaultunits.)

\strip@pt This macro strips the characters pt produced by using \the on a dimen register.
\rem@pt

```
\begingroup
  \catcode`P=12
  \catcode`T=12
  \lowercase{
    \def\x{\def\rem@pt##1.##2PT{##1\ifnum##2>\z@.##2\fi}}}
  \expandafter\endgroup\x
\def\strip@pt{\expandafter\rem@pt\the}
```

(*End definition for* \strip@pt *and* \rem@pt.)

\mathversion \mathversion takes the math *version* name as argument, defines \math@version appropriately and switches to the font selected forcing a call to \glb@settings if the *version* is known to the system.
\math@version

```
\DeclareRobustCommand\mathversion[1]
         {\@nomath\mathversion
          \expandafter\ifx\csname mv@#1\endcsname\relax
          \@latex@error{Math version `#1' is not defined}\@eha\else
          \edef\math@version{#1}%
```

We need to force a math font setup both now and at the point where we return to the previous math version. Forcing a math font setup can simply be done by setting \glb@currsize to an invalid value since this will trigger the setup when the formula starts.

```
          \gdef\glb@currsize{}%
```

When the scope of the current \mathversion ends we need to restore the old setup. However this time we need to force it directly at least if we are inside math, otherwise we could wait. Another way to enhance this code here is todo the setting only if the version really has changed after all. This might be interesting in case of amstext and boldsymbol.

```
          \aftergroup\glb@settings
          \fi}
```

(*End definition for* \mathversion *and* \math@version.)

If TEX would support a hook just before the end of a formula (opposite of \everymath so to speak) the implementation of the algorithm would be much simpler because in that case we would set up the correct math fonts at this point without having to worry about incorrect settings due to nesting. The same would be true if in LATEX the use of $ (as the primitive TEX command) would be impossible and instead only a higher-level interface would be available. Note that this does not mean that a $ couldn't be the short-hand

for starting and stopping that higher-level interface, it only means that the direct TEX function must be hidden.

Anyway, since we don't have this and won't have it in LATEX 2ε we need to implement it in a somewhat slower way.

We test for the current math font setup on entry of a formula, i.e., on the hooks `\everymath` and `\everydisplay`. But since these hooks may contain user data we provide ourselves with an internal version of these hooks which stays frozen.

`\frozen@everymath`
`\frozen@everydisplay`

New internal names for `\everymath` and `\everydisplay`.

```
\let\frozen@everymath\everymath
\let\frozen@everydisplay\everydisplay
```

(*End definition for* `\frozen@everymath` *and* `\frozen@everydisplay`.)

`\everymath`
`\everydisplay`

Now we provide now user hooks that will be called in the frozen internals.

```
\newtoks\everymath
\newtoks\everydisplay
```

(*End definition for* `\everymath` *and* `\everydisplay`.)

`\frozen@everymath`

Now we define the behaviour of the frozen hooks: first check the math setup then call the user hook.

```
\frozen@everymath = {\check@mathfonts
                     \the\everymath}
```

(*End definition for* `\frozen@everymath`.)

`\frozen@everydisplay`

Ditto for the display hook.

```
\frozen@everydisplay = {\check@mathfonts
                        \the\everydisplay}
```

(*End definition for* `\frozen@everydisplay`.)

`\curr@math@size`

This holds locally the current math size.

```
\let\curr@math@size\@empty
```

(*End definition for* `\curr@math@size`.)

3.2 Macros for loading fonts

`\pickup@font`

The macro `\pickup@font` which is used in `\selectfont` is very simple: if the font name is undefined (i.e. not known yet) it calls `\define@newfont` to load it.

```
\def\pickup@font{%
    \expandafter \ifx \font@name \relax
       \define@newfont
    \fi}
```

(*End definition for* `\pickup@font`.)

\split@name

\pickup@font assumes that \font@name is set but it is sometimes called when \f@family, \f@series, \f@shape, or \f@size may have the wrong settings (see, e.g., the definition of \getanddefine@fonts). Therefore we need a macro to extract font *family*, *series*, *shape*, and *size* from the font name. To this end we define \split@name which takes the font name as a list of characters of \catcode 12 (without the backslash at the beginning) delimited by the special control sequence \@nil. This is not very complicated: we first ensure that / has the right \catcode

```
{\catcode`\/=12
```

and define \split@name so that it will define our private \f@encoding, \f@family, \f@series, \f@shape, and \f@size macros.

```
\gdef\split@name#1/#2/#3/#4/#5\@nil{\def\f@encoding{#1}%
                                    \def\f@family{#2}%
                                    \def\f@series{#3}%
                                    \def\f@shape{#4}%
                                    \def\f@size{#5}}}
```

(*End definition for* \split@name.)

\curr@fontshape

Abbreviation which may get removed again for speed.

```
\def\curr@fontshape{\f@encoding/\f@family/\f@series/\f@shape}
```

(*End definition for* \curr@fontshape.)

\define@newfont

Now we can tackle the problem of defining a new font.

```
\def\define@newfont{%
```

We have already mentioned that the token list that \split@name will get as argument must not start with a backslash. To reach this goal we will set the \escapechar to -1 so that the \string primitive will not generate an escape character. To keep this change local we open a group. We use \begingroup for this purpose since \define@newfont might be called in math mode, and an empty \bgroup…\egroup would add an empty Ord atom to the math list and thus affect the spacing.

Also locally redefine \typeout so that 'No file ...fd' Warnings become Font Info message just sent to the log file.

```
  \begingroup
    \let\typeout\@font@info
    \escapechar\m@ne
```

Then we extract *encoding scheme*, *family*, *series*, *shape*, and *size* from the font name. Note the four \expandafter's so that \font@name is expanded first, then \string, and finally \split@name.

```
    \expandafter\expandafter\expandafter
       \split@name\expandafter\string\font@name\@nil
```

If the \curr@fontshape combination is not available, (i.e. undefined) we call the macro \wrong@fontshape to take care of this case. Otherwise \extract@font will load the external font for us.

```
%    \expandafter\ifx
%        \csname\curr@fontshape\endcsname \relax
      \try@load@fontshape % try always
%    \fi
    \expandafter\ifx
       \csname\curr@fontshape\endcsname \relax
      \wrong@fontshape\else
```

To allow substitution we call the `curr@fontshape` macro which usually will expand to `\relax` but may hold code for substitution (see `\subst@fontshape` definition).

```
%       \csname\curr@fontshape\endcsname
       \extract@font\fi
```

We are nearly finished and must only restore the `\escapechar` by closing the group.

```
  \endgroup}
```

```
\def\try@load@fontshape{%
   \expandafter
   \ifx\csname \f@encoding+\f@family\endcsname\relax
     \@font@info{Trying to load font information for
                    \f@encoding+\f@family}%
```

We predefine this combination to be `\@empty` which means that next time we don't try again unnecessary in case we don't find a `.fd` file. If the file contains a `\DeclareFontFamily` command than this setting will be overwritten.

```
     \global\expandafter\let
        \csname\f@encoding+\f@family\endcsname\@empty
```

Set the catcodes used in the syntax, but do it only once (this will be restored at the end of the font loading group).

```
      \nfss@catcodes
      \let\nfss@catcodes\relax
```

For increased portability make the external filename monocase, but look for the (old style) mixed case filename if the first attempt fails.

On any monocase system this means that the file is looked for twice which takes up time and string space, but at least for this release Check for both names to give people time to re-install their private fd files with lowercase names.

```
      \edef\reserved@a{%
        \lowercase{%
          \noexpand\InputIfFileExists{\f@encoding\f@family.fd}}}%
      \reserved@a\relax
           {\@input@{\f@encoding\f@family.fd}}%
   \fi}
```

(*End definition for* `\define@newfont`.)

`\nfss@catcodes` This macro should contain the standard `\catcode` assignments to all characters which are used in the commands found in an `.fd` file and which might have special `\catcode`s in the middle of a document. If necessary, this list can be extended in a package file using a suitable number of `\expandafter`, i.e.,

```
\expandafter\def\expandafter\nfss@catcodes
      \expandafter{\nfss@catcodes <additional settings>}
```

Note, that this macro might get executed several times since it is also called by `\DeclareFontShape`, thus it probably should not be misused as a general purpose hook.

```
\def\nfss@catcodes{%
```

We start by making `@` a letter and ignoring all blanks and newlines.

```
      \makeatletter
      \catcode`\ 9%
      \catcode`\^^I9%
      \catcode`\^^M9%
```

Then we set up \, {, }, # and % in case an .fd file is loaded during a verbatim environment.

```
    \catcode`\\\z@
    \catcode`\{\@ne
    \catcode`\}\tw@
    \catcode`\#6%
    \catcode`\^7%
    \catcode`\%14%
```

The we make sure that the important syntax parts have the right \catcode.

```
  \@makeother\<%
  \@makeother\>%
  \@makeother\*%
  \@makeother\.%
  \@makeother\-%
  \@makeother\/%
  \@makeother\[%
  \@makeother\]%
  \@makeother\`%
  \@makeother\'%
  \@makeother\"%
}
```

(*End definition for* \nfss@catcodes.)

\LoadFontDefinitionFile Load and .fd files for some encoding and family (if it exists).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\LoadFontDefinitionFile}{Loading .fd files}%
\def\LoadFontDefinitionFile#1#2{%
  \begingroup
    \edef\f@encoding{#1}%
    \edef\f@family{#2}%
    \try@load@fontshape
  \endgroup
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\LoadFontDefinitionFile}{Loading .fd files}%
⟨latexrelease⟩
⟨latexrelease⟩\let\LoadFontDefinitionFile\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \LoadFontDefinitionFile.)

\DeclareFontFamilySubstitution The idea for this macro is stolen from the substitutefont package by Günter Milde, with some modifications and a new name.

Its purpose is to provide characters in a special encoding that are not available in the current font family to be taken from a different family that is visually compatible (or not if you choose badly). For example, you can match the GFS Didot Greek characters with TEX Gyre Pagella (Palatino) by specifying

```
\DeclareFontFamilySubstitution{LGR}{qpl}{udidot}
```

This way if you ask for the `LGR` encoding in for the `qpl` family you get the characters from the `udidot` family substituted.

We need to ensure that the macro is defined with `\nfss@catcodes` in force (not quite sure why at the moment to be honest).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩        {\DeclareFontFamilySubstitution}{Provide family substitution}%
\begingroup
\nfss@catcodes
\gdef\DeclareFontFamilySubstitution#1#2#3{%
```

We only provide a set of silent substitutions. The package also (re)declared the family, but this is incorrect in my eyes and it is better to handle that differently.

Of course the families may still need loading at this point and so we arrange for this. Otherwise we might run into trouble because the necessary `\DeclareFontFamily` has not been seen.

```
    \LoadFontDefinitionFile{#1}{#2}%
    \LoadFontDefinitionFile{#1}{#3}%
```

```
    \DeclareFontShape{#1}{#2}{m}{it}{<->ssub * #3/m/it}{}%
    \DeclareFontShape{#1}{#2}{m}{n}{<->ssub * #3/m/n}{}%
    \DeclareFontShape{#1}{#2}{m}{sc}{<->ssub * #3/m/sc}{}%
    \DeclareFontShape{#1}{#2}{m}{sl}{<->ssub * #3/m/sl}{}%
```

These days a few more shapes might be around, so we declare those too. If they don't exist then after the first substitution normal fallbacks will happen.

```
    \DeclareFontShape{#1}{#2}{m}{sw}{<->ssub * #3/m/sw}{}%
    \DeclareFontShape{#1}{#2}{m}{scit}{<->ssub * #3/m/scit}{}%
    \DeclareFontShape{#1}{#2}{m}{scsl}{<->ssub * #3/m/scsl}{}%
```

Same game with `b` and `bx`, for other weights you are on your own:

```
    \DeclareFontShape{#1}{#2}{b}{it}{<->ssub * #3/b/it}{}%
    \DeclareFontShape{#1}{#2}{b}{n}{<->ssub * #3/b/n}{}%
    \DeclareFontShape{#1}{#2}{b}{scit}{<->ssub * #3/b/scit}{}%
    \DeclareFontShape{#1}{#2}{b}{scsl}{<->ssub * #3/b/scsl}{}%
    \DeclareFontShape{#1}{#2}{b}{sc}{<->ssub * #3/b/sc}{}%
    \DeclareFontShape{#1}{#2}{b}{sl}{<->ssub * #3/b/sl}{}%
    \DeclareFontShape{#1}{#2}{b}{sw}{<->ssub * #3/b/sw}{}%
    \DeclareFontShape{#1}{#2}{bx}{it}{<->ssub * #3/bx/it}{}%
    \DeclareFontShape{#1}{#2}{bx}{n}{<->ssub * #3/bx/n}{}%
    \DeclareFontShape{#1}{#2}{bx}{scit}{<->ssub * #3/bx/scit}{}%
    \DeclareFontShape{#1}{#2}{bx}{scsl}{<->ssub * #3/bx/scsl}{}%
    \DeclareFontShape{#1}{#2}{bx}{sc}{<->ssub * #3/bx/sc}{}%
    \DeclareFontShape{#1}{#2}{bx}{sl}{<->ssub * #3/bx/sl}{}%
    \DeclareFontShape{#1}{#2}{bx}{sw}{<->ssub * #3/bx/sw}{}%
}
\endgroup
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩        {\DeclareFontFamilySubstitution}{Provide family substitution}%
⟨latexrelease⟩
```

```
⟨latexrelease⟩\let\DeclareFontFamilySubstitution\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\DeclareFontFamilySubstitution`.)

`\DeclareErrorFont` Declare the last resort shape! We assume that in this fontshape there is a 10pt font but it doesn't really matter. We only loose one macro name if the assumption is false. But at least the font should be there!

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\DeclareErrorFont}{No side effects please}%
\def\DeclareErrorFont#1#2#3#4#5{%
      \xdef\error@fontshape{%
          \noexpand\expandafter\noexpand\split@name\noexpand\string
          \expandafter\noexpand\csname#1/#2/#3/#4/#5\endcsname
          \noexpand\@nil}%
```

Initialize all those internal variables which may or may not have values in the first seconds of NFSS' bootstrapping process. Later on such values will be updated when an encoding is selected, etc.

We definitely don't want to set `\f@encoding`; we can set all the others since if they are left "blank" any selection would grab "error default values" as well. However, this probably should go also—and now it did.

```
%       \gdef\f@encoding{#1}%
      \gdef\default@family{#2}%
      \gdef\default@series{#3}%
      \gdef\default@shape{#4}%
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\DeclareErrorFont}{No side effects please}%
⟨latexrelease⟩
⟨latexrelease⟩\def\DeclareErrorFont#1#2#3#4#5{%
⟨latexrelease⟩      \xdef\error@fontshape{%
⟨latexrelease⟩          \noexpand\expandafter\noexpand\split@name\noexpand\string
⟨latexrelease⟩          \expandafter\noexpand\csname#1/#2/#3/#4/#5\endcsname
⟨latexrelease⟩          \noexpand\@nil}%
⟨latexrelease⟩      \gdef\default@family{#2}%
⟨latexrelease⟩      \gdef\default@series{#3}%
⟨latexrelease⟩      \gdef\default@shape{#4}%
⟨latexrelease⟩      \global\let\f@family\default@family
⟨latexrelease⟩      \global\let\f@series\default@series
⟨latexrelease⟩      \global\let\f@shape\default@shape
⟨latexrelease⟩      \gdef\f@size{#5}%
⟨latexrelease⟩      \gdef\f@baselineskip{#5pt}%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\DeclareErrorFont
```

(*End definition for* `\DeclareErrorFont`.)

\wrong@fontshape Before we come to the macro \extract@font we have to take care of unknown \curr@fontshape combinations. The general strategy is to issue a warning and to try a default *shape*, then a default *series*, and finally a default *family*. If this last one also fails TEX will go into an infinite loop. But if the defaults are set incorrectly one deserves nothing else!

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\wrong@fontshape}%
⟨latexrelease⟩                  {Font substitution in preamble}%
⟨*2ekernel | latexrelease⟩
\def\wrong@fontshape{%
    \csname D@\f@encoding\endcsname   % install defaults if in math
```

We remember the wanted \curr@fontshape combination which we will need in a moment.

```
    \edef\reserved@a{\csname\curr@fontshape\endcsname}%
  \ifx\last@fontshape\reserved@a
     \errmessage{Corrupted NFSS tables}%
     \error@fontshape
  \else
```

Then we warn the user about the mess and set the shape to its default.

```
    \let\f@shape\default@shape
```

If the combination is not known, try the default *series*.

```
    \expandafter\ifx\csname\curr@fontshape\endcsname\relax
       \let\f@series\default@series
```

If this is still undefined, try the default *family*. Otherwise give up. We never try to change the encoding scheme!

```
         \expandafter
           \ifx\csname\curr@fontshape\endcsname\relax
            \let\f@family\default@family
```

If we change the font family and we are in the preamble then the corresponding .fd file may not been loaded yet. Therefore we try this now. Otherwise equating the requested font shape with the finally selected fontshape below will fail and can result in "NFSS tables corrupted". After begin document that will not happen as all .fd files involved in substitution are loaded at \begin{document}.

```
            \begingroup
               \try@load@fontshape
            \endgroup
         \fi \fi
  \fi
```

At this point a valid \curr@fontshape combination must have been found. We inform the user about this fact.

The \expandafter\string here stops TEX adding the space that it usually puts after command names in messages. The similar construction with \@undefined just produces 'undefined', but saves a few tokens.

\@wrong@font@char is locally redefined in \UseTextSymbol from its normal (empty) definition, to report the symbol generating the font switch.

```
     \@font@warning{Font shape `\expandafter\string\reserved@a'
                       \expandafter\@gobble\string\@undefined\MessageBreak
                    using `\curr@fontshape' instead\@wrong@font@char}%
    \global\let\last@fontshape\reserved@a
```

We change \@defaultsubs to produce a warning at the end of the document. The macro \@defaultsubs is initially \relax but gets changed here if some default font substitution happens. It is then executed in \enddocument.

```
    \gdef\@defaultsubs{%
      \@font@warning{Some font shapes were not available, defaults
                     substituted.\@gobbletwo}}%
```

If we substitute a \curr@fontshape combination by the default one we don't want the warning to be printed out whenever this (unknown) combination is used. Therefore we globally \let the macro corresponding to the wanted combination equal to its substitution. This requires the use of four \expandafter's since \csname...\endcsname has to be expanded before \reserved@a (i.e. the requested combination), and this must happen before the \let is executed.

```
    \global\expandafter\expandafter\expandafter\let
       \expandafter\reserved@a
           \csname\curr@fontshape\endcsname
```

Now we can redefine \font@name accordingly. This *must* be done globally since it might occur in the group opened by \define@newfont. If we would this definition were local the closing \endgroup there would restore the old meaning of \font@name and then switch to the wrong font at the end of \selectfont although the correct font was loaded.

```
    \xdef\font@name{%
      \csname\curr@fontshape/\f@size\endcsname}%
```

The last thing this macro does is to call \pickup@font again to load the font if it is not defined yet. At this point this code will loop endlessly if the defaults are not well defined.

```
    \pickup@font}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\wrong@fontshape}%
⟨latexrelease⟩                 {Font substitution in preamble}%
⟨latexrelease⟩\def\wrong@fontshape{%
⟨latexrelease⟩    \csname D@\f@encoding\endcsname
⟨latexrelease⟩    \edef\reserved@a{\csname\curr@fontshape\endcsname}%
⟨latexrelease⟩  \ifx\last@fontshape\reserved@a
⟨latexrelease⟩     \errmessage{Corrupted NFSS tables}%
⟨latexrelease⟩     \error@fontshape
⟨latexrelease⟩  \else
⟨latexrelease⟩    \let\f@shape\default@shape
⟨latexrelease⟩    \expandafter\ifx\csname\curr@fontshape\endcsname\relax
⟨latexrelease⟩       \let\f@series\default@series
⟨latexrelease⟩        \expandafter
⟨latexrelease⟩          \ifx\csname\curr@fontshape\endcsname\relax
⟨latexrelease⟩           \let\f@family\default@family
⟨latexrelease⟩        \fi \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩     \@font@warning{Font shape
⟨latexrelease⟩            `\expandafter\string\reserved@a'
⟨latexrelease⟩            \expandafter\@gobble\string\@undefined
⟨latexrelease⟩            \MessageBreak
⟨latexrelease⟩            using `\curr@fontshape' instead\@wrong@font@char}%
⟨latexrelease⟩    \global\let\last@fontshape\reserved@a
⟨latexrelease⟩    \gdef\@defaultsubs{%
⟨latexrelease⟩      \@font@warning{Some font shapes were not available,
```

```
⟨latexrelease⟩                        defaults substituted.\@gobbletwo}}%
⟨latexrelease⟩     \global\expandafter\expandafter\expandafter\let
⟨latexrelease⟩        \expandafter\reserved@a
⟨latexrelease⟩            \csname\curr@fontshape\endcsname
⟨latexrelease⟩     \xdef\font@name{%
⟨latexrelease⟩       \csname\curr@fontshape/\f@size\endcsname}%
⟨latexrelease⟩     \pickup@font}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\wrong@fontshape`.)

`\@wrong@font@char` Normally empty but redefined in `\UseTextSymbol` so that the Font shape undefined message can refer to the symbol causing the problem.

```
\let\@wrong@font@char\@empty
```

(*End definition for* `\@wrong@font@char`.)

`\@@defaultsubs` `\@defaultsubs` See above.

```
\let\@defaultsubs\relax
```

(*End definition for* `\@@defaultsubs` *and* `\@defaultsubs`.)

`\strip@prefix` In `\extract@font` we will need a way to recover the replacement text of a macro. This is done by the primitive `\meaning` together with the macro `\strip@prefix` (for the details see appendix D of the TEXbook, p. 382).

```
\def\strip@prefix#1>{}
```

(*End definition for* `\strip@prefix`.)

4 Assigning math fonts to *versions*

`\install@mathalphabet` This is just another name for `\gdef` but we can redefine it if necessary later on.

```
\let\install@mathalphabet\gdef
```

(*End definition for* `\install@mathalphabet`.)

`\math@fonts`

```
\let\math@fonts\@empty
```

(*End definition for* `\math@fonts`.)

`\select@group` `\select@group` has four arguments: the new ⟨*math alphabet identifier*⟩ (a control sequence), the ⟨*math group number*⟩, the extra macro for math mode and the `\curr@fontshape` definition macro name. We first check if we are in math mode.

```
%\def\select@group#1#2#3{\relax\ifmmode
```

We do these things locally using `\begingroup` instead of `\bgroup` to avoid the appearance of an empty Ord atom on the math list.

```
%  \begingroup
```

We set the math fonts for the *family* in question by calling `\getanddefine@fonts` in the correct environment.

```
%     \escapechar\m@ne
%    \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
```

We globally select the math fonts...

```
%    \globaldefs\@ne  \math@fonts
```

... and close the group to restore `\globaldefs` and `\escapechar`.

```
%  \endgroup
```

As long as no *size* or *version* change occurs the ⟨*math alphabet identifier*⟩ should simply switch to the installed *math group* instead of calling `\select@group` unnecessarily. So we globally redefine the first argument (the new ⟨*math alphabet identifier*⟩) to expand into a `\mathgroup` switch and then select this *alphabet*. Note that this redefinition will be overwritten by the next call to a *version* macro. The original code for the end of `\select@group` was

```
\gdef#1{#3\mathgroup #2}#1\fi}
```

i.e. first redefining the ⟨*math alphabet identifier*⟩ and then calling the new definition to switch to the wanted ⟨*math group*⟩. Now we define the ⟨*math alphabet identifier*⟩ as a call to the `\use@mathgroup` command.

```
%  \xdef#1{\noexpand\use@mathgroup\noexpand#2%
%          {\number\csname c@mv@\math@version\endcsname}}%
```

But this is not sufficient, as we learned the hard way. The problem here is that the loading of the fonts that comprise the alphabet identifier `#1`, as well as the necessary math font assignments is deferred until it is used. This is OK so far, but if the fonts are switched within the current formula (which may happen if a sub-formula is a box that contains a math version switch) the font assignments for `#1` are not restored unless `#1` is used again. This is disastrous since TeX sees the wrong fonts at the end of the math formula, when it converts the math list into a horizontal list.

This is taken into account as follows: When a math alphabet identifier is used for the first time in a certain version it modifies the corresponding macro `\mv@`⟨*version*⟩ so that it calls `\getanddefine@fonts` directly in future as well. We use the macro `\extract@alph@from@version` to do this. It takes the math alphabet identifier `#1` and the math version macro as arguments.

```
%     \expandafter\extract@alph@from@version
%        \csname mv@\math@version\expandafter\endcsname
%       \expandafter{\number\csname c@mv@\math@version\endcsname}%
%       #1%
%     \stepcounter{mv@\math@version}%
```

Finally, it is not possible to simply call the new definition since we have an argument (the third argument of `\use@mathgroup` or more exactly the argument of `\math@egroup` if the `margid` option is in force) which would swallow our closing `\fi`. So we use the `\expandafter` technique to remove the `\fi` before the `\use@mathgroup` is expanded.

```
%\expandafter #1\fi}
```

(*End definition for* `\select@group`.)

\extract@alph@from@version

We proceed to the definition of the macro \extract@alph@from@version. As stated above, it takes a math alphabet identifier and a math version macro (e.g. \mv@normal) as its arguments.

```
\def\extract@alph@from@version#1#2#3{%
```

To extract and replace the definition of math alphabet identifier #3 in macro #1 we have to recall how this definition looks like: Somewhere in the replacement text of #1 there is the sequence

\install@mathalphabet⟨*math alphabet identifier*⟩ #3{%
⟨*Definitions for* ⟩#3}

Hence, the first thing we do is to extract the tokens preceding this definitions, the definition itself, and the tokens following it. To this end we define one auxiliary macro \reserved@a.

```
    \def\reserved@a##1\install@mathalphabet#3##2##3\@nil{%
```

When \reserved@a is expanded, it will have the tokens preceding the definition in question in its first argument (##1), the following tokens in its third argument (##3), and the replacement text for the math alphabet identifier #3 in its second argument. (##2). This is then recorded for later use in a temporary macro \reserved@b.

```
        \def\reserved@b{##2}%
```

Additionally, we define a macro \reserved@c to reconstruct the definitions for the math version in question from the tokens that will remain unchanged (##1 and ##3) and the yet to build new definitions for the math alphabet identifier #3.

```
        \def\reserved@c####1{\gdef#1{##1####1##3}}}%
```

Then we execute our auxiliary macro.

```
    \expandafter\reserved@a#1\@nil
```

OK, so now we have to build the new definition for #3. To do so, we first extract the interesting parts out of the old one. The old definition looks like:

\select@group⟨*math alphabet identifier*⟩
⟨*math group number*⟩⟨*math extra part*⟩
⟨*curr@fontshape definition*⟩

So we define a new temporary macro \reserved@a that extracts these parts.

```
    \def\reserved@a\select@group#3##1##2\@nil{%
```

This macro can now directly rebuild the math version definition by calling \reserved@c:

```
        \reserved@c{%
           \getanddefine@fonts{#2}##2%
           \install@mathalphabet#3{%
              \relax\ifmmode \else \non@alpherr#3\fi
              \use@mathgroup##1{#2}}}%
```

In addition it defines the alphabet the way it should be used from now on.

```
       \gdef#3{\relax\ifmmode \else \non@alpherr#3\fi
               \use@mathgroup##1{#2}}}%
```

Finally, we only have to call this macro \reserved@a on the old definitions recorded in \reserved@b:

```
    \expandafter\reserved@a\reserved@b\@nil
    }
```

(*End definition for* \extract@alph@from@version.)

\math@bgroup
\math@egroup

Here are the default definitions for \math@bgroup and \math@egroup. We use \bgroup instead of \begingroup to avoid 'leaking out' of style changes. This has the side effect of always producing mathord atoms.

```
\let\math@bgroup\bgroup
\def\math@egroup#1{#1\egroup}
```

(*End definition for* \math@bgroup *and* \math@egroup.)

\calculate@math@sizes

Here is the default definition for \calculate@math@sizes a more elaborate interface is under testing in mthscale.sty.

```
\gdef\calculate@math@sizes{%
  \@font@info{Calculating\space math\space sizes\space for\space
              size\space <\f@size>}%
  \dimen@\f@size \p@
  \@tempdimb \defaultscriptratio \dimen@
  \dimen@ \defaultscriptscriptratio \dimen@
  \expandafter\xdef\csname S@\f@size\endcsname{%
    \gdef\noexpand\tf@size{\f@size}%
    \gdef\noexpand\sf@size{\strip@pt\@tempdimb}%
    \gdef\noexpand\ssf@size{\strip@pt\dimen@}%
    \noexpand\math@fontstrue}}
```

(*End definition for* \calculate@math@sizes.)

\defaultscriptratio
\defaultscriptscriptratio

The default ratio for math sizes is:
1 to \defaultscriptratio to \defaultscriptscriptratio.
By default this is 1 to .7 to .5.

```
\def\defaultscriptratio{.7}
\def\defaultscriptscriptratio{.5}
```

(*End definition for* \defaultscriptratio *and* \defaultscriptscriptratio.)

\noaccents@

If we don't have a definition for \noaccents@ we provide a dummy.

```
\ifx\noaccents@\@undefined
  \let\noaccents@\@empty
\fi
```

(*End definition for* \noaccents@.)

\showhyphens

The \showhyphens command must be redefined since the version in plain.tex uses \tenrm. We have also made some further adjustments for its use in LaTeX.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2017/01/01}{\showhyphens}%
⟨latexrelease⟩                  {XeTeX support for \showhyphens}%
⟨*2ekernel | latexrelease⟩
\ifx\XeTeXcharclass\@undefined
```

Version for engines other than XeTeX.

```
\DeclareRobustCommand\showhyphens[1]{%
  \setbox0\vbox{%
    \color@begingroup
    \everypar{}%
    \parfillskip\z@skip\hsize\maxdimen
    \normalfont
    \pretolerance\m@ne\tolerance\m@ne\hbadness\z@\showboxdepth\z@\ #1%
    \color@endgroup}}
```

```
\else
```

XeTEX version. When using system fonts XeTEX reports consecutive runs of characters as a single item in box logging, which means the standard `\showhyphens` does not work. This version typesets the text into a narrow box to force hyphenation and then reconstructs a horizontal list with explicit hyphens to generate the display. Note that the `lmr` OpenType font is forced, this works even if the characters are not in the font as hyphenation is attempted due to the width of the space and hyphen character. It may generate spurious Missing Character warnings in the log, these are however suppressed from the terminal output by ensuring that `\tracingonline` is locally zero.

```
\DeclareRobustCommand\showhyphens[1]{%
  \setbox0\vbox{%
    \usefont{TU}{lmr}{m}{n}%
    \hsize 1sp %
    \hbadness\@M
    \hfuzz\maxdimen
    \tracingonline\z@
    \everypar={}%
    \leftskip\z@skip
    \rightskip\z@skip
    \parfillskip\z@skip
    \hyphenpenalty=-\@M
    \pretolerance\m@ne
    \interlinepenalty\z@
    \clubpenalty\z@
    \widowpenalty\z@
    \brokenpenalty1127 %
    \setbox\z@\hbox{}%
    \noindent
    \hskip\z@skip
    #1%
    \par
```

Note here we stop the loop if made no progress, non-removable items may mean that we can not process the whole list (which would be testable as `\lastnodetype=-1`).

```
     \loop
     \@tempswafalse
     \ifnum\lastnodetype=11\unskip\@tempswatrue\fi
     \ifnum\lastnodetype=12\unkern\@tempswatrue\fi
     \ifnum\lastnodetype=13 %
      \count@\lastpenalty
      \unpenalty\@tempswatrue
    \fi
    \ifnum\lastnodetype=\@ne
     \setbox\tw@\lastbox\@tempswatrue
     \setbox0\hbox{\unhbox\tw@\unskip\unskip\unpenalty
                   \ifnum\count@=1127 \else\ \fi
                   \unhbox0}%
     \count@\z@
    \fi
    \if@tempswa
    \repeat
   \hbadness\z@
   \hsize\maxdimen
```

```
   \showboxdepth\z@
   \tolerance\m@ne
   \hyphenpenalty\z@
   \noindent\unhbox\z@
}}
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\showhyphens}%
⟨latexrelease⟩                  {XeTeX support for \showhyphens}%
⟨latexrelease⟩\gdef\showhyphens#1{%
⟨latexrelease⟩  \setbox0\vbox{%
⟨latexrelease⟩    \color@begingroup
⟨latexrelease⟩    \everypar{}%
⟨latexrelease⟩    \parfillskip\z@skip\hsize\maxdimen
⟨latexrelease⟩    \normalfont
⟨latexrelease⟩    \pretolerance\m@ne\tolerance\m@ne
⟨latexrelease⟩    \hbadness\z@\showboxdepth\z@\ #1%
⟨latexrelease⟩    \color@endgroup}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\showhyphens`.)

`\addto@hook` We need a macro to add tokens to a hook.

```
\long\def\addto@hook#1#2{#1\expandafter{\the#1#2}}
```

(*End definition for* `\addto@hook`.)

`\@vpt`

```
  \def\@vpt{5}
```

(*End definition for* `\@vpt`.)

`\@vipt`

```
  \def\@vipt{6}
```

(*End definition for* `\@vipt`.)

`\@viipt`

```
  \def\@viipt{7}
```

(*End definition for* `\@viipt`.)

`\@viiipt`

```
  \def\@viiipt{8}
```

(*End definition for* `\@viiipt`.)

`\@ixpt`

```
  \def\@ixpt{9}
```

(*End definition for* `\@ixpt`.)

\@xpt

```
\def\@xpt{10}
```

(*End definition for* `\@xpt`.)

\@xipt

```
\def\@xipt{10.95}
```

(*End definition for* `\@xipt`.)

\@xiipt

```
\def\@xiipt{12}
```

(*End definition for* `\@xiipt`.)

\@xivpt

```
\def\@xivpt{14.4}
```

(*End definition for* `\@xivpt`.)

\@xviipt

```
\def\@xviipt{17.28}
```

(*End definition for* `\@xviipt`.)

\@xxpt

```
\def\@xxpt{20.74}
```

(*End definition for* `\@xxpt`.)

\@xxvpt

```
\def\@xxvpt{24.88}
```

(*End definition for* `\@xxvpt`.)

⟨/2ekernel⟩

File w
ltfssaxes.dtx

This file contains the implementation for handling extra axes splitting the series and the values into sub-categories. selection commands. See other parts of the LaTeX distribution, or *The LaTeX Companion* for higher level documentation of the LaTeX Font Selection Scheme.

Everything in the this file got introduced 2020/02/02, so we use large rollback chunks, only interrupted if necessary.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩    {\DeclareFontSeriesChangeRule}{Series change rules}%
```

1 Changing the font series

In the original NFSS implementation the series was a single attribute stored in `\f@series` and so one always had to specify both weight and width together. This means it was impossible to typeset, a paragraph in a condensed font and inside have a few words in bold weight (but still condensed) without doing this manually by requesting `\fontseries{bc}\selectfont`.

The new implementation now works differently by looking both at the current value of `\f@series` and the requested new series and out of that combination selects a resulting series value. Thus, if the current series is `c` and we ask for `b` we now get `bc`.

This is done by consulting a simple lookup table. This table is configurable (though most likely that flexibility will seldom of ever be needed) Adding or changing entries in this table are done with `\DeclareFontSeriesChangeRule`.

1.1 The series lookup table

`\DeclareFontSeriesChangeRule`

The `\DeclareFontSeriesChangeRule` defines entries in a simple database (implemented as a set of commands) that define mappings between from an existing series and requested new series and maps that to a result series (and additionally offers an alternative if the desired one is not existing):

- `#1` current `\f@series`
- `#2` requested new series
- `#3` result (if that exist for the given font family
- `#4` alternative result (if `#3` does not exist)

If an `.fd` file has its own substitution rules then `#3` exist and thus `#4` is not applied.

If there is no matching database entry or if neither the result nor the alternate result exist in the font family the requested new series is used (which then may trigger substitutions later on.

```
\def\DeclareFontSeriesChangeRule#1#2#3#4{%
  \@namedef{series@#1@#2}{{#3}{#4}}}
```

(*End definition for* `\DeclareFontSeriesChangeRule`.)

1.2 Mapping rules for series changes

The rules set up use explicit series values not `\..default` indirections; my current feeling is that this is in fact better.

With 9 weights and 9 width classes this table is getting a bit large in the end (324 entries) but on the other hand it doesn't change and accessing speed and it is fast this way.

We could alternatively split the axis and maintain weight and width separately, but that would take more processing time and would not allow for setting up explicit exceptions nicely (not sure that this would ever get used though).

Design considerations for mapping entries:

- We make `m` to reset both weight and width (as this is how it always worked). To reset just the width `?m` is provided and to reset just the weight `m?`.
- We do support "`m`*width*" and "*weight*`m`", e.g., `mec` to mean "go to medium weight and extra-condensed width". At the end of the process we automatically drop any leftover `m` in the series name (unless it is just a single `m`).
- If there is no table entry then the target series is used unconditionally. This means that any request to set both weight and width (e.g. `bx` or `ulc`) needs no table entries. For that reason there are no entries which have a weight+width as request (i.e., second argument).

  In particular this is also true for cases involving `m`, e.g., `bm` (bold medium width) which automatically gets reduced result in `b` or `mc` (medium weight condensed) which becomes `c` as a result.
- Only a few entries have "alternative" values and perhaps most of them should get dropped. Or maybe not ... needs some thought perhaps.

  The idea is that you don't want the normal substitution to kick in because that would reset the shape first and it may be better to stay with `b` when a change to `c` is requested and `bc` doesn't exist, than to go to first change the shape to `n` and then find that `bc/n` doesn't exist either and thus ending up with `m/n`.
- Also: while I did set up all nine standard weight values from `ul` to `ub` I only bothered to provide entries for `ec`, `sc`, `c` and `x`, because other levels of compression/expansion are not in any real fonts that I know.

  Could and perhaps should be eventually extended to cover the whole set.

```
\DeclareFontSeriesChangeRule {bc}{b}{bc}{}
\DeclareFontSeriesChangeRule {bc}{c}{bc}{}
\DeclareFontSeriesChangeRule {bc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {bc}{ec}{bec} {bc}
\DeclareFontSeriesChangeRule {bc}{el}{elc}{}
\DeclareFontSeriesChangeRule {bc}{l}{lc}{}
\DeclareFontSeriesChangeRule {bc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {bc}{sc}{bsc} {bc}
\DeclareFontSeriesChangeRule {bc}{sl}{slc}{}
\DeclareFontSeriesChangeRule {bc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {bc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {bc}{x}{bx}{}
```

```
\DeclareFontSeriesChangeRule {bx}{b}{bx}{}
\DeclareFontSeriesChangeRule {bx}{c}  {bc}  {bx} %<-----
\DeclareFontSeriesChangeRule {bx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {bx}{ec}  {bec}  {bx} %<-----
\DeclareFontSeriesChangeRule {bx}{el}{elx}{}
\DeclareFontSeriesChangeRule {bx}{l}{lx}{}
\DeclareFontSeriesChangeRule {bx}{sb} {sbx} {}
\DeclareFontSeriesChangeRule {bx}{sc}  {bsc}  {bx} %<-----
\DeclareFontSeriesChangeRule {bx}{sl}{slx}  {}
\DeclareFontSeriesChangeRule {bx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {bx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {bx}{x}{bx}{}

\DeclareFontSeriesChangeRule {b}{bx} {bx}  {b} %<-----
\DeclareFontSeriesChangeRule {b}{c}  {bc}  {b} %<-----
\DeclareFontSeriesChangeRule {b}{ec}  {bec}  {b} %<-----
\DeclareFontSeriesChangeRule {b}{sb} {sb}  {b} %<-----
\DeclareFontSeriesChangeRule {b}{sc}  {bsc}  {b} %<-----
\DeclareFontSeriesChangeRule {b}{x}  {bx}  {b} %<-----

\DeclareFontSeriesChangeRule {c}{bx} {bx}  {b}  %<-----
\DeclareFontSeriesChangeRule {c}{b}{bc}{}
\DeclareFontSeriesChangeRule {c}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {c}{el}{elc}{}
\DeclareFontSeriesChangeRule {c}{l}{lc}{}
\DeclareFontSeriesChangeRule {c}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {c}{sl}{slc}{}
\DeclareFontSeriesChangeRule {c}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {c}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {c}{x}{x}{m}               %<-----

\DeclareFontSeriesChangeRule {ebc}{b}{bc}{}
\DeclareFontSeriesChangeRule {ebc}{c}{ebc}{}
\DeclareFontSeriesChangeRule {ebc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {ebc}{ec}{ebec}{ebc}
\DeclareFontSeriesChangeRule {ebc}{el}{elc}{}
\DeclareFontSeriesChangeRule {ebc}{l}{lc}{}
\DeclareFontSeriesChangeRule {ebc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {ebc}{sc}{ebsc}{ebc}
\DeclareFontSeriesChangeRule {ebc}{sl}{slc}{}
\DeclareFontSeriesChangeRule {ebc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {ebc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {ebc}{x}{ebx}{}

\DeclareFontSeriesChangeRule {ec}{bx} {bx}  {b}  %<-----
\DeclareFontSeriesChangeRule {ec}{b}{bec}{}
\DeclareFontSeriesChangeRule {ec}{eb}{ebec}{}
\DeclareFontSeriesChangeRule {ec}{el}{elec}{}
\DeclareFontSeriesChangeRule {ec}{l}{lec}{}
\DeclareFontSeriesChangeRule {ec}{sb}{sbec}{}
\DeclareFontSeriesChangeRule {ec}{sl}{slec}{}
\DeclareFontSeriesChangeRule {ec}{ub}{ubec}{}
\DeclareFontSeriesChangeRule {ec}{ul}{ulec}{}
\DeclareFontSeriesChangeRule {ec}{x}{x}{m}              %<-----

\DeclareFontSeriesChangeRule {sc}{bx} {bx}  {b}  %<-----
\DeclareFontSeriesChangeRule {sc}{b}{bsc}{}
```

```
\DeclareFontSeriesChangeRule {sc}{eb}{ebsc}{}
\DeclareFontSeriesChangeRule {sc}{el}{elsc}{}
\DeclareFontSeriesChangeRule {sc}{l}{lsc}{}
\DeclareFontSeriesChangeRule {sc}{sb}{sbsc}{}
\DeclareFontSeriesChangeRule {sc}{sl}{slsc}{}
\DeclareFontSeriesChangeRule {sc}{ub}{ubsc}{}
\DeclareFontSeriesChangeRule {sc}{ul}{ulsc}{}
\DeclareFontSeriesChangeRule {sc}{x}{x}{m}                %<-----

\DeclareFontSeriesChangeRule {ebx}{b}{bx}{}
\DeclareFontSeriesChangeRule {ebx}{c}{ebc}{}
\DeclareFontSeriesChangeRule {ebx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {ebx}{ec}{ebec}{}
\DeclareFontSeriesChangeRule {ebx}{el}{elx}{}
\DeclareFontSeriesChangeRule {ebx}{l}{lx}{}
\DeclareFontSeriesChangeRule {ebx}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {ebx}{sc}{ebsc}{}
\DeclareFontSeriesChangeRule {ebx}{sl}{slx}{}
\DeclareFontSeriesChangeRule {ebx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {ebx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {ebx}{x}{ebx}{}

\DeclareFontSeriesChangeRule {eb}{c}{ebc}{}
\DeclareFontSeriesChangeRule {eb}{ec}{ebec}{}
\DeclareFontSeriesChangeRule {eb}{sc}{ebsc}{}
\DeclareFontSeriesChangeRule {eb}{x}{ebx}{}

\DeclareFontSeriesChangeRule {elc}{b}{bc}{}
\DeclareFontSeriesChangeRule {elc}{c}{elc}{}
\DeclareFontSeriesChangeRule {elc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {elc}{ec}{elec}{}
\DeclareFontSeriesChangeRule {elc}{el}{elc}{}
\DeclareFontSeriesChangeRule {elc}{l}{lc}{}
\DeclareFontSeriesChangeRule {elc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {elc}{sc}{elsc}{}
\DeclareFontSeriesChangeRule {elc}{sl}{slc}{}
\DeclareFontSeriesChangeRule {elc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {elc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {elc}{x}{elx}{}

\DeclareFontSeriesChangeRule {elx}{b}{bx}{}
\DeclareFontSeriesChangeRule {elx}{c}{elc}{}
\DeclareFontSeriesChangeRule {elx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {elx}{ec}{elec}{}
\DeclareFontSeriesChangeRule {elx}{el}{elx}{}
\DeclareFontSeriesChangeRule {elx}{l}{lx}{}
\DeclareFontSeriesChangeRule {elx}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {elx}{sc}{elsc}{}
\DeclareFontSeriesChangeRule {elx}{sl}{slx}{}
\DeclareFontSeriesChangeRule {elx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {elx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {elx}{x}{elx}{}

\DeclareFontSeriesChangeRule {el}{c}{elc}{}
\DeclareFontSeriesChangeRule {el}{ec}{elec}{}
\DeclareFontSeriesChangeRule {el}{sc}{elsc}{}
\DeclareFontSeriesChangeRule {el}{x}{elx}{}
```

```
\DeclareFontSeriesChangeRule {lc}{b}{bc}{}
\DeclareFontSeriesChangeRule {lc}{c}{lc}{}
\DeclareFontSeriesChangeRule {lc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {lc}{ec}{lec}{}
\DeclareFontSeriesChangeRule {lc}{el}{elc}{}
\DeclareFontSeriesChangeRule {lc}{l}{lc}{}
\DeclareFontSeriesChangeRule {lc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {lc}{sc}{lsc}{}
\DeclareFontSeriesChangeRule {lc}{sl}{slc}{}
\DeclareFontSeriesChangeRule {lc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {lc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {lc}{x}{lx}{}

\DeclareFontSeriesChangeRule {lx}{b}{bx}{}
\DeclareFontSeriesChangeRule {lx}{c}{lc}{}
\DeclareFontSeriesChangeRule {lx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {lx}{ec}{lec}{}
\DeclareFontSeriesChangeRule {lx}{el}{elx}{}
\DeclareFontSeriesChangeRule {lx}{l}{lx}{}
\DeclareFontSeriesChangeRule {lx}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {lx}{sc}{lsc}{}
\DeclareFontSeriesChangeRule {lx}{sl}{slx}{}
\DeclareFontSeriesChangeRule {lx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {lx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {lx}{x}{lx}{}

\DeclareFontSeriesChangeRule {l}{bx} {bx}  {b} %<-----
\DeclareFontSeriesChangeRule {l}{b}  {b}   {bx} %<-----
\DeclareFontSeriesChangeRule {l}{c}  {lc}  {l}  % ? %<-----
\DeclareFontSeriesChangeRule {l}{ec}  {lec}  {l}  % ? %<-----
\DeclareFontSeriesChangeRule {l}{sb} {sb}  {b}  % ? %<-----
\DeclareFontSeriesChangeRule {l}{sc}  {lsc}  {l}  % ? %<-----
\DeclareFontSeriesChangeRule {l}{x}  {lx}  {l}  % ? %<-----

\DeclareFontSeriesChangeRule {m}{bx} {bx} {b}    %<-----
\DeclareFontSeriesChangeRule {m}{b}  {b}  {bx} %<-----
\DeclareFontSeriesChangeRule {m}{c}  {c}  {m} %<-----
\DeclareFontSeriesChangeRule {m}{ec}  {ec}  {m} %<-----
\DeclareFontSeriesChangeRule {m}{l}  {l}  {m} %<-----
\DeclareFontSeriesChangeRule {m}{sb} {sb} {b} %<-----
\DeclareFontSeriesChangeRule {m}{sc}  {sc}  {m} %<-----
\DeclareFontSeriesChangeRule {m}{x}  {x}  {m} %<-----

\DeclareFontSeriesChangeRule {sbc}{b}{bc}{}
\DeclareFontSeriesChangeRule {sbc}{c}{sbc}{}
\DeclareFontSeriesChangeRule {sbc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {sbc}{ec}{sbec}{sbc}
\DeclareFontSeriesChangeRule {sbc}{el}{elc}{}
\DeclareFontSeriesChangeRule {sbc}{l}{lc}{}
\DeclareFontSeriesChangeRule {sbc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {sbc}{sc}{sbsc}{sbc}
\DeclareFontSeriesChangeRule {sbc}{sl}{slc}{}
\DeclareFontSeriesChangeRule {sbc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {sbc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {sbc}{x}{sbx}{}

\DeclareFontSeriesChangeRule {sbx}{b}{bx}{}
```

```
\DeclareFontSeriesChangeRule {sbx}{c}{sbc}{}
\DeclareFontSeriesChangeRule {sbx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {sbx}{ec}{sbec}{}
\DeclareFontSeriesChangeRule {sbx}{el}{elx}{}
\DeclareFontSeriesChangeRule {sbx}{l}{lx}{}
\DeclareFontSeriesChangeRule {sbx}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {sbx}{sc}{sbsc}{}
\DeclareFontSeriesChangeRule {sbx}{sl}{slx}{}
\DeclareFontSeriesChangeRule {sbx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {sbx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {sbx}{x}{sbx}{}

\DeclareFontSeriesChangeRule {sb}{c}  {sbc} {bc} %? %<-----
\DeclareFontSeriesChangeRule {sb}{ec}  {sbec} {sbc} %? %<-----
\DeclareFontSeriesChangeRule {sb}{sc}  {sbsc} {sbc} %? %<-----
\DeclareFontSeriesChangeRule {sb}{x}  {sbx} {bx} %? %<-----

\DeclareFontSeriesChangeRule {slc}{b}{bc}{}
\DeclareFontSeriesChangeRule {slc}{c}{slc}{}
\DeclareFontSeriesChangeRule {slc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {slc}{ec}{slec}{}
\DeclareFontSeriesChangeRule {slc}{el}{elc}{}
\DeclareFontSeriesChangeRule {slc}{l}{lc}{}
\DeclareFontSeriesChangeRule {slc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {slc}{sc}{slsc}{}
\DeclareFontSeriesChangeRule {slc}{sl}{slc}{}
\DeclareFontSeriesChangeRule {slc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {slc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {slc}{x}{slx}{}

\DeclareFontSeriesChangeRule {slx}{b}{bx}{}
\DeclareFontSeriesChangeRule {slx}{c}{slc}{}
\DeclareFontSeriesChangeRule {slx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {slx}{ec}{slec}{}
\DeclareFontSeriesChangeRule {slx}{el}{elx}{}
\DeclareFontSeriesChangeRule {slx}{l}{lx}{}
\DeclareFontSeriesChangeRule {slx}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {slx}{sc}{slsc}{}
\DeclareFontSeriesChangeRule {slx}{sl}{slx}{}
\DeclareFontSeriesChangeRule {slx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {slx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {slx}{x}{slx}{}

\DeclareFontSeriesChangeRule {sl}{c}{slc}{}
\DeclareFontSeriesChangeRule {sl}{ec}{slec}{}
\DeclareFontSeriesChangeRule {sl}{sc}{slsc}{}
\DeclareFontSeriesChangeRule {sl}{x}{slx}{}

\DeclareFontSeriesChangeRule {ubc}{b}{bc}{}
\DeclareFontSeriesChangeRule {ubc}{c}{ubc}{}
\DeclareFontSeriesChangeRule {ubc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {ubc}{ec}{ubec}{}
\DeclareFontSeriesChangeRule {ubc}{el}{elc}{}
\DeclareFontSeriesChangeRule {ubc}{l}{lc}{}
\DeclareFontSeriesChangeRule {ubc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {ubc}{sc}{ubsc}{}
\DeclareFontSeriesChangeRule {ubc}{sl}{slc}{}
```

```
\DeclareFontSeriesChangeRule {ubc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {ubc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {ubc}{x}{ubx}{}

\DeclareFontSeriesChangeRule {ubx}{b}{bx}{}
\DeclareFontSeriesChangeRule {ubx}{c}{ubc}{}
\DeclareFontSeriesChangeRule {ubx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {ubx}{ec}{ubec}{}
\DeclareFontSeriesChangeRule {ubx}{el}{elx}{}
\DeclareFontSeriesChangeRule {ubx}{l}{lx}{}
\DeclareFontSeriesChangeRule {ubx}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {ubx}{sc}{ubsc}{}
\DeclareFontSeriesChangeRule {ubx}{sl}{slx}{}
\DeclareFontSeriesChangeRule {ubx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {ubx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {ubx}{x}{ubx}{}

\DeclareFontSeriesChangeRule {ub}{c}{ubc}{}
\DeclareFontSeriesChangeRule {ub}{ec}{ubec}{}
\DeclareFontSeriesChangeRule {ub}{sc}{ubsc}{}
\DeclareFontSeriesChangeRule {ub}{x}{ubx}{}

\DeclareFontSeriesChangeRule {ulc}{b}{bc}{}
\DeclareFontSeriesChangeRule {ulc}{c}{ulc}{}
\DeclareFontSeriesChangeRule {ulc}{eb}{ebc}{}
\DeclareFontSeriesChangeRule {ulc}{ec}{ulec}{ulc}
\DeclareFontSeriesChangeRule {ulc}{el}{elc}{}
\DeclareFontSeriesChangeRule {ulc}{l}{lc}{}
\DeclareFontSeriesChangeRule {ulc}{sb}{sbc}{}
\DeclareFontSeriesChangeRule {ulc}{sc}{ulsc}{ulc}
\DeclareFontSeriesChangeRule {ulc}{sl}{slc}{}
\DeclareFontSeriesChangeRule {ulc}{ub}{ubc}{}
\DeclareFontSeriesChangeRule {ulc}{ul}{ulc}{}
\DeclareFontSeriesChangeRule {ulc}{x}{ulx}{}

\DeclareFontSeriesChangeRule {ulx}{b}{bx}{}
\DeclareFontSeriesChangeRule {ulx}{c}{ulc}{}
\DeclareFontSeriesChangeRule {ulx}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {ulx}{ec}{ulec}{}
\DeclareFontSeriesChangeRule {ulx}{el}{elx}{}
\DeclareFontSeriesChangeRule {ulx}{l}{lx}{}
\DeclareFontSeriesChangeRule {ulx}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {ulx}{sc}{ulsc}{}
\DeclareFontSeriesChangeRule {ulx}{sl}{slx}{}
\DeclareFontSeriesChangeRule {ulx}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {ulx}{ul}{ulx}{}
\DeclareFontSeriesChangeRule {ulx}{x}{ulx}{}

\DeclareFontSeriesChangeRule {ul}{c}{ulc}{}
\DeclareFontSeriesChangeRule {ul}{ec}{ulec}{}
\DeclareFontSeriesChangeRule {ul}{sc}{ulsc}{}
\DeclareFontSeriesChangeRule {ul}{x}{ulx}{}

\DeclareFontSeriesChangeRule {x}{b}{bx}{}
\DeclareFontSeriesChangeRule {x}{c}{c}{}
\DeclareFontSeriesChangeRule {x}{eb}{ebx}{}
\DeclareFontSeriesChangeRule {x}{ec}{ec}{}
\DeclareFontSeriesChangeRule {x}{el}{elx}{}
```

```
\DeclareFontSeriesChangeRule {x}{l}{lx}{}
\DeclareFontSeriesChangeRule {x}{sb}{sbx}{}
\DeclareFontSeriesChangeRule {x}{sc}{sc}{}
\DeclareFontSeriesChangeRule {x}{sl}{slx}{}
\DeclareFontSeriesChangeRule {x}{ub}{ubx}{}
\DeclareFontSeriesChangeRule {x}{ul}{ulx}{}
```

Special rules for `lm` etc. aren't needed because if the target `lm` is request it will used if there is no rule and that id then reduced to `l` automatically. Same for `mc` and friends. Only `?m` and `m?` need rules.

So here are the special rules for `m?`:

```
\DeclareFontSeriesChangeRule {bc}{m?}{c}{}
\DeclareFontSeriesChangeRule {bec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {bsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {bx}{m?}{x}{}
\DeclareFontSeriesChangeRule {b}{m?}{m}{}
\DeclareFontSeriesChangeRule {c}{m?}{c}{}
\DeclareFontSeriesChangeRule {ebc}{m?}{c}{}
\DeclareFontSeriesChangeRule {ebec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {ebsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {ebx}{m?}{x}{}
\DeclareFontSeriesChangeRule {eb}{m?}{m}{}
\DeclareFontSeriesChangeRule {ec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {elc}{m?}{c}{}
\DeclareFontSeriesChangeRule {elec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {elsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {elx}{m?}{x}{}
\DeclareFontSeriesChangeRule {el}{m?}{m}{}
\DeclareFontSeriesChangeRule {lc}{m?}{c}{}
\DeclareFontSeriesChangeRule {lec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {lsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {lx}{m?}{x}{}
\DeclareFontSeriesChangeRule {l}{m?}{m}{}
\DeclareFontSeriesChangeRule {m}{m?}{m}{}
\DeclareFontSeriesChangeRule {sbc}{m?}{c}{}
\DeclareFontSeriesChangeRule {sbec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {sbsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {sbx}{m?}{x}{}
\DeclareFontSeriesChangeRule {sb}{m?}{m}{}
\DeclareFontSeriesChangeRule {sc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {slc}{m?}{c}{}
\DeclareFontSeriesChangeRule {slec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {slsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {slx}{m?}{x}{}
\DeclareFontSeriesChangeRule {sl}{m?}{m}{}
\DeclareFontSeriesChangeRule {ubc}{m?}{c}{}
\DeclareFontSeriesChangeRule {ubec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {ubsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {ubx}{m?}{x}{}
\DeclareFontSeriesChangeRule {ub}{m?}{ub}{}
\DeclareFontSeriesChangeRule {ulc}{m?}{c}{}
\DeclareFontSeriesChangeRule {ulec}{m?}{ec}{}
\DeclareFontSeriesChangeRule {ulsc}{m?}{sc}{}
\DeclareFontSeriesChangeRule {ulx}{m?}{x}{}
```

```
\DeclareFontSeriesChangeRule {ul}{m?}{m}{}
\DeclareFontSeriesChangeRule {x}{m?}{x}{}
```

And there the special rules for `?m`:

```
\DeclareFontSeriesChangeRule {bc}{?m}{b}{}
\DeclareFontSeriesChangeRule {bec}{?m}{b}{}
\DeclareFontSeriesChangeRule {bsc}{?m}{b}{}
\DeclareFontSeriesChangeRule {bsc}{?m}{b}{}
\DeclareFontSeriesChangeRule {bx}{?m}{b}{}
\DeclareFontSeriesChangeRule {b}{?m}{b}{}
\DeclareFontSeriesChangeRule {c}{?m}{m}{}
\DeclareFontSeriesChangeRule {ebc}{?m}{eb}{}
\DeclareFontSeriesChangeRule {ebec}{?m}{eb}{}
\DeclareFontSeriesChangeRule {ebsc}{?m}{eb}{}
\DeclareFontSeriesChangeRule {ebsc}{?m}{eb}{}
\DeclareFontSeriesChangeRule {ebx}{?m}{eb}{}
\DeclareFontSeriesChangeRule {eb}{?m}{eb}{}
\DeclareFontSeriesChangeRule {ec}{?m}{m}{}
\DeclareFontSeriesChangeRule {elc}{?m}{el}{}
\DeclareFontSeriesChangeRule {elec}{?m}{el}{}
\DeclareFontSeriesChangeRule {elsc}{?m}{el}{}
\DeclareFontSeriesChangeRule {elsc}{?m}{el}{}
\DeclareFontSeriesChangeRule {elx}{?m}{el}{}
\DeclareFontSeriesChangeRule {el}{?m}{el}{}
\DeclareFontSeriesChangeRule {lc}{?m}{l}{}
\DeclareFontSeriesChangeRule {lec}{?m}{l}{}
\DeclareFontSeriesChangeRule {lsc}{?m}{l}{}
\DeclareFontSeriesChangeRule {lsc}{?m}{l}{}
\DeclareFontSeriesChangeRule {lx}{?m}{l}{}
\DeclareFontSeriesChangeRule {l}{?m}{l}{}
\DeclareFontSeriesChangeRule {m}{?m}{m}{}
\DeclareFontSeriesChangeRule {sbc}{?m}{sb}{}
\DeclareFontSeriesChangeRule {sbec}{?m}{sb}{}
\DeclareFontSeriesChangeRule {sbsc}{?m}{sb}{}
\DeclareFontSeriesChangeRule {sbsc}{?m}{sb}{}
\DeclareFontSeriesChangeRule {sbx}{?m}{sb}{}
\DeclareFontSeriesChangeRule {sb}{?m}{sb}{}
\DeclareFontSeriesChangeRule {sc}{?m}{m}{}
\DeclareFontSeriesChangeRule {sc}{?m}{m}{}
\DeclareFontSeriesChangeRule {slc}{?m}{sl}{}
\DeclareFontSeriesChangeRule {slec}{?m}{sl}{}
\DeclareFontSeriesChangeRule {slsc}{?m}{sl}{}
\DeclareFontSeriesChangeRule {slsc}{?m}{sl}{}
\DeclareFontSeriesChangeRule {slx}{?m}{sl}{}
\DeclareFontSeriesChangeRule {sl}{?m}{sl}{}
\DeclareFontSeriesChangeRule {ubc}{?m}{ub}{}
\DeclareFontSeriesChangeRule {ubec}{?m}{ub}{}
\DeclareFontSeriesChangeRule {ubsc}{?m}{ub}{}
\DeclareFontSeriesChangeRule {ubsc}{?m}{ub}{}
\DeclareFontSeriesChangeRule {ubx}{?m}{ub}{}
\DeclareFontSeriesChangeRule {ub}{?m}{m}{}
\DeclareFontSeriesChangeRule {ulc}{?m}{ul}{}
\DeclareFontSeriesChangeRule {ulec}{?m}{ul}{}
\DeclareFontSeriesChangeRule {ulsc}{?m}{ul}{}
\DeclareFontSeriesChangeRule {ulsc}{?m}{ul}{}
```

```
\DeclareFontSeriesChangeRule {ulx}{?m}{ul}{}
\DeclareFontSeriesChangeRule {ul}{?m}{ul}{}
\DeclareFontSeriesChangeRule {x}{?m}{m}{}
```

Supporting rollback ...

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩   {\DeclareFontSeriesChangeRule}{Series change rules}%
⟨latexrelease⟩
⟨latexrelease⟩\let\DeclareFontSeriesChangeRule\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

1.3 Changing to a new series

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\fontseries}{delay fontseries update}%
```

`\fontseries` The `\fontseries` command takes one argument which is the requested new font series. In the orginal implementation it simply saved the expanded value in `\f@series`. Now we do a bit more processing and look up the final value in the font series data base. This is done by `\merge@font@series`. But the lookup should be done within the target family and call to `\fontseries` might be followed by a `\fontfamily` call. So we delay the processing to `\selectfont` and only record the necessary action in `\delayed@f@adjustment`.

```
\DeclareRobustCommand\fontseries[1]{\@forced@seriesfalse
    \expandafter\def\expandafter\delayed@f@adjustment\expandafter
        {\delayed@f@adjustment\delayed@merge@font@series{#1}}}
```

(*End definition for* `\fontseries`.)

`\delayed@f@adjustment` The macro holding the delayed action(s) for use in `\selectfont`.

```
\let\delayed@f@adjustment\@empty
```

(*End definition for* `\delayed@f@adjustment`.)

`\fontseriesforce` To change unconditionally to a new series you can use `\fontseriesforce`. Of course, if the series doesn't exist for the current family substitution still happens, but there is not dependency on the current series.

```
\DeclareRobustCommand\fontseriesforce[1]{\@forced@seriestrue
    \expandafter\def\expandafter\delayed@f@adjustment\expandafter
      {\delayed@f@adjustment\edef\f@series{#1}}}
```

(*End definition for* `\fontseriesforce`.)

`\if@forced@series` If the series gets forced we need to know that fact later on.

```
\newif\if@forced@series
```

(*End definition for* `\if@forced@series`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                 {\fontseries}{delay fontseries update}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\fontseries[1]{\@forced@seriesfalse
⟨latexrelease⟩                                    \merge@font@series{#1}}
⟨latexrelease⟩\DeclareRobustCommand\fontseriesforce[1]{\@forced@seriestrue
⟨latexrelease⟩                                         \edef\f@series{#1}}
⟨latexrelease⟩\let\delayed@f@adjustment\@undefined
⟨latexrelease⟩
```

For a roll forward we may have to define `\if@forced@series` but this needs doing in a way that TEX doesn't see it when skipping over conditionals.

```
⟨latexrelease⟩\expandafter\newif\csname if@forced@series\endcsname
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\fontseries}{delay fontseries update}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\fontseries[1]{\edef\f@series{#1}}
⟨latexrelease⟩\let\fontseriesforce\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩    {\merge@font@series}{Merge series values}%
```

`\merge@font@series` We look up the data base value by expanding the right command twice. If no such value exist then the result will be `\relax` otherwise it will be the two brace groups: the desired result and the alternate result. The first case means that the third argument to `\merge@font@series` will be empty.

```
\def\merge@font@series#1{%
  \expandafter\expandafter\expandafter
  \merge@font@series@
    \csname series@\f@series @#1\endcsname
    {#1}%
    \@nil
}
```

(*End definition for* `\merge@font@series`.)

`\merge@font@series@` This now defines the new `\f@series`:

```
\def\merge@font@series@#1#2#3\@nil{%
```

If the third argument is empty there is no database entry for the combination and the second argument holds the new series so we return that.

Originally the test was simply `\ifx!#3!` but that actually dies if `#3` starts with a conditional and in the definition of `\AmSfont` that is actually the case.

```
%\ifcat\expandafter X\detokenize{#1}X%
  \def\reserved@a{#3}%
  \ifx\reserved@a\@empty
    \set@target@series{#2}%
  \else
```

Otherwise we check if the desired result for the series (#1) exists for the font family and the current shape. All this happens inside \selectfont which has already taken care to load the .fd, file if necessary.

```
    \edef\reserved@a{\f@encoding /\f@family /#1/\f@shape}%
     \ifcsname \reserved@a \endcsname
```

If the desired result is available then we use that. However, we do need some post-processing because we need to drop surplus ms due to the way naming convention was designed in the '90s (sigh).

```
        \set@target@series{#1}%
```

If not, then we try the alternate result (#2).

```
    \else
        \ifcsname \f@encoding /\f@family /#2/\f@shape \endcsname
```

If the alternate result exist we use that and also issue a warning (or rather a log entry) that we didn't managed to change to the desired font.

```
          \set@target@series{#2}%
          \@font@shape@subst@warning
```

If that doesn't exist either, then we use the requested series unmodified (again with a warning).

```
        \else
          \set@target@series{#3}%
          \@font@shape@subst@warning
        \fi
    \fi
  \fi
}
```

It is possible that the previous font and the new one are actually identical (and the font was not found because it still needs loading) in which case a warning would look rather odd. So we make a quick check for that (which is the reason why we defined \@reserveda above instead of doing inline testing inside \ifcsname).

```
\def\@font@shape@subst@warning{%
   \edef\reserved@b{\curr@fontshape}%
   \ifx\reserved@a\reserved@b \else
     \@font@warning{Font shape `\reserved@a' undefined\MessageBreak
                    using `\reserved@b' instead}%
   \fi
}
```

(*End definition for* \merge@font@series@.)

\merge@font@series@without@substitution
\merge@font@series@without@substitution@
\delayed@merge@font@series

\merge@font@series@without@substitution works like \merge@font@series, i.e., it looks up the combination in the rule base and if there exists an entry it uses it and if not it uses the new series value. However, it doesn't check if there is actually a font face with the new series value as \merge@font@series does. This simplified command is used in \selectfont at a point where other font attributes are not yet updated so that checking the font face might result incorrect in substitutions.

```
\def\merge@font@series@without@substitution#1{%
  \expandafter\expandafter\expandafter
  \merge@font@series@without@substitution@
    \csname series@\f@series @#1\endcsname
```

```
    {#1}%
    \@nil
}
```

```
\def\merge@font@series@without@substitution@#1#2#3\@nil{%
  \def\reserved@a{#3}%
  \ifx\reserved@a\@empty
    \set@target@series{#2}%
  \else
    \set@target@series{#1}%
  \fi
}
```

(*End definition for* `\merge@font@series@without@substitution`, `\merge@font@series@without@substitution@`, *and* `\delayed@merge@font@series`.)

`\delayed@merge@font@series` When we delay the merge action in `\fontseries` we first attempt to use merging without substitution. If that results in a non-existing font face the merge is redone in `\selectfont` using a version with substitution. See `\selectfont` for details.

```
\let\delayed@merge@font@series\merge@font@series@without@substitution
```

(*End definition for* `\delayed@merge@font@series`.)

`\maybe@load@fontshape` A small helper that we use a couple of times: try loading a fontshape (in a group because `\try@load@fontshape` normalizes catcodes and we also want to change `\typeout` so that it doesn't report missing `.fd` files on the terminal).

```
\def\maybe@load@fontshape{%
  \begingroup
    \let \typeout \@font@info
    \try@load@fontshape
  \endgroup}
```

(*End definition for* `\maybe@load@fontshape`.)

`\set@target@series` Finally the code for normalizing the `\f@series` value.

The combined series value determined by the mapping may still contain an `m` that we have to remove (as the `.fd` files use `c` not `mc` to denote a medium weight condensed series, etc.). We do this in all branches above because a user might have written

```
\DeclareFontSeriesChangeRule {m}{sc}{msc}{mc}
```

instead of using `sc` and `c` as needed in the `.fd` file.

```
\def\set@target@series#1{%
```

We need to `\edef` the argument first in case it starts with a conditional. Then we check (and perhaps drop) an "m" from the value and assign the result to `\f@series`.

```
    \edef\f@series{#1}%
    \series@maybe@drop@one@m\f@series\f@series
}
```

(*End definition for* `\set@target@series`.)

\series@maybe@drop@one@m If the series value is in NFSS notation then it should not contain any "m" unless it is just an "m" by it own. So we need to drop surplus "m"s. But we better don't do this for full names, such as "semibold" as used by autoinst, for example. So we test against the possible explicit values that should drop an "m". After that we assign the result to #2 for further use.

```
\def\series@maybe@drop@one@m#1{%
  \expandafter\series@maybe@drop@one@m@x\expandafter{#1}}

\def\series@maybe@drop@one@m@x#1#2{%
```

The code below is an inline version of the \in@ macro without the group, so that it works in \accent.

```
  \def\in@@##1,#1,{}%
  \series@check@toks\expandafter{\in@@
    ,ulm,elm,lm,slm,mm,sbm,bm,ebm,ubm,muc,mec,mc,msc,msx,mx,mex,mux,{}{},#1,}%
  \edef\in@@{\the\series@check@toks}%
  \ifx\in@@\@empty
```

The default definition for \bfdefault etc is actually b\@empty so that we can detect if the user has changed the default. However that means a) the above test will definitely fail (maybe something to change) and b) we better use \edef on the next line to get rid of it as otherwise the test against #2 (e.g. \bfdef@ult) will fail in other places.

```
    \edef#2{#1}%
  \else
    \edef#2{\expandafter\series@drop@one@m #1m\series@drop@one@m}%
  \fi
}
```

As a precaution we use a private toks register not \toks@ as that is no longer hidden inside the group.

```
\newtoks\series@check@toks
```

(*End definition for* \series@maybe@drop@one@m.)

\series@drop@one@m Drop up to two ms but keep one if that makes the series value empty. Actually, with the current implementation we know that there is at least one in the series value itself and we added one after it, so all we have to do is now returning #1#2 and dropping the rest.

```
\def\series@drop@one@m#1m#2m#3\series@drop@one@m{%
%  \ifx\relax#1#2\relax m\else#1#2\fi
   #1#2%
}
```

(*End definition for* \series@drop@one@m.)

Supporting rollback ...

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩    {\merge@font@series}{Merge series values}%
⟨latexrelease⟩
⟨latexrelease⟩\let\merge@font@series\@undefined
⟨latexrelease⟩\let\merge@font@series@\@undefined
⟨latexrelease⟩\let\@font@shape@subst@warning\@undefined
⟨latexrelease⟩\let\merge@font@series@without@substitution\@undefined
⟨latexrelease⟩\let\merge@font@series@without@substitution@\@undefined
```

```
⟨latexrelease⟩\let\delayed@merge@font@series\@undefined
⟨latexrelease⟩\let\maybe@load@fontshape\@undefined
⟨latexrelease⟩\let\set@target@series\@undefined
⟨latexrelease⟩\let\series@maybe@drop@one@m\@undefined
⟨latexrelease⟩\let\series@drop@one@m\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

2 Changing the shape

Shapes are also split in two axes (though it could be more if that is desirable), essentially building in an "sc" axis).

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩    {\DeclareFontShapeChangeRule}{Font shape change rules}%
```

\DeclareFontShapeChangeRule

The database for shapes is done in exactly the same way, only that it is much smaller and we usually have no alternative shape (or rather it is empty thus not used).

```
\def\DeclareFontShapeChangeRule #1#2#3#4{%
  \@namedef{shape@#1@#2}{{#3}{#4}}}
```

(*End definition for* \DeclareFontShapeChangeRule.)

There is kind of the same problem with returning back from `sc` to normal. It sort of needs its own letter. In `fontspec` this was solved by the first time `\upshape` changes `it` or `sl` back (so only `sc` remains) and second time it changes then `sc` back to normal. Maybe that's not a bad way to handle it, but decided for a slightly different approach: `n` always returns to "normal", ie resets everything and `up` changes italic or slanted to upright and `ulc` undoes small caps.

So we now offer `\normalshape` (using `\shapedefault` which is normally the same as calling both `\ulcshape` and `\upshape`, only more efficient.

\ulcshape
\textulc
\ulcdefault

To request going back to upper/lowercase we need a new command. It uses `ulc` as shape name but this shape is virtual, i.e., it doesn't exist as a real shape, it is only used as part of the database table entries and thus only appears in the second argument there (but not in the first).

```
\DeclareRobustCommand\ulcshape
        {\not@math@alphabet\ulcshape\relax
         \fontshape\ulcdefault\selectfont}
\let\ulcdefault\@undefined      % for rollback
\newcommand\ulcdefault{ulc}
```

(*End definition for* \ulcshape, \textulc, *and* \ulcdefault.)

\swshape
\textsw
\swdefault

New command to select a swash shape. The standard rules put this in the same category as italics or slanted, i.e., if you ask for it then italics are undone. One could provide more complicated rules so that `it` + `sw` becomes `swit` but given that there are only very few fonts that have swash letters that level of flexibility (these days) would be just resulting in a lot of combinations that do not exist.

```
\DeclareRobustCommand\swshape
        {\not@math@alphabet\swshape\relax
         \fontshape\swdefault\selectfont}
\let\swdefault\@undefined      % for rollback
\newcommand\swdefault{sw}
```

(*End definition for* `\swshape`, `\textsw`, *and* `\swdefault`.)

`\sscshape` `\textssc` `\sscdefault`

New command to select spaced small capitals. This is only here because `fontaxes` offered it. There isn't a single free font that supports it. However, some commercial ones do, so we offer it so that at some point `fontaxes` could be retired.

So far there aren't any rules for it—probably there should be some putting it in the same category as `sc`.

```
\DeclareRobustCommand\sscshape
        {\not@math@alphabet\sscshape\relax
         \fontshape\sscdefault\selectfont}
\let\sscdefault\@undefined      % for rollback
\newcommand\sscdefault{ssc}
```

(*End definition for* `\sscshape`, `\textssc`, *and* `\sscdefault`.)

2.1 Mapping rules for shape combinations

Many of the entries are commented out as we will get that result without any entry.

```
%\DeclareFontShapeChangeRule {n}{n}   {n}   {}
\DeclareFontShapeChangeRule {n}{it}  {it}  {sl}
\DeclareFontShapeChangeRule {n}{sl}  {sl}  {it}
%\DeclareFontShapeChangeRule {n}{sw}  {sw}  {}
%\DeclareFontShapeChangeRule {n}{sc}  {sc}  {}
\DeclareFontShapeChangeRule {n}{ulc} {n}   {}
\DeclareFontShapeChangeRule {n}{up} {n}    {}
```

```
%\DeclareFontShapeChangeRule {it}{n}   {n}     {}
%\DeclareFontShapeChangeRule {it}{it}  {it}    {}
\DeclareFontShapeChangeRule {it}{sl}  {sl}    {it}
%\DeclareFontShapeChangeRule {it}{sw}  {sw}    {}
```

If neither `scit` nor `scsl` exist then `sc` will be used as a fallback albeit with a log entry, so except for the latter there will be no change for CM or Latin Modern fonts.

```
\DeclareFontShapeChangeRule {it}{sc}  {scit}  {scsl}
\DeclareFontShapeChangeRule {it}{ulc} {it}    {}
\DeclareFontShapeChangeRule {it}{up} {n}      {}
```

```
%\DeclareFontShapeChangeRule {sl}{n}   {n}     {}
\DeclareFontShapeChangeRule {sl}{it}  {it}    {sl}
%\DeclareFontShapeChangeRule {sl}{sl}  {sl}    {}
%\DeclareFontShapeChangeRule {sl}{sw}  {sw}    {}
\DeclareFontShapeChangeRule {sl}{sc}  {scsl}  {scit}
\DeclareFontShapeChangeRule {sl}{ulc} {sl}    {}
\DeclareFontShapeChangeRule {sl}{up} {n}      {}
```

```
%\DeclareFontShapeChangeRule {sc}{n}   {n}     {}
\DeclareFontShapeChangeRule {sc}{it}  {scit}  {scsl}
\DeclareFontShapeChangeRule {sc}{sl}  {scsl}  {scit}
\DeclareFontShapeChangeRule {sc}{sw}  {scsw}  {sw}
%\DeclareFontShapeChangeRule {sc}{sc}  {sc}    {}
\DeclareFontShapeChangeRule {sc}{ulc} {n}     {}
```

The next rule might be a bit surprising and rightly so. Correct would be that `sc` is not affected by `up`, i.e., remains `sc` as showed in the commented out rule. However, for nearly three decades commands such as sc or `\textup` changed small caps back to the "normal" shape. So for backward compatibility we keep hat behavior.

As a result you are currently typesetting in `scit` or `scsl` using `\upshape` twice will return you to the normal shape too, the first will change to `sc` and the second (because of the rule below) change that to `n`. This is the way `fontspec` implemented its version on this interface, so this rule means we are also compatible with the way `fontspec` behaved. Still it remains an oddity which I would rather liked to have avoided.

```
%\DeclareFontShapeChangeRule {sc}{up} {sc}     {}
\DeclareFontShapeChangeRule {sc}{up} {n}     {}
```

```
%\DeclareFontShapeChangeRule {scit}{n}   {n}    {}
\DeclareFontShapeChangeRule {scit}{it}  {scit}  {}
\DeclareFontShapeChangeRule {scit}{sl}  {scsl}  {scit}
\DeclareFontShapeChangeRule {scit}{sw}  {scsw}  {sc}    % or scit?
\DeclareFontShapeChangeRule {scit}{sc}  {scit}  {}
\DeclareFontShapeChangeRule {scit}{ulc} {it}    {}
\DeclareFontShapeChangeRule {scit}{up} {sc}     {}
```

The previous rule assumes that if `scit` exists then `it` exists as well. If not, the mechanism will save `ulc` in `\f@series` which most certainly doesn't exist. So when a font is later selected that would result in a substitution (so no harm done really). Alternatively, we could in this case use `n` as alternative, which may be a bit faster, but such a setup would be so weird in the first place that this isn't worth the effort.

```
%\DeclareFontShapeChangeRule {scsl}{n}   {n}     {}
\DeclareFontShapeChangeRule {scsl}{it}  {scit}  {scsl}
\DeclareFontShapeChangeRule {scsl}{sl}  {scsl}  {}
\DeclareFontShapeChangeRule {scsl}{sw}  {scsw}  {sc}    % or scsl?
\DeclareFontShapeChangeRule {scsl}{sc}  {scsl}  {}
\DeclareFontShapeChangeRule {scsl}{ulc} {sl}    {}
\DeclareFontShapeChangeRule {scsl}{up}   {sc}   {}
```

```
%\DeclareFontShapeChangeRule {scsw}{n}   {n}     {}
\DeclareFontShapeChangeRule {scsw}{it}  {scit}  {scsw}
\DeclareFontShapeChangeRule {scsw}{sl}  {scsl}  {}
\DeclareFontShapeChangeRule {scsw}{sw}  {scsw}  {}
\DeclareFontShapeChangeRule {scsw}{sc}  {scsw}  {}
\DeclareFontShapeChangeRule {scsw}{ulc} {sw}    {}
\DeclareFontShapeChangeRule {scsw}{up} {sc}     {}
```

```
%\DeclareFontShapeChangeRule {sw}{n}   {n}     {}
%\DeclareFontShapeChangeRule {sw}{it}  {it}    {}
%\DeclareFontShapeChangeRule {sw}{sl}  {sl}    {}
%\DeclareFontShapeChangeRule {sw}{sw}  {sw}    {}
\DeclareFontShapeChangeRule {sw}{sc}  {scsw}  {}
\DeclareFontShapeChangeRule {sw}{ulc} {sw}    {}
\DeclareFontShapeChangeRule {sw}{up} {n}      {}
```

Supporting rollback ...

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩   {\DeclareFontShapeChangeRule}{Font shape change rules}%
⟨latexrelease⟩
⟨latexrelease⟩\let\DeclareFontShapeChangeRule\@undefined
⟨latexrelease⟩\let\ulcshape\@undefined
⟨latexrelease⟩\let\ulcdefault\@undefined
⟨latexrelease⟩\let\swshape\@undefined
```

```
⟨latexrelease⟩\let\swdefault\@undefined
⟨latexrelease⟩\let\sscshape\@undefined
⟨latexrelease⟩\let\sscdefault\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

2.2 Changing to a new shape

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩    {\fontshape}{Font shape change}%
```

`\fontshape` Again the `\fontshape` now has to do a lookup to get to its new value in `\f@shape`. The method is exactly the same as in `\fontseries`.

```
\DeclareRobustCommand\fontshape[1]
   {\expandafter\def\expandafter\delayed@f@adjustment\expandafter
        {\delayed@f@adjustment\delayed@merge@font@shape{#1}}}
```

(*End definition for* `\fontshape`.)

`\fontshapeforce` The unconditional version:

```
\DeclareRobustCommand\fontshapeforce[1]
   {\expandafter\def\expandafter\delayed@f@adjustment\expandafter
        {\delayed@f@adjustment\edef\f@shape{#1}}}
```

(*End definition for* `\fontshapeforce`.)

Supporting rollback ...

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩    {\fontshape}{Font shape change}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\fontshape[1]{\merge@font@shape{#1}}
⟨latexrelease⟩\DeclareRobustCommand\fontshapeforce[1]{\edef\f@shape{#1}}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩    {\fontshape}{Font shape change}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\fontshape [1]{\edef\f@shape{#1}}
⟨latexrelease⟩\let\fontshapeforce\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩    {\merge@font@shape}{Font shape change rules}%
```

`\merge@font@shape` Look up the database entry (if existing) and act accordingly.

```
\def\merge@font@shape#1{%
  \expandafter\expandafter\expandafter
  \merge@font@shape@
    \csname shape@\f@shape @#1\endcsname
    {#1}%
```

```
    \@nil
}
```

(*End definition for* `\merge@font@shape`.)

`\merge@font@shape@` Same game now, except that we look at shapes not series values and we can set the shape without the complication of dropping "m"s from the name as we had to for the series.

```
\def\merge@font@shape@#1#2#3\@nil{%
  \def\reserved@a{#3}%
  \ifx\reserved@a\@empty
    \edef\f@shape{#2}%
  \else
```

`\reserved@a` is used in `\@font@shape@subst@warning` so we have to define it in addition to do the `\ifcsname` test

```
    \edef\reserved@a{\f@encoding /\f@family /\f@series/#1}%
    \ifcsname \reserved@a\endcsname
       \edef\f@shape{#1}%
    \else
       \ifcsname \f@encoding /\f@family /\f@series/#2\endcsname
         \edef\f@shape{#2}%
         \@font@shape@subst@warning
       \else
         \edef\f@shape{#3}%
         \@font@shape@subst@warning
       \fi
    \fi
  \fi
}
```

(*End definition for* `\merge@font@shape@`.)

`\merge@font@shape@without@substitution` `\merge@font@shape@without@substitution@` `\delayed@merge@font@shape` See definition of `\selectfont` for how these macros are used.

```
\def\merge@font@shape@without@substitution#1{%
  \expandafter\expandafter\expandafter
  \merge@font@shape@without@substitution@
    \csname shape@\f@shape @#1\endcsname
    {#1}%
    \@nil
}
```

```
\def\merge@font@shape@without@substitution@#1#2#3\@nil{%
  \def\reserved@a{#3}%
  \ifx\reserved@a\@empty
    \edef\f@shape{#2}%
  \else
    \edef\f@shape{#1}%
  \fi
}
```

```
\let\delayed@merge@font@shape\merge@font@shape@without@substitution
```

(*End definition for* `\merge@font@shape@without@substitution`, `\merge@font@shape@without@substitution@`, *and* `\delayed@merge@font@shape`.)

\normalshape

\normalshape resets both sub-axes if the default rules are used.

```
\protected\def\normalshape
    {\not@math@alphabet\normalshape\relax
      \fontshape\shapedefault\selectfont}%
```

(*End definition for* \normalshape.)

3 Make sure we win ...

This code implements one aspect of what the package fontaxes provide. So its redefinitions for the various shape commands, such as \itshape should no longer happen. We therefore force the standard definitions at \AtBeginDocument (later when this is defined. Once fontaxes is no longer doing such redefinitions that could be taken out again.

We use a separate macro so that we can easily disable this (in case of rollback).

\reinstall@nfss@defs

I use \protected here not \DeclareRobustCommand to avoid extra status lines.

```
\def\reinstall@nfss@defs{%
  \protected\def\upshape
          {\not@math@alphabet\upshape\relax
           \fontshape\updefault\selectfont}%
  \protected\def\slshape
          {\not@math@alphabet\slshape\relax
           \fontshape\sldefault\selectfont}%
  \protected\def\scshape
          {\not@math@alphabet\scshape\relax
           \fontshape\scdefault\selectfont}%
  \protected\def\itshape
          {\not@math@alphabet\itshape\mathit
           \fontshape\itdefault\selectfont}%
  \protected\def\ulcshape
          {\not@math@alphabet\ulcshape\relax
           \fontshape{ulc}\selectfont}%
  \protected\def\swshape
          {\not@math@alphabet\swshape\relax
           \fontshape\swdefault\selectfont}%
  \protected\def\sscshape
          {\not@math@alphabet\sscshape\relax
           \fontshape\sscdefault\selectfont}%
}
```

(*End definition for* \reinstall@nfss@defs.)

Supporting rollback ...

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩   {\merge@font@shape}{Font shape change rules}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\fontshape [1]{\edef\f@shape{#1}}
⟨latexrelease⟩\let\fontshapeforce\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\merge@font@shape\@undefined
⟨latexrelease⟩\let\merge@font@shape@\@undefined
⟨latexrelease⟩
```

```
⟨latexrelease⟩\let\merge@font@shape@without@substitution\@undefined
⟨latexrelease⟩\let\merge@font@shape@without@substitution@\@undefined
⟨latexrelease⟩\let\delayed@merge@font@shape\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\normalshape\@undefined
⟨latexrelease⟩
```

This is always called in `\document` so don't make it undefined.

```
⟨latexrelease⟩
⟨latexrelease⟩\let\reinstall@nfss@defs\relax
⟨latexrelease⟩\EndIncludeInRelease
```

This initializes the 2020/02/02 extensions to NFSS after any changes in the preamble.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\reinstall@nfss@defs}{NFSS series init}%
\g@addto@macro\@kernel@after@begindocument@before
               {\reinstall@nfss@defs\init@series@setup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

The initialization was introduced in 2020/02/02 but

```
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\reinstall@nfss@defs}{NFSS series init}%
⟨latexrelease⟩\AtBeginDocument{\reinstall@nfss@defs\init@series@setup}
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\reinstall@nfss@defs}{NFSS series init}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
⟨/2ekernel⟩
```

File x
ltfsstrc.dtx

1 Introduction

This package contains the code for tracing font loading and font changes. It basically overlays some of the low-level functions of NFSS with additional code used for tracing.

The package accepts the following options:

errorshow Write all information about font changes etc. only to the transcript file unless an error happens. This means that information about font substitution will not be shown on the terminal.

warningshow Show all NFSS warnings on the terminal. This setting corresponds to the default behaviour of NFSS if the `tracefnt` package is *not* loaded!

infoshow Show all NFSS warning and all NFSS info messages (that are normally only written to the transcript file) also on the terminal. This is the default if the `tracefnt` package is loaded.

debugshow In addition to `infoshow` show also changing of math fonts as far as possible (this option can produce a large amount of output.

loading Show the name of external fonts when they are loaded. This option shows only "newly" loaded fonts not those already preloaded in the format or the class file before the `tracefnt` package became active.

pausing Turn all font warnings into errors so that LaTeX will stop.

2 A driver for this document

The next bit of code contains the documentation driver file for TeX, i.e., the file that will produce the documentation you are currently reading. It will be extracted from this file by the DocStrip program.

When this file is processed directly by LaTeX this will produce the documentation as well.

```
⟨*driver⟩
\documentclass{ltxdoc}


%\OnlyDescription  % comment out for implementation details

\begin{document}
   \DocInput{ltfsstrc.dtx}
\end{document}
⟨/driver⟩
```

3 The Implementation

Warning: Read the macro documentation with a grain of salt. It is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

If we are making a package file it is a good idea to test whether we are running under 2e. This code is actually placed at the very beginning of this file for easier maintenance, thus commented out here.

```
⟨*package⟩
%\NeedsTeXFormat{LaTeX2e}
%\ProvidesPackage{tracefnt}[??/??/?? v?.??
%                          Standard LaTeX package (font tracing)]
⟨/package⟩
```

The debug module makes use of commands contained in a special package file named trace.sty.[25]

```
⟨+debug⟩ \input trace.sty
```

4 Handling Options

\tracingfonts

Here is the definition of the integer register for the font trace. As a default in a package file we use 1 to give error messages if fonts are substituted. If this code is used for debugging or tracing reasons in the format file (i.e. in fam.dtx) we use 0 as the default. But if no font trace is used we build a definition that will produce a warning message.

```
⟨*2ekernel⟩
\def\tracingfonts{%
  \@font@warning{Command \noexpand\tracingfonts
           not provided.\MessageBreak
           Use the ‘tracefnt’ package.\MessageBreak Command found:}%
       \count@}
⟨/2ekernel⟩
```

The \count@ in the line above will remove the number after \tracingfonts. Note that this definition will be overwritten be the next line if one of these modules are included.

```
⟨*package, trace, debug⟩
\newcount\tracingfonts
\tracingfonts=0
⟨/package, trace, debug⟩
```

(*End definition for* \tracingfonts.)

The option errorshow turns off all warnings so that only real errors are shown. warningshow corresponds to the NFSS default (when tracefnt is not loaded). infoshow is the default for this package here; and debugshow, loading, and pausing extend the amount of information even further.

```
⟨*package⟩
\DeclareOption{errorshow}{%
   \def\@font@info#1{%
         \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
                     {LaTeX Font Info: \space\space\space#1}}%
```

[25] This package is not in distribution at the moment (and probably doesn't any longer work). Think of this part of the code as being historical artifacts.

```
    \def\@font@warning#1{%
         \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
                        {LaTeX Font Warning: #1}}%
     }
\DeclareOption{warningshow}{%
   \def\@font@info#1{%
         \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
                      {LaTeX Font Info: \space\space\space#1}}%
    \def\@font@warning#1{%
         \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
                        {LaTeX Font Warning: #1}}%
     }
\DeclareOption{infoshow}{%
   \def\@font@info#1{%
         \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
                      {LaTeX Font Info: \space\space\space#1}}%
    \def\@font@warning#1{%
         \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
                        {LaTeX Font Warning: #1}}%
     }
\DeclareOption{loading}{%
    \tracingfonts\tw@
   }
\DeclareOption{debugshow}{%
    \ExecuteOptions{infoshow}%
    \tracingfonts\thr@@
   }

\DeclareOption{pausing}{%
    \def\@font@warning#1{%
      \GenericError
             {(Font)\@spaces\@spaces\@spaces\space\space}%
             {LaTeX Font Warning: #1}%
             {See the LaTeX Companion for details.}%
             {I'll stop for every LaTeX Font Warning because
              you requested\MessageBreak the 'pausing' option
              to the tracefnt package.}}%
   }
```

We make `infoshow` the default, which in turn defines `\font@warning` and `\font@info`.

```
\ExecuteOptions{infoshow}
\ProcessOptions
⟨/package⟩
```

We also need a default definition inside the kernel:

```
⟨*2ekernel⟩
\def\@font@info#1{%
         \GenericInfo{(Font)\@spaces\@spaces\@spaces\space\space}%
                      {LaTeX Font Info: \space\space\space#1}}%
\def\@font@warning#1{%
         \GenericWarning{(Font)\@spaces\@spaces\@spaces\space\space}%
                        {LaTeX Font Warning: #1}}%
⟨/2ekernel⟩
```

5 Macros common to fam.tex and tracefnt.sty

In the first versions of tracefnt.dtx some macros of fam.dtx[26] were redefined to included the extra tracing information. Now these macros are all defined in this file (i.e. removed from fam.dtx) and different production versions can be obtained simply by specifying a different set of modules to include when generating ltfss.dtx.

5.1 General font loading

\extract@font

This macro organizes the font loading. It first calls \get@external@font which will return in \external@font the name of the external font file (the .tfm) as it was determined by the NFSS tables.

```
⟨*2ekernel | package⟩
\def\extract@font{%
   \get@external@font
```

Then the external font is loaded and assigned to the font identifier stored inside \font@name (for this reason we need \expandafter).

```
   \global\expandafter\font\font@name\external@font\relax
```

When tracing we typeout the internal and external font name.

```
⟨*trace⟩
    \ifnum \tracingfonts >\@ne
    \@font@info{External font `\external@font'
              loaded as\MessageBreak \font@name}\fi
⟨/trace⟩
```

Finally we call the corresponding "loading action" macros to finish things. First the font is locally selected to allow the use of \font inside the loading action macros.

```
    \font@name \relax
```

The next two lines execute the "loading actions" for the family and then for the individual font shape.

```
    \csname \f@encoding+\f@family\endcsname
    \csname\curr@fontshape\endcsname
    \relax
       }
⟨/2ekernel | package⟩
```

The \relax at the end needs to be explained. This is inserted to prevent TEX from scanning too far when it is executing the replacement text of the loading code macros.

(*End definition for* \extract@font.)

\get@external@font

This function tries to find an external font name. It will place the name into the macro \external@font. If no font is found it will return the one that was defined via \DeclareErrorFont.

```
⟨*2ekernel⟩
\def\get@external@font{%
```

We don't know the external font name at the beginning.

```
   \let\external@font\@empty
   \edef\font@info{\expandafter\expandafter\expandafter\string
        \csname \curr@fontshape \endcsname}%
   \try@size@range
```

[26] This file is currently not distributed in documented form. Its code is part of ltfss.dtx.

If this failed, we'll try to substitute another size of the same font. This is done by the `\try@size@substitution` macro. It "knows about" `\do@extract@font`, `\font@name`, `\f@size`, and so on.

```
   \ifx\external@font\@empty
      \try@size@substitution
      \ifx\external@font\@empty
         \@latex@error{Font \expandafter \string\font@name\space
                       not found}\@eha
         \error@fontshape
         \get@external@font
   \fi\fi
}
⟨/2ekernel⟩
```

(*End definition for* `\get@external@font`.)

```
⟨*2ekernel | latexrelease | package⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                    {\selectfont}{Add hook to \selectfont}%
```

`\selectfont` The macro `\selectfont` is called whenever a font change must take place.

```
\DeclareRobustCommand\selectfont
        {%
```

When `debug` is specified we actually want something like 'undebug'. The font selection is now stable so that using `\tracingall` on some other macros will show us a lot of unwanted information about font loading. Therefore we disable tracing during font loading as long as `\tracingfonts` is less than 4.

```
⟨+debug⟩  \pushtracing
⟨+debug⟩  \ifnum\tracingfonts<4 \tracingoff
⟨+debug⟩  \else \tracingon\p@selectfont \fi
```

If `\baselinestretch` was redefined by the user it will not longer match its internal counterpart `\f@linespread`. If so we call `\set@fontsize` to prepare `\size@update`.

```
   \ifx\f@linespread\baselinestretch \else
     \set@fontsize\baselinestretch\f@size\f@baselineskip \fi
```

The series and shape updates are only prepared by `\fontseries` and `\fontshape` but not executed until after we are ready to change the font face. This way they happen after a possibly new family is set which is important because they look at the available font faces in that family and alter the selection based on availibility. Several calls to `\fontseries` or `\fontshape` are delayed in the order in which they appear, so that by switching them one can work around missing intermediate font faces and avoid substitutions.

We first attempt to do the merge without any substitution. As we might end up with a non-existing font face we may have to restart and therefore save the current values of `\f@series` and `\f@shape` before the merge.

But first we make a quick test to see if there are any delayed actions, because if not it is pointless to make all the assignments and try loading a missing fontshape.

```
   \ifx\delayed@f@adjustment\@empty
   \else
     \let\f@shape@saved\f@shape
     \let\f@series@saved\f@series
```

The we run the delayed adjustments (which is using the `\..@without@substitution` commands

```
      \delayed@f@adjustment
```

We then check if the resulting cominbation is valid but for this we have to make sure that the appropiate `.fd` is loaded if that hasn't happened so far.

```
      \maybe@load@fontshape
      \ifcsname \f@encoding/\f@family/\f@series/\f@shape \endcsname
```

If this macro is defined then we are good and no further action is necessary.

Otherwise the combination is not valid, so we redo the merge but this time with substitutions.

```
      \else
        \let\f@shape\f@shape@saved
        \let\f@series\f@series@saved
        \let\delayed@merge@font@shape\merge@font@shape
        \let\delayed@merge@font@series\merge@font@series
        \delayed@f@adjustment
        \let\delayed@merge@font@shape\merge@font@shape@without@substitution
        \let\delayed@merge@font@series\merge@font@series@without@substitution
      \fi
```

Now the series and shape values are updated and we clear `\delayed@f@adjustment`. This is important because on the next execution of `\selectfont` we should not mistakenly redo the delayed actions if there wasn't any series or shape change.

```
      \let\delayed@f@adjustment\@empty
    \fi
```

If the series was forced we should now cancel that in case the next series change is done with some low-level setting to `\f@series`.

```
    \@forced@seriesfalse
```

Then we generate the internal name of the font by concatenating *family*, *series*, *shape*, and current *size*, with slashes as delimiters between them. This is much more readable than standard LaTeX's `\twfbf`, etc. We define `\font@name` globally, as always. The reason for this is explained later on.

```
    \xdef\font@name{%
      \csname\curr@fontshape/\f@size\endcsname}%
```

We call the macro `\pickup@font` which will load the font if necessary.

```
    \pickup@font
```

Then we select the font.

```
    \font@name
```

After switching fonts we run a hook, so that packages can make last minute alterations based on the new font (originally provided in everysel but using a different interface).

```
    \UseHook{selectfont}%
```

Finally we call `\size@update`. This macro is normally empty but will contain actions (like setting the `\baselineskip`) that have to be carried out when the font size, the base `\baselineskip` or the `\baselinestretch` have changed.

```
    \size@update
```

A similar function is called to handle anything related to encoding updates. This one is changed from `\relax` by `\fontencoding`.

```
    \enc@update
```

Just before ending this macro we have to pop the tracing stack if it was pushed before.

```
⟨+debug⟩ \poptracing
    }
```

(*End definition for* `\selectfont`.)

`selectfont` Declare the hook used in selecfont in the kernel, but not inside the tracefnt package.

```
⟨-trace⟩\NewHook{selectfont}
```

(*End definition for* `selectfont`.)

If `\tracingfonts` is greater than 2 we also show the font switch inside `\selectfont`. We do this by adding this code to the hook in the tracefnt package: macro might redefine `\font@name`.

```
⟨*trace⟩
\AddToHook{selectfont}
   {\ifnum \tracingfonts>\tw@
       \@font@info{Switching to \font@name}\fi}
⟨/trace⟩
```

```
⟨/2ekernel | latexrelease | package⟩
⟨latexrelease⟩\EndIncludeInRelease
```

With `\selectfont` having different definitions in different kernels we also have to provide them in the `tracefnt` package to support rollback. In packages that works a bit differently and therefore we have to provide an empty block there.

```
⟨package⟩\IncludeInRelease{2021/06/01}%
⟨package⟩                  {\selectfont}{Add hook to \selectfont}%
⟨package⟩\EndIncludeInRelease
```

```
⟨latexrelease | package⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease | package⟩                  {\selectfont}{Add hook to \selectfont}%
⟨latexrelease | package⟩
⟨latexrelease | package⟩\DeclareRobustCommand\selectfont
⟨latexrelease | package⟩   {%
⟨latexrelease | package⟩    \ifx\f@linespread\baselinestretch \else
⟨latexrelease | package⟩      \set@fontsize\baselinestretch\f@size\f@baselineskip \fi
⟨latexrelease | package⟩    \xdef\font@name{%
⟨latexrelease | package⟩      \csname\curr@fontshape/\f@size\endcsname}%
⟨latexrelease | package⟩    \pickup@font
⟨latexrelease | package⟩    \font@name
⟨latexrelease | package⟩    \size@update
⟨latexrelease | package⟩    \enc@update
⟨latexrelease | package⟩   }
⟨latexrelease | package⟩
⟨latexrelease | package⟩\EndIncludeInRelease
```

`\set@fontsize` The macro `\set@fontsize` does the actual work. First it assigns new values to `\f@size`, `\f@baselineskip` and `\f@linespread`.

```
⟨*2ekernel | package⟩
\def\set@fontsize#1#2#3{%
    \@defaultunits\@tempdimb#2pt\relax\@nnil
```

```
    \edef\f@size{\strip@pt\@tempdimb}%
    \@defaultunits\@tempskipa#3pt\relax\@nnil
    \edef\f@baselineskip{\the\@tempskipa}%
    \edef\f@linespread{#1}%
```

For backward compatibility and for later testing within `\selectfont` the internal value of `\f@linespread` is passed back to `\baselinestretch`.

```
    \let\baselinestretch\f@linespread
```

Additional processing will happen within `\selectfont`. For this reason the macro `\size@update` (which will be called in `\selectfont`) will be defined to be:

```
      \def\size@update{%
```

First calculate the new `\baselineskip` and also store it in `normalbaselineskip`

```
        \baselineskip\f@baselineskip\relax
        \baselineskip\f@linespread\baselineskip
        \normalbaselineskip\baselineskip
```

then to set up a new `\strutbox`

```
        \setbox\strutbox\hbox{%
          \vrule\@height.7\baselineskip
                \@depth.3\baselineskip
                \@width\z@}%
```

We end with a bit of tracing information.

```
⟨*trace⟩
   \ifnum \tracingfonts>\tw@
      \ifx\f@linespread\@empty
        \let\reserved@a\@empty
      \else
        \def\reserved@a{\f@linespread x}%
      \fi
      \@font@info{Changing size to \f@size/\reserved@a
                \f@baselineskip}%
      \aftergroup\type@restoreinfo \fi
⟨/trace⟩
```

When all this is processed `\size@update` redefines itself to `\relax` so that in later calls of `\selectfont` no extra code will be executed.

```
        \let\size@update\relax}%
  }
```

Instead of defining this macro internally we might speed things up by placing the code into a separate macro and use `\let`!

(*End definition for* `\set@fontsize`.)

`\size@update` Normally this macro does nothing; it will be redefined by `\set@fontsize` to initiate an update.

```
\let\size@update\relax
```

(*End definition for* `\size@update`.)

\type@restoreinfo This macro produces some info when a font size and/or baseline change will get restored.

```
⟨*trace⟩
  \def\type@restoreinfo{%
    \ifx\f@linespread\@empty
      \let\reserved@a\@empty
    \else
      \def\reserved@a{\f@linespread x}%
    \fi
    \@font@info{Restoring size to
              \f@size/\reserved@a\f@baselineskip}}
⟨/trace⟩
```

(*End definition for* \type@restoreinfo.)

\glb@settings The macro \glb@settings globally selects all math fonts for the current size if necessary.
\glb@currsize

```
\def\glb@settings{%
```

When \glb@settings gains control a size change was requested and all previous font assignments need to be replaced. Therefore the old values of the fonts are no longer needed. For every *math group* the new assignments are appended to \math@fonts. But this happens only if the math@fonts switch is set to true. However, we always set up the correct math sizes for script and scriptscript fonts since they may be needed even if we don't set up the whole math machinery.

Here we set the math size, script size and scriptscript size. If the S@... macro is not defined we have to first calculate the three sizes.

```
    \expandafter\ifx\csname S@\f@size\endcsname\relax
      \calculate@math@sizes
    \fi
```

The effect of this is that \calculate@math@sizes may or may not define the S@... macro. In the first case the next time the same size is requested this macro is used, otherwise \calculate@math@sizes is called again. This also sets the math@fonts switch. If it is true we must switch the math fonts.

```
    \csname S@\f@size\endcsname
    \ifmath@fonts
⟨*trace⟩
      \ifnum \tracingfonts>\tw@
        \@font@info{Setting up math fonts for
                    \f@size/\f@baselineskip}\fi
⟨/trace⟩
```

Inside a group we execute the macro for the current math *version*. This sets \math@fonts to a list of \textfont... assignments. \getanddefine@fonts (which may be called at this point) needs the \escapechar parameter to be set to −1.

```
      \begingroup
        \escapechar\m@ne
        \csname mv@\math@version \endcsname
```

Then we set \globaldefs to 1 so that all following changes are done globally. The math font assignments recorded in \math@fonts are executed and \glb@currsize is set equal to \f@size. This signals that the fonts for math in this size are set up.

```
        \globaldefs\@ne
        \math@fonts
```

```
          \let \glb@currsize \f@size
        \endgroup
```

Finally we execute any code that is supposed to happen whenever the math font setup changes. This register will be executed in local mode which means that everything that is supposed to have any effect should be done globally inside. We can't execute it within `\globaldefs\@ne` as we don't know what ends up inside this register, e.g., it might contain calculations which use some local registers to calculate the final (global) value.

```
         \the\every@math@size
```

Otherwise we announce that the math fonts are not set up for this size.

```
⟨*trace⟩
        \else
          \ifnum \tracingfonts>\tw@
            \@font@info{No math setup for
                        \f@size/\f@baselineskip}\fi
⟨/trace⟩
      \fi
}
⟨/2ekernel | package⟩
```

(*End definition for* `\glb@settings` *and* `\glb@currsize`.)

`\baselinestretch` In `\selectfont` we used `\baselinestretch` as a factor when assigning a value to `\baselineskip`. We use 1 as a default (i.e. no stretch).

```
⟨*2ekernel⟩
\def\baselinestretch{1}
```

(*End definition for* `\baselinestretch`.)

`\every@math@size` We must still define the hook `\every@math@size` we used in `\glb@settings`. We initialize it to nothing. It is important to remember that everything that goes into this hook should to global updates, local changes will have weird effects.

```
\newtoks\every@math@size
\every@math@size={}
⟨/2ekernel⟩
```

(*End definition for* `\every@math@size`.)

5.2 Math fonts setup

5.2.1 Outline of algorithm for math font sizes

TEX uses the math fonts that are current when the end of a formula is reached. If we don't want to keep font setups local to every formula (which would result in an enormous overhead, we have to be careful not to end up with the wrong setup in case formulas are nested, e.g., we need to be able to handle

```
$ a=b+c \mbox{ \small for all $b$ and $c\in Z$}$
```

Here the inner formulae `b` and `c\in Z` are typeset in `\small` but we have to return to `\normalsize` before we reach the closing `$` of the outer formula.

This is handled in the following way:

1. At any point in the document the global variable `\gbl@currsize` contains the point size for which the math fonts currently are set up.

2. Whenever we start a formula we compare its value with the local variable `\f@size` that describes the current text font size.

3. If both are the same we assume that we can use the current math font setup without adjustment.

4. If they differ we call `\gbl@settings` which changes the math font setup and updates `\gbl@currsize`.

   (a) If we are recursively inside another formula (`\if@inmath`) we ensure that `\gbl@settings` is executed again in the outer formula, so that the old setup is automatically restored.

   (b) Otherwise, we set the switch `@inmath` locally to `true` so that all nested formulae will be able to detect that they are nested in some outer formula.

The above algorithm has the following features:

- For sizes which are not containing any formula no math setup is done. Compared to the original algorithm of NFSS this results in the following savings:
  - No unnecessary loading of math fonts for sizes that are not used to typeset any math formulae (explicit or implicit ones).
  - No time overhead due to unnecessary changes of the math font setup on entrance and exit of the text font size.
- Math font setup changes for top-level formulae will survive (there is no restoration after the formula) thus any following formula in the same size will be directly typesetable. Compared to original implementation in NFSS2 the new algorithm has the overhead of one test per formula to see if the current math setup is valid (in the original algorithm the setup was always valid, thus no test was necessary).
- In nested formulae the math font setup is restored in the outer formula by a series of `\aftergroup` commands and checks. Compared to the original algorithm this involves additional checks ($2 \times \langle$non-math levels$\rangle$ per inner formula).

5.2.2 Code for math font size setting

`\check@mathfonts` In the `\check@mathfonts` macros we implement the steps 2 to 4 except that instead of a switch the macro `\init@restore@glb@settings` is used.

```
⟨*2ekernel | package⟩
\def\check@mathfonts{%
  \ifx \glb@currsize \f@size
⟨*trace⟩
    \ifnum \tracingfonts>\thr@@
        \@font@info{*** MATH: no change \f@size\space
         curr/global (\curr@math@size/\glb@currsize)}\fi
⟨/trace⟩
  \else
⟨*trace⟩
    \ifnum \tracingfonts>\thr@@
        \@font@info{*** MATH: setting up \f@size\space
         curr/global (\curr@math@size/\glb@currsize)}\fi
⟨/trace⟩
```

```
    \glb@settings
    \init@restore@glb@settings
  \fi
  \let\curr@math@size\f@size
  \def\init@restore@glb@settings{\aftergroup\restglb@settings}%
}
```

(*End definition for* `\check@mathfonts`.)

`\init@restore@glb@settings` This macros does by default nothing but get redefined inside `\check@mathfonts` to initiate fontsize restoring in nested formulas.

```
⟨-trace⟩\let\init@restore@glb@settings\relax
⟨*trace⟩
\def\init@restore@glb@settings{%
       \ifnum \tracingfonts>\thr@@
        \@font@info{*** MATH: no resetting (not in
                    nested math)}\fi
}
⟨/trace⟩
```

(*End definition for* `\init@restore@glb@settings`.)

`\restglb@settings` This macro will be executed the first time after the current formula.

```
\def\restglb@settings{%
⟨*trace⟩
    \ifnum \tracingfonts>\thr@@
        \@font@info{*** MATH: restoring}\fi
⟨/trace⟩
      \begingroup
        \let\f@size\curr@math@size
        \ifx\glb@currsize \f@size
⟨*trace⟩
    \ifnum \tracingfonts>\thr@@
        \@font@info{*** MATH: ... already okay (\f@size)}\fi
⟨/trace⟩
        \else
⟨*trace⟩
    \ifnum \tracingfonts>\thr@@
        \@font@info{*** MATH: ... to \f@size}\fi
⟨/trace⟩
          \glb@settings
        \fi
      \endgroup
}
```

(*End definition for* `\restglb@settings`.)

5.2.3 Other code for math

`\use@mathgroup` The `\use@mathgroup` macro should be used in user macros to select a math group. Depending on whether or not the `margid` option is in force it has two or three arguments. For this reason it should be called as the last macro.

First we test if we are inside math mode since we don't want to apply a useless definition.

```
\def\use@mathgroup#1#2{\relax\ifmmode
```

```
⟨*trace⟩
  \ifnum \tracingfonts>\tw@
    \count@#2\relax
    \@font@info{Using \noexpand\mathgroup
              (\the\count@) #2}\fi
⟨/trace⟩
```

If so we first call the '=' macro (i.e. argument three) to set up special things for the selected math group. Then we call `\mathgroup` to select the group given by argument two and finally we place `#1` (i.e. the argument of the ⟨*math alphabet identifier*⟩ at the end. This part of the code is surrounded by two commands which behave like `\begingroup` and `\endgroup` if we want ⟨*math alphabet identifier*⟩s but will expand into `\@empty` if we want simply switches to a new math group. Since argument number 2 may be a digit instead of a control sequence we add a `\relax`. Otherwise something like `\mit{1}` would switch to math group 11 (and back) instead of printing an oldstyle 1.

```
      \math@bgroup
          \expandafter\ifx\csname M@\f@encoding\endcsname#1\else
          #1\fi
          \mathgroup#2\relax
```

Before we reinsert the swallowed token (arg. three) into the input stream, in the case that the ⟨*math alphabet identifier*⟩ isn't called in math mode, we remove the `\fi` with the `\expandafter` trick. This is necessary if the token is actually an macro with arguments. In such a case the `\fi` will be misinterpreted as the first argument which would be disastrous.

```
      \expandafter\math@egroup\fi}%
```

The surrounding macros equal `\begingroup` and `\endgroup`. But using internal names makes it possible to overwrite their meaning in certain cases. This is for example used in $\mathcal{A}\mathcal{M}\mathcal{S}$-TEX macros for placing accents.

(*End definition for* `\use@mathgroup`.)

`\math@egroup` If the `margid` option is in force (which can be tested by looking at the definition of `\math@bgroup` we change the `\math@egroup` command a bit to display the current ⟨*math group number*⟩ after it closes the scope of ⟨*math alphabet*⟩ with `\endgroup`.

```
⟨*trace⟩
  \ifx\math@bgroup\bgroup
    \def\math@egroup#1{#1\egroup
      \ifnum \tracingfonts>\tw@
     \@font@info{Restoring \noexpand\mathgroup
        (\ifnum\mathgroup=\m@ne default\else \the\mathgroup \fi)%
        }\fi}
  \fi
⟨/trace⟩
```

(*End definition for* `\math@egroup`.)

`\getanddefine@fonts` `\getanddefine@fonts` has two arguments: the ⟨*math group number*⟩ and the *family/series/shape* name as a control sequence.

```
\def\getanddefine@fonts#1#2{%
```

First we turn of tracing when `\tracingfonts` is less than 4.

```
⟨+debug⟩  \pushtracing
⟨+debug⟩  \ifnum\tracingfonts<4 \tracingoff
⟨+debug⟩  \else \tracingon\getanddefine@fonts \fi
```

```
⟨*trace⟩
  \ifnum \tracingfonts>\tw@
  \count@#1\relax
    \@font@info{\noexpand\mathgroup (\the\count@) #1 :=\MessageBreak
                \string#2 \tf@size/\sf@size/\ssf@size}\fi
⟨/trace⟩
```

We append the current `\tf@size` to `#2` to obtain the font name.[27] Again, `font@name` is defined globally, for the reasons explained in the description of `\wrong@fontshape`.

```
  \xdef\font@name{\csname \string#2/\tf@size\endcsname}%
```

Then we call `\pickup@font` to load it if necessary. We remember the internal name as `\textfont@name`.

```
  \pickup@font \let\textfont@name\font@name
```

Same game for `\scriptfont` and `\scriptscriptfont`:

```
  \xdef\font@name{\csname \string#2/\sf@size\endcsname}%
  \pickup@font \let\scriptfont@name\font@name
  \xdef\font@name{\csname \string#2/\ssf@size\endcsname}%
  \pickup@font
```

Then we append the new `\textfont...` assignments to the `\math@fonts`.

```
  \edef\math@fonts{\math@fonts
                 \textfont#1\textfont@name
                 \scriptfont#1\scriptfont@name
                 \scriptscriptfont#1\font@name}%
```

Just before ending this macro we have to pop the tracing stack if it was pushed before.

```
⟨+debug⟩ \poptracing
    }
⟨/2ekernel | package⟩
```

(*End definition for* `\getanddefine@fonts`.)

6 Scaled font extraction

`\ifnot@nil`

We begin with a simple auxiliary macro. It checks whether its argument is the token `\@nil`. If so, it expands to `\@gobble` which discards the following argument, otherwise it expands to `\@firstofone` which reproduces it argument.

```
⟨*2ekernel⟩
\def\ifnot@nil#1{\def\reserved@a{#1}%
  \ifx\reserved@a\@nnil \expandafter\@gobble
  \else \expandafter\@firstofone\fi}
```

(*End definition for* `\ifnot@nil`.)

`\remove@to@nnil` `\remove@angles` `\remove@star`

Three other auxiliary macros will be needed in the following: `\remove@to@nnil` gobbles up everything up to, and including, the next `\@nnil` token, and `\remove@angles` and `\remove@star` do the same for the character `>` and `*`, respectively, instead of `\@nnil`.

```
\def\remove@to@nnil#1\@nnil{}
\def\remove@angles#1>{\set@simple@size@args}
\def\remove@star#1*{#1}
```

[27] One might ask why this expansion does not generate a macro name that starts with an additional `\` character. The solution is that `\escapechar` is set to −1 before `\getanddefine@fonts` is called.

(*End definition for* `\remove@to@nnil`, `\remove@angles`, *and* `\remove@star`.)

`\extract@sizefn` This macro takes a size specification and parses it into size function and the optional and mandatory arguments.

```
\def\extract@sizefn#1*#2\@nil{%
  \if>#2>\set@size@funct@args#1\@nil
         \let\sizefn@info\@empty
  \else\expandafter\set@size@funct@args\remove@star#2\@nil
       \def\sizefn@info{#1}\fi
  }
```

(*End definition for* `\extract@sizefn`.)

`\try@simple@size` This function tries to extract the given size (specified by `\f@size`) for the requested font shape. The font information must already be present in `\font@info`. The central macro that does the real work is `\extract@fontinfo`. We will first give a simple example how this macro works, and describe it in full generality later.

Assume that the requested parameters are: *encoding scheme* 'OT1', *family* 'cm', *series* 'sansserif', *shape* 'normal', and *size* '12'. The corresponding font definitions have already been extracted from the macro `\OT1/cm/sansserif/normal` and stored in `font@info`. (Otherwise `\extract@fontinfo` doesn't get called.) This information consists of a token list made of characters of category code 12 of the form

```
<10*>cmss10<12*>cmss12<17*>cmss17
```

For reasonable packages one usually needs more sizes but this is sufficient to get the flavour. We will define a macro `\extract@fontinfo` to find the external font name ('cmss12') for us:

```
\def\extract@fontinfo#1<12*#2>#3<#4\@nnil{%
    \set@simple@size@args#3<#4\@nnil
    \execute@size@function{#2}}
```

so that when it gets called via

```
\extract@fontinfo<10*>cmss10<12*>cmss12<17*>cmss17\@nnil
```

`#1` will contain all characters before `<12*>`, `#2` will be empty, `#3` will be exactly `cmss12`, and `#3` will be `17>cmss17`. The expansion is therefore

```
\set@simple@size@args cmss12<17*>cmss17\@nnil
\execute@size@function{}
```

This means: the default (empty) size function will be executed, with its optional argument set to empty and its mandatory argument set to `cmss12` by `\set@simple@size@args`. As we discussed earlier, the effect of the default size function is to load the given external font (cmss12) at the specified size (12)—which is exactly what was intended.

But this is only part of the whole story. It may be that the size requested does not occur in the token list `\font@info`. And the simple definition of `\extract@fontinfo` we gave above does not allow to specify give more than one size specification in front of the external font name.

Let's address these two problems separately. The first one is solved with the following trick: We define `\extract@fontinfo` as follows:

```
\def\extract@fontinfo#1<12*#2>#3<#4\@nnil{%
  \ifnot@nil{#3}%
    {\set@simple@size@args#3<#4\@nnil
     \execute@size@function{#2}%
    }}%
```

How does this work? We call `\extract@fontinfo` via

```
\expandafter\extract@fontinfo\font@info<12*>\@nil<\@nnil
```

i.e. by appending `<12*>\@nil<\@nnil`. If the size ('12' in this case) appears in `\font@info` everything works as explained above, the only difference being that argument `#4` of `\extract@fontinfo` additionally gets the tokens `<12*>\@nil<\@nnil`. However, if the size is not found everything up to the final `<12*>` is in argument `#1`, `#3` gets `\@nil`, and `#2` and `#4` are empty. The macro `\ifnot@nil` will discard the calls to `\set@simple@size@args` and `execute@size@function`, and hence `\font@info` will continue to be equal to `\@empty`. This means that no simple size specification matching the requested size could be found.

The second problem (more than one simple size specification for one external font name) will be addressed in `\set@simple@size@args` below.

The macros are hidden inside other control sequences so that we have to build `\extract@fontinfo` in several steps.

So here's the actual definition of `\extract@font` in `\try@simple@size`.

```
% % this could be replaced by \try@size@range making the subst slower!
\def\try@simple@size{%
```

`\reserved@a` is made an abbreviation for the head of the definition of the macro `\extract@fontinfo`.

```
    \def\reserved@a{\def\extract@fontinfo####1}%
```

Now we can define `\extract@fontinfo`. Here we handle a small but convenient variation: in case of the default (empty) size function it is allowed to omit the `*` character.

```
    \expandafter\reserved@a\expandafter<\f@size>##2<##3\@nnil{%
          \ifnot@nil{##2}%
            {\set@simple@size@args##2<##3\@nnil
             \execute@size@function\sizefn@info
            }}%
```

Now we call `\extract@fontinfo`. Note the `<\@nil` tokens at the end.

```
    \expandafter\expandafter
    \expandafter\extract@fontinfo\expandafter\font@info
    \expandafter<\f@size>\@nil<\@nnil
}
```

(*End definition for* `\try@simple@size`.)

`\set@simple@size@args` As promised above, the macro `\set@simple@size@args` will handle the case of several size specifications in a row. If another size specification follows, the very first token of its argument list is the character `<`. By starting the definition as follows,

```
\def\set@simple@size@args#1<{%
```

parameter #1 is empty in this case, and contains the size function's arguments otherwise. We distinguish these two cases (Note that the character < cannot appear in #1) by calling \remove@angles for empty #1 and \extract@sizefn otherwise. In the latter case we have to take care of the remaining character tokens and discard them. This is done by \remove@to@nnil. Note also the use of Kabelschacht's method.

```
          \if<#1<%
            \expandafter\remove@angles
          \else
            \extract@sizefn#1*\@nil
            \expandafter\remove@to@nnil
          \fi}
```

(*End definition for* \set@simple@size@args.)

Now, we are through with the case of a simple size, except for calling the size function. This will be handled later, as it is the same mechanism for all types of size specification. We will now proceed to macros for extraction of size range specification.

\extract@rangefontinfo

\extract@rangefontinfo goes through a font shape definition in the input until it recognizes the tokens <\@nil->. It looks for font ranges with font size functions. It's operation is rather simple: it discards everything up to the next size specification and passes this on to \is@range for inspection. The specification (parameter #2 is inserted again, in case it is needed later.

```
\def\extract@rangefontinfo#1<#2>{%
        \is@range#2->\@nil#2>}
```

(*End definition for* \extract@rangefontinfo.)

\is@range

\is@range is again a sort of dispatcher macro: if the size specification it is looking at is not a range specification it discards it and calls \extract@rangefontinfo to continue the search. Otherwise it calls \check@range to check the requested size against the specified range.

From the way \is@range is called inside \extract@rangefontinfo we see that #2 is the character > if the size specification found is a simple one (as it does not contain a - character. This is checked easily enough and \extract@rangefontinfo called again. Note that the extra tokens inserted after the \@nil in the call to \is@range appear at the beginning of the first argument to \extract@rangefontinfo and are hence ignored.

```
\def\is@range#1-#2\@nil{%
   \if>#2\expandafter\check@single\else
      \expandafter\check@range\fi}
```

(*End definition for* \is@range.)

\check@range

\check@range takes lower bound as parameter #1, upper bound as #2, size function as #3 and the size function's arguments as #4. If #3 is the special token \@nil \font@info is exhausted and we can stop searching.

```
\def\check@range#1-#2>#3<#4\@nnil{%
  \ifnot@nil{#3}{%
```

If #3 wasn't \@nil we have a range. We start by assuming that we have to recurse. Note that we have to reinsert an < as it was already removed by scanning.

```
      \def\reserved@f{\extract@rangefontinfo<#4\@nnil}%
```

We have to make sure that both boundaries are present, if not we have to set them. Here we check the upper bound. If `\upper@bound` is zero after the assignment we set it to `\maxdimen` (upper open range). We need to use a ⟨*dimen*⟩ register for the scan since we may have a decimal number as the boundary.

```
      \upper@bound0#2\p@
      \ifdim\upper@bound=\z@ \upper@bound\maxdimen\fi
```

Now we check the upper boundary against `\f@size`. If it is larger or equal than `\f@size` this range is no good and we have to recurse.

```
      \ifdim \f@size \p@<\upper@bound
```

Otherwise we have to check the lower bound. This time it is not necessary to scan the boundary value into a register because if it is empty we get zero as desired. We could even omit the `0` which would result in `1pt` as default lower boundary. If `\f@size` is smaller than the boundary we have to recurse.

```
        \lower@bound0#1\p@
        \ifdim \f@size \p@<\lower@bound
         \else
```

If both tests are passed we can try executing the size function.

```
          \set@simple@size@args#3<#4\@nnil
          \execute@size@function\sizefn@info
```

If the function was successful it should have left an external font name in `\external@font`. We use this to see if we can stop scanning. Otherwise we recurse.

```
         \ifx\external@font\@empty
         \else
           \let\reserved@f\@empty
         \fi
        \fi
      \fi
      \reserved@f}}
```

(*End definition for* `\check@range`.)

`\lower@bound` `\upper@bound`

We use two dimen registers `\lower@bound` and `\upper@bound` to store the lower and upper endpoints of the range we found.

```
\newdimen\lower@bound
\newdimen\upper@bound
```

(*End definition for* `\lower@bound` *and* `\upper@bound`.)

`\check@single`

`\check@single` takes the size as parameter `#1`, size function as `#2` and the size function's arguments as `#3`. We can assume that there is always something in the pipeline since the very last entry is a faked range (see above).

```
\def\check@single#1>#2<#3\@nnil{%
```

We start by assuming that we have to recurse. Note that we have to reinsert an `<` as it was already removed by scanning.

```
      \def\reserved@f{\extract@rangefontinfo<#3\@nnil}%
```

Now we check the size against `\f@size`. If it is not equal `\f@size` it is no good and we have to recurse.

```
      \ifdim \f@size \p@=#1\p@
```

Otherwise if this test is passed we can try executing the size function.

```
        \set@simple@size@args#2<#3\@nnil
        \execute@size@function\sizefn@info
```

If the function was successful it should have left an external font name in `\external@font`. We use this to see if we can stop scanning. Otherwise we recurse.

```
        \ifx\external@font\@empty
        \else
          \let\reserved@f\@empty
        \fi
      \fi
      \reserved@f}
```

(*End definition for* `\check@single`.)

`\set@size@funct@args` `\set@size@funct@args@`

This macro sets the optional and mandatory arguments for a size function. If the optional argument is not present it is set to the empty token list. The mandatory argument is delimited by the token `\@nil`.

```
\def\set@size@funct@args{\@ifnextchar[%
  \set@size@funct@args@{\set@size@funct@args@[]}}
```

```
\def\set@size@funct@args@[#1]#2\@nil{%
  \def\mandatory@arg{#2}%
  \def\optional@arg{#1}}
⟨/2ekernel⟩
```

(*End definition for* `\set@size@funct@args` *and* `\set@size@funct@args@`.)

`\DeclareSizeFunction`

This function defines a new size function hiding the internal from the designer. The body of the size function may use `\optional@arg` and `\mandatory@arg` denoting the optional and mandatory argument that may follow the size specification `<...>`.

```
⟨*2ekernel⟩
\def\DeclareSizeFunction#1#2{\@namedef{s@fct@#1}{#2}}
\@onlypreamble\DeclareSizeFunction
⟨/2ekernel⟩
```

(*End definition for* `\DeclareSizeFunction`.)

`\execute@size@function`

This macro is very simple. The only point worth noting is that calling an undefined size function will do nothing (actually execute a `\relax`).

```
⟨*2ekernel | package⟩
\def\execute@size@function#1{%
⟨*trace⟩
          \@ifundefined{s@fct@#1}%
            {\errmessage{Undefined font size function #1}%
             \s@fct@}%
            {\csname s@fct@#1\endcsname}%
⟨/trace⟩
⟨-trace⟩       \csname s@fct@#1\endcsname
}
⟨/2ekernel | package⟩
```

(*End definition for* `\execute@size@function`.)

\try@size@range This macro tries to find a suitable range for requested size (specified by \f@size) in \font@info. All the relevant action is done in \extract@rangefontinfo. All that needs to be done is to stuff in the token list in \font@info so that \extract@rangefontinfo can inspect it. Note the <-*\@nil>< token at the end to stop scanning.

```
⟨*2ekernel⟩
\def\try@size@range{%
    \expandafter\extract@rangefontinfo\font@info <-*>\@nil<\@nnil
}
```

(*End definition for* \try@size@range.)

\try@size@substitution This is the last thing that can be tried. If the desired \f@size is found neither among the simple size specifications nor in one of the ranges the whole list of size specifications is searched for a nearby simple size.

```
\gdef\try@size@substitution{%
```

First we do some initializations. \@tempdimb will hold the difference between the wanted size and the best solution found so far, so we initialise it with \maxdimen. The macro \best@size will hold the best size found, nothing found is indicated by the empty value.

```
  \@tempdimb \maxdimen
  \let \best@size \@empty
```

Now we loop over the specification

```
  \expandafter \try@simples \font@info <\number\@M>\@nil<\@nnil
}
```

(*End definition for* \try@size@substitution.)

\font@submax \fontsubfuzz The macro \font@submax records the maximal deviation from the desired size encountered so far. Its value is used in a warning message at \end{document}. The macro \fontsubfuzz contains the amount that will not cause terminal warnings (warnings still go into the transcript file).

```
\def\font@submax{0pt}
\def\fontsubfuzz{.4pt}
⟨/2ekernel⟩
⟨+package⟩\def\fontsubfuzz{0pt}
```

(*End definition for* \font@submax *and* \fontsubfuzz.)

\try@simples \try@simples goes through a font shape definition in the input until it recognizes the tokens <*\@nil><. It looks for simple sizes to determine the two closest sizes. It is assumed that simple sizes are in increasing order.

```
⟨*2ekernel⟩
\gdef\try@simples#1<#2>{%
  \tryif@simple#2->\tryif@simple}
```

(*End definition for* \try@simples.)

\tryis@simple \tryis@simple is similar to \is@range. If it sees a simple size, it checks it against the value of \f@size and sets \lower@font@size or \higher@font@size. In the latter case, it stops the iteration. By adding <\number\@M> at the end of the line we always have an end point. This is a hack which probably should be corrected.

First it checks whether it is finished already, then whether the size specification in question is a simple one.

```
\gdef\tryif@simple#1-#2\tryif@simple{%
```

Most common case for `\reserved@f` first:

```
\let \reserved@f \try@simples
\if>#2%
```

If so, it compares it to the value of `\f@size`. This is done using a dimen register since there may be fractional numbers.

```
  \dimen@ #1\p@
  \ifdim \dimen@<\@M\p@
```

If `\dimen@` is `\@M\p@` we have reached the end of the fontspec (hopefully) otherwise we compare the value with `\f@size` and compute in `\@tempdimc` the absolute value of the difference between the two values.

```
    \ifdim \f@size\p@<\dimen@
      \@tempdimc \dimen@
      \advance\@tempdimc -\f@size\p@
    \else
      \@tempdimc \f@size\p@
      \advance\@tempdimc -\dimen@
    \fi
```

The result is then compared with the smallest difference we have encountered, if the new value (in `\@tempdimc` is smaller) we have found a size which is a better approximation so we make it the `\best@size` and adjust `\@tempdimb`.

```
    \ifdim \@tempdimc<\@tempdimb
      \@tempdimb \@tempdimc
      \def \best@size{#1}%
    \fi
```

When we have reached the end of the fontspec we substitute the best size found (if any). We code this inline to save macro space; in the past this was done by a macro called `\subst@size`.

```
  \else
```

`\subst@size`

This macro substitutes the size recorded in `\best@size` for the unavailable size `\f@size`. `\font@submax` records the maximum difference between desired size and selected size in the whole run.

```
% %\subst@size             %% coded inline
% %\def\subst@size{%
  \ifx \external@font\@empty
    \ifx \best@size\@empty
    \else
      \ifdim \@tempdimb>\font@submax \relax
        \xdef \font@submax {\the\@tempdimb}%
      \fi
      \let \f@user@size \f@size
      \let \f@size \best@size
      \ifdim \@tempdimb>\fontsubfuzz\relax
        \@font@warning{Font\space shape\space
            `\curr@fontshape'\space in\space size\space
             <\f@user@size>\space not\space available\MessageBreak
             size\space <\f@size>\space substituted}%
      \fi
      \try@simple@size
      \do@subst@correction
```

```
    \fi
  \fi
% %}
```

This brings us back into the main part of `\tryif@simple`. Finally we get rid of any rubbish left over on the input stack.

```
      \let \reserved@f \remove@to@nnil
    \fi
  \fi
```

If it's a range iterate also.

```
  \reserved@f}
```

(*End definition for* `\tryis@simple` *and* `\subst@size`.)

6.1 Sizefunctions

In the following we define some useful size functions.

`\s@fct@` This is the default size function. Mandatory argument is an external font name, optional argument a scale factor. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```
\DeclareSizeFunction{}{\empty@sfcnt\@font@warning}
\DeclareSizeFunction{s}{\empty@sfcnt\@font@info}
```

```
\def\empty@sfcnt#1{%
      \@tempdimb \f@size\p@
      \ifx\optional@arg\@empty
      \else
        \@tempdimb \optional@arg\@tempdimb
        #1{Font\space shape\space `\curr@fontshape'\space
           will\space be\MessageBreak
           scaled\space to\space size\space \the\@tempdimb}%
      \fi
      \edef\external@font{\mandatory@arg\space at\the\@tempdimb}}
```

(*End definition for* `\s@fct@`.)

`\s@fct@gen` `\s@fct@sgen` This size function generates the external name from the mandatory argument and the requested user size, and thus can be used for external names where the size is encoded in the font name. The optional argument a scale factor. The font is scaled to `\f@size` if no optional argument is present, and to `\f@size` multiplied by the optional argument otherwise.

```
\DeclareSizeFunction{gen}{\gen@sfcnt\@font@warning}
\DeclareSizeFunction{sgen}{\gen@sfcnt\@font@info}
```

```
\def\gen@sfcnt{%
      \edef\mandatory@arg{\mandatory@arg\f@size}%
      \empty@sfcnt}
```

(*End definition for* `\s@fct@gen` *and* `\s@fct@sgen`.)

\s@fct@genb
\s@fct@sgenb

This size function is similar to gen, but for fonts where the size is encoded in the font name in centipoints, as in the DC fonts version 1.2. The font is scaled to \f@size if no optional argument is present, and to \f@size multiplied by the optional argument otherwise.

```
\DeclareSizeFunction{genb}{\genb@sfcnt\@font@warning}
\DeclareSizeFunction{sgenb}{\genb@sfcnt\@font@info}
```

```
\def\genb@sfcnt{%
    \edef\mandatory@arg{\mandatory@arg\expandafter\genb@x\f@size..\@@}%
    \empty@sfcnt}
```

(*End definition for* \s@fct@genb *and* \s@fct@sgenb.)

\genb@x
\genb@y

The auxiliary macros \genb@x and \genb@y are used to convert the \f@size into centipoints.

```
\def\genb@x#1.#2.#3\@@{\two@digits{#1}\genb@y#200\@@}
\def\genb@y#1#2#3\@@{#1#2}
```

(*End definition for* \genb@x *and* \genb@y.)

\s@fct@sub

This size function handles font substitution. The mandatory argument is a family/series/shape combination, the optional argument (if present) is ignored. The font encoding scheme cannot be changed. Therefore, the first thing we do is to prepend the encoding scheme.

```
\DeclareSizeFunction{sub}{\sub@sfcnt\@font@warning}
\DeclareSizeFunction{ssub}{\sub@sfcnt\@font@info}
```

```
\def\sub@sfcnt#1{%
    \edef\mandatory@arg{\f@encoding/\mandatory@arg}%
```

Next action is split the arg into its individual components and allow for a late font shape load.

```
    \begingroup
     \expandafter\split@name\mandatory@arg/\@nil
     \try@load@fontshape
    \endgroup
```

Then we record the current \f@size since it may get clobbered.

```
    \let\f@user@size\f@size
```

Then we check whether this new combination is defined and give an error message if not. In this case we also switch to \error@fontshape.

```
    \expandafter
    \ifx\csname\mandatory@arg\endcsname\relax
      \errmessage{No\space declaration\space for\space
                  shape\space \mandatory@arg}%
      \error@fontshape
    \else
```

Otherwise we warn the user about the substitution taking place.

```
      #1{Font\space shape\space `\curr@fontshape'\space in\space
         size\space <\f@size>\space not\space available\MessageBreak
         Font\space shape\space `\mandatory@arg'\space tried\space
         instead}%
      \expandafter\split@name\mandatory@arg/\@nil
    \fi
```

Then we restart the font specification scan by calling `\get@external@font`.

```
    \edef\f@size{\f@user@size}%
    \get@external@font
```

Finally `\do@subst@correction` is called to get the font name right.

```
    \do@subst@correction
}
```

(*End definition for* `\s@fct@sub`.)

`\@font@aliasinfo` Sometimes a substitution is only done to map a long font name to a standard shape or series, e.g.,

```
DeclareFontShape{T1}{Roboto-LF}{b}{it}{<-> alias * Roboto-LF/bold/it}{}
```

Using the `ssub` function in that case will give a strange (and incorrect) warning. As an alternative we therefore offer the size function `alias`. It will still add some info into the `.log` file, but no longer complains that the font shape is not available. It is implemented by grabbing the default warning text and replacing it with a new one.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\@font@aliasinfo}{alias size function}%
\DeclareSizeFunction{alias}{\sub@sfcnt\@font@aliasinfo}
\def\@font@aliasinfo#1{%
  \@font@info{Font\space shape\space `\curr@fontshape'\space
              aliased\space to\MessageBreak `\mandatory@arg'}%
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@font@aliasinfo}{alias size function}%
⟨latexrelease⟩\let\s@fct@alias\@undefined
⟨latexrelease⟩\let\@font@aliasinfo\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@font@aliasinfo`.)

`\s@fct@subf` The `subf` size function allows substitution of another font. The mandatory argument is the external name of the font to be substituted, the optional argument a size scaling factor like in the default size function. The main difference to the default size function is the warning message.

```
\DeclareSizeFunction{subf}{\subf@sfcnt\@font@warning}
\DeclareSizeFunction{ssubf}{\subf@sfcnt\@font@info}
```

```
\def\subf@sfcnt#1{%
      #1{Font\space shape\space `\curr@fontshape'\space in\space
         size\space \f@size\space not\space available\MessageBreak
        external\space font\space `\mandatory@arg'\space used}%
      \empty@sfcnt#1%
      }
```

(*End definition for* `\s@fct@subf`.)

`\s@fct@fixed` The `fixed` size function is for using a font at a different size than requested. A warning message is printed, and the external font to be used is taken from the mandatory argument. If an optional argument is present it is used as the 'at' size for the font. Otherwise the font is loaded at its design size.

```
\DeclareSizeFunction{fixed}{\fixed@sfcnt\@font@warning}
\DeclareSizeFunction{sfixed}{\fixed@sfcnt\@font@info}
```

```
\def\fixed@sfcnt#1{%
  \ifx\optional@arg\@empty
    \let\external@font\mandatory@arg
  \else
    \edef\external@font{\mandatory@arg\space at\optional@arg pt}%
  \fi
  #1{External\space font\space `\external@font'\space loaded\space
     for\space size\MessageBreak
     <\f@size>}%
}
⟨/2ekernel⟩
```

(*End definition for* `\s@fct@fixed`.)

File y
ltfsscmp.dtx

This file contains the implementation of commands giving compatibility with the original 'NFSS1' release of the Font Selection Scheme.

> **Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

Version 1 of NFSS is obsolete now for about 20 years (and was "current" only for a short intermediate time) so with the 2015 release these internal interface commands are removed from the kernel and made available via latexrelease package so that backward compatibility remains ensured for very old documents.

```
⟨*latexrelease⟩
\IncludeInRelease{2015/01/01}{\new@fontshape}%
                             {NFSS version1 commands}%
\let\new@fontshape\@undefined
\let\warn@rel@i\@undefined
\let\scan@fontshape\@undefined
\let\scan@@fontshape\@undefined
\let\subst@fontshape\@undefined
\let\extra@def\@undefined
\let\default@mextra\@undefined
\let\preload@sizes\@undefined
\let\err@rel@i\@undefined
\let\newmathalphabet\@undefined
\let\newmathalphabet@\@undefined
\let\newmathalphabet@@@\@undefined
\let\if@no@font@opt\@undefined
\let\@no@font@optfalse\@undefined
\let\define@mathalphabet\@undefined
\let\define@mathgroup\@undefined
\let\addtoversion\@undefined
\EndIncludeInRelease
```

In older releases we provide the original definitions.

```
\IncludeInRelease{0000/00/00}{\new@fontshape}%
                             {NFSS version1 commands}%
```

`\new@fontshape` The interface is now `\DeclareFontShape`.

```
\gdef\new@fontshape#1#2#3#4{%
     \warn@rel@i\new@fontshape\DeclareFontShape
     \expandafter\scan@fontshape\@gobble#4<\@nil><<%
     \DeclareFontShape U{#1}{#2}{#3}\reserved@f}%
\@onlypreamble\new@fontshape
```

(*End definition for* `\new@fontshape`.)

`\warn@rel@i` The warning message used above.

```
\gdef\warn@rel@i#1#2{%
 \@font@warning{***  NFSS release 1 command
```

```
                \noexpand#1found\MessageBreak
   ***  Update by using release 2 command
        \string#2.\MessageBreak
   ***  Recovery is probably possible}%
}%
\@onlypreamble\warn@rel@i
```

(*End definition for* `\warn@rel@i`.)

`\scan@fontshape` This will scan the old font shape definition syntax.

```
\gdef\scan@fontshape{%
  \let\reserved@f\@empty
  \let\reserved@e\@empty %        holds last info
  \scan@@fontshape
}%
\@onlypreamble\scan@fontshape
```

(*End definition for* `\scan@fontshape`.)

`\scan@@fontshape`

```
\gdef\scan@@fontshape#1>#2#3<{%
  \ifx\@nil#1%
    \edef\reserved@f{\reserved@f\reserved@e}%
  \else
    \def\reserved@b{#1}%       nick names
    \def\reserved@c{#3}%
    \in@{ at}{#3}%
    \ifin@
      \in@{pt}{#3}%  not a proof but a good chance
      \ifin@
```

We grab also everything after pt and discard it if people have forgotten to place a percent sign there.

```
        \def\reserved@a##1 at##2pt##3\@nil{%
           \def\reserved@b{##2}%
           \def\reserved@c{##1}%
           }%
        \reserved@a#3\@nil
      \fi
    \fi
    \ifnum 0<0#2
      \edef\reserved@d{subf*\reserved@c}%
      \ifcase #2\or
      \or
      \else
        \errmessage{*** What's this? NFSS release 0? ***}%
      \fi
    \else
      \edef\reserved@d{#2\reserved@c}%
    \fi
    \ifx\reserved@d\reserved@e
      \edef\reserved@f{\reserved@f<\reserved@b>}%
    \else
      \edef\reserved@f{\reserved@f\reserved@e<\reserved@b>}%add old info
      \let\reserved@e\reserved@d
```

```
    \fi
    \expandafter\scan@@fontshape
  \fi
}%
\@onlypreamble\scan@@fontshape
```

(*End definition for* `\scan@@fontshape`.)

`\subst@fontshape` This is now also handled by the extend syntax of `\DeclareFontShape`.

```
\gdef\subst@fontshape#1#2#3#4#5#6{%
     \warn@rel@i\subst@fontshape\DeclareFontShape
     \DeclareFontShape{U}{#1}{#2}{#3}{<->sub*#4/#5/#6}{}}%
\@onlypreamble\subst@fontshape
```

(*End definition for* `\subst@fontshape`.)

`\extra@def` This was replaced by `\DeclareFontFamily`.

```
\gdef\extra@def#1#2#3{%
     \warn@rel@i\extra@def\DeclareFontFamily
     \DeclareFontFamily{U}{#1}{}%
}%
\@onlypreamble\extra@def
```

(*End definition for* `\extra@def`.)

`\default@mextra` The new name is `\DeclareFontEncodingDefaults` but in this case we don't feel comfortable with this either.

```
\gdef\default@mextra{%
  \warn@rel@i\default@mextra\DeclareFontEncodingDefaults
```

We pick up the argument to `\default@mextra` implicitly as the second argument of `\DeclareFontEncodingDefaults`.

```
  \DeclareFontEncodingDefaults\relax
}%
\@onlypreamble\default@mextra
```

(*End definition for* `\default@mextra`.)

`\preload@sizes` The new interface is `\DeclarePreloadSizes`.

```
\gdef\preload@sizes{%
     \warn@rel@i\preload@sizes\DeclarePreloadSizes
     \DeclarePreloadSizes U%
}%
\@onlypreamble\preload@sizes
```

(*End definition for* `\preload@sizes`.)

`\err@rel@i` This macro is used in cases where emulation with NFSS2 features is not really possible.

```
\gdef\err@rel@i#1#2{%
  \@latex@error{***  NFSS release 1 command \noexpand#1found%
          ^^J***  Recovery not possible. Use \string#2}%
       {The new release of NFSS doesn't support the
        \noexpand#1command^^Jany longer.
        Please upgrade your file to the syntax of NFSS
        release 2^^Jusing the \noexpand#2command.}%
```

Let's die.

```
  \batchmode\input.\relax
}%
\@onlypreamble\err@rel@i
```

(*End definition for* `\err@rel@i`.)

`\newmathalphabet` `\newmathalphabet@@` `\newmathalphabet@@@`

`\newmathalphabet` is the old form.

```
\gdef\newmathalphabet{%
  \if@no@font@opt
    \@latex@error{*** NFSS release 1 command
                    \noexpand\newmathalphabet found%
     ^^J \space*** Automatic recovery not possible.%
     ^^J \space*** TYPE H for Help%
              }%
       {Please look at the file usrguide.tex for hints on
        how to resolve this problem.}%
  \else
     \warn@rel@i\newmathalphabet\DeclareMathAlphabet
  \fi
  \@ifstar\newmathalphabet@@@
          \newmathalphabet@@}%
\gdef\newmathalphabet@@#1{\DeclareMathAlphabet#1{U}{}{}{}}%
\gdef\newmathalphabet@@@#1#2#3#4{%
       \DeclareMathAlphabet{#1}{U}{#2}{#3}{#4}}%
\@onlypreamble\newmathalphabet
\@onlypreamble\newmathalphabet@@
\@onlypreamble\newmathalphabet@@@
```

(*End definition for* `\newmathalphabet`, `\newmathalphabet@@`, *and* `\newmathalphabet@@@`.)

`\if@no@font@opt` `\@no@font@optfalse`

```
\global\let\if@no@font@opt\iftrue
\gdef\@no@font@optfalse{\let\if@no@font@opt\iffalse}%
```

(*End definition for* `\if@no@font@opt` *and* `\@no@font@optfalse`.)

`\define@mathalphabet`

This is a case where dying is best.

```
\gdef\define@mathalphabet{%
      \err@rel@i\define@mathalphabet\DeclareMathAlphabet
}%
\@onlypreamble\define@mathalphabet
```

(*End definition for* `\define@mathalphabet`.)

`\define@mathgroup`

And here is another one

```
\gdef\define@mathgroup{%
      \err@rel@i\define@mathgroup\DeclareSymbolFont
}%
\@onlypreamble\define@mathgroup
```

(*End definition for* `\define@mathgroup`.)

\addtoversion \addtoversion is the old form.

```
\def\addtoversion#1#2{%
  \warn@rel@i\addtoversion\SetMathAlphabet
  \SetMathAlphabet#2{#1}{U}}%
\@onlypreamble\addtoversion
```

(*End definition for* \addtoversion.)

Finishing off this huge \IncludeInRelease argument:

```
\EndIncludeInRelease
⟨/latexrelease⟩
```

File z
ltfssdcl.dtx

This file contains the main implementation of the font selection scheme commands. See other parts of the LaTeX distribution, or *The LaTeX Companion* for higher level documentation of these commands.

> **Warning:** The macro documentation is still basically the documentation from the first NFSS release and therefore in some cases probably not completely accurate.

1 Interface Commands

`\in@` `\ifin@`

`\@in` is a utility macro with two arguments. It determines whether its first argument occurs in its second and sets the switch `\ifin@` accordingly. The first argument may not contain braces nor `#` (more precisely, tokens of category code 1, 2, or 6).

```
⟨*2ekernel⟩
\def\in@#1#2%
 {%
   \begingroup
     \def\in@@##1#1{}%
     \toks@\expandafter{\in@@#2{}{}#1}%
     \edef\in@@{\the\toks@}%
   \expandafter\endgroup
   \ifx\in@@\@empty
     \in@false
   \else
     \in@true
   \fi
 }
\newif\ifin@
```

(*End definition for* `\in@` *and* `\ifin@`.)

Before the `\begin{document}` command several ⟨*math versions*⟩ and ⟨*math alphabet identifiers*⟩ may be declared. In principle, there should be exactly one family/series/shape combination be declared for each version/alphabet pair. But we want to allow for defaults as well for automagical filling of holes.

While building the tables for math alphabet identifiers and math versions we keep several lists:

- the list of all math versions, `\version@list`, each entry prefixed by the control sequence `\version@elt`, i.e. this list has the following form

  `\version@elt`⟨*version*$_1$⟩`\version@elt`⟨*version*$_2$⟩... `\version@elt`⟨*version*$_n$⟩

- the list of all math alphabet identifiers. Here every entry has the form:

  `\group@elt`⟨*math group number*⟩ `{{`⟨*default family*⟩`}{`⟨*default series*⟩`}{`⟨*default shape*⟩`}}`.

- Each defined math alphabet identifier holds a list containing Information about the *versions* for which it is defined. This list has a more complicated structure: it looks as follows:

  \set@alpha⟨*the alphabet identifier itself*⟩
  \reserved@c⟨*math version*⟩⟨*font info*⟩
  ...
  \@nil

  where ⟨*font info*⟩ is either \reserved@e (if the combination is not defined yet) or

  {{⟨*family*⟩}{⟨*series*⟩}{⟨*shape*⟩}}

\version@list We initialize the version list to be empty.

```
\let\version@list=\@empty
\@onlypreamble\version@list
```

(*End definition for* \version@list.)

\version@elt

```
\let\version@elt\relax
\@onlypreamble\version@elt
```

(*End definition for* \version@elt.)

\new@mathversion The macro \new@mathversion is called with the version control sequence as its argument.

```
%\def\new@mathversion#1{%
```

The first thing this macro does is to check if the version identifier is already present in \version@list. We enclose \version@list in braces since it might be empty (if no *version* is defined yet). But this means that we need a suitable number of \expandafter primitives.

```
%  \expandafter\in@\expandafter#1\expandafter{\version@list}%
%  \ifin@
```

If so it prints an error message. The \next macro is used to get rid of the four characters \mv@ that would otherwise appear at the begin of the version name in the error message.

```
%    \@latex@error{Math version
%                 `\expandafter\@gobblefour\string#1'
%                 already defined}\@eha
```

Otherwise we have a new version, and we can proceed with entering it into the tables. We add it to \version@list. This is very easy: we define \version@elt (which is the delimiter in \version@list) to protect itself and the following token from being expanded and simply redefine \version@list.

```
%  \else
%     \global\expandafter\newcount\csname c@\expandafter
%                                 \@gobble\string#1\endcsname
%     \global\csname c@\expandafter
%                                 \@gobble\string#1\endcsname\@ne
%     \def\version@elt{\noexpand\version@elt\noexpand}%
%     \edef\version@list{\version@list\version@elt#1}%
```

Then we prepare to enter the new version into all math alphabet identifier lists. Remember that these lists use `\reserved@c` as delimiter, and that there appears the control sequence `\reserved@e` that must not be expanded. Therefore we take suitable precautions.

```
%     \def\reserved@c{\noexpand\reserved@c\noexpand}%
%     \let\reserved@e\relax
```

We will now go through the `\alpha@list` to process every ⟨*math alphabet identifier*⟩ in turn. Since this list has `\group@elt` as a delimiter we define this control sequence. It has three arguments as every entry consists of three items (as explained above).

```
%     \def\group@elt##1##2##3{%
```

The first of these arguments is the ⟨*math alphabet identifier*⟩. We redefine it by appending the information about the new version at the end of the list contained in it. However, there is one subtlety: the definitions for `\reserved@c` and `\reserved@e` made above prevent the main part of the list from being expanded. But we still have to take care of the header and the trailer. To do this we remove the trailer by means of the macro `\remove@nil` which also protect the header from being expanded. Its definition is given below. Now we can prepare to add the new version.

```
%         \edef##1{\expandafter\remove@nil##1%
%                  \reserved@c
%                  #1%
%                  \reserved@e
%                  \noexpand\@nil}}%
```

Finally we call `\alpha@list` which will now execute the macro `\group@elt` once for every defined ⟨*math alphabet identifier*⟩. And that's all for now.

```
%     \alpha@list
%  \fi}
```

(*End definition for* `\new@mathversion`.)

`\alpha@list` As we explained above every entry in `\alpha@list` has the form

`\alpha@elt`
⟨*alphabet identifier*⟩⟨*internal group number*⟩⟨*default font assignments*⟩...

We initialize it to `\@empty`.

```
\let\alpha@list\@empty
\@onlypreamble\alpha@list
```

(*End definition for* `\alpha@list`.)

`\alpha@elt`

```
\let\alpha@elt\relax
\@onlypreamble\alpha@elt
```

(*End definition for* `\alpha@elt`.)

`\newgroup` Start the group (fam) allocation at 0. (Doesn't belong here.)

```
\count18=-1
```

(*End definition for* `\newgroup`.)

`\stepcounter`

(*End definition for* `\stepcounter`.)

`\select@group` We surround `\select@group` with braces so that functions using it can be used directly after `_` or `^`. However, if we use oldstyle syntax where the math alphabet doesn't have arguments (ie if `\math@bgroup` is not `\bgroup`) we need to get rid of the extra group.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}
⟨latexrelease⟩                  {\select@group}{\select@group}%
⟨*2ekernel | latexrelease⟩
\def\select@group#1#2#3#4{%
 \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
 {%
 \ifmmode
  \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
     \begingroup
       \escapechar\m@ne
       \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
       \globaldefs\@ne  \math@fonts
     \endgroup
     \init@restore@version
     \xdef#1{\noexpand\use@mathgroup\noexpand#2%
             {\number\csname c@mv@\math@version\endcsname}}%
     \global\advance\csname c@mv@\math@version\endcsname\@ne
   \else
     \let#1\relax
     \@latex@error{Too many math alphabets used in
                   version \math@version}%
        \@eha
   \fi
 \else \expandafter\non@alpherr\fi
 #1{#4}%
 }%
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}
⟨latexrelease⟩                  {\select@group}{\select@group}%
⟨latexrelease⟩\def\select@group#1#2#3#4{%
⟨latexrelease⟩ \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
⟨latexrelease⟩ {%
⟨latexrelease⟩ \ifmmode
⟨latexrelease⟩  \ifnum\csname c@mv@\math@version\endcsname<\sixt@@n
⟨latexrelease⟩     \begingroup
⟨latexrelease⟩       \escapechar\m@ne
⟨latexrelease⟩       \getanddefine@fonts
⟨latexrelease⟩         {\csname c@mv@\math@version\endcsname}#3%
⟨latexrelease⟩       \globaldefs\@ne  \math@fonts
⟨latexrelease⟩     \endgroup
⟨latexrelease⟩     \init@restore@version
⟨latexrelease⟩     \xdef#1{\noexpand\use@mathgroup\noexpand#2%
⟨latexrelease⟩             {\number\csname c@mv@\math@version\endcsname}}%
⟨latexrelease⟩     \global\advance\csname c@mv@\math@version\endcsname\@ne
⟨latexrelease⟩   \else
⟨latexrelease⟩     \let#1\relax
⟨latexrelease⟩     \@latex@error{Too many math alphabets used in
⟨latexrelease⟩                   version \math@version}%
```

```
⟨latexrelease⟩         \@eha
⟨latexrelease⟩    \fi
⟨latexrelease⟩ \else \expandafter\non@alpherr\fi
⟨latexrelease⟩ #1{#4}%
⟨latexrelease⟩ }%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\restore@mathversion
```

(*End definition for* `\select@group`.)

`\init@restore@version`

```
\def\init@restore@version{%
        \global\let\init@restore@version\relax
        \xdef\restore@mathversion
             {\expandafter\noexpand\csname mv@\math@version\endcsname
              \global\csname c@mv@\math@version\endcsname
              \number\csname c@mv@\math@version\endcsname\relax}%
        \aftergroup\dorestore@version
}
\@onlypreamble\init@restore@version
```

(*End definition for* `\init@restore@version`.)

`\non@alpherr`

```
\gdef\non@alpherr#1{\@latex@error{%
```

The command here will have a space at the end of its name, so we make sure not to insert an extra one.

```
    \string#1allowed only in math mode}\@ehd}
```

(*End definition for* `\non@alpherr`.)

`\dorestore@version`

```
\def\dorestore@version
 {\ifmmode
    \aftergroup\dorestore@version
  \else
    \gdef\init@restore@version{%
        \global\let\init@restore@version\relax
        \xdef\restore@mathversion
             {\expandafter\noexpand\csname mv@\math@version\endcsname
              \global\csname c@mv@\math@version\endcsname
              \number\csname c@mv@\math@version\endcsname\relax}%
        \aftergroup\dorestore@version
    }%
    \begingroup
      \let\getanddefine@fonts\@gobbletwo
      \restore@mathversion
    \endgroup
  \fi}%
\@onlypreamble\dorestore@version
```

(*End definition for* `\dorestore@version`.)

\c@localalphabets To avoid hitting the "no more math fams available" limit of 16, we keep a defined number of math alphabets flexible/local. If we have to allocate any of those we roll back the allocation after the formula has ended, so the next formula can use other alphabets in the slot(s). This makes the processing a bit slower if you are working at the limit, but that is better than dying with "out of memory".

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}
⟨latexrelease⟩   {\document@select@group}{\document@select@group}%
⟨*2ekernel | latexrelease⟩
```

We don't really undo the declaration on rollback (as that would be hard to maintain), so rolling forward needs to check if the declaration was already made.

```
\ifx\c@localmathalphabets\@undefined
```

There is no need to have this counter as part of the include checkpoints, given that it makes little sense to alter its settings mid document. All we want is the ability to change it using the \setcounter interface.

By default we keep two math fams flexible.

```
  \newcount\c@localmathalphabets
  \setcounter{localmathalphabets}{2}
\fi
```

(*End definition for* \c@localalphabets.)

\document@select@group The \document@select@group command is the version of \select@group (inside math versions) that is used in the document body to set up math alphabets (if used).

```
\def\document@select@group#1#2#3#4{%
 \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
 {%
 \ifmmode
```

We first check if there is still room for allocating another mathgroup. If there is, we check if it can be globally allocated or if we have reached the limit which is given by \e@mathgroup@top with \c@localmathalphabets subtracted.

```
   \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
     \ifnum \numexpr\e@mathgroup@top-\c@localmathalphabets
              >\csname c@mv@\math@version\endcsname
     \else
```

If we are past this point we freeze the current state of the math version so that we can return to it after the formula has ended. Of course, that should be done only once, so we check if \mv@⟨*version*⟩@frozen already exists.

```
       \ifcsname mv@\math@version @frozen\endcsname \else
```

We have to pass the current value of \math@version not the macro itself, because some of the processing is delayed to a point where the value may have changed again—not doing this caused a puzzling error in one setup.

```
         \expandafter\freeze@math@version\expandafter{\math@version}%
       \fi
     \fi
     \begingroup
       \escapechar\m@ne
       \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
       \globaldefs\@ne  \math@fonts
```

```
    \endgroup
    \expandafter\extract@alph@from@version
        \csname mv@\math@version\expandafter\endcsname
        \expandafter{\number\csname
                      c@mv@\math@version\endcsname}%
         #1%
    \global\advance\csname c@mv@\math@version\endcsname\@ne
  \else
    \let#1\relax
    \@latex@error{Too many math alphabets used in
                  version \math@version}%
       \@eha
 \fi
```

Extra `\expandafter` to remove the `\expandafter` added below

```
\else \expandafter\expandafter\expandafter\non@alpherr\fi
```

We surround `\select@group` with braces so that functions using it can be used directly after `_` or `^`.

If the legacy interface is used, e.g., `$\sf -1$` the math alphabet `#1` does not take an argument so we better do not surround `#4` with braces, because then we get `{\relax}` into the formula and introduce an extra Ord atom. The two different cases can be distinguished by looking at the current value of `\math@bgroup`.

```
\expandafter#1\ifx\math@bgroup\bgroup{#4}\else#4\fi
}%
}
```

`\freeze@math@version`

This command stores the current state of the math version and sets things up to return to it after each formula from now on. We use L3 programming layer code to set it up.

```
\ExplSyntaxOn
\cs_new_protected:Npn\freeze@math@version #1 {
```

Save the current `\mv@`⟨*version*⟩ code and the number of allocated mathgroups inside.

```
  \@font@info{Freeze~ math~ alphabet~ allocation~ in~ version~
              #1.\MessageBreak
              Allocated~math~groups:~\int_use:c{ c@mv@ #1 }~
              (local:~  \int_use:N\c@localmathalphabets)      }
  \cs_gset_eq:cc { mv@#1@frozen }{ mv@#1 }
  \tl_gset:cx { g__nfss_frozen_mv_ #1 _tl }{ \int_use:c { c@mv@#1 } }
```

Doing the reset the first time, we wait until we are out of math mode, so we use some recursive `\group_insert_after:N` for this before we execute `\mv@`⟨*version*⟩`@reset`.

```
  \group_insert_after:N \__nfss_init_mv_freeze:N \exp_after:wN
    \group_insert_after:N \cs:w mv@#1@reset \cs_end:
```

The `\check@mathfonts` is called at the very beginning of each math formula, so it is a good way to hook in the resetting. Again that has to happen after the formula has ended, but we know because of the place where `\check@mathfonts` is used that a single `\aftergoup` is sufficient.

```
  \tl_gput_right:No \check@mathfonts
      {
        \exp_after:wN \group_insert_after:N \cs:w mv@#1@reset \cs_end:
      }
```

Here is the definition of \mv@⟨*version*⟩@reset. If there has been no new math alphabet allocation, doing a reset would just cause a lot of unnecessary processing, so we do a quick check upfront for this.

```
\cs_gset:cpn{mv@#1@reset}
   {
       \int_compare:nNnTF { \int_use:c{c@mv@#1} } >
                          { \tl_use:c{g__nfss_frozen_mv_ #1 _tl} }
           {
             \@font@info{Undo~ math~ alphabet~ allocation~ in~ version~ #1}
```

If the undo is necessary, we restore the \mv@⟨*version*⟩ code.

```
             \cs_gset_eq:cc { mv@#1 }{ mv@#1@frozen }
             \int_gset:cn { c@mv@#1 }{ \tl_use:c {g__nfss_frozen_mv_ #1 _tl} }
```

But we also should undo changes to the math alphabet definitions. We therefore run this code with a modified definition for \getanddefine@fonts because there is no need to do anything to the symbol fonts that are permanently allocated.

```
             \group_begin:
               \cs_set_eq:NN \getanddefine@fonts \use_none:nn
               \use:c {mv@#1}
             \group_end:
           }
           {
```

If there was no change, we report that in the log (but this branch could go completely).

```
             \@font@info{No~ math~ alphabet~ change~ to~ frozen~ version~ #1}
           }
   }
}
```

__nfss_init_mv_freeze:N

To do the initial freeze in a safe place, we check if we are in math mode and if so try again after the group has ended by pushing the command and its single token argument with two \group_insert_after:Ns after the current group. If we are no longer in math mode we bypass the conditional and so the next token is our argument which is then finally executed.

```
\cs_new_protected:Npn \__nfss_init_mv_freeze:N #1 {%
  \mode_if_math:T { \group_insert_after:N \__nfss_init_mv_freeze:N
                    \group_insert_after:N } #1
}

\ExplSyntaxOff

⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}
⟨latexrelease⟩  {\document@select@group}{\document@select@group}%
⟨latexrelease⟩
⟨latexrelease⟩\def\document@select@group#1#2#3#4{%
⟨latexrelease⟩ \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
⟨latexrelease⟩ {%
⟨latexrelease⟩ \ifmmode
⟨latexrelease⟩   \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
⟨latexrelease⟩     \begingroup
⟨latexrelease⟩       \escapechar\m@ne
⟨latexrelease⟩       \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
```

```
⟨latexrelease⟩       \globaldefs\@ne  \math@fonts
⟨latexrelease⟩     \endgroup
⟨latexrelease⟩     \expandafter\extract@alph@from@version
⟨latexrelease⟩         \csname mv@\math@version\expandafter\endcsname
⟨latexrelease⟩         \expandafter{\number\csname
⟨latexrelease⟩                       c@mv@\math@version\endcsname}%
⟨latexrelease⟩          #1%
⟨latexrelease⟩     \global\advance\csname c@mv@\math@version\endcsname\@ne
⟨latexrelease⟩   \else
⟨latexrelease⟩     \let#1\relax
⟨latexrelease⟩     \@latex@error{Too many math alphabets used
⟨latexrelease⟩                   in version \math@version}%
⟨latexrelease⟩        \@eha
⟨latexrelease⟩  \fi
⟨latexrelease⟩ \else \expandafter\expandafter\expandafter\non@alpherr\fi
⟨latexrelease⟩ \expandafter#1\ifx\math@bgroup\bgroup{#4}\else#4\fi
⟨latexrelease⟩ }%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2015/01/01}
⟨latexrelease⟩  {\document@select@group}{\document@select@group}%
⟨latexrelease⟩
⟨latexrelease⟩\def\document@select@group#1#2#3#4{%
⟨latexrelease⟩ \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
⟨latexrelease⟩ {%
⟨latexrelease⟩ \ifmmode
⟨latexrelease⟩   \ifnum\csname c@mv@\math@version\endcsname<\e@mathgroup@top
⟨latexrelease⟩     \begingroup
⟨latexrelease⟩       \escapechar\m@ne
⟨latexrelease⟩       \getanddefine@fonts{\csname c@mv@\math@version\endcsname}#3%
⟨latexrelease⟩       \globaldefs\@ne  \math@fonts
⟨latexrelease⟩     \endgroup
⟨latexrelease⟩     \expandafter\extract@alph@from@version
⟨latexrelease⟩         \csname mv@\math@version\expandafter\endcsname
⟨latexrelease⟩         \expandafter{\number\csname
⟨latexrelease⟩                       c@mv@\math@version\endcsname}%
⟨latexrelease⟩          #1%
⟨latexrelease⟩     \global\advance\csname c@mv@\math@version\endcsname\@ne
⟨latexrelease⟩   \else
⟨latexrelease⟩     \let#1\relax
⟨latexrelease⟩     \@latex@error{Too many math alphabets used
⟨latexrelease⟩                   in version \math@version}%
⟨latexrelease⟩        \@eha
⟨latexrelease⟩  \fi
⟨latexrelease⟩ \else \expandafter\non@alpherr\fi
⟨latexrelease⟩ #1{#4}%
⟨latexrelease⟩ }%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}
⟨latexrelease⟩  {\document@select@group}{\document@select@group}%
⟨latexrelease⟩
⟨latexrelease⟩\def\document@select@group#1#2#3#4{%
```

```
⟨latexrelease⟩ \ifx\math@bgroup\bgroup\else\relax\expandafter\@firstofone\fi
⟨latexrelease⟩ {%
⟨latexrelease⟩ \ifmmode
⟨latexrelease⟩   \ifnum\csname c@mv@\math@version\endcsname<\sixt@@n
⟨latexrelease⟩     \begingroup
⟨latexrelease⟩       \escapechar\m@ne
⟨latexrelease⟩       \getanddefine@fonts
⟨latexrelease⟩         {\csname c@mv@\math@version\endcsname}#3%
⟨latexrelease⟩       \globaldefs\@ne  \math@fonts
⟨latexrelease⟩     \endgroup
⟨latexrelease⟩     \expandafter\extract@alph@from@version
⟨latexrelease⟩         \csname mv@\math@version\expandafter\endcsname
⟨latexrelease⟩         \expandafter{\number\csname
⟨latexrelease⟩                       c@mv@\math@version\endcsname}%
⟨latexrelease⟩          #1%
⟨latexrelease⟩     \global\advance\csname c@mv@\math@version\endcsname\@ne
⟨latexrelease⟩   \else
⟨latexrelease⟩     \let#1\relax
⟨latexrelease⟩     \@latex@error{Too many math alphabets used
⟨latexrelease⟩                   in version \math@version}%
⟨latexrelease⟩        \@eha
⟨latexrelease⟩  \fi
⟨latexrelease⟩ \else \expandafter\non@alpherr\fi
⟨latexrelease⟩ #1{#4}%
⟨latexrelease⟩ }%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨∗2ekernel⟩
```

(*End definition for* `\document@select@group`, `\freeze@math@version`, *and* `\__nfss_init_mv_freeze:N`.)

`\process@table`

```
\def\process@table{%
    \def\cdp@elt##1##2##3##4{%
        \@font@info{Checking defaults for
                  ##1/##2/##3/##4}%
        \expandafter
        \ifx\csname##1/##2/##3/##4\endcsname\relax
```

Grouping is important for two reasons, first `\cdp@elt` will get redefined if `\Declare...` functions are executed within the external `.fd` file and secondly `\try@load@fontshape` changes a lot of catcodes without surrounding itself with a group.

```
          \begingroup
           \def\f@encoding{##1}\def\f@family{##2}%
           \try@load@fontshape
          \endgroup
        \fi
        \expandafter
        \ifx\csname##1/##2/##3/##4\endcsname\relax
             \@latex@error{This NFSS system isn't set up properly}%
                       {For encoding scheme ##1 the defaults
                        ##2/##3/##4 do not form a valid font shape}%
        \else
             \@font@info{... okay}%
```

```
        \fi}%
    \cdp@list
```

Now we make sure that `\error@fontshape` is okay.

```
    \begingroup
       \escapechar\m@ne
       \error@fontshape
       \expandafter\ifx\csname \curr@fontshape\endcsname\relax
          \begingroup
            \try@load@fontshape
           \endgroup
       \fi
       \expandafter\ifx\csname \curr@fontshape\endcsname\relax
         \@latex@error{This NFSS system isn't set up properly}%
            {The system maintainer forgot to specify a suitable
             substitution
             font shape using the \noexpand\DeclareErrorFont
             command}%
       \fi
    \endgroup
```

Set `\select@group` to its meaning used within the document body.

```
    \let\select@group\document@select@group
```

Install the default font attributes as they are currently pointing to error font face. We can speed up the process by just using `\edef`, thereby avoiding all kind of extra processing. Don't use `\reset@font` since that would trigger `\selectfont`.

```
    \fontencoding\encodingdefault
    \edef\f@family{\familydefault}%
    \edef\f@series{\seriesdefault}%
    \edef\f@shape{\shapedefault}%
```

Drop stuff not longer needed. We need to add many more!!!!!!

```
 \everyjob{}%
}
\@onlypreamble\process@table
```

(*End definition for* `\process@table`.)

```
%\@onlypreamble\set@mathradical
```

`\DeclareMathVersion`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                    {\DeclareMathVersion}{local alphabets}%
\def\DeclareMathVersion#1{%
```

When declaring a new math version we need to instantiate an L3 variable that is used when we freeze the version, because too many alphabets got allocated. If we don't do this, L3 programming layer complains if it is run in checking mode.

```
  \@namedef{g__nfss_frozen_mv_#1_tl}{}%
  \expandafter\new@mathversion\csname mv@#1\endcsname}
\@onlypreamble\DeclareMathVersion
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\DeclareMathVersion}{local alphabets}%
⟨latexrelease⟩\def\DeclareMathVersion#1{%
⟨latexrelease⟩  \expandafter\new@mathversion\csname mv@#1\endcsname}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\DeclareMathVersion`.)

`\new@mathversion`

```
\def\new@mathversion#1{%
  \expandafter\in@\expandafter#1\expandafter{\version@list}%
  \ifin@
    \@font@info{Redeclaring math version
                `\expandafter\@gobblefour\string#1'}%
  \else
    \expandafter\newcount\csname c@\expandafter
                                 \@gobble\string#1\endcsname
    \def\version@elt{\noexpand\version@elt\noexpand}%
    \edef\version@list{\version@list\version@elt#1}%
  \fi
```

`\toks@` is used to gather all tokens for the math version. `\count@` will be used to count the math groups we add to this version.

```
  \toks@{}%
  \count@\z@
```

Now we loop over `\group@list` to add all math groups defined so far to the version and at the same time to count them.

```
  \def\group@elt##1##2{%
       \advance\count@\@ne
       \addto@hook\toks@{\getanddefine@fonts##1##2}%
       }%
  \group@list
```

We set the counter for this math version to the number of math groups found in `\group@list`.

```
  \global\csname c@\expandafter\@gobble\string#1\endcsname\count@
```

Now we loop over `\alpha@list` to add all math alphabets known so far. We have to distinguish the case that an alphabet by default should produce an error in new versions.

```
  \def\alpha@elt##1##2##3{%
       \ifx##2\no@alphabet@error
         \toks@\expandafter{\the\toks@\install@mathalphabet##1%
             {\no@alphabet@error##1}}%
       \else
         \toks@\expandafter{\the\toks@\install@mathalphabet##1%
             {\select@group##1##2##3}}%
       \fi
          }%
  \alpha@list
```

Finally we define the math version to expand to the contents of `\toks@`.

```
  \xdef#1{\the\toks@}%
}
\@onlypreamble\new@mathversion
```

(*End definition for* `\new@mathversion`.)

`\DeclareSymbolFont`

```
\def\DeclareSymbolFont#1#2#3#4#5{%
 \@tempswafalse
 \edef\reserved@b{#2}%
 \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
      \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
 \cdp@list
 \if@tempswa
   \@ifundefined{sym#1}{%
      \ifnum\count18<15 %
        \expandafter\new@mathgroup\csname sym#1\endcsname
        \expandafter\new@symbolfont\csname sym#1\endcsname
                        {#2}{#3}{#4}{#5}%
      \else
         \@latex@error{Too many symbol fonts declared}\@eha
      \fi
     }%
     {%
      \@font@info{Redeclaring symbol font ‘#1’}%
```

Update the group list.

```
      \def\group@elt##1##2{%
           \noexpand\group@elt\noexpand##1%
           \expandafter\ifx\csname sym#1\endcsname##1%
             \expandafter\noexpand\csname#2/#3/#4/#5\endcsname
           \else
               \noexpand##2%
           \fi}%
      \xdef\group@list{\group@list}%
```

Update the version list.

```
      \def\version@elt##1{%
          \expandafter
          \SetSymbolFont@\expandafter##1\csname#2/#3/#4/#5\expandafter
              \endcsname \csname sym#1\endcsname
          }%
      \version@list
     }%
  \else
    \@latex@error{Encoding scheme  ‘#2’ unknown}\@eha
  \fi
  }
\@onlypreamble\DeclareSymbolFont
```

(*End definition for* `\DeclareSymbolFont`.)

`\group@list`

```
\let\group@list\@empty
\@onlypreamble\group@list
```

(*End definition for* `\group@list`.)

\group@elt

```
\let\group@elt\relax
\@onlypreamble\group@elt
```

(*End definition for* \group@elt.)

\new@symbolfont

```
\def\new@symbolfont#1#2#3#4#5{%
    \toks@\expandafter{\group@list}%
    \edef\group@list{\the\toks@\noexpand\group@elt\noexpand#1%
                      \expandafter\noexpand\csname#2/#3/#4/#5\endcsname}%
    \def\version@elt##1{\toks@\expandafter{##1}%
                     \edef##1{\the\toks@\noexpand\getanddefine@fonts
                     #1\expandafter\noexpand\csname#2/#3/#4/#5\endcsname}%
                    \global\advance\csname c@\expandafter
                                  \@gobble\string##1\endcsname\@ne
                  }%
    \version@list
}
\@onlypreamble\new@symbolfont
```

(*End definition for* \new@symbolfont.)

\SetSymbolFont

```
\def\SetSymbolFont#1#2#3#4#5#6{%
 \@tempswafalse
 \edef\reserved@b{#3}%
 \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
      \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
 \cdp@list
 \if@tempswa
  \expandafter\SetSymbolFont@
    \csname mv@#2\expandafter\endcsname\csname#3/#4/#5/#6\expandafter
    \endcsname \csname sym#1\endcsname
 \else
  \@latex@error{Encoding scheme  `#3' unknown}\@eha
 \fi
}
\@onlypreamble\SetSymbolFont
```

(*End definition for* \SetSymbolFont.)

\SetSymbolFont@

```
\def\SetSymbolFont@#1#2#3{%
  \expandafter\in@\expandafter#1\expandafter{\version@list}%
  \ifin@
    \expandafter\in@\expandafter#3\expandafter{\group@list}%
    \ifin@
      \begingroup
        \expandafter\get@cdp\string#2\@nil\reserved@a
        \toks@{}%
        \def\install@mathalphabet##1##2{%
             \addto@hook\toks@{\install@mathalphabet##1{##2}}%
            }%
```

```
        \def\getanddefine@fonts##1##2{%
          \ifnum##1=#3%
             \addto@hook\toks@{\getanddefine@fonts#3#2}%
             \expandafter\get@cdp\string##2\@nil\reserved@b
             \ifx\reserved@a\reserved@b\else
                \@font@info{Encoding `\reserved@b' has changed
                    to `\reserved@a' for symbol font\MessageBreak
                   `\expandafter\@gobblefour\string#3' in the
                    math version `\expandafter
                    \@gobblefour\string#1'}%
             \fi
             \@font@info{%
                Overwriting symbol font
                `\expandafter\@gobblefour\string#3' in
                 version `\expandafter
                \@gobblefour\string#1'\MessageBreak
                \@spaces \expandafter\@gobble\string##2 -->
                         \expandafter\@gobble\string#2}%
          \else
             \addto@hook\toks@{\getanddefine@fonts##1##2}%
          \fi}%
         #1%
         \xdef#1{\the\toks@}%
      \endgroup
    \else
       \@latex@error{Symbol font `\expandafter\@gobblefour\string#3'
                  not defined}\@eha
    \fi
  \else
    \@latex@error{Math version `\expandafter\@gobblefour\string#1'
       is not
       defined}{You probably misspelled the name of the math
       version.^^JOr you have to specify an additional package.}%
  \fi
}
\@onlypreamble\SetSymbolFont@
```

(*End definition for* `\SetSymbolFont@`.)

`\get@cdp`

```
\def\get@cdp#1#2/#3\@nil#4{\def#4{#2}}
\@onlypreamble\get@cdp
```

(*End definition for* `\get@cdp`.)

`\DeclareMathAlphabet`

```
\def\DeclareMathAlphabet#1#2#3#4#5{%
 \@tempswafalse
 \edef\reserved@b{#2}%
 \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
      \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
 \cdp@list
 \if@tempswa
   \expandafter\ifx
   \csname\expandafter\@gobble\string#1\endcsname
```

```
   \relax
      \new@mathalphabet#1{#2}{#3}{#4}{#5}%
   \else
```

Check if it is already a math alphabet.

```
     \edef\reserved@a{\noexpand\in@{\string\select@group}%
         {\expandafter\meaning\csname \expandafter
          \@gobble\string#1\space\endcsname}}%
     \reserved@a
     \ifin@
       \@font@info{Redeclaring math alphabet \string#1}%
       \def\version@elt##1{%
         \expandafter\SetMathAlphabet@\expandafter
            ##1\csname#2/#3/#4/#5\expandafter\endcsname

            \csname M@#2\expandafter\endcsname
            \csname \expandafter\@gobble\string#1\space\endcsname#1}%
       \version@list
     \else
```

Check if it is a math alphabet defined via `\DeclareSymbolFontAlphabet`.

```
       \edef\reserved@a{\noexpand\in@{\string\use@mathgroup}%
         {\expandafter\meaning\csname \expandafter
          \@gobble\string#1\space\endcsname}}%
       \reserved@a
       \ifin@
```

In that case overwriting is simple since there is nothing inserted in the math version macros.

```
         \@font@info{Redeclaring math alphabet \string#1}%
         \new@mathalphabet#1{#2}{#3}{#4}{#5}%
```

Otherwise panic.

```
       \else
         \@latex@error{Command ‘\string#1’ already defined}\@eha
       \fi
     \fi
  \fi
 \else
  \@latex@error{Encoding scheme  ‘#2’ unknown}\@eha
 \fi
  }
\@onlypreamble\DeclareMathAlphabet
```

(*End definition for* `\DeclareMathAlphabet`.)

`\new@mathalphabet`

```
\def\new@mathalphabet#1#2#3#4#5{%
    \toks@\expandafter{\alpha@list}%
    \edef#1{\expandafter\noexpand\csname \expandafter
            \@gobble\string#1\space\endcsname
            \if/#5/%
               \noexpand\no@alphabet@error
               \noexpand\no@alphabet@error
            \else
               \expandafter\noexpand\csname M@#2\endcsname
```

```
                \expandafter\noexpand\csname#2/#3/#4/#5\endcsname
            \fi
           }%
    \toks2\expandafter{#1}%
    \edef\alpha@list{\the\toks@\noexpand\alpha@elt\the\toks2}%
    \def\version@elt##1{\toks@\expandafter{##1}%
                    \edef##1{\the\toks@\install@mathalphabet
                             \expandafter\noexpand
                             \csname \expandafter\@gobble
                                \string#1\space\endcsname
                            {\if/#5/%
                              \noexpand\no@alphabet@error
                              \noexpand#1%
                             \else
                              \noexpand\select@group\the\toks2
                             \fi}}%
                  }%
    \version@list
    \expandafter\edef\csname \expandafter\@gobble
                 \string#1\space\endcsname{\if/#5/%
              \noexpand\no@alphabet@error
              \noexpand#1%
            \else
              \noexpand\select@group\the\toks2
            \fi}%
    \edef#1{\noexpand\protect
            \expandafter\noexpand\csname \expandafter
            \@gobble\string#1\space\endcsname}%
}
\@onlypreamble\new@mathalphabet
```

(*End definition for* `\new@mathalphabet`.)

`\SetMathAlphabet`

```
\def\SetMathAlphabet#1#2#3#4#5#6{%
 \@tempswafalse
 \edef\reserved@b{#3}%
 \def\cdp@elt##1##2##3##4{\def\reserved@c{##1}%
      \ifx\reserved@b\reserved@c \@tempswatrue\fi}%
 \cdp@list
 \if@tempswa
  \expandafter\SetMathAlphabet@
    \csname mv@#2\expandafter\endcsname\csname#3/#4/#5/#6\expandafter
    \endcsname \csname M@#3\expandafter\endcsname
    \csname \expandafter\@gobble\string#1\space\endcsname#1%
 \else
  \@latex@error{Encoding scheme  `#3' unknown}\@eha
 \fi
}
\@onlypreamble\SetMathAlphabet
```

(*End definition for* `\SetMathAlphabet`.)

`\SetMathAlphabet@`

```
\def\SetMathAlphabet@#1#2#3#4#5{%
  \expandafter\in@\expandafter#1\expandafter{\version@list}%
  \ifin@
    \expandafter\in@\expandafter#4\expandafter{\alpha@list}%
    \ifin@
      \begingroup
        \toks@{}%
        \def\getanddefine@fonts##1##2{%
             \addto@hook\toks@{\getanddefine@fonts##1##2}%
            }%
        \def\reserved@c##1##2##3##4{%                % for message below
            \expandafter\@gobble\string##4}%
        \def\install@mathalphabet##1##2{%
          \ifx##1#4%
             \addto@hook\toks@
                {\install@mathalphabet#4{\select@group#4#3#2}}%
             \@font@info{Overwriting math alphabet
                `\string#5' in version `\expandafter
                 \@gobblefour\string#1'\MessageBreak
                 \@spaces \reserved@c##2 -->
                        \expandafter\@gobble\string#2}%
          \else
             \addto@hook\toks@{\install@mathalphabet##1{##2}}%
          \fi
          }%
        #1%
        \xdef#1{\the\toks@}%
      \endgroup
    \else
```

If the math alphabet was defined via `\DeclareSymbolFontAlphabet` we have remove its external definition and add it as a normal math alphabet to every version before trying to change it in one version.

```
        \edef\reserved@a{%
          \noexpand\in@{\string\use@mathgroup}{\meaning#4}}%
        \reserved@a
        \ifin@
          \def\reserved@b##1\use@mathgroup##2##3{%
              \def\reserved@b{##3}\def\reserved@c{##2}}%
          \expandafter\reserved@b#4%
          \begingroup
            \def\install@mathalphabet##1##2{%
                \addto@hook\toks@{\install@mathalphabet##1{##2}}%
                }%
             \def\getanddefine@fonts##1##2{%
               \addto@hook\toks@{\getanddefine@fonts##1##2}%
               \ifnum##1=\reserved@b
                  \expandafter
                  \addto@hook\expandafter\toks@
                  \expandafter{\expandafter\install@mathalphabet
                  \expandafter#4\expandafter
                        {\expandafter\select@group\expandafter
                          #4\reserved@c##2}}%
               \fi
```

```
                      }%
            \def\version@elt##1{%
                \toks@{}%
                ##1%
                \xdef##1{\the\toks@}%
               }%
            \version@list
          \endgroup
```

Put it into the `\alpha@list` with default 'error'

```
          \expandafter\gdef\expandafter\alpha@list\expandafter
              {\alpha@list
               \alpha@elt #4\no@alphabet@error \no@alphabet@error}%
          \gdef#4{\no@alphabet@error #5}% fake things :-)
```

Then call the internal setting routine again:

```
          \SetMathAlphabet@{#1}{#2}{#3}#4#5%
        \else
          \@latex@error{Command `\string#5' not defined as a
                        math alphabet}%
             {Use \noexpand\DeclareMathAlphabet to define it.}%
        \fi
    \fi
  \else
    \@latex@error{Math version `\expandafter\@gobblefour\string#1'
       is not
       defined}{You probably misspelled the name of the math
       version.^^JOr you have to specify an additional package.}%
  \fi
}
\@onlypreamble\SetMathAlphabet@
```

(*End definition for* `\SetMathAlphabet@`.)

`\DeclareMathAccent` Could do with more checks like allowing single number in `#4` lowercase in `#4` etc

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {DeclareMathAccent}{Make math accents robust}%
\def\DeclareMathAccent#1#2#3#4{%
  \expandafter\in@\csname sym#3\expandafter\endcsname
     \expandafter{\group@list}%
  \ifin@
    \begingroup
      \count\z@=#4\relax
      \count\tw@\count\z@
      \divide\count\z@\sixt@@n
      \count@\count\z@
      \multiply\count@\sixt@@n
      \advance\count\tw@-\count@
      \if\relax\noexpand#1% is command?
        \edef\reserved@a{\noexpand\in@
          {\expandafter\@gobble\string\mathaccent}
          {\expandafter\meaning
           \csname\expandafter\@gobble\string#1\space\endcsname}}%
```

```
        \reserved@a
        \ifin@
          \expandafter\let
            \csname\expandafter\@gobble\string#1\space\endcsname
            \@undefined
          \expandafter\set@mathaccent
             \csname sym#3\endcsname#1#2%
             {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
          \@font@info{Redeclaring math accent \string#1}%
        \else
          \expandafter\ifx
          \csname\expandafter\@gobble\string#1\endcsname
          \relax
            \expandafter\set@mathaccent
               \csname sym#3\endcsname#1#2%
               {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
          \else
            \@latex@error{Command `\string#1' already defined}\@eha
          \fi
        \fi
      \else
       \@latex@error{Not a command name: `\noexpand#1'}\@eha
      \fi
    \endgroup
  \else
    \@latex@error{Symbol font `#3' is not defined}\@eha
  \fi
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {DeclareMathAccent}{Make math accents robust}%
⟨latexrelease⟩\def\DeclareMathAccent#1#2#3#4{%
⟨latexrelease⟩  \expandafter\in@\csname sym#3\expandafter\endcsname
⟨latexrelease⟩     \expandafter{\group@list}%
⟨latexrelease⟩  \ifin@
⟨latexrelease⟩    \begingroup
⟨latexrelease⟩      \count\z@=#4\relax
⟨latexrelease⟩      \count\tw@\count\z@
⟨latexrelease⟩      \divide\count\z@\sixt@@n
⟨latexrelease⟩      \count@\count\z@
⟨latexrelease⟩      \multiply\count@\sixt@@n
⟨latexrelease⟩      \advance\count\tw@-\count@
⟨latexrelease⟩      \if\relax\noexpand#1% is command?
⟨latexrelease⟩        \edef\reserved@a{\noexpand\in@
⟨latexrelease⟩           {\expandafter\@gobble\string\mathaccent}{\meaning#1}}%
⟨latexrelease⟩        \reserved@a
⟨latexrelease⟩        \ifin@
⟨latexrelease⟩          \expandafter\set@mathaccent
⟨latexrelease⟩             \csname sym#3\endcsname#1#2%
⟨latexrelease⟩             {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
⟨latexrelease⟩          \@font@info{Redeclaring math accent \string#1}%
⟨latexrelease⟩        \else
⟨latexrelease⟩          \expandafter\ifx
```

```
⟨latexrelease⟩          \csname\expandafter\@gobble\string#1\endcsname
⟨latexrelease⟩          \relax
⟨latexrelease⟩            \expandafter\set@mathaccent
⟨latexrelease⟩               \csname sym#3\endcsname#1#2%
⟨latexrelease⟩               {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
⟨latexrelease⟩          \else
⟨latexrelease⟩            \@latex@error{Command ‘\string#1’ already defined}\@eha
⟨latexrelease⟩          \fi
⟨latexrelease⟩        \fi
⟨latexrelease⟩      \else
⟨latexrelease⟩       \@latex@error{Not a command name: ‘\noexpand#1’}\@eha
⟨latexrelease⟩      \fi
⟨latexrelease⟩    \endgroup
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@latex@error{Symbol font ‘#3’ is not defined}\@eha
⟨latexrelease⟩  \fi
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\DeclareMathAccent
```

(*End definition for* `\DeclareMathAccent`.)

`\set@mathaccent`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\set@mathaccent}{makemath accents robust}%
\def\set@mathaccent#1#2#3#4{%
  \xdef#2{\mathaccent"\mathchar@type#3\hexnumber@#1#4\relax}%
  \MakeRobust#2%
}
\@onlypreamble\set@mathaccent
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\set@mathaccent}{makemath accents robust}%
⟨latexrelease⟩
⟨latexrelease⟩\def\set@mathaccent#1#2#3#4{%
⟨latexrelease⟩  \xdef#2{\mathaccent"\mathchar@type#3\hexnumber@#1#4\relax}}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\set@mathaccent`.)

`\DeclareMathSymbol`

```
\def\DeclareMathSymbol#1#2#3#4{%
  \expandafter\in@\csname sym#3\expandafter\endcsname
     \expandafter{\group@list}%
  \ifin@
    \begingroup
      \count\z@=#4\relax
      \count\tw@\count\z@
```

```
      \divide\count\z@\sixt@@n
      \count@\count\z@
      \multiply\count@\sixt@@n
      \advance\count\tw@-\count@
      \if\relax\noexpand#1% is command?
```

Store the command name with a space attached inside `\reserved@@b` in case we look at a robust definition.

```
        \edef\reserved@b{\expandafter\noexpand
                         \csname\expandafter\@gobble\string#1\space\endcsname}%
```

Test both `#1` and `#1␣` for containing `mathchar`.

```
        \edef\reserved@a
          {\noexpand\in@{\expandafter\@gobble\string\mathchar}%
                        {\meaning#1\expandafter\meaning\reserved@b}}%
        \reserved@a
```

Drop `#1␣` in case it was defined before.

```
        \global\expandafter\let\reserved@b\@undefined
        \ifin@
          \expandafter\set@mathsymbol
             \csname sym#3\endcsname#1#2%
             {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
          \@font@info{Redeclaring math symbol \string#1}%
        \else
          \expandafter\ifx
            \csname\expandafter\@gobble\string#1\endcsname
            \relax
            \expandafter\set@mathsymbol
               \csname sym#3\endcsname#1#2%
               {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
          \else
            \@latex@error{Command `\string#1' already defined}\@eha
          \fi
        \fi
      \else
        \expandafter\set@mathchar
          \csname sym#3\endcsname#1#2
          {\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
      \fi
    \endgroup
  \else
    \@latex@error{Symbol font `#3' is not defined}\@eha
  \fi
}
\@onlypreamble\DeclareMathSymbol
```

(*End definition for* `\DeclareMathSymbol`.)

`\set@mathchar`

```
\def\set@mathchar#1#2#3#4{%
  \global\mathcode`#2="\mathchar@type#3\hexnumber@#1#4\relax}
\@onlypreamble\set@mathchar
```

(*End definition for* `\set@mathchar`.)

\set@mathsymbol

```
\def\set@mathsymbol#1#2#3#4{%
  \global\mathchardef#2"\mathchar@type#3\hexnumber@#1#4\relax}
\@onlypreamble\set@mathsymbol
```

(*End definition for* `\set@mathsymbol`.)

```
%\def\mathsymbol#1#2#3{%
%  \@tempcnta=#3\relax
%  \@tempcntb\@tempcnta
%  \divide\@tempcnta\sixt@@n
%  \count@\@tempcnta
%  \multiply\count@\sixt@@n
%  \advance\@tempcntb-\count@
%  \mathchar"\mathchar@type#1\hexnumber@#2%
%             \hexnumber@\@tempcnta\hexnumber@\@tempcntb\relax}
%
%\def\DeclareMathAlphabetCharacter#1#2#3{%
%  \DeclareMathSymbol{#1}7{#2}{#3}}
```

\DeclareMathDelimiter

```
\def\DeclareMathDelimiter#1{%
  \if\relax\noexpand#1%
    \expandafter\@DeclareMathDelimiter
  \else
    \expandafter\@xxDeclareMathDelimiter
  \fi
  #1}
\@onlypreamble\DeclareMathDelimiter
```

(*End definition for* `\DeclareMathDelimiter`.)

\@xxDeclareMathDelimiter

This macro checks if the second arg is a "math type" such as `\mathopen`. The undocumented original code didn't use math types when the delimiter was a single letter. For this reason the coding is a bit strange as it tries to support the undocumented syntax for compatibility reasons.

```
\def\@xxDeclareMathDelimiter#1#2#3#4{%
```

7 is the default value returned in the case that `\mathchar@type` is passed something unexpected, like a math symbol font name. We locally move `\mathalpha` out of the way so if you use that the right branch is taken. This will still fail if an explicit number 7 is used!

```
   \begingroup
    \let\mathalpha\mathord
    \ifnum7=\mathchar@type{#2}%
      \endgroup
```

If this branch is taken we have old syntax (5 arguments).

```
      \expandafter\@firstofone
    \else
```

If this branch is taken `\mathchar@type` is different from 7 so we assume new syntax. In this case we also use the arguments to set up the letter as a math symbol for the case where it is not used as a delimiter.

```
      \endgroup
      \DeclareMathSymbol#1{#2}{#3}{#4}%
```

Then we arrange that `\@xDeclareMathDelimiter` only gets `#1`, `#3`, `#4` ... as it does not expect a math type as argument.

```
      \expandafter\@firstoftwo
    \fi
    {\@xDeclareMathDelimiter#1}{#2}{#3}{#4}}
\@onlypreamble\@xxDeclareMathDelimiter
```

(*End definition for* `\@xxDeclareMathDelimiter`.)

`\@DeclareMathDelimiter`

```
\def\@DeclareMathDelimiter#1#2#3#4#5#6{%
  \expandafter\in@\csname sym#3\expandafter\endcsname
     \expandafter{\group@list}%
  \ifin@
    \expandafter\in@\csname sym#5\expandafter\endcsname
       \expandafter{\group@list}%
    \ifin@
      \begingroup
        \count\z@=#4\relax
        \count\tw@\count\z@
        \divide\count\z@\sixt@@n
        \count@\count\z@
        \multiply\count@\sixt@@n
        \advance\count\tw@-\count@
        \edef\reserved@c{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
      %
        \count\z@=#6\relax
        \count\tw@\count\z@
        \divide\count\z@\sixt@@n
        \count@\count\z@
        \multiply\count@\sixt@@n
        \advance\count\tw@-\count@
        \edef\reserved@d{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
      %
        \edef\reserved@a{\noexpand\in@
            {\expandafter\@gobble\string\delimiter}{\meaning#1}}%
        \reserved@a
        \ifin@
          \expandafter\set@mathdelimiter
             \csname sym#3\expandafter\endcsname
             \csname sym#5\endcsname#1#2%
             \reserved@c\reserved@d
          \@font@info{Redeclaring math delimiter \string#1}%
        \else
            \expandafter\ifx
            \csname\expandafter\@gobble\string#1\endcsname
            \relax
            \expandafter\set@mathdelimiter
              \csname sym#3\expandafter\endcsname
              \csname sym#5\endcsname#1#2%
              \reserved@c\reserved@d
          \else
            \@latex@error{Command ‘\string#1’ already defined}\@eha
          \fi
```

```
        \fi
      \endgroup
    \else
      \@latex@error{Symbol font ‘#5’ is not defined}\@eha
    \fi
  \else
    \@latex@error{Symbol font ‘#3’ is not defined}\@eha
  \fi
}
\@onlypreamble\@DeclareMathDelimiter
```

(*End definition for* `\@DeclareMathDelimiter`.)

`\@xDeclareMathDelimiter`

```
\def\@xDeclareMathDelimiter#1#2#3#4#5{%
  \expandafter\in@\csname sym#2\expandafter\endcsname
     \expandafter{\group@list}%
  \ifin@
    \expandafter\in@\csname sym#4\expandafter\endcsname
       \expandafter{\group@list}%
    \ifin@
      \begingroup
        \count\z@=#3\relax
        \count\tw@\count\z@
        \divide\count\z@\sixt@@n
        \count@\count\z@
        \multiply\count@\sixt@@n
        \advance\count\tw@-\count@
        \edef\reserved@c{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
      %
        \count\z@=#5\relax
        \count\tw@\count\z@
        \divide\count\z@\sixt@@n
        \count@\count\z@
        \multiply\count@\sixt@@n
        \advance\count\tw@-\count@
        \edef\reserved@d{\hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
        \expandafter\set@@mathdelimiter
           \csname sym#2\expandafter\endcsname\csname sym#4\endcsname#1%
           \reserved@c\reserved@d
      \endgroup
    \else
      \@latex@error{Symbol font ‘#4’ is not defined}\@eha
    \fi
  \else
    \@latex@error{Symbol font ‘#2’ is not defined}\@eha
  \fi
}
\@onlypreamble\@xDeclareMathDelimiter
```

(*End definition for* `\@xDeclareMathDelimiter`.)

`\set@mathdelimiter` We have to end the definition of a math delimiter like `\lfloor` with a space and not with `\relax` as we did before, because otherwise constructs involving `\abovewithdelims` will prematurely end (pr/1329)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\set@mathdelimiter}{make delimiters robust}%
\def\set@mathdelimiter#1#2#3#4#5#6{%
```

We use `\protected` not `\MakeRobust` so that `\bigl\lfoor` etc. works inside the argument of `\protected@edef`.

```
  \protected
  \xdef#3{\delimiter"\mathchar@type#4\hexnumber@#1#5%
    \hexnumber@#2#6 }%
%  \MakeRobust#3%
}
\@onlypreamble\set@mathdelimiter
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\set@mathdelimiter}{make delimiters robust}%
⟨latexrelease⟩
⟨latexrelease⟩\def\set@mathdelimiter#1#2#3#4#5#6{%
⟨latexrelease⟩  \xdef#3{\delimiter"\mathchar@type#4\hexnumber@#1#5%
⟨latexrelease⟩    \hexnumber@#2#6 }}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\set@mathdelimiter`.)

`\set@@mathdelimiter`

```
\def\set@@mathdelimiter#1#2#3#4#5{%
  \global\delcode`#3="\hexnumber@#1#4\hexnumber@#2#5\relax}
\@onlypreamble\set@@mathdelimiter
```

(*End definition for* `\set@@mathdelimiter`.)

`\DeclareMathRadical`

```
\def\DeclareMathRadical#1#2#3#4#5{%
```

Below is a crude fix to make this macro work if `#1` is undefined or `\relax`. Should be improved!

```
  \expandafter\ifx
      \csname\expandafter\@gobble\string#1\endcsname
      \relax
    \let#1\radical
  \fi
  \edef\reserved@a{\noexpand\in@
      {\expandafter\@gobble\string\radical}{\meaning#1}}%
  \reserved@a
  \ifin@
    \expandafter\in@\csname sym#2\expandafter\endcsname
      \expandafter{\group@list}%
    \ifin@
      \expandafter\in@\csname sym#4\expandafter\endcsname
        \expandafter{\group@list}%
      \ifin@
```

```
        \begingroup
          \count\z@=#3\relax
          \count\tw@\count\z@
          \divide\count\z@\sixt@@n
          \count@\count\z@
          \multiply\count@\sixt@@n
          \advance\count\tw@-\count@
          \edef\reserved@c{%
            \hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
          \count\z@=#5\relax
          \count\tw@\count\z@
          \divide\count\z@\sixt@@n
          \count@\count\z@
          \multiply\count@\sixt@@n
          \advance\count\tw@-\count@
          \edef\reserved@d{%
            \hexnumber@{\count\z@}\hexnumber@{\count\tw@}}%
```

Coded inline instead of using `\set@mathradical`

```
%          \expandafter\set@mathradical
%             \csname sym#2\expandafter\endcsname
%             \csname sym#4\endcsname#1%
%             \reserved@c\reserved@d
          \xdef#1{\radical"\expandafter\hexnumber@
                                 \csname sym#2\endcsname\reserved@c
                              \expandafter\hexnumber@
                                 \csname sym#4\endcsname\reserved@d
                   \relax}%
        \endgroup
      \else
        \@latex@error{Symbol font ‘#4’ is not defined}\@eha
      \fi
    \else
      \@latex@error{Symbol font ‘#2’ is not defined}\@eha
    \fi
  \else
    \@latex@error{Command ‘\string#1’ already defined}\@eha
  \fi
}
\@onlypreamble\DeclareMathRadical
```

(*End definition for* `\DeclareMathRadical`.)

Definition below was wrong it contained `\delimiter` !

```
def\set@mathradical#1#2#3#4#5{%
 \xdef#3{\radical"\hexnumber@#1#4\hexnumber@#2#5\relax}}
```

`\mathalpha` just a dummy currently

```
\let\mathalpha\relax
```

(*End definition for* `\mathalpha`.)

`\mathchar@type`

```
\def\mathchar@type#1{%
  \ifodd 2#11 #1\else             % is this non-negative number?
```

```
    \ifx#1\mathord 0\else
     \ifx#1\mathop   1\else
       \ifx#1\mathbin 2\else
         \ifx#1\mathrel 3\else
           \ifx#1\mathopen 4\else
             \ifx#1\mathclose 5\else
               \ifx#1\mathpunct 6\else
                   7%             % anything else is variable ord
               \fi
             \fi
           \fi
         \fi
       \fi
     \fi
    \fi
  \fi}
\@onlypreamble\mathchar@type
```

(*End definition for* `\mathchar@type`.)

`\DeclareSymbolFontAlphabet`

```
\def\DeclareSymbolFontAlphabet#1#2{%
   \expandafter\DeclareSymbolFontAlphabet@
     \csname \expandafter\@gobble\string#1\space\endcsname{#2}#1}
\@onlypreamble\DeclareSymbolFontAlphabet
```

(*End definition for* `\DeclareSymbolFontAlphabet`.)

`\DeclareSymbolFontAlphabet@`

```
\def\DeclareSymbolFontAlphabet@#1#2#3{%
```

We use the switch `\if@tempswa` to decide if we can declare this symbol font alphabet.

```
    \@tempswatrue
```

First check if `#2` is known to be a symbol font

```
  \expandafter\in@\csname sym#2\expandafter\endcsname
     \expandafter{\group@list}%
  \ifin@
```

Check if `#1` is defined as a math alphabet defined via `\DeclareMathAlphabet`:

```
    \expandafter\in@\expandafter#1\expandafter{\alpha@list}%
    \ifin@
```

If so remove it from the `\alpha@list` and from all math version macros.

```
      \@font@info{Redeclaring math alphabet \string#3}%
      \toks@{}%
      \def\alpha@elt##1##2##3{%
          \ifx##1#1\else\addto@hook\toks@{\alpha@elt##1##2##3}\fi}%
      \alpha@list
      \xdef\alpha@list{\the\toks@}%
```

Now we loop over all versions and remove the math alphabet:

```
      \def\version@elt##1{%
          \begingroup
            \toks@{}%
            \def\getanddefine@fonts####1####2{%
```

```
                \addto@hook\toks@{\getanddefine@fonts####1####2}}%
            \def\install@mathalphabet####1####2{%
                \ifx####1#1\else
                  \addto@hook\toks@{\install@mathalphabet
                                    ####1{####2}}\fi}%
            ##1%
            \xdef##1{\the\toks@}%
          \endgroup
          }%
      \version@list
    \else
```

If #3 is not defined as a math alphabet check if it is defined at all:

```
      \expandafter\ifx
      \csname\expandafter\@gobble\string#1\space\endcsname
      \relax
```

If it is undefined, fine otherwise check if it is a math alphabet defined via \DeclareSymbolFontAlphabet:

```
      \else
        \edef\reserved@a{%
          \noexpand\in@{\string\use@mathgroup}{\meaning#1}}%
        \reserved@a
        \ifin@
          \@font@info{Redeclaring math alphabet \string#3}%
        \else
```

Since the command #3 is defined to be something which is not a math alphabet we have to skip redefining it.

```
          \@tempswafalse
          \@latex@error{Command ‘\string#3’ already defined}\@eha
        \fi
      \fi
    \fi
  \else
```

Since the symbol font is not known we better skip defining this alphabet.

```
    \@tempswafalse
    \@latex@error{Unknown symbol font ‘#2’}\@eha
  \fi
  \if@tempswa
```

When we reach this point we are allowed to define #1 to be a symbol font math alphabet. This means that we have to set it to

\use@mathgroup ⟨*math-settings*⟩ \sym⟨*name*⟩

The ⟨*math-settings*⟩ are the one for the encoding that is used in the font shape where \sym⟨*name*⟩ is pointing to. This means that we have to get it from the information stored in \group@list. Thus we loop through that list after defining \group@elt in a suitable way.

```
    \def\group@elt##1##2{%
        \expandafter\ifx\csname sym#2\endcsname##1%
        \expandafter\reserved@a\string##2\@nil
        \fi}%
    \def\reserved@a##1##2/##3\@nil{%
```

```
        \def\reserved@a{##2}}%
      \group@list
      \toks@{\relax\ifmmode \else \non@alpherr#1\fi}%
      \edef#1{\the\toks@
              \noexpand\use@mathgroup
              \expandafter\noexpand\csname M@\reserved@a\endcsname
              \csname sym#2\endcsname}%
      \def#3{\protect#1}%
    \fi
}
\@onlypreamble\DeclareSymbolFontAlphabet@
⟨/2ekernel⟩
```

(*End definition for* `\DeclareSymbolFontAlphabet@`.)

File A
ltfssini.dtx

This file contains the top level LaTeX interface to the font selection scheme commands. See other parts of the LaTeX distribution, or *The LaTeX Companion* for higher level documentation of these commands.

1 NFSS Initialization

Finally, there are six commands that are to be used in LaTeX and that we will therefore protect against expansion at the wrong point: `\fontfamily`, `\fontseries`, `\fontshape`, `\fontsize`, `\selectfont`, and `\mathversion`.

```
⟨*2ekernel⟩
```

1.1 Providing math *versions*

LaTeX provides two *versions*. We call them normal and bold, respectively.

```
\DeclareMathVersion{normal}
\DeclareMathVersion{bold}
```

Now we define the standard font change commands. We don't allow the use of `\rmfamily` etc. in math mode.

(Actually most are now defined further down in the file.)

First the changes to another *family*:

```
%\DeclareRobustCommand\rmfamily
%        {\not@math@alphabet\rmfamily\mathrm
%         \fontfamily\rmdefault\selectfont}
%\DeclareRobustCommand\sffamily
%        {\not@math@alphabet\sffamily\mathsf
%         \fontfamily\sfdefault\selectfont}
%\DeclareRobustCommand\ttfamily
%        {\not@math@alphabet\ttfamily\mathtt
%         \fontfamily\ttdefault\selectfont}
```

Then the commands changing the *series*:

```
%\DeclareRobustCommand\bfseries
%        {\not@math@alphabet\bfseries\mathbf
%         \fontseries\bfdefault\selectfont}
%\DeclareRobustCommand\mdseries
%        {\not@math@alphabet\mdseries\relax
%         \fontseries\mddefault\selectfont}
\DeclareRobustCommand\upshape
        {\not@math@alphabet\upshape\relax
         \fontshape\updefault\selectfont}
```

Then the commands changing the *shape*:

```
\DeclareRobustCommand\slshape
        {\not@math@alphabet\slshape\relax
         \fontshape\sldefault\selectfont}
\DeclareRobustCommand\scshape
        {\not@math@alphabet\scshape\relax
```

```
         \fontshape\scdefault\selectfont}
\DeclareRobustCommand\itshape
        {\not@math@alphabet\itshape\mathit
         \fontshape\itdefault\selectfont}
```

2 Custom series settings for main document families

This section was introduced 2020/02/02 and for now we support a full rollback (may need splitting later).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                    {\DeclareFontSeriesDefault}{Custom series}%
```

One problem with the NFSS approach of handling the series axis turned out to be that (especially with respect to "boldness") different font families implemented different strategies. For example, with Computer Modern fonts you normally only have `bx` whereas most PostScript fonts offered only `b` but not `bx`. As a result LaTeX's standard setting for `\bfdefault` didn't work with such fonts, but if it got changed to produce `b`, then that didn't work with Computer Modern if the fonts got combined (e.g., using Computer Modern Typewriter with such fonts).

The solution back then was to provide substitution rules in the font `.fd` such that if a `bx` series got requested the `b` series got used. While this works in that particular case, it isn't a very general solution. For example, if you happen to have a font family that has several weights you may want to typeset the whole document in a somewhat lighter or darker font but if you then modify `\mddefault` to allow for this, then of course your change only works with that particular family but not with the typewriter or sans serif family you also want to use.

A better solution was provided by the `mweights` package by Bob Tennent that offers defaults on the level of the three main font families in the document: for "rm", "sf" and "tt" so that font packages could define defaults for the sans serif document font by providing `\bfseries@sf` which then was used when `\bfseries` got executed and the current family was the `\sffamily`.

`\DeclareFontSeriesDefault`

We now support this concept directly from within LaTeX and for use in font packages (or the document preamble) we offer `\DeclareFontSeriesDefault`. This declaration takes three arguments:

document family interface: Can either be `rm`, `sf` or `tt`. This is optional and if not given the overall default.

document series interface: Can be `md` or `bf`.

series value: This is the value that is going to be used with the combination is requested.

For example, `\DeclareFontSeriesDefault[rm]{bf}{sb}` would use `sb` (semi-bold) when `\rmfamily` `\bfseries` is asked for.

If used without the optional argument, e.g., `\DeclareFontSeriesDefault{bf}{b}` then this is like redefining `\bfdefault` or `\mddefault`.

If some family specify defaults aren't given, e.g. if there are no declarations for, say, `tt` then the format defaults of `\mddefault` and `\bfdefault` are assumed. If those are later changed this is *not* reflected![28]

`\DeclareFontSeriesDefault` The command to declare font series defaults for the "rm", "sf" or "tt" family.

```
\let\DeclareFontSeriesDefault\@undefined      % for rollback
\newcommand\DeclareFontSeriesDefault[3][]{%
  \expand@font@defaults
  \maybe@update@bfseries@defaults
  \maybe@update@mdseries@defaults
  \def\reserved@a{#1}%
```

No optional argument: set up general default.

```
  \ifx\reserved@a\@empty
    \ifcsname #2series\endcsname           % supported are
                                           % \[md/bf]default
```

Adding `\@empty` allows us to detect if the default gets redefined with `\renewcommand` or `\def` by the user.

```
      \expandafter\def
        \csname #2default\endcsname{#3\@empty}%
      \expandafter\def
        \csname #2default@previous\endcsname{#3\@empty}%
    \else
       \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
          {Mandatory first argument must be 'md'  or 'bf'.}
    \fi
```

Optional argument given, set up specific default.

```
  \else
    \ifcsname #2series@#1\endcsname          % supported are
                                             % \[md/bf]series@[rm/sf/tt]
      \expandafter\edef
         \csname #2series@#1\endcsname{#3}%
```

If the interface is used we remove the frozen kernel default. This way, we know that something was explicitly set up (even if the setup has the same value as the default).

```
      \expandafter\let
         \csname #2series@#1@kernel\endcsname\@undefined
    \else
       \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
          {Optional argument must be 'rm', 'sf', or 'tt'. \MessageBreak
           Mandatory first argument must be 'md'  or 'bf'.}
    \fi
  \fi
}
```

[28] I see no easy way to achieve this without compromising compatibility with existing packages that currently use mweights and directly define (some) of the `\mdseries@..` commands but not others.

(*End definition for* `\DeclareFontSeriesDefault`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                 {\DeclareFontSeriesDefault}{Custom series}%
⟨latexrelease⟩
⟨latexrelease⟩\let\DeclareFontSeriesDefault\@undefined      % for rollback
⟨latexrelease⟩\newcommand\DeclareFontSeriesDefault[3][]{%
⟨latexrelease⟩  \def\reserved@a{#1}%
⟨latexrelease⟩  \ifx\reserved@a\@empty
⟨latexrelease⟩    \ifcsname #2series\endcsname           % supported are
⟨latexrelease⟩                                           % \[md/bf]default
⟨latexrelease⟩      \expandafter\def
⟨latexrelease⟩        \csname #2default\endcsname{#3\@empty}%
⟨latexrelease⟩      \expandafter\def
⟨latexrelease⟩        \csname #2default@previous\endcsname{#3\@empty}%
⟨latexrelease⟩    \else
⟨latexrelease⟩       \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
⟨latexrelease⟩          {Mandatory first argument must be 'md'  or 'bf'.}
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \ifcsname #2series@#1\endcsname          % supported are
⟨latexrelease⟩                                             % \[md/bf]series@[rm/sf/tt]
⟨latexrelease⟩      \expandafter\edef
⟨latexrelease⟩         \csname #2series@#1\endcsname{#3}%
⟨latexrelease⟩      \expandafter\let
⟨latexrelease⟩         \csname #2series@#1@kernel\endcsname\@undefined
⟨latexrelease⟩    \else
⟨latexrelease⟩       \@latex@error{Wrong syntax for \string\DeclareFontSeriesDefault}%
⟨latexrelease⟩          {Optional argument must be 'rm', 'sf', or 'tt'. \MessageBreak
⟨latexrelease⟩           Mandatory first argument must be 'md'  or 'bf'.}
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\DeclareFontSeriesDefault}{Custom series}%
⟨latexrelease⟩
⟨latexrelease⟩\let\DeclareFontSeriesDefault\@undefined
⟨latexrelease⟩\let\bfseries@rm\@undefined
⟨latexrelease⟩\let\bfseries@sf\@undefined
⟨latexrelease⟩\let\bfseries@tt\@undefined
⟨latexrelease⟩\let\bfseries@rm@kernel\@undefined
⟨latexrelease⟩\let\bfseries@sf@kernel\@undefined
⟨latexrelease⟩\let\bfseries@tt@kernel\@undefined
⟨latexrelease⟩\let\mdseries@rm\@undefined
⟨latexrelease⟩\let\mdseries@sf\@undefined
⟨latexrelease⟩\let\mdseries@tt\@undefined
⟨latexrelease⟩\expandafter\let\csname ver@mweights.sty\endcsname\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\@meta@family@list\@undefined
⟨latexrelease⟩\let\prepare@family@series@update\@undefined
⟨latexrelease⟩\let\update@series@target@value\@undefined
```

```
⟨latexrelease⟩
```

This is always called in `\document` so don't make it undefined.

```
⟨latexrelease⟩\let\init@series@setup\relax
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩

⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                    {\mdseries@rm}{Custom series}%
```

`\mdseries@rm` `\mdseries@sf` `\mdseries@tt` `\bfseries@rm` `\bfseries@sf` `\bfseries@tt`

We initialize the family specific default at the end of the format generation. Later on they may get overwritten in the preamble or a package via `\DeclareFontSeriesDefault` (or possibly directly).

Conceptual change: The `\bfdefault` will be `b` not `bx` because that is what it should be really for nearly every font except Computer/Latin Modern.

To account for the fact that by default we typeset in CM or LM we set up the `\bfseries@..` defaults to use `bx` instead.

This means that it behaves like before because if the default fonts are used then `\bfseries@rm` etc kick in and make `\textbf` use `bx`. However, if the font gets changed then `\bfdefault` will get used.

```
\def\bfseries@rm{bx}
\def\bfseries@sf{bx}
\def\bfseries@tt{bx}
```

Frozen version of the kernel defaults so we can see if they have changed.

```
\let\bfseries@rm@kernel\bfseries@rm
\let\bfseries@sf@kernel\bfseries@sf
\let\bfseries@tt@kernel\bfseries@tt
```

The default for the medium series is `m` and this will be interpreted as resetting both weight and width. To reset only one of them the virtual value `?m` and `m?` are available.

```
\def\mdseries@rm{m}
\def\mdseries@sf{m}
\def\mdseries@tt{m}
```

(*End definition for* `\mdseries@rm` *and others.*)

`\series@change@debug`

For debugging, but right now none of this code is extracted. The idea is to have a separate package with debugging code one day.

```
⟨*debug⟩
\let\series@change@debug\typeout
\let\series@change@debug\@gobble
⟨/debug⟩
```

(*End definition for* `\series@change@debug`.)

`\prepare@family@series@update`

This is core command that prepares for the family update. The big difference to the documented code above is that the nested `\ifx` statements seem to be missing. Instead we loop through an internal list that holds the names of the three meta families. This approach allows us to extend the mechanism at a later stage to allow for additional named meta families.

Here is the current definition of that list:

\@meta@family@list

```
\def\@meta@family@list{\@elt{rm}\@elt{sf}\@elt{tt}}
```

```
\def\prepare@family@series@update#1#2{%
 \if@forced@series
⟨+debug⟩ \series@change@debug{No series preparation (forced \f@series)\on@line}%
   \fontfamily#2%
 \else
⟨+debug⟩ \series@change@debug{Preparing for switching to #1 (#2)\on@line}%
   \expand@font@defaults
```

We prepare for changing the current series. We have to find it before changing the family as discussed above.

```
   \let\target@series@value\@empty
   \def\target@meta@family@value{#1}%
```

As the very last item in the meta family list we add `\@elt{??}` and define this pseudo meta family to be the current font family. So if none of the real meta families matched then this will match. This will cover the following case:

- `\bfseries` is called for a family using `bx` (e.g., CMR)
- Switch to a font family that is none of the meta families, e.g., via `\fontfamily{ptm}\allowbreak\v`
- Then none of the real meta families, match but the final `\@elt{??}` will.
- Therefore if the current series is `\mddefault` or `\bfdefault` it will be detected and the corresponding target series selected.

```
   \expandafter\edef\csname ??def@ult\endcsname{\f@family}%
```

To find it we loop over the meta family list with a suitable definition of `\@elt`.

```
   \let\@elt\update@series@target@value
      \@meta@family@list
```

Last resort pseudo meta family. Will only be looked at f none of the real ones have matched.

```
      \@elt{??}%
   \let\@elt\relax
```

That will figure out the correct series value to use without updating it. Now we can change the family.

```
   \fontfamily#2%
```

After that we update the series. That code is again like the one above.

```
   \ifx\target@series@value\@empty
⟨+debug⟩ \series@change@debug{Target series still empty ...}%
   \else
     \ifx \f@series\target@series@value
⟨+debug⟩ \series@change@debug{Target series unchanged:
⟨+debug⟩                      \f@series \space = \target@series@value}%
     \else
       \maybe@load@fontshape
⟨+debug⟩ \series@change@debug{Target series:
⟨+debug⟩                      \f@series \space -> \target@series@value}%
```

The \target@series@value may contain something like cm (coming from a default) and so we can't directly assign it to \f@series be have to drop any surplus m first.

```
%       \let\f@series\target@series@value
        \series@maybe@drop@one@m\target@series@value\f@series
      \fi
    \fi
  \fi
}
```

(*End definition for* \prepare@family@series@update *and* \@meta@family@list.)

\update@series@target@value

In this macro used in the look you basically find the nested \ifxs from the outline above. The only difference is that is it is parameterized instead of being written out and only for one block of tests because the code is called repeatedly when looping over the meta family list. From the list we get each meta family name in turn.

```
\def\update@series@target@value#1{%
```

There is one additional test at the beginning, because the list contains all meta families and we need to ignore the case where current one from the list and target one are identical.

```
  \def\reserved@a{#1}%
  \ifx\target@meta@family@value\reserved@a   % rm -> rm do nothing
  \else
⟨+debug⟩ \series@change@debug{Trying to match #1: \csname#1def@ult\endcsname
⟨+debug⟩                      \space = \f@family\space ?}%
```

We only "do" something if the current font family matches the current meta family.

```
    \expandafter\ifx\csname#1def@ult\endcsname\f@family
```

If that's the case we know that this is the block that applies (only one meta family can match). So to speed things up we change \@elt so that the rest of the loop gets gobbled.

```
      \let\@elt\@gobble
```

Then we try to find the right new value for the series (as explained above). The two macros defined first are only there because we now need to use \csname and this way the code will be a little faster.

```
      \expandafter\let\expandafter\reserved@b
                      \csname mdseries@\target@meta@family@value\endcsname
      \expandafter\let\expandafter\reserved@c
                      \csname bfseries@\target@meta@family@value\endcsname
⟨+debug⟩\series@change@debug{Targets for mdseries and bfseries:
⟨+debug⟩                     \reserved@b\space and \reserved@c}%
```

This here is now identical to the nested \ifx block from the outline, except that it there appeared twice in \rmfamily. This is now covered by looping and stopping the loop when a match was found.

We have to sanitize the default value first because it may contain something like mc and that would never match \f@series because there it would be called c with the m dropped. It would be probably better to do that differently these days, but it is hard to adjust without causing a lot of issues, so we do the dropping in various places instead.

```
      \expandafter\series@maybe@drop@one@m
          \csname mdseries@#1\endcsname\reserved@d
      \ifx\reserved@d\f@series
⟨+debug⟩   \series@change@debug{mdseries@#1 matched -> \reserved@b}%
                                      \let\target@series@value\reserved@b
      \else
```

Again do some sanitizing.

```
        \expandafter\series@maybe@drop@one@m
           \csname bfseries@#1\endcsname\reserved@d
        \ifx\reserved@d\f@series
⟨+debug⟩  \series@change@debug{bfseries@#1 matched -> \reserved@c}%
                                        \let\target@series@value\reserved@c
      \else\ifx\f@series\mddef@ult    \let\target@series@value\reserved@b
⟨+debug⟩  \series@change@debug{mddef@ult matched -> \reserved@b}%
      \else\ifx\f@series\bfdef@ult    \let\target@series@value\reserved@c
⟨+debug⟩  \series@change@debug{bfdef@ult matched -> \reserved@c}%
      \fi\fi\fi\fi
    \fi
  \fi
}
```

(*End definition for* `\update@series@target@value`.)

`\init@series@setup` This is code to be run at begin document ...

```
\def\init@series@setup{%
```

We only want `bx` in `\bfseries@rm` if the roman font is Computer Modern or Latin Modern, otherwise it should be `b`. It was set to `bx` in the kernel so that any font use with the default families in the preamble get this value. Now at the real document start we check if the fonts have been changed. If there was a `\DeclareFontSeriesDefault` declaration or `\bfseries@rm` was directly altered then it differs from `\bfseries@rm@kernel` and we do nothing. Otherwise we check if `\rmdefault` is one of the CM/LM font families and if so we keep `bx` otherwise we change it to `b`.

This approach doesn't cover one case: CM/LM got changed to a different family that supports `bx`, but the support package for that family used `\def\bfseries@rm{bx}` instead of using `\DeclareFontSeriesDefault`. In that case the code here changes it to `b`. Solution: use the `\DeclareFontSeriesDefault` interface.

```
  \ifx\bfseries@rm@kernel\bfseries@rm
     \expandafter\in@\expandafter{\rmdefault}%
                      {cmr,cmss,cmtt,lcmss,lcmtt,lmr,lmss,lmtt}%
    \ifin@ \else \def\bfseries@rm{b}\fi\fi
```

Same approach for `\bfseries@sf` and `\bfseries@tt`:

```
  \ifx\bfseries@sf@kernel\bfseries@sf
    \expandafter\in@\expandafter{\sfdefault}%
                     {cmr,cmss,cmtt,lcmss,lcmtt,lmr,lmss,lmtt}%
    \ifin@ \else \def\bfseries@sf{b}\fi\fi
  \ifx\bfseries@tt@kernel\bfseries@tt
    \expandafter\in@\expandafter{\ttdefault}%
                     {cmr,cmss,cmtt,lcmss,lcmtt,lmr,lmss,lmtt}%
    \ifin@ \else \def\bfseries@tt{b}\fi\fi
```

If the document preamble has changed the `\familydefault` or if the if the `\rmdefault` contains a new font family, we may have to adjust the series defaults accordingly, before starting typesetting.

Similarly, if the user has changed the `\mddefault` or the medium series for the family selected as document font we may also have to adjust the `\seriesdefault`.

On the other hand if the document font is still CM or LM then `\bfdefault` is wrong, because it is now saying `b` and not `bx` as it should for such fonts.

To fix all this we first run \reset@font (the internal kernel name for \normalfont). This will set up the document encoding, family, series and shape based on the current values of \encodingdefault, \familydefault, \seriesdefault and \shapedefault. However, if the family (from \familydefault) has special medium default we should switch to that (and not use what is current value from \seriesdefault). This can be achieved by afterwards calling \mediumseries and then changing \seriesdefault to the now current series value (in \f@series).

But what should happen if \seriesdefault got explicitly changed? In that case the explicit change should survive and we should not alter \seriesdefault. This is solved by comparing the current value of \seriesdefault with a kernel version saved in the format and if they differ we do not call \mdseries or change \seriesdefault.

```
  \reset@font
  \ifx\seriesdefault\seriesdefault@kernel
    \mdseries
    \let\seriesdefault\f@series
  \fi
}%
```

(*End definition for* \init@series@setup.)

As the kernel code now implements the same functionality as mweights, albeit internally coded slightly differently, that package shouldn't be loaded any more. We therefore pretend that it already got loaded. Thus, a font package that tries to load it and then sets \mdseries@.., etc. will continue to work but will now use the kernel code.

Of course, mid-term such package should probably use \DeclareFontSeriesDefault instead of making using low-level definitions.

```
\expandafter\let\csname ver@mweights.sty\endcsname\fmtversion
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\mdseries@rm}{Custom series}%
⟨latexrelease⟩
⟨latexrelease⟩\let\bfseries@rm\@undefined
⟨latexrelease⟩\let\bfseries@sf\@undefined
⟨latexrelease⟩\let\bfseries@tt\@undefined
⟨latexrelease⟩\let\bfseries@rm@kernel\@undefined
⟨latexrelease⟩\let\bfseries@sf@kernel\@undefined
⟨latexrelease⟩\let\bfseries@tt@kernel\@undefined
⟨latexrelease⟩\let\mdseries@rm\@undefined
⟨latexrelease⟩\let\mdseries@sf\@undefined
⟨latexrelease⟩\let\mdseries@tt\@undefined
⟨latexrelease⟩\expandafter\let\csname ver@mweights.sty\endcsname\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\@meta@family@list\@undefined
⟨latexrelease⟩\let\prepare@family@series@update\@undefined
⟨latexrelease⟩\let\update@series@target@value\@undefined
⟨latexrelease⟩
```

This is always called in \document so don't make it undefined.

```
⟨latexrelease⟩\let\init@series@setup\relax
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                  {\bfseries}{Custom series with hooks}%
```

\bfseries This document command switches to the bold series.

```
\DeclareRobustCommand\bfseries{%
  \not@math@alphabet\bfseries\mathbf
```

In the original NFSS definition it then called \fontseries with the value \bfdefault. In the new scheme we have more alternatives and therefore check if the current family (\f@family) is the current \rmdef@ult, \sfdef@ult or \ttdef@ult and the select the correct family default in that case.

```
  \expand@font@defaults
  \maybe@update@bfseries@defaults
```

```
  \ifx\f@family\rmdef@ult      \fontseries\bfseries@rm
  \else\ifx\f@family\sfdef@ult \fontseries\bfseries@sf
  \else\ifx\f@family\ttdef@ult \fontseries\bfseries@tt
```

If not \bfdefault is used.

```
  \else                        \fontseries\bfdefault
  \fi\fi\fi
```

This hook in contrast is always executed.

```
  \UseHook{bfseries}%
  \selectfont
}
```

(*End definition for* \bfseries.)

\maybe@update@bfseries@defaults If \bfdefault and \bfdefault@previous are different then the default got changed directly through the legacy interface (i.e., via \def or \renewcommand. In that case we reset all meta family defaults so that the document behaves like it was the case before the new mechanism was introduced.

```
\def\maybe@update@bfseries@defaults{%
  \ifx\bfdefault\bfdefault@previous\else
```

We add \@empty and then let \bfdefault@previous to \bfdefault so that we can detect any further change.

```
    \expandafter\def\expandafter\bfdefault
                    \expandafter{\bfdefault\@empty}%
    \let\bfdefault@previous\bfdefault
```

And we reset the meta family defaults (\bfdef@ult is an expanded version of \bfdefault.

```
    \let\bfseries@rm\bfdef@ult
    \let\bfseries@sf\bfdef@ult
    \let\bfseries@tt\bfdef@ult
```

Formats that set up parallel fonts, e.g., for Japanese, can use this hook to add resets here. Not that this hook is only run when resets are necessary.

```
    \UseHook{bfseries/defaults}%
  \fi
}
```

(*End definition for* \maybe@update@bfseries@defaults.)

\mdseries This document command switches to the medium series.

```
\DeclareRobustCommand\mdseries{%
  \not@math@alphabet\mdseries\relax
  \expand@font@defaults
  \maybe@update@mdseries@defaults
  \ifx\f@family\rmdef@ult      \fontseries\mdseries@rm
    \else\ifx\f@family\sfdef@ult \fontseries\mdseries@sf
    \else\ifx\f@family\ttdef@ult \fontseries\mdseries@tt
    \else                        \fontseries\mddefault
  \fi\fi\fi
  \UseHook{mdseries}%
  \selectfont
}
```

(*End definition for* \mdseries.)

\maybe@update@mdseries@defaults

```
\def\maybe@update@mdseries@defaults{%
  \ifx\mddefault\mddefault@previous\else
    \expandafter\def\expandafter\mddefault\expandafter{\mddefault\@empty}%
    \let\mddefault@previous\mddefault
    \let\mdseries@rm\mddef@ult
    \let\mdseries@sf\mddef@ult
    \let\mdseries@tt\mddef@ult
```

Formats that set up parallel fonts, e.g., for Japanese, can use this hook to add resets here.

```
    \UseHook{mdseries/defaults}%
  \fi
}
```

(*End definition for* \maybe@update@mdseries@defaults.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\bfseries}{Custom series with hooks}%
⟨latexrelease⟩
⟨latexrelease⟩\let\maybe@update@bfseries@defaults\@undefined
⟨latexrelease⟩\let\maybe@update@mdseries@defaults\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\bfseries{%
⟨latexrelease⟩  \not@math@alphabet\bfseries\mathbf
⟨latexrelease⟩  \expand@font@defaults
⟨latexrelease⟩  \ifx\bfdefault\bfdefault@previous\else
⟨latexrelease⟩    \expandafter\def\expandafter\bfdefault
⟨latexrelease⟩                     \expandafter{\bfdefault\@empty}%
⟨latexrelease⟩    \let\bfdefault@previous\bfdefault
⟨latexrelease⟩    \let\bfseries@rm\bfdef@ult
⟨latexrelease⟩    \let\bfseries@sf\bfdef@ult
⟨latexrelease⟩    \let\bfseries@tt\bfdef@ult
⟨latexrelease⟩    \UseHook{bfseries/defaults}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩    \ifx\f@family\rmdef@ult      \fontseries\bfseries@rm
⟨latexrelease⟩    \else\ifx\f@family\sfdef@ult \fontseries\bfseries@sf
```

```
⟨latexrelease⟩    \else\ifx\f@family\ttdef@ult \fontseries\bfseries@tt
⟨latexrelease⟩    \else                        \fontseries\bfdefault
⟨latexrelease⟩    \fi\fi\fi
⟨latexrelease⟩  \UseHook{bfseries}%
⟨latexrelease⟩  \selectfont
⟨latexrelease⟩}
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\mdseries{%
⟨latexrelease⟩  \not@math@alphabet\mdseries\relax
⟨latexrelease⟩  \expand@font@defaults
⟨latexrelease⟩  \ifx\mddefault\mddefault@previous\else
⟨latexrelease⟩    \expandafter\def\expandafter\mddefault\expandafter{\mddefault\@empty}%
⟨latexrelease⟩    \let\mddefault@previous\mddefault
⟨latexrelease⟩    \let\mdseries@rm\mddef@ult
⟨latexrelease⟩    \let\mdseries@sf\mddef@ult
⟨latexrelease⟩    \let\mdseries@tt\mddef@ult
⟨latexrelease⟩    \UseHook{mdseries/defaults}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩    \ifx\f@family\rmdef@ult      \fontseries\mdseries@rm
⟨latexrelease⟩    \else\ifx\f@family\sfdef@ult \fontseries\mdseries@sf
⟨latexrelease⟩    \else\ifx\f@family\ttdef@ult \fontseries\mdseries@tt
⟨latexrelease⟩    \else                        \fontseries\mddefault
⟨latexrelease⟩    \fi\fi\fi
⟨latexrelease⟩  \UseHook{mdseries}%
⟨latexrelease⟩  \selectfont
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                 {\bfseries}{Custom series with hooks}%
⟨latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\bfseries{%
⟨latexrelease⟩  \not@math@alphabet\bfseries\mathbf
⟨latexrelease⟩  \expand@font@defaults
⟨latexrelease⟩    \ifx\f@family\rmdef@ult      \fontseries\bfseries@rm
⟨latexrelease⟩    \else\ifx\f@family\sfdef@ult \fontseries\bfseries@sf
⟨latexrelease⟩    \else\ifx\f@family\ttdef@ult \fontseries\bfseries@tt
⟨latexrelease⟩    \else                        \fontseries\bfdefault
⟨latexrelease⟩    \fi\fi\fi
⟨latexrelease⟩  \selectfont
⟨latexrelease⟩}
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\mdseries{%
⟨latexrelease⟩  \not@math@alphabet\mdseries\relax
⟨latexrelease⟩  \expand@font@defaults
⟨latexrelease⟩    \ifx\f@family\rmdef@ult      \fontseries\mdseries@rm
⟨latexrelease⟩    \else\ifx\f@family\sfdef@ult \fontseries\mdseries@sf
⟨latexrelease⟩    \else\ifx\f@family\ttdef@ult \fontseries\mdseries@tt
⟨latexrelease⟩    \else                        \fontseries\mddefault
⟨latexrelease⟩    \fi\fi\fi
⟨latexrelease⟩  \selectfont
⟨latexrelease⟩}
⟨latexrelease⟩
⟨latexrelease⟩
```

```
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\bfseries}{Custom series with hooks}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\bfseries
⟨latexrelease⟩        {\not@math@alphabet\bfseries\mathbf
⟨latexrelease⟩         \fontseries\bfdefault\selectfont}
⟨latexrelease⟩\DeclareRobustCommand\mdseries
⟨latexrelease⟩        {\not@math@alphabet\mdseries\relax
⟨latexrelease⟩         \fontseries\mddefault\selectfont}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩



⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\expand@font@defaults}{Custom series with hooks}%
```

`\expand@font@defaults` `\rm@def@ult` `\sf@def@ult` `\tt@def@ult` `\md@def@ult` `\bf@def@ult`

The family specific defaults are fully expanded, i.e., they are defined via `\edef` inside `\DeclareFontSeriesDefault`. However, the overall defaults, e.g., `\bfdefault` may have been redefined by the user and thus may not be fully expanded. So to enable reliable comparison we make expanded versions of them. That we rerun each time. The alternative would be to only allow for changes before begin document.

```
\def\expand@font@defaults{%
  \edef\rmdef@ult{\rmdefault}%
  \edef\sfdef@ult{\sfdefault}%
  \edef\ttdef@ult{\ttdefault}%
```

The series defaults may contain some surplus `m` that we need to drop here.

```
  \series@maybe@drop@one@m\bfdefault\bfdef@ult
  \series@maybe@drop@one@m\mddefault\mddef@ult
```

Formats that set up parallel fonts, e.g., for Japanese, can use this hook to add additional code here.

```
  \UseHook{expand@font@defaults}%
}
```

(*End definition for* `\expand@font@defaults` *and others.*)

`\rmfamily` Here are the document level commands for changing the main font families, or rather, here is a documented outline of the code, the actual code is then streamlined and somewhat generalized.

```
DeclareRobustCommand\rmfamily{%
 \not@math@alphabet\rmfamily\mathrm
```

If families are changed then we have to do a bit more work. In the original NFSS implementation a family change kept encoding, series shape and size unchanged but now we can't any longer simply reuse the current series value. Instead we may have to change it from one family default to the next.

```
\expand@font@defaults
```

We have to do the testing while the current family is still unchanged but we have to do the adjustment of the series after it got changed (because the new family might have different sets of shapes available and we certainly don't want to see substitution going on. So we use `\target@series@value` to hold the target series (if any).

```
\let\target@series@value\@empty
```

Thus, if the current family is the sans family

```
\ifx\f@family\sfdef@ult
```

and if we using the medium series of the sans family

```
      \ifx\f@series\mdseries@sf
```

then lets switch to the medium series for the serif family

```
                                        \let\target@series@value\mdseries@rm
```

and if we use the bold series of the sans family switch to the bold default of the serif family:

```
      \else\ifx\f@series\bfseries@sf  \let\target@series@value\bfseries@rm
```

However, the sans family may not have any specific defaults set, so we also compare with the overall defaults.

```
      \else\ifx\f@series\mddef@ult    \let\target@series@value\mdseries@rm
      \else\ifx\f@series\bfdef@ult    \let\target@series@value\bfseries@rm
```

If neither test was true we leave the series alone. This way a special manual setting such as `\fontseries{lc}` is not undone if the family changes (of course there may not be any support for it in the new family but then the NFSS substitution kicks in and sorts it out).

```
      \fi\fi\fi\fi
```

We need to do the same if the current family is the typewriter family:

```
\else\ifx\f@family\ttdef@ult
      \ifx\f@series\mdseries@tt       \let\target@series@value\mdseries@rm
      \else\ifx\f@series\bfseries@tt  \let\target@series@value\bfseries@rm
      \else\ifx\f@series\mddef@ult    \let\target@series@value\mdseries@rm
      \else\ifx\f@series\bfdef@ult    \let\target@series@value\bfseries@rm
      \fi\fi\fi\fi
\fi\fi
```

With these preparations for series out of the way we can now change the font family to `\rmdefault`.

```
\fontfamily\rmdefault
```

If \target@series@value is still empty there is nothing more to do other than selecting the new family. However, if not then we should update the font series now as well. But there is one further subtle issue. We may not have loaded an .fd file for our target font family yet. In the past that was done in \selectfont if necessary but since we are now doing all the comparisons in \fontseries we need to make sure that the font family specifications are already loaded prior to calling \fontseries.

```
\ifx\target@series@value\@empty \else
  \maybe@load@fontshape
```

Updating the series in this case means directly changing \f@series to the target value. We don't want to go through \fontseries because that would apply the mappings and then bx + b would keep bx instead of changing to b as desired. as

```
  \let\f@series\target@series@value
\fi
\selectfont}
```

So now for the real definition: most of the code above gets delegated to a helper command \prepare@family@series@update so that the definition becomes again fairly short. In addition we add a hook, mainly for our Japanese friends so that the code can be extended prior to the call to \selectfont.

```
\DeclareRobustCommand\rmfamily{%
   \not@math@alphabet\rmfamily\mathrm
```

This holds all the code discussed above, first argument is the meta family, i.e., rm in this case, and second argument is the default family name, e.g., cmr indirectly accessed via \rmdefault. This is calling \fontfamily and if necessary \fontseries as outline above.

```
   \prepare@family@series@update{rm}\rmdefault
```

Then comes the hook code (by default a no-op) and finally the call to \selectfont.

```
   \UseHook{rmfamily}%
   \selectfont}
```

The definitions for \sffamily and \ttfamily are similar, the differences are only in what font families get checked.

\sffamily
\ttfamily

```
\DeclareRobustCommand\sffamily{%
   \not@math@alphabet\sffamily\mathsf
   \prepare@family@series@update{sf}\sfdefault
   \UseHook{sffamily}%
   \selectfont}

\DeclareRobustCommand\ttfamily{%
   \not@math@alphabet\ttfamily\mathtt
   \prepare@family@series@update{tt}\ttdefault
   \UseHook{ttfamily}%
   \selectfont}
```

(*End definition for* \rmfamily*,* \sffamily*, and* \ttfamily*.*)

rmfamily
sffamily
ttfamily
normalfont
expand@font@defaults
bfseries
bfseries/defaults
mdseries
mdseries/defaults

Declare the hooks used above.

```
\NewHook{rmfamily}
\NewHook{sffamily}
\NewHook{ttfamily}
\NewHook{normalfont}
\NewHook{expand@font@defaults}
\NewHook{bfseries}
\NewHook{bfseries/defaults}
\NewHook{mdseries}
\NewHook{mdseries/defaults}
```

(*End definition for* `rmfamily` *and others.*)

\@rmfamilyhook
\@sffamilyhook
\@ttfamilyhook
\@defaultfamilyhook

These four hooks have legacy versions used in 2020/02/02 so we should support them until they aren't any longer used.

By default the hooks do nothing.

```
\let\@rmfamilyhook\@empty
\let\@sffamilyhook\@empty
\let\@ttfamilyhook\@empty
\let\@defaultfamilyhook\@empty   %FMi sort out
```

(*End definition for* `\@rmfamilyhook` *and others.*)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\expand@font@defaults}{Custom series with hooks}%
⟨latexrelease⟩
⟨latexrelease⟩\def\expand@font@defaults{%
⟨latexrelease⟩   \edef\rmdef@ult{\rmdefault}%
⟨latexrelease⟩   \edef\sfdef@ult{\sfdefault}%
⟨latexrelease⟩   \edef\ttdef@ult{\ttdefault}%
⟨latexrelease⟩   \edef\bfdef@ult{\bfdefault}%
⟨latexrelease⟩   \edef\mddef@ult{\mddefault}%
⟨latexrelease⟩   \edef\famdef@ult{\familydefault}%
⟨latexrelease⟩}
⟨latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\rmfamily{%
⟨latexrelease⟩    \not@math@alphabet\rmfamily\mathrm
⟨latexrelease⟩    \prepare@family@series@update{rm}\rmdefault
⟨latexrelease⟩    \@rmfamilyhook
⟨latexrelease⟩    \selectfont}
⟨latexrelease⟩\DeclareRobustCommand\sffamily{%
⟨latexrelease⟩    \not@math@alphabet\sffamily\mathsf
⟨latexrelease⟩    \prepare@family@series@update{sf}\sfdefault
⟨latexrelease⟩    \@sffamilyhook
⟨latexrelease⟩    \selectfont}
⟨latexrelease⟩\DeclareRobustCommand\ttfamily{%
⟨latexrelease⟩    \not@math@alphabet\ttfamily\mathtt
⟨latexrelease⟩    \prepare@family@series@update{tt}\ttdefault
⟨latexrelease⟩    \@ttfamilyhook
⟨latexrelease⟩    \selectfont}
⟨latexrelease⟩\let\@rmfamilyhook\@empty
⟨latexrelease⟩\let\@sffamilyhook\@empty
```

```
⟨latexrelease⟩\let\@ttfamilyhook\@empty
⟨latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\expand@font@defaults}{Custom series with hooks}%
⟨latexrelease⟩
⟨latexrelease⟩\let\expand@font@defaults\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\bfseries
⟨latexrelease⟩        {\not@math@alphabet\bfseries\mathbf
⟨latexrelease⟩         \fontseries\bfdefault\selectfont}
⟨latexrelease⟩\DeclareRobustCommand\mdseries
⟨latexrelease⟩        {\not@math@alphabet\mdseries\relax
⟨latexrelease⟩         \fontseries\mddefault\selectfont}
⟨latexrelease⟩\DeclareRobustCommand\rmfamily
⟨latexrelease⟩        {\not@math@alphabet\rmfamily\mathrm
⟨latexrelease⟩         \fontfamily\rmdefault\selectfont}
⟨latexrelease⟩\DeclareRobustCommand\sffamily
⟨latexrelease⟩        {\not@math@alphabet\sffamily\mathsf
⟨latexrelease⟩         \fontfamily\sfdefault\selectfont}
⟨latexrelease⟩\DeclareRobustCommand\ttfamily
⟨latexrelease⟩        {\not@math@alphabet\ttfamily\mathtt
⟨latexrelease⟩         \fontfamily\ttdefault\selectfont}
⟨latexrelease⟩
⟨latexrelease⟩\let\@rmfamilyhook\@undefined
⟨latexrelease⟩\let\@sffamilyhook\@undefined
⟨latexrelease⟩\let\@ttfamilyhook\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\IfFontSeriesContextTF` With the ability for `\bfseries` or `\mdseries` to be mapped to different NFSS axis values it becomes important to have the ability to determine the current context as we can no longer look at `\f@series` to answer a question such as "am I currently typesetting in a bold typeface?"

This is provided by the test `\IfFontSeriesContextTF`. It takes three arguments:

- The context we try to check (either `bf` for bold or `md` for medium, i.e., the same that can go into the first mandatory argument of `\DeclareFontSeriesDefault`),
- what to do if we are in this context (true case) and
- what to do if we are not (false case).

This allows you to define commands like `\IfBold`, e.g.,

```
\newcommand\IfBold[2]{\IfSeriesContextTF{bf}{#1}{#2}}
```

and then do

```
This is \IfBold{bold}{non-bold} text.
```

and get the appropriate result.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                    {\IfFontSeriesContextTF}{Font series context}%
\DeclareRobustCommand\IfFontSeriesContextTF[1]{%
  \expand@font@defaults
```

In the beginning we haven't found the context we are looking for.

```
  \@font@series@contextfalse
```

We store the requested context away for use in the tests.

```
  \def\requested@test@context{#1}%
```

The next definition is there to ensure that get a final match during testing even if the current family is non of the meta families (`rm`, `sf` or `tt`). This will then basically tests if the current font family matches the overall default.

```
  \expandafter\edef\csname ??def@ult\endcsname{\f@family}%
```

Then we run through the meta family list (currently containing just the three values) followed by the artificial meta family `??` and test each of them in turn using `\test@font@series@context` as the testing command.

```
  \let\@elt\test@font@series@context
      \@meta@family@list
      \@elt{??}%
  \let\@elt\relax
```

Following that we evaluate the status of `\if@font@series@context` to determine which of the remaining arguments (true/false case) we have to execute.

```
  \if@font@series@context
  \expandafter\@firstoftwo
  \else
  \expandafter\@secondoftwo
  \fi
}
```

(*End definition for* `\IfFontSeriesContextTF`.)

`\test@font@series@context` This tests the context (stored in `\requested@test@context`) and updates the boolean if the right context is found.

```
\def\test@font@series@context#1{%
```

First task is to figure out whether the current family matches `\rmfamily`, `\sffamily`, etc. so in `\reserved@a` we store the value of `\rmdef@ult` (or whatever the given meta family is) and compare that to `\f@family`.

```
  \edef\reserved@a{\csname #1def@ult\endcsname}%
  \ifx\f@family\reserved@a
```

If they match we have found the right meta family so we don't need to test any of the remaining meta family and therefore change `\@elt` to `\@gobble`.

```
    \let\@elt\@gobble
```

Now we have to test if `\f@series` matches the requested context (e.g., whether `\bfseries@rm` has that value if the current meta family is `rm` and we are looking for the `bf` context).

```
    \expandafter\ifx
                \csname\requested@test@context series@#1\endcsname\f@series
```

If yes we change the boolean and are done.

```
      \@font@series@contexttrue
```

If not then maybe the reason is that nothing special was set up for that meta family so we also check now check if `\f@series` matches the overall default (e.g., `\bfdef@ult` if we are looking for the bold context). If that matches we change the boolean.

```
    \else
      \expandafter\ifx
                  \csname\requested@test@context def@ult\endcsname\f@series
        \@font@series@contexttrue
  \fi\fi\fi
}
```

(*End definition for* `\test@font@series@context`.)

`\if@font@series@context` The boolean to signal if we found the requested font series context.

```
\newif\if@font@series@context
```

(*End definition for* `\if@font@series@context`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\IfFontSeriesContextTF}{Font series context}%
⟨latexrelease⟩
⟨latexrelease⟩\let\IfFontSeriesContextTF\@undefined
⟨latexrelease⟩\let\test@font@series@context\@undefined
⟨latexrelease⟩\let\if@font@series@context\@undefined
⟨latexrelease⟩\let\@font@series@contexttrue\@undefined
⟨latexrelease⟩\let\@font@series@contextfalse\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

3 Supporting nested emphasis

By default LaTeX 2_ε supports two levels of nested emphasis: if the current font has an upright shape then it switches to `\itshape` otherwise to `\eminnershape` (which defaults to `\upshape`). This means nested emphasis will oscillate between italic and upright shapes.

Sometimes it would be nice to allow for a more lengthy sequence, but instead of providing a fixed one LaTeX now offers a general mechanism that allows to define arbitrary sequences.

`\DeclareEmphSequence` `\emforce` This declaration expects a comma separated list of (font) change declarations corresponding to increasing levels of emphasis. The mechanism tries to be "smart" and verifies that the declarations actually alter the font. If not it will ignore this level and tries the next one—the assumption being that there was a manual font change in the document

to the font that is now supposed to be used for emphasis. Of course, this only works if the declarations in the list actually change the font and not, say, just the color. In such a case one has to use `\emforce` to which directs the mechanism to use the level even if the font attributes haven't changed.

`\emreset` If the nesting is so deep, that the specified levels are exhausted then `\emreset` is used as a final set of declarations (which by default returns back to the upright shape). Any additional nesting levels will then reuse the list from its beginning.

`\DeclareEmphSequence` `\DeclareEmphSequence` expects a clist of declaration. Spaces in the argument are dropped to avoid spurious spaces in the output. The declarations are additive. At the very end the shape is reset using `\emreset` and `\emforce` so that this case is never skipped.[29] Further nested calls restart at the beginning.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                    {\DeclareEmphSequence}{Nested emph}%
\def\DeclareEmphSequence#1{%
  \protected@edef\emfontdeclare@clist{\zap@space#1, \@empty\emforce\emreset}%
}
```

By default the it is empty, in which case `\eminnershape` is used by LaTeX.

```
\let\emfontdeclare@clist\@empty
```

(*End definition for* `\DeclareEmphSequence`.)

`\emrest` Reset the font to upright and upper/lower case. With the default rules using `\shapedefault` does that for us but to be on the safe side we do it like this:

```
\DeclareRobustCommand\emreset{\upshape\ulcshape}
```

(*End definition for* `\emrest`.)

`\em` The new definition for `\em` (and implicitly `\emph`) is the same as before as long as `\emfontdeclare@clist` is empty.

```
\DeclareRobustCommand\em{%
  \@nomath\em
  \ifx\emfontdeclare@clist\@empty
    \ifdim \fontdimen\@ne\font >\z@
      \eminnershape \else \itshape \fi
  \else
```

But if not we use the list to decide how to do emphasis.

We use the current font to check if the declarations have any effect, so even a size change is allowed and identified as a modification (but a color change, for example, isn't). So first we save the current status.

```
    \edef\em@currfont{\csname\curr@fontshape/\f@size\endcsname}%
```

Then we grab the next element from the list and check if it can be used.

```
    \expandafter\do@emfont@update\emfontdeclare@clist\do@emfont@update
  \fi
}
```

[29] Maybe we should not add `\emforce` but allow that case to be skipped as well. Of course, that might result in an endless loop if somebody defines a sequence without any font change and without `\emforce` but ...

```
\def\eminnershape{\upshape}
```

(*End definition for* `\em`.)

`\do@emfont@update` We know that the list (if not empty) has at least 2 elements separated by a comma, so we pick up the first in `#1` and the rest in `#2`.

```
\def\do@emfont@update#1,#2\do@emfont@update{%
```

First action is to alter the list and move the first entry to the end

```
  \def\emfontdeclare@clist{#2,#1}%
```

Then we execute current declaration. Appending `\selectfont` means one can write just `\fontshape{it}}` and that works then too.

```
%  \typeout{Use: \detokenize{#1}}%
  #1\selectfont
```

We then compare the current font with our saved version, but with a slight twist: we add `\em@force` at the end of the name. Normally this is empty so has no effect but if there was an `\emforce` as part of `#1` it will append a `/` to the font name (making it invalid) thus this will then always fail the test.

If the test fails we are done and the declarations will be used. Otherwise we will try the next declaration in the sequence.

```
  \expandafter\ifx\csname \curr@fontshape/\f@size\em@force
```

For the comparison with `\ifx` we have to expand `\em@currfont` once as the relevant info is inside.

```
                          \expandafter\endcsname
                    \em@currfont
  \expandafter\do@emfont@update\emfontdeclare@clist\do@emfont@update
```

If `\emforce` was used, we have to undo its effect:

```
  \else
    \let\em@force\@empty
  \fi
}
```

(*End definition for* `\do@emfont@update`.)

`\emforce` `\em@force` The definition of `\emforce` is simple: change `\em@force` to make the above test always invalid.

```
\protected\def\emforce{\def\em@force{/}}
\let\em@force\@empty
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\emforce` *and* `\em@force`.)

`\em` `\eminnershape` These are the older definitions for `\em`, prior to 2020.

We also have to define the *emphasize* font change command (i.e. `\em`). This command will look is the current font is sloped (i.e. has a positive `\fontdimen1`) and will then select either `\upshape` or `\itshape`.

```
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\DeclareEmphSequence}{Nested emph}%
⟨latexrelease⟩\let\DeclareEmphSequence\@undefined
⟨latexrelease⟩\let\emfontdeclare@clist\@undefined
⟨latexrelease⟩\let\emreset\@undefined
⟨latexrelease⟩\let\do@emfont@update\@undefined
```

```
⟨latexrelease⟩\let\emforce\@undefined
⟨latexrelease⟩\let\em@force\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\em
⟨latexrelease⟩        {\@nomath\em \ifdim \fontdimen\@ne\font >\z@
⟨latexrelease⟩                       \eminnershape \else \itshape \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\DeclareEmphSequence}{Nested emph}%
⟨latexrelease⟩\DeclareRobustCommand\em
⟨latexrelease⟩        {\@nomath\em \ifdim \fontdimen\@ne\font >\z@
⟨latexrelease⟩                       \upshape \else \itshape \fi}%
⟨latexrelease⟩\let\eminnershape\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\em` *and* `\eminnershape`.)

`\not@math@alphabet` This function generates an error message when it is called in math mode. The same function should be defined in `newlfont.sty`.

```
\def\not@math@alphabet#1#2{%
   \relax
   \ifmmode
     \@latex@error{Command \noexpand#1invalid in math mode}%
        {%
         Please
         \ifx#2\relax
            define a new math alphabet^^J%
            if you want to use a special font in math mode%
          \else
```

We have to a `\noexpand` below to prevent expansion of `#2`. In case of `#1` we can omit this (due to the current definition of robust commands since they do come out right there :-).

```
            use the math alphabet \noexpand#2instead of
            the #1command%
         \fi
         .
        }%
   \fi}
```

(*End definition for* `\not@math@alphabet`.)

Finally we provide two abbreviations to switch to the LaTeX *versions*.

```
\DeclareRobustCommand\boldmath{\@nomath\boldmath
              \mathversion{bold}}
\DeclareRobustCommand\unboldmath{\@nomath\unboldmath
              \mathversion{normal}}
```

Here we switch to the default math version by defining the internal macro `\math@version`. We dare not to call `\mathversion` at this place because this would call `\glb@settings`.

```
\def\math@version{normal}
```

3.1 Legacy

We start by defining a few macros that are part of standard LaTeX's user interface. The use of these functions is not encouraged, but they will allow to process older documents without changes to the source.

\newfont

```
\def\newfont#1#2{\@ifdefinable#1{\font#1=#2\relax}}
```

(*End definition for* \newfont.)

\symbol

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\symbol}{XeTeX change for math}%
\ifdefined\XeTeXversion
  \DeclareRobustCommand\symbol[1]{\Ucharcat#1 12\relax}
\else
  \DeclareRobustCommand\symbol[1]{\char#1\relax}
\fi
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\symbol}{XeTeX change for math}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\symbol[1]{\char#1\relax}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \symbol.)

3.2 Miscellaneous

\@setfontsize
\@setsize

This abbreviation is used by LaTeX's user level size changing commands, such as \large.

```
\def\@setfontsize#1#2#3{\@nomath#1%
```

For the benefit of people relying on keeping the name of the current font command saved in \@currsize we define it. To ensure that \@setfontsize keeps being robust we omit this assignment during times where \protect differs from \@typeset@protect.

```
    \ifx\protect\@typeset@protect
      \let\@currsize#1%
    \fi
    \fontsize{#2}{#3}\selectfont}
```

For compatibility we also define \@setsize the 209 command

```
⟨*compat⟩
\def\@setsize#1#2#3#4{\@setfontsize#1{#4}{#2}}
⟨/compat⟩
```

(*End definition for* \@setfontsize *and* \@setsize.)

\hexnumber@ To set up LaTeX's special math character definitions we first provide a macro to generate hexadecimal numbers. It is a rather simple \ifcase.

```
\def\hexnumber@#1{\ifcase\number#1
 0\or 1\or 2\or 3\or 4\or 5\or 6\or 7\or 8\or
 9\or A\or B\or C\or D\or E\or F\fi}
```

(*End definition for* \hexnumber@.)

\nfss@text In it simplest form \nfss@text is an \mbox. This will produce unbreakable text outside math and inside math you will get text with the same fonts as outside. The only drawback is that such item won't change sizes in subscripts. But this behavior can be easily changed. With the amstex style option one will get a sub style called amstext which will redefine the \nfss@text macro to produce correct text in all sizes.

We have to use \def instead of the shorter \let since \mbox is undefined when we reach this point.

```
\def\nfss@text#1{{\mbox{#1}}}
```

(*End definition for* \nfss@text.)

\copyright The definition of \copyright was changed so that it works in other type styles, and to make it robust. We leave the family untouched so that the copyright notice will come out differently if a different font family is in use. This command is commented out, since it is now defined in ltoutenc.dtx.

```
%\DeclareRobustCommand\copyright
%    {{\ooalign{\hfil
%     \raise.07ex\hbox{\mdseries\upshape c}\hfil\crcr
%     \mathhexbox20D}}}
```

(*End definition for* \copyright.)

\normalfont \reset@font The macro \reset@font is used in LaTeX to switch to a standard font, in order to initialize the current font in situations where typesetting is done in a new visual context (e.g. in a footnote). We define it here to allow the test for the new LaTeX version above but nevertheless are able to run all kind of mixtures.

The user interface name for \reset@font is \normalfont:

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                    {\normalfont}{Add hook to \normalfont}%
\DeclareRobustCommand\normalfont{%
```

Instead of calling \usefont, as it was done in the past, we inline the code from \usefont as we want to add the hook before \selectfont, but after all the font attributes are set.

```
    \fontencoding\encodingdefault
    \edef\f@family{\familydefault}%
    \edef\f@series{\seriesdefault}%
    \edef\f@shape{\shapedefault}%
```

Any earlier \fontseries, etc. should be canceled and we should switch unconditionally to the requested font face so we drop any code that may have been stored in \delayed@f@adjustment.

```
    \let\delayed@f@adjustment\@empty

    \UseHook{normalfont}%
```

This is the old name for the hook introduced in 2020/02/02. It will be removed in one of the future releases!

```
   \@defaultfamilyhook        % hookname from 2020/02 will vanish
   \selectfont}
\let\reset@font\normalfont
```

(*End definition for* `\normalfont` *and* `\reset@font`.)

```
% \changes{v3.2g}{2021/03/18}
%         {Add missing 2020/02/02 latexrelease entry.}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\normalfont}{Add hook to \normalfont}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\normalfont{%
⟨latexrelease⟩   \fontencoding\encodingdefault
⟨latexrelease⟩   \edef\f@family{\familydefault}%
⟨latexrelease⟩   \edef\f@series{\seriesdefault}%
⟨latexrelease⟩   \edef\f@shape{\shapedefault}%
⟨latexrelease⟩   \UseHook{normalfont}%
⟨latexrelease⟩   \@defaultfamilyhook        % hookname from 2020/02 will vanish
⟨latexrelease⟩   \selectfont}
⟨latexrelease⟩
⟨latexrelease⟩\let\reset@font\normalfont
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                 {\normalfont}{Add hook to \normalfont}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\normalfont{%
⟨latexrelease⟩   \fontencoding\encodingdefault
⟨latexrelease⟩   \edef\f@family{\familydefault}%
⟨latexrelease⟩   \edef\f@series{\seriesdefault}%
⟨latexrelease⟩   \edef\f@shape{\shapedefault}%
⟨latexrelease⟩   \@defaultfamilyhook
⟨latexrelease⟩   \selectfont}
⟨latexrelease⟩
⟨latexrelease⟩\let\reset@font\normalfont
⟨latexrelease⟩
⟨latexrelease⟩\let\@defaultfamilyhook\@empty
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\normalfont}{Add hook to \normalfont}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\normalfont
⟨latexrelease⟩         {\usefont\encodingdefault
⟨latexrelease⟩                  \familydefault
⟨latexrelease⟩                  \seriesdefault
⟨latexrelease⟩                  \shapedefault
```

```
⟨latexrelease⟩                    \relax}
⟨latexrelease⟩\let\reset@font\normalfont
⟨latexrelease⟩
⟨latexrelease⟩\let\@defaultfamilyhook\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

We left out the special LaTeX fonts which are not automatically included in the base version of the font selection since these fonts contain only a few characters which are also included in the AMS fonts so anybody who is using these fonts doesn't need them. But for compatibility reasons we will define these symbols.

```
\def\not@base#1{\@latex@error
  {Command \noexpand#1not provided in base LaTeX2e}%
  {Load the latexsym or the amsfonts package to
   define this symbol}}
\def\mho{\not@base\mho}
\def\Join{\not@base\Join}
\def\Box{\not@base\Box}
\def\Diamond{\not@base\Diamond}
\def\leadsto{\not@base\leadsto}
\def\sqsubset{\not@base\sqsubset}
\def\sqsupset{\not@base\sqsupset}
\def\lhd{\not@base\lhd}
\def\unlhd{\not@base\unlhd}
\def\rhd{\not@base\rhd}
\def\unrhd{\not@base\unrhd}
```

We now initialize all variables set by `\DeclareErrorFont`. These values are not really important since they will be overwritten later on by the definition in `fontdef.ltx`.

However, if `fontdef.cfg` is corrupted then at least a hopefully suitable error font is present.

```
\DeclareErrorFont{OT1}{cmr}{m}{n}{10}  %% don't modify this setting
                                       %% overwrite it in fontdef.cfg
                                       %% if necessary
```

We also set some default values for `\f@family` etc. Note that we don't yet have any encodings that comes later. In the past this was implicitly done by `\DeclareErrorFont`.

```
\fontfamily{cmr}
```

Previously the default values for series and shape were set by calling `\fontseries` and `\fontshape`, but their action is now delayed until `\selectfont` which isn't called inside the format (to avoid unnecessarily loading a font that may never get used). We therefore have to set `\f@series` and `\f@shape` directly instead.

```
\def\f@series{m}           % \fontseries{m}
\def\f@shape{n}            % \fontshape{n}
```

```
\fontsize{10}{10}
```

The initial `fontenc` package load list. This will get overwritten in `fonttext` and is only provided in case an old `fonttext.cfg` does not define the command:

```
\def\@fontenc@load@list{\@elt{T1,OT1}}
```

We now load the customizable parts of NFSS.

```
\InputIfFileExists{fonttext.cfg}
           {\typeout{=====================================^^J%
                     ^^J%
                      Local config file fonttext.cfg used^^J%
                     ^^J%
                     ====================================}%
             \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
            }
           {\input{fonttext.ltx}}
\let\@addtofilelist\@gobble
```

Ditto for math although I don't think that we will get a lot of customisation :-)

```
\InputIfFileExists{fontmath.cfg}
           {\typeout{=====================================^^J%
                     ^^J%
                      Local config file fontmath.cfg used^^J%
                     ^^J%
                     ====================================}%
             \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
            }
           {\input{fontmath.ltx}}
\let\@addtofilelist\@gobble
```

Then we preload several fonts. This file might be customized *without* changing the behavior of the format (i.e. necessary font definitions will be loaded at runtime if they are not preloaded). This is done in the file `preload.ltx`.

```
\InputIfFileExists{preload.cfg}
           {\typeout{=====================================^^J%
                     ^^J%
                      Local config file preload.cfg used^^J%
                     ^^J%
                     ====================================}%
             \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
            }
           {\input{preload.ltx}}
\let\@addtofilelist\@gobble
```

`\seriesdefault`
`\seriesdefault@kernel`

After `\seriesdefault` got defined inside `fonttext.ltx` or a `.cfg` file overwriting it, we alter its value by appending `\@empty` to it. This will vanish if expanded but allows us to check if the default gets altered (even to the same value) in the document preamble. All we have to do is to save the current value somewhere and later compare the two. For this we use `\seriesdefault@kernel`.

```
\expandafter\def\expandafter\seriesdefault\expandafter{\seriesdefault\@empty}
\let\seriesdefault@kernel\seriesdefault
```

(*End definition for* `\seriesdefault` *and* `\seriesdefault@kernel`.)

`\@acci`
`\@accii`
`\@acciii`

We also save the values of some accents in `\@acci`, `\@accii` and `\@acciii` so they can be restored by a `minipage` inside a `tabbing` environment.

```
\let\@acci\' \let\@accii\` \let\@acciii\=
```

(*End definition for* `\@acci`, `\@accii`, *and* `\@acciii`.)

`\cal`
`\mit`

Here were the two old ⟨*alphabet identifiers*⟩.

(*End definition for* `\cal` *and* `\mit`.)

⟨/2ekernel⟩

File B
fontdef.dtx

<-latexrelease> [2021/01/15 v3.0i LaTeX Kernel (<-latexrelease> font setup)]

1 Introduction

This file is used to generate the files `fonttext.ltx` (text font declarations) and `fontmath.ltx` (math font declarations), which are used during the format generation. It contains the declaration of the standard text encodings used at the site as well as a minimal subset of font shape groups that NFSS will look at to ensure that the specified encodings are valid.

The math part contains the setup for math encodings as well as the default math symbol declarations that belong to the encoding.

It is possible to change this setup (by using other fonts, or defaults) without losing the ability to process documents written at other sites. Portability in this sense means that a document will compile without errors. It does not mean, however, that identical output will be produced. For this it is necessary that the distributed setup is used at both installations.

2 Customization

You are not allowed to change this source file! If you want to change the default encodings and/or the font shape groups preloaded you should create a copy of `fonttext.ltx` under the name `fonttext.cfg` and change this copy. If LaTeX 2_ε finds a file of this name it will use it, otherwise it uses the standard file which is `fontdef.ltx`.

If you don't plan to use Computer Modern much or at all, it might (!) be a good idea to make your own `fonttext.cfg`. Look at the comments below (docstrip module 'text') to see what should go into such a file.

To change the math font setup use a copy of `fontmath.ltx` under the name `fontmath.cfg` and change this copy. However, dealing with this interface is even more a job for an expert than changing the text font setup — in short, we don't encourage either.

> **Warning:** please note that we don't support customised LaTeX versions. Thus, before sending in a bug report please try your test file with a LaTeX format which is not customised and send in the log from that version (unless the problem goes away).

Please note: the following standard encodings have to be defined in all local variants of `font....cfg` to guarantee that all LaTeX installations behave in the same way.

`T1`	Cork TeX text encoding
`OT1`	old TeX text encoding
`U`	unknown encoding
`OML`	old TeX math letters encoding
`OMS`	old TeX math symbols encoding
`OMX`	old TeX math extension symbols encoding
`TU`	Unicode

Notice that some of these encodings are 'old' in the sense that we hope that they will be superseded soon by encoding standards defined by the TEX user community. Therefore this set of default encodings may change in the future.

The first candidate is `OT1` which will soon be replaced by `T1`, the official TEX text encoding.

> **Warning:** If you add additional encodings to this file there is no guarantee any longer that files processable at your installation will also be processable at other installations. Thus, if you make use of such an encoding in your document, e.g. if you intend to typeset in Cyrillic (`OT2` encoding), you need to specify this encoding in the preamble of your document prior to sending it to another installation. Once the encoding is specified in that place in your document, the document is processable at all LATEX installations (provided they have suitable fonts installed).
>
> For this reason we suggest that you define a short package file that sets up an additional encoding used at your site (rather than putting the encoding into this file) since this package can easily be shipped with your document.

3 The `docstrip` modules

The following modules are used to direct `docstrip` in generating external files:

driver	produce a documentation driver file
text	produce the file `fonttext.ltx`
math	produce the file `fontmath.ltx`
cfgtext	produce a dummy `fonttext.cfg` file
cfgmath	produce a dummy `fontmath.cfg` file

A typical `docstrip` command file would then have entries like:

```
generateFile{fonttext.ltx}{t}{\from{fontdef.dtx}{text}}
```

4 A driver for this document

The next bit of code contains the documentation driver file for TEX, i.e. the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

```
⟨*driver⟩
\documentclass{ltxdoc}
\GetFileInfo{fontdef.dtx}
\begin{document}
   \DocInput{fontdef.dtx}
\end{document}
⟨/driver⟩
```

5 The `fonttext.ltx` file

The identification is done earlier on with a `\ProvidesFile` declaration.

```
⟨*text⟩
\typeout{=== Don't modify this file, use a .cfg file instead ===^^J}
```

5.1 Encodings

This file declares the standard encodings for text and math fonts. All others should be declared in packages or in the documents directly.

For every text encoding there are normally a number of encoding specific commands, e.g. accents, special characters, etc. (The definition for such a command might have to change when the encoding is changed, because the character is in a different position, or not available at all, or the accent is produced in a different way.) This is handled by a general mechanism which is described in `ltoutenc.dtx`.

By convention, text encoding specific declarations, including the `\DeclareFontEncoding` declaration, are kept in separate file of the form ⟨*enc*⟩`enc.def`, e.g. `ot1enc.def`. This allows other applications to make use of the declarations as well.

Similar to the default encoding, the loading of the encoding files for the two major text encodings shouldn't be changed. In particular, the `inputenc` package depends on this.

```
\input {omlenc.def}
\input {omsenc.def}
```

Documents containing a lot of accented characters should really be using T1 fonts. We therefore load this last so that T1 encoding specific commands are executed as fast as possible (encoding files are no longer reloaded in `fontenc`.

```
\input {ot1enc.def}
\input  {t1enc.def}
\input{ts1enc.def}
```

```
\ifx\Umathcode\@undefined
```

We then set the default text font encoding. This will hopefully change some day to `T1`. This setting should *not* be changed to produce a portable format.

```
\fontencoding{OT1}
```

The initial `fontenc` package load list if an 8-bit TEX engine is used:

```
\def\@fontenc@load@list{\@elt{T1,OT1}}
```

```
\def\rmsubstdefault{cmr}
\def\sfsubstdefault{cmss}
\def\ttsubstdefault{cmtt}
\LoadFontDefinitionFile{TS1}{cmr}
```

```
\else
```

Unicode.

```
\input {tuenc.def}
\fontencoding{TU}
```

The initial `fontenc` package load list if a Unicode engine is used:

```
\def\@fontenc@load@list{\@elt{TU}}
```

```
\DeclareFontSubstitution{TU}{lmr}{m}{n}
\LoadFontDefinitionFile{TU}{lmr}
\LoadFontDefinitionFile{TU}{lmss}
\LoadFontDefinitionFile{TU}{lmtt}
```

```
\def\rmsubstdefault{lmr}
\def\sfsubstdefault{lmss}
\def\ttsubstdefault{lmtt}
\LoadFontDefinitionFile{TS1}{lmr}
```

```
\DeclareFontSubstitution{TU}{lmr}{m}{n}
```

End of Unicode branch.

```
\fi
```

If different encodings for text fonts are in use one could put the common setup into `\DeclareFontEncodingDefaults`. There is now a better mechanism so using this interface is discouraged!

```
\DeclareFontEncodingDefaults{}{}
```

Then we define the default substitution for every encoding. This release of LaTeX 2_ε assumes that the ec fonts are available. It is possible to change this to point to some other font family (e.g., Times with the appropriate encoding if it is available) without making documents non-portable. However, in such a case documents will produce different page breaks at other sites. The substitution defaults can all be changed without losing portability as long as there are font shape definitions for the selected substitutions.

```
\DeclareFontSubstitution{T1}{cmr}{m}{n}
\DeclareFontSubstitution{OT1}{cmr}{m}{n}
```

For every encoding declaration, LaTeX 2_ε will try to verify that the given substitution information makes sense, i.e. that it is impossible to go into an endless loop if font substitution happens. This is done at the moment the `\begin{document}` is encountered. LaTeX 2_ε will then check that for every encoding the substitution defaults form a valid font shape group, which means that it will check if there is a `\DeclareFontShape` declaration for this combination. We will therefore load the corresponding `.fd` files now. If we don't do this they would be loaded at verification time (i.e. at `\begin{document}` which would delay processing unnecessarily.

> **Warning:** Please note that this means that you have to regenerate the format whenever you change any of these `.fd` files since LaTeX 2_ε will not read `.fd` files if it already knows about the encoding/family combination.

The `\nfss@catcodes` ensures that white space is ignored in any definitions made in the fd files.

```
\begingroup
\nfss@catcodes
\input  {t1cmr.fd}
\input  {ot1cmr.fd}
\endgroup
```

We also load some other font definition files which are normally needed in a document. This is only done for processing speed and you can comment the next two lines out to save some memory. If necessary these files are then loaded when your document is processed. (Loading `.fd` files is a less drastic step compared to preloading fonts because the number of fonts is limited 255 at (nearly) every TeX installation, while the amount of main memory is not a limiting factor at most installations.)

```
\begingroup
\nfss@catcodes
\input {ot1cmss.fd}
\input {ot1cmtt.fd}
\endgroup
```

Even with all the precautions it is still possible that NFSS will run into problems, for example, when a `.fd` file contains corrupted data. To guard against such cases NFSS has a very low-level fallback font that is installed with the following line.

```
\DeclareErrorFont{OT1}{cmr}{m}{n}{10}
```

This means, "if everything else fails use Computer Modern Roman normal shape at 10pt in the old text encoding". You can change the font used but the encoding should be the same as the one specified with `\fontencoding` above.

5.2 Defaults

To allow the use of `\rmfamily`, `\sffamily`, etc. in documents even if non-standard families are used we provide nine macros which hold the name of the corresponding families, series, and so on. This makes it easy to use other font families (like Times Roman, etc.). One simply has to redefine these defaults.

All these hooks have to be defined in this file but you can change their meaning (except for `\encodingdefault`) without making documents non-portable.

`\encodingdefault` `\rmdefault` `\sfdefault` `\ttdefault`

The following three definitions set up the meaning for `\rmfamily`, `\sffamily`, and `\ttfamily`.

```
\ifx\Umathcode\@undefined
\newcommand\encodingdefault{OT1}
\newcommand\rmdefault{cmr}
\newcommand\sfdefault{cmss}
\newcommand\ttdefault{cmtt}
\else
\newcommand\encodingdefault{TU}
\newcommand\rmdefault{lmr}
\fontfamily{\rmdefault}
\newcommand\sfdefault{lmss}
\newcommand\ttdefault{lmtt}
\fi
⟨/text⟩
⟨latexrelease⟩\IncludeInRelease{2017/01/01}%
⟨latexrelease⟩                  {\encodingdefault}{TU encoding default}%
⟨latexrelease⟩\ifx\Umathcode\@undefined
⟨latexrelease⟩\renewcommand\encodingdefault{OT1}
⟨latexrelease⟩\fontencoding{\encodingdefault}
⟨latexrelease⟩\renewcommand\rmdefault{cmr}
⟨latexrelease⟩\fontfamily{\rmdefault}
⟨latexrelease⟩\renewcommand\sfdefault{cmss}
⟨latexrelease⟩\renewcommand\ttdefault{cmtt}
⟨latexrelease⟩\else
⟨latexrelease⟩\renewcommand\encodingdefault{TU}
⟨latexrelease⟩%done in everyjob\fontencoding{\encodingdefault}
⟨latexrelease⟩\renewcommand\rmdefault{lmr}
⟨latexrelease⟩\fontfamily{\rmdefault}
⟨latexrelease⟩\renewcommand\sfdefault{lmss}
⟨latexrelease⟩\renewcommand\ttdefault{lmtt}
⟨latexrelease⟩\fi
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\encodingdefault}{TU encoding default}%
```

```
⟨latexrelease⟩\fontencoding{OT1}
⟨latexrelease⟩\renewcommand\encodingdefault{OT1}
⟨latexrelease⟩\fontencoding{\encodingdefault}
⟨latexrelease⟩\renewcommand\rmdefault{cmr}
⟨latexrelease⟩\fontfamily{\rmdefault}
⟨latexrelease⟩\renewcommand\sfdefault{cmss}
⟨latexrelease⟩\renewcommand\ttdefault{cmtt}
⟨latexrelease⟩\EndIncludeInRelease
⟨*text⟩
```

(*End definition for* `\encodingdefault` *and others.*)

`\bfdefault` `\mddefault`

Series changing commands are influenced by the following hooks.

```
\newcommand\bfdefault{b}  % overwritten below (for rollback)
\newcommand\mddefault{m}  % overwritten below (for rollback)
```

(*End definition for* `\bfdefault` *and* `\mddefault`.)

`\itdefault` `\sldefault` `\scdefault` `\updefault`

Shape changing commands use the following hooks.

```
\newcommand\itdefault{it}
\newcommand\sldefault{sl}
\newcommand\scdefault{sc}
\newcommand\updefault{up}  % overwritten below (for rollback)
```

(*End definition for* `\itdefault` *and others.*)

```
⟨/text⟩
⟨*text | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\updefault}{font defaults change}%
%     \begin{macrocode}
\renewcommand\updefault{up}
```

We append `\@empty` to the series value so that we can detect if it got changed via `\def` or `\renewcommand` later.

```
\renewcommand\bfdefault{b\@empty}
\renewcommand\mddefault{m\@empty}
```

```
\let\bfdefault@previous\bfdefault
\let\mddefault@previous\mddefault
⟨/text | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\updefault}{font defaults change}%
⟨latexrelease⟩
⟨latexrelease⟩\renewcommand\updefault{n}
⟨latexrelease⟩\renewcommand\bfdefault{bx}
⟨latexrelease⟩
⟨latexrelease⟩\let\bfdefault@previous\undefined
⟨latexrelease⟩\let\mddefault@previous\undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*text⟩
```

\familydefault
\seriesdefault
\shapedefault

Finally we have the hooks that describe the behaviour of the \normalfont command. To stay portable, the definition of \encodingdefault should *not* be changed and should match the setting above for \fontencoding. All other values can be set according to your taste.

```
\newcommand\familydefault{\rmdefault}
\newcommand\seriesdefault{\mddefault}
```

In previous releases \shapedefault pointed to \updefault which resolved to n, but these days that is no longer the case (and up is wrong when you want to do a reset. So we now use n explicitly.

```
\newcommand\shapedefault{n}
```

(*End definition for* \familydefault*,* \seriesdefault*, and* \shapedefault*.*)

This finishes the low-level setup in fonttext.ltx.

```
⟨/text⟩
```

6 The fontmath.ltx file

The identification is done earlier on with a \ProvidesFile declaration.

```
⟨*math⟩
\typeout{=== Don't modify this file, use a .cfg file instead ===^^J}
```

6.1 The font encodings used

```
\DeclareFontEncoding{OML}{}{}
\DeclareFontEncoding{OMS}{}{}
\DeclareFontEncoding{OMX}{}{}
```

Finally a declaration for U encoding which serves for all fonts that do not fit standard encodings. For math this sets up \noaccents@ providing for AMS-LaTeX. This macro is used therein to handle accented characters if they are not supported by the font. In other words, if fonts with U encoding are used in math, all accents (like from \breve) are obtained from some other font that has them.

```
\DeclareFontEncoding{U}{}{\noaccents@}
```

The encodings for math are next:

```
\DeclareFontSubstitution{OML}{cmm}{m}{it}
\DeclareFontSubstitution{OMS}{cmsy}{m}{n}
\DeclareFontSubstitution{OMX}{cmex}{m}{n}
\DeclareFontSubstitution{U}{cmr}{m}{n}
```

```
\begingroup
\nfss@catcodes
\input  {omlcmm.fd}
\input  {omscmsy.fd}
\input  {omxcmex.fd}
\input  {ucmr.fd}
\endgroup
```

6.1.1 Symbolfont and Alphabet declarations

We now define the basic symbol fonts used by LaTeX. These four symbol fonts must be defined by this file.

It is possible to make the symbol fonts point to other external fonts without losing the ability to process documents written at other sites, as long as one defines the same

symbol font names with the same encodings, e.g. `operators` with `OT1` etc. If other encodings are used documents become non-portable. Such a change should therefore be done in a package file.

```
\DeclareSymbolFont{operators}   {OT1}{cmr} {m}{n}
\DeclareSymbolFont{letters}     {OML}{cmm} {m}{it}
\DeclareSymbolFont{symbols}     {OMS}{cmsy}{m}{n}
\DeclareSymbolFont{largesymbols}{OMX}{cmex}{m}{n}
```

```
\SetSymbolFont{operators}{bold}{OT1}{cmr} {bx}{n}
\SetSymbolFont{letters}  {bold}{OML}{cmm} {b}{it}
\SetSymbolFont{symbols}  {bold}{OMS}{cmsy}{b}{n}
```

Below are the seven math alphabets which are defined by NFSS. Again they must be defined by this file. However, as before you can change the fonts used without losing portability, but you should be careful when changing the encoding since that may make documents come out wrong.

```
\DeclareSymbolFontAlphabet{\mathrm}    {operators}
\DeclareSymbolFontAlphabet{\mathnormal}{letters}
\DeclareSymbolFontAlphabet{\mathcal}   {symbols}
\DeclareMathAlphabet      {\mathbf}{OT1}{cmr}{bx}{n}
\DeclareMathAlphabet      {\mathsf}{OT1}{cmss}{m}{n}
\DeclareMathAlphabet      {\mathit}{OT1}{cmr}{m}{it}
\DeclareMathAlphabet      {\mathtt}{OT1}{cmtt}{m}{n}
```

Given the currently available fonts we cannot bold-en `\mathbf` and `\mathtt` but in principle one could use 'ultra bold' or something. The alphabets defined via `\DeclareSymbolFontAlphabet` will change automatically in a new math version if the corresponding symbol font changes.

```
\SetMathAlphabet\mathsf{bold}{OT1}{cmss}{bx}{n}
\SetMathAlphabet\mathit{bold}{OT1}{cmr}{bx}{it}
```

6.2 Math font sizes

The declarations below declare the text, script and scriptscript size to be used for each text font size.

All occurrences of sizes longer than a single character are replaced with the macro name that holds them, saving a number of tokens (but losing a bit of speed, so this may not stay this way).

```
\DeclareMathSizes{5}{5}{5}{5}
\DeclareMathSizes{6}{6}{5}{5}
\DeclareMathSizes{7}{7}{5}{5}
\DeclareMathSizes{8}{8}{6}{5}
\DeclareMathSizes{9}{9}{6}{5}
\DeclareMathSizes{\@xpt}{\@xpt}{7}{5}
\DeclareMathSizes{\@xipt}{\@xipt}{8}{6}
\DeclareMathSizes{\@xiipt}{\@xiipt}{8}{6}
\DeclareMathSizes{\@xivpt}{\@xivpt}{\@xpt}{7}
\DeclareMathSizes{\@xviipt}{\@xviipt}{\@xiipt}{\@xpt}
\DeclareMathSizes{\@xxpt}{\@xxpt}{\@xivpt}{\@xiipt}
\DeclareMathSizes{\@xxvpt}{\@xxvpt}{\@xxpt}{\@xviipt}
```

6.3 The math symbol assignments

We start by setting up math codes for most of the characters typed in directly from the keyboard. Most of them are normally already setup up in the same way by IniTEX. However, we repeat them here to have a complete setup which can be exchanged with another if desired.

6.3.1 The letters

```
\DeclareMathSymbol{a}{\mathalpha}{letters}{`a}
\DeclareMathSymbol{b}{\mathalpha}{letters}{`b}
\DeclareMathSymbol{c}{\mathalpha}{letters}{`c}
\DeclareMathSymbol{d}{\mathalpha}{letters}{`d}
\DeclareMathSymbol{e}{\mathalpha}{letters}{`e}
\DeclareMathSymbol{f}{\mathalpha}{letters}{`f}
\DeclareMathSymbol{g}{\mathalpha}{letters}{`g}
\DeclareMathSymbol{h}{\mathalpha}{letters}{`h}
\DeclareMathSymbol{i}{\mathalpha}{letters}{`i}
\DeclareMathSymbol{j}{\mathalpha}{letters}{`j}
\DeclareMathSymbol{k}{\mathalpha}{letters}{`k}
\DeclareMathSymbol{l}{\mathalpha}{letters}{`l}
\DeclareMathSymbol{m}{\mathalpha}{letters}{`m}
\DeclareMathSymbol{n}{\mathalpha}{letters}{`n}
\DeclareMathSymbol{o}{\mathalpha}{letters}{`o}
\DeclareMathSymbol{p}{\mathalpha}{letters}{`p}
\DeclareMathSymbol{q}{\mathalpha}{letters}{`q}
\DeclareMathSymbol{r}{\mathalpha}{letters}{`r}
\DeclareMathSymbol{s}{\mathalpha}{letters}{`s}
\DeclareMathSymbol{t}{\mathalpha}{letters}{`t}
\DeclareMathSymbol{u}{\mathalpha}{letters}{`u}
\DeclareMathSymbol{v}{\mathalpha}{letters}{`v}
\DeclareMathSymbol{w}{\mathalpha}{letters}{`w}
\DeclareMathSymbol{x}{\mathalpha}{letters}{`x}
\DeclareMathSymbol{y}{\mathalpha}{letters}{`y}
\DeclareMathSymbol{z}{\mathalpha}{letters}{`z}
```

```
\DeclareMathSymbol{A}{\mathalpha}{letters}{`A}
\DeclareMathSymbol{B}{\mathalpha}{letters}{`B}
\DeclareMathSymbol{C}{\mathalpha}{letters}{`C}
\DeclareMathSymbol{D}{\mathalpha}{letters}{`D}
\DeclareMathSymbol{E}{\mathalpha}{letters}{`E}
\DeclareMathSymbol{F}{\mathalpha}{letters}{`F}
\DeclareMathSymbol{G}{\mathalpha}{letters}{`G}
\DeclareMathSymbol{H}{\mathalpha}{letters}{`H}
\DeclareMathSymbol{I}{\mathalpha}{letters}{`I}
\DeclareMathSymbol{J}{\mathalpha}{letters}{`J}
\DeclareMathSymbol{K}{\mathalpha}{letters}{`K}
\DeclareMathSymbol{L}{\mathalpha}{letters}{`L}
\DeclareMathSymbol{M}{\mathalpha}{letters}{`M}
\DeclareMathSymbol{N}{\mathalpha}{letters}{`N}
\DeclareMathSymbol{O}{\mathalpha}{letters}{`O}
\DeclareMathSymbol{P}{\mathalpha}{letters}{`P}
\DeclareMathSymbol{Q}{\mathalpha}{letters}{`Q}
\DeclareMathSymbol{R}{\mathalpha}{letters}{`R}
\DeclareMathSymbol{S}{\mathalpha}{letters}{`S}
```

```
\DeclareMathSymbol{T}{\mathalpha}{letters}{`T}
\DeclareMathSymbol{U}{\mathalpha}{letters}{`U}
\DeclareMathSymbol{V}{\mathalpha}{letters}{`V}
\DeclareMathSymbol{W}{\mathalpha}{letters}{`W}
\DeclareMathSymbol{X}{\mathalpha}{letters}{`X}
\DeclareMathSymbol{Y}{\mathalpha}{letters}{`Y}
\DeclareMathSymbol{Z}{\mathalpha}{letters}{`Z}
```

6.3.2 The digits

```
\DeclareMathSymbol{0}{\mathalpha}{operators}{`0}
\DeclareMathSymbol{1}{\mathalpha}{operators}{`1}
\DeclareMathSymbol{2}{\mathalpha}{operators}{`2}
\DeclareMathSymbol{3}{\mathalpha}{operators}{`3}
\DeclareMathSymbol{4}{\mathalpha}{operators}{`4}
\DeclareMathSymbol{5}{\mathalpha}{operators}{`5}
\DeclareMathSymbol{6}{\mathalpha}{operators}{`6}
\DeclareMathSymbol{7}{\mathalpha}{operators}{`7}
\DeclareMathSymbol{8}{\mathalpha}{operators}{`8}
\DeclareMathSymbol{9}{\mathalpha}{operators}{`9}
```

6.3.3 Punctuation, brace, etc. keys

```
\DeclareMathSymbol{!}{\mathclose}{operators}{"21}
\DeclareMathSymbol{*}{\mathbin}{symbols}{"03} % \ast
\DeclareMathSymbol{+}{\mathbin}{operators}{"2B}
\DeclareMathSymbol{,}{\mathpunct}{letters}{"3B}
\DeclareMathSymbol{-}{\mathbin}{symbols}{"00}
\DeclareMathSymbol{.}{\mathord}{letters}{"3A}
\DeclareMathSymbol{:}{\mathrel}{operators}{"3A}
\DeclareMathSymbol{;}{\mathpunct}{operators}{"3B}
\DeclareMathSymbol{=}{\mathrel}{operators}{"3D}
\DeclareMathSymbol{?}{\mathclose}{operators}{"3F}
```

The following symbols are defined as delimiters below which automatically defines them as math symbols.

```
%\DeclareMathSymbol{(}{\mathopen}{operators}{"28}
%\DeclareMathSymbol{)}{\mathclose}{operators}{"29}
%\DeclareMathSymbol{/}{\mathord}{letters}{"3D}
%\DeclareMathSymbol{[}{\mathopen}{operators}{"5B}
%\DeclareMathSymbol{]}{\mathclose}{operators}{"5D}
%\DeclareMathSymbol{|}{\mathord}{symbols}{"6A}
%\DeclareMathSymbol{<}{\mathrel}{letters}{"3C}
%\DeclareMathSymbol{>}{\mathrel}{letters}{"3E}
```

Should all of the following being activated by default? Probably not.

```
%\DeclareMathSymbol{`\{}{\mathopen}{symbols}{"66}
%\DeclareMathSymbol{`\}}{\mathclose}{symbols}{"67}
%\DeclareMathSymbol{`\\}{\mathord}{symbols}{"6E} % \backslash
\mathcode`\ ="8000 % \space
\mathcode`\'="8000 % ^\prime
\mathcode`\_="8000 % \_
```

6.3.4 Delimitercodes for characters

[to be completed]

Finally, IniTEX sets all `\delcode` values to -1, except `\delcode`.=0

```
\DeclareMathDelimiter{(}{\mathopen} {operators}{"28}{largesymbols}{"00}
\DeclareMathDelimiter{)}{\mathclose}{operators}{"29}{largesymbols}{"01}
\DeclareMathDelimiter{[}{\mathopen} {operators}{"5B}{largesymbols}{"02}
\DeclareMathDelimiter{]}{\mathclose}{operators}{"5D}{largesymbols}{"03}
```

The next two are considered to be relations when not used in the context of a delimiter! And worse, they do even represent different glyphs when being used as delimiter and not as delimiter. This is a user level syntax inherited from plain TEX. Therefore we explicitly redefine the math symbol definitions for these symbols afterwards.

```
\DeclareMathDelimiter{<}{\mathopen}{symbols}{"68}{largesymbols}{"0A}
\DeclareMathDelimiter{>}{\mathclose}{symbols}{"69}{largesymbols}{"0B}
\DeclareMathSymbol{<}{\mathrel}{letters}{"3C}
\DeclareMathSymbol{>}{\mathrel}{letters}{"3E}
```

And here is another case where the non-delimiter version produces a glyph different from the delimiter version.

```
\DeclareMathDelimiter{/}{\mathord}{operators}{"2F}{largesymbols}{"0E}
\DeclareMathSymbol{/}{\mathord}{letters}{"3D}
```

```
\DeclareMathDelimiter{|}{\mathord}{symbols}{"6A}{largesymbols}{"0C}
```

```
\expandafter\DeclareMathDelimiter\@backslashchar
                        {\mathord}{symbols}{"6E}{largesymbols}{"0F}
```

N.B. `{` and `}` should NOT get delcodes; otherwise parameter grouping fails!

6.4 Symbols accessed via control sequences

6.4.1 Greek letters

```
\DeclareMathSymbol{\alpha}{\mathord}{letters}{"0B}
\DeclareMathSymbol{\beta}{\mathord}{letters}{"0C}
\DeclareMathSymbol{\gamma}{\mathord}{letters}{"0D}
\DeclareMathSymbol{\delta}{\mathord}{letters}{"0E}
\DeclareMathSymbol{\epsilon}{\mathord}{letters}{"0F}
\DeclareMathSymbol{\zeta}{\mathord}{letters}{"10}
\DeclareMathSymbol{\eta}{\mathord}{letters}{"11}
\DeclareMathSymbol{\theta}{\mathord}{letters}{"12}
\DeclareMathSymbol{\iota}{\mathord}{letters}{"13}
\DeclareMathSymbol{\kappa}{\mathord}{letters}{"14}
\DeclareMathSymbol{\lambda}{\mathord}{letters}{"15}
\DeclareMathSymbol{\mu}{\mathord}{letters}{"16}
\DeclareMathSymbol{\nu}{\mathord}{letters}{"17}
\DeclareMathSymbol{\xi}{\mathord}{letters}{"18}
\DeclareMathSymbol{\pi}{\mathord}{letters}{"19}
\DeclareMathSymbol{\rho}{\mathord}{letters}{"1A}
\DeclareMathSymbol{\sigma}{\mathord}{letters}{"1B}
\DeclareMathSymbol{\tau}{\mathord}{letters}{"1C}
\DeclareMathSymbol{\upsilon}{\mathord}{letters}{"1D}
\DeclareMathSymbol{\phi}{\mathord}{letters}{"1E}
\DeclareMathSymbol{\chi}{\mathord}{letters}{"1F}
\DeclareMathSymbol{\psi}{\mathord}{letters}{"20}
\DeclareMathSymbol{\omega}{\mathord}{letters}{"21}
\DeclareMathSymbol{\varepsilon}{\mathord}{letters}{"22}
\DeclareMathSymbol{\vartheta}{\mathord}{letters}{"23}
\DeclareMathSymbol{\varpi}{\mathord}{letters}{"24}
```

```
\DeclareMathSymbol{\varrho}{\mathord}{letters}{"25}
\DeclareMathSymbol{\varsigma}{\mathord}{letters}{"26}
\DeclareMathSymbol{\varphi}{\mathord}{letters}{"27}
\DeclareMathSymbol{\Gamma}{\mathalpha}{operators}{"00}
\DeclareMathSymbol{\Delta}{\mathalpha}{operators}{"01}
\DeclareMathSymbol{\Theta}{\mathalpha}{operators}{"02}
\DeclareMathSymbol{\Lambda}{\mathalpha}{operators}{"03}
\DeclareMathSymbol{\Xi}{\mathalpha}{operators}{"04}
\DeclareMathSymbol{\Pi}{\mathalpha}{operators}{"05}
\DeclareMathSymbol{\Sigma}{\mathalpha}{operators}{"06}
\DeclareMathSymbol{\Upsilon}{\mathalpha}{operators}{"07}
\DeclareMathSymbol{\Phi}{\mathalpha}{operators}{"08}
\DeclareMathSymbol{\Psi}{\mathalpha}{operators}{"09}
\DeclareMathSymbol{\Omega}{\mathalpha}{operators}{"0A}
```

6.4.2 Ordinary symbols

```
\DeclareMathSymbol{\aleph}{\mathord}{symbols}{"40}
\DeclareMathSymbol{\imath}{\mathord}{letters}{"7B}
\DeclareMathSymbol{\jmath}{\mathord}{letters}{"7C}
\DeclareMathSymbol{\ell}{\mathord}{letters}{"60}
\DeclareMathSymbol{\wp}{\mathord}{letters}{"7D}
\DeclareMathSymbol{\Re}{\mathord}{symbols}{"3C}
\DeclareMathSymbol{\Im}{\mathord}{symbols}{"3D}
\DeclareMathSymbol{\partial}{\mathord}{letters}{"40}
\DeclareMathSymbol{\infty}{\mathord}{symbols}{"31}
\DeclareMathSymbol{\prime}{\mathord}{symbols}{"30}
\DeclareMathSymbol{\emptyset}{\mathord}{symbols}{"3B}
\DeclareMathSymbol{\nabla}{\mathord}{symbols}{"72}
\DeclareMathSymbol{\top}{\mathord}{symbols}{"3E}
\DeclareMathSymbol{\bot}{\mathord}{symbols}{"3F}
\DeclareMathSymbol{\triangle}{\mathord}{symbols}{"34}
\DeclareMathSymbol{\forall}{\mathord}{symbols}{"38}
\DeclareMathSymbol{\exists}{\mathord}{symbols}{"39}
\DeclareMathSymbol{\neg}{\mathord}{symbols}{"3A}
```

Alias:

```
%    \let\lnot=\neg
\DeclareMathSymbol{\lnot}{\mathord}{symbols}{"3A}
```

```
\DeclareMathSymbol{\flat}{\mathord}{letters}{"5B}
\DeclareMathSymbol{\natural}{\mathord}{letters}{"5C}
\DeclareMathSymbol{\sharp}{\mathord}{letters}{"5D}
\DeclareMathSymbol{\clubsuit}{\mathord}{symbols}{"7C}
\DeclareMathSymbol{\diamondsuit}{\mathord}{symbols}{"7D}
\DeclareMathSymbol{\heartsuit}{\mathord}{symbols}{"7E}
\DeclareMathSymbol{\spadesuit}{\mathord}{symbols}{"7F}
```

```
\DeclareRobustCommand\hbar{{\mathchar'26\mkern-9muh}}
\DeclareRobustCommand\surd{{\mathchar"1270}}
\DeclareRobustCommand\angle{{\vbox{\ialign{$\m@th\scriptstyle##$\crcr
      \not\mathrel{\mkern14mu}\crcr
      \noalign{\nointerlineskip}
      \mkern2.5mu\leaders\hrule \@height.34pt\hfill\mkern2.5mu\crcr}}}}
```

6.4.3 Large Operators

```
\DeclareMathSymbol{\coprod}{\mathop}{largesymbols}{"60}
```

```
\DeclareMathSymbol{\bigvee}{\mathop}{largesymbols}{"57}
\DeclareMathSymbol{\bigwedge}{\mathop}{largesymbols}{"56}
\DeclareMathSymbol{\biguplus}{\mathop}{largesymbols}{"55}
\DeclareMathSymbol{\bigcap}{\mathop}{largesymbols}{"54}
\DeclareMathSymbol{\bigcup}{\mathop}{largesymbols}{"53}
\DeclareMathSymbol{\intop}{\mathop}{largesymbols}{"52}
    \DeclareRobustCommand\int{\intop\nolimits}
\DeclareMathSymbol{\prod}{\mathop}{largesymbols}{"51}
\DeclareMathSymbol{\sum}{\mathop}{largesymbols}{"50}
\DeclareMathSymbol{\bigotimes}{\mathop}{largesymbols}{"4E}
\DeclareMathSymbol{\bigoplus}{\mathop}{largesymbols}{"4C}
\DeclareMathSymbol{\bigodot}{\mathop}{largesymbols}{"4A}
\DeclareMathSymbol{\ointop}{\mathop}{largesymbols}{"48}
    \DeclareRobustCommand\oint{\ointop\nolimits}
\DeclareMathSymbol{\bigsqcup}{\mathop}{largesymbols}{"46}
\DeclareMathSymbol{\smallint}{\mathop}{symbols}{"73}
```

6.4.4 Binary symbols

```
\DeclareMathSymbol{\triangleleft}{\mathbin}{letters}{"2F}
\DeclareMathSymbol{\triangleright}{\mathbin}{letters}{"2E}
\DeclareMathSymbol{\bigtriangleup}{\mathbin}{symbols}{"34}
\DeclareMathSymbol{\bigtriangledown}{\mathbin}{symbols}{"35}
```

Alias:

```
%   \let \varbigtriangledown \bigtriangledown
%   \let \varbigtriangleup \bigtriangleup
\DeclareMathSymbol{\varbigtriangleup}{\mathbin}{symbols}{"34}
\DeclareMathSymbol{\varbigtriangledown}{\mathbin}{symbols}{"35}
```

These last two synonyms are needed because the stmaryrd package redefines them as Operators.

```
\DeclareMathSymbol{\wedge}{\mathbin}{symbols}{"5E}
\DeclareMathSymbol{\vee}{\mathbin}{symbols}{"5F}
```

Alias:

```
%   \let\land=\wedge
%   \let\lor=\vee
\DeclareMathSymbol{\land}{\mathbin}{symbols}{"5E}
\DeclareMathSymbol{\lor}{\mathbin}{symbols}{"5F}
```

```
\DeclareMathSymbol{\cap}{\mathbin}{symbols}{"5C}
\DeclareMathSymbol{\cup}{\mathbin}{symbols}{"5B}
\DeclareMathSymbol{\ddagger}{\mathbin}{symbols}{"7A}
\DeclareMathSymbol{\dagger}{\mathbin}{symbols}{"79}
\DeclareMathSymbol{\sqcap}{\mathbin}{symbols}{"75}
\DeclareMathSymbol{\sqcup}{\mathbin}{symbols}{"74}
\DeclareMathSymbol{\uplus}{\mathbin}{symbols}{"5D}
\DeclareMathSymbol{\amalg}{\mathbin}{symbols}{"71}
\DeclareMathSymbol{\diamond}{\mathbin}{symbols}{"05}
\DeclareMathSymbol{\bullet}{\mathbin}{symbols}{"0F}
\DeclareMathSymbol{\wr}{\mathbin}{symbols}{"6F}
\DeclareMathSymbol{\div}{\mathbin}{symbols}{"04}
\DeclareMathSymbol{\odot}{\mathbin}{symbols}{"0C}
\DeclareMathSymbol{\oslash}{\mathbin}{symbols}{"0B}
\DeclareMathSymbol{\otimes}{\mathbin}{symbols}{"0A}
\DeclareMathSymbol{\ominus}{\mathbin}{symbols}{"09}
```

```
\DeclareMathSymbol{\oplus}{\mathbin}{symbols}{"08}
\DeclareMathSymbol{\mp}{\mathbin}{symbols}{"07}
\DeclareMathSymbol{\pm}{\mathbin}{symbols}{"06}
\DeclareMathSymbol{\circ}{\mathbin}{symbols}{"0E}
\DeclareMathSymbol{\bigcirc}{\mathbin}{symbols}{"0D}
\DeclareMathSymbol{\setminus}{\mathbin}{symbols}{"6E}
\DeclareMathSymbol{\cdot}{\mathbin}{symbols}{"01}
\DeclareMathSymbol{\ast}{\mathbin}{symbols}{"03}
\DeclareMathSymbol{\times}{\mathbin}{symbols}{"02}
\DeclareMathSymbol{\star}{\mathbin}{letters}{"3F}
```

6.4.5 Relations

```
\DeclareMathSymbol{\propto}{\mathrel}{symbols}{"2F}
\DeclareMathSymbol{\sqsubseteq}{\mathrel}{symbols}{"76}
\DeclareMathSymbol{\sqsupseteq}{\mathrel}{symbols}{"77}
\DeclareMathSymbol{\parallel}{\mathrel}{symbols}{"6B}
\DeclareMathSymbol{\mid}{\mathrel}{symbols}{"6A}
\DeclareMathSymbol{\dashv}{\mathrel}{symbols}{"61}
\DeclareMathSymbol{\vdash}{\mathrel}{symbols}{"60}
\DeclareMathSymbol{\nearrow}{\mathrel}{symbols}{"25}
\DeclareMathSymbol{\searrow}{\mathrel}{symbols}{"26}
\DeclareMathSymbol{\nwarrow}{\mathrel}{symbols}{"2D}
\DeclareMathSymbol{\swarrow}{\mathrel}{symbols}{"2E}
\DeclareMathSymbol{\Leftrightarrow}{\mathrel}{symbols}{"2C}
\DeclareMathSymbol{\Leftarrow}{\mathrel}{symbols}{"28}
\DeclareMathSymbol{\Rightarrow}{\mathrel}{symbols}{"29}
   \DeclareRobustCommand\neq{\not=}
```

As `\neq` is robust we should not use `\let` to define `\ne` as then it would change if `\neq` changes.

```
   \DeclareRobustCommand\ne{\not=}
```

It would ok to use `\let` for those declared by `\DeclareMathSymbol` but for a cleaner interface we avoid it always (just in case the internals change).

```
\DeclareMathSymbol{\leq}{\mathrel}{symbols}{"14}
\DeclareMathSymbol{\geq}{\mathrel}{symbols}{"15}
```

Alias:

```
%   \let\le=\leq
%   \let\ge=\geq
\DeclareMathSymbol{\le}{\mathrel}{symbols}{"14}
\DeclareMathSymbol{\ge}{\mathrel}{symbols}{"15}
```

```
\DeclareMathSymbol{\succ}{\mathrel}{symbols}{"1F}
\DeclareMathSymbol{\prec}{\mathrel}{symbols}{"1E}
\DeclareMathSymbol{\approx}{\mathrel}{symbols}{"19}
\DeclareMathSymbol{\succeq}{\mathrel}{symbols}{"17}
\DeclareMathSymbol{\preceq}{\mathrel}{symbols}{"16}
\DeclareMathSymbol{\supset}{\mathrel}{symbols}{"1B}
\DeclareMathSymbol{\subset}{\mathrel}{symbols}{"1A}
\DeclareMathSymbol{\supseteq}{\mathrel}{symbols}{"13}
\DeclareMathSymbol{\subseteq}{\mathrel}{symbols}{"12}
\DeclareMathSymbol{\in}{\mathrel}{symbols}{"32}
\DeclareMathSymbol{\ni}{\mathrel}{symbols}{"33}
```

Alias:

```
%    \let\owns=\ni
```

```
\DeclareMathSymbol{\owns}{\mathrel}{symbols}{"33}
\DeclareMathSymbol{\gg}{\mathrel}{symbols}{"1D}
\DeclareMathSymbol{\ll}{\mathrel}{symbols}{"1C}
\DeclareMathSymbol{\not}{\mathrel}{symbols}{"36}
\DeclareMathSymbol{\leftrightarrow}{\mathrel}{symbols}{"24}
\DeclareMathSymbol{\leftarrow}{\mathrel}{symbols}{"20}
\DeclareMathSymbol{\rightarrow}{\mathrel}{symbols}{"21}
```

Alias:

```
%   \let\gets=\leftarrow
%   \let\to=\rightarrow
\DeclareMathSymbol{\gets}{\mathrel}{symbols}{"20}
\DeclareMathSymbol{\to}{\mathrel}{symbols}{"21}
\DeclareMathSymbol{\mapstochar}{\mathrel}{symbols}{"37}
   \DeclareRobustCommand\mapsto{\mapstochar\rightarrow}
\DeclareMathSymbol{\sim}{\mathrel}{symbols}{"18}
\DeclareMathSymbol{\simeq}{\mathrel}{symbols}{"27}
\DeclareMathSymbol{\perp}{\mathrel}{symbols}{"3F}
\DeclareMathSymbol{\equiv}{\mathrel}{symbols}{"11}
\DeclareMathSymbol{\asymp}{\mathrel}{symbols}{"10}
\DeclareMathSymbol{\smile}{\mathrel}{letters}{"5E}
\DeclareMathSymbol{\frown}{\mathrel}{letters}{"5F}
\DeclareMathSymbol{\leftharpoonup}{\mathrel}{letters}{"28}
\DeclareMathSymbol{\leftharpoondown}{\mathrel}{letters}{"29}
\DeclareMathSymbol{\rightharpoonup}{\mathrel}{letters}{"2A}
\DeclareMathSymbol{\rightharpoondown}{\mathrel}{letters}{"2B}
```

Here cometh much profligate robustification of math constructs. Warning: some of these commands may become non-robust if an AMS package is loaded.

Further potential problems: some math font packages may make unfortunate assumptions about some of these definitions that are not true of the robust versions we need.

```
\DeclareRobustCommand
  \cong{\mathrel{\mathpalette\@vereq\sim}} % congruence sign
\def\@vereq#1#2{\lower.5\p@\vbox{\lineskiplimit\maxdimen\lineskip-.5\p@
    \ialign{$\m@th#1\hfil##\hfil$\crcr#2\crcr=\crcr}}}
\DeclareRobustCommand
  \notin{\mathrel{\m@th\mathpalette\c@ncel\in}}
\def\c@ncel#1#2{\m@th\ooalign{$\hfil#1\mkern1mu/\hfil$\crcr$#1#2$}}
\DeclareRobustCommand
  \rightleftharpoons{\mathrel{\mathpalette\rlh@{}}}
\def\rlh@#1{\vcenter{\m@th\hbox{\ooalign{\raise2pt
          \hbox{$#1\rightharpoonup$}\crcr
        $#1\leftharpoondown$}}}}
\DeclareRobustCommand
  \doteq{\buildrel\textstyle.\over=}
```

6.4.6 Arrows

```
\DeclareRobustCommand
  \joinrel{\mathrel{\mkern-3mu}}
\DeclareRobustCommand
  \relbar{\mathrel{\smash-}} % \smash, because -
                             % has the same height as +
```

In contrast to `plain.tex` `\Relbar` got braces around the equal sign to guard against it being "math active" expanding to `\futurelet`.... This might be the case when packages are implementing shorthands for math, e.g. `=>` meaning `\Rightarrow` etc. It would actually be better not to use `=` in such definitions but instead define something like `\mathequalsign` and use this. However we can't do this now as it would break other math layouts where characters are in different places (since those wouldn't know about the need for a new command name).

```
\DeclareRobustCommand
  \Relbar{\mathrel{=}}
\DeclareMathSymbol{\lhook}{\mathrel}{letters}{"2C}
   \DeclareRobustCommand\hookrightarrow{\lhook\joinrel\rightarrow}
\DeclareMathSymbol{\rhook}{\mathrel}{letters}{"2D}
   \DeclareRobustCommand\hookleftarrow{\leftarrow\joinrel\rhook}
\DeclareRobustCommand
  \bowtie{\mathrel\triangleright\joinrel\mathrel\triangleleft}
\DeclareRobustCommand
  \models{\mathrel{|}\joinrel\Relbar}
\DeclareRobustCommand
  \Longrightarrow{\Relbar\joinrel\Rightarrow}
```

LaTeX Change: `\longrightarrow` and `\longleftarrow` redefined to make then robust.

```
\DeclareRobustCommand\longrightarrow
     {\relbar\joinrel\rightarrow}
\DeclareRobustCommand\longleftarrow
     {\leftarrow\joinrel\relbar}
\DeclareRobustCommand
  \Longleftarrow{\Leftarrow\joinrel\Relbar}
\DeclareRobustCommand
  \longmapsto{\mapstochar\longrightarrow}
\DeclareRobustCommand
  \longleftrightarrow{\leftarrow\joinrel\rightarrow}
\DeclareRobustCommand
  \Longleftrightarrow{\Leftarrow\joinrel\Rightarrow}
\DeclareRobustCommand
  \iff{\;\Longleftrightarrow\;}
```

6.4.7 Punctuation symbols

```
\DeclareMathSymbol{\ldotp}{\mathpunct}{letters}{"3A}
\DeclareMathSymbol{\cdotp}{\mathpunct}{symbols}{"01}
\DeclareMathSymbol{\colon}{\mathpunct}{operators}{"3A}
```

This is commented out, since `\ldots` is now defined in ltoutenc.dtx.

```
%\def\@ldots{\mathinner{\ldotp\ldotp\ldotp}}
%\DeclareRobustCommand\ldots
%          {\relax\ifmmode\@ldots\else\mbox{$\m@th\@ldots\,$}\fi}
\DeclareRobustCommand
  \cdots{\mathinner{\cdotp\cdotp\cdotp}}
\DeclareRobustCommand
  \vdots{\vbox{\baselineskip4\p@ \lineskiplimit\z@
    \kern6\p@\hbox{.}\hbox{.}\hbox{.}}}
\DeclareRobustCommand
  \ddots{\mathinner{\mkern1mu\raise7\p@
    \vbox{\kern7\p@\hbox{.}}\mkern2mu
```

```
    \raise4\p@\hbox{.}\mkern2mu\raise\p@\hbox{.}\mkern1mu}}
```

6.4.8 Math accents

```
\DeclareMathAccent{\acute}{\mathalpha}{operators}{"13}
\DeclareMathAccent{\grave}{\mathalpha}{operators}{"12}
\DeclareMathAccent{\ddot}{\mathalpha}{operators}{"7F}
\DeclareMathAccent{\tilde}{\mathalpha}{operators}{"7E}
\DeclareMathAccent{\bar}{\mathalpha}{operators}{"16}
\DeclareMathAccent{\breve}{\mathalpha}{operators}{"15}
\DeclareMathAccent{\check}{\mathalpha}{operators}{"14}
\DeclareMathAccent{\hat}{\mathalpha}{operators}{"5E}
\DeclareMathAccent{\vec}{\mathord}{letters}{"7E}
\DeclareMathAccent{\dot}{\mathalpha}{operators}{"5F}
\DeclareMathAccent{\widetilde}{\mathord}{largesymbols}{"65}
\DeclareMathAccent{\widehat}{\mathord}{largesymbols}{"62}
```

For some reason plain TEX never bothered to provide a ring accent in math (although it is available in the fonts), but since we got a request for it here we go:

```
\DeclareMathAccent{\mathring}{\mathalpha}{operators}{"17}
```

6.4.9 Radicals

```
\DeclareMathRadical{\sqrtsign}{symbols}{"70}{largesymbols}{"70}
```

6.4.10 Over and under something, etc

```
\DeclareRobustCommand\overrightarrow[1]{\vbox{\m@th\ialign{##\crcr
      \rightarrowfill\crcr\noalign{\kern-\p@\nointerlineskip}
      $\hfil\displaystyle{#1}\hfil$\crcr}}}
\DeclareRobustCommand\overleftarrow[1]{\vbox{\m@th\ialign{##\crcr
      \leftarrowfill\crcr\noalign{\kern-\p@\nointerlineskip}%
      $\hfil\displaystyle{#1}\hfil$\crcr}}}
\DeclareRobustCommand\overbrace[1]
     {\mathop{\vbox{\m@th\ialign{##\crcr\noalign{\kern3\p@}%
      \downbracefill\crcr\noalign{\kern3\p@\nointerlineskip}%
      $\hfil\displaystyle{#1}\hfil$\crcr}}}\limits}
\DeclareRobustCommand\underbrace[1]{\mathop{\vtop{\m@th\ialign{##\crcr
   $\hfil\displaystyle{#1}\hfil$\crcr
   \noalign{\kern3\p@\nointerlineskip}%
   \upbracefill\crcr\noalign{\kern3\p@}}}}\limits}
```

(quite a waste of tokens, IMHO — Frank)

```
\DeclareRobustCommand\skew[3]
  {{\muskip\z@#1mu\divide\muskip\z@\tw@ \mkern\muskip\z@
    #2{\mkern-\muskip\z@{#3}\mkern\muskip\z@}\mkern-\muskip\z@}{}}
\DeclareRobustCommand\rightarrowfill{$\m@th\smash-\mkern-7mu%
  \cleaders\hbox{$\mkern-2mu\smash-\mkern-2mu$}\hfill
  \mkern-7mu\mathord\rightarrow$}
\DeclareRobustCommand\leftarrowfill{$\m@th\mathord\leftarrow\mkern-7mu%
  \cleaders\hbox{$\mkern-2mu\smash-\mkern-2mu$}\hfill
  \mkern-7mu\smash-$}
\DeclareMathSymbol{\braceld}{\mathord}{largesymbols}{"7A}
\DeclareMathSymbol{\bracerd}{\mathord}{largesymbols}{"7B}
\DeclareMathSymbol{\bracelu}{\mathord}{largesymbols}{"7C}
\DeclareMathSymbol{\braceru}{\mathord}{largesymbols}{"7D}
\DeclareRobustCommand\downbracefill{$\m@th \setbox\z@\hbox{$\braceld$}%
  \braceld\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\braceru
```

```
  \bracelu\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\bracerd$}
\DeclareRobustCommand\upbracefill{$\m@th \setbox\z@\hbox{$\braceld$}%
  \bracelu\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\bracerd
  \braceld\leaders\vrule \@height\ht\z@ \@depth\z@\hfill\braceru$}
```

6.4.11 Delimiters

```
\DeclareMathDelimiter{\lmoustache}   % top from (, bottom from )
   {\mathopen}{largesymbols}{"7A}{largesymbols}{"40}
\DeclareMathDelimiter{\rmoustache}   % top from ), bottom from (
   {\mathclose}{largesymbols}{"7B}{largesymbols}{"41}
\DeclareMathDelimiter{\arrowvert}    % arrow without arrowheads
   {\mathord}{symbols}{"6A}{largesymbols}{"3C}
\DeclareMathDelimiter{\Arrowvert}    % double arrow without arrowheads
   {\mathord}{symbols}{"6B}{largesymbols}{"3D}
\DeclareMathDelimiter{\Vert}
   {\mathord}{symbols}{"6B}{largesymbols}{"0D}
```

`\DeclareMathDelimiter` produces a command that is robust (with an internal macro containing the payload) so we should not use `\let` for making an alias

```
%\let\|=\Vert
\DeclareMathDelimiter{\|}
   {\mathord}{symbols}{"6B}{largesymbols}{"0D}
\DeclareMathDelimiter{\vert}
   {\mathord}{symbols}{"6A}{largesymbols}{"0C}
\DeclareMathDelimiter{\uparrow}
   {\mathrel}{symbols}{"22}{largesymbols}{"78}
\DeclareMathDelimiter{\downarrow}
   {\mathrel}{symbols}{"23}{largesymbols}{"79}
\DeclareMathDelimiter{\updownarrow}
   {\mathrel}{symbols}{"6C}{largesymbols}{"3F}
\DeclareMathDelimiter{\Uparrow}
   {\mathrel}{symbols}{"2A}{largesymbols}{"7E}
\DeclareMathDelimiter{\Downarrow}
   {\mathrel}{symbols}{"2B}{largesymbols}{"7F}
\DeclareMathDelimiter{\Updownarrow}
   {\mathrel}{symbols}{"6D}{largesymbols}{"77}
\DeclareMathDelimiter{\backslash}    % for double coset G\backslash H
   {\mathord}{symbols}{"6E}{largesymbols}{"0F}
\DeclareMathDelimiter{\rangle}
   {\mathclose}{symbols}{"69}{largesymbols}{"0B}
\DeclareMathDelimiter{\langle}
   {\mathopen}{symbols}{"68}{largesymbols}{"0A}
\DeclareMathDelimiter{\rbrace}
   {\mathclose}{symbols}{"67}{largesymbols}{"09}
\DeclareMathDelimiter{\lbrace}
   {\mathopen}{symbols}{"66}{largesymbols}{"08}
\DeclareMathDelimiter{\rceil}
   {\mathclose}{symbols}{"65}{largesymbols}{"07}
\DeclareMathDelimiter{\lceil}
   {\mathopen}{symbols}{"64}{largesymbols}{"06}
\DeclareMathDelimiter{\rfloor}
   {\mathclose}{symbols}{"63}{largesymbols}{"05}
\DeclareMathDelimiter{\lfloor}
   {\mathopen}{symbols}{"62}{largesymbols}{"04}
```

\lgroup
\rgroup
\bracevert

There are three plain TEX delimiters which are not fully supported by NFSS, since they partly point into a bold cmr font. Allocating a full symbol font, just to have three delimiters seems a bit too much given the limited space available. For this reason only the extensible sizes are supported. If this is not desired one can use, without losing portability, define \mathbf and \mathtt as font symbol alphabet (setting up cmr/bx/n and cmtt/m/n as symbol fonts first) and modify the delimiter declarations to point with their small variant to those symbol fonts. (This is done in oldlfont.dtx so look there for examples.)

```
\DeclareMathDelimiter{\lgroup} % extensible ( with sharper tips
     {\mathopen}{largesymbols}{"3A}{largesymbols}{"3A}
\DeclareMathDelimiter{\rgroup} % extensible ) with sharper tips
     {\mathclose}{largesymbols}{"3B}{largesymbols}{"3B}
\DeclareMathDelimiter{\bracevert} % the vertical bar that extends braces
     {\mathord}{largesymbols}{"3E}{largesymbols}{"3E}
```

(*End definition for* \lgroup*,* \rgroup*, and* \bracevert*.*)

6.5 Math versions of text commands

The \mathunderscore here is really a text definition, so it has been put back into ltoutenc.dtx (by Chris, 30/04/97) and should be removed from here.

These symbols are the math versions of text commands such as \P, \$, etc.

\mathparagraph
\mathsection
\mathdollar
\mathsterling
\mathunderscore

These math symbols are not in plain TEX.

```
\DeclareMathSymbol{\mathparagraph}{\mathord}{symbols}{"7B}
\DeclareMathSymbol{\mathsection}{\mathord}{symbols}{"78}
\DeclareMathSymbol{\mathdollar}{\mathord}{operators}{"24}
\DeclareRobustCommand\mathsterling{\mathit{\mathchar"7024}}
\DeclareRobustCommand\mathunderscore{\kern.06em\vbox{\hrule\@width.3em}}
```

(*End definition for* \mathparagraph *and others.*)

\mathellipsis

This is plain TEX's \ldots.

```
\DeclareRobustCommand\mathellipsis{\mathinner{\ldotp\ldotp\ldotp}}%
```

(*End definition for* \mathellipsis*.*)

6.6 Other special functions and parameters

6.6.1 Biggggg

```
⟨/math⟩
⟨*math | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                    {\Big}{Start LR-mode}%
\DeclareRobustCommand\big[1]{\leavevmode@ifvmode
   {\hbox{$\left#1\vbox to8.5\p@{}\right.\n@space$}}}
\DeclareRobustCommand\Big[1]{\leavevmode@ifvmode
   {\hbox{$\left#1\vbox to11.5\p@{}\right.\n@space$}}}
\DeclareRobustCommand\bigg[1]{\leavevmode@ifvmode
   {\hbox{$\left#1\vbox to14.5\p@{}\right.\n@space$}}}
\DeclareRobustCommand\Bigg[1]{\leavevmode@ifvmode
   {\hbox{$\left#1\vbox to17.5\p@{}\right.\n@space$}}}
⟨/math | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\Big}{Start LR-mode}%
⟨latexrelease⟩\def\big#1{{\hbox{$\left#1\vbox to8.5\p@{}\right.\n@space$}}}
⟨latexrelease⟩\def\Big#1{{\hbox{$\left#1\vbox to11.5\p@{}\right.\n@space$}}}
⟨latexrelease⟩\def\bigg#1{{\hbox{$\left#1\vbox to14.5\p@{}\right.\n@space$}}}
⟨latexrelease⟩\def\Bigg#1{{\hbox{$\left#1\vbox to17.5\p@{}\right.\n@space$}}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*math⟩
\def\n@space{\nulldelimiterspace\z@ \m@th}
```

6.6.2 The log-like functions

`\operator@font` The `\operator@font` determines the symbol font used for log-like functions.

```
\def\operator@font{\mathgroup\symoperators}
```

(*End definition for* `\operator@font`.)

6.6.3 Parameters

```
\thinmuskip=3mu
\medmuskip=4mu plus 2mu minus 4mu
\thickmuskip=5mu plus 5mu
```

This finishes the low-level setup in `fontmath.ltx`.

```
⟨/math⟩
```

7 Default cfg files

We provide default `cfg` files here to ensure that on installations that search large file trees we do not pick up some strange customisation files from somewhere.

```
⟨*cfgtext | cfgmath | cfgprel⟩
%%
%%
%%
%% Load the standard setup:
%%
⟨+cfgtext⟩\input{fonttext.ltx}
⟨+cfgmath⟩\input{fontmath.ltx}
⟨+cfgprel⟩\input{preload.ltx}
%%
%% Small changes could go here; see documentation in cfgguide.tex for
%% allowed modifications.
%%
%% In particular it is not allowed to misuse this configuration file
%% to modify internal LaTeX commands!
%%
%% If you use this file as the basis for configuration please change
%% the \ProvidesFile lines to clearly identify your modification, e.g.,
%%
⟨+cfgtext⟩%%  \ProvidesFile{fonttext.cfg}[2001/06/01
⟨+cfgmath⟩%%  \ProvidesFile{fonttext.cfg}[2001/06/01
⟨+cfgprel⟩%%  \ProvidesFile{preload.cfg}[2001/06/01
%%                              Customised local font setup]
%%
```

```
%%
⟨/cfgtext | cfgmath | cfgprel⟩
```

File C
preload.dtx

1 Overview

This file contains an number of possible settings for preloading fonts during installation of NFSS2 (which is used by LaTeX 2_ε). It will be used to generate the following files:

preload.min	minimal subset of fonts necessary to run NFSS2
preload.ori	preload of CM fonts similar to the old `lfonts.tex`
preload.ltx	The standard selection of preloads
cmpreloa.xpt	preload of CM fonts for 10pt document size
cmpreloa.xip	preload of CM fonts for 11pt document size
cmpreloa.xii	preload of CM fonts for 12pt document size
dcpreloa.xpt	preload of DC fonts for 10pt size
dcpreloa.xip	preload of DC fonts for 11pt size
dcpreloa.xii	preload of DC fonts for 12pt size

These files are for installations that make use of Computer Modern fonts either old encoding (OT1) or Cork encoding (T1). The Computer Modern fonts with Cork encoding are known as DC-fonts.

Most important is `preload.ltx` which is used during format generation. You are *not* allowed to change this file.

2 Customization

You can customize the preloaded fonts in your LaTeX 2_ε system by installing a file with the name `preload.cfg`. If this file exists it will be used in place of the system file `preload.ltx`. You can, for example, copy one of the files mentioned above (that can be generated from this source) to `preload.cfg`.

Or you can define completely other preloads. In that case start from `preload.min` since that contains the fonts that have to be preloaded by *all* LaTeX 2_ε systems.

Avoid using `preload.ori`, it will load so many fonts that on most installations it is nearly impossible to load other font families afterwards. This file is only generated to show what fonts have been preloaded by LaTeX 2.09.

If you normally use other fonts than Computer Modern `preload.min` might be best.

> **Warning:** If you preload fonts with encodings other than the normally supported encodings you have to declare that encoding in a `fontdef.cfg` configuration file (see the documentation in the file `fontdef.dtx`). Adding an extra encoding to the format might produce non-portable documents, thus this should be avoided if possible.

3 Module switches for the DOCSTRIP program

The DOCSTRIP will generate the above file from this source using the following module directives:

driver	produce a documentation driver file
preload	produce a preload... file
cm	for OT1 encoded Computer Modern
dc	for T1 encoded Computer Modern
min	produce minimal subset
xpt	produce 10pt preloads
xipt	produce 11pt preloads
xiipt	produce 12pt preloads
ori	produce preloads similar to old `lfonts.tex`
tex	produce preload.ltx

A typical DOCSTRIP command file would then have entries like:

```
generateFile{preload.min}{t}{\from{preload.dtx}{preload,min}}
```

for generating preload files.

4 A driver for this document

The next bit of code contains the documentation driver file for TEX, i.e., the file that will produce the documentation you are currently reading. It will be extracted from this file by the DOCSTRIP program.

```
⟨*driver⟩
\documentclass{ltxdoc}
%\OnlyDescription  % comment out for implementation details
\begin{document}
   \DocInput{preload.dtx}
\end{document}
⟨/driver⟩
```

5 The code

We begin by loading the math extension font (cmex10) and the LATEX line and circle fonts. It is necessary to do this explicitly since these are used by the LATEX format. Since the internal font name contains `/` characters and digits we construct the name via `\csname`. These are the only fonts (!) that must be loaded in this file.

All `\DeclarePreloadSizes` can be removed or others can be added, they only influence the processing speed.

```
\expandafter\font\csname OMX/cmex/m/n/10\endcsname=cmex10\relax
\font\tenln  =line10   \font\tenlnw  =linew10\relax
\font\tencirc=lcircle10 \font\tencircw=lcirclew10\relax
```

The above fonts should not be touched but anything below this point here in the preload suggestions can be modified without any problems.

```
⟨-tex⟩%*****************************************
⟨-tex⟩% Start any modification below this point **
⟨-tex⟩%*****************************************
⟨-tex⟩
%%
%% Computer Modern Roman:
%%-----------------------
```

```
⟨*ori⟩
\DeclarePreloadSizes{OT1}{cmr}{m}{n}
        {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74,24.88}
\DeclarePreloadSizes{OT1}{cmr}{bx}{n}{9,10,10.95,12,14.4,17.28}
\DeclarePreloadSizes{OT1}{cmr}{m}{sl}{10,10.95,12}
\DeclarePreloadSizes{OT1}{cmr}{m}{it}{7,8,9,10,10.95,12}
⟨/ori⟩
⟨+xpt & cm⟩ \DeclarePreloadSizes{OT1}{cmr}{m}{n}{5,7,10}
⟨+xpt & dc⟩ \DeclarePreloadSizes{T1}{cmr}{m}{n}{5,7,10}
⟨+xipt & cm⟩ \DeclarePreloadSizes{OT1}{cmr}{m}{n}{6,8,10.95}
⟨+xipt & dc⟩ \DeclarePreloadSizes{T1}{cmr}{m}{n}{6,8,10.95}
⟨+xiipt & cm⟩ \DeclarePreloadSizes{OT1}{cmr}{m}{n}{6,8,12}
⟨+xiipt & dc⟩ \DeclarePreloadSizes{T1}{cmr}{m}{n}{6,8,12}
%%
%% Computer Modern Sans:
%%----------------------
⟨+ori⟩ \DeclarePreloadSizes{OT1}{cmss}{m}{n}{10,10.95,12}
%%
%% Computer Modern Typewriter:
%%----------------------------
⟨+ori⟩ \DeclarePreloadSizes{OT1}{cmtt}{m}{n}{9,10,10.95,12}
%%
%% Computer Modern Math:
%%----------------------
⟨*ori⟩
\DeclarePreloadSizes{OML}{cmm}{m}{it}
        {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
\DeclarePreloadSizes{OMS}{cmsy}{m}{n}
        {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
⟨/ori⟩
```

The math fonts are the same for both DC and CM fonts. So far there isn't an agreed on standard.

```
⟨*xpt⟩
\DeclarePreloadSizes{OML}{cmm}{m}{it}{5,7,10}
\DeclarePreloadSizes{OMS}{cmsy}{m}{n}{5,7,10}
⟨/xpt⟩
⟨*xipt⟩
\DeclarePreloadSizes{OML}{cmm}{m}{it}{6,8,10.95}
\DeclarePreloadSizes{OMS}{cmsy}{m}{n}{6,8,10.95}
⟨/xipt⟩
⟨*xiipt⟩
\DeclarePreloadSizes{OML}{cmm}{m}{it}{6,8,12}
\DeclarePreloadSizes{OMS}{cmsy}{m}{n}{6,8,12}
⟨/xiipt⟩
%%
%% LaTeX symbol fonts:
%%--------------------
⟨*ori⟩
\DeclarePreloadSizes{U}{lasy}{m}{n}
        {5,6,7,8,9,10,10.95,12,14.4,17.28,20.74}
⟨/ori⟩
⟨/preload⟩
```

File D
ltfntcmd.dtx

Abstract

The commands defined in this file `ltfntcmd` are part of the kernel code for LaTeX 2_ε/NFSS2.
It is also meant to serve as documentation for package writers since it demonstrates how to define high-level font changing commands using a small number of creator functions.

1 Introduction

Font changes such as `\bfseries`, `\sffamily`, etc. are declarations; this means that their scope is delimited by the grouping structure, either by the next `\end` of some environment or by explicitly using a group, e.g., writing something like `{\bfseries...}` in the source. If you make the mistake of writing `\bfseries{...}` (thinking of `\bfseries` as a command with one argument) then the result is rather striking.

Font declarations are an artifact of the TeX system and for several reasons it is better to avoid them on the user level whenever possible. In LaTeX3 they will probably all be replaced by environments and by font commands taking one argument.

This file defines a creator function for such declarative font switches. This function creates commands which can be used in both math and text.

This file also defines a number of high-level commands (all starting with `\text..`) that have one argument and typeset this argument in the requested way. Thus these commands are for typesetting short pieces of text in a specific family, series or shape. These are all produced as examples of the use of a creator function which is itself also defined in this file.

Table 1 shows all these high-level commands in action. A further advantage of using these commands is that they automatically take care of any necessary italic correction on either side of their argument.

Thus, when using such commands, one does not have to worry about forgetting the italic correction when changing fonts. Only in very few situations is this additional space wrong but, for example, most typographers recommend omitting the italic correction if a small punctuation character, like a comma, directly follows the font change. Since the amount of correction required is partly a matter of taste, you can define in what situations the italic correction should be suppressed. This is done by putting the characters that should cancel a preceding italic correction in the list `\nocorrlist`.[30] The default definition for this list is produced by the following.

```
\newcommand \nocorrlist {,.}
```

It is best to declare the most often used characters first, because this will make the processing slightly faster. For example,

```
\emph{When using the \NFSS{} high-level commands,
the \emph{proper} use of italic corrections is
automatically taken care of}. Only
```

[30] Any package that changes the `\catcode` of a character inside `\nocorrlist` must then explicitly reset the list. Otherwise the changed character will no longer be recognized by the suppression algorithm.

Command	*Corresponds to*	*Action*
`\textnormal{..}`	`\normalfont`	Typeset argument in normal family
`\textrm{..}`	`\rmfamily`	Typeset argument in roman family
`\textsf{..}`	`\sffamily`	Typeset argument in sans serif family
`\texttt{..}`	`\ttfamily`	Typeset argument in `typewriter` family
`\textmd{..}`	`\mdseries`	Typeset argument in medium series
`\textbf{..}`	`\bfseries`	Typeset argument in **bold** series
`\textup{..}`	`\upshape`	Typeset argument in normal shape
`\textit{..}`	`\itshape`	Typeset argument in *italic* shape
`\textsl{..}`	`\slshape`	Typeset argument in *slanted* shape
`\textsc{..}`	`\scshape`	Typeset argument in SMALL CAPS shape
`\emph{..}`	`\em`	Typeset argument *emphasized*

Table 1: Font-change commands with arguments

> The font change commands provided here all start with `\text..` to emphasize that they are for use in normal text and to be easily memorable. They automatically take care of any necessary italic correction on either side of the argument.

```
\emph{sometimes} one has to help \LaTeX{} by
adding a \verb=\nocorr= command.
```

which results in:

> *When using the NFSS high-level commands, the* proper *use of italic corrections is automatically taken care of.* Only *sometimes* one has to help LaTeX by adding a `\nocorr` command.

In contrast, the use of the declaration forms is often more appropriate when you define your own commands or environments.

```
\newenvironment{bfitemize}{\begin{itemize}\normalfont\bfseries}
                          {\end{itemize}}
\begin{bfitemize}
\item This environment produces boldface items.
\item It is defined in terms of \LaTeX's
  \texttt{itemize} environment and NFSS
  declarations.
\end{bfitemize}
```

This gives:

- **This environment produces boldface items.**
- **It is defined in terms of LaTeX's `itemize` environment and NFSS declarations.**

In addition to global customization of when to insert the italic correction, it is of course sometimes necessary to explicitly insert one with `\/`.

It is also possible to suppress the italic correction in individual instances. For this, the command `\nocorr` is provided.

The `\nocorr` must appear as the first or last token inside the braces of the argument of the `\text...` commands, at that end of the text where you wish to suppress the italic correction.

It is worth pointing out here that inserting a `\/` in places where it can have no function (i.e. anywhere except immediately after a slanted letter) is not an error—it will just be silently ignored. Unfortunately this is not true if the redefinition of `\/` in `amstex.sty` is used as this version can cause space to be removed immediately before the `\/`.

2 The implementation

`\DeclareTextFontCommand` This is the creator function for `\text..` commands. It gives a warning if `\foo` or `\fragfoo` is already defined.

In math mode it simply puts the font declaration and text into a box (possibly an automagically sized one).

Otherwise it first scans the text to see where `\nocorr` occurs within it. This sets the `\check@ic` commands to do what is necessary concerning the italic correction at both ends.

The algorithm for deciding whether to put in an italic correction is not very subtle: one is added whenever the newly current font is not itself positively sloped, unless the next token is a character in the 'nocorr' list. At the end of the text this is done after closing the group so as to check the 'outer font'. Note that this will often result in adding an italic correction token after a character in an unsloped font; we believe (in early 2003) that this is perhaps inefficient but not dangerous.

It also now checks for empty contents of the text command and optimizes this case. Some care is also taken to check that doing dangerous things in vertical mode is avoided.

The italic correction token is added to the horizontal list before (in the list) an immediately preceding non-zero glob of glue (skip) and any non-zero penalty preceding that since, in the typical case, this puts it immediately after the last character in the preceding word.

Note that it is necessary to put in the `\aftergroup\maybe@ic` at the end of the group so that it comes after any other aftergroup tokens and immediately before the following tokens. It is also necessary to remove the `\fi` from the token list before the group ends; this is done by adding an `\expandafter` just before the closing brace.

```
⟨*2ekernel⟩
\def \DeclareTextFontCommand #1#2{%
  \DeclareRobustCommand#1[1]{%
    \ifmmode
      \nfss@text{#2##1}%
    \else
      \hmode@bgroup
       \text@command{##1}%
       #2\check@icl ##1\check@icr
       \expandafter
      \egroup
    \fi
                        }%
}
```

(*End definition for* `\DeclareTextFontCommand`.)

`\textrm` `\textsf` `\texttt` `\textnormal`

Now we define the `\text`⟨*family*⟩ commands in terms of the above; `\texttt` does not look very nice!

```
\DeclareTextFontCommand{\textrm}{\rmfamily}
\DeclareTextFontCommand{\textsf}{\sffamily}
\DeclareTextFontCommand{\texttt}{\ttfamily}
\DeclareTextFontCommand{\textnormal}{\normalfont}
```

(*End definition for* `\textrm` *and others.*)

`\textbf` `\textmd`

For the series attribute:

```
\DeclareTextFontCommand{\textbf}{\bfseries}
\DeclareTextFontCommand{\textmd}{\mdseries}
```

(*End definition for* `\textbf` *and* `\textmd`.)

`\textit` `\textsl` `\textsc` `\textup`

And for the shapes:

```
\DeclareTextFontCommand{\textit}{\itshape}
\DeclareTextFontCommand{\textsl}{\slshape}
\DeclareTextFontCommand{\textsc}{\scshape}
\DeclareTextFontCommand{\textup}{\upshape}
```

(*End definition for* `\textit` *and others.*)

`textulc` `textsw` `textssc`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\textulc}{Additional text commands}%
\DeclareTextFontCommand{\textulc}{\ulcshape}
\DeclareTextFontCommand{\textsw}{\swshape}
\DeclareTextFontCommand{\textssc}{\sscshape}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\textulc}{Additional text commands}%
⟨latexrelease⟩
⟨latexrelease⟩\let\textulc\@undefined
⟨latexrelease⟩\let\textsw\@undefined
⟨latexrelease⟩\let\textssc\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `textulc`, `textsw`, *and* `textssc`.)

`\emph`

Finally we have the `\em` font change declaration of LaTeX. The corresponding definition with argument is

```
\DeclareTextFontCommand{\emph}{\em}
```

(*End definition for* `\emph`.)

`\nocorr`

This is just a label, so it does nothing; it should also be unexpandable.

```
\let \nocorr \relax
```

(*End definition for* `\nocorr`.)

`\check@icl`
`\check@icr`

We define these defaults in case some error causes them to be expanded at the wrong time.

```
\let \check@icl \@empty
\let \check@icr \@empty
```

(*End definition for* `\check@icl` *and* `\check@icr`.)

`\text@command`
`\check@nocorr@`

This checks for a `\nocorr` as the first token in its argument and also for one in any other position not protected within braces (the latter is treated as if it were at the end of the argument).

Is this the correct action in the 'empty' case? It is efficient but typographically it is, strictly, incorrect!

```
\def \text@command #1{%
  \edef \reserved@a {\unexpanded{#1}}%
  \ifx \reserved@a \@empty
    \let \check@icl \@empty
    \let \check@icr \@empty
  \else
```

`\space` is a reserved word in LaTeX or actually already in plain TeX. If somebody really redefines it so many things will break that I don't see any reason to make this routine here slower than necessary.

```
%    \def \reserved@b { }%
%    \ifx \reserved@a \reserved@b
    \ifx \reserved@a \space
      \let \check@icl \@empty
      \let \check@icr \@empty
    \else
      \check@nocorr@ #1\nocorr\@nil
    \fi
  \fi
}
\def \check@nocorr@ #1#2\nocorr#3\@nil {%
```

The two checks are initialised here to their values in the normal case.

```
  \let \check@icl \maybe@ic
  \def \check@icr {\ifvmode \else \aftergroup \maybe@ic \fi}%
  \def \reserved@a {\nocorr}%
  \def \reserved@b {#1}%
  \def \reserved@c {#3}%
  \ifx \reserved@a \reserved@b
    \ifx \reserved@c \@empty
```

In this case there is a `\nocorr` at the start but not at the end, so `\check@icl` should be empty.

```
      \let \check@icl \@empty
    \else
```

Otherwise there is a `\nocorr` both at the start and elsewhere, so no italic corrections should be added.

```
      \let \check@icl \@empty
      \let \check@icr \@empty
    \fi
```

```
  \else
    \ifx \reserved@c \@empty
```

In this case there is no `\nocorr` anywhere, so we need to check for an italic correction at both the beginning and the end. This has been set up as the default so no code is needed here.

```
    \else
```

In this case there is no `\nocorr` at the start but there is one elsewhere, so no `\aftergroup` is needed.

```
      \let \check@icr \@empty
    \fi
  \fi
}
```

(*End definition for* `\text@command` *and* `\check@nocorr@`.)

`\ifmaybe@ic` Switch used solely within `\maybe@ic` not interfering with other switches.

```
\newif\ifmaybe@ic
```

(*End definition for* `\ifmaybe@ic`.)

`\maybe@ic` `\maybe@ic@` These macros implement the italic correction.

```
\def \maybe@ic {\futurelet\@let@token\maybe@ic@}
\def \maybe@ic@ {%
```

We first check to see if the current font is positively sloped. (But do not forget the message Rainer sent about an upright font with non-zero slope! Or is this an urban myth?) It has been suggested that this should test against a small positive value, but what?

```
  \ifdim  \fontdimen\@ne\font>\z@
  \else
    \maybe@ictrue
```

It would be possible, but probably not worthwhile, to continue the forward scan beyond any closing braces.

```
    \expandafter\@tfor\expandafter\reserved@a\expandafter:\expandafter=%
        \nocorrlist
```

We have to hide the `\@let@token` in the macro `\t@st@ic` rather than testing it directly in the loop since it might be `\let` to a `\fi` or `\else`, which would result in chaos.

```
    \do \t@st@ic
```

Frank thinks that the next bit is inefficient if done after the second change. Chris thinks that most all of this is inefficient for the commonest cases: but that is the price of a cleverer algorithm. It is certainly needed to deal with the use of `\nolinebreak`.

```
    \ifmaybe@ic \sw@slant \fi
  \fi
}
```

(*End definition for* `\maybe@ic` *and* `\maybe@ic@`.)

\t@st@ic The next token in the input stream is stored in \@let@token via a \let, the current token from \nocorrlist is stored via \def in \reserved@a. To compare them we have to fiddle around a bit.

If the only things to check were characters then this could be done via an \if thus their catcodes would not matter; but this will not work whilst \futurelet is used above.

```
\def \t@st@ic {%
  \expandafter\let\expandafter\reserved@b\expandafter=\reserved@a\relax
  \ifx\reserved@b\@let@token
```

If they are the same we record the fact and jump out of the loop.

```
    \maybe@icfalse
    \@break@tfor
  \fi
}
```

(*End definition for* \t@st@ic.)

\sw@slant The definition of the mysterious \sw@slant command is as follows.

```
\def \sw@slant {%
```

\fix@penalty

It is surely correct to put in an italic correction when there is no skip. If the last thing on the list is actually a zero skip (including things whose dimension part is zero, such as \hfill), or anything other than a character, then the italic correction will have no effect.

In order to work correctly with unbreakable spaces from ~ (and other common forms of line-breaking control) we also move back across a penalty before the glue.

```
  \ifdim \lastskip=\z@
    \fix@penalty
  \else
    \skip@ \lastskip
    \unskip
    \fix@penalty
    \hskip \skip@
  \fi
}
```

The above code means: "If there is a non-zero space just before the current position (\ifdim...) save the amount of that space (\skip@\lastskip), remove it (\unskip), then do a similar thing if there is a penalty just before the skip, and finally put the space back in."

Since zero glue cannot be distinguished in this context from no glue, we dare not put in an \hskip in this case as this may produce an unwanted breakpoint. This is not satisfactory.

The penalty before the glue is handled similarly, with the same caveats concerning the zero case. Is this the first recorded use of \unpenalty in standard LaTeX code?

```
\def \fix@penalty {%
  \ifnum \lastpenalty=\z@
    \@@italiccorr
  \else
    \count@ \lastpenalty
    \unpenalty
    \@@italiccorr
```

```
    \penalty \count@
  \fi
}
```

(*End definition for* `\sw@slant` *and* `\fix@penalty`.)

`\nocorrlist` This holds the list of characters that should prevent italic correction. They should be ordered by decreasing frequency of use. If any such character is made active later on one needs to redefine the list so that the active character becomes part of it.

```
\def \nocorrlist {,.}
```

(*End definition for* `\nocorrlist`.)

`\nfss@text` This command will by default behave like a LaTeX `\mbox` but may be redefined by packages such as `amstext.sty` to be a bit cleverer.

```
\ifx \nfss@text\@undefined
  \def \nfss@text {\leavevmode\hbox}
\fi
```

(*End definition for* `\nfss@text`.)

`\DeclareOldFontCommand` This is the function used to create declarative font-changing commands that can also be used to change alphabets in math-mode.

Usage: `\DeclareOldFontCommand \fn{`⟨*font-change decls*⟩`}` ⟨*math-alphabet*⟩

Here `\fn` is the font-declaration command being defined, ⟨*font-change decls*⟩ is the declaration it will expand to in text-mode, and ⟨*math-alphabet*⟩ is the (single) math alphabet specifier which is to be used in math-mode.

It does not care whether the command being defined already exists but it does give a warning if it redefines anything.

Here are some typical examples of its use in conjunction with more basic NFSS2 font commands.

```
\DeclareOldFontCommand{\rm}{\normalfont\rmfamily}{\mathrm}
\DeclareOldFontCommand{\sf}{\normalfont\sffamily}{\mathsf}
\DeclareOldFontCommand{\tt}{\normalfont\ttfamily}{\mathtt}
```

```
\def \DeclareOldFontCommand #1#2#3{%
  \DeclareRobustCommand #1{\@fontswitch {#2}{#3}}%
}
```

(*End definition for* `\DeclareOldFontCommand`.)

`\@fontswitch` `\@@math@egroup` `\@@math@egroup` These two commands actually do the necessary tests and declarative font- or alphabet-changing.

```
\def \@fontswitch #1#2{%
  \ifmmode
     \let \math@bgroup \relax
     \def \math@egroup {\let \math@bgroup \@@math@bgroup
                        \let \math@egroup \@@math@egroup}%
```

We need to have a \relax in the following line in case the #2 is something like \mathsf grabbing the next token as an argument. For this reason the code also uses explicit arguments again (see pr/1275).

```
      #2\relax
  \else
      #1%
  \fi
}
\let \@@math@bgroup \math@bgroup
\let \@@math@egroup \math@egroup
```

(*End definition for* \@fontswitch*,* \@@math@egroup*, and* \@@math@egroup*.*)

These commands are available only in the preamble.

```
\@onlypreamble \DeclareTextFontCommand
\@onlypreamble \DeclareOldFontCommand
```

3 Initialization

\normalsize This is defined to produce an error.

```
\def\normalsize{%
  \@latex@error {The font size command \protect\normalsize\space
              is not defined:\MessageBreak
              there is probably something wrong with
              the class file}\@eha
}
⟨/2ekernel⟩
```

(*End definition for* \normalsize*.*)

File E
lttextcomp.dtx

This file contains the implementation for accessing the glyphs provided by the TS1 encoding (Text Companion Encoding). This is now offered as part of the kernel and so the textcomp package which used to provide the definitions is now mainly needed for compatibility reasons (and doesn't do much any more).

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\NewModuleRelease{2020/02/02}{lttextcomp}
⟨latexrelease⟩                  {Text Companion symbols}
```

\oldstylenums
\legacyoldstylenums

Preserve the old definition of \oldstylenums under a different name.

This macro implements old style numerals but only works if we assume that the standard math fonts are used. Thus it needs changing in case other math encodings are used.

```
\DeclareRobustCommand\legacyoldstylenums[1]{%
   \begingroup
```

Provide spacing using the interword space of the current font.

```
    \spaceskip\fontdimen\tw@\font
```

Then switch to the math italic font. We don't change the current value of \f@series which means that you can use bold numerals if \bfseries is in force. As family we use \rmdefault which means that this only works if there exist an OML encoded version of that font or rather a corresponding .fd file (which is the case for standard LaTeX fonts even though they only contain substitutions).

```
    \usefont{OML}{\rmdefault}{\f@series}{it}%
    \mathgroup\symletters #1%
   \endgroup
}
```

And here is the improved one that adjusts depending on surroundings.

```
\DeclareRobustCommand\oldstylenums[1]{%
 \begingroup
 \ifmmode
   \mathgroup\symletters #1%
  \else
```

The \CheckEncodingSubset is discussed below.

```
   \CheckEncodingSubset\@use@text@encoding{TS1}\tc@oldstylesubst2{{#1}}%
 \fi
 \endgroup
}
```

The helper to select the substitution if needed.

```
\def\tc@oldstylesubst#1{%
   \tc@errorwarn
          {Oldstyle digits unavailable for
           family \f@family.\MessageBreak
           Default oldstyle digits used instead}\@eha
  \bgroup
      \expand@font@defaults
```

The substitution defaults are provided in the file `fonttext.ltx`.

```
      \ifx\f@family\rmdef@ult
         \fontfamily\rmsubstdefault
      \else\ifx\f@family\sfdef@ult
         \fontfamily\sfsubstdefault
      \else\ifx\f@family\ttdef@ult
         \fontfamily\ttsubstdefault
      \else
        \fontfamily\textcompsubstdefault
      \fi\fi\fi
      \fontencoding{TS1}\selectfont#1%
  \egroup
}
```

(*End definition for* `\oldstylenums` *and* `\legacyoldstylenums`.)

`\textcompsubstdefault` Here is the default for the "unknown" case:

```
\def\textcompsubstdefault{\rmsubstdefault}
```

(*End definition for* `\textcompsubstdefault`.)

`\DeclareEncodingSubset` The declaration takes 3 mandatory arguments: an *encoding* for which a subsetting is wanted (currently always `TS1`, and most likely forever), the *font family* for which we declare the subset and finally the *subset* number (between `0` (all of the encoding is supported) and `9` many glyphs are missing.

For `TS1` the numbers have been chosen in a way that most fonts can be fairly correctly categorized, but the default settings are always conservative, that is they may claim that less glyphs are supported than there actually are.

As these days many font families are set up to end in `-LF` (lining figures), `-OsF` (oldstyle figures), etc. the declaration supports a shortcut: if the *font family* name ends in `-*` then the star gets replaced by these common ending, e.g.,

```
\DeclareEncodingSubset{TS1}{Alegreya-*}{2}
```

is the same as writing

```
\DeclareEncodingSubset{TS1}{Alegreya-LF}{2}
\DeclareEncodingSubset{TS1}{Alegreya-OsF}{2}
\DeclareEncodingSubset{TS1}{Alegreya-TLF}{2}
\DeclareEncodingSubset{TS1}{Alegreya-TOsF}{2}
```

If only some are needed then one can define them individually but in many cases all four are wanted, hence the shortcut.

The coding of the declaration has no error checking as it is mostly for internal use.

```
\def\DeclareEncodingSubset#1#2{%
  \DeclareEncodingSubset@aux{#1}#2*\DeclareEncodingSubset@aux
}
```

```
\def\DeclareEncodingSubset@aux#1#2*#3\DeclareEncodingSubset@aux#4{%
```

if #3 is empty then there was no star, otherwise we define all four variants.

```
  \expandafter\ifx\expandafter X\detokenize{#3}X%
    \@DeclareEncodingSubset{#1}{#2}{#4}%
  \else
    \@DeclareEncodingSubset{#1}{#2LF}{#4}%
    \@DeclareEncodingSubset{#1}{#2TLF}{#4}%
    \@DeclareEncodingSubset{#1}{#2OsF}{#4}%
    \@DeclareEncodingSubset{#1}{#2TOsF}{#4}%
  \fi
}
```

The subset info is stored in a command with the name *family*:*subset* so if that already exists we change otherwise declare a subset.

```
\def\@DeclareEncodingSubset#1#2#3{%
   \@ifundefined{#1:#2}%
     {\@font@info{Setting #2 sub-encoding to #1/#3}}%
     {\@font@info{Changing #2 sub-encoding to #1/#3}}%
     \@namedef{#1:#2}{#3}}
```

Any reason to allow those in the middle of documents?

```
\@onlypreamble\DeclareEncodingSubset
\@onlypreamble\DeclareEncodingSubset@aux
\@onlypreamble\@DeclareEncodingSubset
```

(*End definition for* `\DeclareEncodingSubset`.)

`\CheckEncodingSubset` The command `\CheckEncodingSubset` will check if the current font family has the right encoding subset to typeset a certain command. It takes five arguments as follows: first argument is either `\UseTextSymbol`, `\UseTextAccent` depending on whether or not the symbol is a text symbol or a text accent.

The second argument is the encoding from which this symbol should be fetched.

The third argument is either a fake accessor command or an error message. the code in that argument (if ever executed) receives two arguments: `#2` and `#5` of `\CheckEncodingSubset`.

Argument four is the subset encoding id to test against: if this value is higher than the subset id of the current font family then we typeset the symbol, i.e., execute `#1{#2}#5` otherwise it runs `#3#5`, e.g., to produce an error message or fake the glyph somehow.

Argument five is the symbol or accent command that is being checked.

For usage examples see definitions below.

```
\def\CheckEncodingSubset#1#2#3#4#5{%
    \ifnum #4>%
      \expandafter\ifx\csname #2:\f@family\endcsname\relax
        0\csname #2:?\endcsname
      \else
        \csname #2:\f@family\endcsname
      \fi
   \relax
   \expandafter\@firstoftwo
  \else
   \expandafter\@secondoftwo
 \fi
  {#1{#2}}{#3}%
  #5%
}
```

(*End definition for* `\CheckEncodingSubset`.)

To set up the glyphs for the subsets we need a number helpers.

`\tc@errorwarn` To we produce errors, warnings, or only info in the transcripts if glyphs require substitutions? By default it is "info" only. With the `textcomp` package that can be changed.

```
\def\tc@errorwarn#1#2{\@latex@info{#1}}
```

(*End definition for* `\tc@errorwarn`.)

`\tc@subst`

```
\def\tc@subst#1{%
   \tc@errorwarn
    {Symbol \string#1 not provided by\MessageBreak
     font family \f@family\space
     in TS1 encoding.\MessageBreak Default family used instead}\@eha
  \bgroup
      \expand@font@defaults
      \ifx\f@family\rmdef@ult
         \fontfamily\rmsubstdefault
      \else\ifx\f@family\sfdef@ult
         \fontfamily\sfsubstdefault
      \else\ifx\f@family\ttdef@ult
         \fontfamily\ttsubstdefault
      \else
         \fontfamily\textcompsubstdefault
      \fi\fi\fi
```

Whatever default was chosen, we claim now (locally hopefully) that it can handle all slots (even if not true) to avoid looping in certain situations, e.g., when something was set up incorrectly.

```
      \@namedef{TS1:\f@family}{0}%
      \selectfont#1%
  \egroup
}
```

(*End definition for* `\tc@subst`.)

`\tc@fake@euro` `\tc@fake@euro` is an example of a "fake" definition to use in arg `#3` of the command `\CheckEncodingSubset` when a symbol is not available in a certain font family. Here we produce a poor man's Euro symbol by combining a "C" with a "=".

```
\def\tc@fake@euro#1{%
   \leavevmode
   \@font@info{Faking \noexpand#1for font family
                          \f@family\MessageBreak in TS1 encoding}%
   \valign{##\cr
      \vfil\hbox to 0.07em{\dimen@\f@size\p@
                           \math@fontsfalse
                           \fontsize{.7\dimen@}\z@\selectfont=\hss}%
      \vfil\cr%
      \hbox{C}\crcr
   }%
}
```

(*End definition for* `\tc@fake@euro`.)

\tc@check@symbol
\tc@check@accent

These are two abbreviations that we use below to check symbols and accents in TS1. Only there to save some space, e.g., we can then write

```
DeclareTextCommandDefault{\textcurrency}{\tc@check@symbol3\textcurrency}
```

to ensure that \textcurrency is only typeset if the current font has a TS1 subset id of less than 3. Otherwise \tc@error is called telling the user that for this font family \textcurrency is not available.

```
\def\tc@check@symbol{\CheckEncodingSubset\UseTextSymbol{TS1}\tc@subst}
```

Accents have been made an error in the textcomp package when not available. Now that we provide the functionality in the kernel we avoid the error by swapping in a T1 accent if the TS1 accent is not available.

```
%\def\tc@check@accent{\CheckEncodingSubset\UseTextAccent{TS1}\tc@error}
\def\tc@check@accent#1{\CheckEncodingSubset\UseTextAccent
                                          {TS1}{\tc@swap@accent#1}}
\def\tc@swap@accent#1#2{\UseTextAccent{T1}#1}
```

(*End definition for* \tc@check@symbol *and* \tc@check@accent.)

1 Sub-encodings

Here are the default definitions for the TS1 symbols. First those that we assume are always available if a font implements TS1.

```
\DeclareTextSymbolDefault{\textdollar}{TS1}
\UndeclareTextCommand{\textdollar}{OT1}  % don't use the OT1 def any longer
\DeclareTextSymbolDefault{\textsterling}{TS1}
\UndeclareTextCommand{\textsterling}{OT1}% don't use the OT1 def any longer
\DeclareTextSymbolDefault{\textperthousand}{TS1}
\UndeclareTextCommand{\textperthousand}{T1} % don't use the T1 def
```

Using \UndeclareTextCommand above is enough only if the encoding definition files are not reloaded afterwards. In the past that happened if fontenc was used in the document preamble (not any longer). So in some sense it is better to fully remove them from the encoding files, but for rollbacks it is easier to keep them in for now.

These are the standard itemize and footnote symbols originally taken from OMS and now from TS1:

```
\DeclareTextSymbolDefault{\textasteriskcentered}{TS1}
\DeclareTextSymbolDefault{\textbullet}{TS1}
\DeclareTextSymbolDefault{\textdaggerdbl}{TS1}
\DeclareTextSymbolDefault{\textdagger}{TS1}
\DeclareTextSymbolDefault{\textparagraph}{TS1}
\DeclareTextSymbolDefault{\textperiodcentered}{TS1}
\DeclareTextSymbolDefault{\textsection}{TS1}
```

And here are the other TS1 glyphs that are implemented by every font (or nearly every—a few are commented out and moved to sub-encoding 9, because they aren't around in some fonts.

```
%%\DeclareTextSymbolDefault{\textbardbl}{TS1} % subst in sub-enc 9 above
\DeclareTextSymbolDefault{\textbrokenbar}{TS1}
%%\DeclareTextSymbolDefault{\textcelsius}{TS1} % subst in sub-enc 9 above
\DeclareTextSymbolDefault{\textcent}{TS1}
```

```
\DeclareTextSymbolDefault{\textcopyright}{TS1}
\DeclareTextSymbolDefault{\textdegree}{TS1}
\DeclareTextSymbolDefault{\textdiv}{TS1}
\DeclareTextSymbolDefault{\textlnot}{TS1}
\DeclareTextSymbolDefault{\textonehalf}{TS1}
\DeclareTextSymbolDefault{\textonequarter}{TS1}
%%\DeclareTextSymbolDefault{\textonesuperior}{TS1} % subst in sub-enc 9 above
\DeclareTextSymbolDefault{\textordfeminine}{TS1}
\DeclareTextSymbolDefault{\textordmasculine}{TS1}
\DeclareTextSymbolDefault{\textpm}{TS1}
\DeclareTextSymbolDefault{\textquotesingle}{TS1}
\DeclareTextSymbolDefault{\textquotestraightbase}{TS1}
\DeclareTextSymbolDefault{\textquotestraightdblbase}{TS1}
\DeclareTextSymbolDefault{\textregistered}{TS1}
%%\DeclareTextSymbolDefault{\textthreequartersemdash}{TS1} % subst in sub-enc 9 above
\DeclareTextSymbolDefault{\textthreequarters}{TS1}
%%\DeclareTextSymbolDefault{\textthreesuperior}{TS1} % subst in sub-enc 9 above
\DeclareTextSymbolDefault{\texttimes}{TS1}
\DeclareTextSymbolDefault{\texttrademark}{TS1}
%%\DeclareTextSymbolDefault{\texttwelveudash}{TS1} % subst in sub-enc 9 above
%%\DeclareTextSymbolDefault{\texttwosuperior}{TS1} % subst in sub-enc 9 above
\DeclareTextSymbolDefault{\textyen}{TS1}
```

```
\DeclareTextSymbolDefault{\textcapitalcompwordmark}{TS1}
\DeclareTextSymbolDefault{\textascendercompwordmark}{TS1}
```

In the following sections the remaining default definitions are ordered by sub-encoding in which they are become **unavailable**, i.e., they are not provided in the sub-encoding with that number and all sub-encodings with higher numbers.

Thus the symbols that are available in sub-encoding x are the symbols above (always available) and the symbols listed as becoming unavailable in sub-encodings $x + 1$ and higher.

1.1 Unavailable in sub-encoding 1 and higher (drop symbols not working in Latin Modern)

The `\textcircled` is available but the glyph is simply too small so we keep using the `OMS` glyph.

```
\DeclareTextCommandDefault{\textcircled}
  {\CheckEncodingSubset\UseTextAccent{TS1}{\UseTextAccent{OMS}}1\textcircled}
```

1.2 Unavailable in sub-encoding 2 (majority of new OTF fonts via autoinst) and higher

```
\DeclareTextCommandDefault{\t}
  {\CheckEncodingSubset\UseTextAccent{TS1}{\UseTextAccent{OML}}2\t}
```

Capital accents are really only very seldom implemented, so from sub-encoding 2 onwards we use the normal `T1` accents if they are asked for in the document.

In Unicode engines we don't implement them at all but always use the basic accents instead. whether that works or not really depends on the font, something like `\"X` usually comes out wrong in Unicode engines.

```
\ifx\Umathcode\@undefined
  \DeclareTextCommandDefault{\capitalacute}
```

```
                            {\tc@check@accent{\'}2\capitalacute}
  \DeclareTextCommandDefault{\capitalbreve}
                            {\tc@check@accent{\u}2\capitalbreve}
  \DeclareTextCommandDefault{\capitalcaron}
                            {\tc@check@accent{\v}2\capitalcaron}
  \DeclareTextCommandDefault{\capitalcedilla}
                            {\tc@check@accent{\c}2\capitalcedilla}
  \DeclareTextCommandDefault{\capitalcircumflex}
                            {\tc@check@accent{\^}2\capitalcircumflex}
  \DeclareTextCommandDefault{\capitaldieresis}
                            {\tc@check@accent{\"}2\capitaldieresis}
  \DeclareTextCommandDefault{\capitaldotaccent}
                            {\tc@check@accent{\.}2\capitaldotaccent}
  \DeclareTextCommandDefault{\capitalgrave}
                            {\tc@check@accent{\`}2\capitalgrave}
  \DeclareTextCommandDefault{\capitalhungarumlaut}
                            {\tc@check@accent{\H}2\capitalhungarumlaut}
  \DeclareTextCommandDefault{\capitalmacron}
                            {\tc@check@accent{\=}2\capitalmacron}
  \DeclareTextCommandDefault{\capitalogonek}
                            {\tc@check@accent{\k}2\capitalogonek}
  \DeclareTextCommandDefault{\capitalring}
                            {\tc@check@accent{\r}2\capitalring}
  \DeclareTextCommandDefault{\capitaltie}
                            {\tc@check@accent{\t}2\capitaltie}
  \DeclareTextCommandDefault{\capitaltilde}
                            {\tc@check@accent{\~}2\capitaltilde}
```

For `\newtie` and `\capitalnewtie` this is actually wrong, they should pick up the accent from the substitution font (not done yet).

```
  \DeclareTextCommandDefault{\newtie}
                            {\tc@check@accent{\t}2\newtie}
  \DeclareTextCommandDefault{\capitalnewtie}
                            {\tc@check@accent{\t}2\capitalnewtie}
```

In Unicode engines we just execute the simple accents:

```
\else
  \DeclareTextCommandDefault\capitalacute{\@tabacckludge'}
  \DeclareTextCommandDefault\capitalbreve{\u}
  \DeclareTextCommandDefault\capitalcaron{\v}
  \DeclareTextCommandDefault\capitalcedilla{\c}
  \DeclareTextCommandDefault\capitalcircumflex{\^}
  \DeclareTextCommandDefault\capitaldieresis{\"}
  \DeclareTextCommandDefault\capitaldotaccent{\.}
  \DeclareTextCommandDefault\capitalgrave{\@tabacckludge`}
  \DeclareTextCommandDefault\capitalhungarumlaut{\H}
  \DeclareTextCommandDefault\capitalmacron{\@tabacckludge=}
  \DeclareTextCommandDefault\capitalnewtie{\t}
  \DeclareTextCommandDefault\capitalogonek{\k}
  \DeclareTextCommandDefault\capitalring{\r}
  \DeclareTextCommandDefault\capitaltie{\t}
  \DeclareTextCommandDefault\capitaltilde{\~}
  \DeclareTextCommandDefault\newtie{\t}
\fi
```

The next two symbols exist in some fonts (faked?), but we ignore that to keep the subsets reasonable compact and most important linear.

```
\DeclareTextCommandDefault{\textlbrackdbl}
                          {\tc@check@symbol2\textlbrackdbl}
\DeclareTextCommandDefault{\textrbrackdbl}
                          {\tc@check@symbol2\textrbrackdbl}
```

Old style numerals are again in some fonts but using `-OsF`, etc. is the better approach to get them, so we claim they aren't in sub-encoding 2 as that's true for most fonts.

```
\DeclareTextCommandDefault{\texteightoldstyle}
                          {\tc@check@symbol2\texteightoldstyle}
\DeclareTextCommandDefault{\textfiveoldstyle}
                          {\tc@check@symbol2\textfiveoldstyle}
\DeclareTextCommandDefault{\textfouroldstyle}
                          {\tc@check@symbol2\textfouroldstyle}
\DeclareTextCommandDefault{\textnineoldstyle}
                          {\tc@check@symbol2\textnineoldstyle}
\DeclareTextCommandDefault{\textoneoldstyle}
                          {\tc@check@symbol2\textoneoldstyle}
\DeclareTextCommandDefault{\textsevenoldstyle}
                          {\tc@check@symbol2\textsevenoldstyle}
\DeclareTextCommandDefault{\textsixoldstyle}
                          {\tc@check@symbol2\textsixoldstyle}
\DeclareTextCommandDefault{\textthreeoldstyle}
                          {\tc@check@symbol2\textthreeoldstyle}
\DeclareTextCommandDefault{\texttwooldstyle}
                          {\tc@check@symbol2\texttwooldstyle}
\DeclareTextCommandDefault{\textzerooldstyle}
                          {\tc@check@symbol2\textzerooldstyle}
```

The next set of glyphs is special to TEX fonts (and available with a few older PS fonts supported through virtual fonts), but not any longer in the majority of fonts provided through autoinst, so we pretend there aren't available in sub-encoding 2 and below.

```
\DeclareTextCommandDefault{\textacutedbl}
                          {\tc@check@symbol2\textacutedbl}
\DeclareTextCommandDefault{\textasciiacute}
                          {\tc@check@symbol2\textasciiacute}
\DeclareTextCommandDefault{\textasciibreve}
                          {\tc@check@symbol2\textasciibreve}
\DeclareTextCommandDefault{\textasciicaron}
                          {\tc@check@symbol2\textasciicaron}
\DeclareTextCommandDefault{\textasciidieresis}
                          {\tc@check@symbol2\textasciidieresis}
\DeclareTextCommandDefault{\textasciigrave}
                          {\tc@check@symbol2\textasciigrave}
\DeclareTextCommandDefault{\textasciimacron}
                          {\tc@check@symbol2\textasciimacron}
\DeclareTextCommandDefault{\textgravedbl}
                          {\tc@check@symbol2\textgravedbl}
\DeclareTextCommandDefault{\texttildelow}
                          {\tc@check@symbol2\texttildelow}
```

Finally those below are only available in CM-based fonts but in no font that has its origin outside of the TEX world.

```
\DeclareTextCommandDefault{\textbaht}
                          {\tc@check@symbol2\textbaht}
```

```
\DeclareTextCommandDefault{\textbigcircle}
                          {\tc@check@symbol2\textbigcircle}
\DeclareTextCommandDefault{\textborn}
                          {\tc@check@symbol2\textborn}
\DeclareTextCommandDefault{\textcentoldstyle}
                          {\tc@check@symbol2\textcentoldstyle}
\DeclareTextCommandDefault{\textcircledP}
                          {\tc@check@symbol2\textcircledP}
\DeclareTextCommandDefault{\textcopyleft}
                          {\tc@check@symbol2\textcopyleft}
\DeclareTextCommandDefault{\textdblhyphenchar}
                          {\tc@check@symbol2\textdblhyphenchar}
\DeclareTextCommandDefault{\textdblhyphen}
                          {\tc@check@symbol2\textdblhyphen}
\DeclareTextCommandDefault{\textdied}
                          {\tc@check@symbol2\textdied}
\DeclareTextCommandDefault{\textdiscount}
                          {\tc@check@symbol2\textdiscount}
\DeclareTextCommandDefault{\textdivorced}
                          {\tc@check@symbol2\textdivorced}
\DeclareTextCommandDefault{\textdollaroldstyle}
                          {\tc@check@symbol2\textdollaroldstyle}
\DeclareTextCommandDefault{\textguarani}
                          {\tc@check@symbol2\textguarani}
\DeclareTextCommandDefault{\textleaf}
                          {\tc@check@symbol2\textleaf}
\DeclareTextCommandDefault{\textlquill}
                          {\tc@check@symbol2\textlquill}
\DeclareTextCommandDefault{\textmarried}
                          {\tc@check@symbol2\textmarried}
\DeclareTextCommandDefault{\textmho}
                          {\tc@check@symbol2\textmho}
\DeclareTextCommandDefault{\textmusicalnote}
                          {\tc@check@symbol2\textmusicalnote}
\DeclareTextCommandDefault{\textnaira}
                          {\tc@check@symbol2\textnaira}
\DeclareTextCommandDefault{\textopenbullet}
                          {\tc@check@symbol2\textopenbullet}
\DeclareTextCommandDefault{\textpeso}
                          {\tc@check@symbol2\textpeso}
\DeclareTextCommandDefault{\textpilcrow}
                          {\tc@check@symbol2\textpilcrow}
\DeclareTextCommandDefault{\textrecipe}
                          {\tc@check@symbol2\textrecipe}
\DeclareTextCommandDefault{\textreferencemark}
                          {\tc@check@symbol2\textreferencemark}
\DeclareTextCommandDefault{\textrquill}
                          {\tc@check@symbol2\textrquill}
\DeclareTextCommandDefault{\textservicemark}
                          {\tc@check@symbol2\textservicemark}
\DeclareTextCommandDefault{\textsurd}
                          {\tc@check@symbol2\textsurd}
```

The `\textpertenthousand` also belongs in this group but here we have a choice: in T1 there is a definition for `\textpertenthousand` making the symbol up from % and

`\char 24` (twice) but in many fonts that char doesn't exist and the slot is reused for random ligatures. So better not use it because often it is wrong. But pointing to TS1 is also not great as only a few fonts have it as a real symbol, so we get a substitution to CM or LM.

Alternatively we could just state that the symbol is unavailable in those fonts. For now I substitute.

```
\DeclareTextCommandDefault{\textpertenthousand}
                          {\tc@check@symbol2\textpertenthousand}
\UndeclareTextCommand{\textpertenthousand}{T1}
```

1.3 Unavailable in sub-encoding 3 and higher

Sub-encoding 2 is the one where we loose many symbols. In the higher-numbered sub-encodings we see only a few dropped additionally.

```
\DeclareTextCommandDefault{\textlangle}
                          {\tc@check@symbol3\textlangle}
\DeclareTextCommandDefault{\textrangle}
                          {\tc@check@symbol3\textrangle}
```

1.4 Unavailable in sub-encoding 4 and higher

```
\DeclareTextCommandDefault{\textcolonmonetary}
                          {\tc@check@symbol4\textcolonmonetary}
\DeclareTextCommandDefault{\textdong}
                          {\tc@check@symbol4\textdong}
\DeclareTextCommandDefault{\textdownarrow}
                          {\tc@check@symbol4\textdownarrow}
\DeclareTextCommandDefault{\textleftarrow}
                          {\tc@check@symbol4\textleftarrow}
\DeclareTextCommandDefault{\textlira}
                          {\tc@check@symbol4\textlira}
\DeclareTextCommandDefault{\textrightarrow}
                          {\tc@check@symbol4\textrightarrow}
\DeclareTextCommandDefault{\textuparrow}
                          {\tc@check@symbol4\textuparrow}
\DeclareTextCommandDefault{\textwon}
                          {\tc@check@symbol4\textwon}
```

1.5 Unavailable in sub-encoding 5 (most older PS fonts) and higher

Most older PS fonts (supported in TEX since the early nineties when virtual fonts became available) are sorted under this sub-encoding. But in reality, many of them don't have all glyphs that should be available in sub-encoding 5. Instead they show little squares, i.e., they produce "tofu" if you are unlucky.

But the coverage is so random that it is impossible to sort them properly and if we tried to ensure that they only typeset those glyphs that are really always available, we would have to put them all into sub-encoding 9; so putting them into 5 is really a compromise.

Modern fonts usually don't typeset a tofu character if a glyph is missing. They are therefore only classified as sub-encoding 5 if they really support its glyph set completely.

```
\DeclareTextCommandDefault{\textestimated}
                          {\tc@check@symbol5\textestimated}
```

```
\DeclareTextCommandDefault{\textnumero}
                          {\tc@check@symbol5\textnumero}
```

1.6 Unavailable in sub-encoding 6 and higher

```
\DeclareTextCommandDefault{\textflorin}
                          {\tc@check@symbol6\textflorin}
\DeclareTextCommandDefault{\textcurrency}
                          {\tc@check@symbol6\textcurrency}
```

1.7 Unavailable in sub-encoding 7 and higher

```
\DeclareTextCommandDefault{\textfractionsolidus}
                          {\tc@check@symbol7\textfractionsolidus}
\DeclareTextCommandDefault{\textohm}
                          {\tc@check@symbol7\textohm}
\DeclareTextCommandDefault{\textmu}
                          {\tc@check@symbol7\textmu}
\DeclareTextCommandDefault{\textminus}
                          {\tc@check@symbol7\textminus}
```

1.8 Unavailable in sub-encoding 8 and higher

```
\DeclareTextCommandDefault{\textblank}
                          {\tc@check@symbol{8}\textblank}
\DeclareTextCommandDefault{\textinterrobangdown}
                          {\tc@check@symbol{8}\textinterrobangdown}
\DeclareTextCommandDefault{\textinterrobang}
                          {\tc@check@symbol{8}\textinterrobang}
```

Fonts with this sub-encoding don't have a Euro symbol, but instead of substituting we fake it.

```
\DeclareTextCommandDefault{\texteuro}
  {\CheckEncodingSubset\UseTextSymbol{TS1}\tc@fake@euro{8}\texteuro}
```

1.9 Unavailable in Sub-encoding 9 (most missing)

```
\DeclareTextCommandDefault{\textcelsius}
                          {\tc@check@symbol{9}\textcelsius}
\DeclareTextCommandDefault{\textonesuperior}
                          {\tc@check@symbol{9}\textonesuperior}
\DeclareTextCommandDefault{\textthreequartersemdash}
                          {\tc@check@symbol{9}\textthreequartersemdash}
\DeclareTextCommandDefault{\textthreesuperior}
                          {\tc@check@symbol{9}\textthreesuperior}
\DeclareTextCommandDefault{\texttwelveudash}
                          {\tc@check@symbol{9}\texttwelveudash}
\DeclareTextCommandDefault{\texttwosuperior}
                          {\tc@check@symbol{9}\texttwosuperior}
\DeclareTextCommandDefault{\textbardbl}
                          {\tc@check@symbol{9}\textbardbl}
```

2 Unicode engine specials

If we are using a unicode engine we handle some glyphs differently, so this here are the definitions for the Unicode encoding (overwriting the defaults above).

```
\ifx \Umathcode\@undefined  \else
```

This set should be taken from TS1 encoding even if it means you get it from the default font for that encoding.

```
%\DeclareTextSymbol{\textcopyleft}{TS1}{171}
%\DeclareTextSymbol{\textdblhyphen}{TS1}{45}
%\DeclareTextSymbol{\textdblhyphenchar}{TS1}{127}
%\DeclareTextSymbol{\textquotestraightbase}{TS1}{13}
%\DeclareTextSymbol{\textquotestraightdblbase}{TS1}{18}
%\DeclareTextSymbol{\textleaf}{TS1}{108}
%\DeclareTextSymbol{\texttwelveudash}{TS1}{21}
%\DeclareTextSymbol{\textthreequartersemdash}{TS1}{22}
```

If oldstyle numerals are asked for we just use \oldstylenums.

```
\DeclareTextCommand{\textzerooldstyle} \UnicodeEncodingName{\oldstylenums{0}}
\DeclareTextCommand{\textoneoldstyle}  \UnicodeEncodingName{\oldstylenums{1}}
\DeclareTextCommand{\texttwooldstyle}  \UnicodeEncodingName{\oldstylenums{2}}
\DeclareTextCommand{\textthreeoldstyle}\UnicodeEncodingName{\oldstylenums{3}}
\DeclareTextCommand{\textfouroldstyle} \UnicodeEncodingName{\oldstylenums{4}}
\DeclareTextCommand{\textfiveoldstyle} \UnicodeEncodingName{\oldstylenums{5}}
\DeclareTextCommand{\textsixoldstyle}  \UnicodeEncodingName{\oldstylenums{6}}
\DeclareTextCommand{\textsevenoldstyle}\UnicodeEncodingName{\oldstylenums{7}}
\DeclareTextCommand{\texteightoldstyle}\UnicodeEncodingName{\oldstylenums{8}}
\DeclareTextCommand{\textnineoldstyle} \UnicodeEncodingName{\oldstylenums{9}}
```

These have Unicode slots so this should be integrated into TU explicitly

```
\DeclareTextSymbol{\textpilcrow}        \UnicodeEncodingName{"00B6}
\DeclareTextSymbol{\textborn}           \UnicodeEncodingName{"002A}
\DeclareTextSymbol{\textdied}           \UnicodeEncodingName{"2020}
\DeclareTextSymbol{\textlbrackdbl}      \UnicodeEncodingName{"27E6}
\DeclareTextSymbol{\textrbrackdbl}      \UnicodeEncodingName{"27E7}
\DeclareTextSymbol{\textguarani}        \UnicodeEncodingName{"20B2}
```

We could make \textcentoldstyle and \textdollaroldstyle point to dollar and cent in the Unicode encoding

```
%\DeclareTextSymbol{\textcentoldstyle}  \UnicodeEncodingName{"00A2}
%\DeclareTextSymbol{\textdollaroldstyle}\UnicodeEncodingName{"0024}
```

but I think it is better to pick them up from TS1 even if that usually means LMR fonts

```
\DeclareTextSymbol{\textdollaroldstyle}{TS1}{138}
\DeclareTextSymbol{\textcentoldstyle}  {TS1}{139}
```

```
\fi               % --- END of Unicode engines specials
```

3 Font family sub-encodings setup

We declare the subsets for a good number of fonts in the kernel ...

But first the default for anything that is not declared. We use 9 which is most likely much too conservative, but with the advantage that we aren't getting missing glyphs (or at least that this is very unlikely). For nearly all font in the TEX Live distribution of 2019 "correct" classifications are given below, so that this default is only used for new font families, and over time the right classifications can be added here too.

```
\DeclareEncodingSubset{TS1}{?}{9}
```

This first block contains the fonts that have been already supported by the `textcomp` package way back, i.e., the font families that have TEX support since the mid-nineties.

```
\DeclareEncodingSubset{TS1}{ccr}     {0}
\DeclareEncodingSubset{TS1}{cmbr}    {0}
\DeclareEncodingSubset{TS1}{cmr}     {0}
\DeclareEncodingSubset{TS1}{cmss}    {0}
\DeclareEncodingSubset{TS1}{cmtl}    {0}
\DeclareEncodingSubset{TS1}{cmtt}    {0}
\DeclareEncodingSubset{TS1}{cmvtt}   {0}
\DeclareEncodingSubset{TS1}{pxr}     {0}
\DeclareEncodingSubset{TS1}{pxss}    {0}
\DeclareEncodingSubset{TS1}{pxtt}    {0}
\DeclareEncodingSubset{TS1}{qag}     {0}
\DeclareEncodingSubset{TS1}{qbk}     {0}
\DeclareEncodingSubset{TS1}{qcr}     {0}
\DeclareEncodingSubset{TS1}{qcs}     {0}
\DeclareEncodingSubset{TS1}{qhvc}    {0}
\DeclareEncodingSubset{TS1}{qhv}     {0}
\DeclareEncodingSubset{TS1}{qpl}     {0}
\DeclareEncodingSubset{TS1}{qtm}     {0}
\DeclareEncodingSubset{TS1}{qzc}     {0}
\DeclareEncodingSubset{TS1}{txr}     {0}
\DeclareEncodingSubset{TS1}{txss}    {0}
\DeclareEncodingSubset{TS1}{txtt}    {0}

\DeclareEncodingSubset{TS1}{lmr}     {1}
\DeclareEncodingSubset{TS1}{lmdh}    {1}
\DeclareEncodingSubset{TS1}{lmss}    {1}
\DeclareEncodingSubset{TS1}{lmssq}   {1}
\DeclareEncodingSubset{TS1}{lmvtt}   {1}
\DeclareEncodingSubset{TS1}{lmtt}    {1} % missing TM, SM and
                                         % pertenthousand for some reason

\DeclareEncodingSubset{TS1}{ptmx}    {2}
\DeclareEncodingSubset{TS1}{ptmj}    {2}
\DeclareEncodingSubset{TS1}{ul8}     {2}

\DeclareEncodingSubset{TS1}{bch} {5} % tofu for blank, ohm
\DeclareEncodingSubset{TS1}{futj}{5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{futs}{5} % tofu for blank, ohm
\DeclareEncodingSubset{TS1}{futx}{5} % probably (currently broken distrib)
\DeclareEncodingSubset{TS1}{pag} {5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{pbk} {5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{pcr} {5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{phv} {5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{pnc} {5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{pplj}{5} % tofu for blank
\DeclareEncodingSubset{TS1}{pplx}{5} % tofu for blank
\DeclareEncodingSubset{TS1}{ppl} {5} % tofu for blank interrobang/down
\DeclareEncodingSubset{TS1}{ptm} {5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{pzc} {5} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{ul9} {5} % tofu for blank, interrobang/down, ohm

\DeclareEncodingSubset{TS1}{dayroms}{6} % tofu for blank, interrobang/down, ohm
\DeclareEncodingSubset{TS1}{dayrom} {6} % tofu for blank, interrobang/down, ohm

\DeclareEncodingSubset{TS1}{augie}{8} % really only missing euro
```

```
\DeclareEncodingSubset{TS1}{put}  {8}
\DeclareEncodingSubset{TS1}{uag}  {8} % probably (currently broken distrib)
\DeclareEncodingSubset{TS1}{ugq}  {8}

\DeclareEncodingSubset{TS1}{zi4}     {9}
```

LucidaBright (sold through TUG) probably not quite correct, I guess as I have the older fonts ...

```
\DeclareEncodingSubset{TS1}{hls}     {5}
\DeclareEncodingSubset{TS1}{hlst}    {5}
\DeclareEncodingSubset{TS1}{hlct}    {5}
\DeclareEncodingSubset{TS1}{hlh}     {5}
\DeclareEncodingSubset{TS1}{hlx}     {8}
\DeclareEncodingSubset{TS1}{hlce}    {8}
\DeclareEncodingSubset{TS1}{hlcn}    {8}
\DeclareEncodingSubset{TS1}{hlcw}    {8}
\DeclareEncodingSubset{TS1}{hlcf}    {8}
```

Below are the newer fonts that have support files for LaTeX. With very few exceptions the classifications are done so that all characters are correctly produced (either being available in the font or substituted.

There are a few fonts that contain "tofu" squares in places (instead of a real glyph) and in a few cases some really seldom needed chars are unavailable, i.e., produce missing glyphs (to avoid that a large number of available chars are unnecessarily substituted.

```
\DeclareEncodingSubset{TS1}{lato-*}       {0}  % with a bunch of tofu inside
\DeclareEncodingSubset{TS1}{opensans-*}   {0}  % with a bunch of tofu inside
\DeclareEncodingSubset{TS1}{cantarell-*}  {0}  % with a bunch of tofu inside
\DeclareEncodingSubset{TS1}{fbb-*}        {0}  % missing centoldstyle

\DeclareEncodingSubset{TS1}{tli}          {1}  % with lots of tofu inside

\DeclareEncodingSubset{TS1}{Alegreya-*}               {2}
\DeclareEncodingSubset{TS1}{AlegreyaSans-*}           {2}
\DeclareEncodingSubset{TS1}{DejaVuSans-TLF}           {2}
\DeclareEncodingSubset{TS1}{DejaVuSansCondensed-TLF}  {2}
\DeclareEncodingSubset{TS1}{DejaVuSansMono-TLF}       {2}
\DeclareEncodingSubset{TS1}{EBGaramond-*}             {2}
\DeclareEncodingSubset{TS1}{Tempora-TLF}              {2}
\DeclareEncodingSubset{TS1}{Tempora-TOsF}             {2}

\DeclareEncodingSubset{TS1}{Arimo-TLF}                {3}
\DeclareEncodingSubset{TS1}{Carlito-*}                {3}
\DeclareEncodingSubset{TS1}{FiraSans-*}               {3}
\DeclareEncodingSubset{TS1}{IBMPlexSans-TLF}          {3}
\DeclareEncodingSubset{TS1}{Merriweather-OsF}         {3}
\DeclareEncodingSubset{TS1}{Montserrat-*}             {3}
\DeclareEncodingSubset{TS1}{MontserratAlternates-*}   {3}
\DeclareEncodingSubset{TS1}{SourceCodePro-TLF}        {3}
\DeclareEncodingSubset{TS1}{SourceCodePro-TOsF}       {3}
\DeclareEncodingSubset{TS1}{SourceSansPro-*}          {3}
\DeclareEncodingSubset{TS1}{SourceSerifPro-*}         {3}
\DeclareEncodingSubset{TS1}{Tinos-TLF}                {3}

\DeclareEncodingSubset{TS1}{AccanthisADFStdNoThree-LF}{4}
\DeclareEncodingSubset{TS1}{Cabin-TLF}                {4}
\DeclareEncodingSubset{TS1}{Caladea-TLF}              {4}
\DeclareEncodingSubset{TS1}{Chivo-*}                  {4}
```

```
\DeclareEncodingSubset{TS1}{ClearSans-TLF}            {4}
\DeclareEncodingSubset{TS1}{Coelacanth-LF}            {4}
\DeclareEncodingSubset{TS1}{CrimsonPro-*}             {4}
\DeclareEncodingSubset{TS1}{FiraMono-TLF}             {4}
\DeclareEncodingSubset{TS1}{FiraMono-TOsF}            {4}
\DeclareEncodingSubset{TS1}{Go-TLF}                   {4}
\DeclareEncodingSubset{TS1}{GoMono-TLF}               {4}
\DeclareEncodingSubset{TS1}{InriaSans-*}              {4}
\DeclareEncodingSubset{TS1}{InriaSerif-*}             {4}
\DeclareEncodingSubset{TS1}{LibertinusSans-*}         {4}
\DeclareEncodingSubset{TS1}{LibertinusSerif-*}        {4}
\DeclareEncodingSubset{TS1}{LibreBodoni-TLF}          {4}
\DeclareEncodingSubset{TS1}{LibreFranklin-TLF}        {4}
\DeclareEncodingSubset{TS1}{LinguisticsPro-LF}        {4}
\DeclareEncodingSubset{TS1}{LinguisticsPro-OsF}       {4}
\DeclareEncodingSubset{TS1}{LinuxBiolinumT-*}         {4}
\DeclareEncodingSubset{TS1}{LinuxLibertineT-*}        {4}
\DeclareEncodingSubset{TS1}{MerriweatherSans-OsF}     {4}
\DeclareEncodingSubset{TS1}{MintSpirit-*}             {4}
\DeclareEncodingSubset{TS1}{MintSpiritNoTwo-*}        {4}
\DeclareEncodingSubset{TS1}{PTMono-TLF}               {4}
\DeclareEncodingSubset{TS1}{PTSans-TLF}               {4}
\DeclareEncodingSubset{TS1}{PTSansCaption-TLF}        {4}
\DeclareEncodingSubset{TS1}{PTSansNarrow-TLF}         {4}
\DeclareEncodingSubset{TS1}{PTSerif-TLF}              {4}
\DeclareEncodingSubset{TS1}{PTSerifCaption-TLF}       {4}
\DeclareEncodingSubset{TS1}{Raleway-TLF}              {4}
\DeclareEncodingSubset{TS1}{Raleway-TOsF}             {4}
\DeclareEncodingSubset{TS1}{Roboto-*}                 {4}
\DeclareEncodingSubset{TS1}{RobotoMono-TLF}           {4}
\DeclareEncodingSubset{TS1}{RobotoSlab-TLF}           {4}
\DeclareEncodingSubset{TS1}{Rosario-*}                {4}
\DeclareEncodingSubset{TS1}{SticksTooText-*}          {4}
\DeclareEncodingSubset{TS1}{UniversalisADFStd-LF}     {4}

\DeclareEncodingSubset{TS1}{Almendra-OsF}             {5}
\DeclareEncodingSubset{TS1}{Baskervaldx-*}            {5}
\DeclareEncodingSubset{TS1}{BaskervilleF-*}           {5}
\DeclareEncodingSubset{TS1}{Bitter-TLF}               {5}
\DeclareEncodingSubset{TS1}{Cinzel-LF}                {5}
\DeclareEncodingSubset{TS1}{CinzelDecorative-LF}      {5}
\DeclareEncodingSubset{TS1}{DejaVuSerif-TLF}          {5}
\DeclareEncodingSubset{TS1}{DejaVuSerifCondensed-TLF} {5}
\DeclareEncodingSubset{TS1}{GilliusADF-LF}            {5}
\DeclareEncodingSubset{TS1}{GilliusADFCond-LF}        {5}
\DeclareEncodingSubset{TS1}{GilliusADFNoTwo-LF}       {5}
\DeclareEncodingSubset{TS1}{GilliusADFNoTwoCond-LF}   {5}
\DeclareEncodingSubset{TS1}{LobsterTwo-LF}            {5}
\DeclareEncodingSubset{TS1}{OldStandard-TLF}          {5}
\DeclareEncodingSubset{TS1}{PlayfairDisplay-TLF}      {5}
\DeclareEncodingSubset{TS1}{PlayfairDisplay-TOsF}     {5}
\DeclareEncodingSubset{TS1}{TheanoDidot-TLF}          {5}
\DeclareEncodingSubset{TS1}{TheanoDidot-TOsF}         {5}
\DeclareEncodingSubset{TS1}{TheanoModern-TLF}         {5}
\DeclareEncodingSubset{TS1}{TheanoModern-TOsF}        {5}
```

```
\DeclareEncodingSubset{TS1}{TheanoOldStyle-TLF}       {5}
\DeclareEncodingSubset{TS1}{TheanoOldStyle-TOsF}      {5}

\DeclareEncodingSubset{TS1}{Crimson-TLF}              {6}
\DeclareEncodingSubset{TS1}{IBMPlexMono-TLF}          {6}
\DeclareEncodingSubset{TS1}{IBMPlexSerif-TLF}         {6}
\DeclareEncodingSubset{TS1}{LibertinusMono-TLF}       {6}
\DeclareEncodingSubset{TS1}{LibertinusSerifDisplay-LF}{6}
\DeclareEncodingSubset{TS1}{LinuxLibertineDisplayT-*} {6}
\DeclareEncodingSubset{TS1}{LinuxLibertineMonoT-LF}   {6}
\DeclareEncodingSubset{TS1}{LinuxLibertineMonoT-TLF}  {6}
\DeclareEncodingSubset{TS1}{Overlock-LF}              {6}

\DeclareEncodingSubset{TS1}{CormorantGaramond-*}      {7}
\DeclareEncodingSubset{TS1}{Heuristica-TLF}           {7}
\DeclareEncodingSubset{TS1}{Heuristica-TOsF}          {7}
\DeclareEncodingSubset{TS1}{IMFELLEnglish-TLF}        {7}
\DeclareEncodingSubset{TS1}{LibreBaskerville-TLF}     {7}
\DeclareEncodingSubset{TS1}{LibreCaslon-*}            {7}
\DeclareEncodingSubset{TS1}{Marcellus-LF}             {7}
\DeclareEncodingSubset{TS1}{NotoSans-*}               {7}
\DeclareEncodingSubset{TS1}{NotoSansMono-TLF}         {7}
\DeclareEncodingSubset{TS1}{NotoSansMono-TOsF}        {7}
\DeclareEncodingSubset{TS1}{NotoSerif-*}              {7}
\DeclareEncodingSubset{TS1}{Quattrocento-TLF}         {7}
\DeclareEncodingSubset{TS1}{QuattrocentoSans-TLF}     {7}
\DeclareEncodingSubset{TS1}{XCharter-TLF}             {7}
\DeclareEncodingSubset{TS1}{XCharter-TOsF}            {7}
\DeclareEncodingSubset{TS1}{erewhon-*}                {7}
\DeclareEncodingSubset{TS1}{ComicNeue-TLF}            {7}
\DeclareEncodingSubset{TS1}{ComicNeueAngular-TLF}     {7}
\DeclareEncodingSubset{TS1}{Forum-LF}      {7}  % the superiors are missing

\DeclareEncodingSubset{TS1}{Cochineal-*}              {8}

\DeclareEncodingSubset{TS1}{AlgolRevived-TLF}         {9}
```

4 Legacy symbol support for lists and footnote symbols

\UseLegacyTextSymbols

```
\def\UseLegacyTextSymbols{%
  \DeclareTextSymbolDefault{\textasteriskcentered}{OMS}%
  \DeclareTextSymbolDefault{\textbardbl}{OMS}%
  \DeclareTextSymbolDefault{\textbullet}{OMS}%
  \DeclareTextSymbolDefault{\textdaggerdbl}{OMS}%
  \DeclareTextSymbolDefault{\textdagger}{OMS}%
  \DeclareTextSymbolDefault{\textparagraph}{OMS}%
  \DeclareTextSymbolDefault{\textperiodcentered}{OMS}%
  \DeclareTextSymbolDefault{\textsection}{OMS}%
  \UndeclareTextCommand{\textsection}{T1}%
  \expandafter\let\csname oldstylenums \expandafter\endcsname
                  \csname legacyoldstylenums \endcsname
}
```

(*End definition for* `\UseLegacyTextSymbols`.)

`\textlegacyasteriskcentered`
`\textlegacybardbl`
`\textlegacybullet`
`\textlegacydaggerdbl`
`\textlegacydagger`
`\textlegacyparagraph`
`\textlegacyperiodcentered`
`\textlegacysection`

Here are new names for the legacy symbols that LaTeX used to pick up from the `OMS` encoded fonts (and used for itemize lists or footnote symbols.

We go the roundabout way via separate OMS declarations so that

```
\renewcommand\textbullet{\textlegacybullet}
```

doesn't produce an endless loop.

```
\DeclareTextSymbol{\textlegacyasteriskcentered}{OMS}{3}   % "03
\DeclareTextSymbol{\textlegacybardbl}{OMS}{107}           % "6B
\DeclareTextSymbol{\textlegacybullet}{OMS}{15}            % "0F
\DeclareTextSymbol{\textlegacydaggerdbl}{OMS}{122}        % "7A
\DeclareTextSymbol{\textlegacydagger}{OMS}{121}           % "79
\DeclareTextSymbol{\textlegacyparagraph}{OMS}{123}        % "7B
\DeclareTextSymbol{\textlegacyperiodcentered}{OMS}{1}     % "01
\DeclareTextSymbol{\textlegacysection}{OMS}{120}          % "78
```

```
\DeclareTextSymbolDefault{\textlegacyasteriskcentered}{OMS}
\DeclareTextSymbolDefault{\textlegacybardbl}{OMS}
\DeclareTextSymbolDefault{\textlegacybullet}{OMS}
\DeclareTextSymbolDefault{\textlegacydaggerdbl}{OMS}
\DeclareTextSymbolDefault{\textlegacydagger}{OMS}
\DeclareTextSymbolDefault{\textlegacyparagraph}{OMS}
\DeclareTextSymbolDefault{\textlegacyperiodcentered}{OMS}
\DeclareTextSymbolDefault{\textlegacysection}{OMS}
```

(*End definition for* `\textlegacyasteriskcentered` *and others.*)

Supporting rollback ...

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩     {lttextcomp}{Undefine text companion symbols}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\oldstylenums[1]{%
⟨latexrelease⟩   \begingroup
⟨latexrelease⟩    \spaceskip\fontdimen\tw@\font
⟨latexrelease⟩    \usefont{OML}{\rmdefault}{\f@series}{it}%
⟨latexrelease⟩    \mathgroup\symletters #1%
⟨latexrelease⟩   \endgroup
⟨latexrelease⟩}
⟨latexrelease⟩\let\legacyoldstylenums\@undefined
⟨latexrelease⟩\def\textcompsubstdefault{cmr}
⟨latexrelease⟩
⟨latexrelease⟩\let\DeclareEncodingSubset\@undefined
⟨latexrelease⟩\let\CheckEncodingSubset\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\DeclareTextSymbolDefault{\textdollar}{OT1}
⟨latexrelease⟩\DeclareTextSymbolDefault{\textsterling}{OT1}
⟨latexrelease⟩\DeclareTextCommand{\textdollar}{OT1}{\hmode@bgroup
⟨latexrelease⟩   \ifdim \fontdimen\@ne\font >\z@
⟨latexrelease⟩      \slshape
⟨latexrelease⟩   \else
⟨latexrelease⟩      \upshape
⟨latexrelease⟩   \fi
```

```
⟨latexrelease⟩   \char`\$\egroup}
⟨latexrelease⟩\DeclareTextCommand{\textsterling}{OT1}{\hmode@bgroup
⟨latexrelease⟩   \ifdim \fontdimen\@ne\font >\z@
⟨latexrelease⟩      \itshape
⟨latexrelease⟩   \else
⟨latexrelease⟩      \fontshape{ui}\selectfont
⟨latexrelease⟩   \fi
⟨latexrelease⟩   \char`\$\egroup}
⟨latexrelease⟩\DeclareTextCommand{\textperthousand}{T1}
⟨latexrelease⟩   {\%\char 24 }
⟨latexrelease⟩
⟨latexrelease⟩\DeclareTextSymbolDefault{\textasteriskcentered}{OMS}
⟨latexrelease⟩\DeclareTextSymbolDefault{\textbullet}{OMS}
⟨latexrelease⟩\DeclareTextSymbolDefault{\textdaggerdbl}{OMS}
⟨latexrelease⟩\DeclareTextSymbolDefault{\textdagger}{OMS}
⟨latexrelease⟩\DeclareTextSymbolDefault{\textparagraph}{OMS}
⟨latexrelease⟩\DeclareTextSymbolDefault{\textperiodcentered}{OMS}
⟨latexrelease⟩\DeclareTextSymbolDefault{\textsection}{OMS}
⟨latexrelease⟩
⟨latexrelease⟩\DeclareTextSymbolDefault{\textbardbl}{OMS}
⟨latexrelease⟩\let\textbrokenbar\@undefined
⟨latexrelease⟩\let\textcelsius\@undefined
⟨latexrelease⟩\let\textcent\@undefined
⟨latexrelease⟩\DeclareTextCommandDefault{\textcopyright}
⟨latexrelease⟩                          {\textcircled{c}}
⟨latexrelease⟩\let\textdegree\@undefined
⟨latexrelease⟩\let\textdiv\@undefined
⟨latexrelease⟩\let\textlnot\@undefined
⟨latexrelease⟩\let\textonehalf\@undefined
⟨latexrelease⟩\let\textonequarter\@undefined
⟨latexrelease⟩\let\textonesuperior\@undefined
⟨latexrelease⟩\DeclareTextCommandDefault{\textordfeminine}
⟨latexrelease⟩                          {\textsuperscript{a}}
⟨latexrelease⟩\DeclareTextCommandDefault{\textordmasculine}
⟨latexrelease⟩                          {\textsuperscript{o}}
⟨latexrelease⟩\let\textpm\@undefined
⟨latexrelease⟩\let\textquotesingle\@undefined
⟨latexrelease⟩\let\textquotestraightbase\@undefined
⟨latexrelease⟩\let\textquotestraightdblbase\@undefined
⟨latexrelease⟩\DeclareTextCommandDefault{\textregistered}
⟨latexrelease⟩    {\textcircled{%
⟨latexrelease⟩        \check@mathfonts\fontsize\sf@size\z@
⟨latexrelease⟩        \math@fontsfalse\selectfont R}}
⟨latexrelease⟩\let\textthreequartersemdash\@undefined
⟨latexrelease⟩\let\textthreequarters\@undefined
⟨latexrelease⟩\let\textthreesuperior\@undefined
⟨latexrelease⟩\let\texttimes\@undefined
⟨latexrelease⟩\DeclareTextCommandDefault{\texttrademark}
⟨latexrelease⟩                          {\textsuperscript{TM}}
⟨latexrelease⟩\let\texttwelveudash\@undefined
⟨latexrelease⟩\let\texttwosuperior\@undefined
⟨latexrelease⟩\let\textyen\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textcapitalcompwordmark\@undefined
```

```
⟨latexrelease⟩\let\textascendercompwordmark\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\DeclareTextAccentDefault{\textcircled}{OMS}
⟨latexrelease⟩\DeclareTextAccentDefault{\t}{OML}
⟨latexrelease⟩
⟨latexrelease⟩\let\capitalacute\@undefined
⟨latexrelease⟩\let\capitalbreve\@undefined
⟨latexrelease⟩\let\capitalcaron\@undefined
⟨latexrelease⟩\let\capitalcedilla\@undefined
⟨latexrelease⟩\let\capitalcircumflex\@undefined
⟨latexrelease⟩\let\capitaldieresis\@undefined
⟨latexrelease⟩\let\capitaldotaccent\@undefined
⟨latexrelease⟩\let\capitalgrave\@undefined
⟨latexrelease⟩\let\capitalhungarumlaut\@undefined
⟨latexrelease⟩\let\capitalmacron\@undefined
⟨latexrelease⟩\let\capitalnewtie\@undefined
⟨latexrelease⟩\let\capitalogonek\@undefined
⟨latexrelease⟩\let\capitalring\@undefined
⟨latexrelease⟩\let\capitaltie\@undefined
⟨latexrelease⟩\let\capitaltilde\@undefined
⟨latexrelease⟩\let\newtie\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textlbrackdbl\@undefined
⟨latexrelease⟩\let\textrbrackdbl\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\texteightoldstyle\@undefined
⟨latexrelease⟩\let\textfiveoldstyle\@undefined
⟨latexrelease⟩\let\textfouroldstyle\@undefined
⟨latexrelease⟩\let\textnineoldstyle\@undefined
⟨latexrelease⟩\let\textoneoldstyle\@undefined
⟨latexrelease⟩\let\textsevenoldstyle\@undefined
⟨latexrelease⟩\let\textsixoldstyle\@undefined
⟨latexrelease⟩\let\textthreeoldstyle\@undefined
⟨latexrelease⟩\let\texttwooldstyle\@undefined
⟨latexrelease⟩\let\textzerooldstyle\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textacutedbl\@undefined
⟨latexrelease⟩\let\textasciiacute\@undefined
⟨latexrelease⟩\let\textasciibreve\@undefined
⟨latexrelease⟩\let\textasciicaron\@undefined
⟨latexrelease⟩\let\textasciidieresis\@undefined
⟨latexrelease⟩\let\textasciigrave\@undefined
⟨latexrelease⟩\let\textasciimacron\@undefined
⟨latexrelease⟩\let\textgravedbl\@undefined
⟨latexrelease⟩\let\texttildelow\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textbaht\@undefined
⟨latexrelease⟩\let\textbigcircle\@undefined
⟨latexrelease⟩\let\textborn\@undefined
⟨latexrelease⟩\let\textcentoldstyle\@undefined
⟨latexrelease⟩\let\textcircledP\@undefined
⟨latexrelease⟩\let\textcopyleft\@undefined
⟨latexrelease⟩\let\textdblhyphenchar\@undefined
⟨latexrelease⟩\let\textdblhyphen\@undefined
```

```
⟨latexrelease⟩\let\textdied\@undefined
⟨latexrelease⟩\let\textdiscount\@undefined
⟨latexrelease⟩\let\textdivorced\@undefined
⟨latexrelease⟩\let\textdollaroldstyle\@undefined
⟨latexrelease⟩\let\textguarani\@undefined
⟨latexrelease⟩\let\textleaf\@undefined
⟨latexrelease⟩\let\textlquill\@undefined
⟨latexrelease⟩\let\textmarried\@undefined
⟨latexrelease⟩\let\textmho\@undefined
⟨latexrelease⟩\let\textmusicalnote\@undefined
⟨latexrelease⟩\let\textnaira\@undefined
⟨latexrelease⟩\let\textopenbullet\@undefined
⟨latexrelease⟩\let\textpeso\@undefined
⟨latexrelease⟩\let\textpilcrow\@undefined
⟨latexrelease⟩\let\textrecipe\@undefined
⟨latexrelease⟩\let\textreferencemark\@undefined
⟨latexrelease⟩\let\textrquill\@undefined
⟨latexrelease⟩\let\textservicemark\@undefined
⟨latexrelease⟩\let\textsurd\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\DeclareTextCommand{\textpertenthousand}{T1}
⟨latexrelease⟩                   {\%\char 24\char 24 }
⟨latexrelease⟩
⟨latexrelease⟩\let\textlangle\@undefined
⟨latexrelease⟩\let\textrangle\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textcolonmonetary\@undefined
⟨latexrelease⟩\let\textdong\@undefined
⟨latexrelease⟩\let\textdownarrow\@undefined
⟨latexrelease⟩\let\textleftarrow\@undefined
⟨latexrelease⟩\let\textlira\@undefined
⟨latexrelease⟩\let\textrightarrow\@undefined
⟨latexrelease⟩\let\textuparrow\@undefined
⟨latexrelease⟩\let\textwon\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textestimated\@undefined
⟨latexrelease⟩\let\textnumero\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textflorin\@undefined
⟨latexrelease⟩\let\textcurrency\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textfractionsolidus\@undefined
⟨latexrelease⟩\let\textohm\@undefined
⟨latexrelease⟩\let\textmu\@undefined
⟨latexrelease⟩\let\textminus\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textblank\@undefined
⟨latexrelease⟩\let\textinterrobangdown\@undefined
⟨latexrelease⟩\let\textinterrobang\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\texteuro\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\textcelsius\@undefined
⟨latexrelease⟩\let\textonesuperior\@undefined
```

```
⟨latexrelease⟩\let\textthreequartersemdash\@undefined
⟨latexrelease⟩\let\textthreesuperior\@undefined
⟨latexrelease⟩\let\texttwelveudash\@undefined
⟨latexrelease⟩\let\texttwosuperior\@undefined
⟨latexrelease⟩\let\textbardbl\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let\UseLegacyTextSymbols\@undefined
⟨latexrelease⟩\let\textlegacyasteriskcentered\@undefined
⟨latexrelease⟩\let\textlegacybardbl\@undefined
⟨latexrelease⟩\let\textlegacybullet\@undefined
⟨latexrelease⟩\let\textlegacydaggerdbl\@undefined
⟨latexrelease⟩\let\textlegacydagger\@undefined
⟨latexrelease⟩\let\textlegacyparagraph\@undefined
⟨latexrelease⟩\let\textlegacyperiodcentered\@undefined
⟨latexrelease⟩\let\textlegacysection\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndModuleRelease
```

5 The textcomp package

```
⟨*TS1sty⟩
\providecommand\DeclareRelease[3]{}
\providecommand\DeclareCurrentRelease[2]{}

\DeclareRelease{}{2018-08-11}{textcomp-2018-08-11.sty}
\DeclareCurrentRelease{}{2020-02-02}

\ProvidesPackage{textcomp}
 [2020/02/02 v2.0n Standard LaTeX package]
```

A precaution in case this is used without rebuilding the format.

```
\NeedsTeXFormat{LaTeX2e}[2020/02/02]
```

This is implemented by defining the default subset:

```
\DeclareOption{full}{\DeclareEncodingSubset{TS1}{?}{0}}
\DeclareOption{almostfull}{\DeclareEncodingSubset{TS1}{?}{1}}
\DeclareOption{euro}{\DeclareEncodingSubset{TS1}{?}{8}}
\DeclareOption{safe}{\DeclareEncodingSubset{TS1}{?}{9}}
```

The default is set up in the kernel is “safe” these days for unknown fonts but LaTeX has definitions for most families so it seldom applies.

If a different default is used then one needs to check the results to ensure that there aren’t “missing glyphs”.

The next set of options define the warning level (default in the kernel is info only). Using the package options you can change this behavior.

```
\DeclareOption{error}
              {\gdef\tc@errorwarn{\PackageError{textcomp}}}
\DeclareOption{warn}
              {\gdef\tc@errorwarn#1#2{\PackageWarning{textcomp}{#1}}}
\DeclareOption{info}
              {\gdef\tc@errorwarn#1#2{\PackageInfo{textcomp}{#1}}}
\DeclareOption{quiet}{\gdef\tc@errorwarn#1#2{}}
```

The “force” option basically changes the sub-encoding to that of the default (which, unless changes, is 9 these days), i.e., it no longer depends on the font in use. This is

mainly there because it might have been used in older documents, but not something that is recommended.

```
\DeclareOption{force}{%
    \def\CheckEncodingSubset#1#2#3#4#5{%
      \ifnum #4>%
           0\csname #2:?\endcsname
           \relax
      \expandafter\@firstoftwo
     \else
      \expandafter\@secondoftwo
    \fi
     {#1{#2}}{#3}%
     #5}%
}
\ExecuteOptions{info}
\ProcessOptions\relax
```

There is not much else to do nowadays, because everything is already set up in the LaTeX kernel.

```
\InputIfFileExists{textcomp.cfg}
  {\PackageInfo{textcomp}{Local configuration file used}}{}
```

⟨/TS1sty⟩

5.1 The old textcomp package code

This section contains the old code for the textcomp package and its documentation. It is only used if we roll back prior to 2020. Thus all the rest is mainly for historians. Note that the old code categorized in the sub-encodings only into 6 classes not 10.

```
⟨*TS1oldsty⟩
\ProvidesPackage{textcomp}
   [2018/08/11 v2.0j Standard LaTeX package]
```

This one is for the `TS1` encoding which contains text symbols for use with the `T1`-encoded text fonts. It therefore first inputs the file `TS1enc.def` and then sets (or resets) the defaults for the symbols it contains. The result of this is that when one of these symbols is accessed and the current encoding does not provide it, the symbol will be supplied by a silent, local change to this encoding.

Since many PostScript fonts only implement a subset of `TS1` many commands only produce black blobs of ink. To resolve the resulting problems a number of options have been introduced and some code has been developed to distinguish sub-encodings.

The sub-encodings have a numerical id and are defined as follows for `TS1`:

#5 those `TS1` symbols that are also in the ISO-Adobe character set; without `textcurrency`, which is often misused for the Euro. Older Type1 fonts from the non-TeX world provide only this subset.

#4 = #5 + `\texteuro`. Most newer fonts provide this.

#3 = #4 + `\textomega`. Can also be described as `TS1` ∩ (`ISO-Adobe` ∪ `MacRoman`). (Except for the missing "currency".)

#2 = #3 + `\textestimated` + `\textcurrency`. Can also be described as `TS1` ∩ `Adobe-Western-2`. This may be relevant for OpenType fonts, which usually show the Adobe-Western-2 character set.

#1 = TS1 without \textcircled and \t. These two glyphs are often not implemented and if their kernel defaults are changed commands like \copyright unnecessarily fail.

#0 = full TS1

And here a summary to go in the transcript file:

```
\PackageInfo{textcomp}{Sub-encoding information:\MessageBreak
   \space\space 5 = only ISO-Adobe without
                              \string\textcurrency\MessageBreak
   \space\space 4 = 5 + \string\texteuro\MessageBreak
   \space\space 3 = 4 + \string\textohm\MessageBreak
   \space\space 2 = 3 + \noexpand\textestimated+
                                \string\textcurrency\MessageBreak
   \space\space 1 = TS1 - \noexpand\textcircled-
                                          \string\t\MessageBreak
   \space\space 0 = TS1 (full)\MessageBreak
   Font families with sub-encoding setting implement\MessageBreak
   only a restricted character set as indicated.\MessageBreak
   Family '?' is the default used for unknown fonts.\MessageBreak
   See the documentation for details\@gobble}
```

\DeclareEncodingSubset

An encoding subset to which a font family belongs is declared by the command \DeclareEncodingSubset that takes the major encoding as the first argument (e.g., TS1), the family name as the second argument (e.g., cmr), and the subset encoding id as a third, (e.g., 0 for cmr).

The default encoding subset to use when nothing is known about the current font family is named ?.

```
\def\DeclareEncodingSubset#1#2#3{%
  \@ifundefined{#1:#2}%
    {\PackageInfo{textcomp}{Setting #2 sub-encoding to #1/#3}}%
    {\PackageInfo{textcomp}{Changing #2 sub-encoding to #1/#3}}%
  \@namedef{#1:#2}{#3}}
\@onlypreamble\DeclareEncodingSubset
```

(*End definition for* \DeclareEncodingSubset.)

The options for the package are the following:

safe for unknown font families enables only symbols that are also in the ISO-Adobe character set; without "currency", which is often misused for the Euro. Older Type1 fonts from the non-TeX world provide only this subset.

euro enables the "safe" symbols plus the \texteuro command. Most newer fonts provide this.

full enables all TS1 commands; useful only with fonts like EC or CM bright.

almostfull same as "full", except that \textcircled and \t are *not* redefined from their defaults to avoid that commands like \copyright suddenly no longer work.

force ignore all subset encoding definitions stored in the package itself or in the configuration file and always use the default subset as specified by one of the other options (seldom useful, only dangerous).

`\iftc@forced` Switch used to implement the `force` option

```
\newif\iftc@forced   \tc@forcedfalse
```

(*End definition for* `\iftc@forced`.)

This is implemented by defining the default subset:

```
\DeclareOption{full}{\DeclareEncodingSubset{TS1}{?}{0}}
\DeclareOption{almostfull}{\DeclareEncodingSubset{TS1}{?}{1}}
\DeclareOption{euro}{\DeclareEncodingSubset{TS1}{?}{4}}
\DeclareOption{safe}{\DeclareEncodingSubset{TS1}{?}{5}}
```

The default is "almostfull" which means that old documents will work except that `\textcircled` and `\t` will use the kernel defaults (with the advantage that this also works if the current font (as often the case) doesn't implement these glyphs.

The "force" option simply sets the switch to true.

```
\DeclareOption{force}{\tc@forcedtrue}
```

The suggestions to user is to use the "safe" option always unless that balks in which case they could switch to "almostfull" but then better check their output manually.

```
\def\tc@errorwarn{\PackageError}
\DeclareOption{warn}{\gdef\tc@errorwarn#1#2#3{\PackageWarning{#1}{#2}}}
\DeclareOption{quiet}{\gdef\tc@errorwarn#1#2#3{}}
```

```
\ExecuteOptions{almostfull}
\ProcessOptions\relax
```

`\CheckEncodingSubset` The command `\CheckEncodingSubset` will check if the current font family has the right encoding subset to typeset a certain command. It takes five arguments as follows: first argument is either `\UseTextSymbol`, `\UseTextAccent` depending on whether or not the symbol is a text symbol or a text accent.

The second argument is the encoding from which this symbol should be fetched.

The third argument is either a fake accessor command or an error message. the code in that argument (if ever executed) receives two arguments: `#2` and `#5` of `\CheckEncodingSubset`.

Argument four is the subset encoding id to test against: if this value is higher than the subset id of the current font family then we typeset the symbol, i.e., execute `#1{#2}#5` otherwise it runs `#3#5`, e.g., to produce an error message or fake the glyph somehow.

Argument five is the symbol or accent command that is being checked.

For usage examples see definitions below.

```
\iftc@forced
```

If the "force" option was given we always use the default for testing against.

```
\def\CheckEncodingSubset#1#2#3#4#5{%
    \ifnum #4>%
        0\csname #2:?\endcsname
        \relax
   \expandafter\@firstoftwo
  \else
   \expandafter\@secondoftwo
 \fi
  {#1{#2}}{#3}%
  #5%
}
```

In normal circumstances the test is a bit more complicated: first check if there exists a macro \⟨*arg2*⟩:⟨*current-family*⟩ and if so use that value to test against, otherwise use the default to test against.

```
\else
\def\CheckEncodingSubset#1#2#3#4#5{%
    \ifnum #4>%
      \expandafter\ifx\csname #2:\f@family\endcsname\relax
        0\csname #2:?\endcsname
      \else
        \csname #2:\f@family\endcsname
      \fi
   \relax
   \expandafter\@firstoftwo
  \else
   \expandafter\@secondoftwo
 \fi
  {#1{#2}}{#3}%
  #5%
}
\fi
```

(*End definition for* `\CheckEncodingSubset`.)

`\tc@subst`

```
\def\tc@subst#1{%
   \tc@errorwarn{textcomp}%
    {Symbol \string#1 not provided by\MessageBreak
     font family \f@family\space
     in TS1 encoding.\MessageBreak Default family used instead}\@eha
  \bgroup\fontfamily\textcompsubstdefault\selectfont#1\egroup
}
```

(*End definition for* `\tc@subst`.)

`\tc@error` `\tc@error` is going to be used in arg `#3` of `\CheckEncodingSubset` when a symbol is not available in a certain font family. It gets pass the encoding it normally lives in (arg one) and the name of the symbol or accent that has a problem.

```
% error commands take argument:
% #1 symbol to be used
\def\tc@error#1{%
   \PackageError{textcomp}%  % should be latex error if general
    {Accent \string#1 not provided by\MessageBreak
     font family \f@family\space
     in TS1 encoding}\@eha
}
```

(*End definition for* `\tc@error`.)

`\tc@fake@euro` `\tc@fake@euro` is an example of a "fake" definition to use in arg `#3` of `\CheckEncodingSubset` when a symbol is not available in a certain font family. Here we produce an Euro symbol by combining a "C" with a "=".

```
\def\tc@fake@euro#1{%
   \leavevmode
   \PackageInfo{textcomp}{Faking \noexpand#1for font family
```

```
                            \f@family\MessageBreak in TS1 encoding}%
   \valign{##\cr
      \vfil\hbox to 0.07em{\dimen@\f@size\p@
                             \math@fontsfalse
                             \fontsize{.7\dimen@}\z@\selectfont=\hss}%
      \vfil\cr%
      \hbox{C}\crcr
   }%
}
```

(*End definition for* `\tc@fake@euro`.)

`\tc@check@symbol` `\tc@check@accent`

These are two abbreviations that we use below to check symbols and accents in TS1. Only there to save some space, e.g., we can then write

```
DeclareTextCommandDefault{\textcurrency}{\tc@check@symbol3\textcurrency}
```

to ensure that `\textcurrency` is only typeset if the current font has a `TS1` subset id of less than 3. Otherwise `\tc@error` is called telling the user that for this font family `\textcurrency` is not available.

```
\def\tc@check@symbol{\CheckEncodingSubset\UseTextSymbol{TS1}\tc@subst}
\def\tc@check@accent{\CheckEncodingSubset\UseTextAccent{TS1}\tc@error}
```

(*End definition for* `\tc@check@symbol` *and* `\tc@check@accent`.)

We start with the commands that are "safe" and which can be unconditionally set up, first the accents...

```
\DeclareTextAccentDefault{\capitalcedilla}{TS1}
\DeclareTextAccentDefault{\capitalogonek}{TS1}
\DeclareTextAccentDefault{\capitalgrave}{TS1}
\DeclareTextAccentDefault{\capitalacute}{TS1}
\DeclareTextAccentDefault{\capitalcircumflex}{TS1}
\DeclareTextAccentDefault{\capitaltilde}{TS1}
\DeclareTextAccentDefault{\capitaldieresis}{TS1}
\DeclareTextAccentDefault{\capitalhungarumlaut}{TS1}
\DeclareTextAccentDefault{\capitalring}{TS1}
\DeclareTextAccentDefault{\capitalcaron}{TS1}
\DeclareTextAccentDefault{\capitalbreve}{TS1}
\DeclareTextAccentDefault{\capitalmacron}{TS1}
\DeclareTextAccentDefault{\capitaldotaccent}{TS1}
```

...and then the other glyphs.

```
\DeclareTextSymbolDefault{\textcapitalcompwordmark}{TS1}
\DeclareTextSymbolDefault{\textascendercompwordmark}{TS1}
\DeclareTextSymbolDefault{\textquotestraightbase}{TS1}
\DeclareTextSymbolDefault{\textquotestraightdblbase}{TS1}
\DeclareTextSymbolDefault{\texttwelveudash}{TS1}
\DeclareTextSymbolDefault{\textthreequartersemdash}{TS1}
\DeclareTextSymbolDefault{\textdollar}{TS1}
\DeclareTextSymbolDefault{\textquotesingle}{TS1}
\DeclareTextSymbolDefault{\textasteriskcentered}{TS1}
\DeclareTextSymbolDefault{\textfractionsolidus}{TS1}
\DeclareTextSymbolDefault{\textminus}{TS1}
\DeclareTextSymbolDefault{\textlbrackdbl}{TS1}
\DeclareTextSymbolDefault{\textrbrackdbl}{TS1}
\DeclareTextSymbolDefault{\textasciigrave}{TS1}
```

```
\DeclareTextSymbolDefault{\texttildelow}{TS1}
\DeclareTextSymbolDefault{\textasciibreve}{TS1}
\DeclareTextSymbolDefault{\textasciicaron}{TS1}
\DeclareTextSymbolDefault{\textgravedbl}{TS1}
\DeclareTextSymbolDefault{\textacutedbl}{TS1}
\DeclareTextSymbolDefault{\textdagger}{TS1}
\DeclareTextSymbolDefault{\textdaggerdbl}{TS1}
\DeclareTextSymbolDefault{\textbardbl}{TS1}
\DeclareTextSymbolDefault{\textperthousand}{TS1}
\DeclareTextSymbolDefault{\textbullet}{TS1}
\DeclareTextSymbolDefault{\textcelsius}{TS1}
\DeclareTextSymbolDefault{\textflorin}{TS1}
\DeclareTextSymbolDefault{\texttrademark}{TS1}
\DeclareTextSymbolDefault{\textcent}{TS1}
\DeclareTextSymbolDefault{\textsterling}{TS1}
\DeclareTextSymbolDefault{\textyen}{TS1}
\DeclareTextSymbolDefault{\textbrokenbar}{TS1}
\DeclareTextSymbolDefault{\textsection}{TS1}
\DeclareTextSymbolDefault{\textasciidieresis}{TS1}
\DeclareTextSymbolDefault{\textcopyright}{TS1}
\DeclareTextSymbolDefault{\textordfeminine}{TS1}
\DeclareTextSymbolDefault{\textlnot}{TS1}
\DeclareTextSymbolDefault{\textregistered}{TS1}
\DeclareTextSymbolDefault{\textasciimacron}{TS1}
\DeclareTextSymbolDefault{\textdegree}{TS1}
\DeclareTextSymbolDefault{\textpm}{TS1}
\DeclareTextSymbolDefault{\texttwosuperior}{TS1}
\DeclareTextSymbolDefault{\textthreesuperior}{TS1}
\DeclareTextSymbolDefault{\textasciiacute}{TS1}
\DeclareTextSymbolDefault{\textmu}{TS1}
\DeclareTextSymbolDefault{\textparagraph}{TS1}
\DeclareTextSymbolDefault{\textperiodcentered}{TS1}
\DeclareTextSymbolDefault{\textonesuperior}{TS1}
\DeclareTextSymbolDefault{\textordmasculine}{TS1}
\DeclareTextSymbolDefault{\textonequarter}{TS1}
\DeclareTextSymbolDefault{\textonehalf}{TS1}
\DeclareTextSymbolDefault{\textthreequarters}{TS1}
\DeclareTextSymbolDefault{\texttimes}{TS1}
\DeclareTextSymbolDefault{\textdiv}{TS1}
```

The `\texteuro` is only available for subsets with id 4 or less. Otherwise we fake the glyph using `\tc@fake@euro`

```
\DeclareTextCommandDefault{\texteuro}
   {\CheckEncodingSubset\UseTextSymbol{TS1}\tc@fake@euro5\texteuro}
```

The `\textohm` is only available for subsets with id 3 or less. Otherwise we produce an error.

```
\DeclareTextCommandDefault{\textohm}{\tc@check@symbol4\textohm}
```

The `\textestimated` and `\textcurrency` are only provided for fonts with subset encoding with id 2 or less.

```
\DeclareTextCommandDefault{\textestimated}%
    {\tc@check@symbol3\textestimated}
\DeclareTextCommandDefault{\textcurrency}%
    {\tc@check@symbol3\textcurrency}
```

Nearly all of the remaining glyphs are provided only with fonts with id 1 or 0, i.e., are essentially complete.

```
\DeclareTextCommandDefault{\capitaltie}%
    {\tc@check@accent2\capitaltie}
\DeclareTextCommandDefault{\newtie}%
    {\tc@check@accent2\newtie}
\DeclareTextCommandDefault{\capitalnewtie}%
    {\tc@check@accent2\capitalnewtie}
\DeclareTextCommandDefault{\textleftarrow}%
    {\tc@check@symbol2\textleftarrow}
\DeclareTextCommandDefault{\textrightarrow}%
    {\tc@check@symbol2\textrightarrow}
\DeclareTextCommandDefault{\textblank}%
    {\tc@check@symbol2\textblank}
\DeclareTextCommandDefault{\textdblhyphen}%
    {\tc@check@symbol2\textdblhyphen}
\DeclareTextCommandDefault{\textzerooldstyle}%
    {\tc@check@symbol2\textzerooldstyle}
\DeclareTextCommandDefault{\textoneoldstyle}%
    {\tc@check@symbol2\textoneoldstyle}
\DeclareTextCommandDefault{\texttwooldstyle}%
    {\tc@check@symbol2\texttwooldstyle}
\DeclareTextCommandDefault{\textthreeoldstyle}%
    {\tc@check@symbol2\textthreeoldstyle}
\DeclareTextCommandDefault{\textfouroldstyle}%
    {\tc@check@symbol2\textfouroldstyle}
\DeclareTextCommandDefault{\textfiveoldstyle}%
    {\tc@check@symbol2\textfiveoldstyle}
\DeclareTextCommandDefault{\textsixoldstyle}%
    {\tc@check@symbol2\textsixoldstyle}
\DeclareTextCommandDefault{\textsevenoldstyle}%
    {\tc@check@symbol2\textsevenoldstyle}
\DeclareTextCommandDefault{\texteightoldstyle}%
    {\tc@check@symbol2\texteightoldstyle}
\DeclareTextCommandDefault{\textnineoldstyle}%
    {\tc@check@symbol2\textnineoldstyle}
\DeclareTextCommandDefault{\textlangle}%
    {\tc@check@symbol2\textlangle}
\DeclareTextCommandDefault{\textrangle}%
    {\tc@check@symbol2\textrangle}
\DeclareTextCommandDefault{\textmho}%
    {\tc@check@symbol2\textmho}
\DeclareTextCommandDefault{\textbigcircle}%
    {\tc@check@symbol2\textbigcircle}
\DeclareTextCommandDefault{\textuparrow}%
    {\tc@check@symbol2\textuparrow}
\DeclareTextCommandDefault{\textdownarrow}%
    {\tc@check@symbol2\textdownarrow}
\DeclareTextCommandDefault{\textborn}%
    {\tc@check@symbol2\textborn}
\DeclareTextCommandDefault{\textdivorced}%
    {\tc@check@symbol2\textdivorced}
\DeclareTextCommandDefault{\textdied}%
    {\tc@check@symbol2\textdied}
```

```
\DeclareTextCommandDefault{\textleaf}%
    {\tc@check@symbol2\textleaf}
\DeclareTextCommandDefault{\textmarried}%
    {\tc@check@symbol2\textmarried}
\DeclareTextCommandDefault{\textmusicalnote}%
    {\tc@check@symbol2\textmusicalnote}
\DeclareTextCommandDefault{\textdblhyphenchar}%
    {\tc@check@symbol2\textdblhyphenchar}
\DeclareTextCommandDefault{\textdollaroldstyle}%
    {\tc@check@symbol2\textdollaroldstyle}
\DeclareTextCommandDefault{\textcentoldstyle}%
    {\tc@check@symbol2\textcentoldstyle}
\DeclareTextCommandDefault{\textcolonmonetary}%
    {\tc@check@symbol2\textcolonmonetary}
\DeclareTextCommandDefault{\textwon}%
    {\tc@check@symbol2\textwon}
\DeclareTextCommandDefault{\textnaira}%
    {\tc@check@symbol2\textnaira}
\DeclareTextCommandDefault{\textguarani}%
    {\tc@check@symbol2\textguarani}
\DeclareTextCommandDefault{\textpeso}%
    {\tc@check@symbol2\textpeso}
\DeclareTextCommandDefault{\textlira}%
    {\tc@check@symbol2\textlira}
\DeclareTextCommandDefault{\textrecipe}%
    {\tc@check@symbol2\textrecipe}
\DeclareTextCommandDefault{\textinterrobang}%
    {\tc@check@symbol2\textinterrobang}
\DeclareTextCommandDefault{\textinterrobangdown}%
    {\tc@check@symbol2\textinterrobangdown}
\DeclareTextCommandDefault{\textdong}%
    {\tc@check@symbol2\textdong}
\DeclareTextCommandDefault{\textpertenthousand}%
    {\tc@check@symbol2\textpertenthousand}
\DeclareTextCommandDefault{\textpilcrow}%
    {\tc@check@symbol2\textpilcrow}
\DeclareTextCommandDefault{\textbaht}%
    {\tc@check@symbol2\textbaht}
\DeclareTextCommandDefault{\textnumero}%
    {\tc@check@symbol2\textnumero}
\DeclareTextCommandDefault{\textdiscount}%
    {\tc@check@symbol2\textdiscount}
\DeclareTextCommandDefault{\textopenbullet}%
    {\tc@check@symbol2\textopenbullet}
\DeclareTextCommandDefault{\textservicemark}%
    {\tc@check@symbol2\textservicemark}
\DeclareTextCommandDefault{\textlquill}%
    {\tc@check@symbol2\textlquill}
\DeclareTextCommandDefault{\textrquill}%
    {\tc@check@symbol2\textrquill}
\DeclareTextCommandDefault{\textcopyleft}%
    {\tc@check@symbol2\textcopyleft}
\DeclareTextCommandDefault{\textcircledP}%
    {\tc@check@symbol2\textcircledP}
```

```
\DeclareTextCommandDefault{\textreferencemark}%
    {\tc@check@symbol2\textreferencemark}
\DeclareTextCommandDefault{\textsurd}%
    {\tc@check@symbol2\textsurd}
```

The `\textcircled` and `\t` are handled specially, unless the current font has a subset id of 0 (i.e. full `TS1`) we pick the symbols up from the math font encodings, i.e., the third argument to `\CheckEncodingSubset` uses `\UseTextAccent` to get them from there.

```
\DeclareTextCommandDefault{\textcircled}
  {\CheckEncodingSubset\UseTextAccent{TS1}%
    {\UseTextAccent{OMS}}1\textcircled}
\DeclareTextCommandDefault{\t}
  {\CheckEncodingSubset\UseTextAccent{TS1}%
    {\UseTextAccent{OML}}1\t}
```

Finally input the encoding-specific definitions for `TS1` thus making the top-level definitions optimized for this encoding (and not for the default encoding).

```
\input{ts1enc.def}
```

Now having the new glyphs available we also want to make sure that they are used. For most cases this will automatically happen but for some glyphs there are inferior definitions already known to LaTeX which will prevent the usage of the `TS1` versions. So we better get rid of them:

```
\UndeclareTextCommand{\textsterling}{OT1}
\UndeclareTextCommand{\textdollar}  {OT1}
```

Similar declarations should probably be made for other encodings like `OT4` if they are in use.

```
%\UndeclareTextCommand{\textsterling}{OT4}
%\UndeclareTextCommand{\textdollar}  {OT4}
```

From the `T1` encoding there are two candidates for removal: ‰ and ‰ since these are both constructed from % followed by a tiny '₀' rather than being a single glyph. The problem with this approach is that in PostScript fonts this small zero is usually not available resulting in %▪ rather than ‰ while the real glyph (at least for `\textperthousand`) is available in the PostScript version of `TS1`. So for the moment we compromise by removing the `T1` declaration for `\textperthousand` but keeping the one for `\textpertenthousand`. This will have the effect that with Computer Modern fonts everything will come out (although ‰ and ‰ are not taken from the same physical font) and with PostScript fonts ‰ will come out correctly while ‰ will most likely look like %▬ — which is probably an improvement over just getting a single '▪' to indicate a completely missing glyph, which would happen if we also 'undeclared' `\textpertenthousand`.

```
\UndeclareTextCommand{\textperthousand}{T1}
%\UndeclareTextCommand{\textpertenthousand}{T1}
```

5.1.1 Supporting oldstyle digits

```
\DeclareRobustCommand\oldstylenums[1]{%
 \begingroup
  \ifmmode
   \mathgroup\symletters #1%
  \else
   \CheckEncodingSubset\@use@text@encoding{TS1}%
       {\PackageWarning{textcomp}%
```

```
          {Oldstyle digits unavailable for
           family \f@family.\MessageBreak
           Lining digits used instead}}%
       \tw@{#1}%
   \fi
 \endgroup
}
```

5.1.2 Subset encoding defaults

For many font families commonly used in the TEX world we provide the subset encoding data here. Users can add additional font families in the file `textcomp.cfg` if they own other fonts.

However, if the option "forced" was given then all subset encoding specifications are ignored, so there is no point in setting any of them up:

```
\iftc@forced \else
```

Computer modern based fonts (e.g., CM, CM-Bright, Concrete):

```
\DeclareEncodingSubset{TS1}{cmr}     {0}
\DeclareEncodingSubset{TS1}{cmss}    {0}
\DeclareEncodingSubset{TS1}{cmtt}    {0}
\DeclareEncodingSubset{TS1}{cmvtt}   {0}
\DeclareEncodingSubset{TS1}{cmbr}    {0}
\DeclareEncodingSubset{TS1}{cmtl}    {0}
\DeclareEncodingSubset{TS1}{ccr}     {0}
```

PSNFSS fonts:

```
\DeclareEncodingSubset{TS1}{ptm}     {4}
\DeclareEncodingSubset{TS1}{pcr}     {4}
\DeclareEncodingSubset{TS1}{phv}     {4}
\DeclareEncodingSubset{TS1}{ppl}     {3}
\DeclareEncodingSubset{TS1}{pag}     {4}
\DeclareEncodingSubset{TS1}{pbk}     {4}
\DeclareEncodingSubset{TS1}{pnc}     {4}
\DeclareEncodingSubset{TS1}{pzc}     {4}
\DeclareEncodingSubset{TS1}{bch}     {4}
\DeclareEncodingSubset{TS1}{put}     {5}
```

Other CTAN fonts (probably not complete):

```
\DeclareEncodingSubset{TS1}{uag}     {5}
\DeclareEncodingSubset{TS1}{ugq}     {5}
\DeclareEncodingSubset{TS1}{ul8}     {4}
\DeclareEncodingSubset{TS1}{ul9}     {4}  % (LuxiSans, one day)
\DeclareEncodingSubset{TS1}{augie}   {5}
\DeclareEncodingSubset{TS1}{dayrom}  {3}
\DeclareEncodingSubset{TS1}{dayroms} {3}
\DeclareEncodingSubset{TS1}{pxr}     {0}
\DeclareEncodingSubset{TS1}{pxss}    {0}
\DeclareEncodingSubset{TS1}{pxtt}    {0}
\DeclareEncodingSubset{TS1}{txr}     {0}
\DeclareEncodingSubset{TS1}{txss}    {0}
\DeclareEncodingSubset{TS1}{txtt}    {0}
```

Latin Modern and TeX Gyre:

```
\DeclareEncodingSubset{TS1}{lmr}     {0}
\DeclareEncodingSubset{TS1}{lmdh}    {0}
```

```
\DeclareEncodingSubset{TS1}{lmss}    {0}
\DeclareEncodingSubset{TS1}{lmssq}   {0}
\DeclareEncodingSubset{TS1}{lmvtt}   {0}
\DeclareEncodingSubset{TS1}{lmtt}    {0}
```

```
\DeclareEncodingSubset{TS1}{qhv}     {0}
\DeclareEncodingSubset{TS1}{qag}     {0}
\DeclareEncodingSubset{TS1}{qbk}     {0}
\DeclareEncodingSubset{TS1}{qcr}     {0}
\DeclareEncodingSubset{TS1}{qcs}     {0}
\DeclareEncodingSubset{TS1}{qpl}     {0}
\DeclareEncodingSubset{TS1}{qtm}     {0}
\DeclareEncodingSubset{TS1}{qzc}     {0}
\DeclareEncodingSubset{TS1}{qhvc}    {0}
```

Fourier-GUTenberg:

```
\DeclareEncodingSubset{TS1}{futs}    {4}
\DeclareEncodingSubset{TS1}{futx}    {4}
\DeclareEncodingSubset{TS1}{futj}    {4}
```

Y&Y's Lucida Bright

```
\DeclareEncodingSubset{TS1}{hlh}     {3}
\DeclareEncodingSubset{TS1}{hls}     {3}
\DeclareEncodingSubset{TS1}{hlst}    {3}
```

The remaining settings for Lucida are conservative: the following fonts contain the `\textohm` character but not the `\texteuro`, i.e., belong to neither subset 4 nor subset 3. If you want to use the `\textohm` with these fonts copy these definition to `textcomp.cfg` and change the subset to 3. However in that case make sure that you do not use the `\texteuro`.

```
\DeclareEncodingSubset{TS1}{hlct}    {5}
\DeclareEncodingSubset{TS1}{hlx}     {5}
\DeclareEncodingSubset{TS1}{hlce}    {5}
\DeclareEncodingSubset{TS1}{hlcn}    {5}
\DeclareEncodingSubset{TS1}{hlcw}    {5}
\DeclareEncodingSubset{TS1}{hlcf}    {5}
```

Other commercial families...

```
\DeclareEncodingSubset{TS1}{pplx}    {3}
\DeclareEncodingSubset{TS1}{pplj}    {3}
\DeclareEncodingSubset{TS1}{ptmx}    {4}
\DeclareEncodingSubset{TS1}{ptmj}    {4}
```

If the file `textcomp.cfg` exists it will be loaded at this point. This allows to define further subset encodings for font families not covered by default.

```
\InputIfFileExists{textcomp.cfg}
  {\PackageInfo{textcomp}{Local configuration file used}}{}
```

```
\fi
```

⟨/TS1oldsty⟩

File F
ltpageno.dtx

1 Page Numbering

Page numbers are produced by a page counter, used just like any other counter. The only difference is that `\c@page` contains the number of the next page to be output (the one currently being produced), rather than one minus it. Thus, it is normally initialized to 1 rather than 0. `\c@page` is defined to be `\count0`, rather than a count assigned by `\newcount`.

`\pagenumbering` The user sets the page number style with the `\pagenumbering{`⟨*foo*⟩`}` command, which sets the page counter to 1 and defines `\thepage` to be `\foo`. For example, `\pagenumbering{roman}` causes pages to be numbered i, ii, etc.

```
⟨*2ekernel⟩
\message{page nos.,}
\countdef\c@page=0 \c@page=1
\def\cl@page{}
\def\pagenumbering#1{%
  \global\c@page \@ne \gdef\thepage{\csname @#1\endcsname
   \c@page}}
⟨/2ekernel⟩
```

File G
ltxref.dtx

1 Cross Referencing

The user writes `\label{`⟨*foo*⟩`}` to define the following cross-references:

`\ref*{`⟨*foo*⟩`}`: value of most recently incremented referenceable counter. in the current environment. (Chapter, section, theorem, footnote and enumeration counters and other counters stepped with `\refstepcounter` are referenceable.)

`\pageref*{`⟨*foo*⟩`}`: page number at which `\label{foo}` command appeared. where foo can be any string of characters not containing '`\`', '`{`' or '`}`'.

Note: The scope of the `\label` command is delimited by environments, so
`\begin{theorem} \label{foo} ... \end{theorem} \label{bar}`
defines `\ref{foo}` to be the theorem number and `\ref{bar}` to be the current section number.

Note: `\label` does the right thing in terms of spacing – i.e., leaving a space on both sides of it is equivalent to leaving a space on either side.

Note: the starred versions `\ref*` and `\pageref*` are provided to align with the use of hyperref. Without hyperref (or some other package using the starred form) the star is simply ignored.

1.1 Cross Referencing

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
⟨*2ekernel⟩
\message{x-ref,}
```

This is implemented as follows. A referenceable counter CNT is incremented by the command `\refstepcounter{CNT}` , which sets `\@currentlabel == {CNT}{eval(\p@cnt\theCNT)}`. The command `\label{FOO}` then writes the following on file `\@auxout` :

```
      \newlabel{FOO}{{eval(\@currentlabel)}{eval(\thepage)}}

\ref{FOO} ==
  BEGIN
    if \r@foo undefined
      then  @refundefined := G T
            ??
            Warning: 'reference foo on page ... undefined'
      else  \@car \eval(\r@FOO)\@nil
    fi
  END

\pageref{foo} =
  BEGIN
    if \r@foo undefined
      then  @refundefined := G T
            ??
```

```
                Warning: 'reference foo on page ... undefined'
        else  \@cdr \eval(\r@FOO)\@nil
      fi
    END
```

End of historical LaTeX 2.09 comments.

`\labelformat` A reference via `\ref` produces by default the data associated with the corresponding `\label` command (typically a number); any additional formatting has to be provided by the user. If, for example, references to equations are always to be typeset as "equation (*number*)", one has to code "`equation (\ref{`*key*`})`". With `\labelformat` there is a possibility to generate such frills automatically without resorting to low-level coding. The command takes two arguments: the first is the name of a counter and the second is its representation when referenced. This means that for a successful usage, one has to know the counter name being used for generating the label, though in practice this should not pose a problem. The current counter number is picked up as an argument. Here are two examples:

```
\labelformat{section}{section~#1}
\labelformat{equation}{equation~(#1)}}
```

`\Ref` A side effect of using `\labelformat` is that, depending on the defined formatting, it becomes impossible to use `\ref` at the beginning of a sentence (if its replacement text starts with a lowercase letter). To overcome this problem we introduce the command `\Ref` that behave like `\ref` except that it uppercases the first token of the generated string.

To make `\Ref` work properly the very first token in the second argument of `\labelformat` has to be a simple ASCII or UTF-8 letter, otherwise the capitalization will fail or worse, you will end up with some error messages. If you actually need something more complicated in this place (e.g., an accented letter not written as a UTF-8 character) you have to explicitly surround it with braces, to identify the part that needs to be capitalized. For example, for figure references in the Hungarian language you might want to write `\labelformat{figure}{{\'a}bra~\thefigure}` or use `\labelformat{figure}{ábra~\thefigure}` which avoids the brace problem.

`\G@refundefinedtrue` `\@refundefined` This does not save on name-space (since `\G@refundefinedfalse` was never needed) but it does make the implementation of such one-way switches more consistent. The extra macro to make the change is used since this change appears several times.

Note despite its name, `\G@refundefinedtrue` does *not* correspond to an `\if` command, and there is no matching ...`false`. It would be more natural to call the command `\G@refundefined` (as inspection of the change log will reveal) but unfortunately such a change would break any package that had defined a `\ref`-like command that mimicked the definition of `\ref`, calling `\G@refundefinedtrue`. Inspection of the TeX archives revealed several such packages, and so this command has been named ...`true` so that the definition of `\ref` need not be changed, and the packages will work without change.

```
% \newif\ifG@refundefined
% \def\G@refundefinedtrue{\global\let\ifG@refundefined\iftrue}
% \def\G@refundefinedfalse{\global\let\ifG@refundefined\iffalse}
\def\G@refundefinedtrue{%
  \gdef\@refundefined{%
    \@latex@warning@no@line{There were undefined references}}}
\let\@refundefined\relax
```

(*End definition for* `\G@refundefinedtrue` *and* `\@refundefined`.)

`\ref` `\pageref` `\@setref` Referencing a `\label`. RmS 91/10/25: added a few extra `\reset@font`, as suggested by Bernd Raichle

RmS 92/08/14: made `\ref` and `\pageref` robust

RmS 93/09/08: Added setting of refundefined switch.

```
\def\@setref#1#2#3{%
  \ifx#1\relax
   \protect\G@refundefinedtrue
   \nfss@text{\reset@font\bfseries ??}%
   \@latex@warning{Reference ‘#3’ on page \thepage \space
             undefined}%
  \else
   \expandafter#2#1\null
  \fi}
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                 {\ref}{Add starred reference commands}%
```

```
\def\@kernel@sref#1{\expandafter\@setref\csname r@#1\endcsname\@firstoftwo{#1}}
\def\@kernel@spageref#1{\expandafter\@setref\csname r@#1\endcsname
                 \@secondoftwo{#1}}
\let\@kernel@ref\@kernel@sref
\let\@kernel@pageref\@kernel@spageref
\NewDocumentCommand\ref{s}
   {\IfBooleanTF{#1}{\@kernel@sref}{\@kernel@ref}}
\NewDocumentCommand\pageref{s}
   {\IfBooleanTF{#1}{\@kernel@spageref}{\@kernel@pageref}}
```

As the commands are now protected we also need expandable versions for use in `\ifthenelse`:

```
\def\@kernel@pageref@exp#1{\csname cs_if_exist:cTF\endcsname
   {r@#1}{\csname tl_item:cn\endcsname{r@#1}{2}}{0}}
\def\@kernel@ref@exp#1{\csname cs_if_exist:cTF\endcsname
   {r@#1}{\csname tl_item:cn\endcsname{r@#1}{1}}{0}}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\ref}{Add starred reference commands}%
⟨latexrelease⟩\def\ref#1{\expandafter\@setref\csname r@#1\endcsname\@firstoftwo{#1}}
⟨latexrelease⟩\def\pageref#1{\expandafter\@setref\csname r@#1\endcsname
⟨latexrelease⟩                                  \@secondoftwo{#1}}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\ref`, `\pageref`, *and* `\@setref`.)

`\newlabel` This command will be written to the `.aux` file to pass label information from one run to another.

The internal form of \newlabel and \bibcite. Note that this macro does it's work inside a group. That way the local assignments it needs to do don't clutter the save stack. This prevents large documents with many labels to run out of save stack.

\@newl@bel

```
\def\@newl@bel#1#2#3{{%
  \@ifundefined{#1@#2}%
    \relax
    {\gdef \@multiplelabels {%
       \@latex@warning@no@line{There were multiply-defined labels}}%
     \@latex@warning@no@line{Label ‘#2’ multiply defined}}%
  \global\@namedef{#1@#2}{#3}}}
```

```
\def\newlabel{\@newl@bel r}
```

```
\@onlypreamble\@newl@bel
```

(*End definition for* \newlabel *and* \@newl@bel.)

\if@multiplelabels
\@multiplelabels

This is redefined to produce a warning if at least one label is defined more than once. It is executed by the \enddocument command.

```
\let \@multiplelabels \relax
```

(*End definition for* \if@multiplelabels *and* \@multiplelabels.)

\label

The commands \label and \refstepcounter have been changed to allow \protect'ed commands to work properly. For example,

```
\def\thechapter{\protect\foo{\arabic{chapter}.\roman{section}}}
```

will cause a \label{bar} command to define \ref{bar} to expand to something like \foo{4.d}. Change made 20 Jul 88.

```
\def\label#1{\@bsphack
  \protected@write\@auxout{}%
         {\string\newlabel{#1}{{\@currentlabel}{\thepage}}}%
  \@esphack}
```

(*End definition for* \label.)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                  {\Ref}{Add starred version}%
```

\refstepcounter

Step the counter and allow for labels to point to its current value.

```
\def\@currentcounter{}
\def\refstepcounter#1{\stepcounter{#1}%
    \edef\@currentcounter{#1}%
    \protected@edef\@currentlabel
```

By generating the second csname first the \p@... command can grab it as an argument which can be helpful for more complicated typesetting arrangements.

The trick is to ensure that \csname the#1\endcsname is turned into a single token before \p@... is expanded further. This way, if the \p@... command is a macro with one argument it will receive \the.... With the original kernel code (i.e., without the \expandafter) it will instead pick up \csname which would be disastrous.

Using \expandafter instead of braces delimiting the argument is better because, assuming that the \p@... command is not defined as a macro with one argument, the

braces will stay and prohibit kerning that might otherwise happen between the glyphs generated by `\the...` and surrounding glyphs.

```
        {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
}
```

(*End definition for* `\refstepcounter`.)

`\labelformat` A shortcut to set the `\p@...` macro for a counter. It will pick up the counter representation as an argument so that it can be specially formatted.

```
\def\labelformat#1{\expandafter\def\csname p@#1\endcsname##1}
```

(*End definition for* `\labelformat`.)

`\Ref` This macro expands the result of `\ref` and then uppercases the first token. Only useful if the label was generated via `\labelformat` and contains some lower case letter at its start. If the label starts with a complicated construct (e.g., an accented letter that is provided via a command, e.g., `\"a` instead of a UTF-8 character like ä) one has to surround everything that needs uppercasing in a brace group in the definition of `\labelformat`.[31]

```
\def\@kernel@Ref#1{\protected@edef\@tempa{\@kernel@ref{#1}}%
        \expandafter\MakeUppercase\@tempa}
\def\@kernel@sRef#1{\protected@edef\@tempa{\@kernel@sref{#1}}%
        \expandafter\MakeUppercase\@tempa}
\NewDocumentCommand\Ref{s}
   {\IfBooleanTF{#1}{\@kernel@sRef}{\@kernel@Ref}}
```

(*End definition for* `\Ref`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\Ref}{Add starred version}%
⟨latexrelease⟩\def\@currentcounter{}
⟨latexrelease⟩\def\refstepcounter#1{\stepcounter{#1}%
⟨latexrelease⟩     \edef\@currentcounter{#1}%
⟨latexrelease⟩     \protected@edef\@currentlabel
⟨latexrelease⟩        {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
⟨latexrelease⟩}
⟨latexrelease⟩\def\labelformat#1{\expandafter\def\csname p@#1\endcsname##1}
⟨latexrelease⟩\DeclareRobustCommand\Ref[1]{\protected@edef\@tempa{\ref{#1}}%
⟨latexrelease⟩    \expandafter\MakeUppercase\@tempa}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\refstepcounter}{Add \labelformat and \Ref}%
⟨latexrelease⟩\let\@currentcounter\@undefined
⟨latexrelease⟩\def\refstepcounter#1{\stepcounter{#1}%
⟨latexrelease⟩     \protected@edef\@currentlabel
⟨latexrelease⟩       {\csname p@#1\expandafter\endcsname\csname the#1\endcsname}%
⟨latexrelease⟩}
⟨latexrelease⟩\def\labelformat#1{\expandafter\def\csname p@#1\endcsname##1}
⟨latexrelease⟩\DeclareRobustCommand\Ref[1]{\protected@edef\@tempa{\ref{#1}}%
⟨latexrelease⟩    \expandafter\MakeUppercase\@tempa}
```

[31] There is one problem with this approach: the braces are kept in a normal `\ref` which might spoil kerning. Perhaps one day this needs redoing.

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\refstepcounter}{Add \labelformat and \Ref}%
⟨latexrelease⟩
⟨latexrelease⟩\def\refstepcounter#1{\stepcounter{#1}%
⟨latexrelease⟩    \protected@edef\@currentlabel
⟨latexrelease⟩       {\csname p@#1\endcsname\csname the#1\endcsname}%
⟨latexrelease⟩}
⟨latexrelease⟩\let\labelformat\@undefined
⟨latexrelease⟩\let\Ref\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\@currentlabel` Default for `\label` commands that come before any environment.

```
\def\@currentlabel{}
```

(*End definition for* `\@currentlabel`.)

```
⟨/2ekernel⟩
```

File H
ltmiscen.dtx

1 Miscellaneous Environments

This section implements the basic environment mechanism, and also a few specific environments including `document`, The math environments and related commands, the 'flushing' environments, (`center`, `flushleft`, `flushright`), and `verbatim`.

```
⟨*2ekernel⟩
\message{environments,}
```

1.1 Environments

`\begin{foo}` and `\end{foo}` are used to delimit environment `foo`.

`\begin{foo}` starts a group and calls `\foo` if it is defined, otherwise it does nothing.

`\end{foo}` checks to see that it matches the corresponding `\begin` and if so, it calls `\endfoo` and does an `\endgroup`. Otherwise, `\end{foo}` does nothing.

If `\end{foo}` needs to ignore blanks after it, then `\endfoo` should globally set the `@ignore` switch true with `\@ignoretrue` (this will automatically be global).

NOTE: `\@@end` is defined to be the `\end` command of TEX82.

`\enddocument` is the user's command for ending the manuscript file.

`\stop` is a panic button — to end TEX in the middle.

Historical LATEX 2.09 comments (not necessarily accurate any more):

```
\enddocument ==
  BEGIN
   \@checkend{document}    %% checks for unmatched \begin
   \clearpage
   \begingroup
     if @filesw = true
       then  close file @mainaux
             if G@refundefined = true
              then LaTeX Warning: 'There are undefined references.' fi
             if @multiplelabels = true
               then LaTeX Warning:
                    'One or more label(s) multiply defined.'
               else
               \@setckpt {ARG1}{ARG2} == null
               \newlabel{LABEL}{VAL} ==
                    BEGIN
                      \reserved@a == VAL
                      if def(\reserved@a) = def(\r@LABEL)
                        else @tempswa := true            fi
                    END
               \bibcite{LABEL}{VAL} == null
                    BEGIN
                      \reserved@a == VAL
                      if def(\reserved@a) = def(\g@LABEL)
                        else @tempswa := true            fi
```

```
                    END
                @tempswa := false
                make @ a letter
                \input \jobname.AUX
                if @tempswa = true
                  then LaTeX Warning: 'Label may have changed.
                                      Rerun to get cross-references right.'
        fi      fi      fi
    \endgroup
    finish up
  END

\@writefile{EXT}{ENTRY} ==
    if tf@EXT undefined
      else \write\tf@EXT{ENTRY}
    fi
```

End of historical LaTeX 2.09 comments.

`\@currenvir` The name of the current environment. Initialized to `document` to so that `\end{document}` works correctly.

```
\def\@currenvir{document}
```

(*End definition for* `\@currenvir`.)

`\if@ignore`
`\@ignoretrue`
`\@ignorefalse`

```
\def\@ignorefalse{\global\let\if@ignore\iffalse}
\def\@ignoretrue {\global\let\if@ignore\iftrue}
\@ignorefalse
```

(*End definition for* `\if@ignore`, `\@ignoretrue`, *and* `\@ignorefalse`.)

`\ignorespacesafterend`

```
\let\ignorespacesafterend\@ignoretrue
```

(*End definition for* `\ignorespacesafterend`.)

`\enddocument` (*end*)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                    {\enddocument}{Use Hooks}%
\def\enddocument{%
```

The `\end{document}` hook is executed first. If necessary it can contain a `\clearpage` to output dangling floats first. In this position it can also contain something like `\end{foo}` so that the whole document effectively starts and ends with some special environment. However, this must be used with care, eg if two applications would use this without knowledge of each other the order of the environments will be wrong after all. `\AtEndDocument` is redefined at this point so that and such commands that get into the hook do not chase their tail...

```
    \@kernel@before@enddocument
    \UseOneTimeHook{enddocument}%
    \@kernel@after@enddocument
```

```
  \@checkend{document}%
  \clearpage
  \UseOneTimeHook{enddocument/afterlastpage}%
  \@kernel@after@enddocument@afterlastpage
  \begingroup
    \if@filesw
      \immediate\closeout\@mainaux
      \let\@setckpt\@gobbletwo
      \let\@newl@bel\@testdef
```

The previous line is equiv to setting

```
\def\newlabel{\@testdef r}%
\def\bibcite{\@testdef b}%
```

We use `\@@input` to load the `.aux` file, so that it doesn't show up in the list of files produced by `\listfiles`.

```
      \@tempswafalse
      \makeatletter \@@input\jobname.aux
    \fi
    \UseOneTimeHook{enddocument/afteraux}%
```

Next hook is expect to contain only code for writing info messages on the terminal.

```
    \UseOneTimeHook{enddocument/info}%
  \endgroup
  \UseOneTimeHook{enddocument/end}%
  \deadcycles\z@\@@end}
```

The public hooks used in `\enddocument`:

```
\NewHook{enddocument}
\NewHook{enddocument/afterlastpage}
\NewHook{enddocument/afteraux}
\NewHook{enddocument/info}
\NewHook{enddocument/end}
```

This is one of the few places where we already add data and rules to a hook already in the kernel.

```
\AddToHook{enddocument/info}[kernel/filelist]{\@dofilelist}
\AddToHook{enddocument/info}[kernel/warnings]{\@enddocument@kernel@warnings}
\DeclareHookRule{enddocument/info}{kernel/filelist}{before}{kernel/warnings}
```

(*End definition for* `\enddocument`.)

`\@enddocument@kernel@warnings`

```
\def\@enddocument@kernel@warnings{%
```

First we check for font size substitution bigger than `\fontsubfuzz`. The `\relax` is necessary because this is a macro not a register.

```
  \ifdim \font@submax >\fontsubfuzz\relax
```

In case you wonder about the `\@gobbletwo` inside the message below, this is a horrible hack to remove the tokens `\on@line.` that are added by `\@font@warning` at the end.

```
    \@font@warning{Size substitutions with differences\MessageBreak
                   up to \font@submax\space have occurred.\@gobbletwo}%
  \fi
```

The macro \@defaultsubs is initially \relax but gets redefined to produce a warning if there have been some default font substitutions.

```
  \@defaultsubs
```

The macro \@refundefined is initially \relax but gets redefined to produce a warning if there are undefined refs.

```
  \@refundefined
```

If a label is defined more than once, \@tempswa will always be true and thus produce a "Label(s) may ..." warning. But since a rerun will not solve that problem (unless one uses a package like varioref that generates labels on the fly), we suppress this message.

```
  \if@filesw
    \ifx \@multiplelabels \relax
      \if@tempswa
        \@latex@warning@no@line{Label(s) may have changed.
            Rerun to get cross-references right}%
      \fi
    \else
      \@multiplelabels
    \fi
    \ifx \@extra@page@added \relax
        \@latex@warning@no@line{Temporary extra page added at the end.
            Rerun to get it removed}%
    \fi
```

We could think of adding a warning that nothing can be corrected while \nofiles is in force. In the past the warnings related to the aux file are simply suppressed in this case.

```
  \fi
}
```

(*End definition for* \@enddocument@kernel@warnings.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\enddocument}{Use Hooks}%
⟨latexrelease⟩
⟨latexrelease⟩\def\enddocument{%
⟨latexrelease⟩   \let\AtEndDocument\@firstofone
⟨latexrelease⟩   \@enddocumenthook
⟨latexrelease⟩   \@checkend{document}%
⟨latexrelease⟩   \clearpage
⟨latexrelease⟩   \begingroup
⟨latexrelease⟩     \if@filesw
⟨latexrelease⟩       \immediate\closeout\@mainaux
⟨latexrelease⟩       \let\@setckpt\@gobbletwo
⟨latexrelease⟩       \let\@newl@bel\@testdef
⟨latexrelease⟩       \@tempswafalse
⟨latexrelease⟩       \makeatletter \@@input\jobname.aux
⟨latexrelease⟩     \fi
⟨latexrelease⟩     \@dofilelist
⟨latexrelease⟩     \ifdim \font@submax >\fontsubfuzz\relax
⟨latexrelease⟩       \@font@warning{Size substitutions with differences\MessageBreak
⟨latexrelease⟩                 up to \font@submax\space have occurred.\@gobbletwo}%
```

```
⟨latexrelease⟩      \fi
⟨latexrelease⟩      \@defaultsubs
⟨latexrelease⟩      \@refundefined
⟨latexrelease⟩      \if@filesw
⟨latexrelease⟩        \ifx \@multiplelabels \relax
⟨latexrelease⟩          \if@tempswa
⟨latexrelease⟩            \@latex@warning@no@line{Label(s) may have changed.
⟨latexrelease⟩                Rerun to get cross-references right}%
⟨latexrelease⟩          \fi
⟨latexrelease⟩        \else
⟨latexrelease⟩          \@multiplelabels
⟨latexrelease⟩        \fi
⟨latexrelease⟩      \fi
⟨latexrelease⟩    \endgroup
⟨latexrelease⟩    \deadcycles\z@\@@end}
⟨latexrelease⟩
⟨latexrelease⟩\let\@enddocument@kernel@warnings\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\@kernel@before@enddocument` The `\@kernel@before@enddocument` hook is slightly different because we initialize it with `\par` so that `\enddocument` always returns to vertical mode as its first action.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\@kernel@before@enddocument}{kernel before hook}%
\def\@kernel@before@enddocument{\par}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

The rollback code renders it harmless.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@kernel@before@enddocument}{kernel before hook}%
⟨latexrelease⟩
⟨latexrelease⟩\let\@kernel@before@enddocument\@empty
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@kernel@before@enddocument`.)

`\@testdef`

```
\def\@testdef #1#2#3{%
  \def\reserved@a{#3}\expandafter \ifx \csname #1@#2\endcsname
 \reserved@a  \else \@tempswatrue \fi}
```

(*End definition for* `\@testdef`.)

Reading data from auxiliary files (like `.toc` normally happens in vertical mode and it therefore doesn't matter if line endings are converted to spaces by TEX during that process.

However, especially the `.toc` file might be read in L-R mode (in cases the `\tableofcontents` attempts to put, say a list of sub-sections as a paragraph. In that case the newlines after a line like

```
\contentsline {subsubsection}{\numberline {1.1.1}A C-head}{2}
```

might result in spurious spaces (e.g., when that level is not included).

That could be fixed by reading in the file using `\endlinechar=-1` but that has the danger that it drops some valid endlines that should be converted to spaces (for example when the user edited the TOC and then used `\nofiles` to preserve it.

So the approach taken instead is this:

- `\addcontentsline` adds the command `\protected@file@percent` to the end of the second argument of `\@writefile` that is written to the `.aux`. As the name indicates this is a protected macro so it doesn't change if it is written out.
- When the `.aux` is read back in at the end of the run, `\@writefile` is executed and writes its second argument unmodified to the file with the extension given by its first argument. Or rather that was how it was in the past.
- Instead we change `\@writefile` slightly: basically it looks at the second argument and if the last token in there is `\protected@file@percent` then it is replaced by a percent character and that is then written out. If not (for example, if the data came from a user issued `\addtocontents`, or from some package that uses `\@writefile` for writing its own files) then the command behaves exactly as before.

`\protected@file@percent` Dummy cs to be replaced by a percent sign inside `\@writefile`. If it survives (when used incorrectly) it will expand to nothing in a typsetting context.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                  {\protected@file@percent}{Mask line endings}%
\protected\def\protected@file@percent{}
```

(*End definition for* `\protected@file@percent`.)

`\add@percent@to@temptokena` Helper function which is used to inspect a sequence of tokens (the second argument of `\@writefile` and it the last token is `\protected@file@percent` it will replace it by a harmless percent. The result is saved in `\@temptokena` for later use.

```
\catcode`\^^A=9
\long\gdef\add@percent@to@temptokena
    #1\protected@file@percent#2\add@percent@to@temptokena
```

When we call this macro in `\@writefile` we stick in `\@empty` at the beginning, so that in case the tokenlist consists of a single brace group the braces aren't stripped. The `\expandafter` then expands this extra token away again.

```
    {\expandafter\ifx\expandafter X\detokenize{#2}X\expandafter\dont@add@percent@to@temptoken
             \expandafter\do@add@percent@to@temptokena\fi{#1}}
```

```
\long\def\dont@add@percent@to@temptokena#1{%
  \@temptokena\expandafter{#1}}
```

`latexrelease` will read this code in high-speed mode in certain situations. During that it will only look for `\if` tests but not actually execute the `\catcode` change above. As a result it will drop anything after the `%` character in the definition. Therefore the `\fi` needs to be on the next line and we need locally another comment character to avoid getting spaces into the definition—a weird problem :-)

```
\begingroup
```

```
\catcode`\%=12
\catcode`\^^A=14
\long\gdef\do@add@percent@to@temptokena#1{\@temptokena\expandafter{#1%^^A
```

Can't be on the same line as the % — see above.

```
  }}
\endgroup
```

(*End definition for* `\add@percent@to@temptokena`.)

`\@writefile`

```
\long\def\@writefile#1#2{%
  \@ifundefined{tf@#1}\relax
    {%
```

If we write to the file we first prepare `#2` using `\add@percent@to@temptokena` and then write the token register out.

```
      \add@percent@to@temptokena
        \@empty#2\protected@file@percent
        \add@percent@to@temptokena
     \immediate\write\csname tf@#1\endcsname{\the\@temptokena}%
    }%
}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\protected@file@percent}{Mask line endings}%
⟨latexrelease⟩\let\protected@file@percent\@undefined
⟨latexrelease⟩\let\add@percent@to@temptokena\@undefined
⟨latexrelease⟩\let\do@add@percent@to@temptokena\@undefined
⟨latexrelease⟩\let\dont@add@percent@to@temptokena\@undefined
⟨latexrelease⟩\long\def\@writefile#1#2{%
⟨latexrelease⟩  \@ifundefined{tf@#1}\relax
⟨latexrelease⟩    {\@temptokena{#2}%
⟨latexrelease⟩     \immediate\write\csname tf@#1\endcsname{\the\@temptokena}%
⟨latexrelease⟩    }%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@writefile`.)

`\stop`

```
\def\stop{\clearpage\deadcycles\z@\let\par\@@par\@@end}
```

(*End definition for* `\stop`.)

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\everypar{\@nodocument} %% To get an error if text appears before the
\nullfont               %% \begin{document}
```

```
\begin, \end, and \@checkend changed so \end{document} will catch
an unmatched \begin.  Changed 24 May 89 as suggested by
Frank Mittelbach and Rainer Sch\"opf.

\begin{NAME} ==
 BEGIN
   IF \NAME undefined   THEN  \reserved@a == BEGIN report error END
                         ELSE  \reserved@a ==
                                   (\@currenvir :=L NAME) \NAME
   FI
   @ignore :=G F       %% Added 30 Nov 88
   \begingroup
   \@endpe := F
   \@currenvir :=L NAME
   \NAME
 END

\end{NAME} ==
 BEGIN
  \endNAME
  \@checkend{NAME}
  \endgroup
  IF @endpe = T                 %% @endpe set True by \@endparenv
    THEN \@doendpe              %% \@doendpe redefines \par and \everypar
                               %% to suppress paragraph indentation in
  FI                           %% immediately following text
  IF @ignore = T
    THEN @ignore :=G F
         \ignorespaces
  FI
 END

\@checkend{NAME} ==
 BEGIN
  IF \@currenvir = NAME
    ELSE \@badend{NAME}
  FI
 END
```

End of historical LaTeX 2.09 comments.

\begin

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\begin}{Use hook system}%
\DeclareRobustCommand*\begin[1]{%
  \UseHook{env/#1/before}%
  \@ifundefined{#1}%
```

```
    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
    {\def\reserved@a{\def\@currenvir{#1}%
        \edef\@currenvline{\on@line}%
        \@execute@begin@hook{#1}%
        \csname #1\endcsname}}%
  \@ignorefalse
  \begingroup\@endpefalse\reserved@a}
```

Before the `\document` code is executed we have to first undo the `\endgroup` as there should be none for this environment to avoid that changes on top-level unnecessarily go to TEX's savestack, and we have to initialize all hooks in the hook system. So we need to test for this environment name. But once it has be found all this testing is no longer needed and so we redefine `\@execute@begin@hook` to simply use the hook.

```
\def\@execute@begin@hook #1{%
  \expandafter\ifx\csname #1\endcsname\document
    \endgroup
    \gdef\@execute@begin@hook##1{\UseHook{env/##1/begin}}%
    \@expl@@@initialize@all@@
  \fi
```

If this is an environment before `\begin{document}` we just run the hook so this can be outside the test.

```
  \UseHook{env/#1/begin}%
}
```

The top level definition for `\end`. for an explanation see below (this is the same as the 2019 version where it was introduced, but for rollback we have to repeat it).

```
\edef\end
  {\unexpanded{%
     \romannumeral
       \ifx\protect\@typeset@protect
       \expandafter       %1
         \expandafter        %2
       \expandafter       %1
           \expandafter         %3 expands the \csname inside \end<space>
       \expandafter       %1
         \expandafter        %2  expands \end<space>
       \expandafter       %1     expands the \else
           \z@
       \else
         \expandafter\z@\expandafter\protect
       \fi
    }%
    \expandafter\noexpand\csname end \endcsname
  }
```

Version that adds hooks (so different from the 2019 version). It fixes tlb3722 but the change should perhaps be made in `tabularx` instead.

```
\@namedef{end }#1{%
  \romannumeral
    \IfHookEmptyTF{env/#1/end}%
        {\expandafter\z@}%
        {\z@\UseHook{env/#1/end}}%
    \csname end#1\endcsname\@checkend{#1}%
    \expandafter\endgroup\if@endpe\@doendpe\fi
```

```
    \UseHook{env/#1/after}%
    \if@ignore\@ignorefalse\ignorespaces\fi
}
```

Version without the fix for tlb3722 for the record:

```
%\@namedef{end }#1{%
%  \UseHook{env/#1/end}%
%  \csname end#1\endcsname\@checkend{#1}%
%  \expandafter\endgroup\if@endpe\@doendpe\fi
%  \UseHook{env/#1/after}%
%  \if@ignore\@ignorefalse\ignorespaces\fi}%
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\begin}{Making \begin/\end robust}%
⟨latexrelease⟩\DeclareRobustCommand\begin[1]{%
⟨latexrelease⟩  \@ifundefined{#1}%
⟨latexrelease⟩    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
⟨latexrelease⟩    {\def\reserved@a{\def\@currenvir{#1}%
⟨latexrelease⟩     \edef\@currenvline{\on@line}%
⟨latexrelease⟩     \csname #1\endcsname}}%
⟨latexrelease⟩  \@ignorefalse
⟨latexrelease⟩  \begingroup\@endpefalse\reserved@a}
```

A version that doesn't start out with `\relax` when in typesetting mode would be the following, but since `\begin` issues a `\begingroup` it wouldn't help much with respect to allowing things like `\noalign` or `\multicolumn` inside.

```
%\edef\begin
%  {\unexpanded{%
%       \ifx\protect\@typeset@protect
%         \expandafter\@gobble
%       \fi
%       \protect
%     }%
%   \expandafter\noexpand\csname begin \endcsname
%  }
%\@namedef{begin }#1{%
%  \@ifundefined{#1}%
%    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
%    {\def\reserved@a{\def\@currenvir{#1}%
%     \edef\@currenvline{\on@line}%
%     \csname #1\endcsname}}%
%  \@ignorefalse
%  \begingroup\@endpefalse\reserved@a}
```

While `\begin` was made robust simply by using `\DeclareRobustCommand` we need to be a bit more subtle with `\end` as there are packages out there that try to look into the top-level contents of `\end{foo}` (that is at the expansion of `\endfoo`) to see if it contains certain macros. This is done by hitting `\end{foo}` with three `\expandafter`s, the first to get

```
\csname endfoo\endcsname        \@checkend{foo}% etc.
```

the second to expand the `\csname`, i.e., to get to

```
\endfoo                          \@checkend{foo}% etc.
```

and the third to finally get to the top-level content of `\endfoo`, i.e.

```
<top-level content of \endfoo> \@checkend{foo}% etc.
```

Therefore a robust replacement should produce the same results after three expansions (there first is obviously different).

Basically the definition of `\end` should either produce `\protect\end␣` (when not doing typesetting) or it should produce `\end␣` (without the `\protect`) when doing typesetting. Furthermore, it should (when in typesetting mode) show exactly the same result as `\end␣` (which is the original fragile definition of `\end`) when you expand either of them twice, i.e.,

```
\endfoo                          \@checkend{foo}% etc.
```

That is achieved with the code below (which is worth studying carefully).

There is some trickery involved here: in particular we use `\romannumeral` to change a single expansion into three successive expansions in one go. That primitive expands until it has scanned a number (0 in this case, so it doesn't produce any output) and so it allows us to place arbitrary many `\expandafter`s inside that are all going to be executed when `\romannumeral` is hit by a single `\expandafter`.

```
⟨latexrelease⟩\edef\end
⟨latexrelease⟩  {\unexpanded{%
⟨latexrelease⟩     \romannumeral
⟨latexrelease⟩       \ifx\protect\@typeset@protect
⟨latexrelease⟩       \expandafter       %1
⟨latexrelease⟩         \expandafter        %2
⟨latexrelease⟩       \expandafter       %1
⟨latexrelease⟩           \expandafter         %3 expands the \csname inside \end<space>
⟨latexrelease⟩       \expandafter       %1
⟨latexrelease⟩         \expandafter        %2  expands \end<space>
⟨latexrelease⟩       \expandafter       %1     expands the \else
⟨latexrelease⟩           \z@
⟨latexrelease⟩       \else
⟨latexrelease⟩         \expandafter\z@\expandafter\protect
⟨latexrelease⟩       \fi
⟨latexrelease⟩   }%
⟨latexrelease⟩   \expandafter\noexpand\csname end \endcsname
⟨latexrelease⟩  }
```

And here is the original definition of `\end` the way it was in LaTeX for several decades now hidden in `\end␣`.

```
⟨latexrelease⟩\@namedef{end }#1{%
⟨latexrelease⟩  \csname end#1\endcsname\@checkend{#1}%
⟨latexrelease⟩  \expandafter\endgroup\if@endpe\@doendpe\fi
⟨latexrelease⟩  \if@ignore\@ignorefalse\ignorespaces\fi}
⟨latexrelease⟩\EndIncludeInRelease
```

An here the rollback in case that is ever needed.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\begin}{Making \begin/\end robust}%
⟨latexrelease⟩\def\begin#1{%
⟨latexrelease⟩  \@ifundefined{#1}%
```

```
⟨latexrelease⟩    {\def\reserved@a{\@latex@error{Environment #1 undefined}\@eha}}%
⟨latexrelease⟩    {\def\reserved@a{\def\@currenvir{#1}%
⟨latexrelease⟩     \edef\@currenvline{\on@line}%
⟨latexrelease⟩     \csname #1\endcsname}}%
⟨latexrelease⟩  \@ignorefalse
⟨latexrelease⟩  \begingroup\@endpefalse\reserved@a}
⟨latexrelease⟩\def\end#1{%
⟨latexrelease⟩  \csname end#1\endcsname\@checkend{#1}%
⟨latexrelease⟩  \expandafter\endgroup\if@endpe\@doendpe\fi
⟨latexrelease⟩  \if@ignore\@ignorefalse\ignorespaces\fi}
⟨latexrelease⟩
```

Also undo the internal commands as some packages unfortunately test for their existence instead of using `\IfFormatAtLeastTF`.

```
⟨latexrelease⟩\expandafter\let\csname begin \endcsname\@undefined
⟨latexrelease⟩\expandafter\let\csname end \endcsname\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\begin` *and* `\end`.)

`\@checkend`

```
\def\@checkend#1{\def\reserved@a{#1}\ifx
      \reserved@a\@currenvir \else\@badend{#1}\fi}
```

(*End definition for* `\@checkend`.)

`\@currenvline` We do need a default value for `\@currenvline` on top-level since the document environment cancels the brace group. This means that a mismatch with `\begin{document}` will not produce a line number. Thus the outer default must be `\@empty` or we will end up with two spaces.

```
\let\@currenvline\@empty
```

(*End definition for* `\@currenvline`.)

`\AtBeginEnvironment`
`\AtEndEnvironment`
`\BeforeBeginEnvironment`
`\AfterEndEnvironment`

We provide 4 high-level hook interfaces directly, the others only when etoolbox is loaded

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\AtBeginEnvironment}{Hooks for environments}%
```

```
\newcommand\AtBeginEnvironment[2][.]     {\AddToHook{env/#2/begin}[#1]}
\newcommand\AtEndEnvironment[2][.]       {\AddToHook{env/#2/end}[#1]}
\newcommand\BeforeBeginEnvironment[2][.]{\AddToHook{env/#2/before}[#1]}
\newcommand\AfterEndEnvironment[2][.]    {\AddToHook{env/#2/after}[#1]}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\AtBeginEnvironment}{Hooks for environments}%
⟨latexrelease⟩
⟨latexrelease⟩\let\AtBeginEnvironment\@undefined
⟨latexrelease⟩\let\AtEndEnvironment\@undefined
⟨latexrelease⟩\let\BeforeBeginEnvironment\@undefined
```

```
⟨latexrelease⟩\let\AfterEndEnvironment\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\AtBeginEnvironment` *and others. These functions are documented on page* 200.)

1.2 Center, Flushright, Flushleft

```
\message{center,}
```

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\center, \flushright and \flushleft set
  \rightskip = 0pt or \@flushglue (as appropriate)
  \leftskip  = 0pt or \@flushglue (as appropriate)
  \parindent = 0pt
  \parfillskip   = 0pt. (except \flushleft)
  \\          == \par \vskip -\parskip
  \\[LENGTH] == \\ \vskip LENGTH
  \\*         == \par \penalty 10000 \vskip -\parskip
  \\*[LEN]    == \\* \vskip LENGTH

They invoke the trivlist environment to handle vertical spacing before
and after them.

\centering, \raggedright and \raggedleft are the declaration analogs
of the above.

\raggedright has a more universal effect, however.  It sets
\@rightskip := flushglue.  Every environment, like the list
environments,
that set \rightskip to its 'normal' value set it to \@rightskip
```

End of historical LaTeX 2.09 comments.

`\@centercr`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                  {\@centercr}{Make robust}%
\protected\def\@centercr{\ifhmode \unskip\else \@nolnerr\fi
       \par\@ifstar{\nobreak\@xcentercr}\@xcentercr}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@centercr}{Make robust}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@centercr{\ifhmode \unskip\else \@nolnerr\fi
⟨latexrelease⟩       \par\@ifstar{\nobreak\@xcentercr}\@xcentercr}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@centercr`.)

`\@xcentercr`

```
\def\@xcentercr{\addvspace{-\parskip}\@ifnextchar
    [\@icentercr\ignorespaces}
```

(*End definition for* `\@xcentercr`.)

`\@icentercr`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@icentercr}{centering, etc support calc}%
\def\@icentercr[#1]{\@vspace@calcify{#1}\ignorespaces}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@icentercr}{centering, etc support calc}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@icentercr[#1]{\vskip #1\ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@icentercr`.)

`center` (*env.*) We use `\relax` to prevent `\item` scanning too far.

```
\def\center{\trivlist \centering\item\relax}
```

```
\def\endcenter{\endtrivlist}
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\centering}{Set finaldhypendemerits}%
```

`\centering`

```
\DeclareRobustCommand\centering{%
  \let\\\@centercr
  \rightskip\@flushglue\leftskip\@flushglue
  \finalhyphendemerits=\z@
  \parindent\z@\parfillskip\z@skip}
```

(*End definition for* `\centering`.)

`\raggedright`

```
\DeclareRobustCommand\raggedright{%
  \let\\\@centercr\@rightskip\@flushglue \rightskip\@rightskip
  \finalhyphendemerits=\z@
  \leftskip\z@skip
  \parindent\z@}
```

(*End definition for* `\raggedright`.)

\raggedleft

```
\DeclareRobustCommand\raggedleft{%
  \let\\\@centercr
  \rightskip\z@skip\leftskip\@flushglue
  \finalhyphendemerits=\z@
  \parindent\z@\parfillskip\z@skip}
```

(*End definition for* \raggedleft.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                 {\centering}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\centering{%
⟨latexrelease⟩  \let\\\@centercr
⟨latexrelease⟩  \rightskip\@flushglue\leftskip\@flushglue
⟨latexrelease⟩  \parindent\z@\parfillskip\z@skip}
⟨latexrelease⟩\DeclareRobustCommand\raggedright{%
⟨latexrelease⟩  \let\\\@centercr\@rightskip\@flushglue \rightskip\@rightskip
⟨latexrelease⟩  \leftskip\z@skip
⟨latexrelease⟩  \parindent\z@}
⟨latexrelease⟩\DeclareRobustCommand\raggedleft{%
⟨latexrelease⟩  \let\\\@centercr
⟨latexrelease⟩  \rightskip\z@skip\leftskip\@flushglue
⟨latexrelease⟩  \parindent\z@\parfillskip\z@skip}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\centering}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\centering
⟨latexrelease⟩\kernel@make@fragile\raggedright
⟨latexrelease⟩\kernel@make@fragile\raggedleft
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\@rightskip

```
\newskip\@rightskip \@rightskip \z@skip
```

(*End definition for* \@rightskip.)

flushleft (*env.*) We use \relax to prevent \item scanning too far.

```
\def\flushleft{\trivlist \raggedright\item\relax}
\def\endflushleft{\endtrivlist}
```

flushright (*env.*) We use \relax to prevent \item scanning too far.

```
\def\flushright{\trivlist \raggedleft\item\relax}
\def\endflushright{\endtrivlist}
```

1.3 Verbatim

```
\message{verbatim,}
```

The verbatim environment uses the fixed-width `\ttfamily` font, turns blanks into spaces, starts a new line for each carriage return (or sequence of consecutive carriage returns), and interprets *every* character literally. I.e., all special characters `\, {, $`, etc. are `\catcode`'d to 'other'.

The command `\verb` produces in-line verbatim text, where the argument is delimited by any pair of characters. E.g., `\verb #...#` takes '`...`' as its argument, and sets it verbatim in `\ttfamily` font.

The *-variants of these commands are the same, except that spaces print as the TEXbook's space character instead of as blank spaces.

`\@vobeyspaces`

```
{\catcode`\ =\active%
\gdef\@vobeyspaces{\catcode`\ \active\let \@xobeysp}}
```

(*End definition for* `\@vobeyspaces`.)

`\@xobeysp`

(*End definition for* `\@xobeysp`.)

`\@xverbatim`
`\@sxverbatim`

```
\begingroup \catcode `|=0 \catcode `[= 1
\catcode`]=2 \catcode `\{=12 \catcode `\}=12
\catcode`\\=12 |gdef|@xverbatim#1\end{verbatim}[#1|end[verbatim]]
|gdef|@sxverbatim#1\end{verbatim*}[#1|end[verbatim*]]
|endgroup
```

(*End definition for* `\@xverbatim` *and* `\@sxverbatim`.)

`\@verbatim` Real start of verbatim environment We use `\relax` to prevent `\item` scanning too far.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2017-04-15}{\@verbatim}%
⟨latexrelease⟩                  {Disable hyphenation in verbatim}%
\def\@verbatim{\trivlist \item\relax
  \if@minipage\else\vskip\parskip\fi
  \leftskip\@totalleftmargin\rightskip\z@skip
  \parindent\z@\parfillskip\@flushglue\parskip\z@skip
```

Added `\@@par` to clear possible `\parshape` definition from a surrounding list (the verbatim guru says). Switch language when in vertical mode.

```
  \@@par
```

Set `\language` here to suppress hyphenation. Done this way rather than setting `\hyphenchar` as that is a global setting.

```
  \language\l@nohyphenation
  \@tempswafalse
  \def\par{%
    \if@tempswa
```

A \leavevmode added: needed if, for example, a blank verbatim line is the first thing in a list item (wow!).

```
      \leavevmode \null \@@par\penalty\interlinepenalty
    \else
      \@tempswatrue
      \ifhmode\@@par\penalty\interlinepenalty\fi
    \fi}%
```

To allow customization we hide the font used in a separate macro.

```
  \let\do\@makeother \dospecials
  \obeylines \verbatim@font \@noligs
```

To avoid a breakpoint after the labels box, we remove the penalty put there by the list macros: another use of \unpenalty!

```
  \everypar \expandafter{\the\everypar \unpenalty}%
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}{\@verbatim}%
⟨latexrelease⟩                 {Disable hyphenation in verbatim}%
⟨latexrelease⟩\def\@verbatim{\trivlist \item\relax
⟨latexrelease⟩  \if@minipage\else\vskip\parskip\fi
⟨latexrelease⟩  \leftskip\@totalleftmargin\rightskip\z@skip
⟨latexrelease⟩  \parindent\z@\parfillskip\@flushglue\parskip\z@skip
⟨latexrelease⟩  \@@par
⟨latexrelease⟩  \@tempswafalse
⟨latexrelease⟩  \def\par{%
⟨latexrelease⟩    \if@tempswa
⟨latexrelease⟩      \leavevmode \null \@@par\penalty\interlinepenalty
⟨latexrelease⟩    \else
⟨latexrelease⟩      \@tempswatrue
⟨latexrelease⟩      \ifhmode\@@par\penalty\interlinepenalty\fi
⟨latexrelease⟩    \fi}%
⟨latexrelease⟩  \let\do\@makeother \dospecials
⟨latexrelease⟩  \obeylines \verbatim@font \@noligs
⟨latexrelease⟩  \hyphenchar\font\m@ne
⟨latexrelease⟩  \everypar \expandafter{\the\everypar \unpenalty}%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \@verbatim.)

verbatim \verbatim (RmS 93/09/19) Protected against 'missing item' error message triggered by empty verbatim environment.
\endverbatim

```
\def\verbatim{\@verbatim \frenchspacing\@vobeyspaces \@xverbatim}
\def\endverbatim{\if@newlist \leavevmode\fi\endtrivlist}
```

(*End definition for* \verbatim *and* \endverbatim.)

\verbatim@font Macro to select the font used for verbatim typesetting. It also does other work if necessary for the font used.

```
\def\verbatim@font{\normalfont\ttfamily}
```

(*End definition for* `\verbatim@font`.)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                  {\verbvisiblespace}{Setup visible space for \verb}%
```

`\asciispace` The character in slot 32, in typewriter fonts (historically) a visible space but in other fonts a real space or something else

```
\DeclareRobustCommand\asciispace{\char 32 }
```

(*End definition for* `\asciispace`.)

`\verbvisiblespace` This defines how to get a visible space in `\verb*` and friends. In classic TEX this is just the slot 32, but in TU encoded fonts we switch fonts and take the character from cmtt.

```
\ifx\Umathcode\@undefined
  \let\verbvisiblespace\asciispace                                % Pdftex version
\else
  \DeclareRobustCommand\verbvisiblespace
           {\leavevmode{\usefont{OT1}{cmtt}{m}{n}\asciispace}}    % xetex/luatex version
\fi
```

(*End definition for* `\verbvisiblespace`.)

`\@setupverbvisiblespace` In pdfTEX a catcode 12 space will produce the character in slot 32 which is assumed to be a visible space character (in a typewriter font in OT1 or T1 encoding). In XeTEX or LuaTEX a font in TU encoding is normally used and that has a real space in this slot. So what we do in this case is this: we check the definition of `\verbvisiblespace` and if it is `\asciispace` we assume that the char32 can be used (e.g., in pdfTEX). We then redefine `\@xobeysp` so that after running `\@vobeyspaces` we get characters from slot 32 for each active space.

```
\def\@setupverbvisiblespace{%
  \ifx\verbvisiblespace\asciispace
    \let\@xobeysp\asciispace
  \else
```

Otherwise we measure the width of a character in the mon-spaced current font and place a `\verbvisiblespace` into a box of the right width which we are then using as the character for a space. By default this will be the space character from OT1 cmtt but by changing `\verbvisiblespace` one could use, for example, the `\textvisiblespace` of the current typewriter font.

```
    \setbox\z@\hbox{x}%
    \setbox\@verbvisiblespacebox\hbox to\wd\z@{\hss\verbvisiblespace\hss}%
    \def\@xobeysp{\leavevmode\copy\@verbvisiblespacebox}%
  \fi
}
```

(*End definition for* `\@setupverbvisiblespace`.)

`\@verbvisiblespacebox` The box to hold the visible space character if it isn't in slot 32 in the current typewriter font.

```
\newbox\@verbvisiblespacebox
```

(*End definition for* `\@verbvisiblespacebox`.)

`verbatim*` (*env.*) For `verbatim*` we also set up the correct visible space character definition and then run `\@vobeyspaces`. As this code is not called as part of the normal verbatim environment (the method is done the other way around this time) we don't have to check if space is already active—it shouldn't be.

```
\@namedef{verbatim*}{\@verbatim
  \@setupverbvisiblespace
  \frenchspacing\@vobeyspaces\@sxverbatim}
\expandafter\let\csname endverbatim*\endcsname =\endverbatim
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\verbvisiblespace}{Setup visible space for \verb}%
⟨latexrelease⟩
⟨latexrelease⟩\@namedef{verbatim*}{\@verbatim\@sxverbatim}
⟨latexrelease⟩
⟨latexrelease⟩\let\asciispace            \@undefined
⟨latexrelease⟩\let\verbvisiblespace      \@undefined
⟨latexrelease⟩\let\@setupverbvisiblespace\@undefined
⟨latexrelease⟩\let\@verbvisiblespacebox  \@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\@sverb` `\@@sverb` Definitions of `\@sverb` and `\@verb` changed so `\verb+ foo+` does not lose leading blanks when it comes at the beginning of a line. Change made 24 May 89. Suggested by Frank Mittelbach and Rainer Schöpf.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\@sverb}{Drop spaces before \verb delimiter}%
```

If the users types `\verb !~! foo` then surprisingly we would get the space as the delimiter and thus "`!~!foo`" in the output. To avoid this scenario we check if `#1` has the character code of a space, if so we recurse otherwise we call `\@@sverb` (which is the original definition of `\@sverb`.

```
\def\@sverb#1{\if\noexpand#1 \expandafter\@sverb\else\@@sverb{#1}\fi}
```

```
\def\@@sverb#1{%
  \catcode`#1\active
  \lccode`\~`#1%
  \gdef\verb@balance@group{\verb@egroup
     \@latex@error{\noexpand\verb illegal in argument}\@ehc}%
  \aftergroup\verb@balance@group
  \lowercase{\let~\verb@egroup}%
```

If `\@sverb` is called from `\@verb` then space is already active and supposed to produce a real space. In this case we do nothing. Otherwise we run `\@setupverbvisiblespace` to setup the right visible space char and afterwards `\@vobeyspaces` to make it the definition for the active space character.

```
  \ifnum\catcode`\ =\active
  \else  \@setupverbvisiblespace \@vobeyspaces \fi
}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                 {\@sverb}{Setup visible space for \verb}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@sverb#1{%
⟨latexrelease⟩  \catcode`#1\active
⟨latexrelease⟩  \lccode`\~`#1%
⟨latexrelease⟩  \gdef\verb@balance@group{\verb@egroup
⟨latexrelease⟩     \@latex@error{\noexpand\verb illegal in command argument}\@ehc}%
⟨latexrelease⟩  \aftergroup\verb@balance@group
⟨latexrelease⟩  \lowercase{\let~\verb@egroup}%
⟨latexrelease⟩  \ifnum\catcode`\ =\active
⟨latexrelease⟩  \else  \@setupverbvisiblespace \@vobeyspaces \fi
⟨latexrelease⟩}
⟨latexrelease⟩\let\@@sverb\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@sverb}{Setup visible space for \verb}%
⟨latexrelease⟩\def\@sverb#1{%
⟨latexrelease⟩  \catcode`#1\active
⟨latexrelease⟩  \lccode`\~`#1%
⟨latexrelease⟩  \gdef\verb@balance@group{\verb@egroup
⟨latexrelease⟩     \@latex@error{\noexpand\verb illegal in command argument}\@ehc}%
⟨latexrelease⟩  \aftergroup\verb@balance@group
⟨latexrelease⟩  \lowercase{\let~\verb@egroup}}%
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@sverb` *and* `\@@sverb`.)

`\@makeother`

```
\def\@makeother#1{\catcode`#112\relax}
```

(*End definition for* `\@makeother`.)

`\verb@balance@group`

```
\let\verb@balance@group\@empty
```

(*End definition for* `\verb@balance@group`.)

`\verb@egroup`

```
\def\verb@egroup{\global\let\verb@balance@group\@empty\egroup}
```

(*End definition for* `\verb@egroup`.)

`\verb@eol@error`

```
\begingroup
  \obeylines%
  \gdef\verb@eol@error{\obeylines%
    \def^^M{\verb@egroup\@latex@error{%
            \noexpand\verb ended by end of line}\@ehc}}%
\endgroup
```

(*End definition for* `\verb@eol@error`.)

`\verb` Typesetting a small piece verbatim.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2017-04-15}{\verb}%
⟨latexrelease⟩                  {Disable hyphenation in verb}%
\def\verb{\relax\ifmmode\hbox\else\leavevmode\null\fi
  \bgroup
    \verb@eol@error \let\do\@makeother \dospecials
    \verbatim@font\@noligs
```

Set `\language` here to suppress hyphenation. Done this way rather than setting `\hyphenchar` as that is a global setting.

```
    \language\l@nohyphenation
    \@ifstar\@sverb\@verb}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}{\verb}%
⟨latexrelease⟩                  {Disable hyphenation in verb}%
⟨latexrelease⟩\def\verb{\relax\ifmmode\hbox\else\leavevmode\null\fi
⟨latexrelease⟩  \bgroup
⟨latexrelease⟩    \verb@eol@error \let\do\@makeother \dospecials
⟨latexrelease⟩    \verbatim@font\@noligs
⟨latexrelease⟩    \@ifstar\@sverb\@verb}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\verb`.)

`\@verb`

```
\def\@verb{\@vobeyspaces \frenchspacing \@sverb}
```

(*End definition for* `\@verb`.)

`\verbatim@nolig@list`

```
\def\verbatim@nolig@list{\do\`\do\<\do\>\do\,\do\'\do\-}
```

(*End definition for* `\verbatim@nolig@list`.)

`\do@noligs`

```
\def\do@noligs#1{%
  \catcode`#1\active
  \begingroup
     \lccode`\~`#1\relax
     \lowercase{\endgroup\def~{\leavevmode\kern\z@\char`#1}}}
```

(*End definition for* `\do@noligs`.)

`\@noligs` To stay compatible with packages that use `\@noligs` we keep it.

```
\def\@noligs{\let\do\do@noligs \verbatim@nolig@list}
```

(*End definition for* `\@noligs`.)

```
⟨/2ekernel⟩
```

File I
ltmath.dtx

1 Math setup

This file contains a lot of the original plain TEX code, as well as the LATEX environments for math. It still needs sorting out.

```
⟨*2ekernel⟩
\message{math definitions,}
```

1.1 Math commands based on plain TEX

1.1.1 The log-like functions

\log The standard operators:

```
\DeclareRobustCommand\log{\mathop{\operator@font log}\nolimits}
\DeclareRobustCommand\lg{\mathop{\operator@font lg}\nolimits}
\DeclareRobustCommand\ln{\mathop{\operator@font ln}\nolimits}
\DeclareRobustCommand\lim{\mathop{\operator@font lim}}
\DeclareRobustCommand\limsup{\mathop{\operator@font lim\,sup}}
\DeclareRobustCommand\liminf{\mathop{\operator@font lim\,inf}}
\DeclareRobustCommand\sin{\mathop{\operator@font sin}\nolimits}
\DeclareRobustCommand\arcsin{\mathop{\operator@font arcsin}\nolimits}
\DeclareRobustCommand\sinh{\mathop{\operator@font sinh}\nolimits}
\DeclareRobustCommand\cos{\mathop{\operator@font cos}\nolimits}
\DeclareRobustCommand\arccos{\mathop{\operator@font arccos}\nolimits}
\DeclareRobustCommand\cosh{\mathop{\operator@font cosh}\nolimits}
\DeclareRobustCommand\tan{\mathop{\operator@font tan}\nolimits}
\DeclareRobustCommand\arctan{\mathop{\operator@font arctan}\nolimits}
\DeclareRobustCommand\tanh{\mathop{\operator@font tanh}\nolimits}
\DeclareRobustCommand\cot{\mathop{\operator@font cot}\nolimits}
\DeclareRobustCommand\coth{\mathop{\operator@font coth}\nolimits}
\DeclareRobustCommand\sec{\mathop{\operator@font sec}\nolimits}
\DeclareRobustCommand\csc{\mathop{\operator@font csc}\nolimits}
\DeclareRobustCommand\max{\mathop{\operator@font max}}
\DeclareRobustCommand\min{\mathop{\operator@font min}}
\DeclareRobustCommand\sup{\mathop{\operator@font sup}}
\DeclareRobustCommand\inf{\mathop{\operator@font inf}}
\DeclareRobustCommand\arg{\mathop{\operator@font arg}\nolimits}
\DeclareRobustCommand\ker{\mathop{\operator@font ker}\nolimits}
\DeclareRobustCommand\dim{\mathop{\operator@font dim}\nolimits}
\DeclareRobustCommand\hom{\mathop{\operator@font hom}\nolimits}
\DeclareRobustCommand\det{\mathop{\operator@font det}}
\DeclareRobustCommand\exp{\mathop{\operator@font exp}\nolimits}
\DeclareRobustCommand\Pr{\mathop{\operator@font Pr}}
\DeclareRobustCommand\gcd{\mathop{\operator@font gcd}}
\DeclareRobustCommand\deg{\mathop{\operator@font deg}\nolimits}
```

(*End definition for* `\log`.)

\bmod And some operators have to be done by hand:

```
\DeclareRobustCommand\bmod{%
  \nonscript\mskip-\medmuskip\mkern5mu%
  \mathbin{\operator@font mod}\penalty900\mkern5mu%
  \nonscript\mskip-\medmuskip}
```

(*End definition for* `\bmod`.)

`\pmod`

```
\DeclareRobustCommand\pmod[1]{%
  \allowbreak\mkern18mu({\operator@font mod}\,\,#1)}
```

(*End definition for* `\pmod`.)

1.1.2 Biggggg

`\big` Variants on `\big` and friends for use with delimiters:

```
\DeclareRobustCommand\bigl{\mathopen\big}
\DeclareRobustCommand\bigm{\mathrel\big}
\DeclareRobustCommand\bigr{\mathclose\big}
\DeclareRobustCommand\Bigl{\mathopen\Big}
\DeclareRobustCommand\Bigm{\mathrel\Big}
\DeclareRobustCommand\Bigr{\mathclose\Big}
\DeclareRobustCommand\biggl{\mathopen\bigg}
\DeclareRobustCommand\biggm{\mathrel\bigg}
\DeclareRobustCommand\biggr{\mathclose\bigg}
\DeclareRobustCommand\Biggl{\mathopen\Bigg}
\DeclareRobustCommand\Biggm{\mathrel\Bigg}
\DeclareRobustCommand\Biggr{\mathclose\Bigg}
```

(*End definition for* `\big`.)

1.1.3 The UNSORTED Rest

The other math commands are lifted from plain TEX.

`\jot`

```
\newdimen\jot
\jot=3pt
```

(*End definition for* `\jot`.)

`\interdisplaylinepenalty`

```
\newcount\interdisplaylinepenalty
\interdisplaylinepenalty=100
```

(*End definition for* `\interdisplaylinepenalty`.)

`\choose`

```
\def\choose{\atopwithdelims()}
```

(*End definition for* `\choose`.)

`\brack`

```
\def\brack{\atopwithdelims[]}
```

(*End definition for* `\brack`.)

\brace

```
\def\brace{\atopwithdelims\{\}}
```

(*End definition for* \brace.)

\mathpalette

```
\def\mathpalette#1#2{%
  \mathchoice
    {#1\displaystyle{#2}}%
    {#1\textstyle{#2}}%
    {#1\scriptstyle{#2}}%
    {#1\scriptscriptstyle{#2}}}
```

(*End definition for* \mathpalette.)

\root
\rootbox
\r@@t

```
\newbox\rootbox
\def\root#1\of{%
  \setbox\rootbox\hbox{$\m@th\scriptscriptstyle{#1}$}%
  \mathpalette\r@@t}
\def\r@@t#1#2{%
  \setbox\z@\hbox{$\m@th#1\sqrtsign{#2}$}%
  \dimen@\ht\z@ \advance\dimen@-\dp\z@
  \mkern5mu\raise.6\dimen@\copy\rootbox
  \mkern-10mu\box\z@}
```

(*End definition for* \root, \rootbox, *and* \r@@t.)

\phantom
\hphantom
\vphantom

```
\newif\ifv@
\newif\ifh@
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\vphantom}{Make commands robust}%
\DeclareRobustCommand\vphantom{\v@true\h@false\ph@nt}
\DeclareRobustCommand\hphantom{\v@false\h@true\ph@nt}
\DeclareRobustCommand\phantom{\v@true\h@true\ph@nt}
```

\mathstrut

```
\DeclareRobustCommand\mathstrut{\vphantom(}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\vphantom}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\vphantom
⟨latexrelease⟩\kernel@make@fragile\hphantom
⟨latexrelease⟩\kernel@make@fragile\phantom
⟨latexrelease⟩\kernel@make@fragile\mathstrut
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\def\ph@nt{%
  \ifmmode
    \expandafter\mathpalette\expandafter\mathph@nt
  \else
    \expandafter\makeph@nt
  \fi}
\def\makeph@nt#1{%
  \setbox\z@\hbox{\color@begingroup#1\color@endgroup}\finph@nt}
\def\mathph@nt#1#2{%
  \setbox\z@\hbox{$\m@th#1{#2}$}\finph@nt}
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                  {\finph@nt}{Start LR-mode}%
\def\finph@nt{%
  \setbox\tw@\null
  \ifv@ \ht\tw@\ht\z@ \dp\tw@\dp\z@\fi
  \ifh@ \wd\tw@\wd\z@\fi

  \leavevmode@ifvmode\box\tw@}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\finph@nt}{Start LR-mode}%
⟨latexrelease⟩\def\finph@nt{%
⟨latexrelease⟩  \setbox\tw@\null
⟨latexrelease⟩  \ifv@ \ht\tw@\ht\z@ \dp\tw@\dp\z@\fi
⟨latexrelease⟩  \ifh@ \wd\tw@\wd\z@\fi \box\tw@}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\phantom` *and others.*)

`\smash`

```
\DeclareRobustCommand\smash{%
  \relax % \relax, in case this comes first in \halign
  \ifmmode
    \expandafter\mathpalette\expandafter\mathsm@sh
  \else
    \expandafter\makesm@sh
  \fi}
\def\makesm@sh#1{%
  \setbox\z@\hbox{\color@begingroup#1\color@endgroup}\finsm@sh}
\def\mathsm@sh#1#2{%
  \setbox\z@\hbox{$\m@th#1{#2}$}\finsm@sh}

⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                  {\finsm@sh}{Start LR-mode}%
\def\finsm@sh{\ht\z@\z@ \dp\z@\z@ \leavevmode@ifvmode\box\z@}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\finsm@sh}{Start LR-mode}%
⟨latexrelease⟩\def\finsm@sh{\ht\z@\z@ \dp\z@\z@ \box\z@}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\smash`.)

`\buildrel`

```
\def\buildrel#1\over#2{\mathrel{\mathop{\kern\z@#2}\limits^{#1}}}
```

(*End definition for* `\buildrel`.)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\cases}{Make commands robust}%
```

`\cases`

```
\DeclareRobustCommand*\cases[1]{\left\{\,\vcenter{\normalbaselines\m@th
    \ialign{$##\hfil$&\quad{##}\hfil\crcr#1\crcr}}\right.}
```

(*End definition for* `\cases`.)

`\matrix`

```
\DeclareRobustCommand*\matrix[1]{\null\,\vcenter{\normalbaselines\m@th
    \ialign{\hfil$##$\hfil&&\quad\hfil$##$\hfil\crcr
      \mathstrut\crcr\noalign{\kern-\baselineskip}
      #1\crcr\mathstrut\crcr\noalign{\kern-\baselineskip}}}\,}
```

(*End definition for* `\matrix`.)

`\pmatrix`

```
\DeclareRobustCommand*\pmatrix[1]{\left(\matrix{#1}\right)}
```

(*End definition for* `\pmatrix`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\cases}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\cases
⟨latexrelease⟩\kernel@make@fragile\matrix
⟨latexrelease⟩\kernel@make@fragile\pmatrix
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\bordermatrix`

```
\def\bordermatrix#1{\begingroup \m@th
  \@tempdima 8.75\p@
  \setbox\z@\vbox{%
    \def\cr{\crcr\noalign{\kern2\p@\global\let\cr\endline}}%
    \ialign{$##$\hfil\kern2\p@\kern\@tempdima&\thinspace\hfil$##$\hfil
      &&\quad\hfil$##$\hfil\crcr
```

```
      \omit\strut\hfil\crcr\noalign{\kern-\baselineskip}%
      #1\crcr\omit\strut\cr}}%
  \setbox\tw@\vbox{\unvcopy\z@\global\setbox\@ne\lastbox}%
  \setbox\tw@\hbox{\unhbox\@ne\unskip\global\setbox\@ne\lastbox}%
  \setbox\tw@\hbox{$\kern\wd\@ne\kern-\@tempdima\left(\kern-\wd\@ne
    \global\setbox\@ne\vbox{\box\@ne\kern2\p@}%
    \vcenter{\kern-\ht\@ne\unvbox\z@\kern-\baselineskip}\,\right)$}%
  \null\;\vbox{\kern\ht\@ne\box\tw@}\endgroup}
```

(*End definition for* `\bordermatrix`.)

`\openup`

```
\protected\def\openup{\afterassignment\@penup\dimen@}
```

```
\def\@penup{\advance\lineskip\dimen@
  \advance\baselineskip\dimen@
  \advance\lineskiplimit\dimen@}
```

(*End definition for* `\openup`.)

`\displaylines`

```
\newif\ifdt@p
```

```
\def\displ@y{\global\dt@ptrue\openup\jot\m@th
  \everycr{\noalign{\ifdt@p \global\dt@pfalse \ifdim\prevdepth>-1000\p@
      \vskip-\lineskiplimit \vskip\normallineskiplimit \fi
      \else \penalty\interdisplaylinepenalty \fi}}}
```

```
\def\@lign{\tabskip\z@skip\everycr{}} % restore inside \displ@y
```

```
\def\displaylines#1{\displ@y \tabskip\z@skip
  \halign{\hb@xt@\displaywidth{$\@lign\hfil\displaystyle##\hfil$}\crcr
    #1\crcr}}
```

(*End definition for* `\displaylines`.)

`\sp`
`\sb`

```
\let\sp=^
\let\sb=_
```

(*End definition for* `\sp` *and* `\sb`.)

`\tmspace`
`\ `
`\thinspace`
`\!`
`\negthinspace`
`\:`
`\medspace`
`\negmedspace`
`\;`
`\thickspace`
`\negthickspace`

Originally LaTeX only provided a small set of spacing commands for use in text and math, some of the commands like `\;` were only supported in math mode. `amsmath` normalized and provided all of them in text and math. This code has now been moved to the kernel so that it is generally available.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                    {\tmspace}{amsmath spacing commands}%
```

`\tmspace` is really meant to be an internal command so it doesn't necessarily has to be robust but it was robust in `amsmath` so we leave it like that.

```
\DeclareRobustCommand\tmspace[3]{%
  \ifmmode\mskip#1#2\else\leavevmode@ifvmode\kern#1#3\fi\relax}
```

In amsmath the text kern is .1667em. For compatibility reasons we keep the longer one.

```
\DeclareRobustCommand\,{\tmspace+\thinmuskip{.16667em}}
\let\thinspace\,
\DeclareRobustCommand\!{\tmspace-\thinmuskip{.16667em}}
\let\negthinspace\!
\DeclareRobustCommand\:{\tmspace+\medmuskip{.2222em}}
\let\medspace\:
```

LaTeX has a second name for this in its manual:

```
\let\>=\:
\DeclareRobustCommand\negmedspace{\tmspace-\medmuskip{.2222em}}
\DeclareRobustCommand\;{\tmspace+\thickmuskip{.2777em}}
\let\thickspace\;
\DeclareRobustCommand\negthickspace{\tmspace-\thickmuskip{.2777em}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\tmspace}{amsmath spacing commands}%
⟨latexrelease⟩
⟨latexrelease⟩\let\tmspace\@undefined
⟨latexrelease⟩\DeclareRobustCommand{\,}{%
⟨latexrelease⟩   \relax\ifmmode\mskip\thinmuskip\else\thinspace\fi}
⟨latexrelease⟩\DeclareRobustCommand\thinspace{\leavevmode@ifvmode\kern .16667em }
⟨latexrelease⟩\DeclareRobustCommand\negthinspace{\leavevmode@ifvmode\kern-.16667em }
⟨latexrelease⟩\def\>{\mskip\medmuskip}
⟨latexrelease⟩\let\:=\>
⟨latexrelease⟩\def\;{\mskip\thickmuskip}
⟨latexrelease⟩\def\!{\mskip-\thinmuskip}
⟨latexrelease⟩

⟨latexrelease⟩\let\negmedspace\@undefined
⟨latexrelease⟩\let\negthickspace\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \tmspace *and others.*)

*

```
\DeclareRobustCommand\*{\discretionary{\thinspace\the\textfont2\char2}{}{}}
```

(*End definition for* *.)

\: Nickname for the medium space since \> is not available inside tabbing.

```
%\let\:=\>
```

(*End definition for* \:.)

\active@math@prime This is the definition of the active math prime.

```
\def\active@math@prime{^\bgroup\prim@s}
```

(*End definition for* \active@math@prime.)

\prime@s

```
{\catcode`\'=\active \global\let'\active@math@prime}
\def\prim@s{%
  \prime\futurelet\@let@token\pr@m@s}
\def\pr@m@s{%
  \ifx'\@let@token
    \expandafter\pr@@@s
  \else
    \ifx^\@let@token
      \expandafter\expandafter\expandafter\pr@@@t
    \else
      \egroup
    \fi
  \fi}
\def\pr@@@s#1{\prim@s}
\def\pr@@@t#1#2{#2\egroup}
```

(*End definition for* `\prime@s`.)

```
{\catcode`\_=\active \gdef_{\_}} % _ in math is
                                 % either subscript or \_
```

1.2 Math Environments

\(\) Produces `$...$` with checks that `\(` isn't used in math mode, and that `\)` is only used in math mode begun with `\(`.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\(}{Make \( robust}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\({%
  \relax\ifmmode\@badmath\else$\fi}%
\DeclareRobustCommand\){%
  \relax\ifmmode\ifinner$\else\@badmath\fi\else \@badmath\fi}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\(}{Make \( robust}%
⟨latexrelease⟩\def\({%
⟨latexrelease⟩  \relax\ifmmode\@badmath\else$\fi}%
⟨latexrelease⟩\expandafter\let\csname\string( \endcsname\@undefined
⟨latexrelease⟩\def\){%
⟨latexrelease⟩  \relax\ifmmode\ifinner$\else\@badmath\fi\else \@badmath\fi}%
⟨latexrelease⟩\expandafter\let\csname\string) \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\(` *and* `\)`.)

\[\] Produces `$$...$$` with checks that `\[` isn't used in math mode, and that `\]` is only used in display math mode (though there is no real test that this display math started with `\[` and not with `$$`).

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\[}{Make \[ robust}%
```

```
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\[{%
   \relax\ifmmode
      \@badmath
   \else
      \ifvmode
         \nointerlineskip
         \makebox[.6\linewidth]{}%
      \fi
      $$%%$$ BRACE MATCH HACK
   \fi
}%
\DeclareRobustCommand\]{%
   \relax\ifmmode
      \ifinner
         \@badmath
      \else
         $$%%$$ BRACE MATCH HACK
      \fi
   \else
      \@badmath
   \fi
   \ignorespaces
}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\[}{Make \[ robust}%
⟨latexrelease⟩\def\[{%
⟨latexrelease⟩   \relax\ifmmode
⟨latexrelease⟩      \@badmath
⟨latexrelease⟩   \else
⟨latexrelease⟩      \ifvmode
⟨latexrelease⟩         \nointerlineskip
⟨latexrelease⟩         \makebox[.6\linewidth]{}%
⟨latexrelease⟩      \fi
⟨latexrelease⟩      $$%%$$ BRACE MATCH HACK
⟨latexrelease⟩   \fi
⟨latexrelease⟩}%
⟨latexrelease⟩\expandafter\let\csname\string[ \endcsname\@undefined
⟨latexrelease⟩\def\]{%
⟨latexrelease⟩   \relax\ifmmode
⟨latexrelease⟩      \ifinner
⟨latexrelease⟩         \@badmath
⟨latexrelease⟩      \else
⟨latexrelease⟩         $$%%$$ BRACE MATCH HACK
⟨latexrelease⟩      \fi
⟨latexrelease⟩   \else
⟨latexrelease⟩      \@badmath
⟨latexrelease⟩   \fi
⟨latexrelease⟩   \ignorespaces
⟨latexrelease⟩}%
⟨latexrelease⟩\expandafter\let\csname\string] \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨*2ekernel⟩
```

(*End definition for* `\[` *and* `\]`.)

`math` (*env.*)
`displaymath` (*env.*)

Disguises for `\(...\)` and `\[...\]`.

```
\let\math=\(
\let\endmath=\)
\def\displaymath{\[}
\def\enddisplaymath{\]\@ignoretrue}
```

`equation` (*env.*)
`\c@equation`

Numbered equations, using the counter `\c@equation`. *Note*: The document style must define `\theequation` etc., and do the appropriate `\@addtoreset`. It should also redefine `\@eqnnum` if another format for the equation number is desired other than the standard (...), or to move the equation numbers to the flushleft. (See comment on the `\def` of `\@eqnnum`.)

```
\@definecounter{equation}
\def\equation{$$\refstepcounter{equation}}
\def\endequation{\eqno \hbox{\@eqnnum}$$\@ignoretrue}
```

(*End definition for* `\c@equation`.)

`\@eqnnum`

Produces the equation number for equation and eqnarray environments. The following definition is for flushright numbers; for flushleft numbers, see leqno.clo. The equation number is set in black roman type even if an eqnarray environment appears in an italic environment.

```
\def\@eqnnum{{\normalfont \normalcolor (\theequation)}}
```

(*End definition for* `\@eqnnum`.)

`\stackrel`

A disguise for plain TEX's buildrel.

```
\DeclareRobustCommand\stackrel[2]{\mathrel{\mathop{#2}\limits^{#1}}}
```

(*End definition for* `\stackrel`.)

`\frac`

A disguise for plain TEX's `\over`.

```
\DeclareRobustCommand\frac[2]{{\begingroup#1\endgroup\over#2}}
```

(*End definition for* `\frac`.)

`\sqrt`
`\@sqrt`

Add an optional argument to plain's `\sqrt` to give the nth root of an expression $\sqrt[n]{e}$.

```
\DeclareRobustCommand\sqrt{\@ifnextchar[\@sqrt\sqrtsign}
\def\@sqrt[#1]{\root #1\of}
```

(*End definition for* `\sqrt` *and* `\@sqrt`.)

`eqnarray` (*env.*)
`\@eqcnt`
`\@eqpen`
`\if@eqnsw`
`\@eqnsel`

Here's the eqnarray environment: Default is for left-hand side of equations to be flushright. To make them flushleft, `\let\@eqnsel = \hfil`.

```
\newcount\@eqcnt
\newcount\@eqpen
\newif\if@eqnsw\@eqnswtrue
\newskip\@centering
\@centering = 0pt plus 1000pt
```

To get a proper `\@currentlabel` we have to redefine it for the whole display. Note that we can't use `\refstepcounter` as this results in `\@currentlabel` getting restored at the wrong and thus always writing the first label to the `.aux` file.

```
\def\eqnarray{%
   \stepcounter{equation}%
   \def\@currentlabel{\p@equation\theequation}%
   \def\@currentcounter{equation}%
   \global\@eqnswtrue
   \m@th
   \global\@eqcnt\z@
   \tabskip\@centering
   \let\\\@eqncr
   $$\everycr{}\halign to\displaywidth\bgroup
       \hskip\@centering$\displaystyle\tabskip\z@skip{##}$\@eqnsel
      &\global\@eqcnt\@ne\hskip \tw@\arraycolsep \hfil${##}$\hfil
      &\global\@eqcnt\tw@ \hskip \tw@\arraycolsep
         $\displaystyle{##}$\hfil\tabskip\@centering
      &\global\@eqcnt\thr@@ \hb@xt@\z@\bgroup\hss##\egroup
         \tabskip\z@skip
      \cr
}
```

```
\def\endeqnarray{%
      \@@eqncr
      \egroup
      \global\advance\c@equation\m@ne
   $$\@ignoretrue
}
```

```
\let\@eqnsel=\relax
```

(*End definition for* `\@eqcnt` *and others.*)

`\nonumber` Switches off equation numbering.

```
\def\nonumber{\global\@eqnswfalse}
```

(*End definition for* `\nonumber`.)

`\@eqncr` `\@xeqncr` `\@yeqncr`

```
\protected\def\@eqncr{%
   {\ifnum0=`}\fi
   \@ifstar{%
      \global\@eqpen\@M\@yeqncr
   }{%
      \global\@eqpen\interdisplaylinepenalty \@yeqncr
   }%
}
```

```
\def\@yeqncr{\@testopt\@xeqncr\z@skip}
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                    {\@xeqncr}{eqnarray support calc syntax}%
\def\@xeqncr[#1]{%
   \ifnum0=`{\fi}%
```

```
   \@@eqncr
   \noalign{\penalty\@eqpen\vskip\jot\@vspace@calcify{#1}}%
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@xeqncr}{eqnarray support calc syntax}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@xeqncr[#1]{%
⟨latexrelease⟩   \ifnum0=`{\fi}%
⟨latexrelease⟩   \@@eqncr
⟨latexrelease⟩   \noalign{\penalty\@eqpen\vskip\jot\vskip #1\relax}%
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@eqncr`*,* `\@xeqncr`*, and* `\@yeqncr`*.*)

`\@@eqncr`

```
\def\@@eqncr{\let\reserved@a\relax
    \ifcase\@eqcnt \def\reserved@a{& & &}\or \def\reserved@a{& &}%
     \or \def\reserved@a{&}\else
       \let\reserved@a\@empty
       \@latex@error{Too many columns in eqnarray environment}\@ehc\fi
     \reserved@a \if@eqnsw\@eqnnum\stepcounter{equation}\fi
     \global\@eqnswtrue\global\@eqcnt\z@\cr}
```

(*End definition for* `\@@eqncr`*.*)

`eqnarray*` `\@seqncr` Here's the eqnarray* environment:

```
\let\@seqncr=\@eqncr
\@namedef{eqnarray*}{\protected\def\@eqncr{\nonumber\@seqncr}\eqnarray}
\@namedef{endeqnarray*}{\nonumber\endeqnarray}
```

(*End definition for* `\@seqncr`*.*)

`\lefteqn` `\lefteqn{FORMULA}` typesets `FORMULA` in display math style flushleft in a box of width zero.

```
\def\lefteqn#1{\rlap{$\displaystyle #1$}}
```

(*End definition for* `\lefteqn`*.*)

`\ensuremath` In math mode, `\ensuremath{text}` is equivalent to text; in LR or paragraph mode, it is equivalent to `$text$`. `\relax` is not needed in front of the `\ifmmode` as `\protect` will be `\let` to `\relax`. This version (due to Donald Arseneau) avoids duplicating its argument in the 'then' and 'else' part of the `\ifmath` which is necessary in nested 'tabular' like environments. See amslatex/2104.

```
\DeclareRobustCommand{\ensuremath}{%
  \ifmmode
    \expandafter\@firstofone
  \else
    \expandafter\@ensuredmath
  \fi}
```

(*End definition for* `\ensuremath`.)

`\@ensuredmath` The `\relax` stops `\ensuremath{}` starting display math.

```
\long\def\@ensuredmath#1{$\relax#1$}
```

(*End definition for* `\@ensuredmath`.)

LuaTEX contains new math primitives to place expression over or under horizontally extensible glyphs. Before LuaTEX 1.14 these did not work correctly with the `\mathstyle` primitive and sometimes did not use cramped style in consistent ways. For newer version, we opt into the corrected behavior.

```
\ifx\mathdefaultsmode\@undefined\else
  \mathdefaultsmode=1
\fi
```

⟨/2ekernel⟩

1.3 External options to the standard document classes

1.3.1 Left equation numbering

`\@eqnnum` To put the equation number on the left side of an equation we have to use a little trick. The number is shifted `\displaywidth` to the left inside a box of (approximately) zero width. This fails when the equation is too wide, the equation number than may overprint the equation itself.

```
⟨*leqno⟩
\renewcommand\@eqnnum{\hb@xt@.01\p@{}%
                      \rlap{\normalfont\normalcolor
                        \hskip -\displaywidth(\theequation)}}
⟨/leqno⟩
```

(*End definition for* `\@eqnnum`.)

1.3.2 Flush left equations

To get the displayed math environments to print the contents flush left (with an indentation) we have to redefine all of LaTeX 2ε's displayed math environments.

`\mathindent` The amount of indentation of the equations is stored in a register.

```
⟨*fleqn⟩
\newskip\mathindent
```

The setting of `\mathindent` has to be deferred until the class file has been processed, because `\leftmargini` is still 0pt wide at the moment `fleqn.clo` is read in.

```
\AtEndOfClass{\mathindent\leftmargini}
```

(*End definition for* `\mathindent`.)

`\[` Begin display math;

```
\IncludeInRelease{2015/01/01}{\[}{Make \[ robust}%
\DeclareRobustCommand\[{\relax
                 \ifmmode\@badmath
                 \else
                   \begin{trivlist}%
                     \@beginparpenalty\predisplaypenalty
```

```
                    \@endparpenalty\postdisplaypenalty
                    \item[]\leavevmode
                    \hb@xt@\linewidth\bgroup $\m@th\displaystyle %$
                      \hskip\mathindent\bgroup
                \fi}
\EndIncludeInRelease
```

```
\IncludeInRelease{0000/00/00}{\[}{Make \[ robust}%
\renewcommand\[{\relax
                \ifmmode\@badmath
                \else
                  \begin{trivlist}%
                    \@beginparpenalty\predisplaypenalty
                    \@endparpenalty\postdisplaypenalty
                    \item[]\leavevmode
                    \hb@xt@\linewidth\bgroup $\m@th\displaystyle %$
                      \hskip\mathindent\bgroup
                \fi}
\EndIncludeInRelease
```

(*End definition for* `\[`.)

`\]` end display math;

```
\IncludeInRelease{2015/01/01}{\]}{Make \] robust}%
\DeclareRobustCommand\]{\relax
                \ifmmode
                      \egroup $\hfil% $
                    \egroup
                  \end{trivlist}%
                \else \@badmath
                \fi}
\EndIncludeInRelease
```

```
\IncludeInRelease{0000/00/00}{\]}{Make \] robust}%
\renewcommand\]{\relax
                \ifmmode
                      \egroup $\hfil% $
                    \egroup
                  \end{trivlist}%
                \else \@badmath
                \fi}
\EndIncludeInRelease
```

(*End definition for* `\]`.)

`equation` (*env.*) The equation environment

```
\renewenvironment{equation}%
    {\@beginparpenalty\predisplaypenalty
     \@endparpenalty\postdisplaypenalty
     \refstepcounter{equation}%
     \trivlist \item[]\leavevmode
       \hb@xt@\linewidth\bgroup $\m@th% $
         \displaystyle
         \hskip\mathindent}%
```

Ensure that there is at least a space between formula and equation number so that they don't bump in each other.

```
        {$\hskip .3em minus.3em\hfil % $
         \displaywidth\linewidth\hbox{\@eqnnum}%
       \egroup
     \endtrivlist}
```

`eqnarray` (*env.*) The eqnarray environment

```
\renewenvironment{eqnarray}{%
    \stepcounter{equation}%
    \def\@currentlabel{\p@equation\theequation}%
    \def\@currentcounter{equation}%
    \global\@eqnswtrue\m@th
    \global\@eqcnt\z@
    \tabskip\mathindent
    \let\\=\@eqncr
    \setlength\abovedisplayskip{\topsep}%
    \ifvmode
      \addtolength\abovedisplayskip{\partopsep}%
    \fi
```

When the documentclass uses a non-zero `\parskip` setting the `\topsep` might have a negative value to compensate for that. Therefore we add `\parskip` to `\abovedisplayskip`.

```
    \addtolength\abovedisplayskip{\parskip}%
    \setlength\belowdisplayskip{\abovedisplayskip}%
    \setlength\belowdisplayshortskip{\abovedisplayskip}%
    \setlength\abovedisplayshortskip{\abovedisplayskip}%
    $$\everycr{}\halign to\linewidth% $$
    \bgroup
      \hskip\@centering
      $\displaystyle\tabskip\z@skip{##}$\@eqnsel&%
      \global\@eqcnt\@ne \hskip \tw@\arraycolsep \hfil${##}$\hfil&%
      \global\@eqcnt\tw@ \hskip \tw@\arraycolsep
        $\displaystyle{##}$\hfil \tabskip\@centering&%
      \global\@eqcnt\thr@@
        \hb@xt@\z@\bgroup\hss##\egroup\tabskip\z@skip\cr}%
      {\@@eqncr
    \egroup
    \global\advance\c@equation\m@ne$$% $$
    \@ignoretrue
    }
⟨/fleqn⟩
```

File J
ltlists.dtx

1 List, and related environments

The generic commands for creating an indented environment – `enumerate`, `itemize`, `quote`, etc – are:

`\list{`⟨*LABEL*⟩`}{`⟨*COMMANDS*⟩`}` ... `\endlist`

which can be invoked by the user as the list environment. The LABEL argument specifies item labeling. COMMANDS contains commands for changing the horizontal and vertical spacing parameters.

Each item of the environment is begun by the command `\item[`ITEMLABEL`]` which produces an item labeled by ITEMLABEL. If the argument is missing, then the LABEL argument of the `\list` command is used as the item label.

The label is formed by putting `\makelabel{`⟨*ITEMLABEL*⟩`}` in an hbox whose width is either its natural width or else `\labelwidth`, whichever is larger. The `\list` command defines `\makelabel` to have the default definition:

`\makelabel{`⟨*ARG*⟩`}` == BEGIN `\hfil` ARG END

which, for a label of width less than `\labelwidth`, puts the label flushright, `\labelsep` to the left of the item's text. However, `\makelabel` can be `\let` to another command by the `\list`'s COMMANDS argument.

A `\usecounter{`⟨*foo*⟩`}` command in the second argument causes the counter *foo* to be initialized to zero, and stepped by every `\item` command without an argument. (`\label` commands within the list refer to this counter.)

When you leave a list environment, returning either to an enclosing list or normal text mode, LaTeX begins a new paragraph if and only if you leave a blank line after the `\end` command. This is accomplished by the `\@endparenv` command.

Blank lines are ignored every other reasonable place–i.e.:

- Between the `\begin{list}` and the first `\item`,
- Between the `\item` and the text of that item.
- Between the end of the last item and the `\end{list}`.

For an environment like quotation, in which items are not labeled, the entire environment is a single item. It is defined by letting `\quotation` == `\list{}{...}\item\relax`. (Note the `\relax`, there in case the first character in the environment is a '['.) The spacing parameters provide a great deal of flexibility in designing the format, including the ability to let the indentation of the first paragraph be different from that of the subsequent ones.

The trivlist environment is equivalent to a list environment whose second argument sets the following parameter values:

`\leftmargin` = **0:** causes no indentation of left margin

`\labelwidth` = **0:** see below for precise effect this has.

\itemindent = 0: with a null label, makes first paragraph have no indentation. Succeeding paragraphs have \parindent indentation. To give first paragraph same indentation, set \itemindent = \parindent before the \item[].

Every \item in a trivlist environment must have an argument—in many cases, this will be the null argument (\item[]). The trivlist environment is mainly used for paragraphing environments, like verbatim, in which there is no margin change. It provides the same vertical spacing as the list environment, and works reasonably well when it occurs immediately after an \item command in an enclosing list.

1.1 List and Trivlist

The following variables are used inside a list environment:

\@totalleftmargin The distance that the prevailing left margin is indented from the outermost left margin,

\linewidth The width of the current line. Must be initialized to \hsize.

\@listdepth A count for holding current list nesting depth.

\makelabel A macro with a single argument, used to generate the label from the argument (given or implied) of the \item command. Initialized to \@mklab by the \list command. This command must produce some stretch—i.e., an \hfil.

\@inlabel A switch that is false except between the time an \item is encountered and the time that TEX actually enters horizontal mode. Should be tested by commands that can be messed up by the list environment's use of \everypar.

\box\@labels When @inlabel = true, it holds the labels to be put out by \everypar.

@noparitem A switch set by \list when @inlabel = true. Handles the case of a \list being the first thing in an item.

@noparlist A switch set true for a list that begins an item. No \topsep space is added before or after \item's such a list.

@newlist Set true by \list, set false by the first text (by \everypar).

@noitemarg Set true when executing an \item with no explicit argument. Used to save space. To save time, make two separate \@item commands.

@nmbrlist Set true by \usecounter command, causes list to be numbered.

\@listctr \def'ed by \usecounter to name of counter.

\@noskipsec A switch set true by a sectioning command when it is creating an in-text heading with \everypar.

Throughout a list environment, \hsize is the width of the current line, measured from the outermost left margin to the outermost right margin. Environments like tabbing should use \linewidth instead of \hsize.

Here are the parameters of a list that can be set by commands in the \list's COMMANDS argument. These parameters are all TeX skips or dimensions (defined by \newskip or \newdimen), so the usual TEX or LATEX commands can be used to set them. The commands will be executed in vmode if and only if the \list was preceded by a \par (or something like an \end{list}), so the spacing parameters can be set according to whether the list is inside a paragraph or is its own paragraph.

1.2 Vertical Spacing (skips)

`\topsep`: Space between first item and preceding paragraph.

`\partopsep`: Extra space added to `\topsep` when environment starts a new paragraph (is called in vmode).

`\itemsep`: Space between successive items.

`\parsep`: Space between paragraphs within an item – the `\parskip` for this environment.

1.3 Penalties

`\@beginparpenalty`: put at the beginning of a list

`\@endparpenalty`: put at end of list

`\@itempenalty`: put between items.

1.4 Horizontal Spacing (dimens)

`\leftmargin`: space between left margin of enclosing environment (or of page if top level list) and left margin of this list. Must be nonnegative.

`\rightmargin`: analogous.

`\listparindent`: extra indentation at beginning of every paragraph of a list except the one started by the `\item` command. May be negative! Usually, labeled lists have `\listparindent` equal to zero.

`\itemindent`: extra indentation added right BEFORE an item label.

`\labelwidth`: nominal width of box that contains the label. If the natural width of the label <= `\labelwidth`, then the label is flushed right inside a box of width `\labelwidth` (with an `\hfil`). Otherwise, a box of the natural width is employed, which causes an indentation of the text on that line.

`\labelsep`: space between end of label box and text of first item.

1.5 Default Values

Defaults for the list environment are set as follows. First, `\rightmargin`, `\listparindent` and `\itemindent` are set to 0pt. Then, one of the commands `\@listi`, `\@listii`, ... , `\@listvi` is called, depending upon the current level of the list. The `\@list` ... commands should be defined by the document style. A convention that the document style should follow is to set `\leftmargin` to `\leftmargini`,..., `\leftmarginvi` for the appropriate level. Items that aren't changed may be left alone, but everything that could possibly be changed must be reset. *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
\list{LABEL}{COMMANDS} ==
 BEGIN
   if \@listdepth > 5
     then LaTeX error: 'Too deeply nested'
     else \@listdepth :=G \@listdepth + 1
```

```
    fi
    \rightmargin      := 0pt
    \listparindent    := 0pt
    \itemindent       := 0pt
    \eval(@list \romannumeral\the\@listdepth)  %% Set default values:
    \@itemlabel       :=L LABEL
    \makelabel        == \@mklab
    @nmbrlist         :=L false
    COMMANDS

    \@trivlist                % commands common to \list and \trivlist

    \parskip          :=L \parsep
    \parindent        :=L \listparindent
    \linewidth        :=L \linewidth - \rightmargin -\leftmargin
    \@totalleftmargin :=L \@totalleftmargin + \leftmargin
    \parshape 1 \@totalleftmargin \linewidth
    \ignorespaces                     % gobble space up to \item
   END

\endlist == BEGIN \@listdepth :=G \@listdepth -1
                  \endtrivlist
            END

\@trivlist ==
 BEGIN
    if @newlist = T then \@noitemerr fi
                    %% This command removed for some forgotten reason.
    \@topsepadd :=L \topsep
    if @noskipsec then leave vertical mode fi  %% Added 11 Jun 85
    if vertical mode
      then \@topsepadd :=L \@topsepadd + \partopsep
      else \unskip \par             % remove glue from end of last line
    fi
    if @inlabel = true
       then @noparitem :=L true
            @noparlist :=L true
       else @noparlist :=L false
            \@topsep   :=L \@topsepadd
    fi
    \@topsep          :=L \@topsep + \parskip  %% Change 4 Sep 85
    \leftskip         :=L 0pt          % Restore paragraphing parameters
    \rightskip        :=L \@rightskip
    \parfillskip      :=L 0pt + 1fil

  NOTE: \@setpar called on every \list in case \par has been
  temporarily  munged before the \list command.
    \@setpar{if @newlist = false then {\@@par} fi}
    \@newlist         :=G T
    \@outerparskip    :=L \parskip
```

```
END

\trivlist  ==
BEGIN
 \parsep     := \parskip
 @nmbrlist := F
 \@trivlist
 \labelwidth := 0
 \leftmargin := 0
 \itemindent := \parindent
 \@itemlabel :=L "empty"          %% added 93/12/13
 \makelabel{LABEL} == LABEL
END

\endtrivlist ==
  BEGIN
    if @inlabel = T then \indent fi
    if horizontal mode then \unskip \par fi
    if @noparlist = true
      else if \lastskip > 0
               then \@tempskipa := \lastskip
                    \vskip - \lastskip
                    \vskip \@tempskipa -\@outerparskip + \parskip
           fi
           \@endparenv
    fi
  END

\@endparenv ==
  BEGIN
   \addpenalty{@endparpenalty}
   \addvspace{\@topsepadd}
   \endgroup    %% ends the \begin command's \begingroup
   \par  ==  BEGIN
               \@restorepar
               \everypar{}
               \par
             END
   \everypar == BEGIN remove \lastbox \everypar{} END
   \begingroup  %% to match the \end commands \endgroup
  END

\item == BEGIN if math mode then WARNING fi
                 if  next char = [
                 then  \@item
                 else  @noitemarg := true
                       \@item[@itemlabel]
         END

\@item[LAB] ==
```

```
BEGIN
 if @noparitem = true
   then @noparitem := false
            % NOTE: then clause  hardly every taken,
            %  so made a macro \@donoparitem
        \box\@labels :=G \hbox{\hskip -\leftmargin
                                \box\@labels
                                \hskip \leftmargin }
        if @minipage = false then
           \@tempskipa := \lastskip
           \vskip -\lastskip
           \vskip \@tempskipa + \@outerparskip - \parskip
        fi
   else if @inlabel = true
          then \indent \par   % previous item empty.
        fi
        if hmode then 2 \unskip's
                        % To remove any space at end of prev.
                        % paragraph that could cause a blank line.
                 \par
        fi
        if @newlist = T
           then if @nobreak = T   % Kludge if list follows \section
                   then \addvspace{\@outerparskip - \parskip}
                   else \addpenalty{\@beginparpenalty}
                        \addvspace{\@topsep}
                        \addvspace{-\parskip}   %% added 4 Sep 85
                 fi
           else \addpenalty{\@itempenalty}
                \addvspace{\itemsep}
        fi
        @inlabel :=G true
 fi

 \everypar{ @minipage :=G F
            @newlist :=G F
            if  @inlabel = true
              then @inlabel :=G false
                   \hskip -\parindent
                   \box\@labels
                   \penalty 0
                         %% 3 Oct 85  – allow line break here
                   \box\@labels :=G null
            fi
            \everypar{} }
@nobreak :=G false
if  @noitemarg = true
   then @noitemarg := false
        if @nmbrlist
          then \refstepcounter{\@listctr}
```

```
  fi      fi
  \@tempboxa   :=L \hbox{\makelabel{LAB}}
  \box\@labels :=G \@labels \hskip \itemindent
                   \hskip - (\labelwidth + \labelsep)
                   if \wd \@tempboxa > \labelwidth
                      then \box\@tempboxa
                      else \hbox to \labelwidth {\unhbox\@tempboxa}
                   fi
                   \hskip\labelsep
  \ignorespaces                          %gobble space up to text
END

\makelabel{LABEL} == ERROR    %% default to catch lonely \item


\usecounter{CTR} == BEGIN   @nmbrlist :=L true
                            \@listctr == CTR
                            \setcounter{CTR}{0}
                    END
```

DEFINE `\dimen`'s and `\count`

End of historical LaTeX 2.09 comments.

`\topskip`
`\partopsep`
`\itemsep`
`\parsep`
`\@topsep`
`\@topsepadd`
`\outerparskip`

```
⟨*2ekernel⟩
\newskip\topsep
\newskip\partopsep
\newskip\itemsep
\newskip\parsep
\newskip\@topsep
\newskip\@topsepadd
\newskip\@outerparskip
```

(*End definition for* `\topskip` *and others.*)

`\leftmargin`
`\rightmargin`
`\listparindent`
`\itemindent`
`\labelwidth`
`\labelsep`
`\@totalleftmargin`

```
\newdimen\leftmargin
\newdimen\rightmargin
\newdimen\listparindent
\newdimen\itemindent
\newdimen\labelwidth
\newdimen\labelsep
\newdimen\linewidth
\newdimen\@totalleftmargin \@totalleftmargin=\z@
```

(*End definition for* `\leftmargin` *and others.*)

\leftmargini
\leftmarginii
\leftmarginiii
\leftmarginiv
\leftmarginv
\leftmarginvi

```
\newdimen\leftmargini
\newdimen\leftmarginii
\newdimen\leftmarginiii
\newdimen\leftmarginiv
\newdimen\leftmarginv
\newdimen\leftmarginvi
```

(*End definition for* `\leftmargini` *and others.*)

\@listdepth
\@itempenalty
\@beginparpenalty
\@endparpenalty

```
\newcount\@listdepth \@listdepth=0
\newcount\@itempenalty
\newcount\@beginparpenalty
\newcount\@endparpenalty
```

(*End definition for* `\@listdepth` *and others.*)

\@labels

```
\newbox\@labels
```

(*End definition for* `\@labels`.)

\if@inlabel
\@inlabelfalse
\@inlabeltrue

```
\newif\if@inlabel \@inlabelfalse
```

(*End definition for* `\if@inlabel`, `\@inlabelfalse`, *and* `\@inlabeltrue`.)

\if@newlist
\@newlistfalse
\@newlisttrue

```
\newif\if@newlist   \@newlistfalse
```

(*End definition for* `\if@newlist`, `\@newlistfalse`, *and* `\@newlisttrue`.)

\if@noparitem
\@noparitemfalse
\@noparitemtrue

```
\newif\if@noparitem \@noparitemfalse
```

(*End definition for* `\if@noparitem`, `\@noparitemfalse`, *and* `\@noparitemtrue`.)

\if@noparlist
\@noparlistfalse
\@noparlisttrue

```
\newif\if@noparlist \@noparlistfalse
```

(*End definition for* `\if@noparlist`, `\@noparlistfalse`, *and* `\@noparlisttrue`.)

\if@noitemarg
\@noitemargfalse
\@noitemargtrue

```
\newif\if@noitemarg \@noitemargfalse
```

(*End definition for* `\if@noitemarg`, `\@noitemargfalse`, *and* `\@noitemargtrue`.)

\if@newlist
\@newlistfalse
\@newlisttrue

```
\newif\if@nmbrlist  \@nmbrlistfalse
```

(*End definition for* `\if@newlist`, `\@newlistfalse`, *and* `\@newlisttrue`.)

list\list

```
\def\list#1#2{%
  \ifnum \@listdepth >5\relax
    \@toodeep
  \else
    \global\advance\@listdepth\@ne
  \fi
  \rightmargin\z@
  \listparindent\z@
  \itemindent\z@
  \csname @list\romannumeral\the\@listdepth\endcsname
  \def\@itemlabel{#1}%
  \let\makelabel\@mklab
  \@nmbrlistfalse
  #2\relax
  \@trivlist
  \parskip\parsep
  \parindent\listparindent
  \advance\linewidth -\rightmargin
  \advance\linewidth -\leftmargin
  \advance\@totalleftmargin \leftmargin
  \parshape \@ne \@totalleftmargin \linewidth
  \ignorespaces}
```

(*End definition for* `\list`.)

`\par@deathcycles`

```
\newcount\par@deathcycles
```

(*End definition for* `\par@deathcycles`.)

`\@trivlist` Because `\par` is sometimes made a no-op it is possible for a missing `\item` to produce a loop that does not fill memory and so never gets trapped by TEX. We thus need to trap this here by setting `\par` to count the number of times a paragraph ii is called with no progress being made started.

```
\def\@trivlist{%
  \if@noskipsec \leavevmode \fi
  \@topsepadd \topsep
  \ifvmode
    \advance\@topsepadd \partopsep
  \else
    \unskip \par
  \fi
  \if@inlabel
    \@noparitemtrue
    \@noparlisttrue
  \else
    \if@newlist \@noitemerr \fi
    \@noparlistfalse
    \@topsep \@topsepadd
  \fi
  \advance\@topsep \parskip
  \leftskip \z@skip
  \rightskip \@rightskip
  \parfillskip \@flushglue
```

```
  \par@deathcycles \z@
  \@setpar{\if@newlist
             \advance\par@deathcycles \@ne
             \ifnum \par@deathcycles >\@m
               \@noitemerr
               {\@@par}%
             \fi
           \else
             {\@@par}%
           \fi}%
  \global \@newlisttrue
  \@outerparskip \parskip}
```

(*End definition for* `\@trivlist`.)

`\trivlist` (*end*)

```
\def\trivlist{%
  \parsep\parskip
  \@nmbrlistfalse
  \@trivlist
  \labelwidth\z@
  \leftmargin\z@
  \itemindent\z@
```

We initialise `\@itemlabel` so that a `trivlist` with an `\item` not having an optional argument doesn't produce an error message.

```
  \let\@itemlabel\@empty
  \def\makelabel##1{##1}}
```

(*End definition for* `\trivlist`.)

`\endlist`

```
\def\endlist{%
  \global\advance\@listdepth\m@ne
  \endtrivlist}
```

(*End definition for* `\endlist`.)

The definition of `\trivlist` used to be in ltspace.dtx so that other commands could be 'let to it'. They now use `\def`.

`\endtrivlist`

```
\def\endtrivlist{%
  \if@inlabel
    \leavevmode
    \global \@inlabelfalse
  \fi
  \if@newlist
    \@noitemerr
    \global \@newlistfalse
  \fi
  \ifhmode\unskip \par
```

We also check if we are in math mode and issue an error message if so (hoping that `\@currenvir` resolves suitably). Otherwise the usual "perhaps a missing item" error will get triggered later which is confusing.

```
  \else
```

```
    \@inmatherr{\end{\@currenvir}}%
  \fi
  \if@noparlist \else
    \ifdim\lastskip >\z@
      \@tempskipa\lastskip \vskip -\lastskip
      \advance\@tempskipa\parskip \advance\@tempskipa -\@outerparskip
      \vskip\@tempskipa
    \fi
    \@endparenv
  \fi
}
```

(*End definition for* `\endtrivlist`.)

`\@endparenv` `\@doendpe`

To suppress the paragraph indentation in text immediately following a paragraph-making environment, `\everypar` is changed to remove the space, and `\par` is redefined to restore `\everypar`. Instead of redefining `\par` and `\everypar`, `\@endparenv` was changed to set the @endpe switch, letting `\end` redefine `\par` and `\everypar`.

This allows paragraph-making environments to work right when called by other environments. (Changed 27 Oct 86)

```
\def\@endparenv{%
  \addpenalty\@endparpenalty\addvspace\@topsepadd\@endpetrue}
```

```
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\@doendpe}{clubpenalty fix}%
\def\@doendpe{\@endpetrue
     \def\par{\@restorepar
```

If a section heading changes `\clubpenalty` to keep lines after it together then this modification is restored via the `\everypar` mechanism at the start of the next paragraph. As we destroy the contents of this token here we explicitly set `\clubpenalty` back to its default.

```
              \clubpenalty\@clubpenalty
              \everypar{}\par\@endpefalse}\everypar
```

Use `\setbox0=\lastbox` instead of `\hskip -\parindent` so that a `\noindent` becomes a no-op when used before a line immediately following a list environment(23 Oct 86).

```
               {{\setbox\z@\lastbox}%
                \everypar{}\@endpefalse}}
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@doendpe}{clubpenalty fix}%
⟨latexrelease⟩\def\@doendpe{\@endpetrue
⟨latexrelease⟩     \def\par{\@restorepar\everypar{}\par\@endpefalse}\everypar
⟨latexrelease⟩                {{\setbox\z@\lastbox}\everypar{}\@endpefalse}}
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\@endparenv` *and* `\@doendpe`.)

`\if@endpe` `\@endpefalse` `\@endpeltrue`

```
\newif\if@endpe
\@endpefalse
```

(*End definition for* `\if@endpe`, `\@endpefalse`, *and* `\@endpeltrue`.)

\@mklab

```
\def\@mklab#1{\hfil #1}
```

(*End definition for* \@mklab.)

\item

```
\def\item{%
  \@inmatherr\item
  \@ifnextchar [\@item{\@noitemargtrue \@item[\@itemlabel]}}
```

(*End definition for* \item.)

\@donoparitem

```
\def\@donoparitem{%
  \@noparitemfalse
  \global\setbox\@labels\hbox{\hskip -\leftmargin
                                \unhbox\@labels
                                 \hskip \leftmargin}%
  \if@minipage\else
    \@tempskipa\lastskip
    \vskip -\lastskip
    \advance\@tempskipa\@outerparskip
    \advance\@tempskipa -\parskip
    \vskip\@tempskipa
  \fi}
```

(*End definition for* \@donoparitem.)

\@item

```
\def\@item[#1]{%
  \if@noparitem
    \@donoparitem
  \else
    \if@inlabel
      \indent \par
    \fi
    \ifhmode
      \unskip\unskip \par
    \fi
    \if@newlist
      \if@nobreak
        \@nbitem
      \else
        \addpenalty\@beginparpenalty
        \addvspace\@topsep
        \addvspace{-\parskip}%
      \fi
    \else
      \addpenalty\@itempenalty
      \addvspace\itemsep
    \fi
    \global\@inlabeltrue
  \fi
  \everypar{%
    \@minipagefalse
    \global\@newlistfalse
```

This \if@inlabel check is needed in case an item starts of inside a group so that \everypar does not become empty outside that group.

```
    \if@inlabel
      \global\@inlabelfalse
```

The paragraph indent is now removed by using \setbox... since this makes \noindent a no-op here, as it should be. Thus the following comment is redundant but is left here for the sake of future historians: this next command was changed from an hskip to a kern to avoid a break point after the parindent box: the skip could cause a line-break if a very long label occurs in raggedright setting. If \noindent was used after \item want to cancel the \itemindent skip. This case can be detected as the indentation box will be void.

```
      {\setbox\z@\lastbox
       \ifvoid\z@
         \kern-\itemindent
       \fi}%
      \box\@labels
      \penalty\z@
    \fi
```

This code is intended to prevent a page break after the first line of an item that comes immediately after a section title. It may be sensible to always forbid a page break after one line of an item? As with all such settings of \clubpenalty it is local so will have no effect if the item starts in a group.

Only resetting \@nobreak when it is true is now essential since now it is sometimes set locally.

```
    \if@nobreak
      \@nobreakfalse
      \clubpenalty \@M
    \else
      \clubpenalty \@clubpenalty
      \everypar{}%
    \fi}%

  \if@noitemarg
    \@noitemargfalse
    \if@nmbrlist

      \refstepcounter\@listctr
    \fi
  \fi
```

We use \sbox to support colour commands.

```
  \sbox\@tempboxa{\makelabel{#1}}%
  \global\setbox\@labels\hbox{%
    \unhbox\@labels
    \hskip \itemindent
    \hskip -\labelwidth
    \hskip -\labelsep
    \ifdim \wd\@tempboxa >\labelwidth
      \box\@tempboxa
```

```
    \else
      \hbox to\labelwidth {\unhbox\@tempboxa}%
    \fi
    \hskip \labelsep}%
  \ignorespaces}
```

(*End definition for* `\@item`.)

`\makelabel`

```
\def\makelabel#1{%
  \@latex@error{Lonely \string\item--perhaps a missing
        list environment}\@ehc}
```

(*End definition for* `\makelabel`.)

`\@nbitem`

```
\def\@nbitem{%
  \@tempskipa\@outerparskip
  \advance\@tempskipa -\parskip
  \addvspace\@tempskipa}
```

(*End definition for* `\@nbitem`.)

`\usecounter`

```
\def\usecounter#1{\@nmbrlisttrue\def\@listctr{#1}\setcounter{#1}\z@}
```

(*End definition for* `\usecounter`.)

1.6 Itemize and Enumerate

Enumeration is done with four counters: `enumi`, `enumii`, `enumiii` and `enumiv`, where `enum`N controls the numbering of the Nth level enumeration. The label is generated by the commands `\labelenumi` ... `\labelenumiv`, which should be defined by the document style. Note that `\p@enum`N`\theenum`N defines the output of a `\ref` command. A typical definition might be:

```
\def\theenumii{\alph{enumii}}
\def\p@enumii{\theenumi}
\def\labelenumii{(\theenumii)}
```

which will print the labels as '(a)', '(b)', ... and print a `\ref` as '3a'.

The item numbers are moved to the right of the label box, so they are always a distance of `\labelsep` from the item.

`\@enumdepth` holds the current enumeration nesting depth.

Itemization is controlled by four commands: `\labelitemi`, `\labelitemii`, `\labelitemiii`, and `\labelitemiv`. To cause the second-level list to be bulleted, you just define `\labelitemii` to be •. `\@itemspacing` and `\@itemdepth` are the analogs of `\@enumspacing` and `\@enumdepth`.

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\enumerate ==
  BEGIN
    if \@enumdepth > 3
      then errormessage: "Too deeply nested".
      else \@enumdepth :=L \@enumdepth + 1
```

```
                \@enumctr :=L eval(enum@\romannumeral\the\@enumdepth)
                \list{\label(\@enumctr)}
                     {\usecounter{\@enumctr}
                      \makelabel{LABEL} ==  \hss \llap{LABEL}}
        fi
      END

 \endenumerate == \endlist
```

End of historical LaTeX 2.09 comments.

`\@enumdepth`

```
\newcount\@enumdepth \@enumdepth = 0
```

(*End definition for* `\@enumdepth`.)

`\c@enumi`
`\c@enumii`
`\c@enumii`
`\c@enumiv`

```
\@definecounter{enumi}
\@definecounter{enumii}
\@definecounter{enumiii}
\@definecounter{enumiv}
```

(*End definition for* `\c@enumi` *and others.*)

`enumerate` (*env.*)

```
\def\enumerate{%
  \ifnum \@enumdepth >\thr@@\@toodeep\else
    \advance\@enumdepth\@ne
    \edef\@enumctr{enum\romannumeral\the\@enumdepth}%

      \expandafter
      \list
        \csname label\@enumctr\endcsname
        {\usecounter\@enumctr\def\makelabel##1{\hss\llap{##1}}}%
  \fi}

\let\endenumerate =\endlist
```

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\itemize ==
  BEGIN
    if \@itemdepth > 3
      then  errormessage: 'Too deeply nested'.
      else \@itemdepth :=L \@itemdepth + 1
           \@itemitem  == eval(labelitem\romannumeral\the\@itemdepth)
           \list{\@nameuse{\@itemitem}}
                 {\makelabel{LABEL} ==  \hss \llap{LABEL}}
    fi
  END

\enditemize ==  \endlist
```

End of historical LaTeX 2.09 comments.

`\@itemdepth`

```
\newcount\@itemdepth \@itemdepth = 0
```

(*End definition for* `\@itemdepth`.)

`itemize` (*env.*)

```
\def\itemize{%
  \ifnum \@itemdepth >\thr@@\@toodeep\else
    \advance\@itemdepth\@ne
    \edef\@itemitem{labelitem\romannumeral\the\@itemdepth}%
    \expandafter
    \list
      \csname\@itemitem\endcsname
      {\def\makelabel##1{\hss\llap{##1}}}%
  \fi}
\let\enditemize =\endlist
⟨/2ekernel⟩
```

File K
ltboxes.dtx

1 LaTeX Box commands

\makebox `\makebox[⟨wid⟩][⟨pos⟩]{⟨obj⟩}`
Puts ⟨*obj*⟩ in an `\hbox` of width ⟨*wid*⟩, positioned by ⟨*pos*⟩.

The possible ⟨*pos*⟩ are:
`s` stretched,
`l` flushleft,
`r` flushright,
`c` (default) centred.

If ⟨*wid*⟩ is missing, then ⟨*pos*⟩ is also missing and ⟨*obj*⟩ is put in an `\hbox` of its natural width.

`\makebox(⟨x⟩,⟨y⟩)[⟨pos⟩]{⟨obj⟩}`
Puts ⟨*obj*⟩ in an `\hbox` of width $x * $ `\unitlength` and height $y * $ `\unitlength`. ⟨*pos*⟩ arguments are `s`, `l`, `r` or `c` (default) for stretched, flushleft, flushright or centred, and `t` or `b` for top, bottom – or combinations like `tr` or `rb`. Default for horizontal and vertical are centered. Note that in this picture mode version of `\makebox` a [b] aligns on the *bottom* of the text as documented. If you want to align on the *baseline* use `\makebox( , )[b]{\raisebox{0pt}[\height][0pt]{xyz}}` or `\makebox( , )[b]{\smash{xyz}}`

\mbox `\mbox{⟨obj⟩}` The same as `\makebox{⟨obj⟩}`, but is more efficient as no checking for optional arguments is done.

\newsavebox `\newsavebox{\cmd}` : If `\cmd` is undefined, then defines it to be a TeX box register.

\savebox `\savebox{\cmd} ...` : `\cmd` is defined to be a TeX box register, and the '...' are any `\makebox` arguments. It is like `\makebox`, except it doesn't produce text but saves the value in `\box \cmd`.

\sbox `\sbox{⟨cmd⟩}{⟨obj⟩}` is an efficient abbreviation for `\savebox{⟨cmd⟩}{⟨obj⟩}`.

lrbox (*env.*) `\begin{lrbox}{⟨cmd⟩}⟨text⟩\end{lrbox}` is equivalent to `\sbox{⟨cmd⟩}{⟨text⟩}`
except that any white space at the beginning and end of ⟨*text*⟩ is ignored.

\framebox `\framebox ...` : like `\makebox`, except it puts a 'frame' around the box. The frame is made of lines of thickness `\fboxrule`, separated by space `\fboxsep` from the text – except for `\framebox(X,Y) ...` , where the thickness of the lines is as for the picture environment, and there is no separation added.

\fbox `\fbox{⟨obj⟩}` is an abbreviation for `\framebox{⟨obj⟩}`.

\parbox `\parbox[⟨pos⟩][⟨height⟩][⟨inner-pos⟩]{⟨width⟩}{⟨text⟩}` : Makes a box with `\hsize` ⟨*width*⟩, positioned by ⟨*pos*⟩ as follows: c : `\vcenter` (placed in `$...$` if not in math mode) b : `\vbox` t : `\vtop` default value is c. Sets `\hsize` := ⟨*width*⟩ and calls `\@parboxrestore`, which does the following: Restores the original definitions of:

```
\par
\\
\-
\'
 \`
\=
```

Resets the following parameters:

\parindent	=	0pt	
\parskip	=	0pt	added 20 Jan 87
\linewidth	=	\hsize	
\@totalleftmargin	=	0pt	
\leftskip	=	0pt	
\rightskip	=	0pt	
\@rightskip	=	0pt	
\parfillskip	=	0pt plus 1fil	
\lineskip	=	\normallineskip	
\baselineskip	=	\normalbaselineskip	

Calls \sloppy

Note: \@arrayparboxrestore same as \@parboxrestore but it doesn't restore \\.

minipage (*env.*) minipage : Similar to \parbox, except it also makes this look like a page by setting \textwidth == \columnwidth == box width

changes footnotes by redefining:

\@mpfn == mpfootnote
\thempfn == \thempfootnote
\@footnotetext == \@mpfootnotetext

resets the following list environment parameters:

\@listdepth == \@mplistdepth

where \@mplistdepth is initialized to zero,

and executes \@minipagerestore to allow the document style to reset any other parameters it desires. It sets @minipage true, and resets \everypar to set it false. This switch keeps \addvspace from putting space at the top of a minipage.

Change added 24 May 89: \minipage sets @minipage globally; \endminipage resets it false.

\rule \rule[⟨*raised*⟩]{⟨*width*⟩}{⟨*height*⟩} : Makes a ⟨*width*⟩∗⟨*height*⟩ rule, raised ⟨*raised*⟩.

\underline \underline{⟨*text*⟩} : Makes an underlined hbox with ⟨*text*⟩ in it.

\raisebox \raisebox{⟨*distance*⟩}[⟨*height*⟩][⟨*depth*⟩]{⟨*box*⟩} :

Raises ⟨*box*⟩ up by ⟨*distance*⟩ length (down if ⟨*distance*⟩ negative). Makes TEX think that the new box extends ⟨*height*⟩ above the line and ⟨*depth*⟩ below, for a total vertical length of ⟨*height*⟩+⟨*depth*⟩. Default values of ⟨*height*⟩ & ⟨*depth*⟩ = actual height and depth of box in new position.

```
⟨*2ekernel⟩
\message{boxes,}
```

\makebox \makebox User level command just looks for optional [or (.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\makebox}{Make \makebox robust}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\makebox{%
  \leavevmode
  \@ifnextchar(%)
    \@makepicbox
    {\@ifnextchar[\@makebox\mbox}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\makebox}{Make \makebox robust}%
```

```
⟨latexrelease⟩\def\makebox{%
⟨latexrelease⟩   \leavevmode
⟨latexrelease⟩   \@ifnextchar(%)
⟨latexrelease⟩     \@makepicbox
⟨latexrelease⟩     {\@ifnextchar[\@makebox\mbox}}%
⟨latexrelease⟩\expandafter\let\csname makebox \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\makebox`.)

`\mbox` The basic horizontal box command for LaTeX.

```
\DeclareRobustCommand\mbox[1]{\leavevmode\hbox{#1}}
```

(*End definition for* `\mbox`.)

`\@makebox` Look for a possible second optional argument (defaults to `c`).

```
\def\@makebox[#1]{%
  \@ifnextchar [{\@imakebox[#1]}{\@imakebox[#1][c]}}
```

(*End definition for* `\@makebox`.)

`\@begin@tempboxa` Helper macro for supporting `\height`, `\width` etc. Grab `#1` into `\@tempboxa` and measure it.

```
\long\def\@begin@tempboxa#1#2{%
   \begingroup
     \setbox\@tempboxa#1{\color@begingroup#2\color@endgroup}%
     \def\width{\wd\@tempboxa}%
     \def\height{\ht\@tempboxa}%
     \def\depth{\dp\@tempboxa}%
     \let\totalheight\@ovri
     \totalheight\height
     \advance\totalheight\depth}
```

(*End definition for* `\@begin@tempboxa`.)

`\@end@tempboxa` End the group started by `\@begin@tempboxa`, so that the scope of `\height` only includes the 'length' argument to the user-command.

```
\let\@end@tempboxa\endgroup
```

(*End definition for* `\@end@tempboxa`.)

`\bm@c` `\bm@l` `\bm@r` `\bm@s` `\bm@t` `\bm@b` Set up spacing.

```
\def\bm@c{\hss\unhbox\@tempboxa\hss}
\def\bm@l{\unhbox\@tempboxa\hss}\let\bm@t\bm@l
\def\bm@r{\hss\unhbox\@tempboxa}\let\bm@b\bm@r
\def\bm@s{\unhbox\@tempboxa}
```

(*End definition for* `\bm@c` *and others.*)

`\@imakebox` Internal form of `\makebox`.

```
\long\def\@imakebox[#1][#2]#3{%
  \@begin@tempboxa\hbox{#3}%
    \setlength\@tempdima{#1}%       support calc
    \hb@xt@\@tempdima{\csname bm@#2\endcsname}%
  \@end@tempboxa}
```

(*End definition for* `\@imakebox`.)

`\@makepicbox` Picture mode form of `\makebox`.

```
\def\@makepicbox(#1,#2){%
  \@ifnextchar[{\@imakepicbox(#1,#2)}{\@imakepicbox(#1,#2)[]}}
```

(*End definition for* `\@makepicbox`.)

`\@imakepicbox` picture mode version

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\@imakepicbox}{default units}%
\long\def\@imakepicbox(#1,#2)[#3]#4{%
  \@defaultunitsset\@tempdimc{#2}\unitlength
  \vbox to\@tempdimc
   {\let\mb@b\vss \let\mb@l\hss\let\mb@r\hss
    \let\mb@t\vss
    \@tfor\reserved@a :=#3\do{%
      \if s\reserved@a
        \let\mb@l\relax\let\mb@r\relax
      \else
        \expandafter\let\csname mb@\reserved@a\endcsname\relax
      \fi}%
    \mb@t
    \@defaultunitsset\@tempdimc{#1}\unitlength
    \hb@xt@\@tempdimc{\mb@l #4\mb@r}%
    \mb@b
```

This kern ensures that a `b` option aligns on the bottom of the text rather than the baseline. this is the documented behaviour in the LaTeX Book. The kern is removed in compatibility mode.

```
    \kern\z@}}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@imakepicbox}{default units}%
⟨latexrelease⟩\long\def\@imakepicbox(#1,#2)[#3]#4{%
⟨latexrelease⟩  \vbox to#2\unitlength
⟨latexrelease⟩   {\let\mb@b\vss \let\mb@l\hss\let\mb@r\hss
⟨latexrelease⟩    \let\mb@t\vss
⟨latexrelease⟩    \@tfor\reserved@a :=#3\do{%
⟨latexrelease⟩      \if s\reserved@a
⟨latexrelease⟩        \let\mb@l\relax\let\mb@r\relax
⟨latexrelease⟩      \else
⟨latexrelease⟩        \expandafter\let\csname mb@\reserved@a\endcsname\relax
⟨latexrelease⟩      \fi}%
⟨latexrelease⟩    \mb@t
⟨latexrelease⟩    \hb@xt@ #1\unitlength{\mb@l #4\mb@r}%
⟨latexrelease⟩    \mb@b
⟨latexrelease⟩    \kern\z@}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@imakepicbox`.)

`\set@color` This macro is initially a no-op, but the color package will redefine it to insert a `\special`.

```
\let\set@color\relax
```

(*End definition for* `\set@color`.)

`\color@begingroup` `\color@endgroup` `\color@setgroup` `\normalcolor` `\color@hbox` `\color@vbox` `\color@endbox`

In the past these macros were initially no-ops, and the color package redefined redefine them to be `\begingroup`, `\endgroup`, `\begingroup\set@color`, `\hbox\bgroup\color@begingroup`, `\color@endgroup\egroup`. and ⟨*set to main document color*⟩ respectively.

Nowadays we always set the group already in the kernel as this makes the coding simpler.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\color@begingroup}{color group settings}%
\let\color@begingroup\begingroup
\def\color@endgroup{\endgraf\endgroup}
\def\color@setgroup{\color@begingroup}        % changed further in color package
\let\normalcolor\relax                         % remains untouched; only changed in a color pa
\def\color@hbox{\hbox\bgroup\color@begingroup}
\def\color@vbox{\vbox\bgroup\color@begingroup}
\def\color@endbox{\color@endgroup\egroup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\color@begingroup}{color group settings}%
⟨latexrelease⟩
⟨latexrelease⟩\let\color@begingroup\relax
⟨latexrelease⟩\let\color@endgroup\relax
⟨latexrelease⟩\let\color@setgroup\relax
⟨latexrelease⟩\let\normalcolor\relax
⟨latexrelease⟩\let\color@hbox\relax
⟨latexrelease⟩\let\color@vbox\relax
⟨latexrelease⟩\let\color@endbox\relax
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\color@begingroup` *and others.*)

`\newsavebox` Allocate a new 'savebox'.

```
\def\newsavebox#1{\@ifdefinable{#1}{\newbox#1}}
```

(*End definition for* `\newsavebox`.)

`\savebox` Save `#1` in a box register.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\savebox}{Make \savebox robust}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\savebox[1]{%
  \@ifnextchar(%)
```

```
    {\@savepicbox#1}{\@ifnextchar[{\@savebox#1}{\sbox#1}}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\savebox}{Make \savebox robust}%
⟨latexrelease⟩\def\savebox#1{%
⟨latexrelease⟩  \@ifnextchar(%)
⟨latexrelease⟩    {\@savepicbox#1}{\@ifnextchar[{\@savebox#1}{\sbox#1}}}%
⟨latexrelease⟩\expandafter\let\csname savebox \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\savebox`.)

`\sbox` Save `#1` in a box register.

```
\DeclareRobustCommand\sbox[2]{\setbox#1\hbox{%
  \color@setgroup#2\color@endgroup}}
```

(*End definition for* `\sbox`.)

`\@savebox` Look for second optional argument.

```
\def\@savebox#1[#2]{%
  \@ifnextchar [{\@isavebox#1[#2]}{\@isavebox#1[#2][c]}}
```

(*End definition for* `\@savebox`.)

`\@isavebox`

```
\long\def\@isavebox#1[#2][#3]#4{%
  \sbox#1{\@imakebox[#2][#3]{#4}}}
```

(*End definition for* `\@isavebox`.)

`\@savepicbox` Picture mode version of `\savebox`.

```
\def\@savepicbox#1(#2,#3){%
  \@ifnextchar[%]
    {\@isavepicbox#1(#2,#3)}{\@isavepicbox#1(#2,#3)[]}}
```

(*End definition for* `\@savepicbox`.)

`\@isavepicbox` Picture mode version of `\savebox`.

```
\long\def\@isavepicbox#1(#2,#3)[#4]#5{%
  \sbox#1{\@imakepicbox(#2,#3)[#4]{#5}}}
```

(*End definition for* `\@isavepicbox`.)

`\lrbox` `lrbox`: the new environment form of `\sbox`. Use `\aftergroup` tricks to enable a *local* assignment to be made to the box, in a way that it still has an effect *outside* the `lrbox` environment.

```
\def\lrbox#1{%
  \edef\reserved@a{%
    \endgroup
    \setbox#1\hbox{%
      \begingroup\aftergroup}%
        \def\noexpand\@currenvir{\@currenvir}%
        \def\noexpand\@currenvline{\on@line}}%
```

```
  \reserved@a
    \@endpefalse
    \color@setgroup
      \ignorespaces}
```

(*End definition for* `\lrbox`.)

`\endlrbox` End the `lrbox` environment.

```
\def\endlrbox{\unskip\color@endgroup}
```

(*End definition for* `\endlrbox`.)

`\usebox` unchanged

```
\DeclareRobustCommand\usebox[1]{\leavevmode\copy #1\relax}
```

(*End definition for* `\usebox`.)

`\frame` The following definition of `\frame` was written by Pavel Curtis (Extra space removed 14 Jan 88) RmS 92/08/24: Replaced occurrence of `\@halfwidth` by `\@wholewidth`

```
\DeclareRobustCommand\frame[1]{%
  \leavevmode
  \hbox{%
    \hskip-\@wholewidth
    \vbox{%
      \vskip-\@wholewidth
      \hrule \@height\@wholewidth
      \hbox{%
        \vrule\@width\@wholewidth
        #1%
        \vrule\@width\@wholewidth}%
      \hrule\@height\@wholewidth
      \vskip-\@wholewidth}%
    \hskip-\@wholewidth}}
```

(*End definition for* `\frame`.)

`\fboxrule` `\fboxsep` user level parameters,

```
\newdimen\fboxrule
\newdimen\fboxsep
```

(*End definition for* `\fboxrule` *and* `\fboxsep`.)

`\fbox` Abbreviated framed box command.

```
\DeclareRobustCommand\fbox[1]{%
  \leavevmode
  \setbox\@tempboxa\hbox{%
    \color@begingroup
      \kern\fboxsep{#1}\kern\fboxsep
    \color@endgroup}%
  \@frameb@x\relax}
```

(*End definition for* `\fbox`.)

\framebox Framed version of \makebox.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\framebox}{Make \framebox robust}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\framebox{%
  \@ifnextchar(%)
    \@framepicbox{\@ifnextchar[\@framebox\fbox}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\framebox}{Make \framebox robust}%
⟨latexrelease⟩\def\framebox{%
⟨latexrelease⟩  \@ifnextchar(%)
⟨latexrelease⟩    \@framepicbox{\@ifnextchar[\@framebox\fbox}}%
⟨latexrelease⟩\expandafter\let\csname framebox \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \framebox.)

\@framebox Deal with optional arguments.

```
\def\@framebox[#1]{%
  \@ifnextchar[%]
    {\@iframebox[#1]}%
    {\@iframebox[#1][c]}}
```

(*End definition for* \@framebox.)

\@iframebox The handling the optional arguments. In order to set the whole box, including the frame to the specified dimension, we first determine that dimension from the natural size of the text, #3. calculated width.

```
\long\def\@iframebox[#1][#2]#3{%
  \leavevmode
  \@begin@tempboxa\hbox{#3}%
    \setlength\@tempdima{#1}%
    \setbox\@tempboxa\hb@xt@\@tempdima
         {\kern\fboxsep\csname bm@#2\endcsname\kern\fboxsep}%
    \@frameb@x{\kern-\fboxrule}%
  \@end@tempboxa}
```

(*End definition for* \@iframebox.)

\@frameb@x Common part of \framebox and \fbox. #1 is a negative kern in the \framebox case so that the vertical rules do not add to the width of the box.

```
\def\@frameb@x#1{%
  \@tempdima\fboxrule
  \advance\@tempdima\fboxsep
  \advance\@tempdima\dp\@tempboxa
  \hbox{%
    \lower\@tempdima\hbox{%
      \vbox{%
        \hrule\@height\fboxrule
        \hbox{%
```

```
          \vrule\@width\fboxrule
          #1%
          \vbox{%
            \vskip\fboxsep
            \box\@tempboxa
            \vskip\fboxsep}%
          #1%
          \vrule\@width\fboxrule}%
        \hrule\@height\fboxrule}%
                            }%
        }%
}
```

(*End definition for* `\@frameb@x`.)

`\@framepicbox` Picture mode version.

```
\def\@framepicbox(#1,#2){%
  \@ifnextchar[{\@iframepicbox(#1,#2)}{\@iframepicbox(#1,#2)[]}}
```

(*End definition for* `\@framepicbox`.)

`\@iframepicbox` Picture mode version.

```
\long\def\@iframepicbox(#1,#2)[#3]#4{%
  \frame{\@imakepicbox(#1,#2)[#3]{#4}}}
```

(*End definition for* `\@iframepicbox`.)

`\parbox` The main vertical-box command for LaTeX.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\parbox}{Make \parbox robust}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\parbox{%
  \@ifnextchar[%]
    \@iparbox
    {\@iiiparbox c\relax[s]}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\parbox}{Make \parbox robust}%
⟨latexrelease⟩\def\parbox{%
⟨latexrelease⟩   \@ifnextchar[%]
⟨latexrelease⟩     \@iparbox
⟨latexrelease⟩     {\@iiiparbox c\relax[s]}}%
⟨latexrelease⟩\expandafter\let\csname parbox \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\parbox`.)

`\@iparbox` Optional argument handling.

```
\def\@iparbox[#1]{%
  \@ifnextchar[%]
    {\@iiparbox{#1}}%
    {\@iiiparbox{#1}\relax[s]}}
```

(*End definition for* `\@iparbox`.)

`\@iiparbox` Optional argument handling.

```
\def\@iiparbox#1[#2]{%
  \@ifnextchar[%]
    {\@iiiparbox{#1}{#2}}%
    {\@iiiparbox{#1}{#2}[#1]}}
```

(*End definition for* `\@iiparbox`.)

`\@iiiparbox` `\@parboxto` The internal version of `\parbox`.

```
\let\@parboxto\@empty
\long\def\@iiiparbox#1#2[#3]#4#5{%
  \leavevmode
  \@pboxswfalse
  \setlength\@tempdima{#4}%
  \@begin@tempboxa\vbox{\hsize\@tempdima\@parboxrestore#5\@@par}%
    \ifx\relax#2\else
      \setlength\@tempdimb{#2}%
      \edef\@parboxto{to\the\@tempdimb}%
    \fi
    \if#1b\vbox
    \else\if #1t\vtop
    \else\ifmmode\vcenter
    \else\@pboxswtrue $\vcenter
    \fi\fi\fi
    \@parboxto{\let\hss\vss\let\unhbox\unvbox
       \csname bm@#3\endcsname}%
    \if@pboxsw \m@th$\fi
  \@end@tempboxa}
```

(*End definition for* `\@iiiparbox` *and* `\@parboxto`.)

`\@arrayparboxrestore` Restore various paragraph parameters.

The rational for allowing two normally global flags to be set locally here was stated originally by Donald Arseneau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within boxes or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in `\set@nobreak`; otherwise this command will be redundant.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2017-04-15}%
⟨latexrelease⟩                  {\normallineskiplimit}
⟨latexrelease⟩                  {reset \lineskiplimit}%
⟨*2ekernel | latexrelease⟩
\def\@arrayparboxrestore{%
  \let\if@nobreak\iffalse
  \let\if@noskipsec\iffalse
  \let\par\@@par
  \let\-\@dischyph
```

Redefined accents to allow changes in font encoding

```
  \let\'\@acci\let\`\@accii\let\=\@acciii
  \parindent\z@ \parskip\z@skip
  \everypar{}%
  \linewidth\hsize
  \@totalleftmargin\z@
  \leftskip\z@skip \rightskip\z@skip \@rightskip\z@skip
  \parfillskip\@flushglue
  \lineskip\normallineskip
  \lineskiplimit\normallineskiplimit
  \baselineskip\normalbaselineskip
  \sloppy}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000-00-00}%
⟨latexrelease⟩                 {\normallineskiplimit}
⟨latexrelease⟩                 {reset \lineskiplimit}%
⟨latexrelease⟩\def\@arrayparboxrestore{%
⟨latexrelease⟩  \let\if@nobreak\iffalse
⟨latexrelease⟩  \let\if@noskipsec\iffalse
⟨latexrelease⟩  \let\par\@@par
⟨latexrelease⟩  \let\-\@dischyph
⟨latexrelease⟩  \let\'\@acci\let\`\@accii\let\=\@acciii
⟨latexrelease⟩  \parindent\z@ \parskip\z@skip
⟨latexrelease⟩  \everypar{}%
⟨latexrelease⟩  \linewidth\hsize
⟨latexrelease⟩  \@totalleftmargin\z@
⟨latexrelease⟩  \leftskip\z@skip \rightskip\z@skip \@rightskip\z@skip
⟨latexrelease⟩  \parfillskip\@flushglue \lineskip\normallineskip
⟨latexrelease⟩  \baselineskip\normalbaselineskip
⟨latexrelease⟩  \sloppy}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@arrayparboxrestore`.)

`\@parboxrestore` Restore various paragraph parameters, and also `\\`.

```
\def\@parboxrestore{\@arrayparboxrestore\let\\\@normalcr}
```

(*End definition for* `\@parboxrestore`.)

`\if@minipage` Switch that is true at the start of a minipage.

```
\def\@minipagefalse{\global\let\if@minipage\iffalse}
\def\@minipagetrue {\global\let\if@minipage\iftrue}
\@minipagefalse
```

(*End definition for* `\if@minipage`.)

`\minipage` Essentially an environment form of `\parbox`.

```
\def\minipage{%
  \@ifnextchar[%]
    \@iminipage
    {\@iiiminipage c\relax[s]}}
```

(*End definition for* `\minipage`.)

`\@iminipage` Optional argument handling.

```
\def\@iminipage[#1]{%
  \@ifnextchar[%]
    {\@iiminipage{#1}}%
    {\@iiiminipage{#1}\relax[s]}}
```

(*End definition for* `\@iminipage`.)

`\@iiminipage` Optional argument handling.

```
\def\@iiminipage#1[#2]{%
  \@ifnextchar[%]
    {\@iiiminipage{#1}{#2}}%
    {\@iiiminipage{#1}{#2}[#1]}}
```

(*End definition for* `\@iiminipage`.)

`\@iiiminipage` Internal form of `minipage`.

```
\def\@iiiminipage#1#2[#3]#4{%
  \leavevmode
  \@pboxswfalse
  \setlength\@tempdima{#4}%
  \def\@mpargs{{#1}{#2}[#3]{#4}}%
  \setbox\@tempboxa\vbox\bgroup
    \color@begingroup
      \hsize\@tempdima
      \textwidth\hsize \columnwidth\hsize
      \@parboxrestore
      \def\@mpfn{mpfootnote}\def\thempfn{\thempfootnote}\c@mpfootnote\z@
      \let\@footnotetext\@mpfootnotetext
      \let\@listdepth\@mplistdepth \@mplistdepth\z@
      \@minipagerestore
      \@setminipage}
```

(*End definition for* `\@iiiminipage`.)

`\@minipagerestore` Hook so that other styles can reset other commands in a minipage.

```
 \let\@minipagerestore=\relax
```

(*End definition for* `\@minipagerestore`.)

`\endminipage`

```
\def\endminipage{%
    \par
    \unskip
    \ifvoid\@mpfootins\else
      \vskip\skip\@mpfootins
      \normalcolor
      \footnoterule
      \unvbox\@mpfootins
    \fi
    \@minipagefalse   %% added 24 May 89
  \color@endgroup
  \egroup
  \expandafter\@iiiparbox\@mpargs{\unvbox\@tempboxa}}
```

(*End definition for* `\endminipage`.)

`\@mplistdepth` `\@mpfootins`

Versions of `\@listdepth` and `\footins` local to minipage.

```
\newcount\@mplistdepth
\newinsert\@mpfootins
```

(*End definition for* `\@mplistdepth` *and* `\@mpfootins`.)

`\@mpfootnotetext`

Minipage version of `\@footnotetext`.

Final `\strut` added 27 Mar 89, on suggestion by Don Hosek

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                  {\@mpfootnotetext}{footnotetext tagging}%
\long\def\@mpfootnotetext#1{%
  \global\setbox\@mpfootins\vbox{%
    \unvbox\@mpfootins
    \reset@font\footnotesize
    \hsize\columnwidth
    \@parboxrestore
    \def\@currentcounter{mpfootnote}%
    \protected@edef\@currentlabel
         {\csname p@mpfootnote\endcsname\@thefnmark}%
    \color@begingroup
      \@makefntext{%
        \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
    \par
    \color@endgroup}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\@mpfootnotetext}{footnotetext tagging}%
⟨latexrelease⟩\long\def\@mpfootnotetext#1{%
⟨latexrelease⟩  \global\setbox\@mpfootins\vbox{%
⟨latexrelease⟩    \unvbox\@mpfootins
⟨latexrelease⟩    \reset@font\footnotesize
⟨latexrelease⟩    \hsize\columnwidth
⟨latexrelease⟩    \@parboxrestore
⟨latexrelease⟩    \protected@edef\@currentlabel
⟨latexrelease⟩         {\csname p@mpfootnote\endcsname\@thefnmark}%
⟨latexrelease⟩    \color@begingroup
⟨latexrelease⟩      \@makefntext{%
⟨latexrelease⟩        \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
⟨latexrelease⟩    \par
⟨latexrelease⟩    \color@endgroup}}
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@mpfootnotetext}{footnotetext tagging}%
⟨latexrelease⟩
⟨latexrelease⟩\long\def\@mpfootnotetext#1{%
⟨latexrelease⟩  \global\setbox\@mpfootins\vbox{%
⟨latexrelease⟩    \unvbox\@mpfootins
⟨latexrelease⟩    \reset@font\footnotesize
```

```
⟨latexrelease⟩     \hsize\columnwidth
⟨latexrelease⟩     \@parboxrestore
⟨latexrelease⟩     \protected@edef\@currentlabel
⟨latexrelease⟩          {\csname p@mpfootnote\endcsname\@thefnmark}%
⟨latexrelease⟩     \color@begingroup
⟨latexrelease⟩       \@makefntext{%
⟨latexrelease⟩         \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
⟨latexrelease⟩     \color@endgroup}}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@mpfootnotetext`.)

```
\newif\if@pboxsw
```

`\rule` Draw a rule of the specified size.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\rule}{Make \rule robust}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\rule{\@ifnextchar[\@rule{\@rule[\z@]}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\rule}{Make \rule robust}%
⟨latexrelease⟩\def\rule{\@ifnextchar[\@rule{\@rule[\z@]}}%
⟨latexrelease⟩\expandafter\let\csname rule \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\rule`.)

`\@rule` Internal form of `\rule`.

```
\def\@rule[#1]#2#3{%
  \leavevmode
  \hbox{%
    \setlength\@tempdima{#1}%
    \setlength\@tempdimb{#2}%
    \setlength\@tempdimc{#3}%
    \advance\@tempdimc\@tempdima
    \vrule\@width\@tempdimb\@height\@tempdimc\@depth-\@tempdima}}
```

(*End definition for* `\@rule`.)

`\@@underline` Saved primitive `\underline`.

```
\let\@@underline\underline
```

(*End definition for* `\@@underline`.)

`\underline` LaTeX version works outside math.

```
\DeclareRobustCommand\underline[1]{%
  \relax
  \ifmmode\@@underline{#1}%
  \else $\@@underline{\hbox{#1}}\m@th$\relax\fi}
```

(*End definition for* `\underline`.)

`\raisebox` Raise a box, and change its vertical dimensions.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\raisebox}{Make \raisebox robust}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand\raisebox[1]{%
  \leavevmode
  \@ifnextchar[{\@rsbox{#1}}{\@irsbox{#1}[]}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\raisebox}{Make \raisebox robust}%
⟨latexrelease⟩\def\raisebox#1{%
⟨latexrelease⟩  \leavevmode
⟨latexrelease⟩  \@ifnextchar[{\@rsbox{#1}}{\@irsbox{#1}[]}}
⟨latexrelease⟩\expandafter\let\csname raisebox \endcsname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\raisebox`.)

`\@rsbox` Optional argument handling.

```
\def\@rsbox#1[#2]{%
  \@ifnextchar[{\@iirsbox{#1}[#2]}{\@irsbox{#1}[#2]}}
```

(*End definition for* `\@rsbox`.)

`\@argrsbox` ...

(*End definition for* `\@argrsbox`.)

`\@irsbox` Internal version of `\raisebox` (less than two optional args).

```
\long\def\@irsbox#1[#2]#3{%
  \@begin@tempboxa\hbox{#3}%
    \setlength\@tempdima{#1}%
    \ifx\\#2\\\else\setlength\@tempdimb{#2}\fi
    \setbox\@tempboxa\hbox{\raise\@tempdima\box\@tempboxa}%
    \ifx\\#2\\\else\ht\@tempboxa\@tempdimb\fi
    \box\@tempboxa
  \@end@tempboxa}
```

(*End definition for* `\@irsbox`.)

`\@iirsbox` Internal version of `\raisebox` (two optional args).

```
\long\def\@iirsbox#1[#2][#3]#4{%
  \@begin@tempboxa\hbox{#4}%
    \setlength\@tempdima{#1}%
    \setlength\@tempdimb{#2}%
    \setlength\dimen@{#3}%
    \setbox\@tempboxa\hbox{\raise\@tempdima\box\@tempboxa}%
    \ht\@tempboxa\@tempdimb
    \dp\@tempboxa\dimen@
    \box\@tempboxa
  \@end@tempboxa}
```

(*End definition for* `\@iirsbox`.)

`\@finalstrut` This macro adds a special strut the *depth* of the box given as `#1`, and height and width 0pt. It is used for ensuring that the last line of a paragraph has the correct depth in 'p' columns of tables and in footnotes. In vertical mode nothing is done, as adding the strut (as done in 2.09) would start a new paragraph. It would be possible to inspect `\prevdepth` to check the depth of the just-completed paragraph, but we do not do that here. Actually we do even less now, skip the vmode test as it broke tabular 'p' columns. .

The `\nobreak` was added (1995/10/31) to allow hyphenation of the final word of the paragraph.

```
\def\@finalstrut#1{%
  \unskip\ifhmode\nobreak\fi\vrule\@width\z@\@height\z@\@depth\dp#1}
```

(*End definition for* `\@finalstrut`.)

1.1 Some low-level constructs

The following commands are basically inherited from plain TEX.

`\leftline` `\rightline` `\centerline` `\@@line` These macros place text on a full line either centred or left or right adjusted.

```
\def\@@line{\hb@xt@\hsize}
\DeclareRobustCommand\leftline[1]{\@@line{#1\hss}}
\DeclareRobustCommand\rightline[1]{\@@line{\hss#1}}
\DeclareRobustCommand\centerline[1]{\@@line{\hss#1\hss}}
```

(*End definition for* `\leftline` *and others.*)

`\rlap` `\llap` `\clap` These macros place text to the left or right of the current reference point without taking up space.

```
\DeclareRobustCommand\rlap[1]{\hb@xt@\z@{#1\hss}}
\DeclareRobustCommand\llap[1]{\hb@xt@\z@{\hss#1}}
```

And here is the version that centers, it was initially introduced by `mathtools`.

```
\DeclareRobustCommand\clap[1]{\hb@xt@\z@{\hss#1\hss}}
```

(*End definition for* `\rlap`, `\llap`, *and* `\clap`.)

⟨/2ekernel⟩

File L
lttab.dtx

1 Tabbing, Tabular and Array Environments

This section deals with 'Lining It Up in Columns'. First the `tabbing` environment is defined, and then in second part, `tabular` together with its variants, `tabular*` and `array`.

Note that the `tabular` defined here is essentially the original LaTeX 2.09 version, not the extended version described in *The LaTeX Companion*. Use the `array` package to obtain the extended version.

1.1 tabbing

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\dimen(\@firsttab + i) = distance of tab stop i from left margin
       0 <= i <= 15 (?).

\dimen\@firsttab is initialized to \@totalleftmargin, so it starts
    at the prevailing left margin.

\@maxtab          = number of highest defined tab register
                      probably = \@firsttab + 12
\@nxttabmar = tab stop number of next line's left margin
\@curtabmar = tab stop number of current line's left margin
\@curtab    = number of the current tab. At start of line,
                    it equals \@curtabmar
\@hightab   = largest tab number currently defined.
\@tabpush   = depth of \pushtab's

\box\@curline     = contents of current line, excluding left margin
                      skip, and excluding contents of current field
\box\@curfield    = contents of current field

@rjfield          = switch: T iff the last field of the line should
                      be right-justified at the right margin.

\tabbingsep           = distance left by the \' command between the
                      current position and the field that is
                      "left-shifted".

UTILITY MACROS
 \@stopfield  : closes the current field
 \@addfield   : adds the current field to the current line.
 \@contfield  : continues the current field
 \@startfield : begins the next field
 \@stopline   : closes the current line and outputs it
```

```
  \@startline  : starts the next line
  \@ifatmargin : an \if that is true iff the current line.
                 has width zero

\@startline ==
 BEGIN
  \@curtabmar :=G \@nxttabmar
  \@curtab :=G \@curtabmar
  \box\@curline :=G null
  \@startfield
  \strut
 END

\@stopline ==
 BEGIN
  \unskip
  \@stopfield
  if @rjfield = T
    then  @rjfield :=G F
          \@tempdima := \@totalleftmargin + \linewidth
          \hb@xt@ \@tempdima{\@itemfudge
                             \hskip \dimen\@curtabmar
                             \box\@curline
                             \hfil
                             \box\@curfield}
    else \@addfield
         \hbox {\@itemfudge
                \hskip \dimen\@curtabmar
                \box\@curline}
  fi
 END

\@startfield ==
 BEGIN
   \box\@curfield :=G \hbox {
 END

\@stopfield ==
 BEGIN
    }
 END

\@contfield ==
 BEGIN
  \box\@curfield :=G \hbox { \unhbox\@currfield  %%} brace matching
 END
\@addfield ==
 BEGIN
  \box\@curline :=G \unbox\@curline * \unbox\@curfield
 END
```

```
\@ifatmargin ==
 BEGIN
  if  dim of box\@curline = 0pt  then
 END


\tabbing ==
 BEGIN
  \lineskip :=L 0pt
  \> == \@rtab
  \< == \@ltab
  \= == \@settab
  \+ == \@tabplus
  \- == \@tabminus
  \‘ == \@tabrj
  \’ == \@tablab
  \\ == BEGIN \@stopline \@startline END
  \\[DIST] == BEGIN
                \@stopline \vskip DIST \@startline\ignorespaces END
  \\* == BEGIN \@stopline \penalty 10000 \@startline END
  \\*[DIST] == BEGIN \@stopline \penalty 10000 \vskip DIST
                     \@startline\ignorespaces              END
  \@hightab :=  \@nxttabmar :=G \@firsttab
  \@tabpush :=G 0
  \dimen\@firsttab := \@totalleftmargin
  @rjfield :=G F
  \trivlist  \item\relax
  if @minipage = F then \vskip \parskip fi
  \box\@tabfbox = \rlap{\indent\the\everypar}
                        % note: \the\everypar sets @inlabel :=G F
  \@itemfudge == BEGIN \box\@tabfbox END
  \@startline
  \ignorespaces
 END

\@endtabbing ==
 BEGIN
  \@stopline
  if \@tabpush > 0 then error message: ”unmatched \poptabs’’ fi
  \endtrivlist
 END

\@rtab ==
 BEGIN
  \@stopfield
  \@addfield
  if \@curtab < \@hightab
    then \@curtab :=G \@curtab + 1
    else error message “Undefined Tab”   fi
```

```
  \@tempdima := \dimen\@curtab - \dimen\@curtabmar
                        - width of box \@curline
  \box\@curline :=G \hbox{\unhbox\@curline + \hskip\@tempdima}
  \@startfield
 END

\@settab ==
 BEGIN
  \@stopfield
  \@addfield
  if \@curtab < \@maxtab
    then \@curtab :=G \@curtab+1
    else error message: "Too many tabs"     fi
  if \@curtab > \@hightab
    then \@hightab :=L \@curtab     fi
  \dimen\@curtab :=L \dimen\@curtabmar + width of \box\@curline
  \@startfield
 END

\@ltab ==
 BEGIN
  \@ifatmargin
    then if \@curtabmar > \@firsttab
            then \@curtab :=G \@curtab - 1
                 \@curtabmar :=G \@curtabmar - 1
            else error message "Too many untabs"       fi
    else error message "Left tab in middle of line"
  fi
 END

\@tabplus ==
 BEGIN
       if  \@nxttabmar < \@hightab
           then \@nxttabmar :=G \@nxttabmar+1
           else error message "Undefined tab"
       fi
 END

\@tabminus ==
 BEGIN
       if \@nxttabmar > \@firsttab
           then \@nxttabmar :=G \@nxttabmar-1
           else error message "Too many untabs"
       fi
 END

\@tabrj ==
 BEGIN \@stopfield
       \@addfield
       @rjfield :=G T
```

```
        \@startfield
 END

\@tablab ==
 BEGIN \@stopfield
     \box\@curline G:= \hbox{\box\@curline %% 'G' added 17 Jun 86
                            \hskip - width of \box\@curfield
                            \hskip -\tabbingsep
                            \box\@curfield
                            \hskip \tabbingsep }
        \@startfield
 END

\pushtabs ==
  BEGIN
    \@stopfield
    \@tabpush :=G \@tabpush + 1
    \begingroup
    \@contfield
  END

\poptabs ==
 BEGIN
   \@stopfield
   if \@tabpush > 0
     then \endgroup
          \@tabpush :=G \@tabpush - 1
     else error message: "Too many \poptabs''
   fi
   \@contfield
 END
```

End of historical LaTeX 2.09 comments.

\a The accents \‘ , \’ , and \= that have been redefined inside a tabbing environment can be called by typing \a‘ , \a’ , and \a=. The macro \a is defined in ltoutenc.dtx.

(*End definition for* \a.)

The ‘2ekernel’ code ensures that a \usepackage{autotabg} is essentially ignored if a ‘full’ format is being used that has picture mode already in the format.

```
⟨2ekernel⟩\expandafter\let\csname ver@autotabg.sty\endcsname\fmtversion
```

\@firsttab
\@maxtab

```
⟨*2ekernel⟩
\newdimen\@gtempa
\chardef\@firsttab=\the\allocationnumber
\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa\newdimen\@gtempa
\newdimen\@gtempa
\chardef\@maxtab=\the\allocationnumber
\dimen\@firsttab=0pt
```

(*End definition for* `\@firsttab` *and* `\@maxtab`.)

`\@nxttabmar`
`\@curtabmar`
`\@curtab`
`\@hightab`
`\@tabpush`

```
\newcount\@nxttabmar
\newcount\@curtabmar
\newcount\@curtab
\newcount\@hightab
\newcount\@tabpush
```

(*End definition for* `\@nxttabmar` *and others.*)

`\@curline`
`\@curfield`
`\@tabfbox`

```
\newbox\@curline
\newbox\@curfield
\newbox\@tabfbox
```

(*End definition for* `\@curline`, `\@curfield`, *and* `\@tabfbox`.)

`\if@rjfield`

```
\newif\if@rjfield
```

(*End definition for* `\if@rjfield`.)

`\@startline` It is, in some sense, an error if the current margin tab setting is higher than the value of `\@hightab` (which is a local variable). That this is allowed is a fundamental design flaw which is not going to be corrected now.

```
\def\@startline{%
     \ifnum \@nxttabmar >\@hightab
       \@badtab
       \global\@nxttabmar \@hightab
     \fi
     \global\@curtabmar \@nxttabmar
     \global\@curtab \@curtabmar
     \global\setbox\@curline \hbox {}%
     \@startfield
     \strut}
```

(*End definition for* `\@startline`.)

`\@stopline`

```
\def\@stopline{%
  \unskip
  \@stopfield
  \if@rjfield
    \global\@rjfieldfalse
    \@tempdima\@totalleftmargin
    \advance\@tempdima\linewidth
    \hb@xt@\@tempdima{%
      \@itemfudge\hskip\dimen\@curtabmar
      \box\@curline
      \hfil
      \box\@curfield}%
  \else
    \@addfield
    \hbox{\@itemfudge\hskip\dimen\@curtabmar\box\@curline}%
  \fi}
```

(*End definition for* `\@stopline`.)

`\@startfield`

```
\def\@startfield{%
  \global\setbox\@curfield\hbox\bgroup\color@begingroup}
```

(*End definition for* `\@startfield`.)

`\@stopfield`

```
\def\@stopfield{%
  \color@endgroup\egroup}
```

(*End definition for* `\@stopfield`.)

`\@contfield`

```
\def\@contfield{%
  \global\setbox\@curfield\hbox\bgroup\color@begingroup
  \unhbox\@curfield}
```

(*End definition for* `\@contfield`.)

`\@addfield`

```
\def\@addfield{\global\setbox\@curline\hbox{\unhbox
     \@curline\unhbox\@curfield}}
```

(*End definition for* `\@addfield`.)

`\@ifatmargin`

```
\def\@ifatmargin{\ifdim \wd\@curline =\z@}
```

(*End definition for* `\@ifatmargin`.)

`\@tabcr`

```
\protected\def\@tabcr{\@stopline \@ifstar{\penalty \@M \@xtabcr}\@xtabcr}
```

(*End definition for* `\@tabcr`.)

`\@xtabcr`

```
\def\@xtabcr{\@ifnextchar[\@itabcr{\@startline\ignorespaces}}
```

(*End definition for* `\@xtabcr`.)

`\@itabcr`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@itabcr}{Tabbing calc syntax}%
\def\@itabcr[#1]{\@vspace@calcify{#1}\@startline\ignorespaces}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@itabcr}{Tabbing calc syntax}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@itabcr[#1]{\vskip #1\@startline\ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

tabbing (*env.*) We use \relax to prevent \item from scanning too far.

\tabbing

```
\def\tabbing{\lineskip \z@skip\let\>\@rtab\let\<\@ltab\let\=\@settab
     \let\+\@tabplus\let\-\@tabminus\let\`\@tabrj\let\'\@tablab
     \let\\=\@tabcr
     \@hightab\@firsttab
     \global\@nxttabmar\@firsttab
     \dimen\@firsttab\@totalleftmargin
     \global\@tabpush\z@ \global\@rjfieldfalse
     \trivlist \item\relax
     \if@minipage\else\vskip\parskip\fi

     \setbox\@tabfbox\hbox{%
       \rlap{\hskip\@totalleftmargin\indent\the\everypar}}%
     \def\@itemfudge{\box\@tabfbox}%
     \@startline\ignorespaces}
```

\endtabbing

```
\def\endtabbing{%
  \@stopline\ifnum\@tabpush >\z@ \@badpoptabs \fi\endtrivlist}
```

Omitted \global added to \@rtab 17 Jun 86

\@rtab

```
\def\@rtab{\@stopfield\@addfield\ifnum \@curtab<\@hightab
      \global\advance\@curtab \@ne \else\@badtab\fi
      \@tempdima\dimen\@curtab
      \advance\@tempdima -\dimen\@curtabmar
      \advance\@tempdima -\wd\@curline
      \global\setbox\@curline\hbox{\unhbox\@curline\hskip\@tempdima}%
      \@startfield\ignorespaces}
```

\@settab

```
\def\@settab{\@stopfield\@addfield
  \ifnum \@curtab <\@maxtab
    \ifnum\@curtab =\@hightab
      \advance\@hightab \@ne
    \fi
    \global\advance\@curtab \@ne
  \else
    \@latex@error{Tab overflow}\@ehd
  \fi
  \dimen\@curtab \dimen\@curtabmar
  \advance\dimen\@curtab \wd\@curline
  \@startfield
  \ignorespaces}
```

\@ltab

```
\def\@ltab{\@ifatmargin\ifnum\@curtabmar >\@firsttab
      \global\advance\@curtab \m@ne \global\advance\@curtabmar\m@ne\else
      \@badtab\fi\else
      \@latex@error{\string\<\space in mid line}\@ehd\fi\ignorespaces}
```

\@tabplus

```
\def\@tabplus{%
  \ifnum\@nxttabmar<\@hightab
```

```
    \global\advance\@nxttabmar\@ne
  \else
    \@badtab
  \fi
  \ignorespaces}
```

\@tabminus

```
\def\@tabminus{%
  \ifnum\@nxttabmar>\@firsttab
    \global\advance\@nxttabmar\m@ne
  \else
    \@badtab
  \fi
  \ignorespaces}
```

\@tabrj

```
\def\@tabrj{%
  \@stopfield\@addfield\global\@rjfieldtrue\@startfield\ignorespaces}
```

\setbox\@curline made \global in \@tablab. 17 Jun 86

\@tablab

```
\def\@tablab{%
  \@stopfield
  \global\setbox\@curline\hbox{%
    \box\@curline
    \hskip-\wd\@curfield \hskip-\tabbingsep
    \box\@curfield
    \hskip\tabbingsep}%
  \@startfield
  \ignorespaces}
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\pushtabs}{Make commands robust}%
```

\pushtabs

```
\DeclareRobustCommand\pushtabs{%
  \@stopfield\@addfield\global\advance\@tabpush \@ne \begingroup
       \@contfield}
```

It is, in some sense, an error if, after the endgroup, the current tab setting is higher than the new value of \@hightab (which is a local variable). That this is allowed is a fundamental design flaw which is not going to be corrected now.

\poptabs

```
\DeclareRobustCommand\poptabs{\@stopfield\@addfield
  \ifnum \@tabpush >\z@
    \endgroup
    \global\advance\@tabpush \m@ne
    \ifnum \@curtab >\@hightab
      \global \@curtab \@hightab
      \@badtab
    \fi
  \else
    \@badpoptabs
  \fi
  \@contfield}
```

```
\DeclareRobustCommand\kill{\@stopfield\@startline\ignorespaces}
```

(*End definition for* `\@itabcr` *and others.*)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\pushtabs}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\pushtabs
⟨latexrelease⟩\kernel@make@fragile\poptabs
⟨latexrelease⟩\kernel@make@fragile\kill
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\tabbingsep`

```
\newdimen\tabbingsep
```

(*End definition for* `\tabbingsep`.)

1.2 array and tabular environments

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
ARRAY PARAMETERS:
 \arraycolsep
      : half the width separating columns in an array environment
 \tabcolsep
      : half the width separating columns in a tabular environment
 \arrayrulewidth
      : width of rules
 \doublerulesep
      : space between adjacent rules in array or tabular
 \arraystretch
      : line spacing in array and tabular environments is done by
        placing a strut in every row of height and depth
        \arraystretch times the height and depth of the strut
        produced by an ordinary \strut command.

PREAMBLE:
 The PREAMBLE argument of an array or tabular environment can
 contain the following:
   l,r,c   : indicate where entry is to be placed.
   |       : for vertical rule
   @{EXP} : inserts the text EXP in every column.
            \arraycolsep or \tabcolsep  spacing is suppressed.
   *{N}{PRE} : equivalent to writing N copies of PRE in the preamble.
               PRE may contain *{N'}{EXP'} expressions.
   p{LEN} : makes entry in parbox of width LEN.

SPECIAL ARRAY COMMANDS:
```

```
\multicolumn{N}{FORMAT}{ITEM} : replaces the next N column
 items by ITEM, formatted according to FORMAT.
 FORMAT should contain at most one l,r or c.
 If it contains none, then ITEM is ignored.

\vline : draws a vertical line the height of the current row.  May
         appear in an array element entry.
\hline : draws a horizontal line between rows.  Must appear either
         before the first entry (to appear above the first row) or
          right after a \\ command.  If followed by another \hline,
          then adds a \vskip of \doublerulesep.

\cline{i-j} : draws horizontal lines between rows covering columns
              i through j, inclusive.  Multiple commands may follow
              one another to provide lines covering several disjoint
              columns
\extracolsep{WIDTH} : for use inside an @ in the preamble.  Causes
            a WIDTH space to be added between columns for the rest
             of the columns.  This is in addition to the ordinary
             intercolumn space.

\array ==
  BEGIN
    \@acol    == \@arrayacol
    \@classz  == \@arrayclassz
    \@classiv == \@arrayclassiv
    \\        == \@arraycr
    \@halignto == NULL
    \@tabarray
  END

\endarray{NAME} ==  BEGIN  \crcr }}  END

\tabular  ==
  BEGIN
    \@halignto == NULL
    \@tabular
  END

\tabular*{WIDTH} ==
  BEGIN
    \@halignto == to WIDTH
    \@tabular
  END

\@tabular ==
  BEGIN
    \leavevmode
    \hbox { $
       \@acol    == \@tabacol
```

```
        \@classz  == \@tabclassz
        \@classiv == \@tabclassiv
        \\        == \@tabularcr
        \@tabarray
  END

\endtabular == BEGIN \crcr}} $} END

\@tabarray == if next char = [ then \@array else \@array[c] fi

\@array[POS]{PREAMBLE} ==
  BEGIN
    define \@arstrutbox to make \@arstrut produce strut of height
      and depth \arraystretch times the height and
      depth of a normal strut.
    \@mkpream{PREAMBLE}
    \@preamble == \halign \@halignto {\tabskip=0pt\@arstrut
                            eval{\@preamble}\tabskip = 0pt\cr %%}
    \@startpbox == \@@startpbox
    \@endpbox == \@@endpbox
    if POS = t then \vtop
               else if POS = b then \vbox
                                   else \vcenter
    fi              fi
   {
    \par          ==L {} % changed 92/09/18
    \@sharp       == #
    \protect      == \relax
    \lineskip     :=L 0pt
    \baselineskip :=L 0pt
    \@preamble
  END


\@arraycr ==
 BEGIN
   $              %% Prevents extra space at end of row's last entry.
   if next char = [
    then  \@argarraycr
    else  $ \cr          %% Needed to balance $
 END

\@argarraycr[LENGTH] ==
 BEGIN
   $                    %% Needed to balance $ of \@arraycr
   if LENGTH > 0
     then  \@tempdima := depth of \@arstrutbox + LENGTH
           \vrule height 0pt width 0pt depth \@tempdima
           \cr
     else  \cr \noalign{\vskip LENGTH}
```

END

`\@tabularcr` and `\@argtabularcr` same as `\@arraycr` and `\@argarraycr` except without the extra `$`'s.

End of historical LaTeX 2.09 comments.

`\extracolsep` This command needs to expand during the tabular preamble construction so can't be robust.

```
\def\extracolsep#1{\tabskip #1\relax}
```

(*End definition for* `\extracolsep`.)

`array` `\array` (*continued*)

```
\def\array{\let\@acol\@arrayacol \let\@classz\@arrayclassz
 \let\@classiv\@arrayclassiv
 \let\\\@arraycr\let\@halignto\@empty\@tabarray}
```

(*End definition for* `\array`.)

`\endarray`
`\endtabular`
`\endtabular*`

```
\def\endarray{\crcr\egroup\egroup}
\def\endtabular{\crcr\egroup\egroup $\egroup}
\expandafter \let \csname endtabular*\endcsname = \endtabular
```

(*End definition for* `\endarray`, `\endtabular`, *and* `\endtabular*`.)

`tabular` `\tabular` (*continued*)

```
\def\tabular{\let\@halignto\@empty\@tabular}
```

(*End definition for* `\tabular`.)

`\tabular*` Note that the change to use `\setlength` slightly alters the timing of the expansion and use of the length in `#1` but this is very unlikely to have any practical effect.

```
\@namedef{tabular*}#1{%
 \setlength\dimen@{#1}%
   \edef\@halignto{to\the\dimen@}\@tabular}
```

(*End definition for* `\tabular*`.)

`\@tabular`

```
\def\@tabular{\leavevmode \hbox \bgroup $\let\@acol\@tabacol
   \let\@classz\@tabclassz
   \let\@classiv\@tabclassiv \let\\\@tabularcr\@tabarray}
```

(*End definition for* `\@tabular`.)

`\@tabarray` RmS 91/11/04 added `\m@th`.

```
\def\@tabarray{\m@th\@ifnextchar[\@array{\@array[c]}}
```

(*End definition for* `\@tabarray`.)

RmS 1993/11/03 changed `\halign` to `\ialign` and removed superfluous `\tabskip` assignment

`\@array`

```
\def\@array[#1]#2{%
  \if #1t\vtop \else \if#1b\vbox \else \vcenter \fi\fi
```

```
\bgroup
```

This next bit of code sets up the strut and then builds the halign and its preamble according to the specification in the second argument.

This code has been moved inside the box. A side effect of this has been to expose what was a buglet in the previous version: since the `\@arstrut` below is expanded and contains an `\ifmmode` then it could produce an unnecessary extra box in every row, thus wasting 'lots of' main memory.

```
\setbox\@arstrutbox\hbox{%
  \vrule \@height\arraystretch\ht\strutbox
         \@depth\arraystretch \dp\strutbox
         \@width\z@}%
\@mkpream{#2}%
\edef\@preamble{%
  \ialign \noexpand\@halignto
    \bgroup \@arstrut \@preamble \tabskip\z@skip \cr}%
```

That is the end of setting up the preamble; now we reset things before executing the halign built-up in `\@preamble`. The restorations could be done by introducing an extra group, thus saving tokens.

```
\let\@startpbox\@@startpbox \let\@endpbox\@@endpbox
\let\tabularnewline\\%
  \let\par\@empty
  \let\@sharp##%
  \set@typeset@protect
  \lineskip\z@skip\baselineskip\z@skip
```

If the parsing of the preamble goes wrong there my be some characters left which TEX then tries to typeset, i.e., we would be in horizontal mode. That would produce an endless loop because the `\halign` expects vertical mode thus issues a `\par` but that is a no-op at this point. So we better test this case issue some error message and make a crude recovery by ending that horizontal mode with force. A better fix would be to ensure that we never pick up more than a single character token (not done).

```
  \ifhmode \@preamerr\z@ \@@par\fi
  \@preamble}
```

(*End definition for* `\@array`.)

`\@arraycr` Array version of `\\`.

```
\protected\def\@arraycr{%
  ${\ifnum0=`}\fi\@ifstar\@xarraycr\@xarraycr}
```

(*End definition for* `\@arraycr`.)

`\@arraycr`

```
\def\@xarraycr{\@ifnextchar[\@argarraycr{\ifnum0=`{\fi}${}\cr}}
```

(*End definition for* `\@arraycr`.)

`\@argarraycr`

```
\def\@argarraycr[#1]{%
  \ifnum0=`{\fi}${}\ifdim #1>\z@ \@xargarraycr{#1}\else
   \@yargarraycr{#1}\fi}
```

(*End definition for* `\@argarraycr`.)

\tabularnewline Tabular version of \\.

```
\let\tabularnewline\relax
```

(*End definition for* \tabularnewline.)

\@tabularcr

```
\protected\def\@tabularcr{%
  {\ifnum0=`}\fi\@ifstar\@xtabularcr\@xtabularcr}
```

(*End definition for* \@tabularcr.)

\@xtabularcr

```
\def\@xtabularcr{\@ifnextchar[\@argtabularcr{\ifnum0=`{\fi}\cr}}
```

(*End definition for* \@xtabularcr.)

\@argtabularcr

```
\def\@argtabularcr[#1]{%
  \ifnum0=`{\fi}%
    \ifdim #1>\z@
      \unskip\@xargarraycr{#1}%
    \else
      \@yargarraycr{#1}%
    \fi}
```

(*End definition for* \@argtabularcr.)

\@xargarraycr

```
\def\@xargarraycr#1{\@tempdima #1\advance\@tempdima \dp \@arstrutbox
   \vrule \@height\z@ \@depth\@tempdima \@width\z@ \cr}
```

(*End definition for* \@xargarraycr.)

\@yargarraycr

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@yargarraycr}{tabular support calc syntax}%
\def\@yargarraycr#1{\cr\noalign{\@vspace@calcify{#1}}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@yargarraycr}{tabular support calc syntax}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@yargarraycr#1{\cr\noalign{\vskip #1}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \@yargarraycr.)

`\multicolumn` *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
\multicolumn{NUMBER}{FORMAT}{ITEM} ==
  BEGIN
  \multispan{NUMBER}
  \begingroup
  \@addamp == null
  \@mkpream{FORMAT}
  \@sharp == ITEM
  \protect == \relax
  \@startpbox == \@@startpbox
  \@endpbox == \@@endpbox
  \@arstrut
  \@preamble
  \endgroup
  END
```

End of historical LaTeX 2.09 comments.

The command `\def\@addamp{}` was removed from `\multicolumn` on 6 Dec 86 because it caused embedded array environments not to work. I think that it was included originally to prevent an error message if the 2nd argument to the `\multicolumn` command had two column specifiers.

8 Feb 89 — `\hbox{}` added after `\@preamble` to correct bug that occurred if `\multicolumn` preceded `\\[D]` with `D > 0`, caused by `\\[]` command doing an `\unskip`, which removed `\tabcolsep` glue inserted by `\multicolumn`.

This has been made long so that, for example, a `p`-column can contain multiple paragraphs; maybe the arguments of `@`-expressions should also be able to contain multiple paragraphs.

```
\long\def\multicolumn#1#2#3{\multispan{#1}\begingroup
  \@mkpream{#2}%
  \def\@sharp{#3}\set@typeset@protect
  \let\@startpbox\@@startpbox\let\@endpbox\@@endpbox
  \@arstrut \@preamble\hbox{}\endgroup\ignorespaces}
```

(*End definition for* `\multicolumn`.)

Historical LaTeX 2.09 comments (not necessarily accurate any more):

Codes for classes and character numbers of array, tabular and multicolumn arguments.

Character	Class	Number
c	0	0
l	0	1
r	0	2
|	1	-
@	2	-
p	3	-
{@-exp}	4	-
{p-arg}	5	-

`\@testpach \foo` : expands `\foo`, which should be an array parameter

token, and sets \@chclass and \@chnum to its class and number. Uses \@lastchclass to distinguish 4 and 5

```
Preamble error codes
   0: 'illegal character'
   1: 'Missing @-exp'
   2: 'Missing p-arg'

\@addamp ==
  BEGIN if @firstamp = true then @firstamp := false
                                 else &                        fi
  END

\@mkpream TOKENLIST ==
  BEGIN
   @firstamp      := T
   \@lastchclass := 6
   \@preamble     == null
   \@sharp        == \relax
   \protect       == BEGIN \noexpand\protect\noexpand END
   \@startpbox    == \relax
   \@endpbox      == \relax
   \@expast{TOKENLIST}
   for \@nextchar := expand(\reserved@a)
     do  \@testpach{\@nextchar}
         case of \@chclass
           0 -> \@classz
           1 -> \@classi
              ...
           5 -> \@classv
         end case
         \@lastchclass := \@chclass
     od
     case of \@lastchclass
        0 -> \hskip \arraycolsep              % lrc
        1 ->                                   % |
        2 -> \@preamerr1 % 'Missing @-exp'    % @
        3 -> \@preamerr2 % 'Missing p-arg'    % p
        4 ->                                   % @-exp
        5 -> \hskip \arraycolsep              % p-exp
     end case
  END

 \@arrayclassz ==
   BEGIN
     \@preamble := \@preamble *
              case of \@lastchclass
                 0 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
                 1 -> \@addamp \hskip \arraycolsep
                 2 ->  % impossible
```

```
                3 ->  % impossible
                4 -> \@addamp
                5 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
                6 -> \@addamp \hskip \arraycolsep
              end case
            * case of \@chnum
                0 -> \hfil$\relax\@sharp$\hfil
                1 -> $\relax\@sharp$\hfil
                2 -> \hfil$\relax\@sharp$
              end case
  END

\@tabclassz == similar to \@arrayclassz

\@classi ==
 BEGIN
   \@preamble := \@preamble *
                case of \@lastchclass
                   0 -> \hskip \arraycolsep \@arrayrule
                   1 -> \hskip \doublerulesep \@arrayrule
                   2 -> % impossible
                   3 -> % impossible
                   4 -> \@arrayrule
                   5 -> \hskip \arraycolsep \@arrayrule
                   6 -> \@arrayrule
                end case
 END

\@classii ==
 BEGIN
   \@preamble := \@preamble *
                case of \@lastchclass
                   0     ->
                   1     -> \hskip .5\arrayrulewidth
                   2     -> % impossible
                   else ->
                end case
 END

\@classiii ==
 BEGIN
   \@preamble := \@preamble *
              case of \@lastchclass
                0 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
                1 -> \@addamp \hskip \arraycolsep
                2 -> % impossible
                3 -> % impossible
                4 -> \@addamp
                5 -> \hskip \arraycolsep \@addamp \hskip \arraycolsep
                6 -> \@addamp \hskip \arraycolsep
```

```
                end case
 END

\@arrayclassiv  ==
     BEGIN  \@preamble := \@preamble * $ \@nextchar$  END

\@tabclassiv   == same as \@arrayclassv except without the $ ... $

\@classv ==
  BEGIN
   \@preamble :=
       \@preamble * \@startpbox{\@nextchar}\ignorespaces\@sharp
                                \@endpbox
  END

\@expast{S}:
 Sets \reserved@a := S with all instances of *{N}{STRING}
 replaced by N copies of STRING, where N > 0.  An *
 appearing inside braces is ignored, but *-expressions
 inside STRING are expanded, so nested *-expressions are
 handled properly.

\@expast{S} == BEGIN  \@xexpast S *0x\@@  END

\@xexpast S1 *{N}{S2} S3 \@@ ==
 BEGIN
   \reserved@a   := S1
   \@tempcnta := N
   if \@tempcnta > 0
     then  while \@tempcnta > 0 do \reserved@a   := \reserved@a S2
                                   \@tempcnta := \@tempcnta - 1 od
           \reserved@b == \@xexpast
     else  \reserved@b == \@xexnoop
   fi
   \expandafter \reserved@b \reserved@a S3 \@@
 END
```

End of historical LaTeX 2.09 comments.

\@xexnoop

```
\def\@xexnoop #1\@@{}
```

(*End definition for* \@xexnoop.)

\@expast

```
\def\@expast#1{\@xexpast #1*0x\@@}
```

(*End definition for* \@expast.)

\@xexpast

```
\def\@xexpast#1*#2#3#4\@@{%
  \edef\reserved@a{#1}%
  \@tempcnta#2\relax
  \ifnum\@tempcnta>\z@
    \@whilenum\@tempcnta>\z@\do
       {\edef\reserved@a{\reserved@a#3}\advance\@tempcnta \m@ne}%
    \let\reserved@b\@xexpast
  \else
    \let\reserved@b\@xexnoop
  \fi
  \expandafter\reserved@b\reserved@a #4\@@}
```

(*End definition for* `\@xexpast`.)

\if@firstamp
\@addamp

```
\newif\if@firstamp
```

```
\def\@addamp{%
  \if@firstamp
    \@firstampfalse
  \else
    \edef\@preamble{\@preamble &}%
  \fi}
```

(*End definition for* `\if@firstamp` *and* `\@addamp`.)

\@arrayacol
\@tabacol
\@ampacol
\@acolampacol

```
\def\@arrayacol{\edef\@preamble{\@preamble \hskip \arraycolsep}}
\def\@tabacol{\edef\@preamble{\@preamble \hskip \tabcolsep}}
\def\@ampacol{\@addamp \@acol}
\def\@acolampacol{\@acol\@addamp\@acol}
```

(*End definition for* `\@arrayacol` *and others.*)

\@mkpream

```
\def\@mkpream#1{\@firstamptrue\@lastchclass6
  \let\@preamble\@empty
  \let\protect\@unexpandable@protect
  \let\@sharp\relax
  \let\@startpbox\relax\let\@endpbox\relax
  \@expast{#1}%
  \expandafter\@tfor \expandafter
    \@nextchar \expandafter:\expandafter=\reserved@a\do
       {\@testpach\@nextchar
    \ifcase \@chclass \@classz \or \@classi \or \@classii \or \@classiii
      \or \@classiv \or\@classv \fi\@lastchclass\@chclass}%
  \ifcase \@lastchclass \@acol
      \or \or \@preamerr \@ne\or \@preamerr \tw@\or \or \@acol \fi}
```

(*End definition for* `\@mkpream`.)

\@arrayclassz

```
\def\@arrayclassz{\ifcase \@lastchclass \@acolampacol \or \@ampacol \or
   \or \or \@addamp \or
   \@acolampacol \or \@firstampfalse \@acol \fi
\edef\@preamble{\@preamble
  \ifcase \@chnum
     \hfil$\relax\@sharp$\hfil \or $\relax\@sharp$\hfil
    \or \hfil$\relax\@sharp$\fi}}
```

(*End definition for* `\@arrayclassz`.)

\@tabclassz RmS 91/08/14 inserted extra braces around entry for NFSS

```
\def\@tabclassz{%
  \ifcase\@lastchclass
    \@acolampacol
  \or
    \@ampacol
  \or
  \or
  \or
    \@addamp
  \or
    \@acolampacol
  \or
    \@firstampfalse\@acol
  \fi
  \edef\@preamble{%
    \@preamble{%
      \ifcase\@chnum
        \hfil

        \hskip1sp%
        \ignorespaces\@sharp\unskip\hfil
      \or

        \hskip1sp\ignorespaces\@sharp\unskip\hfil
      \or
        \hfil\hskip1sp\ignorespaces\@sharp\unskip
      \fi}}}
```

(*End definition for* `\@tabclassz`.)

\@classi

```
\def\@classi{%
  \ifcase\@lastchclass
    \@acol\@arrayrule
  \or
    \@addtopreamble{\hskip \doublerulesep}\@arrayrule
  \or
  \or
  \or
    \@arrayrule
  \or
    \@acol\@arrayrule
  \or
```

```
    \@arrayrule
  \fi}
```

(*End definition for* `\@classi`.)

`\@classii`

```
\def\@classii{%
  \ifcase\@lastchclass
  \or
    \@addtopreamble{\hskip .5\arrayrulewidth}%
  \fi}
```

(*End definition for* `\@classii`.)

`\@classiii`

```
\def\@classiii{\ifcase \@lastchclass \@acolampacol \or
   \@addamp\@acol \or
   \or \or \@addamp \or
   \@acolampacol \or \@ampacol \fi}
```

(*End definition for* `\@classiii`.)

`\@tabclassiv`

```
\def\@tabclassiv{\@addtopreamble\@nextchar}
```

(*End definition for* `\@tabclassiv`.)

`\@arrayclassiv`

```
\def\@arrayclassiv{\@addtopreamble{$\@nextchar$}}
```

(*End definition for* `\@arrayclassiv`.)

`\@classv`

```
\def\@classv{\@addtopreamble{\@startpbox{\@nextchar}\ignorespaces
\@sharp\@endpbox}}
```

(*End definition for* `\@classv`.)

`\@addtopreamble`

```
\def\@addtopreamble#1{\edef\@preamble{\@preamble #1}}
```

(*End definition for* `\@addtopreamble`.)

`\@chclass`
`\@lastchclass`
`\@chnum`

```
\newcount\@chclass
\newcount\@lastchclass
\newcount\@chnum
```

(*End definition for* `\@chclass`, `\@lastchclass`, *and* `\@chnum`.)

`\arraycolsep`
`\tabcolsep`
`\arrayrulewidth`
`\doublerulesep`

```
\newdimen\arraycolsep
\newdimen\tabcolsep
\newdimen\arrayrulewidth
\newdimen\doublerulesep
```

(*End definition for* `\arraycolsep` *and others.*)

`\arraystretch`

```
\def\arraystretch{1}    % Default value.
```

(*End definition for* `\arraystretch`.)

`\@arstrutbox`
`\@arstrut`

```
\newbox\@arstrutbox
\def\@arstrut{%
  \relax\ifmmode\copy\@arstrutbox\else\unhcopy\@arstrutbox\fi}
```

(*End definition for* `\@arstrutbox` *and* `\@arstrut`.)

`\@arrayrule`

```
\def\@arrayrule{\@addtopreamble{\hskip -.5\arrayrulewidth
   \vrule \@width \arrayrulewidth\hskip -.5\arrayrulewidth}}
```

(*End definition for* `\@arrayrule`.)

`\@testpatch`

```
\def\@testpach#1{\@chclass \ifnum \@lastchclass=\tw@ 4 \else
    \ifnum \@lastchclass=3 5 \else
     \z@ \if #1c\@chnum \z@ \else
                                \if #1l\@chnum \@ne \else
                                \if #1r\@chnum \tw@ \else
          \@chclass \if #1|\@ne \else
                    \if #1@\tw@ \else
                    \if #1p3 \else \z@ \@preamerr 0\fi
  \fi  \fi  \fi  \fi  \fi  \fi
\fi}
```

(*End definition for* `\@testpatch`.)

`\hline`

```
\def\hline{%
  \noalign{\ifnum0=`}\fi\hrule \@height \arrayrulewidth \futurelet
   \reserved@a\@xhline}
```

(*End definition for* `\hline`.)

`\@xhline`

```
\def\@xhline{\ifx\reserved@a\hline
               \vskip\doublerulesep
```

Measure from the middle of the rules.

```
               \vskip-\arrayrulewidth
             \fi
      \ifnum0=`{\fi}}
```

(*End definition for* `\@xhline`.)

`\vline`

```
\def\vline{\vrule \@width \arrayrulewidth}
```

(*End definition for* `\vline`.)

\cline
\@cline

The old LaTeX2.09 implementation of \cline used up quite a lot of memory and two precious count registers. This new (1995/09/14) implementation does not use any count registers. It is coded in a way that depends heavily on the definition of \multispan so that command has been moved here from the file ltplain.dtx.

These counters are no longer declared.

```
\newcount\@cla
\newcount\@clb
```

```
\def\cline#1{\@cline#1\@nil}
```

```
\def\@cline#1-#2\@nil{%
  \omit
```

Use the counter from \multispan.

```
  \@multicnt#1%
  \advance\@multispan\m@ne
  \ifnum\@multicnt=\@ne\@firstofone{&\omit}\fi
  \@multicnt#2%
  \advance\@multicnt-#1%
  \advance\@multispan\@ne
```

The original had \unskip at this point, but how could a skip get here ???

```
  \leaders\hrule\@height\arrayrulewidth\hfill
  \cr
```

This is back spacing is fairly horrible, but it is what happened in the old version... An alternative would be to make \cline look ahead for a following \cline as does \hline. This would alter the spacing in existing documents so keep the old version in the kernel. Perhaps a package should do this differently.

```
  \noalign{\vskip-\arrayrulewidth}}
```

(*End definition for* \cline *and* \@cline.)

\mscount

The \mscount counter is no longer declared, saving a csname and a register. It is declared in compatibility mode.

(*End definition for* \mscount.)

\multispan
\@multispan
\sp@n

Modify \multispan slightly from its plain TeX definition to allow more efficient code sharing with \multicolumn. Also share a count register with \multiput.

```
\def\multispan{\omit\@multispan}
```

```
\def\@multispan#1{%
  \@multicnt#1\relax
  \loop\ifnum\@multicnt>\@ne \sp@n\repeat}
```

```
\def\sp@n{\span\omit\advance\@multicnt\m@ne}
```

(*End definition for* \multispan, \@multispan, *and* \sp@n.)

\@startpbox
\@endpbox

Helper macros for 'p' columns.

\@startpbox{⟨*width*⟩} *text* \egroup is essentially \parbox{⟨*width*⟩}{⟨*text*⟩}

\@endpbox is essentially \unskip \strut \par \egroup\hfil (Changed 14 Jan 89) (changed again 1994/05/13)

```
\def\@startpbox#1{\vtop\bgroup \setlength\hsize{#1}\@arrayparboxrestore}
```

```
\def\@endpbox{\@finalstrut\@arstrutbox\par\egroup\hfil}
```

14 Jan 89: Def of `\@endpbox` changed from
`\def\@endpbox{\par\vskip\dp\@arstrutbox\egroup\hfil}`
so vertical spacing works out right if the last line of a 'p' entry has a descender.

(*End definition for* `\@startpbox` *and* `\@endpbox`.)

`\@@startpbox`
`\@@endpbox`

```
\let\@@startpbox=\@startpbox
\let\@@endpbox=\@endpbox
```

(*End definition for* `\@@startpbox` *and* `\@@endpbox`.)

⟨/2ekernel⟩

File M
ltpictur.dtx

1 Picture Mode

Picture mode commands. In addition to the commands available in LaTeX2.09, This section adds the new `\qbezier` command for drawing curves.

`\qbezier` `\qbezier[`⟨*N*⟩`](`⟨*AX,AY*⟩`)(`⟨*BX,BY*⟩`)(`⟨*CX,CY*⟩`)` plots a quadratic Bezier curve from `(`⟨*AX,AY*⟩`)` to `(`⟨*CX,CY*⟩`)`, with `(`⟨*BX,BY*⟩`)` as the third Bezier point, using $N+1$ points equally spaced parametrically. If $N = 0$ (the default value), then a sufficient number of points are used to draw a connected curve–except that at most `\qbeziermax`+1 points are drawn. A "point" is a square of side `\@wholewidth`.

`\bezier` In addition, to be compatible with the old `bezier` package, a variant of this command, `\bezier`, is defined, in which the first argument is not optional.

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\unitlength      = value of dimension argument
\@wholewidth     = current line width
\@halfwidth      = half of current line width
\@linefnt        = font for drawing lines
\@circlefnt      = font for drawing circles

\linethickness{DIM} : Sets the width of horizontal and vertical lines
    in a picture to DIM.  Does not change width of slanted lines
    or circles.   Width of all lines reset by \thinlines and
    \thicklines

\picture(XSIZE,YSIZE)(XORG,YORG)
  BEGIN
    \@picht :=L YSIZE * \unitlength
    box \@picbox :=
         \hb@xt@ XSIZE * \unitlength
           {\hskip -XORG * \unitlength
            \lower YORG * \unitlength
            \hbox{
            \ignorespaces     %% added 13 June 89
  END

\endpicture ==
  BEGIN
                  } \hss }
                  height of \@picbox := \@picht
                  depth   of \@picbox := 0
                  \mbox{\box\@picbox}   %% change 26 Aug 91
  END

\put(X, Y){OBJ} ==
  BEGIN
```

```
    \@killglue
    \raise Y * \unitlength  \hb@xt@ 0pt { \hskip X * \unitlength
                                          OBJ \hss            }
    \ignorespaces
  END

\multiput(X,Y)(DELX,DELY){N}{OBJ} ==
  BEGIN
   \@killglue
   \@multicnt := N
   \@xdim  := X * \unitlength
   \@ydim  := Y * \unitlength
   while \@multicnt > 0
     do \raise \@ydim \hb@xt@ 0pt { \hskip \@xdim
                                          OBJ \hss   }
        \@multicnt := \@multicnt - 1
        \@xdim     := \@xdim + DELX * \unitlength
        \@ydim     := \@ydim + DELY * \unitlength
     od
   \ignorespaces
  END
```

`\shortstack[POS]{TEXT}` : Makes a `\vbox` containing TEXT stacked as a one-column array, positioned l, r or c as indicated by POS.

End of historical LaTeX 2.09 comments.

The '2ekernel' code ensures that a `\usepackage{autopict}` is essentially ignored if a 'full' format is being used that has picture mode already in the format.

```
⟨2ekernel⟩\expandafter\let\csname ver@autopict.sty\endcsname\fmtversion
```

`\@wholewidth`
`\@halfwidth`

```
⟨*2ekernel⟩
\newdimen\@wholewidth
\newdimen\@halfwidth
```

(*End definition for* `\@wholewidth` *and* `\@halfwidth`.)

`\unitlength`

```
\newdimen\unitlength \unitlength =1pt
```

(*End definition for* `\unitlength`.)

`\@picbox`
`\@picht`

```
\newbox\@picbox
\newdimen\@picht
```

(*End definition for* `\@picbox` *and* `\@picht`.)

`\@defaultunitsset` Set a length register, `#1`, accepting number or an etex length expression, `#2`, with default unit, `#3`.

The register name in `#1` can be prefixed by `\advance` so that the register is incremented by the supplied value.

`\@defaultunitsset{\advance\@vxx}{\textwidth-15pt}\unitlength`

`#3` can be a literal unit such as `cm` or a length register such as `\unitlength`.

This is used in all `picture` commands that take picture coordinates. So `\put(2,2)` as previously but now `\put(\textwidth-5cm,0.4\texteight)` Note that you can only use expressions with lengths, `\put(1+2,0)` is not supported.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@defaultunitsset}{default units}%
\def\@defaultunitsset#1#2#3{%
  \@defaultunits#1\dimexpr#2#3\relax\relax\@nnil}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@defaultunitsset}{default units}%
⟨latexrelease⟩\let\@defaultunitsset\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@defaultunitsset`.)

`picture` `\picture` `#1` should be white space.

`#1` should be a `(` (eating any white space before the bracket),

`\pictur@`

```
\long\def\picture#1{\pictur@#1}
\def\pictur@(#1){%
  \@ifnextchar({\@picture(#1)}{\@picture(#1)(0,0)}}
```

(*End definition for* `\picture` *and* `\pictur@`.)

`\@picture`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@picture}{default units}%
\def\@picture(#1,#2)(#3,#4){%
  \@defaultunitsset\@picht{#2}\unitlength
  \@defaultunitsset\@tempdimc{#1}\unitlength
  \setbox\@picbox\hb@xt@\@tempdimc\bgroup
    \@defaultunitsset\@tempdimc{#3}\unitlength
    \hskip -\@tempdimc
    \@defaultunitsset\@tempdimc{#4}\unitlength
    \lower\@tempdimc\hbox\bgroup
      \ignorespaces}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@picture}{default units}%
⟨latexrelease⟩\def\@picture(#1,#2)(#3,#4){%
⟨latexrelease⟩  \@picht#2\unitlength
⟨latexrelease⟩  \setbox\@picbox\hb@xt@#1\unitlength\bgroup
⟨latexrelease⟩    \hskip -#3\unitlength
⟨latexrelease⟩    \lower #4\unitlength\hbox\bgroup
⟨latexrelease⟩      \ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@picture`.)

`\endpicture`

```
\def\endpicture{%
  \egroup\hss\egroup
    \ht\@picbox\@picht\dp\@picbox\z@
    \mbox{\box\@picbox}}
```

(*End definition for* `\endpicture`.)

In the definitions of `\put` and `\multiput`, `\hskip` was replaced by `\kern` just in case arg `#3` = "plus". (Bug detected by Don Knuth. changed 20 Jul 87).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\put}{default units}%
⟨latexrelease⟩\expandafter\let\csname put \endcsname\@undefind
\long\def\put(#1,#2)#3{%
  \@killglue
  \@defaultunitsset\@tempdimc{#2}\unitlength
  \raise\@tempdimc
  \hb@xt@\z@{%
    \@defaultunitsset\@tempdimc{#1}\unitlength
    \kern\@tempdimc
    #3\hss}%
  \ignorespaces}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\put}{default units}%
⟨latexrelease⟩\expandafter\let\csname put \endcsname\@undefind
⟨latexrelease⟩\long\def\put(#1,#2)#3{%
⟨latexrelease⟩  \@killglue\raise#2\unitlength
⟨latexrelease⟩  \hb@xt@\z@{\kern#1\unitlength #3\hss}%
⟨latexrelease⟩  \ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\multiput` `#3` had better be a `(`.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
```

```
⟨latexrelease⟩                  {\multiput}{default units}%
⟨latexrelease⟩\expandafter\let\csname multiput \endcsname\@undefind
\def\multiput(#1,#2)#3{%
  \@defaultunitsset\@xdim{#1}\unitlength
  \@defaultunitsset\@ydim{#2}\unitlength
   \@multiput(}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\multiput}{default units}%
⟨latexrelease⟩\expandafter\let\csname multiput \endcsname\@undefind
⟨latexrelease⟩\def\multiput(#1,#2)#3{%
⟨latexrelease⟩  \@xdim #1\unitlength
⟨latexrelease⟩  \@ydim #2\unitlength
⟨latexrelease⟩   \@multiput(}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\multiput`.)

`\@multiput`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@multiput}{default units}%
\long\def\@multiput(#1,#2)#3#4{%
  \@killglue\@multicnt #3\relax
  \@whilenum \@multicnt >\z@\do
    {\raise\@ydim\hb@xt@\z@{\kern\@xdim #4\hss}%
     \advance\@multicnt\m@ne
     \@defaultunitsset{\advance\@xdim}{#1}\unitlength
     \@defaultunitsset{\advance\@ydim}{#2}\unitlength}%
  \ignorespaces}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@multiput}{default units}%
⟨latexrelease⟩\long\def\@multiput(#1,#2)#3#4{%
⟨latexrelease⟩  \@killglue\@multicnt #3\relax
⟨latexrelease⟩  \@whilenum \@multicnt >\z@\do
⟨latexrelease⟩    {\raise\@ydim\hb@xt@\z@{\kern\@xdim #4\hss}%
⟨latexrelease⟩     \advance\@multicnt\m@ne
⟨latexrelease⟩     \advance\@xdim#1\unitlength\advance\@ydim#2\unitlength}%
⟨latexrelease⟩  \ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@multiput`.)

`\@killglue`

```
\def\@killglue{\unskip\@whiledim \lastskip >\z@\do{\unskip}}
```

(*End definition for* `\@killglue`.)

\thinlines
\thicklines

```
\DeclareRobustCommand\thinlines{\let\@linefnt\tenln
  \let\@circlefnt\tencirc
  \@wholewidth\fontdimen8\tenln \@halfwidth .5\@wholewidth}
\DeclareRobustCommand\thicklines{\let\@linefnt\tenlnw
  \let\@circlefnt\tencircw
  \@wholewidth\fontdimen8\tenlnw \@halfwidth .5\@wholewidth}
```

(*End definition for* \thinlines *and* \thicklines.)

\linethickness

```
\DeclareRobustCommand*\linethickness[1]
   {\@wholewidth #1\relax \@halfwidth .5\@wholewidth \ignorespaces}
```

(*End definition for* \linethickness.)

\ishortstack

```
\def\shortstack{\@ifnextchar[\@shortstack{\@shortstack[c]}}
```

(*End definition for* \ishortstack.)

\@ishortstack

```
\def\@shortstack[#1]{%
  \leavevmode
  \vbox\bgroup
    \baselineskip-\p@\lineskip 3\p@
    \let\mb@l\hss\let\mb@r\hss
    \expandafter\let\csname mb@#1\endcsname\relax
    \let\\\@stackcr
    \@ishortstack}
```

(*End definition for* \@ishortstack.)

\@ishortstack

```
\def\@ishortstack#1{\ialign{\mb@l {##}\unskip\mb@r\cr #1\crcr}\egroup}
```

(*End definition for* \@ishortstack.)

\@stackcr
\@ixstackcr

```
\protected\def\@stackcr{\@ifstar\@ixstackcr\@ixstackcr}
\def\@ixstackcr{\@ifnextchar[\@istackcr{\cr\ignorespaces}}
```

(*End definition for* \@stackcr *and* \@ixstackcr.)

\@istackcr

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@istackcr}{\shortstack calc support}%
\def\@istackcr[#1]{\cr\noalign{\@vspace@calcify{#1}}\ignorespaces}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@istackcr}{\shortstack calc support}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@istackcr[#1]{\cr\noalign{\vskip #1}\ignorespaces}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@istackcr`.)

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\line(X,Y){LEN} ==
BEGIN
 \@xarg    := X
 \@yarg    := Y
 \@linelen := LEN * \unitlength
 if \@xarg = 0
    then \@vline
    else if \@yarg = 0
            then \@hline
            else \@sline
         if
 if
END

\@sline ==
 BEGIN
   if \@xarg < 0
     then @negarg := T
          \@xarg  := -\@xarg
          \@yyarg := -\@yarg
     else @negarg := F
          \@yyarg := \@yarg
   fi
   \@tempcnta := |\@yyarg|
   if \@tempcnta > 6
     then error: 'LATEX ERROR: Illegal \line or \vector argument.'
          \@tempcnta := 0
   fi
   \box\@linechar := \hbox{\@linefnt \@getlinechar(\@xarg,\@yyarg) }
    if \@yarg > 0 then \@upordown = \raise
                         \@clnht := 0
                   else \@upordown = \lower
                        \@clnht := height of \box\@linechar
    fi
    \@clnwd  := width of \box\@linechar
    if @negarg
      then \hskip - width of \box\@linechar
           \reserved@a == \hskip - 2* width of box \@linechar
      else \reserved@a == \relax
    fi
 %% Put out integral number of line segments
```

```
    while \@clnwd <  \@linelen
      do  \@upordown \@clnht \copy\@linechar
          \reserved@a
          \@clnht := \@clnht + ht of \box\@linechar
          \@clnwd := \@clnwd + width of \box\@linechar
      od

 %% Put out last segment
    \@clnht := \@clnht - height of \box\@linechar
    \@clnwd := \@clnwd - width of \box\@linechar
    \@tempdima   := \@linelen - \@clnwd
    \@tempdimb   := \@tempdima - width of \box\@linechar
    if @negarg  then \hskip -\@tempdimb
                 else \hskip  \@tempdimb
    fi
    \@tempdima   := 1000 * \@tempdima
    \@tempcnta   := \@tempdima / width of \box\@linechar
    \@tempdima   := (\@tempcnta * ht of \box\@linechar)/1000
    \@clnht := \@clnht + \@tempdima
    if \@linelen < width of box\@linechar
        then \hskip width of box\@linechar
        else \hbox{\@upordown \@clnht \copy\@linechar}
    fi
END

\@hline ==
  BEGIN
    if \@xarg < 0 then  \hskip -\@linelen \fi
    \vrule height \@halfwidth depth \@halfwidth width \@linelen
    if \@xarg < 0 then  \hskip -\@linelen \fi
 END

\@vline == if \@yarg < 0 \@downline else \@upline  fi


\@getlinechar(X,Y) ==
  BEGIN
    \@tempcnta := 8*X - 9
    if Y > 0
      then \@tempcnta := \@tempcnta + Y
      else \@tempcnta := \@tempcnta - Y + 64
    fi
    \char\@tempcnta
  END

\vector(X,Y){LEN} ==
BEGIN
 \@xarg    := X
 \@yarg    := Y
 \@linelen := LEN * \unitlength
```

```
 if \@xarg = 0
    then \@vvector
    else if \@yarg = 0
            then \@hvector
            else \@svector
         if
 if
END

\@hvector ==
  BEGIN
    \@hline
    {\@linefnt if \@xarg < 0 then  \@getlarrow(1,0)
                                else  \@getrarrow(1,0)
                fi}
  END

\@vvector == if \@yarg < 0 \@downvector else \@upvector  fi

\@svector ==
 BEGIN
  \@sline
  \@tempcnta := |\@yarg|
    if  \@tempcnta < 5
       then  \hskip - width of \box\@linechar
             \@upordown \@clnht \hbox
                      {\@linefnt
                       if @negarg then \@getlarrow(\@xarg,\@yyarg)
                                  else \@getrarrow(\@xarg,\@yyarg)
                       fi }
       else  error: 'LaTeX ERROR: Illegal \line or \vector argument.'
    fi
 END

\@getlarrow(X,Y) ==
 BEGIN
  if Y = 0
    then \@tempcnta := '33
    else \@tempcnta := 16 * X  -  9
         \@tempcntb := 2 * Y
         if \@tempcntb > 0
           then  \@tempcnta := \@tempcnta  +  \@tempcntb
           else  \@tempcnta := \@tempcnta  -  \@tempcntb +  64
         fi
  fi
  \char\@tempcnta
 END

\@getrarrow(X,Y) ==
 BEGIN
```

```
\@tempcntb := |Y|
case of \@tempcntb
  0 : \@tempcnta := '55
  1 : if X < 3
        then \@tempcnta :=  24*X - 6
        else if X = 3
               then \@tempcnta := 49
               else \@tempcnta := 58  fi
      fi
  2 : if X < 3
        then \@tempcnta :=  24*X - 3
        else \@tempcnta := 51      % X must = 3
      fi
  3 : \@tempcnta := 16*X - 2
  4 : \@tempcnta := 16*X + 7
endcase
if Y < 0
  then \@tempcnta := \@tempcnta + 64
fi
\char\@tempcnta
END
```

End of historical LaTeX 2.09 comments.

`\if@negarg`

```
\newif\if@negarg
```

(*End definition for* `\if@negarg`.)

`\line`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\line}{default units}%
⟨latexrelease⟩\expandafter\let\csname line \endcsname\@undefind
\def\line(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
  \@defaultunitsset\@linelen{#3}\unitlength
  \ifdim\@linelen<\z@\@badlinearg\else
    \ifnum\@xarg =\z@ \@vline
      \else \ifnum\@yarg =\z@ \@hline \else \@sline\fi
    \fi
  \fi}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\line}{default units}%
⟨latexrelease⟩\expandafter\let\csname line \endcsname\@undefind
⟨latexrelease⟩\def\line(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
⟨latexrelease⟩  \@linelen #3\unitlength
⟨latexrelease⟩  \ifdim\@linelen<\z@\@badlinearg\else
⟨latexrelease⟩    \ifnum\@xarg =\z@ \@vline
⟨latexrelease⟩      \else \ifnum\@yarg =\z@ \@hline \else \@sline\fi
⟨latexrelease⟩    \fi
```

```
⟨latexrelease⟩   \fi}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\line`.)

`\@sline`

```
\def\@sline{%
  \ifnum\@xarg<\z@ \@negargtrue \@xarg -\@xarg \@yyarg -\@yarg
  \else \@negargfalse \@yyarg \@yarg \fi
\ifnum \@yyarg >\z@ \@tempcnta\@yyarg \else \@tempcnta -\@yyarg \fi
\ifnum\@tempcnta>6 \@badlinearg\@tempcnta\z@ \fi
\ifnum\@xarg>6 \@badlinearg\@xarg \@ne \fi
\setbox\@linechar\hbox{\@linefnt\@getlinechar(\@xarg,\@yyarg)}%
```

If we have something like `\line(5,5){30}` the `\@linechar` will not contain a char and later on we will end in an infinite loop. So we check the width of the box and put in something as an emergency fix if necessary.

```
\ifdim\wd\@linechar=\z@
   \setbox\@linechar\hbox{.}%
   \@badlinearg
\fi
\ifnum \@yarg >\z@ \let\@upordown\raise \@clnht\z@
   \else\let\@upordown\lower \@clnht \ht\@linechar\fi
\@clnwd \wd\@linechar
\if@negarg
  \hskip -\wd\@linechar \def\reserved@a{\hskip -2\wd\@linechar}%
\else
     \let\reserved@a\relax
\fi
\@whiledim \@clnwd <\@linelen \do
  {\@upordown\@clnht\copy\@linechar
   \reserved@a
   \advance\@clnht \ht\@linechar
   \advance\@clnwd \wd\@linechar}%
\advance\@clnht -\ht\@linechar
\advance\@clnwd -\wd\@linechar
\@tempdima\@linelen\advance\@tempdima -\@clnwd
\@tempdimb\@tempdima\advance\@tempdimb -\wd\@linechar
\if@negarg \hskip -\@tempdimb \else \hskip \@tempdimb \fi
\multiply\@tempdima \@m
\@tempcnta \@tempdima
\@tempdima \wd\@linechar \divide\@tempcnta \@tempdima
\@tempdima \ht\@linechar \multiply\@tempdima \@tempcnta
\divide\@tempdima \@m
\advance\@clnht \@tempdima
\ifdim \@linelen <\wd\@linechar
   \hskip \wd\@linechar
```

Warn if line gets so short that it can't be printed. But don't warn if it is exactly zero since that was probably deliberate (e.g., to get a vector head only).

```
   \ifdim \@linelen = \z@
   \else
     \@picture@warn
   \fi
```

```
  \else\@upordown\@clnht\copy\@linechar\fi}
```

(*End definition for* `\@sline`.)

`\@hline`

```
\def\@hline{\ifnum \@xarg <\z@ \hskip -\@linelen \fi
\vrule \@height \@halfwidth \@depth \@halfwidth \@width \@linelen
\ifnum \@xarg <\z@ \hskip -\@linelen \fi}
```

(*End definition for* `\@hline`.)

`\@getlinechar`

```
\def\@getlinechar(#1,#2){\@tempcnta#1\relax\multiply\@tempcnta 8%
  \advance\@tempcnta -9\ifnum #2>\z@ \advance\@tempcnta #2\relax\else
  \advance\@tempcnta -#2\relax\advance\@tempcnta 64 \fi
  \char\@tempcnta}
```

(*End definition for* `\@getlinechar`.)

`\vector`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\vector}{default units}%
⟨latexrelease⟩\expandafter\let\csname vector \endcsname\@undefind
\def\vector(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
  \@tempcnta \ifnum\@xarg<\z@ -\@xarg\else\@xarg\fi
  \ifnum\@tempcnta<5\relax
  \@defaultunitsset\@linelen{#3}\unitlength
  \ifdim\@linelen<\z@\@badlinearg\else
    \ifnum\@xarg =\z@ \@vvector
      \else \ifnum\@yarg =\z@ \@hvector \else \@svector\fi
    \fi
  \fi
  \else\@badlinearg\fi}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\vector}{default units}%
⟨latexrelease⟩\expandafter\let\csname vector \endcsname\@undefind
⟨latexrelease⟩\def\vector(#1,#2)#3{\@xarg #1\relax \@yarg #2\relax
⟨latexrelease⟩  \@tempcnta \ifnum\@xarg<\z@ -\@xarg\else\@xarg\fi
⟨latexrelease⟩  \ifnum\@tempcnta<5\relax
⟨latexrelease⟩  \@linelen #3\unitlength
⟨latexrelease⟩  \ifdim\@linelen<\z@\@badlinearg\else
⟨latexrelease⟩    \ifnum\@xarg =\z@ \@vvector
⟨latexrelease⟩      \else \ifnum\@yarg =\z@ \@hvector \else \@svector\fi
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \else\@badlinearg\fi}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\vector`.)

\@hvector

```
\def\@hvector{\@hline\hb@xt@\z@{\@linefnt
 \ifnum \@xarg <\z@ \@getlarrow(1,0)\hss\else
    \hss\@getrarrow(1,0)\fi}}
```

(*End definition for* \@hvector.)

\@vvector

```
\def\@vvector{\ifnum \@yarg <\z@ \@downvector \else \@upvector \fi}
```

(*End definition for* \@vvector.)

\@svector

```
\def\@svector{\@sline
  \@tempcnta\@yarg \ifnum\@tempcnta <\z@ \@tempcnta -\@tempcnta\fi
  \ifnum\@tempcnta <5%
    \hskip -\wd\@linechar
    \@upordown\@clnht \hbox{\@linefnt  \if@negarg
    \@getlarrow(\@xarg,\@yyarg)\else \@getrarrow(\@xarg,\@yyarg)\fi}%
  \else\@badlinearg\fi}
```

(*End definition for* \@svector.)

\@getlarrow

```
\def\@getlarrow(#1,#2){\ifnum #2=\z@ \@tempcnta 27 % '33
  \else
  \@tempcnta #1\relax\multiply\@tempcnta \sixt@@n
  \advance\@tempcnta -9 \@tempcntb #2\relax\multiply\@tempcntb \tw@
  \ifnum \@tempcntb >\z@ \advance\@tempcnta \@tempcntb
  \else\advance\@tempcnta -\@tempcntb\advance\@tempcnta 64
  \fi\fi\char\@tempcnta}
```

(*End definition for* \@getlarrow.)

\@getrarrow

```
\def\@getrarrow(#1,#2){\@tempcntb #2\relax
\ifnum\@tempcntb <\z@ \@tempcntb -\@tempcntb\relax\fi
\ifcase \@tempcntb\relax \@tempcnta 45  % '55
\or
\ifnum #1<\thr@@ \@tempcnta #1\relax\multiply\@tempcnta
24\advance\@tempcnta -6 \else \ifnum #1=\thr@@ \@tempcnta 49
\else\@tempcnta 58 \fi\fi\or
\ifnum #1<\thr@@ \@tempcnta=#1\relax\multiply\@tempcnta
24\advance\@tempcnta -\thr@@ \else \@tempcnta 51 \fi\or
\@tempcnta #1\relax\multiply\@tempcnta
\sixt@@n \advance\@tempcnta -\tw@ \else
\@tempcnta #1\relax\multiply\@tempcnta
\sixt@@n \advance\@tempcnta 7 \fi\ifnum #2<\z@ \advance\@tempcnta 64 \fi
\char\@tempcnta}
```

(*End definition for* \@getrarrow.)

\@vline

```
\def\@vline{\ifnum \@yarg <\z@ \@downline \else \@upline\fi}
```

(*End definition for* `\@vline`.)

`\@upline`

```
\def\@upline{%
  \hb@xt@\z@{\hskip -\@halfwidth \vrule \@width \@wholewidth
   \@height \@linelen \@depth \z@\hss}}
```

(*End definition for* `\@upline`.)

`\@downline`

```
\def\@downline{%
  \hb@xt@\z@{\hskip -\@halfwidth \vrule \@width \@wholewidth
   \@height \z@ \@depth \@linelen \hss}}
```

(*End definition for* `\@downline`.)

`\@upvector`

```
\def\@upvector{\@upline\setbox\@tempboxa\hbox{\@linefnt\char 54}% '66
  \raise \@linelen \hb@xt@\z@{\lower \ht\@tempboxa\box\@tempboxa\hss}}
```

(*End definition for* `\@upvector`.)

`\@downvector`

```
\def\@downvector{\@downline\lower \@linelen
      \hb@xt@\z@{\@linefnt\char 63  % '77
      \hss}}
```

(*End definition for* `\@downvector`.)

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\dashbox{D}(X,Y) ==
  BEGIN
  leave vertical mode
  \hb@xt@ 0pt {
        \baselineskip := 0pt
        \lineskip     := 0pt
  %% HORIZONTAL DASHES
        \@dashdim := X * \unitlength
        \@dashcnt := \@dashdim + 200 % to prevent roundoff error
        \@dashdim := D * \unitlength
        \@dashcnt := \@dashcnt / \@dashdim
        if \@dashcnt is odd
          then \@dashdim := 0pt
               \@dashcnt := (\@dashcnt + 1) / 2
          else \@dashdim := \@dashdim / 2
               \@dashcnt := \@dashcnt / 2 - 1
               \box\@dashbox   := \hbox{\vrule height \@halfwidth
                                depth \@halfwidth width \@dashdim}
               \put(0,0){\copy\@dashbox}
               \put(0,Y){\copy\@dashbox}
               \put(X,0){\hskip -\@dashdim\copy\@dashbox}
               \put(X,Y){\hskip -\@dashdim\box\@dashbox}
               \@dashdim := 3 * \@dashdim
        fi
```

```
\box\@dashbox := \hbox{\vrule height \@halfwidth
                   depth \@halfwidth width D * \unitlength
                   \hskip D * \unitlength}
\@tempcnta := 0
\put(0,0){\hskip \@dashdim
         while \@tempcnta < \@dascnt
           do \copy\@dashbox
              \@tempcnta := \@tempcnta + 1
           od
        }
\@tempcnta := 0
put(0,Y){\hskip \@dashdim
         while \@tempcnta < \@dascnt
           do \copy\@dashbox
              \@tempcnta := \@tempcnta + 1
           od
        }

%% vertical dashes
\@dashdim := Y * \unitlength
\@dashcnt := \@dashdim + 200 % to prevent roundoff error
\@dashdim := D * \unitlength
\@dashcnt := \@dashcnt / \@dashdim
if \@dashcnt is odd
  then \@dashdim := 0pt
       \@dashcnt := (\@dashcnt + 1) / 2
  else \@dashdim := \@dashdim / 2
       \@dashcnt := \@dashcnt / 2 - 1
       \box\@dashbox   := \hbox{\hskip -\@halfwidth
                                 \vrule width \@wholewidth
                                          height \@dashdim  }
       \put(0,0){\copy\@dashbox}
       \put(X,0){\copy\@dashbox}
       \put(0,Y){\lower\@dashdim\copy\@dashbox}
       \put(X,Y){\lower\@dashdim\copy\@dashbox}
       \@dashdim := 3 * \@dashdim
fi
\box\@dashbox := \hbox{\vrule width \@wholewidth
                          height D * \unitlength       }
\@tempcnta := 0
put(0,0){\hskip -\halfwidth
         \vbox{while \@tempcnta < \@dashcnt
                 do \vskip D*\unitlength
                    \copy\@dashbox
                    \@tempcnta := \@tempcnta + 1
                 od
                \vskip \@dashdim
               } }
\@tempcnta := 0
put(X,0){\hskip -\halfwidth
```

```
                    \vbox{while \@tempcnta < \@dashcnt
                            do \vskip D*\unitlength
                               \copy\@dashbox
                               \@tempcnta := \@tempcnta + 1
                            od
                           \vskip \@dashdim
                          }
                  }
      }     % END DASHES

  \@imakepicbox(X,Y)
 END
```

End of historical LaTeX 2.09 comments.

\dashbox

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\dashbox}{default units}%
⟨latexrelease⟩\expandafter\let\csname dashbox \endcsname\@undefind
\def\dashbox#1(#2,#3){\leavevmode\hb@xt@\z@{\baselineskip \z@skip
\lineskip \z@skip
\@defaultunitsset\@dashdim{#2}\unitlength
\@dashcnt \@dashdim \advance\@dashcnt 200
\@defaultunitsset\@dashdim{#1}\unitlength
\divide\@dashcnt \@dashdim
\ifodd\@dashcnt\@dashdim \z@
\advance\@dashcnt \@ne \divide\@dashcnt \tw@
\else \divide\@dashdim \tw@ \divide\@dashcnt \tw@
\advance\@dashcnt \m@ne
\setbox\@dashbox \hbox{\vrule \@height \@halfwidth \@depth \@halfwidth
\@width \@dashdim}\put(0,0){\copy\@dashbox}%
\put(0,#3){\copy\@dashbox}%
\put(#2,0){\hskip-\@dashdim\copy\@dashbox}%
\put(#2,#3){\hskip-\@dashdim\box\@dashbox}%
\multiply\@dashdim \thr@@
\fi
\setbox\@dashbox \hbox{%
  \@defaultunitsset\@tempdimc{#1}\unitlength
  \vrule \@height \@halfwidth \@depth \@halfwidth \@width \@tempdimc
  \hskip\@tempdimc}%
\@tempcnta\z@
\put(0,0){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
\do{\copy\@dashbox\advance\@tempcnta \@ne }}\@tempcnta\z@
\put(0,#3){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
\do{\copy\@dashbox\advance\@tempcnta \@ne }}%
\@defaultunitsset\@dashdim{#3}\unitlength
\@dashcnt \@dashdim \advance\@dashcnt 200
\@defaultunitsset\@dashdim{#1}\unitlength
\divide\@dashcnt \@dashdim
\ifodd\@dashcnt \@dashdim \z@
\advance\@dashcnt \@ne \divide\@dashcnt \tw@
\else
```

```
\divide\@dashdim \tw@ \divide\@dashcnt \tw@
\advance\@dashcnt \m@ne
\setbox\@dashbox\hbox{\hskip -\@halfwidth
\vrule \@width \@wholewidth
\@height \@dashdim}\put(0,0){\copy\@dashbox}%
\put(#2,0){\copy\@dashbox}%
\put(0,#3){\lower\@dashdim\copy\@dashbox}%
\put(#2,#3){\lower\@dashdim\copy\@dashbox}%
\multiply\@dashdim \thr@@
\fi
\@defaultunitsset\@tempdimb{#1}\unitlength
\setbox\@dashbox\hbox{%
  \vrule \@width \@wholewidth \@height\@tempdimb}%
\@tempcnta\z@
\put(0,0){\hskip -\@halfwidth \vbox{\@whilenum \@tempcnta <\@dashcnt
\do{\vskip\@tempdimb\copy\@dashbox\advance\@tempcnta \@ne }%
\vskip\@dashdim}}\@tempcnta\z@
\put(#2,0){\hskip -\@halfwidth \vbox{\@whilenum \@tempcnta<\@dashcnt
\do{\vskip\@tempdimb\copy\@dashbox\advance\@tempcnta \@ne }%
\vskip\@dashdim}}}\@makepicbox(#2,#3)}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\dashbox}{default units}%
⟨latexrelease⟩\expandafter\let\csname dashbox \endcsname\@undefind
⟨latexrelease⟩\def\dashbox#1(#2,#3){%
⟨latexrelease⟩\leavevmode\hb@xt@\z@{\baselineskip \z@skip
⟨latexrelease⟩\lineskip \z@skip
⟨latexrelease⟩\@dashdim #2\unitlength
⟨latexrelease⟩\@dashcnt \@dashdim \advance\@dashcnt 200
⟨latexrelease⟩\@dashdim #1\unitlength\divide\@dashcnt \@dashdim
⟨latexrelease⟩\ifodd\@dashcnt\@dashdim \z@
⟨latexrelease⟩\advance\@dashcnt \@ne \divide\@dashcnt \tw@
⟨latexrelease⟩\else \divide\@dashdim \tw@ \divide\@dashcnt \tw@
⟨latexrelease⟩\advance\@dashcnt \m@ne
⟨latexrelease⟩\setbox\@dashbox \hbox{%
⟨latexrelease⟩  \vrule \@height \@halfwidth \@depth \@halfwidth
⟨latexrelease⟩  \@width \@dashdim}\put(0,0){\copy\@dashbox}%
⟨latexrelease⟩\put(0,#3){\copy\@dashbox}%
⟨latexrelease⟩\put(#2,0){\hskip-\@dashdim\copy\@dashbox}%
⟨latexrelease⟩\put(#2,#3){\hskip-\@dashdim\box\@dashbox}%
⟨latexrelease⟩\multiply\@dashdim \thr@@
⟨latexrelease⟩\fi
⟨latexrelease⟩\setbox\@dashbox \hbox{%
⟨latexrelease⟩  \vrule \@height \@halfwidth \@depth \@halfwidth
⟨latexrelease⟩  \@width #1\unitlength\hskip #1\unitlength}\@tempcnta\z@
⟨latexrelease⟩\put(0,0){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
⟨latexrelease⟩\do{\copy\@dashbox\advance\@tempcnta \@ne }}\@tempcnta\z@
⟨latexrelease⟩\put(0,#3){\hskip\@dashdim \@whilenum \@tempcnta <\@dashcnt
⟨latexrelease⟩\do{\copy\@dashbox\advance\@tempcnta \@ne }}%
⟨latexrelease⟩\@dashdim #3\unitlength
⟨latexrelease⟩\@dashcnt \@dashdim \advance\@dashcnt 200
⟨latexrelease⟩\@dashdim #1\unitlength\divide\@dashcnt \@dashdim
⟨latexrelease⟩\ifodd\@dashcnt \@dashdim \z@
```

```
⟨latexrelease⟩\advance\@dashcnt \@ne \divide\@dashcnt \tw@
⟨latexrelease⟩\else
⟨latexrelease⟩\divide\@dashdim \tw@ \divide\@dashcnt \tw@
⟨latexrelease⟩\advance\@dashcnt \m@ne
⟨latexrelease⟩\setbox\@dashbox\hbox{\hskip -\@halfwidth
⟨latexrelease⟩\vrule \@width \@wholewidth
⟨latexrelease⟩\@height \@dashdim}\put(0,0){\copy\@dashbox}%
⟨latexrelease⟩\put(#2,0){\copy\@dashbox}%
⟨latexrelease⟩\put(0,#3){\lower\@dashdim\copy\@dashbox}%
⟨latexrelease⟩\put(#2,#3){\lower\@dashdim\copy\@dashbox}%
⟨latexrelease⟩\multiply\@dashdim \thr@@
⟨latexrelease⟩\fi
⟨latexrelease⟩\setbox\@dashbox\hbox{\vrule \@width \@wholewidth
⟨latexrelease⟩\@height #1\unitlength}\@tempcnta\z@
⟨latexrelease⟩\put(0,0){%
⟨latexrelease⟩  \hskip -\@halfwidth \vbox{\@whilenum \@tempcnta <\@dashcnt
⟨latexrelease⟩  \do{\vskip #1\unitlength\copy\@dashbox
⟨latexrelease⟩      \advance\@tempcnta\@ne }%
⟨latexrelease⟩  \vskip\@dashdim}}\@tempcnta\z@
⟨latexrelease⟩\put(#2,0){%
⟨latexrelease⟩  \hskip -\@halfwidth \vbox{\@whilenum \@tempcnta<\@dashcnt
⟨latexrelease⟩  \do{\vskip #1\unitlength\copy\@dashbox
⟨latexrelease⟩      \advance\@tempcnta \@ne }%
⟨latexrelease⟩  \vskip\@dashdim}}}\@makepicbox(#2,#3)}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\dashbox`.)

Historical LaTeX 2.09 comments (not necessarily accurate any more):

CIRCLES AND OVALS

USER COMMANDS:

`\circle{D}` : Produces the circle with the diameter as close as possible to D * `\unitlength`. `\put(X,Y){\circle{D}}` puts the circle with its center at (X,Y).

`\oval(X,Y)` : Makes an oval as round as possible that fits in the rectangle of width X * `\unitlength` and height Y * `\unitlength`. The reference point is the center.

`\oval(X,Y)[POS]` : Save as `\oval(X,Y)` except it draws only the half or quadrant of the oval indicated by POS. E.G., `\oval(X,Y)[t]` draws just the top half and `\oval(X,Y)[br]` draws just the bottom right quadrant. In all cases, the reference point is the same as the unqualified `\oval(X,Y)` command.

`\@ovvert {DELTA1} {DELTA2}` : Makes a vbox containing either the left side or the right side of the oval being constructed. The baseline will coincide with the outside bottom edge of the oval; the left side of the box will coincide with the left edge of the vertical

rule. The width of the box will be `\@tempdima`.
DELTA1 and DELTA2 are added to the character number in `\@tempcnta` to get the characters for the top and bottom quarter circle pieces.

`\@ovhorz` : Makes an hbox containing the straight rule for either the top or the bottom of the oval being constructed. The baseline will coincide with bottom edge of the rule; the left side of the box will coincide with the left side of the oval. The width of the box will be `\@ovxx`.

`\@getcirc {DIAM}` : Sets `\@tempcnta` to the character number of the top-right quarter circle with the largest diameter less than or equal to DIAM.
Sets `\@tempboxa` to an hbox containing that character.
Sets `\@tempdima` to `\wd \@tempboxa`, which is the distance from the circle's left outside edge to its right inside edge.
(These characters are like those described in the TeXbook, pp. 389-90.)

```
\@getcirc {DIAM} ==
  BEGIN
    \@tempcnta       := integer coercion of (DIAM + 2pt)
                                          + 2pt added 1 Nov 88
    \@tempcnta       := \@tempcnta / integer coercion of 4pt
    if \@tempcnta > 10
      then \@tempcnta := 10 fi
    if \@tempcnta > 0
      then \@tempcnta := \@tempcnta-1
      else LaTeX Warning: Oval too small.
    fi
    \@tempcnta       := 4 * \@tempcnta
    \@tempboxa       := \hbox{\@circlefnt \char \@tempcnta}
    \@tempdima       := \wd \@tempboxa
  END

\@put{X}{Y}{OBJ} ==
  BEGIN
    \raise Y \hb@xt@ 0pt{\hskip X OBJ \hss}
  END

\@oval(X,Y)[POS] ==
  BEGIN
    \begingroup
      \boxmaxdepth := \maxdimen
      @ovt := @ovb := @ovl := @ovr := true
      for all E in POS
        do  @ovE := false od
      \@ovxx      := X * \unitlength
      \@ovyy      := Y * \unitlength
```

```
      \@tempdimb := min(\@ovxx,\@ovyy)
      \@getcirc{\@tempdimb-2pt}   %% "-2pt" added 7 Dec 89
      \@ovro     := \ht \@tempboxa
      \@ovri     := \dp \@tempboxa
      \@ovdx     := \@ovxx - \@tempdima
      \@ovdx     := \@ovdx/2
      \@ovdy     := \@ovyy - \@tempdima
      \@ovdy     := \@ovyy/2
      \@circlefnt
      \@tempboxa :=
          \hbox{
                if @ovr
                  then \@ovvert{3}{2} \kern -\@tempdima
                fi
                if @ovl
                  then \kern \@ovxx \@ovvert{0}{1} \kern -\@tempdima
                       \kern -\@ovxx
                fi
                if @ovt
                  then \@ovhorz \kern -\@ovxx
                fi
                if @ovb
                  then \raise \@ovyy \@ovhorz
                fi
               }
      \@ovdx    := \@ovdx + \@ovro
      \@ovdy    := \@ovdy + \@ovro
     \ht\@tempboxa := \dp\@tempboxa := 0
      \@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}
   \endgroup
  END

\@ovvert {DELTA1} {DELTA2} ==
  BEGIN
     \vbox to \@ovyy {
                      if @ovb
                        then \@tempcntb := \@tempcnta + DELTA1
                             \kern -\@ovro
                             \hbox { \char \@tempcntb }
                             \nointerlineskip
                        else \kern \@ovri \kern \@ovdy
                      fi
                      \leaders \vrule width \@wholewidth \vfil
                      \nointerlineskip
                      if @ovt
                        then \@tempcntb := \@tempcnta + DELTA2
                             \hbox { \char \@tempcntb }
                        else \kern \@ovdy \kern \@ovro
                      fi
                     }
```

```
  END

\@ovhorz ==
  BEGIN
   \hb@xt@ \@ovxx{
                  \kern \@ovro
                  if @ovr
                    then
                    else \kern \@ovdx
                  fi
                  \leaders \hrule height \@wholewidth \hfil
                  if @ovl
                    then
                    else \kern \@ovdx
                  fi
                  \kern \@ovri
                 }
  END

\circle{DIAM} ==
  BEGIN
   \begingroup
   \boxmaxdepth := maxdimen
   \@tempdimb := DIAM *\unitlength
   if \@tempdimb > 15.5pt
     then \@getcirc{\@tempdimb}
          \@ovro := \ht \@tempboxa
          \@tempboxa := \hbox{
                  \@circlefnt
                  \@tempcnta := \@tempcnta + 2
                  \char \@tempcnta
                  \@tempcnta := \@tempcnta - 1
                  \char \@tempcnta
                  \kern -2\@tempdima
                  \@tempcnta := \@tempcnta + 2
                  \raise \@tempdima \hbox { \char \@tempcnta }
                  \raise \@tempdima \box\@tempboxa
                 }
          \ht\@tempboxa := \dp\@tempboxa := 0
          \@put{-\@ovro}{-\@ovro}{\@tempboxa}
     else
          \@circ{\@tempdimb}{96}
   fi
  \endgroup
  END

\circle*{DIAM}  ==  \@dot{DIAM} == \@circ{DIAM*\unitlength}{112}

\@circ{DIAM}{CHAR} ==
 BEGIN
```

```
\@tempcnta := integer coercion of (DIAM + .5pt)/1pt.
if \@tempcnta > 15 then \@tempcnta := 15 fi
if \@tempcnta > 1  then \@tempcnta := \@tempcnta - 1 fi
\@tempcnta := \@tempcnta + CHAR
\@circlefnt
\char \@tempcnta
END
```

End of historical LaTeX 2.09 comments.

`\if@ovt` `\if@ovb` `\if@ovl` `\if@ovr`

If producing the Top Bottom Left or Right of an oval.

```
\newif\if@ovt
\newif\if@ovb
\newif\if@ovl
\newif\if@ovr
```

(*End definition for* `\if@ovt` *and others.*)

`\@ovxx` `\@ovyy` `\@ovdx` `\@ovdy` `\@ovro` `\@ovri`

```
\newdimen\@ovxx
\newdimen\@ovyy
\newdimen\@ovdx
\newdimen\@ovdy
\newdimen\@ovro
\newdimen\@ovri
```

(*End definition for* `\@ovxx` *and others.*)

`\advance\@tempdima 2pt\relax` added 1 Nov 88 to fix bug in which size of drawn circle not monotonic function of argument of `\circle`, caused by different rounding for dimensions of large and small circles.

`\@getcirc`

```
\def\@getcirc#1{\@tempdima #1\relax \advance\@tempdima 2\p@
  \@tempcnta\@tempdima
  \@tempdima 4\p@ \divide\@tempcnta\@tempdima
  \ifnum \@tempcnta >10\relax
      \@picture@warn
      \@tempcnta 10\relax
  \fi
  \ifnum \@tempcnta >\z@ \advance\@tempcnta\m@ne
```

Warn if requirements for oval or circle can't be met.

```
    \else \@picture@warn \fi
  \multiply\@tempcnta 4\relax
  \setbox \@tempboxa \hbox{\@circlefnt
  \char \@tempcnta}\@tempdima \wd \@tempboxa}
```

(*End definition for* `\@getcirc`*.*)

`\@picture@warn`

Generic warning for lines, vectors (used in `\@sline`) and oval or circle (used in `\@getcirc`) are not available at right size.

```
\def\@picture@warn{\@latex@warning{%
     \string\oval, \string\circle, or \string\line\space
     size unavailable}}
```

(*End definition for* `\@picture@warn`.)

`\@put`

```
\def\@put#1#2#3{\raise #2\hb@xt@\z@{\hskip #1#3\hss}}
```

(*End definition for* `\@put`.)

`\oval`

```
\def\oval(#1,#2){\@ifnextchar[{\@oval(#1,#2)}{\@oval(#1,#2)[]}}
```

(*End definition for* `\oval`.)

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2016/03/31}%
⟨latexrelease⟩                  {\@ovhlinetrue}%
⟨latexrelease⟩                  {Avoid almost zero length leaders}%
⟨*2ekernel | latexrelease⟩
```

`\if@ovvline` `\if@ovhline` Tests whether horizontal or vertical lines are needed.

```
\newif\if@ovvline \@ovvlinetrue
\newif\if@ovhline \@ovhlinetrue
%     \begin{macrocode}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@ovhlinetrue}%
⟨latexrelease⟩                  {Avoid almost zero length leaders}%
⟨latexrelease⟩\let\if@ovvline\@undefined
⟨latexrelease⟩\let\if@ovhline\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\if@ovvline` *and* `\if@ovhline`.)

`\@oval`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@oval}{default units}%
\def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
  \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue

  \@ovvlinefalse \@ovhlinefalse

  \@tfor\reserved@a :=#3\do{%
    \csname @ov\reserved@a false\endcsname}%
  \@defaultunitsset\@ovxx{#1}\unitlength
  \@defaultunitsset\@ovyy{#2}\unitlength

  \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx \@ovvlinetrue
  \else \@ovyy \ifdim \@ovyy =\@ovxx \else \@ovhlinetrue \fi\fi

  \advance \@tempdimb -2\p@
  \@getcirc \@tempdimb
  \@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
  \@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
  \@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@
```

```
  \ifdim \@ovdx >\z@ \@ovhlinetrue \fi
  \ifdim \@ovdy >\z@ \@ovvlinetrue \fi
  \@circlefnt \setbox\@tempboxa
  \hbox{\if@ovr \@ovvert32\kern -\@tempdima \fi
  \if@ovl \kern \@ovxx \@ovvert01\kern -\@tempdima \kern -\@ovxx \fi
  \if@ovt \@ovhorz \kern -\@ovxx \fi
  \if@ovb \raise \@ovyy \@ovhorz \fi}\advance\@ovdx\@ovro
  \advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
  \@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
  \endgroup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2016/03/31}%
⟨latexrelease⟩                  {\@oval}{default units}%
⟨latexrelease⟩\def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
⟨latexrelease⟩  \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue
⟨latexrelease⟩  \@ovvlinefalse \@ovhlinefalse
⟨latexrelease⟩  \@tfor\reserved@a :=#3\do{%
⟨latexrelease⟩    \csname @ov\reserved@a false\endcsname}%
⟨latexrelease⟩  \@ovxx #1\unitlength
⟨latexrelease⟩  \@ovyy #2\unitlength
⟨latexrelease⟩  \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx \@ovvlinetrue
⟨latexrelease⟩  \else \@ovyy \ifdim \@ovyy =\@ovxx \else \@ovhlinetrue
⟨latexrelease⟩   \fi\fi
⟨latexrelease⟩  \advance \@tempdimb -2\p@
⟨latexrelease⟩  \@getcirc \@tempdimb
⟨latexrelease⟩  \@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
⟨latexrelease⟩  \@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
⟨latexrelease⟩  \@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@
⟨latexrelease⟩  \ifdim \@ovdx >\z@ \@ovhlinetrue \fi
⟨latexrelease⟩  \ifdim \@ovdy >\z@ \@ovvlinetrue \fi
⟨latexrelease⟩  \@circlefnt \setbox\@tempboxa
⟨latexrelease⟩  \hbox{\if@ovr \@ovvert32\kern -\@tempdima \fi
⟨latexrelease⟩  \if@ovl
⟨latexrelease⟩   \kern \@ovxx \@ovvert01\kern -\@tempdima \kern -\@ovxx
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \if@ovt \@ovhorz \kern -\@ovxx \fi
⟨latexrelease⟩  \if@ovb \raise \@ovyy \@ovhorz \fi}\advance\@ovdx\@ovro
⟨latexrelease⟩  \advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
⟨latexrelease⟩  \@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
⟨latexrelease⟩  \endgroup}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@oval}{default units}%
⟨latexrelease⟩\def\@oval(#1,#2)[#3]{\begingroup\boxmaxdepth \maxdimen
⟨latexrelease⟩  \@ovttrue \@ovbtrue \@ovltrue \@ovrtrue
⟨latexrelease⟩  \@tfor\reserved@a :=#3\do
⟨latexrelease⟩                 {\csname @ov\reserved@a false\endcsname}%
⟨latexrelease⟩  \@ovxx #1\unitlength
⟨latexrelease⟩  \@ovyy #2\unitlength
⟨latexrelease⟩  \@tempdimb \ifdim \@ovyy >\@ovxx \@ovxx\else \@ovyy \fi
⟨latexrelease⟩  \advance \@tempdimb -2\p@
⟨latexrelease⟩  \@getcirc \@tempdimb
```

```
⟨latexrelease⟩  \@ovro \ht\@tempboxa \@ovri \dp\@tempboxa
⟨latexrelease⟩  \@ovdx\@ovxx \advance\@ovdx -\@tempdima \divide\@ovdx \tw@
⟨latexrelease⟩  \@ovdy\@ovyy \advance\@ovdy -\@tempdima \divide\@ovdy \tw@
⟨latexrelease⟩  \@circlefnt \setbox\@tempboxa
⟨latexrelease⟩  \hbox{\if@ovr \@ovvert32\kern -\@tempdima \fi
⟨latexrelease⟩  \if@ovl
⟨latexrelease⟩   \kern \@ovxx \@ovvert01\kern -\@tempdima \kern -\@ovxx
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \if@ovt \@ovhorz \kern -\@ovxx \fi
⟨latexrelease⟩  \if@ovb \raise \@ovyy \@ovhorz \fi}\advance\@ovdx\@ovro
⟨latexrelease⟩  \advance\@ovdy\@ovro \ht\@tempboxa\z@ \dp\@tempboxa\z@
⟨latexrelease⟩  \@put{-\@ovdx}{-\@ovdy}{\box\@tempboxa}%
⟨latexrelease⟩  \endgroup}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@oval`.)

`\@ovvert`

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2016/03/31}%
⟨latexrelease⟩                 {\@ovvert}{Avoid almost zero length leaders}%
⟨*2ekernel | latexrelease⟩
\def\@ovvert#1#2{\vbox to\@ovyy{%
    \if@ovb \@tempcntb \@tempcnta \advance \@tempcntb #1\relax
      \kern -\@ovro \hbox{\char \@tempcntb}\nointerlineskip
    \else \kern \@ovri \kern \@ovdy \fi
    \if@ovvline \leaders\vrule \@width \@wholewidth \fi
    \vfil \nointerlineskip
    \if@ovt \@tempcntb \@tempcnta \advance \@tempcntb #2\relax
      \hbox{\char \@tempcntb}%
    \else \kern \@ovdy \kern \@ovro \fi}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@ovvert}{Avoid almost zero length leaders}%
⟨latexrelease⟩\def\@ovvert#1#2{\vbox to\@ovyy{%
⟨latexrelease⟩    \if@ovb \@tempcntb \@tempcnta \advance \@tempcntb #1\relax
⟨latexrelease⟩      \kern -\@ovro \hbox{\char \@tempcntb}\nointerlineskip
⟨latexrelease⟩    \else \kern \@ovri \kern \@ovdy \fi
⟨latexrelease⟩    \leaders\vrule \@width \@wholewidth\vfil \nointerlineskip
⟨latexrelease⟩    \if@ovt \@tempcntb \@tempcnta \advance \@tempcntb #2\relax
⟨latexrelease⟩      \hbox{\char \@tempcntb}%
⟨latexrelease⟩    \else \kern \@ovdy \kern \@ovro \fi}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@ovvert`.)

`\@ovhorz`

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2016/03/31}%
⟨latexrelease⟩                 {\@ovhorz}{Avoid almost zero length leaders}%
```

```
⟨*2ekernel | latexrelease⟩
\def\@ovhorz{\hb@xt@\@ovxx{\kern \@ovro
    \if@ovr \else \kern \@ovdx \fi
    \if@ovhline \leaders \hrule \@height \@wholewidth \fi
    \hfil
    \if@ovl \else \kern \@ovdx \fi
    \kern \@ovri}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@ovhorz}{Avoid almost zero length leaders}%
⟨latexrelease⟩\def\@ovhorz{\hb@xt@\@ovxx{\kern \@ovro
⟨latexrelease⟩    \if@ovr \else \kern \@ovdx \fi
⟨latexrelease⟩    \leaders \hrule \@height \@wholewidth \hfil
⟨latexrelease⟩    \if@ovl \else \kern \@ovdx \fi
⟨latexrelease⟩    \kern \@ovri}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@ovhorz`.)

`\circle`

```
\def\circle{\@inmatherr\circle\@ifstar\@dot\@circle}
```

(*End definition for* `\circle`.)

`\@circle`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\@circle}{default units}%
\def\@circle#1{%
  \begingroup \boxmaxdepth \maxdimen
   \@defaultunitsset\@tempdimb{#1}\unitlength
   \ifdim \@tempdimb >15.5\p@ \@getcirc\@tempdimb
      \@ovro\ht\@tempboxa
     \setbox\@tempboxa\hbox{\@circlefnt
      \advance\@tempcnta\tw@ \char \@tempcnta
      \advance\@tempcnta\m@ne \char \@tempcnta \kern -2\@tempdima
      \advance\@tempcnta\tw@
      \raise \@tempdima \hbox{\char\@tempcnta}\raise \@tempdima
        \box\@tempboxa}\ht\@tempboxa\z@ \dp\@tempboxa\z@
      \@put{-\@ovro}{-\@ovro}{\box\@tempboxa}%
   \else  \@circ\@tempdimb{96}\fi\endgroup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@circle}{default units}%
⟨latexrelease⟩\def\@circle#1{%
⟨latexrelease⟩  \begingroup \boxmaxdepth \maxdimen \@tempdimb #1\unitlength
⟨latexrelease⟩   \ifdim \@tempdimb >15.5\p@ \@getcirc\@tempdimb
⟨latexrelease⟩      \@ovro\ht\@tempboxa
```

```
⟨latexrelease⟩     \setbox\@tempboxa\hbox{\@circlefnt
⟨latexrelease⟩      \advance\@tempcnta\tw@ \char \@tempcnta
⟨latexrelease⟩      \advance\@tempcnta\m@ne \char \@tempcnta
⟨latexrelease⟩      \kern -2\@tempdima
⟨latexrelease⟩      \advance\@tempcnta\tw@
⟨latexrelease⟩      \raise \@tempdima \hbox{\char\@tempcnta}%
⟨latexrelease⟩      \raise \@tempdima
⟨latexrelease⟩        \box\@tempboxa}\ht\@tempboxa\z@ \dp\@tempboxa\z@
⟨latexrelease⟩      \@put{-\@ovro}{-\@ovro}{\box\@tempboxa}%
⟨latexrelease⟩   \else  \@circ\@tempdimb{96}\fi\endgroup}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@circle`.)

`\@dot` Internal form of `\circle*`.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\@dot}{default units}%
\def\@dot#1{%
  \@defaultunitsset\@tempdimb{#1}\unitlength
  \@circ\@tempdimb{112}}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@dot}{default units}%
⟨latexrelease⟩\def\@dot#1{\@tempdimb #1\unitlength \@circ\@tempdimb{112}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@dot`.)

`\@circ`

```
\def\@circ#1#2{\@tempdima #1\relax \advance\@tempdima .5\p@
   \@tempcnta\@tempdima \@tempdima \p@
   \divide\@tempcnta\@tempdima
   \ifnum\@tempcnta >15\relax \@tempcnta 15\relax \fi
   \ifnum \@tempcnta >\z@ \advance\@tempcnta\m@ne\fi
   \advance\@tempcnta #2\relax
   \@circlefnt \char\@tempcnta}
```

(*End definition for* `\@circ`.)

`\@xarg` `\@yarg` `\@yyarg` Counters used for manipulating the 'slope' arguments.

```
\newcount\@xarg
\newcount\@yarg
\newcount\@yyarg
```

(*End definition for* `\@xarg`, `\@yarg`, *and* `\@yyarg`.)

`\@multicnt` Counter used in `\multiput`, and also `\multicolumn`.

```
\newcount\@multicnt
```

(*End definition for* `\@multicnt`.)

\@xdim
\@ydim

Length registers.

```
\newdimen\@xdim
\newdimen\@ydim
```

(*End definition for* `\@xdim` *and* `\@ydim`.)

\@linechar

Box for holding a line segment character, for sloping lines.

```
\newbox\@linechar
```

(*End definition for* `\@linechar`.)

\@linelen

Length of the line currently being built.

```
\newdimen\@linelen
```

(*End definition for* `\@linelen`.)

\@clnwd
\@clnht

Height and width of current line segment.

```
\newdimen\@clnwd
\newdimen\@clnht
```

(*End definition for* `\@clnwd` *and* `\@clnht`.)

\@dashdim
\@dashbox
\@dashcnt

`\dashbox` internal registers.

```
\newdimen\@dashdim
\newbox\@dashbox
\newcount\@dashcnt
```

(*End definition for* `\@dashdim`, `\@dashbox`, *and* `\@dashcnt`.)

Initialization: "`\thinlines`"

```
\let\@linefnt\tenln
\let\@circlefnt\tencirc
\@wholewidth\fontdimen8\tenln
\@halfwidth .5\@wholewidth
```

1.1 Curves

The new `\qbezier` command, based on the old `\bezier` defined in `bezier.sty`. *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
\qbezier[N] == \bezier{N}

\bezier{N}(AX,AY)(BX,BY)(CX,CY) ==
  BEGIN
    IF N = 0
       THEN \@xdima := |BX - AX|
            \@xb := |CX - BX|
            \@xa := Max(\@xa, \@xb)
            \@ya := |BY - AY|
            \@yb := |CY - BY|
            \@ya := Max(\@ya, \@yb)
            @sc := Max(\@xa, \@ya)
            %% The coefficient .5 below is the degree of overlap of
            %% successive points, where 1 is no overlap and 0 is
```

```
        %% complete overlap.  A coefficient of C multiplies
        %% the number of points plotted by 1/C.
        %%
        \@xa := .5 * \@halfwidth
        @sc := @sc / \@halfwidth
        @sc := Max(@sc, qbeziermax)
    ELSE @sc := N
@scp := @sc+1
\@xb := 2 * (BX - AX) * \unitlength
\@xa := ((CX-AX)*\unitlength - \@xb)/@sc
\@yb := 2 * (BY - AY) * \unitlength
\@ya := ((CY-AY)*\unitlength - \@yb)/@sc
\@pictdot := square rule of width \@wholewidth
\count@ := 0
WHILE \count@ < @scp
  DO  \@xdim := ((\count@*\@xa + @xb) / @sc) * \count@
      \@ydim := ((\count@*\@ya + @yb) / @sc) * \count@
      plot pt with relative coords (\@xdim,\@ydim)
      \count@ := \count@+1
  OD
```

End of historical LaTeX 2.09 comments.

`\qbeziermax` The maximum number of points to plot.

```
\def\qbeziermax{500}
```

(*End definition for* `\qbeziermax`.)

In the code below, to save registers `\@a` ... are not used. Instead other registers are reused.

```
\newcounter{@sc} -> \c@multicnt
\newcounter{@scp} -> \@tempcnta
\newdimen\@xa ->  \@ovxx
\newdimen\@xb ->  \@ovdx
\newdimen\@ya ->  \@ovyy
\newdimen\@yb ->  \@ovdy
\newsavebox{\@pictdot} -> \@tempboxa
```

`\qbezier` Main user-level command to plot quadratic bezier curves. `#2` should be `(`.

```
\newcommand\qbezier[2][0]{\bezier{#1}#2}
```

(*End definition for* `\qbezier`.)

`\bezier` Form of `\bezier` compatible with 2.09 `bezier.sty`, but modified to ignore spaces between its arguments. `#2` should be white space, and `#4` should be `(`.

```
\def\bezier#1)#2(#3)#4({\@bezier#1)(#3)(}
```

\@bezier

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@bezier}{default units}%
\def\@bezier#1(#2,#3)(#4,#5)(#6,#7){%
  \ifnum #1=\z@
      \@defaultunitsset\@ovxx{#4}\unitlength
        \@defaultunitsset{\advance\@ovxx}{-#2}\unitlength
        \ifdim \@ovxx<\z@ \@ovxx -\@ovxx \fi
      \@defaultunitsset\@ovdx{#6}\unitlength
        \@defaultunitsset{\advance\@ovdx}{-#4}\unitlength
        \ifdim \@ovdx<\z@ \@ovdx -\@ovdx \fi
        \ifdim \@ovxx<\@ovdx \@ovxx \@ovdx \fi
      \@defaultunitsset\@ovyy{#5}\unitlength
        \@defaultunitsset{\advance\@ovyy}{-#3}\unitlength
        \ifdim \@ovyy<\z@ \@ovyy -\@ovyy \fi
      \@defaultunitsset\@ovdy{#7}\unitlength
        \@defaultunitsset{\advance\@ovdy}{-#5}\unitlength
        \ifdim \@ovdy<\z@  \@ovdy -\@ovdy \fi
        \ifdim \@ovyy<\@ovdy \@ovyy  \@ovdy \fi
      \@multicnt
         \ifdim \@ovxx>\@ovyy \@ovxx \else \@ovyy \fi
      \@ovxx .5\@halfwidth \divide\@multicnt\@ovxx
      \ifnum \qbeziermax<\@multicnt
        \@multicnt\qbeziermax\relax
      \fi
  \else \@multicnt#1\relax \fi
  \@tempcnta\@multicnt \advance\@tempcnta\@ne
  \@defaultunitsset\@ovdx{#4}\unitlength
  \@defaultunitsset{\advance\@ovdx}{-#2}\unitlength
      \multiply\@ovdx \tw@
  \@defaultunitsset\@ovxx{#6}\unitlength
  \@defaultunitsset{\advance\@ovxx}{-#2}\unitlength
      \advance\@ovxx -\@ovdx \divide\@ovxx\@multicnt
  \@defaultunitsset\@ovdy{#5}\unitlength
  \@defaultunitsset{\advance\@ovdy}{-#3}\unitlength
       \multiply\@ovdy \tw@
  \@defaultunitsset\@ovyy{#7}\unitlength
  \@defaultunitsset{\advance\@ovyy}{-#3}\unitlength
      \advance\@ovyy -\@ovdy \divide\@ovyy\@multicnt

  \setbox\@tempboxa\hbox{%
            \hskip -\@halfwidth
            \vrule \@height\@halfwidth
                   \@depth \@halfwidth
                   \@width \@wholewidth}%
   \put(#2,#3){%
     \count@\z@
     \@whilenum{\count@<\@tempcnta}\do
        {\@xdim\count@\@ovxx
           \advance\@xdim\@ovdx
           \divide\@xdim\@multicnt
           \multiply\@xdim\count@
```

```
          \@ydim\count@\@ovyy
             \advance\@ydim\@ovdy
             \divide\@ydim\@multicnt
             \multiply\@ydim\count@
          \raise \@ydim
             \hb@xt@\z@{\kern\@xdim
                          \unhcopy\@tempboxa\hss}%
          \advance\count@\@ne}}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@bezier}{default units}%
⟨latexrelease⟩\def\@bezier#1(#2,#3)(#4,#5)(#6,#7){%
⟨latexrelease⟩  \ifnum #1=\z@
⟨latexrelease⟩      \@ovxx #4\unitlength
⟨latexrelease⟩        \advance\@ovxx -#2\unitlength
⟨latexrelease⟩        \ifdim \@ovxx<\z@ \@ovxx -\@ovxx \fi
⟨latexrelease⟩      \@ovdx #6\unitlength
⟨latexrelease⟩        \advance\@ovdx -#4\unitlength
⟨latexrelease⟩        \ifdim \@ovdx<\z@ \@ovdx -\@ovdx \fi
⟨latexrelease⟩        \ifdim \@ovxx<\@ovdx \@ovxx \@ovdx \fi
⟨latexrelease⟩      \@ovyy #5\unitlength
⟨latexrelease⟩        \advance\@ovyy -#3\unitlength
⟨latexrelease⟩        \ifdim \@ovyy<\z@ \@ovyy -\@ovyy \fi
⟨latexrelease⟩      \@ovdy #7\unitlength
⟨latexrelease⟩        \advance\@ovdy -#5\unitlength
⟨latexrelease⟩        \ifdim \@ovdy<\z@  \@ovdy -\@ovdy \fi
⟨latexrelease⟩        \ifdim \@ovyy<\@ovdy \@ovyy  \@ovdy \fi
⟨latexrelease⟩      \@multicnt
⟨latexrelease⟩         \ifdim \@ovxx>\@ovyy \@ovxx \else \@ovyy \fi
⟨latexrelease⟩      \@ovxx .5\@halfwidth \divide\@multicnt\@ovxx
⟨latexrelease⟩      \ifnum
⟨latexrelease⟩        \qbeziermax<\@multicnt \@multicnt\qbeziermax\relax
⟨latexrelease⟩      \fi
⟨latexrelease⟩  \else \@multicnt#1\relax \fi
⟨latexrelease⟩  \@tempcnta\@multicnt \advance\@tempcnta\@ne
⟨latexrelease⟩  \@ovdx #4\unitlength \advance\@ovdx -#2\unitlength
⟨latexrelease⟩      \multiply\@ovdx \tw@
⟨latexrelease⟩  \@ovxx #6\unitlength \advance\@ovxx -#2\unitlength
⟨latexrelease⟩      \advance\@ovxx -\@ovdx \divide\@ovxx\@multicnt
⟨latexrelease⟩  \@ovdy #5\unitlength \advance\@ovdy -#3\unitlength
⟨latexrelease⟩       \multiply\@ovdy \tw@
⟨latexrelease⟩  \@ovyy #7\unitlength \advance\@ovyy -#3\unitlength
⟨latexrelease⟩      \advance\@ovyy -\@ovdy \divide\@ovyy\@multicnt
⟨latexrelease⟩  \setbox\@tempboxa\hbox{%
⟨latexrelease⟩            \hskip -\@halfwidth
⟨latexrelease⟩            \vrule \@height\@halfwidth
⟨latexrelease⟩                   \@depth \@halfwidth
⟨latexrelease⟩                   \@width \@wholewidth}%
⟨latexrelease⟩   \put(#2,#3){%
⟨latexrelease⟩     \count@\z@
⟨latexrelease⟩     \@whilenum{\count@<\@tempcnta}\do
⟨latexrelease⟩        {\@xdim\count@\@ovxx
⟨latexrelease⟩           \advance\@xdim\@ovdx
```

```
⟨latexrelease⟩            \divide\@xdim\@multicnt
⟨latexrelease⟩            \multiply\@xdim\count@
⟨latexrelease⟩          \@ydim\count@\@ovyy
⟨latexrelease⟩             \advance\@ydim\@ovdy
⟨latexrelease⟩             \divide\@ydim\@multicnt
⟨latexrelease⟩             \multiply\@ydim\count@
⟨latexrelease⟩          \raise \@ydim
⟨latexrelease⟩             \hb@xt@\z@{\kern\@xdim
⟨latexrelease⟩                          \unhcopy\@tempboxa\hss}%
⟨latexrelease⟩          \advance\count@\@ne}}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\bezier` *and* `\@bezier`.)

As the commands above all use "picture" interface we couldn't define them with `\DeclareRobustCommand` so we do that now.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                 {\bezier}{Make commands robust}%
\MakeRobust\bezier
\MakeRobust\circle
\MakeRobust\dashbox
\MakeRobust\line
\MakeRobust\linethickness
\MakeRobust\multiput
\MakeRobust\oval
\MakeRobust\put
\MakeRobust\qbezier
\MakeRobust\shortstack
\MakeRobust\thinlines
\MakeRobust\vector
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\bezier}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\bezier
⟨latexrelease⟩\kernel@make@fragile\circle
⟨latexrelease⟩\kernel@make@fragile\dashbox
⟨latexrelease⟩\kernel@make@fragile\line
⟨latexrelease⟩\kernel@make@fragile\linethickness
⟨latexrelease⟩\kernel@make@fragile\multiput
⟨latexrelease⟩\kernel@make@fragile\oval
⟨latexrelease⟩\kernel@make@fragile\put
⟨latexrelease⟩\kernel@make@fragile\qbezier
⟨latexrelease⟩\kernel@make@fragile\shortstack
⟨latexrelease⟩\kernel@make@fragile\thinlines
⟨latexrelease⟩\kernel@make@fragile\vector
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
⟨/2ekernel⟩
```

File N
ltthm.dtx

1 Theorem Environments

The user creates his own theorem-like environments with the command
`\newtheorem{`⟨*name*⟩`}{`⟨*text*⟩`}[`⟨*counter*⟩`]` or
`\newtheorem{`⟨*name*⟩`}[`⟨*oldname*⟩`]{`⟨*text*⟩`}`
This defines the environment ⟨*name*⟩ to be just as one would expect a theorem environment to be, except that it prints ⟨*text*⟩ instead of "Theorem".

If ⟨*oldname*⟩ is given, then environments ⟨*name*⟩ and ⟨*oldname*⟩ use the same counter, so using a ⟨*name*⟩ environment advances the number of the next ⟨*name*⟩ environment, and vice-versa.

If ⟨*counter*⟩ is given, then environment ⟨*name*⟩ is numbered within ⟨*counter*⟩.

E.g., if ⟨*counter*⟩ = `subsection`, then the first ⟨*name*⟩ in subsection 7.2 is numbered ⟨*text*⟩ 7.2.1.

The way ⟨*name*⟩ environments are numbered can be changed by redefining `\the`⟨*name*⟩.
Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
DOCUMENT STYLE PARAMETERS

\@thmcounter{COUNTER} : A command such that
              \edef\theCOUNTER{\@thmcounter{COUNTER}}
   defines \theCOUNTER to produce a number for a theorem environment.
   The default is:
          BEGIN \noexpand\arabic{COUNTER} END

\@thmcountersep : A separator placed between a theorem number and
        the number of the counter within which it is numbered.
        E.g., to make the third theorem of section 7.2 be numbered
        7.2-3, \@thmcountersep should be \def'ed to '-'.  Its
        default is '.'.

\@begintheorem{NAME}{NUMBER} : A command that begins a theorem
        environment for a 'theorem' named 'NAME NUMBER' –
        e.g., \@begintheorem{Lemma}{3.7} starts Lemma 3.7.

\@opargbegintheorem{NAME}{NUMBER}{OPARG} :
        A command that begins a theorem
        environment for a 'theorem' named 'NAME NUMBER' with optional
        argument OPARG – e.g., \@begintheorem{Lemma}{3.7}{Jones}
        starts 'Lemma 3.7 (Jones):'.

\@endtheorem : A command that ends a theorem environment.

\newtheorem{NAME}{TEXT}[COUNTER] ==
  BEGIN
    if \NAME is definable
```

```
        then \@definecounter{NAME}
             if COUNTER present
               then \@newctr{NAME}[COUNTER] fi
                    \theNAME ==  BEGIN \theCOUNTER \@thmcountersep
                                       eval\@thmcounter{NAME}      END
               else \theNAME ==  BEGIN eval\@thmcounter{NAME} END
             \NAME == \@thm{NAME}{TEXT}
             \endNAME == \@endtheorem
        else  error
      fi
    END

  \newtheorem{NAME}[OLDNAME]{TEXT}==
    BEGIN
      if counter OLDNAME nonexistent
        then ERROR
        else
             if \NAME is definable
               then BEGIN
                    \theNAME == \theOLDNAME
                    \NAME == \@thm{OLDNAME}{TEXT}
                    \endNAME == \@endtheorem
                    END
               else  error
             fi
      fi
    END

  \@thm{NAME}{TEXT} ==
    BEGIN
     \refstepcounter{NAME}
     if next char = [
        then \@ythm{NAME}{TEXT}
        else \@xthm{NAME}{TEXT}
     fi
    END

  \@xthm{NAME}{TEXT} ==
    BEGIN
     \@begintheorem{TEXT}{\theNAME}
     \ignorespaces
    END

  \@ythm{NAME}{TEXT}[OPARG] ==
    BEGIN
     \@opargbegintheorem{TEXT}{\theNAME}{OPARG}
     \ignorespaces
    END
```

End of historical LaTeX 2.09 comments.

\newtheorem

\newtheorem ought really be allowed only in the preamble Which would be good document style, and allow some main memory to be saved by declaring these commands to be \@onlypreamble. Unfortunately the LaTeX book indicates that \newtheorem may be used anywhere in the document...

```
⟨*2ekernel⟩
\def\newtheorem#1{%
  \@ifnextchar[{\@othm{#1}}{\@nthm{#1}}}
```

(*End definition for* \newtheorem.)

\@nthm

```
\def\@nthm#1#2{%
  \@ifnextchar[{\@xnthm{#1}{#2}}{\@ynthm{#1}{#2}}}
```

(*End definition for* \@nthm.)

\@xnthm

92/09/18 RmS: Changed \@addtoreset to \@newctr to produce error message if counter #3 does not exist (to be consistent with behaviour of \newcounter)

```
\def\@xnthm#1#2[#3]{%
  \expandafter\@ifdefinable\csname #1\endcsname
    {\@definecounter{#1}\@newctr{#1}[#3]%
     \expandafter\xdef\csname the#1\endcsname{%
       \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
          \@thmcounter{#1}}%
     \global\@namedef{#1}{\@thm{#1}{#2}}%
     \global\@namedef{end#1}{\@endtheorem}}}
```

(*End definition for* \@xnthm.)

\@ynthm

```
\def\@ynthm#1#2{%
  \expandafter\@ifdefinable\csname #1\endcsname
    {\@definecounter{#1}%
     \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
     \global\@namedef{#1}{\@thm{#1}{#2}}%
     \global\@namedef{end#1}{\@endtheorem}}}
```

(*End definition for* \@ynthm.)

\@othm

```
\def\@othm#1[#2]#3{%
  \@ifundefined{c@#2}{\@nocounterr{#2}}%
    {\expandafter\@ifdefinable\csname #1\endcsname
    {\global\@namedef{the#1}{\@nameuse{the#2}}%
  \global\@namedef{#1}{\@thm{#2}{#3}}%
  \global\@namedef{end#1}{\@endtheorem}}}}
```

(*End definition for* \@othm.)

\@thm

```
\def\@thm#1#2{%
  \refstepcounter{#1}%
  \@ifnextchar[{\@ythm{#1}{#2}}{\@xthm{#1}{#2}}}
```

(*End definition for* \@thm.)

\@xthm
\@ythm

```
\def\@xthm#1#2{%
  \@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}
\def\@ythm#1#2[#3]{%
  \@opargbegintheorem{#2}{\csname the#1\endcsname}{#3}\ignorespaces}
```

(*End definition for* `\@xthm` *and* `\@ythm`.)

Default values

\@thmcounter
\@thmcountersep

```
\def\@thmcounter#1{\noexpand\arabic{#1}}
\def\@thmcountersep{.}
```

(*End definition for* `\@thmcounter` *and* `\@thmcountersep`.)

\@begintheorem
\@opargbegintheorem
\@endtheorem

Providing theorem defaults.

```
\def\@begintheorem#1#2{\trivlist
   \item[\hskip \labelsep{\bfseries #1\ #2}]\itshape}
\def\@opargbegintheorem#1#2#3{\trivlist
      \item[\hskip \labelsep{\bfseries #1\ #2\ (#3)}]\itshape}
\def\@endtheorem{\endtrivlist}
⟨/2ekernel⟩
```

(*End definition for* `\@begintheorem`, `\@opargbegintheorem`, *and* `\@endtheorem`.)

File O
ltsect.dtx

1 Sectioning Commands

This file defines the declarations such as `\author` which are used by `\maketitle`. `\maketitle` itself is defined by each class, not in the LaTeX kernel.

The second part of the file defines the generic commands used for defining sectioning commands such as `\chapter`. Again the actual document level commands are defined in the class files, in terms of these commands.

```
⟨*2ekernel⟩
\message{title,}
```

1.1 The Title

`\title` `\author` `\date` `\thanks` `\and` `\maketitle`

The user defines the title and author by the declarations `\title{`⟨*name*⟩`}`, `\author{`⟨*name*⟩`}`

Similarly the date is declared with `\date{`⟨*date*⟩`}`.

Inside these, the `\thanks{`⟨*footnote text*⟩`}` command may be used to make acknowledgements, notice of address, etc. in a footnote. If there are multiple authors, they have to be separated with the `\and` command.

And finally, the `\maketitle` command produces the actual title, using the information previously saved with the other commands.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\title}{Make commands robust}%
```

`\title` `\title` for use in `\maketitle`. If not given `\maketitle` will produce an error message.

```
\DeclareRobustCommand\title[1]{\gdef\@title{#1}}
```

(*End definition for* `\title`.)

`\author` `\author` for use in `\maketitle`. If not given `\maketitle` will produce a warning message.

```
\DeclareRobustCommand*\author[1]{\gdef\@author{#1}}
```

(*End definition for* `\author`.)

`\date` `\date` for use in `\maketitle`. If not given `\maketitle` will produce `\today` as the default.

```
\DeclareRobustCommand*\date[1]{\gdef\@date{#1}}
```

(*End definition for* `\date`.)

`\thanks`

```
\DeclareRobustCommand\thanks[1]{\footnotemark
    \protected@xdef\@thanks{\@thanks
        \protect\footnotetext[\the\c@footnote]{#1}}%
}
```

(*End definition for* `\thanks`.)

\and

```
\DeclareRobustCommand\and{%   % \begin{tabular}
  \end{tabular}%
  \hskip 1em \@plus.17fil%
  \begin{tabular}[t]{c}}%     % \end{tabular}
```

(*End definition for* \and.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\title}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\title
⟨latexrelease⟩\kernel@make@fragile\author
⟨latexrelease⟩\kernel@make@fragile\date
⟨latexrelease⟩\kernel@make@fragile\thanks
⟨latexrelease⟩\kernel@make@fragile\and
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\@title

```
\def\@title{\@latex@error{No \noexpand\title given}\@ehc}
```

(*End definition for* \@title.)

\@author

```
\def\@author{\@latex@warning@no@line{No \noexpand\author given}}
```

(*End definition for* \@author.)

\@date

```
\gdef\@date{\today}
```

(*End definition for* \@date.)

\@thanks

```
\let\@thanks\@empty
```

(*End definition for* \@thanks.)

```
\message{sectioning,}
```

1.2 Sectioning

\@secpenalty

```
\newcount\@secpenalty
\@secpenalty = -300
```

(*End definition for* \@secpenalty.)

\if@noskipsec
\@noskipsectrue

Way back in 1991 (08/26) FMi & RmS set the \@noskipsec switch to true for the preamble and to false in \document. This was done to trap lists and related text in the preamble but it does not catch everything.

```
\newif\if@noskipsec \@noskipsectrue
```

(*End definition for* `\if@noskipsec` *and* `\@noskipsectrue`.)

`\@startsection` The `\@startsection{`⟨*name*⟩`}{`⟨*level*⟩`}{ `⟨*indent*⟩`}{`⟨*beforeskip*⟩`}{`⟨*afterskip*⟩`}{`⟨*style*⟩`}*[`⟨*altheading*⟩ `]{`⟨*heading*⟩`}` command is the mother of all the user level sectioning commands. The part after the `*`, including the `*` is optional.

name: e.g., 'subsection'

level: a number, denoting depth of section – e.g., chapter = 0, section = 1, etc.

indent: Indentation of heading from left margin

beforeskip: Absolute value = skip to leave above the heading. If negative, then paragraph indent of text following heading is suppressed.

afterskip: if positive, then skip to leave below heading, else negative of skip to leave to right of run-in heading.

style: Commands to set style. Since June 1996 release the *last* command in this argument may be a command such as `\MakeUppercase` or `\fbox` that takes an argument. The section heading will be supplied as the argument to this command. So setting `#6` to, say, `\bfseries\MakeUppercase` would produce bold, uppercase headings.

If '`*`' is missing, then increment the counter. If it is present, then there should be no `[`⟨*altheading*⟩`]` argument. The command uses the counter 'secnumdepth'. It contains a pointer to the highest section level that is to be numbered.

Warning: The `\@startsection` command should be at the same or higher grouping level as the text that follows it. For example, you should *not* do something like

```
\def\foo{ \begingroup ...
            \paragraph{...}
          \endgroup}
```

Pseudocode for the `\@startsection` command *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
 \@startsection
{NAME}{LEVEL}{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE} ==
    BEGIN
     IF  @noskipsec = T  THEN  \leavevmode  FI
                               % true if previous section had no body.

     \par
     \@tempskipa  := BEFORESKIP
     @afterindent := T
     IF \@tempskipa < 0  THEN  \@tempskipa  := -\@tempskipa
                               @afterindent := F
     FI
     IF @nobreak = true
       THEN \everypar == null
       ELSE \addpenalty{\@secpenalty}
            \addvspace{\@tempskipa}
     FI
     IF * next
```

```
        THEN \@ssect{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE}
        ELSE \@dblarg{\@sect
                 {NAME}{LEVEL}{INDENT}
                 {BEFORESKIP}{AFTERSKIP}{STYLE}}
     FI
 END
```

End of historical LaTeX 2.09 comments.

```
\def\@startsection#1#2#3#4#5#6{%
  \if@noskipsec \leavevmode \fi
  \par
  \@tempskipa #4\relax
  \@afterindenttrue
  \ifdim \@tempskipa <\z@
    \@tempskipa -\@tempskipa \@afterindentfalse
  \fi
  \if@nobreak
    \everypar{}%
  \else
    \addpenalty\@secpenalty\addvspace\@tempskipa
  \fi
  \@ifstar
    {\@ssect{#3}{#4}{#5}{#6}}%
    {\@dblarg{\@sect{#1}{#2}{#3}{#4}{#5}{#6}}}}
```

(*End definition for* `\@startsection`.)

`\@sect` Pseudocode for the `\@sect` command *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
 \@sect{NAME}{LEVEL}
        {INDENT}{BEFORESKIP}{AFTERSKIP}
        {STYLE}[ARG1]{ARG2}
            ==
   BEGIN
    IF LEVEL > \c@secnumdepth
      THEN \@svsec :=L null
      ELSE \refstepcounter{NAME}
           \@svsec :=L BEGIN \@seccntformat{#1}\relax END
    FI
    IF AFTERSKIP > 0
      THEN \begingroup
               STYLE
               \@hangfrom{\hskip INDENT\@svsec}
               {\interlinepenalty 10000 ARG2\par}
           \endgroup
           \NAMEmark{ARG1}
           \addcontentsline{toc}{NAME}
              { IF   LEVEL > \c@secnumdepth
                  ELSE \protect\numberline{\theNAME}  FI
                ARG1 }
      ELSE \@svsechd == BEGIN   STYLE
                                \hskip INDENT\@svsec
```

```
                                    ARG2
                                    \NAMEmark{ARG1}
                                    \addcontentsline{toc}{NAME}
                                       { IF   LEVEL > \c@secnumdepth
                                           ELSE
                                             \protect\numberline{\theNAME}
                                           FI
                                         ARG1 }
                            END
    FI
    \@xsect{AFTERSKIP}
 END
```

End of historical LaTeX 2.09 comments.

```
\def\@sect#1#2#3#4#5#6[#7]#8{%
  \ifnum #2>\c@secnumdepth
    \let\@svsec\@empty
  \else
    \refstepcounter{#1}%
```

Since `\@seccntformat` might end with an improper `\hskip` which is scanning forward for `plus` or `minus` we end the definition of `\@svsec` with `\relax` as a precaution.

```
    \protected@edef\@svsec{\@seccntformat{#1}\relax}%
  \fi
  \@tempskipa #5\relax
  \ifdim \@tempskipa>\z@
    \begingroup
```

This `{` used to be after the argument to `\@hangfrom` but was moved here to allow commands such as `\MakeUppercase` to be used at the end of `#6`.

```
      #6{%
        \@hangfrom{\hskip #3\relax\@svsec}%
          \interlinepenalty \@M #8\@@par}%
    \endgroup
    \csname #1mark\endcsname{#7}%
    \addcontentsline{toc}{#1}{%
      \ifnum #2>\c@secnumdepth \else
        \protect\numberline{\csname the#1\endcsname}%
      \fi
      #7}%
  \else
```

`\relax` added 2 May 90

```
    \def\@svsechd{%
      #6{\hskip #3\relax
      \@svsec #8}%
      \csname #1mark\endcsname{#7}%
      \addcontentsline{toc}{#1}{%
        \ifnum #2>\c@secnumdepth \else
          \protect\numberline{\csname the#1\endcsname}%
        \fi
        #7}}%
  \fi
  \@xsect{#5}}
```

(*End definition for* `\@sect`.)

`\@xsect` Pseudocode for the `\@xsect` command *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
\@xsect{AFTERSKIP} ==
 BEGIN
   IF AFTERSKIP > 0
     THEN \par \nobreak
          \vskip AFTERSKIP
          \@afterheading
     ELSE @nobreak :=G F
          @noskipsec :=G T
          \everypar{ IF @noskipsec = T
                       THEN @noskipsec :=G F
                            \clubpenalty := 10000 % local
                            \hskip -\parindent
                            \begingroup
                              \@svsechd
                            \endgroup
                            \unskip
                            \hskip -AFTERSKIP \relax
                                          %% relax added 14 Jan 91
                       ELSE \clubpenalty := \@clubpenalty % local
                            \everypar := NULL
                     FI
                   }
   FI

  END
```

End of historical LaTeX 2.09 comments.

```
\def\@xsect#1{%
  \@tempskipa #1\relax
  \ifdim \@tempskipa>\z@
```

Why not combine `\@sect` and `\@xsect` and save doing the same test twice? It is not possible to change this now as these have become hooks!

This `\par` seems unnecessary.

```
    \par \nobreak
    \vskip \@tempskipa
    \@afterheading
  \else

    \@nobreakfalse
    \global\@noskipsectrue
    \everypar{%
      \if@noskipsec
        \global\@noskipsecfalse
       {\setbox\z@\lastbox}%
        \clubpenalty\@M
        \begingroup \@svsechd \endgroup
        \unskip
        \@tempskipa #1\relax
```

```
        \hskip -\@tempskipa
      \else
        \clubpenalty \@clubpenalty
        \everypar{}%
      \fi}%
  \fi
  \ignorespaces}
```

(*End definition for* `\@xsect`.)

`\@seccntformat` This command formats the section number including the space following it.

```
\def\@seccntformat#1{\csname the#1\endcsname\quad}
```

(*End definition for* `\@seccntformat`.)

Pseudocode for the `\@ssect` command *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
\@ssect{INDENT}{BEFORESKIP}{AFTERSKIP}{STYLE}{ARG} ==
  BEGIN
   IF AFTERSKIP > 0
     THEN \begingroup
            STYLE
            \@hangfrom{\hskip INDENT}
                      {\interlinepenalty 10000 ARG\par}
          \endgroup
     ELSE \@svsechd == BEGIN STYLE
                           \hskip INDENT
                           ARG
                       END
   FI
   \@xsect{AFTERSKIP}
  END
```

End of historical LaTeX 2.09 comments.

Pseudocode for the `\@afterheading` command *Historical LaTeX 2.09 comments (not necessarily accurate any more):*

```
\@afterheading ==
 BEGIN
   @nobreak :=G true
   \everypar := BEGIN IF @nobreak = T
                      THEN @nobreak  :=G false
                           \clubpenalty := 10000 % local
                           IF @afterindent = F
                             THEN remove \lastbox
                           FI
                      ELSE \clubpenalty := \@clubpenalty % local
                           \everypar := NULL
                   FI
                END
 END
```

End of historical LaTeX 2.09 comments.

\@ssect

```
\def\@ssect#1#2#3#4#5{%
  \@tempskipa #3\relax
  \ifdim \@tempskipa>\z@
    \begingroup
```

This { used to be after the argument to \@hangfrom but was moved here to allow commands such as \MakeUppercase to be used at the end of #4.

```
      #4{%
        \@hangfrom{\hskip #1}%
          \interlinepenalty \@M #5\@@par}%
    \endgroup
  \else
    \def\@svsechd{#4{\hskip #1\relax #5}}%
  \fi
  \@xsect{#3}}
```

(*End definition for* \@ssect.)

\if@afterindent
\@afterindenttrue

```
\newif\if@afterindent \@afterindenttrue
```

(*End definition for* \if@afterindent *and* \@afterindenttrue.)

\@afterheading

This hook is used in setting up custom-built headings in classes.dtx.

```
\def\@afterheading{%
  \@nobreaktrue
  \everypar{%
    \if@nobreak
      \@nobreakfalse
      \clubpenalty \@M
      \if@afterindent \else
        {\setbox\z@\lastbox}%
      \fi
    \else
      \clubpenalty \@clubpenalty
      \everypar{}%
    \fi}}
```

(*End definition for* \@afterheading.)

\@hangfrom

\@hangfrom{⟨*text*⟩} : Puts ⟨*text*⟩ in a box, and makes a hanging indentation of the following material up to the first \par. Should be used in vertical mode.

```
\def\@hangfrom#1{\setbox\@tempboxa\hbox{{#1}}%
      \hangindent \wd\@tempboxa\noindent\box\@tempboxa}
```

(*End definition for* \@hangfrom.)

\c@secnumdepth
\c@tocdepth

```
\newcount\c@secnumdepth
\newcount\c@tocdepth
```

(*End definition for* \c@secnumdepth *and* \c@tocdepth.)

\secdef

\secdef{⟨*unstarcmds*⟩}{⟨*unstarcmds*⟩}{ ⟨*starcmds*⟩}

When defining a \chapter or \section command without using \@startsection, you can use \secdef as follows:

1. \def\chapter{ ... \secdef \⟨*starcmd*⟩ \⟨*unstarcmd*⟩ }
2. \def\⟨*starcmd*⟩[#1]#2{ ...} % Command to define \chapter[...]{...}
3. \def\⟨*unstarcmd*⟩#1{ ...} % Command to define \chapter*{...}

```
\def\secdef#1#2{\@ifstar{#2}{\@dblarg{#1}}}
```

(*End definition for* \secdef.)

1.2.1 Initializations

\sectionmark
\subsectionmark
\subsubsectionmark
\paragraphmark
\subparagraphmark

```
\let\sectionmark\@gobble
\let\subsectionmark\@gobble
\let\subsubsectionmark\@gobble
\let\paragraphmark\@gobble
\let\subparagraphmark\@gobble
```

(*End definition for* \sectionmark *and others.*)

```
\message{contents,}
```

1.3 Table of Contents etc.

1.3.1 Convention

\tf@⟨*foo*⟩ = file number for output for table foo. The file is opened only if @filesw = true.

1.3.2 Commands

A \l@⟨*type*⟩{⟨*entry*⟩}{⟨*page*⟩} Macro needs to defined by document style for making an entry of type ⟨*type*⟩ in a table of contents, etc. E.g., the document style should define \l@chapter, \l@section, etc.

Note: When the \protect command is used in the ⟨*entry*⟩ or ⟨*text*⟩ of one of the commands below, it causes the following control sequence to be written on the file without being expanded. The sequence will be expanded when the table of contents entry is processed.

Surprise: Inside an \addcontentsline or \addtocontents command argument, the commands: \index, \glossary, and \label are no-ops . This could cause a problem if the user puts an \index or \label into one of the commands he writes, or into the optional 'short version' argument of a \section or \caption command.

\@starttoc

The \@starttoc{⟨*ext*⟩} command is used to define the commands: \tableofcontents, \listoffigures, etc.

For example: \@starttoc{lof} is used in \listoffigures. This command reads the .⟨*ext*⟩ file and sets up to write the new .⟨*ext*⟩ file.

Historical LaTeX 2.09 comments (not necessarily accurate any more):

\@starttoc{EXT} ==

```
BEGIN
  \begingroup
     \makeatletter
     read file \jobname.EXT
     IF @filesw = true
       THEN  open \jobname.EXT as file \tf@EXT
     FI
     @nobreak :=G FALSE  %% added 24 May 89
  \endgroup
END
```

End of historical LaTeX 2.09 comments.

```
\def\@starttoc#1{%
  \begingroup
    \makeatletter
    \@input{\jobname.#1}%
    \if@filesw
      \expandafter\newwrite\csname tf@#1\endcsname
      \immediate\openout \csname tf@#1\endcsname \jobname.#1\relax
    \fi
    \@nobreakfalse
  \endgroup}
```

(*End definition for* `\@starttoc`.)

`\addcontentsline` The `\addcontentsline{`⟨*table*⟩`}{`⟨*type*⟩`}{`⟨*entry*⟩`}` command allows the user to add his/her own entry to a table of contents, etc. The command adds the entry `\contentsline{`⟨*type*⟩`}{`⟨*entry*⟩`}{`⟨*page*⟩`}{}` to the `.`⟨*table*⟩ file.

This macro is implemented as an application of `\addtocontents`. Note that `\thepage` is not expandable during `\protected@write` therefore one gets the page number at the time of the `\shipout`.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\addcontentsline}{fourth argument}%
\def\addcontentsline#1#2#3{%
```

We add an empty brace pair at the end of `\contentsline` so that the number of argument is identical in documents with and without hyperref.

```
  \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}{}%
                     \protected@file@percent}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                  {\addcontentsline}{Mask line endings}%
⟨latexrelease⟩ \def\addcontentsline#1#2#3{%
⟨latexrelease⟩  \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}%
```

We add `\protected@file@percent` at the end which is turned inside `\@writefile` into a percent character to mask the newline after the closing argument brace.

```
⟨latexrelease⟩             \protected@file@percent}}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\addcontentsline}{Mask line endings}%
```

```
⟨latexrelease⟩\def\addcontentsline#1#2#3{%
⟨latexrelease⟩   \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\addcontentsline`.)

`\addtocontents` The `\addtocontents{`⟨*table*⟩`}{`⟨*text*⟩`}` command adds ⟨*text*⟩ to the `.`⟨*table*⟩ file, with no page number.

```
\long\def\addtocontents#1#2{%
  \protected@write\@auxout
      {\let\label\@gobble \let\index\@gobble \let\glossary\@gobble}%
      {\string\@writefile{#1}{#2}}}
```

(*End definition for* `\addtocontents`.)

`\contentsline` The `\contentsline{`⟨*type*⟩`}{`⟨*entry*⟩`}{`⟨*page*⟩`}{}` macro produces a ⟨*type*⟩ entry in a table of contents, etc. It will appear in the `.toc` or other file. For example, The entry for subsection 1.4.3 in the table of contents for example, might be produced by:

```
\contentsline{subsection}
    {\makebox{30pt}[r]{1.4.3} Gnats and Gnus}{22}
```

The `\protect` command causes command sequences to be written without expanding them.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                  {\contentsline}{Four arguments}%
```

In the toc file `\contentsline` is followed by 4 arguments these days, but only the first 3 are used in the old interface. The fourth was by default empty and only used when hyperref was loaded. We now pick up all 4 arguments, save the last one away in `\@contentsline@destination` and then call the old interface. This is done to simplify the interface to hyperref and to prepare for future changes.

```
\def\contentsline#1#2#3#4{\gdef\@contentsline@destination{#4}%
                          \csname l@#1\endcsname{#2}{#3}}
```

Default definition.

```
\let\@contentsline@destination\@empty
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\contentsline}{Four arguments}%
⟨latexrelease⟩
⟨latexrelease⟩\def\contentsline#1{\csname l@#1\endcsname}
⟨latexrelease⟩\let\@contentsline@destination\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\contentsline`.)

`\@dottedtocline{`⟨*level*⟩`}{`⟨*indent*⟩`}{`⟨*numwidth*⟩ `}{`⟨*title*⟩`}{`⟨*page*⟩`}`: Macro to produce a table of contents line with the following parameters:

level If ⟨*level*⟩ > `\c@tocdepth`, then no line produced.

indent Total indentation from the left margin.

numwidth Width of box for number if the ⟨*title*⟩ has a `\numberline` command. As of 25 Jan 1988, this is also the amount of extra indentation added to second and later lines of a multiple line entry.

title Contents of entry.

page Page number.

Uses the following parameters, which must be set by the document style. They should be defined with `\def`'s.

`pnumwidth` Width of box in which page number is set.

`tocrmarg` Right margin indentation for all but last line of multiple-line entries.

`dotsep` Separation between dots, in mu units. Should be `\def`'d to a number like 2 or 1.7

`\@dottedtocline`

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2018/12/01}%
⟨latexrelease⟩                  {\@dottedtocline}{Prevent protrusion}%
\def\@dottedtocline#1#2#3#4#5{%
  \ifnum #1>\c@tocdepth \else
    \vskip \z@ \@plus.2\p@
    {\leftskip #2\relax \rightskip \@tocrmarg \parfillskip -\rightskip
     \parindent #2\relax\@afterindenttrue
     \interlinepenalty\@M
     \leavevmode
     \@tempdima #3\relax
```

If a document uses fonts other than computer modern, the use of a dot from math can be very disturbing despite the fact that this might be the only place in a document that then uses computer modern. Therefore we surround the dot with an `\hbox` to escape to the surrounding text font.

```
     \advance\leftskip \@tempdima \null\nobreak\hskip -\leftskip
     {#4}\nobreak
     \leaders\hbox{$\m@th
        \mkern \@dotsep mu\hbox{.}\mkern \@dotsep
        mu$}\hfill
    \nobreak
    \hb@xt@\@pnumwidth{\hfil\normalfont \normalcolor #5%
```

We finish off by preventing any protrusion if that is enabled. If protrusion happens the number may shift to the right and as a result you may end up with an additional dot in the toc line in some situations.

```
                        \kern-\p@\kern\p@}%
    \par}%
  \fi}
```

(*End definition for* `\@dottedtocline`.)

`\noprotrusion` This command, if placed directly to the right (or left) of a word, will prevent protrusion of that word into the margin. It is used in the toc entry lines as they shouldn't protrude. It is implemented as to kerns that cancel each other but being there hide the word so that protrusion is not added. Note that a zero kern or an empty box would not work as the protrusion mechanism will skip over those.

```
\DeclareRobustCommand\noprotrusion{\leavevmode\kern-\p@\kern\p@}
```

(*End definition for* `\noprotrusion`.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@dottedtocline}{Prevent protrusion}%
⟨latexrelease⟩\def\@dottedtocline#1#2#3#4#5{%
⟨latexrelease⟩  \ifnum #1>\c@tocdepth \else
⟨latexrelease⟩    \vskip \z@ \@plus.2\p@
⟨latexrelease⟩    {\leftskip #2\relax \rightskip \@tocrmarg \parfillskip -\rightskip
⟨latexrelease⟩     \parindent #2\relax\@afterindenttrue
⟨latexrelease⟩     \interlinepenalty\@M
⟨latexrelease⟩     \leavevmode
⟨latexrelease⟩     \@tempdima #3\relax
⟨latexrelease⟩     \advance\leftskip \@tempdima \null\nobreak\hskip -\leftskip
⟨latexrelease⟩     {#4}\nobreak
⟨latexrelease⟩     \leaders\hbox{$\m@th
⟨latexrelease⟩        \mkern \@dotsep mu\hbox{.}\mkern \@dotsep
⟨latexrelease⟩        mu$}\hfill
⟨latexrelease⟩     \nobreak
⟨latexrelease⟩     \hb@xt@\@pnumwidth{\hfil\normalfont \normalcolor #5}%
⟨latexrelease⟩     \par}%
⟨latexrelease⟩  \fi}
⟨latexrelease⟩
⟨latexrelease⟩\let\noprotrusion\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

Note: `\nobreak`'s added 7 Jan 86 to prevent bad line break that left the page number dangling by itself at left edge of a new line.

Changed 25 Jan 88 to use `\leftskip` instead of `\hangindent` so leaders of multiple-line contents entries would line up properly.

`\numberline` `\numberline{`⟨*number*⟩`}`: For use in a `\contentsline` command. It puts ⟨*number*⟩ flush-left in a box of width `\@tempdima` (Before 25 Jan 88 change, it also added `\@tempdima` to the hanging indentation.)

```
\def\numberline#1{\hb@xt@\@tempdima{#1\hfil}}
⟨/2ekernel⟩
```

(*End definition for* `\numberline`.)

File P
ltfloat.dtx

1 Floats

The different types of floats are identified by a ⟨*type*⟩ name, which is the name of the counter for that kind of float. For example, figures are of type 'figure' and tables are of type 'table'. Each ⟨*type*⟩ has associated a positive ⟨*type number*⟩, which is a power of two. E.g.,
figures might be have type number 1, tables type number 2, programs type number 4, etc.

The locations where a float can go are specified by a ⟨*placement specifier*⟩, which is a list of the possible locations, each denoted by a letter as follows:

h : here — at the current location in the text.
t : top — at the top of a text page.
b : bottom — at the bottom of a text page.
p : page — on a separate float page

In addition, in conjunction with these, you can use '!' which means that the current values of the float positioning parameters are ignored for this float. (Has no effect on 'p', float page positioning.) For example, 'pht' specifies that the float can appear in any of three locations: page, here or top.

1.1 Floating Environments

```
⟨*2ekernel⟩
\message{floats,}
```

Historical LaTeX 2.09 comments (not necessarily accurate any more):

Where floats may appear on a page, and how many may appear there are specified by the following float placement parameters. The numbers are named like counters so the user can set them with the ordinary counter-setting commands.

```
\c@topnumber       : Number of floats allowed at the top of a column.
\topfraction       : Fraction of column that can be devoted to floats.
\c@dbltopnumber, \dbltopfraction
                   : Same as above, but for double-column floats.
\c@bottomnumber, \bottomfraction
                   : Same as above for bottom of page.
\c@totalnumber     : Number of floats allowed in a single column,
                         including in-text floats.
\textfraction      :Minimum fraction of column that must contain text.
\floatpagefraction: Minimum fraction of page that must be taken
                         up by float page.
\dblfloatpagefraction
                   : Same as above, for double-column floats.
```

The document style must define the following.

```
\fps@TYPE    : The default placement specifier for floats of type
               TYPE.

\ftype@TYPE  : The type number for floats of type TYPE.

\ext@TYPE    : The file extension indicating the file on which the
               contents list for float type TYPE is stored.
                 For example,  \ext@figure = 'lof'.

\fnum@TYPE   : A macro to generate the figure number for a caption.
               For example, \fnum@TYPE == Figure \thefigure.

\@makecaption{NUM}{TEXT} :
            A macro to make a caption, with NUM the value
            produced by \fnum@... and TEXT the text of the caption.
            It can assume it's in a \parbox of the appropriate width.

\@float{TYPE}[PLACEMENT] : This macro begins a float environment for a
    single-column float of type TYPE with PLACEMENT as the placement
    specifier.  The default value of PLACEMENT is defined by
    \fps@TYPE.  The environment is ended by \end@float.
    E.g., \figure == \@float{figure}, \endfigure == \end@float.

 \@float{TYPE}[PLACEMENT] ==
  BEGIN
    if hmode then \@bsphack
                  \@floatpenalty := -10002
            else \@floatpenalty := -10003
    fi
    \@captype ==L TYPE
    \@dblflset
    \@fps     ==L PLACEMENT
    \@onelevel@sanitize \@fps
    add default PLACEMENT if at most ! in PLACEMENT ==
\@fpsadddefault
    if inner
      then LaTeX Error: 'Not in outer paragraph mode.'
           \@floatpenalty := 0
      else if \@freelist nonempty
            then \@currbox  :=L head of \@freelist
                 \@freelist :=G tail of \@freelist
                 \count\@currbox :=G 32*\ftype@TYPE +
                                       bits determined by PLACEMENT
            else \@floatpenalty := 0
                 LaTeX Error: 'Too many unprocessed floats'
           fi
    fi
    \@currbox :=G   \color@vbox
```

```
                    \normalcolor
                      \vbox{
                       %% 15 Dec 87 –
                       %% removed \boxmaxdepth :=L 0pt
                       %% that made box 0 depth because it screwed
                       %% things up. Instead, added \vskip0pt at end
                            \hsize = \columnwidth
                            \@parboxrestore
                            \@floatboxreset
  END

 \caption ==
   BEGIN
    \refstepcounter{\@captype}
    \@dblarg{\@caption{\@captype}}
   END
```

In following definition, `\par` moved from after `\addcontentsline` to before `\addcontentsline` because the `\write` could cause an extra blank line to be added to the paragraph above the caption. (Change made 12 Jun 87)

```
 \@caption{TYPE}[STEXT]{TEXT} ==
  BEGIN
    \par
    \addcontentsline{\ext@TYPE}{TYPE}{\numberline{\theTYPE}{STEXT}}
    \begingroup
      \@parboxrestore
      \@normalsize
      \@makecaption{\fnum@TYPE}{TEXT}
      \par
    \endgroup
  END
```

`\@dblfloat`{TYPE}[PLACEMENT] : Macro to begin a float environment for a double-column float of type TYPE with PLACEMENT as the placement specifier. The default value of PLACEMENT is 'tp'
The environment is ended by `\end@dblfloat`.
E.g., `\figure*` == `\@dblfloat`{figure},
`\endfigure*` == `\end@dblfloat`.

`\@dblfloat`{TYPE}[PLACEMENT] ==
Identical to `\@float`{TYPE}[PLACEMENT] except `\hsize` and `\linewidth` are set to `\textwidth`.

End of historical LaTeX 2.09 comments.

`\@floatpenalty`

```
3 \newcount\@floatpenalty
```

(*End definition for* `\@floatpenalty`.)

\caption This is set to be an error message outside a float since no captype is defined there; this may need to be changed by some classes.

```
\def\caption{%
  \ifx\@captype\@undefined
    \@latex@error{\noexpand\caption outside float}\@ehd
    \expandafter\@gobble
  \else
    \refstepcounter\@captype
    \expandafter\@firstofone
  \fi
  {\@dblarg{\@caption\@captype}}%
}
```

(*End definition for* \caption.)

\@caption

```
\long\def\@caption#1[#2]#3{%
  \par
  \addcontentsline{\csname ext@#1\endcsname}{#1}%
    {\protect\numberline{\csname the#1\endcsname}{\ignorespaces #2}}%
  \begingroup
```

The paragraph setting parameters are normalised at this point, however \@parboxrestore resets \everypar which is not correct in this context so \@setminipage is called if needed.

The float mechanism, like minipage, sets the flag @minipage true before executing the user-supplied text. Many LaTeX constructs test for this flag and do not add vertical space when it is true. The intention is that this emulates TeX's 'top of page' behaviour. The flag must be set false at the start of the first paragraph. This is achieved by a redefinition of \everypar, but the call to \@parboxrestore removes that redefinition, so it is re-inserted if needed. If the flag is already false then the \caption was not the first entry in the float, and so some other paragraph has already activated the special \everypar. In this case no further action is needed.

```
    \@parboxrestore
    \if@minipage
      \@setminipage
    \fi
    \normalsize
    \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par
  \endgroup}
```

(*End definition for* \@caption.)

\@float
\@dblflset

```
\def\@float#1{%
  \@ifnextchar[%
    {\@xfloat{#1}}%
    {\edef\reserved@a{\noexpand\@xfloat{#1}[\csname fps@#1\endcsname]}%
     \reserved@a}}
```

(*End definition for* \@float *and* \@dblflset.)

\@dblfloat

```
\def\@dblfloat{%
  \if@twocolumn\let\reserved@a\@dbflt\else\let\reserved@a\@float\fi
  \reserved@a}
```

(*End definition for* `\@dblfloat`.)

`\fps@dbl` Note that all double floats have default fps 'tp'.

(*End definition for* `\fps@dbl`.)

`\@setfps` This sets the fps, dealing with error conditions by adding the default.

(*End definition for* `\@setfps`.)

`\@xfloat` The first part of this sets the count register that stores all the information about the type and fps of the float.

We assume here that the default specifiers already contain no active characters.

It may be better to store the defaults as numbers, rather than symbol strings.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\@xfloat}{Check float options}%
⟨*2ekernel | latexrelease⟩
\def\@xfloat #1[#2]{%
  \@nodocument
  \def \@captype {#1}%
   \def \@fps {#2}%
   \@onelevel@sanitize \@fps
   \def \reserved@b {!}%
   \ifx \reserved@b \@fps
     \@fpsadddefault
   \else
     \ifx \@fps \@empty
       \@fpsadddefault
     \fi
   \fi
   \ifhmode
     \@bsphack
     \@floatpenalty -\@Mii
   \else
     \@floatpenalty-\@Miii
   \fi
  \ifinner
     \@parmoderr\@floatpenalty\z@
  \else
    \@next\@currbox\@freelist
      {%
       \@tempcnta \sixt@@n
       \expandafter \@tfor \expandafter \reserved@a
         \expandafter :\expandafter =\@fps
         \do
```

Start of changes, use a nested if structure, ending in an error.

```
          {%
           \if \reserved@a h%
             \ifodd \@tempcnta
             \else
               \advance \@tempcnta \@ne
             \fi
```

```
          \else\if \reserved@a t%
            \@setfpsbit \tw@
          \else\if \reserved@a b%
            \@setfpsbit 4%
          \else\if \reserved@a p%
            \@setfpsbit 8%
          \else\if \reserved@a !%
            \ifnum \@tempcnta>15
              \advance\@tempcnta -\sixt@@n\relax
            \fi
          \else
            \@latex@error{Unknown float option `\reserved@a'}%
            {Option `\reserved@a' ignored and `p' used.}%
            \@setfpsbit 8%
          \fi\fi\fi\fi\fi
          }%
```

End of changes

```
      \@tempcntb \csname ftype@\@captype \endcsname
      \multiply \@tempcntb \@xxxii
      \advance \@tempcnta \@tempcntb
      \global \count\@currbox \@tempcnta
      }%
    \@fltovf
  \fi
```

The remainder sets up the box in which the float is typeset, and the typesetting environment to be used. It is essential to have the extra box to avoid the unwanted space that would otherwise often be put at the top of the float.

It ends with a hook; not sure how useful this is but it is needed at present to deal with double-column floats.

```
  \global \setbox\@currbox
    \color@vbox
      \normalcolor
      \vbox \bgroup
        \hsize\columnwidth
        \@parboxrestore
        \@floatboxreset
}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@xfloat}{Check float options}%
⟨latexrelease⟩\def\@xfloat #1[#2]{%
⟨latexrelease⟩  \@nodocument
⟨latexrelease⟩  \def \@captype {#1}%
⟨latexrelease⟩   \def \@fps {#2}%
⟨latexrelease⟩   \@onelevel@sanitize \@fps
⟨latexrelease⟩   \def \reserved@b {!}%
⟨latexrelease⟩   \ifx \reserved@b \@fps
⟨latexrelease⟩     \@fpsadddefault
⟨latexrelease⟩   \else
⟨latexrelease⟩     \ifx \@fps \@empty
⟨latexrelease⟩       \@fpsadddefault
```

```
⟨latexrelease⟩      \fi
⟨latexrelease⟩    \fi
⟨latexrelease⟩    \ifhmode
⟨latexrelease⟩      \@bsphack
⟨latexrelease⟩      \@floatpenalty -\@Mii
⟨latexrelease⟩    \else
⟨latexrelease⟩      \@floatpenalty-\@Miii
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \ifinner
⟨latexrelease⟩      \@parmoderr\@floatpenalty\z@
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@next\@currbox\@freelist
⟨latexrelease⟩      {%
⟨latexrelease⟩       \@tempcnta \sixt@@n
⟨latexrelease⟩       \expandafter \@tfor \expandafter \reserved@a
⟨latexrelease⟩         \expandafter :\expandafter =\@fps
⟨latexrelease⟩         \do
⟨latexrelease⟩          {%
⟨latexrelease⟩           \if \reserved@a h%
⟨latexrelease⟩             \ifodd \@tempcnta
⟨latexrelease⟩             \else
⟨latexrelease⟩               \advance \@tempcnta \@ne
⟨latexrelease⟩             \fi
⟨latexrelease⟩           \fi
⟨latexrelease⟩           \if \reserved@a t%
⟨latexrelease⟩             \@setfpsbit \tw@
⟨latexrelease⟩           \fi
⟨latexrelease⟩           \if \reserved@a b%
⟨latexrelease⟩             \@setfpsbit 4%
⟨latexrelease⟩           \fi
⟨latexrelease⟩           \if \reserved@a p%
⟨latexrelease⟩             \@setfpsbit 8%
⟨latexrelease⟩           \fi
⟨latexrelease⟩           \if \reserved@a !%
⟨latexrelease⟩             \ifnum \@tempcnta>15
⟨latexrelease⟩               \advance\@tempcnta -\sixt@@n\relax
⟨latexrelease⟩             \fi
⟨latexrelease⟩           \fi
⟨latexrelease⟩           }%
⟨latexrelease⟩       \@tempcntb \csname ftype@\@captype \endcsname
⟨latexrelease⟩       \multiply \@tempcntb \@xxxii
⟨latexrelease⟩       \advance \@tempcnta \@tempcntb
⟨latexrelease⟩       \global \count\@currbox \@tempcnta
⟨latexrelease⟩       }%
⟨latexrelease⟩    \@fltovf
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \global \setbox\@currbox
⟨latexrelease⟩    \color@vbox
⟨latexrelease⟩      \normalcolor
⟨latexrelease⟩      \vbox \bgroup
⟨latexrelease⟩        \hsize\columnwidth
⟨latexrelease⟩        \@parboxrestore
⟨latexrelease⟩        \@floatboxreset
⟨latexrelease⟩}%
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@xfloat`.)

`\@floatboxreset` The rational for allowing these normally global flags to be set locally here, via `\@parboxrestore`, was stated originally by Donald Arseneau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within marginals or floats or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in `\set@nobreak`; otherwise this command will be redundant.

```
\def \@floatboxreset {%
        \reset@font
        \normalsize
        \@setminipage
}
```

(*End definition for* `\@floatboxreset`.)

`\@setnobreak`

```
\def \@setnobreak{%
  \if@nobreak
    \let\outer@nobreak\@nobreaktrue
    \@nobreakfalse
  \fi
}
```

(*End definition for* `\@setnobreak`.)

`\@setminipage`

```
\def \@setminipage{%
  \@minipagetrue
  \everypar{\@minipagefalse\everypar{}}%
}
```

(*End definition for* `\@setminipage`.)

`\end@float`

```
\def\end@float{%
  \@endfloatbox
  \ifnum\@floatpenalty <\z@
```

We make sure that we never exceed `\textheight`, otherwise float will never get typeset (91/03/15 FMi).

```
    \@largefloatcheck
    \@cons\@currlist\@currbox
    \ifnum\@floatpenalty <-\@Mii
      \penalty -\@Miv
```

Saving and restoring `\prevdepth` added 26 May 87 to prevent extra vertical space when used in vertical mode.

```
      \@tempdima\prevdepth
      \vbox{}%
      \prevdepth\@tempdima
```

```
      \penalty\@floatpenalty
    \else
      \vadjust{\penalty -\@Miv \vbox{}\penalty\@floatpenalty}\@Esphack
    \fi
  \fi
}
```

(*End definition for* `\end@float`.)

`\end@dblfloat`

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\end@dblfloat}{float order in 2-column}%
⟨*2ekernel | latexrelease⟩
\def\end@dblfloat{%
  \if@twocolumn
    \@endfloatbox
    \ifnum\@floatpenalty <\z@
      \@largefloatcheck
```

Force the depth of two column float boxes.

```
      \global\dp\@currbox1sp %
```

What follows is essentially `\end@float` without a starting `\@endfloatbox`.

```
      \@cons\@currlist\@currbox
      \ifnum\@floatpenalty <-\@Mii
        \penalty -\@Miv
        \@tempdima\prevdepth
        \vbox{}%
        \prevdepth\@tempdima
        \penalty\@floatpenalty
      \else
        \vadjust{\penalty -\@Miv \vbox{}\penalty\@floatpenalty}\@Esphack
      \fi
    \fi
  \else
    \end@float
  \fi
}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\end@dblfloat}{float order in 2-column}%
⟨latexrelease⟩\def\end@dblfloat{%
⟨latexrelease⟩\if@twocolumn
⟨latexrelease⟩  \@endfloatbox
⟨latexrelease⟩  \ifnum\@floatpenalty <\z@
```

We make sure that we never exceed `\textheight`, otherwise float will never get typeset (91/03/15 FMi).

```
⟨latexrelease⟩    \@largefloatcheck
⟨latexrelease⟩    \@cons\@dbldeferlist\@currbox
⟨latexrelease⟩  \fi
```

RmS 92/03/18 changed \@esphack to \@Esphack.

```
⟨latexrelease⟩     \ifnum \@floatpenalty =-\@Mii \@Esphack\fi
⟨latexrelease⟩\else
⟨latexrelease⟩   \end@float
⟨latexrelease⟩\fi
⟨latexrelease⟩}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \end@dblfloat.)

\@endfloatbox This macro is not intended to be a hook; it is designed to help maintain the integrity of this code, which is used twice and, as can be seen, is subject to frequent changes.

```
\def \@endfloatbox{%
      \par\vskip\z@skip      %% \par\vskip\z@ added 15 Dec 87
      \@minipagefalse
      \outer@nobreak
    \egroup                  %% end of vbox
  \color@endbox
}
```

(*End definition for* \@endfloatbox.)

\outer@nobreak

```
\let\outer@nobreak\@empty
```

(*End definition for* \outer@nobreak.)

\@largefloatcheck This calculates by how much a float is oversize for the page and prints this in a warning message.

```
\def \@largefloatcheck{%
  \ifdim \ht\@currbox>\textheight
    \@tempdima -\textheight
    \advance \@tempdima \ht\@currbox
    \@latex@warning {Float too large for page by \the\@tempdima}%
    \ht\@currbox \textheight
  \fi
}
```

(*End definition for* \@largefloatcheck.)

\@dbflt
\@xdblfloat

```
\def\@dbflt#1{\@ifnextchar[{\@xdblfloat{#1}}{\@xdblfloat{#1}[tp]}}
\def\@xdblfloat#1[#2]{%
  \@xfloat{#1}[#2]\hsize\textwidth\linewidth\textwidth}
```

(*End definition for* \@dbflt *and* \@xdblfloat.)

Moved to ltoutput 93/12/16

```
%\newcount\c@topnumber
%\newcount\c@dbltopnumber
%\newcount\c@bottomnumber
%\newcount\c@totalnumber
```

`\@floatplacement` An analysis of `\@floatplacement`:

This should be called whenever `\@colht` has been set.

```
\def\@floatplacement{\global\@topnum\c@topnumber
    % Textpage bit, global:
   \global\@toproom \topfraction\@colht
   \global\@botnum  \c@bottomnumber
   \global\@botroom \bottomfraction\@colht
   \global\@colnum  \c@totalnumber
    % Floatpage bit, local:
   \@fpmin   \floatpagefraction\@colht}
⟨/2ekernel⟩
```

(*End definition for* `\@floatplacement`.)

`\@dblfloatplacement` This should be called only within a group. Now changed to provide extra checks in `\@addtodblcol`, needed when processing a BANG float.

```
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩          {\@dblfloatplacement}{float order in 2-column}%
⟨*2ekernel | latexrelease⟩
```

When making two column float area, look for floats with 1sp depth.

```
\def\@dblfloatplacement{\global\@dbltopnum\c@dbltopnumber
   \global\@dbltoproom \dbltopfraction\@colht
   \@textmin \@colht
   \advance \@textmin -\@dbltoproom
   \@fpmin \dblfloatpagefraction\textheight
   \@fptop \@dblfptop
   \@fpsep \@dblfpsep
   \@fpbot \@dblfpbot
```

`\f@depth` is used in `\@testwrongwidth` to look for either column or dbl-column floats. A value of `1sp` signals the latter. Because of this setting here, `\@dblfloatplacment` needs to be called inside a group which is a questionable design.

```
   \def\f@depth{1sp}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩          {\@dblfloatplacement}{float order in 2-column}%
⟨latexrelease⟩\def \@dblfloatplacement {%
```

Textpage bit: global, but need not be.

```
⟨latexrelease⟩  \global \@dbltopnum \c@dbltopnumber
⟨latexrelease⟩  \global \@dbltoproom \dbltopfraction\@colht
```

This new bit uses `\@textmin` to locally store the amount of extra room in the column.

```
⟨latexrelease⟩  \@textmin \@colht
⟨latexrelease⟩  \advance \@textmin -\@dbltoproom
```

Floatpage bit: must be local.

```
⟨latexrelease⟩  \@fpmin \dblfloatpagefraction\textheight
⟨latexrelease⟩  \@fptop \@dblfptop
⟨latexrelease⟩  \@fpsep \@dblfpsep
⟨latexrelease⟩  \@fpbot \@dblfpbot
⟨latexrelease⟩}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@dblfloatplacement`.)

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
MARGINAL NOTES:

Marginal notes use the same mechanism as floats to communicate
with the \output routine.  Marginal notes are distinguished from
floats by having a negative placement specification.  The command
\marginpar [LTEXT]{RTEXT} generates a marginal note in a parbox,
using LTEXT if it's on the left and RTEXT if it's on the right.
(Default is RTEXT = LTEXT.)  It uses the following parameters.

\marginparwidth : Width of marginal notes.
\marginparsep   : Distance between marginal note and text.
      the page layout to determine how to move the marginal
      note into the margin.   E.g., \@leftmarginskip ==
      \hskip -\marginparwidth \hskip -\marginparsep .
\marginparpush  :  Minimum vertical separation between \marginpar's

Marginal notes are normally put on the outside of the page
if @mparswitch = true, and on the right if @mparswitch = false.
The command \reversemarginpar reverses the side where they
are put.  \normalmarginpar undoes \reversemarginpar.
These commands have no effect for two-column output.

SURPRISE: if two marginal notes appear on the same line of
text, then the second one could appear on the next page, in
a funny position.


\marginpar [LTEXT]{RTEXT} ==
 BEGIN
   if hmode then \@bsphack
                 \@floatpenalty := -10002
            else \@floatpenalty := -10003
   fi
   if inner
     then LaTeX Error: 'Not in outer paragraph mode.'
          \@floatpenalty := 0
     else if \@freelist has two elements:
            then get \@marbox, \@currbox  from \@freelist
                 \count\@marbox :=G -1
            else \@floatpenalty := 0
                 LaTeX Error: 'Too many unprocessed floats'
                 \@currbox, \@marbox := \@tempboxa    %%use \def
          fi
   fi
   if optional argument
     then %% \@xmpar ==
          \@savemarbox\@marbox{LTEXT}
          \@savemarbox\@currbox{RTEXT}
```

```
        else %% \@ympar ==
              \@savemarbox\@marbox{RTEXT}
              \box\@currbox :=G \box\@marbox
    fi
    \@xympar
   END

\reversemarginpar == BEGIN \@mparbottom    :=G 0
                           @reversemargin :=G true
                     END

\normalmarginpar  == BEGIN \@mparbottom    :=G 0
                           @reversemargin :=G false
                     END
```

End of historical LaTeX 2.09 comments.

`\marginpar`

```
\def\marginpar{%
  \ifhmode
    \@bsphack
    \@floatpenalty -\@Mii
  \else
    \@floatpenalty-\@Miii
  \fi
  \ifinner
    \@parmoderr
    \@floatpenalty\z@
  \else
    \@next\@currbox\@freelist{}{}%
    \@next\@marbox\@freelist{\global\count\@marbox\m@ne}%
       {\@floatpenalty\z@
        \@fltovf\def\@currbox{\@tempboxa}\def\@marbox{\@tempboxa}}%
  \fi
  \@ifnextchar [\@xmpar\@ympar}
```

(*End definition for* `\marginpar`.)

`\@xmpar`

```
\long\def\@xmpar[#1]#2{%
  \@savemarbox\@marbox{#1}%
  \@savemarbox\@currbox{#2}%
  \@xympar}
```

(*End definition for* `\@xmpar`.)

`\@ympar`

```
\long\def\@ympar#1{%
  \@savemarbox\@marbox{#1}%
  \global\setbox\@currbox\copy\@marbox
  \@xympar}
```

(*End definition for* `\@ympar`.)

\@savemarbox

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\@savemarbox}{Explicit par for marginpar}%
\long\def \@savemarbox #1#2{%
  \global\setbox #1%
    \color@vbox
      \vtop{%
        \hsize\marginparwidth
        \@parboxrestore
        \@marginparreset
        #2\par
        \@minipagefalse
        \outer@nobreak
        }%
    \color@endbox
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@savemarbox}{Explicit par for marginpar}%
⟨latexrelease⟩
⟨latexrelease⟩\long\def \@savemarbox #1#2{%
⟨latexrelease⟩  \global\setbox #1%
⟨latexrelease⟩    \color@vbox
⟨latexrelease⟩      \vtop{%
⟨latexrelease⟩        \hsize\marginparwidth
⟨latexrelease⟩        \@parboxrestore
⟨latexrelease⟩        \@marginparreset
⟨latexrelease⟩        #2%
⟨latexrelease⟩        \@minipagefalse
⟨latexrelease⟩        \outer@nobreak
⟨latexrelease⟩        }%
⟨latexrelease⟩    \color@endbox
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@savemarbox`.)

\@marginparreset The rational for allowing these normally global flags to be set locally here, via `\@parboxrestore` was stated originally by Donald Arseneau and extended by Chris Rowley. It is because these flags are only set globally to true by section commands, and these should never appear within marginals or floats or, indeed, in any group; and they are only ever set globally to false when they are definitely true.

If anyone is unhappy with this argument then both flags should be treated as in `\set@nobreak`; otherwise this command will be redundant.

```
\def \@marginparreset {%
        \reset@font
        \normalsize
%        \let\if@nobreak\iffalse
%        \let\if@noskipsec\iffalse
```

```
%        \@setnobreak
        \@setminipage
}
```

(*End definition for* `\@marginparreset`.)

`\@xympar`

Setting the box here is done only because the code uses `\end@float`; it will be empty and gets discarded.

```
\def \@xympar{%
  \ifnum\@floatpenalty <\z@\@cons\@currlist\@marbox\fi
  \setbox\@tempboxa
    \color@vbox
      \vbox \bgroup
  \end@float
  \@ignorefalse
  \@esphack
}
```

(*End definition for* `\@xympar`.)

`\reversemarginpar`
`\normalmarginpar`

```
\def\reversemarginpar{\global\@mparbottom\z@ \@reversemargintrue}
\def\normalmarginpar{\global\@mparbottom\z@ \@reversemarginfalse}
```

(*End definition for* `\reversemarginpar` *and* `\normalmarginpar`.)

```
\message{footnotes,}
```

1.2 Footnotes

Historical LaTeX 2.09 comments (not necessarily accurate any more):

`\footnote{NOTE}` : User command to insert a footnote.

`\footnote[NUM]{NOTE}`: User command to insert a footnote numbered NUM, where NUM is a number – 1, 2, etc. For example, if footnotes are numbered *, **, etc. within pages, then `\footnote[2]{...}` produces footnote '**'. This command does not step the footnote counter.

`\footnotemark[NUM]` : Command to produce just the footnote mark in the text, but no footnote. With no argument, it steps the footnote counter before generating the mark.

`\footnotetext[NUM]{TEXT}` : Command to produce the footnote but no mark. `\footnote` is equivalent to `\footnotemark \footnotetext` .

As in PLAIN, footnotes use `\insert\footins,` and the following parameters:

`\footnotesize` : Size-changing command for footnotes.

`\footnotesep` : The height of a strut placed at the beginning of every footnote.

`\skip\footins` : Space between main text and footnotes. The rule separating footnotes from text occurs in this space. This space lies above the strut of height `\footnotesep` which is at the beginning of the first footnote.

`\footnoterule` : Macro to draw the rule separating footnotes from text. It is executed right after a `\vspace` of `\skip\footins`. It should take zero vertical space–i.e., it should to a negative skip to compensate for any positive space it occupies. (See PLAIN.TEX.)

`\interfootnotelinepenalty` : Interline penalty for footnotes.

`\thefootnote` : In usual LaTeX style, produces the footnote number. If footnotes are to be numbered within pages, then the document style file must include an `\@addtoreset` command to cause the footnote counter to be reset when the page counter is stepped. This is not a good idea, though, because the counter will not always be reset in time to ensure that the first footnote on a page is footnote number one.

`\@thefnmark` : Holds the current footnote's mark–e.g., `\dag` or '1' or 'a'.

`\@mpfnnumber` : A macro that generates the numbers for `\footnote` and `\footnotemark` commands. It == `\thefootnote` outside a minipage environment, but can be changed inside to generate numbers for `\footnote`'s.

`\@makefnmark` : A macro to generate the footnote marker from `\@thefnmark` The default definition was `\hbox{$^\@thefnmark$}`.

This is now replaced by `\textsuperscript{\@thefnmark}`

`\@makefntext{NOTE}` :

Must produce the actual footnote, using `\@thefnmark` as the mark of the footnote and NOTE as the text. It is called when effectively inside a `\parbox`, with `\hsize` = `\columnwidth`.

For example, it might be as simple as

`$^{\@thefnmark}$` NOTE

In a minipage environment, \footnote and \footnotetext are redefined so that

(a) they use the counter mpfootnote

(b) the footnotes they produce go at the bottom of the minipage.

The switch is accomplished by letting \@mpfn == footnote or mpfootnote and \thempfn == \thefootnote or \thempfootnote, and by redefining \@footnotetext to be \@mpfootnotetext in the minipage.

```
\footnote{NOTE}  ==
 BEGIN
   \stepcounter{\@mpfn}
   begingroup
       \protect == \noexpand
       \@thefnmark :=G eval (\thempfn)
   endgroup
   \@footnotemark
   \@footnotetext{NOTE}
 END

\footnote[NUM]{NOTE} ==
 BEGIN
   begingroup
       \protect == \noexpand
       counter \@mpfn :=L NUM
       \@thefnmark :=G eval (\thempfn)
   endgroup
   \@footnotemark
   \@footnotetext{NOTE}
 END

\footnotemark      ==
 BEGIN \stepcounter{footnote}
        begingroup
            \protect == \noexpand
            \@thefnmark :=G eval(\thefootnote)
        endgroup
        \@footnotemark
 END

\footnotemark[NUM] ==
  BEGIN
       begingroup
         footnote counter :=L NUM
         \protect == \noexpand
        \@thefnmark :=G eval(\thefootnote)
       endgroup
       \@footnotemark
  END
```

```
\@footnotemark ==
  BEGIN
   \leavevmode
   IF hmode THEN \@x@sf := \the\spacefactor FI
   \@makefnmark          % put number in main text
   IF hmode THEN \spacefactor := \@x@sf FI
  END

\footnotetext      ==
   BEGIN begingroup \protect == \noexpand
                    \@thefnmark :=G eval (\thempfn)
         endgroup
         \@footnotetext
   END

\footnotetext[NUM] ==
   BEGIN begingroup  counter \@mpfn :=L NUM
                     \protect == \noexpand
                     \@thefnmark :=G eval (\thempfn)
         endgroup
         \@footnotetext
   END
```

End of historical LaTeX 2.09 comments.

`\footins` LaTeX does use the same insert for footnotes as PLAIN.

```
\newinsert\footins
```

LaTeX leaves these initializations for the `\footins` insert.

```
\skip\footins=\bigskipamount % space added when footnote is present
\count\footins=1000 % footnote magnification factor (1 to 1)
\dimen\footins=8in % maximum footnotes per page
```

(*End definition for* `\footins`.)

`\footnoterule` LaTeX keeps PLAIN TeX's `\footnoterule` as the default.

```
\def\footnoterule{\kern-3\p@
  \hrule \@width 2in \kern 2.6\p@} % the \hrule is .4pt high
```

(*End definition for* `\footnoterule`.)

`\thefootnote`

```
\@definecounter{footnote}
\def\thefootnote{\@arabic\c@footnote}
```

(*End definition for* `\thefootnote`.)

`\thempfootnote` The default display for the footnote counter in minipages is to use italic letters. We use `\itshape` not `\textit` as the latter would add an italic correction.

```
\@definecounter{mpfootnote}
\def\thempfootnote{{\itshape\@alph\c@mpfootnote}}
```

(*End definition for* `\thempfootnote`.)

`\@makefnmark` Default definition.

```
%\def\@makefnmark{\hbox{$^{\@thefnmark}\m@th$}}
\def\@makefnmark{\hbox{\@textsuperscript{\normalfont\@thefnmark}}}
```

(*End definition for* `\@makefnmark`.)

`\textsuperscript` This command provides superscript characters in the current text font. It's implementation might change!!!

```
\DeclareRobustCommand*\textsuperscript[1]{%
  \@textsuperscript{\selectfont#1}}
```

(*End definition for* `\textsuperscript`.)

`\@textsuperscript` This command should not be used directly, but may be used to define other commands `\textsuperscript`, `\@makefnmark`. `#1` should always start with a font selection command, to activate the font size switch.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@textsuperscript}{superscript baseline}%
\def\@textsuperscript#1{%
  {\m@th\ensuremath{^{\mbox{\fontsize\sf@size\sf@size#1}}}}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@textsuperscript}{superscript baseline}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@textsuperscript#1{%
⟨latexrelease⟩  {\m@th\ensuremath{^{\mbox{\fontsize\sf@size\z@#1}}}}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@textsuperscript`.)

`\textsubscript`

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\textsubscript}{\textsubscript}%
⟨*2ekernel | latexrelease⟩
\DeclareRobustCommand*\textsubscript[1]{%
  \@textsubscript{\selectfont#1}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\textsubscript}{\textsubscript}%
⟨latexrelease⟩\let\textsubscript\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\textsubscript`.)

\@textsubscript

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\@textsubscript}{subscript baseline}%
\def\@textsubscript#1{%
  {\m@th\ensuremath{_{\mbox{\fontsize\sf@size\sf@size#1}}}}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\@textsubscript}{subscript baseline}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@textsubscript#1{%
⟨latexrelease⟩  {\m@th\ensuremath{_{\mbox{\fontsize\sf@size\z@#1}}}}}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@textsubscript}{subscript baseline}%
⟨latexrelease⟩\let\@textsubscript\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \@textsubscript.)

\footnotesep

```
\newdimen\footnotesep
```

(*End definition for* \footnotesep.)

\footnote

```
\def\footnote{\@ifnextchar[\@xfootnote{\stepcounter\@mpfn
      \protected@xdef\@thefnmark{\thempfn}%
      \@footnotemark\@footnotetext}}
```

(*End definition for* \footnote.)

\@xfootnote

```
\def\@xfootnote[#1]{%
   \begingroup
     \csname c@\@mpfn\endcsname #1\relax
     \unrestored@protected@xdef\@thefnmark{\thempfn}%
   \endgroup
   \@footnotemark\@footnotetext}
```

(*End definition for* \@xfootnote.)

\@footnotetext

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                  {\@footnotetext}{footnotetext tagging}%
\long\def\@footnotetext#1{\insert\footins{%
    \reset@font\footnotesize
    \interlinepenalty\interfootnotelinepenalty
    \splittopskip\footnotesep
```

```
    \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
    \hsize\columnwidth \@parboxrestore
    \def\@currentcounter{footnote}%
    \protected@edef\@currentlabel{%
       \csname p@footnote\endcsname\@thefnmark
    }%
    \color@begingroup
      \@makefntext{%
        \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
    \par
    \color@endgroup}}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                 {\@footnotetext}{footnotetext tagging}%
⟨latexrelease⟩\long\def\@footnotetext#1{\insert\footins{%
⟨latexrelease⟩    \reset@font\footnotesize
⟨latexrelease⟩    \interlinepenalty\interfootnotelinepenalty
⟨latexrelease⟩    \splittopskip\footnotesep
⟨latexrelease⟩    \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
⟨latexrelease⟩    \hsize\columnwidth \@parboxrestore
⟨latexrelease⟩    \protected@edef\@currentlabel{%
⟨latexrelease⟩       \csname p@footnote\endcsname\@thefnmark
⟨latexrelease⟩    }%
⟨latexrelease⟩    \color@begingroup
⟨latexrelease⟩      \@makefntext{%
⟨latexrelease⟩        \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
⟨latexrelease⟩    \par
⟨latexrelease⟩    \color@endgroup}}%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@footnotetext}{footnotetext tagging}%
⟨latexrelease⟩
⟨latexrelease⟩\long\def\@footnotetext#1{\insert\footins{%
⟨latexrelease⟩    \reset@font\footnotesize
⟨latexrelease⟩    \interlinepenalty\interfootnotelinepenalty
⟨latexrelease⟩    \splittopskip\footnotesep
⟨latexrelease⟩    \splitmaxdepth \dp\strutbox \floatingpenalty \@MM
⟨latexrelease⟩    \hsize\columnwidth \@parboxrestore
⟨latexrelease⟩    \protected@edef\@currentlabel{%
⟨latexrelease⟩       \csname p@footnote\endcsname\@thefnmark
⟨latexrelease⟩    }%
⟨latexrelease⟩    \color@begingroup
⟨latexrelease⟩      \@makefntext{%
⟨latexrelease⟩        \rule\z@\footnotesep\ignorespaces#1\@finalstrut\strutbox}%
⟨latexrelease⟩    \color@endgroup}}%
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@footnotetext`.)

`\footnotemark`

```
\def\footnotemark{%
   \@ifnextchar[\@xfootnotemark
     {\stepcounter{footnote}%
      \protected@xdef\@thefnmark{\thefootnote}%
      \@footnotemark}}
```

(*End definition for* `\footnotemark`.)

`\@xfootnotemark`

```
\def\@xfootnotemark[#1]{%
   \begingroup
      \c@footnote #1\relax
      \unrestored@protected@xdef\@thefnmark{\thefootnote}%
   \endgroup
   \@footnotemark}
```

(*End definition for* `\@xfootnotemark`.)

`\@footnotemark`

```
\def\@footnotemark{%
  \leavevmode
  \ifhmode\edef\@x@sf{\the\spacefactor}\nobreak\fi
  \@makefnmark
  \ifhmode\spacefactor\@x@sf\fi
  \relax}
```

(*End definition for* `\@footnotemark`.)

`\footnotetext`

```
\def\footnotetext{%
     \@ifnextchar [\@xfootnotenext
       {\protected@xdef\@thefnmark{\thempfn}%
    \@footnotetext}}
```

(*End definition for* `\footnotetext`.)

`\@xfootnotenext`

```
\def\@xfootnotenext[#1]{%
  \begingroup
     \csname c@\@mpfn\endcsname #1\relax
     \unrestored@protected@xdef\@thefnmark{\thempfn}%
  \endgroup
  \@footnotetext}
```

(*End definition for* `\@xfootnotenext`.)

`\thempfn`
`\@mpfn`

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
```

(*End definition for* `\thempfn` *and* `\@mpfn`.)

`\footref` This command generates a footnote mark. The value is produced by referencing a `\label` placed into a `\footnote` elsewhere (can be one in the main galley or in a minipage).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\footref}{Add footref}%
\def\footref#1{%
  \begingroup
    \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
  \endgroup
  \@footnotemark
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

We don't remove it when rolling back so that packages offered it in the past do not need to alter their behavior in a rollback situation.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\footref}{Add footref}%
⟨latexrelease⟩
⟨latexrelease⟩  % \let\footref\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\footref`.)

```
⟨/2ekernel⟩
```

File Q
ltidxglo.dtx

1 Index and Glossary Generation

Index and Glossary commands.

`\makeindex` A preamble command to turn on indexing.

`\makeglossary` A preamble command to turn on making glossary entries.

`\index` Make an index entry for `#1`.

`\glossary` Make a glossary entry for `#1`.

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
\makeindex ==
  BEGIN
            \index ==  BEGIN \@bsphack
                             \begingroup
                                \protect{X} == \string X\space
                                 %% added 3 Feb 87 for \index commands
                                 %% in \footnotes
                                 re-\catcode special characters
                                 to 'other'
                                 \@wrindex
  END

\@wrindex{ITEM} ==
  BEGIN
      write of {\indexentry{ITEM}{page number}}
    \endgroup
    \@esphack
  END

INITIALIZATION:

\index == BEGIN \@bsphack
                \begingroup
                   re-\catcode special characters (in case '%' there)
                   \@index
          END

\@index{ITEM} == BEGIN \endgroup \@esphack END
```

Changes made 14 Apr 89 to write `\glossaryentry`'s instead of `\indexentry`'s on the .glo file.

End of historical LaTeX 2.09 comments.

```
⟨*2ekernel⟩
\message{index,}
```

\makeindex

```
\def\makeindex{%
  \newwrite\@indexfile
  \immediate\openout\@indexfile=\jobname.idx
  \def\index{\@bsphack\begingroup
             \@sanitize
             \@wrindex}\typeout
    {Writing index file \jobname.idx}%
```

Opening the write channel should be done only once since on some OS multiple opens are forbidden and in any case it is useless. So we turn this into a no-op after use.

```
  \let\makeindex\@empty
}
\@onlypreamble\makeindex
```

(*End definition for* `\makeindex`.)

\@wrindex

```
\def\@wrindex#1{%
   \protected@write\@indexfile{}%
      {\string\indexentry{#1}{\thepage}}%
 \endgroup
 \@esphack}
```

(*End definition for* `\@wrindex`.)

\index

```
\def\index{\@bsphack\begingroup \@sanitize\@index}
```

(*End definition for* `\index`.)

\@index

```
\def\@index#1{\endgroup\@esphack}
```

(*End definition for* `\@index`.)

\makeglossary

```
\def\makeglossary{%
  \newwrite\@glossaryfile
  \immediate\openout\@glossaryfile=\jobname.glo
  \def\glossary{\@bsphack\begingroup
                \@sanitize
                \@wrglossary}\typeout
    {Writing glossary file \jobname.glo }%
```

Opening the write channel should be done only once since on some OS multiple opens are forbidden and in any case it is useless. So we turn this into a no-op after use.

```
  \let\makeglossary\@empty
}
\@onlypreamble\makeglossary
```

(*End definition for* `\makeglossary`.)

\@wrglossary

```
\def\@wrglossary#1{%
   \protected@write\@glossaryfile{}%
      {\string\glossaryentry{#1}{\thepage}}%
 \endgroup
 \@esphack}
```

(*End definition for* `\@wrglossary`.)

\glossary

```
\def\glossary{\@bsphack\begingroup\@sanitize\@index}
```

(*End definition for* `\glossary`.)

⟨/2ekernel⟩

File R
ltbibl.dtx

1 Bibliography Generation

A bibliography is created by the `thebibliography` environment, which generates a title such as "References", and a list of entries. The BIBTEX program will create a file containing such an environment, which will be read in by the `\bibliography` command. With BIBTEX, the following commands will be used.

`\bibliography` `\bibliography{`⟨*file1,file2, ...,filen*⟩`}` : specifies the bibdata files. Writes a `\bibdata` entry on the `.aux` file and tries to read in `mainfile.bbl`.

`\bibliographystyle` `\bibliographystyle{`⟨*style*⟩`}` : Writes a `\bibstyle` entry on the `.aux` file.

`thebibliography` (*env.*) The `thebibliography` environment is a list environment. To save the use of an extra counter, it should use `enumiv` as the item counter. Instead of using `\item`, items in the bibliography are produced by the following commands:

`\bibitem{`⟨*name*⟩`}` : Produces a numbered entry cited as ⟨*name*⟩.

`\bibitem[`⟨*label*⟩`]{`⟨*name*⟩`}` : Produces an entry labeled by ⟨*Label*⟩ and cited by ⟨*name*⟩.

The former is used for bibliographies with citations like [1], [2], etc.; the latter is used for citations like [Knuth82].

The document class must define the thebibliography environment. This environment has a single argument, which is the widest bibliography label– e.g., if the [Knuth67] is the widest entry, then this argument will be Knuth67. The `\thebibliography` command must begin a list environment, which the `\endthebibliography` command ends.

`\cite` Entries are cited by the command `\cite{`⟨*name*⟩`}`.

`\nocite` `\nocite{`⟨*citations*⟩`}` puts information on the `.aux` file that causes BIBTEX to include the `{`⟨*citations*⟩`}` list in the bibliography, but puts nothing in the text.

`\nocite{*}` is special: it tells BIBTEX to put the whole of a collection of references into the bibliography.

```
⟨*2ekernel⟩
\message{bibliography,}
```

Historical LATEX 2.09 comments (not necessarily accurate any more):

PARAMETERS

```
\@cite    : A macro such that \@cite{LABEL1,LABEL2}{NOTE}
            produces the output for a \cite[NOTE]{FOO1,FOO2} command,
            where entry FOOi is defined by \bibitem[LABELi]{FOOi}.
            The switch @tempswa is true if the optional NOTE argument
            is present.
            The default definition is :
              \@cite{LABELS}{NOTE} ==
                 BEGIN [LABELS
                        IF @tempswa = T THEN , NOTE FI
                        ]
                 END

\@biblabel : A macro to produce the label in the bibliography
             entry.  For \bibitem[LABEL]{NAME}, the label is
```

generated by \@biblabel{LABEL}. It has the default definition \@biblabel{LABEL} -> [LABEL].

CONVENTION

\b@FOO : The name or number of the reference created by \cite{FOO} E.g., if \cite{FOO} -> [17] , then \b@FOO -> 17.

End of historical LaTeX 2.09 comments.

\bibitem

```
\def\bibitem{\@ifnextchar[\@lbibitem\@bibitem}
```

(*End definition for* \bibitem.)

\@lbibitem

```
\def\@lbibitem[#1]#2{\item[\@biblabel{#1}\hfill]\if@filesw
      {\let\protect\noexpand
       \immediate
       \write\@auxout{\string\bibcite{#2}{#1}}}\fi\ignorespaces}
```

(*End definition for* \@lbibitem.)

\@bibitem

```
\def\@bibitem#1{\item\if@filesw \immediate\write\@auxout
       {\string\bibcite{#1}{\the\value{\@listctr}}}\fi\ignorespaces}
```

(*End definition for* \@bibitem.)

\bibcite

```
\def\bibcite{\@newl@bel b}
```

(*End definition for* \bibcite.)

\citation

```
\let\citation\@gobble
```

(*End definition for* \citation.)

\cite

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                  {\cite}{check for blank}%
\DeclareRobustCommand\cite{%
  \@ifnextchar [{\@tempswatrue\@citex@checkblank}{\@tempswafalse\@citex@checkblank[]}}
```

Due to the way \@for as used in \@citex behaves an empty argument to \cite did not produce any warning for a missing citation. So we now inject a command before calling \@citex that does the checking for us. It is not done in \@citex directly, because that command is altered by a number of packages/classes and this way it is more likely that the check survives.

```
\def\@citex@checkblank[#1]#2{%
   \IfBlankTF {#2}%
     {\@citex[#1]{\space}}%
     {\@citex[#1]{#2}}%
}
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\cite}{check for blank}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\cite{%
⟨latexrelease⟩  \@ifnextchar [{\@tempswatrue\@citex}{\@tempswafalse\@citex[]}}
⟨latexrelease⟩\let\@citex@checkblank\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\cite`.)

`\@citex` `\penalty\@m` added to definition of `\@citex` to allow a line break after the ',' in citations like [Jones80,Smith77] (Added 23 Oct 86)

space added after the ',' (21 Nov 87)

```
\def\@citex[#1]#2{\leavevmode
  \let\@citea\@empty
  \@cite{\@for\@citeb:=#2\do
    {\@citea\def\@citea{,\penalty\@m\ }%
     \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
     \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi
```

Using `\hbox` instead of `\mbox` is fine because of the `\leavevmode` above. In fact the use of a box around the citation contents is more than questionable in my view (FMi), but within 2e I have to keep that for compatibility reasons as it would probably change too many existing documents. Its main reason is to avoid hyphenation of labels such as [FOOB89] into [FOO- B89] so in certain styles it makes sense; but, for example, in author year citations it becomes more than questionable.

So Chris added yet another hook here, as suggested by, at least, Donald Arseneau. Note that this one is inside the first argument of the `\@cite` hook. This decouples the top-level typesetting of the citation from the details of the other business conducted here. All this really needs a complete rethink to get the right modularity.

```
      \@ifundefined{b@\@citeb}{\hbox{\reset@font\bfseries ?}%
        \G@refundefinedtrue
        \@latex@warning
          {Citation '\@citeb' on page \thepage \space undefined}}%
        {\@cite@ofmt{\csname b@\@citeb\endcsname}}}}{#1}}
```

(*End definition for* `\@citex`.)

`\bibdata`
`\bibstyle`

```
\let\bibdata=\@gobble
\let\bibstyle=\@gobble
```

(*End definition for* `\bibdata` *and* `\bibstyle`.)

`\bibliography`

```
\def\bibliography#1{%
  \if@filesw
    \immediate\write\@auxout{\string\bibdata{\zap@space#1 \@empty}}%
  \fi
  \@input@{\jobname.bbl}}
```

(*End definition for* `\bibliography`.)

`\bibliographystyle`

```
\def\bibliographystyle#1{%
  \ifx\@begindocumenthook\@undefined\else
    \expandafter\AtBeginDocument
  \fi
    {\if@filesw
       \immediate\write\@auxout{\string\bibstyle{#1}}%
     \fi}}
```

(*End definition for* `\bibliographystyle`.)

`\nocite` (Added 14 Jun 85)

This puts information on the `.aux` file that causes BibTeX to include the citation list in the bibliography, but puts nothing in the text.

RmS 93/08/06: Made loop for `\nocite` like that for `\@citex`, to get rid of leading spaces.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\nocite}{Allow nocite in preamble}%
\def\nocite#1{\@bsphack
```

With the implementation designed already in LaTeX 2.09 the `\nocite` command will not work before `\begin{document}` since it tries to write to the `.aux` file which is not open before that point. As a result the "reference" will appear on the terminal and nothing else will happen.

[This would be easy to fix, but then a document using the fix will silently fail on an older release of LaTeX, missing all citations done with `\nocite`. Thus we do only generate an error message and leave the fix for a LaTeX 2_ε successor.]

Given that we are now a quarter century into using LaTeX 2_ε there is no good reason any more do limit ourself to 2.09 conciderations. So we now simply delay the `\nocide` if it is issued in the preamble.

```
  \ifx\@onlypreamble\document
```

Since we are after `\begin{document}` we can do the citations:

```
    \@for\@citeb:=#1\do{%
      \edef\@citeb{\expandafter\@firstofone\@citeb}%
      \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi
      \@ifundefined{b@\@citeb}{\G@refundefinedtrue
          \@latex@warning{Citation ‘\@citeb’ undefined}}{}}%
  \else
```

But before `\begin{document}` we raised an error message in the past but as of 2021/05 not any longer.

```
%    \@latex@error{Cannot be used in preamble}\@eha
```

Instead we delay the declaration to the start of the document. We have to use a late hook for this, so that it comes after the `.aux` file is open for writing and after `\@preamblecmds` was executed to change the above test. Therefore `\AtBeginDocument` would still be too early.

```
    \AddToHook{begindocument/end}[kernel]{\nocite{#1}}%
  \fi
```

```
  \@esphack}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\nocite}{Allow nocite in preamble}%
⟨latexrelease⟩
⟨latexrelease⟩\def\nocite#1{\@bsphack
⟨latexrelease⟩  \ifx\@onlypreamble\document
⟨latexrelease⟩    \@for\@citeb:=#1\do{%
⟨latexrelease⟩      \edef\@citeb{\expandafter\@firstofone\@citeb}%
⟨latexrelease⟩      \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi
⟨latexrelease⟩      \@ifundefined{b@\@citeb}{\G@refundefinedtrue
⟨latexrelease⟩          \@latex@warning{Citation ‘\@citeb’ undefined}}{}}%
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@latex@error{Cannot be used in preamble}\@eha
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@esphack}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

Since `\nocite{*}` should not produce a warning about undefined citation keys (see PR 557), we need to set the control sequence ‘`\b@*`’ to something other than `\relax`. As a result `\cite{*}` will not warn either (but that never worked with BibTeX in the first place).

```
\expandafter\let\csname b@*\endcsname\@empty
```

(*End definition for* `\nocite`.)

1.1 Default definitions

This hook determines the ‘relative formatting’ of the two logical parts of a citation with comment.

`\@cite`

```
\def\@cite#1#2{[{#1\if@tempswa , #2\fi}]}
```

(*End definition for* `\@cite`.)

`\@cite@ofmt` This is, in general, a command that appears to have one argument whose value is, in the kernel, a single cs whose name is the expansion of `b@\@citeb`; the expansion of this cs will typically be some hmode material that produces the detailed typeset form of just the citations themselves.

```
\let\@cite@ofmt\hbox
```

(*End definition for* `\@cite@ofmt`.)

`\@biblabel`

```
\def\@biblabel#1{[#1]}
⟨/2ekernel⟩
```

(*End definition for* `\@biblabel`.)

File S
ltmarks.dtx

Abstract

Marks are used to communicate information about the content of a page to the output routine. For example, in order to construct running headers, the output routine needs information about which section names are present on a page, and this information is passed to it through the mark system. However, marks may also be used for other purposes. This module provides a generalized mechanism for marks of independent classes.

1 Introduction

The TEX engines offer a low-level mark mechanism to communicate information about the content of the current page to the asynchronous operating output routine. It works by placing `\mark` commands into the source document. When the material for the current page is assembled in box 255, TEX scans for such marks and sets the commands `\topmark`, `\firstmark` and `\botmark`. The `\firstmark` receives the content of the first `\mark` seen in box 255 and `\botmark` the content of the last mark seen. The `\topmark` holds the content of the last mark seen on the previous page or more exactly the value of `\botmark` from the previous page. If there are no marks on the current page then all three are made equal to the `\botmark` from the previous page.

This mechanism works well for simple formats (such as plain TEX) whose output routines are only called to generate pages. It fails, however, in LATEX (and other more complex formats), because here the output routine is sometimes called without producing a page, e.g., when encountering a float and placing it into one of the float regions. In that case the output routine is called, determines where to place the float, alters the goal for assembling text material (if the float was added to the top or bottom region) and then it resumes collecting textual material.

As a result the `\botmark` gets updated and so `\topmark` no longer reflects the situation at the top of the next page when that page is finally boxed.

Another problem for LATEX was that it wanted to use several "independent" marks and in the early implementations of TEX there was only a single `\mark` command available. For that reason LATEX implemented its own mark mechanism where the marks always contained two parts with their own interfaces: `\markboth` and `\markright` to set marks and `\leftmark` and `\rightmark` to retrieve them.

However, this extended mechanism (while supporting scenarios such as chapter/section marks) was far from general. The mark situation at the top of a page (i.e., `\topmark`) remained unusable and the two marks offered were not really independent of each other because `\markboth` (as the name indicates) was always setting both.

The new mechanism overcomes both issues:

- It provides arbitrarily many, fully independent named marks, that can be allocated and, from that point onwards, used.
- It offers access for each such marks to retrieve its top, first, and bottom values separately.
- Furthermore, the mechanism is augmented to give access to marks in different "regions" which may not be just full pages.

2 Design-level and code-level interfaces

The interfaces are mainly meant for package developers, but they are usable (with appropriate care) also in the document preamble, for example, when setting up special running headers with fancyhdr, etc. They are therefore available both as CamelCase commands as well as commands for use in the L3 programming layer. Both are described together below.

`\NewMarkClass` `\NewMarkClass {⟨class⟩}`
`\mark_new_class:n` `\mark_new_class:n {⟨class⟩}`

Declares a new ⟨*class*⟩ of marks to be tracked by LaTeX. Each ⟨*class*⟩ must be declared before it is used.

Mark classes can only be declared before `\begin{document}`.

`\InsertMark` `\InsertMark {⟨class⟩} {⟨text⟩}`
`\mark_insert:nn` `\mark_insert:nn {⟨class⟩} {⟨text⟩}`

Adds a mark to the current galley for the ⟨*class*⟩, containing the ⟨*text*⟩.

It has no effect in places in which you can't place floats, e.g., a mark inside a box or inside a footnote never shows up anywhere.

If used in vertical mode it obeys LaTeX's internal `\@nobreak` switch, i.e., it does not introduce a breakpoint if used after a heading. If used in horizontal mode it doesn't handle spacing (like, for example, `\index` or `\label` does, so it should be attached to material that is typeset.

`insertmark` `\AddToHook {insertmark} {⟨code⟩}`

When marks are inserted, the mark content may need some special treatment, e.g., by default `\label`, `\index`, and `\glossary` do not expand at this time (but only later if and when the mark content is actually used. In order to allow packages to augment or alter this setup there is a public hook `insertmark` that is executed at this point. It runs in a group so local modification to commands are only applied to the ⟨*text*⟩ argument of `\InsertMark` or `\mark_insert:nn`.

\TopMark ⋆	\TopMark [⟨*region*⟩] {⟨*class*⟩}
\FirstMark ⋆	\FirstMark [⟨*region*⟩] {⟨*class*⟩}
\LastMark ⋆	\LastMark [⟨*region*⟩] {⟨*class*⟩}
\mark_use_top:nn ⋆	\mark_use_top:nn {⟨*region*⟩} {⟨*class*⟩}
\mark_use_first:nn ⋆	\mark_use_first:nn {⟨*region*⟩} {⟨*class*⟩}
\mark_use_last:nn ⋆	\mark_use_last:nn {⟨*region*⟩} {⟨*class*⟩}

These functions expand to the appropriate mark ⟨*text*⟩ for the given ⟨*class*⟩ in the specified ⟨*region*⟩. The default ⟨*region*⟩ in the design-level commands is `page`. Note that with the L3 layer commands there are no optional arguments, i.e., both arguments have to be provided.

TEXhackers note: The result is returned within the `\unexpanded` primitive (`\exp_not:n`), which means that the ⟨*text*⟩ does not expand further when appearing in an `x`-type or `e`-type argument expansion.

The "first" and "last" marks are those seen first and last in the current region/page, respectively. The "top" mark is the last mark of the ⟨*class*⟩ seen in an earlier region, i.e., the ⟨*text*⟩ what would be "current" at the very top of the region.

Important! The commands are only meaningful inside the output routine, in other places their result is (while not random) unpredictable due to the way LATEX cuts text material into pages.

Currently, ⟨*region*⟩ is one of `page`, `previous-page`, `column`, and `previous-column`. If a page has just been finished then the region `page` refers to the current page and `previous-page`, as the name indicates, to the page that has been finished previously. This means you are able to access mark information for the current page as well as for the page before if you are inside the output routine, without the need to explicitly save that information beforehand.

In single column documents the `column` is the same as the `page` region, but in two-column documents, `column` refers to the current column that just got finished and previous-column to the one previously finished. Code for running headers are (in standard LATEX) only evaluated when both columns are assembled, which is another way of saying that in that case `previous-column` refers to the left column and `column` to the right column. However, to make this a bit nicer to access, there are also alias regions named `first-column` and `last-column`[32] to access these regions.[33]

Note that you can only look backwards at already processed regions, e.g., in a `twoside` document finishing a recto (odd, right-hand) page you can access the data from the facing verso (left-hand) page, but if you are finishing a left-hand page you can't integrate data from the upcoming right-hand page. If such a scenario needs to be realized then it is necessary to save the left-hand page temporarily instead of finalizing it, process material for the right-hand page and once both are ready, attach running headers and footers and shipout out both in one go.[34]

[32] This is called "last" not "second" in anticipation of extending the mechanism to multiple columns, where first and last would still make sense.

[33] At the moment there aren't any `previous-...-column` regions to access the columns from the previous page. If necessary, the mechanism could be easily augmented to cover them too, though.

[34] As of now that scenario is not yet officially supported.

\IfMarksEqualTF ⋆	\IfMarksEqualTF [⟨*region*⟩] {⟨*class*⟩} {⟨*pos*$_1$⟩} {⟨*pos*$_2$⟩} {⟨*true*⟩} {⟨*false*⟩}
\mark_if_eq:nnnnTF ⋆	\mark_if_eq:nnnnTF {⟨*region*⟩} {⟨*class*⟩} {⟨*pos*$_1$⟩} {⟨*pos*$_2$⟩} {⟨*true*⟩} {⟨*false*⟩}
\mark_if_eq:nnnnnnTF ⋆	\mark_if_eq:nnnnnnTF {⟨*region*$_1$⟩} {⟨*class*$_1$⟩} {⟨*pos*$_1$⟩} {⟨*region*$_2$⟩} {⟨*class*$_2$⟩} {⟨*pos*$_2$⟩} {⟨*true*⟩} {⟨*false*⟩}

These conditionals allow you to compare the content of two marks and act based on the result. The commands work in an expansion context, if necessary.

It is quite common when programming with marks to need to interrogate conditions such as whether marks have appeared on a previous page, or if there are multiple marks present on the current page, and so on. The tests above allow for the construction of a variety of typical test scenarios, with three examples presented below.

The first two conditionals cover only the common scenarios. Both marks are picked up from the same ⟨*region*⟩ (by default `page`) and they have to be of the same ⟨*class*⟩.[35] The ⟨*pos*$_i$⟩ argument can be either `top`, `first`, or `last`.

If you wish to compare marks across different regions or across different classes, you have to do it using the generic test only available in the L3 programming layer or do it manually, i.e., get the marks and then compare the values yourself.[36]

However, the basic version is enough for the following typical use cases:

Test for at most one mark of class `myclass` on current page: If the first and last mark in a region are the same then either there was no mark at all, or there was at most one. To test this on the current page:

```
\NewMarkClass{myclass}
\IfMarksEqualTF{myclass}{first}{last}
                { <zero or one mark> }{ <two or more marks> }
```

Test for no mark of class `myclass` in the previous page: If the top mark is the same as the first mark, there is no mark in the region at all. If we wanted to do this test for the previous page:

```
\IfMarksEqualTF[previous-page]{myclass}{top}{first}
                { <no marks> }{ <at least one mark> }
```

Comparing `top` and `last` would give you the same result.

Test for zero, one, or more than one: Combining the two tests from above you can test for zero, one or more than one mark.

```
\IfMarksEqualTF{myclass}{top}{first}
                { <no marks> }
                {\IfMarksEqualTF{myclass}{first}{last}
                  { <exactly one mark> }{ <more than one mark> }}
```

If you need one of such tests more often (or if you want a separate command for it for readability), then consider defining:

```
\providecommand\IfNoMarkTF[2][page]{\IfMarksEqualTF[#1]{#2}{first}{last}}
```

[35] If an undeclared mark class is used the tests return *true* (not an error).

[36] If two undeclared mark classes are compared the result is always *true*; if a declared and an undeclared mark class is used it is always *false*.

2.1 Debugging mark code

\DebugMarksOn
\DebugMarksOff
\mark_debug_on:
\mark_debug_off:

`\DebugMarksOn ...  \DebugMarksOff`

Commands to turn the debugging of mark code on or off. The debugging output is rather coarse and not really intended for normal use at this point in time.

3 Application examples

If you want to figure out if a break was taken at a specific point, e.g., whether a heading appears at the top of the page, you can do something like this:

```
\newcounter{breakcounter}
\NewMarkClass{break}
\newcommand\markedbreak[1]{\stepcounter{breakcounter}%
                           \InsertMark{break}{\arabic{breakcounter}%
                           \penalty #1\relax
                           \InsertMark{break}{-\arabic{breakcounter}}
```

To test if the break was taken you can test if `\TopMark{break}` is positive (taken) or negative (not taken) or zero (there was never any marked break so far). The absolute value can be used to keep track of which break it was (with some further coding).

to be extended with additional application examples

4 Legacy LaTeX 2_ε interface

Here we describe the interfaces that LaTeX 2_ε offered since the early nineties and some minor extensions.

4.1 Legacy design-level and document-level interfaces

\markboth
\markright

`\markboth {⟨left⟩} {⟨right⟩}`
`\markright {⟨right⟩}`

LaTeX 2_ε uses two marks which aren't fully independent. A "left" mark generated by the first argument of `\markboth` and a "right" mark generated by the second argument of `\markboth` or by the only argument of `\markright`. The command `\markboth` and `\markright` are in turn called from heading commands such as `\chaptermark` or `\sectionmark` and their behavior is controlled by the document class.

For example, in the article class with `twoside` in force the `\sectionmark` will issue `\markboth` with an empty second argument and `\subsectionmark` will issue `\markright`. As a result the left mark will contain chapter titles and the right mark subsection titles.

Note, however, that in one-sided documents the standard behavior is that only `\markright` is used, i.e., there will only be right-marks but no left marks!

\leftmark ⋆ \leftmark
\rightmark ⋆ \rightmark

These functions return the appropriate mark value from the current page and work as before, that is \leftmark will get the last (!) left mark from the page and \rightmark the first (!) right mark.

In other words they work reasonably well if you want to show the section title that is current when you are about to turn the page and also show the first subsection title on the current page (or the last from the previous page if there wasn't one). Other combinations can't be shown using this interface.

The commands are fully expandable, because this is how they have been always defined in LaTeX. However, this is of course only true if the content of the mark they return is itself expandable and does not contain any fragile material. Given that this can't be guaranteed for arbitrary content, a programmer using them in this way should use \protected@edef and *not* \edef to avoid bad surprises as far as this is possible, or use the new interfaces (\TopMark, \FirstMark, and \LastMark) which return the ⟨*text*⟩ in \exp_not:n to prevent uncontrolled expansion.

4.2 Legacy interface extensions

The new implementation adds three mark classes: 2e-left, 2e-right and 2e-right-nonempty and patches \markboth and \markright slightly so that they also update these new mark classes, so that the new classes work with existing document classes.

As a result you can use \LastMark{2e-left} and \FirstMark{2e-right} instead of \leftmark and \rightmark. But more importantly, you can use any of the other retrieval commands to get a different status value from those marks, e.g., \LastMark{2e-right} would return the last subsection on the page (instead of the first as returned by \rightmark).

The difference between 2e-right and 2e-right-nonempty is that the latter will only be updated if the material for the mark is not empty. Thus \markboth{title}{} as issued by, say, \sectionmark, sets a 2e-left mark with title and a 2e-right mark with the empty string but does not add a 2e-right-nonempty mark.

Thus, if you have a section at the start of a page and you would ask for \FirstMark{2e-right} you would get an empty string even if there are subsections on that page. But 2e-right-nonempty would then give you the first or last subsection on that page. Of course, nothing is simple. If there are no subsections it would tell you the last subsection from an earlier page. We therefore need comparison tools, e.g., if top and first are identical you know that the value is bogus, i.e., a suitable implementation would be

```
\IfMarksEqualTF{2e-right-nonempty}{top}{first}
               { <appropriate action if there was no real mark> }
               {\FirstMark{2e-right-nonempty}}
```

5 Notes on the mechanism

In contrast to vanilla TeX, ε-TeX extends the mark system to allow multiple independent marks. However, it does not solve the \topmark problem which means that LaTeX still needs to manage marks almost independently of TeX. The reason for this is that the more complex output routine used by LaTeX to handle floats (and related structures)

means that `\topmark(s)` remain unreliable. Each time the output routine is fired up, TEX moves `\botmark` to `\topmark`, and while ε-TEX extends this to multiple registers the fundamental concept remains the same. That means that the state of marks needs to be tracked by LATEX itself. An early implementation of this package used TEX's `\botmark` only to ensure the correct interaction with the output routine (this was before the ε-TEX mechanism was even available). However, other than in a prototype implementation for LATEX3, this package was never made public.

The new implementation now uses ε-TEX's marks as they have some advantages, because with them we can leave the mark text within the galley and only extract the marks during the output routine when we are finally shipping out a page or storing away a column for use in the next page. That means we do not have to maintain a global data structure that we have to keep in sync with informational marks in the galley but can rely on everything being in one place and thus manipulations (e.g. reordering of material) will take the marks with them without a need for updating a fragile linkage.

To allow for completely independent marks we use the following procedure:

- For every type of marks we allocate a mark class so that in the output routine TEX can calculate for each class the current top, first, and bottom mark independently. For this we use `\newmarks`, i.e., one marks register per class.
- As already mentioned firing up an output routine without shipping out a page means that TEX's top marks get wrong so it is impossible to rely on TEX's approach directly. What we do instead is to keep track of the real marks (for the last page or more generally last region) in some global variables.
- These variables are updated in the output routine at defined places, i.e., when we do real output processing but not if we use special output routines to do internal housekeeping.
- The trick we use to get correctly updated variables is the following: the material that contains new marks (for example the page to be shipped out) is stored in a box. We then use TEX primitive box splitting functions by splitting off the largest amount possible (which should be the whole box if nothing goes really wrong). While that seems a rather pointless thing to do, it has one important side effect: TEX sets up first and bottom marks for each mark class from the material it has split off. This way we get the first and last marks (if there have been any) from the material in the box.
- The top marks are simply the last marks from the previous page or region. And if there hasn't been a first or bottom mark in the box then the new top mark also becomes new first and last mark for that class.
- That mark data is then stored in global token lists for use during the output routine and legacy commands such as `\leftmark` or new commands such as `\TopMark` simply access the data stored in these token lists.

That's about it in a nutshell. Of course, there are some details to be taken care of—those are discussed in the implementation sections.

6 Internal output routine functions

The functions in this section are tied to the output routine and used in the interface to LaTeX 2ε and perhaps at some later time within a new output routine for LaTeX. They are not meant for general use and are therefore made internal. Internal means that `@@` automatically gets replaced in the code (and in the documentation) so we have to give it a suitable value.

```
⟨@@=mark⟩
```

`\__mark_update_singlecol_structures:` `\__mark_update_singlecol_structures:`

LaTeX 2ε integration function in case we are doing single column layouts. It assumes that the page content is already stored in `\@outputbox` and processes the marks inside that box. It is called as part of `\@opcol`.

`\__mark_update_dblcol_structures:` `\__mark_update_singlecol_structures:`

LaTeX 2ε integration function mark used when we are doing double column documents. It assumes that the page content is already stored in `\@outputbox` and processes the marks inside that box. It then does different post-processing depending on the start of the switch `\if@firstcolumn`. If we are in the second column it also has to update page marks, otherwise it only updates column marks. It too is called as part of `\@opcol`.

`\__mark_update_structure:nn` `\__mark_update_structure:nn {⟨region⟩} {⟨material with marks⟩}`

Helper function that inspects the marks inside the second argument and assigns new mark values based on that to the ⟨*region*⟩ given in the first argument. For this it first copies the mark structure from ⟨*region*⟩ to `previous-`⟨*region*⟩ and then takes all last mark values currently in the region and makes them the new top mark values. Finally it assigns new first and last values for all mark classes based on what was found in the second argument.

As a consequence, the allowed values for ⟨*region*⟩ are `page` and `column` because only they have `previous-...` counterparts.

Another important part to keep in mind is that marks are only recognized if they appear on top-level, e.g., if we want to process material stored in boxes we need to put it unboxed (using `\unvcopy` etc.) into the second argument.

`\__mark_update_structure_alias:nn` `\__mark_update_structure_alias:nn {⟨alias⟩} {⟨source⟩}`

Helper function that copies all mark values in the ⟨*source*⟩ region to ⟨*alias*⟩, i.e., make the structures identical. Used to update the `previous-...` structures inside `\__mark_update_structure:nn` and `first-column` and `last-column` structures inside `\__mark_update_singlecol_structures:` or `\__mark_update_dblcol_structures:`.

`\__mark_update_structure_to_err:n` `\__mark_update_structure_to_err:n {⟨region⟩}`

Helper function that sets all mark values in the ⟨*region*⟩ to an error message. This is currently used for `last-column` at times where using marks from it would be questionable/wrong, i.e., when we have just processed the first column in a two-column document.

7 The Implementation

```
⟨*2ekernel | latexrelease⟩
\ExplSyntaxOn
⟨latexrelease⟩\NewModuleRelease{2022/06/01}{ltmarks}
⟨latexrelease⟩                  {Marks~handling}
```

7.1 Allocating new mark classes

\g__mark_classes_seq

A list holding all the mark classes that have been declared.

```
\seq_new:N \g__mark_classes_seq
```

\mark_new_class:n
__mark_new_class:nn

A mark class is created by initializing a number of data structures. First, we get a register number to refer to the mark class. The new mark class is then added to the \g__mark_classes_seq sequence to be able to easily loop over all classes. Finally a number of top-level global token lists are declared that hold various versions of the mark for access.

```
\cs_new_protected:Npn \mark_new_class:n #1
{
  \seq_if_in:NnTF \g__mark_classes_seq {#1}
      {
        \msg_error:nnn { mark } { class-already-defined }
          {#1}
      }
      { \__mark_new_class:nn {#1} }
}
```

This is only available in the preamble.

```
\@onlypreamble \mark_new_class:n
```

The internal command carries out the necessary allocations.

```
\cs_new_protected:Npn \__mark_new_class:nn #1
{
⟨*trace⟩
  \__mark_debug:n { \iow_term:x { Marks:~new~mark:~#1~\msg_line_context: } }
⟨/trace⟩
```

Use the LaTeX 2_ε interface for now as the L3 programming layer doesn't have one for marks yet.

```
  \exp_args:Nc \newmarks {c__mark_class_ #1 _mark}
```

Remember the new class in the sequence.

```
  \seq_gput_right:Nn \g__mark_classes_seq {#1}
```

We need three token lists for each region, one for top, first, and last.

```
  \tl_new:c   { g__mark_page_top_   #1 _tl }
  \tl_new:c   { g__mark_page_first_ #1 _tl }
  \tl_new:c   { g__mark_page_last_  #1 _tl }
```

For the page region we also keep track of the previous-page.

```
  \tl_new:c   { g__mark_previous-page_top_   #1 _tl }
  \tl_new:c   { g__mark_previous-page_first_ #1 _tl }
  \tl_new:c   { g__mark_previous-page_last_  #1 _tl }
```

Same game for `column` and `previous-column`

```
  \tl_new:c   { g__mark_column_top_   #1 _tl }
  \tl_new:c   { g__mark_column_first_ #1 _tl }
  \tl_new:c   { g__mark_column_last_  #1 _tl }
  \tl_new:c   { g__mark_previous-column_top_   #1 _tl }
  \tl_new:c   { g__mark_previous-column_first_ #1 _tl }
  \tl_new:c   { g__mark_previous-column_last_  #1 _tl }
```

But for columns we also allocate token lists for the alias regions `first-column` and `last-column`.

```
  \tl_new:c   { g__mark_first-column_top_   #1 _tl }
  \tl_new:c   { g__mark_first-column_first_ #1 _tl }
  \tl_new:c   { g__mark_first-column_last_  #1 _tl }
  \tl_new:c   { g__mark_last-column_top_    #1 _tl }
  \tl_new:c   { g__mark_last-column_first_  #1 _tl }
  \tl_new:c   { g__mark_last-column_last_   #1 _tl }
}
```

(*End definition for* `\mark_new_class:n` *and* `\__mark_new_class:nn`*. This function is documented on page* 792.)

7.2 Updating mark structures

`\l__mark_box`
`\g__mark_tmp_tl`
`\g__mark_new_top_tl`

For some operations we need a temporary private box and two private global token lists.

```
\box_new:N \l__mark_box
\tl_new:N  \g__mark_tmp_tl
\tl_new:N  \g__mark_new_top_tl
```

(*End definition for* `\l__mark_box`*,* `\g__mark_tmp_tl`*, and* `\g__mark_new_top_tl`*.*)

`\__mark_update_structure:nn`

This function updates the mark structures. The first argument is the region to update and second argument receives the material that holds the marks. Out of this material we extract the first and last marks for all classes (if there are any) to do the assignments.

```
\cs_new_protected:Npn \__mark_update_structure:nn #1#2
  {
```

First thing we do is copying the current structure to `previous-...`; this leaves the current structure untouched so we can update it class by class (which is necessary).

```
    \__mark_update_structure_alias:nn { previous-#1 } {#1}
```

Getting the first and last marks out of the material in `#2` is done by putting the material in a box and then doing a split operation to the maximum size possible (which hopefully means all of the content).[37] Because this is an action only for the sake of getting at the mark values we don't want any underfull box warnings so we turn those (locally) off.

```
    \group_begin:
      \dim_set_eq:NN \tex_splitmaxdepth:D \c_max_dim
      \int_set_eq:NN \tex_vbadness:D      \c_max_int
      \dim_set_eq:NN \tex_vfuzz:D         \c_max_dim
```

[37] We could verify this, maybe we should.

There is a further complication: if the region contains infinite shrinking glue then a \vsplit operation will balk with a low-level error. Now pages or columns, which are our main concern here, can't have such infinite shrinkage if they are cut straight from the galley, however the use of \enlargethispage actually does add some at the very bottom (and also wraps the whole page into a box by itself, so if we leave it this way then a) we get this error and b) we don't see any marks because they are hidden one level down).

Another possible issue are packages or user code that place stray \vboxes directly into the main galley (an example is marginnote that attaches its marginals in this way). If such boxes end up as the last item on the page we should not unpack them.

We therefore do an \unskip to get rid of that glue if present and also check if we have then a \vbox as the last item and if so unpack that too, but only under certain conditions, see below. All this is temporary, just for getting the marks out, so it doesn't affect the final page production.

In fact, we go one step further and set the box to a large negative height possible and afterwards take a look at the reported badness: if it is zero we know that there has still been infinite shrinkage in the box so that we can't do a \vsplit. If that is the case we generate an error message and bypass extracting the marks. We use only half of \c_max_dim because otherwise TEX will report an overfull vbox despite our setting of \tex_vfuzz:D. This test will not find existing infinite shrinkage in all cases, e.g., if there are several glues that cancel each other, but it is the best we can do.

```
      \vbox_set_to_ht:Nnn \l__mark_box { -.5\c_max_dim }
        {
          #2
          \tex_unskip:D
          \box_set_to_last:N \l__mark_box
```

After having removed the last box from the current list (if there was one) we check if the list is now empty. If not, the the last box is definitely not the one from \enlargethispage and so we can and should leave it alone. Otherwise we check if this last box is a \vbox.

```
          \int_compare:nNnT \tex_lastnodetype:D < 0
            {
              \box_if_vertical:NT \l__mark_box
                {
```

If it is we do a further test and reset the \l__mark_box to check if it contains infinitely shrinkable glue.

```
                  \vbox_set_to_ht:Nnn \l__mark_box { -.5\c_max_dim }
                    {
                      \vbox_unpack:N \l__mark_box
                      \tex_kern:D \c_zero_dim % ensure that box
                                              % is not empty
                    }
```

If not, then we unpack it, if yes we still ignore it for the process of mark extraction. We do not generate an error though, because in all likelihood this is an ordinary box like a marginal that does contain something like \vss.

```
                    \int_compare:nNnT \tex_badness:D > 0
                      { \vbox_unpack:N \l__mark_box }
                  }
            }
```

If it wasn't a vbox, it was either an hbox or there was no box. Given that we are only interested in the marks we don't need put it back in that case. However, we have to

make sure that the outer box under construction is not totally empty (which it might have been from the start, or now), because TEX does not report a badness for empty boxes and that means our test would incorrectly conclude that we have infinite shrinking glue. A simple `\kern` is enough to avoid this (the same was already done above).

```
          \tex_kern:D \c_zero_dim
        }
      \int_compare:nNnTF \tex_badness:D > 0
```

If the box had no infinite shrinkage (or rather if our test didn't show any) we vsplit it. Note that it doesn't matter that we set it to this strange size first. If there was infinite shrinkage after all, we end up with a low-level TEX error, but if there is, it is a coding error and needs correcting.

```
        {
          \vbox_set_split_to_ht:NNn \l__mark_box \l__mark_box \c_max_dim
```

After this action we can get first and last marks of the various classes through `\tex_splitfirstmarks:D` and `\tex_splitbotmarks:D`. So now we loop over all classes stored in `\g__mark_classes_seq`.

```
          \seq_map_inline:Nn \g__mark_classes_seq
            {
```

First action: get the last mark from the previous region, i.e., `previous-#1`. But because it is also still inside `#1`, at the moment we use that to construct the name because this is a tiny bit faster. Given that we need this value in various assignments we store it away which avoids unnecessary further csname generations.

```
              \tl_gset_eq:Nc \g__mark_new_top_tl { g__mark_#1_last_##1_tl }
```

This will first of all become the new top mark for the current class.

```
              \tl_gset_eq:cN { g__mark_#1_top_##1_tl } \g__mark_new_top_tl
```

Next action is to get ourselves the new last mark from the material supplied.

```
              \tl_gset:No \g__mark_tmp_tl
                { \tex_splitbotmarks:D \use:c { c__mark_class_##1_mark } }
```

If this mark doesn't exist then obviously first mark does neither, so both become the last mark from the previous region. We have to be a little careful here: something like `\mark_insert:nn{foo}{}` adds an "empty" mark that should not be confused with no mark at all. But no mark in our material will result in `\g__mark_tmp_tl` being fully empty. This is why we have to make sure that "empty" from `\mark_insert:nn` only appears to be empty but fails the next test (see below how this is done).

```
              \tl_if_empty:NTF \g__mark_tmp_tl
                {
                  \tl_gset_eq:cN { g__mark_#1_last_ ##1_tl }
                    \g__mark_new_top_tl
                  \tl_gset_eq:cN { g__mark_#1_first_##1_tl }
                    \g__mark_new_top_tl
                }
```

If it wasn't empty, i.e., if it had a real value then we use this value for our new last mark instead.

```
                {
                  \tl_gset_eq:cN { g__mark_#1_last_##1_tl } \g__mark_tmp_tl
```

Because we had a last mark we also have a first mark (which might be the same, but might be not), so we pick that up and assign it to the appropriate token list. This explains why we first checked for the last mark because that makes the processing faster in case there is none.

```
                  \tl_gset:co { g__mark_#1_first_##1_tl }
                    {
                      \tex_splitfirstmarks:D
                        \use:c { c__mark_class_##1_mark }
                    }
                }
            }
        }
```

If the badness was zero (we actually tested for > 0 but it can't get negative) then we had infinite shrinkage, so we report that and set all marks to the value the last mark had before.

```
        {
          \msg_error:nnn { mark } { infinite-shrinkage } {#1}
          \seq_map_inline:Nn \g__mark_classes_seq
            {
              \tl_gset_eq:cc { g__mark_#1_top_  ##1_tl }
                             { g__mark_#1_last_ ##1_tl }
              \tl_gset_eq:cc { g__mark_#1_first_##1_tl }
                             { g__mark_#1_last_ ##1_tl }
            }
        }
```

Once all mark classes have been processed the data structures are updated and we can close the group which undoes our local changes and retains only the global ones.

```
    \group_end:
  }
```

(*End definition for* `\__mark_update_structure:nn`.)

`\__mark_update_structure_alias:nn` This function copies the structure for one region to another (name), e.g., from `page` to `previous-page` above, or later from `column` to `first-column`, etc.

```
\cs_new_protected:Npn \__mark_update_structure_alias:nn #1#2 {
```

This requires a simple loop through all mark classes copying the token list from one name to the next.

```
  \seq_map_inline:Nn \g__mark_classes_seq
    {
      \tl_gset_eq:cc { g__mark_ #1 _top_   ##1 _tl }
                     { g__mark_ #2 _top_   ##1 _tl }
      \tl_gset_eq:cc { g__mark_ #1 _first_ ##1 _tl }
                     { g__mark_ #2 _first_ ##1 _tl }
      \tl_gset_eq:cc { g__mark_ #1 _last_  ##1 _tl }
                     { g__mark_ #2 _last_  ##1 _tl }
    }
}
```

(*End definition for* `\__mark_update_structure_alias:nn`.)

__mark_update_structure_to_err:n
__mark_error:n

A slight variation is to install a fixed error message as the value.

```
\cs_new_protected:Npn \__mark_update_structure_to_err:n #1 {
  \seq_map_inline:Nn \g__mark_classes_seq
      {
        \tl_gset:cn { g__mark_ #1 _top_   ##1 _tl } { \__mark_error:n {#1} }
        \tl_gset:cn { g__mark_ #1 _first_ ##1 _tl } { \__mark_error:n {#1} }
        \tl_gset:cn { g__mark_ #1 _last_  ##1 _tl } { \__mark_error:n {#1} }
      }
}
```

Given that this is used in only one place, we could hardwire the argument which would be a bit more compact, but who knows, perhaps we end up with another reason to use this error command elsewhere, so for now we keep the argument.

```
\cs_new_protected:Npn \__mark_error:n #1 {
  \msg_error:nnn { mark } { invalid-use } {#1}
}
```

(*End definition for* `\__mark_update_structure_to_err:n` *and* `\__mark_error:n`.)

7.3 Placing and retrieving marks

\mark_insert:nn

This function puts a mark for some ⟨*class*⟩ at the current point.

```
\cs_new_protected:Npn \mark_insert:nn #1#2
{
  \seq_if_in:NnTF \g__mark_classes_seq {#1}
      {
```

We need to pass the evaluated argument into the mark but protected commands should not expand including those protected using the `\protect` approach of LaTeX 2_ε. We also disable `\label` and the like.[38]

At this point the code eventually should get a public (and a kernel) hook instead of a set of hardwired settings.

```
        \group_begin:
```

Within the group we alter some comments, e.g, `\label` or `\index`, to do the right at this point. This is done in the kernel hook `\@kernel@before@insertmark` which is followed by the public hook `insertmark` that can be used by packages to augment or alter that setup as necessary.

```
          \@kernel@before@insertmark
          \hook_use:n { insertmark }
          \unrestored@protected@xdef \g__mark_tmp_tl {#2}
⟨*trace⟩
          \__mark_debug:n{ \iow_term:x { Marks:~ set~#1~<-~
              '\tl_to_str:V \g__mark_tmp_tl' ~ \msg_line_context: } }
⟨/trace⟩
          \tex_marks:D \use:c { c__mark_class_ #1 _mark }
            {
```

Here is the trick to avoid truly empty marks: if the result from the above processing is empty we add something which eventually becomes empty, but not immediately; otherwise we just put `\g__mark_tmp_tl` in.

```
              \tl_if_empty:NTF \g__mark_tmp_tl
```

[38] Straight copy from `latex.ltx` but is this even correct? At least a label in a running header makes little sense if it get set several times! Maybe that needs looking at in the 2e kernel.

```
                { \exp_not:n { \prg_do_nothing: } }
                { \exp_not:o { \g__mark_tmp_tl } }
            }
        \group_end:
```

A mark introduces a possible break point and in certain situations that should not happen in vertical mode in LaTeX. This needs some cleanup ....

```
        \if@nobreak\ifvmode\nobreak\fi\fi
    }
```

If the mark class was not known, raise an error.

```
    {
        \msg_error:nnx { mark } { unknown-class }
          { \tl_to_str:n {#1} }
    }
}
```

(*End definition for* `\mark_insert:nn`. *This function is documented on page* 792.)

`\@kernel@before@insertmark` `insertmark`

By default `\label`, `\index`, and `\glossary` do nothing when the mark is inserted.

```
\cs_new:Npn \@kernel@before@insertmark {
          \cs_set_eq:NN \label    \scan_stop:
          \cs_set_eq:NN \index    \scan_stop:
          \cs_set_eq:NN \glossary \scan_stop:
}
```

The public hook to augment the setup.

```
\hook_new:n {insertmark}
```

(*End definition for* `\@kernel@before@insertmark` *and* `insertmark`.)

`\mark_use_top:nn` `\mark_use_first:nn` `\mark_use_last:nn`

To retrieve the first, last or top region mark, we grab the appropriate value stored in the corresponding token list variable and pass its contents back. These functions should be used only in output routines after `\__mark_update_structure:nn` has acted, otherwise their value will be wrong.

If used with an unknown class or region they generate an error (fairly low-level because we are in an expandable context).

```
\cs_new:Npn \mark_use_first:nn #1#2 { \exp_not:v { g__mark_#1_first_#2_tl } }
\cs_new:Npn \mark_use_last:nn #1#2  { \exp_not:v { g__mark_#1_last_#2_tl }  }
\cs_new:Npn \mark_use_top:nn #1#2   { \exp_not:v { g__mark_#1_top_#2_tl }   }
```

(*End definition for* `\mark_use_top:nn`, `\mark_use_first:nn`, *and* `\mark_use_last:nn`. *These functions are documented on page* 793.)

7.4 Comparing mark values

`\mark_if_eq:nnnnTF` `\mark_if_eq:nnnnnnTF`

Test if in a given region (`#1`) for a given class (`#2`) the marks in position `#3` and `#4` (top, first, or last) are identical

```
\prg_new_conditional:Npnn \mark_if_eq:nnnn #1#2#3#4 { T , F , TF }
{
  \tl_if_eq:ccTF { g__mark_ #1 _#3_ #2 _tl }
                 { g__mark_ #1 _#4_ #2 _tl }
                 \prg_return_true:
                 \prg_return_false:
}
```

The fully general test (with two triplets of the form ⟨*region*⟩, ⟨*class*⟩, and ⟨*position*⟩) is this:

```
\prg_new_conditional:Npnn \mark_if_eq:nnnnnn #1#2#3#4#5#6 { T , F , TF }
{
  \tl_if_eq:ccTF { g__mark_ #1 _#3_ #2 _tl }
                 { g__mark_ #4 _#6_ #5 _tl }
                 \prg_return_true:
                 \prg_return_false:
}
```

(*End definition for* `\mark_if_eq:nnnnTF` *and* `\mark_if_eq:nnnnnnTF`*. These functions are documented on page* 794.)

7.5 Messages

Mark errors are LaTeX kernel errors:

```
\prop_gput:Nnn \g_msg_module_type_prop { mark } { LaTeX }
```

```
\msg_new:nnnn { mark } { class-already-defined }
  { Mark~class~'#1'~already~defined }
  {
    \c__msg_coding_error_text_tl
    LaTeX~was~asked~to~define~a~new~mark~class~called~'#1':~
    this~mark~class~already~exists.
    \c__msg_return_text_tl
  }
```

```
\msg_new:nnnn { mark } { unknown-class }
  { Unknown~mark~class~'#1'. }
  {
    \c__msg_coding_error_text_tl
    LaTeX~was~asked~to~manipulate~a~mark~of~class~'#1',~
    but~this~class~of~marks~does~not~exist.
  }

\msg_new:nnnn { mark } { invalid-use }
  { Mark~region~'#1'~not ~usable }
  {
    \c__msg_coding_error_text_tl
    The~region~'#1'~can~only~be~used~after~
    all~columns~have~been~assembled.
    \c__msg_return_text_tl
  }
```

```
\msg_new:nnnn { mark } { infinite-shrinkage }
  { Infinite~shrinkage~found~in~'#1'. }
  {
    \c__msg_coding_error_text_tl
    The~mark~region~'#1'~contains~some~infinite~negative~glue~
    allowing~it~to~shrink~to~an~arbitrary~size.~
    This~makes~it~impossible~to~split~the~region~apart~to~
    get~at~its~marks.~They~are~lost.
  }
```

7.6 Debugging the mark structures

Code and commands in this section are not final, it needs more experimentation to see what kind of tracing information is going to be useful in practice. For now the tracing is mainly meant to be used for code testing and not so much for application testing.

It is quite likely that the commands and the behavior of the tracing might change in the future once we gained some experience with it.

\g__mark_debug_bool

Holds the current debugging state.

```
\bool_new:N \g__mark_debug_bool
```

(*End definition for* \g__mark_debug_bool.)

\mark_debug_on:
\mark_debug_off:
__mark_debug:n
__mark_debug_gset:

Turns debugging on and off by redefining __mark_debug:n.

```
\cs_new_eq:NN \__mark_debug:n \use_none:n
\cs_new_protected:Npn \mark_debug_on:
  {
    \bool_gset_true:N \g__mark_debug_bool
    \__mark_debug_gset:
  }
\cs_new_protected:Npn \mark_debug_off:
  {
    \bool_gset_false:N \g__mark_debug_bool
    \__mark_debug_gset:
  }
\cs_new_protected:Npn \__mark_debug_gset:
  {
    \cs_gset_protected:Npx \__mark_debug:n ##1
      { \bool_if:NT \g__mark_debug_bool {##1} }
  }
```

(*End definition for* \mark_debug_on: *and others. These functions are documented on page* 795.)

\DebugMarksOn
\DebugMarksOff

CamelCase commands for debugging.

```
\cs_new_eq:NN \DebugMarksOn   \mark_debug_on:
\cs_new_eq:NN \DebugMarksOff  \mark_debug_off:
```

(*End definition for* \DebugMarksOn *and* \DebugMarksOff. *These functions are documented on page* 795.)

__mark_class_status:nn

Shows the mark values across all regions for one mark class (#2). The first argument gives some ⟨*info*⟩ to help identifying where the command was called.

```
⟨*trace⟩
\cs_new_protected:Npn \__mark_class_status:nn #1#2
   {
            \typeout{ Marks:~#2~ #1:}
            \typeout{\@spaces page~ (current):
              | \exp_not:v { g__mark_page_top_ #2 _tl }
              | \exp_not:v { g__mark_page_first_ #2 _tl }
              | \exp_not:v { g__mark_page_last_ #2 _tl }     |}
            \typeout{\@spaces page~ (previous):
              | \exp_not:v { g__mark_previous-page_top_ #2 _tl }
              | \exp_not:v { g__mark_previous-page_first_ #2 _tl }
              | \exp_not:v { g__mark_previous-page_last_ #2 _tl }     |}
            \typeout{\@spaces column~ (previous):
```

```
              | \exp_not:v { g__mark_previous-column_top_ #2 _tl }
              | \exp_not:v { g__mark_previous-column_first_ #2 _tl }
              | \exp_not:v { g__mark_previous-column_last_ #2 _tl }     |}
            \typeout{\@spaces column~ (current):
              | \exp_not:v { g__mark_column_top_ #2 _tl }
              | \exp_not:v { g__mark_column_first_ #2 _tl }
              | \exp_not:v { g__mark_column_last_ #2 _tl }     |}
            \typeout{\@spaces column~ (first):
              | \exp_not:v { g__mark_first-column_top_ #2 _tl }
              | \exp_not:v { g__mark_first-column_first_ #2 _tl }
              | \exp_not:v { g__mark_first-column_last_ #2 _tl }     |}
            \typeout{\@spaces column~ (second):
              | \exp_not:v { g__mark_last-column_top_ #2 _tl }
              | \exp_not:v { g__mark_last-column_first_ #2 _tl }
              | \exp_not:v { g__mark_last-column_last_ #2 _tl }     |}
}
```

(*End definition for* `\__mark_class_status:nn`.)

`\__mark_status:n` Show all mark class values across all regions.

```
\cs_new_protected:Npn \__mark_status:n #1
  {
    \seq_map_inline:Nn \g__mark_classes_seq
      { \__mark_class_status:nn {#1} {##1} }
  }
⟨/trace⟩
```

(*End definition for* `\__mark_status:n`.)

7.7 Designer-level interfaces

`\NewMarkClass` `\InsertMark` These two are identical to the L3 programming layer commands.

```
\cs_new_eq:NN  \NewMarkClass \mark_new_class:n
\@onlypreamble \NewMarkClass
```

```
\cs_new_eq:NN \InsertMark  \mark_insert:nn
```

(*End definition for* `\NewMarkClass` *and* `\InsertMark`. *These functions are documented on page* 792.)

`\TopMark` `\FirstMark` `\LastMark` The following commands take an optional argument that defaults to page. There is no checking that the region is actually valid. If not there is simply an empty return.

```
\NewExpandableDocumentCommand \FirstMark { O{page} m }
                    { \mark_use_first:nn {#1}{#2} }
```

```
\NewExpandableDocumentCommand \LastMark { O{page} m }
                    { \mark_use_last:nn {#1}{#2} }
```

```
\NewExpandableDocumentCommand \TopMark { O{page} m }
                    { \mark_use_top:nn {#1}{#2} }
```

(*End definition for* `\TopMark`, `\FirstMark`, *and* `\LastMark`. *These functions are documented on page* 793.)

\IfMarksEqualTF We only provide a CamelCase command for the case with one region (optional) and one class. One could think of also providing a version for the general case with several optional arguments, but use cases for this are most likely rare, so not done yet.

```
\NewExpandableDocumentCommand \IfMarksEqualTF {O{page}mmm} {
  \mark_if_eq:nnnnTF {#1}{#2}{#3}{#4}
}
```

(*End definition for* `\IfMarksEqualTF`*. This function is documented on page 794.*)

8 LaTeX 2ε integration

8.1 Core LaTeX 2ε integration

__mark_update_singlecol_structures: This command updates the mark structures if we are producing a single column document.

```
\cs_new_protected:Npn \__mark_update_singlecol_structures: {
```

First we update the `page` region (which also updates the `previous-page`.

The `\@outputbox` is normally in `\vbox` in LaTeX but we can't take that for granted (an amsmath test document changed it to an `\hbox` just to trip me up) so we are a little careful with unpack now.

```
  \box_if_vertical:NTF \@outputbox
      {
        \__mark_update_structure:nn {page}
           { \vbox_unpack:N  \@outputbox }
      }
      {
        \__mark_update_structure:nn {page}
           { \hbox_unpack:N  \@outputbox }
      }
```

The we provide the necessary updates for the aliases.

```
  \__mark_update_structure_alias:nn {previous-column}{previous-page}
  \__mark_update_structure_alias:nn {column}{page}
  \__mark_update_structure_alias:nn {first-column}{page}
  \__mark_update_structure_alias:nn {last-column}{page}
⟨*trace⟩
% move this into status itself?
    \__mark_debug:n
        {
          \__mark_status:n
               { in~ OR~ (
                 \legacy_if:nTF {@twoside}
                        { twoside-
                          \int_if_odd:nTF \c@page
                              { odd }{ even }
                        }
                        { oneside }
                        )
               }
        }
⟨/trace⟩
}
```

(*End definition for* `\__mark_update_singlecol_structures:`.)

`\__mark_update_dblcol_structures:` This commands handles the updates if we are doing two-column pages.

```
\cs_new_protected:Npn \__mark_update_dblcol_structures: {
```

First we update the `column` and `previous-column` regions using the material assembled in `\@outputbox`.

```
  \box_if_vertical:NTF \@outputbox
      {
        \__mark_update_structure:nn {column}
           { \vbox_unpack:N  \@outputbox }
      }
      {
        \__mark_update_structure:nn {column}
           { \hbox_unpack:N  \@outputbox }
      }
```

How we have to update the alias regions depends on whether or not `\@opcol` was called to process the first column or to produce the completed page

```
  \legacy_if:nTF {@firstcolumn}
    {
```

If we are processing the first column then `column` is our `first-column` and there is no `last-column` yet, so we make those an error.

```
      \__mark_update_structure_alias:nn {first-column}{column}
      \__mark_update_structure_to_err:n {last-column}
    }
    {
```

If we produce the completed page then the `first-column` is the same as the new `previous-column`. However, the structure should already be correct if you think about it (because is was set to `column` last time which is now the `previous-column`), thus there is no need to make an update.

```
%     \__mark_update_structure_alias:nn {first-column}{previous-column}
```

However, we now have a proper `last-column` so we assign that.

```
      \__mark_update_structure_alias:nn {last-column}{column}
```

What now remains doing is to update the `page` and `previous-page` regions. For this we have to copy the settings in `page` into `previous-page` and then update `page` such that the top and first marks are taken from the `first-column` region and the last marks are taken from the `last-column` region. All this has to be done for all mark classes so we loop over our sequence.

Note that one loop is needed if we arrange the copy statements in a suitable way.

```
      \seq_map_inline:Nn \g__mark_classes_seq
        {
          \tl_gset_eq:cc { g__mark_previous-page_top_   ##1 _tl }
                         { g__mark_page_top_            ##1 _tl }
          \tl_gset_eq:cc { g__mark_previous-page_first_ ##1 _tl }
                         { g__mark_page_first_          ##1 _tl }
          \tl_gset_eq:cc { g__mark_previous-page_last_  ##1 _tl }
                         { g__mark_page_last_           ##1 _tl }
```

The page updates need to come after the corresponding updates for previous-page otherwise we loose the necessary value.

```
          \tl_gset_eq:cc { g__mark_page_top_           ##1 _tl }
                         { g__mark_first-column_top_   ##1 _tl }
          \tl_gset_eq:cc { g__mark_ page_first_        ##1 _tl }
                         { g__mark_first-column_first_ ##1 _tl }
          \tl_gset_eq:cc { g__mark_page_last_          ##1 _tl }
                         { g__mark_last-column_last_   ##1 _tl }
        }
    }
⟨*trace⟩
     \__mark_debug:n
         {
           \__mark_status:n
              { in~ OR~ (
                \legacy_if:nTF {@twoside}
                       { twoside-
                         \int_if_odd:nTF \c@page
                             { odd }{ even }
                       }
                       { oneside }
                       \space
                       \legacy_if:nTF {@firstcolumn}
                              { first~ }{ second~ }
                              column )
              }
         }
⟨/trace⟩
}
```

(*End definition for* `\__mark_update_dblcol_structures:`.)

```
⟨@@=⟩
```

\@expl@@@mark@update@singlecol@structures@@
\@expl@@@mark@update@dblcol@structures@@

```
\cs_new_eq:NN  \@expl@@@mark@update@singlecol@structures@@
               \__mark_update_singlecol_structures:
\cs_new_eq:NN  \@expl@@@mark@update@dblcol@structures@@
               \__mark_update_dblcol_structures:
```

(*End definition for* `\@expl@@@mark@update@singlecol@structures@@` *and* `\@expl@@@mark@update@dblcol@structures@@`.)

8.2 Other LaTeX 2_ε output routines

This section will cover multicol and other packages altering or providing their own output routine. Not done yet.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{ltmarks}%
⟨latexrelease⟩                  {Undo~Marks~handling}
⟨latexrelease⟩
```

We keep the interface commands around even if we roll back in case they are used in packages that don't roll back. Not likely to do a lot of good, but then there is not much we can do, but this at least then doesn't give errors.

```
⟨latexrelease⟩\DeclareRobustCommand \NewMarkClass[1]{}
⟨latexrelease⟩\DeclareRobustCommand \InsertMark[2]{}
⟨latexrelease⟩\RenewExpandableDocumentCommand \FirstMark { O{} m } { }
⟨latexrelease⟩\RenewExpandableDocumentCommand \LastMark { O{} m } { }
⟨latexrelease⟩\RenewExpandableDocumentCommand \TopMark { O{} m } { }
⟨latexrelease⟩\RenewExpandableDocumentCommand \IfMarksEqualTF { O{} mmm }{ }
⟨latexrelease⟩
```

Same here, this avoided extra roll back code in the OR.

```
⟨latexrelease⟩\let \@expl@@@mark@update@singlecol@structures@@ \relax
⟨latexrelease⟩\let \@expl@@@mark@update@dblcol@structures@@ \relax
⟨latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\EndModuleRelease
```

```
\ExplSyntaxOff
```

```
⟨/2ekernel | latexrelease⟩
```

Reset module prefix:

```
⟨@@=⟩
```

File T
ltpage.dtx

1 Page styles and related commands

1.1 Page Style Commands

`\pagestyle{`⟨*style*⟩`}` : sets the page style of the current and succeeding pages to *style*

`\thispagestyle{`⟨*style*⟩`}` : sets the page style of the current page only to *style*.

To define a page style *style*, you must define `\ps@`*style* to set the page style parameters.

1.2 How a page style makes running heads and feet

The `\ps@`... command defines the macros `\@oddhead`, `\@oddfoot`, `\@evenhead`, and `\@evenfoot` to define the running heads and feet. (See output routine.) To make headings determined by the sectioning commands, the page style defines the commands `\chaptermark`, `\sectionmark`, etc., where `\chaptermark{`⟨*text*⟩`}` is called by `\chapter` to set a mark. The `\...mark` commands and the `\...head` macros are defined with the help of the following macros.

(All the `\...mark` commands should be initialized to no-ops.)

1.3 marking conventions

LaTeX extends TeX's `\mark` facility by producing two kinds of marks a 'left' and a 'right' mark, using the following commands:
`\markboth{`⟨*left*⟩`}{`⟨*right*⟩`}` : Adds both marks.
`\markright{`⟨*right*⟩`}` : Adds a 'right' mark.
`\leftmark` : Used in the output routine, gets the current 'left' mark. Works like TeX's `\botmark`.
`\rightmark` : Used in the output routine, gets the current 'right' mark. Works like TeX's `\firstmark`. The marking commands work reasonably well for right marks 'numbered within' left marks—e.g., the left mark is changed by a `\chapter` command and the right mark is changed by a `\section` command. However, it does produce somewhat anomalous results if 2 `\markboth`'s occur on the same page.

Commands like `\tableofcontents` that should set the marks in some page styles use a `\@mkboth` command, which is `\let` by the pagestyle command (`\ps@...`) to `\markboth` for setting the heading or to `\@gobbletwo` to do nothing.

```
⟨*2ekernel⟩
```

`\pagestyle` User command to set the page style for this and following pages.

```
\def\pagestyle#1{%
  \@ifundefined{ps@#1}%
    \undefinedpagestyle
    {\@nameuse{ps@#1}}}
```

(*End definition for* `\pagestyle`.)

\thispagestyle User command to set the page style for this page only.

```
\def\thispagestyle#1{%
  \@ifundefined{ps@#1}%
    \undefinedpagestyle
    {\global\@specialpagetrue\gdef\@specialstyle{#1}}}
```

(*End definition for* \thispagestyle.)

\ps@empty The empty page style: No head or foot line.

```
\def\ps@empty{%
  \let\@mkboth\@gobbletwo\let\@oddhead\@empty\let\@oddfoot\@empty
  \let\@evenhead\@empty\let\@evenfoot\@empty}
```

(*End definition for* \ps@empty.)

\ps@plain The plain page style: No head, centred page number in foot.

```
\def\ps@plain{\let\@mkboth\@gobbletwo
      \let\@oddhead\@empty\def\@oddfoot{\reset@font\hfil\thepage
      \hfil}\let\@evenhead\@empty\let\@evenfoot\@oddfoot}
```

(*End definition for* \ps@plain.)

\@leftmark
\@rightmark We implement \@leftmark and \@rightmark in terms of already defined commands to save token space. We can't get rid of them since they are sometimes used in applications.

```
\let\@leftmark\@firstoftwo
\let\@rightmark\@secondoftwo
```

(*End definition for* \@leftmark *and* \@rightmark.)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                    {\markboth}{New mark support}%
```

\markboth
\markright User commands for setting LaTeX marks.

Test for \@nobreak added 15 Apr 86 in \markboth and \markright letting \label and \index to \relax added 22 Feb 86 so these commands can appear in sectioning command arguments RmS 91/06/21 Same for \glossary

```
\ExplSyntaxOn
\DeclareRobustCommand*\markboth[2]{%
  \begingroup
    \let\label\relax \let\index\relax \let\glossary\relax
    \unrestored@protected@xdef\@themark {{#1}{#2}}%
    \@temptokena \expandafter{\@themark}%
```

In addition to generating the legacy mark we output the individual ones as well at the very same point. The legacy mark is kept unchanged in order to work with packages that expect that mark in exactly the way it is right now.

We might want to think about how to improve this in one-side documents, see comments below.

We have not changed all of the code to L3 prog layer convention, in case packages attempt to do some patching and expect the 2e names being around. Eventually this should and will change.

```
    \mark_insert:nn{2e-left}{#1}
    \mark_insert:nn{2e-right}{#2}
```

```
    \tl_if_empty:nF{#2}{ \mark_insert:nn{2e-right-nonempty}{#2} }
    \mark{\the\@temptokena}%
  \endgroup
  \if@nobreak\ifvmode\nobreak\fi\fi}
```

```
\DeclareRobustCommand*\markright[1]{%
  \begingroup
    \let\label\relax \let\index\relax \let\glossary\relax
```

Protection is handled inside `\@markright`.

```
    \expandafter\@markright\@themark {#1}%
    \@temptokena \expandafter{\@themark}%
```

Same game with `\markright` more or less ...

```
    \mark_insert:nn{2e-right}{#1}
    \tl_if_empty:nF{#1}{ \mark_insert:nn{2e-right-nonempty}{#1} }
```

The legacy LaTeX mechanism always sets left and right mark, i.e., if a sub-mark (i.e., right mark) is set the corresponding main mark also is getting a mark with the same value it had previously. However, for the individual mark classes this means we are losing information so for them that is not done.

```
%   \mark_insert:nn{2e-left}{\exp_after:wN \use_i:nn \@themark }
    \mark{\the\@temptokena}%
  \endgroup
  \if@nobreak\ifvmode\nobreak\fi\fi}
\ExplSyntaxOff
```

(*End definition for* `\markboth` *and* `\markright`*. These functions are documented on page 795.*)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩                  {\markboth}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand*\markboth[2]{%
⟨latexrelease⟩  \begingroup
⟨latexrelease⟩    \let\label\relax \let\index\relax \let\glossary\relax
⟨latexrelease⟩    \unrestored@protected@xdef\@themark {{#1}{#2}}%
⟨latexrelease⟩    \@temptokena \expandafter{\@themark}%
⟨latexrelease⟩    \mark{\the\@temptokena}%
⟨latexrelease⟩  \endgroup
⟨latexrelease⟩  \if@nobreak\ifvmode\nobreak\fi\fi}
⟨latexrelease⟩\DeclareRobustCommand*\markright[1]{%
⟨latexrelease⟩  \begingroup
⟨latexrelease⟩    \let\label\relax \let\index\relax \let\glossary\relax
⟨latexrelease⟩    \expandafter\@markright\@themark {#1}%
⟨latexrelease⟩    \@temptokena \expandafter{\@themark}%
⟨latexrelease⟩    \mark{\the\@temptokena}%
⟨latexrelease⟩  \endgroup
⟨latexrelease⟩  \if@nobreak\ifvmode\nobreak\fi\fi}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\markboth}{Make commands robust}%
⟨latexrelease⟩
⟨latexrelease⟩\kernel@make@fragile\markboth
```

```
⟨latexrelease⟩\kernel@make@fragile\markright
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\@markright
\leftmark
\rightmark

```
\def\@markright#1#2#3{\@temptokena {#1}%
  \unrestored@protected@xdef\@themark{{\the\@temptokena}{#3}}}
\def\leftmark{\expandafter\@leftmark\botmark\@empty\@empty}
\def\rightmark{\expandafter\@rightmark\firstmark\@empty\@empty}
```

(*End definition for* `\@markright`, `\leftmark`, *and* `\rightmark`.)

\@themark

Initialise LaTeX's marks without setting a TeX mark ⟨*whatsit*⟩.

```
\def\@themark{{}{}}
```

(*End definition for* `\@themark`.)

\mark

Test versions of LaTeX 2_ε initialised TeX's `\mark` system at this point, but this was removed before the first release.

```
AtBeginDocument{\mark{{}{}}}
```

(*End definition for* `\mark`.)

\raggedbottom

`\raggedbottom` typesets pages with no vertical stretch, so they have their natural height instead of all being exactly the same height. (Uses a space of .0001fil to avoid interfering with the 1fil space of `\newpage`.)

```
\DeclareRobustCommand\raggedbottom{%
  \def\@textbottom{\vskip \z@ \@plus.0001fil}\let\@texttop\relax}
```

(*End definition for* `\raggedbottom`.)

\flushbottom

`\flushbottom`: Inverse of `\raggedbottom` — makes all pages the same height.

```
\DeclareRobustCommand\flushbottom{%
  \let\@textbottom\relax \let\@texttop\relax}
```

(*End definition for* `\flushbottom`.)

\sloppy

`\sloppy` will never (well, hardly ever) produce overfull boxes, but may produce underfull ones. (14 June 85)

```
\DeclareRobustCommand\sloppy{%
  \tolerance 9999%
  \emergencystretch 3em%
  \hfuzz .5\p@
  \vfuzz\hfuzz}
```

(*End definition for* `\sloppy`.)

sloppypar (*env.*)

A sloppypar environment is equivalent to `{\par \sloppy ... \par}`.

```
\def\sloppypar{\par\sloppy}
\def\endsloppypar{\par}
```

`\fussy` Resets TEX's parameters to their normal finicky values.

```
\DeclareRobustCommand\fussy{%
  \emergencystretch\z@
  \tolerance 200%
  \hfuzz .1\p@
  \vfuzz\hfuzz}
```

(*End definition for* `\fussy`.)

`\overfullrule` LATEX default is no overfull box rule. Changed by document class option.

```
\overfullrule 0pt
```

(*End definition for* `\overfullrule`.)

⟨/2ekernel⟩

File U
ltclass.dtx

1 Introduction

This file implements the following declarations, which replace `\documentstyle` in LaTeX 2_ε documents.

Note that old documents containing `\documentstyle` will be run using a compatibility option—thus keeping everyone happy, we hope!

The overall idea is that there are two types of 'style files': 'class files' which define elements and provide a default formatting for them; and 'packages' which provide extra functionality. One difference between LaTeX 2_ε and LaTeX2.09 is that LaTeX 2_ε packages may have options. Note that options to classes packages may be implemented such that they input files, but these file names are not necessarily directly related to the option name.

2 User interface

`\documentclass[`⟨*main-option-list*⟩`]{`⟨*class*⟩`}[`⟨*version*⟩`]`

There must be exactly one such declaration, and it must come first. The ⟨*main-option-list*⟩ is a list of options which can modify the formatting of elements which are defined in the ⟨*class*⟩ file as well as in all following `\usepackage` declarations (see below). The ⟨*version*⟩ is a version number, beginning with a date in the format `YYYY/MM/DD`. If an older version of the class is found, a warning is issued.

`\documentstyle[`⟨*main-option-list*⟩`]{`⟨*class*⟩`}[`⟨*version*⟩`]`

The `\documentstyle` declaration is kept in order to maintain upward compatibility with LaTeX2.09 documents. It is similar to `\documentclass`, but it causes all options in ⟨*main-option-list*⟩ that the ⟨*class*⟩ does not use to be passed to `\RequirePackage` after the options have been processed. This maintains compatibility with the 2.09 behaviour. Also a flag is set to indicate that the document is to be processed in LaTeX2.09 compatibility mode. As far as most packages are concerned, this only affects the warnings and errors LaTeX generates. This flag does affect the definition of font commands, and `\sloppy`.

`\usepackage[`⟨*package-option-list*⟩`]{`⟨*package-list*⟩`}[`⟨*version*⟩`]`

There can be any number of these declarations. All packages in ⟨*package-list*⟩ are called with the same options.

Each ⟨*package*⟩ file defines new elements (or modifies those defined in the ⟨*class*⟩), and thus extends the range of documents which can be processed. The ⟨*package-option-list*⟩ is a list of options which can modify the formatting of elements defined in the ⟨*package*⟩ file. The ⟨*version*⟩ is a version number, beginning with a date in the format `YYYY/MM/DD`. If an older version of the package is found, a warning is issued.

Each package is loaded only once. If the same package is requested more than once, nothing happens, unless the package has been requested with options that were not given the first time it was loaded, in which case an error is produced.

As well as processing the options given in the ⟨*package-option-list*⟩, each package processes the ⟨*main-option-list*⟩. This means that options that affect all of the packages can be given globally, rather than repeated for every package.

Note that class files have the extension `.cls`, packages have the extension `.sty`.

`filecontents` (*env.*) The environment `filecontents` is intended for passing the contents of packages, options, or other files along with a document in a single file. It has one argument, which is the name of the file to create. If that file already exists (maybe only in the current directory if the OS supports a notion of a 'current directory' or 'default directory') then nothing happens (except for an information message) and the body of the environment is bypassed. Otherwise, the body of the environment is written verbatim to the file name given as the first argument, together with some comments about how it was produced.

The environment can also be called with an optional argument which is used to alter some of its behavior: option `force` or `overwrite` will allow for overwriting existing files, option `nosearch` will only check the current directory when looking if the file exists. This can be useful if you want to generate a local (modified) copy of some file that is already in the search tree of TEX. Finally, you can use `noheader` to prevent it from writing the standard blurb at the top of the file (this is actually the same as using the star form of the environment).

The environment is now allowed anywhere in the document, but to ensure that all packages or options necessary are available when the document is run, it is normally best to place it at the top of your file (before `\documentclass`). A possible use case for using it inside the document body is if you want to reuse some text several times in the document you could then write it and later use `\input` to retrieve it where needed.

The begin and end tags should each be on a line by itself.

2.1 Option processing

When the options are processed, they are divided into two types: *local* and *global*:

- For a class, the options in the `\documentclass` command are local.
- For a package, the options in the `\usepackage` command are local, and the options in the `\documentclass` command are global.

The options for `\documentclass` and `\usepackage` are processed in the following way:

1. The local and global options that have been declared (using `\DeclareOption` as described below) are processed first.

   In the case of `\ProcessOptions`, they are processed in the order that they were declared in the class or package.

   In the case of `\ProcessOptions*`, they are processed in the order that they appear in the option-lists. First the global options, and then the local ones.

2. Any remaining local options are dealt with using the default option (declared using the `\DeclareOption*` declaration described below). For document classes, this usually does nothing, but records the option on a list of unused options. For packages, this usually produces an error.

Finally, when `\begin{document}` is reached, if there are any global options which have not been used by either the class or any package, the system will produce a warning.

3 Class and Package interface

3.1 Class name and version

\ProvidesClass A class can identify itself with the \ProvidesClass{⟨*name*⟩}[⟨*version*⟩] command. The ⟨*version*⟩ should begin with a date in the format YYYY/MM/DD.

3.2 Package name and version

\ProvidesPackage A package can identify itself with the \ProvidesPackage{⟨*name*⟩}[⟨*version*⟩] command. The ⟨*version*⟩ should begin with a date in the format YYYY/MM/DD.

3.3 Requiring other packages

\RequirePackage Packages or classes can load other packages using
\RequirePackage[⟨*options*⟩]{⟨*name*⟩}[⟨*version*⟩].
If the package has already been loaded, then nothing happens unless the requested options are not a subset of the options with which it was loaded, in which case an error is called.

\LoadClass Similar to \RequirePackage, but for classes, may not be used in package files.

\PassOptionsToPackage Packages can pass options to other packages using:
\PassOptionsToPackage{⟨*options*⟩}{⟨*package*⟩}.

\PassOptionsToClass This adds the ⟨*options*⟩ to the options list of any future \RequirePackage or \usepackage command. For example:

```
\PassOptionsToPackage{foo,bar}{fred}
```

is the same as:

```
\RequirePackage[foo,bar,baz]{fred}
```

\LoadClassWithOptions \LoadClassWithOptions{⟨*name*⟩}[⟨*version*⟩]:
This is similar to \LoadClass, but it always calls class ⟨*name*⟩ with exactly the same option list that is being used by the current class, rather than an option explicitly supplied or passed on by \PassOptionsToClass. \RequirePackageWithOptions is the analogous command for packages.

\RequirePackageWithOptions

This is mainly intended to allow one class to simply build on another, for example:

```
\LoadClassWithOptions{article}
```

This should be contrasted with the slightly different construction

```
\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
\ProcessOptions
\LoadClass{article}
```

As used here, the effects are more or less the same, but the version using \LoadClassWithOptions is slightly quicker (and less to type). If, however, the class declares options of its own then the two constructions are different; compare, for example:

```
\DeclareOption{landscape}{...}
\ProcessOptions
\LoadClassWithOptions{article}
```

with:

```
\DeclareOption{landscape}{...}
\DeclareOption*{\PassOptionsToClass{\CurrentOption}{article}}
\ProcessOptions
\LoadClass{article}
```

In the first case, the article class will be called with option `landscape` precisely when the current class is called with this option; but in the second example it will not as in that case article is only passed options by the default option handler, which is not used for `landscape` as that option is explicitly declared.

`\IfPackageLoadedTF` `\IfClassLoadedTF` `\@ifpackageloaded` `\@ifclassloaded`

To find out if a package has already been loaded, use

`\IfPackageLoadedTF{`⟨*package*⟩`}{`⟨*true*⟩`}{`⟨*false*⟩`}`

or the old name `\@ifpackageloaded`.

`\IfPackageAtLeastTF` `\IfClassAtLeastTF` `\@ifpackagelater` `\@ifclasslater`

To find out if a package has already been loaded with a version equal to or more recent than ⟨*date*⟩, use

`\IfPackageAtLeastTF{`⟨*package*⟩`}{`⟨*date*⟩`}{`⟨*true*⟩`}{`⟨*false*⟩`}`

or the old name `\@ifpackagelater`.

`\IfFormatAtLeastTF`

To test the format date use

`\IfFormatAtLeastTF{`⟨*date*⟩`}{`⟨*true*⟩`}{`⟨*false*⟩`}`

`\IfPackageLoadedWithOptionsTF` `\IfClassLoadedWithOptionsTF` `\@ifpackagewith` `\@ifclasswith`

To find out if a package has already been loaded with at least the options ⟨*options*⟩, use

`\IfPackageLoadedWithOptionsTF{`⟨*package*⟩`}{`⟨*options*⟩`}{`⟨*true*⟩`}{`⟨*false*⟩`}`

or the old name `\@ifpackagewith`.

There exists one package that can't be tested with the above commands: the `fontenc` package pretends that it was never loaded to allow for repeated reloading with different options (see `ltoutenc.dtx` for details).

3.4 Declaring new options

Options for classes and packages are built using the same macros.

`\DeclareOption` `\DeclareOption*`

To define a builtin option, use `\DeclareOption{`⟨*name*⟩`}{`⟨*code*⟩`}`.

To define the default action to perform for local options which have not been declared, use `\DeclareOption*{`⟨*code*⟩`}`.

Note: there should be no use of
`\RequirePackage`, `\DeclareOption`, `\DeclareOption*` or `\ProcessOptions`
inside `\DeclareOption` or `\DeclareOption*`.

Possible uses for `\DeclareOption*` include:

`\DeclareOption*{}`
Do nothing. Silently accept unknown options. (This suppresses the usual warnings.)

`\DeclareOption*{\@unkownoptionerror}`
Complain about unknown local options. (The initial setting for package files.)

`\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{`⟨*pkg-name*⟩`}}`
Handle the current option by passing it on to the package ⟨*pkg-name*⟩, which will presumably be loaded via `\RequirePackage` later in the file. This is useful for building

'extension' packages, that perhaps handle a couple of new options, but then pass everything else on to an existing package.

```
\DeclareOption*{\InputIfFileExists{xx-\CurrentOption.yyy}%
                {}%
                {\OptionNotUsed}}
```

Handle the option foo by loading the file `xx-foo.yyy` if it exists, otherwise do nothing, but declare that the option was not used. Actually the `\OptionNotUsed` declaration is only needed if this is being used in class files, but does no harm in package files.

3.5 Safe Input Macros

`\InputIfFileExists` `\InputIfFileExists{`⟨*file*⟩`}{`⟨*then*⟩`}{`⟨*else*⟩`}`

Inputs ⟨*file*⟩ if it exists. Immediately before the input, ⟨*then*⟩ is executed. Otherwise ⟨*else*⟩ is executed.

`\IfFileExists` As above, but does not input the file.

One thing you might like to put in the ⟨*else*⟩ clause is

`\@missingfileerror` This starts an interactive request for a filename, supplying default extensions. Just hitting return causes the whole input to be skipped and entering `x` quits the current run,

`\input` This has been redefined from the LaTeX2.09 definition, in terms of the new commands `\InputIfFileExists` and `\@missingfileerror`.

`\listfiles` Giving this declaration in the preamble causes a list of all files input via the 'safe input' commands to be listed at the end. Any strings specified in the optional argument to `\ProvidesPackage` are listed alongside the file name. So files in standard (and other non-standard) distributions can put informative strings in this argument.

4 Implementation

```
⟨*2ekernel⟩
```

`\if@compatibility` The flag for compatibility mode.

```
\newif\if@compatibility
```

(*End definition for* `\if@compatibility`.)

`\@documentclasshook` This legacy hook is called after the first `\documentclass` command. It is *not* integrated with the new 2020 hook management system! By default this checks to see if `\@normalsize` is undefined, and if so, sets it to `\normalsize`.

```
\def\@documentclasshook{%
   \ifx\@normalsize\@undefined
      \let\@normalsize\normalsize
   \fi
}
```

(*End definition for* `\@documentclasshook`.)

`\@declaredoptions` This list is automatically built by `\DeclareOption`. It is the list of options (separated by commas) declared in the class or package file and it defines the order in which the corresponding `\ds@`⟨*option*⟩ commands are executed. All local ⟨*option*⟩s which are not declared will be processed in the order defined by the optional argument of `\documentclass` or `\usepackage`.

```
\let\@declaredoptions\@empty
```

(*End definition for* `\@declaredoptions`.)

`\@classoptionslist` List of options of the main class.

```
\let\@classoptionslist\relax
%\@onlypreamble\@classoptionslist
```

(*End definition for* `\@classoptionslist`.)

`\@raw@classoptionslist` List of options of the main class (unprocessed).

```
\let\@raw@classoptionslist\relax
```

(*End definition for* `\@raw@classoptionslist`.)

`\@unusedoptionlist` List of options of the main class that haven't been declared or loaded as class option files.

```
\let\@unusedoptionlist\@empty
%\@onlypreamble\@unusedoptionlist
```

(*End definition for* `\@unusedoptionlist`.)

`\CurrentOption` Name of current package or option.

```
\let\CurrentOption\@empty
```

(*End definition for* `\CurrentOption`.)

`\@currpath` Path to the current file if explicitly given.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\@currpath}%
⟨latexrelease⟩   {Add \@currpath}%
\let\@currpath\@empty
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@currpath}%
⟨latexrelease⟩   {Add \@currpath}%
⟨latexrelease⟩\let\@currpath\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
```

(*End definition for* `\@currpath`.)

`\@currname` Name of current package or option.

```
\let\@currname\@empty
```

(*End definition for* `\@currname`.)

`\@currext` The current file extension.

```
\global\let\@currext=\@empty
```

(*End definition for* `\@currext`.)

`\@clsextension` `\@pkgextension` The two possible values of `\@currext`.

```
\def\@clsextension{cls}
\def\@pkgextension{sty}
```

(*End definition for* `\@clsextension` *and* `\@pkgextension`.)

`\@pushfilename` `\@popfilename` `\@currnamestack`

Commands to push and pop the file name and extension.

#1 current name.
#2 current extension.
#3 current catcode of `@`.
#4 Rest of the stack.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\@pushfilename}%
⟨latexrelease⟩  {Add \@expl@push@filename@@ and \@expl@push@filename@aux@@}%
\def\@pushfilename{%
```

The push and pop macros are injected in `\@pushfilename` and `\@popfilename` so that they correctly keep track of the hook labels.

This needs cleanup with the expl3 interfaces also playing here, e.g., `\@expl@push@filename@@` needs cleanup and (and should probably not have this name either).

```
  \@expl@push@filename@@
  \xdef\@currnamestack{%
    {\@currname}%
    {\@currext}%
    {\the\catcode`\@}%
    \@currnamestack}%
```

Temporarily add a stack for `\@currpath` here. This should be integrated in the main file stack eventually, but other packages rely on `\@currnamestack` having three elements per file, so that isn't a trivial change. The prefix `\@kernel@...` hopefully discourages people from using it.

```
  \xdef\@kernel@currpathstack{%
    {\@currpath}%
    \@kernel@currpathstack}%
  \@expl@push@filename@aux@@}
⟨latexrelease⟩\EndIncludeInRelease
```

The following version of `\@pushfilename` didn't formally exist in this file, but in the 2020/02/02 release, expl3 was preloaded and it patched `\@pushfilename` (and `\@popfilename`) by adding some hooks in there. But rolling back to 2020/02/02, expl3 doesn't patch these macros again, so rolling back has to take those hooks into account. Same goes for `\@popfilename`.

```
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}{\@pushfilename}%
⟨latexrelease⟩  {Add \@expl@push@filename@@}%
⟨latexrelease⟩\def\@pushfilename{%
⟨latexrelease⟩  \@expl@push@filename@@
⟨latexrelease⟩  \xdef\@currnamestack{%
⟨latexrelease⟩    {\@currname}%
⟨latexrelease⟩    {\@currext}%
⟨latexrelease⟩    {\the\catcode`\@}%
⟨latexrelease⟩    \@currnamestack}%
⟨latexrelease⟩    \@expl@push@filename@aux@@}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
```

When we roll back from a release that has expl3 preloaded, the definitions of \@pushfilename and \@popfilename can't be completely rolled back otherwise expl3-based packages won't have the automatic \ExplSyntaxOff at the end. Here and below for \@popfilename, we don't roll back all the way through if coming from LaTeX > 2020 − 02 − 02.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@pushfilename}%
⟨latexrelease⟩  {Add \@expl@push@filename@@ and \@expl@push@filename@aux@@}%
⟨latexrelease⟩\ifnum\sourceLaTeXdate<20200202\relax
⟨latexrelease⟩  \GenericInfo{}{Defining 00-00-00\string\@pushfilename.}
⟨latexrelease⟩\def\@pushfilename{%
⟨latexrelease⟩  \xdef\@currnamestack{%
⟨latexrelease⟩    {\@currname}%
⟨latexrelease⟩    {\@currext}%
⟨latexrelease⟩    {\the\catcode`\@}%
⟨latexrelease⟩    \@currnamestack}}
⟨latexrelease⟩\else
⟨latexrelease⟩  \GenericInfo{}{Defining 2020-02-02\string\@pushfilename.}
⟨latexrelease⟩\def\@pushfilename{%
⟨latexrelease⟩  \@expl@push@filename@@
⟨latexrelease⟩  \xdef\@currnamestack{%
⟨latexrelease⟩    {\@currname}%
⟨latexrelease⟩    {\@currext}%
⟨latexrelease⟩    {\the\catcode`\@}%
⟨latexrelease⟩    \@currnamestack}%
⟨latexrelease⟩    \@expl@push@filename@aux@@}
⟨latexrelease⟩\fi
⟨latexrelease⟩\EndIncludeInRelease
\@onlypreamble\@pushfilename
```

```
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\@popfilename}%
⟨latexrelease⟩  {Add \@expl@pop@filename@@}%
\def\@popfilename{\@expl@@@hook@curr@name@pop@@
  \expandafter\@p@pfilename\@currnamestack\@nil
```

Same for popping:

```
  \expandafter\@p@pfilepath\@kernel@currpathstack\@nil
  \@expl@pop@filename@@}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/02/02}{\@popfilename}%
⟨latexrelease⟩  {Add \@expl@push@filename@@}%
⟨latexrelease⟩\def\@popfilename{\expandafter\@p@pfilename\@currnamestack\@nil
⟨latexrelease⟩  \@expl@pop@filename@@}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@popfilename}%
⟨latexrelease⟩  {Add \@expl@push@filename@@ and \@expl@push@filename@aux@@}%
⟨latexrelease⟩\ifnum\sourceLaTeXdate<20200202\relax
⟨latexrelease⟩  \GenericInfo{}{Defining 00-00-00\string\@popfilename.}
⟨latexrelease⟩\def\@popfilename{\expandafter\@p@pfilename\@currnamestack\@nil}
⟨latexrelease⟩\else
⟨latexrelease⟩  \GenericInfo{}{Defining 2020-02-02\string\@popfilename.}
```

```
⟨latexrelease⟩\def\@popfilename{\expandafter\@p@pfilename\@currnamestack\@nil
⟨latexrelease⟩   \@expl@pop@filename@@}
⟨latexrelease⟩\fi
⟨latexrelease⟩\EndIncludeInRelease
\@onlypreamble\@popfilename
```

```
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
```

```
\def\@p@pfilename#1#2#3#4\@nil{%
  \gdef\@currname{#1}%
  \gdef\@currext{#2}%
  \catcode`\@#3\relax
  \gdef\@currnamestack{#4}}
\@onlypreamble\@p@pfilename
```

```
\gdef\@currnamestack{}
\@onlypreamble\@currnamestack
```

(*End definition for* `\@pushfilename`*,* `\@popfilename`*, and* `\@currnamestack`*.*)

`\@kernel@currpathstack` Path to the current file if explicitly given. The auxiliary is needed here to insert a `\@empty` to prevent the loss of braces.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\@kernel@currpathstack}%
⟨latexrelease⟩   {Add \@kernel@currpathstack}%
```

If rolling backwards to this release, `\@kernel@currpathstack` will be defined, so the `\gdef` line should not be executed, thus the `\@gobblethree` will take it out, so the satck isn't touched.

```
⟨latexrelease⟩\@ifundefined{@kernel@currpathstack}{}{\@gobblethree}
\gdef\@kernel@currpathstack{}%
```

If rolling forward to this release, then the `\gdef` line above will define the path stack to be empty (which it can't be, inside a file), so the code below will traverse the `\@currnamestack`, and add as many empty items to `\@kernel@currpathstack` as there are items in `\@currnamestack`, so both are back in sync. Most of the time latexrelease is loaded on top-level, so only one item is needed, but platexrelease loads it internally, so the more complicated loop is needed.

```
⟨latexrelease⟩\ifx\@kernel@currpathstack\@empty
⟨latexrelease⟩   \def\reserved@a#1#2#3{%
⟨latexrelease⟩     \ifx\relax#3\else
⟨latexrelease⟩       \g@addto@macro\@kernel@currpathstack{{}}%
⟨latexrelease⟩       \expandafter\reserved@a
⟨latexrelease⟩     \fi}%
⟨latexrelease⟩   \expandafter\reserved@a\@currnamestack{}{}{\relax}%
⟨latexrelease⟩\fi
\def\@p@pfilepath#1{%
  \gdef\@currpath{#1}\@p@pfilepath@aux\@empty}
\def\@p@pfilepath@aux#1\@nil{%
  \xdef\@kernel@currpathstack{#1}}
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@kernel@currpathstack}%
```

```
⟨latexrelease⟩  {Add \@kernel@currpathstack}%
⟨latexrelease⟩\let\@kernel@currpathstack\@undefined
⟨latexrelease⟩\let\@p@pfilepath\@undefined
⟨latexrelease⟩\let\@p@pfilepath@aux\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
```

(*End definition for* `\@kernel@currpathstack`.)

`\@ptionlist` Returns the option list of the file.

```
\def\@ptionlist#1{%
  \@ifundefined{opt@#1}\@empty{\csname opt@#1\endcsname}}
%\@onlypreamble\@ptionlist
```

(*End definition for* `\@ptionlist`.)

`\@ifpackageloaded` `\@ifclassloaded`

`\@ifpackageloaded{`⟨*name*⟩`}` Checks to see whether a file has been loaded.

```
\def\@ifpackageloaded{\@ifl@aded\@pkgextension}
\def\@ifclassloaded{\@ifl@aded\@clsextension}
```

```
\def\@ifl@aded#1#2{%
  \expandafter\ifx\csname ver@#2.#1\endcsname\relax
    \expandafter\@secondoftwo
  \else
    \expandafter\@firstoftwo
  \fi}
```

(*End definition for* `\@ifpackageloaded` *and* `\@ifclassloaded`.)

`\@ifpackagelater` `\@ifclasslater`

`\@ifpackagelater{`⟨*name*⟩`}{YYYY/MM/DD}{`⟨*true code*⟩`}{`⟨*false code*⟩`}` Checks that the package loaded is more recent or equal to the given date. A better name for it would therefore been `\@ifpackagelaterorequal` but it is in use for more than 30 years, so ...

```
\def\@ifpackagelater{\@ifl@ter\@pkgextension}
\def\@ifclasslater{\@ifl@ter\@clsextension}
```

(*End definition for* `\@ifpackagelater` *and* `\@ifclasslater`.)

`\IfPackageAtLeastTF` `\IfClassAtLeastTF` `\IfFormatAtLeastTF`

`\IfFormatAtLeastTF{YYYY/MM/DD}{`⟨*true code*⟩`}{`⟨*false code*⟩`}` Test if the format is later or equal to the given date.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\IfFormatAtLeastTF}{Test format date}%
\def\IfFormatAtLeastTF{\@ifl@t@r\fmtversion}
\let\IfPackageAtLeastTF\@ifpackagelater
\let\IfClassAtLeastTF\@ifclasslater
```

For rollback pretend it was available since the beginning of dawn.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\IfFormatAtLeastTF}{Test format date}%
⟨latexrelease⟩\def\IfFormatAtLeastTF{\@ifl@t@r\fmtversion}
⟨latexrelease⟩\let\IfPackageAtLeastTF\@ifpackagelater
⟨latexrelease⟩\let\IfClassAtLeastTF\@ifclasslater
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\IfPackageAtLeastTF`, `\IfClassAtLeastTF`, *and* `\IfFormatAtLeastTF`.)

`\@ifl@ter`

```
\def\@ifl@ter#1#2{%
  \expandafter\@ifl@t@r
    \csname ver@#2.#1\endcsname}
⟨/2ekernel⟩
```

This internal macro is also used in `\NeedsTeXFormat`.

```
⟨latexrelease⟩\IncludeInRelease{2018/04/01}%
⟨latexrelease⟩                  {\@ifl@t@r}{Guard against bad input}%
⟨*2ekernel | latexrelease⟩
\def\@ifl@t@r#1#2{%
  \ifnum\expandafter\@parse@version@#1//00\@nil<%
        \expandafter\@parse@version@#2//00\@nil
    \expandafter\@secondoftwo
  \else
    \expandafter\@firstoftwo
  \fi}
\def\@parse@version@#1{\@parse@version0#1}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@ifl@t@r}{Guard against bad input}%
⟨latexrelease⟩\def\@ifl@t@r#1#2{%
⟨latexrelease⟩  \ifnum\expandafter\@parse@version#1//00\@nil<%
⟨latexrelease⟩        \expandafter\@parse@version#2//00\@nil
⟨latexrelease⟩    \expandafter\@secondoftwo
⟨latexrelease⟩  \else
⟨latexrelease⟩    \expandafter\@firstoftwo
⟨latexrelease⟩  \fi}
⟨latexrelease⟩\let\@parse@version@\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@ifl@ter`.)

```
⟨/2ekernel⟩
⟨*2ekernel | latexreleasefirst⟩
\def\@parse@version#1/#2/#3#4#5\@nil{%
\@parse@version@dash#1-#2-#3#4\@nil
}
```

The `\if` test here ensures that an argument with no `/` or `-` produces 0 (actually 00).

```
\def\@parse@version@dash#1-#2-#3#4#5\@nil{%
  \if\relax#2\relax\else#1\fi#2#3#4 }
⟨/2ekernel | latexreleasefirst⟩
⟨*2ekernel⟩
```

`\@ifpackagewith` `\@ifclasswith`

`\@ifpackagewith{`⟨*name*⟩`}{`⟨*option-list*⟩`}` Checks that ⟨*option-list*⟩ is a subset of the options **with** which ⟨*name*⟩ was loaded.

```
\def\@ifpackagewith{\@if@ptions\@pkgextension}
\def\@ifclasswith{\@if@ptions\@clsextension}
```

```
\def\@if@ptions#1#2{%
  \@expandtwoargs\@if@pti@ns{\@ptionlist{#2.#1}}}
```

Probably shouldn't use `\CurrentOption` here... (changed to `\reserved@b`.)

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2017/01/01}%
⟨latexrelease⟩                 {\@if@pti@ns}{Spaces in option clash check}%
⟨*2ekernel | latexrelease⟩
\def\@if@pti@ns#1#2{%
 \let\reserved@a\@firstoftwo
 \edef\reserved@b{\zap@space#2 \@empty}%
 \@for\reserved@b:=\reserved@b\do{%
   \ifx\reserved@b\@empty
   \else
     \expandafter\in@\expandafter{\expandafter,\reserved@b,}{,#1,}%
     \ifin@
     \else
       \let\reserved@a\@secondoftwo
     \fi
   \fi
 }%
 \reserved@a}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@if@pti@ns}{Spaces in option clash check}%
⟨latexrelease⟩\def\@if@pti@ns#1#2{%
⟨latexrelease⟩ \let\reserved@a\@firstoftwo
⟨latexrelease⟩ \@for\reserved@b:=#2\do{%
⟨latexrelease⟩  \ifx\reserved@b\@empty
⟨latexrelease⟩   \else
⟨latexrelease⟩   \expandafter\in@\expandafter
⟨latexrelease⟩                   {\expandafter,\reserved@b,}{,#1,}%
⟨latexrelease⟩    \ifin@
⟨latexrelease⟩    \else
⟨latexrelease⟩     \let\reserved@a\@secondoftwo
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩ }%
⟨latexrelease⟩ \reserved@a}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@ifpackagewith` *and* `\@ifclasswith`.)

`\IfPackageLoadedTF`
`\IfPackageLoadedWithOptionsTF`
`\IfClassLoadedTF`
`\IfClassLoadedWithOptionsTF`

More public names for the commands already available for a long time.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                 {\IfPackageLoadedtTF}{Test package loading}%
\let \IfPackageLoadedTF            \@ifpackageloaded
\let \IfClassLoadedTF              \@ifclassloaded
\let \IfPackageLoadedWithOptionsTF \@ifpackagewith
\let \IfClassLoadedWithOptionsTF   \@ifclasswith
```

For rollback pretend it was available since the beginning of dawn.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\IfPackageLoadedtTF}{Test package loading}%
⟨latexrelease⟩
⟨latexrelease⟩\let \IfPackageLoadedTF            \@ifpackageloaded
⟨latexrelease⟩\let \IfClassLoadedTF              \@ifclassloaded
⟨latexrelease⟩\let \IfPackageLoadedWithOptionsTF \@ifpackagewith
⟨latexrelease⟩\let \IfClassLoadedWithOptionsTF   \@ifclasswith
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\IfPackageLoadedTF` *and others.*)

`\ProvidesPackage` Checks that the current filename is correct, and defines `\ver@filename`.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩  {\ProvidesPackage}{Check name with \strcmp}%
⟨*2ekernel | latexrelease⟩
\def\ProvidesPackage#1{%
  \xdef\@gtempa{#1}%
```

Here `\@currpath` is explicitly added to the file name to report when a package or class is loaded using an explicit path. Loading using a path in the argument is supported but not encouraged.

```
  \@expandtwoargs\@expl@str@if@eq@@nnTF
      {\@gtempa}{\@currpath\@currname}{}{%
    \@latex@warning@no@line{You have requested
      \@cls@pkg\space`\@currpath\@currname',\MessageBreak
       but the \@cls@pkg\space provides `#1'}%
    }%
  \@ifnextchar[\@pr@videpackage{\@pr@videpackage[]}}%]
\@onlypreamble\ProvidesPackage
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
%
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩  {\ProvidesPackage}{Undo: check name with \strcmp}%
⟨latexrelease⟩\def\ProvidesPackage#1{%
⟨latexrelease⟩  \xdef\@gtempa{#1}%
⟨latexrelease⟩  \ifx\@gtempa\@currname\else
⟨latexrelease⟩    \@latex@warning@no@line{You have requested
⟨latexrelease⟩      \@cls@pkg\space`\@currname',\MessageBreak
⟨latexrelease⟩       but the \@cls@pkg\space provides `#1'}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@ifnextchar[\@pr@videpackage{\@pr@videpackage[]}}%]
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\ProvidesPackage`.)

\@pr@videpackage This is the helper command for \ProvidesPackage. It tries to be cautious when handling the identification string in case it contains UTF-8 characters.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\@pr@videpackage}{Allow for package substitution}%
\def\@pr@videpackage[#1]{%
  \expandafter\protected@xdef                 %     <-- protected...
     \csname ver@\@currname.\@currext\endcsname{#1}% Loaded package
  \expandafter\let
    \csname ver@\@currpkg@reqd\expandafter\endcsname % Requested package
    \csname ver@\@currname.\@currext\endcsname
  \ifx\@currext\@clsextension
    \typeout{Document Class: \@gtempa\space#1}%
  \else
    \protected@wlog{Package: \@gtempa\space#1}%   <--- protected
  \fi}
```

(*End definition for* \@pr@videpackage.)

\protected@wlog This is like plain TEX's \wlog but gracefully handles protected commands.

```
\long\def\protected@wlog#1{\begingroup
  \set@display@protect
  \immediate \write \m@ne {#1}\endgroup }
```

(*End definition for* \protected@wlog.)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/02/02}%
⟨latexrelease⟩                 {\@pr@videpackage}{Protection for package info}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@pr@videpackage[#1]{%
⟨latexrelease⟩  \expandafter\protected@xdef                 %     <-- protected...
⟨latexrelease⟩     \csname ver@\@currname.\@currext\endcsname{#1}%
⟨latexrelease⟩\ifx\@currext\@clsextension
⟨latexrelease⟩    \typeout{Document Class: \@gtempa\space#1}%
⟨latexrelease⟩  \else
⟨latexrelease⟩    \protected@wlog{Package: \@gtempa\space#1}%   <--- protected
⟨latexrelease⟩  \fi}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@pr@videpackage}{Protection for package info}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@pr@videpackage[#1]{%
⟨latexrelease⟩  \expandafter\xdef\csname ver@\@currname.\@currext\endcsname{#1}%
⟨latexrelease⟩  \ifx\@currext\@clsextension
⟨latexrelease⟩    \typeout{Document Class: \@gtempa\space#1}%
⟨latexrelease⟩  \else
⟨latexrelease⟩    \wlog{Package: \@gtempa\space#1}%
⟨latexrelease⟩  \fi}
⟨latexrelease⟩\let\protected@wlog\@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\@pr@videpackage
```

\ProvidesClass Like \ProvidesPackage, but for classes. This needs a dummy latexrelease block to copy the definition of \ProvidesPackage as it changes across releases.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩   {\ProvidesClass}{Track \ProvidesPackage}%
⟨*2ekernel | latexrelease⟩
\let\ProvidesClass\ProvidesPackage
\@onlypreamble\ProvidesClass
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \ProvidesClass.)

\ProvidesFile Like \ProvidesPackage, but for arbitrary files. Do not apply \@onlypreamble to these, as we may want to label files input during the document.

\@providesfile

```
\def\ProvidesFile#1{%
  \begingroup
    \catcode`\ 10 %
    \ifnum \endlinechar<256 %
      \ifnum \endlinechar>\m@ne
        \catcode\endlinechar 10 %
      \fi
    \fi
    \@makeother\/%
    \@makeother\&%

    \kernel@ifnextchar[{\@providesfile{#1}}{\@providesfile{#1}[]}}
```

During initex a special version of \@providesfile is used. The real definition is installed right at the end, in ltfinal.dtx.

```
def\@providesfile#1[#2]{%
   \wlog{File: #1 #2}%
   \expandafter\xdef\csname ver@#1\endcsname{#2}%
 \endgroup}
```

(*End definition for* \ProvidesFile *and* \@providesfile.)

\PassOptionsToPackage
\PassOptionsToClass If the package has been loaded, we check that it was first loaded with the options. Otherwise we add the option list to that of the package.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\@pass@ptions}{Raw option lists}%
⟨*2ekernel | latexrelease⟩
\def\@pass@ptions#1#2#3{%
  \@expl@@@filehook@set@curr@file@@nNN
    {\@expl@@@filehook@resolve@file@subst@@w #3.#1\@nil}%
      \reserved@a\reserved@b
  \@expl@@@filehook@clear@replacement@flag@@
  \expandafter\xdef\csname opt@\reserved@a\endcsname{%
```

```
    \@ifundefined{opt@\reserved@a}\@empty
      {\csname opt@\reserved@a\endcsname,}%
    \zap@space#2 \@empty}%
  \expandafter\let
    \csname opt@#3.#1\expandafter\endcsname
    \csname opt@\reserved@a\endcsname
```

Extend raw option list

```
    \@ifundefined{@raw@opt@#3.#1}%
      {\expandafter\gdef\csname @raw@opt@#3.#1\expandafter\endcsname
                \expandafter{#2}}%
      {\expandafter\g@addto@macro\csname @raw@opt@#3.#1\expandafter\endcsname
                \expandafter{\expandafter,#2}}%
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2020/10/01}{\@pass@ptions}
⟨latexrelease⟩  {Add file replacement in \@pass@ptions}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@pass@ptions#1#2#3{%
⟨latexrelease⟩  \@expl@@@filehook@set@curr@file@@nNN
⟨latexrelease⟩    {\@expl@@@filehook@resolve@file@subst@@w #3.#1\@nil}%
⟨latexrelease⟩      \reserved@a\reserved@b
⟨latexrelease⟩  \@expl@@@filehook@clear@replacement@flag@@
⟨latexrelease⟩  \expandafter\xdef\csname opt@\reserved@a\endcsname{%
⟨latexrelease⟩    \@ifundefined{opt@\reserved@a}\@empty
⟨latexrelease⟩      {\csname opt@\reserved@a\endcsname,}%
⟨latexrelease⟩    \zap@space#2 \@empty}%
⟨latexrelease⟩  \expandafter\let
⟨latexrelease⟩    \csname opt@#3.#1\expandafter\endcsname
⟨latexrelease⟩    \csname opt@\reserved@a\endcsname}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@pass@ptions}
⟨latexrelease⟩  {\@pass@ptions}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@pass@ptions#1#2#3{%
⟨latexrelease⟩  \expandafter\xdef\csname opt@#3.#1\endcsname{%
⟨latexrelease⟩    \@ifundefined{opt@#3.#1}\@empty
⟨latexrelease⟩      {\csname opt@#3.#1\endcsname,}%
⟨latexrelease⟩    \zap@space#2 \@empty}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
\@onlypreamble\@pass@ptions
\def\PassOptionsToPackage{\@pass@ptions\@pkgextension}
\def\PassOptionsToClass{\@pass@ptions\@clsextension}
\@onlypreamble\PassOptionsToPackage
\@onlypreamble\PassOptionsToClass
```

(*End definition for* `\PassOptionsToPackage` *and* `\PassOptionsToClass`.)

`\DeclareOption`
`\DeclareOption*`

Adds an option as a `\ds@` command, or the default `\default@ds` command.

```
\def\DeclareOption{%
```

```
  \let\@fileswith@pti@ns\@badrequireerror
  \@ifstar\@defdefault@ds\@declareoption}
\long\def\@declareoption#1#2{%
   \xdef\@declaredoptions{\@declaredoptions,#1}%
   \toks@{#2}%
   \expandafter\edef\csname ds@#1\endcsname{\the\toks@}}
\long\def\@defdefault@ds#1{%
  \toks@{#1}%
  \edef\default@ds{\the\toks@}}
\@onlypreamble\DeclareOption
\@onlypreamble\@declareoption
\@onlypreamble\@defdefault@ds
```

(*End definition for* `\DeclareOption` *and* `\DeclareOption*`.)

`\OptionNotUsed` `\@remove@eq@value`

If we are in a class file, add `\CurrentOption` to the list of unused options. Otherwise, in a package file do nothing.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\OptionNotUsed}{filter unused option list}%
⟨*2ekernel | latexrelease⟩
\def\@remove@eq@value#1=#2\@nil{#1}
```

```
\def\OptionNotUsed{%
  \ifx\@currext\@clsextension
    \xdef\@unusedoptionlist{%
      \ifx\@unusedoptionlist\@empty\else\@unusedoptionlist,\fi
      \expandafter\@remove@eq@value\CurrentOption=\@nil}%
  \fi}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\OptionNotUsed}{filter unused option list}%
⟨latexrelease⟩\let\@remove@eq@value\@undefined
```

```
⟨latexrelease⟩\def\OptionNotUsed{%
⟨latexrelease⟩   \ifx\@currext\@clsextension
⟨latexrelease⟩     \xdef\@unusedoptionlist{%
⟨latexrelease⟩       \ifx\@unusedoptionlist\@empty\else\@unusedoptionlist,\fi
⟨latexrelease⟩       \CurrentOption}%
⟨latexrelease⟩   \fi}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\OptionNotUsed
```

(*End definition for* `\OptionNotUsed` *and* `\@remove@eq@value`.)

`\default@ds`

The default option code. Set by `\@onefilewithoptions` to either `\OptionNotUsed` for classes, or `\@unknownoptionerror` for packages. This may be reset in either case with `\DeclareOption*`.

```
% \let\default@ds\OptionNotUsed
```

(*End definition for* `\default@ds`.)

\ProcessOptions
\ProcessOptions*

\ProcessOptions calls \ds@option for each known package option, then calls \default@ds for each option on the local options list. Finally resets all the declared options to \relax. The empty option does nothing, this has to be reset on the off chance it's set to \relax if an empty element gets into the \@declaredoptions list.

The star form is similar but executes options given in the order specified in the document, not the order they are declared in the file. In the case of packages, global options are executed before local ones.

```
\def\ProcessOptions{%
  \let\ds@\@empty
  \edef\@curroptions{\@ptionlist{\@currname.\@currext}}%
  \@ifstar\@xprocess@ptions\@process@ptions}
\@onlypreamble\ProcessOptions
```

```
\def\@process@ptions{%
  \@for\CurrentOption:=\@declaredoptions\do{%
    \ifx\CurrentOption\@empty\else
      \@expandtwoargs\in@{,\CurrentOption,}{%
          ,\ifx\@currext\@clsextension\else\@classoptionslist,\fi
          \@curroptions,}%
      \ifin@
        \@use@ption
        \expandafter\let\csname ds@\CurrentOption\endcsname\@empty
      \fi
    \fi}%
  \@process@pti@ns}
\@onlypreamble\@process@ptions
```

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\@xprocess@ptions}{safer @xprocess@ptions}%
⟨*2ekernel | latexrelease⟩
\def\@xprocess@ptions{%
  \ifx\@currext\@clsextension\else
   \ifx\@classoptionslist\relax\else
    \@for\CurrentOption:=\@classoptionslist\do{%
      \ifx\CurrentOption\@empty\else
        \@ifundefined{ds@\CurrentOption}{}{%
          \@use@ption
          \expandafter\let\csname ds@\CurrentOption\endcsname\@empty
        }%
      \fi}%
    \fi
  \fi
  \@process@pti@ns}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@xprocess@ptions}{safer @xprocess@ptions}%
⟨latexrelease⟩\let\@remove@eq@value\@undefined
```

```
⟨latexrelease⟩\def\@xprocess@ptions{%
⟨latexrelease⟩   \ifx\@currext\@clsextension\else
⟨latexrelease⟩     \@for\CurrentOption:=\@classoptionslist\do{%
⟨latexrelease⟩       \ifx\CurrentOption\@empty\else
```

```
⟨latexrelease⟩        \@expandtwoargs\in@{,\CurrentOption,}{,\@declaredoptions,}%
⟨latexrelease⟩        \ifin@
⟨latexrelease⟩          \@use@ption
⟨latexrelease⟩          \expandafter\let\csname ds@\CurrentOption\endcsname\@empty
⟨latexrelease⟩        \fi
⟨latexrelease⟩      \fi}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \@process@pti@ns}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\@xprocess@ptions
```

The common part of `\ProcessOptions` and `\ProcessOptions*`.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\@process@pti@ns}{Unused options issue}%
\def\@process@pti@ns{%
  \@for\CurrentOption:=\@curroptions\do{%
    \@ifundefined{ds@\CurrentOption}%
      {\@use@ption
       \default@ds}%
```

There should not be any non-empty definition of `\CurrentOption` at this point, as all the declared options were executed earlier. This is for compatibility with 2.09 styles which use `\def\ds@`... directly, and so have options which do not appear in `\@declaredoptions`.

```
      \@use@ption}%
```

Clear all the definitions for option code. First set all the declared options to `\relax`, then reset the 'default' and 'empty' options. and the lst of declared options.

```
  \@for\CurrentOption:=\@declaredoptions\do{%
    \expandafter\let\csname ds@\CurrentOption\endcsname\relax}%

  \let\CurrentOption\@empty
  \let\@fileswith@pti@ns\@@fileswith@pti@ns
  \AtEndOfPackage{\expandafter\let
                     \csname unprocessedoptions-\@currname.\@currext\endcsname
                     \relax}}
\@onlypreamble\@process@pti@ns
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\@process@pti@ns}{Unused options issue}%
⟨latexrelease⟩
⟨latexrelease⟩\def\@process@pti@ns{%
⟨latexrelease⟩  \@for\CurrentOption:=\@curroptions\do{%
⟨latexrelease⟩    \@ifundefined{ds@\CurrentOption}%
⟨latexrelease⟩      {\@use@ption
⟨latexrelease⟩       \default@ds}%
⟨latexrelease⟩      \@use@ption}%
⟨latexrelease⟩  \@for\CurrentOption:=\@declaredoptions\do{%
⟨latexrelease⟩    \expandafter\let\csname ds@\CurrentOption\endcsname\relax}%
⟨latexrelease⟩  \let\CurrentOption\@empty
⟨latexrelease⟩  \let\@fileswith@pti@ns\@@fileswith@pti@ns
⟨latexrelease⟩  \AtEndOfPackage{\let\@unprocessedoptions\relax}}
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\ProcessOptions` *and* `\ProcessOptions*`.)

`\@options` `\@options` is a synonym for `\ProcessOptions*` for upward compatibility with LaTeX2.09 style files.

```
\def\@options{\ProcessOptions*}
\@onlypreamble\@options
```

(*End definition for* `\@options`.)

`\@use@ption` Execute the code for the current option.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\@use@ption}{filter unused option list}%
⟨*2ekernel | latexrelease⟩
\def\@use@ption{%
  \@expandtwoargs\@removeelement
     {\expandafter\@remove@eq@value\CurrentOption=\@nil}%
  \@unusedoptionlist\@unusedoptionlist
  \csname ds@\CurrentOption\endcsname}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@use@ption}{filter unused option list}%
⟨latexrelease⟩\def\@use@ption{%
⟨latexrelease⟩  \@expandtwoargs\@removeelement\CurrentOption
⟨latexrelease⟩  \@unusedoptionlist\@unusedoptionlist
⟨latexrelease⟩  \csname ds@\CurrentOption\endcsname}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\@use@ption
```

(*End definition for* `\@use@ption`.)

`\ExecuteOptions` `\ExecuteOptions{`⟨*option-list*⟩`}` executes the code declared for each option.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2017/01/01}%
⟨latexrelease⟩                  {\ExecuteOptions}{Spaces in \ExecuteOptions}%
⟨*2ekernel | latexrelease⟩
\def\ExecuteOptions#1{%
```

Use `\@fortmp` here as it is anyway cleared during `\@for` loop so does not change any existing names.

```
  \edef\@fortmp{\zap@space#1 \@empty}%
  \def\reserved@a##1\@nil{%
    \@for\CurrentOption:=\@fortmp\do
             {\csname ds@\CurrentOption\endcsname}%
    \edef\CurrentOption{##1}}%
  \expandafter\reserved@a\CurrentOption\@nil}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
```

```
⟨latexrelease⟩                  {\ExecuteOptions}{Spaces in \ExecuteOptions}%
⟨latexrelease⟩\def\ExecuteOptions#1{%
⟨latexrelease⟩  \def\reserved@a##1\@nil{%
⟨latexrelease⟩    \@for\CurrentOption:=#1\do
⟨latexrelease⟩              {\csname ds@\CurrentOption\endcsname}%
⟨latexrelease⟩    \edef\CurrentOption{##1}}%
⟨latexrelease⟩  \expandafter\reserved@a\CurrentOption\@nil}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
\@onlypreamble\ExecuteOptions
```

(*End definition for* `\ExecuteOptions`.)

The top-level commands, which just set some parameters then call the internal command, `\@fileswithoptions`.

`\documentclass` The main new-style class declaration.

```
\def\documentclass{%
  \let\documentclass\@twoclasseserror
  \if@compatibility\else\let\usepackage\RequirePackage\fi
  \@fileswithoptions\@clsextension}
\@onlypreamble\documentclass
```

(*End definition for* `\documentclass`.)

`\documentstyle` 2.09 style class 'style' declaration.

```
\def\documentstyle{%
  \makeatletter\input{latex209.def}\makeatother
  \documentclass}
\@onlypreamble\documentstyle
```

(*End definition for* `\documentstyle`.)

`\RequirePackage` Load package if not already loaded.

```
\def\RequirePackage{%
  \@fileswithoptions\@pkgextension}
\@onlypreamble\RequirePackage
```

(*End definition for* `\RequirePackage`.)

`\LoadClass` Load class.

```
\def\LoadClass{%
  \ifx\@currext\@pkgextension
     \@latex@error
      {\noexpand\LoadClass in package file}%
      {You may only use \noexpand\LoadClass in a class file.}%
  \fi
  \@fileswithoptions\@clsextension}
\@onlypreamble\LoadClass
```

(*End definition for* `\LoadClass`.)

`\@loadwithoptions` Pass the current option list on to a class or package. `#1` is `\@`*cls-or-pkg*`extension`, `#2` is `\RequirePackage` or `\LoadClass`, `#3` is the class or package to be loaded.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                 {\@loadwithoptions}{Raw option lists load with options}%
⟨*2ekernel | latexrelease⟩
\def\@loadwithoptions#1#2#3{%
  \expandafter\let\csname opt@#3.#1\expandafter\endcsname
       \csname opt@\@currname.\@currext\endcsname
  \expandafter\let\csname @raw@opt@#3.#1\expandafter\endcsname
       \csname @raw@opt@\@currname.\@currext\endcsname
   #2{#3}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}
⟨latexrelease⟩                 {\@loadwithoptions}{Raw option lists load with options}%
⟨latexrelease⟩\def\@loadwithoptions#1#2#3{%
⟨latexrelease⟩  \expandafter\let\csname opt@#3.#1\expandafter\endcsname
⟨latexrelease⟩       \csname opt@\@currname.\@currext\endcsname
⟨latexrelease⟩   #2{#3}}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\@loadwithoptions
```

(*End definition for* `\@loadwithoptions`.)

`\LoadClassWithOptions` Load class '`#1`' with the current option list.

```
\def\LoadClassWithOptions{%
  \@loadwithoptions\@clsextension\LoadClass}
\@onlypreamble\LoadClassWithOptions
```

(*End definition for* `\LoadClassWithOptions`.)

`\RequirePackageWithOptions` Load package '`#1`' with the current option list.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                 {\RequirePackageWithOptions}{Unused options issue}%
\def\RequirePackageWithOptions{%
```

The resetting of the unprocessed options is now done on a par package basis.

```
  \AtEndOfPackage{\expandafter\let
                   \csname unprocessedoptions-\@currname.\@currext\endcsname
                   \relax}%
  \@loadwithoptions\@pkgextension\RequirePackage}
\@onlypreamble\RequirePackageWithOptions
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\RequirePackageWithOptions}{Unused options issue}%
⟨latexrelease⟩
⟨latexrelease⟩\def\RequirePackageWithOptions{%
⟨latexrelease⟩  \AtEndOfPackage{\let\@unprocessedoptions\relax}%
```

```
⟨latexrelease⟩  \@loadwithoptions\@pkgextension\RequirePackage}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\RequirePackageWithOptions`.)

`\usepackage` To begin with, `\usepackage` produces an error. This is reset by `\documentclass`.

```
\def\usepackage#1#{%
  \@latex@error
    {\noexpand \usepackage before \string\documentclass}%
    {\noexpand \usepackage may only appear in the document
      preamble, i.e.,\MessageBreak
      between \noexpand\documentclass and
      \string\begin{document}.}%
  \@gobble}
\@onlypreamble\usepackage
```

(*End definition for* `\usepackage`.)

`\NeedsTeXFormat` Check that the document is running on the correct system.

```
\def\NeedsTeXFormat#1{%
  \def\reserved@a{#1}%
  \ifx\reserved@a\fmtname
    \expandafter\@needsformat
  \else
     \@latex@error{This file needs format ‘\reserved@a’%
       \MessageBreak but this is ‘\fmtname’}{%
       The current input file will not be processed
       further,\MessageBreak
       because it was written for some other flavor of
       TeX.\MessageBreak\@ehd}%
```

If the file is not meant to be processed by LaTeX 2_ε we stop inputting it, but we do not end the run. We just end inputting the current file.

```
     \endinput \fi}
\@onlypreamble\NeedsTeXFormat
```

```
\def\@needsformat{%
  \@ifnextchar[%]
    \@needsf@rmat
    {}}
\@onlypreamble\@needsformat
```

```
\def\@needsf@rmat[#1]{%
    \@ifl@t@r\fmtversion{#1}{}%
    {\@latex@warning@no@line
        {You have requested release ‘#1’ of LaTeX,\MessageBreak
         but only release ‘\fmtversion’ is available}}}
\@onlypreamble\@needsf@rmat
```

(*End definition for* `\NeedsTeXFormat`.)

`\zap@space` `\zap@space foo`⟨*space*⟩`\@empty` removes all spaces from `foo` that are not protected by `{ }` groups.

```
\def\zap@space#1 #2{%
  #1%
```

```
  \ifx#2\@empty\else\expandafter\zap@space\fi
  #2}
```

(*End definition for* \zap@space.)

\@fileswithoptions The common part of \documentclass and \usepackage.

```
\def\@fileswithoptions#1{%
  \@ifnextchar[%]
    {\@fileswith@ptions#1}%
    {\@fileswith@ptions#1[]}}
\@onlypreamble\@fileswithoptions
```

```
\def\@fileswith@ptions#1[#2]#3{%
  \@ifnextchar[%]
  {\@fileswith@pti@ns#1[{#2}]#3}%
  {\@fileswith@pti@ns#1[{#2}]#3[]}}
\@onlypreamble\@fileswith@ptions
```

Then we do some work.

First of all, we define the global variables. Then we look to see if the file has already been loaded. If it has, we check that it was first loaded with at least the current options. If it has not, we add the current options to the package options, set the default version to be 0000/00/00, and load the file if we can find it. Then we check the version number.

Finally, we restore the old file name, reset the default option, and we set the catcode of @.

For classes, we can immediately process the file. For other types, #2 could be a comma separated list, so loop through, processing each one separately.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩        {\@fileswith@pti@ns}{ifx tests in \@fileswith@pti@ns}%
⟨*2ekernel | latexrelease⟩
\def\@fileswith@pti@ns#1[#2]#3[#4]{%
  \ifx#1\@clsextension
    \ifx\@classoptionslist\relax
      \xdef\@classoptionslist{\zap@space#2 \@empty}%
```

Save raw class list.

```
      \gdef\@raw@classoptionslist{#2}%
```

```
      \def\reserved@a{%
        \@onefilewithoptions#3[{#2}][{#4}]#1%
        \@documentclasshook}%
    \else
      \def\reserved@a{%
        \@onefilewithoptions#3[{#2}][{#4}]#1}%
    \fi
  \else
```

build up a list of calls to \@onefilewithoptions (one for each package) without thrashing the parameter stack.

```
    \def\reserved@b##1,{%
```

If #1 is \@nnil we have reached the end of the list (older version used \@nil here but \@nil is undefined so \ifx equal to all undefined commands)

```
      \ifx\@nnil##1\relax\else
```

If `\ifx\@nnil##1\@nnil` is true then `#1` is (presumably) empty (Older code used `\relax` which is slightly easier to get into `#1` by mistake, which would spoil this test.)

```
        \ifx\@nnil##1\@nnil\else
         \noexpand\@onefilewithoptions##1[{\unexpanded{#2}}][{#4}]%
         \noexpand\@pkgextension
        \fi
        \expandafter\reserved@b
      \fi}%
      \edef\reserved@a{\zap@space#3 \@empty}%
      \edef\reserved@a{\expandafter\reserved@b\reserved@a,\@nnil,}%
  \fi
  \reserved@a}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2017/01/01}%
⟨latexrelease⟩        {\@fileswith@pti@ns}{ifx tests in \@fileswith@pti@ns}%
⟨latexrelease⟩\def\@fileswith@pti@ns#1[#2]#3[#4]{%
⟨latexrelease⟩  \ifx#1\@clsextension
⟨latexrelease⟩    \ifx\@classoptionslist\relax
⟨latexrelease⟩      \xdef\@classoptionslist{\zap@space#2 \@empty}%
⟨latexrelease⟩      \def\reserved@a{%
⟨latexrelease⟩        \@onefilewithoptions#3[{#2}][{#4}]#1%
⟨latexrelease⟩        \@documentclasshook}%
⟨latexrelease⟩    \else
⟨latexrelease⟩      \def\reserved@a{%
⟨latexrelease⟩        \@onefilewithoptions#3[{#2}][{#4}]#1}%
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \def\reserved@b##1,{%
⟨latexrelease⟩      \ifx\@nnil##1\relax\else
⟨latexrelease⟩        \ifx\@nnil##1\@nnil\else
⟨latexrelease⟩         \noexpand\@onefilewithoptions##1[{#2}][{#4}]%
⟨latexrelease⟩         \noexpand\@pkgextension
⟨latexrelease⟩        \fi
⟨latexrelease⟩        \expandafter\reserved@b
⟨latexrelease⟩      \fi}%
⟨latexrelease⟩      \edef\reserved@a{\zap@space#3 \@empty}%
⟨latexrelease⟩      \edef\reserved@a{\expandafter\reserved@b\reserved@a,\@nnil,}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \reserved@a}
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩        {\@fileswith@pti@ns}{ifx tests in \@fileswith@pti@ns}%
⟨latexrelease⟩\def\@fileswith@pti@ns#1[#2]#3[#4]{%
⟨latexrelease⟩  \ifx#1\@clsextension
⟨latexrelease⟩    \ifx\@classoptionslist\relax
⟨latexrelease⟩      \xdef\@classoptionslist{\zap@space#2 \@empty}%
⟨latexrelease⟩      \def\reserved@a{%
⟨latexrelease⟩        \@onefilewithoptions#3[{#2}][{#4}]#1%
⟨latexrelease⟩        \@documentclasshook}%
⟨latexrelease⟩    \else
⟨latexrelease⟩      \def\reserved@a{%
⟨latexrelease⟩        \@onefilewithoptions#3[{#2}][{#4}]#1}%
```

```
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \else
⟨latexrelease⟩    \def\reserved@b##1,{%
⟨latexrelease⟩      \ifx\@nil##1\relax\else
⟨latexrelease⟩        \ifx\relax##1\relax\else
⟨latexrelease⟩         \noexpand\@onefilewithoptions##1[{#2}][{#4}]%
⟨latexrelease⟩         \noexpand\@pkgextension
⟨latexrelease⟩        \fi
⟨latexrelease⟩        \expandafter\reserved@b
⟨latexrelease⟩      \fi}%
⟨latexrelease⟩      \edef\reserved@a{\zap@space#3 \@empty}%
⟨latexrelease⟩      \edef\reserved@a{%
⟨latexrelease⟩        \expandafter\reserved@b\reserved@a,\@nil,}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \reserved@a}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\@onlypreamble\@fileswith@pti@ns
```

This macro is used when loading packages or classes.

`\load@onefilewithoptions` Have the main argument as `#1`, so we only need one `\expandafter` above.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩      {\@onefilewithoptions}{Hooks and unused options issue}%
\def\@onefilewithoptions#1[#2][#3]#4{%
```

We have to sanitise file names, so that something like

```
\usepackage{some/local/path/array}
\usepackage{array}
```

won't load `array.sty` twice. It is remotely possible that those are two different files, but as a matter of principles, we will consider that the base file name uniquely identifies a package, regardless of where it lives. This assumption already holds for file hooks, for example, which address the hook to a file by its base name only.

We'll use `\@expl@@@filehook@set@curr@file@@nNN` to parse the file name and return the ⟨*path*⟩ and ⟨*base+ext*⟩ in separate token lists. Further ahead, most operations use `\@currname` which doesn't have a path attached to it; only few actions prepend `\@currpath` to `\@currname` (namely loading, as we have to respect the given path).

A file substituiton isn't followed just yet because at this point we are parsing user input, so the file is still what the user asked for, and not the file actually loaded.

```
  \@expl@@@filehook@set@curr@file@@nNN{#1.#4}\reserved@a\reserved@b
  \edef\reserved@c{\def\noexpand\reserved@c####1%
    \detokenize\expandafter{\expanded{.#4}}%
    \noexpand\@nil{\def\noexpand\reserved@a{####1}}}\reserved@c
  \expandafter\reserved@c\reserved@a\@nil
  \@pushfilename
  \xdef\@currname{\string@makeletter\reserved@a}%
  \xdef\@currpath{\ifx\reserved@b\@empty\else\reserved@b/\fi}%
  \global\let\@currext#4%
```

The command \ver@⟨*file*⟩.⟨*ext*⟩ is used to signal that a package is already loaded, either because it is in fact loaded, or because it's loading was suppressed. In minimal installations, said package may not exist but still have its loading suppressed with \ver@⟨*file*⟩.⟨*ext*⟩, so before checking if the file exists we have to check that we do need to load it with \@ifl@aded. If we don't, then there's no point in checking for a typo or load-disabling.

```
\@ifl@aded\@currext\@currname
```

In the current preferred approach, a key family name will exist for processing using ltkeys. In that case, we replace the previous package options with the new ones, then call the key handler. Otherwise, we use the more classical clash handler.

```
  {%
    \@ifundefined{opt@fam@\@currname.\@currext}
      {\@onefilewithoptions@clashchk{#2}}
      {%
        \@namedef{opt@\@currname.\@currext}{#2}%
        \expandafter\expandafter\expandafter\ProcessKeyOptions
          \expandafter\expandafter\expandafter
            [\csname opt@fam@\@currname.\@currext\endcsname]%
      }%
  }%
  {\makeatletter
```

The next line seems to be necessary for 2.09 compatibility (the way the code is written there) This seems questionable and should be look at as in 2e it is definitely unnecessary at this point!

```
    \@reset@ptions
```

First we take the ⟨*name*⟩ and ⟨*ext*⟩ given in the argument and check if the file exists, and issue an error otherwise asking for a correction with \@missingfileerror. For checking if the file exists we use \@currpath (usually empty) before \@currname.

```
    \IfFileExists{\@currpath\@currname.\@currext}{}%
      {\@missing@onefilewithoptions{#2}}%
```

If \@currname is empty (the user replied to the "Enter file name" prompt with ⟨*RETURN*⟩), so stop here (do \@popfilename to pop the item just added above).

This \@gobble omits the date check at the end.

```
    \ifx\@currname\@empty
      \expandafter\@gobble
    \else
```

If the file exists, check if it was load-prevented, and otherwise do the bookkeeping with \@filehook@file@push then call \set@curr@file to set \@curr@file (and do any required substitution), then actually load the class/package with \load@onefile@withoptions. \set@curr@file also needs the file path.

```
      \@disable@packageload@do{\@currname.\@currext}%
        {\@expl@@@filehook@file@push@@
         \set@curr@file{\@currpath\@currname.\@currext}%
         \@filehook@set@CurrentFile
```

The \set@curr@file line above might have replaced the file, so \@currname and \@currext may no longer hold the actual package being loaded, so in that case we need to update these two token lists (\@curr@file holds the file name after replacement, so we parse that).

The requested file is saved in \@currpkg@reqd to be used in \InputIfFileExists later: if the updated \@currname and \@currext are used we lose track of the substitution, so \CurrentFile and \CurrentFileUsed will be (incorrectly) the same.

```
          \expandafter\@swaptwoargs\expandafter
            {\expandafter{\@currpkg@reqd}}%
            {% <
```

\@currpkg@reqd doesn't take a path because it is used later to assign \opt@... and \ver@....

```
          \edef\@currpkg@reqd{\@currname.\@currext}%
          \ifx\CurrentFile\CurrentFileUsed
          \else
            \filename@parse\@curr@file
            \edef\@currpath{\string@makeletter\filename@area}%
            \edef\@currname{\string@makeletter\filename@base}%
            \edef\@currext{\string@makeletter\filename@ext}%
          \fi
          \load@onefile@withoptions{#2}%
          \def\@currpkg@reqd%{\@currpkg@reqd}
            }% >
```

Now just clean up and exit.

```
          \@expl@@@filehook@file@pop@@}%
        \expandafter\@firstofone
      \fi}%
```

Except in the case where \@currname is empty, the date is checked against the date marked in the package file:

```
    {\@ifl@ter\@currext{\@currname}{#3}{}%
      {\@latex@warning@no@line
        {You have requested,\on@line,
         version\MessageBreak
           `#3' of \@cls@pkg\space \@currname,\MessageBreak
         but only version\MessageBreak
          `\csname ver@\@currname.\@currext\endcsname'\MessageBreak
         is available}}%

     \ifx\@currext\@clsextension\let\LoadClass\@twoloadclasserror\fi}%
    \@popfilename
    \@reset@ptions}
```

If the package is already loaded, check that there were no option clashes.

```
\def\@onefilewithoptions@clashchk#1{%
  \@if@ptions\@currext{\@currname}{#1}{}%
      {\@latex@error
        {Option clash for \@cls@pkg\space \@currname}%
        {The package \@currname\space has already been loaded
         with options:\MessageBreak
         \space\space[\@ptionlist{\@currname.\@currext}]\MessageBreak
         There has now been an attempt to load it
          with options\MessageBreak
         \space\space[#1]\MessageBreak
         Adding the global options:\MessageBreak
         \space\space
```

\@onefilewithoptions@clashchk

```
              \@ptionlist{\@currname.\@currext},#1\MessageBreak
         to your \noexpand\documentclass declaration may fix this.%
         \MessageBreak
         Try typing \space <return> \space to proceed.}}%
     \@firstofone}
```

```
\let\@currpkg@reqd\@empty
\@onlypreamble\@onefilewithoptions
```

The kernel no longer uses `\@unprocessedoptions`

```
\let\@unprocessedoptions\@undefined
```

Now the action taken when a file is not found. Path must be included here as it eventually leads to a file lookup.

`\@missing@onefilewithoptions`

```
\def\@missing@onefilewithoptions#1{%
  \@missingfileerror{\@currpath\@currname}\@currext
  \global\let\@currpath\@missingfile@area
  \global\let\@currname\@missingfile@base
  \global\let\@currext\@missingfile@ext}
```

Now the code that actually does the file loading:

`\load@onefile@withoptions`

```
\def\load@onefile@withoptions#1{%
  \let\CurrentOption\@empty
  \@reset@ptions
```

Grab everything in a macro, so the parameter stack is popped before any processing begins.

```
  \def\reserved@a{%
    \@pass@ptions\@currext{#1}{\@currname}%
    \expandafter\let
      \csname opt@\@currpkg@reqd\expandafter\endcsname
      \csname opt@\@currname.\@currext\endcsname
    \expandafter\let
      \csname @raw@opt@\@currpkg@reqd\expandafter\endcsname
      \csname @raw@opt@\@currname.\@currext\endcsname
    \global\expandafter
    \let\csname ver@\@currname.\@currext\endcsname\@empty
```

We initialize `\...-h@@k` here and only if we load the file so that it remains undefined otherwise.

```
    \expandafter\let\csname\@currname.\@currext-h@@k\endcsname\@empty
```

When the current extension is `\@pkgextension` we are loading a package otherwise, if it is `\@clsextension`, a class, so depending on that we execute different hooks. If the extension is neither, then it is another type of file without special hooks.

```
%----------------------------------------
    \ifx\@currext\@pkgextension
      \UseHook{package/before}%
      \UseOneTimeHook{package/\@currname/before}%
    \else
      \ifx\@currext\@clsextension
        \UseHook{class/before}%
        \UseOneTimeHook{class/\@currname/before}%
      \fi
    \fi
```

Now actually load the file (at this point we are certain it exists, but use `\InputIfFileExists` so that file hooks are executed). `\@currpath` is needed here too.

```
    \InputIfFileExists{\@currpath\@currpkg@reqd}{}%
      {\@latex@error
        {The \@cls@pkg\space\@currpkg@reqd\space failed to load}\@ehd}%
%----------------------------------------
```

In older versions of the code `\@unprocessedoptions` would generate an error for each specified option in a package unless a `\ProcessOptions` has appeared in the package file.

This has changed in 2020. We now use a separate macro per package to avoid interference in case of nested packages. The whole code for handling this issue (GitHub 22) was provided by Hironobu Yamashita, thanks for that.

```
    \expandafter\let\csname unprocessedoptions-\@currname.\@currext\endcsname
                    \@@unprocessedoptions
    \csname\@currname.\@currext-h@@k\endcsname
    \expandafter\let\csname\@currname.\@currext-h@@k\endcsname
              \@undefined
```

Catch the case where the packages has handled the options and redefined `\@unprocessedoptions` to `\relax` (old interface). In that case no error should be produced.

```
    \ifx\@unprocessedoptions\relax
      \let\@unprocessedoptions\@undefined
```

Otherwise run the per package set of unused options.

```
    \else
      \csname unprocessedoptions-\@currname.\@currext\endcsname
    \fi
```

In either case we drop the macro afterwards as it is no longer needed.

```
    \expandafter\let
        \csname unprocessedoptions-\@currname.\@currext\endcsname
       \@undefined
```

And same procedure, James, when we are finished loading, except that the hook order is now reversed.

```
%----------------------------------------
    \ifx\@currext\@pkgextension
      \UseOneTimeHook{package/\@currname/after}%
      \UseHook{package/after}%
    \else
      \ifx\@currext\@clsextension
        \UseOneTimeHook{class/\@currname/after}%
        \UseHook{class/after}%
      \fi
    \fi}%
%----------------------------------------
  \@ifl@aded\@currext\@currname{}{\reserved@a}}
```

Now declare the non-generic package and class hooks used above:

```
\NewHook{package/before}
\NewHook{class/before}
\NewReversedHook{package/after}
\NewReversedHook{class/after}
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩      {\@onefilewithoptions}{Hooks and unused options issue}%
⟨latexrelease⟩
```

Because of the way `\@onfilewithoptions` is changed for rollback handling below we have to define `\load@onefilewithoptions` when rolling back!

```
⟨latexrelease⟩\def\load@onefilewithoptions#1[#2][#3]#4{%
⟨latexrelease⟩  \@pushfilename
⟨latexrelease⟩  \xdef\@currname{#1}%
⟨latexrelease⟩  \global\let\@currext#4%
⟨latexrelease⟩  \let\CurrentOption\@empty
⟨latexrelease⟩  \@reset@ptions
⟨latexrelease⟩  \makeatletter
⟨latexrelease⟩  \def\reserved@a{%
⟨latexrelease⟩    \@ifl@aded\@currext{#1}%
⟨latexrelease⟩      {\@if@ptions\@currext{#1}{#2}{}%
⟨latexrelease⟩        {\@latex@error
⟨latexrelease⟩            {Option clash for \@cls@pkg\space #1}%
⟨latexrelease⟩            {The package #1 has already been loaded
⟨latexrelease⟩             with options:\MessageBreak
⟨latexrelease⟩             \space\space[\@ptionlist{#1.\@currext}]\MessageBreak
⟨latexrelease⟩             There has now been an attempt to load it
⟨latexrelease⟩              with options\MessageBreak
⟨latexrelease⟩             \space\space[#2]\MessageBreak
⟨latexrelease⟩             Adding the global options:\MessageBreak
⟨latexrelease⟩             \space\space
⟨latexrelease⟩                  \@ptionlist{#1.\@currext},#2\MessageBreak
⟨latexrelease⟩             to your \noexpand\documentclass declaration may fix this.%
⟨latexrelease⟩             \MessageBreak
⟨latexrelease⟩             Try typing \space <return> \space to proceed.}}}%
⟨latexrelease⟩      {\@pass@ptions\@currext{#2}{#1}%
⟨latexrelease⟩       \global\expandafter
⟨latexrelease⟩       \let\csname ver@\@currname.\@currext\endcsname\@empty
⟨latexrelease⟩       \expandafter\let\csname\@currname.\@currext-h@@k\endcsname\@empty
⟨latexrelease⟩       \InputIfFileExists
⟨latexrelease⟩         {\@currname.\@currext}%
⟨latexrelease⟩         {}%
⟨latexrelease⟩         {\@missingfileerror\@currname\@currext}%
⟨latexrelease⟩    \let\@unprocessedoptions\@@unprocessedoptions
⟨latexrelease⟩    \csname\@currname.\@currext-h@@k\endcsname
⟨latexrelease⟩    \expandafter\let\csname\@currname.\@currext-h@@k\endcsname
⟨latexrelease⟩              \@undefined
⟨latexrelease⟩    \@unprocessedoptions}%
⟨latexrelease⟩    \@ifl@ter\@currext{#1}{#3}{}%
⟨latexrelease⟩      {\@latex@warning@no@line
⟨latexrelease⟩         {You have requested,\on@line,
⟨latexrelease⟩          version\MessageBreak
⟨latexrelease⟩            ‘#3’ of \@cls@pkg\space #1,\MessageBreak
⟨latexrelease⟩          but only version\MessageBreak
⟨latexrelease⟩           ‘\csname ver@#1.\@currext\endcsname’\MessageBreak
⟨latexrelease⟩          is available}}%
⟨latexrelease⟩    \ifx\@currext\@clsextension\let\LoadClass\@twoloadclasserror\fi
```

```
⟨latexrelease⟩     \@popfilename
⟨latexrelease⟩     \@reset@ptions}%
⟨latexrelease⟩   \reserved@a}
⟨latexrelease⟩
⟨latexrelease⟩\let \load@onefile@withoptions    \@undefined
⟨latexrelease⟩\let \@missing@onefilewithoptions \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@fileswithoptions` *and others.*)

`\@@fileswith@pti@ns` Save the definition (for error checking).

```
\let\@@fileswith@pti@ns\@fileswith@pti@ns
\@onlypreamble\@@fileswith@pti@ns
```

(*End definition for* `\@@fileswith@pti@ns`.)

`\@reset@ptions` Reset the default option, and clear lists of declared options.

```
\def\@reset@ptions{%
  \global\ifx\@currext\@clsextension
    \let\default@ds\OptionNotUsed
   \else
    \let\default@ds\@unknownoptionerror
  \fi
  \global\let\ds@\@empty
  \global\let\@declaredoptions\@empty}
\@onlypreamble\@reset@ptions
```

(*End definition for* `\@reset@ptions`.)

4.1 Hooks

Allow code to be saved to be executed at specific later times.

Save things in macros, I considered using toks registers, (and `\addto@hook` from the NFSS code, that would require stacking the contents in the case of required packages, so just generate a new macro for each package.

`\@begindocumenthook` `\@enddocumenthook` Stuff to appear at the beginning or end of the document.

```
\ifx\@begindocumenthook\@undefined
  \let\@begindocumenthook\@empty
\fi
\let\@enddocumenthook\@empty
```

(*End definition for* `\@begindocumenthook` *and* `\@enddocumenthook`.)

`\AtEndOfPackage` `\AtEndOfClass` `\AtBeginDocument` `\AtEndDocument` The access functions.

```
\def\AtEndOfPackage{%
  \expandafter\g@addto@macro\csname\@currname.\@currext-h@@k\endcsname}
\let\AtEndOfClass\AtEndOfPackage
\@onlypreamble\AtEndOfPackage
\@onlypreamble\AtEndOfClass
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\AtBeginDocument}{Use hook system}%
\DeclareRobustCommand\AtBeginDocument{\AddToHook{begindocument}}
\DeclareRobustCommand\AtEndDocument  {\AddToHook{enddocument}}
%\DeclareRobustCommand\AtEndDocument {\AddToHook{env/document/end}} % alternative impl
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\AtBeginDocument}{Use hook system}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand\AtBeginDocument{\g@addto@macro\@begindocumenthook}
⟨latexrelease⟩\DeclareRobustCommand\AtEndDocument{\g@addto@macro\@enddocumenthook}
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
\@onlypreamble\AtBeginDocument
```

(*End definition for* `\AtEndOfPackage` *and others.*)

`\@cls@pkg` The current file type.

```
\def\@cls@pkg{%
  \ifx\@currext\@clsextension
    document class%
  \else
    package%
  \fi}
\@onlypreamble\@cls@pkg
```

(*End definition for* `\@cls@pkg`.)

`\@unknownoptionerror` Bad option.

```
\def\@unknownoptionerror{%
  \@latex@error
    {Unknown option `\CurrentOption' for \@cls@pkg\space`\@currname'}%
    {The option `\CurrentOption' was not declared in
     \@cls@pkg\space`\@currname', perhaps you\MessageBreak
      misspelled its name.
     Try typing \space <return>
     \space to proceed.}}
\@onlypreamble\@unknownoptionerror
```

(*End definition for* `\@unknownoptionerror`.)

`\@@unprocessedoptions` Declare an error for each option, unless a `\ProcessOptions` occurred.

```
\def\@@unprocessedoptions{%
  \ifx\@currext\@pkgextension
    \edef\@curroptions{\@ptionlist{\@currname.\@currext}}%
    \@for\CurrentOption:=\@curroptions\do{%
        \ifx\CurrentOption\@empty\else\@unknownoptionerror\fi}%
  \fi}
\@onlypreamble\@unprocessedoptions
\@onlypreamble\@@unprocessedoptions
```

(*End definition for* `\@@unprocessedoptions`.)

`\@badrequireerror` `\RequirePackage` or `\LoadClass` occurs in the options section.

```
\def\@badrequireerror#1[#2]#3[#4]{%
  \@latex@error
    {\noexpand\RequirePackage or \noexpand\LoadClass
         in Options Section}%
    {The \@cls@pkg\space '\@currname' is defective.\MessageBreak
     It attempts to load '#3' in the options section, i.e.,\MessageBreak
     between \noexpand\DeclareOption and \string\ProcessOptions.}}
\@onlypreamble\@badrequireerror
```

(*End definition for* `\@badrequireerror`.)

`\@twoloadclasserror` Two `\LoadClass` in a class.

```
\def\@twoloadclasserror{%
  \@latex@error
    {Two \noexpand\LoadClass commands}%
    {You may only use one \noexpand\LoadClass in a class file}}
\@onlypreamble\@twoloadclasserror
```

(*End definition for* `\@twoloadclasserror`.)

`\@twoclasseserror` Two `\documentclass` or `\documentstyle`.

```
\def\@twoclasseserror#1#{%
  \@latex@error
    {Two \noexpand\documentclass or \noexpand\documentstyle commands}%
    {The document may only declare one class.}\@gobble}
\@onlypreamble\@twoclasseserror
```

(*End definition for* `\@twoclasseserror`.)

4.2 Providing shipment

`\two@digits` Prefix a number less than 10 with '0'.

```
\def\two@digits#1{\ifnum#1<10 0\fi\number#1}
```

(*End definition for* `\two@digits`.)

`filecontents` `filecontents*` `\endfilecontents` This environment implements inline files. The star-form does not write extra comments into the file.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\filec@ntents}{Define \q@curr@file directly (gh/220)}%
%
```

We use `@tempswa` to mean no preamble writing and reuse `@filesw` to indicate no overwriting:

```
\def\filecontents{\@tempswatrue\@fileswtrue
  \@ifnextchar[\filec@ntents@opt\filec@ntents
}
\@namedef{filecontents*}{\@tempswafalse\@fileswtrue
  \@ifnextchar[\filec@ntents@opt\filec@ntents
}
```

To handle the optional argument we execute for each option the command `\filec@ntents@OPTION` if it exist or complain about unknown option.

```
\def\filec@ntents@opt[#1]{%
  \edef\@fortmp{\zap@space#1 \@empty}%
  \@for\reserved@a:=\@fortmp\do{%
    \ifcsname filec@ntents@\reserved@a\endcsname
      \csname filec@ntents@\reserved@a\endcsname
    \else
    \@latex@error{Unknown filecontents option \reserved@a}%
       {Valid options are force (or overwrite), nosearch, noheader}%
    \fi}%
  \filec@ntents
}
```

Option `force` (or `overwrite`) changes the overwriting switch

```
\let\filec@ntents@force\@fileswfalse
\let\filec@ntents@overwrite\@fileswfalse  % alternative name
```

and option `noheader` the preamble switch (which is equivalent to using the star form of the environment).

```
\let\filec@ntents@noheader\@tempswafalse
```

Option `nosearch` only checks the current directory not the whole TEX tree for the existence of the file to write.

```
\def\filec@ntents@nosearch{%
  \let\filec@ntents@checkdir\@currdir
  \def\filec@ntents@where{in current directory}}
```

By default we search the whole tree:

```
\let\filec@ntents@checkdir\@empty
\def\filec@ntents@where{exists on the system}
```

```
\begingroup%
\@tempcnta=1
\loop
  \catcode\@tempcnta=12  %
  \advance\@tempcnta\@ne %
\ifnum\@tempcnta<32      %
\repeat                  %
\catcode`\*=11 %
\catcode`\^^M\active%
\catcode`\^^L\active\let^^L\relax%
\catcode`\^^I\active%

\gdef\filec@ntents#1{%
  \set@curr@file{\filec@ntents@checkdir#1}%
  \edef\q@curr@file{"\@curr@file"}%
```

LuaTEX has more writes (and 18 is safe here).

```
  \chardef\reserved@c\ifx\directlua\@undefined 15 \else 127 \fi%
  \openin\@inputcheck\q@curr@file \space %
  \ifeof\@inputcheck%
    \@latex@note@no@line%
        {Writing file `\@currdir\@curr@file'}%
```

```
    \ch@ck7\reserved@c\write\relax%
    \immediate\openout\reserved@c\q@curr@file\relax%
  \else%
```

```
    \if@filesw%
      \@latex@note@no@line%
          {File `\@curr@file' already \filec@ntents@where.\MessageBreak%
             Not generating it from this source}%
      \let\write\@gobbletwo%
      \let\closeout\@gobble%
    \else%
```

If we are overwriting, we try to make sure that the user is not by mistake overwriting the input file (`\jobname`). Of course, this only works for input files ending in `.tex`. If a different extension is used there is no way to see that we are overwriting ourselves!

```
      \edef\reserved@b{\detokenize\expandafter{\jobname}}%
      \ifx\@curr@file\reserved@b%
        \@fileswtrue%
      \else%
        \edef\reserved@b{\reserved@b\detokenize{.tex}}%
        \ifx\@curr@file\reserved@b
          \@fileswtrue%
        \fi%
      \fi%
```

We allocate a write channel but we open it only if it is (hopefully) safe. If not opened that means we are going to write on the terminal.

```
      \ch@ck7\reserved@c\write\relax%
      \if@filesw%  % Foul ... trying to overwrite \jobname!
      \@latex@error{Trying to overwrite `\jobname.tex'}{You can't %
        write to the file you are reading from!\MessageBreak%
        Data is written to screen instead.}%
      \else%
        \@latex@warning@no@line%
           {Writing or overwriting file `\@currdir\@curr@file'}%
        \immediate\openout\reserved@c\q@curr@file\relax%
      \fi%
    \fi%
  \fi%
```

Closing the `\@inputcheck` is done here to avoid having to do this in each branch.

```
  \closein\@inputcheck%
  \if@tempswa%
```

```
    \immediate\write\reserved@c{%
      \@percentchar\@percentchar\space%
          \expandafter\@gobble\string\LaTeX2e file `\@curr@file'^^J%
      \@percentchar\@percentchar\space  generated by the %
        `\@currenvir' \expandafter\@gobblefour\string\newenvironment^^J%
      \@percentchar\@percentchar\space from source `\jobname' on %
         \number\year/\two@digits\month/\two@digits\day.^^J%
      \@percentchar\@percentchar}%
  \fi%
  \let\do\@makeother\dospecials%
```

If there are active characters in the upper half (e.g., from `inputenc` there would be confusion so we render everything harmless.

```
  \count@ 128\relax%
  \loop%
    \catcode\count@ 11\relax%
    \advance\count@ \@ne%
    \ifnum\count@<\@cclvi%
  \repeat%
```

```
  \edef\E{\@backslashchar end\string{\@currenvir\string}}%
  \edef\reserved@b{%
    \def\noexpand\reserved@b%
         ####1\E####2\E####3\relax}%
  \reserved@b{%
    \ifx\relax##3\relax%
```

There was no `\end{filecontents}`

```
      \immediate\write\reserved@c{##1}%
    \else%
```

There was a `\end{filecontents}`, so stop this time.

```
      \edef^^M{\noexpand\end{\@currenvir}}%
      \ifx\relax##1\relax%
      \else%
```

Text before the `\end`, write it with a warning.

```
          \@latex@warning{Writing text ‘##1’ before %
            \string\end{\@currenvir}\MessageBreak
            as last line of \@curr@file}%
        \immediate\write\reserved@c{##1}%
      \fi%
      \ifx\relax##2\relax%
      \else%
```

Text after the `\end`, ignore it with a warning.

```
          \@latex@warning{%
            Ignoring text ‘##2’ after \string\end{\@currenvir}}%
      \fi%
    \fi%
    ^^M}%
```

```
  \catcode‘\^^L\active%
  \let\L\@undefined%
  \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
  \catcode‘\^^I\active%
  \let\I\@undefined%
  \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
  \catcode‘\^^M\active%
  \edef^^M##1^^M{%
    \noexpand\reserved@b##1\E\E\relax}}%
\endgroup%
```

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩    {\filec@ntents}{Spaces in file names + optional arg}%
```

```
⟨latexrelease⟩
⟨latexrelease⟩\def\filecontents{\@tempswatrue\@fileswtrue
⟨latexrelease⟩  \@ifnextchar[\filec@ntents@opt\filec@ntents
⟨latexrelease⟩}
⟨latexrelease⟩\@namedef{filecontents*}{\@tempswafalse\@fileswtrue
⟨latexrelease⟩  \@ifnextchar[\filec@ntents@opt\filec@ntents
⟨latexrelease⟩}
⟨latexrelease⟩\def\filec@ntents@opt[#1]{%
⟨latexrelease⟩  \edef\@fortmp{\zap@space#1 \@empty}%
⟨latexrelease⟩  \@for\reserved@a:=\@fortmp\do{%
⟨latexrelease⟩    \ifcsname filec@ntents@\reserved@a\endcsname
⟨latexrelease⟩      \csname filec@ntents@\reserved@a\endcsname
⟨latexrelease⟩    \else
⟨latexrelease⟩    \@latex@error{Unknown filecontents option \reserved@a}%
⟨latexrelease⟩       {Valid options are force (or overwrite), nosearch, noheader}%
⟨latexrelease⟩    \fi}%
⟨latexrelease⟩  \filec@ntents
⟨latexrelease⟩}
⟨latexrelease⟩\let\filec@ntents@force\@fileswfalse
⟨latexrelease⟩\let\filec@ntents@overwrite\@fileswfalse  % alternative name
⟨latexrelease⟩\let\filec@ntents@noheader\@tempswafalse
⟨latexrelease⟩\def\filec@ntents@nosearch{%
⟨latexrelease⟩  \let\filec@ntents@checkdir\@currdir
⟨latexrelease⟩  \def\filec@ntents@where{in current directory}}
⟨latexrelease⟩\let\filec@ntents@checkdir\@empty
⟨latexrelease⟩\def\filec@ntents@where{exists on the system}
⟨latexrelease⟩\begingroup%
⟨latexrelease⟩\@tempcnta=1
⟨latexrelease⟩\loop
⟨latexrelease⟩  \catcode\@tempcnta=12  %
⟨latexrelease⟩  \advance\@tempcnta\@ne %
⟨latexrelease⟩\ifnum\@tempcnta<32      %
⟨latexrelease⟩\repeat                  %
⟨latexrelease⟩\catcode`\*=11 %
⟨latexrelease⟩\catcode`\^^M\active%
⟨latexrelease⟩\catcode`\^^L\active\let^^L\relax%
⟨latexrelease⟩\catcode`\^^I\active%
⟨latexrelease⟩\gdef\filec@ntents#1{%
⟨latexrelease⟩  \set@curr@file{\filec@ntents@checkdir#1}%
⟨latexrelease⟩  \edef\q@curr@file{\expandafter\quote@name\expandafter{\@curr@file}}%
⟨latexrelease⟩  \chardef\reserved@c\ifx\directlua\@undefined 15 \else 127 \fi%
⟨latexrelease⟩  \openin\@inputcheck\q@curr@file \space %
⟨latexrelease⟩  \ifeof\@inputcheck%
⟨latexrelease⟩    \@latex@warning@no@line%
⟨latexrelease⟩        {Writing file `\@currdir\@curr@file'}%
⟨latexrelease⟩    \ch@ck7\reserved@c\write\relax%
⟨latexrelease⟩    \immediate\openout\reserved@c\q@curr@file\relax%
⟨latexrelease⟩  \else%
⟨latexrelease⟩    \if@filesw%
⟨latexrelease⟩      \@latex@warning@no@line%
⟨latexrelease⟩          {File `\@curr@file' already \filec@ntents@where.\MessageBreak%
⟨latexrelease⟩             Not generating it from this source}%
⟨latexrelease⟩      \let\write\@gobbletwo%
⟨latexrelease⟩      \let\closeout\@gobble%
```

```
⟨latexrelease⟩    \else%
⟨latexrelease⟩      \edef\reserved@a{#1}%
⟨latexrelease⟩      \edef\reserved@a{\detokenize\expandafter{\reserved@a}}%
⟨latexrelease⟩      \edef\reserved@b{\detokenize\expandafter{\jobname}}%
⟨latexrelease⟩      \ifx\reserved@a\reserved@b%
⟨latexrelease⟩        \@fileswtrue%
⟨latexrelease⟩      \else%
⟨latexrelease⟩        \edef\reserved@b{\reserved@b\detokenize{.tex}}%
⟨latexrelease⟩        \ifx\reserved@a\reserved@b
⟨latexrelease⟩          \@fileswtrue%
⟨latexrelease⟩        \fi%
⟨latexrelease⟩      \fi%
⟨latexrelease⟩      \ch@ck7\reserved@c\write\relax%
⟨latexrelease⟩      \if@filesw%  % Foul ... trying to overwrite \jobname!
⟨latexrelease⟩      \@latex@error{Trying to overwrite ‘\jobname.tex’}{You can’t %
⟨latexrelease⟩        write to the file you are reading from!\MessageBreak%
⟨latexrelease⟩        Data is written to screen instead.}%
⟨latexrelease⟩      \else%
⟨latexrelease⟩        \@latex@warning@no@line%
⟨latexrelease⟩           {Writing or overwriting file ‘\@currdir\@curr@file’}%
⟨latexrelease⟩        \immediate\openout\reserved@c\q@curr@file\relax%
⟨latexrelease⟩      \fi%
⟨latexrelease⟩    \fi%
⟨latexrelease⟩  \fi%
⟨latexrelease⟩  \closein\@inputcheck%
⟨latexrelease⟩  \if@tempswa%
⟨latexrelease⟩    \immediate\write\reserved@c{%
⟨latexrelease⟩      \@percentchar\@percentchar\space%
⟨latexrelease⟩          \expandafter\@gobble\string\LaTeX2e file ‘\@curr@file’^^J%
⟨latexrelease⟩      \@percentchar\@percentchar\space  generated by the %
⟨latexrelease⟩        ‘\@currenvir’ \expandafter\@gobblefour\string\newenvironment^^J%
⟨latexrelease⟩      \@percentchar\@percentchar\space from source ‘\jobname’ on %
⟨latexrelease⟩         \number\year/\two@digits\month/\two@digits\day.^^J%
⟨latexrelease⟩      \@percentchar\@percentchar}%
⟨latexrelease⟩  \fi%
⟨latexrelease⟩  \let\do\@makeother\dospecials%
⟨latexrelease⟩  \count@ 128\relax%
⟨latexrelease⟩  \loop%
⟨latexrelease⟩    \catcode\count@ 11\relax%
⟨latexrelease⟩    \advance\count@ \@ne%
⟨latexrelease⟩    \ifnum\count@<\@cclvi%
⟨latexrelease⟩  \repeat%
⟨latexrelease⟩  \edef\E{\@backslashchar end\string{\@currenvir\string}}%
⟨latexrelease⟩  \edef\reserved@b{%
⟨latexrelease⟩    \def\noexpand\reserved@b%
⟨latexrelease⟩         ####1\E####2\E####3\relax}%
⟨latexrelease⟩  \reserved@b{%
⟨latexrelease⟩    \ifx\relax##3\relax%
⟨latexrelease⟩      \immediate\write\reserved@c{##1}%
⟨latexrelease⟩    \else%
⟨latexrelease⟩      \edef^^M{\noexpand\end{\@currenvir}}%
⟨latexrelease⟩      \ifx\relax##1\relax%
⟨latexrelease⟩      \else%
⟨latexrelease⟩          \@latex@warning{Writing text ‘##1’ before %
```

```
⟨latexrelease⟩             \string\end{\@currenvir}\MessageBreak as last line of \@curr@file}%
⟨latexrelease⟩        \immediate\write\reserved@c{##1}%
⟨latexrelease⟩      \fi%
⟨latexrelease⟩      \ifx\relax##2\relax%
⟨latexrelease⟩      \else%
⟨latexrelease⟩         \@latex@warning{%
⟨latexrelease⟩           Ignoring text ‘##2’ after \string\end{\@currenvir}}%
⟨latexrelease⟩      \fi%
⟨latexrelease⟩    \fi%
⟨latexrelease⟩    ^^M}%
⟨latexrelease⟩  \catcode‘\^^L\active%
⟨latexrelease⟩  \let\L\@undefined%
⟨latexrelease⟩  \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
⟨latexrelease⟩  \catcode‘\^^I\active%
⟨latexrelease⟩  \let\I\@undefined%
⟨latexrelease⟩  \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
⟨latexrelease⟩  \catcode‘\^^M\active%
⟨latexrelease⟩  \edef^^M##1^^M{%
⟨latexrelease⟩    \noexpand\reserved@b##1\E\E\relax}}%
⟨latexrelease⟩\endgroup%
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩    {\filec@ntents}{Spaces in file names + optional arg}%
⟨latexrelease⟩
⟨latexrelease⟩\let\filec@ntents@opt        \@undefined
⟨latexrelease⟩\let\filec@ntents@force      \@undefined
⟨latexrelease⟩\let\filec@ntents@overwrite  \@undefined
⟨latexrelease⟩\let\filec@ntents@noheader   \@undefined
⟨latexrelease⟩\let\filec@ntents@nosearch   \@undefined
⟨latexrelease⟩\let\filec@ntents@checkdir   \@undefined
⟨latexrelease⟩\let\filec@ntents@where      \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\begingroup%
⟨latexrelease⟩\@tempcnta=1
⟨latexrelease⟩\loop
⟨latexrelease⟩  \catcode\@tempcnta=12  %
⟨latexrelease⟩  \advance\@tempcnta\@ne %
⟨latexrelease⟩\ifnum\@tempcnta<32      %
⟨latexrelease⟩\repeat                  %
⟨latexrelease⟩\catcode‘\*=11 %
⟨latexrelease⟩\catcode‘\^^M\active%
⟨latexrelease⟩\catcode‘\^^L\active\let^^L\relax%
⟨latexrelease⟩\catcode‘\^^I\active%
⟨latexrelease⟩
⟨latexrelease⟩\gdef\filec@ntents#1{%
⟨latexrelease⟩  \openin\@inputcheck#1 %
⟨latexrelease⟩  \ifeof\@inputcheck%
⟨latexrelease⟩    \@latex@warning@no@line%
⟨latexrelease⟩        {Writing file ‘\@currdir#1’}%
⟨latexrelease⟩    \chardef\reserved@c15 %
⟨latexrelease⟩    \ch@ck7\reserved@c\write%
⟨latexrelease⟩    \immediate\openout\reserved@c#1\relax%
⟨latexrelease⟩  \else%
⟨latexrelease⟩    \closein\@inputcheck%
```

```
⟨latexrelease⟩    \@latex@warning@no@line%
⟨latexrelease⟩            {File ‘#1’ already exists on the system.\MessageBreak%
⟨latexrelease⟩             Not generating it from this source}%
⟨latexrelease⟩    \let\write\@gobbletwo%
⟨latexrelease⟩    \let\closeout\@gobble%
⟨latexrelease⟩  \fi%
⟨latexrelease⟩  \if@tempswa%
⟨latexrelease⟩    \immediate\write\reserved@c{%
⟨latexrelease⟩      \@percentchar\@percentchar\space%
⟨latexrelease⟩          \expandafter\@gobble\string\LaTeX2e file ‘#1’^^J%
⟨latexrelease⟩      \@percentchar\@percentchar\space  generated by the %
⟨latexrelease⟩        ‘\@currenvir’ \expandafter\@gobblefour\string\newenvironment^^J%
⟨latexrelease⟩      \@percentchar\@percentchar\space from source ‘\jobname’ on %
⟨latexrelease⟩         \number\year/\two@digits\month/\two@digits\day.^^J%
⟨latexrelease⟩      \@percentchar\@percentchar}%
⟨latexrelease⟩  \fi%
⟨latexrelease⟩  \let\do\@makeother\dospecials%
⟨latexrelease⟩  \count@ 128\relax%
⟨latexrelease⟩  \loop%
⟨latexrelease⟩    \catcode\count@ 11\relax%
⟨latexrelease⟩    \advance\count@ \@ne%
⟨latexrelease⟩    \ifnum\count@<\@cclvi%
⟨latexrelease⟩  \repeat%
⟨latexrelease⟩  \edef\E{\@backslashchar end\string{\@currenvir\string}}%
⟨latexrelease⟩  \edef\reserved@b{%
⟨latexrelease⟩    \def\noexpand\reserved@b%
⟨latexrelease⟩         ####1\E####2\E####3\relax}%
⟨latexrelease⟩  \reserved@b{%
⟨latexrelease⟩    \ifx\relax##3\relax%
⟨latexrelease⟩      \immediate\write\reserved@c{##1}%
⟨latexrelease⟩    \else%
⟨latexrelease⟩      \edef^^M{\noexpand\end{\@currenvir}}%
⟨latexrelease⟩      \ifx\relax##1\relax%
⟨latexrelease⟩      \else%
⟨latexrelease⟩          \@latex@warning{Writing text ‘##1’ before %
⟨latexrelease⟩             \string\end{\@currenvir}\MessageBreak as last line of #1}%
⟨latexrelease⟩        \immediate\write\reserved@c{##1}%
⟨latexrelease⟩      \fi%
⟨latexrelease⟩      \ifx\relax##2\relax%
⟨latexrelease⟩      \else%
⟨latexrelease⟩         \@latex@warning{%
⟨latexrelease⟩           Ignoring text ‘##2’ after \string\end{\@currenvir}}%
⟨latexrelease⟩      \fi%
⟨latexrelease⟩    \fi%
⟨latexrelease⟩    ^^M}%
⟨latexrelease⟩
⟨latexrelease⟩  \catcode‘\^^L\active%
⟨latexrelease⟩  \let\L\@undefined%
⟨latexrelease⟩  \def^^L{\expandafter\ifx\csname L\endcsname\relax\fi ^^J^^J}%
⟨latexrelease⟩  \catcode‘\^^I\active%
⟨latexrelease⟩  \let\I\@undefined%
⟨latexrelease⟩  \def^^I{\expandafter\ifx\csname I\endcsname\relax\fi\space}%
⟨latexrelease⟩  \catcode‘\^^M\active%
⟨latexrelease⟩  \edef^^M##1^^M{%
```

```
⟨latexrelease⟩     \noexpand\reserved@b##1\E\E\relax}}%
⟨latexrelease⟩\endgroup%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\begingroup
\catcode`|=\catcode`\%
\catcode`\%=12
\catcode`\*=11
\gdef\@percentchar{%}
\gdef\endfilecontents{|
  \immediate\closeout\reserved@c
  \def\T##1##2##3{|
  \ifx##1\@undefined\else
    \@latex@warning@no@line{##2 has been converted to Blank ##3e}|
  \fi}|
  \T\L{Form Feed}{Lin}|
  \T\I{Tab}{Spac}|
  \immediate\write\@unused{}}
\global\let\endfilecontents*\endfilecontents
```

We no longer prevent the code to be used after begin document (no rollback needed for this change).

```
%\@onlypreamble\filecontents
%\@onlypreamble\endfilecontents
%\@onlypreamble\filecontents*
%\@onlypreamble\endfilecontents*
\endgroup
%\@onlypreamble\filec@ntents
```

(*End definition for* `\filecontents` *and* `\endfilecontents`.)

5 Package/class rollback mechanism

```
⟨/2ekernel⟩
⟨*2ekernel | latexreleasefirst⟩
```

`\pkgcls@debug` For testing we have a few extra lines of code that by default do nothing but one can set `\pkgcls@debug` to `\typeout` to get extra info. Sometime in the future this will be dropped.

```
⟨*tracerollback⟩
%\let\pkgcls@debug\typeout
\let\pkgcls@debug\@gobble
⟨/tracerollback⟩
```

(*End definition for* `\pkgcls@debug`.)

`\requestedLaTeXdate` The macro (!) `\requestedLaTeXdate` holds the globally requested rollback date (via `latexrelease`) or zero if no such request was made.

```
\def\requestedLaTeXdate{0}
```

(*End definition for* `\requestedLaTeXdate`.)

\pkgcls@targetdate
\pkgcls@targetlabel
\pkgcls@innerdate

If a rollback for a package or class is requested then \pkgcls@targetdate holds the requested date as a number YYYYMMDD (if there was one, otherwise the value of \requestedLaTeXdate) and \pkgcls@targetlabel will be empty. If there was a request for a named version then \pkgcls@targetlabel holds the version name and \pkgcls@targetdate is set to 1.

\pkgcls@targetdate=0 is used to indicate that there was no rollback request. While loading an old release \pkgcls@targetdate is also reset to zero so that \DeclareRelease declarations are bypassed.

In contrast \pkgcls@innerdate will always hold the requested date (in a macro not a counter) if there was one, otherwise, e.g., if there was no request or a request to a version name it will contain TEX largest legal number. While loading a file this can be used to provide conditionals that select code based on the request.

```
\ifx\pkgcls@targetdate\@undefined
  \newcount\pkgcls@targetdate
\fi
\let\pkgcls@targetlabel\@empty
\def\pkgcls@innerdate{\maxdimen}
```

(*End definition for* \pkgcls@targetdate*,* \pkgcls@targetlabel*, and* \pkgcls@innerdate*.*)

\pkgcls@candidate
\pkgcls@releasedate

When looping through the \DeclareRelease declarations we record if the release is the best candidate we have seen so far. This is recorded in \pkgcls@candidate and we update it whenever we see a better one.

In \pkgcls@releasedate we keep track of the release date of that candidate.

```
\let\pkgcls@candidate\@empty
\let\pkgcls@releasedate\@empty
```

(*End definition for* \pkgcls@candidate *and* \pkgcls@releasedate*.*)

\load@onefilewithoptions
\@onefilewithoptions

the best place to add the rollback code is at the point where \@onefilewithoptions is called to load a single class or package.

To make things easy we save the old definition as \load@onefilewithoptions and then provide a new interface.

Important: as this code is also unconditionally placed into latexrelease we can only do this name change once otherwise both macros will contain the same code.

```
\ifx\load@onefilewithoptions\@undefined
 \let\load@onefilewithoptions\@onefilewithoptions
 \def\@onefilewithoptions#1[#2][#3]#4{%
```

First a bit of tracing normally disabled.

```
⟨*tracerollback⟩
  \pkgcls@debug{--- File loaded request (\noexpand\usepackage or ...)}%
  \pkgcls@debug{\@spaces 1: #1}%
  \pkgcls@debug{\@spaces 2: #2}%
  \pkgcls@debug{\@spaces 3: #3}%
  \pkgcls@debug{\@spaces 4: #4}%
⟨/tracerollback⟩
```

Two of the arguments are needed later on in error/warning messages so we save them.

```
  \def\pkgcls@name{#1}%                    % for info message
  \def\pkgcls@arg {#3}%                    % for info message
```

then we parse the final optional argument to determine if there is a specific rollback request for the current file. This will set \pkgcls@targetdate, \pkgcls@targetlabel and \pkgcls@mindate.

```
\pkgcls@parse@date@arg{#3}%
```

When determining the correct release to load we keep track of candidates in \pkgcls@candidate and initially we don't have any:

```
\let\pkgcls@candidate\@empty
```

If we had a rollback request then #3 may contain data but not necessarily a "minimal date" so instead of passing it on we pass on the content of \pkgcls@mindate. We need to pass the value not the command, otherwise nested packages may pick up the wrong information.

```
  \begingroup
  \edef\reserved@a{%
    \endgroup
    \unexpanded{\load@onefilewithoptions#1[#2]}%
    [\pkgcls@mindate]%
    \unexpanded{#4}}%
   \reserved@a
 }
\fi
```

(*End definition for* \load@onefilewithoptions *and* \@onefilewithoptions.)

\pkgcls@parse@date@arg The \pkgcls@parse@date@arg command parses the second optional argument of \usepackage, \RequirePackage or \documentclass for a rollback request setting the values of \pkgcls@targetdate and \pkgcls@targetlabel.

This optional argument has a dual purpose: If it just contains a date string then this means that the package should have at least that date (to ensure that a certain feature is actually available, or a certain bug has been fixed). When the package gets loaded the information in \Provides... will then be checked against this request.

But if it starts with an equal sign followed by a date string or followed by a version name then this means that we should roll back to the state of the package at that date or to the version with the requested name.

If there was no optional argument or the optional argument does not start with "=" then the \pkgcls@targetdate is set to the date of the overall rollback request (via latexrelease) or if that was not given it is set to 0. In either case \pkgcls@targetlabel will be made empty.

If the argument doesn't start with "=" then it is supposed to be a "minimal date" and we therefore save the value in \pkgcls@mindate, otherwise this macro is made empty.

So in summary we have:

Input		\pkgcls@targetdate	\pkgcls@targetlabel	\pkgcls@mindate
⟨*empty*⟩	→	⟨*global-rollbackdate-as-number*⟩	⟨*empty*⟩	⟨*empty*⟩
⟨*date*⟩	→	⟨*global-rollbackdate-as-number*⟩	⟨*empty*⟩	⟨*date*⟩
=⟨*date*⟩	→	⟨*date-as-number*⟩	⟨*empty*⟩	⟨*empty*⟩
=⟨*version*⟩	→	1	⟨*version*⟩	⟨*empty*⟩
⟨*other*⟩	→	⟨*global-rollbackdate-as-number*⟩	⟨*empty*⟩	⟨*other*⟩

where ⟨*global-rollbackdate-as-number*⟩ is a date request given via latexrelease or if there wasn't one 0.

```
\def\pkgcls@parse@date@arg #1{%
```

If the argument is empty we use the rollback date from `latexrelease` which has the value of zero if there was no rollback request. The label and the minimal date is made empty in that case.

```
  \ifx\@nil#1\@nil
    \pkgcls@targetdate\requestedLaTeXdate\relax
    \let\pkgcls@targetlabel\@empty
    \let\pkgcls@mindate\@empty
```

Otherwise we parse the argument further, checking for a `=` as the first character. We append a `=` at the end so that there is at least one such character in the argument.

```
  \else
    \pkgcls@parse@date@arg@#1=\@nil\relax
  \fi
}
```

The actual parsing work then happens in `\pkgcls@parse@date@arg@`:

```
\def\pkgcls@parse@date@arg@#1=#2\@nil{%
```

We set `\pkgcls@targetdate` depending on the parsing result; the code is expandable so we can do the parsing as part of the assignment.

```
 \pkgcls@targetdate
```

If a `=` was in first position then `#1` will be empty. In that case `#2` will be the original argument with a `=` appended.

This can be parsed with `\@parse@version`, the trailing character is simply ignored. This macro returns the parsed date as a number (or zero if it wasn't a date) and accepts both YYYY/MM/DD and YYYY-MM-DD formats.

```
   \ifx\@nil#1\@nil
     \@parse@version0#2//00\@nil\relax
```

Whatever is returned is thus assigned to `\pkgcls@targetdate` and therefore we can now test its value. If the value is zero we assume that the remaining argument string represents a version and change `\pkgcls@targetdate` and set `\pkgcls@targetlabel` to the version name (after stripping off the trailing `=`.

```
     \ifnum \pkgcls@targetdate=\z@
       \pkgcls@targetdate\@ne
       \def\pkgcls@innerdate{\maxdimen}%
       \pkgcls@parse@date@arg@version#2%
     \else
       \edef\pkgcls@innerdate{\the\pkgcls@targetdate}%
     \fi
     \let\pkgcls@mindate\@empty
   \else
```

If `#1` was not empty then there wasn't a `=` character in first position so we are dealing either with a "minimum date" or with some incorrect data. We assume the former and make the following assignments (the first one finishing the assignment of `\pkgcls@targetdate`):

```
     \requestedLaTeXdate\relax
     \let\pkgcls@targetlabel\@empty
     \def\pkgcls@innerdate{\maxdimen}%
     \def\pkgcls@mindate{#1}%
```

If the min-date is after the requested rollback date (if there is any, i.e., if it is not zero) then we have a conflict and therefore issue a warning.

```
      \ifnum \pkgcls@targetdate > \z@
        \ifnum \@parse@version0#1//00\@nil > \pkgcls@targetdate
          \@latex@warning@no@line{Suspicious rollback/min-date date given\MessageBreak
            A minimal date of #1 has been specified for
             \@cls@pkg\MessageBreak '\pkgcls@name'.\MessageBreak
             But this is in conflict
             with a rollback request to \requestedpatchdate}
        \fi
      \fi
    \fi
}
```

Strip off the trailing `=` and assign the version name to `\pkgcls@targetlabel`.

```
\def\pkgcls@parse@date@arg@version#1={%
  \def\pkgcls@targetlabel{#1}}
```

(*End definition for* `\pkgcls@parse@date@arg`.)

`\DeclareRelease` First argument is the "name" of the release and it can be left empty if one doesn't like to give a name to the release. The second argument is that from which on this release was available (or should be used in case of minor updates). The final argument is the external file name of this release, by convention this should be ⟨*pkg/cls-name*⟩-⟨*date*⟩.⟨*extension*⟩ but this is not enforced and through this argument one can overwrite it.

```
\def\DeclareRelease#1#2#3{%
  \ifnum\pkgcls@targetdate>\z@  % some sort of rollback request
⟨*tracerollback⟩
    \pkgcls@debug{---\string\DeclareRelease:}%
    \pkgcls@debug{\@spaces 1: #1}%
    \pkgcls@debug{\@spaces 2: #2}%
    \pkgcls@debug{\@spaces 3: #3}%
⟨/tracerollback⟩
```

If the date argument `#2` is empty we are dealing with a special release that should be only accessible via its name; a typical use case would be a "beta" release. So if we are currently processing a date request we ignore it and otherwise we check if we can match the name and if so load the corresponding release file.

```
    \ifx\@nil#2\@nil
      \ifnum\pkgcls@targetdate=\@ne  % named request
        \def\reserved@a{#1}%
        \ifx\pkgcls@targetlabel\reserved@a
          \pkgcls@use@this@release{#3}{}%
⟨*tracerollback⟩
        \else
          \pkgcls@debug{Label doesn't match}%
⟨/tracerollback⟩
        \fi
⟨*tracerollback⟩
      \else
        \pkgcls@debug{Date request: ignored}%
⟨/tracerollback⟩
      \fi
    \else
```

If the value of `\pkgcls@targetdate` is greater than 1 (or in reality greater than something like 19930101) we are dealing with a rollback request to a specific date.

```
      \ifnum\pkgcls@targetdate>\@ne  % a real request
```

So we parse the date of this release to check if it is before or after the request date.

```
        \ifnum\@parse@version#2//00\@nil
            >\pkgcls@targetdate
```

If it is after we have to distinguish between two cases: If there was an earlier candidate we use that one because the other is too late, but if there wasn't one (i.e., if current release is the oldest that exists) we use it as the best choice. However in that case something is wrong (as there shouldn't be a rollback to a date where a package used doesn't yet exists. So we make a complained to the user.

```
          \ifx\pkgcls@candidate\@empty
            \pkgcls@rollbackdate@error{#2}%
            \pkgcls@use@this@release{#3}{#2}%
          \else
            \pkgcls@use@this@release\pkgcls@candidate
                                     \pkgcls@releasedate
          \fi
        \else
```

Otherwise, if the release date of this version is before the target rollback and we record it as a candidate. But we don't use it yet as there may be another release which is still before the target rollback.

```
          \def\pkgcls@candidate{#3}%
          \def\pkgcls@releasedate{#2}%
⟨*tracerollback⟩
          \pkgcls@debug{New candidate: #3}%
⟨/tracerollback⟩
        \fi
      \else
```

If we end up in this branch we have a named version request. So we check if `\pkgcls@targetlabel` matches the current name and if yes we use this release immediately, otherwise we do nothing as a later declaration may match it.

```
        \def\reserved@a{#1}%
        \ifx\pkgcls@targetlabel\reserved@a
          \pkgcls@use@this@release{#3}{#2}%
⟨*tracerollback⟩
        \else
          \pkgcls@debug{Label doesn't match}%
⟨/tracerollback⟩
        \fi
      \fi
    \fi
  \fi
}
```

(*End definition for* `\DeclareRelease`.)

`\pkgcls@use@this@release` If a certain release has been selected (stored in the external file given in `#1`) we need to input it and afterwards stop reading the current file.

```
\def\pkgcls@use@this@release#1#2{%
```

Before that we record the selection made inside the transcript.

```
  \pkgcls@show@selection{#1}{#2}%
```

We then set the \pkgcls@targetdate to zero so that any \DeclareRelease or \DeclareCurrentRelease in the file we now load are bypassed[39] and then we finally load the correct release.

After loading that file we need to stop reading the current file so we issue \endinput. Note that the \relax before that is essential to ensure that the \endinput is only happening after the file has been fully processed, otherwise it would act after the first line of the \@@input!

```
  \pkgcls@targetdate\z@
  \@@input #1\relax
  \endinput
}
```

(*End definition for* \pkgcls@use@this@release.)

\pkgcls@show@selection This command records what selection was made. As that is needed in two places (and it is rather lengthy) it was placed in a separate command. The first argument is the name of the external file that is being loaded and is only needed for debugging. The second argument is the date that corresponds to this file and it is used as part of the message.

```
\def\pkgcls@show@selection#1#2{%
⟨*tracerollback⟩
  \pkgcls@debug{Result: use  #1}%
⟨/tracerollback⟩
  \GenericInfo
   {\@spaces\@spaces\space}{Rollback for
    \@cls@pkg\space'\@currname' requested ->
    \ifnum\pkgcls@targetdate>\@ne
       date
       \ifnum\requestedLaTeXdate=\pkgcls@targetdate
          \requestedpatchdate
       \else
          \expandafter\@gobble\pkgcls@arg
       \fi.\MessageBreak
```

Instead of "best approximation" we could say that we have been able to exactly match the date (if it is exact), but that would mean extra tests without much gain, so not done.

```
       Best approximation is
    \else
       version '\pkgcls@targetlabel'.\MessageBreak
       This corresponds to
    \fi
    \ifx\@nil#2\@nil
       a special release%
    \else
       the release introduced on #2%
    \fi
    \@gobble}%
}
```

[39] The older release may also have such declarations inside if it was a simply copy of the .sty or .cls file current at that date. Removing these declarations would make the file load a tiny bit faster, but this way it works in any case.

(*End definition for* `\pkgcls@show@selection`.)

`\pkgcls@rollbackdate@error` This is called if the requested rollback date is earlier than the earliest known release of a package or class.

A similar error is given if global rollback date and min-date on a specific package conflict with each other, but that case is happens only once so it is inlined.

```
\def\pkgcls@rollbackdate@error#1{%
  \@latex@error{Suspicious rollback date given}%
     {The \@cls@pkg\space'\@currname'  has no rollback data
      before #1 which\MessageBreak
      is after your requested rollback date --- so
      something may be wrong here.\MessageBreak
      Continue and we use the earliest known release.}}
```

(*End definition for* `\pkgcls@rollbackdate@error`.)

`\DeclareCurrentRelease` This declares the date (and possible name) of the current version of a package or class.

```
\def\DeclareCurrentRelease#1#2{%
```

First we test if `\pkgcls@targetdate` is greater than zero, otherwise this code is bypassed (as there is no rollback request).

```
  \ifnum\pkgcls@targetdate>\z@  % some sort of rollback request
⟨*tracerollback⟩
    \pkgcls@debug{---DeclareCurrentRelease}%
    \pkgcls@debug{   1: #1}%
    \pkgcls@debug{   2: #2}%
⟨/tracerollback⟩
```

If the value is greater than 1 we have to deal with a date request, so we parse `#2` as a date and compare it with `\pkgcls@targetdate`.

```
    \ifnum\pkgcls@targetdate>\@ne  % a date request
      \ifnum\@parse@version#2//00\@nil
           >\pkgcls@targetdate
```

If it is greater that means the release date if this file is later than the requested rollback date. Again we have two cases: If there was a previous candidate release we use that one as the current release is too young, but if there wasn't we have to use this release nevertheless as there isn't any alternative.

However this case can only happen if there is a `\DeclareCurrentRelease` but no declared older releases (so basically the use of the declaration is a bit dubious).

```
        \ifx\pkgcls@candidate\@empty
          \pkgcls@rollbackdate@error{#2}%
        \else
          \pkgcls@use@this@release\pkgcls@candidate
                                   \pkgcls@releasedate
        \fi
```

Otherwise the current file is the right release, so we record that in the transcript and then carry on.

```
      \else
        \pkgcls@show@selection{current version}{#2}%
      \fi
    \else % a label request
```

Otherwise we have a rollback request to a named version so we check if that fits the current name and if not give an error as this was the last possible opportunity.

```
      \def\reserved@a{#1}%
      \ifx\pkgcls@targetlabel\reserved@a
        \pkgcls@show@selection{current version}{#2}%
      \else
        \@latex@error{Requested version '\pkgcls@targetlabel' for
          \@cls@pkg\space'\@currname' is unknown}\@ehc
      \fi
    \fi
  \fi
}
```

(*End definition for* `\DeclareCurrentRelease`.)

`\IfTargetDateBefore` This enables a simple form of conditional code inside a class or package file. If there is a date request and the request date is earlier than the first argument the code in the second argument is processed otherwise the code in the third argument is processed. If there was no date request then we also execute the third argument, i.e., we will get the "latest" version of the file.

Most often the second argument (before-date-code) will be empty.

```
\DeclareRobustCommand\IfTargetDateBefore[1]{%
  \ifnum\pkgcls@innerdate <%
        \expandafter\@parse@version\expandafter0#1//00\@nil
    \typeout{Exclude code introduced on #1}%
    \expandafter\@firstoftwo
  \else
    \typeout{Include code introduced on #1}%
    \expandafter\@secondoftwo
  \fi
}
```

(*End definition for* `\IfTargetDateBefore`.)

⟨/2ekernel | latexreleasefirst⟩

6 After Preamble

Finally we declare a package that allows all the commands declared above to be `\@onlypreamble` to be used after `\begin{document}`.

```
⟨*afterpreamble⟩
\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{pkgindoc}
         [2020-08-08 v1.3m Package Interface in Document (DPC)]
\def\reserved@a#1\do\@classoptionslist#2\do\filec@ntents#3\relax{%
  \gdef\@preamblecmds{#1#3}}
\expandafter\reserved@a\@preamblecmds\relax
⟨/afterpreamble⟩
```

File V
ltkeys.dtx

1 Creating and using keyval options

As with any key–value input, using key–value pairs as package or class options has two parts: creating the key options and setting (using) them. Options created in this way *may* be used after package loading as general key–value settings: this will depend on the nature of the underlying code.

`\DeclareKeys` `\DeclareKeys [⟨family⟩] {⟨declarations⟩}`

Creates a series of options from a comma-separated ⟨*declarations*⟩ list. Each entry in this list is a key–value pair, with the ⟨*key*⟩ having one or more ⟨*properties*⟩. A small number of "basic" ⟨*properties*⟩ are described below. The full range of properties, provided by l3keys, can also be used for more powerful processing. See `interface3` for the full details.

The basic properties provided here are

- `.code` — execute arbitrary code
- `.if` — sets a TEX `\if...` switch
- `.store` — stores a value in a macro
- `.usage` – defines whether the option can be given only when loading (`load`), in the preamble (`preamble`) or has no limitation on scope (`general`)

The part of the ⟨*key*⟩ before the ⟨*property*⟩ is the ⟨*name*⟩, with the ⟨*value*⟩ working with the ⟨*property*⟩ to define the behaviour of the option.

For example, with

```
\DeclareKeys[mypkg]
  {
    draft.if          = @mypkg@draft      ,
    draft.usage       = preamble          ,
    name.store        = \@mypkg@name      ,
    name.usage        = load              ,
    second-name.store = \@mypkg@other@name
  }
```

three options would be create. The option `draft` can be given anywhere in the preamble, and will set a switch called `\if@mypkg@draft`. The option `name` can only be given during package loading, and will save whatever value it is given in `\@mypkg@name`. Finally, the option `second-name` can be given anywhere, and will save its value in `\@mypkg@other@name`.

Keys created *before* the use of `\ProcessKeyOptions`act as package options.

`\DeclareUnknownKeyHandler` `\DeclareUnknownKeyHandler [⟨family⟩] {⟨code⟩}`

The function `\DeclareUnknownKeyHandler` may be used to define the behavior when an undefined key is encountered. The ⟨*code*⟩ will receive the unknown key name as `#1` and the value as `#2`. These can then be processed as appropriate, e.g. by forwarding to another package.

\ProcessKeyOptions

\ProcessKeyOptions [⟨*family*⟩]

The \ProcessKeyOptions function is used to check the current option list against the keys defined for ⟨*family*⟩. Global (class) options and local (package) options are checked when this function is called in a package.

\SetKeys

\SetKeys [⟨*family*⟩] {⟨*keyvals*⟩}

Sets (applies) the explicit list of ⟨*keyvals*⟩ for the ⟨*family*⟩: it the latter is not given, the value of \@currname used. This command may be used within a package to set options before or after using \ProcessKeyOptions.

1.1 Implementation of ltkeys

```
⟨@@=keys⟩
⟨*2ekernel⟩
\ExplSyntaxOn
```

1.2 Key properties

.code
.if
.store
.usage

```
\group_begin:
  \cs_set_protected:Npn \__keys_tmp:nn #1#2
    {
      \quark_if_recursion_tail_stop:n {#1}
      \cs_new_eq:cc
        { \c__keys_props_root_str . #2 }
        { \c__keys_props_root_str . #1 }
      \__keys_tmp:nn
    }
  \__keys_tmp:nn
    { code:n }          { code }
    { legacy_if_set:n } { if }
    { tl_set:N }        { store }
    { usage:n }         { usage }
    { \q_recursion_tail } { }
    \q_recursion_stop
\group_end:
```

(*End definition for* .code *and others.*)

1.3 Main mechanism

```
\cs_generate_variant:Nn \clist_put_right:Nn { Nv }
```

\l__keys_options_clist

A single list is used for all options, into which they are collected before processing.

```
\clist_new:N \l__keys_options_clist
```

(*End definition for* \l__keys_options_clist.)

\l__keys_options_loading_bool

Used to indicate we are in the loading phase: controls the outcome of warnings.

```
\bool_new:N \l__keys_options_loading_bool
```

__keys_options:n
__keys_options_aux:n
__keys_options_end:

The main function calls functions to collect up the global and local options into `\l__keys_options_clist` before calling the underlying functions to actually do the processing. So that a suitable message is produced if the option is unknown, the special `unknown` key is set if it does not already exist for the current family, and is cleaned up afterwards if required. To allow the LaTeX 2ε layer to know this mechanism is active, and to deal with the key family not matching the file name, we store the family in all cases.

```
\cs_new_protected:Npn \__keys_options:n #1
  { \__keys_options_expand_module:Nn \__keys_options_aux:n {#1} }
\cs_new_protected:Npn \__keys_options_aux:n #1
  {
    \cs_gset_nopar:cpn { opt@fam@\@currname.\@currext } {#1}
    \cs_set_protected:Npn \__keys_option_end: { }
    \clist_clear:N \l__keys_options_clist
    \__keys_options_global:n {#1}
    \__keys_options_local:
    \keys_if_exist:nnF {#1} { unknown }
      {
        \keys_define:nn {#1}
          {
            unknown .code:n =
              {
                \msg_error:nnxx { keys } { option-unknown }
                  { \l_keys_key_str } { \@currname }
              }
          }
        \cs_set_protected:Npn \__keys_option_end:
          { \keys_define:nn {#1} { unknown .undefine: } }
      }
    \bool_set_true:N \l__keys_options_loading_bool
    \keys_set:nV {#1} \l__keys_options_clist
    \bool_set_false:N \l__keys_options_loading_bool
    \AtEndOfPackage { \cs_set_eq:NN \@unprocessedoptions \scan_stop: }
    \__keys_option_end:
    \__keys_options_loaded:n {#1}
  }
\msg_new:nnnn { keys } { option-unknown }
  { Unknown~option~'#1'~for~package~#2. }
  {
    LaTeX~has~been~asked~to~set~an~option~called~'#1'~
    but~the~#2~package~has~not~created~an~option~with~this~name.
  }
```

(*End definition for* `\__keys_options:n`*,* `\__keys_options_aux:n`*, and* `\__keys_options_end:`*.*)

__keys_options_global:n

Global (class) options are handled differently for LaTeX 2ε packages and classes. Hence this function is essentially a check on the current file type. The initial test is needed as LaTeX 2ε allows variables to be equal to `\scan_stop:`, which is usually forbidden in expl3 code.

```
\cs_new_protected:Npn \__keys_options_global:n #1
  {
    \cs_if_eq:NNF \@classoptionslist \scan_stop:
      {
        \cs_if_eq:NNTF \@currext \@clsextension
```

```
          { \__keys_options_class:n {#1} }
          { \__keys_options_package:n {#1} }
      }
  }
```

(*End definition for* `\__keys_options_global:n`.)

`\__keys_options_class:n` For classes, each option (stripped of any content after `=`) is checked for existence as a key. If found, the option is added to the combined list for processing. On the other hand, unused options are stored up in `\@unusedoptionlist`. Before any of that, though, there is a simple check to see if there is an `unknown` key. If there is, then *everything* will match and the mapping can be skipped.

```
\cs_new_protected:Npn \__keys_options_class:n #1
  {
    \cs_if_free:cF { opt@ \@currname . \@currext }
      {
        \keys_if_exist:nnTF {#1} { unknown }
          {
            \clist_put_right:Nv \l__keys_options_clist
              { opt@ \@currname . \@currext }
          }
          {
            \clist_map_inline:cn { opt@ \@currname . \@currext }
              {
                \keys_if_exist:neTF
                  {#1} { \__keys_remove_equals:n {##1} }
                  { \clist_put_right:Nn \l__keys_options_clist {##1} }
                  { \clist_put_right:Nn \@unusedoptionlist {##1} }
              }
          }
      }
  }
```

(*End definition for* `\__keys_options_class:n`.)

`\__keys_options_package:n` For global options when processing a package, the tasks are slightly different from those for a class. The check is the same, but here there is nothing to do if the option is not applicable. Each valid option also needs to be removed from `\@unusedoptionlist`.

```
\cs_new_protected:Npn \__keys_options_package:n #1
  {
    \clist_map_inline:Nn \@classoptionslist
      {
        \keys_if_exist:neT {#1} { \__keys_remove_equals:n {##1} }
          {
            \clist_put_right:Nn \l__keys_options_clist {##1}
            \clist_remove_all:Nn \@unusedoptionlist {##1}
          }
      }
  }
```

(*End definition for* `\__keys_options_package:n`.)

`\__keys_options_local:` If local options are found, the are added to the processing list. LaTeX 2_ε stores options for each file in a macro which may or may not exist, hence the need to use `\cs_if_exist:c`.

```
\cs_new_protected:Npn \__keys_options_local:
  {
    \cs_if_eq:NNF \@currext \@clsextension
      {
        \cs_if_exist:cT { opt@ \@currname . \@currext }
          {
            \clist_put_right:Nv \l__keys_options_clist
              { opt@ \@currname . \@currext }
          }
      }
  }
```

(*End definition for* `\__keys_options_local:`.)

`\__keys_remove_equals:n` `\__keys_remove_equals:w`

As the name suggests, this is a simple function to remove an equals sign from the input. This is all wrapped up in an `n` function so that there will always be a sign available.

```
\cs_new:Npn \__keys_remove_equals:n #1
  { \__keys_remove_equals:w #1 = \s__keys_stop }
\cs_new:Npn \__keys_remove_equals:w #1 = #2 \s__keys_stop { \exp_not:n {#1} }
```

(*End definition for* `\__keys_remove_equals:n` *and* `\__keys_remove_equals:w`.)

1.4 The document interfaces

```
\cs_generate_variant:Nn \keys_define:nn { nx }
```

`\__keys_options_expand_module:Nn` `\__keys_options_expand_module:nN`

To deal with active characters inside the module argument whilst also expanding that argument, we use a combination of `c`- and `f`-type expansion. This works as the definitions for active UTF-8 bytes contain an `\ifincsname` test.

```
\cs_new_protected:Npn \__keys_options_expand_module:Nn #1#2
  {
    \cs:w __keys_options_expand_module:nN \use:e { \cs_end: {#2} } #1
  }
\cs_new_protected:Npn \__keys_options_expand_module:nN #1#2
  { #2 {#1} }
```

(*End definition for* `\__keys_options_expand_module:Nn` *and* `\__keys_options_expand_module:nN`.)

`\DeclareKeys`

Defining key options is quite straight-forward: we have an intermediate function to allow for potential set-up steps.

```
\NewDocumentCommand \DeclareKeys { O { \@currname } +m }
  { \__keys_options_expand_module:Nn \keys_define:nn {#1} {#2} }
```

(*End definition for* `\DeclareKeys`. *This function is documented on page* 868.)

`\DeclareUnknownKeyHandler`

```
\NewDocumentCommand \DeclareUnknownKeyHandler { O { \@currname } +m }
  {
    \cs_set_protected:cpn { __keys_unknown_handler_ #1 :nn } ##1##2 {#2}
    \__keys_options_expand_module:Nn \keys_define:nx {#1}
      {
        unknown .code:n =
          \exp_not:N \exp_args:NV
            \exp_not:c { __keys_unknown_handler_ #1 :nn }
            \exp_not:N \l_keys_key_str {####1}
```

```
      }
  }
```

(*End definition for* `\DeclareUnknownKeyHandler`. *This function is documented on page* 868.)

`\ProcessKeyOptions` We need to deal with the older interface from l3keys2e here: it had a mandatory argument. We can mop that up using a look-ahead, and then exploit that information to determine whether the package option handling is set up for the new approach for clash handling.

```
\NewDocumentCommand \ProcessKeyOptions { O { \@currname } }
  { \__keys_options:n {#1} }
\@onlypreamble \ProcessKeyOptions
```

(*End definition for* `\ProcessKeyOptions`. *This function is documented on page* 869.)

1.5 Option usage scope

`\__keys_options_loaded:n` `\__keys_options_loaded:nn` Indicates that the load-time options for a package have been processed: once this has happened, make them unavailable either with a warning or an error.

```
\cs_new_protected:Npn \__keys_options_loaded:n #1
  {
    \prop_get:NnNT \l_keys_usage_load_prop {#1} \l__keys_tmpa_tl
      {
        \clist_map_inline:Nn \l__keys_tmpa_tl
          {
            \keys_define:nn {#1}
              {
                ##1 .code:n =
                  \__keys_options_loaded:nn {#1} {##1}
              }
          }
      }
  }
\cs_new_protected:Npn \__keys_options_loaded:nn #1#2
  {
    \bool_if:NTF \l__keys_options_loading_bool
      {
        \msg_warning:nnxx { keys } { load-option-ignored }
          { \use:c { opt@fam@\@currname.\@currext } } {#2}
      }
      { \msg_error:nnnn { keys } { load-only } {#1} {#2} }
  }
\msg_new:nnn { keys } { load-option-ignored }
  { Package~"#1"~has~already~been~loaded:~ignoring~load-time~option~"#2". }
\msg_new:nnnn { keys } { load-only }
  { Key~"#2"~may~only~be~used~in~the~during~loading~of~package~"#1". }
  {
    LaTeX~was~asked~to~set~a~key~called~"#2",~but~this~is~only~allowed~
    in~the~optional~argument~when~loading~package~"#1".
  }
```

(*End definition for* `\__keys_options_loaded:n` *and* `\__keys_options_loaded:nn`.)

Disable all preamble options in one shot.

```
\tl_gput_left:Nn \@kernel@after@begindocument
  {
```

```
    \prop_map_inline:Nn \l_keys_usage_preamble_prop
      {
        \clist_map_inline:nn {#2}
          {
            \keys_define:nn {#1}
              {
                ##1 .code:n =
                  \msg_error:nnn { keys } { preamble-only } {##1}
              }
          }
      }
  }
\msg_new:nnnn { keys } { preamble-only }
  { Key~"#1"~may~only~be~used~in~the~preamble. }
  {
    LaTeX~was~asked~to~set~a~key~called~"#1",~but~this~is~only~allowed~
    before~\begin{document}.~You~will~need~to~set~the~key~earlier.
  }
```

1.6 General key setting

\SetKeys A simple wrapper.

```
\NewDocumentCommand \SetKeys { O { \@currname } +m }
  { \__keys_options_expand_module:Nn \keys_set:nn {#1} {#2} }
```

(*End definition for* \SetKeys. *This function is documented on page* 869.)

```
\ExplSyntaxOff
```

⟨/2ekernel⟩

File W
ltfilehook.dtx

1 Introduction

1.1 Provided hooks

The code offers a number of hooks into which packages (or the user) can add code to support different use cases. Many hooks are offered as pairs (i.e., the second hook is reversed. Also important to know is that these pairs are properly nested with respect to other pairs of hooks.

There are hooks that are executed for all files of a certain type (if they contain code), e.g., for all "include files" or all "packages", and there are also hooks that are specific to a single file, e.g., do something after the package `foo.sty` has been loaded.

1.2 General hooks for file reading

There are four hooks that are called for each file that is read using document-level commands such as `\input`, `\include`, `\usepackage`, etc. They are not called for files read using internal low-level methods, such as `\@input` or `\openin`.

`file/before`
`file/.../before`
`file/.../after`
`file/after`

These are:

`file/before`, `file/`⟨*file-name*⟩`/before` These hooks are executed in that order just before the file is loaded for reading. The code of the first hook is used with every file, while the second is executed only for the file with matching ⟨*file-name*⟩ allowing you to specify code that only applies to one file.

`file/`⟨*file-name*⟩`/after`, `file/after` These hooks are after the file with name ⟨*file-name*⟩ has been fully consumed. The order is swapped (the specific one comes first) so that the `/before` and `/after` hooks nest properly, which is important if any of them involve grouping (e.g., contain environments, for example). Furthermore both hooks are reversed hooks to support correct nesting of different packages adding code to both `/before` and `/after` hooks.

So the overall sequence of hook processing for any file read through the user interface commands of LaTeX is:

```
\UseHook{⟨file/before⟩}
\UseHook{⟨file/⟨file name⟩/before⟩}
    ⟨file contents⟩
\UseHook{⟨file/⟨file name⟩/after⟩}
\UseHook{⟨file/after⟩}
```

The file hooks only refer to the file by its name and extension, so the ⟨*file name*⟩ should be the file name as it is on the filesystem with extension (if any) and without paths. Different from `\input` and similar commands, the `.tex` extension is not assumed in hook ⟨*file name*⟩, so `.tex` files must be specified with their extension to be recognized. Files within subfolders should also be addressed by their name and extension only.

Extensionless files also work, and should then be given without extension. Note however that TEX prioritizes `.tex` files, so if two files `foo` and `foo.tex` exist in the search path, only the latter will be seen.

When a file is input, the ⟨*file name*⟩ is available in `\CurrentFile`, which is then used when accessing the `file/`⟨*file name*⟩`/before` and `file/`⟨*file name*⟩`/after`.

`\CurrentFile`

The name of the file about to be read (or just finished) is available to the hooks through `\CurrentFile` (there is no `expl3` name for it for now). The file is always provided with its extension, i.e., how it appears on your hard drive, but without any specified path to it. For example, `\input{sample}` and `\input{app/sample.tex}` would both have `\CurrentFile` being `sample.tex`.

`\CurrentFilePath`

The path to the current file (complement to `\CurrentFile`) is available in `\CurrentFilePath` if needed. The paths returned in `\CurrentFilePath` are only user paths, given through `\input@path` (or `expl3`'s equivalent `\l_file_search_path_seq`) or by directly typing in the path in the `\input` command or equivalent. Files located by `kpsewhich` get the path added internally by the TEX implementation, so at the macro level it looks as if the file were in the current folder, so the path in `\CurrentFilePath` is empty in these cases (package and class files, mostly).

`\CurrentFileUsed`
`\CurrentFilePathUsed`

In normal circumstances these are identical to `\CurrentFile` and `\CurrentFilePath`. They will differ when a file substitution has occurred for `\CurrentFile`. In that case, `\CurrentFileUsed` and `\CurrentFilePathUsed` will hold the actual file name and path loaded by LATEX, while `\CurrentFile` and `\CurrentFilePath` will hold the names that were *asked for*. Unless doing very specific work on the file being read, `\CurrentFile` and `\CurrentFilePath` should be enough.

1.3 Hooks for package and class files

Commands to load package and class files (e.g., `\usepackage`, `\RequirePackage`, `\LoadPackageWithOptions`, etc.) offer the hooks from section 1.2 when they are used to load a package or class file, e.g., `file/array.sty/after` would be called after the `array` package got loaded. But as packages and classes form as special group of files, there are some additional hooks available that only apply when a package or class is loaded.

`package/before`
`package/after`
`package/.../before`
`package/.../after`
`class/before`
`class/after`
`class/.../before`
`class/.../after`

These are:

`package/before`, `package/after` These hooks are called for each package being loaded.

`package/`⟨*name*⟩`/before`, `package/`⟨*name*⟩`/after` These hooks are additionally called if the package name is ⟨*name*⟩ (without extension).

`class/before`, `class/after` These hooks are called for each class being loaded.

`class/`⟨*name*⟩`/before`, `class/`⟨*name*⟩`/after` These hooks are additionally called if the class name is ⟨*name*⟩ (without extension).

All `/after` hooks are implemented as reversed hooks.
The overall sequence of execution for `\usepackage` and friends is therefore:

```
\UseHook{⟨package/before⟩}
\UseHook{⟨package/⟨package name⟩/before⟩}
    \UseHook{⟨file/before⟩}
    \UseHook{⟨file/⟨package name⟩.sty/before⟩}
        ⟨package contents⟩
    \UseHook{⟨file/⟨package name⟩.sty/after⟩}
    \UseHook{⟨file/after⟩}
    code from \AtEndOfPackage if used inside the package
\UseHook{⟨package/⟨package name⟩/after⟩}
\UseHook{⟨package/after⟩}
```

and similar for class file loading, except that `package/` is replaced by `class/` and `\AtEndOfPackage` by `\AtEndOfClass`.

If a package or class is not loaded (or it was loaded before the hooks were set) none of the hooks are executed!

All class or package hooks involving the name of the class or package are implemented as one-time hooks, whereas all other such hooks are normal hooks. This allows for the following use case

```
\AddToHook{package/varioref/after}
      { ... apply my customizations if the package gets
        loaded (or was loaded already) ... }
```

without the need to first test if the package is already loaded.

1.4 Hooks for `\include` files

To manage `\include` files, LaTeX issues a `\clearpage` before and after loading such a file. Depending on the use case one may want to execute code before or after these `\clearpage`s especially for the one that is issued at the end.

Executing code before the final `\clearpage`, means that the code is processed while the last page of the included material is still under construction. Executing code after it means that all floats from inside the include file are placed (which might have added further pages) and the final page has finished.

Because of these different scenarios we offer hooks in three places.[40] None of the hooks are executed when an `\include` file is bypassed because of an `\includeonly` declaration. They are, however, all executed if LaTeX makes an attempt to load the `\include` file (even if it doesn't exist and all that happens is "`No file ⟨filename⟩.tex`").

[40] If you want to execute code before the first `\clearpage` there is no need to use a hook—you can write it directly in front of the `\include`.

include/before
include/.../before
include/end
include/.../end
include/after
include/.../after

These are:

include/before, include/⟨*name*⟩/before These hooks are executed (in that order) after the initial `\clearpage` and after `.aux` file is changed to use ⟨*name*⟩`.aux`, but before the ⟨*name*⟩`.tex` file is loaded. In other words they are executed at the very beginning of the first page of the `\include` file.

include/⟨*name*⟩/end, include/end These hooks are executed (in that order) after LaTeX has stopped reading from the `\include` file, but before it has issued a `\clearpage` to output any deferred floats.

include/⟨*name*⟩/after, include/after These hooks are executed (in that order) after LaTeX has issued the `\clearpage` but before is has switched back writing to the main `.aux` file. Thus technically we are still inside the `\include` and if the hooks generate any further typeset material including anything that writes to the `.aux` file, then it would be considered part of the included material and bypassed if it is not loaded because of some `\includeonly` statement.[41]

include/excluded, include/⟨*name*⟩/excluded The above hooks for `\include` files are only executed when the file is loaded (or more exactly the load is attempted). If, however, the `\include` file is explicitly excluded (through an `\includeonly` statement) the above hooks are bypassed and instead the `include/excluded` hook followed by the `include/`⟨*name*⟩`/excluded` hook are executed. This happens after LaTeX has loaded the `.aux` file for this include file, i.e., after LaTeX has updated its counters to pretend that the file was seen.

All `include` hooks involving the name of the included file are implemented as one-time hooks (whereas all other such hooks are normal hooks).

If you want to execute code that is run for every `\include` regardless of whether or not it is excluded, use the `cmd/include/before` or `cmd/include/after` hooks.

1.5 High-level interfaces for LaTeX

We do not provide any additional wrappers around the hooks (like filehook or scrlfile do) because we believe that for package writers the high-level commands from the hook management, e.g., `\AddToHook`, etc. are sufficient and in fact easier to work with, given that the hooks have consistent naming conventions.

[41] For that reason another `\clearpage` is executed after these hooks which normally does nothing, but starts a new page if further material got added this way.

1.6 Internal interfaces for LaTeX

`\declare@file@substitution`	`\declare@file@substitution {⟨file⟩} {⟨replacement-file⟩}`
`\undeclare@file@substitution`	`\undeclare@file@substitution {⟨file⟩}`

If ⟨*file*⟩ is requested for loading replace it with ⟨*replacement-file*⟩. `\CurrentFile` remains pointing to ⟨*file*⟩ but `\CurrentFileUsed` will show the file actually loaded.

The main use case for this declaration is to provide a corrected version of a package that can't be changed (due to its license) but no longer functions because of LaTeX kernel changes, for example, or to provide a version that makes use of new kernel functionality while the original package remains available for use with older releases.

The `\undeclare@file@substitution` declaration undoes a substitution made earlier.

> *Please do not misuse this functionality and replace a file with another unless if really needed and only if the new version is implementing the same functionality as the original one!*

`\disable@package@load`	`\disable@package@load {⟨package⟩} {⟨alternate-code⟩}`
`\reenable@package@load`	`\reenable@package@load {⟨package⟩}`

If ⟨*package*⟩ is requested do not load it but instead run ⟨*alternate-code*⟩ which could issue a warning, error or any other code.

The main use case is for classes that want to restrict the set of supported packages or contain code that make the use of some packages impossible. So rather than waiting until the document breaks they can set up informative messages why certain packages are not available.

The function is only implemented for packages not for arbitrary files.

1.7 A sample package for structuring the log output

As an application we provide the package structuredlog that adds lines to the `.log` when a file is opened and closed for reading keeping track of nesting level es well. For example, for the current document it adds the lines

```
= (LEVEL 1 START) t1lmr.fd
= (LEVEL 1 STOP) t1lmr.fd
= (LEVEL 1 START) supp-pdf.mkii
= (LEVEL 1 STOP) supp-pdf.mkii
= (LEVEL 1 START) nameref.sty
== (LEVEL 2 START) refcount.sty
== (LEVEL 2 STOP) refcount.sty
== (LEVEL 2 START) gettitlestring.sty
== (LEVEL 2 STOP) gettitlestring.sty
= (LEVEL 1 STOP) nameref.sty
= (LEVEL 1 START) ltfilehook-doc.out
= (LEVEL 1 STOP) ltfilehook-doc.out
= (LEVEL 1 START) ltfilehook-doc.out
= (LEVEL 1 STOP) ltfilehook-doc.out
= (LEVEL 1 START) ltfilehook-doc.hd
```

```
= (LEVEL 1 STOP) ltfilehook-doc.hd
= (LEVEL 1 START) ltfilehook.dtx
== (LEVEL 2 START) ot1lmr.fd
== (LEVEL 2 STOP) ot1lmr.fd
== (LEVEL 2 START) omllmm.fd
== (LEVEL 2 STOP) omllmm.fd
== (LEVEL 2 START) omslmsy.fd
== (LEVEL 2 STOP) omslmsy.fd
== (LEVEL 2 START) omxlmex.fd
== (LEVEL 2 STOP) omxlmex.fd
== (LEVEL 2 START) umsa.fd
== (LEVEL 2 STOP) umsa.fd
== (LEVEL 2 START) umsb.fd
== (LEVEL 2 STOP) umsb.fd
== (LEVEL 2 START) ts1lmr.fd
== (LEVEL 2 STOP) ts1lmr.fd
== (LEVEL 2 START) t1lmss.fd
== (LEVEL 2 STOP) t1lmss.fd
= (LEVEL 1 STOP) ltfilehook.dtx
```

Thus if you inspect an issue in the `.log` it is easy to figure out in which file it occurred, simply by searching back for `LEVEL` and if it is a `STOP` then remove 1 from the level value and search further for `LEVEL` with that value which should then be the `START` level of the file you are in.

2 The Implementation

```
⟨*2ekernel⟩
⟨@@=filehook⟩
```

2.1 Document and package-level commands

`\CurrentFile`
`\CurrentFilePath`
`\CurrentFileUsed`
`\CurrentFilePathUsed`

User-level macros that hold the current file name and file path. These are used internally as well because the code takes care to protect against a possible redefinition of these macros in the loaded file (it's necessary anyway to make hooks work with nested `\input`). The versions `\...Used` hold the *actual* file name and path that is loaded by LaTeX, whereas the other two hold the name as requested. They will differ in case there's a file substitution.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\CurrentFile}{Hook management file}%
\ExplSyntaxOn
\tl_new:N \CurrentFile
\tl_new:N \CurrentFilePath
\tl_new:N \CurrentFileUsed
\tl_new:N \CurrentFilePathUsed
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\CurrentFile}{Hook management file}%
⟨latexrelease⟩
⟨latexrelease⟩\let \CurrentFile         \@undefined
⟨latexrelease⟩\let \CurrentFilePath     \@undefined
⟨latexrelease⟩\let \CurrentFileUsed     \@undefined
⟨latexrelease⟩\let \CurrentFilePathUsed \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\CurrentFile` *and others. These functions are documented on page* *876*.)

2.2 expl3 helpers

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {\__filehook_file_parse_full_name:nN}{File helpers}%
\ExplSyntaxOn
```

`\__filehook_file_parse_full_name:nN`
`\__filehook_full_name:nn`

A utility macro to trigger expl3's file-parsing and lookup, and return a normalized representation of the file name. If the queried file doesn't exist, no normalization takes place. The output of `\__filehook_file_parse_full_name:nN` is passed on to the `#2`—a 3-argument macro that takes the ⟨*path*⟩, ⟨*base*⟩, and ⟨*ext*⟩ parts of the file name.

```
\cs_new:Npn \__filehook_file_parse_full_name:nN #1
  {
    \exp_args:Nf \file_parse_full_name_apply:nN
      {
        \exp_args:Nf \__filehook_full_name:nn
          { \file_full_name:n {#1} } {#1}
      }
  }
\cs_new:Npn \__filehook_full_name:nn #1 #2
  {
    \tl_if_empty:nTF {#1}
      { \tl_trim_spaces:n {#2} }
      { \tl_trim_spaces:n {#1} }
  }
```

(*End definition for* `\__filehook_file_parse_full_name:nN` *and* `\__filehook_full_name:nn`.)

`\__filehook_if_no_extension:nTF`
`\__filehook_drop_extension:N`

Some actions depend on whether the file extension was explicitly given, and sometimes the extension has to be removed. The macros below use `\__filehook_file_parse_full_name:nN` to split up the file name and either check if ⟨*ext*⟩ (`#3`) is empty, or discard it.

```
\cs_new:Npn \__filehook_if_no_extension:nTF #1
  {
    \exp_args:Ne \tl_if_empty:nTF
      { \file_parse_full_name_apply:nN {#1} \use_iii:nnn }
  }
\cs_new_protected:Npn \__filehook_drop_extension:N #1
  {
    \tl_gset:Nx #1
```

```
      {
        \exp_args:NV \__filehook_file_parse_full_name:nN #1
          \__filehook_drop_extension_aux:nnn
      }
  }
\cs_new:Npn \__filehook_drop_extension_aux:nnn #1 #2 #3
   { \tl_if_empty:nF {#1} { #1 / } #2 }
```

(*End definition for* `\__filehook_if_no_extension:nTF` *and* `\__filehook_drop_extension:N`.)

`\g__filehook_input_file_seq`
`\l__filehook_internal_tl`
`\__filehook_file_push:`
`\__filehook_file_pop:`
`\__filehook_file_pop_assign:nnnn`

Yet another stack, to keep track of `\CurrentFile` and `\CurrentFilePath` with nested `\inputs`. At the beginning of `\InputIfFileExists`, the current value of `\CurrentFilePath` and `\CurrentFile` is pushed to `\g__filehook_input_file_seq`, and at the end, it is popped and the value reassigned. Some other places don't use `\InputIfFileExists` directly (`\include`) or need `\CurrentFile` earlier (`\@onefilewithoptions`), so these are manually used elsewhere as well.

```
\tl_new:N \l__filehook_internal_tl
\seq_if_exist:NF \g__filehook_input_file_seq
  { \seq_new:N \g__filehook_input_file_seq }
\cs_new_protected:Npn \__filehook_file_push:
  {
    \seq_gpush:Nx \g__filehook_input_file_seq
      {
        { \CurrentFilePathUsed } { \CurrentFileUsed }
        { \CurrentFilePath     } { \CurrentFile     }
      }
  }
\cs_new_protected:Npn \__filehook_file_pop:
  {
    \seq_gpop:NNTF \g__filehook_input_file_seq \l__filehook_internal_tl
      { \exp_after:wN \__filehook_file_pop_assign:nnnn \l__filehook_internal_tl }
      {
        \msg_error:nnn { latex2e } { should-not-happen }
          { Tried~to~pop~from~an~empty~file~name~stack. }
      }
  }
\cs_new_protected:Npn \__filehook_file_pop_assign:nnnn #1 #2 #3 #4
  {
    \tl_set:Nn \CurrentFilePathUsed {#1}
    \tl_set:Nn \CurrentFileUsed {#2}
    \tl_set:Nn \CurrentFilePath {#3}
    \tl_set:Nn \CurrentFile {#4}
  }
\ExplSyntaxOff
```

(*End definition for* `\g__filehook_input_file_seq` *and others.*)

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

When rolling forward the following expl3 functions may not be defined. If we roll back the code does nothing.

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\file_parse_full_name_apply:nN}{Roll forward help}%
⟨latexrelease⟩
```

```
⟨latexrelease⟩\ExplSyntaxOn
⟨latexrelease⟩\cs_if_exist:NF\file_parse_full_name_apply:nN
⟨latexrelease⟩{
⟨latexrelease⟩\cs_new:Npn \file_parse_full_name_apply:nN #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \exp_args:Ne \__file_parse_full_name_auxi:nN
⟨latexrelease⟩      { \__kernel_file_name_sanitize:n {#1} }
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new:Npn \__file_parse_full_name_auxi:nN #1
⟨latexrelease⟩  {
⟨latexrelease⟩    \__file_parse_full_name_area:nw { } #1
⟨latexrelease⟩      / \s__file_stop
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new:Npn \__file_parse_full_name_area:nw #1 #2 / #3 \s__file_stop
⟨latexrelease⟩  {
⟨latexrelease⟩    \tl_if_empty:nTF {#3}
⟨latexrelease⟩      { \__file_parse_full_name_base:nw { } #2 . \s__file_stop {#1} }
⟨latexrelease⟩      { \__file_parse_full_name_area:nw { #1 / #2 }
⟨latexrelease⟩                                        #3 \s__file_stop }
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new:Npn \__file_parse_full_name_base:nw #1 #2 . #3 \s__file_stop
⟨latexrelease⟩  {
⟨latexrelease⟩    \tl_if_empty:nTF {#3}
⟨latexrelease⟩      {
⟨latexrelease⟩        \tl_if_empty:nTF {#1}
⟨latexrelease⟩          {
⟨latexrelease⟩            \tl_if_empty:nTF {#2}
⟨latexrelease⟩              { \__file_parse_full_name_tidy:nnnN { } { } }
⟨latexrelease⟩              { \__file_parse_full_name_tidy:nnnN { .#2 } { } }
⟨latexrelease⟩          }
⟨latexrelease⟩          { \__file_parse_full_name_tidy:nnnN {#1} { .#2 } }
⟨latexrelease⟩      }
⟨latexrelease⟩      { \__file_parse_full_name_base:nw { #1 . #2 }
⟨latexrelease⟩                                        #3 \s__file_stop }
⟨latexrelease⟩  }
⟨latexrelease⟩\cs_new:Npn \__file_parse_full_name_tidy:nnnN #1 #2 #3 #4
⟨latexrelease⟩  {
⟨latexrelease⟩    \exp_args:Nee #4
⟨latexrelease⟩      {
⟨latexrelease⟩        \str_if_eq:nnF {#3} { / } { \use_none:n }
⟨latexrelease⟩        #3 \prg_do_nothing:
⟨latexrelease⟩      }
⟨latexrelease⟩      { \use_none:n #1 \prg_do_nothing: }
⟨latexrelease⟩      {#2}
⟨latexrelease⟩  }
⟨latexrelease⟩}
⟨latexrelease⟩\ExplSyntaxOff
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
⟨@@=⟩
```

2.3 Declaring the file-related hooks

These hooks have names with three-parts that start with `file/`, `include/`, `class/` or `package/` and end with `/before` or `/after` (or `/end` in the case of `include/`). They are all generic hooks so will be declared only if code is added to them; this declaration is done for you automatically and, indeed, they should not be declared explicitly.

Those named `.../after` and `include/.../end` are, when code is added, declared as reversed hooks.

2.4 Patching LaTeX's `\InputIfFileExists` command

Most of what we have to do is adding `\UseHook` into several LaTeX 2_ε core commands, because of some circular dependencies in the kernel we do this only now and not in `ltfiles`.

`\InputIfFileExists`
`\@input@file@exists@with@hooks`
`\unqu@tefilef@und`

`\InputIfFileExists` loads any file if it is available so we have to add the hooks `file/before` and `file/after` in the right places. If the file doesn't exist no hooks should be executed.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {\InputIfFileExists}{Hook management (files)}%
⟨*2ekernel | latexrelease⟩
```

```
\let\InputIfFileExists\@undefined
\DeclareRobustCommand \InputIfFileExists[2]{%
  \IfFileExists{#1}%
    {%
      \@expl@@@filehook@file@push@@
      \@filehook@set@CurrentFile
```

We pre-expand `\@filef@und` so that in case another file is loaded in the true branch of `\InputIfFileExists`, these don't change their value meanwhile. This isn't a worry with `\CurrentFile...` because they are kept in a stack.

```
      \expandafter\@swaptwoargs\expandafter
        {\expandafter\@input@file@exists@with@hooks
          \expandafter{\@filef@und}}%
        {#2}%
      \@expl@@@filehook@file@pop@@
    }%
}
\def\@input@file@exists@with@hooks#1{%
```

If the file exists then `\CurrentFile` holds its name. But we can't rely on that still being true after the file has been processed. Thus for using the name in the file hooks we need to preserve the name and then restore it for the `file/.../after` hook.

The hook always refers to the file requested by the user. The hook is *always* loaded for `\CurrentFile` which usually is the same as `\CurrentFileUsed`. In the case of a file replacement, the `\CurrentFileUsed` holds the actual file loaded. In any case the file names are normalized so that the hooks work on the real file name, rather than what the user typed in.

expl3's `\file_full_name:n` normalizes the file name (to factor out differences in the `.tex` extension), and then does a file lookup to take into account a possible path from `\l_file_search_path_seq` and `\input@path`. However only the file name and extension

are returned so that file hooks can refer to the file by their name only. The path to the file is returned in `\CurrentFilePath`.

```
  \edef\reserved@a{%
    \@expl@@@filehook@file@pop@assign@@nnnn
      {\CurrentFilePathUsed}%
      {\CurrentFileUsed}%
      {\CurrentFilePath}%
      {\CurrentFile}}%
  \expandafter\@swaptwoargs\expandafter{\reserved@a}%
```

Before adding to the file list we need to make all (letter) characters catcode 11, because several packages use constructions like

```
\filename@parse{<filename>}
\ifx\filename@ext\@clsextension
  ...
\fi
```

and that doesn't work if `\filename@ext` is `\detokenized`. Making `\@clsextension` a string doesn't help much because some packages define their own `\<prefix>@someextension` with normal catcodes. This is not entirely correct because packages loaded (somehow) with catcode 12 alphabetic tokens (say, as the result of a `\string` or `\detokenize` command, or from a TEX string like `\jobname`) will have these character tokens incorrectly turned into letter tokens. This however is rare, so we'll go for the all-letters approach (grepping the packages in TEX Live didn't bring up any obvious candidate for breaking with this catcode change).

```
    {\edef\reserved@a{\unqu@tefilef@und#1\@nil}%
     \@addtofilelist{\string@makeletter\reserved@a}%
     \UseHook{file/before}%
```

The current file name is available in `\CurrentFile` so we use that in the specific hook.

```
     \UseHook{file/\CurrentFile/before}%
     \@@input #1% <- trailing space comes from \@filef@und
    }%
```

And here, `\CurrentFile` is restored (by `\@expl@@@filehook@file@pop@assign@@nnnn`) so we can use it once more.

```
  \UseHook{file/\CurrentFile/after}%
  \UseHook{file/after}}
\def\unqu@tefilef@und"#1" \@nil{#1}
```

Now declare the non-generic file hooks used above:

```
\NewHook{file/before}
\NewReversedHook{file/after}
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
```

Now define `\InputIfFileExists` to input `#1` if it seems to exist. Immediately prior to the input, `#2` is executed. If the file `#1` does not exist, execute '`#3`'.

```
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩          {\InputIfFileExists}{Hook management (files)}%
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand \InputIfFileExists[2]{%
⟨latexrelease⟩  \IfFileExists{#1}%
⟨latexrelease⟩    {%
```

```
⟨latexrelease⟩  \expandafter\@swaptwoargs\expandafter
⟨latexrelease⟩      {\@filef@und}{#2\@addtofilelist{#1}\@@input}}}
⟨latexrelease⟩\let\@input@file@exists@with@hooks\@undefined
⟨latexrelease⟩\let\unqu@tefilef@und\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩          {\InputIfFileExists}{Hook management (files)}%
⟨latexrelease⟩\long\def \InputIfFileExists#1#2{%
⟨latexrelease⟩  \IfFileExists{#1}%
⟨latexrelease⟩    {#2\@addtofilelist{#1}\@@input \@filef@und}}
```

Also undo the internal command as some packages unfortunately test for their existence instead of using `\IfFormatAtLeastTF`.

```
⟨latexrelease⟩\expandafter\let\csname InputIfFileExists \endcsname\@undefined
```

```
⟨latexrelease⟩\let\@input@file@exists@with@hooks\@undefined
⟨latexrelease⟩\let\unqu@tefilef@und\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\InputIfFileExists`, `\@input@file@exists@with@hooks`, *and* `\unqu@tefilef@und`.)

2.5 Declaring a file substitution

```
⟨@@=filehook⟩
```

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {\__filehook_subst_add:nn}{Declaring file substitution}%
\ExplSyntaxOn
```

`\__filehook_subst_add:nn`
`\__filehook_subst_remove:n`
`\__filehook_subst_file_normalize:Nn`
`\__filehook_subst_empty_name_chk:NN`

`\__filehook_subst_add:nn` declares a file substitution by doing a (global) definition of the form `\def\@file-subst@`⟨*file*⟩`{`⟨*replacement*⟩`}`. The file names are properly sanitised, and normalized with the same treatment done for the file hooks. That is, a file replacement is declared by using the file name (and extension, if any) only, and the file path should not be given. If a file name is empty it is replaced by `.tex` (the empty csname is used to check that).

```
\cs_new_protected:Npn \__filehook_subst_add:nn #1 #2
  {
    \group_begin:
      \cs_set:cpx { } { \exp_not:o { \cs:w\cs_end: } }
      \int_set:Nn \tex_escapechar:D { -1 }
      \cs_gset:cpx
        {
          @file-subst@
          \__filehook_subst_file_normalize:Nn \use_ii_iii:nnn {#1}
        }
        { \__filehook_subst_file_normalize:Nn \__filehook_file_name_compose:nnn
                                        {#2} }
    \group_end:
  }
\cs_new_protected:Npn \__filehook_subst_remove:n #1
  {
    \group_begin:
```

```
      \cs_set:cpx { } { \exp_not:o { \cs:w\cs_end: } }
      \int_set:Nn \tex_escapechar:D { -1 }
      \cs_undefine:c
        {
          @file-subst@
          \__filehook_subst_file_normalize:Nn \use_ii_iii:nnn {#1}
        }
    \group_end:
  }
\cs_new:Npn \__filehook_subst_file_normalize:Nn #1 #2
  {
    \exp_after:wN \__filehook_subst_empty_name_chk:NN
      \cs:w \exp_after:wN \cs_end:
        \cs:w \__filehook_file_parse_full_name:nN {#2} #1 \cs_end:
  }
\cs_new:Npn \__filehook_subst_empty_name_chk:NN #1 #2
  { \if_meaning:w #1 #2 .tex \else: \token_to_str:N #2 \fi: }
```

(*End definition for* `\__filehook_subst_add:nn` *and others.*)

`\use_ii_iii:nnn` A variant of `\use_...` to discard the first of three arguments.

Todo: this should move to expl3

```
\cs_gset:Npn \use_ii_iii:nnn #1 #2 #3 {#2 #3}
```

(*End definition for* `\use_ii_iii:nnn`.)

```
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

`\declare@file@substitution` `\undeclare@file@substitution` For two internals we provide LaTeX 2ε names so that we can use them elsewhere in the kernel (and so that they can be used in packages if really needed, e.g., scrlfile).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {\declare@file@substitution}{File substitution}%
\ExplSyntaxOn
\cs_new_eq:NN \declare@file@substitution   \__filehook_subst_add:nn
\cs_new_eq:NN \undeclare@file@substitution \__filehook_subst_remove:n
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

We are not fully rolling back the file substitutions in case a rollback encounters a package that contains them, but is itself not setup for rollback. So we just bypass them and hope for the best.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩          {\declare@file@substitution}{File substitution}%
⟨latexrelease⟩
⟨latexrelease⟩\let \declare@file@substitution   \@gobbletwo
⟨latexrelease⟩\let \undeclare@file@substitution \@gobble
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\declare@file@substitution` *and* `\undeclare@file@substitution`*. These functions are documented on page 879.*)

```
⟨@@=⟩
\ExplSyntaxOff
```

2.6 Selecting a file (`\set@curr@file`)

`\set@curr@file`
`\set@curr@file@nosearch`
`\@curr@file`
`\@curr@file@reqd`

Now we hook into `\set@curr@file` to resolve a possible file substitution, and add `\@expl@@@filehook@set@curr@file@@nNN` at the end, after `\@curr@file` is set.

A file name is built using `\expandafter\string\csname`⟨*filename*⟩`\endcsname` to avoid expanding utf8 active characters. The `\csname` expands the normalization machinery and the routine to resolve a file substitution, returning a control sequence with the same name as the file.

It happens that when ⟨*filename*⟩ is empty, the generated control sequence is `\csname\endcsname`, and doing `\string` on that results in the file `csnameendcsname.tex`. To guard against that we `\ifx`-compare the generated control sequence with the empty csname. To do so, `\csname\endcsname` has to be defined, otherwise it would be equal to `\relax` and we would have false positives. Here we define `\csname\endcsname` to expand to itself to avoid it matching the definition of some other control sequence.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩          {\set@curr@file}{Setting current file name}%
\def\set@curr@file{%
  \begingroup
    \set@curr@file@aux}
\edef\set@curr@file@nosearch{%
  \begingroup
    \let\noexpand\input@path\noexpand\@empty
    \csname seq_clear:N\endcsname
      \expandafter\noexpand\csname l_file_search_path_seq\endcsname
    \noexpand\set@curr@file@aux}
\def\set@curr@file@aux#1{%
    \escapechar\m@ne
    \let\protect\string
    \edef~{\string~}%
    \expandafter\def\csname\expandafter\endcsname
      \expandafter{\csname\endcsname}%
```

Two file names are set here: `\@curr@file@reqd` which is the file requested by the user, and `\@curr@file` which should be the same, except when we have a file substitution, in which case it holds the actual loaded file. `\@curr@file` is resolved first, to check if a substitution happens. If it doesn't, `\@expl@@@filehook@if@file@replaced@@TF` short-cuts and just copies `\@curr@file`, otherwise the full normalization procedure is executed.

At this stage the file name is parsed and normalized, but if the input doesn't have an extension, the default `.tex` is *not* added to `\@curr@file` because for applications other than `\input` (graphics, for example) the default extension may not be `.tex`. First check if the input has an extension, then if the input had no extension, call `\@expl@@@filehook@drop@extension@@N`. In case of a file substitution, `\@curr@file` will have an extension.

```
    \@expl@@@filehook@if@no@extension@@nTF{#1}%
```

```
      {\@tempswatrue}{\@tempswafalse}%
    \@kernel@make@file@csname\@curr@file
      \@expl@@@filehook@resolve@file@subst@@w {#1}%
    \@expl@@@filehook@if@file@replaced@@TF
      {\@kernel@make@file@csname\@curr@file@reqd
         \@expl@@@filehook@normalize@file@name@@w{#1}%
       \if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
      {\if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file \fi
       \global\let\@curr@file@reqd\@curr@file}%
    \@expl@@@filehook@clear@replacement@flag@@
  \endgroup}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩          {\set@curr@file}{Setting current file name}%
⟨latexrelease⟩\def\set@curr@file#1{%
⟨latexrelease⟩  \begingroup
⟨latexrelease⟩    \escapechar\m@ne
⟨latexrelease⟩    \let\protect\string
⟨latexrelease⟩    \edef~{\string~}%
⟨latexrelease⟩    \expandafter\def\csname\expandafter\endcsname
⟨latexrelease⟩      \expandafter{\csname\endcsname}%
⟨latexrelease⟩    \@expl@@@filehook@if@no@extension@@nTF{#1}%
⟨latexrelease⟩      {\@tempswatrue}{\@tempswafalse}%
⟨latexrelease⟩    \@kernel@make@file@csname\@curr@file
⟨latexrelease⟩      \@expl@@@filehook@resolve@file@subst@@w {#1}%
⟨latexrelease⟩    \@expl@@@filehook@if@file@replaced@@TF
⟨latexrelease⟩      {\@kernel@make@file@csname\@curr@file@reqd
⟨latexrelease⟩         \@expl@@@filehook@normalize@file@name@@w{#1}%
⟨latexrelease⟩       \if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
⟨latexrelease⟩      {\if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file \fi
⟨latexrelease⟩       \global\let\@curr@file@reqd\@curr@file}%
⟨latexrelease⟩    \@expl@@@filehook@clear@replacement@flag@@
⟨latexrelease⟩  \endgroup}
⟨latexrelease⟩\let\set@curr@file@nosearch\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {\set@curr@file}{Setting current file name}%
⟨latexrelease⟩\def\set@curr@file#1{%
⟨latexrelease⟩  \begingroup
⟨latexrelease⟩    \escapechar\m@ne
⟨latexrelease⟩    \expandafter\def\csname\expandafter\endcsname
⟨latexrelease⟩      \expandafter{\csname\endcsname}%
⟨latexrelease⟩    \@expl@@@filehook@if@no@extension@@nTF{#1}%
⟨latexrelease⟩      {\@tempswatrue}{\@tempswafalse}%
⟨latexrelease⟩    \@kernel@make@file@csname\@curr@file
⟨latexrelease⟩      \@expl@@@filehook@resolve@file@subst@@w {#1}%
⟨latexrelease⟩    \@expl@@@filehook@if@file@replaced@@TF
⟨latexrelease⟩      {\@kernel@make@file@csname\@curr@file@reqd
⟨latexrelease⟩         \@expl@@@filehook@normalize@file@name@@w{#1}%
⟨latexrelease⟩       \if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file@reqd \fi}%
⟨latexrelease⟩      {\if@tempswa \@expl@@@filehook@drop@extension@@N\@curr@file \fi
⟨latexrelease⟩       \global\let\@curr@file@reqd\@curr@file}%
```

```
⟨latexrelease⟩    \@expl@@@filehook@clear@replacement@flag@@
⟨latexrelease⟩  \endgroup}
⟨latexrelease⟩\let\set@curr@file@nosearch\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{2019/10/01}%
⟨latexrelease⟩          {\set@curr@file}{Setting current file name}%
⟨latexrelease⟩\def\set@curr@file#1{%
⟨latexrelease⟩  \begingroup
⟨latexrelease⟩    \escapechar\m@ne
⟨latexrelease⟩    \xdef\@curr@file{%
⟨latexrelease⟩      \expandafter\expandafter\expandafter\unquote@name
⟨latexrelease⟩      \expandafter\expandafter\expandafter{%
⟨latexrelease⟩      \expandafter\string
⟨latexrelease⟩        \csname\@firstofone#1\@empty\endcsname}}%
⟨latexrelease⟩  \endgroup
⟨latexrelease⟩}
⟨latexrelease⟩\let\set@curr@file@nosearch\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩          {\set@curr@file}{Setting current file name}%
⟨latexrelease⟩\let\set@curr@file\@undefined
⟨latexrelease⟩\let\set@curr@file@nosearch\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\set@curr@file` *and others.*)

`\@filehook@set@CurrentFile`
`\@kernel@make@file@csname`
`\@set@curr@file@aux`

Todo: This should get internalized using `@expl@` *names*

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {\@kernel@make@file@csname}{Make file csname}%
```

```
\def\@kernel@make@file@csname#1#2#3{%
  \xdef#1{\expandafter\@set@curr@file@aux
    \csname\expandafter#2\@firstofone#3\@nil\endcsname}}
```

This auxiliary compares \⟨*filename*⟩ with `\csname\endcsname` to check if the empty `.tex` file was requested.

```
\def\@set@curr@file@aux#1{%
  \expandafter\ifx\csname\endcsname#1%
    .tex\else\string#1\fi}
```

Then we call `\@expl@@@filehook@set@curr@file@@nNN` once for `\@curr@file` to set `\CurrentFile(Path)Used` and once for `\@curr@file@reqd` to set `\CurrentFile(Path)`. Here too the slower route is only used if a substitution happened, but here `\@expl@@@filehook@if@file@replaced@@TF` can't be used because the flag is reset at the `\endgroup` above, so we check if `\@curr@file` and `\@curr@file@reqd` differ. This macro is issued separate from `\set@curr@file` because it changes `\CurrentFile`, and side-effects would quickly get out of control.

```
\def\@filehook@set@CurrentFile{%
  \@expl@@@filehook@set@curr@file@@nNN{\@curr@file}%
    \CurrentFileUsed\CurrentFilePathUsed
  \ifx\@curr@file@reqd\@curr@file
```

```
    \let\CurrentFile\CurrentFileUsed
    \let\CurrentFilePath\CurrentFilePathUsed
  \else
    \@expl@@@filehook@set@curr@file@@nNN{\@curr@file@reqd}%
      \CurrentFile\CurrentFilePath
  \fi}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@filehook@set@CurrentFile`, `\@kernel@make@file@csname`, *and* `\@set@curr@file@aux`.)

`\@@_set_curr_file:nNN`
`\@@_set_curr_file_assign:nnnNN`

When inputting a file, `\set@curr@file` does a file lookup (in `\input@path` and `\l_file_search_path_seq`) and returns the actual file name (⟨*base*⟩ plus ⟨*ext*⟩) in `\CurrentFileUsed`, and in case there's a file substitution, the requested file in `\CurrentFile` (otherwise both are the same). Only the base and extension are returned, regardless of the input (both `path/to/file.tex` and `file.tex` end up as `file.tex` in `\CurrentFile`). The path is returned in `\CurrentFilePath`, in case it's needed.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {@@_set_curr_file:nNN}{Set curr file}%
\ExplSyntaxOn
⟨@@=filehook⟩
\cs_new_protected:Npn \__filehook_set_curr_file:nNN #1
  {
    \exp_args:Nf \__filehook_file_parse_full_name:nN {#1}
      \__filehook_set_curr_file_assign:nnnNN
  }
\cs_new_protected:Npn \__filehook_set_curr_file_assign:nnnNN #1 #2 #3 #4 #5
  {
    \str_set:Nn #5 {#1}
    \str_set:Nn #4 {#2#3}
  }
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@@_set_curr_file:nNN` *and* `\@@_set_curr_file_assign:nnnNN`.)

2.7 Replacing a file and detecting loops

`\__filehook_resolve_file_subst:w`
`\__filehook_normalize_file_name:w`
`\__filehook_file_name_compose:nnn`

Start by sanitizing the file with `\__filehook_file_parse_full_name:nN` then do `\__filehook_file_subst_begin:nnn{`⟨*path*⟩`}{`⟨*name*⟩`}{`⟨*ext*⟩`}`.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩     {\__filehook_resolve_file_subst:w}{Replace files detect loops}%
\ExplSyntaxOn
\cs_new:Npn \__filehook_resolve_file_subst:w #1 \@nil
  { \__filehook_file_parse_full_name:nN {#1} \__filehook_file_subst_begin:nnn }
\cs_new:Npn \__filehook_normalize_file_name:w #1 \@nil
```

```
  { \__filehook_file_parse_full_name:nN {#1} \__filehook_file_name_compose:nnn }
\cs_new:Npn \__filehook_file_name_compose:nnn #1 #2 #3
  { \tl_if_empty:nF {#1} { #1 / } #2#3 }
```

flag␣__filehook_file_replaced
__filehook_if_file_replaced:TF
__filehook_clear_replacement_flag:

Since the file replacement is done expandably in a `\csname`, use a flag to remember if a substitution happened. We use this in `\set@curr@file` to short-circuit some of it in case no substitution happened (by far the most common case, so it's worth optimizing). The flag raised during the file substitution algorithm must be explicitly cleared after the `\__filehook_if_file_replaced:TF` conditional is no longer needed, otherwise further uses of `\__filehook_if_file_replaced:TF` will wrongly return true.

```
\flag_new:n { __filehook_file_replaced }
\cs_new:Npn \__filehook_if_file_replaced:TF #1 #2
  { \flag_if_raised:nTF { __filehook_file_replaced } {#1} {#2} }
\cs_new_protected:Npn \__filehook_clear_replacement_flag:
  { \flag_clear:n { __filehook_file_replaced } }
```

__filehook_file_subst_begin:nnn

First off, start by checking if the current file ($\langle name\rangle + \langle ext\rangle$) has a declared substitution. If not, then just put that as the name (including a possible $\langle path\rangle$ in this case): this is the default case with no substitutions, so it's the first to be checked. The auxiliary `\__filehook_file_subst_tortoise_hare:nn` sees that there's no replacement for `#2#3` and does nothing else.

```
\cs_new:Npn \__filehook_file_subst_begin:nnn #1 #2 #3
  {
    \__filehook_file_subst_tortoise_hare:nn { #2#3 } { #2#3 }
      { \__filehook_file_name_compose:nnn {#1} {#2} {#3} }
  }
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

2.7.1 The Tortoise and Hare algorithm

__filehook_file_subst_tortoise_hare:nn
__filehook_file_subst_loop:NN
__filehook_file_subst_loop:cc

If there is a substitution ($\langle true\rangle$ in the first `\cs_if_exist:cTF` below), then first check if there is no substitution down the line: this should be the second most common case, of one file replaced by another. In that case just leave the substitution there and the job is done. If any substitution happens, then the `\flag __filehook_file_replaced` is raised (conditionally, because checking if a flag is raised is much faster than raising it over and over again).

If, however there are more substitutions, then we need to check for a possible loop in the substitutions, which would otherwise put TEX in an infinite loop if just an exhaustive expansion was used.

To detect a loop, the *Tortoise and Hare* algorithm is used. The name of the algorithm is an analogy to Aesop's fable, in which the Hare outruns a Tortoise. The two pointers here are the csnames which contains each file replacement, both of which start at the position zero, which is the file requested. In the inner part of the macro below, `\__filehook_file_subst_loop:cc` is called with `\@file-subst@`$\langle file\rangle$ and `\@file-subst@\@file-subst@`$\langle file\rangle$; that is, the substitution of $\langle file\rangle$ and the substitution of that substitution: the Tortoise walks one step while the Hare walks two.

Within `\__filehook_file_subst_loop:NN` the two substitutions are compared, and if they lead to the same file it means that there is a loop in the substitutions. If there's

no loop, `\__filehook_file_subst_tortoise_hare:nn` is called again with the Tortoise at position 1 and the hare at 2. Again, the substitutions are checked ahead of the Hare pointer to check that it won't run too far; in case there is no loop in the declarations, eventually one of the `\cs_if_exist:cTF` below will go ⟨*false*⟩ and the algorithm will end; otherwise it will run until the Hare reaches the same spot as the tortoise and a loop is detected.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩  {\__filehook_file_subst_tortoise_hare:nn}{Tortoise and Hare}%
\ExplSyntaxOn
\cs_new:Npn \__filehook_file_subst_tortoise_hare:nn #1 #2 #3
  {
    \cs_if_exist:cTF { @file-subst@ #2 }
      {
        \flag_if_raised:nF { __filehook_file_replaced }
          { \flag_raise:n { __filehook_file_replaced } }
        \cs_if_exist:cTF { @file-subst@ \use:c { @file-subst@ #2 } }
          {
            \__filehook_file_subst_loop:cc
              { @file-subst@ #1 }
              { @file-subst@ \use:c { @file-subst@ #2 } }
          }
          { \use:c { @file-subst@ #2 } }
      }
      { #3 }
  }
```

This is just an auxiliary to check if a loop was found, and continue the algorithm otherwise. If a loop is found, the `.tex` file is used as fallback and `\__filehook_file_subst_cycle_error:cN` is called to report the error.

```
\cs_new:Npn \__filehook_file_subst_loop:NN #1 #2
  {
    \token_if_eq_meaning:NNTF #1 #2
      {
        .tex
        \__filehook_file_subst_cycle_error:cN { @file-subst@ #1 } #1
      }
      { \__filehook_file_subst_tortoise_hare:nn {#1} {#2} {#2} }
  }
\cs_generate_variant:Nn \__filehook_file_subst_loop:NN { cc }
```

`\__filehook_file_subst_cycle_error:NN`
`\__filehook_file_subst_cycle_error:cN`

Showing this type of error expandably is tricky, as we have a very limited amount of characters to show and a potentially large list. As a work around, several errors are printed, each showing one step of the loop, until all the error messages combined show the loop.

```
\cs_new:Npn \__filehook_file_subst_cycle_error:NN #1 #2
  {
    \msg_expandable_error:nnff { latex2e } { file-cycle }
      {#1} { \use:c { @file-subst@ #1 } }
    \token_if_eq_meaning:NNF #1 #2
      { \__filehook_file_subst_cycle_error:cN { @file-subst@ #1 } #2 }
  }
```

```
\cs_generate_variant:Nn \__filehook_file_subst_cycle_error:NN { c }
```

And the error message:

```
\msg_new:nnn { latex2e } { file-cycle }
  { File~loop!~#1~replaced~by~#2... }
```

(*End definition for* `\__filehook_resolve_file_subst:w` *and others.*)

```
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
⟨@@=⟩
```

2.8 Preventing a package from loading

We support the use case of preventing a package from loading but not any other type of files (e.g., classes).

`\disable@package@load`
`\reenable@package@load`
`\@disable@packageload@do`

`\disable@package@load` defines `\@pkg-disable@`⟨*package*⟩ to expand to some code `#2` instead of loading the package.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩          {\disable@package@load}{Disable packages}%
\def\disable@package@load#1#2{%
  \global\@namedef{@pkg-disable@#1.\@pkgextension}{#2}}
\def\@disable@packageload@do#1#2{%
  \@ifundefined{@pkg-disable@#1}{#2}%
     {\@nameuse{@pkg-disable@#1}}}
```

`\reenable@package@load` undefines `\@pkg-disable@`⟨*package*⟩ to reallow loading a package.

```
\def\reenable@package@load#1{%
  \global\expandafter\let
  \csname @pkg-disable@#1.\@pkgextension \endcsname \@undefined}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩          {\disable@package@load}{Disable packages}%
⟨latexrelease⟩
⟨latexrelease⟩\let\disable@package@load   \@undefined
⟨latexrelease⟩\let\@disable@packageload@do\@undefined
⟨latexrelease⟩\let\reenable@package@load  \@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\disable@package@load`, `\reenable@package@load`, *and* `\@disable@packageload@do`. *These functions are documented on page 879.*)

2.9 High-level interfaces for LaTeX

None so far and the general feeling for now is that the hooks are enough. Packages like filehook, etc., may use them to set up their interfaces (samples are given below) but for the now the kernel will not provide any.

2.10 Internal commands needed elsewhere

Here we set up a few horrible (but consistent) LaTeX 2_ε names to allow for internal commands to be used outside this module (and in parts that still use LaTeX 2_ε syntax. We have to unset the `@@` since we want double "at" sign in place of double underscores.

```
⟨@@=⟩
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩    {\@expl@@@filehook@if@no@extension@@nTF}{2e tmp interfaces}%
\ExplSyntaxOn
\cs_new_eq:NN \@expl@@@filehook@if@no@extension@@nTF
              \__filehook_if_no_extension:nTF
\cs_new_eq:NN \@expl@@@filehook@set@curr@file@@nNN
              \__filehook_set_curr_file:nNN
\cs_new_eq:NN \@expl@@@filehook@resolve@file@subst@@w
              \__filehook_resolve_file_subst:w
\cs_new_eq:NN \@expl@@@filehook@normalize@file@name@@w
              \__filehook_normalize_file_name:w
\cs_new_eq:NN \@expl@@@filehook@if@file@replaced@@TF
              \__filehook_if_file_replaced:TF
\cs_new_eq:NN \@expl@@@filehook@clear@replacement@flag@@
              \__filehook_clear_replacement_flag:
\cs_new_eq:NN \@expl@@@filehook@drop@extension@@N
              \__filehook_drop_extension:N
\cs_new_eq:NN \@expl@@@filehook@file@push@@
              \__filehook_file_push:
\cs_new_eq:NN \@expl@@@filehook@file@pop@@
              \__filehook_file_pop:
\cs_new_eq:NN \@expl@@@filehook@file@pop@assign@@nnnn
              \__filehook_file_pop_assign:nnnn
\ExplSyntaxOff
```

This one specifically has to be undefined because it is left over in the input stream from `\InputIfFileExists` and executed when latexrelease is loaded. It cannot be `\let` to `\@undefined` otherwise it would error as well, so it is `\let` to `\relax` to be silently ignored when loading `\latexrelease`.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩    {\@expl@@@filehook@if@no@extension@@nTF}{2e tmp interfaces}%
⟨latexrelease⟩\let\@expl@@@filehook@file@pop@@\relax
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

This ends the kernel code in this file.

```
⟨/2ekernel⟩
```

3 A sample package for structuring the log output

```
⟨*structuredlog⟩
⟨@@=filehook⟩
```

```
\ProvidesExplPackage
    {structuredlog}{\ltfilehookdate}{\ltfilehookversion}
    {Structuring the TeX transcript file}
```

\g__filehook_nesting_level_int

Stores the current package nesting level.

```
\int_new:N \g__filehook_nesting_level_int
```

Initialise the counter with the number of files in the `\@currnamestack` (the number of items divided by 3) minus one, because this package is skipped when printing to the log.

```
\int_gset:Nn \g__filehook_nesting_level_int
  { ( \tl_count:N \@currnamestack ) / 3 - 1 }
```

(*End definition for* `\g__filehook_nesting_level_int`.)

__filehook_log_file_record:n

This macro is responsible for increasing and decreasing the file nesting level, as well as printing to the log. The argument is either `STOPTART` or `STOP` and the action it takes on the nesting integer depends on that.

```
\cs_new_protected:Npn \__filehook_log_file_record:n #1
  {
    \str_if_eq:nnT {#1} {START} { \int_gincr:N \g__filehook_nesting_level_int }
    \iow_term:x
      {
        \prg_replicate:nn { \g__filehook_nesting_level_int } { = } ~
        ( LEVEL ~ \int_use:N \g__filehook_nesting_level_int \c_space_tl #1 ) ~
        \CurrentFileUsed
```

If there was a file replacement, show that as well:

```
        \str_if_eq:NNF \CurrentFileUsed \CurrentFile
          { ~ ( \CurrentFile \c_space_tl requested ) }
        \iow_newline:
      }
    \str_if_eq:nnT {#1} {STOP} { \int_gdecr:N \g__filehook_nesting_level_int }
  }
```

Now just hook the macro above in the generic `file/before`...

```
\AddToHook{file/before}{ \__filehook_log_file_record:n { START } }
```

...and `file/after` hooks. We don't want to install the `file/after` hook immediately, because that would mean it is the first time executed when the package finishes. We therefore put the declaration inside `\AddToHookNext` so that it gets only installed when we have left this package.

```
\AddToHookNext{file/after}
  { \AddToHook{file/after}{ \__filehook_log_file_record:n { STOP } } }
```

(*End definition for* `\__filehook_log_file_record:n`.)

```
⟨@@=⟩
⟨/structuredlog⟩
```

4 Package emulations

4.1 Package **atveryend** emulation

With the new hook management and the hooks in `\enddocument` all of atveryend is taken care of. We can make an emulation only here after the substitution functionality is available:

```
⟨*2ekernel⟩
\declare@file@substitution{atveryend.sty}{atveryend-ltx.sty}
⟨/2ekernel⟩
```

Here is the package file we point to:

```
⟨*atveryend-ltx⟩
\ProvidesPackage{atveryend-ltx}
   [2020/08/19 v1.0a
     Emulation of the original atveryend package^^Jwith kernel methods]
```

Here are new definitions for its interfaces now pointing to the hooks in `\enddocument`

```
\newcommand\AfterLastShipout  {\AddToHook{enddocument/afterlastpage}}
\newcommand\AtVeryEndDocument {\AddToHook{enddocument/afteraux}}
```

Next one is a bit of a fake, but the result should normally be as expected. If not, one needs to add a rule to sort the code chunks in `enddocument/info`.

```
\newcommand\AtEndAfterFileList{\AddToHook{enddocument/info}}
\newcommand\AtVeryVeryEnd     {\AddToHook{enddocument/end}}
```

`\BeforeClearDocument` This one is the only one we don't implement or rather don't have a dedicated hook in the code.

```
\ExplSyntaxOn
\newcommand\BeforeClearDocument[1]
  { \AtEndDocument{#1}
    \atveryend@DEPRECATED{BeforeClearDocument \tl_to_str:n{#1}}
  }
\cs_new:Npn\atveryend@DEPRECATED #1
   {\iow_term:x{======~DEPRECATED~USAGE~#1~==========}}
\ExplSyntaxOff
```

(*End definition for* `\BeforeClearDocument`.)

```
⟨/atveryend-ltx⟩
```

File X
ltshipout.dtx

1 Introduction

The code provides an interface to the `\shipout` primitive of TEX which is called when a finished pages is finally "shipped out" to the target output file, e.g., the `.dvi` or `.pdf` file. A good portion of the code is based on ideas by Heiko Oberdiek implemented in his packages atbegshi and atenddvi even though the interfaces are somewhat different.[42]

1.1 Overloading the `\shipout` primitive

`\shipout` With this implementation TEX's shipout primitive is no longer available for direct use. Instead `\shipout` is running some (complicated) code that picks up the box to be shipped out regardless of how that is done, i.e., as a constructed `\vbox` or `\hbox` or as a box register.

It then stores it in a named box register. This box can then be manipulated through a set of hooks after which it is shipped out for real.

Each shipout that actually happens (i.e., where the material is not discarded for one or the other reason) is recorded and the total number is available in a readonly variable and in a LATEX counter.

`\RawShipout` This command implements a simplified shipout that bypasses the foreground and background hooks, e.g., only `shipout/firstpage` and `shipout/lastpage` are executed and the total shipout counters are incremented.

The command doesn't use `\ShipoutBox` but its own private box register so that it can be used inside of shipout hooks to do some additional shipouts while already in the output routine with the current page being stored in `\ShipoutBox`. It does have access to `\ShipoutBox` if it is used in `shipout/before` (or `shipout/after`) and can use its content.

It is safe to use it in `shipout/before` or `shipout/after` but not necessarily in the other `shipout/...` hooks as they are intended for special processing.

[42] Heiko's interfaces are emulated by the kernel code, if a document requests his packages, so older documents will continue to work.

`\ShipoutBox`
`\l_shipout_box`

This box register is called `\ShipoutBox` (alternatively available via the L3 name `\l_shipout_box`).

This box is a "local" box and assignments to it should be done only locally. Global assignments (as done by some packages with older code where this is box is known as 255) may work but they are conceptually wrong and may result in errors under certain circumstances.

During the execution of `shipout/before` this box contains the accumulated material for the page, but not yet any material added by other shipout hooks. During execution of `shipout/after`, i.e., after the shipout has happened, the box also contains any background or foreground material.

Material from the hooks `shipout/firstpage` or `shipout/lastpage` is not included (but only used during the actual shipout) to facilitate reuse of the box data (e.g., `shipout/firstpage` material should never be added to a later page of the output).

`\l_shipout_box_ht_dim`
`\l_shipout_box_dp_dim`
`\l_shipout_box_wd_dim`
`\l_shipout_box_ht_plus_dp_dim`

The shipout box dimensions are available in the L3 registers `\l_shipout_box_ht_dim`, etc. (there are no LaTeX 2_ε names).[43] These variables can be used inside the hook code for `shipout/before`, `shipout/foreground` and `shipout/background` if needed.

1.2 Provided hooks

`shipout/before`
`shipout/after`
`shipout/foreground`
`shipout/background`
`shipout/firstpage`
`shipout/lastpage`

The code for `\shipout` offers a number of hooks into which packages (or the user) can add code to support different use cases. These are:

`shipout/before` This hook is executed after the finished page has been stored in `\ShipoutBox` / `\l_shipout_box`). It can be used to alter that box content or to discard it completely (see `\DiscardShipoutBox` below).

You can use `\RawShipout` inside this hook for special use cases. It can make use of `\ShipoutBox` (which doesn't yet include the background and foreground material).

Note: It is not possible (or say advisable) to try and use this hook to typeset material with the intention to return it to main vertical list, it will go wrong and give unexpected results in many cases—for starters it will appear after the current page not before or it will vanish or the vertical spacing will be wrong!

`shipout/background` This hook adds a picture environment into the background of the page with the `(0,0)` coordinate in the top-left corner using a `\unitlength` of `1pt`.

It should therefore only receive `\put` commands or other commands suitable in a `picture` environment and the vertical coordinate values would normally be negative.

[43] Might need changing, but HO's version as strings is not really helpful I think).

Technically this is implemented by adding a zero-sized `\hbox` as the very first item into the `\ShipoutBox` containing that `picture` environment. Thus the rest of the box content will overprint what ever is typeset by that hook.

`shipout/foreground` This hook adds a picture environment into the foreground of the page with the `(0,0)` coordinate in the top-left corner using a `\unitlength` of `1pt`.

Technically this is implemented by adding a zero-sized `\hbox` as the very last item into the `\ShipoutBox` and raising it up so that it still has its `(0,0)` point in the top-left corner. But being placed after the main box content it will be typeset later and thus overprints it (i.e., is in the foreground).

`shipout/firstpage` The material from this hook is executed only once at the very beginning of the first output page that is shipped out (i.e., not discarded at the last minute). It should only contain `\special` or similar commands needed to direct post processors handling the `.dvi` or `.pdf` output.[44]

This hook is added to the very first page regardless of how it is shipped out (i.e., with `\shipout` or `\RawShipout`).

`shipout/lastpage` The corresponding hook to add `\special`s at the very end of the output file. It is only executed on the very last page of the output file — or rather on the page that LaTeX believes is the last one. Again it is executed regardless of the shipout method.

It may not be possible for LaTeX to correctly determine which page is the last one without several reruns. If this happens and the hook is non-empty then LaTeX will add an extra page to place the material and also request a rerun to get the correct placement sorted out.

`shipout/after` This hook is executed after a shipout has happened. If the shipout box is discarded this hook is not looked at.

You can use `\RawShipout` inside this hook for special use cases and the main `\ShipoutBox` is still available at this point (but in contrast to `shipout/before` it now includes the background and foreground material).

Note: Just like `shipout/before` this hook is not meant to be used for adding typeset material back to the main vertical list—it might vanish or the vertical spacing will be wrong!

As mentioned above the hook `shipout/before` is executed first and can manipulate the prepared shipout box stored in `\ShipoutBox` or set things up for use in `\write` during the actual shipout. It is even run if there was a `\DiscardShipoutBox` request in the document.

The other hooks (except `shipout/after`) are added inside hboxes to the box being shipped out in the following order:

`shipout/firstpage`	only on the first page
`shipout/background`	
⟨*boxed content of* `\ShipoutBox`⟩	
`shipout/foreground`	
`shipout/lastpage`	only on the last page

[44] In LaTeX 2_ε that was already existing, but implemented using a box register with the name `\@begindvibox`.

If any of the hooks has no code then that particular no box is added at that point.

Once the (page) box has been shipped out the `shipout/after` hook is called (while you are still inside the output routine). It is not called if the shipout box was discarded.

In a document that doesn't produce pages, e.g., only makes `\typeout`s, none of the hooks are ever executed (as there is no `\shipout`) not even the `shipout/lastpage` hook.

If `\RawShipout` is used instead of `\shipout` then only the hooks `shipout/firstpage` and `shipout/lastpage` are executed (on the first or last page), all others are bypassed.

1.3 Legacy LaTeX commands

`\AtBeginDvi` `\AtBeginDvi {⟨code⟩}`
`\AtEndDvi`

`\AtBeginDvi` is the existing LaTeX 2_ε interface to fill the `shipout/firstpage` hook. This is not really a good name as it is not just supporting `.dvi` but also `.pdf` output or `.xdv`.

`\AtEndDvi` is the counterpart that was not available in the kernel but only through the package atenddvi. It fills the `shipout/lastpage` hook.

Neither interface can set a code label but uses the current default label.

As these two wrappers have been available for a long time we continue offering them (but not enhancing them, e.g., by providing support for code labels).

For new code we strongly suggest using the high-level hook management commands directly instead of "randomly-named" wrappers. This will lead to code that is easier to understand and to maintain and it also allows you to set code labels if needed.

For this reason we do not provide any other "new" wrapper commands for the above hooks in the kernel, but only keep the existing ones for backward compatibility.

1.4 Special commands for use inside the hooks

`\DiscardShipoutBox` `\AddToHookNext {shipout/before} {...\DiscardShipoutBox...}`
`\shipout_discard:`

The `\DiscardShipoutBox` declaration (L3 name `\shipout_discard:`) requests that on the next shipout the page box is thrown away instead of being shipped to the `.dvi` or `.pdf` file.

Typical applications wouldn't do this unconditionally, but have some processing logic that decides to use or not to use the page.

Note that if this declaration is used directly in the document it may depend on the placement to which page it applies, given that LaTeX output routine is called in an asynchronous manner! Thus normally one would use this only as part of the `shipout/before` code.

> *Todo: Once we have a new mark mechanism available we can improve on that and make sure that the declaration applies to the page that contains it.*

In the atbegshi package there are a number of additional commands for use inside the `shipout/before` hook. They should normally not be needed any more as one can instead simply add code to the hooks `shipout/before`, `shipout/background` or `shipout/foreground`.[45] If atbegshi gets loaded then those commands become available as public functions with their original names as given below.

[45] If that assumption turns out to be wrong it would be trivial to change them to public functions (right now they are private).

1.5 Provided LuaTEX callbacks

`pre_shipout_filter`

Under LuaTEX the `pre_shipout_filter` Lua callback is provided which gets called immediately before the shipout primitive gets invoked. The signature is

```
function(<node> head)
  return true
end
```

The `head` is the list node corresponding to the box to be shipped out. The return value should always be `true`.

1.6 Information counters

`\ReadonlyShipoutCounter` `\ifnum\ReadonlyShipoutCounter=...`
`\g_shipout_readonly_int` `\int_use:N \g_shipout_readonly_int % expl3 usage`

This integer holds the number of pages shipped out up to now (including the one to be shipped out when inside the output routine). More precisely, it is incremented only after it is clear that a page will be shipped out, i.e., after the `shipout/before` hook (because that might discard the page)! In contrast `shipout/after` sees the incremented value.

Just like with the `page` counter its value is only accurate within the output routine. In the body of the document it may be off by one as the output routine is called asynchronously!

Also important: it *must not* be set, only read. There are no provisions to prevent that restriction, but if you manipulate it, chaos will be the result. To emphasize this fact it is not provided as a LATEX counter but as a TEX counter (i.e., a command), so `\Alph{\ReadonlyShipoutCounter}` etc, would not work.

`totalpages` `\arabic{totalpages}`
`\g_shipout_totalpages_int` `\int_use:N \g_shipout_totalpage_int % expl3 usage`

In contrast to `\ReadonlyShipoutCounter`, the `totalpages` counter is a LATEX counter and incremented for each shipout attempt including those pages that are discarded for one or the other reason. Again `shipout/before` sees the counter before it is incremented. In contrast `shipout/after` sees the incremented value.

Furthermore, while it is incremented for each page, its value is never used by LATEX. It can therefore be freely reset or changed by user code, for example, to additionally count a number of pages that are not build by LATEX but are added in a later part of the process, e.g., cover pages or picture pages made externally.

Important: as this is a page-related counter its value is only reliable inside the output routine!

`\PreviousTotalPages` `\thetotalpages/\PreviousTotalPages`

Command that expands to the number of total pages from the previous run. If there was no previous run or if used in the preamble it expands to `0`. Note that this is a command and not a counter, so in order to display the number in, say, Roman numerals you have to assign its value to a counter and then use `\Roman` on that counter.

1.7 Debugging shipout code

\DebugShipoutsOn
\DebugShipoutsOff
\shipout_debug_on:
\shipout_debug_off:

\DebugShipoutsOn

Turn the debugging of shipout code on or off. This displays changes made to the shipout data structures.

Todo: This needs some rationalizing and may not stay this way.

2 Emulating commands from other packages

The packages in this section are no longer necessary, but as they are used by other packages, they are emulated when they are explicitly loaded with \usepackage or \RequirePackage.

Please note that the emulation only happens if the package is explicitly requested, i.e., the commands documented below are not automatically available in the LaTeX kernel! If you write a new package we suggest to use the appropriate kernel hooks directly instead of loading the emulation.

2.1 Emulating atbegshi

\AtBeginShipoutUpperLeft
\AtBeginShipoutUpperLeftForeground

\AddToHook {shipout/before} {...\AtBeginShipoutUpperLeft{⟨*code*⟩}...}

This adds a picture environment into the background of the shipout box expecting ⟨*code*⟩ to contain picture commands. The same effect can be obtained by simply using kernel features as follows:

\AddToHook{shipout/background}{⟨*code*⟩}

There is one technical difference: if \AtBeginShipoutUpperLeft is used several times each invocation is put into its own box inside the shipout box whereas all ⟨*code*⟩ going into shipout/background ends up all in the same box in the order it is added or sorted based on the rules for the hook chunks.

\AtBeginShipoutUpperLeftForeground is similar with the difference that the picture environment is placed in the foreground. To model it with the kernel functions use the hook shipout/foreground instead.

\AtBeginShipoutAddToBox
\AtBeginShipoutAddToBoxForeground

\AddToHook {shipout/before} {...\AtBeginShipoutAddToBox{⟨*code*⟩}...}

These work like \AtBeginShipoutUpperLeft and \AtBeginShipoutUpperLeftForeground with the difference that ⟨*code*⟩ is directly placed into an \hbox inside the shipout box and not surrounded by a picture environment.

To emulate them using shipout/background or shipout/foreground you may have to wrap ⟨*code*⟩ into a \put statement but if the code is not doing any typesetting just adding it to the hook should be sufficient.

\AtBeginShipoutBox

This is the name of the shipout box as atbegshi knows it.

`\AtBeginShipoutOriginalShipout`

This is the name of the `\shipout` primitive as atbegshi knows it. This bypasses all the mechanisms set up by the LaTeX kernel and there are various scenarios in which it can therefore fail. It should only be used to run existing legacy atbegshi code but not in newly developed applications.

The kernel alternative is `\RawShipout` which is integrated with the LaTeX mechanisms and updates, for example, the `\ReadonlyShipoutCounter` counter. Please use `\RawShipout` for new code if you want to bypass the before, foreground and background hooks.

`\AtBeginShipoutInit` By default atbegshi delayed its action until `\begin{document}`. This command was forcing it in an earlier place. With the new concept it does nothing.

`\AtBeginShipout` `\AtBeginShipout{⟨code⟩}` ≡ `\AddToHook{shipout/before}{⟨code⟩}`
`\AtBeginShipoutNext` `\AtBeginShipoutNext{⟨code⟩}` ≡ `\AddToHookNext{shipout/before}{⟨code⟩}`

This is equivalent to filling the `shipout/before` hook by either using `\AddToHook` or `\AddToHookNext`, respectively.

`\AtBeginShipoutFirst`
`\AtBeginShipoutDiscard`

The atbegshi names for `\AtBeginDvi` and `\DiscardShipoutBox`.

2.2 Emulating everyshi

The everyshi package is providing commands to run arbitrary code just before the shipout starts. One point of difference: in the new shipout hooks the page is available as `\ShipoutBox` for inspection of change, one should not manipulate box 255 directly inside `shipout/before`, so old code doing this would change to use `\ShipoutBox` instead of 255 or `\@cclv`.

`\EveryShipout` `\EveryShipout{⟨code⟩}` ≡ `\AddToHook{shipout/before}{⟨code⟩}`

`\AtNextShipout` `\AtNextShipout{⟨code⟩}` ≡ `\AddToHookNext{shipout/before}{⟨code⟩}`

However, most use cases for everyshi are attempts to put some picture or text into the background or foreground of the page and that can be done today simply by using the `shipout/background` and `shipout/foreground` hooks without any need to coding.

2.3 Emulating atenddvi

The atenddvi package implemented only a single command: `\AtEndDvi` and that is now available out of the box so the emulation makes the package a no-op.

2.4 Emulating everypage

This package patched the original `\@begindvi` hook and replaced it with its own version. Its functionality is now covered by the hooks offered by the kernel so that there is no need for such patching any longer.

`\AddEverypageHook`

```
\AddEverypageHook{⟨code⟩} ≡
    \AddToHook{shipout/background}{\put(1in,-1in){⟨code⟩}}
```

`\AddEverypageHook` is adding something into the background of every page at a position of 1in to the right and 1in down from the top left corner of the page. By using the kernel hook directly you can put your material directly to the right place, i.e., use other coordinates in the `\put` statement above.

`\AddThispageHook`

```
\AddThispageHook{⟨code⟩} ≡
    \AddToHookNext{shipout/background}{\put(1in,-1in){⟨code⟩}}
```

The `\AddThispageHook` wrapper is similar but uses `\AddToHookNext`.

3 The Implementation

```
⟨@@=shipout⟩
```

At the moment the whole module rolls back in one go, but if we make any modifications in later releases this will then need splitting.

```
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                    {\shipout}{Hook management (shipout)}%
\ExplSyntaxOn
```

3.1 Debugging

`\g__shipout_debug_bool`

Holds the current debugging state.

```
\bool_new:N \g__shipout_debug_bool
```

(*End definition for* `\g__shipout_debug_bool`.)

`\shipout_debug_on:` `\shipout_debug_off:` `\__shipout_debug:n` `\__shipout_debug_gset:`

Turns debugging on and off by redefining `\__shipout_debug:n`.

```
\cs_new_eq:NN \__shipout_debug:n  \use_none:n
\cs_new_protected:Npn \shipout_debug_on:
  {
    \bool_gset_true:N \g__shipout_debug_bool
    \__shipout_debug_gset:
  }
\cs_new_protected:Npn \shipout_debug_off:
  {
    \bool_gset_false:N \g__shipout_debug_bool
    \__shipout_debug_gset:
  }
\cs_new_protected:Npn \__shipout_debug_gset:
  {
    \cs_gset_protected:Npx \__shipout_debug:n ##1
      { \bool_if:NT \g__shipout_debug_bool {##1} }
  }
```

(*End definition for* `\shipout_debug_on:` *and others. These functions are documented on page* 903.)

`\ShipoutBox` `\l_shipout_box` The box filled with the page to be shipped out (both L3 and LaTeX 2_ε name).

```
\box_new:N  \l_shipout_box
\cs_set_eq:NN \ShipoutBox \l_shipout_box
```

(*End definition for* `\ShipoutBox` *and* `\l_shipout_box`*. These functions are documented on page* 899.)

`\l__shipout_raw_box` The `\RawShipout` gets its own box but it is internal as there is no hook manipulation for it.

```
\box_new:N  \l__shipout_raw_box
```

(*End definition for* `\l__shipout_raw_box`.)

`\__shipout_finalize_box:` For LuaTeX invoke the `pre_shipout_filter` callback.

```
\sys_if_engine_luatex:TF
  {
    \newprotectedluacmd \__shipout_finalize_box:
    \exp_args:Nx \everyjob {
      \exp_not:V \everyjob
      \exp_not:N \lua_now:n {
        luatexbase.create_callback('pre_shipout_filter', 'list')
        local~call, getbox, setbox = luatexbase.call_callback, tex.getbox, tex.setbox~
        lua.get_functions_table()[\the \allocationnumber] = function()
          local~head = getbox(\the \l_shipout_box)
          local~result = call('pre_shipout_filter', head)
          if~not (result == head) then~
            setbox(\the \l_shipout_box, result~or~nil)
          end~
        end
      }
    }
  } {
    \cs_set_eq:NN \__shipout_finalize_box: \scan_stop:
  }
```

(*End definition for* `\__shipout_finalize_box:`.)

`\__shipout_execute:` This is going to the be the code run by `\shipout`. The code follows closely the ideas from atbegshi, so not documenting that here for now.

```
\cs_set_protected:Npn \__shipout_execute: {
  \tl_set:Nx \l__shipout_group_level_tl
     { \int_value:w \tex_currentgrouplevel:D }
  \tex_afterassignment:D \__shipout_execute_test_level:
  \tex_setbox:D \l_shipout_box
}
```

(*End definition for* `\__shipout_execute:`.)

`\shipout` Overloading the `\shipout` primitive:

```
\cs_gset_eq:NN \shipout \__shipout_execute:
```

(*End definition for* `\shipout`*. This function is documented on page* 898.)

\l__shipout_group_level_tl Helper token list to record the group level at which __shipout_execute: is encountered.

```
\tl_new:N \l__shipout_group_level_tl
```

(*End definition for* \l__shipout_group_level_tl.)

__shipout_execute_test_level: If the group level has changed then we are still constructing \l_shipout_box and to continue we need to wait until the current group has finished, hence the \tex_aftergroup:D.

```
\cs_new:Npn \__shipout_execute_test_level: {
  \int_compare:nNnT
     \l__shipout_group_level_tl < \tex_currentgrouplevel:D
     \tex_aftergroup:D \__shipout_execute_cont:
}
```

(*End definition for* __shipout_execute_test_level:.)

__shipout_execute_cont: This does the actual shipout running several hooks as part of it. The code for them is passed as argument #2 to #4 to __shipout_execute_main_cont:Nnnn; the first argument is the box to be shipped out.

```
\cs_new:Npn \__shipout_execute_cont: {
  \__shipout_execute_main_cont:Nnnn
     \l_shipout_box
     { \hook_use:n {shipout/before} }
     { \hook_if_empty:nF {shipout/foreground}
         { \__shipout_add_foreground_picture:n
             { \hook_use:n {shipout/foreground} } }
```

If the user hook for the background (shipout/background) has no code, there might still code in the kernel hook so we need to test for this too. We only test for the \@kernel@before@shipout@background though. If the \@kernel@after@shipout@background needs executing even if the user hook is empty then we can add another test (or the kernel could put something into the before hook).

```
        \bool_lazy_and:nnF
          { \hook_if_empty_p:n {shipout/background} }
          { \tl_if_empty_p:N \@kernel@before@shipout@background }
          { \__shipout_add_background_picture:n
            { \@kernel@before@shipout@background
              \hook_use:n {shipout/background}
              \@kernel@after@shipout@background }
          }
     }
     { \hook_use:n {shipout/after} }
}
```

(*End definition for* __shipout_execute_cont:.)

__shipout_execute_main_cont:Nnnn When we have reached this point the shipout box has been processed and is available in \l_shipout_box and ready for real ship out (unless it gets discarded during the process).

The three arguments hold hook code that is executed just before the actual shipout (#1), within the shipout adding background and foreground material (#2) and after the shipout has happened (#3). These are passed as arguments because the same code without those hooks is also used when doing a "raw" shipout implemented by \RawShipout. The only hook that is always executed is that for the very last page, i.e., shipout/lastpage.

First we quickly check if it is void (can't happen in the standard LaTeX output routine but \shipout might be called from a package that has some special processing logic). If it is void we aren't shipping anything out and processing ends.[46]

```
\cs_new:Npn \__shipout_execute_main_cont:Nnnn #1#2#3#4 {
  \box_if_empty:NTF #1
    { \@latex@warning@no@line{ Ignoring~ void~ shipout~ box } }
    {
```

Otherwise we assume that we will ship something and prepare for final adjustments (in particular setting the state of \protect while we are running the hook code). We also save the current \protect state to restore it later.

```
%       \bool_gset_false:N \g__shipout_discard_bool  % setting this would disable
                                                     % \DiscardShipoutBox on doc-level
      \cs_set_eq:NN \__shipout_saved_protect: \protect
      \set@typeset@protect
```

We also store the current shipout box dimension in registers, so that they can be used in the hook code.[47]

```
      \__shipout_get_box_size:N #1
```

Then we execute the shipout/before hook (or nothing in case of \RawShipout).

```
      #2
```

In \g_shipout_totalpages_int we count all shipout attempts so we increment that counter already here (the other one is incremented later when we know for sure that we do a \shipout.

We increment it after running the above hook so that the values for \g_shipout_totalpages_int and \g_shipout_readonly_int are in sync while the hook is executed (in the case that totalpages isn't manually altered or through discarding pages that is).

```
      \int_gincr:N \g_shipout_totalpages_int
```

The above hook might contain code that requests the page to be discarded so we now test for it.

```
      \bool_if:NTF \g__shipout_discard_bool
        { \@latex@info@no@line{Completed~ page~ discarded}
          \bool_gset_false:N \g__shipout_discard_bool
```

As we are discarding the page box and not shipping anything out, we need to do some house cleaning and reset TeX's deadcycles so that it doesn't complain about too many calls to the OR without any shipout.

```
          \tex_deadcycles:D \c_zero_int
```

Todo: In atbegshi *the box was dropped but is that actually needed? Or the resetting of* \protect *to its kernel value?*

```
%           \group_begin:
%             \box_set_eq_drop:NN #1 #1
%           \group_end:
%           \cs_set_eq:NN \protect \exp_not:N
        }
```

[46] In that case we don't reset the deadcycles, that would be up to the OR processing logic to do.

[47] This is not really necessary as the code could access them via \box_ht:N, etc., but it is perhaps convenient.

Even if there was no explicit request to discard the box it is possible that the code for the hook `shipout/before` has voided the box (by mistake or deliberately). We therefore test once more but this time make it a warning, because the best practice way is to use the request mechanism.

```
        { \box_if_empty:NTF #1
            { \@latex@warning@no@line { Ignoring~ void~ shipout~ box.
                 \MessageBreak The~ shipout~ box~ was~ voided~ by~ hook~ code }
            }
```

Finally, if the box is still non-empty we are nearly ready to ship it out. First we increment the total page counter so that we can later test if we have reached the final page according to our available information.[48]

```
            {
              \int_gincr:N \g_shipout_readonly_int
              \__shipout_debug:n {
                \typeout{Absolute~ page~ =~ \int_use:N \g_shipout_readonly_int
                         \space (target:~ \@abspage@last)}
              }
```

Then we store the box sizes again (as they may have changed) and then look at the hooks `shipout/foreground` and `shipout/background`. If either or both are non-empty we add a `picture` environment to the box (in the foreground and/or in the background) and execute the hook code inside that environment.

```
              \__shipout_get_box_size:N #1
```

The first hook we run is the `shipout/firstpage` hook. This is only done once, then the `\__shipout_run_firstpage_hook:` command redefines itself to do nothing. If the hook contains `\special`s for integration at the top of the page they will be temporarily stored in a safe place and added later with `\__shipout_add_firstpage_specials:`.

```
              \__shipout_run_firstpage_hook:
```

Run the hooks for background and foreground or, if this is called by `\RawShipout`, copy the box `\l__shipout_raw_box` to `\l_shipout_box` so that firstpage and lastpage material gets added if necessary (that is always done to `\l_shipout_box`.

```
              #3
```

We then run `\__shipout_add_firstpage_specials:` that adds the content of the hook `shipout/firstpage` to the start of the first page (if non-empty). It is then redefined to do nothing on later pages.

```
              \__shipout_add_firstpage_specials:
```

Then we check if we have to add the `shipout/lastpage` hook or the corresponding kernel hook because we have reached the last page. This test will be false for all but one (and hopefully the correct) page.

```
              \int_compare:nNnT \@abspage@last = \g_shipout_readonly_int
                { \bool_lazy_and:nnF
                    { \hook_if_empty_p:n {shipout/lastpage} }
                    { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
                    { \__shipout_debug:n { \typeout{Executing~ lastpage~ hook~
                          on~ page~ \int_use:N \g_shipout_readonly_int } }
                      \__shipout_add_foreground_box:n
                          { \UseHook{shipout/lastpage}
```

[48] Doing that earlier would be wrong because we might end up with the last page counted but discard and then we have no place to add the final objects into the output file.

```
                                \@kernel@after@shipout@lastpage }
                          \bool_gset_true:N \g__shipout_lastpage_handled_bool
```

We record that we have handled the `shipout/lastpage` hook but only if we really did.

```
                        }
                    }
                \__shipout_finalize_box:
```

Finally we run the actual TEX primitive for shipout. As that will expand delayed `\write` statements inside the page in which protected commands should not expand we first change `\protect` to the appropriate definition for that case.

```
                \cs_set_eq:NN \protect \exp_not:N
                \tex_shipout:D \box_use:N \l_shipout_box
```

The `\l_shipout_box` may contain the firstpage material if this was the very first shipout. That makes it unsuitable for reuse in another shipout, so as a safety measure the next command resets `\l_shipout_box` to its earlier state if that is necessary. On later pages this is then a no-op.

```
                \__shipout_drop_firstpage_specials:
```

The `shipout/after` hook (if in `#4`) needs to run with `\protect`ed commands again being executed, because that hook will "typeset" material added at the top of the next page.

```
                \set@typeset@protect
                #4
              }
          }
```

Restore the value of `\protect` in case `\shipout` is called outside of the output routine (where it is automatically restored because of the implicit group).

```
        \cs_set_eq:NN \protect \__shipout_saved_protect:
      }
}
```

(*End definition for* `\__shipout_execute_main_cont:Nnnn`.)

`\__shipout_execute_raw:`
`\__shipout_execute_test_level_raw:`

This implements the "raw" shipout which bypasses the before, foreground, background and after hooks. It follows the same pattern than `\__shipout_execute_raw:` except that it finally calls `\__shipout_execute_main_cont:Nnnn` with three empty arguments. instead of the hook code.

```
\cs_set_protected:Npn \__shipout_execute_raw: {
  \tl_set:Nx \l__shipout_group_level_tl
     { \int_value:w \tex_currentgrouplevel:D }
  \tex_afterassignment:D \__shipout_execute_test_level_raw:
  \tex_setbox:D \l__shipout_raw_box
}
```

```
\cs_new:Npn \__shipout_execute_test_level_raw: {
  \int_compare:nNnT
     \l__shipout_group_level_tl < \tex_currentgrouplevel:D
     \tex_aftergroup:D \__shipout_execute_nohooks_cont:
}
```

Well, not totally empty arguments, we add some debugging if we are actually doing a shipout.

```
\cs_new:Npn \__shipout_execute_nohooks_cont: {
  \__shipout_execute_main_cont:Nnnn \l__shipout_raw_box
```

```
    {} { \__shipout_debug:n{ \typeout{Doing~ raw~ shipout~ ...} }
         \box_set_eq:NN \l_shipout_box \l__shipout_raw_box } {}
}
```

(*End definition for* `\__shipout_execute_raw:` *and* `\__shipout_execute_test_level_raw:`.)

`\RawShipout` The interface name for raw shipout.

```
\cs_gset_eq:NN \RawShipout \__shipout_execute_raw:
```

(*End definition for* `\RawShipout`. *This function is documented on page 898.*)

`\__shipout_saved_protect:` Remember the current `\protect` state.

```
\cs_new_eq:NN  \__shipout_saved_protect: \protect
```

(*End definition for* `\__shipout_saved_protect:`.)

`shipout/before` `shipout/after` `shipout/foreground` `shipout/background` `shipout/firstpage` `shipout/lastpage` Declaring all hooks for the shipout code.

```
\hook_new:n{shipout/before}
\hook_new:n{shipout/after}
\hook_new:n{shipout/foreground}
\hook_new:n{shipout/background}
\hook_new:n{shipout/firstpage}
\hook_new:n{shipout/lastpage}
```

(*End definition for* `shipout/before` *and others. These functions are documented on page 899.*)

`\@kernel@after@shipout@lastpage` `\@kernel@before@shipout@background` `\@kernel@after@shipout@background` And here are the internal kernel hooks going before or after the public ones where needed.

```
\let\@kernel@after@shipout@lastpage\@empty
\let\@kernel@before@shipout@background\@empty
\let\@kernel@after@shipout@background\@empty
```

(*End definition for* `\@kernel@after@shipout@lastpage`, `\@kernel@before@shipout@background`, *and* `\@kernel@after@shipout@background`.)

`\__shipout_run_firstpage_hook:` There are three commands to handle the `shipout/firstpage` hook: `\__shipout_run_firstpage_hook:`, `\__shipout_add_firstpage_specials:` and `\__shipout_drop_firstpage_specials:`.

That hook is supposed to contain `\specials` and similar material to be placed at the very beginning of the output page and so it needs careful placing to avoid that anything else gets in front of it. And this means we have to wait with this until other hooks such as `shipout/background` have added their bits. It is also important that such `\specials` show up only on the very first page, so if this page gets saved before `\shipout` for later reuse, we have to make sure that they aren't in the saved version.

In addition the hook may also contain code to be executed "first", e.g., visible from code in `shipout/background` and this conflicts with adding the `\specials` late.

Therefore the processing is split into different parts: `\__shipout_run_firstpage_hook:` is done early and checks if there is any material in the hook.

```
\cs_new:Npn \__shipout_run_firstpage_hook: {
  \hook_if_empty:nTF {shipout/firstpage}
```

If not then we define the other two commands to do nothing.

```
        {
          \cs_gset_eq:NN \__shipout_add_firstpage_specials:  \prg_do_nothing:
          \cs_gset_eq:NN \__shipout_drop_firstpage_specials: \prg_do_nothing:
        }
```

If there is material we execute inside a box, which means any `\special` will end up in that box and any other code is executed and can have side effects (as long as they are global).

```
        {
          \hbox_set:Nn \l__shipout_firstpage_box { \UseHook{shipout/firstpage} }
        }
```

Once we are here we change the definition to do nothing next time and we also change the command used to implement `\AtBeginDvi` to become a warning and not add further material to a hook that is never used again.

```
  \cs_gset_eq:NN \__shipout_run_firstpage_hook: \prg_do_nothing:
  \cs_gset:Npn \__shipout_add_firstpage_material:Nn ##1 ##2 {
    \@latex@warning{ First~ page~ is~ already~ shipped~ out,~ ignoring
                     \MessageBreak \string##1 }
  }
}
```

(*End definition for* `\__shipout_run_firstpage_hook:`.)

`\__shipout_add_firstpage_specials:`
`\__shipout_drop_firstpage_specials:`

The `\__shipout_add_firstpage_specials:` then adds the `\special`s stored in `\l__shipout_firstpage_box` to the page to be shipped out when the time is ready. Note that if there was no material in the `shipout/firstpage` hook then this command gets redefined to do nothing. But for most documents there is something, e.g., some PostScript header, or some meta data declaration, etc. so by default we assume there is something to do.

```
\cs_new:Npn \__shipout_add_firstpage_specials: {
```

First we make a copy of the `\l_shipout_box` that we can restore it later on.

```
  \box_set_eq:NN \l__shipout_raw_box \l_shipout_box
```

Adding something to the beginning means adding it to the background as that layer is done first in the output.

```
  \__shipout_add_background_box:n { \hbox_unpack_drop:N \l__shipout_firstpage_box }
```

After the actual shipout `\__shipout_drop_firstpage_specials:` is run to restore the earlier content of `\l_shipout_box` and then redefines itself again to do nothing.

As a final act we change the definition to do nothing next time.

```
  \cs_gset_eq:NN \__shipout_add_firstpage_specials: \prg_do_nothing:
}
```

The `\__shipout_drop_firstpage_specials:` is run after the shipout has occurred but before the `shipout/afterpage` hook is executed. That is the point where we have to restore the `\ShipoutBox` to its state without the `shipout/firstpage` material.

```
\cs_new:Npn \__shipout_drop_firstpage_specials: {
    \box_set_eq:NN \l_shipout_box \l__shipout_raw_box
```

If there was no such material then `\__shipout_run_firstpage_hook:` will have changed the definition to a no-op already. Otherwise this is what we do here.

```
    \cs_gset_eq:NN \__shipout_drop_firstpage_specials:  \prg_do_nothing:
  }
```

(*End definition for* `\__shipout_add_firstpage_specials:` *and* `\__shipout_drop_firstpage_specials:`.)

`\l__shipout_firstpage_box` The box to hold any firstpage `\specials`.

```
\box_new:N \l__shipout_firstpage_box
```

(*End definition for* `\l__shipout_firstpage_box`.)

`\g__shipout_lastpage_handled_bool` A boolean to signal if we have already handled the `shipout/lastpage` hook.

```
\bool_new:N \g__shipout_lastpage_handled_bool
```

(*End definition for* `\g__shipout_lastpage_handled_bool`.)

`\__shipout_add_firstpage_material:Nn` This command adds material to the `shipout/firstpage` hook. It is used in `\AtBeginDvi`, etc. The first argument is the command through which is it called. Initially this is ignored but once we are passed the first page it can be used to generate a warning message mentioning the right user command.

```
\cs_new:Npn \__shipout_add_firstpage_material:Nn #1#2 {
   \AddToHook{shipout/firstpage}{#2}
}
```

(*End definition for* `\__shipout_add_firstpage_material:Nn`.)

`\__shipout_get_box_size:N` Store the box dimensions in dimen registers.

> *Todo: This could/should perhaps be generalized to set height depth and width given an arbitrary box.*

```
\cs_new:Npn \__shipout_get_box_size:N #1 {
  \dim_set:Nn \l_shipout_box_ht_dim { \box_ht:N #1 }
  \dim_set:Nn \l_shipout_box_dp_dim { \box_dp:N #1 }
  \dim_set:Nn \l_shipout_box_wd_dim { \box_wd:N #1 }
  \dim_set:Nn \l_shipout_box_ht_plus_dp_dim
      { \l_shipout_box_ht_dim + \l_shipout_box_dp_dim }
}
```

(*End definition for* `\__shipout_get_box_size:N`.)

`\l_shipout_box_ht_dim`
`\l_shipout_box_dp_dim`
`\l_shipout_box_wd_dim`
`\l_shipout_box_ht_plus_dp_dim`

And here are the variables set by `\__shipout_get_box_size:N`.

```
\dim_new:N \l_shipout_box_ht_dim
\dim_new:N \l_shipout_box_dp_dim
\dim_new:N \l_shipout_box_wd_dim
\dim_new:N \l_shipout_box_ht_plus_dp_dim
```

(*End definition for* `\l_shipout_box_ht_dim` *and others. These functions are documented on page* 899.)

`\g__shipout_discard_bool` Indicate whether or not the current page box should be discarded

```
\bool_new:N \g__shipout_discard_bool
```

(*End definition for* `\g__shipout_discard_bool`.)

`\l__shipout_tmp_box`
`\l__shipout_saved_badness_tl`

We need a box for the background and foreground material and a token register to remember badness settings as we disable them during the buildup below.

```
\box_new:N \l__shipout_tmp_box
\tl_new:N  \l__shipout_saved_badness_tl
```

(*End definition for* `\l__shipout_tmp_box` *and* `\l__shipout_saved_badness_tl`.)

`\__shipout_add_background_box:n` In standard LaTeX the shipout box is always a `\vbox` but here we are allow for other usage as well, in case some package has its own output routine.

```
\cs_new:Npn \__shipout_add_background_box:n #1
{ \__shipout_get_box_size:N \l_shipout_box
```

But we start testing for a vertical box as that should be the normal case.

```
  \box_if_vertical:NTF \l_shipout_box
      {
```

Save current values of `\vfuzz` and `\vbadness` then change them to allow box manipulations without warnings.

```
        \tl_set:Nx \l__shipout_saved_badness_tl
           { \vfuzz=\the\vfuzz\relax
             \vbadness=\the\vbadness\relax }
        \vfuzz=\c_max_dim
        \vbadness=\c_max_int
```

Then we reconstruct `\l_shipout_box` ...

```
        \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
             {
```

... the material in `#1` is placed into a horizontal box with zero dimensions.

```
               \hbox_set:Nn \l__shipout_tmp_box
                    { \l__shipout_saved_badness_tl #1 }
               \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
               \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
               \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
```

The we typeset that box followed by whatever was in `\l_shipout_box` before (unpacked).

```
               \skip_zero:N \baselineskip
               \skip_zero:N \lineskip
               \skip_zero:N \lineskiplimit
               \box_use:N \l__shipout_tmp_box
               \vbox_unpack:N \l_shipout_box
```

The `\kern` ensures that the box has no depth which is afterwards explicitly corrected.

```
               \kern \c_zero_dim
             }
        \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
        \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim
```

Todo: The whole boxing maneuver looks a bit like overkill to me, but for the moment I leave.

```
        \l__shipout_saved_badness_tl
      }
      {
```

A horizontal box is handled in a similar way. The last case would be a void box in which case we do nothing hence the missing `F` branch.

```
        \box_if_horizontal:NT \l_shipout_box
            {
              \tl_set:Nx \l__shipout_saved_badness_tl
                 { \hfuzz=\the\hfuzz\relax
```

```
                    \hbadness=\the\hbadness\relax }
              \hfuzz=\c_max_dim
              \hbadness=\c_max_int
              \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
                   {
                     \hbox_set:Nn \l__shipout_tmp_box
                          { \l__shipout_saved_badness_tl #1 }
                     \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
                     \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
                     \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
                     \box_move_up:nn
                         \l_shipout_box_ht_dim
                         { \box_use:N \l__shipout_tmp_box }
                     \hbox_unpack:N \l_shipout_box
                   }
              \l__shipout_saved_badness_tl
            }
      }
}
```

(*End definition for* `\__shipout_add_background_box:n`.)

`\__shipout_add_foreground_box:n` Foreground boxes are done in the same way, only the order and placement of boxes has to be done differently.

```
\cs_new:Npn \__shipout_add_foreground_box:n #1
{
  \box_if_vertical:NTF \l_shipout_box
    {
      \tl_set:Nx \l__shipout_saved_badness_tl
         { \vfuzz=\the\vfuzz\relax
           \vbadness=\the\vbadness\relax }
      \vfuzz=\c_max_dim
      \vbadness=\c_max_int
      \vbox_set_to_ht:Nnn \l_shipout_box \l_shipout_box_ht_plus_dp_dim
           {
             \hbox_set:Nn \l__shipout_tmp_box
                  { \l__shipout_saved_badness_tl #1 }
             \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
             \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
             \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
             \skip_zero:N \baselineskip
             \skip_zero:N \lineskip
             \skip_zero:N \lineskiplimit
             \vbox_unpack:N \l_shipout_box
             \kern -\l_shipout_box_ht_plus_dp_dim
             \box_use:N \l__shipout_tmp_box
             \kern  \l_shipout_box_ht_plus_dp_dim
           }
      \l__shipout_saved_badness_tl
      \box_set_ht:Nn \l_shipout_box \l_shipout_box_ht_dim
      \box_set_dp:Nn \l_shipout_box \l_shipout_box_dp_dim
    }
    {
      \box_if_horizontal:NT \l_shipout_box
```

```
        {
          \tl_set:Nx \l__shipout_saved_badness_tl
            { \hfuzz=\the\hfuzz\relax
              \hbadness=\the\hbadness\relax }
          \hfuzz=\c_max_dim
          \hbadness=\c_max_int
          \hbox_set_to_wd:Nnn \l_shipout_box \l_shipout_box_wd_dim
               {
                 \hbox_unpack:N \l_shipout_box
                 \kern -\box_wd:N \l_shipout_box
                 \hbox_set:Nn \l__shipout_tmp_box
                     { \l__shipout_saved_badness_tl #1 }
                 \box_set_wd:Nn \l__shipout_tmp_box \c_zero_dim
                 \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
                 \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
                 \box_move_up:nn { \box_ht:N \l_shipout_box }
                               { \box_use:N \l__shipout_tmp_box }
                 \kern \box_wd:N \l_shipout_box
               }%
               \l__shipout_saved_badness_tl
        }
    }
}
```

(*End definition for* `\__shipout_add_foreground_box:n`.)

`\__shipout_init_page_origins:` `\c__shipout_horigin_tl` `\c__shipout_vorigin_tl`

Two constants holding the offset of the top-left with respect to the media box.

Setting the constants this way is courtesy of Bruno.

We delay setting the constants to the last possible place as there might be updates in the preamble or even in the `begindocument` hook that affects their setup.

```
\cs_new:Npn \__shipout_init_page_origins: {
  \tl_const:Nx \c__shipout_horigin_tl
     {
       \cs_if_exist_use:NTF \pdfvariable { horigin }
          { \cs_if_exist_use:NF \pdfhorigin { 1in } }
     }
  \tl_const:Nx \c__shipout_vorigin_tl
     {
       \cs_if_exist_use:NTF \pdfvariable { vorigin }
          { \cs_if_exist_use:NF \pdfvorigin { 1in } }
     }
```

After the constants have been set there is no need to execute this command again, in fact it would raise an error, so we redefine it to do nothing.

```
  \cs_gset_eq:NN \__shipout_init_page_origins: \prg_do_nothing:
}
```

(*End definition for* `\__shipout_init_page_origins:`, `\c__shipout_horigin_tl`, *and* `\c__shipout_vorigin_tl`.)

`\__shipout_picture_overlay:n`

Put the argument into a `picture` environment that doesn't take up any size and uses `1pt` for `\unitlength`.

> *Todo: Could perhaps be generalized as it might be useful elsewhere. For now it is not.*

```
\cs_new:Npn \__shipout_picture_overlay:n #1 {
```

The very first time this is executed we have to initialize (and freeze) the origins.

```
    \__shipout_init_page_origins:
    \kern -\c__shipout_horigin_tl \scan_stop:
    \vbox_to_zero:n {
      \kern -\c__shipout_vorigin_tl \scan_stop:
      \unitlength 1pt \scan_stop:
```

This mimics a simple zero-sized picture environment. The `\hss` is need in case there is horizontal material (without using `\put` with a positive width.

```
      \hbox_set_to_wd:Nnn \l__shipout_tmp_box \c_zero_dim
                          { \ignorespaces #1 \hss }
      \box_set_ht:Nn \l__shipout_tmp_box \c_zero_dim
      \box_set_dp:Nn \l__shipout_tmp_box \c_zero_dim
      \box_use:N \l__shipout_tmp_box
      \tex_vss:D
    }
}
```

(*End definition for* `\__shipout_picture_overlay:n`.)

`\__shipout_add_background_picture:n` Put a `picture` env in the background of the shipout box with its reference point in the top-left corner.

```
\cs_new:Npn \__shipout_add_background_picture:n #1 {
   \__shipout_add_background_box:n { \__shipout_picture_overlay:n {#1} }
}
```

(*End definition for* `\__shipout_add_background_picture:n`.)

`\__shipout_add_foreground_picture:n` Put a `picture` env in the foreground of the shipout box with its reference point in the top-left corner.

```
\cs_new:Npn \__shipout_add_foreground_picture:n #1 {
   \__shipout_add_foreground_box:n { \__shipout_picture_overlay:n {#1} }
}
```

(*End definition for* `\__shipout_add_foreground_picture:n`.)

`\shipout_discard:` Request that the next shipout box should be discarded. At the moment this is just setting a boolean, but we may want to augment this behavior that the position of the call is taken into account (in case LaTeX looks ahead and is not using the position for on the next page).

```
\cs_new_protected:Npn \shipout_discard: {
  \bool_gset_true:N \g__shipout_discard_bool
}
```

(*End definition for* `\shipout_discard:`. *This function is documented on page* 901.)

3.2 Handling the end of job hook

At the moment this is partly solved by using the existing hooks. But rather than putting the code into these hooks it should be moved to the right place directly as we shouldn't prefill hooks with material unless it needs to interact with other code.

\g_shipout_readonly_int
\ReadonlyShipoutCounter

We count every shipout activity that makes a page (but not those that are discarded) in order to know how many pages got produced.

```
\int_new:N \g_shipout_readonly_int
```

For LaTeX 2ε it is available as a command (i.e., a TeX counter only.

```
\cs_new_eq:NN \ReadonlyShipoutCounter  \g_shipout_readonly_int
```

(*End definition for* `\g_shipout_readonly_int` *and* `\ReadonlyShipoutCounter`*. These functions are documented on page* 902.)

\g_shipout_totalpages_int
\c@totalpages

We count every shipout attempt (even those that are discarded) in this counter. It is not used in the code but may get used in user code.

```
\int_new:N \g_shipout_totalpages_int
```

For LaTeX 2ε this is offered as a LaTeX counter so can be easily typeset inside the output routine to display things like "`\thepage/\thetotalpages`", etc.

```
\cs_new_eq:NN \c@totalpages \g_shipout_totalpages_int
\cs_new:Npn \thetotalpages { \arabic{totalpages} }
```

(*End definition for* `\g_shipout_totalpages_int` *and* `\c@totalpages`*. These functions are documented on page* 902.)

\@abspage@last

In `\@abspage@last` record the number of pages from the last run. This is written to the `.aux` and this way made available to the next run. In case there is no `.aux` file or the statement is missing from it we initialize it with the largest possible number in TeX. We use this as the default because then we are inserting the `shipout/lastpage` on the last page (or after the last page) but not on page 1 for a multipage document.

```
\xdef\@abspage@last{\number\maxdimen}
```

(*End definition for* `\@abspage@last`.)

\enddocument

Instead of using the hooks `enddocument` and `enddocument/afterlastpage` we add this code to private kernel hooks to be 100% sure when it is executed and to avoid cluttering the hooks with data that is always there.

Inside `\enddocument` there is a `\clearpage`. Just before that we execute this code here. There is a good chance that we are on the last page. Therefore, if we don't know the value from the last run, we assume that the current page is the right one. So we set `\@abspage@last` and as a result the next shipout will run the `shipout/lastpage` code. Of course, if there are floats that still need a placement this guess will be wrong but then rerunning the document will give us the correct value next time around.

\@kernel@after@enddocument

```
\g@addto@macro \@kernel@after@enddocument {
  \int_compare:nNnT \@abspage@last = \maxdimen
    {
```

We use LaTeX 2ε coding as `\@abspage@last` is not an L3 name.

```
      \xdef\@abspage@last{ \int_eval:n {\g_shipout_readonly_int + 1} }
    }
}
```

\@kernel@after@enddocument@afterlastpage

Once the `\clearpage` has done its work inside `\enddocument` we know for sure how many pages this document has, so we record that in the `.aux` file for the next run.

```
\g@addto@macro \@kernel@after@enddocument@afterlastpage {
```

There is one special case: If no output is produced then there is no point in a) recording the number as 0 will never match the page number of a real page and b) adding an extra page to ran the `shipout/lastpage` is pointless as well (as it would remain forever). So we test for this and run the code only if there have been pages.

```
  \int_compare:nNnF \g_shipout_readonly_int = 0
    {
```

This ends up in the `.aux` so we use LaTeX 2_ε names here.

Todo: This needs an interface for `\nofiles` *in expl3, doesn't at the moment!*

```
      \if@filesw
         \iow_now:Nx \@auxout {
           \gdef\string\@abspage@last {\int_use:N \g_shipout_readonly_int}}
      \fi
```

But we may have guessed wrongly earlier and have run it too early or we still have to run the `shipout/lastpage` even though there is no page to place it into. If that is the case we make a trivial extra page and put it there. This temporary page will then vanish again on the next run but helps to keep pdf viewers happy. In either case we should put out an appropriate "rerun" warning.

```
       \bool_if:NTF \g__shipout_lastpage_handled_bool
          {
```

If the hook was already executed, we have to test if that total shipouts match the shipouts from last run (because that corresponds to the page it was executed). If not we output a warning.

```
            \int_compare:nNnF \@abspage@last = \g_shipout_readonly_int
             {
               \@latex@warning@no@line{Hook~ 'shipout/lastpage'~ executed~
                 on~ wrong~ page~ (\@abspage@last\space not~
                 \int_use:N\g_shipout_readonly_int).\MessageBreak
                 Rerun~ to~ correct~ this}%
             }
          }
          {
```

If the hook was not run, we need to add an extra page and place it there. However, making this extra page in case the hook is actually empty would be forcing a rerun without any reason, so we check that condition and also check if `\@kernel@after@shipout@lastpage` contains any code. If both are empty we omit the page generation.

```
           \bool_lazy_and:nnF
             { \hook_if_empty_p:n {shipout/lastpage} }
             { \tl_if_empty_p:N \@kernel@after@shipout@lastpage }
             {
               \tex_shipout:D\vbox to\textheight
                 {
                   \hbox:n { \UseHook{shipout/lastpage}
                             \@kernel@after@shipout@lastpage }
```

This extra page could be totally empty except for the hook content, but to help the user understanding why it is there we put some text into it.

```
                    \__shipout_excuse_extra_page:
                    \null
                  }
```

At this point we also signal to LaTeX's endgame that a rerun is necessary so that an appropriate message can be shown on the terminal. We do this by simply defining a command used as a flag and tested in \enddocument.

```
                \cs_gset_eq:NN \@extra@page@added \relax
              }
            }
      }
}
```

(*End definition for* \enddocument*,* \@kernel@after@enddocument*, and* \@kernel@after@enddocument@afterlastpage*.*)

__shipout_excuse_extra_page:

Say mea culpa ...

```
\cs_new:Npn \__shipout_excuse_extra_page: {
  \vfil
  \begin{center}
    \bfseries Temporary~ page!
  \end{center}
    \LaTeX{}~ was~ unable~ to~ guess~ the~ total~ number~ of~ pages~
    correctly.~ ~ As~ there~ was~ some~ unprocessed~ data~ that~
    should~ have~ been~ added~ to~ the~ final~ page~ this~ extra~
    page~ has~ been~ added~ to~ receive~ it.
    \par
    If~ you~ rerun~ the~ document~ (without~ altering~ it)~ this~
    surplus~ page~ will~ go~ away,~ because~ \LaTeX{}~ now~ knows~
    how~ many~ pages~ to~ expect~ for~ this~ document.
  \vfil
}
```

(*End definition for* __shipout_excuse_extra_page:*.*)

\PreviousTotalPages

\@kernel@before@begindocument

In the preamble before the aux file was read \PreviousTotalPages is always zero.

```
\def\PreviousTotalPages{0}
```

In the aux file there should be an update for \@abspage@last recording the number of pages from the previous run. If not that macro holds the value of \maxdimen. So we test for it and update \PreviousTotalPages if there was a real value. This should happen just before the begindocument hook is executed so that the value can be used inside that hook.

```
\g@addto@macro\@kernel@before@begindocument
  {\ifnum\@abspage@last<\maxdimen
     \xdef\PreviousTotalPages{\@abspage@last}\fi}
```

(*End definition for* \PreviousTotalPages *and* \@kernel@before@begindocument*. These functions are documented on page* 902*.*)

4 Legacy LaTeX 2_ε interfaces

\DiscardShipoutBox

Request that the next shipout box is to be discarded.

```
\cs_new_eq:NN \DiscardShipoutBox \shipout_discard:
```

(*End definition for* `\DiscardShipoutBox`. *This function is documented on page* 901.)

\AtBeginDvi

If we roll forward from an earlier kernel `\AtBeginDvi` is defined so we better not use `\cs_new_protected:Npn` here.

```
\cs_set_protected:Npn \AtBeginDvi
                      {\__shipout_add_firstpage_material:Nn \AtBeginDvi}
```

(*End definition for* `\AtBeginDvi`. *This function is documented on page* 901.)

\DebugShipoutsOn
\DebugShipoutsOff

```
\cs_new_eq:NN \DebugShipoutsOn  \shipout_debug_on:
\cs_new_eq:NN \DebugShipoutsOff \shipout_debug_off:
```

(*End definition for* `\DebugShipoutsOn` *and* `\DebugShipoutsOff`. *These functions are documented on page* 903.)

5 Internal commands needed elsewhere

These internal commands use double and triple `@` signs so we need to stop getting them translated to the module name.

```
⟨@@=⟩
```

\@expl@@@shipout@add@firstpage@material@@Nn
\@expl@@@shipout@add@background@box@@n
\@expl@@@shipout@add@foreground@box@@n
\@expl@@@shipout@add@background@picture@@n
\@expl@@@shipout@add@foreground@picture@@n

Some internals needed elsewhere.

```
\cs_set_eq:NN \@expl@@@shipout@add@firstpage@material@@Nn
              \__shipout_add_firstpage_material:Nn
\cs_set_eq:NN \@expl@@@shipout@add@background@box@@n
              \__shipout_add_background_box:n
\cs_set_eq:NN \@expl@@@shipout@add@foreground@box@@n
              \__shipout_add_foreground_box:n
\cs_set_eq:NN \@expl@@@shipout@add@background@picture@@n
              \__shipout_add_background_picture:n
\cs_set_eq:NN \@expl@@@shipout@add@foreground@picture@@n
              \__shipout_add_foreground_picture:n
```

(*End definition for* `\@expl@@@shipout@add@firstpage@material@@Nn` *and others.*)

```
\ExplSyntaxOff
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

Rolling back here doesn't undefine the interface commands as they may be used in packages without rollback functionality. So we just make them do nothing which may or may not work depending on the code usage.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\shipout}{Hook management (shipout)}%
⟨latexrelease⟩
```

If we roll forward then `\tex_shipout:D` may not be defined in which case `\shipout` does have it original definition and so we must not `\let` it to something else which is `\relax`!

```
⟨latexrelease⟩\ifcsname tex_shipout:D\endcsname
⟨latexrelease⟩\expandafter\let\expandafter\shipout
⟨latexrelease⟩                \csname tex_shipout:D\endcsname
⟨latexrelease⟩\fi
⟨latexrelease⟩
⟨latexrelease⟩\let \RawShipout\@undefined
⟨latexrelease⟩\let \ShipoutBox\@undefined
⟨latexrelease⟩\let \ReadonlyShipoutCounter \@undefined
⟨latexrelease⟩\let \c@totalpages \@undefined
⟨latexrelease⟩\let \thetotalpages \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let \DiscardShipoutBox \@undefined
⟨latexrelease⟩\let \DebugShipoutsOn \@undefined
⟨latexrelease⟩\let \DebugShipoutsOff \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\DeclareRobustCommand \AtBeginDvi [1]{%
⟨latexrelease⟩  \global \setbox \@begindvibox
⟨latexrelease⟩    \vbox{\unvbox \@begindvibox #1}%
⟨latexrelease⟩}
⟨latexrelease⟩
⟨latexrelease⟩\let \AtBeginShipout \@undefined
⟨latexrelease⟩\let \AtBeginShipoutNext \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let \AtBeginShipoutFirst \@undefined
⟨latexrelease⟩
⟨latexrelease⟩\let \ShipoutBoxHeight \@undefined
⟨latexrelease⟩\let \ShipoutBoxDepth \@undefined
⟨latexrelease⟩\let \ShipoutBoxWidth \@undefined
⟨latexrelease⟩
```

We do not undo a substitution when rolling back. As the file support gets undone the underlying data is no longer used (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the `\undeclare@...` and its support macros available in all earlier kernel releases which is pointless (and actually worse).

```
⟨latexrelease⟩
⟨latexrelease⟩\let  \AtEndDvi \@undefined
```

We do not reenable a disabled package load when rolling back. As the file support gets undone the underlying data is no longer checked (and sufficiently obscure that it should not interfere with existing commands) and properly removing it would mean we need to make the `\reenable@package@load` command available in all earlier kernel releases which is pointless (and actually worse).

```
%\reenable@package@load{atenddvi}
```

```
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨∗2ekernel⟩
```

6 Package emulation for compatibility

6.1 Package atenddvi emulation

\AtEndDvi

This package has only one public command, so simulating it is easy and actually sensible to provide as part of the kernel.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2020/10/01}%
⟨latexrelease⟩                  {\AtEndDvi}{atenddvi emulation}%
\ExplSyntaxOn
\cs_new_protected:Npn \AtEndDvi #1 {\AddToHook{shipout/lastpage}{#1}}
\ExplSyntaxOff
```

As the package is integrate we prevent loading (no need to roll that back):

```
\disable@package@load{atenddvi}
   {\PackageWarning{atenddvi}
     {Functionality of this package is already\MessageBreak
      provided by LaTeX.\MessageBreak\MessageBreak
      It is there no longer necessary to load it\MessageBreak
      and you can safely remove it.\MessageBreak
      Found on}}
```

```
⟨/2ekernel | latexrelease⟩
```

```
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\AtEndDvi}{atenddvi emulation}%
⟨latexrelease⟩\let \AtEndDvi \@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\AtEndDvi`*. This function is documented on page* *901*.)

```
⟨/2ekernel⟩
```

6.2 Package atbegshi emulation

```
⟨*atbegshi-ltx⟩
\ProvidesPackage{atbegshi-ltx}
   [2021/01/10 v1.0c
     Emulation of the original atbegshi^^Jpackage with kernel methods]
```

\AtBeginShipoutBox

```
\let \AtBeginShipoutBox \ShipoutBox
```

(*End definition for* `\AtBeginShipoutBox`*. This function is documented on page* *903*.)

\AtBeginShipoutInit

Compatibility only, we aren't delaying ...

```
\let \AtBeginShipoutInit \@empty
```

(*End definition for* `\AtBeginShipoutInit`*. This function is documented on page* *904*.)

\AtBeginShipout
\AtBeginShipoutNext

Filling hooks

```
\protected\long\def\AtBeginShipout     #1{\AddToHook{shipout/before}{#1}}
\protected\long\def\AtBeginShipoutNext #1{\AddToHookNext{shipout/before}{#1}}
```

(*End definition for* `\AtBeginShipout` *and* `\AtBeginShipoutNext`*. These functions are documented on page* 904.)

`\AtBeginShipoutFirst` Slightly more complex as we need to know the name of the command under which the `shipout/firstpage` hook is filled.

```
\protected \def \AtBeginShipoutFirst
   {\@expl@@@shipout@add@firstpage@material@@Nn \AtBeginShipoutFirst}
```

(*End definition for* `\AtBeginShipoutFirst`*. This function is documented on page* 904.)

`\AtBeginShipoutDiscard` Just a different name.

```
\let \AtBeginShipoutDiscard \DiscardShipoutBox
```

(*End definition for* `\AtBeginShipoutDiscard`*. This function is documented on page* 904.)

`\AtBeginShipoutAddToBox` `\AtBeginShipoutAddToBoxForeground` `\AtBeginShipoutUpperLeft` `\AtBeginShipoutUpperLeftForeground` We don't expose them.

```
\let \AtBeginShipoutAddToBox
              \@expl@@@shipout@add@background@box@@n
\let \AtBeginShipoutAddToBoxForeground
              \@expl@@@shipout@add@foreground@box@@n

\let \AtBeginShipoutUpperLeft
              \@expl@@@shipout@add@background@picture@@n
\let \AtBeginShipoutUpperLeftForeground
              \@expl@@@shipout@add@foreground@picture@@n
```

(*End definition for* `\AtBeginShipoutAddToBox` *and others. These functions are documented on page* 903.)

`\AtBeginShipoutOriginalShipout` This offers the raw `\shipout` primitive of the engine. A page shipped out with this is not counted by `\ReadonlyShipoutCounter` counter and thus the mechanism to place `\specials` at the very end of the output might fail, etc. It should therefore not be used in new applications but is only provided to allow running legacy code. For new code use the commands provided by the kernel instead.

```
\ExplSyntaxOn
\cs_new_eq:NN \AtBeginShipoutOriginalShipout \tex_shipout:D
```

(*End definition for* `\AtBeginShipoutOriginalShipout`*. This function is documented on page* 904.)

`\ShipoutBoxHeight` `\ShipoutBoxWidth` `\ShipoutBoxDepth` This is somewhat different from the original in atbegshi where `\ShipoutBoxHeight` etc. only holds the `\the\ht<box>` value. This may has some implications in some use cases and if that is a problem then it might need changing.

```
\cs_new:Npn \ShipoutBoxHeight { \dim_use:N \l_shipout_box_ht_dim }
\cs_new:Npn \ShipoutBoxDepth  { \dim_use:N \l_shipout_box_dp_dim }
\cs_new:Npn \ShipoutBoxWidth  { \dim_use:N \l_shipout_box_wd_dim }
\ExplSyntaxOff
```

(*End definition for* `\ShipoutBoxHeight`*,* `\ShipoutBoxWidth`*, and* `\ShipoutBoxDepth`*.*)

```
⟨/atbegshi-ltx⟩
```

If the package is requested we substitute the one above:

```
⟨*2ekernel⟩
\declare@file@substitution{atbegshi.sty}{atbegshi-ltx.sty}
⟨/2ekernel⟩
```

6.3 Package **everyshi** emulation

This is now directly handled in that package so emulation is not necessary any more.

Rather important :-)

517 ⟨@@=⟩

File Y
ltoutput.dtx

1 Output Routine

1.1 Floats

The '2ekernel' code ensures that a `\usepackage{autoout1}` is essentially ignored if a 'full' format is being used that has the autoload file mode already in the format.

```
⟨defx⟩\begingroup
⟨defx⟩\makeatletter
⟨defx⟩\nfss@catcodes
⟨2ekernel⟩\expandafter\let\csname ver@autoout1.sty\endcsname\fmtversion
```

Historical LaTeX 2.09 comments (not necessarily accurate any more):

```
⟨*2ekernel⟩
\message{output,}
```

```
*************************************
*                OUTPUT             *
*************************************


PAGE LAYOUT PARAMETERS

\topmargin       : Extra space added to top of page.
@twoside         : boolean.  T if two-sided printing
\oddsidemargin   : IF @twoside = T
                     THEN extra space added to left of odd-numbered
                          pages.
                     ELSE extra space added to left of all pages.
\evensidemargin  : IF @twoside = T
                     THEN extra space added to left of even-numbered
                          pages.
\headheight      : height of head
\headsep         : separation between head and text
\footskip        : distance separation between baseline of last
                   line of text and baseline of foot.
                   Note difference between \footSKIP and \headSEP.
\textheight      : height of text on page, excluding head and foot
\textwidth       : width of printing on page
\columnsep       : IF @twocolumn = T
                     THEN width of space between columns
\columnseprule   : IF @twocolumn = T
                     THEN width of rule between columns (0 if none).
\columnwidth     : IF @twocolumn = T
                     THEN (\textwidth - \columnsep)/2
                     ELSE \textwidth
                   It is set by the \twocolumn and
                   \onecolumn commands.
```

`\@textbottom` : Command executed at bottom of vbox holding text of page (including figures). The `\raggedbottom` command almost `\let`'s this to `\vfil` (actually sets it to `\vskip \z@` plus.0001fil).
Should have depth 0pt.

`\@texttop` : Command executed at top of vbox holding text of page (including figures). Used by letter style; can also be used to produce centered pages.
Let to `\relax` by `\raggedbottom` and `\flushbottom`.

Page layout must initialize `\@colht` and `\@colroom` to `\textheight`.

PAGE STYLE PARAMETERS:

`\floatsep` : Space left between floats.
`\textfloatsep` : Space between last top float or first bottom float and the text.
`\topfigrule` : Command to place rule (or whatever) between floats at top of page and text. Executed in inner vertical mode right before the `\textfloatsep` skip separating the floats from the text. Must occupy zero vertical space. (See `\footnoterule`.)
`\botfigrule` : Same as `\topfigrule`, but put after the `\textfloatsep` skip separating text from the floats at bottom of page.
`\intextsep` : Space left on top and bottom of an in-text float.
`\dblfloatsep` : Space between double-column floats.
`\dbltextfloatsep` : Space between top double-column floats and text.
`\dblfigrule` : Similar to `\topfigrule`, but for double-column floats.
`\@fptop` : Glue to go at top of float column − must be 0pt + stretch
`\@fpsep` : Glue to go between floats in a float column.
`\@fpbot` : Glue to go at bottom of float column − must be 0pt + stretch
`\@dblfptop, \@dblfpsep, \@dblfpbot` : Analogous for double-column float page in two-column format.

FOOTNOTES: As in PLAIN, footnotes use `\insert\footins`.

PAGE LAYOUT SWITCHES AND MACROS

@twocolumn : Boolean. T if two columns per page globally.

PAGE STYLE MACROS AND SWITCHES

```
\@oddhead          : IF @twoside = T
                         THEN macro to generate head of odd-numbered
                              pages.
                         ELSE macro to generate head of all pages.
\@evenhead         : IF @twoside = T
                         THEN macro to generate head of even-numbered
                              pages.
\@oddfoot          : IF @twoside = T
                         THEN macro to generate foot of odd-numbered
                              pages.
                         ELSE macro to generate foot of all pages.
\@evenfoot         : IF @twoside = T
                         THEN macro to generate foot of even-numbered
                              pages.
@specialpage     : boolean.  T if current page is to have a special
                             format.
\@specialstyle   : If its value is  foo then
                     IF @specialpage = T
                       THEN the command \ps@foo is executed to
                            temporarily reset the page style parameters
                            before composing the current page.
                            This command should execute only \def's and
                            \edef's, making only local definitions.
```

FLOAT PLACEMENT PARAMETERS

```
The following parameters are set by the macro \@floatplacement.
When \@floatplacement is called,
\@colht is the height of the page or column being built.  I.e.:
        * For single-column page it equals \textheight.
        * For double-column page it equals \textheight - height
          of double-column floats on page.
Note that some are set globally and some locally:
   \@topnum  :=G Maximum number of floats allowed on the top of a
                 column.
   \@toproom :=G Maximum amount of top of column devoted to floats–
                 excluding \textfloatsep separation below the floats
                 and \floatsep separation between them.  For
                 two-column output, should be computed as a function
                 of \@colht.
   \@botnum, \@botroom
                : Analogous to above.
   \@colnum  :=G Maximum number of floats allowed in a column,
                 including in-text floats.
   \@textmin :=L Minimum amount of text (excluding footnotes) that
                 must appear on a text page.
                     %% 27 Sep 85 : made local to
                     %% \@addtocurcol and \@addtonextcol
                 It is now also used locally in processing double
                 floats.
```

`\@fpmin` :=L Minimum height of floats in a float column.

The macro `\@dblfloatplacement` sets the following parameters.

`\@dbltopnum` :=G Maximum number of double-column floats allowed at the top of a two-column page.

`\@dbltoproom` :=G Maximum height of double-column floats allowed at top of two-column page.

`\@fpmin` :=L Minimum height of floats in a float column.

It should also perform the following local assignments where necessary – i.e., where the new value differs from the old one:

```
\@fptop     :=L \@dblfptop
\@fpsep     :=L \@dblfpsep
\@fpbot     :=L \@dblfpbot
```

OUTPUT ROUTINE VARIABLES

`\@colht` : The total height of the current column. In single column style, it equals `\textheight`. In two-column style, it is `\textheight` minus the height of the double-column floats on the current page. MUST BE INITIALIZED TO `\textheight`.

`\@colroom` : The height available in the current column for text and footnotes. It equals `\@colht` minus the height of all floats committed to the top and bottom of the current column.

`\@textfloatsheight` : The total height of in-text floats on the current page.

`\footins` : Footnote insertion number.

`\@maxdepth` : Saved value of TeX's `\maxdepth`. Must be set when any routine sets `\maxdepth`.

CALLING THE OUTPUT ROUTINE

The output routine is called either by TeX's normal page-breaking mechanism, or by a macro putting a penalty `<` or = -10000 in the output list. In the latter case, the penalty indicates why the output routine was called, using the following code.

penalty	reason
-10000	`\pagebreak` `\newpage`
-10001	`\clearpage` (`\penalty` -10000 `\vbox{}` `\penalty` -10001)
-10002	float insertion, called from horizontal mode
-10003	float insertion, called from vertical mode.
-10004	float insertion.

Note: A float or marginpar puts the following sequence in the output list: (i) a penalty of -10004,
(ii) a null `\vbox`
(iii) a penalty of -10002 or -10003.
This solves two special problems:

1. If the float comes right after a `\newpage` or `\clearpage`, then the first penalty is ignored, but the second one invokes the output routine.
2. If there is a split footnote on the page, the second 'page' puts out the rest of the footnote.

THE OUTPUT ROUTINE

FUNCTIONS USED IN THE OUTPUT ROUTINE:

`\@outputpage` : Produces an output page with the contents of box `\@outputbox` as the text part.
Also sets `\@colht` :=G `\textheight`.
The page style is determined as follows.
IF @thispagestyle = true
THEN use `\thispagestyle` style
ELSE use ordinary page style.

`\@tryfcolumn\FLIST` : Tries to form a float column composed of floats from `\FLIST` (if nonempty) with the following parameters:
`\@colht` : height of box
`\@fpmin` : minimum height of floats in the box
`\@fpsep` : interfloat space
`\@fptop` : glue at top of box
`\@fpbot` : glue at bottom of box.
If it succeeds, then it does the following:
* `\@outputbox` :=L the composed float box.
* @fcolmade :=G true
* `\FLIST` :=G `\FLIST` - floats put in box
* `\@freelist` :=G `\@freelist` + floats put in box

If it fails, then:
* @fcolmade :=G false

NOTE: BIT MUST BE A SINGLE TOKEN!

`\@makefcolumn \FLIST` : Same as `\@tryfcolumn` except that it fails to make a float column only if `\FLIST` is empty. Otherwise, it makes a float column containing at least the first box in `\FLIST`, disregarding `\@fpmin`.

`\@startcolumn` :
Calls `\@tryfcolumn\@deferlist`. If `\@tryfcolumn` returns with (globally set) @fcolmade = false, then:
* Globally sets `\@toplist` and `\@botlist` to floats

from \@deferlist to go at top and bottom of column, deleting them from \@deferlist. It does this using \@colht as the total height, the page style parameters \@floatsep and \@textfloatsep, and the float placement parameters \@topnum, \@toproom, \@botnum, \@botroom, \@colnum and \textfraction.

* Globally sets \@colroom to \@colht minus the height of the added floats.

\@startdblcolumn :
Calls \@tryfcolumn\@dbldeferlist{8}. If \@tryfcolumn returns with (globally set) @fcolmade = false, then:

* Globally sets \@dbltoplist to floats from \@dbldeferlist to go at top and bottom of column, deleting them from \@dbldeferlist. It does this using \textheight as the total height, and the parameters \@dblfloatsep, etc.
* Globally sets \@colht to \textheight minus the height of the added floats.

\@combinefloats : Combines the text from box \@outputbox with the floats from \@toplist and \@botlist, putting the new box in \@outputbox. It uses \floatsep and \textfloatsep for the appropriate separations. It puts the elements of \TOPLIST and \BOTLIST onto \@freelist, and makes those lists null.

\@makecol : Makes the contents of \box255 plus the accumulated footnotes, plus the floats in \@toplist and \@botlist, into a single column of height \@colht (unless the page height has been locally changed), which it puts into box \@outputbox. It puts boxes in \@midlist back onto \@freelist and restores \maxdepth.

\@opcol : Outputs a column whose text is in box \@outputbox
If @twocolumn = false, then it calls \@outputpage, sets \@colht :=G \textheight, and calls \@floatplacement.

If @twocolumn = true, then:
If @firstcolumn = true, then it puts box \@outputbox into \@leftcolumn and sets @firstcolumn :=G false.

If @firstcolumn = false, then it puts out the current two-column page, any possible two-column float pages, and determines \@dbltoplist for the next page.

USER COMMANDS THAT CALL OR AFFECT THE OUTPUT ROUTINE

```
\newpage == BEGIN \par\vfil\penalty -10000 END

\clearpage == BEGIN \newpage
                    \write -1{}     % Part of hack to make sure no
                    \vbox{}         % \write's get lost.
                    \penalty -10001
              END

\cleardoublepage == BEGIN \clearpage
                          if @twoside = true and c@page is even
                            then \hbox{} \newpage fi
                    END
```

\twocolumn[BOX] : starts a new page, changing to twocolumn setting and puts BOX in a parbox of width \textwidth across the top. Useful for full-width titles for double-column pages.
SURPRISE: The stretch from \@dbltextfloatsep will be inserted between the BOX and the top of the two columns.

FLOAT-HANDLING MECHANISMS

The float environment obtains an insertion number B from the \@freelist (see below for a description of list manipulation), puts the float into box B and sets \count B to a FLOAT SPECIFIER. For a normal (not double-column) float, it then causes a page break in one of the following two ways:

- In outer hmode: \vadjust{\penalty -10002}
- In vmode : \penalty -10003.

For a double-column float, it puts B onto the \@dbldeferlist.
The float specifier has two components:

* A PLACEMENT SPECIFICATION, describing where the float may be placed.
* A TYPE, which is a power of two–e.g., figures might be type 1 floats, tables type 2 floats, programs type 4 floats, etc.

The float specifier is encoded as follows, where bit 0 is the least significant bit.

Bit	Meaning
0	1 iff the float may go where it appears in the text.
1	1 iff the float may go on the top of a page.
2	1 iff the float may go on the bottom of a page.
3	1 iff the float may go on a float page.
4	1 unless the PLACEMENT includes a !
5	1 iff a type 1 float

```
 6       1 iff a type 2 float
 etc.
```

A negative float specifier is used to indicate a marginal note.

MACROS AND DATA STRUCTURES FOR PROCESSING FLOATS

A FLOAT LIST consisting of the floats in boxes `\boxa` ... `\boxN` has the form:

```
        \@elt \boxa ... \@elt \boxN
```

where `\boxI` is defined by

```
        \newinsert\boxI
```

Normally, `\@elt` is `\let` to `\relax`. A test can be performed on the entire float list by locally `\def'`ing `\@elt` appropriately and executing the list.
This is a lot more efficient than looping through the list.

The following macros are used for manipulating float lists.

```
\@next \CS \LIST {NONEMPTY}{EMPTY} ==  %% NOTE: ASSUME \@elt
= \relax
   BEGIN  assume that \LIST == \@elt \B1 ... \@elt \Bn
          if n = 0
            then  EMPTY
            else  \CS     :=L \B1
                  \LIST  :=G \@elt \B2 ... \@elt \Bn
                  NONEMPTY
          fi
   END
```

```
\@bitor\NUM\LIST : Globally sets switch @test to the disjunction for
        all I of bit  log2 \NUM of the float specifiers of all the
        floats in \LIST.
        I.e., @test is set to true iff there is at least one
        float in \LIST having bit  log2 \NUM  of its float specifier
        equal to 1.
```

Note: log2 [(`\count` I)/32] is the bit number corresponding to the type of float I. To see if there is any float in `\LIST` having the same type as float I, you run `\@bitor` with
  `\NUM` = [(`\count` I)/32] * 32.

```
\@bitor\NUM\LIST ==
  BEGIN
     @test :=G false
     { \@elt \CTR ==  if \NUM <> 0 then
                        if \count\CTR / \NUM is odd
                           then  @test := true        fi fi
```

```
      \LIST
    }
  END
```

`\@cons\LIST\NUM` : Globally sets `\LIST` := `\LIST` * `\@elt \NUM`

```
\@cons\LIST\NUM ==
  BEGIN {  \@elt == \relax
           \LIST :=G \LIST \@elt \NUM
        }
```

BOX LISTS FOR FLOAT-PLACEMENT ALGORITHMS

`\@freelist`	: List of empty boxes for placing new floats.
`\@toplist`	: List of floats to go at top of current column.
`\@midlist`	: List of floats in middle of current column.
`\@botlist`	: List of floats to go at bottom of current column.
`\@deferlist`	: List of floats to go after current column.
`\@dbltoplist`	: List of double-col. floats to go at top of current page.
`\@dbldeferlist`	: List of double-column floats to go on subsequent pages.

FLOAT-PLACEMENT ALGORITHMS

`\@addtobot` : Tries to put insert `\@currbox` on `\@botlist.`
Called only when:
* `\ht` BOX `<` `\@colroom`
* type of `\@currbox` not on `\@deferlist`
* `\@colnum` `>` 0
* @insert = false

If it succeeds, then:
* sets @insert true
* decrements `\@botroom` by `\ht` BOX
* decrements `\@botnum` and `\@colnum` by 1
* decrements `\@colroom` by `\ht` BOX + either `\floatsep` or `\textfloatsep,` as appropriate.
* sets `\maxdepth` to 0pt

`\@addtotoporbot` : Tries to put insert `\@currbox` on `\@toplist` or `\@botlist.`
Called only under same conditions as `\@addtobot.`
If it succeeds, then:
* sets @insert true
* decrements `\@toproom` or `\@botroom` by `\ht` BOX
* decrements `\@colnum` and either `\@topnum` or `\@botnum` by 1
* decrements `\@colroom` by `\ht` BOX + `\floatsep`

or \textfloatsep, as appropriate.

\@addtocurcol : Tries to add \@currbox to current column, setting @insert true if it succeeds, false otherwise.
It will add \@currbox to top only if bit 0 of \count \@currbox is 0, and to the bottom only if bit 0 = 0 or an earlier float of the same type is put on the bottom.
If the float is put in the text, then \penalty\interlinepenalty is put right after the float, before the following \vskip, and \outputpenalty :=L 0.

\@addtonextcol : Tries to add \@currbox to the next column, setting @insert true if it succeeds, false otherwise.

\@addtodblcol : Tries to add \@currbox to the next double-column page, adding it to \@dbltoplist if it succeeds and \@dbldeferlist if it fails.

```
\@addmarginpar ==
 BEGIN
   if \@currlist nonempty
     then remove \@marbox from \@currlist
          add \@marbox and \@currbox to \@freelist
               %% NOTE: \@currbox = left box
     else LaTeX error: ?  %% shouldn't happen
   fi
   \@tempcnta := 1      %% 1 = right, -1 = left
   if @twocolumn = true
     then if @firstcolumn = true
            then \@tempcnta := -1
          fi
     else if @mparswitch = true
            then if count0 odd
                    else \@tempcnta := -1
                 fi
          fi
          if @reversemargin = true
             then \@tempcnta := -\@tempcnta
          fi
   fi
   if \@tempcnta < 0 then \box\@marbox :=G \box\@currbox
   fi
   \@tempdima   :=L maximum(\@mparbottom - \@pageht
                                          + ht of \@marbox, 0)
   if \@tempdima > 0 then LaTeX warning: 'marginpar moved' fi
   \@mparbottom :=G \@pageht + \@tempdima + depth of \@marbox
                        + \marginparpush
```

```
  \@tempdima   :=L \@tempdima - ht of \@marbox
  \box\@marbox :=G \box\@currbox
                            \vbox { \vskip \@tempdima
                                    \box\@marbox
                                  }
  height of \@marbox :=G depth of \@marbox :=G 0
  \kern -\@pagedp
  \nointerlineskip
  \hbox{ if @tempcnta > 0 then \hskip \columnwidth
                               \hskip \marginparsep
                          else \hskip -\marginparsep
                               \hskip -\marginparwidth
         fi
         \box\@marbox \hss
       }
  \nobreak
  \nointerlineskip
  \hbox{\vrule height 0 width 0 depth \@pagedp}
END
```

Floats and marginpars add a lot of dead cycles.
End of historical LaTeX 2.09 comments.

```
\maxdeadcycles = 100
\let\@elt\relax
\def\@next#1#2#3#4{\ifx#2\@empty #4\else
   \expandafter\@xnext #2\@@#1#2#3\fi}
\def\@xnext \@elt #1#2\@@#3#4{\def#3{#1}\gdef#4{#2}}

\def\@testfalse{\global\let\if@test\iffalse}
\def\@testtrue {\global\let\if@test\iftrue}
\@testfalse

\def\@bitor#1#2{\@testfalse {\let\@elt\@xbitor
   \@tempcnta #1\relax #2}}
```

RmS 91/11/22: Added test for `\count#1 = 0`. Suggested by Chris Rowley.

```
\def\@xbitor #1{\@tempcntb \count#1
   \ifnum \@tempcnta =\z@
   \else
     \divide\@tempcntb\@tempcnta
     \ifodd\@tempcntb \@testtrue\fi
   \fi}
```

DEFINITION OF FLOAT BOXES:

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/10/01}%
⟨latexrelease⟩                  {\bx@ZZ}{Extended float list}%
⟨*2ekernel | latexrelease⟩
\let\@elt\newinsert
⟨*2ekernel⟩
\def\@freelist{%
```

```
  \@elt\bx@A\@elt\bx@B\@elt\bx@C\@elt\bx@D\@elt\bx@E
  \@elt\bx@F\@elt\bx@G\@elt\bx@H\@elt\bx@I\@elt\bx@J
  \@elt\bx@K\@elt\bx@L\@elt\bx@M\@elt\bx@N
  \@elt\bx@O\@elt\bx@P\@elt\bx@Q\@elt\bx@R}
\@freelist
⟨/2ekernel⟩
\ifx\numexpr\@undefined\else
\def\reserved@a{%
  \@elt\bx@S\@elt\bx@T\@elt\bx@U\@elt\bx@V
  \@elt\bx@W\@elt\bx@X\@elt\bx@Y\@elt\bx@Z
  \@elt\bx@AA\@elt\bx@BB\@elt\bx@CC\@elt\bx@DD\@elt\bx@EE
  \@elt\bx@FF\@elt\bx@GG\@elt\bx@HH\@elt\bx@II\@elt\bx@JJ
  \@elt\bx@KK\@elt\bx@LL\@elt\bx@MM\@elt\bx@NN
  \@elt\bx@OO\@elt\bx@PP\@elt\bx@QQ\@elt\bx@RR
  \@elt\bx@SS\@elt\bx@TT\@elt\bx@UU\@elt\bx@VV
  \@elt\bx@WW\@elt\bx@XX\@elt\bx@YY\@elt\bx@ZZ}
\reserved@a
\def\@elt{\noexpand\@elt\noexpand}
\edef\@freelist{\@freelist\reserved@a}
\fi
\let\reserved@a\relax
\let\@elt\relax
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\bx@ZZ}{Extended float list}%
⟨latexrelease⟩\def\@freelist{%
⟨latexrelease⟩  \@elt\bx@A\@elt\bx@B\@elt\bx@C\@elt\bx@D\@elt\bx@E
⟨latexrelease⟩  \@elt\bx@F\@elt\bx@G\@elt\bx@H\@elt\bx@I\@elt\bx@J
⟨latexrelease⟩  \@elt\bx@K\@elt\bx@L\@elt\bx@M\@elt\bx@N
⟨latexrelease⟩  \@elt\bx@O\@elt\bx@P\@elt\bx@Q\@elt\bx@R}
⟨latexrelease⟩  \insc@unt=234
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

```
\gdef\@toplist{}
\gdef\@botlist{}
\gdef\@midlist{}
\gdef\@currlist{}
\gdef\@deferlist{}
\gdef\@dbltoplist{}
```

The new algorithm stores page wide floats together with column floats in a single `\@deferlist` list. We keep `\@dbldeferlist` initialised as empty so that packages that are testing for deferred floats can use the same code for old or new float handling.

```
\gdef\@dbldeferlist{}
```

PAGE LAYOUT PARAMETERS

```
\newdimen\topmargin
\newdimen\oddsidemargin
\newdimen\evensidemargin
\let\@themargin=\oddsidemargin
\newdimen\headheight
\newdimen\headsep
\newdimen\footskip
```

```
\newdimen\textheight
\newdimen\textwidth
\newdimen\columnwidth
\newdimen\columnsep
\newdimen\columnseprule
\newdimen\marginparwidth
\newdimen\marginparsep
\newdimen\marginparpush
```

\AtBeginDvi
\@begindvibox

We use a box register in which to put stuff that must appear before anything else in the `.dvi` file.

The stuff in the box should not add any typeset material to the page when it is unboxed.

This interface is no longer used. Instead a new one is inside `ltshipout.dtx`. We only keep the box in case some old code refers to it directly (or we do some rollback).

```
\newbox\@begindvibox
%\DeclareRobustCommand \AtBeginDvi [1]{%
%  \global \setbox \@begindvibox
%    \vbox{\unvbox \@begindvibox #1}%
%}
```

(*End definition for* `\AtBeginDvi` *and* `\@begindvibox`*. These functions are documented on page 901.*)

\@maxdepth

This is not the right place to set this; it needs to be set in a class/style file when `\maxdepth` is set.

Also, many settings to `\maxdepth` should be to `\@maxdepth`, probably?

```
\newdimen\@maxdepth
\@maxdepth = \maxdepth
```

(*End definition for* `\@maxdepth`.)

\paperheight
\paperwidth

New `\paper...` registers.

```
\newdimen\paperheight
\newdimen\paperwidth
```

(*End definition for* `\paperheight` *and* `\paperwidth`.)

\if@insert
\if@fcolmade
\if@specialpage
\if@firstcolumn
\if@twocolumn
\if@twoside
\if@reversemarginpar
\if@mparswitch
\col@number

Local switches first:

```
\newif \if@insert
```

These should definitely be global:

```
\newif \if@fcolmade
\newif \if@specialpage \@specialpagefalse
```

These should be global but are not always set globally in other files.

```
\newif \if@firstcolumn \@firstcolumntrue
\newif \if@twocolumn   \@twocolumnfalse
```

Not sure about these: two questions. Should things which must apply to a whole document be local or global (they probably should be 'preamble only' commands)? Are these three such things?

```
\newif \if@twoside     \@twosidefalse
\newif \if@reversemargin \@reversemarginfalse
\newif \if@mparswitch  \@mparswitchfalse
```

This counter has been imported from 'multicol'.

```
\newcount \col@number
\col@number \@ne
```

(*End definition for* `\if@insert` *and others.*)

Historical LaTeX 2.09 comments (not necessarily accurate any more):
INTERNAL REGISTERS

```
\newcount\@topnum
\newdimen\@toproom
\newcount\@dbltopnum
\newdimen\@dbltoproom
\newcount\@botnum
\newdimen\@botroom
\newcount\@colnum
\newdimen\@textmin
\newdimen\@fpmin
\newdimen\@colht
\newdimen\@colroom
\newdimen\@pageht
\newdimen\@pagedp
\newdimen\@mparbottom \@mparbottom\z@
\newcount\@currtype
\newbox\@outputbox
\newbox\@leftcolumn
\newbox\@holdpg
```

```
\def\@thehead{\@oddhead} % initialization
\def\@thefoot{\@oddfoot}
```

End of historical LaTeX 2.09 comments.

`\clearpage` The tests at the beginning are an experimental attempt to avoid a completely empty page after a `\twocolumn[...]`. This prevents the text from the argument vanishing into a float box, never to be seen again. We hope that it does not produce wrong formatting in other cases.

```
\def\clearpage{%
  \ifvmode
    \ifnum \@dbltopnum =\m@ne
      \ifdim \pagetotal <\topskip
        \hbox{}%
      \fi
    \fi
  \fi
  \newpage
  \write\m@ne{}%
  \vbox{}%
  \penalty -\@Mi
}
```

(*End definition for* `\clearpage`.)

\cleardoublepage

```
\def\cleardoublepage{\clearpage\if@twoside \ifodd\c@page\else
    \hbox{}\newpage\if@twocolumn\hbox{}\newpage\fi\fi\fi}
⟨/2ekernel⟩
```

(*End definition for* \cleardoublepage.)

\onecolumn

```
⟨*2ekernel | fltrace⟩
\def\onecolumn{%
  \clearpage
  \global\columnwidth\textwidth
  \global\hsize\columnwidth
  \global\linewidth\columnwidth
  \global\@twocolumnfalse
  \col@number \@ne
  \@floatplacement}
```

(*End definition for* \onecolumn.)

\newpage The two checks at the beginning ensure that an item label or run-in section title immediately before a \newpage get printed on the correct page, the one before the page break.

All three tests are largely to make error processing more robust; that is why they all reset the flags explicitly, even when it would appear that this would be done by a \leavevmode.

```
⟨/2ekernel | fltrace⟩
⟨latexrelease⟩\IncludeInRelease{2017/04/15}%
⟨latexrelease⟩                    {\newpage}{Check depth of page}%
⟨*2ekernel | latexrelease | fltrace⟩
\def \newpage {%
  \if@noskipsec
    \ifx \@nodocument\relax
      \leavevmode
      \global \@noskipsecfalse
    \fi
  \fi
  \if@inlabel
    \leavevmode
    \global \@inlabelfalse
  \fi
  \if@nobreak \@nobreakfalse \everypar{}\fi
  \par
```

The \vfil at the end of the macro before the break penalty will normally result in the page being run short, even with \flushbottom in effect (in contrast to the behavior of \pagebreak). However, if there is some explicit stretch on the page, say, a \vfill, it has the undesired side-effect, that the last line will not align at its baseline if it contains characters going below the baseline, as the value of \prevdepth is no longer taken into account by TEX. So we back up by that amount (or by \maxdepth if it is really huge), to mimic the normal behavior without the \newpage.

```
  \ifdim\prevdepth>\z@
     \vskip -%
       \ifdim\prevdepth>\maxdepth
```

```
        \maxdepth
      \else
        \prevdepth
      \fi
  \fi
  \vfil
  \penalty -\@M}
⟨/2ekernel | latexrelease | fltrace⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\newpage}{Check depth of page}%
⟨latexrelease⟩\def \newpage {%
⟨latexrelease⟩  \if@noskipsec
⟨latexrelease⟩    \ifx \@nodocument\relax
⟨latexrelease⟩      \leavevmode
⟨latexrelease⟩      \global \@noskipsecfalse
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \if@inlabel
⟨latexrelease⟩    \leavevmode
⟨latexrelease⟩    \global \@inlabelfalse
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \if@nobreak \@nobreakfalse \everypar{}\fi
⟨latexrelease⟩  \par
⟨latexrelease⟩  \vfil
⟨latexrelease⟩  \penalty -\@M}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel | fltrace⟩
```

(*End definition for* `\newpage`.)

`\@emptycol` It may be better to use an invisible rule rather than an empty box here.

```
\def \@emptycol {\vbox{}\penalty -\@M}
```

(*End definition for* `\@emptycol`.)

`\twocolumn` `\@topnewpage` There are several bug fixes to the two-column stuff here.

```
\def \twocolumn {%
  \clearpage
  \global\columnwidth\textwidth
  \global\advance\columnwidth-\columnsep
  \global\divide\columnwidth\tw@
  \global\hsize\columnwidth
  \global\linewidth\columnwidth
  \global\@twocolumntrue
  \global\@firstcolumntrue
  \col@number \tw@
```

There is no reason to put a `\@dblfloatplacement` here since `\@topnewpage` ignores these settings. The `\@floatplacement` is needed in case this comes after some changes.

```
  \@ifnextchar [\@topnewpage\@floatplacement
}
```

Note that here, getting a box from the freelist can assume success since this comes just after a `\clearpage`.

```
\long\def \@topnewpage [#1]{%
  \@nodocument
  \@next\@currbox\@freelist{}{}%
  \global \setbox\@currbox
    \color@vbox
      \normalcolor
      \vbox {%
        \hsize\textwidth
        \@parboxrestore
        \col@number \@ne
        #1%
        \vskip -\dbltextfloatsep
             }%
    \color@endbox
```

Added size test and warning message; perhaps we should use an error message.

```
  \ifdim \ht\@currbox>\textheight
    \ht\@currbox \textheight
  \fi
```

This next line is not essential but it is more robust to make this value non-zero, in case of weird errors.

This next bit is what is needed from `\@addtodblcol`, plus some extra checks for error trapping.

```
  \global \count\@currbox \tw@
  \@tempdima -\ht\@currbox
  \advance \@tempdima -\dbltextfloatsep
  \global \advance \@colht \@tempdima
  \ifx \@dbltoplist \@empty
  \else
    \@latex@error{Float(s) lost}\@ehb
    \let \@dbltoplist \@empty
  \fi
  \@cons \@dbltoplist \@currbox
```

This setting of `\@dbltopnum` is used only to change the typesetting in `\@combinedblfloats`.

```
  \global \@dbltopnum \m@ne
⟨*trace⟩
    \fl@trace{dbltopnum set to -1 (= \the \@dbltopnum) (topnewpage)}%
⟨/trace⟩
```

At points such as this we need to check that there is still a minimal amount of room left on the page; this uses an arbitrary small value at present; but note that this value is larger than that used when checking that page is too full of normal floats.

If there is little room left we just force a page-break, OK? This involves producing two empty columns. The second empty column may be produced by `\output`, in which case an extra, misleading, warning will be generated, OK? (This happens only when there is too little room left on the page for any float.) Otherwise (i.e. if the size is such that it is allowed as a normal float) the extra `\@emptycol` will be invoked in the second column by the conditional code guarded by the `\if@firstcolumn` test.

I now think that the cut-off point here should be `3\baselineskip`, but we make it a bit less so that 3 lines of text will be allowed, OK?

Since this happens only when there is nothing on the page but the 'top-box', the empty box should not cause any problem other than some overfull box messages, which is not entirely misleading.

Here we need two page-ends since both columns need to be empty.

```
 \ifdim \@colht<2.5\baselineskip
   \@latex@warning@no@line {Optional argument of \noexpand\twocolumn
               too tall on page \thepage}%
   \@emptycol
   \if@firstcolumn
   \else
     \@emptycol
   \fi
 \else
   \global \vsize \@colht
   \global \@colroom \@colht
   \@floatplacement
 \fi
}
```

(*End definition for* `\twocolumn` *and* `\@topnewpage`.)

`\output` `\@specialoutput`

This needs some small adjustments. We cannot guarantee that the float mechanism will interact correctly with this stuff, but that mechanism does not always work properly with footnotes already.

RmS 91/09/29:

added reset of `\par` to the output routine. This avoids problems when the output routine is called within a list where `\par` may be a no-op.

```
\output {%
  \let \par \@@par
  \ifnum \outputpenalty<-\@M
    \@specialoutput
  \else
    \@makecol
    \@opcol
```

Moved to `\@opcol`: `\@floatplacement`.

```
    \@startcolumn
```

This loop could be replaced by an `\expandafter` tail recursion in `\@startcolumn`.

```
    \@whilesw \if@fcolmade \fi
      {%
⟨*trace⟩
       \fl@trace{PAGE: float \if@twocolumn column \else page \fi
                     completed}%
⟨/trace⟩
       \@opcol\@startcolumn}%
  \fi
  \ifnum \outputpenalty>-\@Miv
```

At points such as this we need to check that there is still a minimal amount of room left on the page; this uses an arbitrary small value at present. If there is little room left we just force a page-break, OK?

This bit is essential only if a float has just been processed so maybe it should be moved; but this is the natural place at which to set the vsize and a test would need to be done anyway. A check has been added to ensure that there really has been a change in the value of `\@colroom`.

Since this happens only when there is nothing on the page but floats, the empty box should not cause any problem other than some overfull box messages, which is not entirely misleading.

The twocolumn case does not need any extra code here since this is the `\output` itself; in the second column there will still not be enough room left so `\@emptycol` will be executed again when the OR is called by the-page builder when it gets to the penalty inserted by the first execution. (The page-builder is never invoked whilst the OR is being executed since it builds a inner vlist; thus any conditional code for the two-column case within `\output` may not get executed with the correct value of `\if@firstcolumn`.

```
    \ifdim \@colroom<1.5\baselineskip
      \ifdim \@colroom<\textheight
        \@latex@warning@no@line {Text page \thepage\space
                                 contains only floats}%
        \@emptycol
%         \if@twocolumn
%           \if@firstcolumn
%           \else
%             \@emptycol
%           \fi
%         \fi
      \else
        \global \vsize \@colroom
      \fi
    \else
      \global \vsize \@colroom
    \fi
  \else
    \global \vsize \maxdimen
  \fi
}
```

Historical LaTeX 2.09 comments (not necessarily accurate any more):

CHANGES TO `\@specialoutput:`

* `\penalty\z@` changed to `\penalty\interlinepenalty` so `\samepage` works properly with figure and table environments.
  (Changed 23 Oct 86)

* Definition of `\@specialoutput` changed 26 Feb 88 so `\@pageht` and `\@pagedp` aren't changed for a marginal note.
  (Change suggested by Chris Rowley.)

End of historical LaTeX 2.09 comments.

```
\gdef\@specialoutput{%
   \ifnum \outputpenalty>-\@Mii
     \@doclearpage
```

```
  \else
    \ifnum \outputpenalty<-\@Miii
      \ifnum \outputpenalty<-\@MM \deadcycles \z@ \fi
      \global \setbox\@holdpg \vbox {\unvbox\@cclv}%
    \else
```

Note that `\boxmaxdepth` should not be set here since we wish to record the natural depth of the holdpg box.

This is changed so as to not lose anything, such as writes and marks, which may get into box 255 and should be returned to the list. This should only happen when the first penalty in the mechanism is discarded and therefore `\@holdpg` should always be void in this case. This can happen because a penalty is discarded whenever there is no box on the list.

It was just: `\setbox\@tempboxa \box \@cclv`.

The last box which is removed is the box put there by the double-penalty mechanism. The `\unskip` then removes the `\topskip` which is put there since the box is the first on the page.

```
      \global \setbox\@holdpg \vbox{%
                      \unvbox\@holdpg
                      \unvbox\@cclv
```

We must now remove the box added by the float mechanism and the `\topskip` glue therefore added above it by TEX.

```
                      \setbox\@tempboxa \lastbox
                      \unskip
                                    }%
```

These two are needed as separate dimensions only by `\@addmarginpar`; for other purposes we put the whole size into `\@pageht` (see below).

```
      \@pagedp \dp\@holdpg
      \@pageht \ht\@holdpg
      \unvbox \@holdpg
      \@next\@currbox\@currlist{%
        \ifnum \count\@currbox>\z@
```

Putting the whole size into `\@pageht` (see above).

```
          \advance \@pageht \@pagedp
          \ifvoid\footins \else
            \advance \@pageht \ht\footins
            \advance \@pageht \skip\footins
            \advance \@pageht \dp\footins
          \fi
          \ifvbox \@kludgeins
```

We want to make the adjustment due to this insert only if the non-star form is used. The *-form will probably not work with floats, but maybe it still could make some adjustment here even so?

```
            \ifdim \wd\@kludgeins=\z@
              \advance \@pageht \ht\@kludgeins
⟨*trace⟩
              \fl@trace {Extra size added: \the \ht\@kludgeins}%
⟨/trace⟩
            \fi
          \fi
```

This version puts the inserts back just before the additional material; it could be moved earlier, before unboxing the page-so-far. Neither is guaranteed not to put things on the wrong page. This version is similar to the original version.

```
            \@reinserts
            \@addtocurcol
          \else
            \@reinserts
            \@addmarginpar
          \fi
          }\@latexbug
```

A 2e change: use `\addpenalty` instead of `\penalty` here. Some penalty is needed to create a potential break-point immediately after the reinserts (or the marginal). Otherwise there can be no possibility to break here and this can cause the reinserts or the marginal to appear on the next page (which is often incorrect). However, if the nobreak flag is true, a `\nobreak` must be correct.

```
        \ifnum \outputpenalty<\z@
          \if@nobreak
            \nobreak
          \else
            \addpenalty \interlinepenalty
          \fi
        \fi
      \fi
    \fi
}
⟨/2ekernel | fltrace⟩
```

(*End definition for* `\output` *and* `\@specialoutput`.)

`\@testwrongwidth` `\f@depth`

Test if the float box has the wrong width when trying to place it into some area. (Actually the test is for a conventional depth setting rather than for the width of the float. For that reason the box depth was explicitly tailored when the float was created).

```
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\@testwrongwidth}{float order in 2-column}%
⟨*2ekernel | latexrelease | fltrace⟩
\def\@testwrongwidth #1{%
  \ifdim\dp#1=\f@depth
⟨*trace⟩
    \fl@trace{\string#1
              \ifdim\f@depth=\z@ single \else double \fi
              column float -- ok}%
⟨/trace⟩
  \else
    \global\@testtrue
⟨*trace⟩
    \fl@trace{\string#1
              \ifdim\f@depth=\z@ double \else single \fi
              column float -- wrong}%
⟨/trace⟩
  \fi}%
```

Normally looking for single column floats, which have zero depth.

```
\let\f@depth\z@
```

```
⟨/2ekernel | latexrelease | fltrace⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\@testwrongwidth}{float order in 2-column}%
⟨latexrelease⟩\let\@testwrongwidth\@undefined
⟨latexrelease⟩\let\f@depth\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\@testwrongwidth` *and* `\f@depth`.)

`\@doclearpage` This is a very much an emergency action, just dumping everything: footnotes first then floats. A more sophisticated version is needed; but even more urgent is a bug-free version (see, for example, pr/3528).

Also, it puts any left-over non-boxes (writes, specials, etc.) back after any float pages created: this is a very bad bug since, for example, a kludge insert will be in quite the wrong place and, worse, be irremovable and uncancelable.

All the remaining changes are replacing the double column defer list or inserting the extra test `\@testwrongwidth{`⟨*box*⟩`}` at suitable places. That is at places where a box is taken off the deferlist.

```
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\@doclearpage}%
⟨latexrelease⟩                              {float order in 2-column}%
⟨*2ekernel | latexrelease⟩
\def \@doclearpage {%
     \ifvoid\footins
       \ifvbox\@kludgeins
         {\setbox \@tempboxa \box \@kludgeins}%
⟨*trace⟩
         \fl@trace {kludgeins box made void}%
⟨/trace⟩
       \fi
       \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
       \setbox\@tempboxa\box\@cclv
       \xdef\@deferlist{\@toplist\@botlist\@deferlist}%
       \global \let \@toplist \@empty
       \global \let \@botlist \@empty
       \global \@colroom \@colht
       \ifx \@currlist\@empty
       \else
          \@latex@error{Float(s) lost}\@ehb
          \global \let \@currlist \@empty
       \fi
       \@makefcolumn\@deferlist
       \@whilesw\if@fcolmade \fi{\@opcol\@makefcolumn\@deferlist}%
       \if@twocolumn
         \if@firstcolumn
           \xdef\@deferlist{\@dbltoplist\@deferlist}%
           \global \let \@dbltoplist \@empty
           \global \@colht \textheight
           \begingroup
              \@dblfloatplacement
```

```
              \@makefcolumn\@deferlist
              \@whilesw\if@fcolmade \fi{\@outputpage
                                        \@makefcolumn\@deferlist}%
            \endgroup
          \else
            \vbox{}\clearpage
          \fi
        \fi
```

the next line is needed to avoid losing floats in certain circumstances a single call to the original `\doclearpage` will now no longer output all floats.

```
        \ifx\@deferlist\@empty \else\clearpage \fi
      \else
        \setbox\@cclv\vbox{\box\@cclv\vfil}%
        \@makecol\@opcol
        \clearpage
      \fi
}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@doclearpage}%
⟨latexrelease⟩                              {float order in 2-column}%
⟨latexrelease⟩\def \@doclearpage {%
⟨latexrelease⟩      \ifvoid\footins
```

We empty any left over kludge insert box here; this is a temporary fix. It should perhaps be applied to one page of cleared floats, but who cares? The whole of this stuff needs completely redoing for many such reasons.

```
⟨latexrelease⟩        \ifvbox\@kludgeins
⟨latexrelease⟩          {\setbox \@tempboxa \box \@kludgeins}%
⟨*trace⟩
⟨latexrelease⟩          \fl@trace {kludgeins box made void}%
⟨/trace⟩
⟨latexrelease⟩        \fi
⟨latexrelease⟩        \setbox\@tempboxa\vsplit\@cclv to\z@ \unvbox\@tempboxa
⟨latexrelease⟩        \setbox\@tempboxa\box\@cclv
⟨latexrelease⟩        \xdef\@deferlist{\@toplist\@botlist\@deferlist}%
⟨latexrelease⟩        \global \let \@toplist \@empty
⟨latexrelease⟩        \global \let \@botlist \@empty
⟨latexrelease⟩        \global \@colroom \@colht
⟨latexrelease⟩        \ifx \@currlist\@empty
⟨latexrelease⟩        \else
⟨latexrelease⟩           \@latexerr{Float(s) lost}\@ehb
⟨latexrelease⟩           \global \let \@currlist \@empty
⟨latexrelease⟩        \fi
⟨latexrelease⟩        \@makefcolumn\@deferlist
⟨latexrelease⟩        \@whilesw\if@fcolmade \fi
⟨latexrelease⟩                      {\@opcol\@makefcolumn\@deferlist}%
⟨latexrelease⟩        \if@twocolumn
⟨latexrelease⟩          \if@firstcolumn
⟨latexrelease⟩            \xdef\@dbldeferlist{\@dbltoplist\@dbldeferlist}%
```

```
⟨latexrelease⟩            \global \let \@dbltoplist \@empty
⟨latexrelease⟩            \global \@colht \textheight
⟨latexrelease⟩            \begingroup
⟨latexrelease⟩               \@dblfloatplacement
⟨latexrelease⟩               \@makefcolumn\@dbldeferlist
⟨latexrelease⟩               \@whilesw\if@fcolmade \fi
⟨latexrelease⟩                     {\@outputpage\@makefcolumn\@dbldeferlist}%
⟨latexrelease⟩            \endgroup
⟨latexrelease⟩          \else
⟨latexrelease⟩            \vbox{}\clearpage
⟨latexrelease⟩          \fi
⟨latexrelease⟩        \fi
⟨latexrelease⟩      \else
⟨latexrelease⟩        \setbox\@cclv\vbox{\box\@cclv\vfil}%
⟨latexrelease⟩        \@makecol\@opcol
⟨latexrelease⟩        \clearpage
⟨latexrelease⟩      \fi
⟨latexrelease⟩   }%
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\@doclearpage`.)

`\@opcol` Several changes in detail here.

```
⟨*2ekernel | fltrace⟩
\def \@opcol {%
  \if@twocolumn
```

The funny-looking internal commands are interfacing with the new marks mechanism. We make sure (elsewhere) that those are always defined, even when we roll back, so here we add them unconditionally. This still need turning into a hook or config point eventually:

```
    \@expl@@@mark@update@dblcol@structures@@
    \@outputdblcol
  \else
    \@expl@@@mark@update@singlecol@structures@@
    \@outputpage
⟨*trace⟩
    \fl@trace{PAGE: one column (float? see above) page completed}%
⟨/trace⟩
```

Not needed since it comes after `\@outputpage`:

```
%   \global\@colht\textheight
  \fi
```

These do not need to be done every time `\@opcol` is used: they should be grouped together since they all need to be done at the end of the non-special output routine, or at the end of a clearpage one.

```
  \global \@mparbottom \z@ \global \@textfloatsheight \z@
  \@floatplacement
}
⟨/2ekernel | fltrace⟩
```

(*End definition for* `\@opcol`.)

\@makecol We must rewrite this macro to allow for variations in page-makeup required by changes in page-length.

This uses a different macro if a special-length column is being produced.

```
⟨*2ekernel⟩
\gdef \@makecol {%
  \ifvoid\footins
    \setbox\@outputbox \box\@cclv
  \else
    \setbox\@outputbox \vbox {%
```

This \boxmaxdepth setting is to ensure that deep footnotes do not overwrite the footer (on account of the negative skip added later): it should use \@maxdepth otherwise the change is pointless when there are footnotes.

But see also its use when combining floats.

```
      \boxmaxdepth \@maxdepth
%       \@tempdima\dp\@cclv
      \unvbox \@cclv
%       \vskip-\@tempdima
      \vskip \skip\footins

      \color@begingroup
        \normalcolor
        \footnoterule
        \unvbox \footins
      \color@endgroup
      }%
  \fi
```

The h floats have now been finally committed to this page so we can reset their list. The top and bottom floats are then added to the page.

```
  \let\@elt\relax
  \xdef\@freelist{\@freelist\@midlist}%
  \global \let \@midlist \@empty
  \@combinefloats
```

The variations start here in case \enlargethispage has been used.

```
  \ifvbox\@kludgeins
    \@makespecialcolbox
  \else
```

This extra reboxing is only needed to add the \@texttop and \@textbotttom but this could be done earlier, when the floats are added.

The \boxmaxdepth resetting here will have no effect unless \@textbottom ends with a box or rule. So is this (or possibly \@maxdepth) the correct value?

The \vskip -\dimen@ ensures that the visible depth of the box does not affect the placement of anything on the page. Thus very deep pages will overprint the footer; but these should have been prevented by suitable settings of the maxdepths at appropriate times.

If \@textbottom ends with a box or rule of non-zero depth then this skip adjustment should be done again after it.

I think that the final boxing of the main text page could have a common ending which may make it simpler to see what is going on.

This needs further investigation, especially in the 'special case'.

Also, the `\boxmaxdepth` setting here affects what happens within `\@texttop` and `\@textbottom`, should it? Is it needed at all?

RmS 91/10/22: Replaced `\dimen128` by `\dimen@`.

```
    \setbox\@outputbox \vbox to\@colht {%
%       \boxmaxdepth \maxdepth                  %??
      \@texttop
      \dimen@ \dp\@outputbox
      \unvbox \@outputbox
      \vskip -\dimen@
      \@textbottom
      }%
  \fi
  \global \maxdepth \@maxdepth
}
```

(*End definition for* `\@makecol`.)

`\@reinserts` This is the code which reinserts the inserts. It puts them all in one place; this can make some of them come out on the wrong page. It has been put into a separate macro to expedite experimentation.

```
\gdef \@reinserts{%
  \ifvoid\footins\else\insert\footins{\unvbox\footins}\fi
  \ifvbox\@kludgeins\insert\@kludgeins
                      {\unvbox\@kludgeins}\fi
}
⟨/2ekernel⟩
```

(*End definition for* `\@reinserts`.)

`\@makespecialcolbox` This implements certain variations in page-makeup.

```
⟨*2ekernel | fltrace⟩
\gdef \@makespecialcolbox {%
⟨*trace⟩
   \fl@trace{Kludgeins ht \the\ht\@kludgeins\space
                           dp \the\dp\@kludgeins\space
                           wd \the\wd\@kludgeins}%
⟨/trace⟩
```

First we find the natural height of the column.

See above for discussion of what is happening here.

This needs further investigation, especially in this 'special case'.

```
  \setbox\@outputbox \vbox {%
    \@texttop
    \dimen@ \dp\@outputbox
    \unvbox\@outputbox
    \vskip-\dimen@
    }%
  \@tempdima \@colht
  \ifdim \wd\@kludgeins>\z@
```

Note that in this case (the *-version), the height of the `\@kludgeins` box is not used since its value is somewhat arbitrary: it need only be big enough to ensure that the page-break is not taken prematurely.

Here we calculate how much vertical space needs to be added in order to enable the column to fit into a box of size `\@colht` using the best information we have about the amount of shrink available (another thing which is known internally about a box, but cannot be accessed at the TEX level!).

This needs TEX3 otherwise `\pageshrink` is zero anyway; it may not be exactly the figure we wish as it is the total available from the all the material collected before the page-break decision is made. It will, we think, always be an overestimate of the actual shrink in the box; therefore this should always force the shortest possible column with the possibility of an overfull box.

This should work for both flush- and ragged-bottom setting since it makes the contents no smaller than the size (`\@colht`) of the box into which they are put.

Their should perhaps be an upper limit, of 0pt?, on the extra space added to force shrinking.

See above for a discussion of the `\boxmaxdepth` setting here.

```
    \advance \@tempdima -\ht\@outputbox
    \advance \@tempdima \pageshrink
⟨*trace⟩
    \fl@trace {Natural ht of col: \the \ht\@outputbox}%
    \fl@trace {\string \@colht: \the \@colht}%
    \fl@trace {Pageshrink added: \the \pageshrink}%
    \fl@trace {Hence, space added: \the \@tempdima}%
⟨/trace⟩
    \setbox\@outputbox \vbox to \@colht {%
%       \boxmaxdepth \maxdepth
      \unvbox\@outputbox
      \vskip \@tempdima
      \@textbottom
      }%
```

For the unstarred version, the final size of the page is precisely specified. Therefore, at least for the flush-bottom case, we need to ensure that, visually, it has this size exactly.

Thus we calculate this size and set the material in a box of this size, which is then put into a box of size `\@colht` with `\vss` at the bottom.

```
  \else
    \advance \@tempdima -\ht\@kludgeins
⟨*trace⟩
    \fl@trace {Natural ht of col: \the \ht\@outputbox}%
    \fl@trace {\string \@colht: \the \@colht}%
    \fl@trace {Extra size added: -\the \ht \@kludgeins}%
    \fl@trace {Hence, height of inner box: \the \@tempdima}%
    \fl@trace {Max? pageshrink available: \the \pageshrink}%
⟨/trace⟩
```

This type of final packaging could be done always; this may simplify all of this page-makeup.

It is not necessary to set `\boxmaxdepth` here since the `\@outputbox` ends with glue.

```
    \setbox \@outputbox \vbox to \@colht {%
      \vbox to \@tempdima {%
```

```
          \unvbox\@outputbox
          \@textbottom}%
        \vss}%
    \fi
```

Finally we need to explicitly make the insert box void.

```
    {\setbox \@tempboxa \box \@kludgeins}%
⟨*trace⟩
      \fl@trace {kludgeins box made void}%
⟨/trace⟩
}
⟨/2ekernel | fltrace⟩
```

(*End definition for* `\@makespecialcolbox`.)

`\@texttop`
`\@textbottom`

These do nothing as a default.

```
⟨*2ekernel⟩
\let \@texttop \relax
\let \@textbottom \relax
```

(*End definition for* `\@texttop` *and* `\@textbottom`.)

`\@resetactivechars`
`\@activechar@info`

RmS 93/09/06: added hook to protect against certain active characters in the output routine. Default checks are for active space and end-of-line.

```
\def\@activechar@info #1{%
      \@latex@info@no@line {Active #1 character found while
                            output routine is active
                            \MessageBreak
                            This may be a bug in a package file
                            you are using}%
}
```

Do not put any spaces in this next bit!

```
\begingroup
\obeylines\obeyspaces%
\catcode`\'\active%
\gdef\@resetactivechars{%
\def^^M{\@activechar@info{EOL}\space}%
\def {\@activechar@info{space}\space}%
\let'\active@math@prime}%
\endgroup
```

(*End definition for* `\@resetactivechars` *and* `\@activechar@info`.)

`\@outputpage`
`\@shipoutsetup`
`\@writesetup`

The `\color@hbox` hooks here are used to avoid putting just a colour special into an otherwise empty box (in a header or footer). These boxes are often set to be completely empty and so adding a special produces a very underfull box message.

There has been extensive tidying up of the old code here; including the removal of a level of grouping.

The setting of `\protect` immediately before the `\shipout` is needed so that protected commands within `\write`s are handled correctly.

Within shipout's vbox it is reset to its default value, `\relax`.

Resetting it to its default value after the shipout has been completed (and the contents of the writes have been expanded) must be done by use of `\aftergroup`. This

is because it must have the value `\relax` before macros coming from other uses of `\aftergroup` within this box are expanded.

Putting this into the `\aftergroup` token list does not affect the definition used in expanding the `\write`s because the aftergroup token list is only constructed when popping the save-stack, it is not expanded until after the shipout is completed.

Question: should things from an `\aftergroup` within the shipped out box be executed in the environment set up for the writes, or after it finishes?

A lot of this code has been in-lined to prevent mis-use of internal commands as hooks.

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2017/04/15}%
⟨latexrelease⟩  {\@outputpage}{Reset language for hyphenation}%
⟨*2ekernel | latexrelease⟩
\def\@outputpage{%
```

The `\endgroup` is put in by `\aftergroup`.

```
\begingroup
```

Now all the set-up stuff has been in-lined for Frank.

First the stuff for the writes.

From here ... was in the command `\@writesetup`.

```
 \let \protect \noexpand
```

RmS 93/08/19: Redefined accents to allow changes in font encoding; but exactly why was this needed?

Reset `\language` to the value current at `\begin{document}`. In particular this ensures that a pagebreak in `verbatim` does not prevent hyphenation in the page head.

```
 \language\document@default@language
```

The `\catcode`\ = 10` was removed as it was considered useless (presumably because nothing gets tokenized during shipout).

This was put in as some error produced active spaces in a mark, I think.

Why was the hyphen reset?

```
 \@resetactivechars
```

If a page break happens between the start of a list and its first item the `@newlist` will be true and this will mess up any list that is used in the header or footer of the page. So we have to reset that flag.

```
 \global\let\@@if@newlist\if@newlist
 \global\@newlistfalse
```

This next hook replaces the following:

```
 \let\-\@dischyph
 \let\'\@acci\let\`\@accii\let\=\@acciii
 \let\\\@normalcr
 \let\par\@@par %% 15 Sep 87 (this was once inside the box)
```

and it does more than they did; in particular it sets:

```
\parindent\z@
\parskip\z@skip
\everypar{}%
\leftskip\z@skip
\rightskip\z@skip
\parfillskip\@flushglue
\lineskip\normallineskip
\baselineskip\normalbaselineskip
\sloppy
```

```
\@parboxrestore
```

... to here was in the command `\@writesetup`.

```
\shipout \vbox{%
  \set@typeset@protect
  \aftergroup \endgroup
```

Correct? or just restore by ending the group?

```
  \aftergroup \set@typeset@protect
```

This first bit has been moved inside the shipped out box.

Now the setup inside the shipped out box; this should contain all the stuff that could only affect typesetting; other stuff may need to be reset for the writes also.

From here ... was in the command `\@shipoutsetup`.

```
\if@specialpage
  \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
\fi
\if@twoside
  \ifodd\count\z@ \let\@thehead\@oddhead \let\@thefoot\@oddfoot
       \let\@themargin\oddsidemargin
  \else \let\@thehead\@evenhead
     \let\@thefoot\@evenfoot \let\@themargin\evensidemargin
  \fi
\fi
```

The rest was always inside the box.

RmS 91/08/15: added this line:

```
\reset@font
```

RmS 93/08/06 Added `\lineskiplimit=0pt` to guard against it being nonzero: e.g. by `\offinterlineskip` being in effect.

There are probably lots of other things that may need resetting.

```
\normalsize
```

Reset the space factors.

```
\normalsfcodes
```

Reset these here (previously reset separately for head and foot)

```
\let\label\@gobble
\let\index\@gobble
\let\glossary\@gobble
```

```
\baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
```

... to here was in the command `\@shipoutsetup`.

```
    \@begindvi
    \vskip \topmargin
    \moveright\@themargin \vbox {%
      \setbox\@tempboxa \vbox to\headheight{%
        \vfil
        \color@hbox
          \normalcolor
          \hb@xt@\textwidth{\@thehead}%
        \color@endbox
```

22 Feb 87

```
        }%
      \dp\@tempboxa \z@
      \box\@tempboxa
      \vskip \headsep
      \box\@outputbox
      \baselineskip \footskip
      \color@hbox
        \normalcolor
        \hb@xt@\textwidth{\@thefoot}%
      \color@endbox
      }%
    }%
```

`\endgroup` now inserted by `\aftergroup`

Restore `\if@newlist`

```
  \global\let\if@newlist\@@if@newlist
```

```
  \global \@colht \textheight
  \stepcounter{page}%
```

It is now clear that this does something useful, thanks to Piet van Oostrum. It is needed because a float page is made without using TeX's page-builder; thus the output routine is never called so the marks are not updated.

```
  \let\firstmark\botmark
}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩  {\@outputpage}{Reset language for hyphenation}%
⟨latexrelease⟩\def\@outputpage{%
⟨latexrelease⟩\begingroup
⟨latexrelease⟩  \let \protect \noexpand
⟨latexrelease⟩  \@resetactivechars
⟨latexrelease⟩  \global\let\@@if@newlist\if@newlist
⟨latexrelease⟩  \global\@newlistfalse
⟨latexrelease⟩  \@parboxrestore
⟨latexrelease⟩  \shipout \vbox{%
⟨latexrelease⟩    \set@typeset@protect
⟨latexrelease⟩    \aftergroup \endgroup
⟨latexrelease⟩    \aftergroup \set@typeset@protect
⟨latexrelease⟩  \if@specialpage
⟨latexrelease⟩    \global\@specialpagefalse\@nameuse{ps@\@specialstyle}%
⟨latexrelease⟩  \fi
```

```
⟨latexrelease⟩  \if@twoside
⟨latexrelease⟩    \ifodd\count\z@
⟨latexrelease⟩         \let\@thehead\@oddhead \let\@thefoot\@oddfoot
⟨latexrelease⟩         \let\@themargin\oddsidemargin
⟨latexrelease⟩    \else \let\@thehead\@evenhead
⟨latexrelease⟩       \let\@thefoot\@evenfoot \let\@themargin\evensidemargin
⟨latexrelease⟩    \fi
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \reset@font
⟨latexrelease⟩  \normalsize
⟨latexrelease⟩  \normalsfcodes
⟨latexrelease⟩  \let\label\@gobble
⟨latexrelease⟩  \let\index\@gobble
⟨latexrelease⟩  \let\glossary\@gobble
⟨latexrelease⟩  \baselineskip\z@skip \lineskip\z@skip \lineskiplimit\z@
⟨latexrelease⟩    \@begindvi
⟨latexrelease⟩    \vskip \topmargin
⟨latexrelease⟩    \moveright\@themargin \vbox {%
⟨latexrelease⟩      \setbox\@tempboxa \vbox to\headheight{%
⟨latexrelease⟩        \vfil
⟨latexrelease⟩        \color@hbox
⟨latexrelease⟩          \normalcolor
⟨latexrelease⟩          \hb@xt@\textwidth{\@thehead}%
⟨latexrelease⟩        \color@endbox
⟨latexrelease⟩        }%
⟨latexrelease⟩      \dp\@tempboxa \z@
⟨latexrelease⟩      \box\@tempboxa
⟨latexrelease⟩      \vskip \headsep
⟨latexrelease⟩      \box\@outputbox
⟨latexrelease⟩      \baselineskip \footskip
⟨latexrelease⟩      \color@hbox
⟨latexrelease⟩        \normalcolor
⟨latexrelease⟩        \hb@xt@\textwidth{\@thefoot}%
⟨latexrelease⟩      \color@endbox
⟨latexrelease⟩      }%
⟨latexrelease⟩    }%
⟨latexrelease⟩  \global\let\if@newlist\@@if@newlist
⟨latexrelease⟩  \global \@colht \textheight
⟨latexrelease⟩  \stepcounter{page}%
⟨latexrelease⟩  \let\firstmark\botmark
⟨latexrelease⟩}
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@outputpage`, `\@shipoutsetup`, *and* `\@writesetup`.)

`\@begindvi` This unboxes stuff that must appear before anything else in the `.dvi` file, then returns that box register to the free list and cancels itself.

The stuff in the box should not add any typeset material to the page.

```
\def \@begindvi{%
  \unvbox \@begindvibox
  \global\let \@begindvi \@empty
}
```

(*End definition for* `\@begindvi`.)

\@combinefloats
\@cflt
\@cflb

The \boxmaxdepth setting here was not made local to a box so was dangerous. It is needed only within the box made by \@cflt (and not normally even there), so it has been moved there; this also agrees with the original pseudocode.

```
\def \@combinefloats {%
%    \boxmaxdepth \maxdepth
    \ifx \@toplist\@empty \else \@cflt \fi
    \ifx \@botlist\@empty \else \@cflb \fi
}
```

```
\def \@cflt{%
    \let \@elt \@comflelt
    \setbox\@tempboxa \vbox{}%
    \@toplist
    \setbox\@outputbox \vbox{%
                              \boxmaxdepth \maxdepth
                              \unvbox\@tempboxa
                              \vskip -\floatsep
                              \topfigrule
                              \vskip \textfloatsep
                              \unvbox\@outputbox
                              }%
    \let\@elt\relax
    \xdef\@freelist{\@freelist\@toplist}%
    \global\let\@toplist\@empty
}
```

```
\def \@cflb {%
    \let\@elt\@comflelt
    \setbox\@tempboxa \vbox{}%
    \@botlist
    \setbox\@outputbox \vbox{%
                              \unvbox\@outputbox
                              \vskip \textfloatsep
                              \botfigrule
                              \unvbox\@tempboxa
                              \vskip -\floatsep
                              }%
    \let\@elt\relax
    \xdef\@freelist{\@freelist\@botlist}%
    \global \let \@botlist\@empty
}
```

(*End definition for* \@combinefloats, \@cflt, *and* \@cflb.)

\@comflelt
\@comdblflelt
\@combinedblfloats

```
\def\@comflelt#1{\setbox\@tempboxa
      \vbox{\unvbox\@tempboxa\box #1\vskip\floatsep}}
```

```
\def\@comdblflelt#1{\setbox\@tempboxa
      \vbox{\unvbox\@tempboxa\box #1\vskip\dblfloatsep}}
```

```
\def \@combinedblfloats{%
  \ifx \@dbltoplist \@empty
  \else
    \setbox\@tempboxa \vbox{}%
    \let \@elt \@comdblflelt
```

```
    \@dbltoplist
    \let \@elt \relax
    \xdef \@freelist {\@freelist\@dbltoplist}%
    \global\let \@dbltoplist \@empty
    \setbox\@outputbox \vbox to\textheight
```

The setting of `\boxmaxdepth` here has no effect since the `\@outputbox` should already have depth zero. Even so, it would have no effect on the layout of the page.

```
      {%\boxmaxdepth\maxdepth   %% probably not needed, CAR
       \unvbox\@tempboxa\vskip-\dblfloatsep
```

Here we need different typesetting if the top float comes from `\@topnewpage`.

```
       \ifnum \@dbltopnum>\m@ne
         \dblfigrule
       \fi
       \vskip \dbltextfloatsep
```

If pdf links are present in the galley and those links get broken across pages they have to end up being on the same level of boxing (even if not actually in the same structure) due to some engine restrictions in pdfTEX and LuaTEX. We therefore unbox `\@outputbox` here (which only contains a single `\hbox`) so that this case has the same boxing level as a normal twocolumn page without top floats.

```
       \unvbox\@outputbox
       }%
  \fi
}
⟨/2ekernel⟩
```

(*End definition for* `\@comflelt`, `\@comdblflelt`, *and* `\@combinedblfloats`.)

`\@startcolumn`
`\@startdblcolumn`

We could combine (most of) these two into `\@startcol <list>`. Note that `\@xstartcol` was only used once (i.e. in `\@startcolumn`); it has therefore been removed. This is not quite as efficient but it now has the same structure as `\@startdblcolumn`.

The empty-list test has been moved to `\@tryfcolumn`.

```
⟨*2ekernel | fltrace⟩
\def \@startcolumn {%
  \global \@colroom \@colht
  \@tryfcolumn \@deferlist
  \if@fcolmade
⟨*trace⟩
    \fl@trace{PAGE: float \if@twocolumn column \else page \fi
                  completed}%
⟨/trace⟩
  \else

    \begingroup
      \let \reserved@b \@deferlist
      \global \let \@deferlist \@empty
      \let \@elt \@scolelt
      \reserved@b
    \endgroup
  \fi
}
```

This one does not need to set `\@colht`.

```
⟨/2ekernel | fltrace⟩
⟨latexrelease | fltrace⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease | fltrace⟩  {\@startdblcolumn}{float order in 2-column}%
⟨*2ekernel | latexrelease | fltrace⟩
\def \@startdblcolumn {%
  \@tryfcolumn \@deferlist
  \if@fcolmade
⟨fltrace⟩    \fl@trace{PAGE: double float page completed}%
  \else
    \begingroup
      \let \reserved@b \@deferlist
      \global \let \@deferlist \@empty
      \let \@elt \@sdblcolelt
      \reserved@b
    \endgroup
  \fi
}%
⟨/2ekernel | latexrelease | fltrace⟩
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨latexrelease | fltrace⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease | fltrace⟩  {\@startdblcolumn}{float order in 2-column}%
⟨latexrelease | fltrace⟩\def \@startdblcolumn {%
```

Not needed since this always comes after `\@outputpage`:

```
⟨latexrelease | fltrace⟩% \global \@colht \textheight
⟨latexrelease | fltrace⟩  \@tryfcolumn \@dbldeferlist
⟨latexrelease | fltrace⟩  \if@fcolmade
⟨*trace⟩
⟨latexrelease | fltrace⟩    \fl@trace{PAGE: double float page completed}%
⟨/trace⟩
⟨latexrelease | fltrace⟩  \else

⟨latexrelease | fltrace⟩    \begingroup
⟨latexrelease | fltrace⟩      \let \reserved@b \@dbldeferlist
⟨latexrelease | fltrace⟩      \global \let \@dbldeferlist \@empty
⟨latexrelease | fltrace⟩      \let \@elt \@sdblcolelt
⟨latexrelease | fltrace⟩      \reserved@b
⟨latexrelease | fltrace⟩    \endgroup
⟨latexrelease | fltrace⟩  \fi
⟨latexrelease | fltrace⟩}%
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨*2ekernel | fltrace⟩
```

(*End definition for* `\@startcolumn` *and* `\@startdblcolumn`.)

`\@tryfcolumn` Now tests if its list is empty before any further exertion.

```
\def \@tryfcolumn #1{%
  \global \@fcolmadefalse
  \ifx #1\@empty
  \else
⟨*trace⟩
      \fl@trace{PAGE: try float \if@twocolumn column/page\else page\fi
                  ---\string #1}%
```

```
      \fl@trace{----- \string #1: #1}%
⟨/trace⟩
    \xdef\@trylist{#1}%
    \global \let \@failedlist \@empty
    \begingroup
      \let \@elt \@xtryfc \@trylist
    \endgroup
    \if@fcolmade
      \@vtryfc #1%
    \fi
  \fi
}
⟨/2ekernel | fltrace⟩
```

(*End definition for* `\@tryfcolumn`.)

```
⟨*2ekernel⟩
```

`\@scolelt`

```
\def\@scolelt#1{\def\@currbox{#1}\@addtonextcol}
```

(*End definition for* `\@scolelt`.)

`\@sdblcolelt`

```
\def\@sdblcolelt#1{\def\@currbox{#1}\@addtodblcol}
```

(*End definition for* `\@sdblcolelt`.)

`\@vtryfc`

```
\def\@vtryfc #1{%
  \global\setbox\@outputbox\vbox{}%
  \let\@elt\@wtryfc
  \@flsucceed
  \global\setbox\@outputbox \vbox to\@colht{%
    \vskip \@fptop
    \vskip -\@fpsep
    \unvbox \@outputbox
    \vskip \@fpbot}%
  \let\@elt\relax
  \xdef #1{\@failedlist\@flfail}%
  \xdef\@freelist{\@freelist\@flsucceed}}
```

(*End definition for* `\@vtryfc`.)

`\@wtryfc`

```
\def\@wtryfc #1{%
  \global\setbox\@outputbox\vbox{%
    \unvbox\@outputbox
    \vskip\@fpsep
    \box #1}}
```

(*End definition for* `\@wtryfc`.)

\@xtryfc

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{\@xtryfc}%
⟨latexrelease⟩                              {float order in 2-column}%
⟨*2ekernel | latexrelease⟩
\def\@xtryfc #1{%
  \@next\reserved@a\@trylist{}{}%
  \@currtype \count #1%
  \divide\@currtype\@xxxii
  \multiply\@currtype\@xxxii
  \@bitor \@currtype \@failedlist
  \@testfp #1%
  \@testwrongwidth #1%
  \ifdim \ht #1>\@colht
     \@testtrue
  \fi
  \if@test
    \@cons\@failedlist #1%
  \else
    \@ytryfc #1%
  \fi}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{\@xtryfc}%
⟨latexrelease⟩                              {float order in 2-column}%
⟨latexrelease⟩\def\@xtryfc #1{%
⟨latexrelease⟩  \@next\reserved@a\@trylist{}{}%
⟨latexrelease⟩  \@currtype \count #1%
⟨latexrelease⟩  \divide\@currtype\@xxxii
⟨latexrelease⟩  \multiply\@currtype\@xxxii
⟨latexrelease⟩  \@bitor \@currtype \@failedlist
⟨latexrelease⟩  \@testfp #1%
⟨latexrelease⟩  \ifdim \ht #1>\@colht
⟨latexrelease⟩    \@testtrue
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \if@test
⟨latexrelease⟩    \@cons\@failedlist #1%
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@ytryfc #1%
⟨latexrelease⟩  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\@xtryfc`.)

\@ytryfc

```
\def\@ytryfc #1{%
  \begingroup
    \gdef\@flsucceed{\@elt #1}%
    \global\let\@flfail\@empty
    \@tempdima\ht #1%
    \let\@elt\@ztryfc
    \@trylist
```

```
    \ifdim \@tempdima >\@fpmin
      \global\@fcolmadetrue
    \else
      \@cons\@failedlist #1%
    \fi
  \endgroup
  \if@fcolmade
    \let\@elt\@gobble
  \fi}
```

(*End definition for* `\@ytryfc`.)

`\@ztryfc`

```
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}{@ztryfc}%
⟨latexrelease⟩                              {float order in 2-column}%
⟨*2ekernel | latexrelease⟩
\def\@ztryfc #1{%
  \@tempcnta\count #1%
  \divide\@tempcnta\@xxxii
  \multiply\@tempcnta\@xxxii
  \@bitor \@tempcnta {\@failedlist \@flfail}%
  \@testfp #1%
```

not in fixfloats?

```
  \@testwrongwidth #1%
  \@tempdimb\@tempdima
  \advance\@tempdimb\ht #1%
  \advance\@tempdimb\@fpsep
  \ifdim \@tempdimb >\@colht
    \@testtrue
  \fi
  \if@test
    \@cons\@flfail #1%
  \else
    \@cons\@flsucceed #1%
    \@tempdima\@tempdimb
  \fi}%
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{@ztryfc}%
⟨latexrelease⟩                              {float order in 2-column}%
⟨latexrelease⟩\def\@ztryfc #1{%
⟨latexrelease⟩  \@tempcnta \count#1%
⟨latexrelease⟩  \divide\@tempcnta\@xxxii
⟨latexrelease⟩  \multiply\@tempcnta\@xxxii
⟨latexrelease⟩  \@bitor \@tempcnta {\@failedlist \@flfail}%
⟨latexrelease⟩  \@testfp #1%
⟨latexrelease⟩  \@tempdimb\@tempdima
⟨latexrelease⟩  \advance\@tempdimb \ht#1%
⟨latexrelease⟩  \advance\@tempdimb\@fpsep
⟨latexrelease⟩  \ifdim \@tempdimb >\@colht
⟨latexrelease⟩    \@testtrue
⟨latexrelease⟩  \fi
```

```
⟨latexrelease⟩  \if@test
⟨latexrelease⟩    \@cons\@flfail #1%
⟨latexrelease⟩  \else
⟨latexrelease⟩    \@cons\@flsucceed #1%
⟨latexrelease⟩    \@tempdima\@tempdimb
⟨latexrelease⟩  \fi}%
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\@ztryfc`.)

The major changes for float suppression and the changes to the float mechanism to make it conform to the documentation are in these next macros.

`\@addtobot` Lots of changes.

```
⟨*2ekernel | fltrace⟩
\def \@addtobot {%
⟨*trace⟩
   \fl@trace{***Start addtobot}%
⟨/trace⟩
   \@getfpsbit 4\relax
⟨*trace⟩
   \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi bot:
                                                        \the \@fpstype}%
⟨/trace⟩
   \ifodd \@tempcnta
     \@flsetnum \@botnum
     \ifnum \@botnum>\z@
       \@tempswafalse
       \@flcheckspace \@botroom \@botlist
       \if@tempswa
```

This next line means that this page is produced with box 255 having depth zero, rather than the normal maxdepth: is this needed, useful?

```
         \global \maxdepth \z@
         \@flupdates \@botnum \@botroom \@botlist
⟨*trace⟩
         \fl@trace{colroom (after-bot) = \the \@colroom}%
         \fl@trace{colnum (after-bot) = \the \@colnum}%
         \fl@trace{botnum (after-bot) = \the \@botnum}%
         \fl@trace{***Success: bot}%
⟨/trace⟩
         \@inserttrue
       \fi
⟨*trace⟩
     \else
       \fl@trace{Fail: botnum = \the \@botnum:
                                 fpstype \the \@fpstype=ORD?}%
       \ifnum \@fpstype<\sixt@@n
         \fl@trace{ERROR: !b float not successful (addtobot)}%
       \fi
⟨/trace⟩
     \fi
   \fi
}
```

(*End definition for* `\@addtobot`.)

\@addtotoporbot Lots of changes.

```
\def \@addtotoporbot {%
⟨*trace⟩
   \fl@trace{***Start addtotoporbot}%
⟨/trace⟩
   \@getfpsbit \tw@
⟨*trace⟩
   \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi top:
                                                        \the \@fpstype}%
⟨/trace⟩
   \ifodd \@tempcnta
     \@flsetnum \@topnum
     \ifnum \@topnum>\z@
       \@tempswafalse
       \@flcheckspace \@toproom \@toplist
       \if@tempswa
         \@bitor\@currtype{\@midlist\@botlist}%
⟨*trace⟩
           \fl@trace{(mid+bot)list: \@midlist, \@botlist:
                              (addtotoporbot-before)}%
⟨/trace⟩
         \if@test
⟨*trace⟩
         \fl@trace{type already on list: mid or bot---sent to addtobot}%
⟨/trace⟩
         \else
          \@flupdates \@topnum \@toproom \@toplist
⟨*trace⟩
          \fl@trace{colroom (after-top) = \the \@colroom}%
          \fl@trace{colnum (after-top) = \the \@colnum}%
          \fl@trace{topnum (after-top) = \the \@topnum}%
          \fl@trace{***Success: top}%
⟨/trace⟩
          \@inserttrue
         \fi
       \fi
⟨*trace⟩
     \else
       \fl@trace{Fail: topnum = \the \@topnum: fpstype
                                          \the \@fpstype=ORD?}%
       \ifnum \@fpstype<\sixt@@n
         \fl@trace{ERROR: !t float not successful (addtotoporbot)}%
       \fi
⟨/trace⟩
     \fi
   \fi
   \if@insert
   \else
⟨*trace⟩
     \fl@trace{sent to addtobot (addtotoporbot)}%
⟨/trace⟩
     \@addtobot
   \fi
}
```

```
⟨/2ekernel | fltrace⟩
```

(*End definition for* `\@addtotoporbot`.)

`\@addtocurcol` Lots of changes.

```
⟨latexrelease | fltrace | flafter⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease | fltrace | flafter⟩  {\@addtocurcol}{float order in 2-column}%
⟨*2ekernel | latexrelease | fltrace | flafter⟩
\def \@addtocurcol {%
⟨*trace⟩
  \fl@trace{***Start addtocurcol}%
⟨/trace⟩
   \@insertfalse
   \@setfloattypecounts
   \ifnum \@fpstype=8
⟨*trace⟩
     \fl@trace{fpstype !p only (addtocurcol): \the \@fpstype = 8?}%
⟨/trace⟩
   \else
     \ifnum \@fpstype=24
⟨*trace⟩
       \fl@trace{fpstype p only (addtocurcol): \the \@fpstype = 24?}%
⟨/trace⟩
     \else
       \@flsettextmin
```

This is a new adjustment which is quite a major change in functionality; but it implements the documentation. Note that `\@reqcolroom` will include the whole of the page-so-far, and hence includes `\@textfloatsheight` of floats, so before comparing it with `\@textmin`, we add this to `\@textmin` also.

```
⟨*trace⟩
       \fl@trace{textfloatsheight (before) = \the \@textfloatsheight}%
⟨/trace⟩
       \advance \@textmin \@textfloatsheight
       \@reqcolroom \@pageht
```

This line must be removed since `\@specialoutput` changed.

```
%       \advance \@reqcolroom \@pagedp
⟨*trace⟩
       \fl@trace{textmin + textfloatsheight: \the \@textmin}%
       \fl@trace{page-so-far: \the \@reqcolroom}%
⟨/trace⟩
       \ifdim \@textmin>\@reqcolroom
         \@reqcolroom \@textmin
⟨*trace⟩
         \fl@trace{ORD? textmin being used}%
⟨/trace⟩
       \fi
       \advance \@reqcolroom \ht\@currbox
⟨*trace⟩
       \fl@trace{float size = \the \ht \@currbox (addtocurcol)}%
       \fl@trace{colroom = \the \@colroom (addtocurcol)}%
       \fl@trace{reqcolroom = \the \@reqcolroom (addtocurcol)}%
⟨/trace⟩
```

```
        \ifdim \@colroom>\@reqcolroom
          \@flsetnum \@colnum
          \ifnum \@colnum>\z@
            \@bitor\@currtype\@deferlist
```

We need to defer the float also if its width doesn't fit.

```
           \@testwrongwidth\@currbox
⟨*trace⟩
            \fl@trace{deferlist: \@deferlist: (addtocurcol-before)}%
⟨/trace⟩
            \if@test
⟨*trace⟩
              \fl@trace{type already on list: defer (addtocurcol)}%
⟨/trace⟩
            \else
              \@bitor\@currtype\@botlist
⟨*trace⟩
            \fl@trace{botlist: \@botlist: (addtocurcol-before)}%
⟨/trace⟩
              \if@test
⟨*trace⟩
                \fl@trace{type already on list: bot---sent to addtobot}%
⟨/trace⟩
                \@addtobot
              \else
⟨*trace⟩
                \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi
                       here: \the \@fpstype}%
⟨/trace⟩
                \ifodd \count\@currbox
                  \advance \@reqcolroom \intextsep
                  \ifdim \@colroom>\@reqcolroom
                    \global \advance \@colnum \m@ne
                    \global \advance \@textfloatsheight \ht\@currbox
```

This may sometimes give an overestimate.

```
                    \global \advance \@textfloatsheight 2\intextsep
                    \@cons \@midlist \@currbox
⟨*trace⟩
                  \fl@trace{***Success: here}%
                  \fl@trace{textfloatsheight (after-here) =
                       \the \@textfloatsheight}%
                  \fl@trace{colnum (after-here) = \the \@colnum}%
⟨/trace⟩
```

CHANGE TO `\@addtocurcol`:

`\penalty\z@` changed to `\penalty\interlinepenalty` so `\samepage` works properly with figure and table environments. (Changed 23 Oct 86)

There is also an `\addpenalty\interlinepenalty` above.

Since in 2e `\samepage` is no longer supported, these could be removed.

Although it is best to use `\addvspace` in case two h floats come together, this makes other spacing more difficult to adjust; whereas if a user specifies two h floats together then they can more easily get the spacing correct by ad hoc commands.

It is necessary to adjust for the addition of `\parskip` here in case the float is added between paragraphs (i.e. when in vertical mode).

If the nobreak switch is true we need to reset it and clear `\everypar` since the float may not reset the flag and cannot reset the `\everypar` globally.

Typesetting starts here (we are in vertical mode).

```
                    \if@nobreak
                      \nobreak
                      \@nobreakfalse
                      \everypar{}%
                    \else
                      \addpenalty \interlinepenalty
                    \fi
                    \vskip \intextsep
                    \box\@currbox
                    \penalty\interlinepenalty
                    \vskip\intextsep
                    \ifnum\outputpenalty <-\@Mii \vskip -\parskip\fi
```

Typesetting ends here.

```
                    \outputpenalty \z@
                    \@inserttrue
⟨*trace⟩
                  \else
                    \fl@trace{Fail---no room at 2nd test of colroom
                                  (addtocorcol \string\intextsep)}%
⟨/trace⟩
                  \fi
                \fi
                \if@insert
                \else
```

Next set of docstrip guards are a bit weird, essentially `\@addtotoporbot` ends up inside the kernel and the `fltrace` package and `\@addtobot` shows up in the `flafter` package. Guess that could have been done a bit more obvious :-)

```
⟨*2ekernel | fltrace | latexrelease⟩
⟨*trace⟩
                  \fl@trace{not here: sent to addtotoporbot}%
⟨/trace⟩
                  \@addtotoporbot
⟨/2ekernel | fltrace | latexrelease⟩
⟨*!2ekernel&!fltrace&!latexrelease⟩
⟨*trace⟩
                  \fl@trace{not here: sent to addtobot}%
⟨/trace⟩
                  \@addtobot
⟨/!2ekernel&!fltrace&!latexrelease⟩
                \fi
              \fi
            \fi
⟨*trace⟩
          \else
            \fl@trace{Fail: colnum = \the \@colnum:
                          fpstype \the \@fpstype=ORD?}%
            \ifnum \@fpstype<\sixt@@n
```

```
            \fl@trace{ERROR: BANG float not successful (addtocurcol)}%
          \fi
⟨/trace⟩
        \fi
⟨*trace⟩
      \else
        \fl@trace{Fail---no room: fl box ht: \the \ht \@currbox
                                                  (addtocurcol)}%
⟨/trace⟩
      \fi
    \fi
  \fi
  \if@insert
  \else
    \@resethfps
⟨*trace⟩
    \fl@trace{put on deferlist (addtocurcol)}%
⟨/trace⟩
    \@cons\@deferlist\@currbox
⟨*trace⟩
    \fl@trace{deferlist: \@deferlist: (addtocurcol-after)}%
⟨/trace⟩
  \fi
}%
⟨/2ekernel | latexrelease | fltrace | flafter⟩
⟨latexrelease | fltrace | flafter⟩\EndIncludeInRelease
⟨latexrelease | fltrace | flafter⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease | fltrace | flafter⟩  {\@addtocurcol}{float order in 2-column}%
⟨latexrelease | fltrace | flafter⟩\def \@addtocurcol {%
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩  \fl@trace{***Start addtocurcol}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩   \@insertfalse
⟨latexrelease | fltrace | flafter⟩   \@setfloattypecounts
⟨latexrelease | fltrace | flafter⟩   \ifnum \@fpstype=8
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩     \fl@trace{fpstype !p only (addtocurcol):
⟨latexrelease | fltrace | flafter⟩                            \the \@fpstype = 8?}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩   \else
⟨latexrelease | fltrace | flafter⟩     \ifnum \@fpstype=24
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩      \fl@trace{fpstype p only (addtocurcol):
⟨latexrelease | fltrace | flafter⟩                           \the \@fpstype = 24?}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩     \else
⟨latexrelease | fltrace | flafter⟩       \@flsettextmin
```

This is a new adjustment which is quite a major change in functionality; but it implements the documentation. Note that `\@reqcolroom` will include the whole of the page-so-far, and hence includes `\@textfloatsheight` of floats, so before comparing it with `\@textmin`, we add this to `\@textmin` also.

```
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩       \fl@trace{textfloatsheight (before) =
```

```
⟨latexrelease | fltrace | flafter⟩                        \the \@textfloatsheight}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩        \advance \@textmin \@textfloatsheight
⟨latexrelease | fltrace | flafter⟩        \@reqcolroom \@pageht
```

This line must be removed since `\@specialoutput` changed.

```
%        \advance \@reqcolroom \@pagedp
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩        \fl@trace{textmin + textfloatsheight:
⟨latexrelease | fltrace | flafter⟩                                \the \@textmin}%
⟨latexrelease | fltrace | flafter⟩        \fl@trace{page-so-far: \the \@reqcolroom}%
⟨latexrelease | fltrace | flafter⟩
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩        \ifdim \@textmin>\@reqcolroom
⟨latexrelease | fltrace | flafter⟩          \@reqcolroom \@textmin
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩          \fl@trace{ORD? textmin being used}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩        \fi
⟨latexrelease | fltrace | flafter⟩        \advance \@reqcolroom \ht\@currbox
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩        \fl@trace{float size =
⟨latexrelease | fltrace | flafter⟩                \the \ht \@currbox (addtocurcol)}%
⟨latexrelease | fltrace | flafter⟩        \fl@trace{colroom =
⟨latexrelease | fltrace | flafter⟩                    \the \@colroom (addtocurcol)}%
⟨latexrelease | fltrace | flafter⟩        \fl@trace{reqcolroom =
⟨latexrelease | fltrace | flafter⟩                 \the \@reqcolroom (addtocurcol)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩        \ifdim \@colroom>\@reqcolroom
⟨latexrelease | fltrace | flafter⟩          \@flsetnum \@colnum
⟨latexrelease | fltrace | flafter⟩          \ifnum \@colnum>\z@
⟨latexrelease | fltrace | flafter⟩            \@bitor\@currtype\@deferlist
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩            \fl@trace{deferlist:
⟨latexrelease | fltrace | flafter⟩               \@deferlist: (addtocurcol-before)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩            \if@test
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩              \fl@trace{type already on list:
⟨latexrelease | fltrace | flafter⟩                              defer (addtocurcol)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩            \else
⟨latexrelease | fltrace | flafter⟩              \@bitor\@currtype\@botlist
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩            \fl@trace{botlist: \@botlist:
⟨latexrelease | fltrace | flafter⟩                              (addtocurcol-before)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩              \if@test
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩                \fl@trace{type already on list:
⟨latexrelease | fltrace | flafter⟩                          bot---sent to addtobot}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩                \@addtobot
⟨latexrelease | fltrace | flafter⟩              \else
⟨*trace⟩
```

```
⟨latexrelease | fltrace | flafter⟩ \fl@trace{fpstype
⟨latexrelease | fltrace | flafter⟩ \ifodd \@tempcnta OK \else not \fi
⟨latexrelease | fltrace | flafter⟩ here: \the \@fpstype}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩ \ifodd \count\@currbox
⟨latexrelease | fltrace | flafter⟩   \advance \@reqcolroom \intextsep
⟨latexrelease | fltrace | flafter⟩   \ifdim \@colroom>\@reqcolroom
⟨latexrelease | fltrace | flafter⟩    \global \advance \@colnum \m@ne
⟨latexrelease | fltrace | flafter⟩    \global \advance
⟨latexrelease | fltrace | flafter⟩     \@textfloatsheight\ht\@currbox
```

This may sometimes give an overestimate.

```
⟨latexrelease | fltrace | flafter⟩    \global \advance
⟨latexrelease | fltrace | flafter⟩     \@textfloatsheight 2\intextsep
⟨latexrelease | fltrace | flafter⟩     \@cons \@midlist \@currbox
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩   \fl@trace{***Success: here}%
⟨latexrelease | fltrace | flafter⟩   \fl@trace{textfloatsheight
⟨latexrelease | fltrace | flafter⟩        (after-here) =
⟨latexrelease | fltrace | flafter⟩        \the \@textfloatsheight}%
⟨latexrelease | fltrace | flafter⟩   \fl@trace{colnum (after-here) =
⟨latexrelease | fltrace | flafter⟩            \the \@colnum}%
⟨/trace⟩
```

CHANGE TO `\@addtocurcol`:

`\penalty\z@` changed to `\penalty\interlinepenalty` so `\samepage` works properly with figure and table environments. (Changed 23 Oct 86)

There is also an `\addpenalty\interlinepenalty` above.

Since in 2e `\samepage` is no longer supported, these could be removed.

Although it is best to use `\addvspace` in case two h floats come together, this makes other spacing more difficult to adjust; whereas if a user specifies two h floats together then they can more easily get the spacing correct by ad hoc commands.

It is necessary to adjust for the addition of `\parskip` here in case the float is added between paragraphs (i.e. when in vertical mode).

If the nobreak switch is true we need to reset it and clear `\everypar` since the float may not reset the flag and cannot reset the `\everypar` globally.

Typesetting starts here (we are in vertical mode).

```
⟨latexrelease | fltrace | flafter⟩   \if@nobreak
⟨latexrelease | fltrace | flafter⟩     \nobreak
⟨latexrelease | fltrace | flafter⟩     \@nobreakfalse
⟨latexrelease | fltrace | flafter⟩     \everypar{}%
⟨latexrelease | fltrace | flafter⟩   \else
⟨latexrelease | fltrace | flafter⟩     \addpenalty\interlinepenalty
⟨latexrelease | fltrace | flafter⟩   \fi
⟨latexrelease | fltrace | flafter⟩   \vskip \intextsep
⟨latexrelease | fltrace | flafter⟩   \box\@currbox
⟨latexrelease | fltrace | flafter⟩   \penalty\interlinepenalty
⟨latexrelease | fltrace | flafter⟩   \vskip\intextsep
⟨latexrelease | fltrace | flafter⟩   \ifnum\outputpenalty
⟨latexrelease | fltrace | flafter⟩               <-\@Mii \vskip
⟨latexrelease | fltrace | flafter⟩        -\parskip\fi
```

Typesetting ends here.

```
⟨latexrelease | fltrace | flafter⟩   \outputpenalty \z@
```

```
⟨latexrelease | fltrace | flafter⟩                    \@inserttrue
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩                  \else
⟨latexrelease | fltrace | flafter⟩  \fl@trace{Fail---no room at 2nd test of colroom
⟨latexrelease | fltrace | flafter⟩                 (addtocorcol \string\intextsep)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩                  \fi
⟨latexrelease | fltrace | flafter⟩                \fi
⟨latexrelease | fltrace | flafter⟩                \if@insert
⟨latexrelease | fltrace | flafter⟩                \else
```

Next set of docstrip guards are a bit weird, essentially `\@addtotoporbot` ends up inside the kernel and the `fltrace` package and `\@addtotoporbot` shows up in the `flafter` package. Guess that could have been done a bit more obvious :-)

```
⟨*2ekernel | fltrace⟩
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩       \fl@trace{not here: sent to addtotoporbot}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩                  \@addtotoporbot
⟨/2ekernel | fltrace⟩
⟨*!2ekernel&!autoload&!fltrace⟩
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩        \fl@trace{not here: sent to addtobot}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩                  \@addtobot
⟨/!2ekernel&!autoload&!fltrace⟩
⟨latexrelease | fltrace | flafter⟩                \fi
⟨latexrelease | fltrace | flafter⟩              \fi
⟨latexrelease | fltrace | flafter⟩            \fi
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩          \else
⟨latexrelease | fltrace | flafter⟩          \fl@trace{Fail: colnum = \the \@colnum:
⟨latexrelease | fltrace | flafter⟩                    fpstype \the \@fpstype=ORD?}%
⟨latexrelease | fltrace | flafter⟩          \ifnum \@fpstype<\sixt@@n
⟨latexrelease | fltrace | flafter⟩  \fl@trace{ERROR: BANG float not successful
⟨latexrelease | fltrace | flafter⟩                                  (addtocurcol)}%
⟨latexrelease | fltrace | flafter⟩            \fi
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩          \fi
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩        \else
⟨latexrelease | fltrace | flafter⟩          \fl@trace{Fail---no room: fl box ht:
⟨latexrelease | fltrace | flafter⟩                \the \ht \@currbox (addtocurcol)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩        \fi
⟨latexrelease | fltrace | flafter⟩      \fi
⟨latexrelease | fltrace | flafter⟩    \fi
⟨latexrelease | fltrace | flafter⟩    \if@insert
⟨latexrelease | fltrace | flafter⟩    \else
⟨latexrelease | fltrace | flafter⟩      \@resethfps
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩      \fl@trace{put on deferlist (addtocurcol)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩      \@cons\@deferlist\@currbox
```

```
⟨*trace⟩
⟨latexrelease | fltrace | flafter⟩      \fl@trace{deferlist: \@deferlist:
⟨latexrelease | fltrace | flafter⟩                            (addtocurcol-after)}%
⟨/trace⟩
⟨latexrelease | fltrace | flafter⟩    \fi
⟨latexrelease | fltrace | flafter⟩   }%
⟨latexrelease | fltrace | flafter⟩\EndIncludeInRelease
```

(*End definition for* `\@addtocurcol`.)

`\@addtonextcol` Lots of changes.

```
⟨latexrelease | fltrace⟩\IncludeInRelease{2015/01/01}
⟨latexrelease | fltrace⟩   {\@addtonextcol}{float order in 2-column}%
⟨*2ekernel | latexrelease | fltrace⟩
\def\@addtonextcol{%
  \begingroup
⟨*trace⟩
   \fl@trace{***Start addtonextcol}%
⟨/trace⟩
   \@insertfalse
   \@setfloattypecounts
   \ifnum \@fpstype=8
⟨*trace⟩
      \fl@trace{fpstype not curcol: \the \@fpstype = 8?}%
⟨/trace⟩
   \else
      \ifnum \@fpstype=24
⟨*trace⟩
         \fl@trace{fpstype not curcol: \the \@fpstype = 24?}%
⟨/trace⟩
      \else
         \@flsettextmin
⟨*trace⟩
         \fl@trace{text-so-far: 0pt (top of col)}%
⟨/trace⟩
         \@reqcolroom \ht\@currbox
⟨*trace⟩
         \fl@trace{float size: \the \@reqcolroom (addtonextcol)}%
⟨/trace⟩
         \advance \@reqcolroom \@textmin
⟨*trace⟩
         \fl@trace{colroom = \the \@colroom (addtonextcol)}%
         \fl@trace{reqcolroom = \the \@reqcolroom (addtonextcol)}%
⟨/trace⟩
         \ifdim \@colroom>\@reqcolroom
           \@flsetnum \@colnum
           \ifnum\@colnum>\z@
              \@bitor\@currtype\@deferlist
⟨*trace⟩
              \fl@trace{deferlist: \@deferlist: (addtonextcol-before)}%
⟨/trace⟩
              \@testwrongwidth\@currbox
              \if@test
```

```
⟨*trace⟩
                \fl@trace{type already on list: defer (addtonextcol)}%
⟨/trace⟩
              \else
⟨*trace⟩
                \fl@trace{sent to addtotoporbot (addtonextcol)}%
⟨/trace⟩
                \@addtotoporbot
              \fi
           \fi
⟨*trace⟩
         \else
           \fl@trace{Fail---no room: fl box ht: \the \ht \@currbox
                                                   (addtonextcol)}%
⟨/trace⟩
         \fi
       \fi
    \fi
    \if@insert
    \else
⟨*trace⟩
       \fl@trace{put back on deferlist (addtonextcol)}%
⟨/trace⟩
       \@cons\@deferlist\@currbox
⟨*trace⟩
       \fl@trace{deferlist: \@deferlist: (addtonextcol-after)}%
⟨/trace⟩
    \fi
⟨*trace⟩
   \fl@trace{End of addtonextcol -- locally counts:}%
   \fl@trace{col: \the\@colnum. top: \the \@topnum. bot: \the \@botnum.}%
⟨/trace⟩
   \endgroup
⟨*trace⟩
  \fl@trace{End of addtonextcol -- globally counts:}%
  \fl@trace{col: \the\@colnum. top: \the \@topnum. bot: \the \@botnum.}%
⟨/trace⟩
}%
⟨/2ekernel | latexrelease | fltrace⟩
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨latexrelease | fltrace⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease | fltrace⟩  {\@addtonextcol}{float order in 2-column}%
⟨latexrelease | fltrace⟩\def\@addtonextcol{%
⟨latexrelease | fltrace⟩   \begingroup
⟨*trace⟩
⟨latexrelease | fltrace⟩    \fl@trace{***Start addtonextcol}%
⟨/trace⟩
⟨latexrelease | fltrace⟩    \@insertfalse
⟨latexrelease | fltrace⟩    \@setfloattypecounts
⟨latexrelease | fltrace⟩    \ifnum \@fpstype=8
⟨*trace⟩
⟨latexrelease | fltrace⟩      \fl@trace{fpstype not curcol:
⟨latexrelease | fltrace⟩                      \the \@fpstype = 8?}%
⟨/trace⟩
```

```
⟨latexrelease | fltrace⟩    \else
⟨latexrelease | fltrace⟩      \ifnum \@fpstype=24
⟨*trace⟩
⟨latexrelease | fltrace⟩        \fl@trace{fpstype not curcol:
⟨latexrelease | fltrace⟩                        \the \@fpstype = 24?}%
⟨/trace⟩
⟨latexrelease | fltrace⟩      \else
⟨latexrelease | fltrace⟩        \@flsettextmin
⟨*trace⟩
⟨latexrelease | fltrace⟩        \fl@trace{text-so-far: 0pt (top of col)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩        \@reqcolroom \ht\@currbox
⟨*trace⟩
⟨latexrelease | fltrace⟩        \fl@trace{float size:
⟨latexrelease | fltrace⟩                \the \@reqcolroom (addtonextcol)}%
⟨latexrelease | fltrace⟩
⟨/trace⟩
⟨latexrelease | fltrace⟩        \advance \@reqcolroom \@textmin
⟨*trace⟩
⟨latexrelease | fltrace⟩        \fl@trace{colroom =
⟨latexrelease | fltrace⟩                  \the \@colroom (addtonextcol)}%
⟨latexrelease | fltrace⟩        \fl@trace{reqcolroom =
⟨latexrelease | fltrace⟩                \the \@reqcolroom (addtonextcol)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩        \ifdim \@colroom>\@reqcolroom
⟨latexrelease | fltrace⟩          \@flsetnum \@colnum
⟨latexrelease | fltrace⟩          \ifnum\@colnum>\z@
⟨latexrelease | fltrace⟩             \@bitor\@currtype\@deferlist
⟨*trace⟩
⟨latexrelease | fltrace⟩             \fl@trace{deferlist: \@deferlist:
⟨latexrelease | fltrace⟩                          (addtonextcol-before)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩             \if@test
⟨*trace⟩
⟨latexrelease | fltrace⟩               \fl@trace{type already on list:
⟨latexrelease | fltrace⟩                            defer (addtonextcol)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩             \else
⟨*trace⟩
⟨latexrelease | fltrace⟩               \fl@trace{sent to addtotoporbot
⟨latexrelease | fltrace⟩                                  (addtonextcol)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩               \@addtotoporbot
⟨latexrelease | fltrace⟩             \fi
⟨latexrelease | fltrace⟩          \fi
⟨*trace⟩
⟨latexrelease | fltrace⟩        \else
⟨latexrelease | fltrace⟩          \fl@trace{Fail---no room: fl box ht:
⟨latexrelease | fltrace⟩               \the \ht \@currbox (addtonextcol)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩        \fi
⟨latexrelease | fltrace⟩      \fi
⟨latexrelease | fltrace⟩    \fi
⟨latexrelease | fltrace⟩    \if@insert
```

```
⟨latexrelease | fltrace⟩    \else
⟨*trace⟩
⟨latexrelease | fltrace⟩      \fl@trace{put back on deferlist
⟨latexrelease | fltrace⟩                                (addtonextcol)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩      \@cons\@deferlist\@currbox
⟨*trace⟩
⟨latexrelease | fltrace⟩      \fl@trace{deferlist: \@deferlist:
⟨latexrelease | fltrace⟩                          (addtonextcol-after)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩    \fi
⟨*trace⟩
⟨latexrelease | fltrace⟩    \fl@trace{End of addtonextcol --
⟨latexrelease | fltrace⟩                            locally counts:}%
⟨latexrelease | fltrace⟩    \fl@trace{col: \the \@colnum.
⟨latexrelease | fltrace⟩       top: \the \@topnum. bot: \the \@botnum.}%
⟨/trace⟩
⟨latexrelease | fltrace⟩   \endgroup
⟨*trace⟩
⟨latexrelease | fltrace⟩   \fl@trace{End of addtonextcol --
⟨latexrelease | fltrace⟩                          globally counts:}%
⟨latexrelease | fltrace⟩   \fl@trace{col: \the \@colnum.
⟨latexrelease | fltrace⟩        top: \the \@topnum. bot: \the \@botnum.}%
⟨/trace⟩
⟨latexrelease | fltrace⟩}%
⟨latexrelease | fltrace⟩\EndIncludeInRelease
```

(*End definition for* `\@addtonextcol`.)

`\@addtodblcol` Lots of changes.

```
⟨latexrelease | fltrace⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease | fltrace⟩   {\@addtodblcol}{float order in 2-column}%
⟨*2ekernel | latexrelease | fltrace⟩
\def\@addtodblcol{%
  \begingroup
⟨*trace⟩
  \fl@trace{***Start addtodblcol}%
⟨/trace⟩
   \@insertfalse
   \@setfloattypecounts
   \@getfpsbit \tw@
⟨*trace⟩
   \fl@trace{fpstype \ifodd \@tempcnta OK \else not \fi dbltop:
                                                        \the \@fpstype}%
⟨/trace⟩
   \ifodd\@tempcnta
     \@flsetnum \@dbltopnum
     \ifnum \@dbltopnum>\z@
       \@tempswafalse
       \ifdim \@dbltoproom>\ht\@currbox
         \@tempswatrue
⟨*trace⟩
         \fl@trace{Space OK: \@dbltoproom =
                \the \@dbltoproom > \the \ht \@currbox
```

```
                                        (dbltoproom)}%
⟨/trace⟩
        \else
⟨*trace⟩
          \fl@trace{fpstype: \the \@fpstype (addtodblcol)}%
⟨/trace⟩
          \ifnum \@fpstype<\sixt@@n
⟨*trace⟩
            \fl@trace{BANG float ignoring \@dbltoproom}%
            \fl@trace{\@spaces \@dbltoproom = \the \@dbltoproom.
                            Ht float: \the \ht \@currbox-BANG}%
⟨/trace⟩
```

Need to check that there is room on the page, using the local value of `\@textmin` to make the necessary adjustment to `\@dbltoproom`.

```
            \advance \@dbltoproom \@textmin
⟨*trace⟩
            \fl@trace{Local value of texmin: \the\@textmin}%
            \fl@trace{\@spaces space on page = \the \@dbltoproom.
                            Ht float: \the \ht \@currbox-BANG}%
⟨/trace⟩
            \ifdim \@dbltoproom>\ht\@currbox
              \@tempswatrue
⟨*trace⟩
              \fl@trace{Space OK BANG: space on page =
                          \the \@dbltoproom > \the \ht \@currbox}%
            \else
              \fl@trace{fpstype: \the \@fpstype}%
              \fl@trace{Fail---no room dbltoproom-BANG?:}%
              \fl@trace{\@spaces space on page = \the \@dbltoproom.
                            Ht float: \the \ht \@currbox}%
⟨/trace⟩
            \fi
            \advance \@dbltoproom -\@textmin
⟨*trace⟩
          \else
            \fl@trace{fpstype: \the \@fpstype}%
            \fl@trace{Fail---no room dbltoproom-ORD?:}%
            \fl@trace{\@spaces \@dbltoproom = \the \@dbltoproom.
                            Ht float: \the \ht \@currbox}%
⟨/trace⟩
          \fi
        \fi
        \if@tempswa
            \@bitor \@currtype \@deferlist
⟨*trace⟩
            \fl@trace{(dbl)deferlist: \@deferlist: (before)}%
⟨/trace⟩
```

not in fixfloats?

```
          \@testwrongwidth\@currbox
            \if@test
⟨*trace⟩
              \fl@trace{type already on list: (dbl)defer}%
```

```
⟨/trace⟩
            \else
               \@tempdima -\ht\@currbox
               \advance\@tempdima
                 -\ifx \@dbltoplist\@empty \dbltextfloatsep \else
                                           \dblfloatsep \fi
               \global \advance \@dbltoproom \@tempdima
               \global \advance \@colht \@tempdima
               \global \advance \@dbltopnum \m@ne
               \@cons \@dbltoplist \@currbox
⟨*trace⟩
               \fl@trace{dbltopnum (after) = \the \@dbltopnum}%
               \fl@trace{***Success: dbltop}%
⟨/trace⟩
               \@inserttrue
            \fi
        \fi
⟨*trace⟩
      \else
        \fl@trace{Fail: dbltopnum = \the \@dbltopnum: fpstype
                                                 \the \@fpstype=ORD?}%
        \ifnum \@fpstype<\sixt@@n
          \fl@trace{ERROR: !t float not successful (addtodblcol)}%
        \fi
⟨/trace⟩
      \fi
   \fi
   \if@insert
   \else
⟨*trace⟩
      \fl@trace{put on deferlist}%
⟨/trace⟩
      \@cons\@deferlist\@currbox
⟨*trace⟩
      \fl@trace{(dbl)deferlist: \@deferlist: (after)}%
⟨/trace⟩
   \fi
⟨*trace⟩
   \fl@trace{End of addtodblcol -- locally count:}%
   \fl@trace{ dbltop: \the \@dbltopnum.}%
⟨/trace⟩
  \endgroup
⟨*trace⟩
  \fl@trace{End of addtodblcol -- globally count:}%
  \fl@trace{dbltop: \the \@dbltopnum.}%
⟨/trace⟩
}%
⟨/2ekernel | latexrelease | fltrace⟩
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨latexrelease | fltrace⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease | fltrace⟩  {\@addtodblcol}{float order in 2-column}%
⟨latexrelease | fltrace⟩\def\@addtodblcol{%
⟨latexrelease | fltrace⟩  \begingroup
⟨*trace⟩
```

```
⟨latexrelease | fltrace⟩  \fl@trace{***Start addtodblcol}%
⟨/trace⟩
⟨latexrelease | fltrace⟩   \@insertfalse
⟨latexrelease | fltrace⟩   \@setfloattypecounts
⟨latexrelease | fltrace⟩   \@getfpsbit \tw@
⟨*trace⟩
⟨latexrelease | fltrace⟩   \fl@trace{fpstype \ifodd \@tempcnta OK
⟨latexrelease | fltrace⟩                \else not \fi dbltop: \the \@fpstype}%
⟨/trace⟩
⟨latexrelease | fltrace⟩   \ifodd\@tempcnta
⟨latexrelease | fltrace⟩     \@flsetnum \@dbltopnum
⟨latexrelease | fltrace⟩     \ifnum \@dbltopnum>\z@
⟨latexrelease | fltrace⟩       \@tempswafalse
⟨latexrelease | fltrace⟩       \ifdim \@dbltoproom>\ht\@currbox
⟨latexrelease | fltrace⟩         \@tempswatrue
⟨*trace⟩
⟨latexrelease | fltrace⟩         \fl@trace{Space OK: \@dbltoproom =
⟨latexrelease | fltrace⟩                \the \@dbltoproom > \the \ht \@currbox
⟨latexrelease | fltrace⟩                                        (dbltoproom)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩       \else
⟨*trace⟩
⟨latexrelease | fltrace⟩      \fl@trace{fpstype: \the \@fpstype (addtodblcol)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩         \ifnum \@fpstype<\sixt@@n
⟨*trace⟩
⟨latexrelease | fltrace⟩           \fl@trace{BANG float ignoring \@dbltoproom}%
⟨latexrelease | fltrace⟩           \fl@trace{\@spaces \@dbltoproom =
⟨latexrelease | fltrace⟩                    \the \@dbltoproom.
⟨latexrelease | fltrace⟩                    Ht float: \the \ht \@currbox-BANG}%
⟨/trace⟩
```

Need to check that there is room on the page, using the local value of `\@textmin` to make the necessary adjustment to `\@dbltoproom`.

```
⟨latexrelease | fltrace⟩           \advance \@dbltoproom \@textmin
⟨*trace⟩
⟨latexrelease | fltrace⟩       \fl@trace{Local value of texmin: \the\@textmin}%
⟨latexrelease | fltrace⟩       \fl@trace{\@spaces space on page =
⟨latexrelease | fltrace⟩                   \the \@dbltoproom.
⟨latexrelease | fltrace⟩                    Ht float: \the \ht \@currbox-BANG}%
⟨/trace⟩
⟨latexrelease | fltrace⟩           \ifdim \@dbltoproom>\ht\@currbox
⟨latexrelease | fltrace⟩             \@tempswatrue
⟨*trace⟩
⟨latexrelease | fltrace⟩         \fl@trace{Space OK BANG: space on page =
⟨latexrelease | fltrace⟩                \the\@dbltoproom > \the\ht\@currbox}%
⟨latexrelease | fltrace⟩           \else
⟨latexrelease | fltrace⟩         \fl@trace{fpstype: \the \@fpstype}%
⟨latexrelease | fltrace⟩         \fl@trace{Fail---no room dbltoproom-BANG?:}%
⟨latexrelease | fltrace⟩         \fl@trace{\@spaces space on page =
⟨latexrelease | fltrace⟩                     \the \@dbltoproom.
⟨latexrelease | fltrace⟩                      Ht float: \the \ht \@currbox}%
⟨/trace⟩
⟨latexrelease | fltrace⟩           \fi
```

```
⟨latexrelease | fltrace⟩            \advance \@dbltoproom -\@textmin
⟨*trace⟩
⟨latexrelease | fltrace⟩          \else
⟨latexrelease | fltrace⟩            \fl@trace{fpstype: \the \@fpstype}%
⟨latexrelease | fltrace⟩            \fl@trace{Fail---no room dbltoproom-ORD?:}%
⟨latexrelease | fltrace⟩            \fl@trace{\@spaces \@dbltoproom =
⟨latexrelease | fltrace⟩               \the \@dbltoproom.
⟨latexrelease | fltrace⟩               Ht float: \the \ht \@currbox}%
⟨/trace⟩
⟨latexrelease | fltrace⟩          \fi
⟨latexrelease | fltrace⟩        \fi
⟨latexrelease | fltrace⟩        \if@tempswa
⟨latexrelease | fltrace⟩            \@bitor \@currtype \@dbldeferlist
⟨*trace⟩
⟨latexrelease | fltrace⟩            \fl@trace{dbldeferlist:
⟨latexrelease | fltrace⟩                      \@dbldeferlist: (before)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩            \if@test
⟨*trace⟩
⟨latexrelease | fltrace⟩              \fl@trace{type already on list: dbldefer}%
⟨/trace⟩
⟨latexrelease | fltrace⟩            \else
⟨latexrelease | fltrace⟩               \@tempdima -\ht\@currbox
⟨latexrelease | fltrace⟩               \advance\@tempdima
⟨latexrelease | fltrace⟩                 -\ifx \@dbltoplist\@empty
⟨latexrelease | fltrace⟩                       \dbltextfloatsep
⟨latexrelease | fltrace⟩                  \else \dblfloatsep \fi
⟨latexrelease | fltrace⟩               \global \advance \@dbltoproom \@tempdima
⟨latexrelease | fltrace⟩               \global \advance \@colht \@tempdima
⟨latexrelease | fltrace⟩               \global \advance \@dbltopnum \m@ne
⟨latexrelease | fltrace⟩               \@cons \@dbltoplist \@currbox
⟨*trace⟩
⟨latexrelease | fltrace⟩               \fl@trace{dbltopnum (after) =
⟨latexrelease | fltrace⟩                                  \the \@dbltopnum}%
⟨latexrelease | fltrace⟩               \fl@trace{***Success: dbltop}%
⟨/trace⟩
⟨latexrelease | fltrace⟩               \@inserttrue
⟨latexrelease | fltrace⟩            \fi
⟨latexrelease | fltrace⟩        \fi
⟨*trace⟩
⟨latexrelease | fltrace⟩      \else
⟨latexrelease | fltrace⟩        \fl@trace{Fail: dbltopnum = \the \@dbltopnum:
⟨latexrelease | fltrace⟩                          fpstype \the \@fpstype=ORD?}%
⟨latexrelease | fltrace⟩        \ifnum \@fpstype<\sixt@@n
⟨latexrelease | fltrace⟩          \fl@trace{ERROR: !t float not successful
⟨latexrelease | fltrace⟩                                        (addtodblcol)}%
⟨latexrelease | fltrace⟩        \fi
⟨/trace⟩
⟨latexrelease | fltrace⟩      \fi
⟨latexrelease | fltrace⟩    \fi
⟨latexrelease | fltrace⟩    \if@insert
⟨latexrelease | fltrace⟩    \else
⟨*trace⟩
⟨latexrelease | fltrace⟩      \fl@trace{put on dbldeferlist}%
```

```
⟨/trace⟩
⟨latexrelease | fltrace⟩      \@cons\@dbldeferlist\@currbox
⟨*trace⟩
⟨latexrelease | fltrace⟩      \fl@trace{dbldeferlist: \@dbldeferlist: (after)}%
⟨/trace⟩
⟨latexrelease | fltrace⟩    \fi
⟨*trace⟩
⟨latexrelease | fltrace⟩    \fl@trace{End of addtodblcol -- locally count:}%
⟨latexrelease | fltrace⟩    \fl@trace{ dbltop: \the \@dbltopnum.}%
⟨/trace⟩
⟨latexrelease | fltrace⟩   \endgroup
⟨*trace⟩
⟨latexrelease | fltrace⟩   \fl@trace{End of addtodblcol -- globally count:}%
⟨latexrelease | fltrace⟩   \fl@trace{dbltop: \the \@dbltopnum.}%
⟨/trace⟩
⟨latexrelease | fltrace⟩}%
⟨latexrelease | fltrace⟩\EndIncludeInRelease
```

(*End definition for* `\@addtodblcol`.)

`\@addmarginpar`

```
⟨*2ekernel⟩
\def\@addmarginpar{\@next\@marbox\@currlist{\@cons\@freelist\@marbox
    \@cons\@freelist\@currbox}\@latexbug\@tempcnta\@ne
    \if@twocolumn
        \if@firstcolumn \@tempcnta\m@ne \fi
    \else
      \if@mparswitch
         \ifodd\c@page \else\@tempcnta\m@ne \fi
      \fi
      \if@reversemargin \@tempcnta -\@tempcnta \fi
    \fi
    \ifnum\@tempcnta <\z@  \global\setbox\@marbox\box\@currbox \fi
    \@tempdima\@mparbottom
    \advance\@tempdima -\@pageht
    \advance\@tempdima\ht\@marbox
    \ifdim\@tempdima >\z@
      \@latex@warning@no@line {Marginpar on page \thepage\space moved}%
    \else
      \@tempdima\z@
    \fi
    \global\@mparbottom\@pageht
    \global\advance\@mparbottom\@tempdima
    \global\advance\@mparbottom\dp\@marbox
    \global\advance\@mparbottom\marginparpush
    \advance\@tempdima -\ht\@marbox
```

Putting box movement inside the 'marbox':

```
    \global\setbox \@marbox
                   \vbox {\vskip \@tempdima
                          \box \@marbox}%
    \global \ht\@marbox \z@
    \global \dp\@marbox \z@
```

Sticking (rather than gluing:-) the 'marbox' to the line above, changed vskip to kern:

```
    \kern -\@pagedp
    \nointerlineskip
    \hb@xt@\columnwidth
      {\ifnum \@tempcnta >\z@
          \hskip\columnwidth \hskip\marginparsep
       \else
          \hskip -\marginparsep \hskip -\marginparwidth
       \fi
       \box\@marbox \hss}%
```

For this reason the following code can vanish:

```
\nobreak              %% No longer needed.  CAR92/12
\vskip -\@tempdima    %% No longer needed.  CAR92/12
```

```
    \nointerlineskip
    \hbox{\vrule \@height\z@ \@width\z@ \@depth\@pagedp}}
```

(*End definition for* `\@addmarginpar`.)

1.1.1 Kludgeins

This part of the file is part of the implementation of the following two new commands for LaTeX2e.

`\enlargethispage{<dim>}`

Adds `<dim>` to the height of the current column only. On the printed page the bottom of this column is extended downwards by exactly `<dim>` without having any effect on the placement of the footer; this may result in an overprinting.

`\enlargethispage*{<dim>}`

Similar to `\enlargethispage` but it tries to squeeze the column to be printed in as small a space as possible, ie it uses any shrinkability in the column. If the column was not explicitly broken (e.g. with `\pagebreak`) this may result in an overfull box message but except for this it will come out as expected (if you know what to expect).

The star form of this command is dedicated to Leslie Lamport, the other we need for ourselves (FMi, CAR).

These commands may well have unwanted effects if used soon before a `\clearpage`: please give keep them clear of such places.

`\@kludgeins` The insert which makes TeX do a lot of the necessary work. All we need to put into it is the amount by which the pagegoal should be changed.

```
\newinsert \@kludgeins
\global\dimen\@kludgeins \maxdimen
\global\count\@kludgeins 1000
```

(*End definition for* `\@kludgeins`.)

\enlargethispage
\enlargethispage*

The user command.

```
\gdef \enlargethispage {%
   \@ifstar
     {%
⟨*trace⟩
      \fl@trace{Enlarging page height * }%
⟨/trace⟩
      \@enlargepage{\hbox{\kern\p@}}}%
     {%
⟨*trace⟩
      \fl@trace{Enlarging page height exactly---}%
⟨/trace⟩
      \@enlargepage\@empty}%
}
```

(*End definition for* `\enlargethispage` *and* `\enlargethispage*`.)

\@enlargepage

This actually inserts the insert, after checking for extreme values of the change.

```
\gdef\@enlargepage#1#2{%
⟨*trace⟩
   \fl@trace{\@spaces\@spaces by #2}%
⟨/trace⟩
   \@tempskipa#2\relax
   \ifdim \@tempskipa>.5\maxdimen
     \@latex@error{Suggested\space extra\space height\space
                   (\the\@tempskipa)\space dangerously\space
                   large}\@eha
   \else
     \ifdim \vsize<.5\maxdimen
⟨*trace⟩
       \fl@trace {Kludgeins added--pagegoal before: \the\pagegoal}%
⟨/trace⟩
       \@bsphack
         \insert\@kludgeins{#1\vskip-\@tempskipa}%
       \@esphack
```

This next bit is for tracing only:

```
⟨*trace⟩
       \ifvmode \par
         \fl@trace {Kludgeins added--pagegoal after: \the \pagegoal}%
       \fi
⟨/trace⟩
     \else
       \@latex@error{Page\space height\space already\space
                     too\space large}\@eha
     \fi
   \fi
}
```

(*End definition for* `\@enlargepage`.)

\ShowFloat

This command provides some information about the contenta of a float register. Float registers have internal names of the form `\bx@`⟨*Uppercase-letter(s)-or numbers*⟩ and you specify just this letter or letters as the argument, e.g., `\ShowFloat{A}`. (There is not much error recovery if you specify something that isn't a float.)

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/11/15}%
⟨latexrelease⟩                 {\ShowFloat}{Show float register contents}%
\def\ShowFloat#1{\begingroup
    \let \fl@trace \fl@tracemessage
    \fl@trace{***Float #1 details:}%
    \ifcsname bx@#1\endcsname
      \expandafter\fl@ShowFloat\csname bx@#1\endcsname
    \else
      \fl@trace{Not a float!}%
    \fi
  \endgroup
}
\def\fl@ShowFloat#1{%
  \fl@traceval{\count#1}%  % this here should be interpreted on day
  \fl@traceval{\ht#1}%
  \fl@traceval{\dp#1}%
  \fl@traceval{\wd#1}%
  {\tracingonline1\showboxbreadth10\showboxdepth3\showbox#1}%
}
```

Here are two definitions from `fltrace` that make the above code work:

```
\def \fl@traceval #1{\fl@trace{\string #1 = \the #1}}
\def \fl@tracemessage #1{{\let\@elt\@empty\typeout{LaTeX2e: #1}}}
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                 {\ShowFloat}{Show float register contents}%
⟨latexrelease⟩
⟨latexrelease⟩\let\ShowFloat\@undefined
⟨latexrelease⟩\let\fl@ShowFloat\@undefined
⟨latexrelease⟩\let\fl@traceval\@undefined
⟨latexrelease⟩\let\fl@tracemessage\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

(*End definition for* `\ShowFloat`.)

1.1.2 Float control

This part implements controllable floats and other changes to the float mechanism.

It provides, at the document level, the following command for inclusion in LaTeX2e.

`\suppressfloats`

This suppresses all further floats on the current page.

With an optional argument it suppresses only floats only in certain positions on the current page.

`[t]` suppresses only floats at the top of the page `[b]` suppresses only floats at the bottom of the page

It also enables the use of an extra specifier, `!`, in the location optional argument of a float. If this is present then, just for this particular float, whenever it is processed by the float mechanism the following are ignored:

- all restrictions on the number of floats which can appear;
- all explicit restrictions on the amount of space which should (not) be occupied by floats and/or text.

The mechanism will still attempt to ensure that pages are not overfull.

These specifiers override, for the single float, the suppression commands described above.

In its current form, it also supplies a reasonably exhaustive, and somewhat baroque, means of tracing some aspects of the float mechanism.

More tracing.

`\fl@trace` `\tracefloatsoff` `\tracefloats` `\fl@traceval` `\tracefloatvals` `\fl@tracemessage`

Set-up tracing for floats independent of other tracing as it produces mega-output. Default is no tracing.

```
⟨*fltrace⟩
\def \fl@tracemessage #1{{\let\@elt\@empty\typeout{LaTeX2e: #1}}}
\def \tracefloats{\let \fl@trace \fl@tracemessage}
\def \tracefloatsoff {\let \fl@trace \@gobble}
\tracefloatsoff
\def \fl@traceval #1{\fl@trace{\string #1 = \the #1}}
\IncludeInRelease{2015/01/01}{\tracefloatvals}%
                          {trace float vals}%
\def \tracefloatvals{%
```

As `\@dblfloatplacement` sets `\f@depth` it needs to be run inside a group, otherwise the float placement will test for the wrong value.[49]

```
 \begingroup
```

When the user requests `\tracefloatvals` then they should show regardless of the tracing state, so locally we make sure that it is activated.

```
  \tracefloats
  \@dblfloatplacement
  \@floatplacement
  \fl@trace{***Float placement parameters:}%
  \fl@traceval\@colnum
  \fl@traceval\@colroom
  \fl@traceval\@topnum
  \fl@traceval\@toproom
  \fl@traceval\@botnum
  \fl@traceval\@botroom
  \fl@traceval\@fpmin
  \fl@trace{\string\textfraction = \textfraction}%
  \fl@traceval\@dbltopnum
  \fl@traceval\@dbltoproom
  \fl@trace{\string\textfraction = \textfraction}%
  \fl@trace{toplist: \@toplist}%
  \fl@trace{botlist: \@botlist}%
  \fl@trace{midlist: \@midlist}%
  \fl@trace{deferlist: \@deferlist}%
  \fl@trace{dbltoplist: \@dbltoplist}%
%FMi  \fl@trace{dbldeferlist: \@dbldeferlist}%
 \endgroup
```

[49] This is a somewhat questionable design.

```
}
\EndIncludeInRelease
\IncludeInRelease{0000/00/00}{\tracefloatvals}%
                          {trace float vals}%
\def \tracefloatvals{%
 \begingroup
  \tracefloats
  \@dblfloatplacement
  \@floatplacement
  \fl@trace{***Float placement parameters:}%
  \fl@traceval\@colnum
  \fl@traceval\@colroom
  \fl@traceval\@topnum
  \fl@traceval\@toproom
  \fl@traceval\@botnum
  \fl@traceval\@botroom
  \fl@traceval\@fpmin
  \fl@trace{\string\textfraction = \textfraction}%
  \fl@traceval\@dbltopnum
  \fl@traceval\@dbltoproom
  \fl@trace{\string\textfraction = \textfraction}%
  \fl@trace{toplist: \@toplist}%
  \fl@trace{botlist: \@botlist}%
  \fl@trace{midlist: \@midlist}%
  \fl@trace{deferlist: \@deferlist}%
  \fl@trace{dbltoplist: \@dbltoplist}%
% next line only in old releases
  \fl@trace{dbldeferlist: \@dbldeferlist}%
 \endgroup
}
\EndIncludeInRelease
```

We need to make sure that `fltrace` comes before `flafter` to make the tracing work.

```
\@ifpackageloaded{flafter}
 {\PackageWarningNoLine
      {fltrace}{Load 'fltrace' before 'flafter'\MessageBreak
                Attempting to recover by reloading 'flafter'}%
```

Hide the fact that `flafter` was already loaded and then request it anew.

```
    \expandafter\let\csname ver@flafter.sty\endcsname\relax
    \def\reserved@a#1{%
      \expandafter\let\csname\string#1+flafter+IIR\endcsname\relax}%
    \reserved@a\@addtocurcol
    \reserved@a\@addtonextcol
    \RequirePackage{flafter}}{}
⟨/fltrace⟩
```

As the code for `flafter` will contain tracing calls so that it works in conjunction with `fltrace` we need to provide a dummy definition for `\fl@trace` in that package.

```
⟨*flafter⟩
\providecommand\fl@trace[1]{}
⟨/flafter⟩
```

(*End definition for* `\fl@trace` *and others.*)

\suppressfloats
\@flstop

Float suppression commands: these set the relevant counter globally to zero. Thus they are overridden for a particular float by an ! specifier.

```
⟨*2ekernel⟩
\def \suppressfloats {%
   \@ifnextchar [%
     \@flstop
    {\global \@colnum \z@}%
}
```

Maybe this should be a loop over #1?

```
\def \@flstop [#1]{%
   \if t#1%
     \global \@topnum \z@
   \fi
   \if b#1%
     \global \@botnum \z@
   \fi
}
```

(*End definition for* \suppressfloats *and* \@flstop.)

Manipulation of float placement and type; both their strings and the corresponding count registers.

\@fpstype
\@reqcolroom
\@textfloatsheight

First a new count register to go with \@currtype.

Then a new skip register, for information needed to remove the \@maxsep conservatism: it is possible that this could use a temporary register.

Finally a dimension register to hold the total height of in-text floats on the current page. This is needed to implement a major change in the functionality of \@addtocurcol which is, nevertheless, a bug fix. It is not local and therefore cannot be a temporary register.

```
\newcount \@fpstype
\newdimen \@reqcolroom
\newdimen \@textfloatsheight
⟨/2ekernel⟩
```

(*End definition for* \@fpstype*,* \@reqcolroom*, and* \@textfloatsheight.)

\@fpsadddefault

Adds the default placement to what is already there.

Should not need to change this, but could do it as follows:

```
def \@fpsadddefault {%
  \@temptokena \expandafter\expandafter\expandafter
               {\csname fps@\@captype \endcsname}%
  \edef \reserved@a {\the\@temptokena}%
  \@onelevel@sanitize \reserved@a
  \edef \@fps {\@fps\reserved@a}%
```

```
⟨*2ekernel | fltrace⟩
\def \@fpsadddefault {%
⟨*trace⟩
   \fl@trace{fps changed from: \@fps}%
⟨/trace⟩
```

```
  \edef \@fps {\@fps\csname fps@\@captype \endcsname}%
  \@latex@warning {%
    No positions in optional float specifier.\MessageBreak
    Default added (so using ‘\@fps’)}%
}
```

(*End definition for* `\@fpsadddefault`.)

`\@setfloattypecounts` Sets counters `\@fpstype` and `\@currtype`.

BANG == bit4 of `\count\@currbox` = 0.

```
\def \@setfloattypecounts {%
  \@currtype \count\@currbox
  \@fpstype \count\@currbox
  \divide\@currtype\@xxxii \multiply\@currtype\@xxxii
  \advance \@fpstype -\@currtype
⟨*trace⟩
  \fl@trace{(mod 32) fpstype: \the \@fpstype}%
  \fl@trace{(mult of 32) currtype: \the \@currtype}%
% Tracing only: but some should be changed into real errors/warnings?
  \ifnum \@fpstype<\sixt@@n
    \ifnum \@fpstype=\z@
      \fl@trace{ERROR: no PLACEMENT, fpstype = \the \@fpstype = 0?}%
    \fi
    \ifnum \@fpstype=\@ne
      \fl@trace{WARNING: only h, fpstype = \the \@fpstype = 1?}%
    \fi
    \fl@trace{BANG float}%
  \else
    \ifnum \@fpstype=\sixt@@n
      \fl@trace{ERROR: no PLACEMENT, fpstype = \the \@fpstype = 16?}%
    \fi
    \ifnum \@fpstype=17
      \fl@trace{WARNING: only h, fpstype = \the \@fpstype = 17?}%
    \fi
    \fl@trace{ORD float}%
  \fi
⟨/trace⟩
}
⟨/2ekernel | fltrace⟩
```

(*End definition for* `\@setfloattypecounts`.)

Macros for getting, testing and setting bits of the fps.

`\@getfpsbit` Sets `\@tempcnta` to required bit of `\count\@currbox`.

```
⟨*2ekernel⟩
\def \@getfpsbit {%
   \@boxfpsbit \@currbox
}
```

(*End definition for* `\@getfpsbit`.)

`\@boxfpsbit` Used above.

```
\def \@boxfpsbit #1#2{%
   \@tempcnta \count#1%
   \divide \@tempcnta #2\relax
}
```

(*End definition for* `\@boxfpsbit`.)

`\@testfp` New definition of the float page test.

```
\def \@testfp #1{%
   \@boxfpsbit #18\relax % Really ‘#1 8’ for human readers!
   \ifodd \@tempcnta
   \else
     \@testtrue
   \fi
}
```

(*End definition for* `\@testfp`.)

`\@setfpsbit` Sets required bit of `\@tempcnta` (to 1).

```
\def \@setfpsbit #1{%
   \@tempcntb \@tempcnta
   \divide \@tempcntb #1\relax
   \ifodd \@tempcntb
   \else
     \advance \@tempcnta #1\relax
   \fi
}
⟨/2ekernel⟩
```

(*End definition for* `\@setfpsbit`.)

`\@resethfps` Globally adds t as a possible location for an h or !h only placement: this must be done using the count.

Although it will leave `\@fpstype` set to 17 even if it was originally 1, this does not matter since it is the last thing in `\@addtocurcol`.

```
⟨*2ekernel | fltrace⟩
\def \@resethfps {%
   \let\reserved@a\@empty
   \ifnum \@fpstype=\@ne
      \def \reserved@a {!}%
      \@fpstype 17
   \fi
   \ifnum \@fpstype=17
     \global \advance \count\@currbox \tw@
     \@latex@warning@no@line {%
       ‘\reserved@a h’ float specifier changed to ‘\reserved@a ht’}%
⟨*trace⟩
     \fl@trace{%
        ‘t’ added to ‘\reserved@a h’- new Count: \the \count\@currbox}%
⟨/trace⟩
   \fi
}
```

(*End definition for* `\@resethfps`.)

Special stuff for BANG floats.

`\@flsetnum` Ignores any zero float counter value in case BANG.

It uses a local assignment to the normally global counter: a bit naughty, perhaps?

These assignments are safe so long as the counter involved is only consulted once (i.e. only for the 'bang float') with the changed value. This is the case within `\@addtocurcol` because it is used only once within a call of the output routine (which forms a group).

For `\@addtonextcol` this is achieved by putting a group around its code; this is needed because it is called (by `\@startcolumn`) for each float which was on the deferlist. Almost identical considerations pertain to `\@addtodblcol`. There may be more efficient ways to handle this, but the group seems to be the simplest.

```
\def \@flsetnum #1{%
⟨*trace⟩
   \fl@trace{fpstype: \the \@fpstype (flsetnum \string#1)}%
⟨/trace⟩
   \ifnum \@fpstype<\sixt@@n
     \ifnum #1=\z@
⟨*trace⟩
       \fl@trace{BANG float resetting \string#1 to 1}%
⟨/trace⟩
       #1\@ne
     \fi
   \fi
⟨*trace⟩
   \fl@trace{#1 (before) = \the #1}%
⟨/trace⟩
}
```

(*End definition for* `\@flsetnum`.)

`\@flsettextmin` This ignores `\textfraction` space restriction in case BANG.

```
\def \@flsettextmin {%
⟨*trace⟩
   \fl@trace{fpstype: \the \@fpstype (flsettextmin)}%
⟨/trace⟩
   \ifnum \@fpstype<\sixt@@n
⟨*trace⟩
     \fl@trace{BANG ignoring textmin}%
⟨/trace⟩
     \@textmin \z@
   \else
     \@textmin \textfraction\@colht
⟨*trace⟩
     \fl@trace{ORD textmin = \the \@textmin}%
⟨/trace⟩
   \fi
}
```

(*End definition for* `\@flsettextmin`.)

`\@flcheckspace` This ignores space restriction in case BANG; this is still slightly conservative since it does not allow for the fact that, if there is no text in the column then `\textfloatsep` is not needed. Sets `@tempswa` true if there is room for `\@currbox`.

```
\def \@flcheckspace #1#2{%
```

```
   \advance \@reqcolroom
     \ifx #2\@empty \textfloatsep \else \floatsep \fi
⟨*trace⟩
   \fl@trace{colroom = \the \@colroom
                                   (flcheckspace \string#1 \string#2)}%
   \fl@trace{reqcolroom = \the \@reqcolroom
                                   (flcheckspace \string#1 \string#2)}%
⟨/trace⟩
   \ifdim \@colroom>\@reqcolroom
     \ifdim #1>\ht\@currbox
       \@tempswatrue
⟨*trace⟩
       \fl@trace{Space OK: #1 = \the #1 > \the \ht \@currbox
                                   (flcheckspace \string#1 \string#2)}%
⟨/trace⟩
     \else
⟨*trace⟩
       \fl@trace{fpstype: \the \@fpstype
                                   (flcheckspace \string#1 \string#2)}%
⟨/trace⟩
       \ifnum \@fpstype<\sixt@@n
⟨*trace⟩
         \fl@trace{BANG float ignoring #1
                                   (flcheckspace \string#1 \string#2):}%
         \fl@trace{\@spaces #1 = \the #1.  Ht float: \the \ht \@currbox
                                                        BANG}%
⟨/trace⟩
         \@tempswatrue
⟨*trace⟩
       \else
         \fl@trace{Fail---no room (flcheckspace \string#1 \string#2)
                       (fpstype \the \@fpstype=ORD?):}%
         \fl@trace{\@spaces #1 = \the #1.  Ht float: \the \ht \@currbox
                                                        ORD?}%
⟨/trace⟩
       \fi
     \fi
⟨*trace⟩
   \else
     \fl@trace{Fail---no room at 2nd test of colroom
                   (flcheckspace \string#1 \string#2)}%
⟨/trace⟩
   \fi
}
⟨/2ekernel | fltrace⟩
```

(*End definition for* `\@flcheckspace`.)

`\@flupdates` This updates everything when a float is placed.

```
⟨*2ekernel⟩
\def \@flupdates #1#2#3{%
   \global \advance #1\m@ne
   \global \advance \@colnum \m@ne
   \@tempdima -\ht\@currbox
```

```
  \advance \@tempdima
    -\ifx #3\@empty \textfloatsep \else \floatsep \fi
  \global \advance #2\@tempdima
  \global \advance \@colroom \@tempdima
  \@cons #3\@currbox
}
⟨/2ekernel⟩
```

(*End definition for* `\@flupdates`.)

Interesting facts about float mechanisms past and present, together with a summary of various features, some unresolved:

1. The value `\textfraction` does not affect the processing of doublecol floats: this seems sensible, but should be documented.
2. `\twocolumn` floatplacement was wrong: dbl not needed, ord needed.
3. `\@floatplacement` was not called after `\@startdblcol` or `\@topnewpage`. This has been changed; it is clearly a bug fix.
4. The use `\@topnewpage` when `\dblfigrule` is non-trivial produced a rule in the wrong place. This has been fixed by not using `\dblfigrule` when processing the 'float' from `\@topnewpage`.
5. If the specifier was just h and the float could not be put here, it went on the deferlist and stayed there until a clearpage. It now gets changed to a 'th': this is only an error-recovery action, putting just h or !h should be deprecated.
6. `\@dblmaxsep` was 'the maximum of `\dblfloatsep` and `\dbltexfloatsep`'. But it was never used! Now gone completely, like `\@maxsep`.
7. After an h float is put on a page, it was counted as text when applying the `\textfraction` test; this is possibly too big a change although it is a bug fix?
8. Two consecutive h floats are separated by twice `\intextsep`: this could be changed to one by use of `\addvspace`, OK? Note that it would also mean that less space is put in if an h float immediately follows other spaces. This is also possibly too big a change, at least for compatibility mode? Or it may be simply wrong! It has not been changed.
9. Now `\@addtocurcol` checks first for just p fps. I think that this is an increase in efficiency, but maybe the coding should be made even more efficient.
10. `\@tryfcolumn` now tests if the list is empty first, otherwise lots of wasted time! Thus this test has been removed from `\@startcolumn`. As Frank pointed out, this makes `\@startcolumn` less efficient. But it is now the same as `\@startdblcolumn`: I can see no reason why they should be different, but which is best?
11. Why is `\@colroom` set in `\@doclearpage`?
12. Footnotes. Check what `\clearpage` does when footnotes are left over. Footnotes are not put on float pages and, also, `\@addtonextcol` ignores the existence of held-over footnotes in deciding what floats can go on the page. Not changed.
13. `\clearpage` can still lose non-boxes, at least when floats are involved. It also moves some to the 'wrong page', but this may be a coding problem.

14. The ! option makes it necessary to check in `\output` that there is enough room left on the page after adding a float. (This would have been necessary anyway if anyone set `\@textmin` too close to zero! A similar danger existed also if the text in a `\twocolumn[text]` entity gets too large.) The current implementation of this also makes the normal case a little less efficient, OK? Not enough room means, at present, less than `\baselineskip`, with a warning: is this OK? Should it be made generic (another parameter)?

15. There are four possibilities for supporting this:

    `\twocolumn[\maketitle more text]`

    One is to change `\maketitle` slightly to allow this. Another is to change `\@topnewpage` so that more than one `\twocolumn[]` command is allowed; in this case `\maketitle\twocolumn[more text]` will work. The former is more robust from the user's viewpoint, but makes the code for `\maketitle` rather ad hoc (maybe it is already?). Another is to misuse the global twocolumn flag locally within `\@topnewpage`. Yet another is to move the column count register from the multicol package into the kernel. This has been done.

16. Where should the reinserts be put to maximise the probability that footnotes come out on the correct page? Or should we go for as much compatibility as possible (but see next item)?

17. Should we continue to support (as much as possible) `\samepage`? Some of its intended functionality is now advertised as being provided by `\enlargethispage`. Use of either is likely to result in wrongly placed footnotes, marginals, etc. Which should have priority: obeying the pagination instructions, or correct placement of notes/marginalia?

18. Is the adjustment of space to cause shrinking in the kludge-* case correct? Should it be limited to 0pt?

19. Is the setting of `\boxmaxdepth` in makecol and friends needed? It only has any effect if `\@textbottom` ends with a box or rule, in which case the vskip to allow for its depth should also be added. If it is kept, it should probably be the last thing in the box. It has now been removed.

    It would perhaps be better to document that `\@textbottom` and `\@texttop` must have natural height 0pt.

20. I cannot see why the vskip adjustment for the depth is needed if boxmaxdepth is used to ensure that there is never a too deep box.

21. The value of `\boxmaxdepth` should be explicitly set whenever necessary: it is too risky to assume that it has any particular value. Care is needed in deciding what to set it to.

    It is interesting to note that the value of `\boxmaxdepth` is unique in being read before the local settings for the box group are reset; all other parameter settings which affect the box construction use their values outside the box group.

22. Should `\@maxdepth` store the setting of `\maxdepth` from lplain? Or should we provide a proper interface to class files for setting these?

An analysis of various other macros.

`\@opcol` should do `\@floatplacement`, but where? Right at the end, since it always occurs at the start of a column.

```
\def\@opcol{%
  % Why is this done first?
  \global \@mparbottom \z@
  \if@twocolumn
    \@outputdblcol
  \else
    \@outputpage
    % This is not needed since it is done at the end of
    %   |\@outputpage|:
    \global \@colht \textheight
  \fi}
```

Only tracing has been added to these.

```
⟨latexrelease | fltrace⟩\IncludeInRelease{2017/01/01}%
⟨latexrelease | fltrace⟩  {\@makefcolumn}{negative height floats}%
⟨*2ekernel | fltrace | latexrelease⟩
\def\@makefcolumn #1{%
  \begingroup
    \@fpmin -\maxdimen
    \let \@testfp \@gobble
    \@tryfcolumn #1%
  \endgroup
⟨*trace⟩
  \if@fcolmade
    \fl@trace{PAGE: in \string\clearpage
                              \if@twocolumn ---twocolumn\fi---}%
    \fl@trace{----- float column/page completed from \string#1}%
  \fi
⟨/trace⟩
}
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨latexrelease | fltrace⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease | fltrace⟩  {\@makefcolumn}{negative height floats}%
⟨latexrelease | fltrace⟩\def\@makefcolumn #1{%
⟨latexrelease | fltrace⟩  \begingroup
⟨latexrelease | fltrace⟩    \@fpmin \z@
⟨latexrelease | fltrace⟩    \let \@testfp \@gobble
⟨latexrelease | fltrace⟩    \@tryfcolumn #1%
⟨latexrelease | fltrace⟩  \endgroup
⟨*trace⟩
⟨latexrelease | fltrace⟩  \if@fcolmade
⟨latexrelease | fltrace⟩    \fl@trace{PAGE: in \string\clearpage
⟨latexrelease | fltrace⟩                      \if@twocolumn ---twocolumn\fi---}%
⟨latexrelease | fltrace⟩    \fl@trace{----- float column/page completed
⟨latexrelease | fltrace⟩                      from \string#1}%
⟨latexrelease | fltrace⟩  \fi
⟨/trace⟩
```

```
⟨latexrelease | fltrace⟩}
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨/2ekernel | fltrace | latexrelease⟩
```

This will line up the last baselines in the two columns provided they are constructed in the normal way: i.e. ending in a skip of minus the original depth, with `\@textbottom` adding nothing.

Thus again it is essential for `\@textbottom` to have depth 0pt.

```
⟨latexrelease | fltrace⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease | fltrace⟩   {\@outputdblcol}{2 column marks}%
⟨*2ekernel | fltrace | latexrelease⟩
```

This is just a change to the single command `\@outputdblcol` so that it saves mark information for the first column and restores it in the second column.

```
\def\@outputdblcol{%
  \if@firstcolumn
    \global\@firstcolumnfalse
```

Save the left column

```
    \global\setbox\@leftcolumn\copy\@outputbox
⟨fltrace⟩     \fl@trace{PAGE: first column boxed}%
```

Remember the marks from the first column

```
    \splitmaxdepth\maxdimen
    \vbadness\maxdimen
```

In case of `\enlargethispage` we will have infinite negative glue at the bottom of the page (coming from `\vss`) and that will earn us an error message if we `\vsplit` to get at the marks. So we need to remove the last glue (if any) at the end of `\@outputbox` as we are only interested in marks that change doesn't matter.

```
     \setbox\@outputbox\vbox{\unvbox\@outputbox\unskip}%
     \setbox\@outputbox\vsplit\@outputbox to\maxdimen
```

One minor difference from the current `fixmarks` package, pass the marks through a token register to stop any `#` tokens causing an error in a `\def`.

```
    \toks@\expandafter{\topmark}%
    \xdef\@firstcoltopmark{\the\toks@}%
    \toks@\expandafter{\splitfirstmark}%
    \xdef\@firstcolfirstmark{\the\toks@}%
```

This test does not work if truly empty marks have been inserted, but LaTeX marks should always have (at least) two brace groups. (Except before the first mark is used, when the marks are empty, but that is OK here.)

```
    \ifx\@firstcolfirstmark\@empty
      \global\let\@setmarks\relax
    \else
      \gdef\@setmarks{%
        \let\firstmark\@firstcolfirstmark
        \let\topmark\@firstcoltopmark}%
    \fi
```

End of change

```
  \else
    \global\@firstcolumntrue
    \setbox\@outputbox\vbox{%
     \hb@xt@\textwidth{%
```

```
        \hb@xt@\columnwidth{\box\@leftcolumn \hss}%
        \hfil
```

The color of the \vrule should be \normalcolor as to not inherit the color from the column.

```
        {\normalcolor\vrule \@width\columnseprule}%
        \hfil
       \hb@xt@\columnwidth{\box\@outputbox \hss}}}%
⟨fltrace⟩    \fl@trace{PAGE: second column also boxed}%
  \@combinedblfloats
```

Override current first and top with those of first column if necessary

```
    \@setmarks
```

End of change

```
    \@outputpage
⟨fltrace⟩    \fl@trace{PAGE: two column page completed}%
    \begingroup
      \@dblfloatplacement
      \@startdblcolumn
      \@whilesw\if@fcolmade \fi{\@outputpage
⟨fltrace⟩      \fl@trace{PAGE: double float page completed}%
     \@startdblcolumn}%
    \endgroup
  \fi}%
```

```
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨latexrelease | fltrace⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease | fltrace⟩  {\@outputdblcol}{2 column marks}%
⟨latexrelease | fltrace⟩\def\@outputdblcol{%
⟨latexrelease | fltrace⟩  \if@firstcolumn
⟨latexrelease | fltrace⟩    \global \@firstcolumnfalse
⟨latexrelease | fltrace⟩    \global \setbox\@leftcolumn \box\@outputbox
⟨*trace⟩
⟨latexrelease | fltrace⟩    \fl@trace{PAGE: first column boxed}%
⟨/trace⟩
⟨latexrelease | fltrace⟩  \else
⟨latexrelease | fltrace⟩    \global \@firstcolumntrue
⟨latexrelease | fltrace⟩    \setbox\@outputbox \vbox {%
⟨latexrelease | fltrace⟩                        \hb@xt@\textwidth {%
⟨latexrelease | fltrace⟩                          \hb@xt@\columnwidth {%
⟨latexrelease | fltrace⟩                            \box\@leftcolumn \hss}%
⟨latexrelease | fltrace⟩                          \hfil
⟨latexrelease | fltrace⟩                          {\normalcolor\vrule
⟨latexrelease | fltrace⟩                              \@width\columnseprule}%
⟨latexrelease | fltrace⟩                          \hfil
⟨latexrelease | fltrace⟩                          \hb@xt@\columnwidth {%
⟨latexrelease | fltrace⟩                            \box\@outputbox \hss}%
⟨latexrelease | fltrace⟩                                          }%
⟨latexrelease | fltrace⟩                             }%
⟨*trace⟩
⟨latexrelease | fltrace⟩    \fl@trace{PAGE: second column also boxed}%
⟨/trace⟩
⟨latexrelease | fltrace⟩    \@combinedblfloats
⟨latexrelease | fltrace⟩    \@outputpage
⟨*trace⟩
```

```
⟨latexrelease | fltrace⟩     \fl@trace{PAGE: two column page completed}%
⟨/trace⟩
⟨latexrelease | fltrace⟩     \begingroup
⟨latexrelease | fltrace⟩       \@dblfloatplacement
⟨latexrelease | fltrace⟩       \@startdblcolumn
```

This loop could be replaced by an `\expandafter` tail recursion in `\@startdblcolumn`.

```
⟨latexrelease | fltrace⟩       \@whilesw\if@fcolmade \fi
⟨latexrelease | fltrace⟩         {\@outputpage
⟨*trace⟩
⟨latexrelease | fltrace⟩       \fl@trace{PAGE: double float page completed}%
⟨/trace⟩
⟨latexrelease | fltrace⟩          \@startdblcolumn}%
⟨latexrelease | fltrace⟩     \endgroup
⟨latexrelease | fltrace⟩   \fi
⟨latexrelease | fltrace⟩}%
⟨latexrelease | fltrace⟩\EndIncludeInRelease
⟨/2ekernel | fltrace | latexrelease⟩
```

1.1.3 Float placement parameters

The main purpose of this section is to ensure that all the float-placement parameters which need to be set in a class file or package have been declared. It also describes their use and sets values for them which are reasonable for typical documents using US letter or A4 sized paper.

Limits for the placement of floating objects

`\c@topnumber` This counter holds the maximum number of floats that can appear at the top of a text page or column.

```
⟨*2ekernel⟩
\newcount\c@topnumber
\setcounter{topnumber}{2}
```

(*End definition for* `\c@topnumber`.)

`\topfraction` This macro holds the maximum proportion (as a decimal number) of a text page or column that can be occupied by floats at the top.

```
\newcommand\topfraction{.7}
```

(*End definition for* `\topfraction`.)

`\c@bottomnumber` This counter holds the maximum number of floats that can appear at the bottom of a text page or column.

```
\newcount\c@bottomnumber
\setcounter{bottomnumber}{1}
```

(*End definition for* `\c@bottomnumber`.)

`\bottomfraction` This macro holds the maximum proportion (as a decimal number) of a text page or column that can be occupied by floats at the bottom.

```
\newcommand\bottomfraction{.3}
```

(*End definition for* `\bottomfraction`.)

`\c@totalnumber` This counter holds the maximum number of floats that can appear on any text page or column.

```
\newcount\c@totalnumber
\setcounter{totalnumber}{3}
```

(*End definition for* `\c@totalnumber`.)

`\textfraction` This macro holds the minimum proportion (as a decimal number) of a text page or column that must be occupied by text.

```
\newcommand\textfraction{.2}
```

(*End definition for* `\textfraction`.)

`\floatpagefraction` This macro holds the minimum proportion (as a decimal number) of a page or column that must be occupied by floating objects before a 'float page' is produced.

```
\newcommand\floatpagefraction{.5}
```

(*End definition for* `\floatpagefraction`.)

`\c@dbltopnumber` This counter holds the maximum number of double-column floats that can appear on the top of a two-column text page.

```
\newcount\c@dbltopnumber
\setcounter{dbltopnumber}{2}
```

(*End definition for* `\c@dbltopnumber`.)

`\dbltopfraction` This macro holds the maximum proportion (as a decimal number) of a two-column text page that can be occupied by double-column floats at the top.

```
\newcommand\dbltopfraction{.7}
```

(*End definition for* `\dbltopfraction`.)

`\dblfloatpagefraction` This macro holds the minimum proportion (as a decimal number) of a page that must be occupied by double-column floating objects before a 'double-column float page' is produced.

```
\newcommand\dblfloatpagefraction{.5}
```

(*End definition for* `\dblfloatpagefraction`.)

Floats on a text page

\floatsep
\textfloatsep
\intextsep

When a floating object is placed on a page with text, these parameters control the separation between the float and the other objects on the page. These parameters are used for both one-column mode and single-column floats in two-column mode. They are all rubber lengths.

\floatsep is the space between adjacent floats that are placed at the top or bottom of the text page or column.

\textfloatsep is the space between the main text and floats at the top or bottom of the page or column.

\intextsep is the space between in-text floats and the text.

```
\newskip\floatsep
\newskip\textfloatsep
\newskip\intextsep
\setlength\floatsep    {12\p@ \@plus 2\p@ \@minus 2\p@}
\setlength\textfloatsep{20\p@ \@plus 2\p@ \@minus 4\p@}
\setlength\intextsep   {12\p@ \@plus 2\p@ \@minus 2\p@}
```

(*End definition for* \floatsep*,* \textfloatsep*, and* \intextsep*.*)

\dblfloatsep
\dbltextfloatsep

When double-column floats (floating objects that span the whole \textwidth) are placed at the top of a text page in two-column mode, the separation between the float and the text is controlled by \dblfloatsep and \dbltextfloatsep. They are rubber lengths.

\dblfloatsep is the space between adjacent double-column floats placed at the top of the text page.

\dbltextfloatsep is the space between the main text and double-column floats at the top of the page.

```
\newskip\dblfloatsep
\newskip\dbltextfloatsep
\setlength\dblfloatsep    {12\p@ \@plus 2\p@ \@minus 2\p@}
\setlength\dbltextfloatsep{20\p@ \@plus 2\p@ \@minus 4\p@}
```

(*End definition for* \dblfloatsep *and* \dbltextfloatsep*.*)

Floats on their own page or column

\@fptop
\@fpsep
\@fpbot

When floating objects are placed on a separate page or column, called a 'float page', the layout of the page is controlled by these parameters, which are rubber lengths.

At the top of the page \@fptop is inserted; typically this supplies some stretchable whitespace. At the bottom of the page \@fpbot is inserted. Between adjacent floats \@fpsep is inserted.

These parameters are used for all floating objects on a 'float page' in one-column mode, and for single-column floats in two-column mode.

Note that at least one of the two parameters \@fptop and \@fpbot should contain a plus ...fil so as to fill the remaining empty space.

```
\newskip\@fptop
\newskip\@fpsep
\newskip\@fpbot
\setlength\@fptop{0\p@ \@plus 1fil}
\setlength\@fpsep{8\p@ \@plus 2fil}
\setlength\@fpbot{0\p@ \@plus 1fil}
```

(*End definition for* \@fptop*,* \@fpsep*, and* \@fpbot*.*)

\@dblfptop
\@dblfpsep
\@dblfpbot

Double-column 'float pages' in two-column mode use similar parameters.

```
\newskip\@dblfptop
\newskip\@dblfpsep
\newskip\@dblfpbot
\setlength\@dblfptop{0\p@ \@plus 1fil}
\setlength\@dblfpsep{8\p@ \@plus 2fil}
\setlength\@dblfpbot{0\p@ \@plus 1fil}
```

(*End definition for* `\@dblfptop`, `\@dblfpsep`, *and* `\@dblfpbot`.)

\topfigrule
\botfigrule
\dblfigrule

The macros can be used to put in rules between floats and text; whatever they insert should be vertical mode material which takes up zero space.

```
\let\topfigrule=\relax
\let\botfigrule=\relax
\let\dblfigrule=\relax
⟨/2ekernel⟩
```

(*End definition for* `\topfigrule`, `\botfigrule`, *and* `\dblfigrule`.)

File Z
lthyphen.dtx

This file contains the code for loading hyphenation patterns into LaTeX. Most of this will end up in a file called `hyphen.ltx`. If you wish to customize your LaTeX system in respect of hyphenation patterns, write a file `hyphen.cfg`. If this file exists, it will be loaded instead of `hyphen.ltx`. See the comments below for additional information.

To produce the printed version of this file the following code is used. It can be extracted with the DOCSTRIP program, or one can run this file directly through LaTeX 2_ε.

```
⟨*driver⟩
\documentclass{ltxdoc}
\begin{document}
\DocInput{lthyphen.dtx}
\end{document}
⟨/driver⟩
```

The default file `hyphen.ltx` loads hyphenation patterns for US english. If you want to load additional or other hyphenation patterns, you should create a file `hyphen.cfg`. This is best done by starting from `hyphen.ltx`.

For backward compatibility, the default file, `hyphen.ltx`, first tries to load the file `hyphen.tex`. If this file exists, an information message is issued and the appropriate defaults for TeX's internal parameters are set: `\language` is initialized to 0, and `\lefthyphenmin` and `\righthyphenmin` to 2 and 3, respectively, to disallow x- or -xx breaks.

```
⟨*default⟩
\InputIfFileExists{hyphen.tex}%
   {\message{Loading hyphenation patterns for US english.}%
    \language=0
    \lefthyphenmin=2 \righthyphenmin=3 }%
```

Otherwise, since we cannot do anything without any hyphenation patterns, an error message is printed and the IniTeX run is terminated by invoking `\@@end` (which is the LaTeX 2_ε name for TeX's `\end` primitive).

```
   {\errhelp{The configuration for hyphenation is incorrectly
             installed.^^J%
             If you don't understand this error message you need
             to seek^^Jexpert advice.}%
    \errmessage{OOPS! I can't find any hyphenation patterns for
                US english.^^J \space Think of getting some or the
                latex2e setup will never succeed}\@@end}
⟨/default⟩
```

The following example describes the possible contents of a file `hyphen.cfg` that will load both US English and German hyphenation patterns, making the former the default. It sets `\language` to 0 for the US patterns and to 1 for the German patterns. Then `\language` is set to 0 to make this the default and the default values of `\lefthyphenmin` and `\righthyphenmin` are set.

```
language=0
input hyphen % (or \input ushyphen1 if the file has been renamed)
language=1
input ghyph31
```

```
language=0
lefthyphenmin=2
righthyphenmin=3
endinput
```

Another possibility is to use the package `babel`, by Johannes Braams. That package is distributed with a suitable `hyphen.cfg` file.

File aa
ltfinal.dtx

1 Final settings

This section contains the final settings for LaTeX. It initializes some debugging and typesetting parameters, sets the default \catcodes and uc/lc codes, and inputs the hyphenation file.

1.1 Debugging

By default, LaTeX shows statistics:

```
⟨*2ekernel⟩
\tracingstats1
```

1.2 Typesetting parameters

\@lowpenalty
\@medpenalty
\@highpenalty

These are penalties used internally.

```
\newcount\@lowpenalty
\newcount\@medpenalty
\newcount\@highpenalty
```

(*End definition for* \@lowpenalty*,* \@medpenalty*, and* \@highpenalty*.*)

\newmarks

Allocate extended marks types if etex is active. Placed here at the end of the format to increase compatibility with count allocations in earlier releases.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩                  {\newmarks}{Extended Allocation}%
\ifx\marks\@undefined\else
\def\newmarks{%
  \e@alloc\marks \e@alloc@chardef{\count256}\m@ne\e@alloc@top}
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\newmarks}{Extended Allocation}%
⟨latexrelease⟩\let\newmarks\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* \newmarks*.*)

Allocate 3 mark classes to be used in \markboth and \markright. Should be done earlier but for that definition of \newmarks needs moving (which it should I guess).

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2022/06/01}%
⟨latexrelease⟩                  {2e-left}{Delayed legacy marks}%
\NewMarkClass {2e-left}
```

```
\NewMarkClass {2e-right}
\NewMarkClass {2e-right-nonempty}
```

No rollback really, the marks will remain.

```
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {2e-left}{Delayed legacy marks}%
⟨latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

\newXeTeXintercharclass
\xe@alloc@intercharclass
\e@alloc@intercharclass@top

Allocate \XeTeXintercharclass types if xetex is active. previously defined in xetex.ini.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩               {\newXeTeXintercharclass}{Extended Allocation}%
```

Classes allocated 1 to 4094 (or 254 on older xetex) (In earlier XeLaTeX versions 1, 2 and 3 were pre-set for CJK).

```
\ifx\XeTeXcharclass\@undefined
\else
\ifdim\the\XeTeXversion\XeTeXrevision\p@>0.99993\p@
  \chardef\e@alloc@intercharclass@top=4095
\else
  \chardef\e@alloc@intercharclass@top=255
\fi
\def\newXeTeXintercharclass{%
 \e@alloc\XeTeXcharclass
   \chardef\xe@alloc@intercharclass\m@ne\e@alloc@intercharclass@top}
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩               {\newXeTeXintercharclass}{Extended Allocation}%
⟨latexrelease⟩ \ifx\XeTeXcharclass\@undefined
⟨latexrelease⟩ \else
⟨latexrelease⟩    \def\xe@alloc@#1#2#3#4#5{\global\advance#1\@ne
⟨latexrelease⟩     \xe@ch@ck#1#4#2%
⟨latexrelease⟩     \allocationnumber#1%
⟨latexrelease⟩     \global#3#5\allocationnumber
⟨latexrelease⟩     \wlog{\string#5=\string#2\the\allocationnumber}}
⟨latexrelease⟩    \def\xe@ch@ck#1#2#3{%
⟨latexrelease⟩     \ifnum#1<#2\else
⟨latexrelease⟩      \errmessage{No room for a new #3}%
⟨latexrelease⟩     \fi}
⟨latexrelease⟩    \def\newXeTeXintercharclass{%
⟨latexrelease⟩     \xe@alloc@\xe@alloc@intercharclass
⟨latexrelease⟩                    \XeTeXcharclass\chardef\@cclv}
⟨latexrelease⟩ \fi
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2016/02/01}%
```

```
⟨latexrelease⟩  {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
\ifx\XeTeXcharclass\@undefined
\else
  \countdef\xe@alloc@intercharclass=257
  \xe@alloc@intercharclass=\z@
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{2015/01/01}%
⟨latexrelease⟩  {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
⟨latexrelease⟩ \ifx\XeTeXcharclass\@undefined
⟨latexrelease⟩ \else
⟨latexrelease⟩   \xe@alloc@intercharclass=\thr@@
⟨latexrelease⟩ \fi
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩  {\xe@alloc@intercharclass}{Start of XeTeX class allocator}%
⟨latexrelease⟩ \ifx\XeTeXcharclass\@undefined
⟨latexrelease⟩ \else
⟨latexrelease⟩   \newcount\xe@alloc@intercharclass
⟨latexrelease⟩   \xe@alloc@intercharclass=\thr@@
⟨latexrelease⟩ \fi
⟨latexrelease⟩\EndIncludeInRelease
⟨∗2ekernel⟩
```

(*End definition for* `\newXeTeXintercharclass`, `\xe@alloc@intercharclass`, *and* `\e@alloc@intercharclass@top`.)

trace\string_stack\string_levels

Now define the Lua function to emulate `\tracingstacklevels` and install it in the `input_level_string` callback.

```
⟨/2ekernel⟩
⟨∗2ekernel | latexrelease⟩
```

In `latexrelease` mode we always remove the function from the callback, then add the correct version later.

```
⟨latexrelease⟩\ifx\directlua\@undefined
⟨latexrelease⟩\else
⟨latexrelease⟩  \directlua{%
⟨latexrelease⟩    if luatexbase.callbacktypes['input_level_string'] and %
⟨latexrelease⟩       luatexbase.in_callback('input_level_string','tracingstacklevels') then
⟨latexrelease⟩        luatexbase.remove_from_callback('input_level_string','tracingstacklevels')
⟨latexrelease⟩    end}%
⟨latexrelease⟩\fi
⟨latexrelease⟩\IncludeInRelease{2021/06/01}{trace_stack_levels}%
⟨latexrelease⟩                 {Lua trace_stack_levels function}%
\ifx\directlua\@undefined
\else
⟨∗2ekernel⟩
  \expanded{%
    \everyjob{\the\everyjob
    \noexpand%\directlua
⟨/2ekernel⟩
    \directlua{%
      local function trace_stack_levels (input_ptr)
        local tracingstacklevels = tex.count.tracingstacklevels
```

```
        if tex.tracingmacros > 0 or input_ptr < tracingstacklevels then
          if tracingstacklevels > 0 then
            if input_ptr < tracingstacklevels then
              return "\string\n\string~" .. string.rep(".",input_ptr)
            else
              return "\string~\string~"
            end
          else
            return "\string\n"
          end
        else
          return ""
        end
      end
⟨latexrelease⟩    if luatexbase.callbacktypes['input_level_string'] then
      luatexbase.add_to_callback('input_level_string',
        trace_stack_levels,'tracingstacklevels')
⟨latexrelease⟩    end
    }%
⟨*2ekernel⟩
  }}%
⟨/2ekernel⟩
\fi
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩
```

Then for the full rollback, just do nothing, since the function was already taken out of the rollback above.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}{trace_stack_levels}%
⟨latexrelease⟩                 {Lua trace_stack_levels function}%
⟨latexrelease⟩% Nothing here
⟨latexrelease⟩\EndIncludeInRelease
⟨/2ekernel | latexrelease⟩
⟨*2ekernel⟩
```

(*End definition for* `trace\string_stack\string_levels`.)

The default values of the picture and `\fbox` parameters:

```
\unitlength = 1pt
\fboxsep = 3pt
\fboxrule = .4pt
```

The saved value of TEX's `\maxdepth`:

```
\@maxdepth       = \maxdepth
```

`\vsize` initialized because a `\clearpage` with `\vsize < \topskip` causes trouble. `\@colroom` and `\@colht` also initialized because `\vsize` may be set to them if a `\clearpage` is done before the `\begin{document}`

```
\vsize = 1000pt
\@colroom = \vsize
\@colht = \vsize
```

Initialise `\textheight` `\textwidth` and page style, to avoid internal errors if they are not set by the class.

```
\textheight=.5\maxdimen
\textwidth=\textheight
\ps@empty
```

1.3 Lccodes for hyphenation

For 7- and 8-bit engines the assumption of T1 encodings is the basis for the hyphenation patterns. That's not the case for the Unicode engines, where the assumption is engine-native working. The common loader system provides access to data from the Unicode Consortium covering not only `\lccode` but also other related data. The `\lccode` part of that at least needs to be loaded before hyphenation is tackled: XeTEX follows the standard TEX route of building patterns into the format. LuaTEX doesn't require this data be loaded *here* but it does need to be loaded somewhere. Rather than test for the Unicode engines by name, the approach here is to look for the extended math mode handling both provide: any other engine developed in this area will presumably also provide `\Umathcode`.

```
\ifnum 0%
  \ifx\Umathcode\@undefined\else 1\fi
  \ifx\XeTeXmathcode\@undefined\else 1\fi
  >\z@
  \message{ Unicode character data,}
  \input{load-unicode-data}
⟨/2ekernel⟩
⟨latexrelease⟩\IncludeInRelease{2016/02/01}%
⟨latexrelease⟩  {\XeTeXintercharclasses}{XeTeX character classes}%
⟨latexrelease⟩  \ifx\XeTeXinterchartoks\undefined
⟨latexrelease⟩  \else
⟨latexrelease⟩    \begingroup
⟨latexrelease⟩      \chardef\XeTeXcharclassID = 0 %
⟨latexrelease⟩      \chardef\XeTeXcharclassOP = 0 %
⟨latexrelease⟩      \chardef\XeTeXcharclassCL = 0 %
⟨latexrelease⟩      \chardef\XeTeXcharclassEX = 0 %
⟨latexrelease⟩      \chardef\XeTeXcharclassIS = 0 %
⟨latexrelease⟩      \chardef\XeTeXcharclassNS = 0 %
⟨latexrelease⟩      \chardef\XeTeXcharclassCM = 0 %
⟨latexrelease⟩      \input{load-unicode-xetex-classes}
⟨latexrelease⟩    \endgroup
⟨latexrelease⟩    \global\let\xtxHanGlue\undefined
⟨latexrelease⟩    \global\let\xtxHanSpace\undefined
⟨latexrelease⟩    \global\XeTeXinterchartoks 0 1 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 0 2 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 0 3 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 1 0 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 2 0 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 3 0 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 1 1 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 1 2 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 1 3 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 2 1 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 2 2 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 2 3 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 3 1 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 3 2 = {}
⟨latexrelease⟩    \global\XeTeXinterchartoks 3 3 = {}
⟨latexrelease⟩  \fi
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
```

```
⟨latexrelease⟩  {\XeTeXintercharclasses}{XeTeX character classes}%
⟨latexrelease⟩  \ifx\XeTeXinterchartoks\undefined
⟨latexrelease⟩  \else
⟨latexrelease⟩   \input{load-unicode-xetex-classes}
⟨latexrelease⟩   \gdef\xtxHanGlue{\hskip0pt plus 0.1em\relax}
⟨latexrelease⟩   \gdef\xtxHanSpace{\hskip0.2em plus 0.2em minus 0.1em\relax}
⟨latexrelease⟩   \global\XeTeXinterchartoks 0 1 = {\xtxHanSpace}
⟨latexrelease⟩   \global\XeTeXinterchartoks 0 2 = {\xtxHanSpace}
⟨latexrelease⟩   \global\XeTeXinterchartoks 0 3 = {\nobreak\xtxHanSpace}
⟨latexrelease⟩   \global\XeTeXinterchartoks 1 0 = {\xtxHanSpace}
⟨latexrelease⟩   \global\XeTeXinterchartoks 2 0 = {\nobreak\xtxHanSpace}
⟨latexrelease⟩   \global\XeTeXinterchartoks 3 0 = {\xtxHanSpace}
⟨latexrelease⟩   \global\XeTeXinterchartoks 1 1 = {\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 1 2 = {\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 1 3 = {\nobreak\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 2 1 = {\nobreak\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 2 2 = {\nobreak\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 2 3 = {\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 3 1 = {\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 3 2 = {\xtxHanGlue}
⟨latexrelease⟩   \global\XeTeXinterchartoks 3 3 = {\nobreak\xtxHanGlue}
⟨latexrelease⟩  \fi
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

There is one over-ride that makes sense here (see below for the same for 8-bit engines): setting the lccode for `-` to itself.

```
  \lccode`\- =`\- % default hyphen char
```

The alternative is that a "traditional" engine is in use.

```
\else
```

We set things up so that hyphenation files can assume that the default (T1) lccodes are in use (at present this also sets up the uccodes). We temporarily define `\reserved@a` to apply `\reserved@c` to all the numbers in the range of its arguments.

```
\def\reserved@a#1#2{%
   \@tempcnta#1\relax
   \@tempcntb#2\relax
   \reserved@b
}
\def\reserved@b{%
   \ifnum\@tempcnta>\@tempcntb\else
      \reserved@c\@tempcnta
      \advance\@tempcnta\@ne
      \expandafter\reserved@b
   \fi
}
```

Depending on the TEX version, we might not be allowed to do this for non-ASCII characters.

```
\def\reserved@c#1{%
   \count@=#1\advance\count@ by -"20
   \uccode#1=\count@
   \lccode#1=#1
}
```

```
\reserved@a{`\a}{`\z}
\reserved@a{"A0}{"BC}
\reserved@a{"E0}{"FF}
```

The upper case characters need their `\uccode` and `\lccode` values set, and their `\sfcode` set to 999.

```
\def\reserved@c#1{%
   \count@=#1\advance\count@ by "20
   \uccode#1=#1
   \lccode#1=\count@
   \sfcode#1=999
}
\reserved@a{`\A}{`\Z}
\reserved@a{"80}{"9C}
\reserved@a{"C0}{"DF}
```

Well, it would be nice if that were correct, but unfortunately, the Cork encoding contains some odd slots whose uccode or lccode isn't quite what you'd expect.

```
\uccode`\^^Y=`\I     % dotless i
\lccode`\^^Y=`\^^Y   % dotless i
\uccode`\^^Z=`\J     % dotless j, ae in OT1
\lccode`\^^Z=`\^^Z   % dotless j, ae in OT1
\lccode`\^^9d=`\i    % dotted I
\uccode`\^^9d=`\^^9d % dotted I
\lccode`\^^9e=`\^^9e % d-bar
\uccode`\^^9e=`\^^d0 % d-bar
```

Finally here is one that helps hyphenation in the OT1 encoding.

```
\lccode`\^^[=`\^^[   % oe in OT1
```

And we also set the `\lccode` of `\-` and `\textcompwordmark` so that they do not prevent hyphenation in the remainder of the word (as suggested by Lars Helström).

```
\lccode`\- =`\-   % default hyphen char
\lccode 127=127   % alternate hyphen char
\lccode 23 =23    % textcompwordmark in T1
```

End of the conditional to select either Unicode or T1 encoding defaults.

```
\fi
```

At this stage, we can install any last-minute expl3 set-up.

```
\@expl@finalise@setup@@
\def\@expl@finalise@setup@@{}
```

This is as good a place as any to active a few XeTEX-specific settings

```
\ifx\XeTeXuseglyphmetrics\@undefined
\else
  \XeTeXuseglyphmetrics=1 %
  \XeTeXdashbreakstate=1 %
\fi
```

1.4 Hyphenation

The following code will be compiled into the format file. It checks for the existence of `hyphen.cfg` in inputs that file if found. Otherwise it inputs `hyphen.ltx`. Note that these are loaded in *before* the `\catcode`s are set, so local hyphenation files can use 8-bit input.

We try to load the customized hyphenation description file.

```
\InputIfFileExists{hyphen.cfg}
          {\typeout{=========================================^^J%
                     Local configuration file hyphen.cfg used^^J%
                    =========================================}%
            \def\@addtofilelist##1{\xdef\@filelist{\@filelist,##1}}%
          }
          {\input{hyphen.ltx}}
\let\@addtofilelist\@gobble
```

`\l@nohyphenation`

```
\ifx\l@nohyphenation \@undefined
  \newlanguage\l@nohyphenation
\fi
```

(*End definition for* `\l@nohyphenation`.)

`\document@default@language` Default document language. -1 acts as language 0, but used as a flag in `\document` to see if it has been set in the preamble.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2017/04/15}%
⟨latexrelease⟩       {\document@default@language}{Save language for hyphenation}%
\let\document@default@language\m@ne
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩       {\document@default@language}{Save language for hyphenation}%
%
⟨latexrelease⟩\let\document@default@language\@undefined
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

(*End definition for* `\document@default@language`.)

1.5 Font loading

Fonts loaded during the formatting process might already have changed the `\font@submax` from `0pt` to something higher. If so, we put out a bold warning.

```
\ifdim \font@submax >\z@
   \@font@warning{Size substitutions with differences\MessageBreak
                  up to \font@submax\space have occurred.\MessageBreak
                 \MessageBreak
                 Please check the transcript file
                 carefully\MessageBreak
                 and redo the format generation if necessary!
                 \@gobbletwo}%
   \errhelp{Only stopped, to give you time to
            read the above message.}
   \errmessage{}
```

We reset the macro. Otherwise every user will get a warning on every job.

```
\def\font@submax{0pt}
\fi
```

For pdfTEX preload and enable automatic glyph to Unicode mapping for more reliable copy and paste support.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
⟨latexrelease⟩\IncludeInRelease{2021/06/01}%
⟨latexrelease⟩                  {\pdfgentounicode}{Preload glyphtounicode}%
\ifx \pdfgentounicode \@undefined \else
⟨*2ekernel⟩
  \ifnum 0=0%
    \ifdefined\pdftexversion
% \pdftexversion<140 does not have \pdfgentounicode, so we only check higher values
      \ifnum \pdftexversion=140 \ifnum\pdftexrevision<22 1\fi\fi
    \fi
    \relax
⟨/2ekernel⟩
    \input glyphtounicode
⟨*2ekernel⟩
  \else
    \begingroup
      \everyeof{\noexpand}\endlinechar-1
      \edef\x{\endgroup
        \everyjob{\the\everyjob\@@input glyphtounicode }%
    }\x
  \fi
⟨/2ekernel⟩
  \pdfgentounicode=1
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
```

When rolling back we can't unload the glyphtounicode mappings, but we can reset `\pdfgentounicode` to ensure that they aren't used.

```
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\pdfgentounicode}{Preload glyphtounicode}%
⟨latexrelease⟩\ifx \pdfgentounicode \@undefined \else
⟨latexrelease⟩  \pdfgentounicode=0
⟨latexrelease⟩\fi
⟨latexrelease⟩\EndIncludeInRelease
⟨*2ekernel⟩
```

1.6 Input encoding

Starting with the 2018 LATEX release default the inputencoding to UTF-8. Unless the format is being used with luatex, xetex, enctex or mltex.

This is done in a way largely compatible with older releases: `utf8.def` is input just as if

`\usepackage[utf8]{inputenc}`

had been used, however rather than input the whole package a minimal core part just enough to support loading the UTF-8 encoding files is defined here.

If a document re-specifies UTF-8 this is silently ignored.

```
⟨/2ekernel⟩
⟨*2ekernel | latexrelease⟩
```

Check that a classic 8-bit tex engine is being used (LaTeX or PDFLaTeX).

```
⟨latexrelease⟩\IncludeInRelease{2018/04/01}%
⟨latexrelease⟩                  {\UTFviii@invalid}{UTF-8 default}%
```

Skip this section in Unicode TeX, or if MLTeX and EncTeX are enabled.

```
\ifnum0%
  \ifx\Umathcode\@undefined\else 1\fi
  \ifx\mubyte\@undefined\else 1\fi
  \ifx\charsubdef\@undefined\else 1\fi
  =\z@
```

```
\def\saved@space@catcode{10}
\let\@inpenc@test\relax
\def\IeC{%
  \ifx\protect\@typeset@protect
    \expandafter\@firstofone
  \else
    \noexpand\IeC
  \fi
}
```

Make characters active for UTF-8 input formats

```
\@tempcnta=1
\loop
  \catcode\@tempcnta=13  %
  \advance\@tempcnta\@ne %
\ifnum\@tempcnta<32      %
\repeat                  %
\catcode0=15  % null
\catcode9=10  % tab
\catcode10=12 % ctrl J
\catcode12=13 % ctrl L
\catcode13=5  % newline
\@tempcnta=128
\loop
  \catcode\@tempcnta=13
  \advance\@tempcnta\@ne
\ifnum\@tempcnta<256
\repeat
```

`\UseRawInputEncoding` Reset 8 bit characters to catcode 12 so the input encoding matches the "Raw" font encoding. Useful for special behaviours, or for compatibility with older LaTeX formats.

```
\def\UseRawInputEncoding{%
\let\inputencodingname\@undefined                      % revert
\let\DeclareFontEncoding@\DeclareFontEncoding@saved   % revert
\let\DeclareUnicodeCharacter\@undefined                % revert
\@tempcnta=1
\loop
  \catcode\@tempcnta=15  %
  \advance\@tempcnta\@ne %
\ifnum\@tempcnta<32      %
\repeat                  %
\catcode0=15  % null
\catcode9=10  % tab
```

```
\catcode10=12 % ctrl J
\catcode12=13 % ctrl L
\catcode13=5  % newline
\@tempcnta=128
\loop
  \catcode\@tempcnta=12
  \advance\@tempcnta\@ne
\ifnum\@tempcnta<256
\repeat
}
```

(*End definition for* `\UseRawInputEncoding`.)

`\DeclareFontEncoding@saved` Saved version of `\DeclareFontEncoding@` before `utf8.def` modifies it for use in `\UseRawInputEncoding` above.

```
\let\DeclareFontEncoding@saved\DeclareFontEncoding@
```

(*End definition for* `\DeclareFontEncoding@saved`.)

```
\edef\inputencodingname{utf8}%
\input{utf8.def}
\let\UTFviii@undefined@err@@\UTFviii@undefined@err
\let\UTFviii@invalid@err@@\UTFviii@invalid@err
\let\UTFviii@two@octets@@\UTFviii@two@octets
\let\UTFviii@three@octets@@\UTFviii@three@octets
\let\UTFviii@four@octets@@\UTFviii@four@octets
⟨2ekernel⟩\def\UTFviii@undefined@err#1{\@gobble#1}%
⟨2ekernel⟩\let\UTFviii@invalid@err\string
⟨2ekernel⟩\let\UTFviii@two@octets\string
⟨2ekernel⟩\let\UTFviii@three@octets\string
⟨2ekernel⟩\let\UTFviii@four@octets\string
⟨2ekernel⟩\everyjob\expandafter{\the\everyjob
⟨2ekernel⟩\let\UTFviii@undefined@err\UTFviii@undefined@err@@
⟨2ekernel⟩\let\UTFviii@invalid@err\UTFviii@invalid@err@@
⟨2ekernel⟩\let\UTFviii@two@octets\UTFviii@two@octets@@
⟨2ekernel⟩\let\UTFviii@three@octets\UTFviii@three@octets@@
⟨2ekernel⟩\let\UTFviii@four@octets\UTFviii@four@octets@@
⟨2ekernel⟩}
\let\@inpenc@test\@undefined
\let\saved@space@catcode\@undefined
```

For formats not set up for UTF-8 default, set the C0 controls to catcode 15.

```
\else
\@tempcnta=0
\loop
  \catcode\@tempcnta=15  %
  \advance\@tempcnta\@ne %
\ifnum\@tempcnta<32      %
\repeat                  %
\catcode0=15  % null
\catcode9=10  % tab
\catcode10=12 % ctrl J
\catcode12=13 % ctrl L
\catcode13=5  % newline
```

```
\let\UseRawInputEncoding\relax
```

This ends the skipped code in Unicode engines:

```
\fi
⟨/2ekernel | latexrelease⟩
⟨latexrelease⟩\EndIncludeInRelease
⟨latexrelease⟩\IncludeInRelease{0000/00/00}%
⟨latexrelease⟩                  {\UTFviii@invalid}{UTF-8 default}%
```

The first block of commands got only introduced in 2019 but we revert all of Unicode support in one go not jump to the intermediate version.

```
⟨latexrelease⟩  \let\UTFviii@two@octets@combine\@undefined
⟨latexrelease⟩  \let\UTFviii@three@octets@combine\@undefined
⟨latexrelease⟩  \let\UTFviii@four@octets@combine\@undefined
⟨latexrelease⟩  \let\UTFviii@two@octets@string\@undefined
⟨latexrelease⟩  \let\UTFviii@three@octets@string\@undefined
⟨latexrelease⟩  \let\UTFviii@four@octets@string\@undefined
⟨latexrelease⟩  \let\UTFviii@two@octets@noexpand\@undefined
⟨latexrelease⟩  \let\UTFviii@three@octets@noexpand\@undefined
⟨latexrelease⟩  \let\UTFviii@four@octets@noexpand\@undefined
```

```
⟨latexrelease⟩\@tempcnta=0
⟨latexrelease⟩\loop
⟨latexrelease⟩  \catcode\@tempcnta=15
⟨latexrelease⟩  \advance\@tempcnta\@ne
⟨latexrelease⟩\ifnum\@tempcnta<32
⟨latexrelease⟩\repeat       %
⟨latexrelease⟩\catcode9=10  % tab
⟨latexrelease⟩\catcode10=12 % ctrl J
⟨latexrelease⟩\catcode12=13 % ctrl L
⟨latexrelease⟩\catcode13=5  % newline
⟨latexrelease⟩\@tempcnta=128
⟨latexrelease⟩\loop
⟨latexrelease⟩\catcode\@tempcnta=12
⟨latexrelease⟩\advance\@tempcnta\@ne
⟨latexrelease⟩\ifnum\@tempcnta<256
⟨latexrelease⟩\repeat
⟨latexrelease⟩\let\IeC\@undefined
⟨latexrelease⟩\def\DeclareFontEncoding@#1#2#3{%
⟨latexrelease⟩  \expandafter
⟨latexrelease⟩  \ifx\csname T@#1\endcsname\relax
⟨latexrelease⟩     \def\cdp@elt{\noexpand\cdp@elt}%
⟨latexrelease⟩     \xdef\cdp@list{\cdp@list\cdp@elt{#1}%
⟨latexrelease⟩                    {\default@family}{\default@series}%
⟨latexrelease⟩                    {\default@shape}}%
⟨latexrelease⟩     \expandafter\let\csname#1-cmd\endcsname\@changed@cmd
⟨latexrelease⟩  \else
⟨latexrelease⟩     \@font@info{Redeclaring font encoding #1}%
⟨latexrelease⟩  \fi
⟨latexrelease⟩  \global\@namedef{T@#1}{#2}%
⟨latexrelease⟩  \global\@namedef{M@#1}{\default@M#3}%
⟨latexrelease⟩  \xdef\LastDeclaredEncoding{#1}%
⟨latexrelease⟩  }
⟨latexrelease⟩  \let\UseRawInputEncoding\@undefined
⟨latexrelease⟩  \let\DeclareFontEncoding@saved\@undefined
⟨latexrelease⟩  \let\inputencodingname\@undefined
⟨latexrelease⟩\EndIncludeInRelease
```

```
⟨*2ekernel⟩
%    \begin{macrocode}
%
% We temporarily define |\reserved@a| to apply |\reserved@c| to all the
% numbers in the range of its arguments.
%    \begin{macrocode}
\def\reserved@a#1#2{%
   \@tempcnta#1\relax
   \@tempcntb#2\relax
   \reserved@b
}
\def\reserved@b{%
   \ifnum\@tempcnta>\@tempcntb\else
      \reserved@c\@tempcnta
      \advance\@tempcnta\@ne
      \expandafter\reserved@b
   \fi
}
```

Set the special catcodes (although some of these are useless, since an error will have occurred if the catcodes have changed). Note that `^^J` has catcode 'other' for use in warning messages.

```
\catcode`\ =10
\catcode`\#=6
\catcode`\$=3
\catcode`\%=14
\catcode`\&=4
\catcode`\\=0
\catcode`\^=7
\catcode`\_=8
\catcode`\{=1
\catcode`\}=2
\catcode`\~=13
\catcode`\@=11
\catcode`\^^I=10
\catcode`\^^J=12
\catcode`\^^L=13
\catcode`\^^M=5
```

Set the 'other' catcodes.

```
\def\reserved@c#1{\catcode#1=12\relax}
\reserved@c{`\!}
\reserved@c{`\"}
\reserved@a{`\'}{`\?}
\reserved@c{`\[}
\reserved@c{`\]}
\reserved@c{`\`}
\reserved@c{`\|}
```

Set the 'letter' catcodes.

```
\def\reserved@c#1{\catcode#1=11\relax}
\reserved@a{`\A}{`\Z}
\reserved@a{`\a}{`\z}
```

All the characters in the range 0–31 and 127–255 are illegal, *except* tab (`^^I`), nl (`^^J`), ff (`^^L`) and cr (`^^M`).

1.7 Lccodes and uccodes

We now again set up the default (T1) uc/lccodes. The lower case characters need their `\uccode` and `\lccode` values set. Some of this is a repeat of the set-up before loading hyphenation files. Depending on the TEX version, we might not be allowed to do this for non-ASCII characters. For the Unicode engines (XeTEX and LuaTEX) there is no need to do any of this: they use hyphenation data which does not alter any of the set up and so this entire block is skipped.

```
\ifnum 0%
  \ifx\Umathcode\@undefined\else 1\fi
  \ifx\XeTeXmathcode\@undefined\else 1\fi
  >\z@
\else
\def\reserved@c#1{%
   \count@=#1\advance\count@ by -"20
   \uccode#1=\count@
   \lccode#1=#1
}
\reserved@a{`\a}{`\z}
\reserved@a{"A0}{"BC}
\reserved@a{"E0}{"FF}
```

The upper case characters need their `\uccode` and `\lccode` values set, and their `\sfcode` set to 999.

```
\def\reserved@c#1{%
   \count@=#1\advance\count@ by "20
   \uccode#1=#1
   \lccode#1=\count@
   \sfcode#1=999
}
\reserved@a{`\A}{`\Z}
\reserved@a{"80}{"9C}
\reserved@a{"C0}{"DF}
```

Well, it would be nice if that were correct, but unfortunately, the Cork encoding contains some odd slots whose uccode or lccode isn't quite what you'd expect.

```
\uccode`\^^Y=`\I     % dotless i
\lccode`\^^Y=`\^^Y   % dotless i
\uccode`\^^Z=`\J     % dotless j, ae in OT1
\lccode`\^^Z=`\^^Z   % dotless j, ae in OT1
\lccode`\^^9d=`\i    % dotted I
\uccode`\^^9d=`\^^9d % dotted I
\lccode`\^^9e=`\^^9e % d-bar
\uccode`\^^9e=`\^^d0 % d-bar
```

Finally here is one that helps hyphenation in the OT1 encoding.

```
\lccode`\^^[=`\^^[   % oe in OT1
\fi % End of reset block for 8-bit engines
```

`\MakeUppercase`
`\MakeUppercase`
`\NoCaseChange`
`\@uclclist`
`\@expl@text@lowercase@@n`
`\@expl@text@uppercase@@n`
`\@uclclist`

And whilst we're doing things with uc/lc tables, here are two commands to upper- and lower-case a string.

Note that this implementation is subject to change! At the moment we're not providing any way to extend the list of uc/lc commands, since finding a good interface is difficult. These commands have some nasty features, such as uppercasing mathematics,

environment names, labels, etc. A much better long-term solution is to use all-caps fonts, but these aren't generally available.

Two wrappers around the L3 case changing functions. `\protected` to make them mostly safe as replacements for `uppercase` and `\lowercase`.

```
\ExplSyntaxOn
\protected\def\@expl@text@lowercase@@n{\text_lowercase:n}
\protected\def\@expl@text@uppercase@@n{\text_uppercase:n}
```

`\NoCaseChange` protects its argument from the case change functions.

```
\tl_put_right:Nn \l_text_case_exclude_arg_tl  { \NoCaseChange }
\cs_new_protected:Npn \NoCaseChange #1 {#1}
\ExplSyntaxOff
```

```
\DeclareRobustCommand{\MakeUppercase}[1]{{%
      \def\i{I}\def\j{J}%
      \def\reserved@a##1##2{\let##1##2\reserved@a}%
      \expandafter\reserved@a\@uclclist\reserved@b{\reserved@b\@gobble}%
```

Tell UTF-8 processing to process chars even though we are in an `\protected@edef`.

```
      \protected@edef\reserved@a{\@expl@text@uppercase@@n{\noexpand\unexpanded{#1}}}%
      \reserved@a
   }}
\DeclareRobustCommand{\MakeLowercase}[1]{{%
      \def\reserved@a##1##2{\let##2##1\reserved@a}%
      \expandafter\reserved@a\@uclclist\reserved@b{\reserved@b\@gobble}%
      \protected@edef\reserved@a{\@expl@text@lowercase@@n{\noexpand\unexpanded{#1}}}%
      \reserved@a
   }}
```

```
\def\@uclclist{\oe\OE\o\O\ae\AE
      \dh\DH\dj\DJ\l\L\ng\NG\ss\SS\ij\IJ\th\TH}
```

The above code works, but has the nasty side-effect that if you say something like:

```
\markboth{\MakeUppercase\contentsname}
         {\MakeUppercase\contentsname}
```

then the uppercasing is only done to the first letter of the contents name, since the mark expands out to:

```
\mark{\protect\MakeUppercase Table of Contents}
     {\protect\MakeUppercase Table of Contents}
```

In order to get round this, we redefine `\MakeUppercase` and `\MakeLowercase` to grab their argument and brace it. This is a very low-level hack, and is *not* recommended practice! This is an instance of a general problem that makes it unsafe to grab arguments unbraced, and probably needs a more general solution. For the moment though, this hack will do:

```
\protected@edef\MakeUppercase#1{\MakeUppercase{#1}}
\protected@edef\MakeLowercase#1{\MakeLowercase{#1}}
```

(*End definition for* `\MakeUppercase` *and others.*)

1.8 Applying Patch files

Between major releases, small patches will be distributed in files `ltpatch.ltx` which must be added at this point.

Patch file code removed.

```
%\IfFileExists{ltpatch.ltx}
%  {\typeout{================================^^J%
%             Applying patch file ltpatch.ltx^^J%
%            ================================}
%   \def\fmtversion@topatch{unknown}
%   \input{ltpatch.ltx}
%   \ifx\fmtversion\fmtversion@topatch
%      \ifx\patch@level\@undefined
%        \typeout{^^J^^J^^J%
%         !!!!
```

```
\let\reserved@a\@filelist
\let\reserved@b=\@undefined
\let\reserved@c=\@undefined
\let\reserved@d=\@undefined
\let\reserved@e=\@undefined
\let\reserved@f=\@undefined
```

(*End definition for* `\reserved@a` *and* `\reserved@b`.)

`\toks`

```
\toks0{}
\toks2{}
\toks4{}
\toks6{}
\toks8{}
```

(*End definition for* `\toks`.)

`\errhelp` Empty the error help message, which may have some rubbish:

```
\errhelp{}
```

(*End definition for* `\errhelp`.)

1.10 Initialise file list

`\@providesfile` Initialise for use in the document. During initex a modified version has been used which leaves debugging information for `latexbug.tex`.

```
\def\@providesfile#1[#2]{%
    \wlog{File: #1 #2}%
    \expandafter\xdef\csname ver@#1\endcsname{#2}%
  \endgroup}
```

(*End definition for* `\@providesfile`.)

`\@filelist` `\@addtofilelist` Reset `\@filelist` so files input while making the format are not listed. The list built up so far may take up a lot of memory and so it is moved to `\reserved@a` where it will be overwritten as soon as almost any LaTeX command is issued in a class file. However the `latexbug.tex` program will be able to access this information and insert it into a bug report.

```
\let\@filelist\@gobble
\def\@addtofilelist#1{\xdef\@filelist{\@filelist,#1}}%
```

(*End definition for* `\@filelist` *and* `\@addtofilelist`.)

1.11 Preparation for supporting PDF in backends

At the current point in time, basic support for PDF in backends is not part of LaTeX core; it is provided by external packages. At some time in the future that work will be placed into the kernel but for now it is separate and has to be explicitly loaded in the document.

In that code there is a command `\IfPDFManagementActiveTF` which can be used by packages in order to execute different code depending on the whether this basic backend support is loaded.

To make this also work properly when this external package is not loaded at all, we here add this command already in the kernel (with a trivial definition); thus any package can query this loading state in all circumstances. Once this basic PDF backend support gets moved to the kernel, this definition will vanish again from here or, rather, it will be replaced by a real test.

`\IfPDFManagementActiveTF` So long as the code for the basic backend support for PDF is not loaded, the test that is implicit here will always return the false branch. Once this code is loaded, this definition will get replaced by a real test (as it is then possible that the management code is either activated or not activated).

```
\let \IfPDFManagementActiveTF \@secondoftwo
```

(*End definition for* `\IfPDFManagementActiveTF`.)

1.12 Do some temporary work for pre-release

This is a good place to load code that hasn't yet been integrated into the other files ...

1.13 Some last minute initializations ...

Load the first aid set of definitions for external packages that await updates.

```
\@input{latex2e-first-aid-for-external-files.ltx}
```

1.14 Dumping the format

Finally we make `@` into a letter, ensure the format will be in the 'normal' error mode, and dump everything into the format file.

```
\makeatother
\errorstopmode
\dump
⟨/2ekernel⟩
```

Change History

1985-11-04 ltmath.dtx LaTeX2.09
- General: produce warning message if line extends into margin. Doesn't warn about formula overprinting equation number. 648

1989-04-10 ltfssbas.dtx v1.0a
- General: Starting with version numbers! `\ifmmode` added in `\math@group` 410

1989-04-10 ltfssbas.dtx v1.0b
- General: `\preload@sizes` added. . . 410
- `\wrong@fontshape` changed to define substitution font/shape macro. 410

1989-04-10 ltfssini.dtx v1.0a
- General: Starting with version numbers `\newif` for `\@tempswa` added since this switch is unknown at the time when this file is read in. (latex.tex is loaded later.) `\math@famname` changed to `\math@version`. 518

1989-04-14 ltfssbas.dtx v1.0c
- General: More documentation added. 410

1989-04-15 ltfssini.dtx v1.0b
- General: `\mathfontset` renamed to `\mathversion`. 518

1989-04-19 ltfssbas.dtx v1.0d
- General: Even more doc. 410

1989-04-21 ltfssbas.dtx v1.0e
- General: Documentation is fun! Parameters of `\define@mathalphabet` changed. 410

1989-04-21 ltfssini.dtx v1.0c
- General: Changed to conform to fam.tex. 518

1989-04-23 ltfssbas.dtx v1.0f
- General: % in `\getanddefinefonts` added. 410

1989-04-26 ltfssini.dtx v1.0d
- General: `\xpt` added. 518

1989-04-27 ltfssbas.dtx v1.0g
- General: Documentation revised. . . 410

1989-04-27 ltfssini.dtx v1.0e
- General: Definitions of LaTeX symbols corrected. 518

1989-04-29 ltfssbas.dtx v1.0h
- General: Documented problem with `\halign`, and `\noalign` 410
- `\mathversion`: Test if version defined added. 421

1989-04-29 ltfssbas.dtx v1.0i
- General: Removed the `\halign` `\noalign` correction (wasn't bugfree) 410

1989-04-29 ltfssini.dtx v1.0f
- General: Corrections to LaTeX tabular env. added. 518

1989-05-01 ltfssbas.dtx v1.0j
- General: Default for `\baselinestretch` added. 410

1989-05-22 ltfssbas.dtx v1.0k
- General: Lines longer than 72 characters folded. 410

1989-05-22 ltfssini.dtx v1.0g
- General: Lines shortened to 72 characters 518

1989-09-14 ltfssbas.dtx v1.0m
- General: Global replacement: `\group` to `\mathgroup` 410
- `\mathversion`: Corrected typo: `\endscname` to `\endcsname`. 421

1989-11-07 ltfssini.dtx v1.0i
- General: All family, series, and shape names abbreviated. 518

1989-11-08 ltfssbas.dtx v1.0o
- General: First parameter of `\define@mathalphabet` and `\define@mathgroup` changed from string to control sequence. 410

1989-11-14 ltfssbas.dtx v1.0p
- `\math@version`: Math version prefix 'mv@' added. 421

1989-11-19 ltfssbas.dtx v1.0q
- `\define@newfont`: Group added. . . 423
- `\wrong@fontshape`: Instead of calling `\family\default@family`, etc. we directly set `\f@family`, etc. 428

1989-11-22 ltfssbas.dtx v1.0r
- `\math@version`: `\def` → `\edef` for `\math@version`. 421

1989-11-25 ltfssbas.dtx v1.0s
- General: All `\edef\font@name` changed to `\xdef\font@name`. Necessary after introduction of `\begingroup`/`\endgroup` in v1.0q. 410
- extra// → + in `\extra@def`. . . . 410

1989-11-26 ltfssbas.dtx v1.0t
\select@group: \bgroup/\egroup changed to \begingroup/\endgroup to avoid empty Ord atom on math list. . . 430
1989-12-02 ltfssini.dtx v1.1b
General: \rmmath renamed to \mathrm 518
1989-12-03 ltfssini.dtx v1.1c
General: Some internal macros renamed to make them inaccessible. 518
1989-12-05 ltfssbas.dtx v1.0u
\addto@hook: \addto@hook added. . 435
1989-12-05 ltfsstrc.dtx v1.0u fam.dtx
\every@math@size: Hook \every@size added. 467
1989-12-13 ltfsstrc.dtx v1.0f
\use@mathgroup: \expandafter added before final \fi. 470
1989-12-16 ltfssbas.dtx v1.1a
\select@group: \relax in front added. 430
Now four arguments. 430
Redefinition of alphabet now simpler. 431
Usage of '=' macro added. 431
1989-12-16 ltfsstrc.dtx v1.1a
\selectfont: Changed order of calls. 462
\use@mathgroup: Redefinition of alphabet now simpler. 469
Usage of '=' macro added. 469
1990-01-18 ltfsstrc.dtx v1.0h
General: \tracingfonts meaning changed. 458
1990-01-20 ltfssbas.dtx v1.2a
\math@bgroup: Def. placed in this file. 433
\math@egroup: Def. placed in this file. 433
\select@group: Def for alph id changed. 431
1990-01-21 ltfssbas.dtx v1.2b
\select@group: Code moved to \use@mathgroup. 431
1990-01-21 ltfsstrc.dtx v1.2b
\use@mathgroup: Macro added to allow cleaner interface. 469
1990-01-23 ltfssbas.dtx v1.2c
General: \no@version@warning renamed to \no@alphabet@error. 410
Macro \no@alphabet@help added 410
\no@alphabet@error: Changed to error call 410
1990-01-25 ltfssini.dtx v1.1e
\nfss@text: Macro added. 541
1990-01-27 ltfssbas.dtx v1.2d
\DeclarePreloadSizes: Font identifier set to \relax. 416
1990-01-28 ltfssbas.dtx v1.2e
\mathgroup: \newfam let to \new@mathgroup. 410
1990-01-28 ltfssbas.dtx v1.2f
\define@newfont: Added call to \curr@fontshape macro to allow substitution. 423
\wrong@fontshape: Warning message slightly changed. 428
1990-01-28 ltfssini.dtx v1.2b
\em: Call to \@nomath added. 538
1990-02-08 ltfssini.dtx v1.1g
General: Protected the commands \family, \series, \shape, \size, \selectfont, and \mathversion. 518
1990-02-16 ltfssbas.dtx v1.2g
General: Support for changes of \baselineskip without changing the size. 410
\math@version: \@nomath added. . . 421
1990-02-18 ltfsstrc.dtx v1.0j
\selectfont: Redefine unprotected version \p@selectfont instead of \selectfont. 462
1990-03-14 ltfsstrc.dtx v1.0k
General: Added code for TeX3. . . . 458
\extract@font: Added code for TeX3. 461
1990-03-30 ltfssbas.dtx v1.2h
\math@egroup: Changed to have one arg. 433
1990-03-30 ltfsstrc.dtx v1.2h
\use@mathgroup: Third argument removed (see \math@egroup). . . . 469
1990-04-01 ltfssbas.dtx v1.2i
General: Code added from tracefnt.dtx. 410
Support for TeX3. 410
1990-04-01 ltfsstrc.dtx v1.0l
General: Part of code moved to fam.dtx. 458
\tracingfonts: Check if \tracingfonts already defined. . 459
1990-04-01 ltfsstrc.dtx v1.0o
\tracingfonts: Check if \tracingfonts defined removed again. 459

1990-04-02 ltfssini.dtx v1.1i
General: \input of files now handled by docstrip. 518
1990-04-05 ltfsstrc.dtx v1.0m
\selectfont: Call \tracingon only if \tracingfonts greater than 3. . 462
1990-05-05 ltfsstrc.dtx v1.0n
\selectfont: \tracingon with new syntax. 462
1990-06-23 ltfssini.dtx v1.1k
\nfss@text: Changed to \mbox. . . . 541
1990-06-24 ltfssbas.dtx v1.2j
\DeclarePreloadSizes: Missing percent added. 416
1990-06-24 ltfsstrc.dtx v1.0o
\baselinestretch: Moved to tracefnt.dtx. 467
\getanddefine@fonts: \Adding tracing code. 471
\Macro moved from fam.dtx. . . . 470
Adding debug code. 470
\use@mathgroup: Tracing code added. 470
1990-06-30 ltfssbas.dtx v1.2l
\showhyphens: Macro added. 433
1990-06-30 ltfsstrc.dtx v1.0p
\use@mathgroup: Added \relax after math group number. 470
1990-07-07 ltfsstrc.dtx v1.0q
\getanddefine@fonts: Group number added to tracing. 471
\math@egroup: Tracing code added. 470
\use@mathgroup: Group number added to tracing. 470
1990-08-27 ltfsstrc.dtx 1.0r
\type@restoreinfo: Some extra tracing info. 466
1990-08-27 ltfsstrc.dtx v1.0r
\getanddefine@fonts: Correcting missing name after \tracingon. . 470
1991-03-28 ltfssini.dtx v1.1m
\copyright: Extra braces added. . . 541
1991-03-30 ltfssini.dtx v1.2g
\newfont: Definition added. 540
\symbol: Definition added. 540
1991-07-24 ltmiscen.dtx LaTeX2.09
\@verbatim: Added \penalty\interlinepenalty to definition of \par so that \samepage works 633
1991-08-14 ltmath.dtx LaTeX2.09
\cases: (RmS) inserted extra braces around entry for NFSS 643
1991-08-14 ltpictur.dtx LaTeX2.09
General: (RmS) inserted extra braces around entry for NFSS 716
1991-08-14 ltthm.dtx LaTeX2.09
\@endtheorem: Moved \itshape after \item to make it work with NFSS 746
1991-08-26 ltfssini.dtx v1.1n
\reset@font: Macro introduced . . . 541
1991-08-26 ltmiscen.dtx LaTeX2.09
\@verbatim: \@@par added 633
1991-08-26 ltpictur.dtx LaTeX2.09
\endpicture: (RmS & FMi) extra boxing level around \@picbox to guard against unboxing in math mode (proposed by John Hobby) 714
1991-08-26 ltplain.dtx LaTeX209
\tracingall: Added \errorcontextlines=\maxdimen, suggested by J. Schrod 35
1991-09-29 ltboxes.dtx LaTeX2.09
\@mpfootnotetext: (RmS) added \reset@font 682
1991-09-29 ltfloat.dtx LaTeX2.09
\@footnotetext: (RmS) added \reset@font 779
1991-09-29 ltmath.dtx LaTeX2.09
\@eqnnum: RmS: \reset@font added. 648
1991-09-29 ltsect.dtx LaTeX2.09
\@dottedtocline: (RmS) added \reset@font for page number . . 758
1991-10-17 ltcntrl.dtx LaTeX209
\@tfor: (Rms) \xdef replaced by \def (See FMi's array.doc) 280
1991-10-25 ltbibl.dtx LaTeX2.09
\@citex: added \reset@font, suggested by Bernd Raichle. . . . 788
1991-11-01 ltfloat.dtx LaTeX2.09
\footnote: (RmS) Added \let\protect\noexpand in \footnote, \footnotemark, and \footnotetext, since \xdef is used 779
1991-11-04 ltlists.dtx LaTeX2.09
\makelabel: (RmS) added default definition for \makelabel, to produce an error message. 667
1991-11-04 ltplain.dtx RmS
General: Removed \itemitem since never needed/useful with LaTeX. . 33
1991-11-06 ltbibl.dtx LaTeX2.09
\@citex: added code to remove a leading blank 788

1991-11-13 ltbibl.dtx LaTeX2.09
\@bibitem: Changed counter enumi to enumiv, as it says in the comment above 787
1991-11-21 ltfssini.dtx v1.1o
\reset@font: Added extra braces for robustness. 541
Changed to protected version of macro. 541
1991-11-22 ltfloat.dtx LaTeX2.09
\footnote: (RmS) Added \let\protect\noexpand in \@xfootnote, \@xfootnotemark, and \@xfootnotetext 779
1991-11-22 ltlists.dtx LaTeX2.09
\@item: (RmS) Changed second call to \makelabel to \unhbox\@tempboxa. Avoids problems with side effects in \makelabel and is more efficient. 667
1991-11-27 ltfssbas.dtx v1.3a
General: All \family, \shape etc. renamed to \fontfamily etc. . . . 410
1991-11-27 ltfssini.dtx v1.2a
General: All \family, \shape etc. renamed to \fontfamily etc. . . . 518
1992-01-06 ltfssini.dtx v1.2c
General: added slitex code 518
1992-01-10 ltbibl.dtx LaTeX2.09
\@bibitem: Changed \c@enumiv to \value of \@listctr 787
1992-01-10 ltmath.dtx LaTeX2.09
equation: RmS: put \hbox around \@eqnnum to typeset the equation number in text mode (as in the eqnarray env.) 648
1992-01-10 ltthm.dtx LaTeX2.09
\@othm: (RmS) Check for existence of theorem environment 745
1992-01-14 ltbibl.dtx LaTeX2.09
\@biblabel: removed \hfill 790
1992-01-14 ltsect.dtx 0.0
\@starttoc: (RmS) added \immediate to \openout as all \write commands are also executed \immediate 756
1992-02-26 ltbibl.dtx LaTeX2.09
\@lbibitem: Added \hfill to restore left-alignment of bibliography labels in alpha style 787
1992-03-18 ltdefns.dtx LaTeX209
General: (RMS) changed input channel from 0 to \@inputcheck to avoid conflicts with other channels allocated by \newread 80
1992-03-18 ltfloat.dtx LaTeX2.09
\@xympar: (RmS) added \global\@ignorefalse 774
\end@float: (RmS) changed \@esphack to \@Esphack 768
1992-03-18 ltlists.dtx 0.0
\trivlist: RmS: added \@nmbrlistfalse 663
1992-03-18 ltmiscen.dtx LaTeX2.09
\begin: Changed \@ignoretrue to \@ignorefalse (as documented) 625
1992-03-21 ltfssini.dtx v1.2d
General: Renamed \text to \nfss@text to make it internal. . 518
1992-05-12 ltfssbas.dtx v1.3c
\extract@alph@from@version: Macro added. 432
\select@group: Added call to \extract@alph@from@version. . 431
1992-07-26 ltfssbas.dtx v1.9a
\curr@fontshape: 423
\DeclareFontShape: Introduced \DeclareFontShape 411
\define@newfont: 423
\math@fonts: 430
\select@group: 431
\split@name: Added splitting into \f@encoding. 423
\wrong@fontshape: 428
1992-07-26 ltfsstrc.dtx v2.0b
\s@fct@: 479
\s@fct@sub: documentation fixes . . 480
\selectfont: 463
\try@simple@size: 473
\try@size@range: 477
\use@mathgroup: 470
1992-08-14 ltbibl.dtx LaTeX2.09
\@citex: added missing argument braces around \hbox, found by Ed Sznyter 788
1992-08-14 ltboxes.dtx LaTeX209
\endminipage: (RmS) replaced \vskip-\lastskip by \unskip (proposed by FMi) 681
1992-08-17 ltbibl.dtx LaTeX2.09
\@citex: simplified code for removing leading blanks in citation key (proposed by Frank Jensen and Kresten Krab Thorup) 788
1992-08-19 ltsect.dtx 0.0
\@xsect: (RmS) corrected bug: stretch and shrink in argument to \hskip

previously not negated 752
1992-08-19 ltthm.dtx LaTeX2.09
\\@othm: (RmS) Changed error message to complain about undefined counter 745
1992-08-20 ltfssini.dtx v1.4b
\\@setsize: Added \\@currsize. . . . 540
1992-08-24 ltdefns.dtx LaTeX209
\\@ifnextchar: (Rms) \\@ifnextchar didn't work if its first argument was an equal sign. 102
1992-08-24 ltmiscen.dtx LaTeX2.09
\\begin: Added code to \\begin to remember line number. Used by \\@badend to display position of non-matching \\begin. 625
\\verb: Changed \\verb and \\@sverb to work correctly in math mode . . . 638
1992-08-25 ltsect.dtx LaTeX2.09
\\@sect: (FMi) replaced explicit setting of \\@svsec by call to \\@seccntformat 751
1992-09-18 ltlists.dtx LaTeX2.09
\\item: (RmS) Added warning if \\item is used in math mode 665
1992-09-18 lttab.dtx LaTeX2.09
\\@array: Changed \\par to \\@empty to avoid starting new row e.g. after \\hline 699
1992-09-19 ltfsstrc.dtx v2.0c
\\try@simple@size: 473
1992-09-21 ltfssini.dtx v1.4d
\\not@math@alphabet: Macro defined. 539
1992-09-22 ltfssbas.dtx v1.91a
General: Introduced \\tf@size for math size. 410
1992-09-22 ltfsstrc.dtx v2.1a
\\getanddefine@fonts: Introduced \\tf@size for math size. 471
1992-11-13 ltfssini.dtx v?
\\hexnumber@: Made expandable. . . . 541
1992-11-23 ltcounts.dtx LaTeX209
\\stepcounter: Replaced {} in \\stepcounter by \\begingroup \\endgroup to avoid adding an empty ord in math mode 402
1992-11-26 ltboxes.dtx LaTeX2.09
\\@mpfootnotetext: (RmS) added protection for \\edef 682
1992-11-26 ltfloat.dtx LaTeX2.09
\\@footnotetext: (RmS) added protection for \\edef 779
\\footnote: (RmS) Changed all to 'def'protect'noexpand'protect'noexpand 779
1992-12-03 ltfssini.dtx v?
\\hexnumber@: Make it accept counters. 541
1993-03-08 preload.dtx v2.0b
General: Added 12pt preloads 567
1993-03-18 ltfssbas.dtx v2.0c
General: Changed all \\@tempdima in \\@tempdimb to avoid killing \\numberline 410
1993-03-18 ltfsstrc.dtx v2.1b
General: Changed all \\@tempdima in \\@tempdimb to avoid killing \\numberline 458
Changed all \\@tempdimb in \\@tempdimx to avoid killing \\numberline 458
1993-03-18 ltfsstrc.dtx v2.1c
\\DeclareSizeFunction: Added all args to avoid blanks problems . . 476
1993-04-09 lterror.dtx v1.0e
\\@latexerr: Mention The Companion 287
1993-04-11 lterror.dtx v1.0f
\\@latexerr: Remove setting of errorcontextlines 287
1993-05-05 ltfntcmd.dtx v2.0b
General: Removed all LaTeX related cmds 570
1993-05-16 ltfssbas.dtx v2.0e
\\showhyphens: Use \\reset@font . . 433
1993-07-16 ltfsstrc.dtx v2.1h
General: Changed layout of info messages 458
1993-07-17 ltoutenc.dtx 1.0d
General: changed \\catcoding @ . . . 357
1993-08-03 ltmiscen.dtx LaTeX2.09
\\enddocument: Changed redefinition of \\global to redefinition of \\@setckpt. 619
1993-08-05 ltpictur.dtx LaTeX2.09
\\circle: (RMS) Added error message if \\circle is used in math mode. 736
1993-08-05 ltsect.dtx LaTeX2.09
\\@sect: (RmS) Made sure that \\protect works correctly in expansion of \\the counter 751
1993-08-05 ltspace.dtx LaTeX2e
\\@hspace: (RmS) Removed superfluous \\leavevmode in \\@hspace and \\@hspacer, as suggested by CAR. 329

1993-08-05 lttab.dtx latex2e
\tabular*: Replaced \expandafter\def by \@namedef. 698
1993-08-06 ltbibl.dtx LaTeX2.09
\@citex: Moved writing to .aux file in loop over citation keys so that leading blanks are removed there as well. 788
1993-08-13 ltoutenc.dtx 1.0f
General: Protected against active @ sign. 357
1993-08-13 preload.dtx v2.0c
General: Added \relax at end of font names. 568
1993-08-16 ltoutenc.dtx 1.0g
General: Needs space after \string 357
1993-08-18 ltfssdcl.dtx v2.0e
\new@mathversion: Exchanged names of encodings in warning message of \SetSymbolFont. 499
1993-09-02 ltfsstrc.dtx v2.1i
General: Corrected name of sgen size function. 458
1993-09-03 ltmiscen.dtx LaTeX2.09
\verbatim@nolig@list: Replaced \@noligs by extensible list 638
1993-09-07 ltmiscen.dtx LaTeX2.09
\verb@balance@group: (RmS) Changed definition of \verb so that it detects a missing second delimiter. 637
1993-09-08 ltmiscen.dtx LaTeX2.09
\enddocument: Added warning in case of undefined references. 619
1993-09-15 ltfssbas.dtx v2.0g
\DeclareFontEncoding: Corrected: \default@T to \default@M. 414
1993-09-15 ltfsstrc.dtx v2.1j
General: Corrected spelling of \noxpand. 458
1993-09-19 lterror.dtx LaTeX2.09
\@invalidchar: (RmS) Error message for invalid input characters. 291
1993-11-02 ltmath.dtx LaTeX2.09
General: RmS: Corrected description of \@eqnsel, moved \@eqnsel accordingly and removed extra \tabskip assignment. 648
1993-11-03 ltmath.dtx LaTeX2e
General: RmS: Initialized \everycr to empty 648
1993-11-03 ltpictur.dtx LaTeX2.09
General: (RmS) changed \halign to \ialign to initialize \tabskip and \everycr 716
1993-11-11 ltfssini.dtx v2.1a
\normalfont: Macro added 541
1993-11-11 ltfsstrc.dtx v2.2a
General: Option concept added for LaTeX2e 458
1993-11-14 ltclass.dtx v0.2a
\@currext: Name changed from \@currextension 823
\@reset@ptions: macro added 849
\AtEndDocument: Included extension in the generated macro name for package and class hooks. 849
\documentstyle: Added \RequirePackage \@unusedoptionlist stuff. 838
\load@onefilewithoptions: Moved resetting of \default@ds, \ds@ and \@declaredoptions here, from the end of \ProcessOptions. 843
\NeedsTeXFormat: made more robust for alternative syntax for other formats. 840
\ProcessOptions*: Optimize 'empty option' code. 835
Stop adding the global option list inside class files. 835
1993-11-14 ltdefns.dtx v0.2a
\g@addto@macro: Made global 107
1993-11-15 ltclass.dtx v0.2b
\documentstyle: Modified to match \ProcessOption* 838
\ProcessOptions*: Star form added. 835
1993-11-17 ltclass.dtx v0.2c
\@@fileswith@pti@ns: Macro added 849
\@badrequireerror: Macro added . 851
\@twoloadclasserror: Macro added 851
\CurrentOption: Name changed from \@curroption 823
\DeclareOption*: Error checking added 833
\load@onefilewithoptions: Added trap for two \LoadClass commands. 845
\NeedsTeXFormat: Name changed from \NeedsFormat 840
\ProcessOptions*: restoring \@fileswith@pti@ns added. . . . 835
1993-11-18 ltclass.dtx v0.2d
\documentstyle: Modified \RequirePackage stuff. 838
\ExecuteOptions: Use \CurrentOption not \reserved@a 837

\NeedsTeXFormat: \fmtname \fmtversion not \@... 840
1993-11-21 ltfiles.dtx LaTeX2e
\@missingfileerror: Stop infinite looping on \@er@ext 350
1993-11-21 ltmiscen.dtx v0.9a
\@verbatim: use \verbatim@font instead of \tt 634
\verb: Use \verbatim@font instead of \tt. 638
\verbatim@font: Macro added 634
1993-11-22 ltclass.dtx v0.2f
\@fileswithoptions: Made the default [] not [\@unknownversion] 841
\@ifl@ter: Added //00 so parsing never produces a runaway argument. 828
General: \@unknownversion removed 818
\load@onefilewithoptions: Made the initial version [] not [\@unknownversion] 843
1993-11-22 ltdefns.dtx LaTeX2e
\@minus: Macro added 79
\@plus: Macro added 79
\CheckCommand: Macro added 86
\providecommand: Macro added 86
1993-11-22 lterror.dtx LaTeX2e
\c@errorcontextlines: Macro added 287
1993-11-22 ltfiles.dtx LaTeX2e
\listfiles: Removed checking for \@unknownversion 352
1993-11-22 ltlength.dtx LaTeX2e
\@settodim: Macro added 408
\@settopoint: Macro added 409
\settodepth: Macro added 408
\settoheight: Macro added 408
1993-11-22 ltlogos.dtx LaTeX2e
\LaTeXe: Macro added 331
1993-11-23 ltclass.dtx v0.2g
\@use@ption: Name changed from \@executeoption 837
General: Various macros now moved to latex.tex. 822
Warnings and errors now directly coded. 822
1993-11-23 ltdefns.dtx LaTeX2e
\@argdef: Macro added 82
\@ifundefined: Redefined to remove a trailing \fi 101
\@newcommand: Macro added 82
\@newenv: Macro interface changed . . 85
\@xargdef: Macro interface changed . 82
\@yargd@f: Avoid \@?@? token 83
Macro interface changed 83
\newcommand: Macro reimplemented and extended 81
\renewcommand: Macro reimplemented and extended 84
\renewenvironment: Macro reimplemented and extended 85
\two@digits: Macro added 78
1993-11-23 ltoutput.dtx v0.1a
\paperheight: Register added 938
\paperwidth: Register added 938
1993-11-23 ltoutput.dtx v0.1c
\@enlargepage: Command added . . 983
\@kludgeins: Insert added 982
\@makecol: Command changed 950
\@specialoutput: Command changed 943
\enlargethispage*: Commands added 983
1993-11-24 ltfntcmd.dtx v2.1a
\maybe@ic@: Use \t@st@ic 575
\t@st@ic: Macro added 576
1993-11-24 ltfssini.dtx v2.1a
General: Removed \xpt stuff 541
1993-11-24 ltlogos.dtx LaTeX2e
\LaTeX: Macro changed 331
1993-11-28 ltclass.dtx v0.2h
\@twoclasseserror: Macro added . 851
General: Assorted commands now in the kernel removed. 822
Directory syntax checking moved to dircheck.dtx 822
Primitive filenames now terminated by space not \relax. 822
\endfilecontents: Don't globally allocate a write stream (always use 15) 851
1993-11-28 ltfiles.dtx LaTeX2e
\@missingfileerror: Use filename parser from dircheck 350
1993-11-29 ltoutput.dtx v1.0b
\@makecol: \@makespecialcolbox added 950
\@makespecialcolbox: Command added 951
1993-11-29 ltplain.dtx LaTeX2e
General: All accents in decimals; suggested by Paul Taylor 34
1993-11-30 ltoutput.dtx v1.0c
\fl@tracemessage: Commands added 985
1993-12-01 fontdef.dtx v2.1a
General: Update for LaTeX2e 546
1993-12-01 ltoutput.dtx v1.0e
\@reinserts: Command added . . . 951
1993-12-03 ltboxes.dtx v0.1a
\@argrsbox: macro removed 684

\@begin@tempboxa: macro added . . 672
\@end@tempboxa: macro added 672
\@iirsbox: redefined to support \height 684
\@imakebox: macro modified 672
\@irsbox: redefined to support \height 684
\@isavebox: color support 675
extra group 675
\@isavepicbox: extra group 675
\@makebox: default changed from x to c 672
\@makepicbox: macro modified 673
\@savebox: default c not x 675
\bm@b: macros added 672
\endlrbox: macro added 676
\fbox: extra group 676
\lrbox: color support 675
macro added 675
\makebox: modified 671
\mbox: extra group 672
\minipage: Redefined to support extra optional arguments 680
\newsavebox: Pass the whole of arg 1 to \@ifdefinable 674
\parbox: Redefined to support extra optional arguments 678
\raisebox: redefined to support \height 684
\sbox: color support 675
extra group 675
\set@color: color support 674
macro added 674

1993-12-03 ltclass.dtx v0.2i
\@cls@pkg: Name changed to avoid clash with output routine. 850
General: \@onlypreamble: Many commands declared. 822
Removed obsolete \@documentclass 822

1993-12-03 lterror.dtx v1.0b
\@latexerr: Set \c@errorcontextlines to -1 . . . 287

1993-12-03 ltfssini.dtx v2.1a
General: update for LaTeX2e 518

1993-12-04 ltfilehook.dtx v0.9b
\unqu@tefilef@und: Macro added . 885

1993-12-04 ltfiles.dtx v0.9b
\@iinput: Macro reimplemented . . . 349
\@input: Macro reimplemented . . . 350
\IfFileExists@: Macro added 347
\input: Macro reimplemented 349

1993-12-05 ltfloat.dtx LaTeX2e
\@dblfloatplacement: Command changed 770
\@xfloat: Command changed 764

1993-12-05 ltoutput.dtx v1.0f
\@addtobot: Command changed . . . 964
\@addtocurcol: Command changed 966
\@addtodblcol: Command changed 976
\@addtonextcol: Command changed 973
\@addtotoporbot: Command changed 965
\@boxfpsbit: Command added . . . 988
\@flcheckspace: Command added . 990
\@flsetnum: Command added 990
\@flsettextmin: Command added . 990
\@flstop: Commands added 987
\@flupdates: Command added . . . 991
\@fpsadddefault: Command added 987
\@getfpsbit: Command added . . . 988
\@opcol: Command changed 949
Hook added 949
\@outputpage: Command changed . 953
\@resethfps: Command added . . . 989
\@setfloattypecounts: Command added 988
\@setfpsbit: Command added . . . 989
\@shipoutsetup: Command added . 953
\@startcolumn: Command changed 959
\@startdblcolumn: Command changed 959
\@testfp: Command added 989
\@textfloatsheight: Commands added 987
\@topnewpage: Commands changed 941
\@tryfcolumn: Command changed . 960
\@writesetup: \@startpagehook added 953
\output: Command changed 943

1993-12-06 ltclass.dtx v0.2k
\ExecuteOptions: Preserve \CurrentOption. 837

1993-12-06 ltoutput.dtx v1.0f
\@specialoutput: Unboxing of 255 added to rescue writes 943

1993-12-06 ltoutput.dtx v1.0g
\@topnewpage: \@floatplacement placement bug fixed 941

1993-12-07 ltclass.dtx v0.2l
\ProvidesFile: Macro added 832

1993-12-07 ltclass.dtx v0.2m
\load@onefilewithoptions: Reset \CurrentOption 843

1993-12-07 ltoutenc.dtx 1.1
General: Protected all special characters with \string. 357

1993-12-07 ltoutenc.dtx v1.1
General: Made all character numbers decimal. 354
Removed a lot of equal signs and the like. 354
1993-12-08 ltboxes.dtx v0.1b
\@begin@tempboxa: Extra braces for color support (braces removed from other macros) 672
\@irsbox: fix typo 684
\@parboxto: \endgraf added due to extra group in \@begin@tempboxa 679
\lrbox: move \@endpefalse out of the inner group 675
1993-12-08 ltfntcmd.dtx v2.1b
General: Macros \rm, \bf and \sf moved to classes.dtx 578
1993-12-08 ltlists.dtx LaTeX2e
\@item: use \sbox to support colour 666
1993-12-08 ltspace.dtx LaTeX2e
\@bsphack: Command reimplemented 319
Command reimplemented; late birthday present for Chris 319
\@vbsphack: Command added 322
1993-12-09 ltboxes.dtx v0.1c
\@irsbox: fix another typo 684
1993-12-09 ltclass.dtx v0.2n
\documentstyle: input 209 compatibility file. 838
1993-12-09 ltfiles.dtx v0.9e
\document: Hook added 334
1993-12-09 ltmiscen.dtx v0.9e
\enddocument: Hook added 619
1993-12-10 ltoutenc.dtx v1.2
General: Added source code for t1enc.sty. 354
1993-12-11 ltfntcmd.dtx v3.0a
General: Complete reworking of all text commands, using just one creator function 570
italic correction now put in front of penalty before glue 570
newcommands replaced by defs . . 570
newfontswitch command corrected and changed 570
\DeclareTextFontCommand: Macro changed 572
\emph: Macro changed 573
\fix@penalty: Macro added 576
\maybe@ic: Macro name changed . . 575
\maybe@ic@: Macro and name changed 575
\sw@slant: Macro changed 576
\textup: Macros changed 573
1993-12-11 ltmath.dtx v0.9g
General: Added a group around the first argument of \frac to prevent changes (for example font changes) from modifying the contents of the second argument. 648
1993-12-11 ltoutenc.dtx v1.2a
General: Corrected for t1enc, math. 354
1993-12-11 ltsect.dtx LaTeX2e
\author: Added default 747
\title: Added default 747
1993-12-11 ltxref.dtx LaTeX2e
\@setref: Macro added 614
\pageref: Macro reimplemented . . . 614
\ref: Macro reimplemented 614
1993-12-12 ltoutput.dtx v1.0h
\@cflb: boxmaxdepth setting moved 958
defs changed to lets 958
\@cflt: name changed 958
\@doclearpage: defs changed to lets 948, 949
\@makecol: defs changed to lets . . . 950
\@resethfps: Warnings added: minimal 989
\@startdblcolumn: defs changed to lets 959, 960
\@topnewpage: braces removed 941
\@tryfcolumn: defs changed to lets . 961
\fl@tracemessage: Commands changed 985
1993-12-13 ltclass.dtx v0.2o
General: Removed setting \errorcontextlines (now in latex.tex) 822
\documentstyle: compatibility file now latex209.sty. 838
\usepackage: Fixed error handling . 840
1993-12-13 ltdirchk.dtx v0.2a
General: on the 'docstrip' pass, do not check openin path 10
\IfFileExists: Removed interactive prompting for current directory syntax 10
\strip@prefix: modified, name changed from \stripmeaning. . . . 5
1993-12-13 ltlists.dtx latex2e
\trivlist: Initialised \@itemlabel 663
1993-12-13 ltmiscen.dtx v0.9h
\@noligs: Readded \@noligs 638
\@verbatim: Readded \@noligs . . . 634
Removed optional argument of \item 633
center: Removed optional argument of \item 631

flushleft: Removed optional argument of \item 632
flushright: Removed optional argument of \item 632
1993-12-13 ltoutenc.dtx v1.2b
General: Corrected file name in driver code. 354
1993-12-13 lttab.dtx latex2e
\tabbing: Removed optional argument of \item 693
1993-12-14 ltoutput.dtx v1.0i
General: Section added to declare all parameters 997
1993-12-15 ltboxes.dtx v0.1d
\@iminipage: Changed default from 'c' to 's' 681
\@iparbox: Changed default from 'c' to 's' 678
\minipage: Changed default from 'c' to 's' 680
extra space removed. 680
\parbox: Changed default from 'c' to 's' 678
1993-12-15 ltclass.dtx v0.2p
General: Removed extra '.'s from \@@warnings 822
1993-12-16 ltlogos.dtx LaTeX2e
\LaTeXe: Extended logo by DPC . . 331
1993-12-16 ltmath.dtx v0.9i
\@@eqncr: use \refstepcounter instead of shortcut 650
General: use \refstepcounter instead of shortcut 648
1993-12-16 ltmiscen.dtx v0.9i
General: \literal added 638
1993-12-16 ltpage.dtx LaTeX2e
\mark: Init \mark at begin document 816
1993-12-16 ltspace.dtx LaTeX2e
\@bsphack: Corrected optimisation :-) 319
1993-12-16 lttab.dtx latex2e
\@xhline: Measure from middle of vertical rules 708
1993-12-17 ltclass.dtx v0.2q
\@documentclasshook: Macro added 822
\@fileswithoptions: Add \@compatibility hook 841
\documentstyle: Match Alan's new code. 838
1993-12-17 ltoutenc.dtx 1.3
General: Added this section 358
Removed all the hackery for use in \DeclareFontEncoding, and redid everything using \DeclareTextFoo. 370, 372
Removed the catcode hackery, since the file is only read as a package in the preamble, and removed all the messages on the screen, which just confuse users. Replaced them by the appropriate \ProvidesPackage commands. Added XXXenc. . . . 357
1993-12-17 ltoutenc.dtx v1.3
General: Added \EncodingSpecificAccent, \EncodingSpecificAccentedLetter and \EncodingSpecificCommand. 354
Made Rokicki's encoding a proper encoding scheme rather than a variant of OT1. 354
1993-12-17 ltoutput.dtx v1.0j
\@opcol: Hook removed 949
\@specialoutput: Page room test added 944
\@topnewpage: check for vsize too small added 941
Page room test added 943
\@writesetup: —and then removed 953
\fl@tracemessage: tracefloatvals made a document command . . . 985
1993-12-17 ltpage.dtx LaTeX2e
\mark: Removed init \mark at begin document, since it doesn't work. 816
\rightmark: Stopgap solution to mark \leftmark and \rightmark work without initializing mark until the problem is solved. 816
1993-12-18 ltoutenc.dtx 1.3b
General: Fixed typos with \ProvidesPackage lines. Added the \NeedsTeXFormat line. Added the last argument to \DeclareEncoding. Moved the use of the encodings to after their declaration. 357
Replaced the missing last argument to \DeclareFontEncoding. 370, 372
1993-12-18 ltoutenc.dtx 1.3c
General: Rewrote for the new syntax of \EncodingSpecific. . . . 370, 372
Split \EncodingSpecificAccent up into \EncodingSpecific and \DeclareAccent. 358
1993-12-18 ltoutenc.dtx v1.3a
General: Replaced OT3 by XXX . . 354
1993-12-18 ltoutenc.dtx v1.3b
General: Corrected typos. 354
Replaced the missing last argument to \DeclareFontEncoding. 354

1993-12-18 ltoutenc.dtx v1.3c
General: A new syntax, separating accent-definitions from encoding-specific definitions, and allowing encoding-specific `\chardef`, `\let`, etc. 354
Rewrote for the new syntax of `\EncodingSpecific`. 354
1993-12-18 ltoutenc.dtx v1.3d
General: Some T1 stuff had drifted into the OT1 file. 354
1993-12-18 ltpage.dtx LaTeX2e
`\sloppy`: Added `\emergencystretch` 816
1993-12-19 ltclass.dtx v0.2r
`\endfilecontents`: Different message when ignoring a file 851
1993-12-19 ltfntcmd.dtx v3.0b
General: `\@pdef` command added . . 570
Added by ASAJ. 578
Made `\@newfontswitch` produce an error if command already exists, and added `\@renewfontswitch`, ASAJ 570
Other tidying 570
Some more tidying done 570
Untidying added, so this is now a TEMPORARY version. 570
Wording changes by CAR. 578
`\DeclareOldFontCommand`: Corrected and tidied 577
`\DeclareTextFontCommand`: Corrected and tidied 572
1993-12-19 ltspace.dtx LaTeX2e
`\@bsphack`: There seem to be problems with selfmade birthday presents . 320
1993-12-20 ltdefns.dtx LaTeX2e
`\@reargdef`: Kept old version of `\@reargdef`, for array.sty 83
1993-12-20 ltfiles.dtx v0.9m
`\@obsoletefile`: Added this command, removed @oldfilewarning 352
1994-01-05 fontdef.dtx v2.1d
General: Removed nf prefix from file names. 548
1994-01-13 ltmath.dtx v0.9o
`\@@eqncr`: correcting 0.9i 650
General: correcting 0.9i 648
1994-01-14 ltdirchk.dtx v0.2d
`\IfFileExists`: Close the texsys.aux output stream 10
1994-01-15 ltfiles.dtx v0.9o
`\document`: move `\@preamblecmds` after document hook 336
1994-01-17 ltclass.dtx v0.2s
`\@fileswithoptions`: Modify to reduce parameter stack usage . . 841
General: Added many more `\@onlypreamble` commands 822
Wrapped long lines to column 72 822
`\load@onefile@withoptions`: Modify to reduce parameter stack usage 846
1994-01-17 ltfiles.dtx LaTeX2e
`\listfiles`: New Version, adds '.tex' if needed, and lines up columns . 352
1994-01-17 ltfssbas.dtx v2.1a
General: New math font setup 410
`\curr@math@size`: New math font setup 422
`\everydisplay`: New math font setup 422
`\everymath`: New math font setup . 422
`\frozen@everydisplay`: New math font setup 422
`\frozen@everymath`: New math font setup 422
`\math@version`: New math font setup 421
1994-01-17 ltfssini.dtx v2.1e
`\not@math@alphabet`: Message changed 539
1994-01-17 ltfsstrc.dtx v2.3a
General: New math font setup 458
`\check@mathfonts`: New math font setup 468
`\glb@currsize`: New math font setup 466
`\restglb@settings`: New math font setup 469
1994-01-18 ltbibl.dtx LaTeX2e
`\bibliography`: Use `\@input@` so include files are listed. 788
1994-01-18 ltclass.dtx v0.2t
`\@ifclassloaded`: Fix typo `\@pkgetension` 827
1994-01-18 ltfilehook.dtx v0.9p
`\unqu@tefilef@und`: New Definition 885
1994-01-18 ltfiles.dtx v0.9p
`\@iffileonpath`: Macro added 348
`\@input`: do not use a different definition for `\input@path` 350
`\@input@`: Macro added 350
`\IfFileExists@`: New Definition . . 347
`\includeonly`: Use `\@input@` so include files are listed. 340
1994-01-18 ltfssini.dtx v2.1f
`\not@math@alphabet`: Message corrected 539
1994-01-18 ltmiscen.dtx v0.9p
`\@verbatim`: Add `\global\@inlabelfalse` 633

Only add \penalty if in hmode . 633
1994-01-19 fontdef.dtx v2.1e
General: Added missing setting for symbols in bold version. 553
1994-01-19 ltdirchk.dtx v0.2e
\IfFileExists: name changed from \test 9
\input@path: No longer check that an empty group is in the path 11
\strip@prefix: name changed from \strip@meaning, to match NFSS. 5
1994-01-19 ltmath.dtx v1.0n classes
\mathindent: Deferred setting of \mathindent 651
1994-01-20 ltdirchk.dtx v0.2f
General: \@copytexsys and the texsys.new file removed 9
Modify all of ltxcheck 14
\IfFileExists: \@copytexsys removed 10
1994-01-21 ltclass.dtx v0.2u
\documentstyle: compatibility file now latex209.def. 838
1994-01-21 ltdirchk.dtx v0.2g
General: Improve documentation, reorganize docstrip module 1
\filename@parse: Minor changes, and add Mac version (:) 11
\today: Name changed from \stamp, to save memory 9
1994-01-21 ltfloat.dtx LaTeX2e
\@xfloat: Added missing percent characters. 764
1994-01-21 ltmiscen.dtx v0.9s
\verbatim@font: Removed unnecessary category code hackery. 634
1994-01-24 ltdirchk.dtx v0.2h
\IfFileExists: Stop testing once texsys.aux has been found 10
1994-01-24 ltpage.dtx LaTeX2e
\pagestyle: (DPC) Complain if pagestyle is undefined. 813
1994-01-25 ltdirchk.dtx v0.2i
General: Protect against looping on \@@input and \@@end. 3
1994-01-25 ltfssbas.dtx v2.1b
\math@version: Corrections for math setup 421
1994-01-25 ltmath.dtx LaTeX2e
\bordermatrix: Removed \p@renwd. 643
1994-01-26 ltfsstrc.dtx v2.3c
\check@mathfonts: Correct trace info placement 468
\restglb@settings: Correct trace info placement 469
1994-01-27 ltfntcmd.dtx v3.1a
\nocorrlist: Only ., used as default for cm fonts 577
1994-01-29 ltclass.dtx v0.2v
\@@unprocessedoptions: Macro added. 850
\load@onefile@withoptions: All options raise error if no \ProcessOptions appears 847
1994-01-31 ltdefns.dtx v0.2w
\g@addto@macro: Use toks register to avoid 'hash' problems 107
1994-01-31 ltfiles.dtx v0.9t
\document: set \@normalsize or \normalsize if necessary 335
1994-01-31 ltfntcmd.dtx v3.1b
General: \@normalsize no longer defined 570
1994-02-01 ltpage.dtx LaTeX2e
\pagestyle: (DPC) Modify to get nicer error message 813
\thispagestyle: (DPC) Modify to get nicer error message 814
1994-02-02 ltclass.dtx v0.2x
\load@onefile@withoptions: Only run the hook and options check if the file was loaded. 847
1994-02-03 ltoutput.dtx v1.0k
\@makespecialcolbox: correct mistakes in the documentation . . 952
1994-02-07 ltclass.dtx v0.2y
\@fileswithoptions: Run \@compatibility on the first class to start (not the first to finish) . 841
\@ifclasswith: Add extra ,s so 'two' is not matched with 'twocolumn' 829
\ProcessOptions*: Add extra ,s so 'two' is not matched with 'twocolumn' 835
1994-02-07 ltfssbas.dtx v2.1c
\DeclareFontEncoding: revert catcode settings earlier 414
\DeclareFontShape@: revert catcode settings earlier 411
1994-02-08 ltoutput.dtx v1.0k
\@makespecialcolbox: boxmaxdepth setting added 952
boxmaxdepth setting removed . . 951
General: Documentation and tasks tidied. 926

1994-02-10 ltclass.dtx v0.2z
\\@documentclasshook: Changed the name from \\@compatibility to \\@documentclasshook, and added the check for whether \\@normalsize has been defined. ASAJ. 822
\\@fileswithoptions: Renamed \\@compatibility to \\@documentclasshook. ASAJ. . . 841
1994-02-10 ltfssbas.dtx v2.1d
\\addto@hook: Made \\addto@hook long. 435
1994-02-10 ltfsscmp.dtx v2.1d
\\scan@@fontshape: scan away stuff after pt 484
1994-02-22 ltfssini.dtx v2.1g
General: Correct error message 543
1994-02-24 ltfssbas.dtx v2.1e
\\DeclareFontShape: Separate restoration of catcodes for fd cmds 411
\\define@newfont: Separate restoration of catcodes for fd cmds 424
\\nfss@catcodes: Separate restoration of catcodes for fd cmds 424
1994-02-25 ltdirchk.dtx v0.2j
General: Remove need for drv file 1
1994-03-01 ltdirchk.dtx v0.2k
General: Add unstripped module, so that dircheck.dtx may be used with initex 1
1994-03-02 ltboxes.dtx v0.1e
General: Add 2ekernel module 671
Remove need for drv file 671
1994-03-02 ltclass.dtx v0.3a
General: Remove need for driver file 822
1994-03-03 ltboxes.dtx v0.1f
\\@irsbox: Replaced a missing \\else 684
1994-03-04 ltfloat.dtx v1.0a
General: Initial version, split from latex.dtx 760
1994-03-04 ltsect.dtx v1.0a
General: Initial version, split from latex.dtx 747
1994-03-04 lttab.dtx v1.0a
General: Initial version, split from latex.dtx 686
1994-03-04 ltvers.dtx v1.0a
General: Initial version, split from latex.dtx 39
1994-03-07 ltboxes.dtx v0.1a
\\@mpfootnotetext: Extra group for color 682
1994-03-07 ltboxes.dtx v1.0a
General: Unify format with other Kernel files 671
1994-03-07 ltdefns.dtx v1.0a
\\@@italiccorr: Macro added 79
1994-03-07 ltfiles.dtx v1.0a
General: Initial version, split from latex.dtx 332
Long lines wrapped to 72 columns 332
1994-03-07 ltfinal.dtx v0.1a
General: Add code from the old dump.dtx 1017
Initial version, split from latex.dtx 1003
move code here from lhyphen.dtx 1009
Remove oldcomments environment 1003
use \\InputIfFileExists not \\IfFileExists 1009
1994-03-07 ltfloat.dtx v1.0a
\\@endfloatbox: (DPC) Extra group for colour 769
\\@footnotetext: (DPC) Extra group for colour 779
\\@xfloat: (DPC) Extra group for colour 765
1994-03-07 lthyphen.dtx v0.1c
General: move the 2ekernel code to ltfinal.dtx 1001
1994-03-07 ltlength.dtx v1.0a
\\@settodim: (DPC) Extra group for colour 408
1994-03-07 ltlists.dtx v1.0a
General: Initial version, split from latex.dtx 655
Long lines wrapped to 72 columns 655
1994-03-07 ltpage.dtx v1.0a
General: Initial version, split from ltherest.dtx 813
1994-03-07 ltpictur.dtx v0.1a
General: Initial version, split from latex.dtx 711
Long lines wrapped to 72 columns 711
1994-03-07 ltsect.dtx v1.0a
\\@hangfrom: (DPC)Extra groups for colour 754
1994-03-07 lttab.dtx v1.0a
General: Long lines wrapped to 72 columns 686
1994-03-08 ltclass.dtx v0.3b
General: Modify driver code into 'new style' 822

1994-03-08 ltdirchk.dtx v1.0a
General: Reorganize driver module into 'new style' 1
1994-03-08 ltplain.dtx v1.0a
General: Remove need for a driver file. 15
1994-03-10 ltfssbas.dtx v2.2f
`\math@egroup`: Changed `\begingroup`/`\endgroup` to `\bgroup`/`\egroup`. 433
1994-03-11 ltfssdcl.dtx v2.1b
`\DeclareSymbolFontAlphabet@`: Added check against use of alphabet switch outside of math mode. 516
`\SetMathAlphabet@`: Changed parameter template in temporary macro to catch check add below. 505
1994-03-12 ltclass.dtx v0.3c
General: Change name from docclass to ltclass 822
`\ProvidesFile`: Add `\wlog` 832
`\ProvidesPackage`: Add `\wlog` 830
use `\@gtempa` 830
1994-03-12 ltdefns.dtx v1.0b
`\@reargdef`: New defn, in terms of `\@yargdef` 83
`\@yargd@f`: Name changed from `\XXX@argdef` 83
1994-03-12 ltdirchk.dtx v1.0b
General: Change name from dircheck.dtx 1
Minor edits to the typeouts in ltxcheck 1
1994-03-12 ltfloat.dtx v1.0b
`\@savemarbox`: (DPC) Extra group for colour 773
`\@xympar`: (DPC) Extra bgroup for colour 774
1994-03-12 ltplain.dtx v1.0b
General: Name changed from lplain. The end of an era 15
1994-03-12 ltplain.dtx v1.0e
General: Replaced remaining width, height, depth by LaTeX macro names to save tokens. 15
1994-03-13 ltcntrl.dtx v1.0c
`\@tfor`: (DPC) Add `\@tf@r` so a single group is correctly treated. 280
1994-03-13 ltfilehook.dtx v0.3b
`\unqu@tefilef@und`: Use new cmd `\@addtofilelist` 885
1994-03-13 ltfiles.dtx LaTeX2e
`\@addtofilelist`: Macro added . . . 352
`\listfiles`: Reset `\@addtofilelist` at begin document 353
1994-03-13 ltfssbas.dtx v2.1g
General: add 2ekernel module to omit repeated code 410
1994-03-13 ltfssdcl.dtx v2.1c
General: add 2ekernel module to omit repeated code 488
1994-03-14 ltboxes.dtx v1.0b
`\@isavebox`: Use `\color@setgroup` . 675
`\@isavepicbox`: Use `\color@setgroup` 675
`\color@begingroup`: macro added for color support 674
`\color@endgroup`: macro added for color support 674
`\lrbox`: Use `\color@setgroup` 675
`\sbox`: Use `\color@setgroup` 675
1994-03-14 ltfloat.dtx 1.0c
`\@xympar`: (DPC) Use `\color@begingroup` 774
1994-03-14 ltfloat.dtx v1.0c
`\@endfloatbox`: (DPC) Use `\color@endgroup` 769
`\@footnotetext`: (DPC) Use `\color@begingroup`, add `\endgraf` 779
`\@savemarbox`: (DPC) Use `\color@begingroup` 773
`\@xfloat`: (DPC) Use `\color@begingroup` 765
1994-03-15 ltfiles.dtx LaTeX2e
`\@missingfileerror`: Quit on x or X just like a real error 350
1994-03-15 ltfntcmd.dtx v3.2a
General: Adapted to mass formatting 570
Changed `\/` to `\@@italiccorr` . . 570
Removed `\@renewfontswitch` . . . 570
Removed defs of short-forms and all sizes except `\normalize` 570
1994-03-15 ltoutput.dtx v1.0l
`\@addtocurcol`: Changed `\addvspace` to `\vskip` 968, 971
`\@combinedblfloats`: Removed boxmaxdepth setting. 959
`\@makecol`: `\maxdepth` changed to `\@maxdepth` 950
Removed boxmaxdepth setting. . 951
`\@makespecialcolbox`: Removed boxmaxdepth setting. 952
`\@topnewpage`: Corrected and amended warning message 942
Warning added: it should be improved 943

General: Added some warnings when page gets full of top floats. 926
Driver added and further tidying. 926
Removed duplicated code and corrected docstrip options. 926
Some boxmaxdepth settings removed. 926
1994-03-16 ltclass.dtx v0.3f
General: Add pkgindoc package . . . 867
1994-03-16 ltfiles.dtx LaTeX2e
`\listfiles`: Move this code directly into `\document` 353
1994-03-16 ltfiles.dtx v1.0c
`\document`: (DPC) directly add file list settings 336
1994-03-16 ltmiscen.dtx v1.0b
`\@verbatim`: Remove `\global\@inlabelfalse` again. . 633
1994-03-28 ltalloc.dtx v1.0d
General: Redefinition of 'new' allocations removed. 275
1994-03-28 ltdirchk.dtx v1.0d
General: Improve documentation 1
1994-03-28 lterror.dtx v1.0d
`\@invalidchar`: (DPC) Comment out (use catcode15 instead) 291
General: Remove test for `\inputlineno` undefined. 287
1994-03-28 ltfiles.dtx v1.0d
`\document`: (DPC) Use `\normalsize` not `\@normalsize` 335
(DPC) remove `\@normalsize check` 335
1994-03-28 ltfloat.dtx v1.0b
`\@caption`: Use `\normalsize` not `\@normalsize` 763
General: Split further from ltherest.dtx 760
1994-03-28 ltlists.dtx v1.0b
General: Improve documentation . . 654
1994-03-28 ltmiscen.dtx v1.0c
General: Improve Documentation . . 618
1994-03-28 ltplain.dtx v1.0c
`\newlanguage`: Remove some `\outer` declarations. 18
1994-03-28 ltsect.dtx v1.0b
General: Split further from ltherest.dtx 747
1994-03-28 lttab.dtx v1.0b
General: Improve documentation . . 686
1994-03-28 ltthm.dtx v1.0a
General: Initial version, split from latex.dtx 743
1994-03-29 ltcounts.dtx v1.0c
General: Create file from parts of ltmiscen and ltherest. 400
1994-03-29 ltlength.dtx v1.0c
General: Create file ltcntlen from parts of ltmiscen and ltherest. 408
1994-03-29 ltmiscen.dtx v1.0d
General: Remove counter macros to ltcntlen 618
1994-03-29 ltpageno.dtx v1.0c
General: Create file ltcntlen from parts of ltmiscen and ltherest. 611
1994-03-29 ltxref.dtx v1.0c
General: Create file ltcntlen from parts of ltmiscen and ltherest. 612
1994-03-31 ltbibl.dtx v1.0a
General: Initial version of ltidxbib.dtx, split from ltherest.dtx 786
1994-03-31 ltidxglo.dtx v1.0a
General: Initial version of ltidxbib.dtx, split from ltherest.dtx 783
1994-04-09 ltcounts.dtx v1.0d
`\@newctr`: `\@nocnterr` now has counter name argument 401
`\addtocounter`: `\@nocnterr` now has counter name argument 401
`\setcounter`: `\@nocnterr` now has counter name argument 401
`\stepcounter`: Use `\addtocounter` to have name checked 402
1994-04-09 ltthm.dtx v1.0b
`\@othm`: Use standard counter error message (FMi) 745
1994-04-11 ltclass.dtx v0.3g
`\endfilecontents`: Add star form, don't write `\endinput` at the end of the file. 851
`\ProvidesFile`: Protect against weird catcodes. 832
1994-04-11 ltfssbas.dtx v2.1h
General: Added `\defaultscriptratio` and `\defaultscriptscriptratio`. ASAJ. 410
`\defaultscriptratio`: Macro added 433
`\defaultscriptscriptratio`: Macro added 433
1994-04-12 ltboxes.dtx v1.0c
General: Remove `\@acci`, now defined in ltplain.dtx 679
Remove `\@dischyph`, now defined in ltinit.dtx 679
1994-04-12 ltdefns.dtx v1.0g
`\@dischyph`: Define `\@dischyph`, was previously in ltboxes.dtx 105

1994-04-12 ltplain.dtx v1.0d
General: Define \@acci 34
1994-04-12 ltvers.dtx v1.0b
General: Have version info generated automatically. 39
1994-04-14 ltfntcmd.dtx v3.2b
General: Macros renamed to non-private forms, JB 570
\DeclareOldFontCommand: Renamed from \@newfontswitch 577
1994-04-15 ltboxes.dtx v1.0d
\@isavebox: Added missing percent character. 675
1994-04-17 ltcounts.dtx v1.0e
\@newctr: Use \@nocounterr instead of \@nocnterr 401
\addtocounter: Use \@nocounterr instead of \@nocnterr 401
\setcounter: Use \@nocounterr instead of \@nocnterr 401
1994-04-17 lterror.dtx v1.0h
\@nocounterr: New name for error message, old error message (without arg) kept 288
1994-04-17 ltthm.dtx v1.0c
\@othm: Use new std counter error message (FMi) 745
1994-04-18 ltfinal.dtx v0.1b
General: Initialise \textheight, \textwidth and page style . . . 1006
1994-04-18 ltfloat.dtx v1.0d
\@footnotetext: (DPC) Remove Colour support 779
\@savemarbox: (DPC) Remove Colour support 773
1994-04-18 ltfssbas.dtx v2.1i
General: Macro \no@alphabet@help removed again 410
\calculate@math@sizes: Changed message to log only 433
\no@alphabet@error: Use std LaTeX error macro 410
1994-04-18 ltfssdcl.dtx ???
\DeclareMathAlphabet: Pass correct arg (2 not 3) 503
1994-04-18 ltfssdcl.dtx v2.1d
General: Removed surplus \no@alphabet@error (see fam.dtx) 488
1994-04-18 ltfsstrc.dtx v2.3d
General: Changed to new error/warning scheme 458
\font@submax: Changed dimen to macro 477
\fontsubfuzz: Changed dimen to macro 477
\subst@size: \font@submax and \fontsubfuzz now macros 478
1994-04-19 ltpage.dtx v1.0b
General: Improve documentation . . 813
1994-04-20 ltfntcmd.dtx v3.3a
General: Documentation up-dated . 570
New implementation of \nocorr . 570
\check@nocorr@: Macros added . . . 574
\maybe@ic@: \nocorr etc removed from list of tokens to check, leaving only punctuation characters 575
1994-04-20 ltmiscen.dtx v1.0e
\@enddocument@kernel@warnings: Changed logic for producing warning messages 621
1994-04-21 ltboxes.dtx v1.0e
\@iiiminipage: Extra \bgroup for color 681
\@mpfootnotetext: Extra \endgraf for color 682
\endminipage: Extra \egroup for color 681
1994-04-21 ltfinal.dtx v0.1c
General: Added comments, set the catcodes of 128–255. 1003
1994-04-22 ltfssini.dtx v2.1g
\not@math@alphabet: Message changed again 539
1994-04-23 ltfinal.dtx v0.1d
General: Check that \font@submax is still zero 1003
1994-04-24 ltoutput.dtx v1.0m
\@resethfps: Number 2 changed to \tw@ 989
Warning changed 989
\@specialoutput: Message changed to give more info and 'top' removed 944
\@topnewpage: Message changed to give more info 943
Warning message removed as it will be generated later 942
General: Changed \@normalsize to \normalsize. 926
Corrected unverbed commands in documentation. 926
Removed some long lines and other aesthetic changes. 926
Warning messages changed/corrected. 926
1994-04-24 ltpictur.dtx v0.1b
General: Removed surplus spaces after \hbox to in several cases 711

1994-04-25 ltclass.dtx v0.3h
General: Removed spurious extra ‘.’s at the end of error messages 822
1994-04-25 ltfloat.dtx v1.0e
\@largefloatcheck: Changed warning message to give more info 769
Command added 769
General: Changed warning messages 760
Removed obsolete tracing code . . 760
1994-04-27 ltfsstrc.dtx v2.3e
General: Corrected item that was forgotten in last change. 458
1994-04-28 lterror.dtx v1.0j
\@inmatherr: Macro added 290
1994-04-28 lterror.dtx v1.1c
\@inmatherr: Replaced \noexpand with \protect. 290
1994-04-28 ltfssdcl.dtx v2.1e
General: Removed all \uppercase in hex num parsing macros 488
1994-04-28 ltlists.dtx v1.0c
\item: Replaced \@ltxnomath by \@inmatherr 665
1994-04-28 ltpictur.dtx v0.1c
\@multiput: (DPC) Macro added . . 715
General: bezier curves added 738
\multiput: (DPC) Ignore spaces between)(. 714
\picture: (DPC) Ignore spaces before (. 713
1994-04-28 ltplain.dtx v1.0g
General: Turn off overfull box tracing in log 27
1994-04-29 ltclass.dtx v1.0a
General: Change version number to 1 (no other change) 822
1994-04-29 ltmiscen.dtx v1.0f
\@verbatim: \leavevmode added . . 634
Change to \everypar added 634
1994-04-29 ltoutenc.dtx 1.4a
General: Removed \EncodingSpecific. Renamed all the commands. Added \DeclareTextGlyph and \UndeclareTextCommand. 358
Removed Rokicki’s OT1 variant encoding. Moved the driver to the top. 357
1994-04-30 ltfntcmd.dtx v3.3b
General: Documentation up-dated and tidied 570
Prefix frag@ changed to frag in \@protecteddef 570
Title changed 570
Warning changed to info message in \@protecteddef 570
1994-04-30 ltoutput.dtx v1.0n
\@activechar@info: \@activechar@warning changed to \@activechar@info 953
\@combinedblfloats: Removed rule in topnewpage case 959
\@emptycol: Empty column action added: \@emptycol 941
\@flsetnum: Rogue space removed . 990
\@specialoutput: Cut-off point changed to 2\baselineskip 944
Empty column action added: \@emptycol 944
Extra empty column added for twocolumn case 944
Extra empty column added for twocolumn case (wrong, see below) 944
\@topnewpage: Added setting of \col@number 941, 942
Cut-off point changed to 3\baselineskip 943
Empty column action added: \@emptycol 943
Message changed for Frank 943
General: \@activechar@warning changed to an info message. 926
Added \col@number. 926
Documentation tidied. 926
Empty column action added. . . . 926
Fixed bug from \dblfigrule with \@topnewpage. 926
Full of floats action improved. . . . 926
\col@number: Added \col@number . 938
\onecolumn: Added setting of \col@number 940
1994-05-01 lterror.dtx v1.0k
\@latexerr: (CAR) Added draft \@latexinfo. 287
1994-05-01 ltoutenc.dtx 1.4a
General: Added the \a command. . . 366
Added the \SaveAtCatcode and \RestoreAtCatcode commands. . 370
Removed the uc/lc table settings, since the T1 uc/lc table is now the default. 378
Rewrote for the new syntax. . 370, 372
1994-05-01 ltoutenc.dtx v1.4a
General: Removed Rokicki’s encoding. 354
Renamed the commands, removed the \EncodingSpecific command.

Turned all slots into decimal.
Added \a. 354
1994-05-02 ltcntrl.dtx v1.0l
\@break@tfor: Macro added (from ltfiles.dtx) 280
1994-05-02 ltdefns.dtx v1.1f
\renewcommand: Removed surplus \space in error 84
\renewenvironment: Removed surplus \space in error 85
1994-05-02 ltfiles.dtx v1.0f
\@iffileonpath: \@break@loop renamed to \@break@tfor 348
\@obsoletefile: Make \@onlypreamble 352
1994-05-02 ltfinal.dtx v0.1e
General: Added setting the 'letter' catcodes. 1015
Added setting the 'other' catcodes. 1015
Added setting the special catcodes. 1015
Made slot 127 illegal 1015
Set all the catcodes 1003
1994-05-02 ltfinal.dtx v0.1f
General: Set the catcode of control-J. 1015
1994-05-02 ltmiscen.dtx v1.0g
General: Changed 91 to 1991 and moved some bits 618
1994-05-02 ltoutput.dtx v1.0o
\@resethfps: Code shortened 989
General: Code of \@resethfps shortened. 926
1994-05-03 ltbibl.dtx v1.0b
\nocite: Make \nocite issue a warning for an undefined citation key. 789
1994-05-03 ltfinal.dtx v0.1f
General: Set the catcode of control-J to be 'other', for use in messages. 1003
1994-05-03 ltfloat.dtx v1.0f
General: (CAR) Added \@largefloatcheck 760
Removed unnecessary braces from arguments of \@ifnextchar 760
\end@dblfloat: \@largefloatcheck added 768
\end@float: (CAR) Added \@largefloatcheck 767
1994-05-03 ltfssdcl.dtx v2.1f
General: Renamed \@@DeclareMathDelimiter to \@DeclareMathDelimiter 488
1994-05-03 ltlists.dtx v1.0d
\@item: \hskip changed to \kern . . 666
\item: Removed superfluous braces 665
1994-05-03 ltmiscen.dtx v1.0h
\@centercr: \@badcrerr replaced by \@nolnerr 630
1994-05-03 lttab.dtx v1.0d
\@endpbox: Use \@finalstrut based on depth of \@arstrutbox 709
1994-05-04 ltclass.dtx v1.0b
\NeedsTeXFormat: Changed wording of the warning 840
1994-05-04 lterror.dtx v1.0m
\@badcrerr: Error message removed 290
1994-05-05 ltbibl.dtx v1.0c
\@citex: Set switch for warning and end of run. 788
\nocite: Do not write page number in \nocite warning message. 789
Set switch for warning and end of run. 789
1994-05-05 ltfinal.dtx v0.1g
General: Added empty errhelp. . . . 1003
\errhelp: Set error help empty. . . 1019
1994-05-05 ltfntcmd.dtx v3.3c
\@@math@egroup: Corrected \@fontswitch and added saved versions 577
General: Corrected \@fontswitch . . 570
1994-05-05 ltmiscen.dtx v1.0i
General: Removed braces from ifnextchar and ifstar arguments . 618
1994-05-07 lttab.dtx v1.0c
\@maxtab: Changed \@firsttab to \chardef 690
Changed \@maxtab to \chardef . 690
General: Removed definition of \+ . 686
Removed surplus braces from \@ifnextchar constructs 686
1994-05-08 ltfntcmd.dtx v3.3d
General: Removed \@undefinedfonterror 570
\normalsize: Removed \@undefinedfonterror 578
1994-05-09 ltfntcmd.dtx v3.3f
General: Replaced all \next by \@let@token and undo change 3.3e, whatever that was. 570
1994-05-10 ltdefns.dtx v1.0n
General: (ASAJ) Added \DeclareProtectedCommand. 78
Added \DeclareProtectedCommand 87
Removed braces around \@ifundefined argument. ASAJ. 84

\makeatother: Added \makeatletter and \makeatother ASAJ. 105
1994-05-10 lterror.dtx v1.0n
\@latexerr: (ASAJ) Added extra blank lines to \@latexerr. 287
1994-05-10 ltmiscen.dtx v1.0j
\@@sverb: Slight change in error message text. 636
1994-05-11 ltboxes.dtx v1.0f
\@begin@tempboxa: Use new \color@setgroup concept. 672
\@iiiminipage: Use new \color@setgroup concept. 681
\@mpfootnotetext: Use new \color@setgroup concept. 682
Use new \normalcolor and \@finalstrut. 682
General: Superfluous braces removed from several commands 671
\color@setgroup: macro added for color support 674
\endminipage: Use new \color@setgroup concept. 681
1994-05-11 ltclass.dtx v1.0c
\endfilecontents: Add checks for form feed and tab 851
1994-05-11 ltdirchk.dtx v1.0e
General: Add \ProvidesFile as used in fd files. 4
1994-05-11 lterror.dtx v1.0o
\@latexerr: (ASAJ) Removed one of the extra blank lines to \@latexerr. 287
1994-05-11 ltlogos.dtx v1.0o
\LaTeX: Use \DeclareProtectedCommand. ASAJ. 331
\LaTeXe: Use \DeclareProtectedCommand. ASAJ. 331
1994-05-11 ltoutenc.dtx 1.5a
General: Made T1 and OT1 generate packages rather than def files. Renamed the 'package' module to 'teststy'. 357
1994-05-11 ltoutenc.dtx v1.5a
General: Reimplemented \DeclareTextCommand using \@changed@cmd and \DeclareProtectedCommand. . . . 358
Renamed the commands again. Made the encoding part of the command syntax. Added the \DeclareTextCommand interface. Used \DeclareProtectedCommand. . . . 354
\DeclareTextAccent: Reimplemented using \DeclareTextCommand. . . . 360
1994-05-11 ltspace.dtx v1.0o
\hspace: Use \DeclareRobustCommand. ASAJ. 328
1994-05-12 ltboxes.dtx v1.0g
\@finalstrut: macro added 685
\fbox: New definition, merged with \framebox 676
\framebox: Merged \fbox and \framebox 677
\normalcolor: macro added for color support 674
1994-05-12 ltdefns.dtx v1.0p
General: (ASAJ) Fixed a bug with \relax which was using \@gobble before defining it. 78
Fixed a bug with \relax which was using \@gobble before defining it. 87
1994-05-12 ltfssbas.dtx v2.1j
General: New baselinestretch concept 410
Replaced hand-protected commands by \DeclareRobustCommand defs 410
\f@linespread: New macro 420
\fontencoding: Use \DeclareRobustCommand. 418
\fontfamily: Use \DeclareRobustCommand. 419
\fontseries: Use \DeclareRobustCommand. 419
\fontshape: Use \DeclareRobustCommand. 419
\fontsize: Redefined to use \set@fontsize 420
\linespread: New macro 420
\mathversion: Use \DeclareRobustCommand. 421
1994-05-12 ltfssdcl.dtx v2.1g
General: Allow \relax as undefined command 488
Allow \relax'ed cmds to be declared 488
1994-05-12 ltfssini.dtx v2.1i
General: Moved \fontencoding to fam.dtx 518
Moved \fontfamily to fam.dtx . 518
Moved \fontseries to fam.dtx . 518
Moved \fontshape to fam.dtx . . 518
Moved \fontsize to fam.dtx . . . 518
Moved \mathversion to fam.dtx . 518
Moved \selectfont to tracefnt.dtx 518

1994-05-12 ltfsstrc.dtx v2.3f
\selectfont: Use \DeclareRobustCommand 462
1994-05-12 ltoutenc.dtx 1.5a
General: Removed the \SaveAtCatcode and \RestoreAtCatcode commands. . 370
Rewrote for the new syntax. . 370, 372
1994-05-12 ltoutput.dtx v1.0p
\@writesetup: \normalcoloradded 953
General: \normalcoloradded in various places (DPC). 926
1994-05-13 ltboxes.dtx v1.0h
\@arrayparboxrestore: New accent system, use \let not \def 680
1994-05-13 ltcounts.dtx v1.0f
General: Removed \@Ialph 405
Removed \@ialph 405
1994-05-13 ltdefns.dtx v1.0q
General: (ASAJ) Renamed \DeclareProtectedCommand to \DeclareRobustCommand. Removed \@if@short@command. . . 78
(ASAJ) Replaces \space by ‘ ’ in \csname. 78
Renamed \DeclareProtectedCommand to \DeclareRobustCommand. Removed \@if@short@command. Moved to after the definition of \@gobble. 87
1994-05-13 ltdefns.dtx v1.0r
General: (ASAJ) Added logging message to \DeclareProtectedCommand. 78
Added logging message to \DeclareProtectedCommand. 87
1994-05-13 ltdefns.dtx v1.0s
General: (ASAJ) Added \@backslashchar. 78
(ASAJ) Coded \@ifdefinable more efficiently. 78
Coded more efficiently, thanks to FMi. 84
1994-05-13 ltfiles.dtx LaTeX2e
\listfiles: Stop \listfiles being run twice 352
1994-05-13 ltfiles.dtx v1.0g
\document: Added execution of \every@size 335
1994-05-13 ltfinal.dtx v0.1h
General: Added package ot1enc, and defined \@acci, \@accii and \@acciii. 1003
1994-05-13 ltfinal.dtx v1.0h
General: Added output enc stuff . . 1017
1994-05-13 ltfloat.dtx v1.0g
\@footnotetext: (DPC) Add new style colour support: \normalcolor 779
(DPC) Use \@finalstrut 779
\@xfloat: (DPC) Use \normalcolor 765
1994-05-13 ltfntcmd.dtx v3.3g
General: Replaced \@protecteddef by \DeclareRobustCommand 570
1994-05-13 ltfssbas.dtx v2.1k
General: Remove File identification ‘typeout’ 410
1994-05-13 ltfssbas.dtx v2.1l
\DeclareFontEncoding: Init encoding change command 414
\define@newfont: Use \@input@ for fd files 424
1994-05-13 ltfssdcl.dtx v2.1h
General: Removed file identification typeout 488
1994-05-13 ltfssini.dtx v2.1j
General: Removed file identification typeout 518
1994-05-13 ltfsstrc.dtx v2.3g
General: Removed typeouts as \ProvidesPackage writes to log. 458
1994-05-13 ltoutenc.dtx v1.5b
General: Added \{, \} and \$. 354
Renamed \DeclareProtectedCommand to \DeclareRobustCommand. 354
Replaces \space by ‘ ’ in \csname. 354
1994-05-13 ltpictur.dtx v0.1d
General: Removed surplus braces from \@if.. constructions 711
1994-05-13 lttab.dtx v1.0d
\@contfield: Colour support 692
\@startfield: Colour support 692
\@stopfield: Colour support 692
\a: moved to ltoutenc 690
1994-05-14 fontdef.dtx v2.1f
General: Removed .def files. 548
1994-05-14 ltfssbas.dtx v2.1m
\enc@update: Macro added 419
1994-05-14 ltfssbas.dtx v2.1n
General: Set defaults for all \f@... 420
\DeclareErrorFont: Don’t set \f@encoding 427
\DeclareFontEncoding: Log if encoding is redeclared 414
Only init enc change cmd when new encoding 414

1994-05-14 ltfssini.dtx v2.1k
General: Init error font just before checking for fontdef.cfg 543
`\reset@font`: Remove surplus braces 541
1994-05-14 ltfsstrc.dtx v2.3h
`\selectfont`: Added `\enc@update` . 464
1994-05-14 ltoutenc.dtx 1.5d
General: Moved the driver to the top. 357
1994-05-14 ltoutenc.dtx v1.5c
General: Added the fontenc package 397
Added the fontenc package. 354
Fixed a bug which caused an infinite loop if `\f@encoding` was incorrectly set. 354, 358
Moved fontsmpl to its own dtx file. 354
1994-05-14 ltoutenc.dtx v1.5d
General: Rewrote `\DeclareTextCommand` to define its argument to use the current encoding by default, rather than the encoding provided to `\DeclareTextCommand`. . . . 354, 358
Tidied up the documentation. . . . 354
1994-05-14 ltoutenc.dtx v1.5e
General: Replaced `\ENC@cmd` by `\ENC-cmd`. 354
1994-05-15 ltfssbas.dtx v2.1o
General: encoding cmds changed to enc-cmd 410
1994-05-16 fontdef.dtx v2.1g
General: Removed `\DeclareFontEncoding` for ot1 and t1 and input .def files instead . . 548
1994-05-16 ltalloc.dtx v1.1a
General: (ASAJ) Split from ltinit.dtx. 275
1994-05-16 ltcntrl.dtx v1.0a
General: (ASAJ) Split from ltinit.dtx. 277
1994-05-16 ltdefns.dtx v1.1a
General: (ASAJ) Split from ltinit.dtx. 78
1994-05-16 lterror.dtx v1.1a
General: (ASAJ) Completely new error interface. 281
(ASAJ) Split from ltinit.dtx. . . . 281
1994-05-16 ltfinal.dtx v1.0i
General: moved output enc stuff to lfonts 1017
1994-05-16 ltfssbas.dtx v2.1p
`\fontsize`: Pass `\baselinstretch` not `\f@linespread` 420
`\linespread`: Remove surplus braces 420
1994-05-16 ltfssini.dtx v2.1m
`\@acciii`: Define saved versions of accents 544
1994-05-16 ltlogos.dtx v1.1a
General: (ASAJ) Split from ltinit.dtx. 331
1994-05-16 ltmath.dtx v1.0k
`\ensuremath`: Use `\DeclareRobustCommand` and add extra braces in math mode 650
1994-05-16 ltoutenc.dtx 1.5h
General: `\pounds` was still using u rather than ui shape. 370
1994-05-16 ltoutenc.dtx v1.5f
General: enc files now have uc encoding name parts (FMi) 354
Revert code so that the encoding given is used in `\DeclareTextCommand` (FMi) . . . 354
1994-05-16 ltoutenc.dtx v1.5g
General: Made fontenc.sty use the new mixed-case encoding files. 354
Removed the lowercasing of the filename. 397
1994-05-16 ltoutenc.dtx v1.5h
General: Added `\NG`, `\ng`, `\TH`, `\th`, `\DH`, `\dh`, `\DJ` and `\dj`. 354
Added `\r` (ring accent) and `\k` (ogonek) accents. 354
Fixed a bug with `\pounds`. 354
Removed `\P` from the OT1 definitions file. 354
1994-05-16 ltoutenc.dtx v1.5i
General: Fixed a bug with `\d`. . . . 354
1994-05-16 ltoutput.dtx v1.0q
`\@writesetup`: Changed setting of accents (FMi): with the new encoding setup they can use `\let`. It could also use the new internal commands? 954
General: Changed setting of accents (FMi). 926
1994-05-16 ltpar.dtx v1.1a
General: (ASAJ) Split from ltinit.dtx. 292
1994-05-16 ltplain.dtx v1.0h
General: Comment out encoding specific commands 33
Remove `\@acci` and friends again . 34
Remove unnecessary def for `\item` 33
`\loop`: Use Kabelschacht method . . . 31
`\m@th`: Remove unnecessary space . . . 32
1994-05-16 ltspace.dtx v1.1a
General: (ASAJ) Split from ltinit.dtx. 312
1994-05-17 ltclass.dtx v1.0e
`\@use@ption`: Execute option after removing from list, not before . . 837

1994-05-17 ltdefns.dtx 1.1b
General: (ASAJ) Added the `\@protect@...` commands. 88
1994-05-17 ltdefns.dtx v1.1b
General: (ASAJ) Added definitions for protect. 78
(ASAJ) Removed warnings and logging to lterror.dtx. 78
Added the discussion of protected commands, defined the values that `\protect` should have. 88
1994-05-17 ltdefns.dtx v1.1c
General: (ASAJ) Redid definitions for protect. 78
1994-05-17 lterror.dtx v1.1b
General: (ASAJ) Moved error stuff from ltdefns.dtx. 281
1994-05-17 ltfssini.dtx v2.1n
`\copyright`: Really add extra braces 541
`\nfss@text`: Added braces to allow use in subscripts 541
1994-05-17 ltmath.dtx v1.0i
General: Replaced `\let` by `\gdef`, for indirect definition. 646
1994-05-17 ltoutenc.dtx v1.5j
General: Added braces to `\pounds` so it works as a subscript. 354
1994-05-18 ltdefns.dtx 1.1c
General: (ASAJ) Renamed the commands, and removed one which is no longer needed. 88
1994-05-18 ltdefns.dtx v1.1c
General: Redid the discussion and definitions, in line with the proposed new setting of `\protect` in the output routine. 88
1994-05-18 ltfinal.dtx v0.1j
General: Corrected the lccode for d-bar. 1003
1994-05-18 ltlogos.dtx v1.1b
General: (ASAJ) Added the TEX logo. 331
(ASAJ) Made the LATEX 2ε logo use the text font '2' rather than the math font '2'. 331
1994-05-18 ltoutenc.dtx v1.5k
General: Made dotted-i produce 'i'. . 354
Removed braces from `\pounds` and `\dollar`. 354
Replaced `\defaultencoding` with `\encodingdefault`. 354
1994-05-19 ltbibl.dtx v1.1a
General: Initial version of ltbibl.dtx, split from ltidxbib.dtx 786
1994-05-19 ltcounts.dtx v1.1a
General: Extracted file from ltcntlen. 400
1994-05-19 ltdefns.dtx v1.1d
General: (RmS) Added definitions for `\@namedef` and `\@nameuse` again. . 78
1994-05-19 ltfinal.dtx v0.1k
General: Removed `\makeat...` . . . 1003
1994-05-19 ltidxglo.dtx v1.1a
General: Initial version of ltidxglo.dtx, split from ltidxbib.dtx 783
1994-05-19 ltlength.dtx v1.1a
General: Extract file ltlength from ltcntlen. 408
1994-05-19 ltpageno.dtx v1.1a
General: Extract file ltpageno from ltcntlen. 611
1994-05-19 ltplain.dtx v0.1k ltfinal
`\showoutput`: used `\maxdimen` not 99999 34
`\showoverfull`: used `\@ne` not 1 34
1994-05-19 ltxref.dtx v1.1a
General: Extract file ltxref from ltcntlen. 612
1994-05-20 ltdefns.dtx v1.1e
General: Changed command name from `\@checkcommand` to `\CheckCommand`. 78
`\CheckCommand`: Changed name from `\@checkcommand` to `\CheckCommand`. 86
1994-05-20 lterror.dtx v1.1c
General: (ASAJ) Added `\@latex@info@no@line`. 281
(ASAJ) Added missing full stops. 281
(ASAJ) Fixed a bug with `\@inmatherr`. 281
1994-05-20 ltfinal.dtx v0.1l
General: Use new font warning commands 1010
1994-05-20 ltfloat.dtx v1.0h
`\@endfloatbox`: Restore outer value of @nobreak switch. 769
`\outer@nobreak`: Macro added: default is to do nothing. 769
1994-05-20 ltfntcmd.dtx v3.3h
General: Use new error commands . 570
1994-05-20 ltfssbas.dtx v2.1q
General: Use new error commands . 410
1994-05-20 ltfsstrc.dtx v2.3i
General: Use new error command names 458
1994-05-20 ltmiscen.dtx v1.0l
`\@writefile`: Added correct setting of `\protect`. 624

1994-05-20 ltmiscen.dtx v1.0m
General: Use new warning commands 618
1994-05-20 ltoutput.dtx v1.0s
\@writesetup: Added setting of \protect during \shipout. 953
General: Added setting of \protect during \shipout. 926
1994-05-20 ltpage.dtx v1.0d
\markright: Changed setting for \protect. 814
1994-05-20 ltsect.dtx v1.0c
General: Correct setting of \protect. 757
\addcontentsline: Correct setting of \protect. 756
1994-05-21 ltbibl.dtx v1.1b
General: Use new warning commands 786
1994-05-21 lterror.dtx v1.1d
General: (ASAJ) Made the error commands robust. 281
1994-05-21 ltfiles.dtx v1.0h
General: Use new error commands . 332
1994-05-21 ltlists.dtx v1.0f
General: Use new error commands . 654
1994-05-21 ltmiscen.dtx v1.0n
General: Use new error commands . 618
1994-05-21 ltsect.dtx v1.0d
General: Use new error commands . 747
1994-05-21 lttab.dtx v1.0f
General: Use new error commands . 686
1994-05-21 ltxref.dtx v1.1b
General: Use new warning commands 612
\newlabel: Use new warning commands 614
1994-05-22 ltclass.dtx v1.0f
General: Use new warning and error commands 818
1994-05-22 ltdefns.dtx v1.1f
General: Use new warning and error cmds 78
1994-05-22 lterror.dtx v1.1e
General: (ASAJ) Replaced bgroup by begingroup in error messages, to stop extra mathords creeping into math mode. 281
1994-05-22 lterror.dtx v1.2a
General: (ASAJ) Made \GenericError, \GenericWarning and \GenericInfo robust. 281
(ASAJ) Replaced \\ and tilde by \MessageBreak and \space. 281
(ASAJ) Replaced \@generic@message and \@generic@error by \GenericError, \GenericWarning and \GenericInfo. 281
(ASAJ) Replaces \string by \protect in some messages. . . . 281
1994-05-22 lterror.dtx v1.2d
\GenericError: (DPC) Alternative version added for old TeXs 282
(DPC) New version using long command name. 282
1994-05-22 ltfloat.dtx v1.0i
General: Use new warning commands 760
1994-05-22 ltoutput.dtx v1.0t
General: Changed warnings and infos to new commands. 926
1994-05-22 ltpictur.dtx v0.1e
General: Use new warning cmds . . . 711
1994-05-23 ltclass.dtx v1.0h
\NeedsTeXFormat: Don't stop completely when format is wrong 840
\usepackage: Remove argument if possible 840
1994-05-23 ltdirchk.dtx v1.0f
General: Document \@TeXversion . . . 1
1994-05-23 ltfsstrc.dtx v2.3j
General: Removed def of \f@warn@break 476
1994-05-23 ltoutput.dtx v1.0u
\@activechar@info: Added \MessageBreak 953
\@writesetup: Changed resetting of \protect after shipout to use \aftergroup 953
General: Added \MessageBreak. . . . 926
Changed resetting of \protect after shipout. 926
1994-05-24 lterror.dtx v1.2e
\@latex@info@no@line: Macro added 285
1994-05-24 lterror.dtx v1.2f
General: (DPC) wrap long lines . . . 281
1994-05-24 ltfntcmd.dtx v3.3i
General: Tidying and typos fixed . . 570
1994-05-24 ltmiscen.dtx v1.0q
\@currenvline: Use \@empty as outer default 629
1994-05-25 ltdirchk.dtx v1.0g
\filename@parse: Mac parser had " typo for : 12
1994-05-25 ltfntcmd.dtx v3.3j
General: Insertion of \aftergroups to implement \nocorr moved to the end of the group 570
\check@icr: Macros added 574

\check@nocorr@: Insertion of \aftergroups moved and defaults set up for efficiency 574
\DeclareTextFontCommand: \expandafter inserted 572
Insertion of \aftergroups moved 572
1994-05-25 ltoutput.dtx v1.0v
General: Extra documentation. 926
1994-05-25 ltsect.dtx v1.0e
\@dottedtocline: Put braces around argument 4 (the actual toc entry) to avoid font (and possibly other) changes leaking out to the leaders. 758
1994-05-25 ltthm.dtx v1.0c
General: Modify documentation . . . 743
1994-05-25 ltvers.dtx v1.0d
General: Remove PRELIMINARY TEST RELEASE from startup banner (spring is here) 39
1994-05-25 ltxref.dtx v1.1c
General: Modify documentation . . . 612
1994-05-26 ltfiles.dtx LaTeX2e
\@missingfileerror: Modify message format 350
1994-05-26 ltlogos.dtx v1.1c
General: Remove \SLiTeX logo 331
1994-05-26 ltmiscen.dtx v1.0r
General: \literal removed 638
1994-05-26 ltplain.dtx v1.1m
\iterate: (CAR) added \long 31
\underbar: (CAR/FMi) changed to use box \tw@ 32
1994-05-26 ltplain.dtx v1.1p
\underbar: (DPC) changed to use \sbox 32
1994-05-29 ltfssdcl.dtx v2.1j
General: Use new error commands . 488
1994-05-31 ltfinal.dtx v1.0n
General: Renamed lthyphen.* to lthyphen.*. 1003
1994-06-01 ltboxes.dtx v1.0i
\@frameb@x: Macro added. 677
\@iframebox: New version, so \width is correct in \framebox 677
\fbox: New version, using \@frameb@x 676
\framebox: New version, so \width is correct in \framebox 677
1994-06-01 ltlogos.dtx v1.1d
\LaTeX: Add \m@th to force math size calculations 331
1994-06-01 ltoutput.dtx v1.0w
General: Tidied up typesetting. . . . 926
1994-06-08 ltfinal.dtx v1.0m
General: Add patch file system . . . 1018
1994-06-09 ltfinal.dtx v1.0n
General: For TEX2, do not set codes for higher half of character table. 1008, 1016
1994-06-09 ltfntcmd.dtx v3.3k
General: Tidying and typos fixed in documentation 570
1994-06-18 ltfntcmd.dtx v3.3l
General: Added check for empty text 570
\check@nocorr@: Added check for empty text 574
1994-06-22 ltfntcmd.dtx v3.3m
General: Removed space from \nfss@text 570
Renamed \check@nocorr 570
\check@nocorr@: Renamed \check@nocorr to \text@command to improve \long error message . 574
\DeclareTextFontCommand: Removed space from \nfss@text 572
1994-06-22 ltmath.dtx v1.2t classes
\mathindent: Set \mathindent at the end of the class instead of at begin document 651
1994-07-20 ltlogos.dtx v1.1e
\LaTeX: Save a few tokens 331
\LaTeXe: Save a few tokens 331
1994-07-20 ltpage.dtx v1.0h
\sloppy: Save a few tokens 816
1994-09-16 ltfssbas.dtx v2.1s
\nfss@catcodes: Reset [and] as well, just in case 425
1994-10-07 ltoutenc.dtx v1.5l
General: Moved the ogonek accent. . 354
1994-10-11 ltdirchk.dtx v1.0h
\@TeXversion: Check for TeX3.14 . . 13
General: Modify all of ltxcheck again 14
1994-10-12 ltsect.dtx v1.0f
General: Doc. typos 747
1994-10-14 fontdef.dtx v2.2a
General: New coding 546
1994-10-14 ltfssini.dtx v2.2a
General: New coding for cfg files . . . 518
1994-10-14 ltmiscen.dtx v1.0s
General: Move math to other file . . 618
1994-10-14 ltplain.dtx v1.1a
General: Moved code to other files. . . 15
1994-10-15 ltfssbas.dtx v2.1t
\extract@alph@from@version: Warn if math alpha is used outside math 432

1994-10-18 ltboxes.dtx v1.0j
\@frameb@x: \leavevmode added . . 677
\@iframebox: \leavevmode moved to \@frameb@x 677
\@parboxto: Macro added to remove misuse of \@empty 679
General: stuff from ltpatch done . . . 671
\fbox: \long added 676
\mbox: \long added 672
\sbox: \long added 675
1994-10-18 ltclass.dtx v1.0j
General: Move \listfiles to ltfiles.dtx 818
1994-10-18 ltdefns.dtx v1.2a
\@star@or@long: macro added 81
General: Add extra test for \endgraf 78
Add star-forms for all commands . 78
\renew@environment: reset end command 85
1994-10-18 ltfiles.dtx v1.0i
\listfiles: code moved here from ltclass 352
1994-10-18 ltoutenc.dtx v1.5l
General: Added new definitions of \patterns and \hyphenation. . . 366
1994-10-18 ltoutenc.dtx v1.5m
General: Added new definitions of \patterns and \hyphenation. . . 354
1994-10-18 ltsect.dtx v1.0g
\@dottedtocline: Added \normalcolor for page number . 758
General: Added \normalcolor 747
1994-10-19 ltfssbas.dtx v2.1t
\DeclareFontEncoding: Add missing \relax. 414
1994-10-23 ltfsstrc.dtx v23.k
\every@math@size: Renamed to \every@math@size 467
1994-10-23 ltmath.dtx v1.0l
\@eqnnum: Added \normalcolor since \eqno introduces a subgroup of the displayed math group 648
\ensuremath: Remove extra braces: but see p 168 of Leslie's book . . 650
1994-10-24 ltboxes.dtx v1.0k
\fbox: Inner braces added (to fix latex/1061) 676
1994-10-25 fontdef.dtx v2.2c
General: Added OMSenc.def 548
1994-10-25 ltboxes.dtx v1.0l
\@isavepicbox: missing percent (moved from ltpatch) 675
1994-10-25 ltdefns.dtx v1.2b
General: Documentation improvements 78
1994-10-25 ltoutenc.dtx 1.6a
General: Added \textdollar, \textlbrace, \textrbrace, \textsterling, \textunderline. 372
Removed \textlbrace, \textrbrace, \textunderline to give them their proper names. . . 372
1994-10-25 ltoutenc.dtx v1.6a
General: Added \ProvideTextCommand, \UseTextSymbol, \UseTextAccent, \DeclareTextSymbolDefault, \DeclareTextAccentDefault, \DeclareTextCommandDefault, and \ProvideTextCommandDefault. . 354
Added the \Provide commands, and the default definitions. 358
Added the defaults. 366
Added the files OT1enc.def, T1enc.def and OMSenc.def. 366
Added the OMS encoding. 378
1994-10-27 ltoutenc.dtx 1.6b
General: Added \textasciicircum \textasciitilde \textbackslash \textbar \textbraceleft \textbraceright \textcompwordmark \textemdash \textendash \textexclamdown \textgreater \texthyphenchar \texthyphen \textless \textquestiondown \textquotedblleft \textquotedblright \textquotedbl \textquoteleft \textquoteright \textunderscore \textvisiblespace 372
Added: \textemdash \textendash \textexclamdown \texthyphenchar \texthyphen \textquestiondown \textquotedblleft \textquotedblright \textquoteleft \textquoteright 370
1994-10-27 ltoutenc.dtx v1.5d
General: Rewrote \DeclareTextSymbol to define its argument to use the current

encoding by default, to fit with \DeclareTextCommand. 358
1994-10-27 ltoutenc.dtx v1.6b
General: Added \textbackslash. . . 378
Added more defaults for OT1. . . 366
Removed the enc.def files 354
Removed the files OT1enc.def, T1enc.def and OMSenc.def. 366
Renamed \textlbrace to \textbraceleft and \textrbrace to \textbraceright. 378
1994-10-29 ltmath.dtx 1.0m
General: ASAJ: Added \DeclareMathOperator. 639
ASAJ: Tidied up documentation. 646
1994-10-29 ltmath.dtx v1.0m
General: ASAJ: Added \mathellipsis, \mathdollar and \mathsterling. 646
ASAJ: Removed \dag, \ddag. . . . 646
ASAJ: Renamed \S and \P to \mathsection and \mathparagraph and made them \mathchardefs. 646
1994-10-29 ltoutenc.dtx v1.6c
General: Added commands like \dots for use in text and math. 366
Renamed \P, \S, \dag and \ddag to \textparagraph, \textsection, \textdagger and \textdaggerdbl. 354
1994-10-30 ltdefns.dtx v1.2c
\@onelevel@sanitize: Macro added 104
General: (CAR)\@onelevel@sanitize added 78
1994-10-30 ltdefns.dtx v1.2f
General: (DPC)\newwrite's moved to ltfiles 78
1994-10-30 ltmath.dtx v1.0n
General: ASAJ: Moved the new commands to ltoutenc. 646
1994-10-30 ltoutenc.dtx v1.6d
General: Added \DeclareTextCompositeCommand. 354
Added \textcircled. . 354, 368, 378
Added \t. 368
Added math commands. 354
Added OML encoding. 354, 368
Added the OML encoding. 379
Made \textless and \textgreater come from OML. 368
Moved math commands here from ltmath. 370
Removed \textregistered. 368
Rewrote \copyright to use \textcircled. 368
1994-10-31 fontdef.dtx v2.2d
General: Added OMLenc.def 548
1994-10-31 fontdef.dtx v2.2e
General: ... and moved further down 548
1994-10-31 ltfloat.dtx v1.1a
\@dblfloat: Major changes since two-column and one-column cases merged 763
\@dblflset: Macro added 763
Major changes to parameter parsing, setting of local variables, etc; two-column and one-column cases merged; space hacks moved 763
\@endfloatbox: (DPC/CAR) Extra box added to remove colour resetting from vmode 769
\@floatboxreset: Macro added . . . 767
\@footnotetext: (DPC/CAR) Move colour setting to output routine . 779
\@savemarbox: (DPC/CAR) Extra box added for colour 773
\@setfps: Macro added 764
\@xdblfloat: Macros removed: \@dbflt, \@xdblfloat 769
\@xfloat: (DPC/CAR) Extra box added to remove colour resetting from vmode 765
Major changes, removing setting of local variables, space hacks etc; two-column and one-column cases merged 764
Reset hook added 765
\@xympar: (DPC/CAR) Extra box added since needed for floats . . . 774
\fps@dbl: Macro added 764
1994-10-31 ltoutput.dtx v1.1a
\@makecol: (DPC/CAR) Colour resetting moved to here 950
\@topnewpage: (DPC/CAR) Extra box added to remove colour resetting from vmode 942
(DPC/CAR) Use \color@begingroup for colour . . 942
(DPC/CAR) Use \normalcolor . 942
1994-11-02 ltoutenc.dtx v1.6d
General: Wrapped lines longer than 70 characters. 354
1994-11-03 ltclass.dtx v1.0k
General: Move \@missingfileerror to ltfiles 822

1994-11-03 ltdirchk.dtx v1.0i
General: Generate an error if latex.ltx not used with clean initex 1
1994-11-03 ltfiles.dtx v1.0j
`\@missingfileerror`: Move here from ltclass 350
1994-11-04 ltboxes.dtx v1.0m
`\@mpfootnotetext`: Added `\protected@edef`. ASAJ. 682
1994-11-04 ltdefns.dtx v1.2e
General: Added `\set@display@protect` to `\typeout`. ASAJ. 78
Added commands for setting and restoring `\protect`. ASAJ. 90
Rewrote protected short commands using `\x@protect`. ASAJ. 88
1994-11-04 lterror.dtx v1.2g
General: Added `\set@display@protect` to `\Generic*` commands. ASAJ. . . 281
1994-11-04 ltfiles.dtx v1.0k
`\nofiles`: Added setting of `\protected@write`, `\makeindex` and `\makeglossary` to `\nofiles`. ASAJ. 339
`\protected@write`: Macro added ASAJ. 339
1994-11-04 ltfloat.dtx v1.1b
`\@footnotetext`: (ASAJ) Added `\protected@edef`. 779
`\footnotemark`: Added `\protected@xdef` to `\footnotemark`. 780
1994-11-04 ltidxglo.dtx v1.1b
`\@wrglossary`: Added `\protected@write` to `\@wrglossary`. 785
`\@wrindex`: Added `\protected@write` to `\@wrindex`. 784
General: Removed `\if@filesw` from `\makeindex`. 783
`\makeglossary`: Removed `\if@filesw` from `\makeglossary`. 784
1994-11-04 ltmiscen.dtx v1.0t
`\@writefile`: Removed setting of `\protect`. ASAJ. 624
1994-11-04 ltoutenc.dtx v1.6f
General: Added `\_` 369
Added `\mathunderscore`. 370
1994-11-04 ltpage.dtx v1.0e
`\markright`: Added `\@unexpandable@protect`. ASAJ. 814
1994-11-04 ltsect.dtx 1.0h
`\@sect`: (ASAJ) Added `\protected@edef`. 751
General: (ASAJ) Added `\protected@xdef` to `\thanks`. . . 747
1994-11-04 ltsect.dtx v1.0h
General: Added `\protected@write` to `\addtocontents`. ASAJ. 757
`\addcontentsline`: Added `\protected@write` to `\addcontentsline`. ASAJ. . . . 756
1994-11-04 lttab.dtx v1.0h
`\@mkpream`: (ASAJ) Added `\@unexpandable@protect` to `\@mkpream`. 705
`\multicolumn`: (ASAJ) added `\set@typeset@protect`. 701
1994-11-04 ltxref.dtx v1.1d
`\label`: (ASAJ)Added `\protected@edef` 615
(ASAJ)Added `\protected@write` 615
1994-11-05 ltboxes.dtx v1.0n
`\@mpfootnotetext`: Color resetting for footnotes moved to endminipage: as for main page. 682
`\color@endbox`: macro added for color support 674
`\color@hbox`: macro added for color support 674
`\endminipage`: Color resetting for footnotes moved to here: as for main page. 681
1994-11-05 ltboxes.dtx v1.0o
`\@mpfootnotetext`: Color groups restored here. 682
1994-11-05 ltfloat.dtx v1.1c
`\@dblflset`: Add compatibility with old version of `\@xfloat`. 763
`\@endfloatbox`: Use new `\color@hbox` concept. 769
`\@footnotetext`: Removed `\normalcolor` (again) 779
`\@savemarbox`: Use new `\color@hbox` concept. 773
`\@setfps`: Add compatibility with old version of `\@xfloat`. 764
`\@xfloat`: Add compatibility with old version of `\@xfloat`: but the arguments, provided at exorbitant cost, are now completely ignored 764
Use new `\color@hbox` concept. . . 765
`\@xympar`: Use new `\color@hbox` concept. 774

1994-11-05 ltoutenc.dtx v1.6g
General: Added setting of \@typeset@protect to \patterns and \hyphenation. 366
1994-11-05 ltoutput.dtx v1.1b
\@topnewpage: Use new \color@hbox concept. 942
\@writesetup: Change protect settings for new-style, protect-free aux-files. 953
Use new \color@hbox concept. . . 953
1994-11-05 ltoutput.dtx v1.1c
\@begindvi: Added macro 957
\@begindvibox: Added macro 938
\@writesetup: Add new \AtBeginDvi concept 953
\AtBeginDvi: Added macro 938
1994-11-06 ltfssbas.dtx v2.1u
\cf@encoding: New macro 420
\DeclareFixedFont: Renamed \every@size to \every@math@size. 412
1994-11-06 ltfssini.dtx v2.2b
\@setsize: Use \@typeset@protect 540
1994-11-06 ltfsstrc.dtx v2.3k
\glb@currsize: New implementation 466
\try@simples: New implementation 477
\try@size@substitution: New implementation 477
\tryis@simple: New implementation 477
1994-11-07 fontdef.dtx v2.2f
General: (DPC) Add \DeclareMathSizes declarations 553
(DPC) Updated to use \ProvidesFile 548
1994-11-07 ltfiles.dtx v1.0m
\document: Renamed \every@size to \every@math@size. 335
1994-11-07 ltplain.dtx v1.0l
\@unused: move here from ltdefns, remove duplicate \@mainaux 24
1994-11-07 preload.dtx v2.1e
General: (DPC) Updated to use \ProvidesFile 567
1994-11-09 ltboxes.dtx v1.0p
\@finalstrut: Revert \finalstrut to 2.09 equivalent (from ltpatch) . . 685
General: more color changes... . . . 671
1994-11-09 ltfssbas.dtx v2.1v
\@vpt: (DPC) macros added, from setsize.dtx 435
(DPC) reduce save stack usage latex/1742 435
1994-11-10 ltbibl.dtx v1.1c
General: Fix \nocite{*} 786
\nocite: Fix \nocite{*} 789
1994-11-10 ltmath.dtx v1.2v classes
eqnarray: Added value of \parskip to \abovedisplayskip to compensate for negative \topsep 653
1994-11-10 ltoutput.dtx v1.1e
\@writesetup: Modify \protect setting 953
1994-11-10 ltplain.dtx v1.1b
General: (CAR) added patch to \loop. 15
\iterate: (CAR) added extra \relax 31
1994-11-11 ltspace.dtx v1.2a
\\: (DPC) Make robust 316
1994-11-12 ltfntcmd.dtx v3.3o
\normalsize: Added \MessageBreak 578
1994-11-12 ltlists.dtx v1.2b ltspace
\endtrivlist: Changed order of tests to make \@noitemerror correct: end of an era. 663
1994-11-12 ltmiscen.dtx v1.0u
center: Changed end macro to \def: safer and consistent 631
flushleft: Changed end macro to \def: safer and consistent 632
flushright: Changed end macro to \def: safer and consistent 632
1994-11-12 ltplain.dtx v1.1c
General: Comment out more encoding specific commands 33
1994-11-12 ltspace.dtx v1.2b
\addpenalty: Corrected error message 324
\addvspace: Corrected error message 323
1994-11-13 ltspace.dtx v1.2c
\addpenalty: Recorrected error message 324
\addvspace: Recorrected error message 323
1994-11-14 ltoutput.dtx v1.1f
\@begindvi: Use normal box register: why a box? 957
\@begindvibox: Use normal box register: why a box? 938
\@writesetup: Modify new \AtBeginDvi concept 953
General: Removed old definition of \@testfp. 926
1994-11-14 ltspace.dtx v1.2d
\\: (DPC) Macro modified 316
1994-11-14 lttab.dtx v1.0i
\tabularnewline: (DPC) Macro added 700

1994-11-16 fontdef.dtx v2.2h
General: (DPC) Removed \{ and \} 548
1994-11-17 ltboxes.dtx v1.0q
General: \@tempa to \reserved@a . . 671
1994-11-17 ltclass.dtx v1.0l
General: \@tempa to \reserved@a . . 818
1994-11-17 ltcntrl.dtx v1.0b
General: \@tempa to \reserved@a . . 277
1994-11-17 ltdefns.dtx v1.0g
General: \@tempa to \reserved@a . . . 78
1994-11-17 ltdirchk.dtx v1.0j
General: \@tempa to \reserved@a 1
1994-11-17 lterror.dtx v1.2h
General: \@tempa to \reserved@a . . 281
1994-11-17 ltfiles.dtx v1.0n
General: \@tempa to \reserved@a . . 332
1994-11-17 ltfinal.dtx v1.0o
General: \@tempa to \reserved@a . 1003
1994-11-17 ltfloat.dtx v1.1e
General: \@tempa to \reserved@a . . 760
1994-11-17 ltfntcmd.dtx v3.3p
General: \@tempa to \reserved@a . . 570
1994-11-17 ltfssbas.dtx v2.1w
General: \@tempa to \reserved@a . . 410
1994-11-17 ltfssdcl.dtx v2.1m
General: \@tempa to \reserved@a . . 488
1994-11-17 ltfsstrc.dtx v2.3l
General: \@tempa to \reserved@a . . 458
1994-11-17 ltmath.dtx v1.0o
General: \@tempa to \reserved@a . . 639
1994-11-17 ltmiscen.dtx v1.0v
General: \@tempa to \reserved@a . . 618
1994-11-17 ltoutenc.dtx v1.6h
General: (DPC) \@tempa to \reserved@a 354
1994-11-17 ltoutput.dtx v1.1h
General: \@tempa to \reserved@a. . 926
1994-11-17 ltpictur.dtx v1.0f
General: \@tempa to \reserved@a . . 711
1994-11-17 ltsect.dtx v1.0i
General: \@tempa to \reserved@a . . 747
1994-11-17 lttab.dtx v1.0j
General: \@tempa to \reserved@a . . 686
1994-11-18 ltboxes.dtx v1.0r
\color@vbox: macro added for color support 674
1994-11-18 ltfinal.dtx v1.0n
General: re-allow slots 127–255 . . . 1015
1994-11-18 ltfssbas.dtx v2.1x
General: (DPC) use \reserved@f not \next 410
1994-11-18 ltfssdcl.dtx v2.1m
\DeclareMathDelimiter: (DPC) \expandafter instead of \next . 510
1994-11-18 ltfsstrc.dtx v2.3m
General: \next to \reserved@f . . . 458
1994-11-18 ltmath.dtx v1.0p
\phantom: (DPC) colour support . . 641
(DPC) use \expandafter instead of \next 641
\prime@s: (DPC) use \@let@token instead of \next and \expandafter instead of \nxt . . 646
\smash: (DPC) colour support 642
(DPC) use \expandafter instead of \next 642
1994-11-21 ltfloat.dtx v1.1f
\@endfloatbox: Added reset of minipage flag 769
Corrected position of \outer@nobreak 769
\@marginparreset: Macro added . . 773
\@savemarbox: Added \@setminipage etc 773
Added resetting of size and font . 773
Changed to \color@vbox 773
Use \@setnobreak etc 773
\@setminipage: Macro added 767
\@setnobreak: Macro added 767
\@xfloat: Added \@setminipage . . 765
Added resetting of size and font . 765
Changed to \color@vbox so that large floats overflow at the bottom 765
Missing percents reinserted after 4, 8: these are not numbers. 764
Use \@setnobreak 765
\@xympar: Changed to \color@vbox 774
1994-11-21 ltoutput.dtx v1.1i
\@addtocurcol: Added \if@nobreak test before float box 968, 971
\@specialoutput: Added \if@nobreak test 946
\@topnewpage: Changed to \color@vbox 942
1994-11-22 ltfssdcl.dtx v2.1o
General: wrap long lines 488
1994-11-22 ltoutenc.dtx v1.6i
General: Corrected \dots so that there's no kerning in monowidth fonts. 354
Corrected typo with \mathunderscore. 354
Fixed empty accents. Again. . . . 354
1994-11-24 ltdefns.dtx v1.2h
\@newenv: Added test for \endgraf . . 85

1994-11-25 ltplain.dtx v1.1f
General: (DPC) Comment out lots of obsolete code 15
1994-11-26 ltfloat.dtx v1.1b
`\footnote`: (ASAJ) Added `\protected@xdef`. 779
1994-11-28 ltcntrl.dtx v1.0c
General: Documentation improvements 277
1994-11-30 ltfiles.dtx v1.0o
`\@dofilelist`: Macro added 353
`\listfiles`: Use `\@dofilelist` . . . 352
`\nofiles`: There is no `\@gobblethree`... 339
1994-11-30 ltfssbas.dtx v2.1y
`\fontshape`: Use `\@current@cmd` in `\@@enc@update`. ASAJ. 419
1994-11-30 ltmath.dtx 1.0q
General: ASAJ: `\DeclareMathOperator` moved to AMSLaTeX. 639
1994-11-30 ltmiscen.dtx v1.0w
`\@enddocument@kernel@warnings`: (DPC) Do warnings even for `\nofiles` 620
`\enddocument`: (DPC) Use `\@dofilelist` 620
1994-11-30 ltoutenc.dtx 1.7a
General: Redefined `\a` for the new scheme. 366
1994-11-30 ltoutenc.dtx v1.6g
General: Removed new definitions of `\patterns` and `\hyphenation`, since encoding-specific commands now expand in the mouth. 366
1994-11-30 ltoutenc.dtx v1.7a
General: Added new code for encoding-specific commands. These now expand in the mouth, which means that ligaturing and kerning can happen. 354
Always load the enc.def file, so that the default encoding for the commands will change. 397
Redefined `\@changed@cmd` to expand in the mouth. 358
Removed `\@changed@x@mouth` since `\@changed@x` now expands in the mouth. 358
Rewrote `\@text@composite` so it allows an empty argument, or an argument containing lots of commands. 360
1994-12-01 ltfinal.dtx v1.0p
General: Renamed lthyphen.* to hyphen.*. 1003
1994-12-01 lthyphen.dtx v1.0g
General: Rename lthyphen.ltx/cfg to hyphen.ltx/cfg 1001
1994-12-01 ltplain.dtx v1.1g
General: (DPC) More doc changes . . 15
1994-12-02 fontdef.dtx v2.2i
General: Commented out `\ldots`. ASAJ. 546
1994-12-02 ltfssini.dtx v2.2c
`\copyright`: `\copyright` is now in ltoutenc. ASAJ 541
1994-12-02 ltlists.dtx v1.0e
`\@trivlist`: RmS: Added check for looping 662
1994-12-02 ltoutenc.dtx 1.7b
General: Redefined `\a` properly. . . . 366
1994-12-02 ltoutenc.dtx v1.7b
General: Fixed a bug with `\a`. 354
1994-12-04 lthyphen.dtx v1.0h
General: Documentation edits for /1989 1001
1994-12-05 ltoutenc.dtx v1.7c
General: Added braces to `\textcircled`. 354
1994-12-06 ltfssbas.dtx v2.1z
`\DeclareFontEncoding`: use `\nfss@catcodes` 414
`\nfss@catcodes`: Added tab char as well 424
1994-12-08 ltoutenc.dtx v1.7d
General: Added `\null` and `\sh@ft` to `\b` and `\d`. 354
1994-12-08 lttab.dtx v1.0k
`\@array`: Add `\tabularnewline` . . . 699
`\tabularnewline`: (DPC) Made it `\relax` 700
1994-12-09 ltbibl.dtx v1.1d
`\bibliographystyle`: (DPC) Allow use in preamble. 789
1994-12-10 ltfloat.dtx v1.1g
`\@dblfloat`: Old version reinstated temporarily 763
`\@dblflset`: Macro removed temporarily 763
Old version reinstated temporarily 763
`\@setfps`: Macro removed temporarily 764
`\@xdblfloat`: Macros reinserted temporarily 769
`\@xfloat`: Old version reinstated temporarily 764

Sanitization added temporarily . . 764
General: Some temps reinserted temporarily 760
`\fps@dbl`: Macro removed temporarily 764
1994-12-10 ltfntcmd.dtx v3.3q
`\@@math@egroup`: Don't read arguments 577
`\check@nocorr@`: Use `\space` command for comparison 574
1994-12-10 ltfssdcl.dtx v2.1p
`\document@select@group`: Surround with braces (add fourth arg) . . . 494
`\select@group`: Surround with braces (add fourth arg) 491
1994-12-10 ltoutenc.dtx v1.7e
General: Added documentation for the OML encoding. 354
Replaced width with `\@width` and ditto height in vrules. 354
1994-12-14 ltoutenc.dtx v1.7f
General: Added braces to `\copyright` so it works unbraced in subscripts. 354
Added check for math mode in `\@changed@cmd`. 354
Commented out `\textasciicircum`, `\textasciitilde`, `\textbackslash`, `\textbar`, `\textgreater`, `\texthyphenchar`, `\texthyphen` and `\textless` to save memory. 354
1995-01-12 ltmath.dtx v1.2y classes
`\@eqnnum`: Added `\normalcolor` . . . 651
1995-03-03 ltoutenc.dtx 1.7g
General: Corrected an error in documentation referring to the tabular rather than the tabbing environment. 366
1995-04-02 ltfntcmd.dtx v3.3r
`\@@math@egroup`: Read them again to be able to add `\relax`. 577
1995-04-02 ltfssdcl.dtx v2.1q
`\document@select@group`: fix problem for pr/1275 494
`\select@group`: fix problem for pr/1275 491
`\set@mathdelimiter`: fix pr/1329 . . 512
1995-04-02 ltfssini.dtx v2.2d
`\not@math@alphabet`: add `\noexpand` to second part of message 539
1995-04-21 ltclass.dtx v1.0m
`\DeclareOption*`: Made long /1498 833
`\endfilecontents`: Close input check stream: latex/1487 851
1995-04-21 ltfinal.dtx v1.0q
General: Allow initial patch level 0 1018
1995-04-21 ltoutenc.dtx v1.7h
General: Added `\null` `\k` latex/1274 354
1995-04-22 ltfiles.dtx v1.0p
`\includeonly`: Allow blanks in argument 340
1995-04-22 ltmiscen.dtx v1.0x
General: Removed extra def of `\@gobble` 618
1995-04-23 ltsect.dtx v1.0j
`\addcontentsline`: Use `\contentsline` internally. 756
1995-04-24 ltbibl.dtx v1.1e
`\@citex`: Add `\mbox` to undefined case: latex/1239. 788
1995-04-24 ltbibl.dtx v1.1f
`\bibcite`: Make `\@onlypreamble` /1388. 787
1995-04-24 ltcntrl.dtx v1.0d
`\@for`: Don't expand second argument with `\edef`: /1317 (DPC) 280
1995-04-24 ltoutput.dtx v1.1j
`\fl@tracemessage`: Do not add to kernel unless 'trace' specified . . . 985
1995-04-24 ltoutput.dtx v1.1l
`\@begindvibox`: Add `\vbox` latex/1392 938
`\@writesetup`: Reset `\\` latex/1451 (DPC) 954
1995-04-24 ltpage.dtx v1.0f
`\fussy`: reset `\emergencystretch` latex/1344 817
1995-04-24 ltplain.dtx v1.1h
`\newlanguage`: Remove remaining `\outer` declarations. 18
1995-04-24 ltxref.dtx v1.1e
`\newlabel`: Make `\@onlypreamble` for /1388. 614
1995-04-25 ltdefns.dtx v1.2i
`\@check@c`: Make `\long` for latex/1346 86
`\new@environment`: Parse arguments slowly but safely /1507 84
1995-04-25 ltfiles.dtx v1.0q
`\document`: Removed execution of `\every@size` latex/1407 335
1995-04-25 ltsect.dtx v1.0k
`\@dottedtocline`: Added `\hbox` around dots. 758
1995-04-27 ltboxes.dtx v1.0s
`\@frameb@x`: Move `\leavevmode` for graphics/1512 677

\@iframebox: Move \leavevmode for graphics/1512 677
\@iirsbox: Move \leavevmode for graphics/1512 684
\@irsbox: Move \leavevmode for graphics/1512 684
\fbox: Move \leavevmode for graphics/1512 676
\raisebox: Move \leavevmode for graphics/1512 684
1995-04-27 ltfiles.dtx v1.0r
\document: Added \global to support groups in hook 336
1995-04-27 ltmiscen.dtx v1.0y
\enddocument: \@checkend moved after hook 619
1995-04-27 ltplain.dtx v1.1i
General: Move \hang and \textindent to latex209.def 33
1995-04-29 ltcntrl.dtx v1.0e
General: Moved init of \protect to ltdefns.dtx 280
Removed unused defs for \@setprotect and \@resetprotect 280
1995-04-29 ltdefns.dtx v1.2j
\protect: Init \protect here 90
1995-04-29 ltpar.dtx v1.1b
General: (TO) Comments clean-up. 292
1995-05-02 ltsect.dtx v1.0l
\@dottedtocline: Don't reset to \rmfamily 758
1995-05-03 ltsect.dtx v1.0m
General: TO: Promoted documentation to doc.sty standard 747
1995-05-06 ltsect.dtx 1.0n
\@seccntformat: Use \quad instead of \hskip 753
\@sect: Added \relax after \@seccntformat just in case . . . 751
1995-05-07 ltboxes.dtx v1.0t
General: Use \hb@xt@ 671
1995-05-07 ltdefns.dtx v1.2k
\hb@xt@: Macro added 79
1995-05-07 ltmath.dtx v1.0r
General: Use \hb@xt@ 639
1995-05-07 ltoutput.dtx v1.1m
General: Use \hb@xt@. 926
1995-05-07 ltpictur.dtx v1.0g
General: Use \hb@xt@ 711
1995-05-07 ltplain.dtx v1.1j
General: Use \hb@xt@ 15
1995-05-07 ltsect.dtx v1.0o
General: Use \hb@xt@ 747
1995-05-07 lttab.dtx v1.0l
General: Use \hb@xt@ 686
1995-05-08 ltbibl.dtx v1.1g
\@citex: Use \@firstofone 788
\bibitem: Removed unnecessary braces 787
\nocite: Use \@firstofone 789
1995-05-08 ltdefns.dtx v1.2k
\typein: Use \@firstofone 80
1995-05-08 ltdefns.dtx v1.2l
\typein: Remove unnecessary braces 80
Replace \def by \let 80
1995-05-08 ltfsstrc.dtx v2.3n
\ifnot@nil: Use \@firstofone . . . 471
1995-05-11 fontdef.dtx v2.2j
General: Updates to some plain macros 546
1995-05-12 ltclass.dtx v1.0n
\DeclareOption*: Use \toks@ to remove need to double hash /1557 833
1995-05-12 ltfloat.dtx v1.1h
\@footnotemark: Add \nobreak to allow hyphenation. latex/1605 . . 781
1995-05-12 ltpictur.dtx v1.0h
\pictur@: Macro added for latex/1355 713
1995-05-12 ltvers.dtx v1.0e
General: Add autoload docstrip guards 39
Check for format older than 1 year 39
1995-05-13 ltfsstrc.dtx v2.3o
General: Use single hash mark in \DeclareOption 459
1995-05-16 ltfloat.dtx v1.1i
\@makefnmark: Now use \textsuperscript. 778
\textsuperscript: Command added./pr1503 778
\thefootnote: Streamlined parts of code. 777
1995-05-17 ltboxes.dtx v1.0u
\@irsbox: Removed surplus braces . 684
1995-05-17 ltdefns.dtx v1.0o
\g@addto@macro: Make long for latex/1522 107
1995-05-17 ltlists.dtx v1.0g
\@item: Removed surplus braces . . . 666
\@nbitem: Removed surplus braces . 667
enumerate: Use \thr@@ and remove surplus braces 668
itemize: Use \thr@@ 669
1995-05-18 ltfloat.dtx v1.1j
\@makefnmark: Added \normalfont. 778

\thempfootnote: Added \itshape. . 777
1995-05-19 ltpictur.dtx v1.1a
General: Support autoloading feature 711
1995-05-20 ltcounts.dtx v1.1b
\@definecounter: Streamlined code 402
\@fnsymbol: Allowing both text and math 406
\fnsymbol: Streamlined code 405
1995-05-20 ltcounts.dtx v1.1c
\@definecounter: And do it right . 402
1995-05-20 ltfloat.dtx v1.1k
\@makefnmark: Moved \normalfont back and use \@textsuperscript 778
Moved \normalfont to \textsuperscript 778
\textsuperscript: Use \normalfont. 778
1995-05-21 ltfssdcl.dtx v2.1t
\DeclareMathRadical: Allow for undefined cs names 513
1995-05-21 ltlists.dtx v1.0f
General: Moved to doc.sty standard 654
1995-05-21 ltmath.dtx v1.0r
\@sqrt: Use \sqrtsign 648
General: Remove \mathhexbox from this file 644
Update some plain macros 639
\lefteqn: Use \rlap 650
\r@@t: Use \sqrtsign instead of \sqrt 641
1995-05-21 ltoutenc.dtx v1.7h
\@inmathwarn: Added several \@onlypreamble 358
1995-05-21 ltoutenc.dtx v1.7j
General: Updated some plain macros 370
1995-05-21 ltplain.dtx v1.1j
General: Moved some code to other files 15
1995-05-22 ltplain.dtx v1.1k
General: Definitions of \footins and \footnoterule moved to ltfloat. . 34
1995-05-22 lttab.dtx v1.1a
General: Support autoloading feature 686
1995-05-23 ltfssini.dtx v2.2e
\newfont: Font assignment made local again. 540
1995-05-24 ltdefns.dtx v1.1l
\newif: (DPC) New implementation . 85
1995-05-24 ltdefns.dtx v1.2m
\typein: (DPC) New implementation 80
1995-05-24 ltfloat.dtx v1.1l
\@textsuperscript: Command added. 778
General: Moved definition of \footins and \footnoterule from ltplain. 777
\textsuperscript: Use \@textsuperscript 778
1995-05-24 ltfssbas.dtx v3.0a
General: (DPC) Make file from previous file, fam.dtx 1995/05/20 v2.2d 410
\mathgroup: (DPC) No need to redefine \newfam as not outer . . 410
1995-05-24 ltfsscmp.dtx v3.0a
General: (DPC) Make file from previous file, fam.dtx 1995/05/20 v2.2d 483
1995-05-24 ltfssdcl.dtx v3.0a
General: (DPC) Make file from previous file, latint.dtx 1995/05/21 v2.1t 488
1995-05-24 ltfssini.dtx v3.0a
General: (DPC) Make file from previous file, lfonts.dtx 1995/05/23 v2.2e 518
\cal: (DPC) Remove definition . . . 544
\mit: (DPC) Remove definition . . . 544
1995-05-24 ltfsstrc.dtx v3.0a
General: (DPC) Make file from previous file, tracefnt 1995/05/16 v2.3o 458
1995-05-24 ltfsstrc.dtx v3.0b
General: (DPC) Fix \ProvidesFile usage 458
1995-05-25 ltclass.dtx v1.0p
\endfilecontents: Delete \filec@ntents after preamble . . 851
1995-05-25 ltfilehook.dtx v1.0t
\unqu@tefilef@und: (CAR) added \long 885
1995-05-25 ltfiles.dtx v1.0s
\document: Added check for \topskip zero 336
1995-05-25 ltfiles.dtx v1.0t
\@iffileonpath: (CAR) added \long 348
\document: Corrected typo 336
\IfFileExists@: (CAR) added \long 347
\nofiles: (CAR) added \long 339
\protected@write: (CAR) added \long 339
1995-05-25 ltfloat.dtx v1.1m
\@savemarbox: (CAR) Resettings moved to hook 773
\@xfloat: (CAR) Resettings moved to hook 765
1995-05-25 ltlists.dtx v1.0i
\endtrivlist: Macros moved from ltspace.dtx 663

1995-05-25 ltmath.dtx v1.3c classes
\\@eqnnum: replace \\reset@font\\rmfamily with \\normalfont (PR 1578) 651
1995-05-25 ltspace.dtx v1.2f
\\@vbsphack: (CAR) not used so 'removed'. 322
\\@vspacer: (CAR) \\@restorepar added to avoid possible infinite tail recursion caused by a typo in the argument. 325
(CAR) macros modified to be more efficient 325
General: Macros moved to ltlists.dtx 312
1995-05-26 ltdefns.dtx v1.2n
\\@gobblefour: (CAR) Added \\longs 87
1995-05-26 ltmath.dtx v1.0s
\\@eqnnum: Removed \\rmfamily (PR 1578), replaced \\reset@font with \\normalfont 648
1995-05-26 ltpage.dtx v1.0g
\\ps@plain: removed \\rmfamily (PR 1578) 814
1995-05-27 ltfssbas.dtx v3.0b
\\mathgroup: (FMi) But a need to define \\new@mathgroup 410
1995-06-05 fontdef.dtx v2.2k
General: Moved math commands from ltoutenc.dtx. 564
1995-06-05 ltfinal.dtx v1.0r
General: Added \\MakeUppercase and \\MakeLowercase. 1003
1995-06-05 ltoutenc.dtx v1.7k
\\@inmathwarn: Removed \\protected@cmd and replaced with explicit \\noexpand. 358
General: Allowed \\ProvideTextCommandDefault after the preamble. 360
Commented out \\textless and \\textgreater. 368
Moved math commands to fontdef.dtx. 370
Save some tokens in \\textvisiblespace and \\textunderscore. 368
1995-06-06 ltfinal.dtx v1.0s
General: Made \\MakeUppercase and \\MakeLowercase brace their argument. 1003
1995-06-09 ltoutenc.dtx v1.7l
\\DeclareTextComposite: Rewrote \\DeclareTextComposite to define the composite as a no-argument command rather than a two-argument command. 361
1995-06-11 ltspace.dtx v1.2g
\\restorecr: (CAR) \\relax added to stop silent eating of *. 330
1995-06-13 ltfinal.dtx v1.0t
General: Add patch level string more carefully 1018
Call \\errorstopmode 1020
1995-06-13 ltpictur.dtx v1.1b
General: Use \\ProvidesFile in autoload 711
1995-06-14 lttab.dtx v1.1b
General: Use \\ProvidesFile in autoload 686
1995-06-15 ltfssbas.dtx v3.0c
General: (DPC) minor documentation changes 410
1995-06-15 ltfsscmp.dtx v3.0b
General: (DPC) minor documentation edits 483
1995-06-15 ltfssdcl.dtx v3.0b
General: (DPC) minor documentation changes 488
1995-06-19 ltbibl.dtx v1.1h
\\bibcite: Call \\@newl@bel so repeated keys produce better warning. 787
1995-06-19 ltclass.dtx v1.0q
\\documentclass: Don't redefine \\usepackage in compat mode for /1634 838
1995-06-19 ltxref.dtx v1.1e
\\newlabel: Use \\@newl@bel to share code with \\bibcite 614
1995-06-28 ltfssini.dtx v3.0b
General: (DPC) Fix documentation typos 518
1995-06-28 ltmath.dtx v1.0t
General: minor doc edits 639
1995-07-02 ltplain.dtx v1.1n
General: Removed surplus 'by' and '=' in various places 15
\\offinterlineskip: Replaced 1000 by \\@m 31
\\showoutput: Use \\showoverfull to save space 34
\\tracingall: Use \\showoutput to save space 35
1995-07-03 ltdefns.dtx v1.2o
\\set@typeset@protect: Use \\@typeset@protect for init 90

1995-07-03 ltfntcmd.dtx v3.3s
\t@st@ic: Use clean interface for jump 576
1995-07-05 ltfntcmd.dtx v3.3s
\t@st@ic: Renamed from \test@next 576
1995-07-05 ltspace.dtx v1.2h
\@gnewline: Use \break 318
\@no@pgbk: Macro replaces \@pgbk and \@nopgbk 316
\nopagebreak: Reimplemented both using \@no@pgbk 315
1995-07-09 ltcntrl.dtx v1.0f
\@iforloop: Reimplemented using Kabelschacht method 280
\@iwhiledim: Reimplemented using Kabelschacht method 278
\@iwhilenum: Reimplemented using Kabelschacht method 278
\@iwhilesw: Reimplemented using Kabelschacht method 278
\@tfor: Reimplemented using Kabelschacht method 280
1995-07-09 ltlists.dtx v1.0j
enumerate: Use \expandafter 668
itemize: Use \expandafter 669
1995-07-12 ltpictur.dtx v1.1d
General: allow 2e commands in 209 mode. latex/1737 711
1995-07-13 ltdefns.dtx v1.0p
General: Updates to documentation . 78
1995-07-13 ltfiles.dtx v1.0u
General: Updates to docu 332
1995-07-13 ltfssbas.dtx v3.0d
\@@defaultsubs: macro added 430
\@defaultsubs: macro added 430
General: minor documentation changes 410
\wrong@fontshape: Change a macro not a switch to flag default font substitutions 429
1995-07-13 ltmiscen.dtx v1.0z
\@centercr: Use \nobreak 630
\@enddocument@kernel@warnings: Use \@defaultsubs instead of switch 621
\@writefile: Added missing percent and use \relax in the THEN case 624
\@xobeysp: Use \nobreak 633
General: Improve Documentation . . 618
\enddocument: Set \@setckpt to \@gobbletwo instead of defining it by hand 619
Shorten redefinition of \bibcite and \newlabel 620
1995-07-14 ltbibl.dtx v1.1i
\bibcite: Remove \@onlypreamble so still defined in new \enddocument 787
1995-07-14 ltxref.dtx v1.1g
\newlabel: Remove \@onlypreamble so still defined in new \enddocument 614
1995-07-19 ltfssini.dtx v3.0d
General: (DPC) TeX2 support 544
1995-07-20 ltboxes.dtx v1.0v
\@isavebox: Use \sbox 675
\@isavepicbox: Use \sbox 675
1995-07-21 ltoutput.dtx v1.1o
\@writesetup: Command added . . . 953
New, experimental, versions: need in-lining 953
1995-08-09 ltmath.dtx v1.0u
General: Added code for class options leqno and fleqn 651
1995-08-11 ltlength.dtx v1.1b
General: Doc typos fixed for latex/753 408
1995-08-16 ltcntrl.dtx v1.0g
\@break@tfor: Made long 280
\@forloop: Made defs long 280
\@fornoop: Made defs long 280
\@iforloop: Made defs long 280
\@iwhiledim: Made defs long 278
Removed \@whilenoop 278
\@iwhilenum: Made defs long 278
Removed \@whilenoop 278
\@iwhilesw: Removed \@whileswnoop 278
\@tfor: Made defs long 280
1995-08-16 ltfiles.dtx v1.0v
\document: set \@maxdepth 336
set \do globally 336
set \topskip globally 336
1995-08-24 ltfssbas.dtx v3.0f
General: Added autoload code 410
1995-08-24 ltfsstrc.dtx v3.0c
General: Macro \gobble@font@spec removed 472
\tryis@simple: 479
1995-08-25 ltoutput.dtx v1.1p
General: Support autoloading feature (FMi). 926
1995-09-01 lterror.dtx v1.2i
General: Add autoload support . . . 281
1995-09-01 ltplain.dtx v1.1m
\empty: Use \let to save space 29
\I: Use \let to save space 28

1995-09-14 ltplain.dtx v1.1o
General: Moved \multispan to lttab.dtx 15
1995-09-14 lttab.dtx v1.1c
\cline: (DPC) New implementation 709
1995-09-15 ltfssini.dtx v3.0e
General: (DPC) Modify TeX2 message 544
1995-09-19 ltmiscen.dtx v1.1a
\verb: Put \@noligs after \verbatim@font where it belongs. 638
1995-10-01 ltfiles.dtx LaTeX2e
\@addtofilelist: Macro added . . . 352
1995-10-02 ltdefns.dtx v1.2q
\@ifnch: Use \@let@token for internal/924, save \reserved@e . 103
\@ifnextchar: Use \@let@token . . 102
\@protected@testopt: Macro added . 83
\@testopt: Macro added 82
\@xargdef: New implementation, using \@test@opt 82
1995-10-03 fontdef.dtx v2.2l
General: \@@sqrt from patch file for /1701 546
1995-10-03 ltdefns.dtx v1.2r
\typein: Add missing \@typein for /1710 (from patch file) 80
1995-10-03 ltpictur.dtx v1.1e
General: New autoload code 711
1995-10-04 ltfssbas.dtx v3.0g
General: Modify autoload code 410
1995-10-04 ltfsstrc.dtx v3.0d
General: (DPC) Modify autoload code 458
1995-10-04 lttab.dtx v1.1d
General: Modify autoload support . 686
1995-10-06 ltfiles.dtx v1.0w
\@missingfileerror: Autoload error 350
1995-10-09 lterror.dtx v1.2j
General: Modify autoload support . 281
1995-10-09 ltoutenc.dtx v1.7m
\@inmathwarn: Autoload error 359
1995-10-10 ltfssbas.dtx v3.0h
\showhyphens: Use \normalfont and make colour safe, and autoloadable 433
1995-10-10 ltfssdcl.dtx v3.0c
\non@alpherr: (DPC) autoload error message 492
1995-10-10 ltplain.dtx v1.1r
General: Autoload tracing code 15
1995-10-10 ltthm.dtx v1.0f
General: Make \newtheorem 'only preamble' 743
1995-10-11 ltoutput.dtx v1.1r
\clearpage: Added a check so that it does not lose the argument of \twocolumn[...] 939
1995-10-16 ltbibl.dtx v1.1j
\cite: (DPC) Make robust 787
1995-10-16 ltboxes.dtx v1.0w
General: Clarify makebox description 671
1995-10-16 ltdefns.dtx v1.2u
\@ifstar: (DPC) New implementation, for /1910 103
\new@command: (DPC) Use \@testopt /1911 82
\new@environment: (DPC) Use \@testopt /1911 84
\typein: (DPC) Use \@testopt /1911 80
1995-10-16 ltfssini.dtx v3.0f
\reset@font: Added \relax after \usefont, as the latter eats up spaces. 541
1995-10-16 ltmath.dtx v1.0y
\@yeqncr: (DPC) Use \@testopt /1911 649
\sqrt: (DPC) Make robust /1808 . . 648
1995-10-16 ltspace.dtx v1.2j
\nolinebreak: (DPC) Use \@testopt /1911 315
\nopagebreak: (DPC) Use \@testopt /1911 315
1995-10-16 ltthm.dtx v1.0g
General: Revert to previous \newtheorem behaviour 743
1995-10-17 ltclass.dtx v1.0r
\@providesfile: Delay definition of \ProvidesFile till ltfinal 832
\ProcessOptions*: Reset \CurrentOption for graphics/1873 836
1995-10-17 ltdirchk.dtx v1.0l
General: Modify initex version of \ProvidesFile 4
1995-10-17 ltfinal.dtx v1.0v
\@providesfile: reset macro 1019
\reserved@b: reset here after the \input above 1018
1995-10-17 ltplain.dtx v1.1s
\eject: Move \superreject to compat file 32
1995-10-17 lttab.dtx v1.1e
\@cline: (DPC) Use \@multicnt . . 709
\@multispan: (DPC) Macro added. 709
1995-10-19 ltfinal.dtx v1.0w
\@filelist: Move after \reserved@a setting:-) 1019

1995-10-20 ltbibl.dtx v1.1k
\\@citex: Removed refundefined flag 788
\\nocite: Removed refundefined flag 789
1995-10-20 ltclass.dtx v1.0s
\\@begindocumenthook: Make setting conditional, for autoload version 849
1995-10-20 ltfssbas.dtx v3.0i
General: (DPC) Modify autoload code, change \\undefined 410
1995-10-20 ltfsstrc.dtx v3.0e
General: (DPC) Modify autoload code 458
1995-10-22 ltfssbas.dtx v3.0j
General: (RmS) New size function macro \\genb@sfcnt needs to be disabled at \\document. 410
1995-10-22 ltfsstrc.dtx v3.0f
General: Added 'genb' and 'sgenb' size functions to support new DC font naming scheme. 458
1995-10-23 lttab.dtx v1.1f
\\@settab: (CAR)Ensure that \\@hightab increases by at most one 693
\\@startline: (CAR)Ensure that \\@nxttabmar is never larger than \\@hightab 691
\\poptabs: (CAR)Ensure that \\@curtab is never larger than \\@hightab 694
\\tabbing: (CAR)Make \\@hightab consistently a local variable 693
1995-10-24 ltfiles.dtx v1.1a
\\document: Removed multiplelabels switch 335
Removed refundefined switch . . . 335
1995-10-24 ltfssbas.dtx v3.0k
\\@@defaultsubs: macro removed . . 430
\\wrong@fontshape: Make this code inline since it happens only here 429
1995-10-24 ltmiscen.dtx v1.1b
\\@enddocument@kernel@warnings: Changed logic for producing warning messages and removed switch 621
Use \\@refundefined instead of switch 621
1995-10-24 ltxref.dtx v1.1h
\\@multiplelabels: Switch for multiplelabels removed 615
\\@newl@bel: Switch for multiplelabels replaced by inline code 615
\\@refundefined: Switch for refundefined replaced 613
\\@setref: Switch for refundefined renamed 614
\\if@multiplelabels: Macro removed 615
1995-10-25 ltalloc.dtx v1.1b
General: General doc improvements 275
1995-10-25 ltfloat.dtx v1.1n
\\@endfloatbox: (CAR) macro added: to unify code for double and single versions 769
\\end@dblfloat: (CAR) unify code for double and single versions 768
\\end@float: (CAR) unify code for double and single versions 767
1995-10-25 ltidxglo.dtx v1.1d
General: Doc cleanup 783
1995-10-25 ltsect.dtx v1.0q
\\subparagraphmark: Use \\let not \\def to save space. 755
1995-10-27 ltpictur.dtx v1.1f
General: Move initialization to kernel from autoload file 738
1995-10-31 ltboxes.dtx v1.0x
\\@finalstrut: Add \\nobreak in horiz mode to allow hyphenation. internal/1931 685
1995-11-01 fontdef.dtx v2.2m
General: add \\nfss@catcodes for internal/1932 549
1995-11-01 ltdirchk.dtx v1.0n
General: Initialise \\@addtofilelist to \\@gobble 4
1995-11-01 ltfinal.dtx v1.0x
General: (DPC) Switch meaning of \\@addtofilelist for cfg files . . 1009
1995-11-01 ltfssbas.dtx v3.0m
\\DeclareFontShape@: (DPC) Test for \\relax not \\undefined, internal/1933 411
1995-11-01 ltfssini.dtx v3.0g
General: (DPC) Switch meaning of \\@addtofilelist for cfg files . . . 544
1995-11-02 ltfssbas.dtx v3.0n
\\wrong@fontshape: (DPC) Remove extra space with \\string for latex/1676 428
1995-11-02 ltoutenc.dtx v1.7n
General: Changed internal name \\a to \\@tabacckludge to protect against redefinition by malicious users. . 366
1995-11-07 ltlists.dtx v1.0k
\\@doendpe: Enclosed \\setbox0 assignment by a group so that it leaves the contents of box 0 intact. 664

1995-11-07 ltoutenc.dtx v1.7o
General: Added \leavevmode at start of \c, otherwise the output routine might be invoked within the macro. 370
Changed \char32 to \@xxxii (two tokens less). 371
Replaced octal number 27 by decimal number 23 to protect against the quote character being active. 371
Replaced some 0's by \z@ (faster). 371
1995-11-10 ltoutput.dtx v1.1s
\@shipoutsetup: Command removed 953
\@writesetup: Command removed . 953
In-lined 953
1995-11-14 ltclass.dtx v1.0t
\@@unprocessedoptions: Allow empty option 850
\@loadwithoptions: macro added . 839
\LoadClassWithOptions: macro added 839
\RequirePackageWithOptions: macro added 839
1995-11-17 ltfssbas.dtx v3.0m
\@wrong@font@char: (DPC) Macro added. latex/1676 430
\define@newfont: Redefine \typeout latex/1676 423
\wrong@fontshape: Support \@wrong@font@char latex/1676 . 428
1995-11-17 ltoutenc.dtx v1.7p
\UseTextSymbol: Support \@wrong@font@char latex/1676 . 363
1995-11-18 ltoutenc.dtx v1.7q
\UseTextSymbol: Modify message slightly 363
1995-11-21 fontdef.dtx v2.2n
General: Incorporate changed figures, as in plain.tex 562
1995-11-27 ltfssbas.dtx v3.0n
\nfss@catcodes: Reset hash, for definitions in fd files 425
1995-11-28 ltfloat.dtx v1.1n
General: documentation fixes 760
1995-11-28 ltfsstrc.dtx v3.0g
General: documentation fixes 458
1995-11-28 ltoutenc.dtx v1.7r
General: Added math mode checks to text commands. 358
doc fixes 354
Renamed \@changed@x@err to \TextSymbolUnavailable. 358
1995-11-29 ltoutenc.dtx v1.7t
General: Added \textasciicircum, \textasciitilde, \textbackslash, \textbar, \textgreater and \textless. . . 374
Added \textasciicircum, \textasciitilde, \textregistered and \texttrademark. 368
Added \textbackslash and \textbar. 367, 378
Added \textless and \textgreater. 368, 379
1995-12-01 ltoutenc.dtx v1.7u
General: Made \SS a Default, rather than having the default point to the OT1 definition. 368
1995-12-04 ltspace.dtx v1.2k
\nobreakspace: (Macro added 328
1995-12-04 ltspace.dtx v1.2l
\@xobeysp: (braces added to definition of tilde 328
1995-12-04 preload.dtx v2.4e
General: Ulrik Vieth. added 12pt OMS and OML preloads /1989 . 569
1995-12-05 ltdefns.dtx 1.2w
\@unexpandable@protect: Removed \unexpandable@noexpand as never used. internal/1733 88
1995-12-05 ltfiles.dtx v1.1c
\document: \ignorespaces added for latex/1933 336
1995-12-05 ltfloat.dtx v1.1n
\@textsuperscript: Use \ensuremath for latex/1984. 778
1995-12-05 ltoutenc.dtx v1.7v
\@inmathwarn: Changed \TextSymbolUnavailable text . . 359
1995-12-06 ltfssbas.dtx v3.00
\nfss@catcodes: Reset hat, for typeouts etc in fd files 425
1995-12-07 ltbibl.dtx v1.1l
\@citex: Restored name of \G@refundefinedtrue 788
1995-12-07 ltfloat.dtx v1.1m
\@textsuperscript: Move \m@th out of the \ensuremath for latex/1984. 778
1995-12-07 ltxref.dtx v1.1i
\@setref: Switch for refundefined restored 614
\G@refundefinedtrue: Renamed (back) from \G@refundefined . . 613

1995-12-11 ltoutenc.dtx v1.7w
General: Modified \copyright 368
1995-12-13 ltdefns.dtx 1.2x
\-: Documentation changed. 105
1996-01-10 ltfiles.dtx v1.1d
\@iffileonpath: Change argument handling to not require doubled hash. latex/2024 348
1996-01-20 ltidxglo.dtx v1.1e
\makeglossary: Make no-op after use pr/2048 784
\makeindex: Make no-op after use pr/2048 784
1996-01-20 ltspace.dtx v1.2m
\vspace: Made robust 325
1996-03-25 ltmath.dtx v1.1a
\@ensuredmath: Macro added for amslatex/2104 651
\ensuremath: Reimplement for amslatex/2104 650
1996-04-18 ltpage.dtx v1.0i
General: Improve documentation . . 813
1996-04-22 ltmiscen.dtx v1.1c
General: Improve Documentation . . 618
1996-04-22 ltspace.dtx v1.2n
General: Documentation Improvements 312
1996-04-22 lttab.dtx v1.1g
\@tabclassz: (DPC) Extra \hskip keeps tabcolsep in empty columns internal/2122 706
1996-04-23 ltcounts.dtx v1.1d
General: Documentation improvements 400
1996-04-24 ltfiles.dtx v1.1e
\document: (DPC) Reset \AtBeginDocument eg for latex/1297 335
1996-05-08 ltfsstrc.dtx v3.0h
\math@egroup: Use \bgroup instead of \begingroup to match a kernel change made in 1994!! 470
1996-05-09 ltfntcmd.dtx v3.3t
\check@icr: Default definitions added 574
1996-05-17 fontdef.dtx v2.2o
General: \@@sqrt removed, at last 546, 562
1996-05-17 ltfiles.dtx v1.1f
\nofiles: added \write to \protected@write for latex/2146 339
1996-05-18 ltoutenc.dtx v1.7x
General: Produce error if encoding not found. pr/2054 397
1996-05-21 ltoutenc.dtx v1.7y
General: Corrected error message (CAR) 397
1996-05-21 ltsect.dtx v1.0s
\@sect: (DPC) Added extra braces for internal/2148 751
(DPC) Moved brace to allow commands like \MakeUppercase in 6th argument. Changed \par to \endgraf to allow non-long commands. internal/2148 751
\@ssect: (DPC) Added extra braces for internal/2148 754
(DPC) Moved brace to allow commands like \MakeUppercase in 4th argument. Changed \par to \endgraf to allow non-long commands. internal/2148 754
1996-05-23 ltoutenc.dtx v1.7z
\@strip@args: \expandafter added to match other changes for latex/2133 363
\add@accent: macro added. latex/2133 360
\DeclareTextAccent: Reimplemented using \add@accent to save space latex/2133 360
\DeclareTextCompositeCommand: Modified to cope with new \add@accent command: required removal of check for one argument-command 361
1996-05-24 ltoutput.dtx v1.1t
\@specialoutput: Check that \@colroom is less than \vsize, indicating that a float has been added 944
Cut-off point changed to 1.5\baselineskip 944
\@topnewpage: Cut-off point changed to 2.5\baselineskip 943
1996-05-25 ltoutput.dtx v1.1u
\@specialoutput: Correct the above check 944
1996-06-03 ltmiscen.dtx v1.1d
\@verbatim: Exchanged the following two code lines so that \dospecials cannot reset the category code of characters handled by \@noligs. 634
General: Move setting of verbatim font and \@noligs. 618
\verb: Put setting of verbatim font after \dospecials so that \dospecials cannot reset the

category code of characters handled by \@noligs. 638
1996-06-10 ltboxes.dtx v1.0y
\@parboxto: (DPC) Changed \endgraf to \@@par 679
1996-06-10 ltsect.dtx v1.0t
\@sect: (DPC) Changed \endgraf to \@@par 751
\@ssect: (DPC) Changed \endgraf to \@@par 754
1996-06-13 ltdirchk.dtx v1.0r
General: documentation improvements mainly from internal/2174 1
1996-06-14 lttab.dtx v1.1h
\@tabclassz: (DPC) Change both\z@skip to 1sp for latex/2160 706
1996-06-22 ltspace.dtx v1.2o
General: Documentation of problems added 312
1996-07-10 ltfinal.dtx v1.0y
\toks: Free up memory from scratch registers /2213 1019
1996-07-19 ltoutenc.dtx v1.8a
\@strip@args: Use char 0 not @ as carrier for \lowercase /2197 . . . 363
1996-07-26 ltboxes.dtx v1.0z
\if@minipage: put \global into definition 680
1996-07-26 ltclass.dtx v1.0u
\@classoptionslist: made only preamble 823
\@unusedoptionlist: made only preamble 823
1996-07-26 ltdefns.dtx v1.2y
\@reargdef: third arg picked up by \@yargdef 83
\renew@command: use \noexpand instead of \string 84
use \relax in place of empty arg . 84
\renew@environment: use \relax in place of empty arg 85
1996-07-26 ltfloat.dtx v1.1n
\@endfloatbox: remove unnecessary \global before \@minipage... . 769
\@savemarbox: remove unnecessary \global before \@minipage... . 773
\@setminipage: remove unnecessary \global before \@minipage... . 767
\@setnobreak: remove unnecessary \global before \@nobreak... . . 767
1996-07-26 ltfssbas.dtx v3.0p
\@DeclareMathSizes: use faster \if test 417
\nfss@catcodes: omit \relax as not needed 424
1996-07-26 ltfssdcl.dtx v3.0e
\init@restore@version: Removed \ifrestore@version switch and replaced by \init@restore@version 492
1996-07-26 ltfsstrc.dtx v3.0i
\init@restore@glb@settings: macro added replacing \if@inmath switch 469
1996-07-26 ltlists.dtx v1.0l
\@item: Remove unnecessary \global before \@minipage... 665
Remove unnecessary \global before \@nobreak... 666
1996-07-26 ltmath.dtx v1.1b
General: Removed \global before \@ignoretrue in various places. . 639
1996-07-26 ltmiscen.dtx v1.1e
\@ignorefalse: put \global into definition 619
\begin: remove \global before \@ignore... 625
\end: remove \global before \@ignore... 628
\ignorespacesafterend: user level macro added 619
1996-07-26 ltoutput.dtx v1.1v
\@testfp: remove \global before \@test... 989
\@xtryfc: remove \global before \@test... 962
\@ztryfc: remove \global before \@test... 963
General: put \global into definition 936
remove \global before \@test... 936
\clearpage: add number of missing percents 939
1996-07-26 ltplain.dtx v1.1t
\sh@ft: replace \dimen\z@ by \dimen@ 33
1996-07-26 ltsect.dtx v1.0u
\@starttoc: removed \global before \@nobreak... 756
\@xsect: Removed \global before \@nobreak... 752
1996-07-26 ltspace.dtx v1.2p
\if@nobreak: put \global inside definition 318
1996-07-27 ltfssbas.dtx v3.0q
General: \if@inmath switch removed 422
1996-07-27 ltspace.dtx v1.2q
General: Further documentation of problems 312

1996-07-27 ltspace.dtx v1.2r
General: Correct documentation of problems 312
1996-08-02 ltfloat.dtx v1.1o
\@xympar: Remove \global before \@ignore... 774
1996-08-02 ltsect.dtx v1.0v
\@afterheading: Removed \global before \@nobreak... 754
1996-08-02 ltspace.dtx v1.2s
\@Esphack: Remove \global before \@ignore... 321
1996-08-25 ltfssbas.dtx v3.0r
\nfss@catcodes: Reset the acute, grave and double quote chars as well 425
1996-09-21 ltoutput.dtx v1.1w
\@writesetup: Added \@parboxrestore and made consequent deletions: wait for the howls of protest 953
1996-09-25 ltdirchk.dtx v1.0t
General: Move ltxcheck to separate file 14
1996-09-28 ltmiscen.dtx v1.1f
\@xobeysp: Moved to ltspace.dtx . . 633
1996-09-28 ltspace.dtx v1.2t
\@xobeysp: Moved from ltmiscen.dtx and redefined to use \nobreakspace 328
1996-09-29 ltfiles.dtx v1.1g
\document: Added disabling of \@nodocument 336
1996-09-29 ltoutput.dtx v1.1x
\newpage: Checks for noskipsec and inlabel added 940
1996-09-29 ltsect.dtx 1.0w
\@noskipsectrue: Added documentation 748
1996-09-30 ltoutput.dtx v1.1y
\newpage: Checks for noskipsec and inlabel removed pending further tests 940
1996-10-04 ltclass.dtx v1.0v
\RequirePackageWithOptions: Reset \@unprocessedoptions for /2269 839
1996-10-05 ltfiles.dtx v1.1h
\@clubpenalty: Added setting its value 334
1996-10-08 ltfntcmd.dtx v3.3u
\DeclareTextFontCommand: Removed \check@icr when in vmode since it causes various errors (see pr/2157) 572
1996-10-21 lttab.dtx v1.1i
\@array: Use \set@typeset@protect 699
General: Moved the code associated with \@mkpream into the group provided by the box, for robustness (latex/2183) 698
\multicolumn: Make \multicolumn long (latex/2180) 701
\tabbing: Moved the \indent so that the \everypar can remove it when necessary; this is needed because the code for items in lists has changed (see pr/22111) 693
1996-10-23 ltlists.dtx v1.0m
\@item: \@nobreak... moved into the \everypar and not executed unconditionally, see above 666
\kern... changed to \setbox... 666
Added setting of \clubpenalty and set \@nobreakfalse only when necessary 666
1996-10-23 ltsect.dtx v1.0x
\@xsect: Replaced \hskip... with \setbox... as used in \@afterheading 752
1996-10-24 ltboxes.dtx v1.1a
\@arrayparboxrestore: Added local settings of flags: dangerous! 679
\@iiiminipage: Use it or lose it (@setminpage): Frank will want to lose it 681
1996-10-24 ltfloat.dtx v1.1p
\@floatboxreset: Added local settings of flags: dangerous! 767
\@marginparreset: Added local settings of flags: dangerous! 773
\@xfloat: Added \@nodocument to trap floats in the preamble 764
1996-10-24 ltoutput.dtx v1.1z
\@addtocurcol: Added \nobreak, etc as appropriate 968, 971
\@specialoutput: Added \nobreak as appropriate 946
\@topnewpage: Added \@nodocument to trap \twocolumn in the preamble 942
\newpage: Better checks for noskipsec and inlabel added, plus nobreak . 940
1996-10-25 ltlists.dtx v1.0n
\endtrivlist: Change \indent to \leavevmode 663
Reset flags explicitly 663
1996-10-25 ltoutput.dtx v1.2a
\newpage: Reset all flags explicitly . 940

1996-10-26 ltlists.dtx v1.0o
\endtrivlist: Correct typo 663
1996-10-27 ltoutenc.dtx v1.8c
\@strip@args: Removed macro . . . 361
General: Added \r A 371
Added \textasteriskcentered . . 367, 378
Corrected syntax descriptions . . . 355
Removed \aa and \AA . 367, 371, 374
1996-10-28 ltplain.dtx v1.1u
General: (CAR) More doc changes . . 15
\dotfill: Removed math mode 34
1996-10-29 ltplain.dtx v1.1v
\dotfill: Got arithmetic correct (CAR) 34
1996-10-29 ltspace.dtx v1.2u
\@gnewline: Added macro 318
\@no@lnbk: Macro replaces \@lnbk and \@nolnbk 316
\\: Corrected and rationalised code 316
\nolinebreak: Reimplemented both using \@no@lnbk 315
1996-10-31 ltfinal.dtx v1.0z
General: Added extra \lcode, hoping it does no harm in T1 (pr/1969) 1009, 1016
1996-10-31 ltlists.dtx v1.0p
\@trivlist: Added check for missing item in outer list 662
1996-10-31 ltsect.dtx v1.0y
General: Corrected and tidied documentation; removed long lines 747
1996-11-03 ltplain.dtx v1.1w
\dotfill: Saved tokens by using \hb@xt@ 34
1996-11-04 lterror.dtx v1.2m
\@nodocument: Always define \@nodocument in kernel, so that it can be cleared by \document. . . . 288
1996-11-04 ltlists.dtx v1.0q
\@trivlist: Moved check for missing item: only checked when not inlabel flag is false 662
1996-11-05 ltfiles.dtx v1.1i
\nofiles: Standard \if@nobreak test added 339
1996-11-09 ltmath.dtx v1.1c
\@ensuredmath: Made long, as it was before. /2104 651
1996-11-18 ltfssbas.dtx v3.0s
\define@newfont: (DPC) lowercase fd file names. internal/1044 424
1996-11-18 ltoutenc.dtx v1.8d
General: (DPC) lowercase external file names. internal/1044 397
1996-11-20 fontdef.dtx v2.2p
General: lowercase fd and enc.def file names /1044 546
1996-11-20 ltvers.dtx v1.0f
General: Check for old format modified /2319 39
1996-11-23 ltoutenc.dtx v1.8e
General: Corrected description 355
Extended description 356
1996-11-28 ltvers.dtx v1.0g
General: Check for old format modified /2319 39
1996-12-06 ltdirchk.dtx v1.0u
\IfFileExists: *** removed from various messages for GNU Make. internal/2338 10
1996-12-06 ltfloat.dtx v1.1r
\@caption: Call \@setminpage if needed. latex/2318 763
1996-12-06 ltfssini.dtx v3.0h
General: (DPC) Remove *** from messages internal/2338 544
1996-12-17 ltdefns.dtx v1.0w
\g@addto@macro: Use \begingroup to save making a mathord 107
1996-12-20 ltsect.dtx v1.0z
\@dottedtocline: Added \nobreak for latex/2343 758
1997-01-08 fontdef.dtx v2.2q
General: Use \DeclareMathDelimiter to set delimiter codes 555
\mathparagraph: Define using \DeclareMathSymbol 564
1997-01-08 ltfiles.dtx v1.1j
\@include: reset \deadcycles latex/2365 343
1997-01-08 ltmath.dtx v1.1d
\root: (DPC) Remove spurious space tokens from plain TEX definition /2359 641
1997-02-05 ltdefns.dtx v1.0x
\g@addto@macro: missing percent /2402 107
1997-02-21 ltlists.dtx v1.0r
\@item: \ifvoid check added for \noindent. latex/2414 666
1997-03-21 ltcounts.dtx v1.1e
\fnsymbol: Use \mathsection and \mathparagraph. latex/2445 . . . 405

1997-04-14 ltfiles.dtx v1.1k
\document: Set the document space factor defaults. latex/2404 335
\normalsfcodes: Macro added (from patch file) latex/2404 339
1997-04-14 ltoutput.dtx v1.2b
\@writesetup: Call \normalsfcodes (from patch file) latex/2404 955
Move \label and \index (from patch file) 955
1997-04-24 ltbibl.dtx v1.1m
\@citex: \@empty to avoid primitive error on empty cite keys. latex/2432 788
1997-04-30 ltoutenc.dtx v1.9a
General: Changed \textsc to \scshape 368
Introduced \textcopyright and modified \copyright 368
Introduced \textcopyright and modify \copyright 369
Modified \textunderscore, removing \mathunderscore 368
Modified \underscore, removing \mathunderscore 369
1997-04-30 ltoutenc.dtx v1.9b
General: Added \leavevmode to \textunderscore 368
1997-05-04 ltoutenc.dtx v1.9c
General: Added 'hex index tabs' . . . 375
Added TS1 encoding v2.2.beta . . 381
1997-05-07 ltoutenc.dtx v1.9d
General: Added \leavevmode to \textcompwordmark 368
1997-05-07 ltspace.dtx v1.2v
\newline: Made completely robust. 317
1997-05-29 ltfsstrc.dtx v3.0j
General: Replaced \\ by \MessageBreak, as suggested by Donald Arseneau. 460
1997-05-29 ltlogos.dtx v1.1f
\LaTeXe: Added \m@th so that the LaTeX 2ε logo works with non-zero values of \mathsurround. 331
1997-06-16 ltdirchk.dtx v1.0v
General: documentation improvements mainly from internal/2520 1
1997-06-16 ltfloat.dtx v1.1s
General: documentation fixes 760
1997-06-16 ltfntcmd.dtx v3.3v
General: Fix typo in documentation. 570
1997-08-05 ltoutenc.dtx v1.9e
General: Corrected order of arguments in \UseTextSymbol example. . . . 355
1997-08-29 ltoutenc.dtx v1.9f
General: Added OT4 encoding, provided by Marcin Woliński. . . 354
1997-09-09 ltdefns.dtx v1.2z
\provide@command: Use \begingroup to avoid generating math ords if used in math mode. pr/2573 86
1997-09-15 ltpictur.dtx v1.1g
\@getcirc: Warn if lines become invisible pr/2524 732
\@picture@warn: Macro added pr/2524 732
\@sline: Warn if lines become invisible pr/2524 721
1997-10-06 ltcounts.dtx v1.1f
\@Roman: Change \@Roman to be fully expandable, so that the result is written properly to files. 405
\@slowromancap: Macro added. . . . 405
1997-10-08 ltlogos.dtx v1.1h
\LaTeX: Simplify macro (force loading of suitable math fonts once). . . . 331
1997-10-10 ltclass.dtx v1.0y
\endfilecontents: \@currenvir in banner 853
\reserved@c not \verbatim@out to save a csname 853
Check for text before or after \end environment. latex/2636 854
Use \@gobbletwo 853
1997-10-17 ltfntcmd.dtx v3.3w
\check@nocorr@: Check for vertical mode moved here, from \DeclareTextFontCommand (see PR/2646). 574
\DeclareTextFontCommand: Reinstalled \check@icr as check is now done in \check@nocorr@ (see PR/2646). 572
1997-10-20 ltfinal.dtx v1.1a
\@uclclist: Removed \aa and \AA from \@uclclist as these are macros. 1016
1997-10-21 ltdefns.dtx v1.2z1
\renew@command: Use \begingroup/\endgroup rather than braces for grouping, to avoid generating empty math atom. . . . 84
1997-10-21 ltfssbas.dtx v3.0t
\define@newfont: Move \makeatletter to \nfss@catcodes. 424

\nfss@catcodes: Moved \makeatletter from \try@load@font@shape. 424
1997-11-09 ltoutput.dtx v1.2c
\@specialoutput: Remove incorrect code: only one \@emptycol is needed here 944
\@topnewpage: Documentation of vsize check enhanced 941
1997-11-13 ltfssdcl.dtx v3.0f
\DeclareSymbolFont: (DPC) Really update \group@list don't leave new version in \toks@. latex/2661 500
\stepcounter: (DPC) Remove as never used. (Re)defined in ltcounts 490
1997-11-19 ltfloat.dtx v1.1t
\@footnotetext: Missing percent, again 779
1997-11-19 ltoutput.dtx v1.2d
\@vtryfc: Reindent code, to be understandable(DPC). 961
1997-11-20 ltfssdcl.dtx v3.0g
\document@select@group: (DPC) inline use of \stepcounter (faster, and saves a csname per math version as no reset list) 493
\select@group: (DPC) inline use of \stepcounter (faster, and saves a csname per math version as no reset list) 491
1997-11-23 ltoutenc.dtx v1.9g
General: Use \textperthousand, \textpertenthousand and \textfractionsolidus not \textpermill, \textpertenmill and \textfraction. /2673 381
1997-12-17 ltoutenc.dtx v1.9h
General: Added \textperthousand and \textpertenthousand . 372, 373
Added code for textcomp.sty. . . . 397
Added section. 397
Added textcomp.sty. 354
As in OT1, Added \leavevmode at start of \c, otherwise the output routine might be invoked within the macro. 373
Changed to decimal codes in \ooalign. 383
Changed to decimal codes. 379
Documentation changes and additions. 354
Example corrected, braces removed. 354
Removed default settings, see next section. 381
1997-12-19 ltoutenc.dtx v1.9i
General: Documentation corrections. 354
1997-12-20 fontdef.dtx v2.2s
General: Added documentation . . . 548
1997-12-31 ltoutenc.dtx v1.9k
General: Further correction 355
1998-01-12 ltoutenc.dtx v1.9k
General: Added \ProvidesPackage for textcomp.sty 354
Adding missing braces and \ushape. 383
1998-01-16 ltoutenc.dtx v1.9m
General: fixed decimal codes. latex/2734 379
1998-03-04 ltdefns.dtx v1.2z2
\@xargdef: Unnecessary \expandafter removed: pr/2758 . 82
1998-03-05 ltoutenc.dtx v1.9n
General: Added masc/fem ords as in pr/2579 368
1998-03-20 ltdefns.dtx v1.2z3
\@thirdofthree: Macro added 87
1998-03-20 ltoutenc.dtx v1.9o
General: Documentation added about order of decls 357
Documentation added for pr/2783 356
\UndeclareTextCommand: Macro added for pr/2783 365
1998-03-20 lttextcomp.dtx v1.9o
General: Added various \UndeclareTextCommand declarations for pr/2783 608
Load decls after defaults for speed. 608
1998-03-21 ltclass.dtx v1.0z
General: Added to documentation of filecontents 818
1998-03-21 ltclass.dtx v1.1a
\@providesfile: Allow &. Internal/2702 832
General: Correct to new onlypreamble command list 867
1998-03-25 ltfssbas.dtx v3.0u
\showhyphens: Suppress unnecessary error when used in preamble . . . 433
1998-04-11 fontdef.dtx v2.2t
General: Added \mathring accent (pr2785) 562
1998-04-15 fontdef.dtx v2.2u
General: Use new syntax for \DeclareMathDelimiter 555

1998-04-15 ltfssdcl.dtx v3.0h
\@xxDeclareMathDelimiter: Macro added (pr/2662) 510
1998-04-17 fontdef.dtx v2.2v
General: Reinsert symbol defs for < and > chars. 556
1998-04-18 fontdef.dtx v2.2w
General: Reinsert symbol def for / char. 556
1998-05-07 ltclass.dtx v1.1b
\@onefilewithoptions@clashchk: Modify help message for latex/2805 845
1998-05-18 lttab.dtx v1.1j
\@endpbox: Use \setlength to set \hsize, so that the changes in the calc package apply here. 709
\tabular*: Use \setlength, so that calc extensions apply. 698
1998-05-20 ltfinal.dtx v1.1b
General: Set up lccodes before loading hyphenation files: pr/2639 1008
Set up uc/lccodes after loading hyphenation files: pr/2639 1016
1998-05-28 lterror.dtx v1.2n
\@notdefinable: Added message re 'end...' pr/1555 288
1998-06-04 ltboxes.dtx v1.1c
\@rule: Support calc-expressions . . 683
1998-06-12 ltoutenc.dtx v1.9p
General: Corrected 130 and 131, see pr/2834 384
Renamed \textmacron pr/2840 . 385
1998-06-12 ltoutenc.dtx v1.9q
\add@accent: Explicitly set \spacefactor after \accent (pr/2877) 361
1998-06-12 lttextcomp.dtx v1.9p
General: Renamed \textmacron pr/2840 604
1998-06-18 lttab.dtx v1.1k
General: Small addition to documentation 686
1998-07-06 lttab.dtx v1.1l
General: Small correction to documentation 686
1998-08-17 ltboxes.dtx v1.1e
General: (RmS) Minor Documentation fixes. 670
1998-08-17 ltclass.dtx v1.1c
General: (RmS) Minor documentation fixes. 818
1998-08-17 ltdirchk.dtx v1.0w
General: (RmS) Documentation improvements. 1
1998-08-17 ltfntcmd.dtx v3.3x
General: (RmS) Minor documentation fixes. 570
1998-08-17 ltfssbas.dtx v3.0v
General: (RmS) Documentation fixes. 410
1998-08-17 ltfssdcl.dtx v3.0i
General: (RmS) Corrected minor glitches in changes entries. 488
1998-08-17 ltfssini.dtx v3.0i
General: (RmS) Minor documentation fixes. 518
1998-08-17 ltlogos.dtx v1.1i
General: (RmS) Minor documentation fixes. 331
1998-08-17 ltmath.dtx v1.1c
General: (RmS) Minor documentation fixes. 639
1998-08-17 ltmiscen.dtx v1.1g
General: (RmS) Minor documentation fixes. 618
1998-08-17 ltspace.dtx v1.2w
General: Documentation fixes. 312
1998-08-17 preload.dtx v2.1g
General: (RmS) Minor documentation fixes. 567
1998-09-19 ltoutenc.dtx v1.9r
\a: Added \string (pr/2878) 366
1998-11-13 lttab.dtx v1.1m
\@array: Check for hmode to see if something went wrong during parsing (pr/2884) 699
1999-01-05 fontdef.dtx v2.2x
General: Need special protection for character > in \changes entry. . . 546
1999-01-06 ltfssbas.dtx v3.0w
\DeclareFontEncoding: Added \LastDeclaredEncoding to support cyrillic integration (pr/2988) 414
\LastDeclaredEncoding: Added \LastDeclaredEncoding to support cyrillic integration (pr/2988) 414
1999-01-06 ltoutenc.dtx v1.9r
\@strip@args: New impl for latex/2930 363
General: Minor documentation fix. . 383
1999-01-06 ltoutput.dtx v1.2e
\@makecol: Added negative vskip, as when processing outputbox below:

suggested by Fred Bartlett pr/2892 950
1999-01-07 ltdefns.dtx v1.3a
\@ifnextchar: made long 102
\@newenvb: made long and brace optional arg. latex/2896 85
\@testopt: made long and brace optional arg. latex/2896 82
1999-01-07 ltdefns.dtx v1.3b
\@ifnextchar: extra \long. latex/2902 102
1999-01-07 ltoutenc.dtx v1.9r
General: Hackery to allow using fontenc several times 399
Hackery to temp support cyrillic uc/lc 397
1999-01-13 ltoutenc.dtx v1.9s
\@strip@args: Simplified solution for latex/2930 363
1999-01-18 ltdefns.dtx v1.3c
\@yargd@f: New implementation DPC /2942 83
1999-02-09 ltdefns.dtx v1.3d
\@yargd@f: catch bad argument forms by re-inserting #3 83
1999-02-12 lttextcomp.dtx v3.0j
\legacyoldstylenums: Use \rmdefault instead of cmm (pr/2954) 579
1999-02-24 ltoutenc.dtx v1.9t
General: Corrected hackery cyrillic uc/lc list 397
1999-03-01 ltdefns.dtx v1.3e
\@ifnextchar: remove extra \long. internal/2967 102
1999-04-15 ltpictur.dtx v1.1h
\@getlarrow: Replaced octal number, CAR 723
\@upvector: Replaced octal number, CAR 724
General: Replaced octal number, CAR 723, 724
Replaced octal numbers, CAR . . 711
1999-04-19 ltfloat.dtx v1.1u
\caption: Made caption an error outside a float: latex/2815 763
1999-04-27 ltboxes.dtx v1.1f
\@parboxto: (CAR) Changed \@empty to \relax as flag for natural width: pr/2975 679
1999-04-29 ltdefns.dtx v1.3f
\@yargd@f: Full expansion and conversion needed for digit in new version, see pr/3013 83
New macro added 83
1999-06-10 ltoutenc.dtx v1.9u
General: Ensure that we also forget old options (pr/2888) 399
1999-06-12 ltoutenc.dtx v1.9v
General: Extend \@uclclist only once 398
1999-10-09 ltmath.dtx v1.1e
\active@math@prime: Macro added, see PR 3104. 645
\prime@s: Introduce \active@math@prime. 646
1999-10-09 ltoutput.dtx 1.2f
\@activechar@info: Reset definition of active prime character (used in math mode) 953
1999-10-28 ltoutenc.dtx v1.9w
\add@accent: Give \accent@spacefactor a default definition (pr/3084) 361
1999-12-08 ltoutenc.dtx v1.9x
General: Changed \CYRRHOOK and \cyrrhook to\CYRRHK and \cyrrhk as name changed in the cyrillic bundle for naming consistency with other “hook” glyphs. 397
2000-01-07 ltmiscen.dtx v1.1h
\@verbatim: Disable hyphenation even if the font allows it. 634
2000-01-15 ltpictur.dtx v1.1i
\@upvector: Removed space at end-of-line, CAR 724
2000-01-30 ltfntcmd.dtx v3.3y
\DeclareTextFontCommand: Use \hmode@bgroup now (pr/3160) . . 572
2000-01-30 ltoutenc.dtx v1.9y
General: Use \hmode@bgroup where applicable (pr/3160) . . . 370–373, 378–381, 383
\add@accent: Use \hmode@bgroup where applicable (pr/3160) 360
\hmode@bgroup: Macro added 361
2000-01-30 ltoutenc.dtx v1.9z
\@use@text@encoding: Macro reimplemented (pr/3160) . . 363, 364
\add@accent: Macro reimplemented (pr/3160) 360
\hmode@start@before@group: Macro added (pr/3160) 364
2000-05-19 ltmiscen.dtx v1.1i
\enddocument: Reset \AtEndDocument for latex/3060 619

2000-05-26 ltpage.dtx v1.0j
\\@markright: Reimplementation to fix expansion error (pr/3203). 816
\\leftmark: Use \\@empty instead of brace group (pr/3203). 816
\\markright: Reimplementation to fix expansion error (pr/3203). 814
\\rightmark: Use \\@empty instead of brace group (pr/3203). 816
2000-06-02 ltpage.dtx v1.0k
\\@markright: Small adjustment to give slightly less expansion, CAR 816
\\markright: Small adjustment to give slightly less expansion, CAR . . . 814
Tidied 1.0j reimplementation, CAR 814
2000-07-11 ltmiscen.dtx v1.1j
\\@enddocument@kernel@warnings: Fix typo in warning 620
2000-07-12 ltoutput.dtx 1.2g
General: Ensure that rule is in \\normalcolor 995
2000-07-12 ltoutput.dtx 1.2i
\\@makecol: Removed negative vskip, as it gives unacceptable results when the depth is large: pr/3189 950
2000-07-19 ltoutput.dtx v1.2h
\\@writesetup: Reset and restore \\@if@newlist for internal/3231 . 954
2000-08-23 ltfinal.dtx v1.1c
General: Fix typo in warning 1010
2000-08-30 ltoutenc.dtx v1.91
\\@use@text@encoding: Rearranged but no change to final code, CAR (pr/3160) 363
\\add@accent: Rearranged but no change to final code, CAR (pr/3160) 360
2000-09-01 ltfinal.dtx v1.1d
\\errhelp: Set error help empty at very end (pr/449 done correctly). . . 1019
2000-09-24 ltfloat.dtx v1.2b
\\end@dblfloat: FMi: use output routine to defer float 768
2000-09-24 ltoutput.dtx v1.2b
\\@doclearpage: FMi: ensure \\doclearpage is called again until all floats are output. 948
2000-09-24 ltoutput.dtx v1.2n
\\@addtocurcol: FMi: test for wide float was in wrong place 967
2001-01-07 ltoutput.dtx v1.2j
\\@writesetup: And do it in the right macro (pr/3286) 954
2001-02-16 ltxref.dtx v1.1k
\\@newl@bel: Added an extra grouplevel (PR3250), jlb 615
2001-05-25 ltclass.dtx v1.1d
\\@providesfile: Explicitly set catcode of \\endlinechar to 10 (pr/3334) 832
2001-05-25 ltdirchk.dtx v1.0x
General: Explicitly set catcode of \\endlinechar to 10 (pr/3334) . . . 4
2001-05-28 ltoutenc.dtx v1.93
General: Added composites for compatibility with T1, pr/3295 . 372
Changed the effect of \\.\\i, pr/3295 375
2001-06-02 fontdef.dtx v2.2y
General: Provide default cfg files (pr/3264) 565
2001-06-04 fontdef.dtx v2.2z
General: Guard against math active equal and pipe sign in \\models (pr/3333) 561
Guard against math active equal sign in \\Relbar (pr/3333) 561
2001-06-04 ltclass.dtx v1.1e
\\@providesfile: But only if it is a char (pr/3334) 832
2001-06-04 ltdirchk.dtx v1.0y
General: But only if it is a char (pr/3334) 4
2001-06-04 ltpictur.dtx v1.1j
\\@sline: Don't warn for exactly zero pr/3318 721
2001-06-04 ltvers.dtx v1.0i
General: Check for old format disabled 39
2001-06-05 ltoutenc.dtx v1.94
General: Text composite Commands need kludges for ',' – see tlb1903.lvt 372
2001-08-26 ltclass.dtx v1.1f
\\@providesfile: Readded setting of space char (pr/3353) 832
2002-02-24 ltplain.dtx v1.1x
\\loggingall: Macro added 35
\\loggingoutput: Macro added 34
\\showoutput: Use newly added \\loggingoutput 34
\\tracingall: Use newly added \\loggingoutput 35
2002-06-16 ltoutenc.dtx v1.95
General: Added \\textbardbl (pr/3400) 378
Added default for \\textbardbl (pr/3400) 367

2002-06-17 ltoutenc.dtx v1.95
General: Corrected \c for T1 (pr/3442) 373
Definition of \textexclamdown changed (pr/3368) 371
Definition of \textquestiondown changed (pr/3368) 371
2002-06-18 ltoutenc.dtx v1.95
General: Changed def for \textregistered to avoid small caps (pr/3420) 368
2002-10-01 ltfloat.dtx v1.1v
\thempfootnote: Use braces around \itshape to keep font change local (pr/3460). 777
2002-10-02 ltfssbas.dtx v3.0x
\DeclareFontSubstitution: Adding \LastDeclaredEncoding introduced a bug as on some occasions that macro name was stored in the internal lists instead of the actual encoding. (pr/3459) 414
2002-10-28 ltlists.dtx v1.0s
\endtrivlist: Check for math mode (pr/3437) 663
2002-10-28 ltoutenc.dtx v1.96
General: coding change, to follow bug fix by DEK in plain.tex (pr/3469) 371, 380
2002-12-13 ltbibl.dtx v1.1n
\@citex: Added \leavevmode in case citation is at start of paragraph (pr/3486) 788
2003-01-01 ltfntcmd.dtx v3.3z
General: Code checked and documentation extended by Chris 572
2003-05-18 ltbibl.dtx v1.1o
\nocite: Check if we are after \document 789
2003-08-27 ltpictur.dtx v1.1k
\@bezier: added missing displacement pr/3566 740
\@sline: check for \@linechar being empty pr/3570 721
2003-10-13 ltfinal.dtx v1.1e
General: Added extra \lccode for \- and \textcompwordmark 1009
2003-12-16 ltoutput.dtx v1.2k
\@makecol: Ensure that \@elt has a defined state (pr/3586) 950
2003-12-30 ltpictur.dtx v1.1j
\@getcirc: issue warning if circle size can't be met pr/3473 732
2004-01-03 ltoutenc.dtx v1.99b
General: Added \textogonekcentered (pr/3532) 373
Added composites for \k (pr/3532) 378
Use \ooalign for \k (pr/3532) . . 373
2004-01-04 ltbibl.dtx v1.1p
\nocite: Changed error message . . 789
2004-01-04 ltoutenc.dtx v1.99c
General: More adjustments for ogonek (pr/3532) 373
2004-01-23 ltdefns.dtx v1.1g
\@newenva: Use kernel version of \@ifnextchar (pr/3501) 85
\@testopt: Use kernel version of \@ifnextchar (pr/3501) 82
\@xargdef: Use kernel version of \@ifnextchar (pr/3501) 82
\@xdblarg: Use kernel version of \@ifnextchar (pr/3501) 104
2004-01-23 ltdefns.dtx v1.3g
\kernel@ifnextchar: Added macro (pr/3501) 103
2004-01-28 ltclass.dtx v1.1g
\@providesfile: Use kernel version of \@ifnextchar (pr/3501) 832
2004-01-28 ltvers.dtx v1.0k
General: Check for old format made 5 years (pr/3601) 39
2004-02-02 fontdef.dtx v2.3
General: Many things from here on made robust 560
2004-02-02 ltoutenc.dtx v1.99
General: Added \textbigcircle . . 378
2004-02-04 fontdef.dtx v2.3a
General: Added bigtriangle synonyms for stmaryrd 558
2004-02-04 ltspace.dtx v1.3
\nobreakdashes: (Macro added . . . 327
2004-02-06 ltoutenc.dtx v1.99d
\@inmathwarn: New command added to fix severe bug: pr/3563 358
2004-02-07 ltoutput.dtx v1.2l
\@doclearpage: Empty kludgeins box if necessary, pr/3528 948
2004-02-13 ltoutenc.dtx v1.99e
General: Documentation fixes: typos 354
2004-02-15 ltbibl.dtx v1.1q
\@cite@ofmt: Added hook with default value \hbox 790
\@citex: Changed to use a hook with default value \hbox 788
2004-02-15 ltspace.dtx v1.3a
\nobreakdashes: (Added spacefactor setting 327

2004-10-20 ltoutput.dtx v1.2m
\\@makecol: Removed dead code . . . 950
2005-07-27 ltfssdcl.dtx v3.0j
\\DeclareMathAlphabet: (MH) Make document commands robust . . . 502
\\DeclareSymbolFontAlphabet: (MH) Make document commands robust 515
\\new@mathalphabet: (MH) Make document commands robust . . . 503
\\non@alpherr: (MH) Change because command is now properly robust 492
\\SetMathAlphabet: (MH) Make document commands robust . . . 504
2005-09-27 ltoutenc.dtx v1.99g
General: Replace \\sh@ft by \\ltx@sh@ft 370, 373, 380
2005-09-27 ltplain.dtx v1.1y
\\ltx@sh@ft: New macro 34
\\sh@ft: Macro no longer used but left for compatibility 33
2005-11-08 ltoutenc.dtx v1.99h
General: Added \\ij and \\IJ from babel. (pr/3771) 367, 372, 374
2005-11-10 ltmath.dtx v1.1g
\\[: (MH) Fixed potential problem in \\[(pr/3399). 646
General: (MH) Minor documentation fixes. 639
2006-05-18 ltboxes.dtx v1.1g
\\@parboxto: Ensure \\@parboxto holds the value of \\@tempdimb not the register itself (pr/3867) 679
2006-09-13 ltoutput.dtx v1.1m
General: Ensure that rule is in \\normalcolor 996
2007-08-05 ltclass.dtx v1.1h
\\@fileswithoptions: Prevent loss of brackets PR/3965 841
2007-08-06 ltcntrl.dtx v1.0h
\\@fornoop: Really make defs long . . 280
2007-08-31 ltfssdcl.dtx v3.0l
\\SetSymbolFont@: Font warning changed to info for encoding change (pr/3975) 501
2009-09-24 ltvers.dtx v1.0l
General: Stop checking for old format 39
2009-10-20 ltfssdcl.dtx v3.0m
\\in@: More robust thanks to Heiko. 488
2009-10-28 lttextcomp.dtx v1.99k
General: Added Latin Modern and TeX Gyre subsets 609
2009-11-04 lttextcomp.dtx v1.99l
General: Added more Latin Modern and TeX Gyre subsets 609
2009-12-14 ltfntcmd.dtx v3.4a
\\ifmaybe@ic: Macro added 575
\\maybe@ic@: Use switch \\ifmaybe@ic instead of \\if@tempswa 575
\\t@st@ic: Use switch \\ifmaybe@ic instead of \\if@tempswa 576
2010-08-17 ltmiscen.dtx v1.1k
\\enddocument: Use braces around \\input arg (pr/4124) 620
2010-08-17 ltmiscen.dtx v1.1l
\\enddocument: Change of plan: use \\@@input instead (pr/4124) 620
2011-05-08 ltfssdcl.dtx v3.0n
\\in@: Simplified thanks to Bruno. . . 488
2011-08-19 ltclass.dtx v1.1i
\\@ifclasswith: Re-jig definition after more stringent \\in@ test. 829
2011-09-03 ltfssdcl.dtx v3.0o
\\new@mathversion: (Will) Remove \\global before \\newcount (unnecessary and caused etex bug). 499
2012-01-20 ltplain.dtx v2.0b
\\loggingall: etex tracing if available 35
2013-07-07 ltclass.dtx v1.1i
General: Correctly describe how the date in \\@ifpackagelater is used 821
2014-04-18 ltoutput.dtx v1.1o
General: Handle infinite glue from \\enlargethispage (pr/4023) . . . 995
2014-04-24 ltoutput.dtx v1.2n
\\fl@tracemessage: Renamed internal trace commands; provide as package 985
2014-04-27 ltfloat.dtx v1.2b
\\end@dblfloat: Inline the code to allow some coexistence with packages that hook into \\end@float and do not know about the algorithm change 768
2014-06-10 ltfloat.dtx v1.2b
\\end@dblfloat: missing \\fi added . 768
2014-12-30 ltfinal.dtx v2.0a
\\newmarks: macro added 1003
\\newXeTeXintercharclass: macro added 1004
2014-12-30 ltfloat.dtx v1.2a
\\@textsubscript: Command added (latexrelease) 779
\\textsubscript: Command added (latexrelease) 778
2014-12-30 ltfssbas.dtx v3.0y
\\mathgroup: move allocation to ltplain. 410

2014-12-30 ltoutput.dtx v1.2m
General: Command updated (latexrelease) 995
2014-12-30 ltplain.dtx v2.0a
\e@alloc: macro added 20
\e@alloc@chardef: macro added . . . 19
\e@alloc@top: macro added 19
\e@ch@ck: macro added 20
\extrafloats: macro added 21
\newlanguage: New engine-specific allocation scheme (latexrelease) . . 18
2014-12-30 ltspace.dtx v1.3b
\@: \@ discards spaces when moving (pr3039)(latexrelease) 328
2015-01-03 ltdefns.dtx v1.4a
\typein: use modified definition in luatex 80
2015-01-03 ltdirchk.dtx v1.1
General: Enable extra primitives when LuaTEX is used 3
2015-01-03 ltfinal.dtx v2.0a
General: Skip resetting codes with Unicode engines 1016
Unicode data loading added . . . 1007
2015-01-07 ltvers.dtx v1.0n
\@check@IncludeInRelease: macro added 41
2015-01-08 ltboxes.dtx v1.1h
\framebox: Make Robust (latexrelease) 677
\makebox: Make Robust (latexrelease) 671
\parbox: Make Robust (latexrelease) 678
\raisebox: Make Robust (latexrelease) 684
\rule: Make Robust (latexrelease) . 683
\savebox: Make Robust (latexrelease) 674
2015-01-08 ltdefns.dtx v1.4a
\MakeRobust: Added macro 90
2015-01-08 ltlength.dtx v1.1c
\setlength: to ensure first length argument is terminated. (latexrelease) 408
2015-01-08 ltmath.dtx v1.1h
\): Make Robust (latexrelease) 646
\]: Make Robust (latexrelease) 646
2015-01-09 ltfssini.dtx v3.1a
\em: Allow \emph to produce small caps (latexrelease) 538
\eminnershape: macro added (latexrelease) 538
2015-01-09 ltspace.dtx v1.1h
\addpenalty: Donald Arseneau's fix from PR/377703 (latexrelease) . . 324
2015-01-10 ltcounts.dtx v1.1h
\@fnsymbol: Unse \TextOrMath (latexrelease) 406
\@stpelt: Reset all within counters in one go (latexrelease) 402
2015-01-11 ltcounts.dtx v1.1h
\TextOrMath: Add command to solve robustness issues (pr/3752) (latexrelease) 407
2015-01-11 ltfloat.dtx v1.2b
\@dblfloatplacement: float order in 2-column (latexrelease) 770
\@xfloat: Check for valid option (latexrelease) 764
\end@dblfloat: float order in 2-column (latexrelease) 768
2015-01-11 ltfssbas.dtx v3.0y
\@DeclareMathSizes: Allow arbitrary units (latexrelease) 417
2015-01-11 ltspace.dtx v1.3d
\@Esphack: Allow hyphenation (Donald Arseneau pr/3498) (latexrelease) 321
\@esphack: Allow hyphenation (Donald Arseneau pr/3498) (latexrelease) 320
2015-01-14 ltoutput.dtx v1.2n
\@addtocurcol: float order in 2-column (latexrelease) 966
\@addtodblcol: float order in 2-column (latexrelease) 976
\@addtonextcol: float order in 2-column (latexrelease) 973
\@doclearpage: Empty kludgeins box if necessary, pr/3528 947
float order in 2-column (latexrelease) 947
\@startdblcolumn: float order in 2-column (latexrelease) 960
\@xtryfc: float order in 2-column (latexrelease) 962
\@ztryfc: float order in 2-column (latexrelease) 963
2015-01-14 ltspace.dtx v1.3e
\addpenalty: Avoid adding redundant skips (DPC) 324
2015-01-17 ltvers.dtx v1.0m
\@check@IncludeInRelease: modified with \@currname 41
2015-01-19 ltvers.dtx v1.0o
\@check@IncludeInRelease: Optional argument 41

2015-01-20 ltoutput.dtx v1.2m
\fl@tracemessage: Reset \IncludeInRelease flags 986
2015-01-22 ltvers.dtx v1.0p
General: Preserve any \everyjob material inserted by a loader (.ini file) 40
2015-01-23 ltfinal.dtx v2.0b
\newmarks: use reserved count 256 1003
\newXeTeXintercharclass: use reserved count 257 1004
2015-01-23 ltplain.dtx v2.0c
\extrafloats: reserve counts 256–265 21
2015-01-24 ltfinal.dtx v2.0c
General: Skip T1-code entirely with Unicode engines 1007
2015-02-03 ltfinal.dtx v2.0d
General: Set \lccode for - with Unicode engines 1008
2015-02-16 ltoutenc.dtx v1.99m
General: Added \textcommabelow latex/4414 369
2015-02-16 ltoutenc.dtx v1.99n
General: Added \textcommaabove . . 370
Added composites for ç 378
Added composites for \c 372
2015-02-16 lttextcomp.dtx v1.99m
General: Added lmtt (Heiko Oberdiek) latex/4415 609
2015-02-19 ltvers.dtx v1.0q
\@check@IncludeInRelease: Swap argument order 41
2015-02-20 ltplain.dtx v2.0d
\loggingall: Spell commands correctly :-) 35
2015-02-21 ltdefns.dtx v1.4b
General: Removed autoload support . 78
2015-02-21 lterror.dtx v1.2o
General: Removed autoload support 281
2015-02-21 ltfiles.dtx v1.1m
General: Removed autoload support 332
2015-02-21 ltfssbas.dtx v3.0z
General: Removed autoload code . . 410
2015-02-21 ltfsscmp.dtx v3.0d
General: Removed autoload code . . 483
2015-02-21 ltfssdcl.dtx v3.0p
General: Removed autoload code . . 488
2015-02-21 ltfsstrc.dtx v3.0k
General: Removed autoload code . . 458
2015-02-21 ltoutenc.dtx v1.99m
General: Removed autoload code . . 354
2015-02-21 ltoutput.dtx v1.2n
General: Removed autoload code . . 926
\f@depth: macro added(latexrelease) 946
2015-02-21 ltpictur.dtx v1.1k
General: Removed autoload code . . 711
2015-02-21 ltplain.dtx v2.0e
General: Removed autoload code . . . 15
2015-02-21 lttab.dtx v1.1n
General: Removed autoload code . . 686
2015-02-21 ltvers.dtx v1.0r
General: Removed autoload code . . . 39
2015-02-21 ltvers.dtx v1.0w
\@check@IncludeInRelease: set \@currname empty here (in case \IncludeInRelease input early) . 40
2015-02-22 ltfsscmp.dtx v3.0e
General: Moved all code into latexrelease - obsolete commands are no longer automatically part of the kernel 483
2015-03-02 ltplain.dtx v2.0f
\e@mathgroup@top: macro added . . . 20
\newlanguage: allow 255 math groups in Unicode engines 18
2015-03-10 ltplain.dtx v2.0g
\hideoutput: macro added 37
\loggingall: Reorganize to be less noisy 35
\tracingnone: macro added 36
2015-03-12 ltoutput.dtx v1.2m
General: initialise \@dbldeferlist again 937
2015-03-18 ltfssdcl.dtx v3.0q
\DeclareSymbolFont: Restrict Symbol fonts to 0-15 500
\document@select@group: Introduce \e@mathgroup@top 493
\select@group: Introduce \e@mathgroup@top 491
2015-03-26 ltfinal.dtx v2.0d
General: Use renamed unicode-letters.def 1007
2015-04-07 ltfssbas.dtx v3.1a
\wrong@fontshape: Try loading fd file if family has changed 428
2015-04-28 ltfinal.dtx v2.0f
\newXeTeXintercharclass: define \xe@alloc@intercharclass for compatibility with older xelatex initialization 1004
2015-05-10 ltlists.dtx v1.0t
\@doendpe: Explicitly reset \clubpenalty before clearing \everypar; see also pr/0462 and pr/4065 664

2015-06-19 ltfinal.dtx v2.0g
- \e@alloc@intercharclass@top: Use −1 for first range to get contiguous allocation 1004
- \newmarks: Use −1 for first range to get contiguous allocation 1003

2015-06-19 ltplain.dtx v2.0h
- General: delete spurious old definition of \newtoks 24
- \e@alloc: extra braces in case arguments not single token 20
- \newlanguage: Use −1 for first range to get contiguous allocation 18

2015-06-23 ltfinal.dtx v2.0h
- General: set \patch@level in ltvers rather than in ltfinal/ltpatch . . 1018

2015-06-23 ltvers.dtx v1.0t
- General: set \patch@level in ltvers rather than in ltfinal/ltpatch 39

2015-08-06 ltplain.dtx v2.0i
- \extrafloats: Add \string in case argument is not an unexpandable primitive 21

2015-08-23 ltdirchk.dtx v1.2
- General: Do not use luatex prefix 3

2015-08-23 ltvers.dtx v1.0v
- General: Allow negative patchlevel for pre-release 40

2015-08-30 ltplain.dtx v2.1a
- \newinsert: new \newinsert implementation 23

2015-09-205 ltoutput.dtx v1.3a
- General: extended \@freelist 936

2015-09-24 ltluatex.dtx v1.0a
- call_callback: Function added 67
- callback.register: Function modified 63
- callback_descriptions: Function added 70
- \catcodetable@atletter: Macro added 51
- \catcodetable@initex: Macro added 51
- \catcodetable@latex: Macro added . 51
- \catcodetable@string: Macro added 51
- add_to_callback: Function added . . 67
- remove_from_callback: Function added 68
- new_attribute: Function added 59
- disable_callback: Function added . 69
- in_callback: Function added 69
- \newattribute: Macro added 50
- \newcatcodetable: Macro added . . . 51
- \newluabytecode: Macro added 53
- \newluachunkname: Macro added . . . 54
- \newluafunction: Macro added 52
- \newwhatsit: Macro added 53
- module_error: Function added 57
- module_info: Function added 57
- module_warning: Function added . . . 57
- modules: Function modified 56
- create_callback: Function added . . 66
- provides_module: Function added . . 56
- luatexbase: Table added 56

2015-10-02 ltdirchk.dtx v1.2a
- General: Allow backing out of unprefixed names 3

2015-10-02 ltluatex.dtx v1.0b
- General: Fix backing out of TEX code 54

2015-10-02 ltluatex.dtx v1.0c
- General: Allow backing out of Lua code 54

2015-10-02 ltluatex.dtx v1.0e
- uninstall: Function added 70

2015-10-03 ltluatex.dtx v1.0f
- provides_module: use luatexbase_log 56

2015-10-27 ltplain.dtx v2.1b
- \extrafloats: Use global assignment when switching to extended range 21

2015-11-07 ltspace.dtx v1.3f
- \@esphack: Only space if there is no space at the end of the hlist latex/4443 320

2015-11-14 ltluatex.dtx v1.0g
- General: Track LuaTEX changes for (new)token.create 58

2015-11-18 ltplain.dtx v2.2a
- \newlanguage: Extended stream allocation in luatex (0.85) 18

2015-11-19 ltplain.dtx v2.2b
- \newlanguage: Only extend allocation of write streams (see luatex list) . 18

2015-11-27 ltluatex.dtx v1.0h
- callback_descriptions: Match test in in-callback latex/4445 70
- in_callback: Guard against undefined list latex/4445 69

2015-11-29 ltluatex.dtx v1.0i
- General: Declare this as local before used in the module error definitions (PHG) 56
- call_callback: Check name is not nil in error message (PHG) 67
- create_callback: Check name is not nil in error message (PHG) 66

2015-12-02 ltluatex.dtx v1.0j
- General: Adjust hashtokens to store the result of tex.hashtokens()), not the function (PHG) 58

Assorted typos fixed (PHG) 48
Declaration/use of first_ head fixed (PHG) 57
Remove nonlocal iteration variables (PHG) 48
Remove unreachable code after calls to error() (PHG) 48
2015-12-02 ltluatex.dtx v1.0k
General: resolve name and i.description (PHG) 65
`call_callback`: Give more specific error messages (PHG) 67
`add_to_callback`: Give more specific error messages (PHG) 67
`remove_from_callback`: adjust initialization of cb local (PHG) . . 68
Give more specific error messages (PHG) 68
`create_callback`: Give more specific error messages (PHG) 66
2015-12-10 ltfinal.dtx v2.0i
General: Use new common Unicode data loaders 1007
2015-12-18 ltluatex.dtx v1.0l
General: Load Unicode data from source 51
2016-01-04 ltfinal.dtx v2.0j
General: Do not set up inter character classes for XeTeX 1007
`\e@alloc@intercharclass@top`: Start allocation at one not three 1004
2016-01-05 ltfinal.dtx v2.0k
`\e@alloc@intercharclass@top`: Remove duplicated code 1004
2016-01-05 ltfinal.dtx v2.0l
General: Correct latexrelease guards 1007
Ensure old definitions for inter-character class toks are available using latexrelease 1007
Missing brace 1007
2016-01-05 ltfinal.dtx v2.0m
General: Undefine XeTeX classes when using patching an older kernel . 1007
2016-01-05 ltfinal.dtx v2.0p
General: Only apply XeTeX change if XeTeX is in use 1007
2016-02-11 ltluatex.dtx v1.0m
General: pdf_stream_filter_callback removed 63
process_ rule, [hv]pack_ quality append_ to_ vlist_ filter added . 62
read_ cidmap_ file added 62
show_warning_message added . . . 63
token_ filter removed 62
2016-02-18 ltfssdcl.dtx v3.0r
`\@DeclareMathDelimiter`: Check for delimiter not `\delimiter` 511
`\DeclareMathAccent`: Check for mathaccent not `\mathaccemt` . . . 506
`\DeclareMathRadical`: Check for radical not `\radical` 513
`\DeclareMathSymbol`: Check for mathchar not `\mathchar` 508
2016-03-13 ltluatex.dtx v1.0n
General: contribute_ filter added . . . 62
insert_ local_ par added 62
2016-03-29 ltpictur.dtx v1.1l
`\@oval`: add setting of line tests 733, 734
initialise tests 733
`\@ovhorz`: use glue not leaders if horizontal line not required 736
`\@ovvert`: use glue not leaders if vertical line not required 735
`\if@ovhline`: macro added (latex/4452) 733
`\if@ovvline`: macro added (latex/4452) 733
2016-04-22 ltfinal.dtx v2.0q
`\e@alloc@intercharclass@top`: XeTeX 0.99996 has 4096 char classes not 256 1004
2016-06-19 ltoutenc.dtx v1.99m
General: OT1 definition (was duplicate T1 definition) 372
2016-06-20 ltclass.dtx v1.1j
General: don't declare as `\@onlypreamble` 828
2016-07-29 ltplain.dtx v2.2c
`\extrafloats`: use `\global \chardef` 21
`\newinsert`: fix for tlb-newinsert-001 23
2016-10-02 ltclass.dtx v1.2a
`\@ifclasswith`: Ignore spaces while checking for option clash 829
`\ExecuteOptions`: Ignore spaces in argument 837
2016-10-15 ltdirchk.dtx v1.2b
General: Require eTEX 4
2016-10-15 lterror.dtx v1.2p
General: Require eTEX 281
2016-10-15 ltfinal.dtx v2.0r
General: Require eTEX 1003
2016-10-15 ltfinal.dtx v2.0s
General: Tidy up status of char 127 1003
2016-10-15 ltfssini.dtx v3.1b
General: Require eTEX 518
2016-10-15 ltplain.dtx v2.2d
General: Require eTEX 15

2016-10-16 ltplain.dtx v2.3a
\newlanguage: Allow languages up to 16383 in luatex 18
2016-10-19 ltcounts.dtx v1.1j
\TextOrMath: Test directly for \protected 407
2016-11-06 ltplain.dtx v2.3b
General: Drop \outer entirely 15
2016-11-09 ltclass.dtx v2.1b
\@fileswithoptions: Improve \ifx tests PR/4497 841
2016-11-17 ltluatex.dtx v1.0p
General: call_edit added 63
2016-12-03 fontdef.dtx v3.0a
General: (DPC) Default to TU encoding for Unicode TeX engines 548
\shapedefault: (DPC) Default to TU encoding for Unicode TeX engines 552
2016-12-04 ltoutenc.dtx v2.0a
General: Added TU encoding 386
2017-01-01 ltoutput.dtx v1.3b
General: make fpmin negative so ignored even if float height is negative 994
2017-01-10 ltfssbas.dtx v3.2a
\showhyphens: Add version of \showhyphens that works with XeTEX. 433
2017-01-23 ltoutenc.dtx v2.0b
General: Added TU specific commands in ASCII range pr/4500 386
2017-01-24 ltoutenc.dtx v2.0c
General: Declare TU composites for i and j 386
Make \textasteriskcentered U+2217 not U+204E 386
TeX ligature syntax for xetex and luatex reversed 386
2017-01-24 ltoutenc.dtx v2.0d
General: Declare macron composites for YyGg 386
2017-02-12 ltoutenc.dtx v2.0e
General: Declare fallback code for \textasteriskcentered 386
2017-02-18 ltluatex.dtx v1.1c
new_attribute: Parameterize count used in tracking 59
new_bytecode: Parameterize count used in tracking 60
new_chunkname: Parameterize count used in tracking 60
new_whatsit: Parameterize count used in tracking 59
2017-02-19 ltoutenc.dtx v2.0f
General: add \@empty to guard against 3rd argument being empty 371
declare composites with empty base for hat and tilde, use same slots for \textasciicircum ans \textasciitilde 386
declare straight quotes using new \remove@tlig command 386
2017-02-22 ltoutenc.dtx v2.0g
General: Fix typo introduced at 2.0f 386
2017-02-24 ltoutenc.dtx v2.0h
General: introduce \DeclareUnicodeAccent 386
\DeclareTextCompositeCommand: add check whether the accent command is defined for this encoding 361
2017-03-08 ltclass.dtx v1.2c
General: add \@parse@version@dash to support yyyy-mm-dd as well as yyyy/mm/dd 828
2017-03-09 ltfinal.dtx v2.0t
\l@nohyphenation: ensure \l@nohyphenation is defined. . 1010
2017-03-09 ltmiscen.dtx v1.1m
\@verbatim: Use \language not \hyphenchar 634
\verb: Use \language to stop hyphenation 638
2017-03-10 ltfiles.dtx v1.1n
\document: Save language default . . 335
2017-03-10 ltoutput.dtx v1.3c
\@writesetup: Reset \language . . . 954
2017-03-13 ltdefns.dtx v1.5a
\-: Define \- in terms of \hyphenchar 105
2017-03-27 ltdefns.dtx v1.5b
\@dischyph: Define \@dischyph after \- 105
2017-03-28 ltluatex.dtx v1.1e
General: glyph_stream_provider added 63
2017-03-29 ltboxes.dtx v1.3a
\@arrayparboxrestore: Reset \lineskiplimit 680
2017-04-05 ltoutenc.dtx v2.0i
\DeclareTextCompositeCommand: Declare accent command if not already declared when declaring a composite. 361
2017-04-10 ltplain.dtx v2.3c
\newlanguage: Correction to code to skip write18 in luatex 18

2017-04-11 ltoutput.dtx v2.4a
\newpage: account for the depth of the last row of the page 940
2017-12-17 ltoutput.dtx v1.4b
\@addtonextcol: fix doc guards . . . 973
2018-01-06 ltdefns.dtx 1.5c
\@ifundefined: Avoid defining undefined commands to \relax . 101
2018-02-18 ltclass.dtx v1.2d
\@ifl@ter: Added 0 up front to make bad data come out as 0. 828
General: Introduce rollback concept 859
2018-03-08 ltcounts.dtx v1.1k
\@ifbothcounters: Interface added 403
\@removefromreset: Interface added 403
\counterwithin: Interface added . . 404
2018-03-24 ltclass.dtx v1.2e
\pkgcls@use@this@release: Use full file name for old release 865
2018-03-25 ltfinal.dtx v2.1a
General: default to UTF-8 1011
\UseRawInputEncoding: Macro added 1012
2018-03-27 ltclass.dtx v1.2f
\endfilecontents: Use full file name for old release 854
2018-04-06 ltfinal.dtx v2.1b
\UseRawInputEncoding: Undo changes to \DeclareFontEncoding@ and definition of \DeclareUnicodeCharacter . . . 1012
2018-04-07 ltfinal.dtx v2.1c
\UseRawInputEncoding: Undefine \inputencodingname 1012
2018-04-08 ltclass.dtx v1.2g
\@ifl@ter: Strip leading spaces from dates. 828
2018-04-08 ltclass.dtx v1.2h
\@onefilewithoptions: Pass expanded date 861
2018-04-08 ltfinal.dtx v2.1d
General: Delay full UTF-8 handling to \everyjob 1013
2018-04-11 ltcounts.dtx v1.1l
\counterwithin: Correct default (issue/38) 404
2018-05-02 ltluatex.dtx v1.1g
General: find_ sfd_ file removed . . . 62
finish_synctex_callback added . . . 63
glyph_not_found added 63
read_ sfd_ file removed 62
2018-05-08 ltclass.dtx v1.2i
\pkgcls@parse@date@arg: Make suspicious rollback a warning not error: github issue 43 863
2018-05-11 ltfinal.dtx v2.18
General: Make invalid UTF-8 also safe, for legacy filesystem encodings . 1013
2018-05-29 ltclass.dtx v1.2j
\endfilecontents: use \csname not \@undefined 854
2018-08-11 ltoutenc.dtx v2.0j
General: Provide \guillemetleft and \guillemetright 374, 380, 389
2018-08-18 ltluatex.dtx v1.1h
General: append_ to_ vlist_ filter is exclusive 62
2018-08-24 ltfinal.dtx v2.1f
\document@default@language: Add to latexrelease (github/68) 1010
2018-09-02 ltsect.dtx v1.1b
\@dottedtocline: Prevent protrusion (https://tex.stackexchange.com/q/172785/10109) 758
2018-09-24 fontdef.dtx v3.0b
General: Start LR-mode if necessary (git/49) 564
2018-09-24 ltmath.dtx v1.2b
\smash: Start LR-mode if necessary (git/49) 642
\vphantom: Start LR-mode if necessary (git/49) 642
2018-09-24 ltspace.dtx v1.3h
\enspace: Start LR-mode if necessary (git/49) 329
\leavevmode@ifvmode: Macro added (git/49) 329
2018-09-26 ltdefns.dtx v1.5e
\renew@command: Always explicitly generate a space after the csname and not rely on \noexpand to save tokens (git/41) 84
2018-09-26 ltmiscen.dtx v1.1n
\@writefile: Sometimes mask the endline char when writing to files (github/73) 624
\add@percent@to@temptokena: Sometimes mask the endline char when writing to files (github/73) 623
\protected@file@percent: Sometimes mask the endline char when writing to files (github/73) 623
2018-09-26 ltsect.dtx v1.1c
\addcontentsline: Sometimes mask the endline char when writing to

files (github/73) 756
2018-10-10 ltspace.dtx v1.3i
\@esphack: Don't introduce breakpoints if @nobreak is true and after sections 320
2018-10-11 ltmiscen.dtx v1.1o
\@@sverb: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) 636
\@setupverbvisiblespace: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) 635
\@verbvisiblespacebox: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) 635
\asciispace: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) 635
verbatim*: Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) 636
\verbvisiblespace: Provide \verbvisiblespace such that it is usable in normal text (github/70) 635
Provide visible space in \verb* also for XeTeX and LuaTeX (github/69) 635
2018-10-21 ltluatex.dtx v1.1i
new_luafunction: Function added . . 61
2018-11-09 ltbibl.dtx LaTeX2e
\bibliography: Zap spaces in the argument as BibTeX doesn't support them (github/88) 788
2018-11-18 ltoutenc.dtx v2.0k
General: Provide \Hwithstroke and \hwithstroke 391
2018-11-19 ltoutenc.dtx v2.0k
General: Added \Hwithstroke and \hwithstroke 373
2018-11-28 ltoutput.dtx v1.4d
\@combinedblfloats: Unbox \@outputbox to preserve boxing level (github/94) 959
2018-12-30 lttab.dtx v1.1p
\@tabclassz: Add extra \hskip to guard against an \unskip at the start of a c-column cell (gh/102) 706
2019-02-07 ltfilehook.dtx v1.1o
\unqu@tefilef@und: Expand \@filef@und before executing second argument (github/109) . . 885
2019-02-07 ltfiles.dtx v1.1o
\@swaptwoargs: Helper macro added 349
2019-02-07 ltfssbas.dtx v3.2b
\define@newfont: Changed wording of warning (github/107) 424
2019-06-18 ltluatex.dtx v1.1j
General: finish_synctex_callback renamed finish_synctex 63
font_descriptor_objnum_provider added 63
make_extensible added 63
new_ graf added 62
page_objnum_provider added . . . 63
process_pdf_image_content added 63
wrapup_run added 63
2019-07-01 ltclass.dtx v1.3a
\endfilecontents: Support UTF8 and spaces in filecontents environment file name 851
2019-07-01 ltfiles.dtx v1.2a
\IfFileExists: Support UTF-8 . . . 346
\includeonly: Support UTF-8 340
\set@curr@file: Support UTF-8 . . 345
2019-07-09 ltfssbas.dtx v3.2c
\DeclareErrorFont: Don't set any \f@... macros 427
2019-07-09 ltfssini.dtx v3.1c
General: Explicitly set some defaults 543
2019-08-22 ltxref.dtx v1.1l
\labelformat: Commanded moved from varioref.sty 616
\Ref: Commanded moved from varioref.sty 616
\refstepcounter: Allow \p@... to have an argument 616
2019-08-27 fontdef.dtx v3.0c
General: Various commands made robust throughout the file 557
2019-08-27 ltboxes.dtx v1.3b
General: Various commands made robust 670
2019-08-27 ltclass.dtx v1.3b
\endfilecontents: Make various commands robust 851
2019-08-27 ltdefns.dtx v1.5f
General: Make various commands robust 106
\MakeRobust: Make the assignments global as we may need to apply them inside a group 90
2019-08-27 ltfilehook.dtx v1.2b
\unqu@tefilef@und: Make command robust 885
2019-08-27 ltfiles.dtx v1.2b
\IfFileExists: Make command robust 346

2019-08-27 ltfssbas.dtx v3.2d
General: Make various commands robust 410
2019-08-27 ltfssdcl.dtx v3.0s
`\DeclareMathAccent`: Make math accents robust 506
`\set@mathdelimiter`: Make math delimiters robust 513
2019-08-27 ltfssini.dtx v3.1d
General: Make various commands robust 518
2019-08-27 ltidxglo.dtx v1.1f
General: Make `\index` and `\gloassary` robust 783
2019-08-27 ltlength.dtx v1.1d
General: Make various command robust 408
2019-08-27 ltlogos.dtx v1.1j
`\TeX`: Make `\TeX` command robust . 331
2019-08-27 ltmath.dtx v1.2c
General: Make various commands robust 639
2019-08-27 ltmiscen.dtx v1.1p
General: Make various commands robust 618
`\begin`: Make command robust . . . 625
`\end`: Make command robust 628
2019-08-27 ltoutput.dtx v1.4e
`\@begindvibox`: Make `\AtBeginDvi` robust 938
2019-08-27 ltpage.dtx v1.0l
General: Make various commands robust 813
2019-08-27 ltpictur.dtx v1.1m
General: Make various commands robust 711
Remove several unnecessary `\gdef` definitions 711
2019-08-27 ltsect.dtx v1.1d
General: Make various commands robust 747
2019-08-27 ltspace.dtx v1.3j
General: Make various commands robust 312
2019-08-27 lttab.dtx v1.1q
General: Make various commands robust 686
Remove several unnecessary `\gdef` definitions 686
2019-08-30 lterror.dtx v1.2q
`\conditionally@traceoff`: Macro added 291
`\conditionally@traceon`: Macro added 291
2019-09-09 ltfssdcl.dtx v3.0s
`\DeclareMathSymbol`: Allow definition if the math symbol was a command already robust 508
2019-09-11 ltclass.dtx v1.3c
`\endfilecontents`: Support optional argument for filecontents 851
2019-09-14 ltfinal.dtx v2.1h
`\@uclclist`: Expand UTF8 chars when case changing (github/177) 1017
2019-09-16 ltxref.dtx v1.1m
General: Correctly revert the `\p@...` change 616
2019-09-21 fontdef.dtx v3.0d
General: Distangle alias (gh/184) 559, 563
2019-10-02 ltexpl.dtx v0.0
General: Initial version 72
2019-10-02 ltfinal.dtx v2.2
General: Load ltexpl 1018
2019-10-02 ltluatex.dtx v1.1k
General: linebreak_ filter is `exclusive` 62
mlist_ to_ hlist is `exclusive` 62
process_ rule is `exclusive` 62
2019-10-07 lttab.dtx v1.1q
`\extracolsep`: This needs to expand 698
2019-10-11 ltfiles.dtx v1.2c
`\set@curr@file`: Remove one brace group 345
2019-10-11 ltfsstrc.dtx v3.0l
`\@font@aliasinfo`: Added 'alias' size function 481
2019-10-18 ltclass.dtx v1.3d
`\load@onefilewithoptions`: Initialize `\...-h@@k` only when loading the package or class (gh/198) 843
2019-10-22 ltluatex.dtx v1.1j
General: page_objnum_provider and process_pdf_image_content classified data 63
2019-10-25 ltmiscen.dtx v1.1q
`\add@percent@to@temptokena`: Allow unbalanced conditionals in `#1` (gh/202) 623
2019-10-26 ltfiles.dtx v1.2d
`\@iffileonpath`: quote on openin . . 348
`\IfFileExists`: don't quote name . 346
`\IfFileExists@`: quote on openin . . 347
`\set@curr@file`: remove quotes . . . 345
2019-11-01 ltdirchk.dtx v1.3a
`\filename@parse`: take last . not first 12
2019-11-02 ltmiscen.dtx v1.1s
`\@centercr`: Make `\@centercr` robust (gh/203) 630

2019-11-02 ltspace.dtx v1.3k
\@normalcr: Make also \@normalcr robust 316
2019-11-09 ltfiles.dtx v1.2e
\set@curr@file: expand and \string before removing quotes 345
2019-11-10 ltmiscen.dtx v1.1r
\add@percent@to@temptokena: fix to special comment catcodes (gh/202) 623
2019-11-11 ltfiles.dtx v1.2f
\@iffileonpath: make \@filef@und match quoting used on \openin . 348
2019-11-22 ltoutenc.dtx v2.0l
General: Avoid spurious if fontenc selects LY1 as default encoding (gh/199) 399
2019-11-29 ltclass.dtx v1.3e
\@pr@videpackage: Protect package info text (gh/52) 831
2019-12-17 fontdef.dtx v3.0e
\mddefault: Set \bfdefault to "b" 551
\shapedefault: Set \shapedefault explicitly to "n" 552
\updefault: Set \updefault to "up" 551
2019-12-17 ltfntcmd.dtx v3.4c
textssc: Macro added 573
2019-12-17 ltfssbas.dtx v3.2e
\usefont: Don't call \fontseries or \fontshape 419
2019-12-17 ltfssini.dtx v3.1e
General: Provide custom series settings a la mweights 519
\DeclareEmphSequence: Provide \emph sequences 537
2019-12-18 ltoutenc.dtx v2.0m
General: Don't fake \textcompwordmark; take default from T1 instead 368
\add@accent: Avoid code that breaks \accent 361
2019-12-21 fontdef.dtx v3.0e
General: Distangle alias (gh/184) 557–560
2020-01-05 ltclass.dtx v1.3f
\endfilecontents: Support more write streams in LuaTeX gh/238 851
2020-01-11 ltfssini.dtx v3.1f
\rmfamily: Streamlined implementation with hook 532
\ttfamily: Streamlined implementation with hook 532
2020-01-20 ltfssdcl.dtx v3.0t
\set@mathdelimiter: fix for gh/251 513
2020-01-20 ltoutenc.dtx v2.0n
General: fix for gh/251 369
2020-01-22 lttextcomp.dtx v1.0b
\tc@subst: The overall default is \textcompsubstdefault not \substdefault 582
2020-01-25 fontdef.dtx v3.0f
General: Load t1enc.def last (gh/255) 548
2020-01-25 ltoutenc.dtx v2.0m
General: Load each encoding file only once (gh/255) 398
2020-01-27 ltclass.dtx v1.3g
\endfilecontents: Fix typo in error message 853
2020-01-28 ltclass.dtx v1.3h
\endfilecontents: Allow spaces in option string and display only unknown options not the whole option list (gh/256) 852
2020-01-31 ltvers.dtx v1.1e
General: Allow for upcoming format as pre-release 0 40
2020-02-02 ltluatex.dtx v1.1l
General: Add reverselist callback type 65
glyph_info added 63
page_order_index added 63
post_ linebreak_ filter is reverselist 62
create_callback: Provide proper fallbacks for user-defined callbacks without user-provided default handler 66
2020-02-05 ltfssini.dtx v3.1g
\DeclareFontSeriesDefault: Clarified error text 520
Corrected misspelled csname (gh/264) 520
2020-02-05 lttextcomp.dtx v2.0n
General: Changed the package default to info (gh/262) 599
Ensure we are on a new format (gh/260) 599
2020-02-07 ltfssini.dtx v3.1h
\symbol: XeTeX-specific version to avoid bug in maths mode. 540
2020-02-10 ltfssaxes.dtx v1.0c
\fontseries: Switch \if@forced@series added 446
\fontseriesforce: Switch \if@forced@series added 446
\if@forced@series: Switch \if@forced@series added 446

2020-02-10 ltfssini.dtx v3.1h
\\@defaultfamilyhook: Add \\@defaultfamilyhook to \\normalfont (gh/269) 533
\\reset@font: Add \\@defaultfamilyhook to \\normalfont (gh/269) 541
2020-02-10 lttextcomp.dtx v1.0c
General: Use \\@tabacckludge for tabbing where necessary (gh/271) 585
2020-02-11 fontdef.dtx v3.0g
General: Provide value for \\@fontenc@load@list (gh/273) . 548
2020-02-11 ltfssini.dtx v3.1h
General: Provide default value for \\@fontenc@load@list (gh/273) . 543
2020-02-11 ltoutenc.dtx v2.0o
General: Update \\@fontenc@load@list with option list (gh/273) 399
2020-02-14 ltpictur.dtx v1.1n
\\linethickness: Suppress spaces following the declaration (gh/274) 716
2020-02-18 ltfssini.dtx v3.1i
\\bfseries: Make the \\ifx selection outside of \\fontseries argument so that it is not done several times 527
\\mdseries: Make the \\ifx selection outside of \\fontseries argument so that it is not done several times 528
\\prepare@family@series@update: No series auto-update when forced (gh/277) 523
Recognize current family if it is not a "meta" family and auto-update series using \\bfdefault (gh/277) 523
2020-02-18 ltmath.dtx v1.2d
\\mathindent: Make \\mathindent a skip register to match amsmath (gh/252) 651
equation: Separate formula and eqn number by at least a space in fleqn option 653
2020-02-20 ltclass.dtx v1.3j
\\endfilecontents: Fix missing quotes around file name (gh/284) 853
2020-02-24 ltfssbas.dtx v3.2f
\\DeclareFontShape@: Drop surplus "m" in series when defining fontshape (gh/289) 411
2020-02-25 ltfssini.dtx v3.1j
\\bf@def@ult: Drop surplus "m" from \\bfdef@ult and \\mddef@ult (gh/291) 530
\\prepare@family@series@update: Drop surplus "m" from \\target@series@value (gh/291) 524
\\update@series@target@value: Drop surplus "m" from \\reserved@d (gh/291) 524, 525
2020-02-27 ltdefns.dtx v1.5g
\\@gobblethree: Macro added 87
2020-02-27 ltfssaxes.dtx v1.0d
\\series@maybe@drop@one@m: Drop "m" in certain values from a fixed list (gh/293) 450
\\set@target@series: Drop "m" only in a specific set of values (gh/293) 449
2020-02-27 ltfssbas.dtx v3.2g
\\DeclareFontShape@: Only "m" if the series value is a member of a fixed list and issue warning if doing it (gh/293) 411
2020-03-02 ltexpl.dtx v1.0a
General: Don't load expl3 if already in the format (gh/295) 72
2020-03-05 ltexpl.dtx v1.1
General: Load xparse.ltx if \\NewDocumentCommand is not defined by expl3.ltx 72
2020-03-06 ltboxes.dtx v1.3c
\\clap: Macro \\clap added 685
2020-03-07 ltluatex.dtx v1.1m
remove_from_callback: Do not call callback.register for user-defined callbacks 68
2020-03-07 ltmath.dtx v1.2e
\\negthickspace: Add amsmath math/text spacing commands to the kernel (gh/303) 644
2020-03-07 ltspace.dtx v1.3l
General: Moved \\thinspace, \\negthinspace and \\, to ltmath.dtx (gh/303) 312
2020-03-19 fontdef.dtx v3.0h
General: Support legacy use of \\bfdefault and \\mddefault (gh/306) 551
2020-03-19 ltfssdcl.dtx v3.0u
\\document@select@group: fix for (gnats/3357) 494
2020-03-19 ltfssini.dtx v3.1k
\\DeclareFontSeriesDefault: Support legacy use of \\bfdefault and \\mddefault (gh/306) 520
\\maybe@update@bfseries@defaults: Support legacy use of \\bfdefault and \\mddefault (gh/306) 527

\mdseries: Support legacy use of \bfdefault and \mddefault (gh/306) 528
2020-04-06 ltfssini.dtx v3.1m
\bf@def@ult: Hook added (gh/306) 530
\maybe@update@bfseries@defaults: Hook added (gh/306) 527
\maybe@update@mdseries@defaults: Hook added (gh/306) 528
2020-04-07 ltclass.dtx v1.3k
\IfFormatAtLeastTF: Macro added; also in rollback (gh/168) 827
\load@onefile@withoptions: Use different method to ignore unprocessed options (gh/22) . . . 847
\ProcessOptions*: Use different method to ignore unprocessed options (gh/22) 836
\RequirePackageWithOptions: Use different method to ignore unprocessed options (gh/22) . . . 839
2020-04-09 ltfloat.dtx v1.2d
\@textsubscript: Set non-zero baseline (gh/249) 779
\textsubscript: Set non-zero baseline (gh/249) 778
2020-04-13 ltfssdcl.dtx v3.0v
\process@table: Small update for speed. 498
2020-04-13 ltfssini.dtx v3.1n
\init@series@setup: Handling \seriesdefault changes (gh/315) 526
\seriesdefault@kernel: Handling \seriesdefault changes (gh/315) 544
2020-04-21 ltmath.dtx v1.2f
\@yeqncr: Support calc syntax (gh/152) 649
2020-04-21 ltmiscen.dtx v1.1t
\@icentercr: Support calc syntax (gh/152) 631
2020-04-21 ltpictur.dtx v1.1o
\@istackcr: Support calc syntax (gh/152) 716
2020-04-21 ltspace.dtx v1.3m
\@hspace: Support calc syntax (gh/152) 329
\@newline: Support calc syntax (gh/152) 317
\@vspace@calcify: Support calc syntax (gh/152) 317
\@vspacer: Support calc syntax (gh/152) 326
\addvspace: Support calc syntax (gh/152) 323
2020-04-21 lttab.dtx v1.1r
\@itabcr: Support calc syntax (gh/152) 692
\@yargarraycr: Support calc syntax (gh/152) 700
2020-04-22 ltmiscen.dtx v1.1u
\@@sverb: Drop spaces before \verb delimiter (gh/327) 636
2020-04-22 ltoutenc.dtx v2.0p
General: y unicode value in tuenc.def 354
2020-04-29 lttextcomp.dtx v1.0d
General: Make all capital accents text commands for hyperref (gh/332) 585
2020-05-02 ltfiles.dtx v1.2g
\@include: Support spaces in filenames by enclosing the names of .aux-files in quotes (gh/217) . 341
\includeonly: Get rid of leading and trailing spaces from the filename (gh/217) 340
Improved support for spaces in filenames (gh/217) 340
Pass the filename to \@include by value instead of by reference (gh/217) 340
2020-05-05 ltxref.dtx v1.1n
\refstepcounter: record the counter name in \@currentcounter 615
2020-05-06 ltspace.dtx v1.3n
General: Made softhyphen active in TU engines 330
2020-05-09 ltdefns.dtx v1.5j
\@if@DeclareRobustCommand: Added \DeclareCommandCopy (gh/239) . . 98
\DeclareCommandCopy: Added \DeclareCommandCopy (gh/239) . . 96
2020-05-11 ltdefns.dtx v1.5j
\@dischyph: Do not overwrite \- under LuaTEX 105
2020-05-15 ltdefns.dtx v1.5g
\typeout: Allow \par in the argument (gh/335) 78
2020-05-19 ltfssaxes.dtx v1.0e
\series@maybe@drop@one@m: Need to use \edef (gh/336) 450
2020-05-19 ltfssini.dtx v3.2a
\IfFontSeriesContextTF: Macros added (gh/335) 535
2020-05-31 ltmiscen.dtx v1.1u
\centering: Added \finalhyphendemerits setting (gh/247) 631

\raggedleft: Added \finalhyphendemerits setting (gh/247) 632
\raggedright: Added \finalhyphendemerits setting (gh/247) 631
2020-06-04 ltexpl.dtx v1.2c
General: Define a local version of some LaTeX 2ε basic macros to support package loading 72
2020-06-04 ltfinal.dtx v2.2a
General: Load ltexpl in ltdefns . . 1018
2020-06-05 ltclass.dtx v1.3l
\@currnamestack: Added \@expl@pop@filename@@ 825
Added \@expl@push@filename@@ and \@expl@push@filename@aux@@ . . 824
2020-06-05 ltfiles.dtx v1.2h
\document: Added hook to load l3backend code 334
2020-06-10 ltluatex.dtx v1.1n
General: Define \@gobble/\@firstofone even for LaTeX to allow early loading. 48
2020-07-04 ltoutenc.dtx v2.0q
General: Implement \remove@tlig in LuaTeXwithout font reloading . . 386
2020-07-08 ltexpl.dtx v1.2d
General: Add a last-minute hook for expl3 73
2020-07-08 ltfinal.dtx v2.2b
General: Add a last-minute hook for expl3 1009
2020-07-27 ltmath.dtx v1.2g
\cases: Don't make the command \long (gh/354) 643
\matrix: Don't make the command \long (gh/354) 643
\pmatrix: Don't make the command \long (gh/354) 643
2020-07-27 ltoutenc.dtx v2.0r
\@use@text@encoding: Don't make the command \long (gh/354) . 363, 364
2020-07-27 ltpage.dtx v1.0m
\markright: Don't make the command \long (gh/354) 814, 815
2020-07-27 ltpictur.dtx v1.1p
\linethickness: Don't make the command \long (gh/354) 716
2020-07-27 ltsect.dtx v1.1e
\author: Don't make the command \long (gh/354) 747
\date: Don't make the command \long (gh/354) 747
2020-08-01 ltluatex.dtx v1.1p
General: new_ graf is exclusive . . . 62
2020-08-02 ltluatex.dtx v1.1q
\newattribute: Move reset to 0 inside conditional 50
\newluabytecode: Move reset to 0 inside conditional 53
\newluachunkname: Move reset to 0 inside conditional 54
\newluafunction: Move reset to 0 inside conditional 52
\newwhatsit: Move reset to 0 inside conditional 53
2020-08-08 ltclass.dtx v1.3m
\endfilecontents: define \q@curr@file directly as the quotes have already been removed (gh/220) 852
2020-08-10 ltluatex.dtx v1.1r
General: Load ltluatex Lua module during format building 54
2020-08-15 ltpictur.dtx v1.2a
\@defaultunitsset: Macro added . 713
2020-08-19 ltdefns.dtx v1.5k
\@carcube: Made \long for \NewCommandCopy 81
\robust@command@act: Made \robust@command@act (was \declare@command@copy) more generic 94
\ShowCommand: Added \ShowCommand (gh/373) 97
2020-08-19 ltexpl.dtx v1.2e
General: Add \@expl@cs@⟨*thing*⟩@spec@@N for \ShowCommand (gh/373) 76
Add \@expl@cs@to@str@@N and \@expl@str@if@eq@@nnTF for \NewCommandCopy (gh/239) 75
2020-08-20 ltplain.dtx v2.3d
\alloc@: Define \alloc@ in terms of \e@alloc 22
2020-08-21 ltclass.dtx v1.3o
General: Integration of new hook management interface 818
2020-08-21 ltdefns.dtx v1.5l
General: Integration of new hook management interface 78
2020-08-21 ltdefns.dtx v1.5m
\MakeRobust: Make \MakeRobust produce the same command

structure as
\DeclareRobustCommand 90
2020-08-21 ltexpl.dtx v1.2d
General: Dropped unused command . 72
2020-08-21 ltfiles.dtx v1.2i
General: Integration of new hook management interface 332
2020-08-21 ltfinal.dtx v2.2i
General: Integration of new hook management interface 1003
2020-08-21 ltfssaxes.dtx v1.0g
General: Integration of new hook management interface 457
2020-08-21 ltfssini.dtx v3.2b
\bf@def@ult: Integration of new hook management interface 530
mdseries/defaults: Integration of new hook management interface 533
\maybe@update@bfseries@defaults: Integration of new hook management interface 527
\maybe@update@mdseries@defaults: Integration of new hook management interface 528
\reset@font: Integration of new hook management interface 541
\rmfamily: Integration of new hook management interface 532
\ttfamily: Integration of new hook management interface 532
2020-08-21 ltmiscen.dtx v1.1v
General: Integration of new hook management interface 618
2020-08-21 ltoutput.dtx v1.4f
\@begindvibox: Integration of new hook management interface 938
2020-08-23 ltxref.dtx v1.1o
\refstepcounter: add default definition of \@currentcounter . 615
2020-09-06 ltclass.dtx v1.3q
\load@onefilewithoptions: Save \@currpkg@reqd so that we don't lose track of package substitutions. 844
2020-09-06 ltdefns.dtx v1.5n
\char@if@alph: Macro added 104
2020-09-06 ltexpl.dtx v1.2f
General: Add \@expl@str@map@function@@NN and \@expl@str@map@function@@Nn for \string@makeletter (gh/386) 76
2020-09-09 ltshipout.dtx v1.0b
__shipout_picture_overlay:n: Prevent overfull box warnings (gh/387) 917
2020-09-26 ltfinal.dtx v2.2j
General: Load first aid file if existing 1020
2020-09-30 ltfssini.dtx v3.2d
\maybe@update@bfseries@defaults: \bfdefault@previous not \bfseries@previous (gh/395) . . 527
\mdseries: \mddefault@previous not \mdseries@previous (gh/395) . . 528
2020-10-01 ltclass.dtx v1.3r
\@pr@videpackage: Allow for package substitution 831
2020-10-01 ltsect.dtx v1.1e
\addcontentsline: add a fourth argument for better hyperref compatibility 756
2020-10-04 ltfiles.dtx v1.2j
\@include: Quotes around the aux file name removed, they are not needed and upset BibTeX (gh/400) 342
2020-10-04 lthooks.dtx v1.0d
General: Definition \AddToHookNext was supposed to be for \AddToHook vice versa (gh/401) 254
2020-10-08 ltclass.dtx v1.3s
\@currnamestack: Added missing 2020/02/02 \IncludeInRelease . 824
2020-10-11 ltclass.dtx v1.3t
\load@onefilewithoptions: Restore \@currpkg@reqd after finished loading a package file (gh/408). . 845
2020-10-18 ltclass.dtx v1.3t
\PassOptionsToClass: Drop path from \input@path (gh/414). . . . 832
2020-10-23 ltmiscen.dtx v1.1w
\enddocument: Make enddocument/afteraux one-time 620
2020-10-26 ltmiscen.dtx v1.1x
\@kernel@before@enddocument: \enddocument should always start out in vmode (gh/385) 622
2020-11-09 ltclass.dtx v1.3u
\pkgcls@rollbackdate@error: Change help text because the package may have existed then — there is just no rollback data (gh/423). 866
2020-11-09 ltmath.dtx v1.2h
\negmedspace and \negthickspace have been only in amsmath, so we need to undefine for rollback (gh/423) 645
2020-11-20 ltclass.dtx v1.3u
\@currpath: Macro added 823

\@kernel@currpathstack: Macro added 826
\load@onefile@withoptions: Copy option list to the requested package. 846
\PassOptionsToClass: Copy option list to the requested package. . . . 833
\ProvidesPackage: Use string comparison instead of \ifx 830
2020-11-20 ltcmd.dtx v1.0a
General: Initial version derived from xparse.dtx 108
2020-11-20 ltfilehook.dtx v1.0d
\unqu@tefilef@und: Move loading to \@input@file@exists@with@hooks and expand \@filef@und to avoid getting the wrong file name in the case of a substitution. 884
2020-11-23 ltshipout.dtx v1.0d
__shipout_execute_cont:: Check for both kernel and user hook (gh/431) 907
__shipout_execute_main_cont:Nnnn: Check for both kernel and user hook (gh/431) 909
2020-11-24 ltexpl.dtx v1.2g
General: Support for roll forward (gh/434) 74–76
2020-11-24 ltfilehook.dtx v1.0d
General: Support for roll forward (gh/434) 882
2020-11-24 lthooks.dtx v1.0f
__hook_end_document_label_check:: Support for roll forward (gh/434) 215
2020-11-24 ltshipout.dtx v1.0d
General: Support for roll forward (gh/434) 922
\AtBeginDvi: Support for roll forward (gh/434) 921
2020-11-25 ltdefns.dtx v1.5o
\@carcube: Added missing latexrelease entry 81
2020-12-02 ltluatex.dtx v1.1s
General: Fix return value of list callbacks 65
2020-12-03 ltfsstrc.dtx v3.0m
\selectfont: Install a hook in \selectfont (gh/444) 463
2020-12-04 ltfilehook.dtx v1.0d
\undeclare@file@substitution: Don't drop file substitution commands on rollback 887
2020-12-04 ltfssaxes.dtx v1.0h
General: Reorganized the rollback data 437
\fontseries: Distangle series and shape update (gh/444) 446
\fontshape: Distangle series and shape update (gh/444) 454
\fontshapeforce: Distangle series and shape update (gh/444) 454
2020-12-04 ltfssini.dtx v3.2f
General: Adjust start values for series and shape (gh/444) 543
2020-12-10 ltbibl.dtx v1.1s
\nocite: Delay any \nocite in the preamble instead of raising an error 789
2020-12-10 ltfssbas.dtx v3.2h
\usefont: Drop "m" if the series value is a member of a fixed list and issue warning if doing it (gh/453) 419
2020-12-14 ltclass.dtx v1.3v
\@currnamestack: Removed \@expl@@@hook@curr@name@push@@n 824
2020-12-18 ltexpl.dtx v1.2h
\@kernel@after@enddocument@afterlastpage: Define kernel \enddocument hooks early 72
2020-12-22 ltfssaxes.dtx v1.0h
\delayed@merge@font@series: Distangle series and shape update (gh/444) 448, 449
\delayed@merge@font@shape: Distangle series and shape update (gh/444) 455
2020-12-22 ltfsstrc.dtx v3.0n
\selectfont: Execute delayed series and shape updates (gh/444) . . . 462
2021-01-07 ltfilehook.dtx v1.0e
General: Added rollback for this case to avoid spurious errors (part of gh/463) 895
\unqu@tefilef@und: Restore \CurrentFile(Path)(Used) after the input (gh/464) 885
2021-01-07 lthooks.dtx v1.0h
__hook_strip_double_slash:w: Assume hook name has at least three nonempty parts (gh/464) . 224
__hook_tl_set:cx: Manually define some l3tl commands to work around expl3 changes 206

2021-01-08 ltshipout.dtx v1.0f
__shipout_execute_cont:: Added another kernel hook for more flexibility (cf https://github.com/pgf-tikz/pgf/issues/1900 907
2021-01-10 ltshipout.dtx v1.0g
\@kernel@after@shipout@background: Internal hook \@kernel@after@shipout@background added 911
\RawShipout: Macro added 911
2021-01-19 ltshipout.dtx v1.0h
__shipout_run_firstpage_hook:: Handling of firstpage hook altered 911
2021-01-21 ltclass.dtx v1.3w
\@kernel@currpathstack: Add empty entry for latexrelease 826
2021-01-21 ltexpl.dtx v1.3a
General: Move xparse rollback code to ltcmd.dtx 75
2021-01-21 ltfinal.dtx v2.2l
General: Load glyphtounicode.tex for pdfTEX 1011
2021-01-22 ltshipout.dtx v1.0i
__shipout_finalize_box:: Add pre_shipout_filter Lua callback 906
2021-01-24 ltexpl.dtx v1.3a
General: Define expl3 hooks conditionally 72
2021-01-31 ltfilehook.dtx v1.0f
\@curr@file@reqd: set \protect to \string gh/481 888
2021-02-03 ltfloat.dtx v1.2e
\@savemarbox: Explicitly end with \par (gh/489) 773
2021-02-04 ltboxes.dtx v1.4b
\color@endbox: Always add the color groups (gh/488) 674
2021-02-08 ltfilehook.dtx v1.0g
\unqu@tefilef@und: Undo the internal for robust \InputIfFileExists in rollback (gh/494) 886
2021-02-08 ltmiscen.dtx v1.1y
\end: Undo the internals for robust \begin and \end in rollback (gh/494) 629
2021-02-10 ltboxes.dtx v1.4b
\@mpfootnotetext: Explicitly run \par in support for paragraph tagging 682
2021-02-10 ltfloat.dtx v1.2e
\@footnotetext: Explicitly run \par at the end of footnote text in preparation for paragraph hooks 779
2021-02-15 ltfssdcl.dtx v3.0w
\document@select@group: fix for (gh/501) 494
2021-02-16 ltfloat.dtx v1.2f
\footref: \footref added 782
2021-02-17 ltoutenc.dtx v2.0t
General: Adjust values for \textasteriskcentered To match TS1 definition (gh/502) 391
Special definition for \textasteriskcentered when missing in TS1 (gh/502) 382
2021-02-18 ltclass.dtx v1.3x
\@fileswithoptions: save raw class option list (gh/85) 841
\@remove@eq@value: macro added (gh/85) 834
\@use@ption: value from unused option list (gh/85) 837
\OptionNotUsed: value from unused option list (gh/85) 834
\PassOptionsToClass: save raw option lists (gh/85) 832
2021-02-19 ltoutenc.dtx v2.0u
General: Add \textnonbreakinghyphen, \textfiguredash and \texthorizontalbar (gh/404) 371, 375, 390
2021-02-25 ltfinal.dtx v2.2m
General: Improve speed of ToUnicode everyjob loading code 1011
2021-03-03 ltclass.dtx v1.3y
\endfilecontents: Fix overwrite check for files with UTF-8 (gh/415) 853
2021-03-05 ltclass.dtx v1.3z
\ProcessOptions*: modify so braces to not give errors (gh/513) 835
2021-03-12 ltfiles.dtx v1.2k
\IfFileExists@: Allow unbalanced conditionals (gh/530) 347
2021-03-18 ltcmd.dtx v1.0b
General: Use \NewModuleRelease. . 108
2021-03-18 ltfilehook.dtx v1.0h
__filehook_file_pop_assign:nnnn: Define \g_@@_input_file_seq to avoid losing data when rolling back. 882

2021-03-18 ltfssaxes.dtx v1.0i
General: Fix rollforward definition. . 447
2021-03-18 ltfssini.dtx v3.2g
General: Add legacy hook definitions for rollback. 533
2021-03-18 lthooks.dtx v1.0i
`\__hook_end_document_label_check:`: Only add `top-level` if not already there. 215
Remove the (empty) "top-level" from `\@currnamestack`. 216
General: Use `\NewModuleRelease`. . 204
2021-03-18 ltvers.dtx v1.1f
`\@check@IncludeInRelease`: Add support for usage in `\NewModuleRelease` 41
`\new@moduledate`: Added `\NewModuleRelease`. 42
2021-03-19 lttextcomp.dtx v1.0e
General: Use `\NewModuleRelease` . . 579
2021-03-26 ltplain.dtx v2.3e
`\@unused`: Allocate `\@inputcheck` and `\@unused` early so that they are before expl3 allocates more streams (gh/538) 24
2021-03-27 ltclass.dtx v1.4a
`\@currnamestack`: Do not completely roll back if expl3 is loaded. 825
2021-04-16 ltvers.dtx v1.1g
`\new@moduledate`: `\NewModuleRelease` with the same arguments as `\IncludeInRelease`. 42
2021-04-17 ltfiles.dtx v1.2m
`\@kernel@after@begindocument`: Move `\@kernel@before@begindocument` and `\@kernel@after@begindocument` init earlier so that other modules can write to the hooks 337
2021-04-18 ltluatex.dtx v1.1t
General: input_level_string added . . 63
2021-04-18 ltplain.dtx v2.3f
`\loggingall`: 3 35
Drop pre-ε-TEX support 35
`\tracingnone`: 3 36
Drop pre-ε-TEX support 36
2021-04-19 ltcmd.dtx v1.0d
`\__cmd_cmd_type_cases:Nnnnn`: Renamed `\__cmd_cmd_if_xparse:NTF` to `\__kernel_cmd_if_xparse:NTF` for cross-module usage 169
2021-04-20 ltexpl.dtx v1.3c
`\@kernel@after@enddocument@afterlastpage`: Don't empty kernel hooks on rollback 72
2021-04-20 ltfilehook.dtx v1.0i
`\@curr@file@reqd`: Make expand to a string (tracks change in l3kernel) 888
2021-04-26 ltfssbas.dtx v3.2i
`\usefont`: Unconditionally switch to the requested font face (gh/444) 419
2021-04-26 ltfssini.dtx v3.2h
`\reset@font`: Unconditionally switch to the requested font face (gh/444) 541
2021-04-26 ltfsstrc.dtx v3.0o
`\selectfont`: Unset the forced series boolean when reaching `\selectfont` (gh/444) 463
2021-04-29 lthooks.dtx v1.0m
`\ActivateGenericHook`: Add `\ProvideHook` etc. 250
2021-04-29 ltoutenc.dtx v2.0v
General: Add composites for `\ae/\AE/æ/Æ` (gh/552) 395
2021-05-18 ltclass.dtx v1.4b
`\@raw@classoptionslist`: Initialise to `\relax` to match `\@classoptionslist` 823
2021-05-24 ltcmd.dtx v1.0e
General: Use `\msg_...` instead of `\__kernel_msg...` 108
2021-05-24 ltcmdhooks.dtx v1.0b
General: Use `\msg_...` instead of `\__kernel_msg...` 259
2021-05-24 ltfilehook.dtx v1.0k
General: Use `\msg_...` instead of `\__kernel_msg...` 880
2021-05-24 lthooks.dtx v1.0n
General: Use `\msg_...` instead of `\__kernel_msg...` 204
2021-05-24 ltpara.dtx v1.0g
General: Use `\msg_...` instead of `\__kernel_msg...` 302
2021-05-26 ltdefns.dtx v1.5p
`\MakeRobust`: Normalize error message in `\MakeRobust` 90
2021-06-03 ltclass.dtx v1.4c
`\@kernel@currpathstack`: Take care of `\@kernel@currpathstack` when rolling back/forward. 826
2021-06-04 ltcmd.dtx v1.0f
General: Normalize various error messages 171

2021-06-05 ltmiscen.dtx v1.1z
\@@sverb: Normalize error message . 636
2021-06-06 ltclass.dtx v1.4c
\@loadwithoptions: handle raw options for gh/580 839
\load@onefile@withoptions: Copy raw options for gh/580 846
\PassOptionsToClass: apply \expandafter to raw options for gh/580 833
2021-06-09 ltclass.dtx v1.4b
\endfilecontents: Use \@latex@note@no@line to display the information 852, 853
2021-06-09 lterror.dtx v1.2r
\@latex@note@no@line: Macros added 286
2021-06-09 ltfssbas.dtx v3.2j
\DeclareFontShape@: Improve information message 411
2021-07-08 ltcounts.dtx v1.1m
\counterwithin: New implementation for \counterwithout and \counterwithin 403
2021-07-11 lterror.dtx v1.2s
\PackageNoteNoLine: Provide \ClassNote and \PackageNote . 285
2021-07-12 ltclass.dtx v1.4d
\@fileswithoptions: add \unexpanded 842
2021-07-19 ltclass.dtx v1.4e
\@classoptionslist: Drop \@onlypreamble 823
\@ifclasslater: Drop \@onlypreamble 827
\@ifclassloaded: Drop \@onlypreamble 827
\@ifclasswith: Drop \@onlypreamble 828, 829
\@ifl@ter: Drop \@onlypreamble . 828
\@pkgextension: Drop \@onlypreamble 823
\@ptionlist: Drop \@onlypreamble 827
\@unusedoptionlist: Drop \@onlypreamble 823
\IfFormatAtLeastTF: Drop \@onlypreamble 827
2021-07-20 ltcmdhooks.dtx v1.0c
__hook_patch_DeclareRobustCommand:Nnn: Use \robust@command@chk@safe before \@if@newcommand. 264
2021-07-22 lthooks.dtx v1.0o
__hook_gremove_code:nn: Do not queue removals (gh/625) 225
__hook_hook_gput_code_do:nnn: Do not queue removals (gh/625) . . . 217
2021-07-23 ltclass.dtx v1.4e
\load@onefile@withoptions: Make class/name/after a one-time hook 847
Make class/name/before a one-time hook 846
Make package/name/after a one-time hook 847
Make package/name/before a one-time hook 846
2021-07-23 ltfiles.dtx v1.2n
\@include: Make include/name/after a one-time hook 342
Make include/name/before a one-time hook 342
Make include/name/end a one-time hook 342
2021-07-27 lthooks.dtx v1.0o
__hook_clear_next:n: Macro made public 242
\ClearHookNext: Macro added 250
2021-07-28 ltsect.dtx v1.1f
\contentsline: Pick up four arguments (gh/633) 757
2021-07-30 ltcmd.dtx v1.0d
__cmd_cmd_type_cases:Nnnnn: Added \@@_cmd_type_cases:NnnnnF for \NewCommandCopy and \ShowCommand support 169
2021-07-31 ltoutput.dtx v1.4e
\fl@tracemessage: Enable display when doing \tracefloatvals . . 985
2021-07-31 ltoutput.dtx v1.4g
\ShowFloat: Macro added 983
2021-08-02 lthooks.dtx v1.0o
\ActivateGenericHook: Change name 250
\DisableGenericHook: Change name 250
2021-08-07 ltcmd.dtx v1.0g
__cmd_add_grabber:N: Replicate argument processors for all embellishments (gh/639) 132
__cmd_add_type_E:w: Replicate argument processors for all embellishments (gh/639) 130
2021-08-08 ltfinal.dtx v2.2p
\IfPDFManagementActiveTF: Default definition added (gh/640) 1020
2021-08-10 ltvers.dtx v1.1h
\@check@IncludeInRelease: Add error to aid debugging 41

2021-08-11 ltluatex.dtx v1.1u
General: Define missing local function 56
2021-08-20 lterror.dtx v1.2t
`\@badend`: Improve `\@badend` error message (gh/587) 289
2021-08-20 lthooks.dtx v1.0p
General: Added deprecation warnings for old generic hook commands (gh/638) 252
Documentation updates for generic hook commands (gh/638) 182
Renames of generic hook commands (gh/638) 212
Section on generic hooks added (gh/638) 197
2021-08-25 ltclass.dtx v1.4f
General: Standardise generic hook names (gh/648) 818
`\load@onefile@withoptions`: Declare non-generic package and class hooks 847
2021-08-25 ltcmdhooks.dtx v1.0d
`\__hook_try_put_cmd_hook:w`: Simplify generic hook detection . 261
2021-08-25 ltfilehook.dtx v1.0l
`\unqu@tefilef@und`: Declare non-generic file hooks 885
2021-08-25 ltfiles.dtx v1.2o
`\@include`: Declare non-generic include hooks 343
Standardise generic hook names (gh/648) 342
2021-08-25 lthooks.dtx v1.0p
`\__hook_try_declaring_generic_next_hook:nn`: Standardise generic hook names (gh/648) 219
2021-08-27 ltcmd.dtx v1.0h
`\NewDocumentEnvironment`: Check for end-of-environment command . . 177
2021-08-27 ltfilehook.dtx v1.0l
`\__filehook_file_pop_assign:nnnn`: Internal message name changes . 882
`\__filehook_file_subst_cycle_error:cN`: Use `\msg_...` not `\__kernel_msg_...` 893
2021-08-27 lthooks.dtx v1.0q
General: Internal message name changes 247
2021-08-27 ltpara.dtx v1.0i
General: Internal message name changes 308
2021-08-30 ltcmd.dtx v1.0h
General: Added support for `\NewCommandCopy` 137
Added support for `\ShowCommand` 142
2021-09-03 ltoutput.dtx v1.4h
`\ShowFloat`: Renamed, original name never distributed 983
2021-09-06 ltfinal.dtx v2.2q
`\@uclclist`: Correctly upper and lowercase `\ij` and `\IJ` (gh/658) 1017
2021-09-06 lthooks.dtx v1.0r
`\__hook_hook_gput_code_do:nnn`: Use dedicated conditional (gh/606) . 217
`\__hook_if_execute_immediately:n`: Macro added (gh/606) 244
`\__hook_use_once:n`: Clean up after `\UseOneTimeHook` (gh/606) 244
`\__hook_use_once_clear:n`: Clean up after `\UseOneTimeHook` (gh/606) 244
2021-09-10 ltfssini.dtx v3.2i
`\bfseries`: Do delayed changes to `\bfdefault` in a separate macro for better reuse (gh/663) 527
`\DeclareFontSeriesDefault`: Do delayed changes to `\bfdefault` or `\mddefault` first (gh/663) 520
`\maybe@update@bfseries@defaults`: Do delayed changes to `\bfdefault` in a separate macro for better reuse (gh/663) 527
`\maybe@update@mdseries@defaults`: Do delayed changes to `\mddefault` in a separate macro for better reuse (gh/663) 528
`\mdseries`: Do delayed changes to `\mddefault` in a separate macro for better reuse (gh/663) 528
2021-09-12 ltfntcmd.dtx v3.5a
`\check@nocorr@`: use `\unexpanded` to make # safe 574
2021-09-12 ltoutenc.dtx v2.0w
General: Move zero skip between i and j for hyphenation (gh/658) 372
2021-09-18 ltpara.dtx v1.0i
`\para_end:`: Use skip rather than kern as guard. 306
2021-09-26 ltfssdcl.dtx v3.0x
`\__nfss_init_mv_freeze:N`: Macro added for (gh/676) 495
`\c@localalphabets`: Counter added for (gh/676) 493
`\document@select@group`: Test if we should freeze the version (gh/676) 493
`\freeze@math@version`: Macro added for (gh/676) 494

2021-09-28 ltcmdhooks.dtx v1.0e
- `\__hook_make_prefixes:w`: Make patching of commands a global operation (gh/674) 267
- `\__hook_patch_retokenize:Nnnn`: Make patching of commands a global operation (gh/674) 273

2021-09-28 lthooks.dtx v1.0s
- `\__hook_if_usable_use:n`: Correct usage of older `\@@_if_file_hook:wTF` (gh/675) 243
- `\__hook_try_declaring_generic_hook_split:nNNnn`: Correct usage of older `\@@_if_file_hook:wTF` (gh/675) 219

2021-10-14 ltboxes.dtx v1.4c
- `\@mpfootnotetext`: Explicitly set `\@currentcounter` (gh/687) . . . 682

2021-10-14 ltfiles.dtx v1.2p
- `\@include`: Warn about use in preamble 342

2021-10-14 ltfloat.dtx v1.2g
- `\@footnotetext`: Explicitly set `\@currentcounter` (gh/687) . . . 779

2021-10-14 ltmath.dtx v1.2j
- `\@eqnsel`: Explicitly set `\@currentcounter` (gh/687) . . . 649
- `eqnarray`: Explicitly set `\@currentcounter` (gh/687) . . . 653

2021-10-15 ltfssdcl.dtx v3.0y
- `\DeclareMathVersion`: Initialize variable for freezing math version (gh/676) 498

2021-10-15 ltluatex.dtx v1.1v
- General: provide_charproc_data added 63

2021-10-16 ltoutenc.dtx v2.0x
- `\add@accent`: Dont set `\spacefactor in math mode gh/643` 361

2021-10-19 ltpara.dtx v1.0k
- General: Remove content from `\tex_everypar:D` on rollback . . . 309

2021-10-20 ltcmdhooks.dtx v1.0f
- `\__hook_make_prefixes:w`: Correct patching by expansion+redefinition when the macro contains a parameter tokens (gh/697). 264

2021-11-17 ltluatex.dtx v1.1w
- General: hpack_ quality is `exclusive` 62
  - Never pass on `true` return values for list callbacks 65
  - vpack_ quality is `exclusive` 62

2021-11-30 ltclass.dtx v1.5a
- `\@onefilewithoptions@clashchk`: Separated out from `\@onefilewithoptions` 845

2021-11-30 ltexpl.dtx v1.3d
- `\skipeval`: Moved over from `xfp` package (gh/711) 76

2021-12-02 ltcmd.dtx v1.0i
- `\__cmd_run_code:`: Correct defaults for optional arguments in end-of-environment code (gh/712) 116
- `\__cmd_start_aux:ccnnnn`: Correct defaults for optional arguments in end-of-environment code (gh/712) 116

2021-12-07 ltexpl.dtx v1.3d
- `\skipeval`: Added `\dimeval` and `\skipeval` (gh/711) 77

2021-12-11 ltdirchk.dtx v1.3a
- General: Add comment lines into latex.ltx to indicate temp definitions that are later overwritten (gh/725) 2

2021-12-12 ltoutenc.dtx v2.0y
- General: `\DeclareUnicodeAccent` now makes the encoding argument implicit (gh/253) 388
  - Added `\DeclareUnicodeCommand` and `\DeclareUnicodeSymbol` (gh/253) 388

2021-12-27 ltluatex.dtx v1.1x
- `\newprotectedluacmd`: Macros added 53

2021-12-28 ltexpl.dtx v1.3d
- `\ExpandArgs`: Added document level names for `\exp_args:Nc` and the like (gh/735) 77

2021-13-31 ltcmd.dtx v1.0j
- `\__cmd_show_environment:N`: Make `\ShowCommand` stop for interaction 142, 143

2022-01-06 ltexpl.dtx v1.3e
- `\ExpandArgs`: Adjust document level names for `\exp_args:Nc` and the like (gh/735) 77

2022-01-06 ltshipout.dtx v1.0l
- `\AtBeginShipoutNext`: Correctly simulate `\AtBeginShipout` and `\AtBeginShipoutNext` without extending the syntax 923
- `\AtEndDvi`: Correctly simulate `\AtEndDvi` without extending the syntax 923

2022-01-15 ltkeys.dtx v1.0b
- `\__keys_options_aux:n`: Clear option list in end-of-package hook 870

2022-01-25 ltplain.dtx v2.3h
\obeyspaces: Provide redirection to support special use cases (gh/367) 29
2022-02-05 ltkeys.dtx v1.0b
.usage: Create properties in ltlkeys 869
2022-02-07 ltkeys.dtx v1.0c
.usage: Correct ..code property . . . 869
2022-02-15 ltkeys.dtx v1.0c
\DeclareKeys: Expand module argument 872
\DeclareUnknownKeyHandler: Added \DeclareUnknownKeysHandler . . 872
\ProcessKeyOptions: Expand module argument 873
\SetKeys: Expand module argument 874
2022-02-16 ltkeys.dtx v1.0d
\DeclareKeys: Allow for active characters in module argument . 872
\DeclareUnknownKeyHandler: Allow for active characters in module argument 872
Rename \DeclareUnknownKeysHandler to \DeclareUnknownKeyHandler . . . 872
\ProcessKeyOptions: Allow for active characters in module argument . 873
\SetKeys: Allow for active characters in module argument 874
2022-02-19 ltcmd.dtx v1.0k
\IfBlankTF: Added \IfBlankTF and friends 179
2022-02-20 ltfinal.dtx v2.2r
\@uclclist: Use \@expl@text@uppercase@@n, removing local redefinition of \UTF@two@octets@noexpand . . . 1017
use \text_lowercase:n 1016
2022-02-21 ltkeys.dtx v1.0e
__keys_options_expand_module:Nn: Faster approach to module expansion 872
2022-02-28 ltcmd.dtx v1.0k
General: Move latexrelease redefinitions from ltcmd.dtx . . . 180
2022-02-28 ltexpl.dtx v1.3f
General: Move latexrelease redefinitions from ltcmd.dtx 75
2022-02-28 ltvers.dtx v1.1i
\new@moduledate: Detect a missing \IncludeInRelease{0000/00/00}. 42
2022-03-10 ltbibl.dtx v1.1t
\cite: Ensure that an empty argument generates a warning (gh/790) 787
2022-03-10 ltfilehook.dtx v1.0m
\@curr@file@reqd: Add \set@curr@file@nosearch for graphicx 888
2022-03-18 ltclass.dtx v1.5b
\load@onefilewithoptions: Switch to \ProcessKeyOptions 844
2022-03-18 ltcmd.dtx v1.0l
__cmd_cmd_type_cases:Nnnnn: Fix \@@_cmd_type_cases:NnnnnF " prematurely expanding macros (gh/795) 169
2022-03-18 ltkeys.dtx v1.0f
__keys_options:n: Simplify to always cover global options 870
__keys_options_global:n: Simplify to always cover global options . . 870
\ProcessKeyOptions: Remove \ProcessKeyPackageOptions . . . 873
2022-04-01 ltfiles.dtx v1.2q
\@include: Process some hooks is an include file is bypassed 343
2022-04-01 lthooks.dtx v1.0t
\c__hook_generic_include/./end_tl: Support generic include/.../excluded hooks . . 224
2022-04-03 ltfinal.dtx v2.2s
General: Integration of new mark management interface 1003
2022-04-03 ltoutput.dtx v1.ih
\@opcol: Interface with new mark mechanism 949
2022-04-04 ltpage.dtx v1.0n
\markright: Interface with new mark mechanism 814, 815
2022-04-08 ltmath.dtx v1.2k
\openup: Make \protected (gh/123) 644
2022-04-12 ltxref.dtx LaTeX2e
\pageref: Macro reimplemented with a starred version 614
\ref: Macro reimplemented with a starred version 614
2022-04-12 ltxref.dtx v1.1p
General: Add starred variants for the ref commands 612
\Ref: Macro reimplemented with a starred version 616
2022-04-21 ltfinal.dtx v2.2t
\@uclclist: Support \noexpand in argument of \@expl@text@uppercase@@n . . . 1017
2022-05-06 ltmarks.dtx v1.0c
__mark_new_class:nn: Wrong command made \@onlypreamble 799

2022-05-08 ltmath.dtx v1.2l
General: Use consistent math styles under LuaTEX 651
2022-05-08 ltshipout.dtx v1.0m
`\@kernel@after@enddocument@afterlastpage`: Handle case where shipout/lastpage is run too early (gh/813) 919
`\__shipout_execute_main_cont:Nnnn`: Handle case where shipout/lastpage is run too early (gh/813) 910
2022-05-13 lthooks.dtx v1.0u
`\__hook_use_once_clear:n`: Check if prop exists to avoid l3debug error 244
2022-05-17 lthooks.dtx v1.0u
`\__hook_initialize_hook_code:n`: Refuse sorting one-time hooks (gh/818). 230
2022-05-17 ltmeta.dtx v1.0b
General: Default definition for targets added 311
2022-05-27 ltfiles.dtx v1.2r
`\listfiles`: Try saved version string, if ver@.. is `\relax` (gh/825) . . . 352
2022-05-27 ltoutenc.dtx v2.0z
General: Save the version string (gh/825) 399
2022-06-01 ltmarks.dtx v1.0d
`\__mark_update_structure:nn`: Extend the logic for detecting the marks in the box (gh/836) 801
General: Marks are kernel errors . . . 806
2022-06-02 ltfinal.dtx v2.2u
`\@uclclist`: Add `\NoCaseChange` . 1017

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols

\! aa523, b398, b400
\! I201
\" aa524, s226, s378, s419, s457, s468, s579, s611, s638, s646, s652, s656, s662, s666, s672, s678, s685, s686, s692, s696, s746, s792, s1244, s1262, s1268, s1272, s1278, s1282, s1288, s1294, s1301, s1302, s1308, s1312, s1314, s1421, v416, E171, E198
\# aa507, a65, a78, b6, b14, b498, f696, i341, v403
\$ aa508, a77, b4, b13, f695, s307, s444, s451, s565, s804, s811, E631, E638
\$ *1040*
\% aa509, a78, a108, a110, a130, b14, b496, f696, s491, s493, v405, E640, E760, H135, U1451, U1452
\& . . aa510, a77, b5, b13, b497, f695, U376
\' aa525, b518, s227, s379, s421, s455, s465, s581, s591, s597, s599, s602, s604, s612, s618, s624, s626, s629, s631, s639, s643, s650, s654, s659, s664, s667, s669, s676, s681, s682, s689, s694, s697, s747, s794, s813, s815, s816, s817, s820, s822, s823, s824, s826, s827, s1238, s1259, s1266, s1270, s1275, s1280, s1283, s1285, s1292, s1297, s1298, s1305, s1310, s1313, s1321, s1322, s1369, s1370, s1375, s1376, s1387, s1388, s1393, s1394, s1422, s1423, s1437, s1438, s1439, s1440, s1453, s1454, v415, A775, B253, E161, H576, I241, K290, K311, L72, Y586
\(. I332
\(. I258
\) b518, I333
\) I258
* v408, U1132, U1263, U1377, U1453
* I238
\+ L72
\+ *1038*
\, . b399, b401, B506, H576, I7, I8, I40, I154, I156, I159, I184, I207, I208, I224
\, ... *1079*
\- aa224, aa264, b367, f24, p416, p478, s416, s417, s574, s788, s789, v410, H576, K289, K310, L72
\- f730, *105*
\. b398, b400, r45, r114, r172, s228, s380, s452, s453, s474, s587, s588, s614, s615, s641, s748, s818, s825, s1243, s1325, s1326, s1335, s1336, s1345, s1346, s1363, s1424, s1425, s1461, s1462, v409, E173, E199
\. *1067*
\..default *438*
.code V4
.if V4
.store V4
.usage V4
\/ a100, f25, i199, v357, v411, U375
\/ *1034*
\: I201, I211, I212, I213, I229, I239, I239, f690, f691, b399, b401
\; b399, b401, B500, I185
\; I201, *644*
\< s575, s739, v406, H576, L71, L109
\= s229, s381, s473, s749, s1241, s1315, s1316, s1331, s1332, s1354, s1355, s1356, s1381, s1382, s1407, s1408, s1441, s1442, s1443, s1444, s1459, s1460, s1467, s1468, A775, E179, K290, K311, L71
\> s572, s740, v407, H576, I213, I228, I229, I239, L71
\? aa525, b398, b400
@@ commands:
  \@@_cmd_type_cases:NnnnnTF . . . *1089*
  \@@_if_file_hook:wTF *1088*
  \g_@@_input_file_seq *1084*
  \@@_set_curr_file:nNN W387
  \@@_set_curr_file_assign:nnnNN W387
\@@\textvisiblespace␣\meta␣{hook} . *207*
\@@_next\textvisiblespace␣\meta␣{hook} *207*
\@@par *292*
\@TeXversion *6*, *1*
@botlist commands:
  \@botlist: Y1031, Y1125, Y1284
@botnum commands:
  \@botnum: Y1005
\@car *80*
\@cdr *80*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

@citeb commands:
\@citeb: R36, R65, R82
@colht commands:
\@colht: Y543, Y557
@colnum commands:
\@colnum: Y1190, Y1358
\@cons *80*
\@currdir *6*, *1*
@currname commands:
\@currname: r718
\@dblarg *79*
@dbldeferlist commands:
\@dbldeferlist: Y1757, Y1799
@dbltopnum commands:
\@dbltopnum: Y1656, Y1783
@deferlist commands:
\@deferlist: Y1116, Y1213, Y1274, Y1382, Y1426, Y1455, Y1513, Y1545, Y1631, Y1671
\@ifclasslater *821*
\@ifclassloaded *821*
\@ifclasswith *821*
\@ifdefinable *79*
\@ifnextchar *79*
\@ifpackagelater *821*
\@ifpackageloaded *821*
\@ifpackagewith *821*
\@ifstar *79*
\@ifundefined *79*
\@missingfileerror *822*
\@namedef *79*
\@nameuse *79*
\@restorepar *292*
\@setpar *292*
@topnum commands:
\@topnum: Y1051
\[. aa526, v412, A43, A54, A76, A87, I334
\[. I276, I435, *1069*
\\ aa511, a48, a49, a77, a250, a251, a252, a253, a256, a263, a264, a265, a266, a269, a276, a277, a278, a279, a282, a289, a295, a296, a300, a302, a303, a307, a312, a313, a316, a322, b13, d272, d425, f219, f276, f437, f525, f543, f695, g399, g463, g617, g629, g660, g1009, g1015, g2233, g2263, g2277, g2284, g2313, g2403, g2443, g2454, g2480, g2486, g2493, h930, h941, h1351, h1357, h1367, h1388, h1392, h1393, h1395, h1401, h1412, h1413, h1418, h1423, h1428, h1444, h1570, h1571, h1572, i338, i397, l277, n104, n111, n118, n119, n120, n121, p480, r711, r730, s560, v400, B251, H358, H363, H368, H378, H382, H386, H410, I357, I496, K322, K472, K474, L73, L170, L180, L194, *312*, M139
\\ p52, *1051*
\{ aa514, a6, a10, a77, b2, b13, g548, g1676, i339, l22, s308, s562, v401, B249, H409, I59, I154
\} aa515, a11, a77, b3, b13, i340, l21, s309, s563, v402, B250, H409, I59
\⟨*addto-cmd*⟩ *183*
\⟨*cmd*⟩␣ *138*
\⟨*cmd*⟩␣(arg␣⟨*num*⟩) *140*
\⟨*cmd*⟩␣␣ *138*
\⟨*cmd*⟩␣code *138*
\⟨*cmd*⟩␣defaults *138*
\⟨*filename*⟩ *890*
\⟨*function*⟩ *158*
\␣ aa506, a77, a94, b13, b404, b433, b434, b451, f695, h1393, l19, l20, l21, l22, l25, p421, v397, v647, v683, v708, B252, H406, H407, H512, H527, N36, N38, R37, U369
\] aa527, b518, v413, I335
\] I276, I459
\^ . . aa255, aa256, aa257, aa258, aa259, aa260, aa261, aa262, aa263, aa512, aa518, aa519, aa520, aa521, aa555, aa556, aa557, aa558, aa559, aa560, aa561, aa562, aa563, a66, a75, a78, a122, a333, b7, b9, b11, b14, b404, b405, b424, b425, b446, b447, f20, f696, g6, g7, g1712, g1972, g1977, g2657, p480, p482, p484, s231, s286, s382, s456, s466, s558, s644, s651, s655, s660, s665, s670, s677, s683, s684, s690, s695, s750, s1239, s1256, s1260, s1267, s1271, s1276, s1281, s1286, s1293, s1299, s1300, s1306, s1311, s1323, s1324, s1341, s1342, s1349, s1350, s1364, s1365, s1366, s1395, s1396, s1417, s1418, s1419, s1420, v398, v399, v404, E169, E197, H127, H136, U1133, U1134, U1135, U1216, U1219, U1222, U1264, U1265, U1266, U1348, U1351, U1354, U1378, U1379, U1380, U1438, U1441, U1444
_ s314, B254, I256, I257, aa513, f696, b8, b14, a78, *1047*
\‘ . . aa528, s232, s383, s420, s454, s464, s580, s642, s649, s653, s658, s663, s668, s675, s679, s680, s688, s693, s751, s793, s1237, s1258, s1265,

s1269, s1274, s1279, s1284, s1291, s1295, s1296, s1304, s1309, v414, A775, E175, H576, K290, K311, L72
\| aa529, s561, t169, t180, B573, B574
\~ aa516, a78, b10, b14, f696, l20, p422, s239, s287, s384, s467, s559, s645, s657, s661, s671, s687, s691, s752, s1240, s1257, s1261, s1273, s1277, s1287, s1303, s1307, s1351, s1352, s1353, s1405, s1406, E187, E207, H507, H522, H537, H580

A

\A aa252, aa531, aa552
\a s223, L1, aa243, aa532, aa543, *1057*
\AA s240, s428, s526, b410, *1062*
\aa s245, s422, s536, b410, *1063*
\abovedisplayshortskip I504, b385
\abovedisplayskip I497, I499, I501, I502, I503, I504, b384, *1048*
\accent .. s73, s393, s423, s479, s763, *1078*
\ActivateGenericHook .. h1452, h1458, *197*
\active a122, H406, H407, H506, H512, H521, H527, H536, H578, I241, I256, U1133, U1134, U1135, U1216, U1219, U1222, U1264, U1265, U1266, U1348, U1351, U1354, U1378, U1379, U1380, U1438, U1441, U1444, Y586, a333, b10, b11, a67, b424, b425, b433, b434, b446, b447, b451
\acute B516
add commands:
add_to_callback d711
\add_to_callback *47*
\addcontentsline O70, O80, O159, P16, *1047*
\AddEverypageHook *905*
\Adding *1023*
\addpenalty p270, J124, J170, J175, O50, Y338, Y1155, Y1321, *324*
\AddThispageHook *905*
\addtocontents O164, O171, O177, O180, *623*
\addtocounter *400*
\addtocounter t6, t18, *1035*
\AddToHook x152, H38, H39, H303, H304, H305, H306, R72, U1038, U1039, U1040, W558, W560, W570, W571, W572, W573, X188, X471, X494, h1461, h1591, *183*
\AddToHookNext W559, X495, h1463, h1589, *905*
\addtolength *408*
\addtolength u16, I499, I501
\addtoversion y20, y139
\addvspace p233, H336, J124, J171, J172, J176, J224, O50, *1034*
\adjdemerits b332
\AE s241, s398, s527, s768, s1127, s1437, s1441, aa584
\ae s246, s401, s537, s772, s1133, s1439, s1443, aa584
\afterassignment ... s212, s220, v328, I186, f256, f262, f305, b468, b471, *91*
\AfterEndEnvironment H299, *200*
\aftergoup *494*
\aftergroup v91, v342, x202, x268, z114, z121, z129, D64, H510, H525, H540, K148, Y606, Y607, Y664, Y665, *1043*
\AfterLastShipout W570
\afterpreamble *336*
\aleph B308
\allocationnumber n39, d52, d53, d54, d91, d213, L4, L9, X34, aa58, aa59, aa60, b37, b57, b69, b71, b143, b144, b145, b195, b196, b237, b238, b239, b252, b253, b254, b271, b277, b283, b284, b297, b298, b299, *304*
\allowbreak I40, f772, f773, f792, f794, b475
\Alph *400*
\Alph t140, *902*
\alph *400*
\alph t139
\alpha B268
\amalg B379
\AmSfont *447*
\and *747*
\and O14, O27
\angle B337
\approx B422
\arabic *400*
\arabic t79, t87, t136, N33, X348, *400*
\arccos I13
\arcsin I10
\arctan I16
\arg I26
\ArgumentSpecification g2060, g2067, g2083, g2090, *166*
array (env.) L168
\array L168
\arraycolsep I360, I361, I509, I510, L258, L338
\arrayrulewidth ... L324, L338, L346, L347, L359, L363, L366, L376, L378
\arraystretch L186, L187, L342
\Arrowvert B569
\arrowvert B567

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\asciispace H466, H468, H471, H474, H475, H494
\ast B232, B395
\asymp B449
\AtBeginDocument r125, r180, w737, R54, U1029, *198*
\atbegindocumenthook *336*
\AtBeginDvi X410, X446, Y86, *913*
\AtBeginEnvironment H299, *200*
\AtBeginShipout X451, X494, *904*
\AtBeginShipoutAddToBox X499, *903*
\AtBeginShipoutAddToBoxForeground X499, *903*
\AtBeginShipoutBox X492, *903*
\AtBeginShipoutDiscard X498, *904*
\AtBeginShipoutFirst . . . X454, X496, *904*
\AtBeginShipoutInit X493, *904*
\AtBeginShipoutNext . . . X452, X494, *1088*
\AtBeginShipoutOriginalShipout X507, *904*
\AtBeginShipoutUpperLeft X499, *903*
\AtBeginShipoutUpperLeftForeground X499, *903*
\AtEndAfterFileList W572
\AtEndDocument . . H69, U1029, W576, *201*
\AtEndDvi X461, X466, *901*
\AtEndEnvironment H299, *200*
\AtEndOfClass I434, U1029, *877*
\AtEndOfPackage U541, U560, U658, U669, U1029, V49, *877*
\AtEndPreamble *201*
\AtNextShipout *904*
\atopwithdelims I57, I58, I59
\attribute d79, *44*
\attributedef d79, d223
\attributezero d223
\AtVeryEndDocument W571
\AtVeryVeryEnd W573
\author *747*
\author O8, O24, O32

B

\b s233, s389, s475, s759, s1248, *1050*
\backslash B251, B590
\bar B520
\baselineskip x186, x187, x188, x190, x191, B510, I158, I159, I178, I184, I188, K299, K318, L198, M136, M314, M373, X220, X271, Y242, Y273, Y624, Y639, Y683, Y698, b403, b466, b502, *1037*
\baselinestretch v319, x120, x121, x166, x167, x184, x245, *1021*
\baselinstretch *1041*
\batchmode r656, r687, r688, y106, e89, e95, e105, aa604, aa625, *351*
\BeforeBeginEnvironment H299, *200*
\BeforeClearDocument W574
\begin r344, r396, x7, B4, B102, C4, H167, H168, I439, I451, M461, O14, O17, U679, V185, X392, Z3, aa489, aa493, g1213, g1319, h1480, i65, l246, l248, *200*
\begingroup *1062*
\belowdisplayshortskip I503, b387
\belowdisplayskip I502, b386
\beta B269
\bezier *711*
\bezier M682, M683, M805, M806, M821, M823
\bf *1029*
\bfdefault A15, A261, A267, A268, A269, A270, A310, A311, A312, A313, A322, A358, A382, A401, A442, A476, B92, B104, B106, B114, *519*
\bfseries A13, A14, A253, A254, A302, A307, A308, A349, A352, A353, A378, A380, A381, A474, A475, D19, G13, N36, N38, R40, X393, *523*
bfseries A420
bfseries/defaults A420
\bgroup b417, *1036*
\bibcite R7, R9, R10, *1055*
\bibdata R45, R49
\bibitem R3
\bibliography *786*
\bibliography R47
\bibliographystyle *786*
\bibliographystyle R52
\bibstyle R45, R57
\Big . B623, B626, B635, B637, I44, I45, I46
\big B624, B636, I41
\bigbreak f774, f795, b482
\bigcap B345
\bigcirc B392
\bigcup B346
\Bigg B630, B639, I50, I51, I52
\bigg B628, B638, I47, I48, I49
\Biggl I50
\biggl I47
\Biggm I51
\biggm I48
\Biggr I52
\biggr I49
\Bigl I44
\bigl I41
\Bigm I45

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\bigm I42
\bigodot B353
\bigoplus B352
\bigotimes B351
\Bigr I46
\bigr I43
\bigskip p400, b487
\bigskipamount . . . p402, p403, P391, b486
\bigsqcup B356
\bigtriangledown B361, B362
\bigtriangleup B360, B363
\biguplus B344
\bigvee B342
\bigwedge B343
\binoppenalty b323
\bmod I35
\boldmath q14, A613
bool commands:
\bool_gset_false:N S226, X15, X81, X90, h15
\bool_gset_true:N S221, X10, X120, X342, h10
\bool_if:NTF S232, V152, X21, X88, X363, g96, g107, g119, g123, g132, g134, g144, g153, g154, g157, g162, g164, g250, g394, g403, g405, g460, g474, g487, g537, g570, g614, g624, g657, g665, g670, g671, g679, g701, g714, g782, g828, g829, g883, g896, g913, g933, g1713, g1947, g2225, g2236, h21, h1041, h1050, i159, i163, i175, i297, *178*
\bool_lazy_and:nnTF X66, X112, X374, g653, h132, h1043, h1266
\bool_lazy_and_p:nn h1269
\bool_lazy_any:nTF g414
\bool_lazy_or:nnTF g69, h541
\bool_new:N . S217, V23, X6, X186, X201, g16, g18, g20, g31, g32, g34, g36, g39, g42, g43, g44, h6, h24
\bool_set_false:N V48, g53, g79, g188, g231, g381, g382, g383, g384, g385, g406, g468, g505, g519, g541, g542, g543, g558, g620, g663, g674, g675, g691, g692, g694, g698, g705, g833, g834, g1603, g2033, h1033
\bool_set_true:N V46, g58, g189, g220, g380, g404, g480, g493, g494, g666, g667, g721, g722, g728, g729, g735, g736, g850, g868, g1608, g2039, h1030
\bool_while_do:nn h837
\c_false_bool g1948, g2197, g2495, g2600, i140, i150, i288, *178*
\c_true_bool g1949, g2199, g2496, g2598, i145, *178*
bool internal commands:
\g__mark_debug_bool S217, S221, S226, S232
\BooleanFalse g1596, g1941, g2495
\BooleanTrue g1595, g1940, g2495
\bordermatrix I172
\bot B321
\botfigrule Y744, Y2361
\botmark T79, Y649, Y708, *791*
\bottomfraction P275, Y2330
\bowtie B482
\Box A726
\box *655*
box commands:
\box_dp:N X192
\box_gclear:N n47
\box_gset_to_last:N n75, n14
\box_ht:N X191, X300, *908*
\box_if_empty:NTF X78, X97
\box_if_horizontal:NTF . . X232, X284
\box_if_vertical:NTF S60, S284, S315, X206, X257
\box_move_up:nn X246, X300
\box_new:N n42, S43, X23, X25, X185, X202
\box_set_dp:Nn X219, X228, X245, X270, X281, X299, X330
\box_set_eq:NN . . . X148, X177, X182
\box_set_eq_drop:NN X93
\box_set_ht:Nn X218, X227, X244, X269, X280, X298, X329
\box_set_to_last:N S57
\box_set_wd:Nn X217, X243, X268, X297
\box_use:N X125, X223, X248, X276, X301, X331
\box_use_drop:N n44
\box_wd:N X193, X294, X302
box internal commands:
\l__mark_box S43, S53, S57, S60, S62, S64, S69, S76, *801*
\boxmaxdepth M475, M503, M533, M611, M628, Y488, Y508, Y548, Y717, Y726, Y766, b378
\brace I59
\braceld . . B553, B557, B558, B560, B562
\bracelu B555, B559, B561
\bracerd B554, B559, B561
\braceru B556, B558, B562
\bracevert B608
\brack I58
\break . . p115, f775, f796, b475, b480, *1055*
\breve B521

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\brokenpenalty v666, b328
\buildrel B469, I149
\bullet B381

C

\c s234, s335, s337, s339, s341, s343, s345, s347, s349, s351, s372, s374, s392, s459, s478, s606, s608, s633, s635, s648, s674, s701, s704, s705, s706, s707, s708, s709, s710, s711, s712, s762, s1250, s1264, s1290, s1347, s1348, s1367, s1368, s1371, s1372, s1377, s1378, s1389, s1390, s1397, s1398, s1401, s1402, E167, E196, *1058*
\cal A776
call commands:
call_callback d692
\call_callback *48*
callback commands:
callback_descriptions d822
callback.register d576
\callback_descriptions *48*
\cap B372
\capitalacute s839, E160, E161, E193, E690, E943
\capitalbreve s846, E162, E163, E194, E691, E950
\capitalcaron s845, E164, E165, E195, E692, E949
\capitalcedilla s832, E166, E167, E196, E693, E940
\capitalcircumflex s840, E168, E169, E197, E694, E944
\capitaldieresis s842, E170, E171, E198, E695, E946
\capitaldotaccent s848, E172, E173, E199, E696, E952
\capitalgrave s838, E174, E175, E200, E697, E942
\capitalhungarumlaut s843, E176, E177, E201, E698, E947
\capitalmacron s847, E178, E179, E202, E699, E951
\capitalnewtie s852, E190, E191, E203, E700, E1017, E1018, *585*
\capitalogonek s835, E180, E181, E204, E701, E941
\capitalring s844, E182, E183, E205, E702, E948
\capitaltie s850, E184, E185, E206, E703, E1013, E1014
\capitaltilde s841, E186, E187, E207, E704, E945
\caption P4
\cases I153, I154, I164, I166
\catcode *623*
\catcodetable d89, d109, *44*
\catcodetable@atletter *45*
\catcodetable@initex *45*
\catcodetable@latex *45*
\catcodetable@string *45*
\catcoding *1025*
\cdot B394
\cdotp B502, B508
\cdots B508
center (env.) H351
\center H351
\centering H351, H356, H357, H375, H377, H392, H394
\centerline K489
\changes A667, *75*
\chaptermark *795*
\char s391, s394, s430, s433, s444, s451, s477, s481, s486, s489, s491, s493, s733, s761, s764, s797, s804, s811, s834, s837, s866, s896, s1006, s1041, s1165, s1167, s1169, s1216, A626, A633, E631, E638, E640, E760, H466, H581, I238, M232, M282, M296, M304, M307, M448, M563, M568, M576, M580, M616, M617, M619, M632, M633, M636, M663, f737, f752, *1058*
char commands:
\char_generate:nn . e142, g1425, g1721
\char_set_catcode_active:N . . . g1972
\char_set_catcode_active:n . . . g2096
\char_set_catcode_escape:N i338
\char_set_catcode_group_begin:N i339
\char_set_catcode_group_end:N . . i340
\char_set_catcode_other:N g1710
\char_set_catcode_other:n g1714
\char_set_catcode_parameter:N . . i341
\char_set_catcode_parameter:n . g1715
\char_set_lccode:nn . . . g1977, g2106
\char_value_catcode:n i292
\chardef r52, r121, s18, v14, d22, d26, d38, d47, d48, d89, d157, d224, L4, L9, U1139, U1270, U1387, aa42, aa44, aa48, aa67, aa171, aa172, aa173, aa174, aa175, aa176, aa177, b10, b16, b17, b18, b19, b20, b58, b64, b66, b73, b79, b82, b84, b94, b96, b97, b98, b99, b108, b114, b115, b128, b130, b194, b253, b257, b259, b283, b298, a67, a73, a74, j2, b496, b497, b498, *1038*
\charsubdef aa353

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\charzero d224
\check B522
\CheckCommand f187, *1042*
\CheckEncodingSubset E16, E61, E109, E110, E111, E156, E158, E352, E621, E832, E882, E938, E939, E1007, E1124, E1127, E1141, *579*
\chi B288
\choose I57
\circ B391
\circle . . M450, M605, M807, M824, *1025*
\citation R11, R39, R67, R84
\cite *786*
\cite R12, *787*
\clap K493, *1079*
class/.../after *876*
class/.../before *876*
class/after *876*
class/before *876*
\ClassError l84
\ClassInfo l84
\ClassNote l136, *1086*
\ClassNoteNoLine l136
\ClassWarning l84
\ClassWarningNoLine l84
\cleaders B548, B551, b516
\cleardoublepage Y138
\ClearHookNext h1465, *185*
\ClearHookRule h1502, h1605, *189*
\clearpage r296, r323, r327, r358, r381, r384, r405, r423, H17, H72, H165, Y125, Y138, Y143, Y200, Y407, Y410, Y414, Y455, Y461, Y2207, Y2224, *342*
\cline L367
clist commands:
\clist_clear:N V30
\clist_gclear:N h836
\clist_gput_left:Nn h782
\clist_gput_right:Nn h784
\clist_if_empty:NTF h1060
\clist_map_inline:Nn V78, V90, V140
\clist_map_inline:nn V171, h572, h581
\clist_new:N V22, h86
\clist_put_right:Nn V21, V74, V82, V83, V94, V105
\clist_remove_all:Nn V95
\clist_use:Nn h1062
\clubpenalty r8, r25, r94, r151, v664, J128, J194, J196, O100, O106, O130, O135, b325, *303*
\clubsuit B331
cmd internal commands:
__cmd_add_arg:n g1361, g1372, g1377, g1378, g1412, g1500, g1507, g1582, g1595, g1596, g1669, g1727, g1734, g1747, g1747, g1752, *146*
__cmd_add_arg_spec:n g503, g517, g577, g651, g651, g686
__cmd_add_arg_spec_mandatory:n g549, g559, g565, g651, g677
__cmd_add_default: g743, g781, g798, g844, g847, g854, g864, g931, g940, *129*
__cmd_add_default:n g750, g790, g806, g844, g844, g861, g875, *129*
__cmd_add_default_E:nn g758, g844, g859, g909
__cmd_add_expandable_grabber:nn g888, g901, g912, g932, g942, g949, g949
__cmd_add_expandable_type_+:w g866
__cmd_add_expandable_type_D:w g871, g871
__cmd_add_expandable_type_D_-aux:NN g871, g877, g894
__cmd_add_expandable_type_D_-aux:NNN g871, g878, g881
__cmd_add_expandable_type_D_-aux:NNNn . . . g871, g872, g873, g937
__cmd_add_expandable_type_E:w g907, g907
__cmd_add_expandable_type_E_-aux:n g907, g911, g923
__cmd_add_expandable_type_m:w g929, g929
__cmd_add_expandable_type_R:w g936, g936
__cmd_add_expandable_type_t:w g938, g938
__cmd_add_grabber:N g744, g751, g764, g783, g791, g799, g807, g821, g821, *131*
__cmd_add_type_!:w g725
__cmd_add_type_+:w g718
__cmd_add_type_>:w g732
__cmd_add_type_b:w g740, g740
__cmd_add_type_D:w g747, g747
__cmd_add_type_E:w g755, g755
__cmd_add_type_m:w g779, g779
__cmd_add_type_R:w g787, g787
__cmd_add_type_t:w g795, g795
__cmd_add_type_v:w g803, g803

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__cmd_allowed_token_check:N ... g501, g513, g534, g555, g593, g593
\l__cmd_arg_spec_tl ... g11, g88, g379, g466, g535, g668, *108*
\l__cmd_args_i_tl ... g13, g259, g265, g270, g271, g273, *108*
\l__cmd_args_ii_tl ... g14, g269, g271, g273, g311, g316, g323, *108*
__cmd_args_process: ... g249, g309, g309, *129*
__cmd_args_process_aux:n ... g309, g322, g326
__cmd_args_process_loop:nn ... g309, g315, g318
\l__cmd_args_tl ... g12, g212, g237, g254, g259, g265, g284, g313, g316, g329, g330, g1321, g1322, g1327, g1330, g1478, g1512, g1749, *146*
__cmd_bad_arg_spec:wn ... g436, g441, g450, g459, g473, g486, g500, g510, g511, g516, g527, g533, g554, g645, g645
__cmd_bad_def:wn ... g392, g400, g429, g464, g478, g491, g574, g582, g590, g609, g618, g630, g645, g650, g661, g683, *137*
__cmd_bool_reverse:N ... g1945, g1945, g2631
__cmd_break_point:n ... g91, g93, g93, g645, g650, g998, g1005, g1176
__cmd_cant_copy:nwn ... g995, g1005, g1005, g1082, g1145, g1174
__cmd_check_definable:nNTF ... g2093, g2093, g2499, g2512, g2525, g2530, g2555, g2568, g2581, g2589, g2638, g2644
__cmd_check_definable_aux:nN ... g2093, g2094, g2097, *168*
__cmd_check_end:n g1141, g1143, g1149
__cmd_check_end:Nn ... g1128, g1129, g1141, g1141, g1220
__cmd_check_end:w g1141, g1151, g1154
__cmd_chk_if_free_cs:N ... g2065, g2648, g2649
__cmd_cmd_if_xparse:NTF ... *1085*
__cmd_cmd_if_xparse_aux:N ... g2160
__cmd_cmd_type_cases:Nnnnn ... g2160
__cmd_cmd_type_cases:NnnnnTF ... g990, g1169, g2160, g2182, *142*
__cmd_copy:NN ... g983, g985, g985, g1019, g1159, *138*
__cmd_copy_command:nnNN ... g991, g1020, g1020, *138*
__cmd_copy_command:NnNNnnnn ... g1020, g1025, g1027, *138*
__cmd_copy_environment:nnNN ... g993, g1115, g1115
__cmd_copy_environment:Nnnnnnn ... g1115, g1121, g1124
__cmd_copy_environment_end:nnNN ... g994, g1126, g1126
__cmd_copy_environment_end_aux:nnNN ... g1126, g1130, g1133
__cmd_copy_expandable:nnN ... g1060, g1065, g1068, g1095, g1105, g1111, g1113
__cmd_copy_expandable:nnNN ... g992, g1033, g1033
__cmd_copy_expandable:NnNNNNnnn ... g1033, g1041, g1043, *138*
__cmd_copy_expandable_signature:NnNNNNnnn ... g1039, g1060, g1060, *138*
__cmd_copy_grabber_⟨*type*⟩:w ... *139*
__cmd_copy_grabber_D:w ... g1085, g1085, g1098, g1099
__cmd_copy_grabber_D_alt:w ... g1085, g1097, g1100
__cmd_copy_grabber_E:w ... g1085, g1101, g1107
__cmd_copy_grabber_E_long:w ... g1085, g1107
__cmd_copy_grabber_m:w ... g1085, g1113, g1114
__cmd_copy_grabber_m_long:w ... g1085, g1114
__cmd_copy_grabber_R:w g1085, g1099
__cmd_copy_grabber_R_alt:w ... g1085, g1100
__cmd_copy_grabber_t:w g1085, g1108
__cmd_copy_parse_grabber:w ... g1060, g1072, g1076, *139*
\l__cmd_current_arg_int ... g15, g25, g104, g133, g140, g202, g283, g287, g292, g293, g377, g388, g411, g467, g481, g495, g520, g690, g849, g856, g1063, g1071, g1089, g1093, g1094, g1104, g1227, g1293, g1302, *129*
__cmd_declare_cmd:Nnn ... g51, g51, g2507, g2515, g2526, g2531
__cmd_declare_cmd_aux:Nnn ... g51, g54, g59, g61
__cmd_declare_cmd_code:Nnn ... g89, g94, g94
__cmd_declare_cmd_code_aux:Nnn ... g94, g98, g100

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__cmd_declare_cmd_code_expandable:Nnn g94, g97, g128
__cmd_declare_cmd_internal:Nnnn g51, g80, g82, g195, *115*
__cmd_declare_env:nnnn g174, g174, g2540, g2546, g2550, g2552
__cmd_declare_env_internal:nnnn g174, g190, g193
__cmd_declare_expandable_-cmd:Nnn g51, g56, g2563, g2571, g2584, g2590
__cmd_defaults: g248, g256, g256
__cmd_defaults_aux: g256, g260, g261, g262, g267
\l__cmd_defaults_bool g16, g119, g134, g157, g694, g850, *109*
__cmd_defaults_def: g256, g258, g280
__cmd_defaults_def:nn g256, g285, g290
__cmd_defaults_def:nnn g256, g293, g295
__cmd_defaults_error:w g256, g263, g275
\l__cmd_defaults_tl g17, g120, g141, g240, g248, g284, g695, g851, g857, *109*
__cmd_delimiter_check:nnn g548, g557, g634, g634
__cmd_end_expandable:NNw g336, g338, g338
__cmd_end_expandable_aux:nNNNN g338, g341, g342
__cmd_end_expandable_aux:w g338, g339, g340
__cmd_end_expandable_defaults:nnnNNn g338, g345, g354, g363, g373, g374, *119*
__cmd_end_expandable_defaults:nnw g338, g362, g366
__cmd_end_expandable_defaults:nw g338, g369, g370, g372
\l__cmd_environment_bool . . . g18, g79, g107, g189, g220, g231, g250, g405, g570, g2033, g2039, g2236, *109*
__cmd_environment_or_command: g278, g391, g423, g427, g477, g490, g573, g580, g589, g604, g648, g682, g1580, g1724, g1731, g2049, g2053, g2234, g2234
\l__cmd_environment_str g19, g110, g176, g177, g178, g179, g182, g186, g191, g219, g222, g223, g251, g2040, g2042, g2237, *109*
\l__cmd_expandable_aux_name_tl . . g21, g22, g886, g890, g899, g903, *109*
\l__cmd_expandable_bool g20, g53, g58, g132, g144, g188, g394, g403, g460, g614, g624, g657, g701, *109*
__cmd_expandable_grab_D:nnNNNwNN g1753, g1777, g1783
__cmd_expandable_grab_D:NNNwNNn g1753, g1754, g1757
__cmd_expandable_grab_D:NNNwNNnnn g1753, g1768, g1775, g1801, g1896, *159*
__cmd_expandable_grab_D:Nw g1753, g1779, g1782
__cmd_expandable_grab_D:w g1753, g1753
__cmd_expandable_grab_D_-alt:NNwn g1820, g1827, g1923
__cmd_expandable_grab_D_-alt:NNwNNn . . . g1805, g1806, g1809
__cmd_expandable_grab_D_alt:Nwn g1805
__cmd_expandable_grab_D_alt:w g1805, g1805
__cmd_expandable_grab_E:w g1840, g1840
__cmd_expandable_grab_E_aux:w g1840, g1841, g1843, g1844, g1872
__cmd_expandable_grab_E_end:nnw g1840, g1856, g1873
__cmd_expandable_grab_E_-find:nnw g1840, g1870, g1871
__cmd_expandable_grab_E_find:w g1840, g1861, g1869
__cmd_expandable_grab_E_long:w g1840, g1842
__cmd_expandable_grab_E_-loop:nnnNNw g1840, g1848, g1852, g1863
__cmd_expandable_grab_E_-test:nnw g1840, g1845, g1846
__cmd_expandable_grab_m:w g1875, g1875, *140*
__cmd_expandable_grab_m_aux:wNn g1875, g1876, g1878, g1879
__cmd_expandable_grab_m_long:w g1875, g1877
__cmd_expandable_grab_R:w g1881, g1881
__cmd_expandable_grab_R_alt:w g1908, g1908
__cmd_expandable_grab_R_alt_-aux:NNwNNn . . . g1908, g1909, g1912
__cmd_expandable_grab_R_-aux:NNNwNNn . . . g1881, g1882, g1885
__cmd_expandable_grab_t:w g1935, g1935

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__cmd_expandable_grab_t_-aux:NNwn g1935, g1936, g1937
__cmd_flush_m_args: g701, g720, g727, g734, g742, g749, g757, g789, g797, g805, g810, g810, *129*
\l__cmd_fn_code_tl g29, g239, g254, *109*
\l__cmd_fn_tl g28, g85, g238, g1323, g1366, g1390, g1396, g1406, g1416, g1425, g1430, g1434, g1465, g1491, g1499, g1501, g1506, g1508, g1519, g1520, g1525, g1526, g1531, g1532, g1537, g1538, g1543, g1544, g1549, g1550, g1555, g1556, g1561, g1562, g1592, g1598, g2034, g2241, *146*
\l__cmd_function_tl g24, g30, g84, g86, g103, g114, g115, g131, g139, g149, g152, g156, g158, g166, g172, g399, g463, g617, g629, g660, *110*
__cmd_get_arg_spec:N g2068, g2068, g2639
__cmd_get_arg_spec:n g2068, g2073, g2641
__cmd_get_arg_spec:NTF .. g2056, g2056, g2070, g2075, g2082, g2088
__cmd_get_arg_spec_error:N g2031, g2031, g2071, g2084
__cmd_get_arg_spec_error:n g2031, g2037, g2078, g2091
__cmd_get_arg_spec_error_aux:n g2031, g2035, g2041, g2044
__cmd_get_grabber:NN g925, g941, g954, g954, *135*
__cmd_get_grabber_auxi:NN g954, g957, g960, g968
__cmd_get_grabber_auxii:NN g954, g975, g978
__cmd_grab_b:w g1309, g1309
__cmd_grab_b_aux:NNw ... g1309, g1310, g1312, g1314, g1316, g1317
__cmd_grab_b_end:Nw g1309, g1320, g1325
__cmd_grab_b_long:w .. g1309, g1311
__cmd_grab_b_long_obey_spaces:w g1309, g1315
__cmd_grab_b_obey_spaces:w g1309, g1313
__cmd_grab_D:w g1336, g1336
__cmd_grab_D_aux:NNnN g1319, g1356, g1358, g1363, g1575
__cmd_grab_D_aux:NNnNN .. g1338, g1343, g1348, g1353, g1356, g1356
__cmd_grab_D_call:Nw g1360, g1420, g1420, g1577, *147*
__cmd_grab_D_long:w .. g1336, g1341
__cmd_grab_D_long_obey_spaces:w g1336, g1351
__cmd_grab_D_nested:NNnN g1369, g1383, g1386
__cmd_grab_D_nested:w g1383, g1401, g1418
__cmd_grab_D_obey_spaces:w g1336, g1346
__cmd_grab_E:nnNN g1439, g1441, g1447, g1453, g1459, g1463
__cmd_grab_E:w g1439, g1439
__cmd_grab_E_finalise: g1439, g1472, g1488, g1495
__cmd_grab_E_long:w .. g1439, g1445
__cmd_grab_E_long_obey_spaces:w g1439, g1457
__cmd_grab_E_loop:NnN g1439, g1468, g1483, g1485, g1492
__cmd_grab_E_obey_spaces:w g1439, g1451
\l__cmd_grab_expandably_bool g31, g96, g380, g404, g406, g468, g505, g519, g541, g558, g620, g663, g714, *110*
__cmd_grab_m:w g1496, g1496
__cmd_grab_m_1:w g1510
__cmd_grab_m_2:w g1510
__cmd_grab_m_3:w g1510
__cmd_grab_m_4:w g1510
__cmd_grab_m_5:w g1510
__cmd_grab_m_6:w g1510
__cmd_grab_m_7:w g1510
__cmd_grab_m_8:w g1510
__cmd_grab_m_9:w g1510
__cmd_grab_m_aux:Nnnnnnnnn g1510, g1510, g1519, g1525, g1531, g1537, g1543, g1549, g1555, g1561
__cmd_grab_m_long:w .. g1496, g1503
__cmd_grab_R:w g1569, g1569
__cmd_grab_R_aux:NNnN g1569, g1570, g1572, g1573
__cmd_grab_R_long:w .. g1569, g1571
__cmd_grab_t:w g1585, g1585
__cmd_grab_t_aux:NNw g1585, g1586, g1588, g1589
__cmd_grab_t_obey_spaces:w g1585, g1587
__cmd_grab_v:w g1601, g1601
__cmd_grab_v_aux:w g1601, g1604, g1609, g1611, *155*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__cmd_grab_v_aux_abort:n g1627, g1645, g1651, g1664, g1683, g1706, g1708, g1717, *154*
__cmd_grab_v_aux_catcodes: g1642, g1674, g1708, g1708, *153*
__cmd_grab_v_aux_loop:N g1637, g1643, g1647, g1661
__cmd_grab_v_aux_loop:NN g1637, g1650, g1653
__cmd_grab_v_aux_loop_end: g1637, g1658, g1666, g1697
__cmd_grab_v_aux_put:N g1641, g1660, g1676, g1694, g1702, g1737, g1737
__cmd_grab_v_aux_test:N g1626, g1637, g1637
__cmd_grab_v_bgroup: g1622, g1672, g1672
__cmd_grab_v_bgroup_loop: g1672, g1677, g1679, g1695, g1703
__cmd_grab_v_bgroup_loop:N g1672, g1682, g1685
__cmd_grab_v_group_end: g1601, g1631, g1668, g1719, *154*
__cmd_grab_v_long:w .. g1601, g1606
__cmd_grab_v_token_if_char:NTF . g1639, g1655, g1687, g1745, g1745, *154*
\g__cmd_grabber_int g27, g967, g971, *109*
\c__cmd_ignore_def_tl ... g2232, g2250, g2257, g2271, g2292, g2321, g2328, g2335, g2343, g2351, g2360, g2367, g2374, g2381, g2393, g2400, *171*
\l__cmd_last_delimiters_tl g33, g378, g396, g504, g518, g540, g576, g626, g636, g685, *110*
\l__cmd_long_bool g34, g382, g474, g480, g543, g654, g665, g670, g674, g691, g721, g828, g833, g868, g883, g896, g913, g933, g1603, g1608, g1713, *134*
\l__cmd_m_args_int g35, g693, g784, g812, g815, g817, g819, *110*
\l__cmd_nesting_a_tl g1383
\l__cmd_nesting_b_tl g1383
__cmd_normalize_arg_spec:n g87, g375, g375
__cmd_normalize_arg_spec_loop:n g375, g386, g408, g469, g482, g496, g506, g521, g544, g550, g560, g566
__cmd_normalize_check_gv:N g564, g612, g612
__cmd_normalize_check_lu:N g612, g622
__cmd_normalize_E_unique_-check:w g498, g514, g523, g528
__cmd_normalize_type_!:w g457
__cmd_normalize_type_+:w g457
__cmd_normalize_type_>:w g457
__cmd_normalize_type_b:w g568, g568
__cmd_normalize_type_D:w g437, g445, g447, g498, g498
__cmd_normalize_type_d:w g432, g434
__cmd_normalize_type_E:w g442, g498, g508
__cmd_normalize_type_e:w g432, g439
__cmd_normalize_type_m:w g546, g546
__cmd_normalize_type_O:w g432, g446
__cmd_normalize_type_o:w g432, g444
__cmd_normalize_type_R:w g451, g546, g552
__cmd_normalize_type_r:w g432, g448
__cmd_normalize_type_s:w g432, g453
__cmd_normalize_type_t:w g454, g498, g531
__cmd_normalize_type_v:w g546, g562
\l__cmd_obey_spaces_bool g32, g381, g487, g493, g537, g542, g671, g675, g692, g728, g829, g834, *110*
__cmd_peek_cs_check_equal:NNN .. g2196, g2210, g2216
__cmd_peek_meaning:NTF g2187, g2196, g2196
__cmd_peek_meaning_aux:NNTF ... g2196, g2197, g2199, g2200
__cmd_peek_meaning_remove:NTF .. g1349, g1354, g1455, g1461, g1588, g2189, g2196, g2198
__cmd_peek_nonspace:NTF g2186, g2186
__cmd_peek_nonspace_aux:nNNTF .. g2186, g2187, g2189, g2190, g2193
__cmd_peek_nonspace_remove:NTF . g1339, g1344, g1443, g1449, g1576, g1586, g2186, g2188
__cmd_peek_true_remove:NNw .. g2196
__cmd_peek_true_remove:Nw g2207, g2211, g2219, g2223
\l__cmd_prefixed_bool g36, g705, g722, g729, g735, g782, *110*
__cmd_prepare_signature:N g688, g700, g703, g745, g753, g766, g785, g793, g801, g808, g869, g879, g921, g934, g947, *129*
__cmd_prepare_signature:n g88, g688, g688

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__cmd_prepare_signature_-bypass:N g688, g706, g708, g723, g730, g738, *129*
\l__cmd_process_all_tl . g37, g124, g241, g249, g314, g696, g816, g835, *110*
\l__cmd_process_one_tl g38, g697, g737, g762, g771, g839, g842, *110*
\l__cmd_process_some_bool g39, g123, g698, g736, *110*
__cmd_put_arg_expandable:nw g1789, g1794, g1795, g1830, g1835, g1836, g1943, g1943, g1944
__cmd_replicate_processor:nn g761, g768, g768
__cmd_run_code: g243, g246, g246, g1317, g1325, g1333, g1336, g1341, g1346, g1351, g1439, g1445, g1451, g1457, g1481, g1496, g1503, g1514, g1516, g1522, g1528, g1534, g1540, g1546, g1552, g1558, g1569, g1571, g1589, g1611, g1750, *116*
\l__cmd_saved_args_tl g40, g1321, g1329, *111*
__cmd_set_environment_end:n g207, g251
__cmd_set_eq_if_exist:NN g985, g1002, g1004, g1023, g1036, g1037, g1038, g1118
__cmd_show:N g1162, g1164, g1164, g1224, g1306, *143*
__cmd_show_arg_spec:N g2080, g2080, g2645
__cmd_show_arg_spec:n g2080, g2086, g2647
__cmd_show_command:N g1170, g1180, g1180
__cmd_show_command:NnNNwN g1180, g1181, g1182
__cmd_show_command_aux:nNNn . . . g1180, g1183, g1187, g1188, g1212, *142*
__cmd_show_delim:Nw . . g1254, g1254
__cmd_show_delims:Nw . g1254, g1256
__cmd_show_delims_opt:Nw g1254, g1258
__cmd_show_E:Nw g1254, g1273
__cmd_show_e:Nw g1254, g1262
__cmd_show_environment:N g1172, g1180, g1198, g1221
__cmd_show_environment:Nnnw g1200, g1208
__cmd_show_environment_end:N g1173, g1218
__cmd_show_expandable:N g1171, g1180, g1184
__cmd_show_expandable:NnNNNNnN g1180, g1185, g1186
__cmd_show_opt:Nw g1254, g1260
__cmd_show_prefix:Nw . g1254, g1286
__cmd_show_processor:Nw g1254, g1288
\c__cmd_show_type_!_tl g1248
\c__cmd_show_type_+_tl g1248
\c__cmd_show_type_>_tl g1248
\c__cmd_show_type_D_tl g1248
\c__cmd_show_type_d_tl g1248
\c__cmd_show_type_E_tl g1248
\c__cmd_show_type_e_tl g1248
\c__cmd_show_type_O_tl g1248
\c__cmd_show_type_R_tl g1248
\c__cmd_show_type_r_tl g1248
\c__cmd_show_type_t_tl g1248
\l__cmd_signature_tl g41, g117, g160, g699, g752, g765, g792, g800, g814, g823, g951, g1320, g1365, g1471, g1481, g1498, g1505, g1514, g1518, g1524, g1530, g1536, g1542, g1548, g1554, g1560, g1591, g1613, g1750, *146*
__cmd_single_token_check:n g501, g502, g512, g534, g555, g556, g584, g584
\l__cmd_some_long_bool g43, g154, g162, g384, g655, g666, *111*
\l__cmd_some_obey_spaces_bool g42, g383, g494, g679, *111*
\l__cmd_some_short_bool g44, g153, g164, g385, g667, *120*
__cmd_split_add_item:n g1287, g1290, g1289, g1295, *145*
__cmd_split_argument:nnn g1986, g1986, g2632
__cmd_split_argument_aux:n g1986, g2002, g2021
__cmd_split_argument_aux:nnnn g1986, g1989, g1993
__cmd_split_argument_aux:wn g1986, g2022, g2023
__cmd_split_end_item:n g1246, g1255, g1257, g1259, g1261, g1267, g1278, g1290, g1297, *145*
__cmd_split_list:nn g1951, g1953, g1988, g2633
__cmd_split_list_multi:nn g1951, g1958, g1961, g1963, g1970, g1983

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\l__cmd_split_list_seq g1951, g1965, g1967, *164*
__cmd_split_list_single:Nn g1951, g1959, g1973
\l__cmd_split_list_tl g1952, g1975, g1981, g1983, *164*
__cmd_split_signature:n g1190, g1225, g1225, *142*
__cmd_split_signature_loop:Nw g1230, g1232, g1232, g1246, g1255, g1257, g1259, g1261, g1269, g1282, g1287, g1289
__cmd_split_start_item: g1235, g1266, g1277, g1290, g1290, *144*
__cmd_start:nNNnnn g113, g215, g226, g2168, *130*
__cmd_start_aux:NNnnnn g221, g232, g235, g235, g245
__cmd_start_env:nnnnn g109, g215, g215, g2170, *169*
__cmd_start_expandable:nNNNNn g147, g333, g333, g2169, *113*
__cmd_tl_mapthread_function:NNN g284, g312, g2134, g2134
__cmd_tl_mapthread_function:nnN g360, g1280, g2134, g2147, *145*
__cmd_tl_mapthread_loop:w g2134, g2137, g2149, g2153, g2158
__cmd_tmp:w g45, g48, g270, g286, g328, g330, g432, g456, g956, g962, g980, g1147, g1157, g1248, g1251, g1253, g1271, g1275, g1281, g1285, g1755, g1774, g1807, g1826, g1883, g1907, g1910, g1934, g2228, *117*
\l__cmd_tmp_prop g45, g1467, g1470, g1476, *111*
\l__cmd_tmpa_tl g46, g282, g287, g297, g925, g927, g941, g944, g1058, g1064, g1079, g1087, g1103, g1110, g1128, g1131, g1194, g1220, g1221, g1228, g1299, g1404, g1407, g2202, g2227, g2230, *142*
\l__cmd_tmpb_tl . g47, g910, g915, g926, g1129, g1131, g1229, g1235, g1292, g1296, g1300, g1301, g1476, g1477, g1479, g2203, g2214, g2220, *144*
__cmd_token_if_cs:NTF g1428, g2125, g2125, g2209, *125*
__cmd_trim_spaces:n g2029, g2029, g2634
\l__cmd_v_arg_tl ... g1600, g1616, g1635, g1669, g1725, g1732, g1739, *153*
\l__cmd_v_nesting_int g1671, g1675, g1691, g1692, g1701, *155*
\colon B503
\columnsep r27, r96, r153, Y81, Y202
\columnseprule Y82, Y2262, Y2296
\columnwidth r24, r27, r28, r30, r93, r96, r97, r99, r150, r153, r154, r157, K346, K377, K395, K412, P99, P168, P470, P489, P507, Y80, Y144, Y145, Y146, Y201, Y202, Y203, Y204, Y205, Y1845, Y1847, Y2260, Y2264, Y2292, Y2298
\cong B457
\contentsline O164, O171, O177, O184, *757*
\coprod B341
\copyright s285, s316, A649, *1063*
\cos I12
\cosh I14
\cot I18
\coth I19
\countdef d75, d85, d174, d190, d198, d206, d225, F3, aa75, b37, b38, b39, b41, b51, b90, a69
\counterwithin *400*
\counterwithin t75, *1086*
\counterwithout *400*
\counterwithout t75, *1086*
\CountZero d225
\cr s500, s506, s516, s522, E101, E105, E930, E934, I175, I179, I365, I411, I513, L192, L203, L210, L219, L224, L230, L377, M141, M143, M148, M154, b413
\crcr s327, s362, s363, s390, s394, s397, s476, s480, s484, s486, s489, s732, s760, s764, s767, s834, s837, s895, s1253, A651, B337, B338, B340, B459, B462, B466, B530, B531, B532, B533, B534, B535, B537, B538, B539, B540, B541, B543, E106, E935, I155, I157, I158, I159, I175, I177, I178, I179, I197, I198, L171, L172, M141, b503
create commands:
create_callback d667
\create_callback *48*
\CS *80*
\cs h1472, h1473, h1475
cs commands:
\cs:w z187, z190, V116, W211, W225, W237, W238, g1431, g2173, h219, h741, h775, h776, h828, h848, h851, h867, h868, h891, h892, h893, h900, h907, h1159, h1165, h1178, h1188, h1224, h1254, h1299, h1329, *214*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\cs_argument_spec:N e139, g2164, i158, i287, *270*
\cs_end: . z187, z190, V116, W211, W225, W237, W238, g1431, g2175, h219, h448, h744, h775, h776, h828, h848, h851, h867, h868, h882, h892, h893, h900, h907, h1100, h1159, h1164, h1165, h1178, h1184, h1197, h1224, h1254, h1299, h1329
\cs_generate_from_arg_count:NNnn g102, g130, g138, g200, g286, g289, g328
\cs_generate_variant:Nn V21, V113, W462, W470, g245, g289, g1004, g1752, g1944, g1970, h35, h36, h37, h44, h45, h52, h53, h54, h57, h63, h67, h870, i19
\cs_gset:Npn z192, W242, X171
\cs_gset:Npx W213
\cs_gset_eq:NN z184, z198, e136, e137, e138, e139, e140, e141, e142, X52, X150, X164, X165, X170, X179, X183, X319, X385, g2066, g2648, h451, h748, h761, h762, h1151, i55, i384
\cs_gset_nopar:Npn V28
\cs_gset_nopar:Npx h47, h49, h51
\cs_gset_protected:Npn h1485
\cs_gset_protected:Npx S231, X20, h20
\cs_if_eq:NNTF V61, V63, V101, g962, g1487
\cs_if_exist:N *871*
\cs_if_exist:NTF V103, W93, W439, W443, g63, g179, g965, g1003, g2035, g2042, g2501, g2514, g2526, g2535, g2538, g2545, g2550, g2557, g2570, g2583, h1309, h1317, i72, i80, *893*
\cs_if_exist_p:N g70, g71
\cs_if_exist_use:NTF e181, X311, X312, X316, X317, g412, g1081, h661, h686
\cs_if_free:NTF V70
\cs_new:Npn ... n43, n46, n71, n83, e179, S160, S166, S167, S168, V110, V112, W30, W38, W44, W57, W95, W100, W105, W112, W127, W234, W240, W412, W414, W416, W419, W423, W437, W453, W463, W579, X54, X59, X77, X140, X145, X161, X176, X181, X187, X190, X204, X255, X308, X321, X335, X338, X348, X390, X509, X510, X511, g333, g338, g340, g342, g354, g366, g372, g1027, g1043, g1124, g1149, g1154, g1418, g1753, g1757, g1775, g1782, g1783, g1805, g1809, g1827, g1840, g1842, g1844, g1846, g1852, g1869, g1871, g1873, g1875, g1877, g1879, g1881, g1885, g1908, g1912, g1935, g1937, g1943, g2021, g2023, g2134, g2147, g2153, g2234, g2592, g2609, g2610, g2614, g2615, g2616, h39, h170, h176, h189, h199, h200, h202, h216, h222, h559, h561, h563, h723, h739, h793, h794, h871, h872, h1076, h1162, h1182, h1190, h1204, h1307, h1315, h1327, h1491, h1492, i224, i234, i244, i246, i248, i259, i278, i279, i282, i409
\cs_new_eq:NN n93, e159, e160, e161, e162, e178, S218, S234, S235, S271, S273, S368, S370, V8, W252, W253, W506, W508, W510, W512, W514, W516, W518, W520, W522, W524, X7, X151, X345, X347, X409, X412, X413, X508, g48, g93, g1099, g1100, g1107, g1114, g2065, g2495, g2496, g2611, g2612, g2613, g2619, g2620, g2621, g2631, g2632, g2633, g2634, g2635, g2641, g2647, h7, h23, h34, h64, h702, h708, h746, h946, h947, h948, h949, h950, h951, h1197, h1504, h1505, h1575, h1577, i12, i13, i335
\cs_new_protected:Npn n51, z179, z210, S7, S17, S46, S112, S123, S131, S134, S219, S224, S229, S237, S265, S283, S314, V24, V26, V59, V68, V88, V99, V114, V118, V136, V150, W49, W62, W70, W79, W208, W222, W393, W398, W421, W544, X8, X13, X18, X341, X471, aa569, g51, g56, g61, g82, g94, g100, g128, g174, g193, g207, g215, g235, g246, g256, g267, g275, g280, g290, g295, g309, g318, g326, g375, g408, g434, g439, g444, g446, g448, g453, g457, g471, g484, g498, g508, g523, g531, g546, g552, g562, g568, g584, g593, g612, g622, g634, g645, g650, g651, g677, g688, g703, g708, g718, g725, g732, g740, g747, g755, g768, g779, g787, g795, g803, g810, g821, g844, g854, g859, g866, g871, g873, g881, g894, g907, g923, g929, g936, g938, g949, g954, g960, g978, g985, g1002, g1005, g1020,

g1033, g1060, g1068, g1076, g1085, g1097, g1101, g1108, g1113, g1115, g1126, g1133, g1141, g1164, g1180, g1182, g1184, g1186, g1188, g1198, g1208, g1218, g1225, g1232, g1254, g1256, g1258, g1260, g1262, g1273, g1286, g1288, g1290, g1295, g1297, g1309, g1311, g1313, g1315, g1317, g1325, g1336, g1341, g1346, g1351, g1356, g1363, g1386, g1439, g1445, g1451, g1457, g1463, g1485, g1495, g1496, g1503, g1516, g1522, g1528, g1534, g1540, g1546, g1552, g1558, g1569, g1571, g1573, g1585, g1587, g1589, g1601, g1606, g1611, g1631, g1637, g1647, g1653, g1666, g1679, g1685, g1708, g1717, g1737, g1745, g1747, g1945, g1953, g1963, g1973, g1986, g1993, g2029, g2031, g2037, g2044, g2056, g2068, g2073, g2080, g2086, g2093, g2097, g2125, g2160, g2180, g2186, g2188, g2190, g2196, g2198, g2200, g2216, g2223, g2497, g2510, g2523, g2528, g2533, g2543, g2549, g2551, g2553, g2566, g2579, g2587, g2636, g2642, h8, h13, h18, h40, h42, h46, h48, h50, h55, h58, h65, h68, h70, h79, h91, h100, h102, h107, h109, h123, h125, h142, h147, h149, h167, h223, h232, h237, h245, h269, h271, h287, h295, h305, h314, h323, h325, h342, h366, h373, h380, h390, h395, h400, h409, h443, h445, h453, h455, h458, h460, h602, h604, h637, h644, h675, h697, h703, h709, h714, h717, h720, h721, h747, h764, h800, h873, h880, h889, h896, h903, h910, h918, h924, h935, h952, h959, h971, h976, h981, h983, h985, h1078, h1093, h1098, h1107, h1123, h1125, h1135, h1140, h1148, h1150, h1154, h1168, h1173, h1195, h1210, h1219, h1228, h1233, h1240, h1242, h1493, h1494, h1495, h1496, h1506, h1513, h1520, h1527, h1534, h1536, h1538, h1545, h1552, h1559, h1566, i17, i22, i24, i33, i35, i45, i53, i62, i76, i96, i116, i129, i134, i143, i148, i153, i217, i284, i319, i336, i362, *921*

`\cs_new_protected:Npx` g226, g1564, g1672

`\cs_new_protected_nopar:Npn` g1420, g1510

`\cs_prefix_spec:N` e138, i204

`\cs_replacement_spec:N` e140, g1195, g1204

`\cs_set:Npn` g140, g201, g286, g328, g956, i196, i351, i368, *146*

`\cs_set:Npx` W211, W225, g169, g884, g897

`\cs_set_eq:NN` . n49, n50, n94, n95, n96, n98, n99, n100, n134, n135, n136, n139, z201, S161, S162, S163, V49, X24, X44, X83, X95, X124, X131, X415, X417, X419, X421, X423, g203, g204, g980, g1003, g1022, g1035, g1092, g1117, g1122, g1137, g1139, g1519, g1525, g1531, g1537, g1543, g1549, g1555, g1561, g1710, g2228, h781, h782, h783, h784, h973, h978, i168, i169, i189, i190, i195, i347, i348, i364, i365, i422

`\cs_set_nopar:Npn` *146*

`\cs_set_nopar:Npx` g145, g166, g171, g198, g209, g885, g898, g1040, g1135, h41, h43

`\cs_set_protected:Npn` V5, V29, V43, V124, X46, X134, X410, g104, g432, g1147, g1248, g1271, g1275, g1312, g1316, g1343, g1353, g1448, g1460, g1472, g1506, g1572, g1592, g1755, g1807, g1883, g1910, h258, h1080, h1110, i170

`\cs_set_protected_nopar:Npn` g1310, g1314, g1338, g1348, g1442, g1454, g1499, g1570

`\cs_set_protected_nopar:Npx` g105, g145, g1024, g1120

`\cs_to_str:N` e136, g70, g71, g84, g996, g998, g1176, g1203, g1205, g1220, g1431, g2175, i111, i132, i146, i151, *110*

`\cs_undefine:N` W227, g2625, g2626, g2627, g2649, h128, h722, i58

cs\check@icr commands:

`\cs_gset_eq:NN` *75*

`\csc` I21

`\csname` *1040*

`\csname\endcsname` *888*

`\cup` B373

`\CurrentFile` U848, W3, W67, W84, W166, W171, W174, W378, W382, W552, W553, *885*

`\CurrentFilePath` W3, W67, W83, W165, W379, W382, *882*

`\CurrentFilePathUsed` W3, W66, W81, W163, W376, W379, *876*

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

\CurrentFileUsed U848, W3, W66, W82, W164, W376, W378, W551, W552, *876*
\CurrentOption ... s1536, s1539, s1544, s1556, U14, U455, U466, U479, U480, U485, U498, U499, U501, U515, U516, U519, U533, U538, U539, U552, U557, U558, U571, U573, U579, U581, U593, U594, U595, U603, U604, U605, U898, U963, U1061, U1062, U1072, *1028*
CurrentOption commands:
\CurrentOption: U478, U497, U514, U532, U537, U551, U556, U592, U602, U1071
\CYRA s1508
\cyra s1508, s1559
\CYRABHCH s1508
\cyrabhch s1508
\CYRABHCHDSC s1508
\cyrabhchdsc s1508
\CYRABHDZE s1509
\cyrabhdze s1508
\CYRABHHA s1509
\cyrabhha s1509
\CYRAE s1509
\cyrae s1509
\CYRB s1509
\cyrb s1509
\CYRBYUS s1510
\cyrbyus s1509
\CYRC s1510
\cyrc s1510
\CYRCH s1510
\cyrch s1510
\CYRCHLDSC s1510
\cyrchldsc s1510
\CYRCHRDSC s1511
\cyrchrdsc s1510
\CYRCHVCRS s1511
\cyrchvcrs s1511
\CYRD s1511
\cyrd s1511
\CYRDELTA s1511
\cyrdelta s1511
\CYRDJE s1512
\cyrdje s1512
\CYRDZE s1512
\cyrdze s1512
\CYRDZHE s1512
\cyrdzhe s1512
\CYRE s1512
\cyre s1512
\CYREPS s1513
\cyreps s1512
\CYREREV s1513
\cyrerev s1513
\CYRERY s1513
\cyrery s1513
\CYRF s1513
\cyrf s1513
\CYRFITA s1514
\cyrfita s1513
\CYRG s1514
\cyrg s1514
\CYRGDSC s1514
\cyrgdsc s1514
\CYRGDSCHCRS s1514
\cyrgdschcrs s1514
\CYRGHCRS s1515
\cyrghcrs s1515
\CYRGHK s1515
\cyrghk s1515
\CYRGUP s1515
\cyrgup s1515
\CYRH s1515
\cyrh s1515
\CYRHDSC s1516
\cyrhdsc s1516
\CYRHHCRS s1516
\cyrhhcrs s1516
\CYRHHK s1516
\cyrhhk s1516
\CYRHRDSN s1517
\cyrhrdsn s1516
\CYRI s1517
\cyri s1517
\CYRIE s1517
\cyrie s1517
\CYRII s1517
\cyrii s1517
\CYRISHRT s1517
\cyrishrt s1517
\CYRISHRTDSC s1518
\cyrishrtdsc s1518
\CYRIZH s1518
\cyrizh s1518
\CYRJE s1518
\cyrje s1518
\CYRK s1518
\cyrk s1518
\CYRKBEAK s1519
\cyrkbeak s1519
\CYRKDSC s1519
\cyrkdsc s1519
\CYRKHCRS s1519
\cyrkhcrs s1519
\CYRKHK s1520
\cyrkhk s1519

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\CYRKVCRS s1520
\cyrkvcrs s1520
\CYRL s1520
\cyrl s1520
\CYRLDSC s1520
\cyrldsc s1520
\CYRLHK s1521
\cyrlhk s1520
\CYRLJE s1521
\cyrlje s1521
\CYRM s1521
\cyrm s1521
\CYRMDSC s1521
\cyrmdsc s1521
\CYRMHK s1521
\cyrmhk s1521
\CYRN s1522
\cyrn s1522
\CYRNDSC s1522
\cyrndsc s1522
\CYRNG s1522
\cyrng s1522
\CYRNHK s1522
\cyrnhk s1522
\CYRNJE s1523
\cyrnje s1522
\CYRNLHK s1523
\cyrnlhk s1523
\CYRO s1523
\cyro s1523
\CYROTLD s1523
\cyrotld s1523
\CYRP s1523
\cyrp s1523
\CYRPHK s1524
\cyrphk s1524
\CYRQ s1524
\cyrq s1524
\CYRR s1524
\cyrr s1524
\CYRRDSC s1524
\cyrrdsc s1524
\CYRRHK s1525, *1066*
\cyrrhk s1524, *1066*
\CYRRHOOK *1066*
\cyrrhook *1066*
\CYRRTICK s1525
\cyrrtick s1525
\CYRS s1525
\cyrs s1525
\CYRSACRS s1525
\cyrsacrs s1525
\CYRSCHWA s1526
\cyrschwa s1526
\CYRSDSC s1526
\cyrsdsc s1526
\CYRSEMISFTSN s1526
\cyrsemisftsn s1526
\CYRSFTSN s1527
\cyrsftsn s1527
\CYRSH s1527
\cyrsh s1527
\CYRSHCH s1527
\cyrshch s1527
\CYRSHHA s1527
\cyrshha s1527
\CYRT s1528
\cyrt s1528
\CYRTDSC s1528
\cyrtdsc s1528
\CYRTETSE s1528
\cyrtetse s1528
\CYRTSHE s1528
\cyrtshe s1528
\CYRU s1529
\cyru s1529
\CYRUSHRT s1529
\cyrushrt s1529
\CYRV s1529
\cyrv s1529
\CYRW s1529
\cyrw s1529
\CYRY s1529
\cyry s1529
\CYRYA s1530
\cyrya s1530
\CYRYAT s1530
\cyryat s1530
\CYRYHCRS s1530
\cyryhcrs s1530
\CYRYI s1530
\cyryi s1530
\CYRYO s1531
\cyryo s1530
\CYRYU s1531
\cyryu s1531
\CYRZ s1531
\cyrz s1531
\CYRZDSC s1531
\cyrzdsc s1531
\CYRZH s1531
\cyrzh s1531
\CYRZHDSC s1532
\cyrzhdsc s1532

D

\d s235, s395, s482, s765, s1249, s1463, s1464, s1465,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

s1466, s1469, s1470, s1471, s1472, s1473, s1474, s1475, s1476, s1477, s1478, s1479, s1480, s1481, s1482, s1483, s1484, s1485, s1486, s1487, s1488, s1489, s1490, s1491, s1492, s1493, s1494, s1495, s1496, s1497, s1498, s1499, s1500, s1501, s1502, *1041*
\dag s312, *1046*
\dagger . s312, t165, t171, t179, t180, B375
\dashbox M309, M808, M825
\dashv B403
\date *747*
\date O9, O25
\day a188, U1183, U1316, U1405
\dblfigrule Y769, Y2361, *1037*
\dblfloatpagefraction P287, P301, Y2338
\dblfloatsep Y755, Y767, Y1642, Y1768, Y2345
\dbltextfloatsep Y222, Y230, Y771, Y1641, Y1767, Y2345
\dbltopfraction P284, P298, Y2337
\ddag s313, *1046*
\ddagger s313, t166, t172, t179, t181, B374
\ddot B518
\ddots B513
\deadcycles r334, r390, r429, H32, H99, H165, Y299, *1062*
debug commands:
\debug_resume: *206*
\debug_suspend: *206*
\DebugHooksOff h1495, h1601, *191*
\DebugHooksOn h1495, h1600, *191*
\DebugMarksOff S234, *795*
\DebugMarksOn S234, *795*
\DebugShipoutsOff X412, X444, *903*
\DebugShipoutsOn X412, X443, *903*
\DeclareAccent *1030*
\DeclareCommandCopy . . f460, f461, f463, *94*
\DeclareCurrentRelease E812, E815, U1640
\DeclareDefaultHookRule h1499, h1604, *189*
\DeclareDocumentCommand g2497
\DeclareDocumentEnvironment g2533
\DeclareEmphSequence *536*
\DeclareEmphSequence A541, A577, A578, A590, *537*
\DeclareEncoding *1030*
\DeclareEncodingSubset E40, E397, E398, E399, E400, E401, E402, E403, E404, E405, E406, E407, E408, E409, E410, E411, E412, E413, E414, E415, E416, E417, E418, E419, E420, E421, E422, E423, E424, E425, E427, E428, E429, E430, E431, E432, E433, E434, E435, E436, E437, E438, E439, E440, E441, E442, E443, E444, E445, E446, E447, E448, E449, E450, E451, E452, E453, E454, E455, E456, E457, E458, E459, E460, E461, E462, E463, E464, E465, E466, E467, E468, E469, E470, E471, E472, E473, E474, E475, E476, E477, E478, E479, E480, E481, E482, E483, E484, E485, E486, E487, E488, E489, E490, E491, E492, E493, E494, E495, E496, E497, E498, E499, E500, E501, E502, E503, E504, E505, E506, E507, E508, E509, E510, E511, E512, E513, E514, E515, E516, E517, E518, E519, E520, E521, E522, E523, E524, E525, E526, E527, E528, E529, E530, E531, E532, E533, E534, E535, E536, E537, E538, E539, E540, E541, E542, E543, E544, E545, E546, E547, E548, E549, E550, E551, E552, E553, E554, E555, E556, E557, E558, E559, E560, E561, E562, E563, E564, E565, E566, E567, E568, E569, E570, E571, E572, E573, E574, E575, E620, E820, E821, E822, E823, E865, E872, E873, E874, E875, E1151, E1152, E1153, E1154, E1155, E1156, E1157, E1158, E1159, E1160, E1161, E1162, E1163, E1164, E1165, E1166, E1167, E1168, E1169, E1170, E1171, E1172, E1173, E1174, E1175, E1176, E1177, E1178, E1179, E1180, E1181, E1182, E1183, E1184, E1185, E1186, E1187, E1188, E1189, E1190, E1191, E1192, E1193, E1194, E1195, E1196, E1197, E1198, E1199, E1200, E1201, E1202, E1203, E1204, E1205, E1206, E1207, E1208, E1209, E1210, E1211
\DeclareErrorFont v477, z342, A735, B49
\DeclareExpandableDocumentCommand g2553
\DeclareFixedFont v75
\DeclareFontEncoding s377, s463, s716, s738, s744, s830, s1038, v118, B126, B127, B128, B129, *1041*
\DeclareFontEncodingDefaults v168, y90, y91, B36

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\DeclareFontFamily . . . v93, y85, y86, *426*
\DeclareFontFamilySubstitution . . v437
\DeclareFontSeriesChangeRule . . . . . .
. . . . . w3, w4, w6, w7, w8, w9, w10, w11, w12, w13, w14, w15, w16, w17, w18, w19, w20, w21, w22, w23, w24, w25, w26, w27, w28, w29, w30, w31, w32, w33, w34, w35, w36, w37, w38, w39, w40, w41, w42, w43, w44, w45, w46, w47, w48, w49, w50, w51, w52, w53, w54, w55, w56, w57, w58, w59, w60, w61, w62, w63, w64, w65, w66, w67, w68, w69, w70, w71, w72, w73, w74, w75, w76, w77, w78, w79, w80, w81, w82, w83, w84, w85, w86, w87, w88, w89, w90, w91, w92, w93, w94, w95, w96, w97, w98, w99, w100, w101, w102, w103, w104, w105, w106, w107, w108, w109, w110, w111, w112, w113, w114, w115, w116, w117, w118, w119, w120, w121, w122, w123, w124, w125, w126, w127, w128, w129, w130, w131, w132, w133, w134, w135, w136, w137, w138, w139, w140, w141, w142, w143, w144, w145, w146, w147, w148, w149, w150, w151, w152, w153, w154, w155, w156, w157, w158, w159, w160, w161, w162, w163, w164, w165, w166, w167, w168, w169, w170, w171, w172, w173, w174, w175, w176, w177, w178, w179, w180, w181, w182, w183, w184, w185, w186, w187, w188, w189, w190, w191, w192, w193, w194, w195, w196, w197, w198, w199, w200, w201, w202, w203, w204, w205, w206, w207, w208, w209, w210, w211, w212, w213, w214, w215, w216, w217, w218, w219, w220, w221, w222, w223, w224, w225, w226, w227, w228, w229, w230, w231, w232, w233, w234, w235, w236, w237, w238, w239, w240, w241, w242, w243, w244, w245, w246, w247, w248, w249, w250, w251, w252, w253, w254, w255, w256, w257, w258, w259, w260, w261, w262, w263, w264, w265, w266, w267, w268, w269, w270, w271, w272, w273, w274, w275, w276, w277, w278, w279, w280, w281, w282, w283, w284, w285, w286, w287, w288, w289, w290, w291, w292, w293, w294, w295, w296, w297, w298, w299, w300, w301, w302, w303, w304, w305, w306, w307, w308, w309, w310, w311, w312, w313, w314, w315, w316, w317, w318, w319, w320, w321, w322, w323, w324, w325, w326, w327, w328, w329, w330, w331, w332, w333, w334, w335, w336, w337, w338, w339, w340, w341, w342, w343, w344, w345, w346, w347, w348, w349, w350, w351, w352, w353, w354, w355, w356, w357, w358, w359, w360, w361, w362, w363, w364, w365, w366, w367, w368, w369, w370, w371, w372, w373, w374, w375, w376, w377, w378, w379, w380, w381, w382, w386, w388, *437*
\DeclareFontSeriesDefault *519*
\DeclareFontSeriesDefault A34, A35, A69, A71, A72, A82, A93, A102, A104, *519*
\DeclareFontShape v18, v446, v447, v448, v449, v450, v451, v452, v453, v454, v455, v456, v457, v458, v459, v460, v461, v462, v463, v464, v465, v466, y25, y27, y81, y82, *1024*
\DeclareFontShapeChangeRule w523, w524, w541, w542, w543, w544, w545, w546, w547, w548, w549, w550, w551, w552, w553, w554, w555, w556, w557, w558, w559, w560, w561, w562, w563, w564, w565, w566, w567, w568, w569, w570, w571, w572, w573, w574, w575, w576, w577, w578, w579, w580, w581, w582, w583, w584, w585, w586, w587, w588, w589, w590, w591, w592, w593, w594, w595, w596, w597, w601, w603
\DeclareFontSubstitution s745, s831, v141, B26, B34, B37, B38, B130, B131, B132, B133
\DeclareHookRule . H40, h1497, h1603, *188*
\DeclareHookrule *188*
\DeclareKeys V120, *868*
\DeclareMathAccent . z696, B516, B517, B518, B519, B520, B521, B522, B523, B524, B525, B526, B527, B528
\DeclareMathAlphabet . . . . . .

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

. . . . . y119, y123, y125, y132, z522, z685, B151, B152, B153, B154
\DeclareMathAlphabetCharacter . . . z871
\DeclareMathDelimiter z873, B255, B256, B257, B258, B259, B260, B263, B265, B266, B563, B565, B567, B569, B571, B574, B576, B578, B580, B582, B584, B586, B588, B590, B592, B594, B596, B598, B600, B602, B604, B606, B608, B610, B612, *563*
\DeclareMathOperator *1050*
\DeclareMathRadical z1008, B529
\DeclareMathSizes v205, v211, v233, B157, B158, B159, B160, B161, B162, B163, B164, B165, B166, B167, B168, *1048*
\DeclareMathSizes* v205
\DeclareMathSymbol . . z809, z872, z889, B169, B170, B171, B172, B173, B174, B175, B176, B177, B178, B179, B180, B181, B182, B183, B184, B185, B186, B187, B188, B189, B190, B191, B192, B193, B194, B195, B196, B197, B198, B199, B200, B201, B202, B203, B204, B205, B206, B207, B208, B209, B210, B211, B212, B213, B214, B215, B216, B217, B218, B219, B220, B221, B222, B223, B224, B225, B226, B227, B228, B229, B230, B231, B232, B233, B234, B235, B236, B237, B238, B239, B240, B241, B242, B243, B244, B245, B246, B247, B248, B249, B250, B251, B261, B262, B264, B268, B269, B270, B271, B272, B273, B274, B275, B276, B277, B278, B279, B280, B281, B282, B283, B284, B285, B286, B287, B288, B289, B290, B291, B292, B293, B294, B295, B296, B297, B298, B299, B300, B301, B302, B303, B304, B305, B306, B307, B308, B309, B310, B311, B312, B313, B314, B315, B316, B317, B318, B319, B320, B321, B322, B323, B324, B325, B327, B328, B329, B330, B331, B332, B333, B334, B341, B342, B343, B344, B345, B346, B347, B349, B350, B351, B352, B353, B354, B356, B357, B358, B359, B360, B361, B364, B365, B366, B367, B370, B371, B372, B373, B374, B375, B376, B377, B378, B379, B380, B381, B382, B383, B384, B385, B386, B387, B388, B389, B390, B391, B392, B393, B394, B395, B396, B397, B398, B399, B400, B401, B402, B403, B404, B405, B406, B407, B408, B409, B410, B411, B414, B415, B418, B419, B420, B421, B422, B423, B424, B425, B426, B427, B428, B429, B430, B432, B433, B434, B435, B436, B437, B438, B441, B442, B443, B445, B446, B447, B448, B449, B450, B451, B452, B453, B454, B455, B477, B479, B501, B502, B503, B553, B554, B555, B556, B614, B615, B616, *1062*
\DeclareMathVersion z355, A2, A3
\DeclareOldFontCommand D125, D141
\DeclareOption *821*
\DeclareOption . . s1535, x29, x37, x45, x53, x56, x60, E820, E821, E822, E823, E824, E826, E828, E830, E831, E872, E873, E874, E875, E876, E878, E879, U433, U1082, *1052*
\DeclareOption* *821*
\DeclareOption* U433
\DeclarePreloadSizes v185, y95, y96, C19, C21, C22, C23, C25, C26, C27, C28, C29, C30, C34, C38, C43, C45, C49, C50, C53, C54, C57, C58, C64
\DeclareProtectedCommand *1040*
\DeclareRelease E811, E814, U1547
DeclareRelease commands:
\DeclareRelease: U1550
\DeclareRobustCommand p7, p8, p9, p10, p11, p68, p92, p330, p406, p420, p437, p461, q2, q3, q13, r468, r581, s150, s158, s307, s310, s311, s312, s313, s314, s316, s318, s320, t189, u19, u20, u21, v251, v279, v280, v281, v286, v298, v308, v316, v318, v336, v641, v650, w394, w398, w407, w409, w419, w526, w531, w536, w615, w618, w626, w627, w633, w713, x115, x164, A4, A7, A10, A13, A16, A19, A22, A25, A28, A254, A277, A307, A328, A352, A363, A380, A383, A405, A410, A415, A448, A453, A458, A474, A477, A480, A483, A486, A500, A549, A550,

A585, A591, A613, A615, A624, A626, A633, A649, A657, A675, A691, A708, B335, B336, B337, B348, B355, B412, B413, B444, B456, B460, B463, B468, B470, B472, B475, B478, B480, B481, B483, B485, B487, B489, B491, B493, B495, B497, B499, B505, B507, B509, B512, B530, B533, B536, B540, B544, B547, B550, B557, B560, B617, B618, B619, B624, B626, B628, B630, D3, D126, E4, E11, E610, E1136, G88, G99, H172, H228, H357, H362, H367, H377, H381, H385, H466, H470, I3, I4, I5, I6, I7, I8, I9, I10, I11, I12, I13, I14, I15, I16, I17, I18, I19, I20, I21, I22, I23, I24, I25, I26, I27, I28, I29, I30, I31, I32, I33, I34, I35, I39, I41, I42, I43, I44, I45, I46, I47, I48, I49, I50, I51, I52, I81, I82, I83, I84, I126, I154, I156, I160, I205, I207, I209, I211, I214, I215, I217, I224, I226, I227, I238, I261, I263, I279, I290, I340, I341, I342, I416, I436, I460, K7, K24, K120, K133, K156, K157, K173, K184, K238, K428, K446, K454, K490, K491, K492, K493, K494, K495, L139, L142, L154, M124, M127, M130, O7, O8, O9, O10, O14, O222, P402, P423, R16, R28, S375, S376, T23, T34, T51, T59, T82, T84, T86, T93, U1038, U1039, U1040, U1046, U1047, U1670, W148, f221, W184, X446, Y87, aa571, aa578, f728, f729, f735, f750, l4, l11, l30, l57, *100*

\DeclareSizeFunction x417, x490, x491, x502, x503, x507, x508, x514, x515, x543, x557, x558, x565, x566

\DeclareSymbolFont y136, z403, B141, B142, B143, B144

\DeclareSymbolFontAlphabet z1082, B148, B149, B150

\DeclareTextAccent s64, s378, s379, s380, s381, s382, s383, s384, s385, s386, s387, s388, s464, s465, s466, s467, s468, s469, s470, s471, s472, s473, s474, s741, s746, s747, s748, s749, s750, s751, s752, s753, s754, s755, s756, s838, s839, s840, s841, s842, s843, s844, s845, s846, s847, s848, s849, s850, s851, s852

\DeclareTextAccentDefault s185, s226, s227, s228, s229, s230, s231, s232, s233, s234, s235, s236, s237, s238, s239, s279, s282, E687, E688, E940, E941, E942, E943, E944, E945, E946, E947, E948, E949, E950, E951, E952, *1045*

\DeclareTextCommand s3, s58, s65, s83, s389, s392, s395, s409, s410, s411, s414, s415, s422, s424, s426, s428, s434, s436, s438, s445, s475, s478, s482, s485, s487, s490, s492, s494, s510, s568, s569, s570, s730, s757, s759, s762, s765, s798, s805, s832, s835, s865, s893, s1053, s1080, E376, E377, E378, E379, E380, E381, E382, E383, E384, E385, E625, E632, E639, E759, *1039*

\DeclareTextCommandDefault s57, s186, s188, s283, s286, s287, s288, s290, s292, s296, s300, s301, s303, s304, s305, s306, s326, s355, E155, E157, E160, E162, E164, E166, E168, E170, E172, E174, E176, E178, E180, E182, E184, E186, E188, E190, E193, E194, E195, E196, E197, E198, E199, E200, E201, E202, E203, E204, E205, E206, E207, E208, E210, E212, E214, E216, E218, E220, E222, E224, E226, E228, E230, E232, E234, E236, E238, E240, E242, E244, E246, E248, E250, E252, E254, E256, E258, E260, E262, E264, E266, E268, E270, E272, E274, E276, E278, E280, E282, E284, E286, E288, E290, E292, E294, E296, E298, E300, E302, E304, E306, E309, E311, E313, E315, E317, E319, E321, E323, E325, E327, E329, E331, E333, E335, E337, E339, E341, E343, E345, E347, E349, E351, E353, E355, E357, E359, E361, E363, E365, E654, E662, E664, E670, E678, E1006, E1008, E1009, E1011, E1013, E1015, E1017, E1019, E1021, E1023, E1025, E1027, E1029, E1031, E1033, E1035, E1037, E1039, E1041, E1043, E1045, E1047, E1049, E1051, E1053, E1055, E1057, E1059, E1061, E1063, E1065, E1067, E1069, E1071, E1073, E1075, E1077,

E1079, E1081, E1083, E1085, E1087, E1089, E1091, E1093, E1095, E1097, E1099, E1101, E1103, E1105, E1107, E1109, E1111, E1113, E1115, E1117, E1119, E1121, E1123, E1126, *1045*

`\DeclareTextComposite` s76, s452, s453, s587, s588, s589, s590, s591, s592, s593, s594, s595, s596, s597, s598, s599, s600, s601, s602, s603, s604, s605, s606, s607, s608, s609, s610, s611, s612, s613, s614, s615, s616, s617, s618, s619, s620, s621, s622, s623, s624, s625, s626, s627, s628, s629, s630, s631, s632, s633, s634, s635, s636, s637, s638, s639, s640, s641, s642, s643, s644, s645, s646, s647, s648, s649, s650, s651, s652, s653, s654, s655, s656, s657, s658, s659, s660, s661, s662, s663, s664, s665, s666, s667, s668, s669, s670, s671, s672, s673, s674, s675, s676, s677, s678, s679, s680, s681, s682, s683, s684, s685, s686, s687, s688, s689, s690, s691, s692, s693, s694, s695, s696, s697, s812, s813, s814, s815, s816, s817, s818, s819, s820, s821, s822, s823, s824, s825, s826, s827, *1054*

`\DeclareTextCompositeCommand` s76, s431, s454, s455, s456, s457, s459, s698, s699, s701, s704, s705, s706, s707, s708, s709, s710, s711, s712, s795, s1059, *1046*

`\DeclareTextFontCommand` D1, D15, D16, D17, D18, D19, D20, D21, D22, D23, D24, D29, D30, D31, D42, D140, *1063*

`\DeclareTextFoo` *1030*

`\DeclareTextGlyph` *1037*

`\DeclareTextSymbol` s3, s398, s399, s400, s401, s402, s403, s404, s405, s406, s407, s408, s412, s413, s416, s417, s418, s419, s420, s421, s526, s527, s528, s529, s530, s531, s532, s533, s534, s535, s536, s537, s538, s539, s540, s541, s543, s544, s545, s546, s547, s548, s549, s550, s551, s552, s553, s554, s555, s556, s557, s558, s559, s560, s561, s562, s563, s564, s565, s566, s567, s571, s572, s573, s574, s575, s576, s577, s578, s579, s580, s581, s582, s583, s584, s585, s586, s717, s718, s719, s720, s721, s722, s723, s724, s725, s726, s727, s728, s729, s739, s740, s768, s769, s770, s771, s772, s773, s774, s776, s777, s778, s779, s780, s781, s782, s783, s784, s785, s786, s787, s788, s789, s790, s791, s792, s793, s794, s853, s854, s855, s856, s857, s858, s859, s860, s861, s862, s863, s864, s876, s877, s878, s879, s880, s881, s882, s883, s884, s885, s886, s887, s888, s889, s890, s891, s892, s899, s900, s901, s902, s903, s904, s905, s906, s907, s908, s909, s910, s911, s912, s913, s914, s915, s916, s917, s918, s919, s920, s921, s922, s923, s924, s925, s926, s927, s928, s929, s930, s931, s932, s933, s934, s935, s936, s937, s938, s939, s940, s941, s942, s943, s944, s945, s946, s947, s948, s949, s950, s951, s952, s953, s954, s955, s956, s957, s958, s959, s960, s961, s962, s963, s964, s965, s966, s967, s968, s969, s970, s971, s972, s973, s974, s975, s976, s977, s978, s1079, E368, E369, E370, E371, E372, E373, E374, E375, E386, E387, E388, E389, E390, E391, E392, E393, E394, E395, E589, E590, E591, E592, E593, E594, E595, E596, *1045*

`\DeclareTextSymbolDefault` s185, s240, s241, s242, s243, s244, s245, s246, s247, s248, s249, s250, s251, s252, s253, s254, s255, s256, s257, s258, s259, s260, s261, s262, s263, s264, s265, s266, s267, s268, s269, s270, s271, s272, s273, s274, s275, s276, s277, s278, s280, s281, s291, E114, E116, E118, E120, E121, E122, E123, E124, E125, E126, E127, E128, E129, E130, E131, E132, E133, E134, E135, E136, E137, E138, E139, E140, E141, E142, E143, E144, E145, E146, E147, E148, E149, E150, E151, E152, E153, E154, E577, E578, E579, E580, E581, E582, E583, E584, E597, E598, E599, E600, E601, E602, E603, E604, E623, E624, E642, E643, E644, E645, E646, E647, E648, E650, E953, E954, E955, E956, E957, E958, E959, E960, E961, E962, E963, E964, E965, E966,

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

E967, E968, E969, E970, E971, E972, E973, E974, E975, E976, E977, E978, E979, E980, E981, E982, E983, E984, E985, E986, E987, E988, E989, E990, E991, E992, E993, E994, E995, E996, E997, E998, E999, E1000, E1001, E1002, E1003, E1004, E1005, *1045*
\DeclareUnicode... . . . . *388*
\DeclareUnicodeAccent s1042, s1237, s1238, s1239, s1240, s1241, s1242, s1243, s1244, s1245, s1246, s1247, s1248, s1249, s1250, s1251, *1088*
\DeclareUnicodeCharacter . . . aa384, *1075*
\DeclareUnicodeCommand s1080, s1081, s1082, s1083, s1164, s1166, s1168, s1215, s1252, *1088*
\DeclareUnicodeComposite s1057, s1256, s1257, s1258, s1259, s1260, s1261, s1262, s1263, s1264, s1265, s1266, s1267, s1268, s1269, s1270, s1271, s1272, s1273, s1274, s1275, s1276, s1277, s1278, s1279, s1280, s1281, s1282, s1283, s1284, s1285, s1286, s1287, s1288, s1289, s1290, s1291, s1292, s1293, s1294, s1295, s1296, s1297, s1298, s1299, s1300, s1301, s1302, s1303, s1304, s1305, s1306, s1307, s1308, s1309, s1310, s1311, s1312, s1313, s1314, s1315, s1316, s1317, s1318, s1319, s1320, s1321, s1322, s1323, s1324, s1325, s1326, s1327, s1328, s1329, s1330, s1331, s1332, s1333, s1334, s1335, s1336, s1337, s1338, s1339, s1340, s1341, s1342, s1343, s1344, s1345, s1346, s1347, s1348, s1349, s1350, s1351, s1352, s1353, s1354, s1355, s1356, s1357, s1358, s1359, s1360, s1361, s1362, s1363, s1364, s1365, s1366, s1367, s1368, s1369, s1370, s1371, s1372, s1373, s1374, s1375, s1376, s1377, s1378, s1379, s1380, s1381, s1382, s1383, s1384, s1385, s1386, s1387, s1388, s1389, s1390, s1391, s1392, s1393, s1394, s1395, s1396, s1397, s1398, s1399, s1400, s1401, s1402, s1403, s1404, s1405, s1406, s1407, s1408, s1409, s1410, s1411, s1412, s1413, s1414, s1415, s1416, s1417, s1418, s1419, s1420, s1421, s1422, s1423, s1424, s1425, s1426, s1427, s1428, s1429, s1430, s1431, s1432, s1433, s1434, s1435, s1436, s1437, s1438, s1439, s1440, s1441, s1442, s1443, s1444, s1445, s1446, s1447, s1448, s1449, s1450, s1451, s1452, s1453, s1454, s1455, s1456, s1457, s1458, s1459, s1460, s1461, s1462, s1463, s1464, s1465, s1466, s1467, s1468, s1469, s1470, s1471, s1472, s1473, s1474, s1475, s1476, s1477, s1478, s1479, s1480, s1481, s1482, s1483, s1484, s1485, s1486, s1487, s1488, s1489, s1490, s1491, s1492, s1493, s1494, s1495, s1496, s1497, s1498, s1499, s1500, s1501, s1502, *388*
\DeclareUnicodeSymbol s1079, s1084, s1085, s1086, s1087, s1088, s1089, s1090, s1091, s1092, s1093, s1094, s1095, s1096, s1097, s1098, s1099, s1100, s1101, s1102, s1103, s1104, s1106, s1107, s1108, s1109, s1110, s1111, s1112, s1113, s1114, s1115, s1116, s1117, s1118, s1119, s1120, s1122, s1123, s1124, s1125, s1126, s1127, s1128, s1129, s1130, s1131, s1132, s1133, s1134, s1135, s1136, s1137, s1138, s1139, s1140, s1141, s1142, s1143, s1144, s1145, s1146, s1147, s1148, s1149, s1150, s1151, s1152, s1153, s1154, s1155, s1156, s1157, s1158, s1159, s1160, s1161, s1162, s1163, s1170, s1171, s1172, s1173, s1174, s1175, s1176, s1177, s1178, s1179, s1180, s1181, s1182, s1183, s1184, s1185, s1186, s1187, s1188, s1189, s1190, s1191, s1192, s1193, s1194, s1195, s1196, s1197, s1198, s1199, s1200, s1201, s1202, s1203, s1204, s1205, s1206, s1207, s1208, s1209, s1210, s1211, s1213, s1214, s1226, s1227, s1228, s1229, s1230, s1231, s1232, s1233, s1234, s1235, s1236, *1088*
\DeclareUnknownKeyHandler . . . V122, *868*
\DeclareUnknownKeysHandler *1089*
\def *1026*
\defaultencoding *1042*
\defaulthyphenchar f738, f753, b367
\defaultscriptratio v624, v631, *1035*
\defaultscriptscriptratio v625, v631, *1035*
\defaultskewchar b368
\deg I34
\delcode z1006
\delimiter z919, z989, z1000, *1073*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\delimiterfactor b369
\delimitershortfall b379
\Delta B298
\delta B271
\depth K32, K35
\det I30
\detokenize r253, c93, c94, s998, s1040, c179, w434, A563, E44, H130, U815, U1154, U1158, U1286, U1287, U1291, f527, f545, f609, l249, l250, *885*
\DH s528, s1128, aa585, *1041*
\dh s538, s1134, aa585, *1041*
\Diamond A727
\diamond B380
\diamondsuit B332
\dim I28
dim commands:
  \dim_eval:n e161
  \dim_new:N . . . X197, X198, X199, X200
  \dim_set:Nn . . X191, X192, X193, X194
  \dim_set_eq:NN S50, S52
  \dim_use:N X509, X510, X511
  \c_max_dim S50, S52, S53, S62, S76, X211, X237, X262, X289, *801*
  \c_zero_dim n60, S65, S72, X217, X218, X219, X225, X243, X244, X245, X268, X269, X270, X297, X298, X299, X327, X329, X330
\dimen *1060*
\dimendef . . d226, b42, b43, b44, b52, b91
\dimenzero d226
\dimeval *76*
\dimeval e155, e171, *1088*
\dimexpr s503, s519, s869, s872, s1219, s1222, M13
\directlua s1011, d2, d14, d29, d213, d231, d256, d261, d265, a12, a15, f34, U1139, U1270, a20, aa98, aa100, aa108, aa113, aa115, a23, f649, f734, a28, b65, b81, b105, b256, b349, b359
disable commands:
  disable_callback d814
\disable_callback *48*
\DisableGenericHook . . . h1453, h1587, *182*
\DisableHook h1538, *182*
\DiscardShipoutBox X82, X409, X442, X498, *904*
\discretionary I238, f736, f751, f761
\displaylines I190
displaymath (env.) I332
\displaymath I334
\displaystyle B532, B535, B539, B541, I62, I197, I359, I362, I415, I443, I455, I483, I508, I511
\displaywidowpenalty b327
\displaywidth I197, I358, I430, I486
\div B383
\DJ s529, s1138, aa585, *1041*
\dj s539, s1139, aa585, *1041*
\do r66, r69, r134, r137, r189, r192, r232, r304, r366, r413, r552, r569, r712, r718, a129, D90, H431, H452, H560, H570, H576, H582, K57, K76, L244, L269, M104, M116, M123, M203, M337, M339, M362, M365, M394, M396, M417, M422, M478, M506, M535, M731, M787, P65, P134, R36, R65, R82, U230, U247, U478, U497, f69, U514, U532, U537, U551, U556, U592, U602, U1071, U1108, U1186, U1239, U1319, U1408, U1685, b13, b14, g1710, a77, a78, k3, k7, k16, k26, *1055*
\DocInput x8, B5, C5, Z4
\doclearpage *1067*
\document *332*
document (env.) H8
\document r9, H183, R64, R81, *526*
\documentclass d16, x2, B2, C2, U609, U616, U675, U678, U885, U980, U1091, Z2, *310*
\DocumentMetadata o6, o11, o15, o18, o34, *311*
\documentstyle U614, U1091
\dollar *1042*
\dospecials a129, H431, H452, H560, H570, U1186, U1319, U1408, b13, g1711, a77, *1059*
\dot B525
\doteq B469
\dotfill f776, f797, b513
\dots s320, s322, *1046*
\doublehyphendemerits b330
\doublerulesep L311, L338, L362
\Downarrow B586
\downarrow B580
\downbracefill B538, B557
\dump aa651

E

\E U1193, U1196, U1224, U1326, U1329, U1356, U1415, U1418, U1446
\edef *30*
\egroup b417, *1022*
\eject b480

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\ell B311
\else *1033*
else commands:
\else: W241, g1155, h448, h728, h735, h743, h885, h1185, h1256, h1301, h1331, n29
\em A550, A577, D42, *538*
\emergencystretch T88, T94, *1051*
\emforce *536*
\emforce A546, A573, A582, *537*
\eminnershape A554, A560, A577, *537*
\emph D42, h1474, *537*
\empty b415
\emptyset B318
\emreset *537*
\emreset A546, A549, A580, *537*
\emrest A549
\ENC-cmd *1041*
\encodingdefault . s990, s1536, s1569, s1570, z347, d260, d275, d283, A658, A676, A692, A709, B50, *526*
\EncodingSpecific *1037*
\EncodingSpecificAccent *1030*
\EncodingSpecificAccentedLetter . . *1030*
\EncodingSpecificCommand *1030*
\end x9, B6, C6, H190, H197, H199, H227, H253, H410, H411, I464, I473, J112, O15, O17, f23, U1201, U1205, U1212, U1334, U1338, U1344, U1423, U1427, U1433, X394, Z5, f671, g1203, g1319, g1334, a72, l250, *146*
\endarray L171
\endcenter H352
\endcsname *186*
\enddisplaymath I335
\enddocument . . . H8, H66, H68, X350, *622*
\endenumerate J240
\endeqnarray I367, I414
\endequation I338
\endfilecontents U1095
\endflushleft H402
\endflushright H404
\endgraf n98, n136, K94, b412, *1036*
\endgroup *890*
\EndIncludeInRelease b546, p20, p30, p64, p77, p85, p90, b580, p103, p109, p151, p165, b588, p177, p188, p205, p217, p251, p268, p306, p328, p365, p398, b613, p431, p435, p444, p450, p464, p471, r82, r139, r194, r255, b653, r276, r288, b658, r351, r355, b668, r434, b673, r472, r495, r518, r536, r543, r562, r579, r592, r596, r614, r625, r635, r674, r701, s103, s123, s168, s175, s330, s352, s367, s375, c68, t28, t33, t68, t73, t98, t125, t134, t176, t182, t202, t205, u10, u14, v52, v73, v231, v248, v294, v304, v314, v430, v435, v470, v475, v492, v510, v549, v582, v698, v710, w384, w390, w403, w415, w422, w505, w520, w599, w611, w622, w629, w636, w709, w727, w734, w738, w741, x157, x160, x176, x549, x555, y21, y143, z77, z105, z216, z246, z276, z308, z364, z369, d234, d257, z745, z787, z800, z807, d280, d284, z995, z1003, A67, A100, A122, A227, A248, A300, A347, A376, A387, A434, A468, A494, A530, A539, A576, A588, A595, A629, A635, A670, A686, A703, A718, B80, B90, B109, B118, B633, B640, D33, D40, G37, G44, G78, G90, G101, G112, H64, H103, H111, H117, H150, H163, H225, H275, H294, H308, H317, H327, H334, H344, H349, H373, H389, H398, H436, H457, H488, H498, H516, H531, H543, H565, H573, I86, I95, I117, I124, I143, I147, I162, I170, I219, I236, I266, I274, I303, I330, I394, I403, I446, I458, I467, I476, J132, J137, K13, K22, K69, K86, K101, K113, K124, K131, K188, K195, K243, K251, K302, K320, K388, K404, K421, K430, K435, K458, K465, L64, L69, L156, L164, L226, L231, e10, M15, M19, M38, M47, e18, M68, M76, M88, M96, M111, M121, e27, M150, M155, M171, M182, M249, M263, M368, M425, M463, M469, M500, M530, M555, M571, M582, M595, M603, M624, M641, M651, M655, M745, M800, M819, M836, O19, e110, O29, O167, O173, O178, O192, O198, e131, O224, O246, e144, P104, P172, e153, P231, P246, P293, P306, P351, P368, P411, P417, P426, P430, P439, P445, e165, P449, P481, P498, P516, e173, P558, P564, R24, R32, R76, R92, e188, e194, f12, f18, T47, T68, T75, U21, U26, U49, U61, U84, U93, U99, U111, U142, U149, U173, U179, U197,

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

U208, U242, U259, U270, U279, U296, U308, U329, U342, U355, U365, U401, f60, U417, U426, f64, U458, U468, U508, U524, U546, U561, U575, U582, U597, U606, U640, U647, U664, U671, U750, U777, U805, U955, U1012, U1042, U1049, U1227, U1358, U1448, W14, W23, W88, W140, W179, W191, W200, W245, W256, W263, W299, W322, W343, W357, W362, W385, W405, W430, W475, W491, W498, W528, W533, f312, X427, X464, X481, X485, Y53, Y62, f340, Y178, Y196, Y365, Y370, f368, Y418, f373, Y464, f392, Y652, Y710, f406, Y813, Y832, Y895, Y913, Y955, Y976, Y1218, f447, Y1387, f457, Y1469, Y1563, Y1685, Y1812, f487, Y1922, Y1930, Y1964, f496, Y1993, Y2213, f510, Y2231, f515, Y2278, Y2322, aa15, aa19, aa29, aa33, aa51, aa69, aa79, aa86, aa94, aa141, aa146, aa198, aa222, aa292, aa297, aa338, aa344, aa440, aa487, f613, f628, a309, f660, f669, a319, f719, f726, f748, f759, f762, a25, f790, f811, b87, b101, g1158, g1161, b118, b123, g1304, g1308, b133, b137, b147, b150, b167, b181, b185, b219, b224, b232, b240, a53, g2622, g2629, b288, b300, h138, h144, h163, h169, h387, b355, h415, b363, h467, h495, h519, h533, h553, h556, h569, h587, h592, h595, h601, h672, h696, h1170, h1198, h1201, h1227, h1454, h1460, b438, b455, i30, i44, i388, i400, l157, l161, l204, l210, *30*

`\EndIncludeRelease` c75
`\endinput` *1035*
`\enditemize` J251
`\endline` I175, b412
`\endlinechar` a95, a96, a97, r649, r683, a207, f37, f39, f44, U370, U371, U372, aa329, *1067*
`\endlist` J98, J240, J251
`\endlrbox` K155
`\endmath` I333
`\endminipage` K354
`\EndModuleRelease` n141, o36, c108, c109, c149, E809, S386, g2654, h1609, i424
`\endpicture` M49
`\endscname` *1021*
`\endsloppypar` T92
`\endtabbing` L84
`\endtabular` L171
`\endtabular*` L171
`\endtrivlist` H352, H402, H404, H460, I488, J100, J101, L85, N39
`\endverbatim` H459, H486
`\enlargethispage` Y1857, *1069*
`\enlargethispage*` Y1857
`\enskip` p473
`\enspace` p461, p469
`\ensuremath` t178, I416, P409, P416, P437, P444, *1058*
`enumerate` (env.) J231
`\enumerate` J231
environments:
  `array` L168
  `center` H351
  `displaymath` I332
  `document` H8
  `enumerate` J231
  `eqnarray` I344, I489
  `eqnarray*` I412
  `equation` I336, I477
  `filecontents` *819*, U1095
  `flushleft` H401
  `flushright` H403
  `itemize` J242
  `list` J34
  `lrbox` *670*
  `math` I332
  `minipage` *671*
  `picture` M21
  `sloppypar` T91
  `tabbing` L71
  `tabular` L174
  `thebibliography` *786*
  `trivlist` J89
  `verbatim` H459
  `verbatim*` H483
`\epsilon` B272
`eqnarray` (env.) I344, I489
`\eqnarray` I349, I413
`eqnarray*` (env.) I412
`\eqno` I338, *1045*
`equation` (env.) I336, I477
`\equation` I337
`\equiv` B448
`\errhelp` c31, a220, Z12, aa307, aa640, l39, l66
`\errmessage` c32, v521, v556, d63, x425, x525, y65, a7, e79, e94, a225, Z16, aa63, aa309, b164, b178, b304, a61, l47, l72

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

\ERROR g1397, g1407, g1416, g1769, g1782, g1802, g1821, g1897, g1924, h871, h872, *300*
\errorcontextlines b555, b571, b586, b600, b624, b641, b372, l212, b536, *1023*
\errorstopmode aa650, b521, *1054*
\escapchar *345*
\escapechar r453, v367, v591, x229, z58, z86, z158, z226, z256, d212, z287, z331, f126, f169, f173, f181, W281, W304, W327, W348, f275, f276, f300, f437, f525, f543, *99*
\eta B274
\etatcatcode d862
\eTeXversion a60
\evensidemargin Y73, Y615, Y674
\everycr I192, I195, I358, I505, b501, *1026*
\everydisplay v345, v346, v351
\everyeof aa329
\everyjob c37, c42, c47, d216, z351, d262, d263, X29, X30, aa112, aa331, aa416, aa610, aa611, aa613, *1075*
\everymath v344, v346, v349
\everypar *292*
\everypar n78, n88, n101, n139, r43, r112, r170, v644, v657, v704, H166, H433, H455, J129, J131, J135, J136, J180, J197, K292, K313, L81, O48, O96, O107, O127, O136, P187, Y165, Y192, Y1153, Y1319, n32, n35, *308*
\EveryShipout *904*
\ExecuteOptions x57, x70, E843, E880, U585
\exhyphenpenalty b322, b474
\exists B324
\exp I31
exp commands:
  \exp:w h438, *221*
  \exp_after:wN z186, z190, T41, W73, W236, W237, g254, g270, g324, g330, g344, g1025, g1039, g1041, g1072, g1121, g1151, g1181, g1185, g1200, g1330, g1366, g1390, g1406, g1424, g1430, g1434, g1465, g1499, g1506, g1519, g1525, g1531, g1537, g1543, g1549, g1555, g1561, g1592, g1720, g2136, g2137, g2138, g2139, g2140, g2141, g2142, g2172, g2241, h49, h56, h61, h218, h219, h264, h437, h682, h775, h884, h991, h1103, h1165, h1253, h1298, i167, i220, i221, i270, *221*
  \exp_args:Nc S22, g195, g957, g968, g1204, g1221, g1323, g2075, g2088, h1137, i28, i41, i73, i131
  \exp_args:Ncc g130
  \exp_args:Ne W46, W97, g2162, h404, h405, h1214, h1215
  \exp_args:Nee W129
  \exp_args:Nf W32, W34, W395, g349, g1901, g1928, g1989, g2164, g2240, i158
  \exp_args:NNc i145, i150
  \exp_args:NNNo g330, g1633
  \exp_args:Nnnv h115
  \exp_args:NNo h867, i166
  \exp_args:NNV h841, i185
  \exp_args:NNx g1220, h789
  \exp_args:No g88, g251, g341, g360, g369, g456, g806, g1157, g1774, g1785, g1826, g1907, g1934, g2104, g2130, h1077, h1121, i166, i185
  \exp_args:Nof g1777
  \exp_args:Noo g1130
  \exp_args:NV V128, W53, g190, g293, g1285, i186
  \exp_args:Nv h1020, h1027, h1101
  \exp_args:Nx X29, g2103, g2106, g2129, h270, h312
  \exp_end: h438
  \exp_last_unbraced:Ne g2174
  \exp_last_unbraced:Nf i109
  \exp_last_unbraced:NNNNo . h221, i115
  \exp_last_unbraced:NnNo g2001
  \exp_last_unbraced:NNo i281
  \exp_not:N n37, n38, V128, V129, V130, X31, X95, X124, g86, g114, g115, g147, g149, g150, g156, g158, g199, g211, g228, g229, g230, g232, g300, g815, g825, g890, g903, g927, g945, g952, g990, g997, g998, g1030, g1045, g1046, g1047, g1051, g1054, g1055, g1057, g1076, g1079, g1080, g1081, g1089, g1136, g1155, g1169, g1175, g1176, g1213, g1214, g1566, g1567, g1674, g1676, g1677, g1742, g2165, g2168, g2169, g2170, g2172, h229, i107, i109, i110, i111, i181, i196, i203, i204, i208, i212, i228, i269, i275, i293, i302, i354, i355, i380, i381, *266*
  \exp_not:n S149, S150, S166, S167, S168, S241, S242, S243, S245, S246, S247, S249, S250, S251, S253, S254, S255, S257, S258, S259, S261, S262, S263, V112, W211, W225, X30, g109, g113, g117, g120, g124, g141, g148, g160, g212, g231, g300, g303, g304, g538,

g672, g762, g773, g775, g776, g839, g891, g904, g915, g927, g944, g1029, g1031, g1045, g1058, g1090, g1125, g1314, g1316, g1329, g1375, g1376, g1419, g1479, g1675, g1792, g1793, g1833, g1834, g2016, g2025, g2165, h758, i168, i181, i184, i186, i214, i273, i303, i305, i306, i308, i309, *266*
`\exp_stop_f:` g1241, g1779, h725, h733
expandable commands:
`\expandable_grab_⟨type⟩:w` *139*
`\expandafter` *1022*
expandafter commands:
`\expandafter:` D88, L269
`\ExpandArgs` *77*
`\ExpandArgs` e174, e190, e193
`\expanded` U815, aa111, *214*
`\ExplSyntaxOff` n142, o37, z214, e143, e163, e186, S387, T45, V189, W12, W86, W138, W243, W254, W266, W403, W428, W473, W526, W581, X425, X472, X512, aa570, g2655, h1610, i298, i425, *825*
`\ExplSyntaxOn` o2, z178, e135, e158, e177, S3, T22, V3, W7, W29, W92, W207, W251, W391, W411, W436, W505, W574, X5, X470, X507, aa565, g8, h3, i3, i298, n3, *77*
`\extracolsep` L167
`\extrafloats` b152, b189, b274

F

`\fam` v15, d22, d26, d38, b98
`\family` *1021*
`\familydefault` s1570, z348, A444, A659, A677, A693, A710, B120, *526*
`\fbox` *670*
`\fbox` K173, K186, K193, *1039*
`\fboxrule` K171, K207, K210, K216, K218, K225, K226, aa151
`\fboxsep` K171, K177, K206, K211, K221, K223, aa150
`\fi` *1027*
fi commands:
`\fi:` n61, W241, g773, g776, g838, g1155, g1243, h450, h729, h737, h743, h887, h1104, h1166, h1187, h1258, h1303, h1333, i263, i266, i271, i278, n30, *269*
`\filbreak` b478
file commands:
`\g_file_curr_name_str` h1488
`\file_full_name:n` W35, *884*
`\file_parse_full_name_apply:nN` W32, W47, W90, W93, W95
`\l_file_search_path_seq` *891*
file internal commands:
`\__file_parse_full_name_area:nw` W102, W105, W109
`\__file_parse_full_name_auxi:nN` W97, W100
`\__file_parse_full_name_base:nw` W108, W112, W124
`\__file_parse_full_name_tidy:nnnN` W119, W120, W122, W127
`file/.../after` *875*
`file/.../before` *875*
`file/after` *875*
`file/before` *875*
`filecontents` (env.) *819*, U1095
`\filecontents` U1095
filehook internal commands:
`\__filehook_clear_replacement_flag:` W418, W421, W517
`\__filehook_drop_extension:N` W44, W49, W519
`\__filehook_drop_extension_aux:nnn` W54, W57
`\__filehook_file_name_compose:nnn` .. W218, W407, W415, W416, W426
`\__filehook_file_parse_full_name:nN` W28, W30, W30, W53, W238, W395, W413, W415, *891*
`\__filehook_file_pop:` W59, W70, W523
`\__filehook_file_pop_assign:nnnn` W59, W73, W79, W525
`\__filehook_file_push:` W59, W62, W521
`\__filehook_file_subst_begin:nnn` W413, W423, W423, *891*
`\__filehook_file_subst_cycle_error:NN` W458, W463, W463, W468, W470, *893*
`\__filehook_file_subst_loop:NN` W432, W445, W453, W462, *892*
`\__filehook_file_subst_tortoise_hare:nn` W425, W432, W435, W437, W460, *893*
`\__filehook_full_name:nn` W30, W34, W38
`\__filehook_if_file_replaced:TF` W418, W419, W515, *892*
`\__filehook_if_no_extension:nTF` W44, W44, W507
`\g__filehook_input_file_seq` W59, *882*
`\l__filehook_internal_tl` W59

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__filehook_log_file_record:n ... W544, W544, W558, W560
\g__filehook_nesting_level_int .. W541, W546, W549, W550, W556
__filehook_normalize_file_name:w ... W407, W414, W513
__filehook_resolve_file_subst:w ... W407, W410, W412, W511
__filehook_set_curr_file:nNN ... W393, W509
__filehook_set_curr_file_assign:nnnNN ... W396, W398
__filehook_subst_add:nn ... W206, W208, W208, W252, *886*
__filehook_subst_empty_name_chk:NN ... W208, W236, W240
__filehook_subst_file_normalize:Nn .. W208, W216, W218, W230, W234
__filehook_subst_remove:n ... W208, W222, W253
\filename@parse ... *6*, *1*
\filesize ... e72, e118
\fill ... p454
\finalhyphendemerits ... H360, H364, H370, b331, *1081*
\finalstrut ... *1048*
\FirstMark ... S274, S377, *796*
\firstmark . T80, Y649, Y708, Y2253, *791*
flag internal commands:
\flag␣__filehook_file_replaced . *892*
flag␣__filehook_file_replaced . W418
flag commands:
\flag_clear:n ... W422
\flag_if_raised:nTF ... W420, W441
\flag_new:n ... W418
\flag_raise:n ... W442
\flat ... B328
\floatingpenalty ... P469, P488, P506
\floatpagefraction ... P278, Y2334
\floatsep ... Y728, Y746, Y753, Y2140, Y2190, Y2339
\flushbottom ... T84
flushleft (env.) ... H401
\flushleft ... H401
flushright (env.) ... H403
\flushright ... H403
\fmtname ... c1, c38, c40, c43, c45, c48, c57, U684, U688, *1027*
\fmtversion . c1, c19, c38, c40, c43, c45, c48, c57, c102, c115, c163, s1538, d276, A225, L1, M1, U169, U176, U701, U704, Y4, aa594, aa620, l2, *1027*
\fnsymbol ... *400*
\fnsymbol ... t141
\font ... s297, s298, s299, s439, s446, s799, s806, s866, s1003, s1004, s1060, s1165, s1167, s1169, s1216, v81, v87, v89, x84, A553, A586, A592, A618, C8, C9, C10, D85, E6, E612, E626, E633, H454, f737, f740, f752, f755, b506, b511
\fontdimen ... s297, s298, s299, s439, s446, s799, s806, A553, A586, A592, D85, E6, E612, E626, E633, M126, M129, M679, b506, b511
\fontencoding . s867, s1569, v251, v286, v298, v308, z347, d259, d260, d282, d283, A658, A676, A692, B16, B24, B67, B74, B83, B85, E36, *1039*
\fontfamily . v279, A6, A9, A12, A145, A156, A482, A485, A488, A738, B58, B69, B76, B87, E28, E30, E32, E34, E85, E87, E89, E91, E916, *1024*
\fontname ... s1004, v89
\fontseries ... v279, w393, w394, w405, w407, w417, w419, A15, A18, A258, A259, A260, A261, A281, A282, A283, A284, A319, A320, A321, A322, A339, A340, A341, A342, A355, A356, A357, A358, A366, A367, A368, A369, A382, A385, A476, A479, A739, *532*
\fontseriesforce . w398, w409, w420, *446*
\fontshape ... s449, s809, v279, w528, w533, w538, w614, w615, w624, w626, w631, w633, w684, w688, w691, w694, w697, w700, w703, w706, w713, A21, A24, A27, A30, A740, E636, *462*
\fontshapeforce . w618, w627, w634, w714
\fontsize ... q6, s302, s328, s360, s868, s1218, s1254, v79, v318, A641, A741, E104, E672, E933, P409, P416, P437, P444, *1039*
\fontsubfuzz .. x441, x475, H42, H82, *1036*
\FOO ... *79*
\foo ... *265*
\footins P390, P465, P484, P502, Y314, Y315, Y316, Y317, Y375, Y422, Y484, Y492, Y496, Y519, *1053*
\footnote ... P452, *1023*
\footnotemark ... O10, P518, *1023*
\footnoterule ... K360, P394, Y495, *1053*
\footnotesep K384, K401, K418, P451, P468, P477, P487, P495, P505, P513
\footnotesize ... K376, K394, K411, P466, P485, P503
\footnotetext ... O12, P535, *1023*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\footref P547, *1084*
\footskip Y77, Y639, Y698
\forall B323
fp commands:
  \fp_eval:n e159
\fpeval *76*
\fpeval e155, e167, e169, *76*
\frac I341, *1029*
\frame K157, K233
\framebox *670*
\framebox K180, *1044*
\frenchspacing r46, r115, r173, H459, H485, H575, f777, f798, b398
\frown B451
\fussy T93
\futurelet p410, p418, D83, I243, L359, e49, f677, f691

G

\g_@@_\meta␣{hook}_code_prop *207*
\Gamma B297
\gamma B270
\gcd I33
\gdef *1042*
gdef commands:
  \gdef_ I256
\ge B417, B419
\Generic* *1047*
\GenericError x62, l18, l85, l111, l164, *1043*
\GenericInfo c103, c105, c116, c119, c124, c159, c160, c165, c169, c173, c194, x31, x34, x39, x75, e63, U66, U74, U104, U107, U1611, l4, l104, l130, l182, *1043*
\GenericWarning x42, x47, x50, x78, l11, l94, l120, l141, l149, l173, l195, *1043*
\geq B415, B417
\getanddefinefonts *1021*
\GetDocumentCommandArgSpec g2636
\GetDocumentEnvironmentArgSpec . . g2636
\GetFileInfo B3
\gets B439, B441
\gg B433
\gloassary *1077*
\global *1061*
\globaldefs v593, x231, z60, z89, z160, z228, z258, z290
\glossary *783*
\glossary O182, Q23, Q35, S163, T25, T36, T53, T61, Y623, Y682, *792*
\glossaryentry Q32
\goodbreak f778, f799, b478
\grave B517
\group *1021*
group commands:
  \group_align_safe_begin/end: . . *153*
  \group_align_safe_begin: g218, g230, g335, *119*
  \group_align_safe_end: g252, g358, g1621, *116*
  \group_begin: z200, S49, S138, V4, W210, W224, X92, g1614, g1971, g1976, g2095, g2099, g2127, h225, i198, n15, n21
  \c_group_begin_token g595, g606, g1619, g1700, g2206
  \group_end: z203, S110, S152, V20, W220, W232, X94, g1634, g1980, g1985, g2109, g2110, g2112, g2114, g2124, g2131, g2132, h228, i202, n17, n25
  \c_group_end_token g598, g1689
  \group_insert_after:N z186, z187, z190, z211, z212, *494*
\guillemetleft . . . s540, s773, s1104, *1075*
\guillemetright . . s541, s774, s1120, *1075*
\guillemotleft s543, s776, s1106
\guillemotright s544, s777, s1122
\guilsinglleft s545, s1183
\guilsinglright s546, s1184

H

\H s230, s385, s469, s601, s609, s628, s636, s753, s1246, s1385, s1386, s1413, s1414, E177, E201, l24
\halign . . . I127, I197, I358, I505, b501, *89*
\hang *1052*
\hangindent O139
\hat B523
\hbadness v647, v654, v689, v708, X236, X238, X288, X290, b318
\hbar B335
\hbox *903*
hbox commands:
  \hbox:n X380
  \hbox_set:Nn X168, X215, X241, X266, X295
  \hbox_set_to_wd:Nnn X239, X291, X327
  \hbox_unpack:N S291, S322, X249, X293
  \hbox_unpack_drop:N X178
\hbox␣to␣ *1036*
\headheight Y75, Y628, Y687
\headsep Y76, Y637, Y696
\heartsuit B333
\height s872, s1222, K31, K34, *1028*
\hfil *656*
\hfill *1024*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\hfuzz v655, T89, T90, T96, T97, X235, X237, X287, X289, b373
\hglue b468
\hideoutput b659
\hideskip b309, b492
\hidewidth s327, s329, s358, s362, s390, s391, s394, s397, s476, s477, s481, s484, s486, s489, s501, s506, s522, s760, s761, s764, s767, s834, s837, s1253, s1255, b492
\hline L358, L361, *1025*
\holdinginserts b335
\hom I29
hook commands:
\hook_activate_generic:n . . h145, h146, h147, h165, h167, h1451, h1452, h1456, h1518, h1537, h1550, *212*
\hook_debug_off: . . h7, h13, h1496, *193*
\hook_debug_on: . . h7, h8, h1495, *193*
\hook_disable:n h1506, h1506
\hook_disable_generic:n h121, h122, h123, h140, h142, h1453, h1511, h1543, *191*
\hook_gclear_next_code:n h1148, h1148, h1466, *192*
\hook_gput_code:n *210*
\hook_gput_code:nnn h323, h323, h376, h393, h1462, *192*
\hook_gput_next_code:nn h383, h398, h1123, h1123, h1464, *192*
\hook_gremove_code:nn h602, h602, h1468, *193*
\hook_gset_rule:nnnn h637, h637, h1498, h1500, h1503, *226*
\hook_if_empty:n h1262
\hook_if_empty:nTF X63, X162, h1000, h1262, h1504, *185*
\hook_if_empty_p:n X67, X113, X375, h1045, h1262, *193*
\hook_log:n . . . h971, h971, h1494, *193*
\hook_new:n S165, X152, X153, X154, X155, X156, X157, h68, h68, h108, h506, h1447, *246*
\hook_new_pair:nn h107, h107, h1449, n6, n7, *191*
\hook_new_reversed:n h100, h100, h108, h1448, *191*
\g_hook_patch_action_list_tl i6, i90, i123
\hook_provide:n h1506, h1513
\hook_provide_pair:nn . h1506, h1527
\hook_provide_reversed:n h1506, h1520
\hook_show:n . . h971, h976, h1493, *193*
\hook_use:n n56, n63, S140, X62, X65, X71, X75, h761, h1152, h1152, h1154, h1171, h1173, h1491, n20, n28, *210*
\hook_use_once:n h1228, h1228, h1492, *244*
hook internal commands:
\g__hook_??_code_prop h634
\g__hook_??_reversed_tl h634
\g__hook_⟨*hook*⟩_code_prop *245*
\g__hook_⟨*hook*⟩_labels_clist . . . *210*
\g__hook_⟨*hook*⟩_reversed_tl . . . *207*
__hook_activate_generic:n . . . h145
__hook_activate_generic:nn h148, h149, h1535
__hook_activate_generic_pair:nn h1506, h1532, h1536, h1564
__hook_activate_generic_-reversed:n h1506, h1525, h1534, h1537, h1557
\g__hook_all_seq h28, h83, h750
__hook_apply_-rule_->:nnn . . . h946
__hook_apply_-rule_<-:nnn . . . h946
__hook_apply_-rule_<:nnn h946
__hook_apply_-rule_>:nnn h946
__hook_apply_-rule_xE:nnn . . . h946
__hook_apply_-rule_xW:nnn . . . h946
__hook_apply_label_pair:nnn h818, h819, h873, h873, *232*
__hook_apply_rule:nnn h883, h889, h889, *234*
__hook_apply_rule:nnnN *235*
__hook_apply_rule_->:nnn h924
__hook_apply_rule_<-:nnn h924
__hook_apply_rule_<:nnn h896
__hook_apply_rule_>:nnn h896
__hook_apply_rule_xE:nnn h910
__hook_apply_rule_xW:nnn h910
__hook_clean_to_scan:w h39, h39, h651, h657, h1253, h1298
__hook_clear_next:n h1145, h1148, h1149, h1150
__hook_clist_gput:Nn h782, h784, h842, h871, h872
__hook_cmd_begindocument_code: i45, i53, i58, i61, i422, *274*
__hook_cmd_if_scanable:Nn i345
__hook_cmd_if_scanable:NnTF i323, i345, *272*
__hook_cmd_patch_xparse:Nnn i127, i148, i148
__hook_cmd_try_patch:nn i51, i62, i62
\l__hook_cur_hook_tl h29, h804, h930, h941, *236*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__hook_curr_name_pop: h255, h287, h1484, h1578, *216*
__hook_curr_name_push:n h255, h269, h1482, h1487, *216*
__hook_curr_name_push_aux:n h255, h270, h271
__hook_currname_or_default: h173, h181, h185, h201, h202, h202, h350, h1363, h1407, *213*
__hook_debug:n h7, h7, h20, h344, h749, h754, h766, h788, h823, h843, h898, h905, h912, h920, h926, h937, i18, i27, i38, i47, i48, i64, i68, *204*
\g__hook_debug_bool h6, h10, h15, h21
__hook_debug_gset: h7, h11, h16, h18
__hook_debug_label_data:N h823, h864, h959, h959
__hook_debug_print_rules:n h1107, h1107
__hook_declare_deprecated_generic:NNn h437, h458
__hook_declare_deprecated_generic:NNw h453, h459, h460
__hook_def_cmd:w i12, i13, i189, i195, i220, *267*
\g__hook_delayed_patches_prop i16, i50, i56, i57
__hook_deprecated_generic_warn:n h436, h443, h628, h648, h679, h989, *221*
__hook_deprecated_generic_warn:Nn h443
__hook_deprecated_generic_warn:Nw h443
__hook_deprecated_generic_warn:w h444, h445
__hook_deprecated_warn:nn h1508, h1515, h1522, h1529, h1540, h1547, h1554, h1561, h1566, h1566
__hook_disable:n .. h121, h124, h125
__hook_do_deprecated_generic:Nn .. h453, h453, h629, h649, h680, h990
__hook_do_deprecated_generic:Nw h453, h454, h455
__hook_double_hashes:n i185, i246, i246, i280, *268*
__hook_double_hashes:w i246, i247, i248, i276, i280, i283, *268*
__hook_double_hashes_group:n i246, i254, i279
__hook_double_hashes_output:N i246, i251, i259, *269*
__hook_double_hashes_space:w i246, i255, i282
__hook_double_hashes_stop:w i246, i262, i278
__hook_end_document_label_check: h255, h294, h295, h302
__hook_exp_not:n i168, i169, i173, i184, *266*
__hook_exp_not:NN i12, i12, i190, i196, i212, i214
__hook_file_hook_normalize:n h405, h554, h554, h557, h559, h1215, *223*
\l__hook_front_tl h795, h834, h837, h840, h842, h843, h844, h857, h858
\c__hook_generic_⟨*type*⟩/./⟨*place*⟩_tl *220*
\c__hook_generic_class/./after_tl h570
\c__hook_generic_class/./before_tl h570
\c__hook_generic_cmd/./after_tl h570
\c__hook_generic_cmd/./before_tl h570
\c__hook_generic_env/./after_tl h570
\c__hook_generic_env/./before_tl h570
\c__hook_generic_env/./begin_tl h570
\c__hook_generic_env/./end_tl . h570
\c__hook_generic_file/./after_tl h570
\c__hook_generic_file/./before_tl h570
\c__hook_generic_include/./after_tl h570
\c__hook_generic_include/./before_tl h570
\c__hook_generic_include/./end_tl h570
\c__hook_generic_package/./after_tl h570
\c__hook_generic_package/./before_tl h570
\c__hook_generics_file_prop h546, h593
\c__hook_generics_prop h476, h504, h570, h588, h590
\c__hook_generics_reversed_ii_prop h484, h507, h593
\c__hook_generics_reversed_iii_prop h487, h510, h593
__hook_gput_code:nnn h323, h324, h325
__hook_gput_next_code:nn h1124, h1125, h1125
__hook_gput_next_do:nn h384, h398, h1125, h1131, h1135, *219*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__hook_gput_next_do:Nnn h1125, h1137, h1140
__hook_gput_undeclared_hook:nnn h366, h366, h377, h393, *219*
__hook_gremove_code:nn h602, h603, h604, h629
__hook_gset_rule:nnnn h637, h639, h642, h644, h649, h673, h675, h680
\c__hook_hash_tl i11, i176, i177, i179, i264, *269*
\g__hook_hook_curr_name_tl h32, h204, h214, h255, h267, h282, h283, h290, h300, h301, h321, *215*
__hook_hook_gput_code_do:nnn h115, h323, h332, h342, h369
__hook_if_declared:n h1290
__hook_if_declared:nTF h72, h154, h506, h1290, i66, *209*
__hook_if_declared_p:n h1290
__hook_if_deprecated_generic:n h1313
__hook_if_deprecated_generic:nTF . h434, h626, h646, h677, h987, h1305
__hook_if_deprecated_generic:w h1314, h1315
__hook_if_deprecated_generic_p:n h1305
__hook_if_disabled:n h130
__hook_if_disabled:nTF ... h121, h151, h336, h998, h1071, h1127, *208*
__hook_if_disabled_p:n h121
__hook_if_execute_immediately:n h1249
__hook_if_execute_immediately:nTF h327, h653, h1230, h1249
__hook_if_execute_immediately_p:n h1249
__hook_if_file_hook:w h520, h522, h534, h536
__hook_if_file_hook:wTF h402, h520, h1212, *223*
__hook_if_file_hook_p:w h520
__hook_if_generic:n h1305
__hook_if_generic:nTF h421, h525, h995, h1305
__hook_if_generic:w .. h1306, h1307
__hook_if_generic_p:n h1305
__hook_if_generic_reversed:n h1325
__hook_if_generic_reversed:nTF h159, h429, h1325
__hook_if_generic_reversed:w h1326, h1327
__hook_if_generic_reversed_p:n h1325
__hook_if_has_hash:n i232
__hook_if_has_hash:nTF i166, i232, *268*
__hook_if_has_hash:w i232, i233, i234, i240, i242
__hook_if_has_hash_check:w i232, i239, i244
__hook_if_has_hash_p:n i232
__hook_if_label_case:nnnnn h739, h739, h816, h1085
__hook_if_public_command:N i107, *263*
__hook_if_public_command:NTF i76, i86
__hook_if_public_command:w i76, i110, i116
__hook_if_reversed:n h1296
__hook_if_reversed:nTF h780, h1014, h1051, h1053, h1296
__hook_if_reversed_p:n h1296
__hook_if_structure_exist:n h1284
__hook_if_structure_exist:nTF h93, h606, h1130, h1264, h1284, h1438, *209*
__hook_if_structure_exist_p:n h1284
__hook_if_usable:n h1278
__hook_if_usable:nTF h330, h345, h423, h478, h622, h769, h996, h1013, h1069, h1251, h1278, h1505, *209*
__hook_if_usable_p:n . h1044, h1278
__hook_if_usable_use:n h1199, h1214, h1217, h1219, *243*
__hook_include_legacy_code_chunk:n h88, h109, h109, h768
__hook_init_structure:n ... h85, h91, h91, h352, h368, h659, h684, *210*
__hook_initialize_all: h747, h747, h1576
__hook_initialize_hook_code:n h748, h764, h764, h1169, h1196, *234*
__hook_initialize_single:NNn h786, h800, h800, h870, *229*
\l__hook_label_0_tl h795
__hook_label_if_exist_apply:nnnTF h873, h875, h877, h880, *240*
__hook_label_ordered:nn .. h731, *229*
__hook_label_ordered:nnTF h700, h706, h712, h731, *228*
__hook_label_ordered_p:nn ... h731
__hook_label_pair:nn h699, h705, h711, h715, h718, h722, h723, h723, h955, h956, *228*
\l__hook_labels_int h795, h803, h807, h839, h860, *234*
\l__hook_labels_seq h795, h802, h808, h826, h961

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__hook_list_if_rule_exists:nnnTF h1078, h1095, h1096, h1098
__hook_list_one_rule:nnn h1078, h1087, h1088, h1093
__hook_list_rules:nn h1031, h1078, h1078, h1112, *240*
__hook_log:nN h971, h974, h979, h985, h990
__hook_log_cmd:n h973, h978, h982, h984, h994
__hook_log_line:n h971, h981, h997, h999, h1003, h1010, h1022, h1029, h1047, h1066
__hook_log_line_indent:n h971, h983, h1005, h1008, h1016, h1023, h1034, h1042
__hook_log_next_code:n h1027, h1076, h1076
__hook_make_name:n h195, h201, h210, h216, h216, h270, h312, *214*
__hook_make_name:w h216, h218, h222
__hook_make_prefixes:w i153, i204, i224, i229
__hook_make_usable:n h76, h79, h79, h157, h427, h482, *220*
__hook_msg_pair_found:nnn h898, h905, h912, h920, h928, h939, h952, h952
\g__hook_name_stack_seq h32, h256, h257, h261, h268, h282, h289, h297, h307
__hook_new:n ... h68, h69, h70, h104
__hook_new_reversed:n h100, h101, h102
__hook_next␣⟨*hook*⟩ *225*
__hook_normalize_hook_args:Nn .. h69, h101, h124, h148, h223, h232, h974, h979, h1124, h1149, h1231, h1535
__hook_normalize_hook_args:Nnn . h223, h237, h324, h603
__hook_normalize_hook_args_-aux:Nn h223, h223, h234, h239, h247
__hook_normalize_hook_rule_-args:Nnnnn h223, h245, h639
\l__hook_param_text_tl i8, i172, i193, i221, *267*
__hook_parse_dot_label:n h174, h176, h176
__hook_parse_dot_label:w h176, h186, h189
__hook_parse_dot_label_aux:w ... h176, h192, h200
__hook_parse_dot_label_cleanup:w h176, h196, h199
__hook_parse_label_default:n ... h170, h170, h235, h241, h242, h249, h250, h252
__hook_patch_check:NNnn i76, i80, i83, i86, i96
__hook_patch_cmd_or_delay:Nnn .. i28, i41, i45, i45, i55, *261*
__hook_patch_command:Nnn i55, i73, i76, i76, *262*
__hook_patch_debug:n i17, i17, i78, i79, i82, i85, i88, i155, i286, i322, i325, i326, i331
__hook_patch_DeclareRobustCommand:Nnn i125, i129, i129, *264*
__hook_patch_DeclareRobustCommand_-aux:Nnn i131, i134
__hook_patch_expand_redefine:NNnn . i140, i145, i150, i153, i153, i288, *264*
__hook_patch_newcommand:Nnn ... i126, i139, i143, i143, *264*
\l__hook_patch_num_args_int i7, i156, i161, i164, i178
\l__hook_patch_prefixes_tl i8, i203, i219, *267*
__hook_patch_required_catcodes: i336, i336, i357, i383, *273*
__hook_patch_retokenize:Nnnn ... i327, i362, i362, *271*
__hook_preamble_hook:n h762, h993, h1152, h1158, h1168, h1177, h1195, h1223, h1235, *242*
\l__hook_rear_tl h795, h824, h830, h831, h853, h854
__hook_redefine_with_hooks:Nnnn i153, i208, i217, *267*
\l__hook_replace_text_tl i8, i173, i180, i181, i182, i187, i194, i214, *265*
__hook_retokenize_patch:Nnn ... i91, i284, i284
\l__hook_return_tl h25, h289, h290, h297, h301, h358, h361, h618, h840, h841
__hook_rule_<_gset:nnn h697
__hook_rule_>_gset:nnn h697
__hook_rule_after_gset:nnn h697, h703, h708
__hook_rule_before_gset:nnn ... h697, h697, h702, *232*
__hook_rule_gclear:nnn h660, h685, h720, h721, *228*
__hook_rule_incompatible-error_-gset:nnn h714
__hook_rule_incompatible-warning_-gset:nnn h714

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__hook_rule_unrelated_gset:nnn h720, h720, *228*
__hook_rule_voids_gset:nnn h709, h709
__hook_seq_csname:n h793, h794, h810, h844, h901, h908, h966
__hook_set_default_hook_label:n h305, h305, h1470
__hook_set_default_label:n h305, h312, h314
__hook_str_compare:nn h23, h23, h725, h733, h742
__hook_strip_double_slash:n h554, h560, h561
__hook_strip_double_slash:w h554, h562, h563, h567
__hook_tl_csname:n h793, h793, h799, h809, h825, h828, h830, h834, h846, h848, h851, h853, h858, h899, h900, h906, h907, h965
__hook_tl_gclear:N h65, h65, h67, h117, h611, h612, h616, h835, h1244, h1245, h1246
__hook_tl_gput:Nn h781, h783, h841, h867, h871, h871, *234*
__hook_tl_gput_left:Nn h58, h58, h63, h781
__hook_tl_gput_right:Nn h55, h55, h57, h353, h783, h868, h1146
__hook_tl_gset:Nn h46, h46, h48, h50, h52, h53, h54, h56, h60, h699, h705, h711, h715, h718, h773, h1145, h1241
__hook_tl_gset_eq:NN . h64, h64, h66
__hook_tl_set:Nn h40, h40, h42, h44, h45, h809, *206*
__hook_tmp:w h34, h34, h258, h262, h264, h1080, h1101, h1110, h1121, i170, i176, i177, i179, i348, i351, i355, i365, i368, i381, *273*
\l__hook_tmpa_bool h24, h1030, h1033, h1041, h1050, *238*
\l__hook_tmpa_tl h25, h268, i163, i165, i167, i290, i305, i308, i354, i357, i380, i383
\l__hook_tmpb_tl . h25, i295, i306, i309
__hook_toplevel␣⟨*hook*⟩ *218*
__hook_try_declaring_generic_-hook:nnn h338, h371, h371, h373, h388, h390, *219*
__hook_try_declaring_generic_-hook:nNNnn h392, h397, h400, h400, *219*
__hook_try_declaring_generic_-hook:wn h416, h418, h468, h470, h496, h498
__hook_try_declaring_generic_-hook:wnTF h375, h382, h411, h416, h463, *221*
__hook_try_declaring_generic_-hook_split:nNNnn h400, h404, h407, h409
__hook_try_declaring_generic_-next_hook:nn h371, h380, h395, h1132, *219*
__hook_try_file_hook:n h1199, h1207, h1210, *243*
__hook_try_patch_with_catcodes:Nnnnw i302, i319, i319, i332, *270*
__hook_try_put_cmd_hook:n h426, h481, i20, i20, i22, i31, i33
__hook_try_put_cmd_hook:w i20, i23, i24, i34, i35
__hook_unpatchable_cases:n i407, i409
__hook_update_hook_code:n h333, h623, h664, h689, h746, h746, h748, h752, h1143, *229*
__hook_use:wn h1180, h1193, h1199, h1199, h1202, h1204, *243*
__hook_use_end: h1152, h1188, h1190, h1197
__hook_use_initialized:n h761, h1152, h1162, h1182, h1237, *242*
__hook_use_once:n h1228, h1231, h1233
__hook_use_once_clear:n h1238, h1240, h1242, *244*
__hook_use_once_set:n h1236, h1240, h1240, *244*
__hook_use_undefined:w h1152, h1186, h1190
\g__hook_used_prop h31, h749, h756, h789
\l__hook_work_prop h30, h785, h805, h812, h814, h823, h840, h864, h933, h944, *232*
hook␣?? internal commands:
__hook␣?? *226*
hook␣⟨*hook*⟩ internal commands:
__hook␣⟨*hook*⟩ *230*
\hookleftarrow B480
\hookrightarrow B478
hook ?? internal commands:
__hook~?? h634
\hphantom I75
\hrule p350, p358, p384, p392, s289, s294, B340, B618,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

K163, K168, K216, K226, L359, L376, M590, M600, P395, b469, b513
\hrulefill f779, f800, b513
\hsize *1065*
\hskip *1024*
\hskip... . . . . *1061*
\hspace p437, p441, p446
\hss *917*
\Hwithstroke s494, s1213, *1076*
\hwithstroke s510, s1214, *1076*
\hyphenation s205, *1048*
\hyphenchar H454, f737, f740, f749, f752, f755, f760, *1074*
\hyphenpenalty v661, v693, b321

I

\I U1220, U1352, U1442, U1462, aa255, aa555, b404
\i s247, s402, s452, s453, s454, s455, s456, s457, s547, s587, s588, s680, s682, s684, s686, s778, s1140, s1295, s1297, s1299, s1301, s1352, s1355, s1358, s1361, s1431, aa259, aa559, aa572, *1067*
\ialign B337, B459, B530, B533, B537, B540, I155, I157, I176, L191, M141, b501, b503, *1026*
\IeC aa357, aa361, aa468
\if *1060*
if commands:
  \if:w h1254, h1299, *244*
  \if_case:w g1241, h725, h742
  \if_catcode:w i269, *269*
  \if_charcode:w g838, h1329
  \if_cs_exist:w h448, h882, h1100, h1164, h1184
  \if_false: g773, g776
  \if_int_compare:w n59, h733
  \if_meaning:w W241, g1155, i261, i264
  \if_mode... . . . . *305*
  \if_mode_horizontal: n29
\if... . . . . *868*
\IfBlankF g2617
\IfBlankT g2617
\IfBlankTF R19, g2617, *1089*
\IfBold *534*
\IfBooleanF t82, t90, g2592
\IfBooleanT g2592
\IfBooleanTF . . G29, G31, G76, g2592, *178*
\IfClassAtLeastTF *821*
\IfClassAtLeastTF U165
\IfClassLoadedTF *821*
\IfClassLoadedTF U261
\IfClassLoadedWithOptionsTF *821*
\IfClassLoadedWithOptionsTF U261
\ifcsname w440, w443, w653, w656, x128, z153, A42, A53, A75, A86, U1109, U1240, X431, Y1905, f635, f652, *448*
\ifdefined . b601, A623, e22, e71, e72, e73, e74, e117, e118, e119, aa319, b537
\IfDocumentMetadataTF o5, o17
\iff B500
\IfFileExists *332*, *822*
\IfFileExists r468, r480, r582, r638, r663, a181, e37, e68, e114, U835, W149, W185, W195, aa588, *1033*
\iffontchar s866, s1060, s1165, s1167, s1169, s1216
\IfFontSeriesContextTF A496, A532, A534, *534*
\IfFormatAtLeastTF *821*
\IfFormatAtLeastTF U165, *886*
\IfHookEmptyTF . . H210, h1504, h1607, *189*
\IfHookExistsTF h1505, h1606, *252*
\ifincsname *872*
\ifinner I264, I272, I292, I319, P57, P126, P315
\IfMarksEqualTF S280, S380, *794*
\ifmmode *1021*
\IfNoValueF g2611
\IfNoValueT g2611
\IfNoValueTF g2611
\ifnum *902*
\ifodd z1064, M320, M344, M378, M400, P68, P137, Y21, Y138, Y612, Y670, Y984, Y987, Y1020, Y1023, Y1134, Y1137, Y1296, Y1299, Y1576, Y1579, Y1697, Y1700, Y1820, Y2075, Y2083
\IfPackageAtLeastTF *821*
\IfPackageAtLeastTF U165
\IfPackageLoadedTF *821*
\IfPackageLoadedTF U261
\IfPackageLoadedtTF U264, U272
\IfPackageLoadedWithOptionsTF *821*
\IfPackageLoadedWithOptionsTF . . . U261
\IfPDFManagementActiveTF . . . aa647, *1019*
\IfTargetDateBefore U1670
\ifthenelse *614*
\IfValueF g2614
\IfValueT g2614
\IfValueTF g2614
\ifvbox . . . Y319, Y376, Y423, Y504, Y520
\ifvoid *1062*
\ifx *538*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\ignorespaces p49, p143, p162, p174, p185, p201, p214, p483, r71, r138, r193, s72, v292, v302, v312, H216, H223, H274, H289, H337, H342, H348, I300, I327, J55, J217, K154, K384, K401, K418, L57, L62, L68, L83, L92, L105, L109, L116, L123, L125, L134, L154, L237, L301, L303, L305, L332, M36, M46, M66, M75, M109, M120, M131, M143, M148, M154, N30, N32, O110, P17, P24, P477, P495, P513, R7, R9, X328, *201*
\ignorespacesafterend H7
\IJ . . . s250, s436, s550, s1141, aa585, *1087*
\ij . . . s249, s434, s549, s1142, aa585, *1069*
\Im B314
\imath B309
\immediate *202*
\in B429, B461
in commands:
in_callback d798
\in_callback *48*
\include *332*
\include r217, r265, r267, r283, r285, r344, r396, *201*
include/.../after *878*
include/.../before *878*
include/.../end *878*
include/after *878*
include/before *878*
include/end *878*
\IncludeInRelease b548, n125, o31, p5, p21, p54, p65, p81, p86, p98, p104, b582, p132, p152, p166, p178, b589, p191, p206, p235, p252, p271, p307, p333, p366, p426, b615, p432, p440, p445, p459, p465, r10, r83, r141, r219, r256, b655, r277, r292, b660, r353, r402, b670, r463, r473, r499, r519, r537, r547, r563, r588, r593, r601, r615, r626, r642, r675, s77, s104, s148, s169, s324, s332, s353, s369, c68, c177, c181, c185, c189, t24, t30, t46, t69, t77, t99, t126, t161, t177, t185, t203, u5, u11, v24, v53, v210, v232, v284, v295, v305, v420, v431, v439, v471, v479, v493, d3, v514, v550, v637, v699, w2, w385, w392, w404, w416, w424, w506, w522, w600, w613, w623, w630, w638, w710, w729, w735, w739, x113, x158, x161, x541, x550, y2, y22, z49, z78, z138, z217, z247, z278, z357, z365, d235, z698, d258, z746, z792, z801, d281, z985, z996, A33, A68, A101, A126, A228, A252, A301, A348, A377, A395, A435, A469, A498, A531, A543, A577, A590, A621, A630, A655, A672, A688, A705, B63, B81, B100, B110, B622, B634, D27, D34, E607, G21, G38, G62, G79, G91, G102, H10, H65, H107, H112, H124, H151, H170, H226, H276, H301, H309, H322, H328, H340, H345, H355, H374, H391, H415, H437, H464, H489, H502, H517, H533, H556, H566, I79, I87, I109, I118, I139, I144, I152, I163, I203, I220, I259, I267, I277, I304, I386, I395, I435, I447, I459, I468, J125, J133, K4, K14, K50, K70, K91, K102, K117, K125, K181, K189, K235, K244, K281, K303, K371, K389, K405, K425, K431, K451, K459, L60, L65, L137, L157, L222, L227, e2, e11, M10, M16, M26, M39, M55, M69, e20, M80, M89, M100, M112, M146, M151, M160, M172, M235, M250, M311, M369, e58, M455, M464, M473, M501, M531, M558, M572, M585, M596, M608, M625, M645, M652, M686, M746, M804, M820, O5, O20, e112, O161, O168, O174, O186, O193, O202, O225, e133, P35, P105, e145, P206, P232, P280, P294, P335, P352, e156, P406, P412, P420, P427, P434, P440, P446, e166, P463, P482, P499, P549, P559, e175, R14, R25, R61, R77, e189, f5, f13, S372, T20, T48, T69, U18, U23, U36, U51, U63, U87, U95, U101, U126, U144, U167, U174, U185, U198, U224, U243, U263, U271, U282, U298, U312, U330, U343, U359, f56, U379, U402, U418, f62, U447, U459, U491, U509, U529, U547, U566, U576, U586, U598, U630, U641, U655, U665, U721, U751, U778, U810, U956, U1036, U1043, U1097, U1228, U1359, W5, W15, W27, W89, W144, W181, W192, W205, W249, W257, W269, W300, W323, W344, W358, W366, W389, W409, W434, W480, W492, W503, W530, f272, X3, f314, X428, X468,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

X482, Y24, Y54, f342, Y151, Y179, Y345, Y366, Y371, f370, Y419, f377, Y593, f394, Y653, Y796, f410, Y814, Y875, Y896, Y932, Y956, Y1068, Y1219, f448, Y1388, a21, Y1470, f460, Y1564, Y1686, Y1900, f488, Y1923, Y1937, Y1965, f499, a293, Y2196, Y2214, f511, Y2233, Y2279, f518, aa8, aa16, aa23, aa30, aa37, aa52, aa71, aa80, aa87, aa106, aa143, aa166, aa199, aa288, aa293, aa314, aa339, aa348, aa441, f614, f631, a310, f661, f702, f721, f732, f749, f760, f771, f791, a26, b49, b88, g983, b103, g1159, g1162, b119, b125, g1306, b134, b139, b148, b154, b168, b182, b186, b220, b228, b233, b244, g2617, g2623, g2651, b289, h121, h139, h145, h164, b347, h371, h388, b357, h416, h468, h496, h520, h534, h554, h557, h570, h588, h593, h596, h642, h673, b421, h1152, h1171, h1199, h1202, h1450, h1455, b439, h1580, i20, i31, i386, i389, i419, l138, l158, l192, l205, b524, *1071*

`\includeonly` *332*

`\includeonly` r217, r257, r259, r278, r279, *878*

`\indent` p462, J161, L81, *307*

`\IndentBox` n49, n129, *299*

`\index` *783*

`\index` O182, Q6, Q18, S162, T25, T36, T53, T61, Y622, Y681, *804*

`\indexentry` Q15

`\inf` I25

`\infty` B316

`\initcatcodetable` d91

`\input` *332*, *822*

`\input` r598, d18, x16, y106, A751, A761, A771, B10, B11, B12, B13, B14, B23, B41, B42, B46, B47, B136, B137, B138, B139, B654, B655, B656, a177, a180, E1129, e108, e130, f22, a237, U615, aa164, aa178, aa203, aa281, aa325, aa405, aa593, a71, *888*

`\input@path` *6*, *1*

input@path commands:

`\input@path:` a242

`\inputencodingname` aa382, aa404, aa486, *1075*

`\InputIfFileExists` *332*, *822*

`\InputIfFileExists` o7, r581, r604, r619, r629, r639, r693, s1546, v391, A743, A753, A763, E845, E1212, U921, U987, W143, Z8, aa275, *845*

`\inputlineno` a330, l214, *1035*

`\insert` P465, P484, P502, Y519, Y520, Y1885, b254, b279, b281, b284, b299, *295*

`\InsertMark` S271, S376, *204*

`insertmark` S160, *792*

`\int` B348

int commands:

`\int_add:Nn` g520, g1104

`\int_compare:nNnTF` z194, S58, S68, S74, X55, X111, X141, X351, X357, X365, g388, g515, g770, g812, g1692, g1995, g1997, h828, h850, h860, h1342, i161, i292

`\int_decr:N` g467, g481, g495, g1691, h839

`\int_eval:n` e160, X353, g2009, h847, h900, h907

`\int_gdecr:N` W556

`\int_gincr:N` . W546, X87, X102, g967

`\int_gset:Nn` z199, W542

`\int_if_odd:nTF` S305, S355

`\int_incr:N` g292, g411, g784, g849, g856, g1071, g1302, g1701, h807, *140*

`\int_new:N` W541, X344, X346, g15, g27, g35, g1671, h796, i7

`\int_set:Nn` . . . W212, W226, g989, g999, g1168, g1177, g1227, g1675, g2102, g2128, i156, i199, i342, i343

`\int_set_eq:NN` S51

`\int_step_inline:nnn` i164, i178

`\int_use:N` z182, z183, z185, z194, W550, X104, X116, X361, X369, g25, g815, g971, g999, g1089, g1093, g1094, g1177, g1293, *902*

`\int_value:w` X48, X136

`\int_zero:N` g283, g377, g690, g693, g819, g1063, h803

`\c_max_int` S51, X212, X238, X263, X290

`\c_zero_int` X91, i161

`\interdisplaylinepenalty` p13, I55, I194, I380

`\interfootlinepenalty` b394

`\interfootnotelinepenalty` p18, P467, P486, P504, b394

`\interlinepenalty` p11, v663, H426, H429, H447, H450, O67, O118, O209, O232, P467, P486, P504, Y338, Y1155, Y1159, Y1321, Y1325, *1023*

`\inteval` *76*

`\inteval` e155, e170, *76*

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

\intextsep Y1138, Y1142, Y1157, Y1160, Y1167, Y1300, Y1306, Y1323, Y1326, Y1335, Y2339
\intop B347, B348
\iota B276
iow commands:
  \iow_char:N n111, n118, n119, n120, n121, g399, g463, g548, g617, g629, g660, g1009, g1015, g1676, g2403, g2493, h930, h941, h1357, h1393, h1401, h1413, h1418, h1423, h1570, h1572, i397
  \iow_log:n h973
  \iow_newline: W554, g1193, g1203, g1300
  \iow_now:Nn X360
  \iow_term:n S20, S143, W547, W580, h344, h755, h757, h767, h843, h862, h863, h865, h929, h940, h954, h960, h961, h962, h965, h969, h978, h1109, h1114, i18, i27, i38, i47, i49, i65, i69
\ishortstack M132
\itdefault w697, A30, B94
\item H351, H401, H403, H417, H439, I442, I454, I481, J141, J219, L78, N36, N38, R4, R8, l280, *1030*
\itemindent .. J9, J42, J95, J187, J208, *656*
\itemitem *1023*
itemize (env.) J242
\itemize J242
\itemsep J1, J176, *656*
\iterate b457, a84, a85
\itshape s447, s807, w695, w696, A28, A29, A554, A587, A593, D21, E634, N36, N38, P399, *456*

J

\J aa257, aa557
\j s248, s403, s548, s779, s1150, s1365, s1451, aa572
\jmath B310
\jobname *885*
\Join A725
\joinrel B471, B478, B480, B482, B484, B486, B488, B490, B492, B496, B498
\jot I53, I191, I391, I401

K

\k ... s485, s590, s595, s617, s622, s698, s699, s757, s758, s812, s814, s819, s821, s1251, s1319, s1320, s1337, s1338, s1360, s1361, s1362, s1415, s1416, s1449, s1450, E181, E204, *1068*
\kanjiskip e74
\kappa B277
\ker I27
\kern *1038*
\kern... ..... *1061*
kernel internal commands:
  __kernel_chk_if_free_cs:N g2065, g2066, g2648, *166*
  __kernel_cmd_if_xparse:NTF g1019, g1224, g2058, g2160, g2180, i127, *137*
  __kernel_exp_not:w h41, h47, h49, h56, h61
  \l__kernel_expl_bool i297
  __kernel_file_name_sanitize:n W98
  __kernel_msg... ..... *1085*
  __kernel_msg_... ..... *1087*
\kerneltmpDoNotUse i335, i347, i353, i358, i364, i371, i384, *271*
keys commands:
  \keys_define:nn V35, V44, V113, V121, V125, V142, V173
  \keys_if_exist:nnTF V33, V72, V80, V92
  \l_keys_key_str V40, V130
  \keys_set:nn V47, V188
  \l_keys_usage_load_prop V138
  \l_keys_usage_preamble_prop .. V169
keys internal commands:
  __keys_option_end: .. V29, V43, V50
  __keys_options:n ... V24, V24, V134
  __keys_options_aux:n V24, V25, V26
  __keys_options_class:n V64, V68, V68
  \l__keys_options_clist V22, V30, V47, V74, V82, V94, V105, *870*
  __keys_options_end: V24
  __keys_options_expand_module:Nn . V25, V114, V114, V121, V125, V188
  __keys_options_expand_module:nN V114, V118
  __keys_options_global:n V31, V59, V59
  __keys_options_loaded:n V51, V136, V136
  __keys_options_loaded:nn V136, V145, V150
  \l__keys_options_loading_bool V23, V46, V48, V152, *869*
  __keys_options_local: V32, V99, V99
  __keys_options_package:n V65, V88, V88
  \c__keys_props_root_str V9, V10
  __keys_remove_equals:n V81, V92, V110, V110

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

__keys_remove_equals:w V110, V111, V112
__keys_tmp:nn V5, V11, V13
\l__keys_tmpa_tl V138, V140
\kill L154, L162

L

\L s242, s424, s530, s771, s1143, U1217, U1349, U1439, U1461, aa585
\l s251, s426, s551, s780, s1144, aa585
\label G56, O182, S161, T25, T36, T53, T61, Y621, Y680, *1063*
\labelenumi *667*
\labelenumiv *667*
\labelformat *613*
\labelformat G70, G87, G92, G98, G103, G109
\labelitemi *667*
\labelitemii *667*
\labelitemiii *667*
\labelitemiv *667*
\labelsep .. J9, J210, J216, N36, N38, *656*
\labelwidth . J9, J93, J209, J211, J214, *656*
\Lambda B300
\lambda B278
\land B368, B370
\langle B594
\language r52, r121, H422, H562, Y599, Z10, b35, b82, b84, b99, *1074*
\lastbox v681, I180, I181, J130, J136, J185, O99, O132, Y305, *301*
\LastDeclaredEncoding v137, v140, aa482, *1068*
\LastMark S274, S378, *796*
\lastnamedcs f653
\lastnodetype v674, v675, v676, v680
\lastpenalty v677, D112, D115
\lastskip p44, p128, p140, p159, p220, p221, p225, p227, p228, p240, p258, p280, p283, p315, p318, p319, D102, D105, J115, J116, J150, J151, M123, b481, b482, b484, b486, *1024*
\LaTeX q3, q15, U1179, U1312, U1401, X395, X401, f732
\LaTeXe q13
\latexrelease *895*
\latexreleaseversion c1
\lbrace s308, B598
\lbrack b408
\lccode s140, s1065, H507, H522, H537, H580, aa224, aa241, aa249, aa256, aa258, aa259, aa261, aa263, aa264, aa265, aa266, aa541, aa549, aa556, aa558, aa559, aa561, aa563, l19, l20, l21, l22, l23, l24, *1071*
\lceil B602
\lcode *1062*
\ldotp B501, B504, B619
\ldots s322, B505, *1050*
\le B416, B418
\leaders B340, B558, B559, B561, B562, L376, M565, M578, M590, M600, O214, O237, b513
\leadsto A728
\leavevmode p407, p421, s75, s184, s289, s290, s393, s425, s429, s432, s479, s763, s796, D123, E98, E927, H426, H447, H460, H471, H479, H558, H568, H581, I442, I454, I481, J58, J103, K8, K17, K24, K156, K158, K174, K202, K263, K339, K438, K455, K462, L178, M134, M314, M373, O40, O210, O222, O233, P530, R34, Y157, Y162, Y184, Y189, b472, b499, b502, b513, b515, *1063*
\left .. B625, B627, B629, B631, B636, B637, B638, B639, I154, I160, I182
\Leftarrow B410, B492, B498
\leftarrow B437, B439, B480, B490, B496, B550
\leftarrowfill B534, B550
\lefteqn I415
\leftharpoondown B453, B467
\leftharpoonup B452
\lefthyphenmin Z11
\leftline K489
\leftmargin J9, J52, J53, J94, J146, J148, *656*
\leftmargini I434, J17, *656*
\leftmarginii J17
\leftmarginiii J17
\leftmarginiv J17
\leftmarginv J17
\leftmarginvi J17, *656*
\leftmark T77, *797*
\Leftrightarrow B409
\leftrightarrow B436
\leftskip v658, H359, H365, H369, H379, H383, H387, H419, H441, J74, K295, K316, O207, O212, O230, O235, b494
legacy commands:
\legacy_if:nTF S303, S324, S353, S360
\legacyoldstylenums E4, E617
\leq B414, B416
\let *1041*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\LetLtxMacro *98*
\lfloor B606
\lg I4
\lgroup B608
\lhd A731
\lhook B477, B478
\lim I6
\liminf I8
\limits B539, B543, I149, I340
\limsup I7
\line M158, M450, M809, M826, l269
\linebreak *312*
\linebreak p9, p26
\linepenalty b320
\lineskip B458, I187, K297, K317, L71, L198, M136, M315, M374, X221, X272, Y624, Y683, b402, b467, b502
\lineskiplimit B458, B510, I189, I193, K283, K298, K305, X222, X273, Y624, Y683, b403, b467, b504, b505, *1074*
\linespread v316
\linethickness M130, M810, M827
\linewidth r30, r99, r157, I285, I311, I443, I455, I482, I486, I505, J15, J51, J52, J54, K293, K314, L36, P266, Y146, Y205, *655*
\LinkTargetOff o20
\LinkTargetOn o20
list (env.) J34
\list J34, J236, J247
\listfiles *822*
\listfiles r708, *1040*
\listparindent J9, J41, J50, *656*
\literal *1030*
\ll B434
\llap J238, J249, K493
\lmoustache B563
\ln I5
\lnot B326, B327
\LoadClass *820*
\LoadClass U621, U651, U869, U1004, U1078, U1086, U1087, *1026*
\LoadClassWithOptions *820*
\LoadClassWithOptions U650
\LoadFontDefinitionFile v418, v444, v445, B21, B27, B28, B29, B33
\LoadPackageWithOptions *876*
\loccount d17
\log I3
\loggingall b524
\loggingoutput b556, b572, b586, b520, b538, *1067*
\LogHook h1493, *190*
\long *1081*
\Longleftarrow B492
\longleftarrow B489
\Longleftrightarrow B498, B500
\longleftrightarrow B496
\longmapsto B494
\Longrightarrow B486
\longrightarrow B487, B494
\loop . . v672, d150, d159, L382, U1127, U1188, U1258, U1321, U1372, U1410, aa365, aa376, aa386, aa397, aa427, aa453, aa463, b457, a84, *1048*
\looseness b333
\lor B369, B371
\lower q2, B458, K214, M35, M45, M196, M305, M306, M353, M354, M409, M410
\lowercase s141, s1066, s1544, v332, v390, H511, H526, H541, H581, l26, *1060*
\lq b406
lrbox (env.) *670*
\lrbox K144
\ltfilehookdate W539
\ltfilehookversion W539
lua commands:
  \lua_now:n X31
\luabytecode d202
\luachunk d210
\luadef d182, d186, *44*
\luafunction d178, d182, d186, *44*
luatexbase d288
\luatexluafunction a21, a26
\luatexversion . . . s994, d5, e73, a14, e119

M

\M b404
\Macro *1023*
\magstep b395
\magstephalf b395
\makeat... . . . . *1042*
\makeatletter r32, r101, r159, v396, H26, H79, O151, U615, U833, U965, Y2, f728, i293, *1064*
\makeatother U615, aa649, f728, i293, *1039*
\makebox *670*
\makebox I285, I311, K3
\makeglossary *783*
\makeglossary r204, Q20, *1047*
\makeindex *783*
\makeindex r203, Q3, *1047*
\makelabel J45, J97, J205, J218, J238, J249, *655*
\MakeLinkTarget o20, *311*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\MakeLowercase aa578, aa587, *1054*
\MakeRobust z796, z991, M806, M807, M808, M809, M810, M811, M812, M813, M814, M815, M816, M817, f271, f773, f774, f775, f776, f777, f778, f779, f780, f781, f782, f783, f784, f785, f786, f787, f788, *1081*
\maketitle *747*
\MakeUppercase G72, G74, G89, G100, aa565, *1054*
\mapsto B444
\mapstochar B443, B444, B494
\marginpar P308, *297*
\marginparpush Y85, Y1836
\marginparsep Y84, Y1847, Y1849
\marginparwidth . P341, P359, Y83, Y1849
\mark T31, T42, T56, T64, T82, *791*
mark commands:
\mark_debug_off: S218, S224, S235, *795*
\mark_debug_on: S218, S219, S234, *795*
\mark_if_eq:nnnn S169
\mark_if_eq:nnnnnn S176
\mark_if_eq:nnnnnnTF S169, *794*
\mark_if_eq:nnnnTF .. S169, S281, *794*
\mark_insert:nn S134, S134, S273, T28, T29, T30, T39, T40, T41, *802*
\mark_new_class:n S7, S7, S16, S271, *792*
\mark_use_first:nn S166, S166, S275, *793*
\mark_use_last:nn S166, S167, S277, *793*
\mark_use_top:nn S166, S168, S279, *793*
mark internal commands:
__mark_class_status:nn S236, S237, S268
__mark_debug:n S20, S143, S218, S218, S231, S299, S349, *807*
__mark_debug_gset: S218, S222, S227, S229
__mark_error:n S123, S126, S127, S128, S131
__mark_new_class:nn ... S7, S14, S17
__mark_status:n S265, S265, S301, S351
__mark_update_dblcol_structures: S314, S314, S371, *798*
__mark_update_singlecol_structures: . S283, S283, S369, *798*
__mark_update_structure:nn S46, S46, S286, S290, S317, S321, *798*
__mark_update_structure_alias:nn S48, S112, S112, S293, S294, S295, S296, S326, S330, S331, *798*
__mark_update_structure_to_err:n S123, S123, S327, *798*
\markboth T21, T22, T49, T51, T70, T72, *795*
\markright T22, T59, T73, *1003*
\marks d37, aa10, aa12
math (env.) I332
\math I332
\mathaccemt *1073*
\mathaccent z713, z761, z795, z805
\mathalpha .. z883, z1062, B169, B170, B171, B172, B173, B174, B175, B176, B177, B178, B179, B180, B181, B182, B183, B184, B185, B186, B187, B188, B189, B190, B191, B192, B193, B194, B195, B196, B197, B198, B199, B200, B201, B202, B203, B204, B205, B206, B207, B208, B209, B210, B211, B212, B213, B214, B215, B216, B217, B218, B219, B220, B221, B222, B223, B224, B225, B226, B227, B228, B229, B230, B297, B298, B299, B300, B301, B302, B303, B304, B305, B306, B307, B516, B517, B518, B519, B520, B521, B522, B523, B525, B528
\mathbf A14, A255, A308, A353, A381, A475, B151
\mathbin z1067, B232, B233, B235, B358, B359, B360, B361, B364, B365, B366, B367, B370, B371, B372, B373, B374, B375, B376, B377, B378, B379, B380, B381, B382, B383, B384, B385, B386, B387, B388, B389, B390, B391, B392, B393, B394, B395, B396, B397, I37
\mathcal B150
\mathchar z824, z868, B335, B336, B617, b500, *1073*
\mathchardef s70, d227, z859, b21, b22, b23, b24, b107, b110, b111, j3, j4, j5, j6, *1046*
\mathcharzero d227
\mathchoice I61
\mathclose z1070, B231, B240, B242, B245, B250, B256, B258, B260, B566, B593, B597, B601, B605, B611, I43, I46, I49, I52
\mathcode z856, B252, B253, B254
\mathdefaultsmode I423, I424
\mathdollar s307, B614, *1046*
\mathellipsis s321, B619, *1046*
\mathfontset *1021*
\mathgroup v14, x303, x309, x315, x316, x327, B643, E8, E14, E614, E1139, b79, *1021*
\mathhexbox A652, b500, *1053*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\mathindent I432, I444, I456, I484, I495, *1044*
\mathinner B504, B508, B513, B619
\mathit w696, A29, B153, B156, B617
\mathnormal B149
\mathop z1066, B341, B342, B343, B344, B345, B346, B347, B349, B350, B351, B352, B353, B354, B356, B357, B537, B540, I3, I4, I5, I6, I7, I8, I9, I10, I11, I12, I13, I14, I15, I16, I17, I18, I19, I20, I21, I22, I23, I24, I25, I26, I27, I28, I29, I30, I31, I32, I33, I34, I149, I340
\mathopen z1069, B241, B244, B249, B255, B257, B259, B564, B595, B599, B603, B607, B609, I41, I44, I47, I50
\mathord z883, z1065, B236, B243, B246, B251, B263, B264, B265, B267, B268, B269, B270, B271, B272, B273, B274, B275, B276, B277, B278, B279, B280, B281, B282, B283, B284, B285, B286, B287, B288, B289, B290, B291, B292, B293, B294, B295, B296, B308, B309, B310, B311, B312, B313, B314, B315, B316, B317, B318, B319, B320, B321, B322, B323, B324, B325, B327, B328, B329, B330, B331, B332, B333, B334, B524, B526, B527, B549, B550, B553, B554, B555, B556, B568, B570, B572, B575, B577, B591, B613, B614, B615, B616
\mathpalette B457, B461, B464, I60, I69, I99, I129
\mathparagraph s310, t168, t180, B614, *1062*
\mathpunct z1071, B234, B238, B501, B502, B503
\mathrel z1068, B237, B239, B247, B248, B261, B262, B338, B398, B399, B400, B401, B402, B403, B404, B405, B406, B407, B408, B409, B410, B411, B414, B415, B418, B419, B420, B421, B422, B423, B424, B425, B426, B427, B428, B429, B430, B432, B433, B434, B435, B436, B437, B438, B441, B442, B443, B445, B446, B447, B448, B449, B450, B451, B452, B453, B454, B455, B457, B461, B464, B471, B473, B476, B477, B479, B482, B484, B579, B581, B583, B585, B587, B589, I42, I45, I48, I51, I149, I340
\mathring B528, *1064*
\mathrm A5, A406, A449, A481, B148, *1022*
\mathsection . s311, t167, t179, B614, *1062*
\mathsf A8, A411, A454, A484, B152, B155
\mathsterling s319, B614, *1046*
\mathstrut I84, I93, I158, I159
\mathsurround b488, *1063*
\mathsymbol z861
\mathtt A11, A416, A459, A487, B154
\mathunderscore B614, *1047*
\mathversion v336, A614, A616, *1022*
\mathversion. *1021*
\matrix I156, I160, I167
\max I22
\maxdeadcycles Y7
\maxdepth p287, r60, r128, r183, Y92, Y169, Y170, Y508, Y516, Y548, Y717, Y726, Y766, Y993, aa152, b376, *1034*
\maxdimen b555, b571, b586, v645, v655, v690, v705, x384, x437, B458, M475, M503, M533, M611, M628, U1482, U1523, U1532, X349, X351, X407, Y291, Y1855, Y1875, Y1880, Y2201, Y2241, Y2242, Y2244, aa156, b309, b377, b378, b467, b505, b521, b536, b537, *1023*
\mbox *670*
\mbox q13, s293, s409, s568, s1165, A648, B506, K11, K20, K24, M52, P409, P416, P437, P444, b500, *1051*
\mddefault A18, A284, A290, A291, A292, A331, A332, A333, A342, A369, A385, A402, A443, A479, B92, B105, B107, B121, *1079*
\mdseries A16, A17, A221, A277, A328, A329, A363, A364, A383, A384, A477, A478, A651, D20, *534*
mdseries A420
mdseries/defaults A420
\meaning z535, z548, z649, z714, z761, z825, z919, z1015, z1119, a222, a231, f228, f290, f328, f356, f439, f699, a326
\medbreak f780, f801, b482
\mediumseries *526*
\medmuskip B645, I36, I38, I211, I214, I228
\medskip p400, b485
\medskipamount p401, p403, b484
\medspace I201
\MessageBreak o13, s161, c98, s988, s1549, s1552, v34, v35, v536, v570, w456, x20, x21, x67, x88, x327, x478, x498, x530,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

x546, x561, x574, y31, y33, z181, z490, z499, z637, A61, A94, D144, E23, E79, E81, E100, E851, E853, E854, E855, E857, E859, E860, E861, E862, E863, E913, E915, E922, E929, E1144, H43, H83, e78, e81, e82, e83, e84, e85, e86, e99, e100, e101, e102, e103, U290, U304, U677, U688, U690, U692, U703, U864, U865, U866, U867, U877, U878, U880, U881, U882, U884, U886, U972, U973, U975, U976, U977, U979, U981, U999, U1000, U1001, U1002, U1063, U1080, U1081, U1149, U1166, U1205, U1280, U1299, U1338, U1393, U1427, U1536, U1538, U1620, U1623, U1636, U1638, f204, f279, X99, X173, X369, f318, X475, X476, X477, X478, f346, Y580, Y1996, Y2033, aa300, aa301, aa302, aa304, l3, l6, l13, l33, l46, l60, l73, l220, l222, l228, l235, *1063*

\mho A724
\mid B402
\min I23
minipage (env.) *671*
\minipage K326
\mit A776
\mkern B335, B338, B340, B462, B471, B513, B514, B515, B545, B546, B547, B548, B549, B550, B551, B552, I36, I37, I40, I73, I74, O215, O238

mlist commands:
mlist_to_hlist d847

mode commands:
\mode_if_horizontal:TF n53, n58
\mode_if_inner:TF n54
\mode_if_math:TF z211
\mode_if_vertical:TF n72, n84

\models B484, *1067*

module commands:
module_error d345
module_info d345
module_warning d345

\module_error *47*
\module_info *47*
\module_warning *47*
modules d298
\month . . . c17, a188, U1183, U1316, U1405
\moveright Y627, Y686
\mp B389
\mscount L379

msg commands:
\msg_... . . . . *1085*
\msg_error:nn . . . n80, n90, h274, h291
\msg_error:nnn S11, S101, S132, S156, V176, W75, g277, g659, g2048, g2052, g2536, g2539, g2547, h73, h299, h337, h355, h1128
\msg_error:nnnn n66, V39, V157, g390, g398, g422, g426, g462, g476, g489, g572, g579, g588, g616, g628, g647, g681, g1006, g1579, g2116, g2120, g2503, g2517, g2559, g2573, i42, i100, i314, n18, n30
\msg_error:nnnnn g603, g1723, g1730, g2008, h278, h309, h318
\msg_error:nnnnnn h655, h667, h692, h913
\msg_expandable_error:nn h180
\msg_expandable_error:nnn e182, g348, g2605, h208
\msg_expandable_error:nnnn W465, g1900, g1927
\msg_info:nnnn . . g65, g76, g181, g185
\msg_line_context: S20, S144, g2460, g2465, g2470, g2475, h1362, h1367, h1414
\g_msg_module_name_prop h1337
\g_msg_module_type_prop S183, g50, h1335, h1336
\msg_new:nnn e184, V159, W471, g1007, g2402, g2457, g2462, g2467, g2472, g2477, g2489, h1360, h1365, h1410, h1416, h1421, h1426, h1431, h1435, h1442, h1568
\msg_new:nnnn n102, n113, S184, S192, S200, S208, V53, V161, V181, g2245, g2252, g2259, g2266, g2273, g2280, g2287, g2294, g2301, g2308, g2316, g2323, g2330, g2337, g2345, g2353, g2362, g2369, g2376, g2383, g2389, g2395, g2404, g2410, g2417, g2423, g2430, g2436, g2447, h1338, h1348, h1353, h1370, h1386, h1399, i391, i401
\msg_redirect_module:nnn g49
\msg_warning:nnn g73, h152
\msg_warning:nnnn V154, g640, h619, h631, h1567
\msg_warning:nnnnn h449
\msg_warning:nnnnnn h921

msg internal commands:
\c__msg_coding_error_text_tl S187, S195, S203, S211
\c__msg_return_text_tl . . . S190, S206

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\mskip . I36, I38, I206, I225, I228, I230, I231
\mu B279
\mubyte aa352
\multicolumn L233, *627*
\multiput M78, M811, M828
\multispan L233, L379, *1056*
\muskip . . . d34, B545, B546, b29, b55, b93
\muskipdef d228, b55, b93
\muskipzero d228

N

\n d332, d334, d341, d343, d470, d578, d603, d627, d672, d694, d713, d721, d722, d742, d755, d762, d763, d770, d782, aa121, aa126
\nabla B319
\NAME *79*
\narrower b493
\natural B329
\ncallback d677
\ndefault d682, d686
\ne B413, *559*
\nearrow B405
\NeedsFormat *1026*
\NeedsTeXFormat x12, E819, U682, U1682, *1030*
\neg B325, B326
\negmedspace I201, *1082*
\negthickspace I201, *1082*
\negthinspace p468, I201, *1079*
\neq B412, *559*
new commands:
  new_attribute d411
  new_bytecode d445
  new_chunkname d458
  new_luafunction d474
  new_whatsit d433
\new_attribute *45*
\new_bytecode *45*
\new_chunkname *45*
\new_luafunction *45*
\new_whatsit *45*
\newattribute *44*
\newattribute d74, d238
\newbox H482, I66, J27, K115, L16, L17, L18, L343, M6, M670, M675, Y86, Y120, Y121, Y122, b47, b314, b490, j13
\newcatcodetable *44*
\newcatcodetable d84, d93, d94, d120, d121, d242
\newcommand *79*
\newcommand s4, w530, w535, w540, A36, A72, B51, B52, B53, B54, B56, B57, B59, B60, B92, B93, B94, B95, B96, B97, B120, B121, B122, H303, H304, H305, H306, M682, f77, W570, W571, W572, W573, W575, Y2327, Y2330, Y2333, Y2334, Y2337, Y2338, *100*
\NewCommandCopy f461, f463, g984, g1160, *1081*
\newcount p124, r7, t36, x25, z27, z142, z377, I55, I344, I345, J23, J24, J25, J26, J56, J226, J241, K367, L11, L12, L13, L14, L15, L335, L336, L337, M664, M665, M666, M667, M676, O36, O140, O141, P3, P267, P268, P269, P270, U1479, Y103, Y105, Y107, Y109, Y111, Y119, Y2022, Y2325, Y2328, Y2331, Y2335, aa3, aa4, aa5, aa91, b47, b352, b394, j7, j8, *1069*
\newcounter *400*
\newcounter t10
\newdimen p123, x398, x399, I53, J9, J10, J11, J12, J13, J14, J15, J16, J17, J18, J19, J20, J21, J22, K171, K172, L3, L5, L6, L7, L8, L166, L338, L339, L340, L341, M3, M4, M5, M7, M431, M432, M433, M434, M435, M436, M668, M669, M671, M672, M673, M674, P451, Y71, Y72, Y73, Y75, Y76, Y77, Y78, Y79, Y80, Y81, Y82, Y83, Y84, Y85, Y91, Y93, Y94, Y106, Y108, Y110, Y112, Y113, Y114, Y115, Y116, Y117, Y118, Y2023, Y2024, b47, b309, b311, b312, b393, j10, j11, j12
\NewDocumentCommand o20, o28, o29, o30, t79, t87, G28, G30, G75, V120, V122, V133, V187, g2497, h1447, h1448, h1449, h1452, h1453, h1461, h1463, h1465, h1467, h1469, h1481, h1483, h1497, h1499, h1502, *94*
\NewDocumentEnvironment g2276, g2283, g2533
\newenvironment *80*
\newenvironment U1181, f146, U1314, U1403, *199*
\NewExpandableDocumentCommand S274, S276, S278, S280, g2553
\newfam v16, d38, b47, *1053*
\newfont A618
\newgroup z47
\newhelp b306
\NewHook r72, r73, r74, r347, r350, r399, x150, A420, A421, A422,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

A423, A424, A425, A426, A427, A428, H33, H34, H35, H36, H37, U950, U951, W177, h1447, h1583, *199*
\NewHookPair *257*
\newif r5, r6, c70, v204, w401, w413, z15, A528, D82, E871, G3, I75, I76, I190, I346, J28, J29, J30, J31, J32, J33, J138, K423, L19, L251, M157, M427, M428, M429, M430, M459, M460, O38, O124, U2, f168, Y95, Y96, Y97, Y98, Y99, Y100, Y101, Y102, f767, j9, *1021*
\newinsert K368, P390, Y27, Y1854, b193, b242, *1072*
\newlabel G46, G58, *1055*
\newlanguage aa284, b47
\newlength *408*
\newlength u3
\newline p92, p99, p105
\newlinechar f20, a75
\newluabytecode *45*
\newluabytecode d197, d252
\newluachunkname *45*
\newluachunkname d205, d254
\newluacmd *44*
\newluacmd d181, *45*
\newluafunction *44*
\newluafunction . d4, d173, d236, d248, *44*
\NewMarkClass S271, S375, aa25, aa26, aa27, *792*
\newmarks S22, aa6, *797*
\newmathalphabet y13, y109
\NewMirroredHookPair . . h1447, h1585, *182*
\NewModuleRelease o3, c149, E2, S4, g9, h4, i4, n4, *1084*
\newmuskip b47
\newpage Y133, Y139, Y150
\newprotectedluacmd *45*
\newprotectedluacmd . . . s1010, d181, X28
\newread b47, b307, *1024*
\NewReversedHook r348, r349, r400, r401, U952, U953, W178, h1447, h1584, *181*
\newrobustcmd *94*
\newsavebox *670*
\newsavebox K115
\newskip p403, p404, p405, p454, u3, H400, I347, I433, J2, J3, J4, J5, J6, J7, J8, Y2339, Y2340, Y2341, Y2345, Y2346, Y2349, Y2350, Y2351, Y2355, Y2356, Y2357, b47, b310, b313, b391, b392, j14, j15, j17
\newtheorem N1, *1056*
\newtie s851, E188, E189, E208, E705, E1015, E1016, *585*
\newtoks v346, v347, w499, x247, b47, b306, j16, n35, *1072*
\newwhatsit *45*
\newwhatsit d189, d250
\newwrite r3, r4, O154, Q4, Q21, b47, b308, *1046*
\newXeTeXintercharclass aa35
\next *1049*
\NextLinkTarget o20
nfss internal commands:
__nfss_init_mv_freeze:N z186, z210, z210, z211
\NG s531, s1145, aa585, *1041*
\ng s552, s1146, aa585, *1041*
\ni B430, B431
\noalign B339, B531, B534, B537, B538, B542, B543, I158, I159, I175, I178, I192, I391, I401, L224, L230, L359, L378, M148, M154, *627*
\nobreak p59, p71, p115, p141, p147, p160, p173, p199, p351, p359, p385, p393, p414, p421, p452, r202, r214, s409, s435, s437, s568, s1165, H325, H332, K488, O90, O212, O213, O217, O235, O236, O240, P531, S153, T33, T44, T58, T66, Y336, Y1151, Y1317, aa208, aa210, aa214, aa215, aa216, aa220, f781, f802, b470, b473, b475, *1052*
\nobreakdashes p406
\nobreakspace p420
\nobreakspace␣ *1061*
\NoCaseChange aa565, *1090*
\nocide *789*
\nocite *786*
\nocite R59, *1048*
\nocorr D43, D58, D62, D65, *1036*
\nocorrlist D89, D121
\noexpand *1089*
\nofiles *332*
\nofiles r198, *1050*
\noindent v668, v694, O139, *1062*
\nointerlineskip B339, B531, B534, B538, B542, I284, I310, M563, M566, M576, M578, Y1844, Y1852, b465
\nolimits B348, B355, I3, I4, I5, I9, I10, I11, I12, I13, I14, I15, I16, I17, I18, I19, I20, I21, I26, I27, I28, I29, I31, I34
\nolinebreak *312*
\nolinebreak p9, p27
\nonfrenchspacing r48, r117, r175, b676, f782, f803, b398
\nonscript I36, I38

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\nonumber I374, I413, I414
\nopagebreak *312*
\nopagebreak p7, p25
\noprotrusion O222, O245
\normalbaselines I154, I156, b402
\normalbaselineskip x188, K299, K318, b391, b403
\normalcolor I339, I429, K89, K359, O218, O241, P97, P166, Y216, Y494, Y631, Y641, Y690, Y700, Y2262, Y2295, *1051*
\normalfont . . v646, v706, A653, A673, A675, A684, A689, A691, A699, A706, A708, A714, D18, H461, I339, I429, O218, O241, P401, *1056*
normalfont A420
\normalize *1034*
\normallineskip . K297, K317, b391, b402
\normallineskiplimit I193, K282, K298, K304, b391, b403
\normalmarginpar P387
\normalsfcodes r44, r46, r48, r113, r115, r117, r171, r173, r175, r197, Y620, Y679, *1063*
\normalshape w682, w723, *451*
\normalsize r42, r111, r169, D142, P23, P176, P372, U5, Y619, Y678, *1035*
\not B338, B412, B413, B435
\notexpanded *268*
\notin B461
\noxpand *1026*
\nu B280
\null s327, s363, s486, s489, s834, s837, s1253, G17, H426, H447, H558, H568, I112, I121, I156, I185, O212, O235, X383, b416, *1050*
\nulldelimiterspace B642, b380
\nullfont H167
\number c49, c58, t142, v596, v599, d105, x439, z64, z93, z113, z128, z164, z232, z262, z294, A645, f2, f114, U1094, U1183, U1316, U1405, X349, a89
\numberline . . . O72, O82, O248, P17, *1025*
\numexpr s1034, d82, d105, d157, z150, Y36, f642, b189, b205, b215, b246
\nunknown d699
\nwarrow B407
\nxt *1049*

O

\O s244, s400, s533, s770, s1130, aa584
\o s253, s405, s554, s781, s1136, aa584
\oalign b502
\obeycr p480
\obeyedline b426, b430, b453, *30*
\obeyedspace b431, b434, b454, *30*
\obeylines H432, H453, H549, H550, Y585, f783, f804, b419, *30*
\obeyspaces Y585, f784, f805, b419, *30*
\oddsidemargin . . . Y72, Y74, Y613, Y672
\odot B384
\OE . . . s243, s399, s532, s769, s1147, aa584
\oe . . . s252, s404, s553, s782, s1148, aa584
\of I67, I343
\offinterlineskip b465
\oint B355
\ointop B354, B355
\oldstylenums E4, E376, E377, E378, E379, E380, E381, E382, E383, E384, E385, E610, E1136, *579*
\Omega B307
\omega B290
\ominus B387
\omit . . I178, I179, L369, L372, L379, L383
\OmitIndent n49, n128, *297*
\onecolumn Y141
\OnlyDescription x5, C3
\ooalign s327, s357, s394, s480, s486, s488, s499, s515, s731, s764, s834, s837, s894, s1253, A650, B462, B465, b502, *1068*
\openin *1078*
\openout *1024*
\openup I186, I191
\oplus B388
\OptionNotUsed U446, U471, U1018
or commands:
\or: g1242, g1243, h727, h743
\oslash B385
\OT s372
\otimes B386
\outer d21, d38, *1074*
\outerparskip J1
\output Y256
\outputpenalty Y258, Y272, Y295, Y298, Y299, Y334, Y1161, Y1162, Y1327, Y1330
\oval M450, M453, M812, M829
\over B469, I149, I341
\overbrace B536
\overfullrule T98, b375
\overleftarrow B533
\overrightarrow B530
\owns B431, B432

P

\P s310, *1046*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

package/.../after *876*
package/.../before *876*
package/after *876*
package/before *876*
\PackageError c74, c132, c144, s1547, E825, E877, E921, l84
\PackageInfo E829, E846, E851, E867, E868, E928, E1213, l84
\PackageNote l136, *1086*
\PackageNoteNoLine l136
\PackageWarning E827, E878, E1142, X474, l84
\PackageWarningNoLine . . s986, Y1995, l84
\pagebreak *312*
\pagebreak p6, p7, p22, p24
\pagegoal Y1882, Y1889
\pagenumbering *611*
\pagenumbering F5
\pageref G10
\pageshrink Y540, Y544, Y560
\pagestyle T2
\pagetotal Y128
\paperheight Y93
\paperwidth Y93
\par n98, n134, a123, v671, d156, H109, H165, H325, H332, H424, H445, J63, J110, J127, J129, J135, J161, J164, K288, K309, K355, K385, K402, L195, L385, O41, O90, O220, O242, P15, P24, P249, P344, P478, P496, f9, f21, T91, T92, X399, Y166, Y193, Y257, Y1888, b11, b412, b428, b430, b447, b469, b478, b479, b480, b482, b484, b486, m3, m4, m5, *1084*
para commands:
  \para_end: n51, n51, n98, n99, n100, *298*
  \g_para_indent_box n42, n44, n47, n49, n75, n14, *299*
  \para_omit_indent: n46, n50, *304*
  \para_raw_end: . . . n71, n93, n96, *307*
  \para_raw_indent: . n71, n71, n94, *299*
  \para_raw_noindent: n71, n83, n95, *299*
para internal commands:
  __para_handle_indent: n43, n43, n77, n31
  \g__para_standard_everypar_tl n36, n76, n87, n12, n34, *303*
para/after n6, *297*
para/before n6, *297*
para/begin n6, *297*
para/end n6, *297*
\paracntvalue *300*
\paragraphmark O143
\parallel B401
\parbox *670*
\parbox K234, *295*
\parfillskip v645, v660, v705, H361, H371, H380, H388, H420, H442, J76, K296, K317, O207, O230, b390, *306*
\parindent H361, H366, H371, H380, H384, H388, H420, H442, J50, K291, K312, O208, O231, b382, b494, b495, *294*
\parsep J1, J49, J90, *656*
\parseunicodedataI d123, d162
\parseunicodedataII d124, d126
\parseunicodedataIII d128, d134
\parseunicodedataIV d130, d142
\parseunicodedataV d146, d149
\parshape J54, *302*
\parskip H336, H418, H420, H440, H442, I501, J49, J73, J88, J90, J117, J153, J172, J223, K291, K312, L79, Y1161, Y1329, b383, *301*
\partial B315
\partopsep I499, J1, J61, *656*
\PassOptionsToClass *820*
\PassOptionsToClass U378
\PassOptionsToPackage *820*
\PassOptionsToPackage U378
\patterns s205, *1045*
\pausing b334
\pdffilesize e71, e117
\pdfgentounicode aa315, aa316, aa320, aa335, aa340, aa341, aa342
\pdfhorigin X312
\pdftexrevision aa321
\pdftexversion aa319, aa320, aa321
\pdfvariable X311, X316
\pdfvorigin X317
peek commands:
  \peek_meaning:NTF g2204, *170*
  \peek_meaning_remove:NTF g1619, g1721, g2192, *155*
  \peek_N_type:TF . g1625, g1649, g1681
  \peek_remove_spaces:n g1617
\penalty p34, p37, p46, p281, p291, p316, p320, D118, H426, H429, H447, H450, I37, I194, I391, I401, J190, L56, P195, P199, P201, P217, P221, P223, R37, Y136, Y176, Y195, Y198, Y1159, Y1325, b474, b475, b476, b477, b478, b479, b483, b485, b487, *1023*
\perp B447
\phantom I75

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\Phi B305
\phi B287
\Pi B302
\pi B282
picture (env.) M21
\picture M21
\pm B390
\pmatrix I160, I168
\pmod I39
\PopDefaultHookLabel h1469, *187*
\poptabs L142, L161, l256
\poptracing x148, x340
\postdisplaypenalty . p12, I441, I453, I479
\pounds s318, *1042*
\Pr I32
pre commands:
pre_shipout_filter *902*
\prec B421
\preceq B424
\predisplaypenalty . I440, I452, I478, b329
\pretolerance v647, v662, v707, b316
\prevdepth p287, p288, p349, p354, p383, p388, I192, P196, P198, P218, P220, Y167, Y169, Y172, b465, b469, b470, *324*
\PreviousTotalPages X405, *902*
prg commands:
\prg_break:n g2595, g2597, g2599, g2601, g2602
\prg_break_point: g2603
\prg_do_nothing: S149, W132, W134, X164, X165, X170, X179, X183, X319, g339, g851, g1562, i190, i304, i422, *133*
\prg_new_conditional:Npnn . S169, S176, h130, h522, h536, h731, h1249, h1262, h1278, h1284, h1290, h1296, h1305, h1313, h1325, i232
\prg_new_protected_conditional:Npnn h418, h470, h498, i106, i345
\prg_replicate:nn W549, g774, g817, g862, g917, g2015, g2022
\prg_return_false: S174, S181, h136, h440, h474, h492, h502, h515, h529, h531, h544, h548, h551, h736, h1257, h1260, h1274, h1282, h1288, h1294, h1302, h1311, h1320, h1323, h1332, i121, i245, i360, *221*
\prg_return_true: S173, S180, h135, h431, h490, h513, h528, h547, h734, h1255, h1273, h1276, h1281, h1287, h1293, h1300, h1310, h1321, h1330, i120, i245, i359
\prime B253, B317, I243
\ProcessedArgument . . g320, g324, g331, g1948, g1949, g1966, g1968, g1990, g1999, g2005, g2013, g2030, g2630, *165*
\ProcessKeyOptions U828, V133, *1089*
\ProcessKeyPackageOptions *1089*
\ProcessList g2635
\ProcessOption* *1026*
\ProcessOptions s1568, x71, E844, E881, U472, U563, U1082, *1026*
\ProcessOptions* U472
\prod B349
prop commands:
\prop_clear:N g1470
\prop_const_from_keyval:Nn h590, h598, h599, h600
\prop_gclear:N h610, h749, i57
\prop_gclear_new:N h1247
\prop_get:NnN h840
\prop_get:NnNTF . . V138, g1476, h358
\prop_gpop:NnNTF h618
\prop_gput:Nnn . . S183, g50, h360, h363, h789, h1335, h1336, h1337, i50
\prop_if_empty:NTF h771, h1004
\prop_if_empty_p:N h1267
\prop_if_exist:NTF h1286
\prop_if_in:NnTF h476, h484, h487, h504, h507, h510, h546
\prop_map_break: h817, h1086
\prop_map_function:NN i56
\prop_map_inline:Nn V169, h756, h805, h812, h814, h963, h1007, h1081, h1083
\prop_new:N g45, h30, h31, h95, h634, h635, i16
\prop_put:Nnn g1467, h933, h944
\prop_set_eq:NN h785
\prop_show:N *240*
\propto B398
\protect r210, s26, s32, s51, s55, s209, s217, z598, z1146, A638, D143, G12, H193, H203, H238, H241, H256, H266, L264, O12, O72, O82, O164, O171, O177, P17, R5, f102, f220, f234, W282, W305, f243, f248, f251, f252, f254, f255, f260, f261, f266, f269, f270, X83, X95, X124, X131, X151, f295, f333, f361, Y598, Y657, f533, f553, aa358, l246, l248, l250, l256, l262, l269, l277, l280, l286, *1043*
\protected o6, p56, p462, s308, s309, t194, w682, w686, w689, w692, w695, w698, w701, w704, d186, z988, A573,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

H126, H324, I186, I375, I413, L56, L201, L208, M142, f7, X494, X495, X496, f443, aa566, aa567, b430, *513*
\Provide *1045*
\providecommand s6, s981, E811, E812, f178, Y2006, h1592, h1595
\ProvideCommandCopy *96*
\ProvideDocumentCommand g2497
\ProvideDocumentEnvironment g2533
\ProvideExpandableDocumentCommand g2553
\ProvideHook h1538, *1085*
\ProvideMirroredHookPair h1538
\ProvideReversedHook h1538
provides commands:
provides_module d299
\provides_module *47*
\ProvidesClass *820*
\ProvidesClass U358
\ProvidesExplPackage W538
\ProvidesFile a92, B665, B667, B668, B669, U367, *1048*
\ProvidesPackage *820*
\ProvidesPackage x13, E817, E849, U281, U360, U362, U1683, W567, X489, *831*
\ProvideTextCommand s3, s60, *1045*
\ProvideTextCommandDefault . . . s57, *1054*
\Psi B306
\psi B289
\PushDefaultHookLabel h1469, *187*
\pushtabs . . . L139, L138, L158, L160, l256
\pushtracing x117, x321
\put M56, M58, M70, M72, M325, M326, M327, M328, M336, M338, M351, M352, M353, M354, M361, M364, M384, M385, M386, M387, M393, M395, M407, M408, M409, M410, M415, M420, M729, M785, M813, M830, *903*

Q

\qbezier *711*
\qbezier M682, M814, M831
\qbeziermax M681, M707, M708, M768
\qquad p473
\quad . . . p473, I155, I157, I177, O111, *1052*
quark commands:
\q_mark g1152, g1155, g1849, g1853, g1865, g2142, g2150, g2153, g2158
\q_nil . . g514, g1144, g1155, g1253, g1376, g1397, g1401, g1407, g1416, g1418, g1769, g1793, g1802, g1834, g1849, g1853, g1865, g1871, g1897, *159*
\quark_if_nil:NTF . . . g525, g1855, *160*
\quark_if_nil:nTF g1250
\quark_if_recursion_tail_stop:N g710, g1234
\quark_if_recursion_tail_stop:n V7, g410, g578, g1070, g2155, g2156, h260
\quark_if_recursion_tail_stop_-do:Nn g533
\quark_if_recursion_tail_stop_-do:nn g436, g441, g450, g459, g473, g486, g500, g510, g554, i321
\quark_new:N g1385, i14, i15
\q_recursion_stop V19, g264, g275, g387, g700, g1066, g1230, g1468, g1483, g1485, g1492, g2145, g2151, h266, i312
\q_recursion_tail V18, g387, g700, g1066, g1230, g1483, g1487, g2141, g2144, g2150, g2151, h265, h266, i312, *122*
\q_stop . . . g352, g514, g523, g528, g1152, g1154, g1401, g1418, g2006
quark internal commands:
\q__cmd g336, g340, g886, g1181, g1182, g1200, g1208, g1383, g1753, g1754, g1757, g1762, g1768, g1769, g1771, g1775, g1780, g1783, g1786, g1797, g1801, g1802, g1805, g1806, g1809, g1820, g1823, g1827, g1838, g1840, g1841, g1842, g1843, g1844, g1845, g1846, g1850, g1869, g1870, g1871, g1872, g1873, g1874, g1875, g1876, g1877, g1878, g1879, g1880, g1881, g1882, g1885, g1890, g1896, g1897, g1903, g1908, g1909, g1912, g1923, g1930, g1935, g1936, g1937, g1940, g1941, g1943, *160*
\q__hook_recursion_stop i14, i247, i248, i257, i278
\q__hook_recursion_tail i14, i247, i261
\quotedblbase s555, s783, s1176
\quotesinglbase s556, s1173

R

\r s236, s388, s431, s470, s610, s637, s647, s673, s756, s795, s1245, s1263, s1289, s1411, s1412, E183, E205, b410, b411, *1062*
\radical z1012, z1015, z1045, *1073*
\raggedbottom T82
\raggedleft H367, H385, H396, H403
\raggedright H362, H381, H395, H401
\raise s327, s359, s430, s433, s732, s797, s895, s1253, A651, B465, B513, B515, I73, K473, K482,

M61, M73, M105, M117, M195, M305, M452, M495, M526, M551, M619, M636, M637, M740, M796
\raisebox *671*
\raisebox s872, s1222, K450
\rangle B592
\RawIndent n94, n130, *299*
\RawNoIndent n94
\RawNoindent n95, n131, *299*
\RawParEnd n94, n132, b449, *299*
\RawShipout X150, X436, *899*
\rbrace s309, B596
\rbrack b408
\rceil B600
\Re B313
\read *351*
\ReadonlyShipoutCounter X344, X438, *902*
\Ref *613*
\Ref G63, G71, G80, G88, G92, G99, G103, G110
\ref G10, G88, G99, P553, *667*
\refstepcounter *400*
\refstepcounter G64, G82, G92, G94, G103, G105, I337, I480, J202, N27, O59, P9, *1030*
\registernumber *46*
registernumber d390
\relax *895*
\relax␣ *1039*
\Relbar B476, B484, B486, B492, *1067*
\relbar B473, B488, B490
\relpenalty b324
remove commands:
remove_from_callback d753
\remove_from_callback *47*
\RemoveFromHook h1467, h1594, *183*
\removelastskip . . b481, b483, b485, b487
\renewcommand *79*
\renewcommand B66, B68, B70, B71, B73, B75, B77, B78, B84, B86, B88, B89, B103, B104, B105, B113, B114, I428, I448, I469, f124, *527*
\RenewCommandCopy f461, f463, *96*
\RenewDocumentCommand g2497
\RenewDocumentEnvironment . g2290, g2533
\renewenvironment *80*
\renewenvironment I477, I489, f152
\RenewExpandableDocumentCommand S377, S378, S379, S380, g2553, *177*
\repeat v688, d154, d164, L382, U1131, U1192, U1262, U1325, U1376, U1414, aa369, aa380, aa390, aa401, aa431, aa457, aa467, b457, a84, a86
\requestedLaTeXdate U1477, U1510, U1530, U1616
\requestedpatchdate U1540, U1617
\RequirePackage *820*
\RequirePackage d24, U611, U618, U661, U670, U1078, Y2003, *903*
\RequirePackageWithOptions *820*
\RequirePackageWithOptions U653
reserved@a commands:
\reserved@a: r232, r304, r366, r413, U1108, U1239
reserved@b commands:
\reserved@b: U230, U247
reserved@c commands:
\reserved@c: r712
\reservedb *411*
\RestoreAtCatcode *1037*
\restorecr p480
\ReverseBoolean g2631
\reversemarginpar P387
\rfloor B604
\rgroup B608
\rhd A733
\rho B283
\rhook B479, B480
\right . B625, B627, B629, B631, B636, B637, B638, B639, I155, I160, I184
\Rightarrow B411, B486, B498
\rightarrow B438, B440, B444, B478, B488, B496, B549
\rightarrowfill B531, B547
\rightharpoondown B455
\rightharpoonup B454, B466
\righthyphenmin Z11
\rightleftharpoons B464
\rightline K489
\rightmargin J9, J40, J51, *656*
\rightmark T77, *796*
\rightskip . . v659, H359, H363, H369, H379, H382, H387, H419, H441, J75, K295, K316, O207, O230, b495
\rlap s430, s433, s797, I415, I429, K493, L81, *1053*
\rm *1029*
\rmdefault A6, A208, A398, A407, A439, A450, A482, B50, B120, E7, E613, *525*
\rmfamily A4, A5, A405, A448, A449, A480, A481, D15, *1054*
rmfamily A420
\rmmath *1022*
\rmoustache B565
\rmsubstdefault . B18, B30, E28, E39, E85
\Roman *400*
\Roman t138, *902*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\roman *400*
\roman t137
\romannumeral t143, t144, H192, H209, H255, J43, J234, J245, *628*
\root I66, I343
\rootbox I66
\rq b406
\rule *671*
\rule K384, K401, K418, K424, P477, P495, P513

S

\S s311, *1046*
\samepage *312*
\samepage p11, p28, *1023*
\SaveAtCatcode *1040*
\savebox *670*
\savebox K116
\savecatcodetable d117, d168, d170
\sb I199
\sbox *670*
\sbox q4, s498, s514, J205, K122, K129, K133, K138, K143, b489, *1055*
scan commands:
  \scan_new:N h38
  \scan_stop: n52, S161, S162, S163, V49, V61, X44, X323, X325, X326, g1615, g1712, h375, h382, h411, h419, h451, h463, h471, h499, h1326, h1327, i347, i348, i364, i365, *870*
scan internal commands:
  \s__file_stop W103, W105, W108, W110, W112, W125
  \s__hook_mark h38, h39, h186, h189, h192, h196, h199, h200, h402, h444, h446, h454, h456, h459, h461, h523, h537, h562, h563, h567, h670, h1180, h1193, h1204, h1212, h1255, h1257, h1300, h1302, h1306, h1307, h1314, h1315, i23, i25, i34, i36, i112, i117, i233, i244, i352, i355, i369, i381, *206*
  \s__keys_stop V111, V112
\scdefault w694, A27, B94
\scriptfont x338
\scriptscriptfont x339
\scriptscriptstyle I65, I68
\scriptspace b381
\scriptstyle B337, I64
\scshape s300, w692, w693, A25, A26, D23, *1063*
\searrow B406
\sec I20
\secdef O142
\secondoftwo *347*
\sectionmark O143, *796*
\selectfont q7, s302, s329, s360, s449, s809, s871, s1221, s1255, s1569, v291, v301, v311, w528, w533, w538, w684, w688, w691, w694, w697, w700, w703, w706, x114, x115, x159, x162, x164, A6, A9, A12, A15, A18, A21, A24, A27, A30, A264, A287, A325, A345, A360, A371, A382, A385, A409, A414, A419, A452, A457, A462, A476, A479, A482, A485, A488, A564, A641, A665, A682, A697, E36, E94, E104, E636, E673, E916, E933, P403, P424, *1022*
selectfont x150
seq commands:
  \seq_clear:N h802
  \seq_clear_new:N h810
  \seq_gpop:NNTF W72, h289, h297
  \seq_gpop_right:NN h268
  \seq_gpush:Nn W64, h282
  \seq_gput_right:Nn S23, h83, h257, h261
  \seq_if_empty:NTF h256, h307
  \seq_if_exist:NTF W60
  \seq_if_in:NnTF S9, S136
  \seq_map_inline:Nn S77, S102, S113, S124, S267, S332, g1967, h750, h826, h844
  \seq_mapthread_function:NNN . . . *168*
  \seq_new:N S6, W61, g1951, h28, h33, h795
  \seq_put_right:Nn . . h808, h901, h908
  \seq_set_split:Nnn g1965
  \seq_use:Nnnn h961, h966
seq internal commands:
  \g__mark_classes_seq S6, S9, S23, S77, S102, S113, S124, S136, S267, S332, *799*
\series *1022*
\seriesdefault s1570, z349, A220, A222, A660, A678, A694, A711, A773, B120, *526*
\setattribute *45*
\setattribute d82, d239
\setbox... . . . . *1061*
\setbox0 . . . . . *1057*
\setcounter *400*
\setcounter . . r444, t2, t37, z143, J225, Y2326, Y2329, Y2332, Y2336, *493*
\SetDefaultHookLabel h1469, *215*
\SetKeys V187, *869*
\setlength *408*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\setlength . p83, p243, p442, u4, I497, I502, I503, I504, K43, K204, K265, K268, K341, K440, K441, K442, K471, K472, K479, K480, K481, L176, L384, Y2342, Y2343, Y2344, Y2347, Y2348, Y2352, Y2353, Y2354, Y2358, Y2359, Y2360, *1065*
\SetMathAlphabet v11, y140, y141, z603, B155, B156
\setminus B393
\setrangecatcode . . d96, d104, d113, d114
\SetSymbolFont z458, B145, B146, B147, *1026*
\settodepth *408*
\settodepth u17
\settoheight *408*
\settoheight u17
\settowidth *408*
\settowidth u17
\sf *1029*
\sfcode . . p416, r45, r114, r172, aa250, aa550, b398, b399, b400, b401, b518
\sfdefault A9, A212, A399, A412, A440, A455, A485, B50
\sffamily A7, A8, A410, A453, A454, A483, A484, D16, *532*
sffamily A420
\sfsubstdefault B19, B31, E30, E87
\shape *1024*
\shapedefault s1570, w684, z350, A661, A679, A695, A712, B120, *526*
\sharp B330
\shipout X4, X52, X429, X432, Y604, Y662, *911*
shipout commands:
\l_shipout_box . . . X23, X35, X38, X50, X61, X125, X148, X177, X182, X205, X206, X213, X224, X227, X228, X232, X239, X249, X257, X264, X274, X280, X281, X284, X291, X293, X294, X300, X302, *909*
\l_shipout_box_dp_dim X192, X195, X197, X228, X281, X510, *899*
\l_shipout_box_ht_dim X191, X195, X197, X227, X247, X280, X509, *899*
\l_shipout_box_ht_plus_dp_dim X194, X197, X213, X264, X275, X277, *899*
\l_shipout_box_wd_dim X193, X197, X239, X291, X511, *899*
\shipout_debug_off: X7, X13, X413, *903*
\shipout_debug_on: X7, X8, X412, *903*
\shipout_discard: X341, X341, X409, *901*
\g_shipout_readonly_int X102, X104, X111, X116, X344, X353, X357, X361, X365, X369, *902*
\g_shipout_totalpage_int *902*
\g_shipout_totalpages_int X87, X346, *902*
shipout internal commands:
__shipout_add_background_box:n X178, X204, X204, X336, X418
__shipout_add_background_picture:n . X69, X335, X335, X422
__shipout_add_firstpage_material:Nn X171, X187, X187, X411, X416
__shipout_add_firstpage_specials: X110, X164, X176, X176, X179, *912*
__shipout_add_foreground_box:n X117, X255, X255, X339, X420
__shipout_add_foreground_picture:n . X64, X338, X338, X424
__shipout_debug:n X7, X7, X20, X103, X115, X147, *905*
\g__shipout_debug_bool X6, X10, X15, X21
__shipout_debug_gset: X7, X11, X16, X18
\g__shipout_discard_bool X81, X88, X90, X201, X342
__shipout_drop_firstpage_specials: X126, X165, X176, X181, X183, *912*
__shipout_excuse_extra_page: X382, X390, X390
__shipout_execute: X46, X46, X52, *907*
__shipout_execute_cont: X57, X59, X59
__shipout_execute_main_cont:Nnnn X60, X77, X77, X146, *910*
__shipout_execute_nohooks_cont: X143, X145
__shipout_execute_raw: X134, X134, X150, *910*
__shipout_execute_test_level: X49, X54, X54
__shipout_execute_test_level_raw: X134, X137, X140
__shipout_finalize_box: X26, X28, X44, X123
\l__shipout_firstpage_box X168, X178, X185, *912*
__shipout_get_box_size:N X85, X107, X190, X190, X205, *913*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\l__shipout_group_level_tl X47, X53, X56, X135, X142
\c__shipout_horigin_tl .. X308, X323
__shipout_init_page_origins: X308, X308, X319, X322
\g__shipout_lastpage_handled_bool X120, X186, X363
__shipout_picture_overlay:n X321, X321, X336, X339
\l__shipout_raw_box X25, X138, X146, X148, X177, X182, *909*
__shipout_run_firstpage_hook: X108, X161, X161, X170, *911*
\l__shipout_saved_badness_tl X202, X208, X216, X229, X234, X242, X251, X259, X267, X279, X286, X296, X304
__shipout_saved_protect: X83, X131, X151, X151
\l__shipout_tmp_box X202, X215, X217, X218, X219, X223, X241, X243, X244, X245, X248, X266, X268, X269, X270, X276, X295, X297, X298, X299, X301, X327, X329, X330, X331
\c__shipout_vorigin_tl .. X308, X325
shipout/after X152, *899*
shipout/background X152, *899*
shipout/before X152, *899*
shipout/firstpage X152, *899*
shipout/foreground X152, *899*
shipout/lastpage X152, *899*
\ShipoutBox X23, X437, X492, *904*
\ShipoutBoxDepth X457, X509
\ShipoutBoxHeight X456, X509, *924*
\ShipoutBoxWidth X458, X509
\shortstack M132, M147, M152, M815, M832
\show f505, f575, f576, *99*
show commands:
\show_hook:n *237*
\showbox Y1917
\showboxbreadth b598, b622, b639, b664, Y1917, b370, b521
\showboxdepth . b597, b621, b638, b665, v647, v691, v708, Y1917, b371, b521
\ShowCommand f498, g1163, g1307, *97*
\ShowDocumentCommandArgSpec g2636
\ShowDocumentEnvironmentArgSpec .. g2636
\ShowFloat Y1898
\ShowHook h1493, h1599, *190*
\showhyphens v636, *1074*
\showoutput b520, *1054*
\showoverfull b579, b587, b519, b522, b544, *1054*
\showtokens f611, *101*
\Sigma B303
\sigma B284
\sim B445, B457
\simeq B446
\sin I9
\sinh I11
\size *1022*
\skew B544
\skip d33, K358, P391, Y316, Y492, b28, b53, b92, b208, b250, b295
skip commands:
\skip_eval:n e162
\skip_zero:N X220, X221, X222, X271, X272, X273, n23
\skipdef d229, b45, b53, b92
\skipeval *76*
\skipeval e155, e172, *76*
\skipzero d229
\slash f785, f806, b474
\sldefault w691, A24, B94
\SLiTeX *1044*
\sloppy K300, K319, T86, T91
sloppypar (env.) T91
\sloppypar T91
\slshape s440, s800, w689, w690, A22, A23, D22, E627
\small *184*
\smallbreak f786, f807, b482
\smallint B357
\smallskip p400, b483
\smallskipamount p400, p403, b482
\smash o25, B473, B547, B548, B551, B552, I126
\smile B450
\sourceLaTeXdate c161, U65, U103
\sp I199
\space b414, *1038*
\spacefactor o24, o26, p129, p138, p157, p171, p183, p197, p211, p416, p429, p434, s70, s73, P531, P533, b472, b473, *1065*
\spacefactor␣in␣math␣mode␣gh/643 . *1088*
\spaceskip E6, E612
\spadesuit B334
\span L383
\special o22, *912*
\SplitArgument g2631
\splitfirstmark Y2247
\SplitList g2631, *179*
\splitmaxdepth P469, P488, P506, Y2241, b377
\splittopskip ... P468, P487, P505, b389
\sqcap B376

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\sqcup B377
\sqrt I342, *1053*
\sqrtsign B529, I71, I342, *1053*
\sqsubset A729
\sqsubseteq B399
\sqsupset A730
\sqsupseteq B400
\SS s304, s534, s1157, aa585, *1058*
\ss . . . s254, s406, s557, s784, s1132, aa585
\sscdefault w536, w609, w706
\sscshape . . w536, w608, w704, w705, D31
\stackrel I340
\stamp *1032*
\star B397
\stepcounter *400*
\stepcounter t17, t27, v601, z48, G65, G82, G94, G105, I350, I410, I490, P452, P520, Y648, Y707, *1025*
\stop H165
\storedpar d156, d161
str commands:
\c_backslash_str i146, i315
\c_hash_str g1293
\str_case:nn g1010, i411
\str_case:nnTF g2482, i39
\str_case_e:nnTF g2162
\str_count:n i158
\str_gset:Nn h1488
\str_head:n g2107
\str_if_eq:nn *229*
\str_if_eq:NNTF W552
\str_if_eq:nnTF e137, W131, W546, W556, g357, g1050, g1055, g1374, g1746, g1759, g1761, g1791, g1811, g1813, g1832, g1859, g1887, g1889, g1914, g1916, g1939, g2218, h184, h276, h316, h348, h350, h425, h480, h527, h539, h608, h615, h954, h1037, h1117, h1206, h1341, h1374, i209, i287, i373, i376, *158*
\str_if_eq_p:nn g416, g417, g418, g419, h543, h837
\str_map_function:NN e141
\str_new:N g19
\str_set:Nn W400, W401, g176, g177, g219, g2040
\str_tail:n . . g1746, g2104, g2130, *157*
\str_uppercase:n g2418
str internal commands:
__str_if_eq:nn h23, *205*
\strcmp U283, U299
\stretch p456
\string *1084*
\stripmeaning *1029*
\strut I178, I179, L29, f787, f808, b490, *204*
\strutbox x189, K384, K401, K418, L186, L187, P469, P477, P488, P495, P506, P513, b490
\subparagraphmark O143
\subsectionmark O143, *795*
\subset B426
\subseteq B428
\substdefault *1078*
\subsubsectionmark O143
\succ B420
\succeq B423
\sum B350
\sup I24
\superreject *1056*
\suppressfloats Y2008
\supset B425
\supseteq B427
\surd B336
\swarrow B408
\swdefault w531, w607, w703
\swshape . . . w531, w606, w701, w702, D30
\symbol s162, A619
\symletters E8, E14, E614, E1139
\symoperators B643
sys commands:
\sys_if_engine_luatex:TF X26

T

\T s335, s337, s339, s341, s343, s345, s347, s349, s351, s374, U1457, U1461, U1462, l23
\t s282, s741, s849, E157, E158, E185, E189, E191, E203, E206, E208, E688, E859, E1126, E1128, *1046*
tabbing (env.) L71
\tabbing L71
\tabbingsep L130, L132, L166
\tabcolsep L259, L338
\tableofcontents *622*
\tabskip I195, I196, I356, I359, I362, I364, I495, I508, I511, I513, L167, L192, b501, *1026*
tabular (env.) L174
\tabular L174
\tabular* L175
\tabularnewline L194, L207, *1050*
\tan I15
\tanh I17
\tau B285
\tencirc C10, M125, M678
\tencircw C10, M128
\tenln C9, M124, M126, M677, M679
\tenlnw C9, M127, M129

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\test *1032*
\TeX q1, q12, *1077*
TEX and LATEX 2ε commands:
\...-h@@k *1077*
\..@without@substitution *463*
\@ p425, q2, d20, d862, U43, U58, U71, U80, U118, aa517, f728, f729, a68, i292, l19, *1027*
\@...hook *210*
\@?@? *1027*
\@@ r710, r730, x510, x512, x513, L238, L239, L240, L250, Y10, Y11, a334, a335, k15, k19, k20, k21, k22, k24, k27, k28, k30, k31
\@@DeclareMathDelimiter *1038*
\@@defaultsubs v585
\@@enc@update . s183, v259, v263, *1050*
\@@end . r687, r688, H32, H99, H165, a225, f23, Z18, aa604, aa625, a72, *351*
\@@endpbox L193, L236, L386
\@@eqncr . . I368, I390, I400, I405, I514
\@@fileswith@pti@ns U540, U559, U1014
\@@hyph f24, f745
\@@hyphenation s205
\@@if@newlist Y601, Y646, Y659, Y705
\@@ifdefinable s17, f132
\@@input r585, r598, r638, H26, H79, f22, U1604, W172, W188, W196, aa331, a71, *1032*
\@@italiccorr . . D113, D117, f25, *1034*
\@@line K489
\@@math@bgroup D131, D138
\@@math@egroup D128
\@@par n98, n135, H165, H421, H426, H429, H443, H447, H450, J82, J85, K266, K288, K309, L199, O67, O118, f21, Y257, m4, *1060*
\@@patterns s205
\@@protect f254, f260, f269
\@@sqrt *1059*
\@@startpbox L193, L236, L386
\@@sverb H500, *636*
\@@underline K445, K448, K449
\@@unprocessedoptions U926, U991, U1068
\@@warning l215, *1030*
\@Alph t140, t156, *104*
\@DeclareEncodingSubset E45, E47, E48, E49, E50, E53, E60
\@DeclareMathDelimiter z875, z894, *1038*
\@DeclareMathSizes . . v206, v207, v209
\@Esphack p190, P201, P223, P241, *1024*
\@Ialph *1040*
\@IncludeInRele@se c68
\@IncludeInRelease c68
\@M p11, p12, p13, p14, p15, p16, p17, p18, p119, v654, v661, x439, x452, I378, J194, L56, O67, O100, O118, O130, O209, O232, f37, f39, Y176, Y195, Y198, Y258, b21, b475, b476
\@MM . P469, P488, P506, Y299, b21, *275*
\@Mi Y136, j3
\@Mii P53, P122, P194, P216, P241, P311, Y295, Y1161, Y1328, j3
\@Miii P55, P124, P313, Y298, j3
\@Miv P195, P201, P217, P223, Y272, j3
\@Roman t138, t144, *1063*
\@TeXversion a329, l28, *2*
\@abspage@last X105, X111, X349, X351, X353, X361, X365, X368, X407, X408, *920*
\@acci A775, K290, K311, *1040*
\@accii A775, K290, K311, *1040*
\@acciii A775, K290, K311, *1040*
\@acol L168, L178, L260, L261, L273, L274, L277, L294, L309, L317, L327
\@acolampacol L258, L275, L277, L284, L292, L326, L329
\@activechar@info Y577, *1037*
\@activechar@warning *1037*
\@addamp L251, L260, L261, L276, L290, L327, L328
\@addfield L43, L53, L86, L93, L125, L140, L142
\@addmarginpar Y331, Y1813
\@addtobot Y977, Y1064, Y1131, Y1183, Y1292, Y1351
\@addtocurcol . . . Y328, Y1068, Y2001
\@addtodblcol Y856, Y1564
\@addtofilelist r64, r132, r187, a104, r585, r707, a106, A749, A752, A759, A762, A769, A772, W169, W188, W196, aa279, aa282, aa645, *1057*
\@addtonextcol . . Y855, Y1388, Y2002
\@addtopreamble L311, L324, L330, L331, L332, L334, L346
\@addtoreset t16, t39, t44, t89, t115, t118
\@addtotoporbot Y1014, Y1177, Y1345, Y1437, Y1526
\@afterheading O92, O125, *1061*
\@afterindentfalse O45
\@afterindenttrue O43, O124, O208, O231
\@alph t139, t152, P399, *104*
\@ampacol L258, L275, L286, L329

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@arabic t43, t111, t123, t136, t142, P397
\@argarraycr L203, L204
\@argdef f80
\@argrsbox K469
\@argtabularcr L210, L211
\@array L181, L182
\@arrayacol L168, L258
\@arrayclassiv L169, L331
\@arrayclassz L168, L275
\@arraycr L170, L201, L203
\@arrayparboxrestore K280, K322, L384
\@arrayrule L309, L311, L315, L317, L319, L346
\@arstrut L192, L237, L343
\@arstrutbox L185, L218, L343, L385, *1038*
\@author O8, O32
\@auxout r216, r222, r266, r284, r308, r341, r370, r393, r417, r432, G57, O181, R7, R8, R39, R49, R57, R67, R84, X360
\@backslashchar . . . B266, U1193, U1326, U1415, f219, f469, f582, f594, f598, f599, f604, l234, l236, *1040*
\@badcrerr l277, *1038*
\@badend H297, l247, *1025*
\@badlinearg M165, M177, M188, M189, M193, M242, M247, M257, M262, M275, l267
\@badmath I262, I264, I269, I272, I281, I293, I298, I307, I320, I325, I437, I449, I465, I474, l251
\@badpoptabs L85, L151, l255
\@badrequireerror U434, U1076
\@badtab L22, L87, L108, L114, L121, L148, l258
\@begin@tempboxa K27, K42, K203, K266, K470, K478, *1029*
\@begindocumenthook r61, r126, r129, r181, r184, R53, U1025, U1046, *210*
\@begindvi Y625, Y684, Y712, *905*
\@begindvibox X447, X448, Y86, Y713, *900*
\@beginparpenalty p14, I440, I452, I478, J23, J170, *656*
\@begintheorem N30, N35
\@bezier M684, M683
\@bibitem R3, R8
\@biblabel R4, R97
\@bitor Y15, Y883, Y903, Y939, Y962, Y1029, Y1113, Y1123, Y1271, Y1282, Y1424, Y1511, Y1629, Y1754
\@botlist Y65, Y384, Y386, Y431, Y433, Y719, Y740, Y749, Y750, Y991, Y994, Y1029, Y1123, Y1282, Y1957, Y1985
\@botnum P274, Y109, Y988, Y989, Y994, Y998, Y1460, Y1465, Y1553, Y1560, Y1949, Y1977, Y2019
\@botroom P275, Y110, Y991, Y994, Y1950, Y1978
\@boxfpsbit Y2067, Y2069, Y2074
\@break@loop *1038*
\@break@tfor r558, r575, D98, k31, *1038*
\@bsphack . . . p36, p125, p340, p356, p374, p390, G56, P52, P121, P310, Q6, Q18, Q23, Q35, R63, R80, Y1884
\@caption P12, P14
\@captype P5, P9, P12, P40, P88, P109, P157, Y2031
\@car q14, s89, s110, f53
\@carcube f55, f135, f585
\@cclv Y300, Y304, Y382, Y383, Y412, Y429, Y430, Y459, Y485, Y489, Y490, aa67, b16, *904*
\@cclvi d30, d58, U1191, U1324, U1413, b21, b57, b82, b93, b95, b99, b159, b173
\@cdr r250, f53, f671, f672
\@centercr H320, H358, H363, H368, H378, H382, H386, *1077*
\@centering I347, I348, I356, I359, I362, I507, I511
\@cflb Y716
\@cflt Y716
\@changed@cmd s3, s63, s223, v131, v267, aa476, *1051*
\@changed@x s3, s211, s219, *1050*
\@changed@x@err *1058*
\@changed@x@mouth . . . s211, s219, *1050*
\@charlb r438, r446
\@charrb r440, r446
\@chclass L271, L272, L335, L348, L353
\@check@IncludeInRelease c68
\@check@c f189, f191
\@check@eq f195, f196, f200
\@checkcommand *1042*
\@checkend H16, H71, H213, H220, H272, H287, H296, *1052*
\@chnum L279, L298, L335, L350, L351, L352
\@circ M622, M640, M649, M654, M657
\@circle M605, M606
\@circlefnt M125, M128, M447, M491, M520, M545, M615, M631, M663, M678

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@cite R36, R95
\@cite@ofmt R44, R96
\@citea R35, R37
\@citeb R38, R39, R40, R43, R44, R66, R67, R68, R69, R83, R84, R85, R86
\@citex R20, R21, R29, R34, *787*
\@citex@checkblank . . . R17, R18, R30
\@classi L271, L307
\@classii L271, L321
\@classiii L271, L326
\@classiv L169, L180, L272
\@classoptionslist U9, U481, U496, U497, U514, U726, U727, U755, U756, U782, U783, U1685, V61, V90, *1085*
\@classv L272, L332
\@classz L168, L179, L271
\@cline L367
\@clnht M195, M196, M204, M206, M208, M218, M225, M273, M672
\@clnwd M197, M203, M207, M209, M210, M672
\@cls@pkg . U290, U291, U304, U305, U865, U875, U923, U970, U1000, U1052, U1061, U1063, U1080, U1538, U1613, U1635, U1665, h1407
\@clsextension U31, U156, U164, U220, U320, U336, U348, U430, U452, U463, U481, U495, U513, U612, U627, U651, U725, U754, U781, U869, U916, U943, U1004, U1017, U1053, V63, V101, *846*
\@clubpenalty r7, r25, r94, r151, J128, J196, O106, O135
\@colht r22, r91, r148, P273, P275, P278, P284, P285, P298, P299, Y114, Y231, Y242, Y251, Y252, Y387, Y399, Y434, Y447, Y476, Y507, Y537, Y543, Y547, Y557, Y562, Y647, Y706, Y779, Y817, Y861, Y886, Y905, Y945, Y967, Y1644, Y1770, Y2132, aa155
\@colnum P276, Y111, Y997, Y1042, Y1111, Y1112, Y1140, Y1148, Y1269, Y1270, Y1302, Y1314, Y1422, Y1423, Y1460, Y1465, Y1509, Y1510, Y1552, Y1559, Y1945, Y1973, Y2012, Y2187
\@colroom r23, r92, r149, Y115, Y252, Y273, Y274, Y285, Y288, Y387, Y434, Y779, Y996, Y1041, Y1107, Y1110, Y1139, Y1264, Y1268, Y1301, Y1418, Y1421, Y1504, Y1508, Y1946, Y1974, Y2142, Y2147, Y2192, aa154, *1059*
\@combinedblfloats Y752, Y2266, Y2305
\@combinefloats Y503, Y716
\@comdblflelt Y752
\@comflelt Y722, Y738, Y752
\@compatibility *1032*
\@cons t44, P193, P215, P239, P379, f52, Y237, Y890, Y909, Y925, Y949, Y951, Y971, Y973, Y1143, Y1211, Y1307, Y1380, Y1453, Y1543, Y1646, Y1669, Y1772, Y1797, Y1814, Y1815, Y2193, b196, b213
\@contentsline@destination O188, O190, O197, *757*
\@contfield L50, L141, L153
\@copy@... . . . . *97*
\@copy@DeclareRobustCommand f483, f520, f541, f616, f619
\@copy@newcommand f306, f484, f520, f562, f591, f616, f622, *91*
\@copytexsys *1032*
\@ctrerr . . t155, t159, t173, t181, l243
\@curfield L16, L41, L47, L51, L52, L54, L130, L131
\@curline . L16, L27, L39, L44, L53, L54, L55, L90, L91, L103, L128, L129
\@curr@enc s154, s156
\@curr@file r226, r227, r236, r238, r262, r270, r451, r470, r605, r620, U850, U1138, U1143, U1149, U1155, U1159, U1170, U1179, U1206, U1269, U1274, U1280, U1303, U1312, U1338, W267, W375, W377, *888*
\@curr@file@reqd W267, W377, W381, *890*
\@currbox P60, P91, P95, P129, P160, P164, P193, P214, P215, P239, P257, P259, P261, P319, P322, P327, P331, Y213, Y214, Y225, Y226, Y228, Y229, Y237, Y311, Y312, Y855, Y856, Y1104, Y1106, Y1114, Y1137, Y1141, Y1143, Y1158, Y1199, Y1211, Y1259, Y1262, Y1299, Y1304, Y1307, Y1324, Y1369, Y1380, Y1412, Y1428, Y1442, Y1453, Y1495, Y1532, Y1543, Y1583, Y1587, Y1598, Y1604, Y1606, Y1610, Y1615, Y1624, Y1633, Y1639, Y1646, Y1669, Y1704, Y1708, Y1720, Y1727, Y1729, Y1733,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

Y1739, Y1749, Y1764, Y1772, Y1797, Y1815, Y1824, Y2037, Y2038, Y2067, Y2097, Y2102, Y2148, Y2151, Y2163, Y2171, Y2188, Y2193, b275, b276, b277
\@currdir a111, a133, a135, a141, a143, a149, a151, a156, a158, a168, a181, a246, U1121, U1143, U1170, U1252, U1274, U1303, U1386, a259, a272, *9*
\@current@cmd s25, v271, *1050*
\@currentcounter . . G64, G66, G81, G83, G93, I352, I492, K379, P471, *1088*
\@currentlabel . . . G58, G67, G84, G95, G106, G114, I351, I491, K380, K397, K414, P472, P490, P508, *649*
\@currenvir H3, H176, H231, H248, H281, H297, J112, K149, U1181, U1193, U1201, U1205, U1212, U1314, U1326, U1334, U1338, U1344, U1403, U1415, U1423, U1427, U1433, l249, *289*
\@currenvline H177, H232, H249, H282, H298, K150, l249
\@currext U30, U42, U57, U70, U79, U117, U316, U319, U320, U335, U336, U347, U348, U452, U463, U474, U481, U495, U513, U542, U622, U635, U637, U645, U659, U821, U822, U824, U827, U830, U835, U840, U842, U847, U853, U861, U867, U869, U873, U878, U884, U893, U896, U901, U904, U907, U909, U910, U912, U916, U925, U927, U928, U933, U936, U939, U943, U949, U962, U967, U968, U973, U979, U983, U985, U986, U988, U990, U992, U993, U996, U1002, U1004, U1017, U1030, U1053, U1069, U1070, V28, V63, V70, V75, V78, V101, V103, V106, V155, *845*
\@currextension *1026*
\@currlist . P193, P215, P379, Y67, Y311, Y388, Y391, Y435, Y438, Y1814
\@currname . . r719, c68, c113, c121, U29, U41, U56, U69, U78, U116, U288, U290, U302, U304, U316, U319, U335, U347, U474, U542, U635, U637, U645, U659, U819, U822, U824, U827, U830, U835, U837, U840, U842, U847, U852, U861, U865, U867, U873, U875, U876, U878, U884, U893, U895, U901, U904, U907, U909, U910, U914, U918, U925, U927, U928, U933, U936, U940, U944, U949, U961, U985, U986, U988, U990, U992, U993, U1030, U1061, U1063, U1070, U1080, U1613, U1635, U1665, V28, V40, V70, V75, V78, V103, V106, V120, V122, V133, V155, V187, h206, h212, h267, *844*
\@currnamestack U33, U136, W543, h264, *826*
\@curroption *1026*
\@curroptions U474, U482, U532, U551, U1070, U1071
\@currpath U15, U46, U139, U288, U290, U820, U835, U842, U851, U893, U894, U921, *843*
\@currpkg@reqd U318, U845, U847, U856, U889, U903, U906, U921, U923, *1082*
\@currsize A639, *1025*
\@currtype Y119, Y880, Y881, Y882, Y883, Y900, Y901, Y902, Y903, Y1029, Y1113, Y1123, Y1271, Y1282, Y1424, Y1511, Y1629, Y1754, Y2037, Y2039, Y2040, Y2043
\@curtab L11, L26, L86, L87, L88, L94, L95, L98, L102, L103, L107, L146, L147, *1057*
\@curtabmar L11, L25, L26, L38, L44, L89, L102, L106, L107
\@d@r a164, a165
\@dashbox M324, M325, M326, M327, M328, M331, M337, M339, M349, M351, M352, M353, M354, M358, M362, M365, M382, M384, M385, M386, M387, M390, M394, M396, M405, M407, M408, M409, M410, M413, M417, M422, M674
\@dashcnt M317, M319, M320, M321, M322, M323, M336, M338, M341, M343, M344, M345, M347, M348, M361, M364, M376, M377, M378, M379, M380, M381, M393, M395, M398, M399, M400, M401, M403, M404, M416, M421, M674
\@dashdim M316, M317, M318, M319, M320, M322, M325, M327, M328, M329, M336, M338, M340, M341, M342, M343, M344, M347, M351, M353, M354, M355, M363, M366, M375, M376, M377, M378, M380, M384, M386, M387, M388, M393, M395, M397, M398,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

M399, M400, M403, M407, M409, M410, M411, M419, M424, M674
\@date O9, O33
\@dbflt P32, P264, *1046*
\@dblarg O54, O142, P12, f693
\@dbldeferlist . P239, Y70, Y445, Y450, Y452, Y818, Y825, Y826, Y1754, Y1797, Y1961, Y1990, *1071*
\@dblfloat P31
\@dblfloatplacement r31, r100, r158, P280, Y401, Y449, Y1942, Y1970, Y2271, Y2311
\@dblflset P26
\@dblfpbot P290, P304, Y2355
\@dblfpsep P289, P303, Y2355
\@dblfptop P288, P302, Y2355
\@dbltoplist . . . Y69, Y232, Y235, Y237, Y397, Y398, Y445, Y446, Y757, Y761, Y763, Y764, Y1641, Y1646, Y1766, Y1772, Y1960, Y1988
\@dbltopnum P283, P297, Y107, Y127, Y238, Y240, Y768, Y1580, Y1581, Y1645, Y1648, Y1676, Y1681, Y1701, Y1702, Y1771, Y1775, Y1804, Y1809, Y1953, Y1981
\@dbltoproom P284, P286, P298, P300, Y108, Y1583, Y1586, Y1587, Y1596, Y1597, Y1600, Y1603, Y1606, Y1610, Y1614, Y1618, Y1623, Y1643, Y1704, Y1707, Y1708, Y1717, Y1718, Y1719, Y1722, Y1726, Y1729, Y1733, Y1738, Y1742, Y1747, Y1748, Y1769, Y1954, Y1982
\@dec@text@cmd s3
\@declarecommandcopylisthook f480, f482, f494, g1018, *97*
\@declaredoptions U8, U437, U478, U516, U537, U556, U1023, *1026*
\@declareoption . . U435, U436, U444
\@defaultfamilyhook A429, A664, A681, A696, A701, A716, *1079*
\@defaultsubs v539, v573, v585, H46, H86, *1055*
\@defaultunits . v214, v218, v219, v220, v235, v328, x179, x181, M13
\@defaultunitsset K53, K64, M8, M29, M30, M32, M34, M60, M63, M84, M85, M107, M108, M164, M241, M316, M318, M332, M340, M342, M357, M480, M481, M612, M648, M690, M691, M693, M694, M697, M698, M700, M701, M712, M713, M715, M716, M718, M719, M721, M722
\@defdefault@ds . . U435, U440, U445
\@deferlist Y68, Y384, Y393, Y394, Y397, Y402, Y404, Y410, Y431, Y440, Y442, Y780, Y788, Y789, Y800, Y805, Y806, Y1113, Y1211, Y1271, Y1380, Y1424, Y1453, Y1511, Y1543, Y1629, Y1669, Y1959, Y1987
\@definecounter t12, t36, I336, J227, J228, J229, J230, N8, N16, P396, P398
\@depth . . x191, B558, B559, B561, B562, K444, K488, L187, L219, M227, M300, M303, M324, M333, M383, M391, M727, M783, f26, Y1853
\@dir a163, a166, a168, a170, a171
\@disable@packageload@do U840, W478
\@dischyph K289, K310, f730, f764, *1035*
\@doclearpage Y296, Y371
\@documentclass *1028*
\@documentclasshook U3, U731, U759, U786, *1033*
\@doendpe H214, H221, H273, H288, J123
\@dofilelist r716, r736, H38, H81, *1050*
\@donoparitem J144, J158
\@dot M605, M643
\@dotsep O215, O238
\@dottedtocline . . O200, O226, O227
\@downline M297, M301, M306
\@downvector M268, M306
\@eha r223, r267, r285, s52, s84, c192, v28, v58, v102, v144, v187, v253, v339, x106, z25, z70, z99, z172, z240, z270, z302, z416, z437, z469, z510, z555, z560, z615, z733, z737, z741, z776, z780, z784, z841, z851, z936, z941, z944, z976, z979, z1052, z1055, z1058, z1125, z1131, D146, E24, E81, E915, E924, H175, H230, H247, H280, R71, R88, f280, f319, f347, Y1878, Y1894, l219, l237, l239, l241, l250, l252, l282
\@ehb Y234, Y390, Y437, l219, l244, l270, l272, l274
\@ehc c181, H509, H524, H539, H552, I409, J220, O31, f128, f155, U1665, f469, l219, l277, l280, l286, l288
\@ehd c99, c156, z118, L100, L109, e88, P6, U692, U923, l219, l246, l254, l257, l259, l265
\@elt r439, s1572, s1574, t20, t35, t53, t56, A141, A152, A154, A155, A180, A505, A507, A508,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

A518, A742, B17, B25, f52, Y8, Y11, Y15, Y27, Y30, Y31, Y32, Y33, Y38, Y39, Y40, Y41, Y42, Y43, Y44, Y45, Y47, Y51, Y57, Y58, Y59, Y60, Y500, Y722, Y733, Y738, Y748, Y760, Y762, Y790, Y807, Y827, Y846, Y859, Y866, Y917, Y920, Y929, Y1920, Y1932, *523*
\@empty k14, *520*
\@emptycol Y198, Y245, Y248, Y277, Y281, *1037*
\@end@check@IncludeInRelease c140, c142
\@end@tempboxa K36, K45, K208, K279, K476, K486
\@enddocument@kernel@warnings H39, H41, H101
\@enddocumenthook . H70, U1025, U1047
\@endfloatbox P190, P211, P236, P248
\@endparenv J120, J123, *664*
\@endparpenalty p15, I441, I453, I479, J23, J124, *656*
\@endpbox L193, L236, L266, L333, L384, L387
\@endpefalse H181, H235, H252, H285, J129, J131, J135, J136, J138, K152, *1029*
\@endpeltrue J138
\@endpetrue J124, J126, J134
\@endpreamblehook *336*
\@endtheorem N13, N19, N25, N35
\@enlargepage . . Y1863, Y1868, Y1870
\@ensuredmath I420, I422
\@enumctr J234, J237, J238
\@enumdepth J226, J232, J233, J234, *667*
\@enumspacing *667*
\@eqcnt I344, I406, I411, I494, I509, I510, I512
\@eqncr . . . I357, I375, I412, I413, I496
\@eqnnum I338, I339, I410, I427, I486, *1024*
\@eqnsel I344, I508, *1026*
\@eqnswfalse I374
\@eqnswtrue I346, I353, I411, I493
\@eqpen . . . I344, I378, I380, I391, I401
\@er@ext *1027*
\@err@ l37, l41, l44, l52, l64, l68, l71, l79
\@esphack p38, p131, p345, p362, p379, p396, G59, P385, Q17, Q19, Q34, R74, R90, Y1886, *1024*
\@evenfoot T12, T15, Y615, Y674
\@evenhead T12, T15, Y614, Y673
\@execute@begin@hook H178, H182, H185, *626*
\@executeoption *1027*
\@expandtwoargs c185, U222, U287, U480, U516, U570, U579, f217
\@expast L239, L267
\@expl@@@filehook@clear@replacement@flag@@ U386, U409, W296, W319, W340, W516
\@expl@@@filehook@drop@extension@@N W293, W294, W316, W317, W337, W338, W518, *888*
\@expl@@@filehook@file@pop@@ U858, W157, W522, W532
\@expl@@@filehook@file@pop@assign@@nnnn W162, W524, *885*
\@expl@@@filehook@file@push@@ U841, W151, W520
\@expl@@@filehook@if@file@replaced@@TF W290, W313, W334, W514, *890*
\@expl@@@filehook@if@no@extension@@nTF W286, W309, W330, W504, W506, W531
\@expl@@@filehook@normalize@file@name@@w W292, W315, W336, W512
\@expl@@@filehook@resolve@file@subst@@w U384, U407, W289, W312, W333, W510
\@expl@@@filehook@set@curr@file@@nNN U383, U406, U813, W375, W381, W508, *890*
\@expl@@@hook@curr@name@pop@@ U89, h1575
\@expl@@@hook@curr@name@push@@n *1083*
\@expl@@@initialize@all@@ H186, h1575
\@expl@@@mark@update@dblcol@structures@@ S368, S383, Y468
\@expl@@@mark@update@singlecol@structures@@ S368, S382, Y471
\@expl@@@shipout@add@background@box@@n X415, X500
\@expl@@@shipout@add@background@picture@@n X415, X504
\@expl@@@shipout@add@firstpage@material@@Nn X415, X497
\@expl@@@shipout@add@foreground@box@@n X415, X502
\@expl@@@shipout@add@foreground@picture@@n X415, X506
\@expl@char@generate@@nn e142, f709, *1082*
\@expl@cs@⟨*thing*⟩@spec@@N *1081*
\@expl@cs@argument@spec@@N e139, e150, f610
\@expl@cs@prefix@spec@@N e138, e149, f607

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@expl@cs@replacement@spec@@N e140, e151, f568, f602, f610
\@expl@cs@to@str@@N e133, e136, e145, e147, f477, f534, f554, f556, f557, f570, f582, f594, f598, f599, f604, *1081*
\@expl@finalise@setup@@ e30, aa268, aa269
\@expl@pop@filename@@ e26, U88, U92, U98, U109, *1081*
\@expl@push@filename@@ e24, U37, U39, U52, U54, U64, U76, U96, U102, *824*
\@expl@push@filename@aux@@ e25, U37, U48, U60, U64, U82, U102, h1485, *251*
\@expl@str@if@eq@@nnTF e137, e148, U287, f441, f443, *1081*
\@expl@str@map@function@@NN e141, e152, f706, *104*
\@expl@str@map@function@@NN and \@expl@char@generate@@nn . . . *1082*
\@expl@sys@load@backend@@ r17, e21, e23
\@expl@text@lowercase@@n aa565
\@expl@text@uppercase@@n aa565, *1089*
\@extra@page@added H57, X385
\@failedlist . . Y844, Y867, Y883, Y890, Y903, Y909, Y925, Y939, Y962
\@fcolmadefalse Y835
\@fcolmadetrue Y923
\@file-subst@⟨*file*⟩ *886*
\@filef@und r490, r511, r532, r555, r572, r585, r638, W155, W172, W188, W196, *884*
\@filehook@file@push *844*
\@filehook@set@CurrentFile r314, r375, U843, W152, W364
\@filelist r63, r131, r186, r706, r707, r718, A749, A759, A769, aa279, aa629, aa645
\@fileswfalse r199, U1117, U1118, U1248, U1249
\@fileswith@pti@ns U434, U540, U559, U717, U718, U722, U724, U752, U753, U779, U780, U807, U1014, *1026*
\@fileswith@ptions U712, U713, U715, U719
\@fileswithoptions U612, U619, U627, U710
\@fileswtrue r5, U1100, U1103, U1156, U1160, U1231, U1234, U1289, U1293
\@finalstrut . . K384, K401, K418, K487, L385, P477, P495, P513, *1038*
\@firstampfalse . . . L254, L277, L294
\@firstamptrue L262
\@firstcolfirstmark Y2248, Y2249, Y2253
\@firstcoltopmark Y2246, Y2254
\@firstcolumnfalse Y2238, Y2283
\@firstcolumntrue r28, r97, r155, Y98, Y207, Y2257, Y2289
\@firstofone r125, r180, r458, s68, s153, d12, d100, d108, x346, d166, z53, z81, z146, z221, z251, z282, z886, H69, I418, L372, e34, e61, e76, P10, R38, R66, R83, U859, U888, f212, W353, W370, f465, f470, f471, f474, f475, aa359, *1081*
\@firstoftwo o17, r512, r556, r573, s133, c82, t191, t196, z890, A510, E69, E836, E887, E903, G23, G40, e35, e43, T16, U161, U193, U205, U228, U246, U1674, f212, f442, f444, f466, f537, f587, f645, f655, f665, f692, f716, a90, *349*
\@firsttab L2, L74, L75, L76, L106, L118, *1038*
\@flcheckspace . . Y991, Y1027, Y2138
\@flfail Y867, Y918, Y939, Y949, Y962, Y971
\@float P26, P32
\@floatboxreset . . . P101, P170, P174
\@floatpenalty P3, P53, P55, P58, P122, P124, P127, P191, P194, P199, P201, P212, P216, P221, P223, P237, P241, P311, P313, P317, P321, P379
\@floatplacement r31, r100, r158, P271, Y149, Y209, Y253, Y479, Y1943, Y1971, *1028*
\@flsetnum Y988, Y1024, Y1111, Y1269, Y1422, Y1509, Y1580, Y1701, Y2106
\@flsettextmin Y1087, Y1239, Y1408, Y1491, Y2122
\@flstop Y2008
\@flsucceed Y860, Y868, Y917, Y951, Y973
\@fltovf P93, P162, P322, l273
\@flupdates Y994, Y1039, Y2184
\@flushglue H359, H363, H369, H379, H382, H387, H420, H442, J76, K296, K317, j17
\@fnsymbol t141, t160
\@font@aliasinfo x539

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@font@info v133, v171, v177, v366, v383, v621, w478, x30, x38, x46, x74, x87, x154, x200, x214, x225, x239, x255, x261, x274, x281, x288, x293, x303, x315, x327, x491, x503, x508, x515, x545, x558, x566, z180, z197, z206, z312, z327, z374, z420, z489, z495, z539, z552, z635, z724, z767, z832, z926, z1093, z1122, E55, E56, E99, aa478
\@font@series@contextfalse A502, A538
\@font@series@contexttrue A521, A525, A537
\@font@shape@subst@warning w445, w448, w453, w511, w658, w661, *455*
\@font@warning v3, v535, v540, v567, v574, w456, x19, x33, x41, x49, x61, x77, x476, x490, x502, x507, x514, x557, x565, y30, H43, H83, aa300
\@fontenc@load@list s1573, A742, B17, B25, *1079*
\@fontswitch D126, D128, *1038*
\@footnotemark P454, P460, P522, P528, P529, P555
\@footnotetext K349, P454, P460, P461, P538, P544
\@for r232, r304, r366, r413, r718, R36, R65, R82, U230, U247, U478, U497, U514, U532, U537, U551, U556, U592, U602, U1071, U1108, U1239, k16, *787*
\@forced@seriesfalse w394, w407, x140
\@forced@seriestrue w398, w409
\@forloop k19, k20
\@fornoop k15, k23, k29
\@fortmp U590, U592, U1107, U1108, U1238, U1239, k17, k18, k26
\@fpbot P290, P304, Y865, Y2349
\@fpmin . . P278, P287, P301, Y113, Y922, Y1951, Y1979, Y2201, Y2218
\@fps P41, P42, P44, P47, P64, P110, P111, P113, P116, P133, Y2029, Y2031, Y2034
\@fpsadddefault P45, P48, P114, P117, Y2026
\@fpsep P289, P303, Y863, Y872, Y944, Y966, Y2349
\@fpstype Y985, Y1006, Y1007, Y1021, Y1052, Y1053, Y1077, Y1079, Y1082, Y1084, Y1135, Y1191, Y1192, Y1227, Y1230, Y1233, Y1236, Y1297, Y1359, Y1360, Y1398, Y1400, Y1403, Y1405, Y1479, Y1482, Y1485, Y1488, Y1577, Y1592, Y1594, Y1612, Y1621, Y1657, Y1658, Y1698, Y1713, Y1715, Y1735, Y1745, Y1784, Y1785, Y2022, Y2038, Y2040, Y2042, Y2045, Y2046, Y2047, Y2049, Y2050, Y2054, Y2055, Y2057, Y2058, Y2092, Y2094, Y2096, Y2108, Y2110, Y2124, Y2126, Y2156, Y2159, Y2170
\@fptop P288, P302, Y862, Y2349
\@frameb@x . . . K179, K207, K209, *1044*
\@framebox K186, K193, K197
\@framepicbox K186, K193, K230
\@freelist P60, P129, P319, P320, Y29, Y34, Y48, Y56, Y213, Y501, Y734, Y749, Y763, Y868, Y1814, Y1815, b196, b213, b275, *1072*
\@generic@error *1043*
\@generic@message *1043*
\@getcirc M437, M485, M514, M541, M613, M629
\@getfpsbit Y982, Y1018, Y1574, Y1695, Y2065
\@getlarrow M266, M274, M276
\@getlinechar M190, M229
\@getpen p34, p37, p46, p117
\@getrarrow M267, M274, M283
\@glossaryfile Q21, Q22, Q31
\@gnewline p95, p101, p108, p111
\@gobble o15, p75, p483, r64, r132, r187, r465, r467, r706, s29, c160, c184, v536, v569, d11, d98, x345, y26, z28, z30, z378, z389, z453, z500, z501, z530, z536, z544, z549, z567, z581, z591, z600, z613, z630, z639, z713, z715, z719, z727, z761, z770, z822, z824, z835, z919, z929, z1010, z1015, z1084, z1115, A139, A180, A518, A752, A762, A772, E864, H239, e33, e65, e88, O143, O144, O145, O146, O147, O182, P7, R11, R45, R46, U680, U838, f111, U1092, U1152, f133, U1179, U1283, U1312, U1396, U1401, U1475, U1619, U1631, f208, f219, W261, f236, f240, f277, f283, f286, f296, f316, f322, f325, f334, f344, f350, f353, f362, f380, f384, f386, f387, f389, Y621, Y622, Y623, f397, Y680, Y681, Y682, f401, f403, Y929, Y1934, Y2202, Y2219, aa282, aa411, aa574,

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

aa580, aa645, k6, k9, l101, l127, l147, l155, l180, l189, l202, *1040*
\@gobble@AddToHook@args h1591, h1592
\@gobble@IncludeInRelease c68
\@gobble@RemoveFromHook@arg h1594, h1595
\@gobblecr p481, p482
\@gobblefour z24, z375, z491, z493, z497, z499, z509, z513, z637, z689, U1181, U1314, U1403, f208
\@gobblethree U128, f208, f596, f609, *1050*
\@gobbletwo r32, r101, r159, v541, v575, z132, H23, H44, H76, H84, e123, e128, T11, T13, U1151, U1282, U1395, f175, f176, f208, W260, aa306, k12, *1055*
\@gtempa r650, r651, r657, r658, r659, r684, r685, r687, r688, r689, L3, L5, L6, L7, L8, U286, U288, U301, U302, U321, U323, U337, U339, U349, U351, f126, f127, f181, f183, f528, f536, *1034*
\@halfwidth M2, M126, M129, M131, M227, M299, M302, M324, M333, M349, M361, M364, M383, M391, M405, M416, M421, M680, M706, M725, M726, M727, M766, M781, M782, M783
\@halignto L170, L174, L177, L191
\@hangfrom O66, O117, O138
\@height p350, p358, p384, p392, s293, s295, x190, B340, B558, B559, B561, B562, K163, K168, K216, K226, K444, K488, L186, L219, L359, L376, M227, M300, M303, M324, M333, M351, M359, M383, M391, M407, M414, M590, M600, M726, M782, f26, Y1853, b469
\@highpenalty p118, aa3
\@hightab L11, L21, L23, L74, L86, L95, L96, L111, L146, L147, *1057*
\@hline M167, M179, M226, M265
\@holdpg Y122, Y300, Y302, Y303, Y308, Y309, Y310
\@hspace p437, p438, p453, *1025*
\@hspacer p437, p452, *1025*
\@hvector M244, M259, M265
\@ialph *1040*
\@icentercr H337, H338
\@iden f215
\@if f171, f172, f174
\@if.. . . . . *1040*
\@if@DeclareRobustCommand f483, f507, f518, f519, f523, f614, f615, f618, i125, *98*
\@if@newcommand . f304, f484, f508, f519, f561, f573, f578, i126, i137, *264*
\@if@newlist *1067*
\@if@pti@ns U222, U225, U227, U244, U245
\@if@ptions U219, U220, U221, U873, U968
\@if@short@command *1040*
\@ifatmargin L55, L106
\@ifbothcounters t61, t72, t80, t88, t104, t106, t115, t117
\@ifclasslater . . . U163, U171, U178
\@ifclassloaded . . U155, U266, U275
\@ifclasswith U219, U268, U277
\@ifdefinable s14, s17, t11, u3, A618, K115, N7, N15, N22, f84, f86, f130, f132, f238, *1040*
\@iffileonpath r486, r507, r528, r545, r566
\@ifl@aded U155, U156, U157, U822, U949, U967, *844*
\@ifl@t@r s1538, U169, U176, U182, U186, U188, U199, U200, U701
\@ifl@ter s1579, s1580, U163, U164, U181, U861, U996
\@ifl@ter@@ s1579, s1580
\@ifnch e49, e50, f677, f679, f691
\@ifnextchar p93, p482, a101, r598, t13, x411, H336, I342, J143, K9, K11, K18, K20, K26, K47, K121, K122, K128, K129, K136, K140, K185, K186, K192, K193, K198, K231, K239, K247, K254, K258, K327, K331, K335, K428, K433, K456, K463, K468, L57, L181, L203, L210, M23, M132, M143, e45, M453, N3, N5, N28, P27, P264, P324, P452, P519, P536, R3, R17, R29, U293, U307, U696, U711, U716, U1101, U1104, U1232, U1235, Y209, Y2010, f673, f678, f692, *1038*
\@iforloop k21, k22
\@ifpackagelater U163, U170, U177, *1069*
\@ifpackageloaded U155, U265, U274, Y1994, *821*
\@ifpackagewith U219, U267, U276, *821*
\@iframebox K199, K200, K201
\@iframepicbox K231, K232

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@ifstar p59, p71, p330, p437, t102, t113, v206, y121, H325, H332, H563, H572, I377, L56, L202, L209, M142, M605, O52, O142, U435, U475, f73, Y1858, f692
\@ifundefin@d@i . f635, f636, f653, f656
\@ifundefin@d@ii f635, f638, f641
\@ifundefined t3, t7, t16, t50, t62, t64, v100, v186, x424, z410, E54, E866, G47, H141, H158, H174, H229, H246, H279, N21, e132, R40, R68, R85, T3, T7, U128, U153, U388, U394, U411, U423, U499, U533, U552, U824, f127, f134, f154, f161, f183, f194, W485, f277, f283, f316, f322, f344, f350, f380, f397, f478, f630, g2656, *1038*
\@ignore... . . . . *1061*
\@ignorefalse H4, H180, H216, H223, H234, H251, H274, H284, H289, P384, *1024*
\@ignoretrue p200, p213, H4, H7, I335, I338, I371, I517, *1060*
\@iiiminipage K329, K333, K336, K337, K338
\@iiiparbox K241, K249, K256, K259, K260, K261, K366
\@iiminipage K332, K334
\@iinput r598, r599, *349*
\@iiparbox K255, K257
\@iirsbox K468, K477
\@imakebox K26, K41, K138
\@imakepicbox . K47, K48, K143, K233
\@iminipage K328, K330
\@include . . r227, r270, r286, r290, *1080*
\@includeinreleasefalse c71, c76, c130, c138, f768
\@includeinreleasetrue c120
\@index Q18, Q19, Q35
\@indexfile Q4, Q5, Q14
\@inlabel *655*
\@inlabelfalse J28, J104, J184, Y163, Y190, *1035*
\@inlabeltrue J28, J178
\@inmatherr J112, J142, M605, l283, *1037*
\@inmathwarn s3
\@inpenc@test aa356, aa423
\@input r34, r103, r161, r298, r360, r407, r637, O152, aa648, *875*
\@input@ r318, r345, r378, r397, r422, r639, v393, R51, *1031*
\@input@file@exists@with@hooks W143, *1083*
\@inputcheck r481, r482, r489, r502, r503, r510, r523, r524, r531, r553, r554, r557, r570, r571, r574, a194, a195, a198, a206, e38, e39, e42, f38, f45, U1140, U1141, U1175, U1271, U1272, U1308, U1383, U1384, U1391, b307, a73, *853*
\@insertfalse Y1075, Y1225, Y1396, Y1477, Y1572, Y1693
\@insertrue Y1001, Y1046, Y1163, Y1331, Y1651, Y1778
\@invalidchar l288
\@iparbox K240, K248, K253
\@irsbox . . . K456, K463, K468, K469
\@isavebox K136, K137
\@isavepicbox K141, K142
\@ishortstack M133, M141
\@istackcr M143, M144
\@itabcr L57, L58
\@item J143, J156
\@itemdepth J241, J243, J244, J245, *667*
\@itemfudge L38, L44, L82
\@itemitem J245, J248
\@itemlabel J44, J96, J143, *1029*
\@itempenalty p16, J23, J175, *656*
\@itemspacing *667*
\@iwhiledim k7
\@iwhilenum k3
\@iwhilesw k10
\@ixpt v717
\@ixstackcr M142
\@kernel@... . . . . *824*
\@kernel@Ref G71, G76
\@kernel@after@⟨*hook*⟩ *198*
\@kernel@after@begindocument r58, r75, e7, V167, i60, *1085*
\@kernel@after@begindocument@before r16, r75, w731, *336*
\@kernel@after@enddocument H15, e1, X350
\@kernel@after@enddocument@afterlastpage H19, e1, X356, h293
\@kernel@after@para@after n64, n8, *298*
\@kernel@after@para@end . n57, n8, *298*
\@kernel@after@shipout@background X72, X158, *907*
\@kernel@after@shipout@lastpage . . X114, X119, X158, X376, X381, *919*
\@kernel@before@⟨*hook*⟩ *198*
\@kernel@before@begindocument r56, r75, e7, X405, *1085*
\@kernel@before@enddocument H13, H105, *622*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@kernel@before@insertmark S139, S160, *804*
\@kernel@before@para@before n8, n19, *297*
\@kernel@before@para@begin n8, n27, *298*
\@kernel@before@shipout@background X68, X70, X158, *907*
\@kernel@currpathstack U45, U47, U91, U123, *1085*
\@kernel@make@file@csname W288, W291, W311, W314, W332, W335, W364
\@kernel@pageref G27, G31
\@kernel@pageref@exp G32
\@kernel@ref G26, G29, G71
\@kernel@ref@exp G34
\@kernel@rename@newcommand f285, f302, f339, f367, f372, f385, *93*
\@kernel@sRef G73, G76
\@kernel@spageref G24, G27, G31
\@kernel@sref ... G23, G26, G29, G73
\@killglue M59, M73, M103, M115, M123
\@kludgeins Y319, Y320, Y321, Y323, Y376, Y377, Y423, Y424, Y504, Y520, Y521, Y527, Y528, Y529, Y538, Y554, Y558, Y568, Y1854, Y1885
\@labels J27, J146, J147, J189, J206, J207, *655*
\@largefloatcheck P192, P213, P238, P256, *1038*
\@lastchclass L262, L272, L273, L275, L283, L308, L322, L326, L335, L348, L349
\@latex@error o10, r223, r267, r285, s50, s84, c97, c156, c181, c192, v5, v28, v58, v102, v144, v187, v253, v339, x105, y100, y111, z23, z68, z97, z117, z170, z238, z268, z300, z323, z339, z416, z437, z469, z509, z513, z555, z560, z615, z683, z689, z733, z737, z741, z776, z780, z784, z841, z851, z936, z941, z944, z976, z979, z1052, z1055, z1058, z1125, z1131, A49, A60, A82, A93, A600, A720, D143, H175, H230, H247, H280, H509, H524, H539, H551, I409, J219, L100, L109, e80, O31, P6, P83, R71, R88, U623, U674, U687, U874, U922, U969, U1060, U1077, U1085, U1090, U1112, f128, U1165, U1243, U1298, f155, U1634, U1664, f278, f317, f345, Y234, Y390, f469, Y1876, Y1893, l163, l217, l233, l239, l241, l244, l246, l248, l252, l254, l256, l259, l263, l268, l272, l274, l276, l277, l279, l282, l286, l288
\@latex@info s85, E76, f224, f298, f336, f364, f730, l163, l208, *287*
\@latex@info@no@line X89, Y578, l163, l209, *1042*
\@latex@note v33, l190
\@latex@note@no@line U1142, U1148, l190, *1086*
\@latex@warning r343, r395, s55, G14, M449, P260, R42, R69, R86, U1204, U1211, U1337, U1343, U1426, U1432, X172, Y2032, l163, l215
\@latex@warning@no@line r19, r88, r145, r704, G8, G50, G51, H51, H58, H91, e98, O32, U289, U303, U702, U862, U997, U1169, U1273, U1279, U1302, U1385, U1392, U1459, U1536, f202, X79, X98, X367, Y243, Y275, Y1829, Y2098, l163, l216
\@latexbug Y333, Y1815, l275
\@latexerr Y437, l215, *1039*
\@latexinfo *1037*
\@latexrelease@catcode@null g6, g2657
\@lbibitem R3, R4
\@ldots B504, B506
\@leftcolumn Y121, Y2239, Y2260, Y2284, Y2293
\@leftmark T16, T79
\@let@token p410, p411, p418, D83, D96, I243, I245, I248, e49, e51, f677, f680, f683, f691, *1049*
\@lign I195, I197
\@linechar M190, M191, M192, M196, M197, M199, M204, M206, M207, M208, M209, M211, M215, M216, M219, M220, M225, M272, M670, *1068*
\@linefnt M124, M127, M190, M265, M273, M304, M307, M677
\@linelen M164, M165, M176, M177, M203, M210, M219, M221, M226, M227, M228, M241, M242, M256, M257, M300, M303, M305, M306, M671
\@list *656*
\@listctr J202, J225, R9, *655*
\@listdepth J23, J35, J38, J43, J99, K350, *655*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@listfiles . r62, r130, r185, r710, r729
\@listi *656*
\@listii *656*
\@listvi *656*
\@lnbk *1062*
\@loadwithoptions U629, U651, U661, U670
\@lowpenalty p117, aa3
\@ltab L71, L106
\@ltxnomath *1037*
\@m p288, p429, p434, r45, r114, r172, J80, M213, M217, R37, b21, b396, b398, b399, b465, b466, *1054*
\@mainaux r3, r37, r38, r106, r107, r164, r165, r216, r298, r341, r360, r393, r407, r432, H22, H75, *1048*
\@makebox K11, K20, K25
\@makecaption P24
\@makecol Y261, Y413, Y460, Y482
\@makefcolumn Y393, Y394, Y402, Y404, Y440, Y442, Y450, Y452, Y2197, Y2199, Y2215, Y2216
\@makefnmark P400, P532
\@makefntext K383, K400, K417, P476, P494, P512
\@makeother a100, v406, v407, v408, v409, v410, v411, a129, v412, v413, v414, v415, v416, H431, H452, H545, H560, H570, U375, U376, U1186, U1319, U1408, f695, f696, a79
\@makepicbox K10, K19, K46, M366, M424
\@makespecialcolbox Y505, Y524, *1027*
\@marbox P320, P322, P326, P330, P331, P379, Y1814, Y1824, Y1827, Y1835, Y1837, Y1838, Y1840, Y1841, Y1842, Y1851
\@marginparreset . . . P343, P361, P370
\@markright T37, T62, T77
\@maxdepth r60, r128, r183, Y91, Y488, Y516, aa152, *1034*
\@maxtab L2, L94, *1038*
\@medpenalty p118, aa3
\@meta@family@list A116, A141, A153, A242, A506
\@midlist . Y66, Y501, Y502, Y1029, Y1031, Y1143, Y1307, Y1958, Y1986
\@minipage... . . . . *1060*
\@minipagefalse J181, K323, K325, K363, P187, P250, P345, P363
\@minipagerestore K351, K353
\@minipagetrue K324, P186
\@minus f26, Y2342, Y2343, Y2344, Y2347, Y2348
\@missing@onefilewithoptions U836, U892, U1010
\@missingfile@area r611, r652, r665, U894
\@missingfile@base r611, r653, r666, U895
\@missingfile@ext r611, r654, r667, U896
\@missingfileerror r606, r621, r631, r640, U893, U990, *844*
\@mkboth T11, T13
\@mklab J45, J140
\@mkpream L189, L234, L262, *1047*
\@mparbottom P387, P388, Y118, Y478, Y1825, Y1833, Y1834, Y1835, Y1836
\@mpargs K342, K366
\@mparswitchfalse Y102
\@mpfn . K348, P452, P457, P541, P545
\@mpfootins K357, K358, K361, K367, K374, K375, K392, K393, K409, K410
\@mpfootnotetext K349, K369
\@mplistdepth K350, K367
\@multicnt L370, L372, L373, L374, L381, L382, L383, M103, M104, M106, M115, M116, M118, M667, M704, M706, M707, M708, M710, M711, M717, M723, M734, M738, M764, M766, M768, M770, M771, M775, M779, M790, M794, *1056*
\@multiplelabels r33, r102, r160, G49, G55, H49, H55, H89, H95
\@multiput M86, M95, M98
\@multispan L371, L375, L379
\@mypkg@name *868*
\@mypkg@other@name *868*
\@namedef r445, v135, v136, v160, w5, w525, x418, z360, E57, E93, E869, G52, H208, H218, H245, H271, H483, H492, I413, I414, L175, N12, N13, N18, N19, N23, N24, N25, f50, U827, U1103, U1234, W483, aa480, aa481, *1042*
\@nameuse . . . r335, r391, r430, r444, N23, T5, f51, W486, Y609, Y667, *1042*
\@nbitem J168, J221
\@ne b16, *275*
\@needsf@rmat U697, U700, U705
\@needsformat U685, U695, U699
\@negargfalse M186
\@negargtrue M185
\@newcommand f79, f80
\@newctr t13, t15, N8
\@newenv f150, f151, f160
\@newenva f149, f148

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@newenvb f151, f150
\@newfontswitch *1036*
\@newl@bel . . G46, H24, H77, R10, *1054*
\@newline p94, p96
\@newlistfalse J29, J33, J108, J182, Y602, Y660
\@newlisttrue J29, J33, J87
\@next . P60, P129, P319, P320, Y9, Y213, Y311, Y879, Y899, Y1814, b275
\@nextchar L269, L270, L330, L331, L332
\@nil q14, r246, r247, r248, c13, c19, s89, s110, c80, c101, c102, c114, c115, s996, s1000, s1063, s1075, s1077, c162, c163, c164, v358, v369, v485, v500, v604, v607, v608, v616, w431, w433, w465, w467, w645, w647, w671, w673, x350, x351, x353, x366, x372, x376, x377, x413, x434, x439, x519, x533, y26, y44, y53, y57, z40, z479, z487, z520, z1136, z1138, a164, a165, D58, D62, L367, L368, U90, U91, U97, U105, U108, U115, U140, U189, U190, U201, U202, U212, U213, U215, f53, f54, U384, f58, U407, f63, U450, U455, U571, U591, U595, U601, U605, U793, U802, U816, U817, f135, U1509, U1514, U1517, U1519, U1520, U1535, U1555, U1572, U1626, U1648, U1672, W168, W176, W370, W412, W414, f439, f440, f585, f671, f672, k13, k19, k27
\@nmbrlistfalse . . J33, J46, J91, *1024*
\@nmbrlisttrue J225
\@nnil r247, r248, v214, v218, v219, v220, v235, x179, x181, x345, x347, x359, x361, x366, x380, x382, x389, x400, x401, x403, x434, x439, M13, U738, U739, U746, U766, U767, U774, f417, f423, k13, k20, k21, k22, k28
\@no@font@optfalse y17, y129
\@no@lnbk p9, p10, p40, *1062*
\@no@pgbk p7, p8, p32, *1055*
\@nobreak *792*
\@nobreak... . . . . *1060*
\@nobreakfalse p120, p122, J193, O94, O129, O157, P182, Y165, Y192, Y1152, Y1318, *1061*
\@nobreaktrue p121, O126, P181
\@nocnterr l240, *1035*
\@nocounterr t4, t8, t16, t62, t64, N21, l240, *1036*
\@nodocument n101, r68, r136, r191, r295, r357, H166, P39, P108, Y156, Y183, Y212, l245, *1061*
\@noitemargfalse J32, J200
\@noitemargtrue J32, J143
\@noitemerr p248, p266, p303, p326, J69, J81, J107, l278
\@noitemerror *1048*
\@noligs H432, H453, H561, H571, H582, *1056*
\@nolnbk *1062*
\@nolnerr p42, p113, H324, H331, l238, *1038*
\@nomath v1, v337, A551, A586, A592, A613, A615, A637, *1022*
\@noparitemfalse J30, J145
\@noparitemtrue J30, J66
\@noparlistfalse J31, J70
\@noparlisttrue J31, J67
\@nopgbk *1055*
\@normalcr p52, p92, K322, *1078*
\@normalsize U4, U5, *1035*
\@normalsize␣check *1035*
\@noskipsec *655*
\@noskipsecfalse r54, r123, r178, O98, Y158, Y185
\@noskipsectrue O38, O95
\@notdefinable f136, f137, f141, f466, l232
\@notprerr r66, r134, r189, l281
\@nthm N3, N4
\@nxttabmar L11, L21, L23, L25, L75, L111, L112, L118, L119, *1057*
\@obsoletefile r703
\@oddfoot T11, T14, T15, Y124, Y612, Y671
\@oddhead . T11, T14, Y123, Y612, Y671
\@onefilewithoptions U730, U734, U740, U758, U762, U768, U785, U789, U795, U811, U812, U890, U957, U1485, *882*
\@onefilewithoptions@clashchk U825, U872
\@onelevel@sanitize P42, P111, f697, *1046*
\@onfilewithoptions *848*
\@onlypreamble r196, r205, r242, r705, r735, s23, s24, s61, s62, s66, s125, s145, s189, s190, s204, v17, v115, v117, v123, v139, v167, v182, v203, v208, v250, v512, x419, y28, y36, y42, y79, y83, y88, y93, y98, y108, y126, y127, y128, y134, y138, y142, z17, z19, z44,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

z46, z107, z116, z136, z353, z354, z362, z402, z440, z442, z444, z457, z472, z519, z521, z563, z602, z618, z695, z789, z798, z854, z857, z860, z880, z893, z947, z982, z993, z1007, z1061, z1081, z1085, z1149, D140, D141, E58, E59, E60, E870, G54, Q12, Q29, R64, R81, S16, S272, U10, U13, U85, U112, U120, U122, U154, U294, U357, U363, U428, U431, U432, U443, U444, U445, f66, U470, U476, U489, U526, U544, U564, U584, U608, U613, U617, U620, U628, U649, U652, U662, U681, U694, U699, U705, U714, U719, U807, U890, U1015, U1024, U1032, U1033, U1051, U1058, U1067, U1074, U1075, U1083, U1088, U1093, U1465, U1466, U1467, U1468, U1470, f188, f190, V135, f199, f207, h1501, *1086*

\@opargbegintheorem N32, N35

\@opcol Y262, Y270, Y394, Y413, Y442, Y460, Y465, *810*

\@options U563

\@othm N3, N20

\@outerparskip J8, J88, J117, J152, J222

\@outputbox S284, S287, S291, S315, S318, S322, Y120, Y485, Y487, Y507, Y510, Y511, Y531, Y533, Y534, Y539, Y542, Y547, Y549, Y556, Y562, Y564, Y638, Y697, Y725, Y731, Y741, Y742, Y765, Y772, Y858, Y861, Y864, Y870, Y871, Y2239, Y2243, Y2244, Y2258, Y2264, Y2284, Y2290, Y2299, *798*

\@outputdblcol Y469, Y2234, Y2236, Y2280, Y2281

\@outputpage .. Y403, Y452, Y472, Y592, Y2268, Y2273, Y2306, Y2314

\@oval M453, M471

\@ovbtrue M476, M504, M534

\@ovdx M431, M487, M489, M495, M497, M516, M518, M526, M528, M543, M551, M553, M589, M592, M599, M601, M693, M694, M695, M696, M712, M713, M714, M717, M733, M753, M754, M755, M756, M772, M773, M775, M789

\@ovdy M431, M488, M490, M496, M497, M517, M519, M527, M528, M544, M552, M553, M564, M569, M577, M581, M700, M701, M702, M703, M718, M719, M720, M723, M737, M760, M761, M762, M763, M776, M777, M779, M793

\@ovhlinefalse M477, M505

\@ovhlinetrue M456, M460, M465, M483, M489, M511, M518

\@ovhorz M494, M495, M525, M526, M550, M551, M584

\@ovltrue M476, M504, M534

\@ovri .. K33, M431, M486, M515, M542, M564, M577, M593, M602

\@ovro M431, M486, M495, M496, M515, M526, M527, M542, M551, M552, M563, M569, M576, M581, M588, M598, M614, M621, M630, M639

\@ovrtrue M476, M504, M534

\@ovttrue M476, M504, M534

\@ovvert M492, M493, M521, M523, M546, M548, M557

\@ovvlinefalse M477, M505

\@ovvlinetrue M459, M482, M490, M510, M519

\@ovxx . M431, M480, M482, M483, M487, M493, M494, M508, M510, M511, M516, M523, M525, M537, M539, M543, M548, M550, M588, M598, M690, M691, M692, M696, M705, M706, M715, M716, M717, M732, M750, M751, M752, M756, M765, M766, M774, M775, M788

\@ovyy . M431, M481, M482, M483, M488, M495, M509, M510, M511, M517, M526, M538, M539, M544, M551, M561, M574, M697, M698, M699, M703, M705, M721, M722, M723, M736, M757, M758, M759, M763, M765, M778, M779, M792

\@p@pfilename U90, U97, U105, U108, U115, U120

\@p@pfilepath U91, U138, U147

\@p@pfilepath@aux . U139, U140, U148

\@pagedp Y117, Y308, Y313, Y1093, Y1246, Y1843, Y1853

\@pageht Y116, Y309, Y313, Y315, Y316, Y317, Y321, Y1092, Y1245, Y1826, Y1833

\@par m3, m5

\@parboxrestore K266, K322, K347, K378, K396, K413, P19, P100, P169, P342, P360, P470, P489, P507, Y219, Y603, Y661, *1061*

\@parboxto K261, *1069*

\@parmoderr P58, P127, P316, l271

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@parse@version c80, c101, c102, c114, c115, c162, c163, c164, U195, U201, U202, U212, U1520, U1535, U1572, U1648, U1672
\@parse@version@ U189, U190, U195, U207
\@parse@version@dash U213, U215, *1074*
\@partaux r3, r222, r266, r284, r308, r310, r311, r331, r370, r372, r373, r387, r417, r419, r420, r426, r438, r440, r443
\@partlist r231, r235, r236, r238, r262, r281, r304, r366, r413
\@partswfalse r6
\@partswtrue r230, r260, r280
\@pass@ptions U380, U382, U402, U403, U405, U418, U419, U421, U428, U429, U430, U901, U983
\@pboxswfalse K264, K340
\@pboxswtrue K274
\@pdef *1031*
\@penup I186, I187
\@percentchar a109, U1178, U1180, U1182, U1184, U1311, U1313, U1315, U1317, U1400, U1402, U1404, U1406, U1454
\@pgbk *1055*
\@picbox M6, M31, M43, M51, M52, *1023*
\@picht M6, M29, M42, M51
\@picture M23, M24
\@picture@warn M223, M441, M445, M449
\@pkgetension *1031*
\@pkgextension U31, U155, U163, U219, U429, U619, U622, U661, U670, U741, U769, U796, U912, U939, U1069, W483, W489, *846*
\@plus p456, O16, O206, O229, f26, T83, Y2342, Y2343, Y2344, Y2347, Y2348, Y2352, Y2353, Y2354, Y2358, Y2359, Y2360
\@pnumwidth O218, O241
\@popfilename . U33, U870, U1005, *824*
\@pr@videpackage U293, U307, U310, U331, U333, U344, U346, U357
\@preamble L190, L192, L200, L237, L256, L258, L259, L263, L278, L296, L297, L334
\@preamblecmds r67, r135, r190, f66, U1686, U1687, *1031*
\@preamerr L199, L274, L355, l260
\@process@pti@ns U488, U506, U523, U530, U531, U544, U548, U550
\@process@ptions .. U475, U477, U489
\@protect@... ..... *1042*
\@protected@testopt f89, f101, f580, f592
\@protecteddef *1037*
\@providesfile a101, a102, U367, aa641
\@ptionlist U152, U222, U474, U878, U884, U973, U979, U1070
\@pushfilename . U33, U818, U960, *251*
\@put M452, M497, M528, M553, M621, M639
\@qend f136, f671, l236
\@qrelax f137, f671
\@raw@classoptionslist ... U11, U728
\@rc@ifdefinable . s14, f130, f132, f238
\@reargdef f122, *1031*
\@refundefined r55, r124, r179, G3, H47, H87, *1057*
\@reinserts Y327, Y330, Y518
\@remove@eq@value . U446, U511, U571
\@remove@tlig s996, s1004
\@remove@tlig@ s996, s997
\@remove@tlig@@ s997, s1000
\@remove@tlig@@@ s1010, s1029
\@removeelement U570, U579, k32
\@removefromreset t46, t70, t71, t81, t104, t107
\@renewfontswitch *1031*
\@reqcolroom Y1092, Y1093, Y1096, Y1098, Y1099, Y1104, Y1108, Y1110, Y1138, Y1139, Y1245, Y1246, Y1250, Y1253, Y1254, Y1259, Y1266, Y1268, Y1300, Y1301, Y1412, Y1414, Y1416, Y1419, Y1421, Y1495, Y1498, Y1501, Y1506, Y1508, Y2022, Y2139, Y2144, Y2147
\@reserveda *448*
\@reset@ptions U834, U871, U899, U964, U1006, U1016
\@resetactivechars Y577, Y600, Y658
\@resethfps Y1207, Y1376, Y2089, *1038*
\@resetprotect *1052*
\@restorepar p341, p357, p375, p391, J127, J135, m5, *1054*
\@reversemarginfalse ... P388, Y101
\@reversemargintrue P387
\@rightmark T16, T80
\@rightskip H363, H382, H400, J75, K295, K316
\@rjfieldfalse L34, L77
\@rjfieldtrue L125
\@rmfamilyhook A429, A451, A463, A490
\@roman t137, t143
\@rsbox K456, K463, K467
\@rtab L71, L86

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@rule K428, K433, K437
\@sanitize . . . Q7, Q18, Q24, Q35, f695
\@savebox K122, K129, K135
\@savemarbox . P326, P327, P330, P333
\@savepicbox K122, K129, K139
\@savsf o24, o26, p123, p129, p138, p157, p171, p183, p197, p211
\@savsk p123, p128, p139, p158, p172, p184, p198, p212
\@scolelt Y790, Y855
\@sdblcolelt Y807, Y827, Y856
\@seccntformat O60, O111, *1025*
\@secondoftwo a91, o5, r505, r550, r567, s131, c84, c182, t190, t195, A512, E71, E838, E889, E905, G25, G42, e36, e40, T17, U159, U191, U203, U236, U254, U1677, f212, f445, f539, aa647, f589, f640, f647, f667, f714
\@secpenalty p17, O36, O50
\@sect O54, O55
\@seqncr I412
\@set@curr@file@aux W364
\@setckpt . . r438, r445, H23, H76, *1025*
\@setfloattypecounts Y1076, Y1226, Y1397, Y1478, Y1573, Y1694, Y2036
\@setfontsize A637
\@setfps P34
\@setfpsbit P73, P75, P77, P85, P143, P146, P149, Y2080
\@setmarks Y2250, Y2252, Y2267
\@setminipage K352, P21, P177, P185, P376, *1049*
\@setminpage *1062*
\@setnobreak P179, P375, *1049*
\@setpar J78, m3
\@setprotect *1052*
\@setref G10
\@setsize A637
\@settab L71, L93
\@settodim u17
\@settopoint u22
\@setupverbvisiblespace H473, H484, H496, H513, H528
\@sffamilyhook A429, A456, A464, A491
\@sharp L196, L235, L265, L280, L281, L301, L303, L305, L333
\@shipoutsetup Y592
\@shortstack M132, M133
\@show@... . . . . *97*
\@show@DeclareRobustCommand f507, f521, f566, f617, f620
\@show@newcommand f508, f521, f574, f600, f617, f623, *99*
\@show@newcommand@aux f600, f627, *100*
\@showcommandlisthook f504, f506, f514, g1223, *97*
\@skipping@modulefalse c151, c170, c197
\@skipping@moduletrue . . . c150, c174
\@sline M167, M179, M184, M269
\@slowromancap t144, t145
\@spaces l218
\@specialoutput Y256
\@specialpagefalse . Y97, Y609, Y667
\@specialpagetrue T9
\@specialstyle T9, Y609, Y667
\@sptoken f680, f690
\@sqrt I342
\@ssect O53, O112
\@stackcr M139, M142
\@star@or@long f72, f77, f124, f146, f152, f178, f187, f221
\@startcolumn Y263, Y270, Y777
\@startdblcolumn Y777, Y2272, Y2275, Y2312, Y2318
\@startfield L28, L46, L92, L104, L125, L133
\@startline L20, L57, L62, L68, L83, L154
\@startpagehook *1028*
\@startpbox L193, L236, L266, L332, L384, L386
\@startsection O39
\@starttoc O149
\@stopfield L32, L48, L86, L93, L125, L127, L140, L142, L154
\@stopline L30, L56, L85
\@stpelt t20, t23
\@string@makeletter f701, *104*
\@strip@args s76
\@strip@tex@ext r226, r236, r238, r243, r273, *340*
\@strip@tex@ext@aux r243, r274
\@svector M244, M259, M269
\@sverb . H500, H563, H572, H575, *636*
\@svsec . . . O57, O60, O66, O78, *1025*
\@svsechd O76, O101, O121
\@swaptwoargs r584, r586, U844, W153, W167, W187
\@sxverbatim H408, H485, H492
\@tabacckludge s223, s225, s454, s455, E193, E200, E202, *1057*
\@tabacol L178, L258
\@tabarray L170, L180, L181
\@tabclassiv L180, L330
\@tabclassz L179, L282
\@tabcr L56, L73
\@tabfbox L16, L80, L82

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@tablab L72, L126
\@tabminus L72, L117
\@tabplus L72, L110
\@tabpush L11, L77, L85, L140, L143, L145
\@tabrj L72, L124
\@tabular L174, L177, L178
\@tabularcr L180, L208
\@tempa G71, G72, G73, G74, G88, G89, G99, G100, *1049*
\@tempboxa s69, u17, u18, J205, J211, J212, J214, K29, K30, K31, K32, K37, K38, K39, K40, K175, K205, K212, K222, K343, K366, K473, K474, K475, K482, K483, K484, K485, M304, M305, M447, M448, M486, M491, M496, M497, M515, M520, M527, M528, M542, M545, M552, M553, M614, M615, M620, M621, M630, M631, M638, M639, M724, M742, M780, M798, O138, O139, P322, P380, Y305, Y377, Y382, Y383, Y424, Y429, Y430, Y568, Y628, Y635, Y636, Y687, Y694, Y695, Y723, Y727, Y739, Y745, Y752, Y753, Y754, Y755, Y759, Y767, j13, *1024*
\@tempcnta z862, z863, z864, z865, z869, L242, L243, L244, L245, M187, M188, M214, M215, M216, M229, M230, M231, M232, M239, M240, M254, M255, M270, M271, M276, M278, M279, M280, M281, M282, M285, M287, M288, M289, M290, M291, M292, M293, M294, M295, M296, M335, M336, M337, M338, M339, M360, M361, M362, M363, M364, M365, M392, M393, M394, M395, M396, M414, M416, M418, M419, M421, M423, M438, M439, M440, M442, M444, M446, M448, M562, M567, M575, M579, M616, M617, M618, M619, M632, M633, M635, M636, M658, M659, M660, M661, M662, M663, M711, M731, M771, M787, P62, P68, P70, P79, P80, P90, P91, P131, P137, P139, P152, P153, P159, P160, U1126, U1128, U1129, U1130, U1257, U1259, U1260, U1261, U1371, U1373, U1374, U1375, Y16, Y18, Y20, Y936, Y937, Y938, Y939, Y959, Y960, Y961, Y962, Y984, Y987, Y1020, Y1023, Y1134, Y1296, Y1576, Y1579, Y1697, Y1700, Y1815, Y1817, Y1820, Y1822, Y1824, Y1846, Y2070, Y2071, Y2075, Y2081, Y2085, aa227, aa232, aa233, aa234, aa364, aa366, aa367, aa368, aa375, aa377, aa378, aa379, aa385, aa387, aa388, aa389, aa396, aa398, aa399, aa400, aa426, aa428, aa429, aa430, aa452, aa454, aa455, aa456, aa462, aa464, aa465, aa466, aa495, aa500, aa501, aa502, j7
\@tempcntb z863, z867, z869, M279, M280, M281, M283, M284, M285, M562, M563, M567, M568, M575, M576, M579, M580, P88, P89, P90, P157, P158, P159, Y17, Y20, Y21, Y2081, Y2082, Y2083, aa228, aa232, aa496, aa500, j7
\@tempdima v219, v224, I173, I176, I182, K43, K44, K204, K205, K210, K211, K212, K214, K265, K266, K341, K345, K440, K443, K444, K471, K473, K479, K482, L35, L36, L37, L88, L89, L90, L91, L218, L219, M210, M211, M213, M214, M215, M216, M217, M218, M437, M438, M439, M448, M487, M488, M492, M493, M516, M517, M521, M523, M543, M544, M546, M548, M617, M619, M634, M636, M637, M657, M658, M659, O211, O212, O234, O235, O248, P196, P198, P218, P220, P258, P259, P260, Y229, Y230, Y231, Y489, Y491, Y537, Y539, Y540, Y545, Y550, Y554, Y559, Y563, Y919, Y922, Y942, Y952, Y964, Y974, Y1639, Y1640, Y1643, Y1644, Y1764, Y1765, Y1769, Y1770, Y1825, Y1826, Y1827, Y1828, Y1831, Y1834, Y1837, Y1839, Y2188, Y2189, Y2191, Y2192, j10, *1025*
\@tempdimb v220, v225, v624, v628, x179, x180, x437, x460, x461, x470, x471, x475, x493, x496, x499, x501, K268, K269, K441, K444, K472, K474, K480, K483, M211, M212, M357, M359, M362, M365, M482, M484, M485, M510, M513, M514, M539, M540, M541, M612, M613, M622, M628, M629, M640, M648, M649, M654, Y942, Y943, Y944, Y945, Y952, Y964,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

Y965, Y966, Y967, Y974, j10, *1069*
\@tempdimc x454, x455, x457, x458, x460, x461, K53, K54, K64, K65, K442, K443, K444, M30, M31, M32, M33, M34, M35, M60, M61, M63, M64, M332, M333, M334, j10
\@tempdimx *1025*
\@tempskipa p44, p47, p48, p285, p292, p294, p297, x181, x182, J116, J117, J118, J150, J152, J153, J154, J222, J223, J224, O42, O44, O45, O50, O62, O63, O88, O89, O91, O103, O104, O113, O114, Y1874, Y1875, Y1877, Y1885, j14
\@tempskipb p220, p222, p224, p227, p229, p243, p261, p283, p285, p286, p290, p292, p294, p295, p318, p321, j14, *324*
\@tempswa *1021*
\@tempswafalse r302, r364, r411, s1537, v94, v673, z404, z459, z523, z604, z1124, z1130, H25, H78, H423, H444, R17, R29, U1103, U1119, U1234, U1250, W287, W310, W331, Y990, Y1026, Y1582, Y1703, b262, a81
\@tempswatrue r300, r305, r362, r367, r409, r414, s1540, s1541, v97, v674, v675, v678, v681, z407, z462, z526, z607, z1087, H121, H428, H449, R17, R29, U1100, U1231, W287, W310, W331, Y1584, Y1607, Y1705, Y1730, Y2149, Y2166, b268, a82
\@temptokena .. H133, H137, H146, H159, H160, T27, T31, T38, T42, T55, T56, T63, T64, T77, T78, j16, *623*
\@test... ..... *1060*
\@test@opt *1056*
\@testdef H24, H77, H119
\@testfalse Y12, Y14, Y15
\@testfp Y884, Y904, Y940, Y963, Y2073, Y2202, Y2219, *1048*
\@testopt p7, p8, p9, p10, I383, f33, f79, f99, f103, f148, *1056*
\@testpach L270, L348
\@testpatch L348
\@testtrue Y13, Y21, Y356, Y887, Y906, Y946, Y968, Y2077
\@testwrongwidth Y345, Y885, Y941, Y1114, Y1428, Y1633
\@text@composite s76, s1070, s1075, *1050*
\@text@composite@x s76
\@textbottom T83, T85, Y513, Y551, Y565, Y574
\@textfloatsheight Y478, Y1089, Y1091, Y1141, Y1142, Y1147, Y1242, Y1244, Y1304, Y1306, Y1312, Y2022
\@textmin P285, P286, P299, P300, Y112, Y1091, Y1095, Y1098, Y1099, Y1244, Y1249, Y1253, Y1254, Y1416, Y1501, Y1600, Y1602, Y1618, Y1722, Y1724, Y1742, Y2130, Y2132, Y2134
\@textsubscript P424, P432
\@textsuperscript P401, P403, P404, *1053*
\@texttop . T83, T85, Y509, Y532, Y574
\@tf@r k25, k26, *1034*
\@tfor r551, r568, r712, D88, K57, K76, L268, M478, M506, M535, P63, P132, k25
\@tforloop k27, k28, k30
\@thanks O11, O34
\@thefnmark K381, K398, K415, P400, P401, P453, P458, P473, P491, P509, P521, P526, P537, P542, P553
\@thefoot Y124, Y612, Y615, Y642, Y671, Y674, Y701
\@thehead Y123, Y612, Y614, Y632, Y671, Y673, Y691
\@themargin Y74, Y613, Y615, Y627, Y672, Y674, Y686
\@themark T26, T27, T37, T38, T41, T54, T55, T62, T63, T78, T81
\@thirdofthree s197, f216
\@thm N12, N18, N24, N26
\@thmcounter N11, N17, N33
\@thmcountersep N10, N33
\@title O7, O31
\@tocrmarg O207, O230
\@toodeep J36, J232, J243, l253
\@toplist Y64, Y384, Y385, Y431, Y432, Y718, Y724, Y734, Y735, Y1027, Y1039, Y1956, Y1984
\@topnewpage Y199, *1037*
\@topnum P271, Y105, Y1024, Y1025, Y1039, Y1043, Y1460, Y1465, Y1553, Y1560, Y1947, Y1975, Y2016
\@toproom P273, Y106, Y1027, Y1039, Y1948, Y1976
\@topsep J1, J71, J73, J171
\@topsepadd ... J1, J59, J61, J71, J124
\@totalleftmargin H419, H441, J9, J53, J54, K294, K315, L35, L76, L81, *655*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\@trivlist J48, J57, J92
\@tryfcolumn Y780, Y800, Y818, Y834, Y2203, Y2220
\@trylist Y843, Y846, Y879, Y899, Y921
\@ttfamilyhook A429, A461, A465, A492
\@twoclasseserror U610, U1089
\@twocolumnfalse Y99, Y147
\@twocolumntrue Y206
\@twoloadclasserror U869, U1004, U1084
\@twosidefalse Y100
\@typein f32, f33, f40, f48, *1056*
\@typeset@protect .. s26, s32, s210, s218, A638, H193, H238, H256, f102, f243, f250, f252, aa358, *1048*
\@uclclist s1506, s1507, s1560, aa565, *1063*
\@undefind M57, M71, M82, M91, M162, M174, M237, M252, M313, M371
\@undefined b549, n128, n129, n130, n131, n132, o34, p89, b617, p470, p476, r61, r62, r129, r130, r184, r185, r273, r274, b657, b672, r476, r477, r478, r483, r504, r525, r540, r595, s195, s197, c50, c59, s333, s335, s337, s339, s341, s343, s345, s347, s349, s351, s370, s372, s374, s458, a111, a112, a113, s700, s703, t204, v434, v474, d2, v536, v569, d15, d16, d17, v633, v640, d29, d30, w388, w411, w420, d74, w509, w510, w511, w512, w513, w514, w515, w516, w517, w518, d84, w529, w534, w539, w603, w604, w605, w606, w607, w608, w609, w634, w714, w716, w717, w719, w720, w721, w723, a134, x552, x553, y4, y5, y6, y7, y8, y9, y10, y11, y12, y13, y14, y15, y16, y17, y18, y19, y20, d173, d189, a142, d197, z141, d205, d237, d238, d239, d240, d241, d242, d243, d244, d245, d246, d247, d248, d249, d250, d251, d252, d253, d254, d255, z720, d261, z827, a150, A35, A58, A71, A91, A104, A105, A106, A107, A108, A109, A110, A111, A112, A113, A114, A116, A117, A118, A231, A232, A233, A234, A235, A236, A237, A238, A239, A240, A242, A243, A244, A304, A305, a157, A472, A490, A491, A492, A534, A535, A536, A537, A538, A578, A579, A580, A581, A582, A583, A594, A716, B15, B50, B65, D37, D38, D39, D122, E159, E367, E617, E620, E621, E651, E652, E653, E656, E657, E658, E659, E660, E661, E666, E667, E668, E669, E674, E675, E676, E677, E680, E681, E682, E684, E685, E690, E691, E692, E693, E694, E695, E696, E697, E698, E699, E700, E701, E702, E703, E704, E705, E707, E708, E710, E711, E712, E713, E714, E715, E716, E717, E718, E719, E721, E722, E723, E724, E725, E726, E727, E728, E729, E731, E732, E733, E734, E735, E736, E737, E738, E739, E740, E741, E742, E743, E744, E745, E746, E747, E748, E749, E750, E751, E752, E753, E754, E755, E756, E757, E762, E763, E765, E766, E767, E768, E769, E770, E771, E772, E774, E775, E777, E778, E780, E781, E782, E783, E785, E786, E787, E789, E791, E792, E793, E794, E795, E796, E797, E799, E800, E801, E802, E803, E804, E805, E806, E807, G93, G109, G110, H101, H153, H154, H155, H156, H291, H292, H312, H313, H314, H315, H467, H494, H495, H496, H497, H530, I223, I233, I234, I270, I273, I316, I329, I423, K21, K130, K194, K250, K434, K464, a208, e4, e13, M18, e14, e15, e16, a212, M467, M468, O197, O245, P5, e147, e148, e149, e150, e151, e152, P429, P448, e169, e170, e171, e172, P562, R30, R53, e192, e193, U4, U25, f34, U146, U147, U148, a238, U207, U353, U461, U511, U891, a245, U929, U931, U937, U994, U1009, U1010, U1025, U1139, U1217, U1220, U1270, U1349, U1352, U1362, U1363, U1364, U1365, U1366, U1367, U1368, U1439, U1442, U1458, U1478, U1485, W18, W19, W20, W21, W147, f223, W189, W190, W197, W198, W199, W321, W342, W356, W360, W361, W489, W495, W496, W497, f307, f308, X436, X437, X438, X439, X440, X442, X443, X444, X451,

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

X452, X454, X456, X457, X458, X461, X484, Y36, f339, f367, Y368, Y369, f371, f372, f389, f403, f450, f451, f452, f453, f454, f455, f456, f490, Y1926, Y1927, Y1928, Y1929, f491, f492, f493, f494, f495, f513, f514, aa10, aa18, aa39, aa54, aa73, aa82, aa89, aa98, aa108, aa160, aa161, aa270, aa283, aa296, aa316, aa341, aa351, aa352, aa353, aa382, aa384, aa423, aa424, aa443, aa444, aa445, aa446, aa447, aa448, aa449, aa450, aa451, aa468, aa484, aa485, aa486, aa534, aa535, aa595, aa630, aa631, aa632, aa633, aa634, f618, f619, f620, f621, f622, f623, f625, f626, f627, f642, f649, f723, f724, f725, f734, a329, a330, b65, b81, b105, b106, b121, b122, b127, b136, b149, b184, b189, b222, b223, b246, b256, b291, b349, b359, b361, a71, a72, b442, b443, b453, b454, l28, *1075*
`\@undefinedfonterror` *1038*
`\@unexpandable@protect` r210, L264, f220, f255, f261, f266, *1047*
`\@unknownoptionerror` U1020, U1059, U1072
`\@unknownversion` *1027*
`\@unprocessedoptions` U560, U669, U891, U930, U931, U991, U995, U1074, V49, *846*
`\@unused` f10, f17, U1463, b307, l15, l32, l59, *1085*
`\@unusedoptionlist` r18, r20, r87, r89, r144, r146, U12, U453, U454, U464, U465, U572, U580, V83, V95, *1026*
`\@upline` M297, M298, M304
`\@upordown` M195, M196, M204, M225, M273
`\@upvector` M268, M304
`\@use@ption` U484, U500, U518, U534, U536, U553, U555, U565
`\@use@text@encoding` s150, E16, E1141
`\@vbsphack` p219
`\@verb` H563, H572, H575
`\@verbatim` . . . H413, H459, H483, H492
`\@verbvisiblespacebox` H478, H479, H482, H497
`\@vereq` B457, B458
`\@viiipt` v716
`\@viipt` v715
`\@vipt` v714
`\@vline` M166, M178, M297
`\@vobeyspaces` H406, H459, H485, H513, H528, H575
`\@vpt` v713
`\@vspace` p330
`\@vspace@calcify` p79, p101, p241, p337, p342, p352, p360, H342, I391, L62, L224, M148
`\@vspacer` p330
`\@vtryfc` Y849, Y857
`\@vvector` M243, M258, M268
`\@warning` l215
`\@wckptelt` r439, r442
`\@whiledim` M123, M203, k7
`\@whilenoop` k3, *1055*
`\@whilenum` L244, M104, M116, M336, M338, M361, M364, M393, M395, M416, M421, M731, M787, k3
`\@whilesw` Y264, Y394, Y403, Y441, Y451, Y2273, Y2313, k10
`\@whileswnoop` k10, *1055*
`\@wholewidth` K160, K162, K163, K165, K167, K168, K169, K170, M2, M126, M129, M131, M299, M302, M350, M359, M406, M413, M565, M578, M590, M600, M679, M680, M728, M784
`\@width` p452, s289, s294, x192, B618, K165, K167, K218, K225, K444, K488, L188, L219, L347, L366, M227, M299, M302, M325, M333, M350, M359, M384, M392, M406, M413, M565, M578, M728, M784, P395, f26, Y1853, Y2262, Y2296, b472, *1051*
`\@wrglossary` Q25, Q30, *1047*
`\@wrindex` Q8, Q13, *1047*
`\@writeckpt` r329, r385, r424, r436
`\@writefile` r32, r101, r159, H140, O183, *623*
`\@writesetup` Y592
`\@wrong@font@char` s161, v537, v571, v584, *1058*
`\@wtryfc` Y859, Y869
`\@x@protect` f105, f242
`\@x@sf` P531, P533
`\@xDeclareMathDelimiter` . . z892, z948
`\@xaddvskip` p219, p244, p262
`\@xarg` M163, M166, M175, M178, M185, M189, M190, M226, M228, M238, M239, M243, M253, M254, M258, M266, M274, M664
`\@xargarraycr` L205, L214, L218
`\@xargdef` f80

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

\@xarraycr L202, L203
\@xbitor Y15, Y17
\@xcentercr H325, H332, H336
\@xdblarg f693
\@xdblfloat P264, *1046*
\@xdim M84, M93, M105, M107, M117, M119, M668, M732, M733, M734, M735, M741, M788, M789, M790, M791, M797
\@xeqncr I375
\@xexnoop L238, L248
\@xexpast L239, L240
\@xfloat . . P28, P29, P34, P266, *1047*
\@xfootnote P452, P455, *1024*
\@xfootnotemark . . . P519, P523, *1024*
\@xfootnotenext P536, P539
\@xfootnotetext *1024*
\@xhline L360, L361
\@xifnch f681, f691
\@xiipt v720, B164, B166, B167
\@xipt v719, B163
\@xivpt v721, B165, B167
\@xmpar P324, P325
\@xnewline p60, p61, p72, p73, p93
\@xnext Y10, Y11
\@xnthm N5, N6
\@xobeysp p420, H407, H408, H475, H479, *328*
\@xprocess@ptions U475, U492, U494, U510, U512, U526
\@xpt v718, B162, B165, B166
\@xsect O86, O87, O123
\@xtabcr L56, L57
\@xtabularcr L209, L210
\@xthm N28, N29
\@xtryfc Y846, Y874
\@xtypein f33, f35, f42
\@xverbatim H408, H459
\@xviipt v722, B166, B168
\@xxDeclareMathDelimiter . z877, z881
\@xxpt v723, B167, B168
\@xxvpt v724, B168
\@xxxii s425, s427, P89, P158, Y881, Y882, Y901, Y902, Y937, Y938, Y960, Y961, Y2039, j2, *1058*
\@xympar P328, P332, P378
\@yarg M163, M167, M175, M179, M185, M186, M195, M238, M244, M253, M259, M268, M270, M297, M664
\@yargarraycr L206, L216, L220
\@yargd@f f107
\@yargdef f84, f94, f107, f123, *1060*
\@ydim M85, M94, M105, M108, M117, M119, M668, M736, M737, M738, M739, M740, M792, M793, M794, M795, M796
\@yeqncr I375
\@ympar P324, P329
\@ynthm N5, N14
\@ythm N28, N29
\@ytryfc Y892, Y911, Y915
\@yyarg M185, M186, M187, M190, M274, M664
\@ztryfc Y920, Y931
\@@end *202*
\accent@spacefactor s70, s73, s74, *1066*
\active@math@prime I240, I241, Y590, *1066*
\add@accent s65, s67, *1059*
\add@percent@to@temptokena H127, H143, H145, H154, *624*
\add@unicode@accent s1039, s1053
\addto@hook v152, v154, v712, z386, z482, z486, z503, z627, z633, z641, z657, z660, z663, z1096, z1103, z1106, *1022*
\AddToHook *256*
\AddToHookNext *256*
\alloc@ v14, d22, d26, d38, b90, b91, b92, b93, b94, b95, b96, b97, b98, b99, b226, *1081*
\alpha@elt z45, z390, z577, z679, z1095, z1096
\alpha@list z41, z43, z399, z565, z577, z622, z677, z678, z1091, z1097, z1098
\apptocmd *256*
\atveryend@DEPRECATED . W577, W579
\best@size x438, x462, x468, x474
\bf@def@ult A397
\bfdef@ult A200, A271, A272, A273, A314, A315, A316, A401, A442, *1079*
\bfdefault@previous A267, A270, A310, A313, B106, B116, *527*
\bfseries@.. . . . . *522*
\bfseries@previous *1082*
\bfseries@rm A105, A128, A207, A210, A231, A258, A271, A314, A319, A355, *525*
\bfseries@rm@kernel A108, A131, A207, A234, *525*
\bfseries@sf A106, A128, A211, A214, A232, A259, A272, A315, A320, A356, *525*
\bfseries@sf@kernel A109, A132, A211, A235

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\bfseries@tt A107, A128, A215, A218, A233, A260, A273, A316, A321, A357, *525*
\bfseries@tt@kernel A110, A133, A215, A236
\bm@b K37
\bm@c K37
\bm@l K37
\bm@r K37
\bm@s K37
\bm@t K37
\botmark *797*
\bx@ *983*
\bx@A Y30, Y57
\bx@AA Y40
\bx@B Y30, Y57
\bx@BB Y40
\bx@C Y30, Y57
\bx@CC Y40
\bx@D Y30, Y57
\bx@DD Y40
\bx@E Y30, Y57
\bx@EE Y40
\bx@F Y31, Y58
\bx@FF Y41
\bx@G Y31, Y58
\bx@GG Y41
\bx@H Y31, Y58
\bx@HH Y41
\bx@I Y31, Y58
\bx@II Y41
\bx@J Y31, Y58
\bx@JJ Y41
\bx@K Y32, Y59
\bx@KK Y42
\bx@L Y32, Y59
\bx@LL Y42
\bx@M Y32, Y59
\bx@MM Y42
\bx@N Y32, Y59
\bx@NN Y42
\bx@O Y33, Y60
\bx@OO Y43
\bx@P Y33, Y60
\bx@PP Y43
\bx@Q Y33, Y60
\bx@QQ Y43
\bx@R Y33, Y60
\bx@RR Y43
\bx@S Y38
\bx@SS Y44
\bx@T Y38
\bx@TT Y44
\bx@U Y38
\bx@UU Y44
\bx@V Y38
\bx@VV Y44
\bx@W Y39
\bx@WW Y45
\bx@X Y39
\bx@XX Y45
\bx@Y Y39
\bx@YY Y45
\bx@Z Y39
\bx@ZZ Y25, Y45, Y55
\c@bottomnumber . . P269, P274, Y2328
\c@dbltopnumber P268, P283, P297, Y2335
\c@enumi J227
\c@enumii J227
\c@enumiv J227, *1024*
\c@equation I336, I370, I516
\c@errorcontextlines l212, *1028*
\c@footnote O12, P397, P525
\c@localalphabets z137
\c@localmathalphabets z141, z142, z150, z183, *493*
\c@mpfootnote K348, P399
\c@ncel B461, B462
\c@page F3, F6, F7, S305, S355, Y138, Y1820
\c@secnumdepth . O56, O71, O81, O140
\c@tocdepth O140, O205, O228
\c@topnumber P267, P271, Y2324
\c@totalnumber . . . P270, P276, Y2331
\c@totalpages X346, X439
\calculate@math@sizes . . . v620, x219
\catcodetable@atletter d93, d246
\catcodetable@initex d93, d243
\catcodetable@latex d93, d245
\catcodetable@string d93, d244
\cdp@elt v96, v116, v127, v128, v149, v152, v154, z311, z406, z461, z525, z606, aa472, aa473
\cdp@list v98, v114, v128, v156, v157, z329, z408, z463, z527, z608, aa473
\cf@encoding s34, s41, s44, s51, s154, v256, v266, v276, v326
\ch@ck U1144, U1163, U1275, U1296, U1388, b206, b207, b208, b209, b236, b248, b249, b250, b251, b279, b281, b293, b294, b295, b296, b302
\char@if@alph f701
\chardef@text@cmd s3
\check@command f187, f189
\check@icl D9, D44, D49, D55, D63, D70, D72

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\check@icr D9, D44, D50, D56, D64, D73, D78, *1061*
\check@mathfonts q5, s302, s328, s360, s1254, v348, v350, x250, z188, E672, *494*
\check@nocorr *1044*
\check@nocorr@ D46, *1063*
\check@range x379, x380
\check@single x378, x400
\cl@@ckpt r439, t35
\cl@page F4
\col@number Y95, Y148, Y208, Y220, *1037*
\color@begingroup v643, v703, I104, I134, K29, K89, K176, K344, K382, K399, K416, L47, L51, P475, P493, P511, Y493, *1046*
\color@endbox . . K89, P253, P348, P366, Y224, Y633, Y643, Y692, Y702
\color@endgroup v648, v709, I104, I134, K29, K89, K134, K155, K178, K364, K386, K403, K419, L49, P479, P497, P514, Y497, *1034*
\color@hbox K89, Y630, Y640, Y689, Y699, *1048*
\color@setgroup K89, K134, K153, *1034*
\color@vbox K89, P96, P165, P339, P357, P381, Y215, *1049*
\conditionally@traceoff g217, g229, l289, *291*
\conditionally@traceon . . . g253, l289
\contionally@traceon *291*
\copy@kernel@robust@command f541, f625
\count@ c14, c15, c16, c17, c18, c20, v677, v683, v685, x22, x302, x304, x326, x327, z383, z385, z389, z708, z709, z710, z756, z757, z758, z817, z818, z819, z865, z866, z867, z905, z906, z907, z913, z914, z915, z959, z960, z961, z967, z968, z969, z1028, z1029, z1030, z1036, z1037, z1038, D115, D118, a182, a183, a184, a189, M730, M731, M732, M735, M736, M739, M743, M786, M787, M788, M791, M792, M795, M799, U1187, U1189, U1190, U1191, U1320, U1322, U1323, U1324, U1409, U1411, U1412, U1413, f169, f173, f275, f300, aa239, aa240, aa247, aa249, aa539, aa540, aa547, aa549, b41, b191, b192, b197, b199, b205, b206, b207, b208, b209, b210, a69, b472, b473
\counterwithin@s t113, t114, t132
\counterwithin@x t113, t116, t133
\counterwithout@s . . . t102, t103, t129
\counterwithout@x . . . t102, t105, t130
\curr@fontshape . s180, v88, v363, v371, v375, v377, v519, v525, v528, v537, v544, v546, v554, v560, v563, v571, v578, v580, w454, x92, x100, x142, x169, x477, x497, x529, x545, x560, z333, z338, A556, A565, *1022*
\curr@math@size v352, x256, x262, x267, x284
\declare@command@copy *1081*
\declare@commandcopy f464, f468, f473, f476, f493, *96*
\declare@commandcopy@let f481, f485, f495, f563, f564, *96*
\declare@file@substitution W247, W564, X515, *879*
\declare@robustcommand f221
\DeclareEncodingSubset@aux E41, E43, E59
\DeclareFontEncoding@ v122, v124, v139, aa383, aa403, aa469, *1075*
\DeclareFontEncoding@saved aa383, aa403, aa485
\DeclareFontShape@ v21, v22
\DeclareRobustCommand *263*
\DeclareSymbolFontAlphabet@ z1083, z1086
\DeclareUnicodeAccent@ s1046, s1048, s1052
\def *272*
\default@ds U442, U471, U535, U554, U1018, U1020, *1026*
\default@family v129, v161, v487, v501, v504, v529, v564, aa474, *1021*
\default@M v136, v176, v179, v183, aa481, *1026*
\default@mextra y10, y89
\default@series v129, v162, v488, v502, v505, v526, v561, aa474
\default@shape v130, v163, v489, v503, v506, v524, v559, aa475
\default@T v170, v173, v183, v272, *1026*
\define@mathalphabet y18, y131, *1021*
\define@mathgroup . . . y19, y135, *1021*
\define@newfont v355, v364
\delayed@f@adjustment v290, w395, w396, w397, w399, w400, w411, w616, w617, w619, w620, x122, x126, x134, x138, A662, *419*
\delayed@merge@font@series w396, w460, w475, w514, x133, x136

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\delayed@merge@font@shape w617, w666, w721, x132, x135
\development@branch@name c11, c36, c50, c51, c52, c59, c60, c61
\dimen@ p349, p354, p383, p388, s429, s430, s432, s433, s796, s797, v214, v216, v222, v235, v238, v242, v623, v624, v625, v629, x451, x452, x453, x454, x458, E102, E104, E931, E933, I72, I73, I186, I187, I188, I189, K481, K484, L176, L177, Y510, Y512, Y533, Y535, b41, b469, b470, l28, l29, b506, b507, b509, b511, *1060*
\dimen@i b41
\dimen@ii v218, v223, b41
\disable@package@load W478, X473, *879*
\displ@y I191, I195, I196
\do@add@percent@to@temptokena H131, H137, H155
\do@emfont@update . A557, A561, A581
\do@noligs H577, H582
\do@subst@correction v84, x482, x537
\document@default@language r51, r52, r120, r121, Y599, aa286
\document@select@group z139, z145, z346, *493*
\dont@add@percent@to@temptokena H130, H132, H156
\dorestore@version z114, z119
\ds@ U473, U1022, *1026*
\dt@pfalse I192
\dt@ptrue I191
\e@alloc d15, d49, d79, d89, d178, d182, d186, d194, d202, d210, aa12, aa47, b51, b52, b53, b55, b56, b63, b64, b66, b68, b79, b82, b84, b138, b230, *1081*
\e@alloc@attribute@count d66, d74, d75, d76, d80, d237
\e@alloc@bytecode@count d70, d197, d198, d199, d203, d253
\e@alloc@ccodetable@count d67, d84, d85, d86, d90, d241
\e@alloc@chardef . d48, d178, d194, d202, d210, aa12, b60, b102, b210, b211
\e@alloc@intercharclass@top .. aa35
\e@alloc@luachunk@count d71, d205, d206, d207, d211, d255
\e@alloc@luafunction@count d68, d173, d174, d175, d179, d183, d187, d247, d249
\e@alloc@top d47, d80, d179, d183, d187, d195, d203, d211, aa12, b55, b63, b102, b188, b259
\e@alloc@whatsit@count d69, d189, d190, d191, d195, d251
\e@ch@ck d51, d55, b142, b152
\e@insert@top . b257, b259, b276, b291
\e@mathgroup@top z56, z149, z150, z224, z254, b79, b124, *1071*
\em@currfont A556, A567, *538*
\em@force A565, A570, A573, A583, *538*
\emfontdeclare@clist A546, A548, A552, A557, A562, A568, A579, *537*
\empty@sfcnt x490, x491, x492, x506, x511, x563
\ENC@cmd *1041*
\enc@update v257, v259, v275, v278, x147, x173, *1041*
\end@dblfloat P205
\end@float P189, P227, P243, P383, *1069*
\endlinechar *272*
\enlargethispage *801*
\err@rel@i y12, y99, y132, y136
\error@fontshape v482, v497, v522, v557, x107, x527, z332
\escapechar *267*
\et@xmaxfam d22, d26, d30, d38
\et@xmaxregs d29, d31, d32, d33, d34, d35, d36, d37
\every@math@size v78, x235, x247, *1045*
\every@size *1022*
\execute@size@function x362, x390, x404, x421
\expand@font@defaults A37, A148, A256, A279, A309, A330, A354, A365, A396, A397, A436, A438, A470, A472, A501, E26, E83, *203*
expand@font@defaults A420
\external@font x84, x87, x98, x102, x104, x391, x405, x467, x501, x569, x571, x573
\extra@def y9, y84, *1021*
\extract@alph@from@version v597, v603, z162, z230, z260, z292, *1024*
\extract@default@composite s1062, s1069
\extract@default@composite@a s1071, s1075
\extract@default@composite@b s1073, s1077
\extract@font v378, x81
\extract@fontinfo x358, x365
\extract@rangefontinfo x375, x382, x401, x434

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\extract@sizefn x350, x372
\f@... ..... *1040*
\f@baselineskip s870, s1220, v317, v324, v508, x121, x167, x182, x186, x201, x215, x226, x240
\f@depth P291, Y345
\f@encoding s178, v251, v270, v273, v274, v276, v326, v358, v363, v382, v384, v386, v391, v393, v424, v486, v518, v553, w439, w443, w652, w656, x91, x128, x307, x517, z317, d260, d275, d283, *1040*
\f@family v279, v287, v299, v309, v320, v359, v363, v382, v384, v386, v391, v393, v425, v504, v529, v564, w439, w443, w652, w656, x91, x128, z317, z348, A151, A178, A179, A258, A259, A260, A281, A282, A283, A319, A320, A321, A339, A340, A341, A355, A356, A357, A366, A367, A368, A504, A517, A659, A677, A693, E23, E27, E29, E31, E63, E66, E80, E84, E86, E88, E93, E100, E897, E900, E914, E923, E929, E1144, *527*
\f@linespread v320, x120, x166, x183, x184, x187, x195, x198, x209, x212, *1041*
\f@series ... q14, v279, v310, v321, v360, v363, v505, v526, v561, w400, w410, w419, w429, w463, w482, w483, w652, w656, x125, x128, x131, z349, A144, A160, A162, A166, A167, A168, A189, A195, A198, A200, A222, A520, A524, A660, A678, A694, A739, E7, E613, *446*
\f@series@saved x125, x131
\f@shape v279, v289, v301, v311, v322, v361, v363, v506, v524, v559, w439, w443, w620, w627, w633, w643, w650, w654, w657, w660, w669, w676, w678, w713, x124, x128, x130, z350, A661, A679, A695, A740, *543*
\f@shape@saved x124, x130
\f@size s180, s869, s1219, v88, v317, v323, v362, v507, v546, v580, v622, v623, v626, v627, x121, x142, x167, x169, x180, x200, x215, x218, x221, x226, x233, x240, x252, x255, x261, x267, x284, x285, x288, x293, x359, x366, x385, x387, x402, x453, x455, x457, x473, x474, x479, x493, x505, x510, x522, x530, x535, x561, x575, A556, A565, E102, E931
\f@user@size .. x473, x478, x522, x535
\f@warn@break *1043*
\famdef@ult A444
\filec@ntents U1098, U1101, U1104, U1115, U1136, U1229, U1232, U1235, U1246, U1267, U1360, U1382, U1470, U1685, *1053*
\filec@ntents@checkdir U1121, U1123, U1137, U1252, U1254, U1268, U1367
\filec@ntents@force U1117, U1248, U1363
\filec@ntents@noheader U1119, U1250, U1365
\filec@ntents@nosearch U1120, U1251, U1366
\filec@ntents@opt . U1101, U1104, U1106, U1232, U1235, U1237, U1362
\filec@ntents@OPTION *852*
\filec@ntents@overwrite U1118, U1249, U1364
\filec@ntents@where U1122, U1124, U1149, U1253, U1255, U1280, U1368
\filename@area r607, r622, r632, r664, r665, r669, r694, r697, r714, r730, r732, U851, a249, a255, a262, a268, a275, a281, a288
\filename@base r607, r622, r632, r664, r666, r669, r694, r697, r721, r730, U852, a298, a305, a318
\filename@dot a316, a322
\filename@dots a300, a302, a307
\filename@ext r608, r623, r633, r660, r661, r664, r667, r669, r690, r691, r694, r697, r722, U853, a297, a304, a314, a316, *885*
\filename@parse r605, r620, r630, r659, r689, r719, a113, a245, U850
\filename@path .. a250, a251, a256, a263, a264, a269, a276, a277, a282
\filename@simple a253, a266, a279, a289, a293, a295, a310, a312
\finish@module@release c86, c90
\finph@nt I104, I106, I110, I111, I119, I120
\finsm@sh I134, I136, I140, I141, I145, I146
\fix@penalty D101
\fixed@sfcnt x565, x566, x567
\fl@ShowFloat .. Y1906, Y1912, Y1927
\fl@trace Y240, Y267, Y323, Y351, Y358, Y379, Y426, Y474, Y527, Y542, Y543, Y544, Y545,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

Y556, Y557, Y558, Y559, Y560, Y570, Y783, Y802, Y821, Y839, Y841, Y980, Y984, Y996, Y997, Y998, Y999, Y1005, Y1008, Y1016, Y1020, Y1031, Y1036, Y1041, Y1042, Y1043, Y1044, Y1051, Y1054, Y1062, Y1073, Y1079, Y1084, Y1089, Y1095, Y1096, Y1101, Y1106, Y1107, Y1108, Y1116, Y1120, Y1125, Y1129, Y1134, Y1145, Y1146, Y1148, Y1166, Y1175, Y1181, Y1190, Y1193, Y1199, Y1209, Y1213, Y1223, Y1229, Y1235, Y1241, Y1248, Y1250, Y1256, Y1261, Y1263, Y1265, Y1273, Y1278, Y1284, Y1289, Y1295, Y1309, Y1310, Y1313, Y1334, Y1343, Y1349, Y1358, Y1361, Y1368, Y1378, Y1382, Y1394, Y1400, Y1405, Y1410, Y1414, Y1418, Y1419, Y1426, Y1431, Y1435, Y1442, Y1451, Y1455, Y1459, Y1460, Y1464, Y1465, Y1475, Y1481, Y1487, Y1493, Y1497, Y1503, Y1505, Y1513, Y1518, Y1523, Y1531, Y1540, Y1545, Y1550, Y1552, Y1557, Y1559, Y1570, Y1576, Y1586, Y1592, Y1596, Y1597, Y1602, Y1603, Y1609, Y1612, Y1613, Y1614, Y1621, Y1622, Y1623, Y1631, Y1636, Y1648, Y1649, Y1656, Y1659, Y1667, Y1671, Y1675, Y1676, Y1680, Y1681, Y1691, Y1697, Y1707, Y1713, Y1717, Y1718, Y1724, Y1725, Y1732, Y1735, Y1736, Y1737, Y1745, Y1746, Y1747, Y1756, Y1761, Y1774, Y1776, Y1783, Y1786, Y1795, Y1799, Y1803, Y1804, Y1808, Y1809, Y1861, Y1866, Y1872, Y1882, Y1889, Y1903, Y1904, Y1908, Y1919, Y1931, Y2029, Y2042, Y2043, Y2047, Y2050, Y2052, Y2055, Y2058, Y2060, Y2101, Y2108, Y2113, Y2119, Y2124, Y2128, Y2134, Y2142, Y2144, Y2151, Y2156, Y2161, Y2163, Y2169, Y2171, Y2178, Y2207, Y2209, Y2224, Y2226, Y2240, Y2265, Y2269, Y2274, Y2286, Y2303, Y2308, Y2316

`\fl@tracemessage` Y1903, Y1920, Y1929, Y1931

`\fl@traceval` Y1913, Y1914, Y1915, Y1916, Y1919, Y1928, Y1931

`\float@count` b51, b52, b53, b62, b188, b205, b210, b212, b213, b222, b230

`\fmtversion@topatch` aa592, aa594, aa606, aa607, aa619, aa627

`\font@info` x99, x365, x434, x439

`\font@name` s179, s182, v86, v194, v196, v354, v369, v545, v579, x84, x88, x90, x105, x141, x144, x154, x168, x171, x330, x331, x332, x333, x334, x339, *1021*

`\font@submax` x441, x470, x471, H42, H44, H82, H84, aa299, aa301, aa310, *1036*

`\fps@dbl` P34

`\freeze@math@version` z154, z178

`\frozen@everydisplay` v344, v350

`\frozen@everymath` v344, v348

`\g@addto@macro` w731, U133, U397, U1030, U1046, U1047, X350, X356, X406, f813, i60, *210*

`\G@refundefined` *1058*

`\G@refundefinedfalse` G5, *613*

`\G@refundefinedtrue` G3, G12, R41, R68, R85, *1058*

`\gen@sfcnt` x502, x503, x504

`\genb@sfcnt` . . . x507, x508, x509, *1057*

`\genb@x` x510, x512

`\genb@y` x512

`\get@cdp` z479, z487, z520

`\get@external@font` . . . x83, x96, x536

`\getanddefine@fonts` v592, v610, x320, z59, z87, z132, z159, z201, z227, z257, z288, z386, z450, z484, z486, z503, z626, z627, z659, z660, z1102, z1103, *495*

`\glb@currsize` r41, r110, r168, v341, x217, x252, x256, x262, x285

`\glb@settings` . v342, x217, x264, x295

`\gobble@finish@module@release` c106, c108, c167

`\gobble@font@spec` *1055*

`\group@elt` z35, z384, z421, z422, z443, z447, z1134

`\group@list` z388, z428, z441, z446, z447, z476, z702, z750, z811, z896, z899, z950, z953, z1019, z1022, z1089, z1140, *1064*

`\h@false` I81

`\h@true` I82, I83

File Key: a=`ltdirchk.dtx`, b=`ltplain.dtx`, c=`ltvers.dtx`, d=`ltluatex.dtx`, e=`ltexpl.dtx`, f=`ltdefns.dtx`, g=`ltcmd.dtx`, h=`lthooks.dtx`, i=`ltcmdhooks.dtx`, j=`ltalloc.dtx`, k=`ltcntrl.dtx`, l=`lterror.dtx`, m=`ltpar.dtx`, n=`ltpara.dtx`, o=`ltmeta.dtx`, p=`ltspace.dtx`, q=`ltlogos.dtx`, r=`ltfiles.dtx`, s=`ltoutenc.dtx`, t=`ltcounts.dtx`, u=`ltlength.dtx`, v=`ltfssbas.dtx`, w=`ltfssaxes.dtx`, x=`ltfsstrc.dtx`, y=`ltfsscmp.dtx`, z=`ltfssdcl.dtx`, A=`ltfssini.dtx`, B=`fontdef.dtx`, C=`preload.dtx`, D=`ltfntcmd.dtx`, E=`lttextcomp.dtx`, F=`ltpageno.dtx`, G=`ltxref.dtx`, H=`ltmiscen.dtx`, I=`ltmath.dtx`, J=`ltlists.dtx`, K=`ltboxes.dtx`, L=`lttab.dtx`, M=`ltpictur.dtx`, N=`ltthm.dtx`, O=`ltsect.dtx`, P=`ltfloat.dtx`, Q=`ltidxglo.dtx`, R=`ltbibl.dtx`, S=`ltmarks.dtx`, T=`ltpage.dtx`, U=`ltclass.dtx`, V=`ltkeys.dtx`, W=`ltfilehook.dtx`, X=`ltshipout.dtx`, Y=`ltoutput.dtx`, Z=`lthyphen.dtx`, aa=`ltfinal.dtx`

\hb@xt@ s425, I197, I363, I428, I443, I455, I482, I513, K44, K65, K83, K205, K489, K493, K494, K495, L37, M31, M43, M62, M74, M105, M117, M265, M299, M302, M305, M307, M314, M373, M452, M588, M598, M741, M797, O218, O241, O248, f29, Y632, Y642, Y691, Y701, Y1845, Y2259, Y2260, Y2264, Y2291, Y2292, Y2298, b516, *1052*
\hexnumber@ z723, z731, z766, z774, z795, z805, z831, z839, z847, z856, z859, z868, z869, z908, z916, z962, z970, z989, z990, z1000, z1001, z1006, z1032, z1040, z1045, z1047, A645
\hgl@ b471, b472
\hmode@bgroup s67, s75, s327, s356, s390, s396, s427, s438, s445, s476, s483, s486, s488, s496, s512, s730, s760, s766, s798, s805, s833, s836, s893, s1253, D7, E625, E632, *1066*
\hmode@start@before@group s68, s151, s153, s159, s184
\if@afterindent O124, O131
\if@compatibility U2, U611
\if@endpe H214, H221, H273, H288, J138
\if@eqnsw I344, I410
\if@fcolmade Y95, Y264, Y394, Y403, Y441, Y451, Y781, Y801, Y819, Y848, Y928, Y2206, Y2223, Y2273, Y2313
\if@filesw r5, r36, r105, r163, r297, r309, r330, r359, r371, r386, r406, r418, r425, r437, H21, H48, H74, H88, O153, R4, R8, R39, R48, R56, R67, R84, U1147, U1164, U1278, U1297, X359, *1047*
\if@firstamp L251
\if@firstcolumn Y95, Y246, Y279, Y396, Y444, Y1817, Y2237, Y2282, *798*
\if@font@series@context A509, A528, A536, *535*
\if@forced@series . . . w401, A143, *447*
\if@ignore H4, H216, H223, H274, H289
\if@includeinrelease c70, c73, c129, f767
\if@inlabel J28, J65, J102, J160, J183, Y161, Y188
\if@inmath *1060*
\if@insert Y95, Y1059, Y1171, Y1205, Y1339, Y1374, Y1448, Y1537, Y1664, Y1792
\if@minipage p239, p257, p276, p311, H418, H440, J149, K323, L79, P20
\if@mparswitch Y95, Y1819
\if@multiplelabels G55
\if@mypkg@draft *868*
\if@negarg . . M157, M198, M212, M273
\if@newlist H460, J29, J33, J69, J78, J106, J166, Y601, Y646, Y659, Y705
\if@nmbrlist J33, J201
\if@no@font@opt y16, y110, y129
\if@nobreak p120, p147, p278, p313, r202, r214, J167, J192, K286, K307, O47, O128, P180, P373, S153, T33, T44, T58, T66, Y165, Y192, Y335, Y1150, Y1316, *1062*
\if@noitemarg J32, J199
\if@noparitem J30, J157
\if@noparlist J31, J114
\if@noskipsec p147, J58, K287, K308, O38, O40, O97, P374, Y155, Y182
\if@ovb M427, M495, M526, M551, M562, M575
\if@ovhline M459, M590
\if@ovl M427, M493, M522, M547, M592, M601
\if@ovr M427, M492, M521, M546, M589, M599
\if@ovt M427, M494, M525, M550, M567, M579
\if@ovvline M459, M565
\if@partsw r5, r301, r363, r410
\if@pboxsw K278, K423
\if@reversemargin Y101, Y1822
\if@reversemarginpar Y95
\if@rjfield L19, L33
\if@skipping@module . c134, c146, c149
\if@specialpage . . . Y95, Y608, Y666
\if@tempswa r307, r369, r416, s1542, v99, v687, z409, z464, z528, z609, z1133, H50, H90, H425, H446, R95, U1176, U1309, U1398, W293, W294, W316, W317, W337, W338, Y992, Y1028, Y1628, Y1753, b270, a81, a82, a83, j9, *1069*
\if@test Y12, Y13, Y889, Y908, Y948, Y970, Y1034, Y1118, Y1127, Y1276, Y1287, Y1429, Y1516, Y1634, Y1759
\if@twocolumn r26, r95, r152, P32, P210, P235, Y95, Y139, Y267, Y278, Y395, Y443, Y467, Y783, Y839, Y1816, Y2208, Y2225
\if@twoside . . . Y95, Y138, Y611, Y669

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\ifdt@p I190, I192
\IfFileExists@ r470, r497
\ifG@refundefined G3, G4, G5
\ifh@ I76, I114, I123
\ifin@ s1558, s1561, y50, y52, z1, z22, z373, z475, z477, z538, z551, z621, z623, z651, z703, z717, z751, z763, z812, z828, z897, z900, z921, z951, z954, z1017, z1020, z1023, z1090, z1092, z1121, A210, A214, A218, U234, U252, U483, U517
\ifmath@fonts v204, x222
\ifmaybe@ic D82, D91, *1069*
\ifnot@nil x343, x360, x381
\ifrestore@version *1060*
\iftc@forced E871, E882, E1150
\ifv@ I75, I113, I122
\ifx *272*
\in@ s1556, s1559, y49, y51, z1, z21, z372, z474, z476, z534, z547, z620, z622, z649, z701, z712, z749, z760, z810, z824, z895, z898, z918, z949, z952, z1014, z1018, z1021, z1088, z1091, z1119, A208, A212, A216, U233, U250, U480, U516, *1069*
\in@@ w489, w490, w492, w493, z5, z6, z7, z9
\in@false z10
\in@true z12
\init@restore@glb@settings x265, x268, x270
\init@restore@version z62, z91, z108, z123, z124, *1060*
\init@series@setup w732, w737, A120, A206, A246
\input@path r483, r504, r525, r552, r569, a112, a134, a136, a142, a144, a150, a152, a157, a159, a169, a236, W276, *876*
\insc@unt Y61, b37, b51, b52, b53, b62, b90, b91, b92, b94, b247, b248, b249, b250, b251, b252, b263, b264, b265, b266, b267, b271, b273, b292, b293, b294, b295, b296, b297
\install@mathalphabet v587, v604, v611, z392, z395, z481, z482, z579, z631, z634, z641, z656, z657, z664, z1104, z1106
\is@range x376, x377
\kern *802*
\kernel@ifnextchar c87, U377, f81, f100, f150, f678, f693
\kernel@make@fragile p24, p25, p26, p27, p28, s172, s173, H394, H395, H396, I90, I91, I92, I93, I166, I167, I168, L160, L161, L162, M823, M824, M825, M826, M827, M828, M829, M830, M831, M832, M833, M834, O23, O24, O25, O26, O27, T72, T73, f375, f794, f795, f796, f797, f798, f799, f800, f801, f802, f803, f804, f805, f806, f807, f808, f809, *30*
\l@ngrel@x f74, f75, f76, f120, f167
\l@nohyphenation H422, H562, aa283, *1074*
\last@fontshape v520, v538, v555, v572
\latexrelease@postltcmd g2656
\latexrelease@postltexpl e132
\leavevmode@ifvmode p461, p462, p470, B624, B626, B628, B630, I115, I141, I206, I226, I227
\load@onefile@withoptions U855, U897, U1009, *844*
\load@onefilewithoptions U808, U959, U1485, *848*
\lower@bound x386, x387, x398
\lst@vskip *305*
\ltx@sh@ft s390, s397, s476, s484, s760, s767, b508, *1069*
\m@ne b39, *275*
\m@th q13, B337, B459, B461, B462, B465, B506, B530, B533, B537, B540, B547, B550, B557, B560, B642, I68, I71, I106, I136, I154, I156, I172, I191, I354, I443, I455, I482, I493, K278, K449, L181, O214, O237, P400, P409, P416, P437, P444, b488, b500, *1063*
\makeph@nt I101, I103
\makesm@sh I131, I133
\mandatory@arg x414, x501, x505, x510, x517, x519, x524, x526, x531, x533, x546, x562, x569, x571
\math@bgroup . . . v618, x306, x312, z53, z81, z146, z175, z221, z243, z251, z282, D130, D131, D138, *494*
\math@egroup v618, x310, x311, D131, D132, D139, *1022*
\math@famname *1021*
\math@fonts v588, v593, x232, x336, z60, z89, z160, z228, z258, z290
\math@fontsfalse q7, s302, s329, s360, s1255, v77, v206, v216, v239, E103, E673, E932
\math@fontstrue v204, v630
\math@group *1021*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\math@version v7, v336, v592, v596, v598, v599, v601, x230, z56, z59, z64, z65, z69, z84, z88, z93, z94, z98, z111, z112, z113, z126, z127, z128, z149, z151, z153, z154, z159, z163, z165, z167, z171, z224, z227, z231, z233, z235, z239, z254, z257, z261, z263, z265, z269, z285, z289, z293, z295, z297, z301, A617, *1021*
\math@version. *1021*
\mathchar@type . . z795, z805, z856, z859, z868, z884, z989, z1000, z1063
\mathph@nt I99, I105
\mathsm@sh I129, I135
\maybe@ic D63, D64, D83
\maybe@ic@ D83
\maybe@icfalse D97
\maybe@ictrue D87
\maybe@load@fontshape s71, w476, w515, x127, A164, *361*
\maybe@update@bfseries@defaults A38, A257, A266, A304
\maybe@update@mdseries@defaults A39, A280, A289, A305
\mb@b K55, K66, K74, K84
\mb@l K55, K59, K65, K74, K78, K83, M137, M141
\mb@r K55, K59, K65, K74, K78, K83, M137, M141
\mb@t K56, K63, K75, K82
\md@def@ult A397
\mddef@ult A198, A293, A294, A295, A334, A335, A336, A402, A443, *1079*
\mddefault@previous A290, A292, A331, A333, B107, B117, *1082*
\mdseries@.. . . . . *520*
\mdseries@previous *1082*
\mdseries@rm A111, A127, A128, A229, A237, A281, A293, A334, A339, A366
\mdseries@sf A112, A128, A238, A282, A294, A335, A340, A367
\mdseries@tt A113, A128, A239, A283, A295, A336, A341, A368
\meaning *272*
\merge@font@series w408, w425, w426, w507, w509, x133, *447*
\merge@font@series@ w428, w433, w510
\merge@font@series@without@substitution w460, w475, w512, x136, *448*
\merge@font@series@without@substitution@ w460, w513
\merge@font@shape w626, w639, w640, w711, w716, x132
\merge@font@shape@ . w642, w647, w717
\merge@font@shape@without@substitution w666, w719, x135
\merge@font@shape@without@substitution@ w666, w720
\mv@⟨*version*⟩ *494*
\mv@⟨*version*⟩@frozen *493*
\mv@⟨*version*⟩@reset *495*
\n@space B625, B627, B629, B631, B636, B637, B638, B639, B642
\new@command f78, f77, f131, f165, f184, f239
\new@environment f147, f146, f159
\new@fontshape y2, y4, y22, y24
\new@mathalphabet . . . z532, z553, z564
\new@mathgroup v14, d27, z412, b78, b80, b98, b100, *1022*
\new@mathversion . z20, z361, z368, z371
\new@module@skip c135, c147, c149
\new@moduledate . c79, c98, c101, c149
\new@modulename c93, c149
\new@symbolfont z413, z445
\newcommand *259*
\NewCommandCopy *263*
\NewDocumentCommand *257*
\newlinechar *272*
\newmathalphabet@ y14
\newmathalphabet@@ y109
\newmathalphabet@@@ y15, y109
\nfss@catcodes v19, v120, v387, v388, v395, v442, B40, B45, B135, Y3, *1057*
\nfss@text s315, s317, A648, D5, D122, G13, *1024*
\no@alphabet@error v4, z391, z393, z569, z570, z584, z593, z679, z680, *1036*
\no@alphabet@help *1022*
\no@version@warning *1022*
\noaccents@ v633, B129
\noexpand *273*
\non@alpherr v612, v614, z72, z101, z117, z174, z242, z272, z304, z1141
\not@base A720, A724, A725, A726, A727, A728, A729, A730, A731, A732, A733, A734
\not@math@alphabet w527, w532, w537, w683, w687, w690, w693, w696, w699, w702, w705, A5, A8, A11, A14, A17, A20, A23, A26, A29, A255, A278, A308, A329, A353, A364, A381, A384, A406, A411, A416, A449, A454, A459, A475, A478, A481, A484, A487, A597
\now@and@everyjob . . s1011, d215, d221

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\o@lign s390, s397, s476, s484, s760, s767, b502
\on@line A144, A147, H177, H232, H249, H282, K150, U863, U998, h347, h767, l8, l15, l214, *300*
\operator@font B643, I3, I4, I5, I6, I7, I8, I9, I10, I11, I12, I13, I14, I15, I16, I17, I18, I19, I20, I21, I22, I23, I24, I25, I26, I27, I28, I29, I30, I31, I32, I33, I34, I37, I40
\optional@arg x415, x494, x496, x568, x571
\outer@nobreak P181, P251, P255, P346, P364, *1049*
\p@ b311
\p@... . . . . *1076*
\p@enum *667*
\p@equation I351, I491
\p@renwd *1032*
\p@selectfont x119, *1022*
\par *158*
\par@deathcycles . . . J56, J77, J79, J80
\patch@level c1, c36, c41, c43, c45, c49, c58, aa595, aa607, aa609, *1072*
\patchcmd *257*
\ph@nt I81, I82, I83, I97
\pickup@font s181, v195, v353, v547, v581, x143, x170, x331, x333, x335
\pictur@ M21
\pkgcls@arg U1496, U1619
\pkgcls@candidate . U1483, U1498, U1574, U1578, U1582, U1650, U1653
\pkgcls@debug U1473, U1489, U1490, U1491, U1492, U1493, U1550, U1551, U1552, U1553, U1562, U1567, U1585, U1594, U1609, U1643, U1644, U1645
\pkgcls@innerdate U1478, U1523, U1526, U1532, U1671
\pkgcls@mindate U1503, U1512, U1528, U1533, *861*
\pkgcls@name U1495, U1538
\pkgcls@parse@date@arg . U1497, U1508
\pkgcls@parse@date@arg@ U1514, U1517
\pkgcls@parse@date@arg@version U1524, U1545
\pkgcls@releasedate U1483, U1579, U1583, U1654
\pkgcls@rollbackdate@error U1575, U1633, U1651
\pkgcls@show@selection U1602, U1607, U1657, U1662
\pkgcls@targetdate U1478, U1510, U1518, U1521, U1522, U1526, U1534, U1535, U1548, U1556, U1571, U1573, U1603, U1614, U1616, U1641, U1647, U1649, *861*
\pkgcls@targetlabel U1478, U1511, U1531, U1546, U1558, U1590, U1623, U1661, U1664, *861*
\pkgcls@use@this@release . U1559, U1576, U1578, U1591, U1601, U1653
\pr@@@s I246, I254
\pr@@@t I249, I255
\pr@m@s I243, I244
\preload@sizes y11, y94, *1021*
\prepare@family@series@update A117, A141, A243, A407, A412, A417, A450, A455, A460, *532*
\pretocmd *256*
\prim@s I240, I242, I254
\prime@s I241
\process@table . . r40, r109, r167, z310
\protected *242*
\protected@cmd *1054*
\protected@edef t192, A546, G67, G71, G73, G84, G88, G95, G99, G106, K380, K397, K414, O60, P472, P490, P508, f253, aa575, aa581, aa586, aa587, *796*
\protected@file@percent H122, H129, H144, H152, H153, O165, O172, *756*
\protected@wlog U323, U325, U339, U353
\protected@write r201, r206, G57, O181, Q14, Q31, *1047*
\protected@xdef O11, P453, P521, P537, U315, U334, f253, *1047*
\provide@command f179, f178
\ps@empty T10, aa158
\ps@plain T13
\q@curr@file U1098, U1138, U1140, U1145, U1171, U1269, U1271, U1276, U1304, *1081*
\quote@@name r461, r477
\quote@name r461, r474, r476, r553, r555, r564, U1269
\r@@t I66
\reenable@package@load W478, X462, *879*
\reinstall@nfss@defs w685, w726, w730, w732, w736, w737, w740
\relax *273*
\rem@pt v329
\remove@angles x347, x370
\remove@nil z36
\remove@star x347, x353

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\remove@tlig .. s1001, s1003, s1005, s1029, s1034, s1081, s1082, s1083, *1081*
\remove@to@nnil v328, x347, x373, x486
\renew@command .. f125, f124, f185, f193
\renew@environment f153, f152
\requested@test@context A503, A520, A524, *535*
\reserved@@b *509*
\reserved@a p409, p412, r211, r212, r234, r243, r252, r305, r367, r414, r484, r486, r491, r493, r505, r507, r512, r514, r515, r516, r526, r528, r533, r535, r550, r556, r560, r567, r573, r577, r606, r609, r610, r612, r621, r624, c13, r631, r634, r656, r657, r658, r662, r670, c19, r687, r688, r692, r698, r720, r724, r727, r732, c34, s81, s82, s86, s89, s97, s107, s110, s119, s138, s143, s995, s999, s1043, s1045, s1046, s1048, s1050, s1058, s1067, c178, c179, a124, v30, v31, v32, v41, v44, v47, v63, v66, v69, v105, v108, v110, v147, v151, a128, v389, v392, a129, v519, v520, v535, v538, v543, v554, v555, v568, v572, v577, v604, v607, v608, v616, w435, w436, w439, w440, w455, w456, w468, w469, w648, w649, w652, w653, w674, w675, x196, x198, x200, x210, x212, x215, x344, x345, x358, x359, y53, y57, z479, z488, z490, z534, z537, z547, z550, z648, z650, z712, z716, z760, z762, z823, z826, z918, z920, z1014, z1016, z1118, z1120, z1136, z1138, z1139, z1144, A40, A41, A73, A74, A174, A175, A516, A517, D47, D48, D53, D54, D65, D68, D88, D95, H120, H121, H175, H176, H181, H230, H231, H235, H247, H248, H252, H280, H281, H285, H296, H297, I405, I406, I407, I408, I410, a198, a199, K57, K58, K61, K76, K77, K80, K145, K151, a202, L241, L245, L250, L269, L360, L361, e22, e23, e24, e25, e26, M199, M201, M205, e47, e52, M478, M479, M506, M507, M535, M536, e89, e95, e105, a220, P29, P30, P32, P33, P63, P67, P72, P74, P76, P78, P83, P84, P132, a224, P136, P142, P145, P148, P151, U131, U134, U136, U228, U236, U240, U246, U254, U258, U385, U387, U388, U389, U393, U408, U410, U411, U412, U416, U591, U595, U601, U605, U683, U684, U687, U729, U733, U745, U746, U748, U757, U761, U773, U774, U776, U784, U788, U800, U801, U802, U804, U813, U816, U817, U819, U900, U949, U966, f117, a246, U1007, f120, U1109, U1110, U1112, f133, f134, f135, f137, U1240, U1241, U1243, U1285, U1286, U1288, U1292, U1500, U1505, U1557, U1558, U1589, U1590, U1660, U1661, a253, U1685, U1687, f184, f185, f186, f192, f193, f194, f195, f198, a256, f218, a258, W161, W167, W168, W169, f226, a259, f230, a266, f288, f292, a269, a271, f326, f330, Y37, Y46, Y48, Y50, a272, f354, f358, a279, Y879, Y899, a282, a284, f469, f477, f478, Y1999, Y2001, Y2002, Y2091, Y2093, Y2099, Y2102, f526, f529, aa226, aa243, aa244, aa245, aa252, f544, aa253, aa254, f546, f549, f558, aa491, aa494, aa525, aa531, aa532, aa543, aa544, aa545, aa552, aa553, aa554, aa573, aa574, aa575, aa576, aa579, aa580, aa581, aa582, aa608, aa611, aa612, aa629, f579, f586, f608, f611, f675, f684, a334, a335, a336, b193, k33, k37, l234, *1049*
\reserved@b p410, p411, p418, r303, r305, r365, r367, r412, r414, r551, r553, r555, r568, r570, r572, r656, r657, r658, r723, r725, r726, r733, s90, s97, s112, s119, s998, s999, s1044, s1045, s1067, s1076, s1078, v31, v32, v38, a125, v95, v97, a126, v150, v151, v605, v616, w454, w455, w457, y47, y54, y71, y73, z405, z407, z460, z462, z487, z488, z489, z524, z526, z605, z607, z652, z653, z654, z661, z821, z825, z827, A181, A186, A190, A191, A198, A199, D52, D53, D66, D68, D95, D96, L246, L248, L250, e48, e54, P43, P44, P112, P113, U229, U230, U231, U233, U248, U251, U385, U408, U737, U743, U746, U765, U771, U774, U792, U798, U802, U813, U820, f109, f111, f118, U1154, U1155, U1158, U1159, U1194, f135, U1195, U1197,

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

f136, U1224, U1287, U1288, U1291, U1292, U1327, U1328, U1330, U1356, U1416, U1417, U1419, U1446, f227, f228, f230, f289, f290, f292, f327, f328, f330, f355, f356, f358, Y788, Y791, Y805, Y808, Y825, Y828, f527, f529, aa229, aa231, aa235, f545, f549, aa497, aa499, aa503, aa574, aa580, aa629, f583, f586, f676, f686, k33, k34, k37
\reserved@c r713, v96, v97, a126, a131, v606, v609, y48, y55, y61, y68, z33, z37, z406, z407, z461, z462, z525, z526, z606, z607, z629, z638, z653, z667, z908, z925, z934, z962, z973, z1031, z1044, z1046, A183, A186, A196, A197, A200, A201, D67, D69, D76, U814, U816, U817, U1139, U1144, U1145, U1163, U1171, U1177, U1199, U1207, U1270, U1275, U1276, U1296, U1304, U1310, U1332, U1339, U1387, U1388, U1389, U1399, U1421, U1428, U1456, aa233, aa238, aa246, aa491, aa501, aa522, aa523, aa524, aa526, aa527, aa528, aa529, aa530, aa538, aa546, aa631, f681, f684, f686, f689, *1063*
\reserved@d r711, r713, a129, a132, y61, y68, y70, y74, z916, z925, z934, z970, z973, z1039, z1044, z1048, A188, A189, A194, A195, e46, e51, aa632, f674, f683, *1079*
\reserved@e p57, p59, p69, p71, p100, p107, p115, y39, y45, y70, y73, y74, z34, z39, aa633, *1056*
\reserved@f p58, p59, p70, p71, p115, s1543, s1544, s1545, s1546, s1548, s1555, v190, v192, v198, v199, x382, x393, x397, x401, x407, x410, x449, x486, x489, y27, y38, y45, y71, y73, aa634, *1049*
\reset@font . . . A219, A653, A684, A699, A714, G13, K376, K394, K411, P175, P371, P466, P485, P503, R40, T14, Y618, Y677, *1054*
\restglb@settings x268, x278
\restore@mathversion z107, z110, z125, z133
\restore@protect f253
\rlh@ B464, B465
\rm@def@ult A397
\rmdef@ult A258, A281, A319, A339, A355, A366, A398, A439, E27, E84, *535*
\robust@command@act f410, f411, f413, f479, f503, i89, *1081*
\robust@command@act@chk@args f435, f456, *94*
\robust@command@act@do . f421, f453, *95*
\robust@command@act@end f418, f419, f431, f434, f454, *94*
\robust@command@act@loop f415, f421, f451, *95*
\robust@command@act@loop@aux f421, f452
\robust@command@chk@safe . . . f303, f414, f435, f455, f560, f572, i136, *1086*
\s@fct@ x426, x490
\s@fct@alias x552
\s@fct@fixed x565
\s@fct@gen x502
\s@fct@genb x507
\s@fct@sgen x502
\s@fct@sgenb x507
\s@fct@sub x514
\s@fct@subf x557
\saved@space@catcode . . aa355, aa424
\scan@@fontshape y7, y40, y43
\scan@fontshape y6, y26, y37
\scantokens *269*
\scriptfont@name x333, x338
\section *257*
\select@group v589, v608, z48, z346, z396, z534, z587, z596, z634, z666, *493*
\series@change@debug A137, A144, A147, A158, A161, A165, A177, A185, A190, A196, A199, A201
\series@check@toks . w490, w492, w499
\series@drop@one@m . w496, w500, w518
\series@maybe@drop@one@m v31, w483, w485, w517, A168, A187, A193, A401, A402
\series@maybe@drop@one@m@x w486, w488
\seriesdefault@kernel A220, A773, *544*
\set@@mathdelimiter z971, z1005
\set@color K88
\set@curr@file r225, r234, r261, r269, r451, r469, U842, U1137, U1268, W267, *844*
\set@curr@file@aux W273, W279, W280
\set@curr@file@nosearch . W267, *1089*
\set@display@protect f8, f16, U326, f251, l7, l14, l34, l61, *1047*
\set@fontsize v317, v319, x121, x167, x177, *1039*
\set@mathaccent z721, z729, z764, z772, z790

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\set@mathchar z845, z855
\set@mathdelimiter .. z922, z931, z983
\set@mathradical z354, z1041
\set@mathsymbol z829, z837, z858
\set@simple@size@args .....
..... x348, x361, x368, x389, x403
\set@size@funct@args x351, x353, x411
\set@size@funct@args@ x411
\set@target@series .....
..... v288, v300, w437, w441,
w444, w447, w470, w472, w481, w516
\set@typeset@protect .....
.... L197, L235, f251, f270, X84,
X127, Y605, Y607, Y663, Y665, *1047*
\SetMathAlphabet@ ... z541, z610, z619
\SetSymbolFont@ z431, z465, z473
\sf@def@ult A397
\sf@size .....
. q6, s302, v224, v243, v628, x328,
x332, E672, P409, P416, P437, P444
\sfdef@ult A259, A282, A320, A340,
A356, A367, A399, A440, E29, E86, *527*
\sh@ft b506, *1050*
\show@kernel@robust@command f566, f626
\ShowCommand *263*
\sixt@@n v14, d30, z84, z285, z707,
z709, z755, z757, z816, z818, z864,
z866, z904, z906, z912, z914, z958,
z960, z966, z968, z1027, z1029,
z1035, z1037, M278, M293, M295,
P62, P80, P131, P153, Y1007,
Y1053, Y1192, Y1360, Y1594,
Y1658, Y1715, Y1785, Y2045,
Y2054, Y2110, Y2126, Y2159,
b16, b64, b66, b96, b97, b98, a74
\sixt@@n␣ *275*
\size@update .....
..... x146, x172, x185, x204, x206
\sizefn@info .....
..... x352, x354, x362, x390, x404
\skip@ p83, p442, D105,
D108, b41, b468, b470, b471, b473
\sp@n L379
\split@name .....
.. v357, v369, v483, v498, x519, x533
\ssf@size s328, s360,
s1254, v225, v244, v629, x328, x334
\string@makeletter U819,
U851, U852, U853, W169, f701, *1082*
\strip@meaning *1032*
\strip@prefix a114, v586,
a231, f228, f290, f328, f356, f698, a326
\strip@pt .....
v216, v222, v223, v224, v225, v238,
v242, v329, v628, v629, x180, b510
\sub@sfcnt x514, x515, x516, x543
\subf@sfcnt x557, x558, x559
\subst@correction v85, v91
\subst@fontshape y8, y80
\subst@size x465
\sw@slant D91, D101
\t@st@ic D90, D94, *1027*
\target@meta@family@value .....
..... A150, A175, A182, A184
\target@series@value A149,
A157, A160, A162, A166, A167,
A168, A191, A197, A198, A200, *1079*
\tc@check@accent E109,
E161, E163, E165, E167, E169,
E171, E173, E175, E177, E179,
E181, E183, E185, E187, E189,
E191, E938, E1014, E1016, E1018
\tc@check@symbol E109,
E211, E213, E215, E217, E219,
E221, E223, E225, E227, E229,
E231, E233, E235, E237, E239,
E241, E243, E245, E247, E249,
E251, E253, E255, E257, E259,
E261, E263, E265, E267, E269,
E271, E273, E275, E277, E279,
E281, E283, E285, E287, E289,
E291, E293, E295, E297, E299,
E301, E303, E305, E307, E310,
E312, E314, E316, E318, E320,
E322, E324, E326, E328, E330,
E332, E334, E336, E338, E340,
E342, E344, E346, E348, E350,
E354, E356, E358, E360, E362,
E364, E366, E938, E1008, E1010,
E1012, E1020, E1022, E1024,
E1026, E1028, E1030, E1032,
E1034, E1036, E1038, E1040,
E1042, E1044, E1046, E1048,
E1050, E1052, E1054, E1056,
E1058, E1060, E1062, E1064,
E1066, E1068, E1070, E1072,
E1074, E1076, E1078, E1080,
E1082, E1084, E1086, E1088,
E1090, E1092, E1094, E1096,
E1098, E1100, E1102, E1104,
E1106, E1108, E1110, E1112,
E1114, E1116, E1118, E1120, E1122
\tc@error E110, E918, E939
\tc@errorwarn .....
.... E21, E76, E78, E825, E827,
E829, E830, E877, E878, E879, E912

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\tc@fake@euro E97, E352, E926, E1007
\tc@forcedfalse E871
\tc@forcedtrue E876
\tc@oldstylesubst E16, E20
\tc@subst E77, E109, E911, E938
\tc@swap@accent E112, E113
\test@font@series@context A505, A515, A535, *535*
\test@next *1055*
\text@command D8, D46, *1044*
\textfont@name x331, x337
\tf@size v223, v243, v627, x328, x330, *1025*
\thr@@ b574, x58, x254, x260, x273, x280, x287, x292, I363, I512, J232, J243, M287, M288, M290, M291, M329, M355, M388, M411, aa84, aa92, b16, b530, b540, *1052*
\toks@ p408, p409, p414, c91, c103, c105, c112, c116, c119, c124, v148, v152, v154, v157, v221, v226, z6, z7, z382, z386, z392, z395, z400, z446, z447, z449, z450, z480, z482, z486, z503, z506, z565, z577, z578, z579, z625, z627, z633, z641, z645, z657, z660, z663, z671, z673, z1094, z1096, z1098, z1101, z1103, z1106, z1109, z1141, z1142, U438, U439, U441, U442, Y2245, Y2246, Y2247, Y2248, f815, f816, b41, *450*
\topmark *797*
\topmark(s) *797*
\try@load@font@shape *1064*
\try@load@fontshape . . v372, v380, v426, v531, w479, x520, z318, z335, *449*
\try@simple@size x356, x481
\try@simples x439, x445, x449
\try@size@range x101, x356, x432
\try@size@substitution . . . x103, x436
\tryif@simple x447, x448
\tryis@simple x448
\tt@def@ult A397
\ttdef@ult A260, A283, A321, A341, A357, A368, A400, A441, E31, E88, *527*
\tw@ b16, *1044*
\two@digits x512, a188, a189, f2, U1094, U1183, U1316, U1405, a89
\type@restoreinfo x202, x207
\undeclare@... . . . . *922*
\undeclare@file@substitution W247, *879*
\unexpandable@noexpand *1058*
\unexpanded *793*
\unqu@tefilef@und W143
\unquote@name . r455, r461, r478, W350
\unrestored@protected@xdef P458, P526, P542, P553, S141, T26, T54, T78, f253
\unskip *801*
\update@series@target@value A118, A152, A173, A244
\update@uclc@with@cyrillic s1505, s1533, s1563, s1571
\upper@bound . . x383, x384, x385, x398
\use@mathgroup v595, v613, v615, x299, z63, z92, z547, z649, z652, z1119, z1143, *1022*
\UTF@two@octets@noexpand *1089*
\UTFviii@four@octets aa410, aa415, aa421
\UTFviii@four@octets@@ . aa410, aa421
\UTFviii@four@octets@combine . aa445
\UTFviii@four@octets@noexpand . aa451
\UTFviii@four@octets@string . . aa448
\UTFviii@invalid aa349, aa442
\UTFviii@invalid@err aa407, aa412, aa418
\UTFviii@invalid@err@@ . aa407, aa418
\UTFviii@three@octets aa409, aa414, aa420
\UTFviii@three@octets@@ aa409, aa420
\UTFviii@three@octets@combine . aa444
\UTFviii@three@octets@noexpand aa450
\UTFviii@three@octets@string . aa447
\UTFviii@two@octets aa408, aa413, aa419
\UTFviii@two@octets@@ . aa408, aa419
\UTFviii@two@octets@combine . . aa443
\UTFviii@two@octets@noexpand . aa449
\UTFviii@two@octets@string . . . aa446
\UTFviii@undefined@err aa406, aa411, aa417
\UTFviii@undefined@err@@ aa406, aa417
\v@false I82
\v@true I81, I83
\vbox *801*
\ver@... . . . . *353*
\ver@@... . . . . *353*
\ver@⟨*file*⟩.⟨*ext*⟩ *844*
\verb@balance@group . H508, H510, H523, H525, H538, H540, H546, H547
\verb@egroup H508, H511, H523, H526, H538, H541, H547, H551
\verb@eol@error . . H548, H560, H570
\verbatim@font H432, H453, H461, H561, H571, *1056*
\verbatim@nolig@list . . . H576, H582
\verbatim@out *1063*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\version@elt z18, z31, z32, z379, z380, z429, z449, z540, z578, z670, z1099
\version@list z16, z21, z32, z372, z380, z434, z455, z474, z545, z590, z620, z675, z1112
\vgl@ b468, b469
\voidb@x u18, b311, b499
\vsplit *801*
\vss *801*
\warn@rel@i y5, y25, y29, y81, y85, y90, y95, y119, y140
\wrong@fontshape v376, v513, *1021*
\x@protect f231, f242, f293, f331, f359, f530, f550, *1047*
\xe@alloc@ aa56, aa66
\xe@alloc@intercharclass . aa35, *1071*
\xe@ch@ck aa57, aa61
\XXX@argdef *1034*
\z@ b311, *1060*
\z@skip b311, *1060*
\zap@space r261, r281, A546, R49, U229, U390, U413, U425, U590, U706, U727, U745, U756, U773, U783, U800, U1107, U1238

tex commands:
\tex_afterassignment:D X49, X137, g2227
\tex_aftergroup:D ... X57, X143, *907*
\tex_badness:D S68, S74
\tex_currentgrouplevel:D X48, X56, X136, X142
\tex_deadcycles:D X91
\tex_endlinechar:D g1712, g1714, g1715, g1721, i342
\tex_escapechar:D W212, W226, g989, g999, g1168, g1177, g1615, g2102, g2128, i199, *168*
\tex_everypar:D n74, n76, n86, n87, n138, n139, n18, n22, n26, n34, n34, *302*
\tex_gdef:D i189, *267*
\tex_hskip:D n60
\tex_indent:D n81
\tex_kern:D S65, S72
\tex_lastnodetype:D ... n59, S58, *306*
\tex_lowercase:D g1978, g2108
\tex_marks:D S146
\tex_newlinechar:D i343
\tex_noindent:D n91, n24, *303*
\tex_par:D n62, n69, n93, n134, n135, n136, n16, *306*
\tex_parskip:D n23
\tex_setbox:D X50, X138
\tex_shipout:D ... X125, X378, X508
\tex_splitbotmarks:D S82, *802*
\tex_splitfirstmarks:D S94, *802*
\tex_splitmaxdepth:D S50
\tex_unskip:D n55, S56, *306*
\tex_vbadness:D S51
\tex_vfuzz:D S52, *801*
\tex_vss:D X332
\tex_xdef:D i195, *267*
\text *1024*

text commands:
\l_text_case_exclude_arg_tl .. aa568
\text_lowercase:n aa566, *1089*
\text_uppercase:n aa567
\textacutedbl s915, s1153, E234, E235, E721, E971
\textascendercompwordmark s854, E154, E685, E954
\textasciiacute s965, s1114, E236, E237, E722, E995
\textasciibreve s913, s1152, E238, E239, E723, E968
\textasciicaron s914, s1151, E240, E241, E724, E969
\textasciicircum . s286, s558, s1088, *1045*
\textasciidieresis s953, s1101, E242, E243, E725, E985
\textasciigrave s904, s1082, E244, E245, E726, E966
\textasciimacron s960, s1109, E246, E247, E727, E990
\textasciitilde .. s287, s559, s1093, *1074*
\textasteriskcentered s267, s717, s864, s865, s1215, t164, t170, E120, E577, E642, E961, *1084*
\textbackslash s268, s560, s718, s1087, *1051*
\textbaht s939, s1156, E252, E253, E731, E1101, E1102
\textbar s269, s561, s719, s1091, *1058*
\textbardbl s270, s720, s919, s1170, t169, E127, E365, E366, E578, E650, E797, E974, *1067*
\textbf D19, *522*
\textbigcircle s729, s892, s1232, E254, E255, E732, E1053, E1054, *1068*
\textblank s861, s1229, E345, E346, E785, E1023, E1024
\textborn s905, E256, E257, E387, E733, E1059, E1060
\textbraceleft s271, s308, s562, s721, s1090, *1046*
\textbraceright s272, s309, s563, s722, s1092, *1046*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\textbrokenbar s951, s1099, E128, E651, E983
\textbullet s273, s723, s921, s1179, E121, E579, E643, E976
\textcapitalcompwordmark s853, E153, E684, E953
\textcelsius s922, s1198, E129, E353, E354, E652, E791, E977
\textcent .. s947, s1095, E130, E653, E980
\textcentoldstyle . s924, E258, E259, E392, E395, E734, E1075, E1076, *590*
\textcircled s279, s283, s300, s301, s730, s893, E155, E156, E655, E671, E687, E858, E1123, E1125, *383*
\textcircledP s958, s1200, E260, E261, E735, E1117, E1118
\textcolonmonetary s926, s1191, E313, E314, E765, E1077, E1078
\textcommaabove s353, s355, s369, s370, s458, s459, s700, s701, *1071*
\textcommabelow s324, s326, s332, s333, s703, s704, s705, s706, s707, s708, s709, s710, s711, s712, s1252, s1455, s1456, s1457, s1458, *1071*
\textcompsubstdefault E34, E39, E91, E618, E916, *1078*
\textcompwordmark s290, s291, s564, s1158, *1063*
\textcopyleft s956, E262, E263, E368, E736, E1115, E1116
\textcopyright s283, s317, s954, s1102, E131, E654, E986, *1063*
\textcurrency s949, s1097, E335, E336, E778, E853, E857, E1011, E1012
\textdagger s275, s312, s725, s917, s1177, t165, t171, E123, E581, E645, E972, *1046*
\textdaggerdbl s274, s313, s724, s918, s1178, t166, t172, E122, E580, E644, E973, *1046*
\textdblhyphen s876, E266, E267, E369, E738, E1025, E1026
\textdblhyphenchar s912, E264, E265, E370, E737, E1071, E1072
\textdegree . s961, s1110, E132, E656, E991
\textdied s907, E268, E269, E388, E739, E1063, E1064
\textdiscount s941, s1190, E270, E271, E740, E1105, E1106
\textdiv .. s978, s1135, E133, E657, E1005
\textdivorced s906, s1235, E272, E273, E741, E1061, E1062
\textdollar s255, s307, s438, s565, s798, s862, s1084, E114, E115, E623, E625, E959, E1131, E1133, *1045*
\textdollaroldstyle s923, E274, E275, E393, E394, E742, E1073, E1074, *590*
\textdong s935, s1195, E315, E316, E766, E1095, E1096
\textdownarrow s903, s1210, E317, E318, E767, E1057, E1058
\texteightoldstyle s886, E214, E215, E384, E710, E1043, E1044
\textellipsis s296, s321, s1180
\textemdash s256, s407, s411, s566, s570, s785, s1162, *1045*
\textendash s257, s408, s410, s567, s569, s786, s1161, *1045*
\textestimated s942, s1206, E329, E330, E774, E856, E1009, E1010
\texteuro s976, s1196, E351, E352, E789, E854, E1006, E1007
\textexclamdown s258, s412, s414, s571, s787, s1094, *1045*
\textfiguredash s410, s569, s1160, s1166, *1084*
\textfiveoldstyle s883, E216, E217, E381, E711, E1037, E1038
\textfloatsep Y730, Y743, Y2140, Y2190, Y2339
\textflorin s925, s1149, E333, E334, E777, E978
\textfont x337, I238
\textfouroldstyle s882, E218, E219, E380, E712, E1035, E1036
\textfraction Y1952, Y1955, Y1980, Y1983, Y2132, Y2333, *1064*
\textfractionsolidus s877, s1187, E337, E338, E780, E962, *1064*
\textgravedbl s916, s1154, E248, E249, E728, E970
\textgreater . s281, s572, s740, s1086, *1045*
\textguarani s929, E276, E277, E391, E743, E1083, E1084
\textheight r22, r23, r91, r92, r148, r149, P257, P258, P261, P287, P301, X378, Y78, Y225, Y226, Y274, Y399, Y447, Y476, Y647, Y706, Y765, Y817, aa156, aa157, *1036*
\texthorizontalbar s411, s570, s1163, s1168, *1084*
\texthyphen ... s260, s417, s574, s789, *1051*
\texthyphenchar s259, s416, s573, s788, *1045*
\textindent *1052*
\textinterrobang s933, s1186, E349, E350, E787, E1091, E1092

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\textinterrobangdown s934, s1236, E347, E348, E786, E1093, E1094
\textit D21
\textlangle s888, s1227, E309, E310, E762, E1047, E1048
\textlbrace *1045*
\textlbrackdbl s900, E210, E211, E389, E707, E964
\textleaf s908, E278, E279, E373, E744, E1065, E1066
\textleftarrow s859, s1207, E319, E320, E768, E1019, E1020
\textlegacyasteriskcentered E589, E800
\textlegacybardbl E589, E801
\textlegacybullet E589, E802
\textlegacydagger E589, E804
\textlegacydaggerdbl E589, E803
\textlegacyparagraph E589, E805
\textlegacyperiodcentered . . E589, E806
\textlegacysection E589, E807
\textless . . . s280, s575, s739, s1085, *1045*
\textlira s931, s1192, E321, E322, E769, E1087, E1088
\textlnot . . s957, s1107, E134, E658, E988
\textlquill s945, s1188, E280, E281, E745, E1111, E1112
\textmacron *1065*
\textmarried s909, s1234, E282, E283, E746, E1067, E1068
\textmd D19
\textmho s891, s1205, E284, E285, E747, E1051, E1052
\textminus s889, s1211, E343, E344, E783, E963
\textmu s966, s1115, E341, E342, E782, E996
\textmusicalnote s910, s1233, E286, E287, E748, E1069, E1070
\textnaira s928, s1193, E288, E289, E749, E1081, E1082
\textnineoldstyle s887, E220, E221, E385, E713, E1045, E1046
\textnonbreakinghyphen s409, s568, s1159, s1164, *1084*
\textnormal D15
\textnumero s940, s1199, E331, E332, E775, E1103, E1104
\textogonekcentered s487, s698, s699, *1068*
\textohm s899, s1204, E339, E340, E781, E855, E1008
\textonehalf s974, s1124, E135, E659, E1002
\textoneoldstyle s879, E222, E223, E377, E714, E1029, E1030
\textonequarter s973, s1123, E136, E660, E1001
\textonesuperior s970, s1118, E137, E355, E356, E661, E792, E999
\textopenbullet s943, s1231, E290, E291, E750, E1107, E1108
\textordfeminine s305, s955, s1103, E138, E662, E987
\textordmasculine s306, s971, s1119, E139, E664, E1000
\TextOrMath t161, t164, t165, t166, t167, t168, t169, t170, t171, t172, t177, t184, *1070*
\textparagraph s276, s310, s726, s967, s1116, t168, E124, E582, E646, E997, *1046*
\textperiodcentered s277, s727, s968, s1117, E125, E583, E647, E998
\textpermill *1064*
\textpertenmill *1064*
\textpertenthousand s492, s937, s1182, E306, E307, E308, E759, E1097, E1098, E1135, *587*
\textperthousand . . s490, s920, s1181, E118, E119, E639, E975, E1134, *1064*
\textpeso s930, s1197, E292, E293, E751, E1085, E1086
\textpilcrow s938, E294, E295, E386, E752, E1099, E1100
\textpm s962, s1111, E140, E666, E992
\textquestiondown s261, s413, s415, s576, s790, s1126, *1068*
\textquotedbl s579, s1083, *1045*
\textquotedblleft s262, s418, s577, s791, s1174, *1045*
\textquotedblright s263, s419, s578, s792, s1175, *1045*
\textquoteleft s264, s420, s580, s793, s1171, *1045*
\textquoteright s265, s421, s581, s794, s1172, *1045*
\textquotesingle s863, s1081, E141, E667, E960
\textquotestraightbase s855, E142, E371, E668, E955
\textquotestraightdblbase s856, E143, E372, E669, E956
\textrangle s890, s1228, E311, E312, E763, E1049, E1050
\textrbrace *1045*
\textrbrackdbl s901, E212, E213, E390, E708, E965
\textrecipe s932, s1201, E296, E297, E753, E1089, E1090
\textreferencemark s969, s1185, E298, E299, E754, E1119, E1120

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\textregistered s300, s301, s959, s1108, E144, E670, E989, *1058*
\textrightarrow s860, s1209, E323, E324, E770, E1021, E1022
\textrm D15
\textrquill s946, s1189, E300, E301, E755, E1113, E1114
\textsc D21, *1063*
\textsection s278, s311, s582, s728, s952, s1100, t167, E126, E584, E585, E648, E984, *1046*
\textservicemark s944, s1202, E302, E303, E756, E1109, E1110
\textsevenoldstyle s885, E224, E225, E383, E715, E1041, E1042
\textsf D15
\textsixoldstyle s884, E226, E227, E382, E716, E1039, E1040
\textsl D21
\textssc w536, D31, D39
textssc D25
\textsterling s266, s319, s445, s583, s805, s948, s1096, E116, E117, E624, E632, E981, E1130, E1132, *1045*
\textstyle q15, B469, I63
\textsubscript P419
\textsuperscript s303, s305, s306, E663, E665, E679, P402, *1052*
\textsurd s972, s1226, E304, E305, E757, E1121, E1122
\textsw w531, D30, D38
textsw D25
\TextSymbolUnavailable ... s3, s758, *1058*
\textthreeoldstyle s881, E228, E229, E379, E717, E1033, E1034
\textthreequarters s975, s1125, E146, E675, E1003
\textthreequartersemdash . s858, E145, E357, E358, E375, E674, E793, E958
\textthreesuperior s964, s1113, E147, E359, E360, E676, E794, E994
\texttildelow s911, s1155, E250, E251, E729, E967
\texttimes s977, s1129, E148, E677, E1004
\texttrademark s303, s936, s1203, E149, E678, E979, *1058*
\texttt D15
\texttwelveudash s857, E150, E361, E362, E374, E680, E795, E957
\texttwooldstyle s880, E230, E231, E378, E718, E1031, E1032
\texttwosuperior s963, s1112, E151, E363, E364, E681, E796, E993
\textulc w526, D28, D29, D35, D37
textulc D25
\textunderline *1045*
\textunderscore s288, s315, s584, s1089, *1063*
\textup D21, *452*
\textuparrow s902, s1208, E325, E326, E771, E1055, E1056
\textvisiblespace s292, s585, s1230, *1054*
\textwidth r24, r93, r150, K346, P266, Y79, Y144, Y201, Y218, Y632, Y642, Y691, Y701, Y2259, Y2291, aa157, *1036*
\textwon s927, s1194, E327, E328, E772, E1079, E1080
\textyen ... s950, s1098, E152, E682, E982
\textzerooldstyle s878, E232, E233, E376, E719, E1027, E1028
\TH s535, s1131, aa585, *1041*
\th s586, s1137, aa585, *1041*
\thanks *747*
\thanks O10, O26, *1047*
\the *304*
thebibliography (env.) *786*
\theenum *667*
\theequation I339, I351, I430, I491
\thefootnote P396, P521, P526, P546
\thempfn K348, P453, P458, P537, P542, P545
\thempfootnote K348, P398
\thepage r208, F6, G14, G58, O164, O171, O177, Q15, Q32, R43, T14, Y244, Y275, Y1829, *918*
\Theta B299
\theta B275
\thetotalpages X348, X440, *918*
\thicklines M124
\thickmuskip B646, I215, I217, I230
\thickspace I201
\thinlines M124, M816, M833
\thinmuskip ... B644, I207, I209, I225, I231
\thinspace p460, p466, p467, I176, I201, I238, *1079*
\thispagestyle T6
\tilde B519
\time a182, a186
\times B396
\title *747*
\title O6, O7, O21, O23, O31
tl commands:
  \c_empty_tl h66, h1151
  \c_novalue_tl g456, g806, g857, g918, g1285, g1361, g1477, g1582, g1727, g1734, g1774, g1826, g1907, g1934, g2016, *133*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\c_space_tl n40, W550, W553, g24, g86, g103, g114, g115, g131, g139, g149, g152, g154, g156, g158, g166, g172, g222, g223, g1037, g1051, g1052, g1293, i282
\tl_clear:N g237, g282, g311, g378, g379, g576, g685, g695, g696, g697, g699, g842, g910, g1064, g1228, g1229, g1301, g1322, g1388, g1389, g1405, g1616, g1966, i193
\tl_const:Nn X309, X314, g1251, g2232, h574, h575, h577, h578, h579, h580, h583, h584, h586, i11
\tl_count:N W543, g329, g1990
\tl_count:n g515, g520, g761, g863, g917, g1104
\tl_gclear:N *241*
\tl_gclear_new:N h127
\tl_gput_left:Nn V167
\tl_gput_right:Nn n36, z188, g1018, g1223, h293, *230*
\tl_gremove_once:Nn h35, h35
\tl_gset:Nn z185, S81, S92, S126, S127, S128, W51, h105, h158, h255, h267, h283, h321, h430, h485, h488, h508, h511, i123, n13
\tl_gset_eq:NN S79, S80, S85, S87, S91, S104, S106, S115, S117, S119, S334, S336, S338, S340, S342, S344, h64, h290, h301
\tl_head:N g2165
\tl_if_blank:nTF g511, g1371, g1788, g1829, g2619, g2620, g2621, h273
\tl_if_empty:N *245*
\tl_if_empty:NTF . S83, S148, g248, g249, g396, g626, g1235, h113, h204, h206, h1018, h1025, h1142, h1144
\tl_if_empty:nTF T30, T40, W40, W46, W58, W107, W114, W116, W118, W417, g1785, g2103, g2129, g2164, g2357, g2452, h178, h191, h194, h473, h501, h565, h1319, i119, i226, i245
\tl_if_empty_p:N X68, X114, X376, h1270, h1271
\tl_if_empty_p:n h542
\tl_if_eq:NNTF S171, S178, g271
\tl_if_eq:nnTF g638, g876, g2108
\tl_if_exist:N *242*
\tl_if_exist:NTF g1236, h81, h111, h1156, h1175, h1221, h1280, h1292
\tl_if_exist_p:N h133, h134
\tl_if_head_is_group:nTF i253
\tl_if_head_is_N_type:nTF i250
\tl_if_in:NnTF g1402
\tl_if_in:nnTF g527, g1368, g1394, *159*
\tl_if_novalue:nTF . . . g302, g321, g368, g846, g1858, g2611, g2612, g2613, g2614, g2615, g2616, h172
\tl_if_single:nTF g1955, g2594
\tl_if_single_token:nTF g586, g2100, g2596, i236, *178*
\tl_item:Nn g2060
\tl_log:n h35, h37, h974
\tl_map_function:nN g322, g512, g513, g861, g911, g2635
\tl_map_inline:Nn g636
\tl_map_inline:nn g1264, g1474
\tl_new:N S24, S25, S26, S27, S28, S29, S30, S31, S32, S33, S34, S35, S36, S37, S38, S39, S40, S41, S44, S45, W8, W9, W10, W11, W59, X53, X203, g11, g12, g13, g14, g17, g21, g28, g29, g30, g33, g37, g38, g40, g41, g46, g47, g1383, g1384, g1600, g1952, g2067, g2630, h25, h26, h27, h29, h32, h75, h84, h87, h96, h97, h156, h636, h797, h798, h799, i6, i8, i9, i10, n12
\tl_put_left:Nn g737, g1320
\tl_put_right:Nn aa568, g297, g323, g466, g504, g518, g535, g540, g668, g752, g765, g792, g800, g814, g816, g823, g835, g851, g857, g926, g951, g1079, g1087, g1103, g1110, g1296, g1299, g1392, g1393, g1400, g1410, g1478, g1512, g1739, g1749, g1968, g2013, i165, i179
\tl_replace_all:Nnn g1981
\tl_rescan:nn i19, i19, i357, i383
\tl_set:Nn W81, W82, W83, W84, X47, X135, X208, X234, X259, X286, g22, g84, g85, g238, g239, g240, g241, g269, g320, g771, g963, g981, g1143, g1292, g1327, g1365, g1471, g1498, g1505, g1518, g1524, g1530, g1536, g1542, g1548, g1554, g1560, g1591, g1613, g1635, g1948, g1949, g1975, g1999, g2030, g2034, g2060, g2202, g2203, h804, h824, h825, h830, h831, h846, h853, h854, h899, h906, i163, i176, i177, i180, i182, i203, i290, i295, i354, i380
\tl_set_eq:NN g259, g265, g273, g316, g1321, g1404, g1477, h834, h857, i194
\tl_show:N g2083, g2090, *167*
\tl_show:n g1191, g1201, h35, h36, h979, h1057

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\tl_tail:N g1669
\tl_to_str:N g1725, g1732
\tl_to_str:n S144, S157, W577, g66, g77, g182, g186, g391, g399, g412, g423, g427, g463, g557, g581, g589, g604, g617, g629, g648, g682, g1077, g1151, g1157, g1296, g1300, g1726, g1733, g1902, g1929, g2009, g2010, g2076, g2089, g2117, g2121, h222, h347, h1008, h1020, h1077, i112, i117, i352, i369, *167*
\tl_trim_spaces:n W41, W42, g178, g349, g466, g1310, g1312, g1901, g1928, g2030, g2240, h251, i228, *267*
\tl_trim_spaces_apply:nN g586, g2094, h174
\tl_use:N z195, z199, g1194, g1241, h965
tl internal commands:
\g__mark_new_top_tl S43, S79, S80, S86, S88
\g__mark_tmp_tl S43, S81, S83, S91, S141, S144, S148, S150, *804*
\tmspace I201, *644*
\to B440, B442
\today a187, a191, a199, a202, O33
token commands:
\c_space_token g2192
\token_if_active:NTF g1741
\token_if_cs:NTF g1957, *168*
\token_if_eq_catcode:NNTF g1422, i238
\token_if_eq_charcode:NNTF g344, g1657, g1689, g1700
\token_if_eq_meaning:NNTF W455, W467, g595, g598, g606, g1144, g2206, g2598, g2600, i184, i358
\token_if_macro:NTF i83, *263*
\token_to_meaning:N . . . i79, i355, i381
\token_to_str:N W241, g66, g74, g77, g349, g715, g958, g1072, g1193, g1203, g1435, g1581, g1742, g1901, g1928, g2104, g2117, g2121, g2130, g2241, g2504, g2505, g2518, g2519, g2560, g2561, g2574, g2575, h219, i78, i79, i101, i374, i377, *167*
\toks n38, d36, z576, z577, z587, z596, aa635, b31, b63, b95, *304*
\toksdef d230, b46, b63, b95
\tokszero d230
\tolerance v647, v692, v707, T87, T95, b317
\top B320
\topfigrule Y729, Y2361
\topfraction P273, Y2327
\topmargin Y71, Y626, Y685
\TopMark S274, S379, *797*
\topmark Y2245, Y2254, *791*
\topsep I497, J2, J59, *656*
\topskip r59, r127, r182, J1, Y128, b388, *336*
\totalheight K33, K34, K35
totalpages *902*
trace\check@icr commands:
trace\string_stack\string_levels aa96
\tracefloats Y1931
\tracefloatsoff Y1931
\tracefloatvals Y1931, *1086*
\traceoff *291*
\traceon *291*
\tracingall b524, *291*
\tracingassigns . . b576, b593, b634, b542
\tracingcommands b558, b574, b583, b596, b620, b637, b343, b540
\tracingfonts x17, x54, x58, x86, x118, x153, x194, x224, x238, x254, x260, x273, x280, x287, x292, x301, x314, x322, x325, *1023*
\tracinggroups . . . b567, b605, b645, b532
\tracingifs b568, b604, b644, b533
\tracinglostchars . b553, b565, b584, b608, b628, b648, b342, b525, b530
\tracingmacros b557, b573, b585, b607, b627, b647, b337, b539
\tracingnesting . . b570, b602, b642, b535
\tracingnone b589
\tracingoff x118, x322
\tracingon x119, x323, *1023*
\tracingonline b595, b619, b636, b666, v656, Y1917, b336, b519
\tracingoutput b599, b623, b640, b663, b341, b520
\tracingpages b552, b564, b584, b609, b629, b649, b340, b529
\tracingparagraphs b554, b566, b585, b606, b626, b646, b339, b531
\tracingrestores b559, b575, b585, b594, b625, b635, b344, b541
\tracingscantokens b549, b569, b603, b617, b643, b534
\tracingstacklevels b601, b347, b350, b352, b353, b357, b361, b525, b537, *1005*
\tracingstats b551, b563, b583, b610, b630, b650, aa2, b338, b528
\triangle B322
\triangleleft B358, B482
\triangleright B359, B482
\TrimSpaces g2631
trivlist (env.) J89

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\trivlist . . . H351, H401, H403, H417, H439, I481, J89, L78, N35, N37, *663*
\tt *1027*
\ttdefault A12, A216, A400, A417, A441, A460, A488, B50
\ttfamily A10, A11, A410, A458, A459, A486, A487, D17, H461, *532*
ttfamily A420
\ttsubstdefault B20, B32, E32, E89
\twocolumn Y199, *1061*
\twocolumn[...] *1056*
\twocolumn[] *336*
\typein *80*, *80*
\typein f31
\typeout *80*
\typeout r200, r638, r639, r645, r679, c21, r717, r731, r734, c38, c43, c48, a119, v366, w478, A138, A563, A744, A754, A764, B9, B125, a175, a200, a202, a214, Q8, a229, Q25, f3, S239, S240, S244, S248, S252, S256, S260, a236, f36, f43, U321, U337, U349, a247, U1474, U1673, U1676, a260, X104, X115, X147, a273, a286, Y1920, Y1932, aa276, f567, f568, aa589, aa596, aa608, aa609, aa617, f601, f602, f607, a324, a76, l74, *100*

U

\u s237, s386, s472, s589, s596, s616, s623, s754, s1242, s1317, s1318, s1333, s1334, s1343, s1344, s1357, s1358, s1359, s1383, s1384, s1409, s1410, E163, E194
\uccode aa240, aa248, aa255, aa257, aa260, aa262, aa540, aa548, aa555, aa557, aa560, aa562
\Ucharcat A624
\uchyph b366
\ulcdefault w526, w605
\ulcshape w526, w604, w698, w699, A549, D29, *451*
\Umathcode p476, d30, B15, B50, B65, E159, E367, H467, aa160, aa351, aa534, b127
\unboldmath A615
\UndeclareTextCommand s191, E115, E117, E119, E308, E585, E1130, E1131, E1132, E1133, E1134, E1135, *583*
\undefined t71, t72, t128, t129, t130, t131, t132, t133, B116, B117, a12, a14, a20, aa168, aa180, aa181, aa201, a60, *1057*
\undefinedpagestyle T4, T8
\underbar f788, f809, b489
\underbrace B540
\underline *671*
\underline K445, K446, b489
\underscore *1063*
\unexpanded D47, H191, H237, H254, U740, U1502, U1504, aa575, aa581, f584, f595, *1086*
\unhbox *1024*
\unhcopy L345, M742, M798, b491
\unicodedataline d143, d146, d160, d161, d162
\UnicodeEncodingName s981, s987, s1038, s1044, s1048, s1059, s1063, s1079, s1080, E376, E377, E378, E379, E380, E381, E382, E383, E384, E385, E386, E387, E388, E389, E390, E391, E392, E393, *388*
\UnicodeFontFile s1036
\UnicodeFontName s1037
\UnicodeFontTeXLigatures s993, s1033
\unicoderead d143, d157, d158, d159, d160, d165
uninstall d838
\unitlength K53, K64, K73, K83, M5, M29, M30, M32, M34, M42, M43, M44, M45, M60, M63, M73, M74, M84, M85, M93, M94, M107, M108, M119, M164, M176, M241, M256, M316, M318, M332, M340, M342, M357, M375, M377, M392, M397, M399, M414, M417, M422, M480, M481, M508, M509, M537, M538, M612, M628, M648, M654, M690, M691, M693, M694, M697, M698, M700, M701, M712, M713, M715, M716, M718, M719, M721, M722, M750, M751, M753, M754, M757, M758, M760, M761, M772, M774, M776, M778, X326, aa149, *899*
\unkern v675
\unless d151, d159, d161
\unlhd A732
\unpenalty v678, v682, D116, H433, H455, *301*
\unrhd A734
\unsetattribute *45*
\unsetattribute d82, d240
\unskip *1024*
\unvcopy I180, *798*
\Uparrow B584

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\uparrow B578
\upbracefill B543, B560
\updefault w688, A21, B94, B101, B103, B111, B113, *1078*
\Updownarrow B588
\updownarrow B582
\uplus B378
\uppercase *1037*
\upshape s442, s732, s802, s895, w686, w687, A19, A20, A549, A560, A593, A651, D24, E629, *536*
\Upsilon B304
\upsilon B286
use commands:
\use:N z202, e178, S82, S95, S146, V155, W443, W447, W449, W466, g711, g1238, h915, h916, h956
\use:n V116, g136, g596, g599, g759, g987, g1074, g1166, g1210, g2595, g2597, g2602, h226, h1105, h1231, i104, i169, i172, i200, i206, i267, i300, i321, i349, i366, *269*
\use:nn h886, h1121, h1413, i211
\use:nnn g2504, g2518, g2560, g2574, *176*
\use_i:nn T41, g838, g1393, g2132, g2184
\use_i:nnn g2110, *229*
\use_i:nnnn i265, *269*
\use_i_delimit_by_q_recursion_stop:nw i328
\use_i_delimit_by_q_stop:nw . . g358
\use_ii:nn g1377, g1765, g1778, g1817, g1835, g1860, g1893, g1920, g2131, g2606, i56, i138, *229*
\use_ii:nnn g1376, g1834, g2114, g2599
\use_ii:nnnn i270
\use_ii_i:nn i210
\use_ii_iii:nnn W216, W230, W242, W242
\use_iii:nn *229*
\use_iii:nnn W47, g1794, g2109, g2112, g2183, g2601
\use_iii:nnnn g1793
\use_iv:nnnn g344, g350
\use_none:n . . . S218, W131, W134, X7, g93, g600, g1371, g1372, g1375, g1378, g1392, g1419, g1556, g1829, g1830, g1833, g1836, g2066, h7, h682, h746, h762, h884, i272, i328, *242*
\use_none:nn z201, g1003, g1550, g1788, g1789, g1792, g1795, h1077, h1103
\use_none:nnn g770, g1544, g1786, g2174, *159*
\use_none:nnnn g1538
\use_none:nnnnn g1532, h991
\use_none:nnnnnn g1526
\use_none:nnnnnnn g1520
\use_none:nnnnnnnnn h682, h991
\use_none_delimit_by_q_recursion_stop:w g272
\use_none_delimit_by_q_stop:w g2004, g2023, g2027
\usebox K156
\usecounter J225, J238
\usefont s1570, v80, v282, v652, A709, E7, E613, H471, *1056*
\UseHook r315, r321, r326, r337, r376, r380, r383, x145, A263, A274, A286, A296, A317, A324, A337, A344, A403, A408, A413, A418, A663, A680, H173, H185, H188, H212, H215, H219, H222, U913, U917, U941, U945, W170, W171, W174, W175, X118, X168, X380, h1491, h1597, i212, i374, i377, *267*
\UseLegacyTextSymbols E576, E799
\UseName *77*
\UseName e174, e192
\UseOneTimeHook . . r15, r57, r70, r316, r320, r325, r338, r377, r379, r382, H14, H18, H28, H29, H31, U914, U918, U940, U944, h1491, h1598, *1087*
\usepackage U611, U673, U1489, *187*
\UseRawInputEncoding aa381, aa437, aa484
\UseTextAccent s149, s150, s188, E110, E111, E113, E156, E158, E939, E1124, E1125, E1127, E1128, *1045*
\UseTextSymbol s150, s186, E109, E352, E938, E1007, *1063*
\usetikzlibrary *187*
\ushape *1064*

V

\v s238, s387, s471, s592, s593, s594, s598, s600, s603, s605, s607, s613, s619, s620, s621, s625, s627, s630, s632, s634, s640, s755, s1247, s1327, s1328, s1329, s1330, s1339, s1340, s1373, s1374, s1379, s1380, s1391, s1392, s1399, s1400, s1403, s1404, s1426, s1427, s1428, s1429, s1430, s1431, s1432, s1433, s1434, s1435, s1436, s1445, s1446, s1447, s1448, s1451, s1452, E165, E195
\vadjust p37, p59, p71, p100, p107, p341, p357, p375, p391, P201, P223, *295*
\valign E101, E930
\value *400*

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\value t14, R9, *1024*
\varbigtriangledown B362, B365
\varbigtriangleup B363, B364
\varepsilon q15, B291
\varphi B296
\varpi B293
\varrho B294
\varsigma B295
\vartheta B292
\vbadness X210, X212, X261, X263, Y2242, b319, *914*
\vbox *295*
vbox commands:
  \vbox_set_split_to_ht:NNn S76
  \vbox_set_to_ht:Nnn S53, S62, X213, X264
  \vbox_to_zero:n X324
  \vbox_unpack:N S64, S69, S287, S318, X224, X274
\vdash B404
\vdots B510
\vec B524
\vector M233, M817, M834, l269
\vee B367, B369
\verb . . H465, H490, H503, H509, H518, H524, H534, H539, H552, H554, *1080*
\verb* *1076*
verbatim (env.) H459
\verbatim H459
verbatim* (env.) H483
\verbvisiblespace H465, H467, H474, H478, H490, H495, *1076*
\Vert B571, B573
\vert B576
\vfil E102, E105, E931, E934, M566, M578, X391, X403, Y175, Y194, Y412, Y459, Y629, Y688, b478
\vfilneg b478
\vfuzz T90, T97, X209, X211, X260, X262, b374, *914*
\vglue b468
\vline L366
\vphantom s497, s513, I75
\vrule p452, s293, s295, s502, s518, x190, B558, B559, B561, B562, K165, K167, K218, K225, K444, K488, L186, L219, L347, L366, M227, M299, M302, M324, M333, M350, M359, M383, M391, M406, M413, M565, M578, M726, M782, Y1853, Y2262, Y2295, b472, *996*
\vsize *1059*
\vskip *305*
\vspace p330, p400, p401, p402
\vsplit Y382, Y429, Y2244

W

\wedge B366, B368
\whatsit d194, *45*
\widehat B527
\widetilde B526
\widowpenalties b106
\widowpenalty v665, b326
\width K30, *1044*
\wlog a103, d6, d7, d8, d54, U351, aa60, aa642, b40, b145, b239, b254, b284, b299, *1034*
\wp B312
\wr B382
\write *1024*

X

\x c93, c96, v333, v334, aa330, aa332
\xdef *1023*
\XeTeXcharclass v640, aa39, aa47, aa54, aa67, aa73, aa82, aa89
\XeTeXcharclassCL aa173
\XeTeXcharclassCM aa177
\XeTeXcharclassEX aa174
\XeTeXcharclassID aa171
\XeTeXcharclassIS aa175
\XeTeXcharclassNS aa176
\XeTeXcharclassOP aa172
\XeTeXcharglyph s1034
\XeTeXdashbreakstate aa273
\XeTeXglyph s1034
\XeTeXintercharclasses . . . aa167, aa200
\XeTeXinterchartoks . . . aa168, aa182, aa183, aa184, aa185, aa186, aa187, aa188, aa189, aa190, aa191, aa192, aa193, aa194, aa195, aa196, aa201, aa206, aa207, aa208, aa209, aa210, aa211, aa212, aa213, aa214, aa215, aa216, aa217, aa218, aa219, aa220
\XeTeXmathcode aa161, aa535
\XeTeXrevision aa41
\XeTeXuseglyphmetrics aa270, aa272
\XeTeXversion A623, aa41
\Xi B301
\xi B281
\xpt *1027*
\xtxHanGlue aa180, aa204, aa212, aa213, aa214, aa215, aa216, aa217, aa218, aa219, aa220
\xtxHanSpace aa181, aa205, aa206, aa207, aa208, aa209, aa210, aa211

Y

\y c94, c96

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx

\year c14, a188, U1183, U1316, U1405

Z

\Z aa252, aa531, aa552
\z aa243, aa532, aa543
\zeta B273

File Key: a=ltdirchk.dtx, b=ltplain.dtx, c=ltvers.dtx, d=ltluatex.dtx, e=ltexpl.dtx, f=ltdefns.dtx, g=ltcmd.dtx, h=lthooks.dtx, i=ltcmdhooks.dtx, j=ltalloc.dtx, k=ltcntrl.dtx, l=lterror.dtx, m=ltpar.dtx, n=ltpara.dtx, o=ltmeta.dtx, p=ltspace.dtx, q=ltlogos.dtx, r=ltfiles.dtx, s=ltoutenc.dtx, t=ltcounts.dtx, u=ltlength.dtx, v=ltfssbas.dtx, w=ltfssaxes.dtx, x=ltfsstrc.dtx, y=ltfsscmp.dtx, z=ltfssdcl.dtx, A=ltfssini.dtx, B=fontdef.dtx, C=preload.dtx, D=ltfntcmd.dtx, E=lttextcomp.dtx, F=ltpageno.dtx, G=ltxref.dtx, H=ltmiscen.dtx, I=ltmath.dtx, J=ltlists.dtx, K=ltboxes.dtx, L=lttab.dtx, M=ltpictur.dtx, N=ltthm.dtx, O=ltsect.dtx, P=ltfloat.dtx, Q=ltidxglo.dtx, R=ltbibl.dtx, S=ltmarks.dtx, T=ltpage.dtx, U=ltclass.dtx, V=ltkeys.dtx, W=ltfilehook.dtx, X=ltshipout.dtx, Y=ltoutput.dtx, Z=lthyphen.dtx, aa=ltfinal.dtx