

Photo Card Organizer

A practical guide to safe camera-card imports, organized libraries, verified moves, named destinations, Digest Inboxes, travel sync, backups, and editing exports.

USER GUIDE | VERSION 0.7.1


WINDOWS + LINUX

COPY IS THE DEFAULT

MOVE REQUIRES VERIFICATION

Start here

Photo Card Organizer monitors identified camera cards and ordinary folders, reads available metadata, and places media into a configurable library. This guide follows the normal setup sequence and highlights every action that can modify source media.



The safety promise

Copy leaves source files untouched. Move is performed as copy, cryptographic checksum verification, required backup verification, transfer-log writes, and only then source deletion.

Guide map

Section	Use it for
Install and launch	Install the self-contained package and open the desktop or tray application.
Manage libraries	Name local, mounted-network, and removable destinations and select a default.
Onboard a card	Identify a card, choose a camera label, configure sorting, and approve the first scan.
Organize a folder	Import an existing library or working folder without placing identity files in it.
Digest incoming folders	Retain varied folder sources, process only new work, and review per-file state.
Travel and export	Move verified sessions between clients and prepare grouped copies for editing.
Safety and recovery	Understand checksums, backups, conflicts, space limits, logs, and error handling.
Reference	Find folder tokens, command-line operations, and troubleshooting steps.

Before using Move

Run at least one copy session with the real camera, card reader, primary library, and backup drives. Open several imported JPEG, RAW, video, and sidecar files before enabling source deletion.

1. Install and launch

Windows

1**Run the installer**

Open **PhotoCardOrganizer-Installer-0.7.1.exe**. This is separate from PhotoCardOrganizer.exe, which launches the installed application. The single offline installer contains Python, PySide6, all application dependencies, and this guide.

2**Choose integration**

Review the per-user destination and select Start Menu, desktop, and login-monitoring shortcuts. The Start Menu group includes the current PDF guide and a clearly named Uninstall shortcut. Administrator access is not normally required.

3**Install, repair, or remove**

The Ready page summarizes the operation before files are changed. When an installation is detected, the same Installer file offers repair/upgrade or uninstall.

4**Launch**

Start Photo Card Organizer from the wizard or selected shortcut. Only one application instance runs; a later launch restores the existing window.

```
PhotoCardOrganizer-Installer-0.7.1.exe
```

Linux

```
sudo apt install ./photo-card-organizer_0.7.1_amd64.deb
photo-card-organizer
```

```
chmod +x PhotoCardOrganizer-0.7.1-x86_64.AppImage
./PhotoCardOrganizer-0.7.1-x86_64.AppImage
```

The Debian package and AppImage contain the Python application runtime. The same executable also supports command-line operations. Tray availability depends on the desktop environment, particularly on Wayland.


Optional ExifTool

When ExifTool is available on PATH, it expands RAW and video metadata support. Files still transfer without it; unavailable fields fall back to other metadata readers, file time, or the retained card profile.

Installation maintenance

Keep the downloaded Installer file as the single Windows maintenance entry point. Running it again detects the installed package and offers repair/upgrade or uninstall. The application footer reports the detected installation and opens the registered uninstaller; Windows Installed apps and the Start Menu expose the same uninstall path. The uninstaller preserves per-user settings, profiles, and logs by default and never targets imported media or transfer records. Developer environments expose their local scripts.

2. Find your way around



Page	Purpose
Dashboard	Connected-card status, destination space, manual import, monitor pause, and immediate scan.
Libraries	Set up named local, mounted-network, and removable destinations, choose the default, and maintain versioned library metadata.
Cards and drives	Guided onboarding, offline profiles, identity folders, and connection status.
Import or merge	Follow Source, Destination, and Review steps before adding files from another folder or library.
Digest inboxes	Retain varied incoming folders, run or monitor copy ingestion, and review per-file state.
Travel sync	Separate tabs for direct laptop libraries and publish/catch hubs on SMB, USB, or synchronized folders.
Library export	Scan the master library, select captures or groups, and make verified copy-only editing exports.
Organization	Independent extensions, one to twelve editable folder levels, and filename rules for photos, RAW, videos, sidecars, and records.
Safety and location	Verification, checksums, conflicts, space reserves, retries, backups, local history, and place names.
Conflict review	Search and page large queues, compare files side by side, and bulk-update review status.
Activity	See transfer, warning, retry, conflict, and error events.
Help & about	Open the version-matched PDF manual, read the in-app changelog, and view project credits.

Progress remains visible below every page. Save settings is highlighted only when controls differ from the saved processing snapshot. The footer holds library, settings, and installation commands; Help & about opens this guide and the changelog.

3. Onboard a card or drive

Onboarding pauses automatic monitoring and collects all settings before writing the root identity or beginning the first scan.

1

Card identity

Choose the card or drive root, display name, stable card ID, optional camera-name override, and media source folders such as DCIM. An existing identity is detected and loaded.

2

Destination

Choose a named primary library, optional Wedding, Client Shoot, Trip, or custom subfolder route, and transfer method. Copy is recommended for initial use.

3

Organization and safety

Choose a folder preset or retain detailed rules, enable media classes, select copy verification and move checksum, set destination reserves, and optionally enable online place names.

4

Review

Read the concise source, destination, operation, media, camera, verification, organization, and backup summary. Nothing is written or scanned until the **Confirm initial scan and import** prompt is accepted.

Move receives another warning

After the initial review, Move displays a separate confirmation naming the checksum algorithm, required logs, and required backup destinations before transfer work begins.

Identity layout

```
CARD_ROOT/  
|-- .photocard/  
|   |-- identity.json  
|   |-- transfers/  
|-- DCIM/
```

The identity folder is stored at the card root, not inside DCIM. Its folder name, identity filename, history folder, and transfer-record naming are configurable. The root marker lets multiple computers recognize the same card.

Retained profiles

A matching local profile retains the card name, root, camera override, source folders, library subfolder, operation, enabled state, and empty-folder cleanup preference. Offline profiles remain editable while the card is disconnected.

4. Camera metadata and folder organization

Named library destinations

Libraries retains multiple primary destinations and one default. Set up library creates or connects a destination; connecting an existing folder does not scan, import, or move media. A destination may be local, removable, or a network folder already mounted and authenticated by the operating system. Each library keeps versioned identity, migration state, manifests, and session records under its own .photocard-organizer folder. Initialize, check, upgrade, or repair metadata requires a separate confirmation and never changes media files.

Camera make and model are extracted automatically from EXIF when available. ExifTool is preferred when installed; Pillow and ExifRead provide additional fallbacks. The Camera folder token resolves in this order:



When to use the override

Leave Camera name override empty for normal EXIF behavior. Enter a value when a camera writes inconsistent model strings, metadata is absent, or several cards should share one controlled library label.

Camera folders reduce collisions, but do not guarantee uniqueness

Two bodies of the same model normally report the same EXIF camera label, and many cameras restart names such as IMG_0001. For a mixed library, keep the override blank, organize by date and camera, use a filename such as {date:%Y%m%d_%H%M%S}_{original}, and retain the conflict suffix policy.

Folder presets

Preset	Result below the optional library subfolder
Date then camera	Media type / year / shoot date / camera
Camera then date	Media type / camera / year / shoot date
Date only	Media type / year / shoot date
Media folder only	Media type
None (no folders)	Filename directly below the library subfolder
Use current detailed rules	Keeps the independent Organization-page levels for each media class

Detailed folder tokens

Token	Example	Source
{date:%Y-%m-%d}	2026-07-12	Capture date, then file time fallback
{date:%m - %B}	07 - July	Standalone capture month
{camera}	Canon EOS R5	Override or EXIF camera

Token	Example	Source
{location}	Asheville, North Carolina	GPS and optional online place lookup
{rating}	4 stars	EXIF/XMP rating
{card}	R5 Card A	Retained card name
{media}	Raw	Detected media class
{capture_group}	Long Exposure Brackets	High-confidence conditional group; omitted otherwise
{original}	IMG_0421.CR3	Original filename

Conditional long-exposure folders

Capture grouping can detect nearby photo/RAW exposures that share a source folder and camera label, contain at least the configured number of captures, include a long exposure, and vary shutter duration or exposure bias. Add Long-exposure brackets as a media folder level to use the result. Non-qualifying files omit that level; same-stem sidecars inherit a qualifying capture's group.

5. Import or merge a library

Use **Import or merge** for media already stored in a normal folder, another managed library, a backup, or a removable transfer drive. This workflow never creates a .photocard identity or portable history inside the source.

1**Source**

Select the source folder, accept or edit its source name, and choose whether the scan includes subfolders. Folder selection does not open another dialog or begin analysis.

2**Destination**

Choose the receiving library, optional import grouping, Copy or verified Move, enabled media types, folder layout, and optional camera override. Event/project fields appear only for a named grouping. Analyze source folders only when a read-only editable mapping would be useful.

3**Review**

Read the exact scan scope, destination, operation, media, organization, verification, and backup plan. Save settings + Import opens the final confirmation, saves the reviewed settings, and only then starts the scan; Move then receives the separate checksum-and-deletion warning.

Detected mappings follow the source scope

Changing the source path, recursive scan setting, or enabled media types clears a previously detected mapping. Analyze again or choose another folder layout so stale source assumptions are never reused silently.

Analysis preview versus full import

Structure analysis previews at most 10,000 filesystem files and offers up to twelve editable source-folder levels. If the preview limit is reached, the dialog says so and shows how many files informed the mapping. The eventual import is not capped and scans every enabled media file in the selected scope.

Why a separate destination is required

Scanning and reorganizing in place can cause source/destination overlap, repeated discovery, or name ambiguity. Use a second folder or drive, verify the result, and only then retire the old layout.

Supported file classes

JPEG/photos, RAW, video, and sidecar files each have an enabled switch, customizable extension list, one to twelve independent folder levels, and a filename template. Add or remove levels in Organization, enter a fixed folder name directly, disable an unneeded class, or set a level to None where no directory segment is desired.

First backup-library test

Use an empty destination, Copy, SHA-256 copy verification, recursive scanning, and the normal rename policy for conflicts. Keep Camera override empty so each file can use its own EXIF make/model. Exact-content duplicates are preserved according to the configured duplicate policy; a second run of the same retained source should report no new imports. The current manifest tracks stable sources and expected destination collisions, but is not yet a whole-library fingerprint catalog for identical media arriving through unrelated historical paths.

6. Digest incoming folders

Digest inboxes retains ordinary incoming folders with any existing hierarchy. A source may be a local staging folder, removable drive, SMB/UNC path, Linux mount, or locally synchronized cloud folder. It must remain separate from the managed master library.

1**Add an inbox**

Choose a stable name and incoming folder. Enable subfolders for a varied legacy tree, then optionally select a master-library subfolder or camera override.

2**Choose source handling**

Leave Copy selected for normal use. Optional automatic checks are copy-only and use the configured interval. Move is manual and disables automatic digestion.

3**Review and digest**

Select one or more available inboxes. Confirm source names, master destination, copy and move verification, required backups, organization rules, and any offline sources before scanning.

4**Review state**

Filter the queue by pending, processed, failed, or conflict. The table labels the latest visible entries against the complete retained total; each relative source path keeps its state in the local manifest, and each manual scan creates a separate digest run record.

Copy does not multiply unchanged files

Copy leaves the incoming source in place, but a later scan recognizes the same relative path, size, and modification time and reports it as already handled instead of creating another destination copy. A changed file is treated as new work.

Verified move is a deliberate cleanup action

Move requires the normal review and a second warning. A source is removed only after its primary destination, every required backup, cryptographic checksum, and required transfer records succeed. Any failure leaves that source in place for retry.

Cloud and shared folders

Photo Card Organizer works with the local folder exposed by the operating system or synchronization client. Automatic digestion never deletes source files. Avoid Move on a synchronized folder unless remote deletion propagation is intentional, separately backed up, and tested with disposable data.

Forgetting a profile removes only its saved connection. Incoming files, master-library files, and retained local digest history are unchanged.


7. Copy and verified Move

Copy



Copy is the default globally and per card. Existing destination files are not overwritten. The source remains unchanged even if a backup, log, location lookup, or metadata field fails.

Move



Deletion gate

The source is retained whenever checksum verification, required replica verification, portable history, or required local history is incomplete. A verified primary copy may remain for safe retry without being duplicated.

If the computer loses power during a temporary copy, the source remains. On the next write to that folder, the app removes abandoned partial files owned by the same client; it does not remove another client's in-progress partials.

Verification choices

Setting	Choices	Notes
Copy verification	Size, SHA-256, SHA-512, BLAKE2b	Size is faster; cryptographic choices compare content.
Move checksum	SHA-256, SHA-512, BLAKE2b	Cryptographic verification is mandatory for source deletion.
Replica verification	SHA-256, SHA-512, BLAKE2b	Required replicas must verify before completion.

The footer progress bar reports files checked during scans and imports. Activity records meaningful events without inserting every progress tick.

8. Backups, clones, and free space

Add multiple destinations under Safety and location > Backups and clones. Each destination can be enabled, required or optional, configured to receive matching history, and assigned a replica conflict policy.

Destination type	Import behavior	Move behavior
Primary library	Always required	Must verify before deletion
Required backup	Failure leaves work pending for retry	Must verify before deletion
Optional clone	Failure is recorded as a warning	Does not block deletion after all required targets succeed

Space safeguards

The application checks both minimum free percentage and minimum free GB. It can block, try fallback destinations then block, or continue below the configured reserve when enough physical bytes remain.

A full drive never offers Continue

Manual space prompts can offer another destination, skip, or stop. Continue below reserve appears only when the drive has enough physical space for the file.

A low source free-space threshold is informational. It never silently changes Copy to Move.

9. Duplicates and filename conflicts

Before placement, same-name files are compared by content. Exact-content duplicates and different-content collisions have separate policies. The default preserves both files.

Policy	Result
Rename	Keep the organized destination and append a configurable value such as _2, (2), or a custom {number} pattern.
Conflict folder	Place the incoming file below the configured conflict root while retaining the normal media/date/camera hierarchy.
Skip	Keep both source and existing destination unchanged; record the decision.
Ask	Manual imports show a decision dialog; the choice can apply to the remaining session.

Conflict review

Preserved conflicts are queued in Conflict review. SQL-backed search and fixed 200-record pages keep very large histories bounded. Select one row for side-by-side paths, sizes, modification times, and supported image previews. Multi-select routine groups to mark their review status together; this status change never modifies either media file. RAW or video formats without a preview still show details and can be opened externally.

Background scans do not interrupt

Unattended scans use saved conflict, duplicate, space, and error policies. Only manual imports can pause for an in-the-moment decision.

10. Transfer records and multiple computers

Each transfer session receives its own JSON Lines record and, when cryptographic verification is used, a separate checksum file. Session names can include date, card, computer, session, instance, library, card ID, and algorithm tokens. Library metadata and application-owned records use the canonical .photocard-organizer folder.

```
CARD_ROOT/.photocard/transfers/2026/2026-07/  
2026-07-12_14-30-05_R5-Card_Studio-PC_a1b2c3d4.jsonl  
2026-07-12_14-30-05_R5-Card_Studio-PC_a1b2c3d4.sha256
```

Matching local records

```
DESTINATION/.photocard-organizer/transfer-records/CARD_ID/
```

The destination also stores a local SQLite manifest for already-imported source lookup, pending-transfer recovery, Digest Inbox item/run state, same-name conflict review, hub receipts, and cached place names. It is not a whole-library content-deduplication engine.

Cross-computer use

The card identity and portable session records allow another configured computer to recognize the same card and determine which source items were already handled. Retained client profiles control local preferences while the stable card ID links the records.

Do not manually edit active session files

A malformed or unwritable required record blocks source deletion. Preserve identity and history folders when reformatting or retiring a card if the audit history is still needed.

Identity and session records remain uncompressed by default. They are generally tiny beside camera media, directly readable during recovery, and safer to synchronize between computers as separate completed files.

11. Travel sync and shared transfer hubs

Travel sync provides two copy-only ways to reconcile a laptop or removable library with the main desktop library. Use the Laptop libraries tab for a directly reachable source and Shared hubs for USB, SMB/NAS, or locally synchronized cloud-folder transport.

Method	Best use	Behavior
Retained travel source	A laptop share, attached travel drive, or USB library	Scan that source directly and retain its stable profile so later runs import only new work.
Publish/catch hub	USB shuttle drive, SMB/NAS share, or locally synchronized cloud folder	A producer publishes verified sessions to its channel; a consumer catches new sessions and records digestion receipts.

USB drive workflow

1

Configure the laptop

Add a hub on the USB drive with role Publish and a unique producer channel, such as Field-Laptop. A card import can copy to this hub as a replica, or Publish now can backfill media imported while the drive was absent.

2

Wait for completion

Confirm the publish progress and session record finish before using the operating system's safe-eject command. Source and laptop-library files are never deleted by hub publication.

3

Configure the desktop

Attach the USB drive, add the same hub folder with role Catch, and select Catch new sessions. The desktop applies its own organization rules to the incoming producer channel.

4

Confirm digestion

After the desktop manifest records the import, the app writes matching local and shared receipts. A repeated catch should import zero new files.

Paths can change

If Windows assigns a different USB drive letter, or Linux mounts the drive at a different path, edit the saved hub folder before running it. The producer channel and recorded sessions remain unchanged.

Network and cloud folders

For SMB/NAS, authentication and reconnect behavior are handled by the operating system. For Google Drive or another cloud service, choose a normal locally synchronized folder and make its files available offline. Version 0.7.1 does not request cloud API credentials, and reported local free space may not reflect remote quota.

Use one role per client for a given hub and a distinct producer channel for every publishing laptop or tablet. This prevents circular publication and keeps receipts attributable.

12. Export captures for editing

Library export scans the master library without modifying it and builds capture sets from files with the same stem and corresponding organized path. Configured media partitions such as Photos, RAW, and Sidecars are normalized during matching, so one exposure can travel together even when its files live under separate media-root folders.

1**Scan the master library**

Choose the configured library and scan it. Internal manifest and transfer-record folders are excluded.

2**Review detected sets**

Adjust the bracket/burst and interval thresholds, then review camera, capture time, rating, media types, and group labels.

3**Select work**

Select one or more captures or expand a detected group. Optional group subfolders keep bracketed and interval sequences together.

4**Export**

Choose a separate editing folder and review the confirmation, including group folders, conflict suffix, and free-space reserve. Export is always copy-only, uses SHA-256 verification, reuses exact existing files, preserves different-content filename collisions with a suffix, and writes a JSON Lines record under `.photocard-organizer/export-sessions`.

Grouping is a review aid

Bracket and interval detection is based on timestamps, folder, and compatible camera labels. Review the selected rows before export; the app does not infer creative intent or alter the master library.

The editing folder cannot be inside the master library or contain it. The configured destination free-percent and free-GB reserves also apply to editing exports. If a source changes while it is being copied, the issue is recorded and no partial destination is committed.

13. Tray, monitoring, and settings portability

Closing the window hides the application when tray support is available. The tray menu can restore the window, scan now, pause or resume monitoring, and quit. Copy cards and enabled copy-only Digest Inboxes can be handled automatically; Move sources wait for an explicit manual confirmation.

Portable client settings

Export settings creates a JSON file containing organization, named-library definitions, safety, media, card-profile, backup, travel/hub, Digest Inbox, and history definitions. Machine-specific library, card, backup, travel, hub, digest, fallback, and local-log paths are removed. Named libraries, travel sources, hubs, and Digest Inboxes arrive without another computer's local path; importing over the same stable ID retains that client's existing path and enabled state.

1**Export**

Use Export settings from the footer and store the JSON file securely.

2**Install on the other computer**

Complete installation and choose local destination and log paths.

3**Import**

Use Import settings, review the merge confirmation, and then map retained card or backup roots as needed.

Online place names

Online GPS-to-place lookup is off by default. When enabled, coordinates are sent to the configured provider. Nominatim requests are rate-limited and cached locally. Lookup failure never blocks transfer; the folder rule falls back to coordinates or Unknown location.

14. Troubleshooting

Symptom	What to check
Windows shows an unknown publisher	The private release is currently unsigned. Verify the installer filename and SHA-256 checksum before choosing Run anyway.
Installer reports the app is running	Close the main window and quit from the tray icon, then continue. The installer uses the application mutex to prevent files from changing underneath a running transfer.
Application opens instead of installer	PhotoCardOrganizer.exe is the installed application launcher. Run the separately downloaded PhotoCardOrganizer-Installer-version.exe for install, repair, upgrade, or maintenance uninstall.
Structure preview reaches its limit	The 10,000-file limit applies only to organization analysis. Review the proposed mapping; the confirmed import still scans the complete selected source scope.
Installation verification failed	Run the same Installer file again to repair the package. Existing settings and card profiles are stored separately and remain in place.
Card is not detected	Confirm the card root contains the configured identity folder and identity filename; refresh cards; check the retained root; reconnect the reader.
No files were imported	Check enabled media classes and extensions, source folders, recursion, settle time, transfer history, and Activity messages.
Move kept the source	This is a safety result. Review checksum, required backup, portable history, local history, destination space, and permission errors.
Destination is unavailable	Reconnect the drive, choose an alternate destination during a manual import, or configure fallback roots.
USB hub is offline	Reconnect it and confirm the saved hub folder. If the drive letter or mount point changed, edit the profile before Publish or Catch.
Hub catch repeats files	Confirm both clients use stable producer/consumer identities and do not delete the hub session records or local manifest. Review receipt status.
Digest Inbox repeats a file	Confirm the profile ID and local manifest were retained and the source path, size, or modification time did not change. A changed source is intentionally new work.
Digest move kept the source	Review the per-file failed state, Activity, checksum, required backup, required record, source-change, and destination-space results. Keeping the source is the safe outcome.
A conflict was preserved	Open Conflict review. Search by filename, compare both files, and use their external-open actions. Multi-select only records you have actually reviewed.
The in-app manual is unavailable	Repair the installed package or rebuild the release so the PDF version matches the application version exactly.
Tray icon is absent on Linux	Verify StatusNotifierItem/AppIndicator support. GNOME may need an AppIndicator extension. The window remains usable without tray support.
Scrolling appears inactive	Place the pointer over the form area. Lists, tables, and text regions intentionally handle their own wheel events.
An import action asks to save first	Save settings is highlighted because visible controls differ from the saved configuration. Save before normal processing, or use the reviewed Import or merge action and its Save settings + Import button.

Safe response to an unfamiliar error

Choose Skip or Stop rather than forcing continuation. Source media is retained when transfer integrity is uncertain. Review Activity and the session records before retrying.

15. Command reference

```
python app.py                Open the desktop application
python app.py --service       Start hidden in the tray
python app.py --scan-once --dry-run  Preview connected-card work
python app.py --scan-once     Import copy cards once
python app.py --scan-once --confirm-move
python app.py --import-folder D:\Incoming --import-name "Travel"
python app.py --import-folder /mnt/incoming --no-subfolders
python app.py --digest-inbox legacy-drop
python app.py --digest-all
python app.py --digest-inbox disposable-move --confirm-move
python app.py --export-settings client-settings.json
python app.py --import-settings client-settings.json
python app.py --install-autostart
python app.py --init-config
python app.py --version
```

For a Debian installation, replace **python app.py** with **photo-card-organizer**. For an AppImage, use its path. All command-line arguments are forwarded to the bundled executable.

Create a card identity from the command line

```
python app.py --create-identity E:\ --card-name "Canon R5 Card A" --card-id canon-r5-a
```

Use **--digest-inbox PROFILE_ID** more than once to run selected saved profiles, or **--digest-all** for every enabled profile. Move operations from the command line require the explicit **--confirm-move** flag. Without it, destructive work remains blocked.

Validate the release

```
python -m unittest discover -s tests -v
```

Version 0.7.1 includes 120 focused automated checks for named libraries, versioned metadata migration, organization, bracket confidence and I/O, folder recursion, retained profiles, verified moves, Digest Inbox repeat safety and background polling, local and portable records, replicas and transfer hubs, travel-source reconciliation, grouped editing exports, retries, large conflict paging/search/bulk review, portable settings, packaging/icon contracts, UI workflows, space refusal, source mutation, destination races, timestamps, and single-instance activation.

Release history

The complete cumulative CHANGELOG.md is included with every packaged release and opens from Help & about.

Version	Released	Highlights
0.7.1	2026-07-31	Simplified Libraries and Import or merge workflows, clearer metadata actions, destination carry-over, and focused progressive disclosure.
0.7.0	2026-07-28	Named libraries, schema-5 and library metadata migration, named import routes, Month and conditional long-exposure folders, saved-settings enforcement, and persistent progress.
0.6.1	2026-07-27	Large/deep library analysis clarity, twelve editable levels, bounded-result transparency, and clearly named Windows maintenance.
0.6.0	2026-07-27	Guided existing-library import, explicit structure analysis, focused Travel tabs, in-app changelog, and clearer disabled actions.
0.5.0	2026-07-26	Digest Inboxes, scalable conflict review, Help/manual/changelog access, and high-resolution taskbar/tray icons.
0.4.0	2026-07-26	Travel libraries, shared USB/SMB/cloud-folder hubs, digestion receipts, grouped editing exports, and consolidated maintenance.
0.3.0	2026-07-18	Upgradeable Windows installer, repair/uninstall flow, Linux packages and CLI, schema migration, and versioned PDF packaging.
0.2.0	2026-07-15	PySide6 desktop/tray UI, multi-card queue, existing-library import, profiles, replicas, conflicts, and workflow polish.
0.1.0	2026-07-15	First working camera-card import release preserved as a separate snapshot.

Quick operating checklist

Before import	After import
Destination and required backups are connected	Progress completed and Activity has no unresolved error
Correct card or folder source is selected	Representative JPEG, RAW, video, and sidecar files open
Copy is selected for a new workflow	Folder names match date, camera, location, and rating expectations
Enabled extensions match the camera	Required backup copies and transfer records exist
Digest Inbox is separate and Copy is selected	Per-file queue is processed and a repeat imports nothing
USB/network hub path and role are correct	Publish/catch receipts exist and a repeated catch imports nothing
Free-space reserves leave adequate headroom	Only then consider enabling Move for later sessions

Recommended first session

Onboard one card, leave Copy selected, use Date then camera, enable only the media classes the camera writes, and import a small test shoot. Inspect primary and backup results before unattended use.

Release: Photo Card Organizer 0.7.1

This guide applies to Photo Card Organizer 0.7.1. Configuration and transfer-record files are plain JSON or JSON Lines; the local manifest is SQLite. Imported media is never intentionally overwritten.

Programmers / designers

The Meat Popsicle - product direction, design judgment, field testing, and possession of the cameras.
Codex, Latest Robot Overlord - programming, systems design, documentation, and strictly limited authority over folder names.