Quick start for LaTeXing with the IEEEtran class for IEEE Computer Society Conferences

First Author, Second Author
University of Examples, Germany
{lastname}@example.org

Third Author
School of Electrical and
Computer Examples
Georgia Institute of Examples
Atlanta, Georgia 30332–0250
http://www.example.org

***Abstract*—Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.**

I. Introduction

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate met[image_ref id="1" box="0.605,0.353,0.643,0.380" /]u enim. Vestibulum pellentesque felis eu massa.TODO!

The remainder of the paper starts with a presentation of related work (Section II). It is followed by a presentation of hints on LaTeX (Section IV). The paper closes with a conclusion and an outlook on future work (Section V).

II. Related Work

Winery [1] is a graphical modeling tool. The whole idea of TOSCA is explained by Binz et al. [2].

To search for related work, ScienceOS[1] can be used; it stores data in the EU and backs its answers with citations, which you still have to read and check yourself. Writing hints for student theses are given in the open-access book *Student Thesis Projects*[2]. More hints are given in *Writing for Computer Science*[3].

III. Writing in Markdown

This section uses plain Markdown, not LaTeX. Its source is the file `content-markdown.md`, which the main file includes with the `markdownInput` command of the `markdown` package[4]. This needs LuaLaTeX. Text can be *emphasized* or **bold**, and a citation looks like this [3]. Section IV-O shows more Markdown.

IV. LaTeX Hints

This section contains hints on writing LaTeX. It focuses on minimal examples, which can be directly adapted to the content

[1] https://www.scienceos.ai/
[2] https://vdf.ch/product/student-thesis-projects-en.html
[3] https://doi.org/10.1007/978-1-4471-6639-9
[4] https://ctan.org/pkg/markdown

A. *Handling of paragraphs*

One sentence per line. This rule is important for the usage of version control systems. A new line is generated with a blank line. As you would do in Word: New paragraphs are generated by pressing enter. In LaTeX, this does not lead to a new paragraph as LaTeX joins subsequent lines. To start a new paragraph, press enter twice. This leads to an empty line. In word, there is the functionality to press shift and enter. This leads to a hard line break. The text starts at the beginning of a new line. In LaTeX, you can do that by using two backslashes (\\).
Running text seldom needs a hard line break.

Please do *not* use two backslashes for new paragraphs. For instance, this sentence belongs to the same paragraph, whereas the last one started a new one. Andrew Stacey gives a long motivation for that in the section "Line Wrapping" of his *Document Revision System*[5].

Corresponding LaTeX code of `paper.tex`

```
747 One sentence per line.
748 This rule is important for the usage of
    ↪ version control systems.
749 A new line is generated with a blank
    ↪ line.
750 As you would do in Word:
751 New paragraphs are generated by pressing
    ↪ enter.
752 In LaTeX, this does not lead to a new
    ↪ paragraph as LaTeX joins subsequent
    ↪ lines.
753 To start a new paragraph, press enter
    ↪ twice.
754 This leads to an empty line.
755 In word, there is the functionality to
    ↪ press shift and enter.
756 This leads to a hard line break.
757 The text starts at the beginning of a new
    ↪ line.
758 In LaTeX, you can do that by using two
    ↪ backslashes
    ↪ (\textbackslash\textbackslash).
759 \\
760 Running text seldom needs a hard line
    ↪ break.
761
762 Please do \textit{not} use two
    ↪ backslashes for new paragraphs.
763 For instance, this sentence belongs to
    ↪ the same paragraph, whereas the last
    ↪ one started a new one.
764 Andrew Stacey gives a long motivation for
    ↪ that in the section \enquote{Line
    ↪ Wrapping} of his \href{https://
    ↪ loopspace.mathforge.org/
    ↪ HowDidIDoThat/TeX/VCS/#section.3}{
    ↪ \emph{Document Revision
    ↪ System}}\footnote{\url{https://
    ↪ loopspace.mathforge.org/
    ↪ HowDidIDoThat/TeX/VCS/}}.
```

Once the text is final, single paragraphs can be polished. If the last line of a paragraph holds only a word or two, or is nearly full, let TeX set the paragraph one line shorter or longer: write `\looseness=-1` (or `=1`) as the first thing in that paragraph. TeX resets `\looseness` at the end of every paragraph, so only that one paragraph is affected. With LuaLaTeX, a lone short word as the last line is avoided automatically (package impnattypo).

[5] https://loopspace.mathforge.org/HowDidIDoThat/TeX/VCS/

B. *Notes separated from the text*

The package mindflow enables writing down notes and annotations in a way so that they are separated from the main text.

This is a small note.

Corresponding LaTeX code of `paper.tex`

```
777 \begin{mindflow}
778 This is a small note.
779 \end{mindflow}
```

C. *Handling TODOs*

Marked text.

Corresponding LaTeX code of `paper.tex`

```
785 \textmarker{Marked text.}
```

With `\textmarker`, only the text color is changed, since this also works well for individual words.
Marked text.

Corresponding LaTeX code of `paper.tex`

```
791 \textcomment{Marked text.}{A comment on
    ↪ it.}
```

Manual marking for text that has been changed since the last version.

Corresponding LaTeX code of `paper.tex`

```
795 \modified{Manual marking for text that has
    ↪ been changed since the last version.}
```

This is some text. Changed text.

Corresponding LaTeX code of `paper.tex`

```
799 This is some text.
800 \change{FL1: text adjusted}{Changed
    ↪ text}.
```

Here is a comment.

Corresponding LaTeX code of `paper.tex`

```
804 Here is a comment\sidecomment{Comment}.
```

TODO!

Corresponding LaTeX code of paper.tex

```
\todo{A lot of text still needs to be produced here}
```

Several authors can mark their edits and comments with the phfcc package; the initials of the author appear once per page in the margin. Define one command per author in the preamble (`\phfMakeCommentingCommand`); `\phfDisableCommentingCommands` hides everything for the final version.

Quantum mechanics developed quickly thanks to the works of Schrödinger, Heisenberg, and Dirac, who drew inspiration FA from earlier ideas by Planck and Einstein [Einstein must not be missing here.] ~~This sentence is to be removed.~~ **!!! This is important. !!!**

Corresponding LaTeX code of paper.tex

```
Quantum mechanics developed quickly thanks to the works of Schrödinger, Heisenberg, and Dirac, who drew inspiration from earlier ideas by Planck \FA{and Einstein} \FA[Einstein must not be missing here.] \FA*{This sentence is to be removed.} \FA!{This is important.}
```

D. Hyphenation

LaTeX automatically hyphenates words. When using microtype, there should be fewer hyphenations than in other settings. You might still need to tweak the hyphenation. Here are some hints:

In case you write “application-specific”, then the word will only be hyphenated at the dash. You can also insert `\allowbreak{}` into the word, as in application-specific, but this is much more effort.

You can now write words containing hyphens which are hyphenated at other places in the word. For that, write `"=` instead of −, as in application”=specific. This is enabled by an additional configuration of the babel package.

Corresponding LaTeX code of paper.tex

```
In case you write \enquote{application-specific}, then the word will only be hyphenated at the dash.
You can also insert \verb1\allowbreak{}1 into the word, as in applica\allowbreak{}tion-specific, but this is much more effort.

You can now write words containing hyphens which are hyphenated at other places in the word.
For that, write \verb1"=1 instead of \verb1-1, as in application"=specific.
This is enabled by an additional configuration of the babel package.
```

Table I
EXAMPLE TABLE FOR ZCREF DEMO

Heading1	Heading2
One	Two
Three	Four

E. Typesetting Units

Numbers can be written plain text (such as 100), by using the siunitx package as follows: $100\,\frac{\mathrm{km}}{\mathrm{h}}$, or by using plain LaTeX (and math mode): $100\,\frac{km}{h}$.

Corresponding LaTeX code of paper.tex

```
Numbers can be written plain text (such as 100), by using the \href{https://ctan.org/pkg/siunitx}{siunitx} package as follows:
\SI{100}{\km\per\hour},
or by using plain \LaTeX{} (and math mode):
$100 \frac{\mathit{km}}{h}$.
```

$5\,\%$ of $10\,\mathrm{kg}$

Corresponding LaTeX code of paper.tex

```
\SI{5}{\percent} of \SI{10}{kg}
```

Numbers are automatically grouped: $123\,456$.

Corresponding LaTeX code of paper.tex

```
Numbers are automatically grouped: \num{123456}.
```

F. Surrounding Text by Quotes

Please use the “enquote command” to quote something. Quoting with “quote” or “quote” also works.

Corresponding LaTeX code of paper.tex

```
Please use the \enquote{enquote command} to quote something.
Quoting with "`quote"' or ``quote'' also works.

```

G. Zref-clever examples

Demonstration of zref-clever: Zcref (short for zcref[S]) at the beginning of a sentence, zcref in all other cases.

Fig. 1 shows a simple fact, although Fig. 1 could also show something else.

Table I shows a simple fact, although Table I could also show something else.

Section IV-G shows a simple fact, although Section IV-G could also show something else.




Fig. 1. Example figure for zcref demo




Fig. 2. Simple Figure. Based on Scharrer [3].

Corresponding LaTeX code of `paper.tex`

```
888  \Zcref{fig:ex:cref} shows a simple fact,
     ↪  although \zcref{fig:ex:cref} could
     ↪  also show something else.
889
890  \Zcref{tab:ex:cref} shows a simple fact,
     ↪  although \zcref{tab:ex:cref} could
     ↪  also show something else.
891
892  \Zcref{sec:ex:cref} shows a simple fact,
     ↪  although \zcref{sec:ex:cref} could
     ↪  also show something else.
```

H. Figures

Fig. 2 shows something interesting.

Corresponding LaTeX code of `paper.tex`

```
898  \Zcref{fig:label} shows something
     ↪  interesting.
899
900  \begin{figure}
901    \centering
902    \includegraphics[width=.8\linewidth]{
       ↪  example-image-golden}
903    \caption[Simple Figure]{
904      Simple Figure.
905      Based on \citet{mwe}.
906    }
907    \label{fig:label}
908  \end{figure}
```



Fig. 3. Ulm Minster. Photo: wkrauth, CC0, via Wikimedia Commons.

Photos in JPEG or PNG format are included the same way, as shown in Fig. 3.

Corresponding LaTeX code of `paper.tex`

```
914  \begin{figure}
915    \centering
916    \includegraphics[width=.5\linewidth]{
       ↪  figures/ulm-minster.jpg}
917    \caption{Ulm Minster. Photo: wkrauth,
       ↪  CC0, via Wikimedia Commons.}
918    \label{fig:jpg}
919  \end{figure}
```

A figure spans multiple columns when using `\begin{figure*}`. See Fig. 4 as an example.

Corresponding LaTeX code of `paper.tex`

```
926  \begin{figure*}
927    \centering
928    % note that \textwidth is used instead
       ↪  of \linewidth
929    % This ensures that the graphics width
       ↪  is 60% of the "page" (text block),
       ↪  and not just 60% of the current
       ↪  text column
930    % See https://tex.stackexchange.com/a/
       ↪  17085/9075 for details
931    \includegraphics[width=.6\textwidth]{
       ↪  example-image-16x9}
932    \caption{16x9 Figure}
933    \label{fig:16x9}
934  \end{figure*}
```

I. Sub Figures

An example of two sub figures is shown in Fig. 5.

Corresponding LaTeX code of `paper.tex`

```
943  \begin{figure*}[!t]
944    \centering
```





Fig. 4. 16x9 Figure



(a) Case I (b) Case II

Fig. 5. Example figure with two sub figures.

```
\subfloat[Case I]{\includegraphics[width=.4\linewidth]{example-image-a}%
  \label{fig:first_case}}
\hfil
\subfloat[Case II]{\includegraphics[width=.4\linewidth]{example-image-b}%
  \label{fig:second_case}}
\caption{Example figure with two sub figures.}
\label{fig:two_sub_figures}
\end{figure*}
```


Note that often IEEE papers with subfigures do not employ subfigure captions (using the optional argument to `\subfloat[]`), but instead will reference/describe all of them (a), (b), etc., within the main caption. Be aware that for the subfig package to generate the (a), (b), etc., subfigure labels, the optional argument to `\subfloat` must be present. If a subcaption is not desired, leave its contents blank, e.g., `\subfloat[]`. An example is shown in Fig. 6.

Corresponding LaTeX code of `paper.tex`

```
\begin{figure*}[!t]
  \centering
  \subfloat[]{\includegraphics[width=.4\linewidth]{example-image-a}%
    \label{fig:first_case_ieee}}
  \hfil
  \subfloat[]{\includegraphics[width=.4\linewidth]{example-image-b}%
    \label{fig:second_case_ieee}}
  \caption{Example figure with two sub figures. IEEE style. (a) The first case. (b) The second case.}
  \label{fig:two_sub_figures_ieee}
\end{figure*}
```

J. *Figures with tikz*

The tikz package creates graphics programmatically. This package generates grids and other regular structures.



(a) (b)

Fig. 6. Example figure with two sub figures. IEEE style. (a) The first case. (b) The second case.




Fig. 7. A regular grid generated easily with two for loops.

Corresponding LaTeX code of `paper.tex`

```
\begin{figure}[ht]
  \centering
  \begin{tikzpicture}
    \draw(0,0) rectangle (4,4);
    \foreach \x in
     ↪ {0.5,1,1.5,2,2.5,3,3.5}
    \foreach \y in
     ↪ {0.5,1,1.5,2,2.5,3,3.5}
    \draw(\x,\y) circle (1pt);
  \end{tikzpicture}
  \caption{A regular grid generated
   ↪ easily with two for
   ↪ loops.}\label{fig:tikz_example}
\end{figure}
```

K. Plots with pgfplots

The pgfplots package plots functions directly in LaTeX, similar to MATLAB or gnuplot. Some visual examples are available in the package documentation[6].

Corresponding LaTeX code of `paper.tex`

```
\begin{figure}[ht]
  \centering
  \begin{tikzpicture}
```

[6]http://texdoc.net/pkg/pgfplots




Fig. 8. Plot of $\sin(x)$ directly inside the figure environment with pgfplots.

```
    \begin{axis}[xlabel=$x$,
     ↪ ylabel=$\sin(x)$]
      \addplot {sin(deg(x))};  % Plot the
       ↪ sine function
    \end{axis}
  \end{tikzpicture}
  \caption{Plot of $\sin(x)$ directly
   ↪ inside the figure environment with
   ↪ pgfplots.}
  \label{fig:pgfplots_example}
\end{figure}
```

Coordinates can also be given explicitly instead of as a function:

Corresponding LaTeX code of `paper.tex`

```
\begin{figure}[ht]
  \centering
  \begin{tikzpicture}
    \begin{axis}[xlabel=$x$, ylabel=$y$]
```




Fig. 9. Explicit coordinates plotted with pgfplots.

Table II
SIMPLE TABLE

Heading1	Heading2
One	Two
Three	Four

```
1019        \addplot coordinates {(0,0) (1,1)
             ↪  (2,4) (3,9)};  % Plot explicit
             ↪  coordinates
1020      \end{axis}
1021    \end{tikzpicture}
1022    \caption{Explicit coordinates plotted
         ↪  with pgfplots.}
1023    \label{fig:pgfplots_coords}
1024  \end{figure}
```

L. Tables

Corresponding LaTeX code of `paper.tex`

```
1030  \begin{table}
1031    \caption{Simple Table}
1032    \label{tab:simple}
1033    \centering
1034    \begin{tabular}{ll}
1035      \toprule
1036      Heading1 & Heading2 \\
1037      \midrule
1038      One      & Two      \\
1039      Three    & Four     \\
1040      \bottomrule
1041    \end{tabular}
1042  \end{table}
```

A table caption goes above the table (`\caption` before the `tabular`), a figure caption below the figure.

Rows and cells can be colored with `\rowcolor` and `\cellcolor` from the colortbl package, which xcolor loads with its option `table`.

Table III
TABLE WITH COLORED CELLS

Test	Result
A	pass
B	fail

Table IV
TABLE WITH A FOOTNOTE

Heading1	Heading2[7]
One	Two

Corresponding LaTeX code of `paper.tex`

```
1050  \begin{table}
1051    \caption{Table with colored cells}
1052    \label{tab:colored}
1053    \centering
1054    \begin{tabular}{ll}
1055      \toprule
1056      \rowcolor{gray!20}
1057      Test & Result                    \\
1058      \midrule
1059      A    & \cellcolor{green!20}pass \\
1060      B    & \cellcolor{red!20}fail   \\
1061      \bottomrule
1062    \end{tabular}
1063  \end{table}
```

A `\footnote` inside a floating table is lost. Use `\tablefootnote` from the tablefootnote package instead: it is set as a normal footnote at the bottom of the page. If the notes should appear directly below the table instead (common in journals), use the threeparttable package.

Corresponding LaTeX code of `paper.tex`

```
1071  \begin{table}
1072    \caption{Table with a footnote}
1073    \label{tab:footnote}
1074    \centering
1075    \begin{tabular}{ll}
1076      \toprule
1077      Heading1 & Heading2\tablefootnote{A
           ↪  footnote inside a table.} \\
1078      \midrule
1079      One      & Two
           ↪  \\
1080      \bottomrule
1081    \end{tabular}
1082  \end{table}
```

Corresponding LaTeX code of `paper.tex`

```
1086  % Adapted from https://
       ↪  tex.stackexchange.com/a/468994/9075
1087  \begin{table}
1088    \caption{Table with diagonal line}
1089    \label{tab:diag}
```

[7] A footnote inside a table.

Table V
TABLE WITH DIAGONAL LINE

Row \ Column	A	B
1	x	y

```
\begin{center}
  \begin{tabular}{|l|c|c|}
    \hline
    \diagbox{Row}{Column} & A & B \\
    \hline
    1                     & x & y \\
    \hline
  \end{tabular}
\end{center}
\end{table}
```

M. Source Code

The minted package highlights listings properly. It uses the pygments library, which in turn requires Python.

Listing 1 shows source code written in XML. Line 2 contains a comment.

```xml
<listing name="example">
  <!-- comment -->
  <content>not interesting</content>
</listing>
```

List. 1. Example XML listing using minted

Corresponding LaTeX code of `paper.tex`

```
\Zcref{lst:XML} shows source code written in XML.
\Zcref{line:comment} contains a comment.

\begin{listing}[htbp]
  \begin{minted}[linenos=true,escapeinside=||]{xml}
<listing name="example">
  <!-- comment --> |\label{line:comment}|
  <content>not interesting</content>
</listing>
\end{minted}
  \caption{Example XML listing using minted}
  \label{lst:XML}
\end{listing}
```

One can also typeset JSON as shown in Listing 2.

```json
{
  key: "value"
}
```

List. 2. Example JSON listing using minted

Corresponding LaTeX code of `paper.tex`

```
\begin{listing}[htbp]
  \begin{minted}[linenos=true,escapeinside=||]{json}
{
  key: "value"
}
\end{minted}
  \caption{Example JSON listing using minted}
  \label{lst:flJSON}
\end{listing}
```

Java is also possible as shown in Listing 3.

```java
public class Hello {
    public static void main (String[] args) {
        System.out.println("Hello World!");
    }
}
```

List. 3. Java code rendered using minted

Corresponding LaTeX code of `paper.tex`

```
\begin{listing}[htbp]
  \begin{minted}[linenos=true,escapeinside=||]{java}
public class Hello {
    public static void main (String[] args) {
        System.out.println("Hello World!");
    }
}
\end{minted}
  \caption{Java code rendered using minted}
  \label{lst:flJava}
\end{listing}
```

N. Itemization

One can list items as follows:

- Item One
- Item Two

Corresponding LaTeX code of `paper.tex`

```
\begin{itemize}
  \item Item One
  \item Item Two
\end{itemize}
```

With the package paralist, one can create itemizations with lesser spacing:

- Item One
- Item Two

Corresponding LaTeX code of `paper.tex`

```
\begin{compactitem}
  \item Item One
  \item Item Two
\end{compactitem}
```

One can enumerate items as follows:

1) Item One
2) Item Two

Corresponding LaTeX code of `paper.tex`

```
\begin{enumerate}
  \item Item One
  \item Item Two
\end{enumerate}
```

With the package paralist, one can create enumerations with lesser spacing:

1) Item One
2) Item Two

Corresponding LaTeX code of `paper.tex`

```
\begin{compactenum}
  \item Item One
  \item Item Two
\end{compactenum}
```

With paralist, one can even have all items typeset after each other and have them clean in the TeX document:

1) The first item, 2) the second item, and 3) the third item appear in one line.

Corresponding LaTeX code of `paper.tex`

```
\begin{inparaenum}
  \item The first item,
  \item the second item, and
  \item the third item appear in one
    ↪ line.
\end{inparaenum}
```

O. Writing in Markdown

If you are new to LaTeX, you can start by writing your text in Markdown using the markdown package. LaTeX then takes care of the typesetting. Markdown and LaTeX can be mixed: Table VI is written in Markdown and referenced from LaTeX. A whole section can be written in a separate Markdown file included by `\markdownInput`, as Section III shows. The markdown-latex-quickstart shows a complete document written in Markdown.

Text can be *emphasized* or **bold**, and `code` is set in a monospaced font. A citation looks like this [3], and here is a footnote.[8] Referenced footnotes work as well[9].

- first point
- second point
  - sub-point

1. firstly
2. secondly

[8]This is an inline footnote.

[9]This is a footnote defined at a different place in the text.

Right	Left	Centered
12	12	12
123	123	123

Table VI
A TABLE WRITTEN IN MARKDOWN

Table VI shows a table with caption. Its identifier `{#tbl:markdown}` is referenced by `<#tbl:markdown>`.

Corresponding LaTeX code of `paper.tex`

```
  \begin{markdown}
Text can be *emphasized* or **bold**, and
  ↪ `code` is set in a monospaced font.
A citation looks like this [@mwe], and
  ↪ here is a footnote.^[This is an
  ↪ inline footnote.]
Referenced footnotes work as
  ↪ well[^detail].

[^detail]: This is a footnote defined at a
  ↪ different place in the text.

- first point
- second point
  - sub-point

1) firstly
2) secondly

| Right | Left | Centered |
|------:|:-----|:--------:|
|    12 | 12   |    12    |
|   123 | 123  |   123    |

: A table written in Markdown
  ↪ {#tbl:markdown}

<#tbl:markdown> shows a table with
  ↪ caption.
Its identifier `{#tbl:markdown}` is
  ↪ referenced by `<#tbl:markdown>`.
\end{markdown}
```

P. Other Features

The words “workflow” and “dwarflike” can be copied from the PDF and pasted to a text file.

Corresponding LaTeX code of `paper.tex`

```
The words \enquote{workflow} and
  ↪ \enquote{dwarflike} can be copied from
  ↪ the PDF and pasted to a text file.
```

The symbol for powerset is now correct: $\wp$ and not a Weierstrass p ($\wp$).

$\wp(1, 2, 3)$

Corresponding LaTeX code of `paper.tex`

```
The symbol for powerset is now correct:
↪ $\powerset$ and not a Weierstrass p
↪ ($\wp$).

$\powerset({1,2,3})$
```

Brackets work as designed: <test> One can also input backticks in verbatim text: `` `test` ``.

Corresponding LaTeX code of `paper.tex`

```
Brackets work as designed:
<test>
One can also input backticks in verbatim
↪ text: \verb|`test`|.
```

Acronyms can be typeset in running text with `\initialism`, which sets them as small caps that blend into the surrounding lowercase text. It is the lightweight alternative to the full acronym and glossary management (`\gls`, with an automatic list of abbreviations) provided by the thesis variants: `\initialism` only typesets the acronym and does not add it to any list. The macro and the ready-made acronyms (`\OMG`, `\BPEL`, `\BPMN`, `\UML`) are defined in `commands.tex`, where you can add your own.

The UML is maintained by the OMG; related standards include BPEL and BPMN. Any acronym can be set inline with REST or HTTP.

Corresponding LaTeX code of `paper.tex`

```
The \UML is maintained by the \OMG;
↪ related standards include \BPEL and
↪ \BPMN.
Any acronym can be set inline with
↪ \initialism{REST} or
↪ \initialism{HTTP}.
```

V. Conclusion and Outlook

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Acknowledgment

Identification of funding sources and other support, and thanks to individuals and groups that assisted in the research and the preparation of the work should be included in an acknowledgment section, which comes right before the reference section in your document [4].

(2015/08/26)

References

[1] O. Kopp *et al.*, "Winery – A Modeling Tool for TOSCA-based Cloud Applications," in *Proceedings of 11th International Conference on Service-Oriented Computing (ICSOC'13)*, ser. LNCS, vol. 8274. Springer Berlin Heidelberg, 2013, pp. 700–704, doi: 10.1007/978-3-642-45005-1_64.

[2] T. Binz, G. Breiter, F. Leymann, and T. Spatzier, "Portable Cloud Services Using TOSCA," *IEEE Internet Computing*, vol. 16, no. 03, pp. 80–85, May 2012, doi: 10.1109/mic.2012.43.

[3] M. Scharrer, *The mwe Package*, 2017. [Online]. Available: http://texdoc.net/mwe

[4] B. Veytsman, "Latex class for the association for computing machinery – acknowledgement information," Aug. 2021. [Online]. Available: https://github.com/borisveytsman/acmart/blob/1704c8bf7eee92a1515ff755f5118b6a22bb1f8e/samples/samples.dtx#L709

All links were last followed on October 5, 2020.