Paper Title

Firstname Lastname und Firstname Lastname

Institute

Zusammenfassung. Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Schlüsselwörter: First keyword · Second keyword · Third keyword

1 Einleitung

Hier steht die Einleitung zu dieser Ausarbeitung. Sie soll nur als Beispiel dienen. Nun viel Erfolg bei der Arbeit!

Die Arbeit ist in folgender Weise gegliedert: Zuerst werden Grundlagen und verwandte Arbeiten vorgestellt (Abschnitt 2). It is followed by a presentation of hints on LaTeX (Abschnitt 3). Schließlich fasst Abschnitt 4 die Ergebnisse der Arbeit zusammen und stellt Anknüpfungspunkte vor.

2 Verwandte Arbeiten

Eine Beschreibung relevanter wissenschaftlicher Arbeiten mit Bezug zur eigenen Arbeit. Der Abschnitt kann je nach Kontext auch an anderer Stelle stehen.

Winery [2] is a graphical modeling tool. The whole idea of TOSCA is explained by Binz et al. [1].

Für die Suche nach verwandten Arbeiten eignet sich ScienceOS[1]; es speichert Daten in der EU und belegt seine Antworten mit Quellen, die man trotzdem selbst lesen und prüfen muss. Schreibhinweise für studentische Arbeiten gibt das Open-Access-Buch *Student Thesis Projects*[2]. Weitere Hinweise gibt *Writing for Computer Science*[3].

[1] https://www.scienceos.ai/
[2] https://vdf.ch/product/student-thesis-projects-en.html
[3] https://doi.org/10.1007/978-1-4471-6639-9

3 LaTeX Hinweise

Hier sollen allgemeine LaTeX-Hinweise gegeben werden, damit man Minimalbeispiele vorliegen hat, um sofort loszulegen.

3.1 Trennung von Absätzen

Pro Satz eine neue Zeile. Das ist wichtig, um sauber versionieren zu können. In LaTeX werden Absätze durch eine Leerzeile getrennt. Analogie zu Word: Bei Word werden neue Absätze durch einmal Eingabetaste herbeigeführt. Dies führt bei LaTeX jedoch nicht zu einem neuen Absatz, da LaTeX direkt aufeinanderfolgende Zeilen zu einer Zeile zusammenfügt. Mächte man nun einen Absatz haben, muss man zweimal die Eingabetaste drücken. Dies führt zu einer leeren Zeile. In Word gibt es die Funktion Großschreibetaste und Eingabetaste gleichzeitig. Wenn man dies drückt, wird einer harter Umbruch erzwungen. Der Text fängt am Anfang der neuen Zeile an. In LaTeX erreicht man dies durch Doppelbackslashes (\\) erzeugt.
Dies verwendet man quasi nie.

Folglich werden neue Absätze insbesondere *nicht* durch Doppelbackslashes erzeugt. Beispielsweise begann der letzte Satz in einem neuen Absatz. Andrew Stacey begründet dies ausführlich im Abschnitt „Line Wrapping“ seines *Document Revision System*[4].

[4] `https://loopspace.mathforge.org/HowDidIDoThat/TeX/VCS/`

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
699 Pro Satz eine neue Zeile.
700 Das ist wichtig, um sauber versionieren zu können.
701 In LaTeX werden Absätze durch eine Leerzeile getrennt.
702 Analogie zu Word: Bei Word werden neue Absätze durch einmal
    ↪ Eingabetaste herbeigeführt.
703 Dies führt bei LaTeX jedoch nicht zu einem neuen Absatz, da
    ↪ LaTeX direkt aufeinanderfolgende Zeilen zu einer Zeile
    ↪ zusammenfügt.
704 Mächte man nun einen Absatz haben, muss man zweimal die
    ↪ Eingabetaste drücken.
705 Dies führt zu einer leeren Zeile.
706 In Word gibt es die Funktion Großschreibetaste und
    ↪ Eingabetaste gleichzeitig.
707 Wenn man dies drückt, wird einer harter Umbruch erzwungen.
708 Der Text fängt am Anfang der neuen Zeile an.
709 In LaTeX erreicht man dies durch Doppelbackslashes
    ↪ (\textbackslash\textbackslash) erzeugt.
710 \\
711 Dies verwendet man quasi nie.
712
713 Folglich werden neue Absätze insbesondere \emph{nicht} durch
    ↪ Doppelbackslashes erzeugt.
714 Beispielsweise begann der letzte Satz in einem neuen Absatz.
715 Andrew Stacey begründet dies ausführlich im Abschnitt
    ↪ \enquote{Line Wrapping} seines
    ↪ \href{https://loopspace.mathforge.org/HowDidIDoThat/TeX/
    ↪ VCS/#section.3}{\emph{Document Revision
    ↪ System}}\footnote{\url{https://loopspace.mathforge.org/
    ↪ HowDidIDoThat/TeX/VCS/}}.
```

3.2 Notes separated from the text

The package mindflow enables writing down notes and annotations in a way so that they are separated from the main text.

This is a small note.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
724 \begin{mindflow}
725 This is a small note.
726 \end{mindflow}
```

3.3 Umgang mit TODOs

Markierter Text.

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
732 \textmarker{Markierter Text.}
```

Bei \textmarker wird nur die Textfarbe geändert, da dies auch bei einigen Worten gut funktioniert.

Markierter Text.

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
738 \textcomment{Markierter Text.}{Kommentar dazu.}
```

Manuelle Markierung für Text, der seit der letzten Version geändert wurde.

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
742 \modified{Manuelle Markierung für Text, der seit der letzten
    ↪ Version geändert wurde.}
```

Das ist ein Text. Geänderter Text.

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
746 Das ist ein Text.
747 \change{FL1: Text angepasst}{Geänderter Text}.
```

Hier nur ein Kommentar.

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
751 Hier nur ein Kommentar\sidecomment{Kommentar}.
```

TODO!

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
755 \todo{Hier muss noch kräftig Text produziert werden}
```

3.4 Hyphenation

LaTeX automatically hyphenates words. When using microtype, there should be fewer hyphenations than in other settings. You might still need to tweak the hyphenation. Here are some hints:

In case you write „application-specific“, then the word will only be hyphenated at the dash. You can also insert `\allowbreak{}` into the word, as in applica tion-specific, but this is much more effort.

You can now write words containing hyphens which are hyphenated at other places in the word. For that, write `"=` instead of `-`, as in application-specific. This is enabled by an additional configuration of the babel package.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
766 In case you write \enquote{application-specific}, then the
    ↪ word will only be hyphenated at the dash.
767 You can also insert \verb1\allowbreak{}1 into the word, as in
    ↪ applica\allowbreak{}tion-specific, but this is much more
    ↪ effort.
768
769 You can now write words containing hyphens which are
    ↪ hyphenated at other places in the word.
770 For that, write \verb1"=1 instead of \verb1-1, as in
    ↪ application"=specific.
771 This is enabled by an additional configuration of the babel
    ↪ package.
```

3.5 Typesetting Units

Numbers can be written plain text (such as 100), by using the siunitx package as follows: 100 $\frac{\mathrm{km}}{\mathrm{h}}$, or by using plain LaTeX (and math mode): 100 $\frac{km}{h}$.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
777 Numbers can be written plain text (such as 100), by using the
    ↪ \href{https://ctan.org/pkg/siunitx}{siunitx} package as
    ↪ follows:
778 \SI{100}{\km\per\hour},
779 or by using plain \LaTeX{} (and math mode):
780 $100 \frac{\mathit{km}}{h}$.
```

5 % of 10 kg

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
784 \SI{5}{\percent} of \SI{10}{kg}
```

Numbers are automatically grouped: 123 456.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
788 Numbers are automatically grouped: \num{123456}.
```

3.6 Surrounding Text by Quotes

Please use the „enquote command“ to quote something. Quoting with „quote“ or “quote” also works.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
794 Please use the \enquote{enquote command} to quote something.
795 Quoting with "`quote"' or ``quote'' also works.
796
```

3.7 Zref-clever examples

Demonstration of zref-clever: Zcref (short for zcref[S]) at the beginning of a sentence, zcref in all other cases.




Abb. 1: Example figure for zcref demo

Abbildung 1 shows a simple fact, although Abb. 1 could also show something else.

Tabelle 1 shows a simple fact, although Tabelle 1 could also show something else.

Heading1	Heading2
One	Two
Three	Four

Tabelle 1: Example table for zcref demo

Abschnitt 3.7 shows a simple fact, although Abschnitt 3.7 could also show something else.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
826 \Zcref{fig:ex:cref} shows a simple fact, although
    ↪ \zcref{fig:ex:cref} could also show something else.
827
828 \Zcref{tab:ex:cref} shows a simple fact, although
    ↪ \zcref{tab:ex:cref} could also show something else.
829
830 \Zcref{sec:ex:cref} shows a simple fact, although
    ↪ \zcref{sec:ex:cref} could also show something else.
```

3.8 Theorem-like Environments and Mathematics

The `llncs` class already provides the theorem-like environments `theorem`, `proposition`, `lemma`, `corollary`, `definition`, `example`, `exercise`, `note`, `problem`, `question`, `remark`, and `solution` as well as the unnumbered `proof` environment – no additional package is required.

Definition 1 (Idempotence). *An operation f is* idempotent *if $f(f(x)) = f(x)$ holds for all inputs x.*

Proposition 1. *The identity operation is idempotent.*

Lemma 1. *An idempotent operation fixes every element of its image.*

Theorem 1. *If two idempotent operations f and g commute, their composition $f \circ g$ is idempotent.*

Beweis. Since f and g commute and are idempotent,

$$(f \circ g)((f \circ g)(x)) = f(f(g(g(x)))) = f(g(x)) = (f \circ g)(x). \tag{1}$$

□

Korollar 1. *Applying $f \circ g$ a second time yields no further change, as Gleichung (1) shows.*

Beispiel 1. Trimming spaces in a string is idempotent: Lemma 1 applies to every already-trimmed string.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```latex
\begin{definition}[Idempotence]
  An operation $f$ is \emph{idempotent} if $f(f(x)) = f(x)$
   ↪ holds for all inputs $x$.
\end{definition}

\begin{proposition}
  The identity operation is idempotent.
\end{proposition}

\begin{lemma}\label{lem:fixed}
  An idempotent operation fixes every element of its image.
\end{lemma}

\begin{theorem}\label{thm:idempotent-composition}
  If two idempotent operations $f$ and $g$ commute, their
   ↪ composition $f \circ g$ is idempotent.
\end{theorem}

\begin{proof}
  Since $f$ and $g$ commute and are idempotent,
  \begin{equation}
    (f \circ g)\bigl((f \circ g)(x)\bigr) =
     ↪ f\bigl(f(g(g(x)))\bigr) = f(g(x)) = (f \circ g)(x).
    \label{eq:idempotent-composition}
  \end{equation}
  \qed
\end{proof}

\begin{corollary}
  Applying $f \circ g$ a second time yields no further change,
   ↪ as \zcref{eq:idempotent-composition} shows.
\end{corollary}

\begin{example}
  Trimming spaces in a string is idempotent: \zcref{lem:fixed}
   ↪ applies to every already-trimmed string.
\end{example}
```

3.9 Abbildungen

Abbildung 2 zeigt etwas Interessantes

Füge deine Abbildung hier ein.

Abb. 2: Bildunterschrift.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\Zcref{fig:label} zeigt etwas Interessantes

\begin{figure}
  \centering
  Füge deine Abbildung hier ein.
  \caption{Bildunterschrift.}
  \label{fig:label}
\end{figure}
```

Fotos im JPEG- oder PNG-Format werden genauso eingebunden, wie Abb. 3 zeigt.



Abb. 3: Ulmer Münster. Foto: wkrauth, CC0, via Wikimedia Commons.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
888 \begin{figure}
889   \centering
890   \includegraphics[width=.5\linewidth]{figures/ulm-minster.jpg}
891   \caption{Ulmer Münster. Foto: wkrauth, CC0, via Wikimedia
      ↪ Commons.}
892   \label{fig:jpg}
893 \end{figure}
```

One can also have pictures floating inside text:




Abb. 4: A floating figure


Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
900 \begin{floatingfigure}{.33\linewidth}
901   \includegraphics[width=.29\linewidth]{example-image-a}
902   \caption{A floating figure}
903 \end{floatingfigure}
904 \lipsum[2]
```

3.10 Sub Figures

An example of two sub figures is shown in Abb. 5.



(a) Case I **(b)** Case II

Abb. 5: Example figure with two sub figures.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
912 \begin{figure}[!b]
913   \centering
914   \subfloat[Case I]{\includegraphics[width=.4\linewidth]{
      ↪  example-image-a}%
915     \label{fig:first_case}}
916   \hfil
917   \subfloat[Case II]{\includegraphics[width=.4\linewidth]{
      ↪  example-image-b}%
918     \label{fig:second_case}}
919   \caption{Example figure with two sub figures.}
920   \label{fig:two_sub_figures}
921 \end{figure}
```

3.11 Figures with tikz

The tikz package creates graphics programmatically. This package generates grids and other regular structures.




Abb. 6: A regular grid generated easily with two for loops.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{figure}[ht]
  \centering
  \begin{tikzpicture}
    \draw(0,0) rectangle (4,4);
    \foreach \x in {0.5,1,1.5,2,2.5,3,3.5}
    \foreach \y in {0.5,1,1.5,2,2.5,3,3.5}
    \draw(\x,\y) circle (1pt);
  \end{tikzpicture}
  \caption{A regular grid generated easily with two for
   ↪  loops.}\label{fig:tikz_example}
\end{figure}
```

3.12 Plots with pgfplots

The pgfplots package plots functions directly in LaTeX, similar to MATLAB or gnuplot. Some visual examples are available in the package documentation[5].




Abb. 7: Plot of $\sin(x)$ directly inside the figure environment with pgfplots.

[5] `http://texdoc.net/pkg/pgfplots`

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
948 \begin{figure}[ht]
949   \centering
950   \begin{tikzpicture}
951     \begin{axis}[xlabel=$x$, ylabel=$\sin(x)$]
952       \addplot {sin(deg(x))};  % Plot the sine function
953     \end{axis}
954   \end{tikzpicture}
955   \caption{Plot of $\sin(x)$ directly inside the figure
      ↪  environment with pgfplots.}
956   \label{fig:pgfplots_example}
957 \end{figure}
```

Coordinates can also be given explicitly instead of as a function:




Abb. 8: Explicit coordinates plotted with pgfplots.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{figure}[ht]
  \centering
  \begin{tikzpicture}
    \begin{axis}[xlabel=$x$, ylabel=$y$]
      \addplot coordinates {(0,0) (1,1) (2,4) (3,9)};  % Plot
        ↪ explicit coordinates
    \end{axis}
  \end{tikzpicture}
  \caption{Explicit coordinates plotted with pgfplots.}
  \label{fig:pgfplots_coords}
\end{figure}
```

3.13 Tables

Tabelle 2: Simple Table

Heading1	Heading2
One	Two
Three	Four

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{table}
  \caption{Simple Table}
  \label{tab:simple}
  \centering
  \begin{tabular}{ll}
    \toprule
    Heading1 & Heading2 \\
    \midrule
    One      & Two      \\
    Three    & Four     \\
    \bottomrule
  \end{tabular}
\end{table}
```

Rows and cells can be colored with `\rowcolor` and `\cellcolor` from the colortbl package, which xcolor loads with its option `table`.

Tabelle 3: Table with colored cells

Test	Result
A	pass
B	fail

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{table}
  \caption{Table with colored cells}
  \label{tab:colored}
  \centering
  \begin{tabular}{ll}
    \toprule
    \rowcolor{gray!20}
    Test & Result                    \\
    \midrule
    A    & \cellcolor{green!20}pass \\
    B    & \cellcolor{red!20}fail   \\
    \bottomrule
  \end{tabular}
\end{table}
```

Tabelle 4: Table with diagonal line

Row \ Column	A	B
1	x	y

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
% Adapted from https://tex.stackexchange.com/a/468994/9075
\begin{table}
  \caption{Table with diagonal line}
  \label{tab:diag}
  \begin{center}
    \begin{tabular}{|l|c|c|}
      \hline
      \diagbox{Row}{Column} & A & B \\
      \hline
      1                     & x & y \\
      \hline
    \end{tabular}
  \end{center}
\end{table}
```

3.14 Tables spanning multiple pages

The longtable package typesets tables that automatically break across page boundaries. The header (`\endhead`) and footer (`\endfoot`) rows are repeated on every page; once enough rows are added, the table spans more than one page on its own.

Tabelle 5: A sample long table.

First column	Second column	Third column
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D
A	BC	D

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{longtable}{|l|l|l|}
  \caption{A sample long table.}\label{tab:long} \\
  \hline
  \multicolumn{1}{|c|}{\textbf{First column}} &
   ↪ \multicolumn{1}{c|}{\textbf{Second column}} &
   ↪ \multicolumn{1}{c|}{\textbf{Third column}} \\ \hline
  \endfirsthead

  \multicolumn{3}{c}{{\bfseries \tablename\ \thetable{} --
   ↪ continued from previous page}} \\
  \hline
  \multicolumn{1}{|c|}{\textbf{First column}} &
   ↪ \multicolumn{1}{c|}{\textbf{Second column}} &
   ↪ \multicolumn{1}{c|}{\textbf{Third column}} \\ \hline
  \endhead

  \hline \multicolumn{3}{|r|}{{Continued on next page}} \\
   ↪ \hline
  \endfoot

  \hline\hline
  \endlastfoot

  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
  A & BC & D \\
\end{longtable}
```

3.15 Source Code

The minted package highlights listings properly. It uses the pygments library, which in turn requires Python.

Listing 1 shows source code written in XML. Zeile 2 contains a comment.

```xml
<listing name="example">
  <!-- comment -->
  <content>not interesting</content>
</listing>
```

List. 1: Example XML listing using minted

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\Zcref{lst:XML} shows source code written in XML.
\refline{line:comment} contains a comment.

\begin{listing}[htbp]
  \begin{minted}[linenos=true,escapeinside=||]{xml}
<listing name="example">
  <!-- comment --> |\labelline{line:comment}|
  <content>not interesting</content>
</listing>
\end{minted}
  \caption{Example XML listing using minted}
  \label{lst:XML}
\end{listing}
```

One can also typeset JSON as shown in Listing 2.

```json
{
  key: "value"
}
```

List. 2: Example JSON listing using minted

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{listing}[htbp]
  \begin{minted}[linenos=true,escapeinside=||]{json}
{
  key: "value"
}
\end{minted}
  \caption{Example JSON listing using minted}
  \label{lst:flJSON}
\end{listing}
```

Java is also possible as shown in Listing 3.

```java
public class Hello {
    public static void main (String[] args) {
        System.out.println("Hello World!");
    }
}
```

List. 3: Java code rendered using minted

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{listing}[htbp]
  \begin{minted}[linenos=true,escapeinside=||]{java}
public class Hello {
    public static void main (String[] args) {
        System.out.println("Hello World!");
    }
}
\end{minted}
  \caption{Java code rendered using minted}
  \label{lst:flJava}
\end{listing}
```

3.16 Itemization

One can list items as follows:

- Item One
- Item Two

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{itemize}
  \item Item One
  \item Item Two
\end{itemize}
```

One can enumerate items as follows:

1. Item One
2. Item Two

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{enumerate}
  \item Item One
  \item Item Two
\end{enumerate}
```

With paralist, one can even have all items typeset after each other and have them clean in the TeX document:

1. The first item, 2. the second item, and 3. the third item appear in one line.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
\begin{inparaenum}
  \item The first item,
  \item the second item, and
  \item the third item appear in one line.
\end{inparaenum}
```

3.17 Writing in Markdown

If you are new to LaTeX, you can start by writing your text in Markdown using the markdown package. LaTeX then takes care of the typesetting. Markdown and LaTeX can be mixed: Tabelle 6 is written in Markdown and referenced from LaTeX. A longer part, such as a whole section, can be placed in a separate file included by `\markdownInput{introduction.md}`. The markdown-latex-quickstart shows a complete document written in Markdown.

Text can be *emphasized* or **bold**, and `code` is set in a monospaced font. A citation looks like this [3], and here is a footnote.[6]

- first point
- second point
  - sub-point

1. firstly
2. secondly

Right	Left	Centered
12	12	12
123	123	123

Tabelle 6: A table written in Markdown

Tabelle 6 shows a table with caption. Its identifier `{#tbl:markdown}` is referenced by `<#tbl:markdown>`.

[6] This is an inline footnote.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
  \begin{markdown}
Text can be *emphasized* or **bold**, and `code` is set in a
↪  monospaced font.
A citation looks like this [@mwe], and here is a
↪  footnote.^[This is an inline footnote.]

- first point
- second point
  - sub-point

1) firstly
2) secondly

| Right | Left | Centered |
|------:|:-----|:--------:|
|    12 | 12   |    12    |
|   123 | 123  |   123    |

: A table written in Markdown {#tbl:markdown}

<#tbl:markdown> shows a table with caption.
Its identifier `{#tbl:markdown}` is referenced by
↪  `<#tbl:markdown>`.
\end{markdown}
```

3.18 Other Features

The words „workflow“ and „dwarflike“ can be copied from the PDF and pasted to a text file.

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
The words \enquote{workflow} and \enquote{dwarflike} can be
↪  copied from the PDF and pasted to a text file.
```

The symbol for powerset is now correct: $\powerset$ and not a Weierstrass p ($\wp$).
$\powerset(\{1,2,3\})$

Zugehöriger LaTeX-Quelltext aus `./paper-de.tex`

```
The symbol for powerset is now correct: $\powerset$ and not a
↪  Weierstrass p ($\wp$).

$\powerset(\{1,2,3\})$
```

Brackets work as designed: <test> One can also input backticks in verbatim text: `test`.

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
Brackets work as designed:
<test>
One can also input backticks in verbatim text: \verb|`test`|.
```

Acronyms can be typeset in running text with \initialism, which sets them as small caps that blend into the surrounding lowercase text. It is the lightweight alternative to the full acronym and glossary management (\gls, with an automatic list of abbreviations) provided by the thesis variants: \initialism only typesets the acronym and does not add it to any list. The macro and the ready-made acronyms (\OMG, \BPEL, \BPMN, \UML) are defined in commands.tex, where you can add your own.

The UML is maintained by the OMG; related standards include BPEL and BPMN. Any acronym can be set inline with REST or HTTP.

Zugehöriger LaTeX-Quelltext aus ./paper-de.tex

```
The \UML is maintained by the \OMG; related standards include
  ↪ \BPEL and \BPMN.
Any acronym can be set inline with \initialism{REST} or
  ↪ \initialism{HTTP}.
```

4 Zusammenfassung und Ausblick

Hier bitte einen kurzen Durchgang durch die Arbeit.

Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetuer id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut

massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

...und anschließend einen Ausblick.

Danksagungen Identification of funding sources and other support, and thanks to individuals and groups that assisted in the research and the preparation of the work should be included in an acknowledgment section, which comes right before the reference section in your document [4].

Literatur

1. Binz, T., Breiter, G., Leymann, F., Spatzier, T.: Portable Cloud Services Using TOSCA. IEEE Internet Computing **16**(03), 80–85 (May 2012), ISSN 1089-7801, `https://doi.org/10.1109/mic.2012.43`
2. Kopp, O., et al.: Winery – A Modeling Tool for TOSCA-based Cloud Applications. In: Proceedings of 11th International Conference on Service-Oriented Computing (ICSOC'13), LNCS, vol. 8274, pp. 700–704, Springer Berlin Heidelberg (2013), `https://doi.org/10.1007/978-3-642-45005-1_64`
3. Scharrer, M.: The `mwe` Package (2017), URL `http://texdoc.net/mwe`
4. Veytsman, B.: Latex class for the association for computing machinery – acknowledgement information (Aug 2021), URL `https://github.com/borisveytsman/acmart/blob/1704c8bf7eee92a1515ff755f5118b6a22bb1f8e/samples/samples.dtx#L709`

Alle Links wurden zuletzt am 29.03.2021 geprüft.