


## Πίνακας Αποδόσεων / Performance table

Αντλία	Κινητήρας	Παροχή Capacity	$m^3/h$	0	68	80	88	92	96	104	112
	,		1/min	0	1133	1333	1467	1200	1600	1733	1867
Pump	Motor	Ca	1/sec	0	18,9	22,2	24,4	20	26,7	28,9	31,1
SS 896/01	6′′ - 5,5			16	14	13	12	12	11	10	9
SS 896/02	6'' - 10			33	28	26	24	23	22	19	17
SS 896/03	6'' - 15			50	41	38	36	35	33	29	26
SS 896/04	6′′ - 20			67	55	51	48	46	44	39	34
SS 896/05	6'' - 25			84	69	64	60	58	55	49	43
SS 896/06	6′′ - 30			100	83	77	72	69	66	58	51
SS 896/07	6'' - 35			117	97	90	84	81	77	68	60
SS 896/08	6′′ - 40	ρα	tres	134	110	102	96	92	88	78	68
SS 896/09	8'' - 50	μέτρ	ı me	151	124	115	108	104	99	87	77
SS 896/10	8'' - 50	30	d in	160	138	128	120	115	110	97	85
SS 896/11	8'' - 60	ıκό	ו Hea	184	152	141	132	127	121	107	94
SS 896/12	8'' - 60	บาลเ	H=m tric F	201	166	154	144	138	132	116	102
SS 896/13	8′′ - 70	Ολικό Μανομετρικό σε μέτρα	r met	218	179	166	156	150	143	126	111
SS 896/14	8′′ - 70	Ψ̈́	ano	225	193	179	168	161	154	136	119
SS 896/15	8'' - 75	лко́	H=m Total Manometric Head in metres	242	207	192	180	173	165	146	128
SS 896/16	8′′ - 80	රි		257	221	205	192	184	176	155	136
SS 896/17	8'' - 90		1	274	235	218	204	196	187	165	145
SS 896/18	8'' - 90			302	248	230	216	207	198	175	153
SS 896/19	8'' - 100			319	262	243	228	219	209	184	162
SS 896/20	8'' - 100			336	276	256	240	230	220	194	170
SS 896/21	8'' - 110			352	290	269	252	242	231	204	179
SS 896/22	8'' - 110			369	304	282	264	253	242	213	187
SS 896/23	8'' - 125			386	317	294	276	265	253	223	196



Τύπος Αντλίας		Ισχύς Κινητήρα Motor Power			Διαστάσεις Dimensions							Βάρος σε kg Weight in kg		
Pump :.		kW	HP	L		В	Ф Мах		D	Αντλία	Κινητήρα	Ολικό		
Type	in	KW I	HP	L	A	В	Pump	Motor	Rp	Pump	Motor	Total		
SS 896/01		4	5,5	1249	570	679	174	143	5′′	22	43	65		
SS 896/02		7,5	10	1397	698	699	174	143	5′′	25	45	70		
SS 896/03		11	15	1585	826	759	174	143	5′′	29	53	82		
SS 896/04	6′′	15	20	1808	954	854	174	143	5′′	32	61	93		
SS 896/05	6	18,5	25	1981	1082	899	174	143	5′′	35	66	101		
SS 896/06		22	30	2199	1210	989	174	143	5′′	38	77	115		
SS 896/07		26	35	2432	1338	1094	174	143	5′′	41	88	129		
SS 896/08		30	40	2660	1466	1194	174	143	5′′	44	98	142		
SS 896/09		37	50	2745	1605	1140	182	194	5′′	47	140	187		
SS 896/10		37	50	2873	1733	1140	182	194	5′′	50	140	190		
SS 896/11		45	60	3091	1861	1230	182	194	5′′	53	156	209		
SS 896/12		45	60	3219	1989	1230	182	194	5′′	55	156	211		
SS 896/13		52	70	3457	2117	1340	182	194	5′′	58	179	237		
SS 896/14		52	70	3585	2245	1340	182	194	5′′	60	179	239		
SS 896/15		55	75	3713	2373	1340	182	194	5′′	63	179	242		
SS 896/16	8′′	60	80	3971	2501	1470	182	194	5′′	65	198	263		
SS 896/17		67	90	4099	2629	1470	182	194	5′′	68	198	266		
SS 896/18		67	90	4227	2757	1470	182	194	5′′	70	198	268		
SS 896/19		75	100	4445	2885	1560	182	194	5′′	73	215	288		
SS 896/20		75	100	4573	3013	1560	182	194	5′′	75	215	290		
SS 896/21		83	110	4881	3141	1740	182	194	5′′	78	247	325		
SS 896/22		83	110	5009	3269	1740	182	194	5′′	81	247	328		
SS 896/23		93	125	5137	3397	1740	182	194	5′′	83	247	330		



## Αποδόσεις σε / Performance at 2900 r.p.m. 50 Hz

