

# Chapter 4. Pointers

Programming Concepts in Scientific  
Programming


EPFL, Master class

October 9, 2017

# Pointers and the Computer Memory

## Addresses

```
int x = 1;  
int y = 2;  
std::cout << &x << "\n";
```



Debug this program (breakpoint on line 3)

```
(gdb) x/2wx &x
```

```
(gdb) x/2wx &y
```

```
(gdb) x/2wx &x
```


```
(gdb) x/2wx &y
```

Want to know more ?  $\Rightarrow$  (gdb) help x

# Pointers and the Computer Memory

## Addresses

```
int total_sum = 10;
```



Getting an address: &

```
std::cout << &total_sum << "\n";
```

# Pointers and the Computer Memory

## Pointer Variables

Using the *star* in types:

```
double *p_x;
```

Example of use

```
// x stores a double precision number  
double x = 3;  
// p_x stores the address of a double  
double *p_x = &x;
```

Try it with CLion !

```
double x = 3;
```

```
double *p_x = &x;
```

```
std::cout << p_x << std::endl;
```


Debug this program (breakpoint on line 6)

Hit this command in gdb:

```
(gdb) x/3wx &x
```

Try it with CLion !

What is the memory structure ?



## String of characters

Declare an array of characters:

```
char name[250] = "yopla";
```

However, I can write:

```
char *ptr = name;
```

because an array of characters is actually a pointer!

## Main: argv structure

Considering this code:

```
int main(int argc, char ** argv){  
    int p = atoi(argv[1]);  
    double z = atoi(argv[2]);  
}
```

If I launch the executable like this:

```
> ./exec 10 8.985985
```

What is the memory structure in that case ?



## Aliasing/de-reference

```
double y = 3.0;  
double *p_x = &y;
```

```
// This changes the value of y  
*p_x = 1.0;
```

## Warnings on the Use of Pointers

What is the problem with this code ?

```
double *p_x;
```

```
*p_x = 1.0;
```

## Warnings on the Use of Pointers

```
// p_x stores the address of a double  
// not yet specified
```

```
double *p_x;
```

```
// trying to assign 1.0 in an unspecified  
// memory location
```

```
*p_x = 1.0;
```

## Dynamic Allocation of Memory

```
int *x = new int;
```

```
*x = 10;
```

```
delete x;
```

# Dynamic Allocation of Memory

## Vectors

```
double *x = new double[10];  
double *y = new double[10];  
  
for (int i = 0; i < 10; i++) {  
    x[i] = double(i);  
    y[i] = 2.0 * x[i];  
}
```

```
delete[] x;  
delete[] y;
```

# Matrices

```
int rows = 5, cols = 3;  
double **A = new double *[rows];
```

```
for (int i = 0; i < rows; i++) {  
    A[i] = new double[cols];  
}
```

```
// you can access the values of the array with  
A[2][4] = 5;
```

```
// At the end: deallocate the memory  
for (int i = 0; i < rows; i++) {  
    delete[] A[i];  
}  
delete[] A;
```

## ROW MAJOR format

```
double *p_a = new double[rows * cols];
```

```
double **A = new double *[rows];  
for (int i = 0; i < rows; i++) {  
    A[i] = &p_a[i * rows];  
    A[i] = p_a + i * rows;  
}
```

*// you can access the values of the array with*

```
A[2][4] = 5;
```

*// or with*

```
p_a[2 * rows + 4] = 5;
```

*// At the end: de-allocate the memory*

```
delete[] A;
```

```
delete[] p_a;
```

## ROW MAJOR format

- ▶ ROW MAJOR: C, C++
- ▶ COLUMN MAJOR: Matlab and Fortran



## Tips

- ▶ Pointer Aliasing: e.g. coding
  - ▶  $C = A \cdot B$
  - ▶  $A = A \cdot B$
- ▶ Dynamic Allocation: check non-null pointer:

```
int *p_x = new int;  
assert(p_x != NULL);
```

- ▶ Every new Has a delete