Linear Discriminant Analysis

K. Gibert (1,2,3)

(1)Department of Statistics and Operation Research

(2) Knowledge Engineering and Machine Learning group at Intelligent Data Science and Artificial Intelligence Specific Research Center

(3) Institut Universitari de Recerca en Ciència I Tecnologia de la Sostenibilitat

karina.gibert@upc.edu, https://www.eio.upc.edu/en/homepages/karina



 Find the function that better predicts the class of an object

Based on Factorial methods



Given

- A data matrix X (nxp) centered
 - n individuals
 - p variables
- Y categorical variable (m modalities)



Total Variability of X:

$$-T_{pp} = X'PX$$

- P = diagonal(1/n)
$$T_{pp} = V(X) = \frac{(X-X)^2}{n}$$

Matricial notation. Care, centered data means \bar{X} =0




- Variability decomposition
 - Total variability $T_{pp} = X^{t}PX$
 - T= E+D
 - E= G^tHG
 - G centroids matrix
 - H= diag (n_k/n)
 - D= X'^tPX
 - $\bullet X' = (x_{ij} g_{kj})$
 - P= diag (1/n)



Linear Discriminant Analysis

Find the axis that better discriminates






Factorial spaces

- \blacksquare < X_{nxp} , \mathbb{I}_p , P_{nxn} >
- \blacksquare < G_{mxp} , \mathbb{I}_p , H_{mxm} >
- \blacksquare < G_{mxp} , D_{pxp} , H_{mxm} >
- Projected variabilities on direction \overrightarrow{w}
- Total variability projected w^tTw
- Between Classes variability projected $\overrightarrow{w}^t \mathbf{E} \overrightarrow{w}$
- Within Classes variability projected $\vec{w}^t D \vec{w}$

Linear Discriminant Analysis

- Find the axis that better discriminates
- Find the axis that maximizes $\vec{w}^t E \vec{w}$



- <G,D⁻¹, H>
- Search direction \vec{w} such that $\vec{w}^t E \vec{w}$ is maximized
- Diagonalization of

$$\vec{u}^{\text{t}} \, \mathbf{D}^{-1} \, \mathbf{G}^{\text{t}} \, \mathbf{H} \, \mathbf{G} \, \mathbf{D}^{-1} \, \vec{u}$$

subject to $\vec{u}^{\text{t}} \, \mathbf{D} \, \vec{u} = 1$

 The first eigen value points to an eigen vector that gives solution

