

LaTeX reference

Laurel Farris

July 31, 2016

- https://www.sharelatex.com/learn/Main_Page
- <http://texdoc.net/texmf-dist/doc/latex/lshort-english/lshort.pdf>
- <http://texdoc.net/texmf-dist/doc/latex/titlesec/titlesec.pdf>

Contents

1	Types of documents	3	11 Lists	10
			11.1 itemize	11
2	Units	3	11.2 enumerate	12
			11.3 description	12
3	Margins	3	11.4 Make your own list	12
4	Horizontal spacing and alignment	4	12 Color	13
			12.1 Color background	13
5	Vertical spacing and alignment	4	12.2 Color text	13
			12.3 Define your own colors	13
6	Breaking up text (or preventing it)	5	13 Hyperlinks	13
7	Headers and footers	5	14 Putting text in a box	14
	7.1 Page numbers	5	15 Columns	14
	7.2 Footnotes	5	16 Symbols	15
8	Fonts	7	17 Writing code into a Latex document	15
	8.1 Font size	7	18 New and renewed commands and environments	16
	8.2 Font style	7	18.1 Commands	16
	8.2.1 Modal	7	18.2 Environments	16
	8.2.2 Textblock	7	19 Verbatim	16
9	Sections	8	20 Figures	16
	9.1 Example of nested section settings . .	8	21 Tables	17
	9.1.1 My subsubsection title	8	22 Bibliographies	17
	9.2 Nested section options	8	22.1 Creating and using a makefile	17
	9.3 Space around section titles	9	23 Maths!	18
	9.4 Simpler way to change only size/style	9		
	9.5 Color	9		
	9.6 Labels	9		
	9.7 Referring to sections in text using section labels	9		
10	Table of contents	10		

23.1	Inside text	18	23.5.1	Integrals	20
23.2	Equations	18	23.5.2	Square root	20
23.2.1	Numbered equations	18	23.5.3	Summation (and the multipli-	
23.2.2	Equations without numbering .	18		cation version)	20
23.2.3	Aligning equations	19			
23.3	Size of brackets, parentheses, etc. . . .	19	24	Beamer	21
23.4	Referring to parts of equation	19			
23.5	Operations	20	25	Questions and things to be added	21

Check `filename.log` for version of packages used. May need to add `\listfiles` in the preamble first.

Types of documents

```
\documentclass{article}
\documentclass[twoside]{article} % two-sided document (affects page-numbers)
```

Units

px pixels, depends on browser, use for electronic media
pt points, use in print media
em *Horizontal* size, 1em is equal to the font size of the text.
ex *Vertical* size, 1ex is equal to the height of the letter ‘x’ in the relevant font (usually).

Margins

1. Sides (odd- and even-numbered pages):

```
\addtolength{\oddsidemargin}{-0.875in}
\addtolength{\evensidemargin}{-0.875in}
\addtolength{\textwidth}{1.75in}
```

2. Top/bottom:

```
\addtolength{\topmargin}{-0.875in}
\addtolength{\textheight}{1.75in}
```

A better way (both do the same thing; can customize the second a little more):

- `\usepackage{fullpage}`
- `\usepackage[margin=1in]{geometry}`

```
\geometry{paperwidth=140mm, paperheight=105mm}
```

```
\usepackage{changepage}
\begin{document}
\begin{adjustwidth}{<left>}{<right>}
...
\end{adjustwidth}
```

```
\newenvironment{changemargin}[2]{%
\begin{list}{}{%
\setlength{\topsep}{0pt}%
\setlength{\leftmargin}{#1}%
\setlength{\rightmargin}{#2}%
\setlength{\listparindent}{\parindent}%
\setlength{\itemindent}{\parindent}%
\setlength{\parsep}{\parskip}%
}%
\item[]{} \end{list}}
```

This environment will indent the left and right margins by the values given.

Leave sections and headers alone, and reduce the margins of regular text? Increase subsection margins halfway.

Add notes to margins: can use marginnote (with package) or marginpar (no package needed). Not sure which is better yet.

```
\usepackage{marginnote}
\usepackage{showframe,marginnote} % box around margins
\setlength{\marginparwidth}{1in}

\renewcommand*{\raggedleftmarginnote}{}
\renewcommand*{\raggedrightmarginnote}{\centering}

\marginfont{}: % Don't actually use this
\renewcommand*{\marginfont}{\color{red}\sffamily}

\begin{document}
\marginnote{<right>} % aligned left
\marginpar{<right>} % aligned left
\reversemarginpar % Switch to left side margins
\marginnote{<left>} % aligned right
\marginpar{<left>} % aligned left
\normalmarginpar % switch back
```

Horizontal spacing and alignment

- `\setlength{\parindent}{0m}` Set indent for new paragraphs
- `\hspace` horizontal space
- `\hspace{20 mm}` horizontal blank space equal to 20 mm
- `\hfill` Pad with horizontal space to end of line
- `\noindent` self-explanatory

```
\usepackage{ragged2e}

• \begin{flushright}... \end{flushright}
• \begin{center} ... \end{center}
• \begin{justify} ... \end{justify}
• \centering
• \center is not a thing.
```

Vertical spacing and alignment

<http://www.terminally-incoherent.com/blog/2007/09/19/latex-squeezing-the-vertical-white-space/>

- `\setlength{\parskip}{0.5ex}` Set spacing between paragraphs
- `\vspace{}` vertical space
- `\renewcommand{\baselinestretch}{1.5}`
This changes the spacing for everything in the document, including footnotes and tables.
- `\usepackage{setspace}... \setstretch{1.5}`
Can apply this to only part of text?
- `\usepackage[doublespacing]{setspace}` Same as previous option?

[ctb] Options like this will center at top, center, bottom, etc. Actually this usually doesn't work.

Breaking up text (or preventing it)

- `\` Force line break
- `\newline` ?
- `\newpage` Jump to a new page after previous section
- `\clearpage` ?
- `\begin{samepage}... \end{samepage}` Keep something from being split by a page break.

Headers and footers

In preamble:

```
\usepackage{fancyhdr}
\pagestyle{fancy}
\setlength{\headheight}{15pt}
\lhead{text} % Top left
\rhead{text} % Top right
\chead{text} % Top center
\lfoot{text} % Bottom left
\rfoot{text} % Bottom right
\cfoot{text} % Bottom center
```

The `\headheight` option sets the amount of space between the header and the top edge of the paper. Value has to be greater than 13.6, otherwise will get an error message. Document still compiles, but better safe than sorry.

1. Page numbers

```
\fancyhf{} % Clear all headers and footers (including default page number).
\renewcommand{\headrulewidth}{0pt} % remove the header rule
\rfoot{\thepage}
\lfoot{\thepage}
```

2. Footnotes

```
\usepackage[symbol]{footmisc} % Use symbols instead of numbers

\usepackage{perpage}
\MakePerPage{footnote} % Markers re-start after each page
...
\begin{document}
...
Here is some relevant information\footnote{See Guy et al. for additional
information.}

Here is some relevant information1

\renewcommand{\footnoterule}{%
  \kern -3pt
  \hrule width \textwidth height 1pt
  \kern 2pt
}
```

¹See Guy et al. for additional information.

or

```
\renewcommand\footnoterule{\rule{\linewidth}{5pt}}
```

Fonts

- <https://www.tug.org/pracjourn/2006-1/schmidt/schmidt.pdf>
- <https://en.wikibooks.org/wiki/LaTeX/Fonts>

```
\usepackage{lmodern}           Font that applies to entire doc.
\renewcommand*\familydefault{\sfdefault} % Only if the base font of the document is to be sans serif
\usepackage[T1]{fontenc}
```

1. Font size

```
\documentclass[12pt]{article}
\documentclass[11pt]{article}
\documentclass[10pt]{article}
\fontsize{<font size>}{<line size>}
\Huge
\huge
\Large
\large
\normalsize
\small
\footnotesize
\scriptsize
\tiny
```

10pt is the default font size.

Not entirely sure how this works yet.

Example:

```
{\Large I want this text to be big.}
I want this text to be big.
(enclosing entire thing in {}s keeps from having to use
\normalsize at the end).
```

2. Font style

2.1 Modal

```
\mdseries
\bfseries
\upshape
\itshape
\scshape
\slshape
\rmfamily
\sffamily
\ttfamily
```

These don't read text as an argument, and can somehow be used in the verbatim environment?

2.2 Textblock

```
\textbf{bold}
\textit{italics, for quotes or titles}
\texttt{computer style}
\textsf{sans serif}
\textsl{slanted}
\textsc{Small caps}
\emph{This text is also in italics, for emphasis}
\underline{This text is underlined}
```

```
bold
italics, for quotes or titles
computer style
sans serif
slanted
SMALL CAPS
This text is also in italics, for emphasis
This text is underlined
```

Sections

https://www.sharelatex.com/learn/Sections_and_chapters#Numbered_and_unnumbered_sections Lorem ipsum dolor sit amet, consectetur adipiscing elit. Ut purus elit, vestibulum ut, placerat ac, adipiscing vitae, felis. Curabitur dictum gravida mauris. Nam arcu libero, nonummy eget, consectetur id, vulputate a, magna. Donec vehicula augue eu neque. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Mauris ut leo. Cras viverra metus rhoncus sem. Nulla et lectus vestibulum urna fringilla ultrices. Phasellus eu tellus sit amet tortor gravida placerat. Integer sapien est, iaculis in, pretium quis, viverra ac, nunc. Praesent eget sem vel leo ultrices bibendum. Aenean faucibus. Morbi dolor nulla, malesuada eu, pulvinar at, mollis ac, nulla. Curabitur auctor semper nulla. Donec varius orci eget risus. Duis nibh mi, congue eu, accumsan eleifend, sagittis quis, diam. Duis eget orci sit amet orci dignissim rutrum.

1. Example of nested section settings

Nam dui ligula, fringilla a, euismod sodales, sollicitudin vel, wisi. Morbi auctor lorem non justo. Nam lacus libero, pretium at, lobortis vitae, ultricies et, tellus. Donec aliquet, tortor sed accumsan bibendum, erat ligula aliquet magna, vitae ornare odio metus a mi. Morbi ac orci et nisl hendrerit mollis. Suspendisse ut massa. Cras nec ante. Pellentesque a nulla. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Aliquam tincidunt urna. Nulla ullamcorper vestibulum turpis. Pellentesque cursus luctus mauris.

1.1 My subsection title

Nulla malesuada porttitor diam. Donec felis erat, congue non, volutpat at, tincidunt tristique, libero. Vivamus viverra fermentum felis. Donec nonummy pellentesque ante. Phasellus adipiscing semper elit. Proin fermentum massa ac quam. Sed diam turpis, molestie vitae, placerat a, molestie nec, leo. Maecenas lacinia. Nam ipsum ligula, eleifend at, accumsan nec, suscipit a, ipsum. Morbi blandit ligula feugiat magna. Nunc eleifend consequat lorem. Sed lacinia nulla vitae enim. Pellentesque tincidunt purus vel magna. Integer non enim. Praesent euismod nunc eu purus. Donec bibendum quam in tellus. Nullam cursus pulvinar lectus. Donec et mi. Nam vulputate metus eu enim. Vestibulum pellentesque felis eu massa.

2. Nested section options

```
\section{My First Section}
\subsection{My Subsection}
\subsubsection{A subsubsection}
\paragraph{text}
\subparagraph{text}
```

```
\usepackage{titlesec}
\titleformat{<command>}
  [<shape>][<format>][<label>][<sep>][<before-code>][<after-code>]
```

Paragraphs are not numbered or followed by a line break. Note that `\paragraph{}` and `\par` are not the same thing. `\par` does the same thing as a blank line.

Shape:

`hang` (default)

`in, leftmargin` Titles are in the margins, rather than body of page.

```
\titleformat{\subsubsection}{%
  \filcenter\bfseries\fontsize{16}{14}\selectfont\color{cadmiumorange}}
```



```
{\arabic{subsection}.\arabic{subsubsection}\;}
{1em}{}
```

Centers title horizontally, length of 1em between section number and text in title. Also customized how the titles should be labelled (#.#)

3. Space around section titles

```
\usepackage{titlesec}
\titlespacing*{command}{left}{before-sep}{after-sep}[right-sep]
\titlespacing*{\section}{-0.50in}{0pt}{0pt}
\titlespacing*{\subsection}{-0.25in}{0pt}{0pt}
```

Left margin adds or subtracts from what is already there. The “-sep” values are absolute, so negative makes no sense (I think). Setting these to 0pt reduces the default spacing a little. The asterisk removes paragraph indentation following the section title (doesn’t do anything if there is no indentation anyway).

4. Simpler way to change only size/style

```
\usepackage{titlesec}
\titleformat*{\section}{\LARGE\bfseries}
\titleformat*{\subsection}{\Large\bfseries}
\titleformat*{\subsubsection}{\large\bfseries}
```

5. Color

This actually overrides the titlesec package, which can also be used to set section title colors. Probably better to use that one.

```
\usepackage{sectsty}
\sectionfont{\color{blue}}
\subsectionfont{\color{blue}}
\subsubsectionfont{\color{blue}}
```

6. Labels

```
\renewcommand{\thesection}{Text \arabic{section}} % Text in front of label
\renewcommand{\thesection}{\Roman{section}} % Roman numerals
\setcounter{secnumdepth}{0} % Depth to be labelled
```

Setting this to 1 would number sections only, setting it to 2 would number sections and subsections, but not subsubsections, etc.

7. Referring to sections in text using section labels

```
See section $\S$\ref{data} for the data description.
...
\subsection{The Data}\label{data}
...
```

May need to run `pdflatex` twice for this to take effect. Obviously won’t have anything to refer to if the sections aren’t numbered.

Table of contents

<http://texblog.org/2011/09/09/10-ways-to-customize-tocloft/> \tableofcontents wherever you want it to go. You will have to run pdf_lat_{ex} twice. It appears that creating a toc puts headers on all pages, which may not be desired. See §7 for getting rid of them.

In preamble: \setcounter{tocdepth}{n} where n is the number of levels deep to go, e.g. 1: sections, 2: sections and subsections, etc.

Some sections, like those with “*” won’t be included. To add them: Syntax: \addcontentsline{type}{section_level}{entry}

Example: \addcontentsline{toc}{section}{Preface}

To change space between items in toc:

```
\usepackage{setspace}
...
\begin{document}
\addtocontents{toc}{\protect\setstretch{n}}
```

where n is between 0 and 1? Set to fraction of default? “protect” has something to do with “fragile” things.

Include figures and tables:

```
\listoffigures
\listoftables
```

Note that the figure and table environments need to be used.

Two columns:

```
\usepackage[toc]{multitoc}
\renewcommand*{\multicolumntoc}{2} # but 2 is the default...?
\setlength{\columnseprule}{0.5pt}
```

Lists

- <ftp://ftp.nyu.ru/mirrors/ftp.dante.de/tex-archive/macros/latex/contrib/enumitem/enumitem.pdf>
- <https://www.ntg.nl/maps/11/33.pdf>
- https://www.sharelatex.com/learn/Lists#Reference_guide
- <http://ctan.mirrors.hoobly.com/macros/latex/contrib/enumitem/enumitem.pdf>
- <http://www.troubleshooters.com/linux/lyx/ownlists.htm>

New (unorganized) stuff: “Label” refers to the bullet, number, or description item.

In preamble:

```
\usepackage{enumitem}
\setlist[<typeoflist>,<n>]{<options>}
```

typeoflist can be itemize, enumerate, description, etc. n is the nested level (1 for top level). Options are as follows:

Horizontal spacing

labelindent Used, but not described...

rightmargin Change right margin of description text.

`leftmargin` Distance from the left edge of the current environment (leftmost edge of labelwidth) to the left margin of the item label (not text?). Remember, environments can nest. Defaults to 0. Can only make this so big, eventually text doesn't move anymore. Need to figure out exactly what all this is doing. Pretty sure this only affects multi-line descriptions (the text NOT on the same line as the label).

`listparindent` The indent of the first line of each paragraph in an item, except for the first paragraph of an item. If you're pressed for vertical space and want to decrease interparagraph spacing within items while still giving the user cues as where new paragraphs begin, this is the way to do it.

`labelwidth` Width allotted to the label. This should be equal to or greater than the longest *expected* label. Good for lining up text when labels are left-aligned.

`labelsep` The distance between the rightmost part of the label (assuming you haven't changed the label from its default right justification) to the left margin of the item body. This is one of the handiest adjustments you can make to create the ultimately readable list for your exact situation. Use it early and often.

BEWARE: This setting enforces this distance by shoving the label left rather than moving the body left margin right. If you set this you might need to add a corresponding amount to `leftmargin`, if you want your labels in a specific place. Space between label and following text

`itemindent` Only indents the first line (with the label) This length is capable of causing some real ugliness – leave it alone unless you have a really good reason not to. What this horrid adjustment does is takes the label and first line of a multiline body, and push them left from the normal item body left margin. This makes the body lines not line up. It's ugly. If you already have a list where multiline items look wrong, try setting this length to 0 to see whether a previous global setting of this length has caused problems.

Don't set this length except out of self-defense. It's trouble.

Vertical spacing

`parskip` Space between paragraphs outside of a list, and part of the space between a non-list paragraph and a list item. **This is NOT a list property; it can be set globally for entire document (see `SS ref{}`).**

`topsep` Extra space added to `parskip` before the first AND after the last item.

`parsep` Paragraph separation within a single item.

`itemsep` Extra inter-item spacing added to `parsep`

`partopsep` This is added to the top and/or bottom of the list if and only if there's a blank line above or below the first or last item. *Leave this alone unless blank lines become a problem.*

```
leftmargin=*      % Align with main text
font=\normalfont % Not bold, which is the default
style=nextline   % For when text is too long?
style=multiline  % ???
```

1. itemize

Change bullet size/style. Not sure what the difference is between the two.

```
\renewcommand{\labelitemi}{\vcenter{\hbox{\tiny$\bullet$}}}$}
\renewcommand{\labelitemi}{\tiny$\bullet$}$}
```

2. enumerate

```
\setlist[enumerate]{font={\bfseries}}% global settings, for all lists
\setlist[enumerate,1]{label={(\arabic*)}}
\setlist[enumerate,1]{label={(\roman*)}}
```

```
\setenumerate[0]{label=(\Alph*)} % Different package?
```

1.1, 1.2 \rightarrow 1.2.1, 1.2.2, etc

```
\usepackage{enumitem}
\setlist[enumerate,1]{%
  label={\arabic{section}.\arabic*} }
\setlist[enumerate,2]{%
  label={\arabic{section}.\arabic{enumi}.\arabic*} }
```

Or use the `enumerate` package:

```
\usepackage{enumerate}
\begin{document}
\begin{enumerate}[label*=\arabic*.] % ???
\begin{enumerate}[I]
\begin{enumerate}[I.]
\begin{enumerate}[(a)]
```

3. description

To customize the description labels (the items inside the brackets), in the preamble:

```
\renewcommand{\descriptionlabel}[1]{%
  \hspace{\labelsep}
  \ttfamily
  \textcolor{red}{\#1}
}
```

This puts the labels in typewriter font in a different color. By default, description labels start a distance equal to `hspace` to the *left* of the text, so adding that line causes them to line up with the left edge of the text instead.

4. Make your own list

```
\begin{list}{\default_label}{\decls}
  default_label: Text to be used as a label (leave blank if none desired)
  decls: geometrical parameters
```

Alternative way to get rid of the space between items (without `enumitem` package):

```
\usepackage{mdwlist}
...
\begin{document}
...
\begin{itemize*}
  \item ...
\end{itemize*}
```

```
\up{tasks} ???
...
\begin{tasks}(4)
```

```

\task one
\tast two
\end{tasks}

```

These will be listed horizontally, rather than vertically.

```

\begin{list}{}
...
\end{list}

```

Brackets by list will set the style; leave this empty for no symbols

Color

```

\usepackage{color}
\usepackage{xcolor}

\colorlet{<new color name>}{<old color name>}
\color{blue!30!green}

```

1. Color background

```

\usepackage{xcolor}
\pagecolor{yellow!30}

```

2. Color text

```

\usepackage{color}
...
\textcolor{red}{I want the text in the brackets to be red.}

```

`color` is required for pre-defined colors (white, black, red, green, blue, cyan, magenta, yellow) `xcolor` is needed to define new colors (see § 12.3). The use of colour mixtures is a big addition brought along by `xcolor`. If you don't need the additional features of `xcolor` you can simply stick with `color`; even though there appears to be no disadvantage in using `xcolor` all the time.

3. Define your own colors

<http://latexcolor.com>

```

\usepackage[usenames, dvipsnames]{color}
\definecolor{color}{HTML}{AF00D7} % HTML must be in caps!
\definecolor{mypink1}{rgb}{0.858, 0.188, 0.478}
\definecolor{mypink2}{RGB}{219, 48, 122}
\definecolor{mypink3}{cmyk}{0, 0.7808, 0.4429, 0.1412}
\definecolor{mygray}{gray}{0.6}
\textcolor{mygray}{text I want to be gray}.

```

Hyperlinks

In preamble:

```

\usepackage{hyperref}
\hypersetup{colorlinks=true,
  urlcolor=blue,
  linkcolor=black
}
\urlstyle{same}

```

Insert hyperlink in text:

```

\url{http://google.com}
\href{http://google.com}{link text}
\href{http://google.com}{\textcolor{blue}{link text}}

```

Putting text in a box

```
\usepackage{xcolor}
\usepackage{lipsum}
\begin{document}
\lipsum[1]
\medskip
\noindent\fcolorbox{red}{yellow}{%
  \minipage[t]{\dimexpr0.48\linewidth-2\fbboxsep-2\fbboxrule\relax}
  \lipsum[2]
\endminipage}\hfill
\colorbox{red}{yellow}{%
  \minipage[t]{\dimexpr0.48\linewidth-2\fbboxsep-2\fbboxrule\relax}
  \lipsum[3]
\endminipage}
\medskip
\lipsum[4]

\colorbox{hl}{\parbox{0.9\textwidth}
text to go in box}
```

Notes: You can adjust the thickness of border and padding of `\fcolorbox{<border-color>}{<background-color>}{<contents>}` by setting `\fbboxrule=<value><unit>` and `\fbboxsep=<value><unit>`, respectively. Put the setting before invoking `\fcolorbox{<border-color>}{<background-color>}{<contents>}`. For example: `\fbboxrule=1pt` and `\fbboxsep=5pt`. Use `t`, `c`, `b` options to align the base line of the most top row, the center row and the most bottom row with the surrounding baseline.

```
\usepackage{tcolorbox}
\begin{tcolorbox}[<options>]
...
\end{tcolorbox}
```

Example:

```
\usepackage{tcolorbox}
\begin{tcolorbox}[colback=red!5!white,colframe=red!75!black,title=My nice heading]
  My awesome color box.
\end{tcolorbox}
```

My nice heading

My awesome color box.

Columns

```
\begin{minipage}[t]{0.2\textwidth}
  stuff
\end{minipage}
\begin{minipage}[t]{0.8\textwidth}
  longer stuff
\end{minipage}

\begin{multicols}{2}           % Start 2-columns
\begin{multicols*}{2}         % No forcing cols to equal heights
\raggedcolumns                 % No forcing cols to fill vertical space
```

```
\vfill           % No forcing cols to fill vertical space (not working)
\columnbreak     % Start at top of next column
```

`\addtolength{\columnsep}{5mm}` add space between columns. Verbatim text will continue into second column.

Symbols

```
\AA{} % Angstrom (does not go between $s)
\infty % infinity
\sim % '~'
\approx % 'double ~'
\propto % proportionality symbol (like alpha)
\equiv % like '=', but with three lines.
& \% % include these symbols in document
      % (also precede a space with '\' when in math mode).
\pm % plus or minus (\mp for minus or plus)
\textbackslash % \
\textgreater % >
\textless % <
```

some text

Writing code into a Latex document

A nicer alternative to verbatim.

```
\usepackage{listings}
\usepackage{color}

\definecolor{mygreen}{rgb}{0,0.6,0}
\definecolor{mygray}{rgb}{0.5,0.5,0.5}
\definecolor{mymauve}{rgb}{0.58,0,0.82}

\lstset{ %
  backgroundcolor=\color{white}, % choose the background color; you must add \usepackage{color} or \usepackage{xcolor}
  basicstyle=\footnotesize, % the size of the fonts that are used for the code
  breakatwhitespace=false, % sets if automatic breaks should only happen at whitespace
  breaklines=true, % sets automatic line breaking
  captionpos=b, % sets the caption-position to bottom
  commentstyle=\color{mygreen}, % comment style
  deletekeywords={...}, % if you want to delete keywords from the given language
  escapeinside={\%*}{*}, % if you want to add LaTeX within your code
  extendedchars=true, % lets you use non-ASCII characters; for 8-bits encodings only, does not work with x86
  frame=single, % adds a frame around the code
  keepspaces=true, % keeps spaces in text, useful for keeping indentation of code (possibly needs configuration)
  keywordstyle=\color{blue}, % keyword style
  language=Octave, % the language of the code
  otherkeywords={*,...}, % if you want to add more keywords to the set
  numbers=left, % where to put the line-numbers; possible values are (none, left, right)
  numbersep=5pt, % how far the line-numbers are from the code
  numberstyle=\tiny\color{mygray}, % the style that is used for the line-numbers
  rulecolor=\color{black}, % if not set, the frame-color may be changed on line-breaks within not-black text (e.g. comments)
  showspaces=false, % show spaces everywhere adding particular underscores; it overrides 'showstringspaces'
```

```

    showstringspaces=false,      % underline spaces within strings only
    showtabs=false,              % show tabs within strings adding particular underscores
    stepnumber=2,                % the step between two line-numbers. If it's 1, each line will be numbered
    stringstyle=\color{mymauve}, % string literal style
    tabsize=2,                   % sets default tabsize to 2 spaces
    title=\lstname                % show the filename of files included with \lstinputlisting; also try caption in
}
...
\begin{lstlisting}
    code code code
\end{lstlisting}

```

New and renewed commands and environments

1. Commands

Syntax: `\newcommand{<cmd>}[<n>][<opt>]{<stuff>}`

`n` Number of arguments

`opt` Options

`stuff` stuff

Existing environments (list, adjustwidth, etc.) can be used inside new commands!

2. Environments

```

\renewenvironment{name}{%
    ...}

\newenvironment{name}[#]{%
    {<initialization code> (before text)}
    {<finalization code> (after text)}
}

```

Verbatim

`verb` is used “in line”, while `verbatim` is a separate environment:

```

\begin{verbatim}
... text ...
\end{verbatim}

```

```
\verb|\documentclass{article}|
```

How to make the begin verbatim text a different color in vi? E.g. a dark gray, but the enclosed text is lighter.

Figures

```
\usepackage{graphicx}
```



```

...
\begin{figure}[h]
\centering
\includegraphics[width=5.0in]{GreekSymbols.jpg}
\caption{How to insert greek symbols in LaTeX}
\label{greek}
\end{figure}

```

placement specifiers: [`htbp!`] ‘here’, ‘top’, ‘bottom’,...

Tables

```

\begin{table}[h]
\caption{Values for polytropic index  $n = 4.5$ }
\centering
\begin{tabular}{cccccccc}
\hline\hline
 $n$  &  $\xi_1$  &  $\rho_c/\rho$  &  $N_n$  &  $W_n$  &  $\Theta_n$  &  $\rho_c[g, cm^{-3}]$  &  $P_c[dyne, cm^{-2}]$  &  $T_c[K]$  \\
\hline
4.5 & 31.841 & 6187.500 & 0.658 & 4917.415 & 3.329 & 8718.704 & 5.535e19 & 4.742e7 \\
\hline
\end{tabular}
\label{table:nonlin}
\end{table}

```

For the `tabular` line, `c` stands for center-justified; use `l` and `r` for left and right justified.

Bibliographies

```

\bibliographystyle{plain}
\begin{document}
... \cite{id} ...
\bibliography{reffile}
\end{document}

```

1. Creating and using a makefile

```

cl> vi reffile.bib
  @ARTICLE{label_name,
    title={},
    journal={},
    ...
  }
cl> vi makefile
my_paper: paper.tex
  pdflatex paper
  bibtex paper
  pdflatex paper
  pdflatex paper
cl> make my_paper

```

Maths!

<http://www.math.harvard.edu/texman/node17.html>

1. Inside text

Examples

- $\frac{1}{4} \rightarrow \frac{1}{4}$
- $G = 6.67 \times 10^{-8} \rightarrow G = 6.67 \times 10^{-8}$

If text is bold, make math symbols bold as well:

```
\textbf{This article discusses the \boldmath$\beta$ parameter}
```

This article discusses the β parameter

2. Equations

2.1 Numbered equations

```
\begin{equation}
P_{\text{mag}} = \frac{B^2}{\sqrt{4\pi\rho_o}}
\end{equation}
```

$$P_{\text{mag}} = \frac{B^2}{\sqrt{4\pi\rho_o}} \quad (1)$$

INCLUDE LABELING AND REFERENCING HERE!

2.2 Equations without numbering

Note that the `\boxed{...}` commands are putting the examples in boxes, but are not necessary for writing equations.

```
\begin{equation*}
\boxed{
P_{\text{mag}} = \frac{B^2}{\sqrt{4\pi\rho_o}}
}
\end{equation*}
```

$$P_{\text{mag}} = \frac{B^2}{\sqrt{4\pi\rho_o}}$$

Or simply put double `$`s on each side of equation:

```
$$
P_{\text{mag}} = \frac{B^2}{\sqrt{4\pi\rho_o}}
$$
```

$$P_{\text{mag}} = \frac{B^2}{\sqrt{4\pi\rho_o}}$$

This may not work for more complicated math, such as matrices. Apparently it is now best to use brackets rather than `$$`:

```
\[
P_{\text{mag}} = \frac{B^2}{\sqrt{4\pi\rho_o}}
\]
```

2.3 Aligning equations

```
\usepackage{amsmath}
...
\begin{align}
k_1 &= hf(x_n, y_n) \\
k_2 &= hf(x_n + \frac{1}{2}h, y_n + \frac{1}{2}k_1) \\
k_3 &= hf(x_n + \frac{1}{2}h, y_n + \frac{1}{2}k_2) \\
k_4 &= hf(x_n + h, y_n + k_3) \\
y_{n+1} &= y_n + \frac{1}{6}k_1 + \frac{1}{3}k_2 + \frac{1}{3}k_3 + \frac{1}{6}k_4 + O(h^5)
\end{align}
```

$$k_1 = hf(x_n, y_n) \tag{2}$$

$$k_2 = hf(x_n + \frac{1}{2}h, y_n + \frac{1}{2}k_1) \tag{3}$$

$$k_3 = hf(x_n + \frac{1}{2}h, y_n + \frac{1}{2}k_2) \tag{4}$$

$$k_4 = hf(x_n + h, y_n + k_3) \tag{5}$$

$$y_{n+1} = y_n + \frac{1}{6}k_1 + \frac{1}{3}k_2 + \frac{1}{3}k_3 + \frac{1}{6}k_4 + O(h^5) \tag{6}$$

$$\tag{7}$$

Can also remove numbering from aligned equations:

```
\begin{align*}
...
\end{align*}
```

3. Size of brackets, parentheses, etc.

In order of increasing size:

```
\big( ... \big)
\Big( ... \Big)
\bigg( ... \bigg)
\Bigg( ... \Bigg)
```

BETTER:

```
\left( ... \right)
```

to scale size of brackets to what is inside them!

Increase size of fraction inside text:

```
\cfrac{1}{2}
```

There are $\frac{1}{2}$ as many as there were.

There are $\frac{1}{2}$ as many as there were.

4. Referring to parts of equation

```
\usepackage{amsmath}
...
\begin{document}
...
\<command>[<width>][<depth>]{<stuff>}
```

Possible commands:

```
underbrace
overbrace
underbracket
overbracket
```

```
\usepackage{mathtools}
\usepackage{ragged2e}
\newlength\ubwidth
\newcommand\parunderbrace[2]{%
  \settowidth\ubwidth{${#1}$}
  \underbrace{#1}-{\parbox{\ubwidth}{\scriptsize RaggedRight#2}}}
```

Example:

```
\underbrace{P(X \mid O)}_{p_1} \propto \overbrace{P(X)P(O \mid X)}^{p_2} \\
\underbrace{P(X \mid O)}_{\text{This explains this part}} \propto \overbrace{P(X)P(O \mid X)}^{\text{And this explains the other part}}
```

$$\underbrace{P(X \mid O)}_{p_1} \propto \overbrace{P(X)P(O \mid X)}^{p_2}$$

$$\underbrace{P(X \mid O)}_{\text{This explains this part}} \propto \overbrace{P(X)P(O \mid X)}^{\text{And this explains the other part}}$$

5. Operations

5.1 Integrals

```
$$\int$ % indefinite integral
$\int_{x1}^{x2}$ % definite integral, between x1 and x2
```

5.2 Square root

```
$$\sqrt{2\ln(2)}$
```

5.3 Summation (and the multiplication version)

```
$$\sum_{n=1}^{\infty} 2^{-n} = 1$
```

$$\sum_{n=1}^{\infty} 2^{-n} = 1$$

```


$$P(D|M) \propto \prod_{i=0}^{N-1} \left\{ \exp \left[ -\frac{1}{2} \left[ \frac{y_i - y(x_i|a_j)}{\sigma} \right]^2 \right] \Delta y \right\}$$


```

$$P(D|M) \propto \prod_{i=0}^{N-1} \left\{ \exp \left[-\frac{1}{2} \left[\frac{y_i - y(x_i|a_j)}{\sigma} \right]^2 \right] \Delta y \right\}$$

Beamer

Read in beamer template here at some point.

```

\setbeamerfont{frametitle}{%
  font=\fontsize{16pt}{16pt}\itshape
  vs.
  size=\fontsize{}{ },
  family=\rmfamily,
  shape=scshape,
  series=...
}

\setbeamertemplate{<elementname>}[<predefinedoptions>]<args>
\addtobeamertemplate{<elementname>}{<pre-text>}{<post-text>}

```

Use the first to change something (bullet symbol). Use the second to add something (vertical space).

```

\begin{columns}
  \column{0.5\textwidth}
  content goes here
  \column{0.5\textwidth}
  more content here
\end{columns}

```

Questions and things to be added

Could make a new environment using `\tt` for stuff that doesn't apply to latex itself. . .

In `think_python.tex`, add part for using straight single quotes in verbatim environment.