

Think Python (and other useful things)

Allen B. Downey (and Laurel Farris)

July 22, 2016

<http://www.greenteapress.com/thinkpython/html/index.html>

Contents

1	The way of the program	4	3.14 Debugging	11
2	Variables, expressions, and statements	4	4 Case study: interface design	11
2.1	Values and types	4	4.1 TurtleWorld	11
2.2	Variables	4	4.2 Simple repetition	12
2.3	Variable names and keywords	4	4.3 Exercises	12
2.4	Operators and operands	4	4.4 Encapsulation	12
2.5	Expressions and statements	4	4.5 Generalization	12
2.6	Interactive mode and script mode	5	4.6 Interface design	12
2.7	Order of operations	5	4.7 Refactoring	12
2.8	String operations	5	4.8 A development plan	12
2.9	Comments	5	4.9 docstring	12
2.10	Debugging	5	4.10 Debugging	12
3	Functions	5	5 Conditionals and recursion	12
3.1	Function calls	5	5.1 Modulus operator	12
3.2	Type conversion functions	6	5.2 Boolean expressions	12
3.3	Math functions	6	5.3 Logical operators	13
3.4	Composition	6	5.4 Conditional execution	13
3.5	Adding new functions	7	5.5 Alternative execution	13
3.6	Definitions and uses	7	5.6	13
3.7	Flow of execution	8	6 Fruitful functions	13
3.8	Parameters and arguments	8	7 Iteration	13
3.9	Variables and parameters are local	9	8 Strings	14
3.10	Stack diagrams	9	8.1 A string is a sequence	14
3.11	Fruitful functions and void functions	10	8.2 len	14
3.12	Why functions?	10	8.3 Traversal with a for loop	14
3.13	Importing with from	10		

8.4	String slices	14	14.2	Reading and writing	25
8.5	Strings are immutable	14	14.3	Format operator	25
8.6	Searching	14	14.4	Filenames and paths	26
8.7	Looping and counting	14	14.5	Catching exceptions	26
8.8	String methods	14	14.6	Databases	26
8.9	The in operator	15	14.7	Pickling	27
8.10	String comparison	15	14.8	Pipes	27
8.11	Debugging	15	14.9	Writing modules	27
9	Case study: word play	16	14.10	Debugging	28
10	Lists	16	15	Classes and objects	29
10.1	A list is a sequence	16	15.1	User-defined types	29
10.2	Lists are mutable	16	15.2	Attributes	29
10.3	Traversing a list	17	15.3	Rectangles	30
10.4	List operations	17	15.4	Instances as return values	31
10.5	List slices	18	15.5	Objects are mutable	31
10.6	List methods	18	15.6	Copying	31
10.7	Map, filter, and reduce	18	15.7	Debugging	32
10.8	Deleting elements	18	16	Classes and functions	34
10.9	Lists and strings	18	17	Classes and methods	35
10.10	Objects and values	18	18	Inheritance	36
10.11	Aliasing	18	19	Case study: Tkinter	37
10.12	List arguments	18	20	Debugging	38
10.13	Debugging	18	21	Analysis of Algorithms	39
11	Dictionaries	18	22	Lumpy	40
12	Tuples	18	Glossary		40
12.1	Tuples are immutable	18	23	Quick reference	41
12.2	Tuple assignment	19	Execution		41
12.3	Tuples as return values	20	Debugging		41
12.4	Variable-length argument tuples	20	Strings		41
12.5	Lists and tuples	21	Mathematical operators		41
12.6	Dictionaries and tuples	22	bitwise operators		41
12.7	Comparing tuples	22	logical operators		41
12.8	Sequences of sequences	23	relational		41
12.9	Debugging	24	boolean		41
13	Case study: data structure selection	24			
14	Files	24			
14.1	Persistence	24			

conditionals	41	FITS files	43
Looping	41	Dynamic memory allocation	43
I/O	41	Classes	43
Type changes	41	Plotting	43
Math	42	Imaging	44
Lists	42	Legend	44
numpy arrays	42	Save figures	44
Functions	42		

1 The way of the program

The single most important skill for a computer scientist is **problem solving**. Problem solving means the ability to formulate problems, think creatively about solutions, and express a solution clearly and accurately. As it turns out, the process of learning to program is an excellent opportunity to practice problem-solving skills.

...

2 Variables, expressions, and statements

2.1 Values and types

If you are not sure what type a value has, the interpreter can tell you:

```
>>> type('Hello, World!')
<type 'str',>
>>> type(17)
<type 'int',>
>>> type(3.2)
<type 'float',>
```

2.2 Variables

An **assignment statement** creates new variables and gives them values.

2.3 Variable names and keywords

Variable names can be arbitrarily long. They can contain both letters and numbers, but they have to begin with a letter. It is legal to use uppercase letters, but it is a good idea to begin variable names with a lowercase letter.

The interpreter uses **keywords** to recognize the structure of the program, and they cannot be used as variable names.

Python 2 has 31 keywords:

and	del	from	not	while
as	elif	global	or	with
assert	else	if	pass	yield
break	except	import	print	
class	exec	in	raise	
continue	finally	is	return	
def	for	lambda	try	

2.4 Operators and operands

2.5 Expressions and statements

An **expression** is a combination of values, variables, and operators. A value all by itself is considered an expression, and so is a variable, so the following are all legal expressions (assuming that the variable `x` has been assigned a value):

```
17
x
x + 17
```

A **statement** is a unit of code that the Python interpreter can execute. We have seen two kinds of statement: print and assignment.

Technically an expression is also a statement, but it is probably simpler to think of them as different things. The important difference is that an expression has a value; a statement does not.

2.6 Interactive mode and script mode

2.7 Order of operations

- Parentheses
- Exponents
- Multiplication/Division
- Addition/Subtraction

2.8 String operations

To perform a concatenation between two strings:

```
>> a = 1
>> print 'list_', + str(a) + '.txt',
list_1.txt
>> print 'Spam',*3
SpamSpamSpam
```

2.9 Comments

It is reasonable to assume that the reader can figure out *what* the code does; it is much more useful to explain *why*.

This comment is redundant with the code and useless:

```
v = 5      # assign 5 to v
```

This comment contains useful information that is not in the code:

```
v = 5      # velocity in meters/second.
```

Good variable names can reduce the need for comments, but long names can make complex expressions hard to read, so there is a tradeoff.

2.10 Debugging

3 Functions

3.1 Function calls

In the context of programming, a **function** is a named sequence of statements that performs a computation. To define a function, specify the name and sequence of statements. Then “call” the function by name later. Example of a **function call**:

```
>> type(32)
<type 'int',>
```

The name of the function is `type`. The expression in parentheses is called the **argument** of the function. The result, for this function, is the type of the argument.

It is common to say that a function “takes” an argument and “returns” a result. The result is called the **return value**.

3.2 Type conversion functions

Python provides built-in functions that convert values from one type to another. The `int` function takes any value and converts it to an integer:

```
>>> int('32,')
32
>>> int(3.999)
3
```

Note that decimals are truncated, not rounded.

The `float` function converts integers and strings to floating-point numbers:

```
>>> float(32)
32.0
>>> float('3.14159,')
3.14159
```

The `str` function converts its argument to a string:

```
>>> str(32)
'32,'
>>> str(3.14159)
'3.14159,'
```

3.3 Math functions

Python has a `math` module that provides most of the familiar mathematical functions. A **module** is a file that contains a collection of related functions. Modules must be imported before they can be used (such as `>>> import math`, which creates a **module object**) named `math`. If you print the module object, you get some information about it:

```
>>> print math
<module 'math' from '/usr/lib/python2.5/lib-dynload/math.so,>
```

The module object contains the functions and variables defined in the module. To access one of the functions, you have to specify the name of the module and the name of the function, separated by a dot (this format is called **dot notation**).

```
>>> ratio = signal_power / noise_power
>>> decibels = 10 * math.log10(ratio)

>>> radians = 0.7
>>> height = math.sin(radians)
```

The first example computes the logarithm base 10 of the signal-to-noise ratio. The `math` module also provides a function called `log` that computes logarithms base *e*.

The second example finds the sine of `radians`. Trigonometric functions (`sin`, `cos`, `tan`, etc.) **take arguments in radians**.

The expression `math.pi` gets the variable `pi` from the `math` module, which is accurate to about 15 digits.

3.4 Composition

So far, we have looked at the elements of a program—variables, expressions, and statements—in isolation. One of the most useful features of programming languages is their ability to take small building blocks and **compose** them. For example, the argument of a function can be any kind of expression, including arithmetic operators and function calls:

```
x = math.sin(degrees / 360.0 * 2 * math.pi)
x = math.exp(math.log(x+1))
```

3.5 Adding new functions

A **function definition** specifies the name of a new function and the sequence of statements that execute when the function is called, e.g.:

```
def do_nothing():  
    print "Doing nothing..."
```

`def` is a keyword that indicates that this is a function definition. The name of the function is `do_nothing`. You should avoid having a variable and a function with the same name. The empty parentheses indicate that this function doesn't take any arguments.

The first line of the function definition is called the **header**; the rest is called the **body**. The header has to end with a colon and the body has to be indented. By convention, the indentation is always four spaces (see Section 3.13).

If you type a function definition in interactive mode, the interpreter prints ellipses (...) to let you know that the definition isn't complete:

```
>>> def print_lyrics():  
...     print "I,m a lumberjack, and I,m okay...",  
...     print "I sleep all night and I work all day...",  
... 
```

To end the function, enter an empty line (this is not necessary in a script).

Defining a function creates a variable with the same name.

```
>>> print print_lyrics  
<function print_lyrics at 0xb7e99e>  
>>> type(print_lyrics)  
<type 'function'>
```

The value of `print_lyrics` is a **function object**, which has type `'function'`.

The syntax for calling the new function is the same as for built-in functions:

```
>>> print_lyrics()  
I,m a lumberjack, and I,m okay.  
I sleep all night and I work all day.
```

Once you have defined a function, you can use it inside another function. For example, to repeat the previous refrain, we could write a function called `repeat_lyrics`:

```
def repeat_lyrics():  
    print_lyrics()  
    print_lyrics()
```

And then call `repeat_lyrics`:

```
>>> repeat_lyrics()  
I,m a lumberjack, and I,m okay.  
I sleep all night and I work all day.  
I,m a lumberjack, and I,m okay.  
I sleep all night and I work all day.
```

3.6 Definitions and uses

Pulling together the code fragments from the previous section, the whole program looks like this:

```
def print_lyrics():
    print "I,m a lumberjack, and I,m okay.,,
    print "I sleep all night and I work all day.,,

def repeat_lyrics():
    print_lyrics()
    print_lyrics()

repeat_lyrics()
```

This program contains two function definitions: `print_lyrics` and `repeat_lyrics`. Function definitions get executed just like other statements, but the effect is to create function objects. The statements inside the function do not get executed until the function is called, and the function definition generates no output. As you might expect, you have to create a function before you can execute it. In other words, the function definition has to be executed before the first time it is called.

3.7 Flow of execution

In order to ensure that a function is defined before its first use, you have to know the order in which statements are executed, which is called the **flow of execution**.

Execution always begins at the first statement of the program. Statements are executed one at a time, in order from top to bottom.

Function definitions do not alter the flow of execution of the program, but remember that statements inside the function are not executed until the function is called.

A function call is like a detour in the flow of execution. Instead of going to the next statement, the flow jumps to the body of the function, executes all the statements there, and then comes back to pick up where it left off.

That sounds simple enough, until you remember that one function can call another. While in the middle of one function, the program might have to execute the statements in another function. But while executing that new function, the program might have to execute yet another function!

Fortunately, Python is good at keeping track of where it is, so each time a function completes, the program picks up where it left off in the function that called it. When it gets to the end of the program, it terminates.

Whatâ€™s the moral of this sordid tale? When you read a program, you donâ€™t always want to read from top to bottom. Sometimes it makes more sense if you follow the flow of execution.

3.8 Parameters and arguments

Some of the built-in functions we have seen require arguments. For example, when you call `math.sin` you pass a number as an argument. Some functions take more than one argument: `math.pow` takes two, the base and the exponent.

Inside the function, the arguments are assigned to variables called **parameters**. Here is an example of a user-defined function that takes an argument:

```
def print_twice(bruce):
    print bruce
    print bruce
```

This function assigns the argument to a parameter named `bruce`. When the function is called, it prints the value of the parameter (whatever it is) twice.

This function works with any value that can be printed.

```
>>> print_twice('Spam,')
Spam
Spam
>>> print_twice(17)
```



```

17
17
>> print_twice(math.pi)
3.14159265359
3.14159265359

```

The same rules of composition that apply to built-in functions also apply to user-defined functions, so we can use any kind of expression as an argument for `print_twice`:

```

>> print_twice('Spam ',*4)
Spam Spam Spam Spam
Spam Spam Spam Spam
>> print_twice(math.cos(math.pi))
-1.0
-1.0

```

The argument is evaluated before the function is called, so in the examples the expressions `'Spam '*4` and `math.cos(math.pi)` are only evaluated once.

You can also use a variable as an argument:

```

>> michael = 'Eric, the half a bee.'
>> print_twice(michael)
Eric, the half a bee.
Eric, the half a bee.

```

The name of the variable we pass as an argument (`michael`) has nothing to do with the name of the parameter (`bruce`). It doesn't matter what the value was called back home (in the caller); here in `print_twice`, we call everybody `bruce`.

3.9 Variables and parameters are local

When you create a variable inside a function, it is **local**, which means that it only exists inside the function. For example:

```

def cat_twice(part1, part2):
    cat = part1 + part2
    print_twice(cat)

```

This function takes two arguments, concatenates them, and prints the result twice. Here is an example that uses it:

```

>> line1 = 'Bing tiddle '
>> line2 = 'tiddle bang.'
>> cat_twice(line1, line2)
Bing tiddle tiddle bang.
Bing tiddle tiddle bang.

```

When `cat_twice` terminates, the variable `cat` is destroyed. If we try to print it, we get an exception:

```

>> print cat
NameError: name 'cat' is not defined

```

Parameters are also local. For example, outside `print_twice`, there is no such thing as `bruce`.

3.10 Stack diagrams

Meh.

3.11 Fruitful functions and void functions

Some of the functions we are using, such as the math functions, yield results; for lack of a better name, I call them **fruitful functions**. Other functions, like `print_twice`, perform an action but don't return a value. They are called **void functions**.

When you call a fruitful function, you almost always want to do something with the result; for example, you might assign it to a variable or use it as part of an expression:

```
x = math.cos(radians)
golden = (math.sqrt(5) + 1) / 2
```

When you call a function in interactive mode, Python displays the result:

```
>>> math.sqrt(5)
2.2360679774997898
```

But in a script, if you call a fruitful function all by itself, the return value is lost forever.

```
math.sqrt(5)
```

This script computes the square root of 5, but since it doesn't store or display the result, it is not very useful.

Void functions might display something on the screen or have some other effect, but they don't have a return value. If you try to assign the result to a variable, you get a special value called `None`.

```
>>> result = print_twice('Bing')
Bing
Bing
>>> print result
None
```

The value `None` is not the same as the string `'None'`. It is a special value that has its own type:

```
>>> print type(None)
<type 'NoneType'>
```

The functions we have written so far are all void. We will start writing fruitful functions in a few chapters.

3.12 Why functions?

It may not be clear why it is worth the trouble to divide a program into functions. There are several reasons:

- Creating a new function gives you an opportunity to name a group of statements, which makes your program easier to read and debug.
- Functions can make a program smaller by eliminating repetitive code. Later, if you make a change, you only have to make it in one place.
- Dividing a long program into functions allows you to debug the parts one at a time and then assemble them into a working whole.
- Well-designed functions are often useful for many programs. Once you write and debug one, you can reuse it.

3.13 Importing with from

Python provides two ways to import modules; we have already seen one:

```
>>> import math
>>> print math
<module 'math' (built-in)>
>>> print math.pi
3.14159265359
```

If you import `math`, you get a module object named `math`. The module object contains constants like `pi` and functions like `sin` and `exp`.

But if you try to access `pi` directly, you get an error.

```
>> print pi
Traceback (most recent call last):
  File "<stdin>,,, line 1, in <module>"
NameError: name 'pi' is not defined
```

As an alternative, you can import an object from a module like this:

```
>> from math import pi
```

Now you can access `pi` directly, without dot notation.

```
>> print pi
3.14159265359
```

Or you can use the star operator to import *everything* from the module:

```
>> from math import *
>> cos(pi)
-1.0
```

The advantage of importing everything from the `math` module is that your code can be more concise. The disadvantage is that there might be conflicts between names defined in different modules, or between a name from a module and one of your variables.

3.14 Debugging

If you are using a text editor to write your scripts, you might run into problems with spaces and tabs. The best way to avoid these problems is to use spaces exclusively (no tabs). Most text editors that know about Python do this by default, but some don't.

Tabs and spaces are usually invisible, which makes them hard to debug, so try to find an editor that manages indentation for you.

Also, don't forget to save your program before you run it. Some development environments do this automatically, but some don't. In that case the program you are looking at in the text editor is not the same as the program you are running.

Debugging can take a long time if you keep running the same, incorrect, program over and over!

Make sure that the code you are looking at is the code you are running. If you're not sure, put something like `print 'hello'` at the beginning of the program and run it again. If you don't see `hello`, you're not running the right program!

4 Case study: interface design

4.1 TurtleWorld

A **package** is a collection of modules.

```
from package_name.module_name import *
```

This should import all functions from the module. If you downloaded the Package modules but did not install them as a package, you can either work in the directory that contains the Package files, or add that directory to Python's search path. Then you can import Module like this:

```

from Module import *

from Package.Module import *
var1 = Module()
var2 = Instance() # One of several possible instances
func(var2, args)

```

4.2 Simple repetition

4.3 Exercises

4.4 Encapsulation

4.5 Generalization

4.6 Interface design

4.7 Refactoring

4.8 A development plan

4.9 docstring

4.10 Debugging

5 Conditionals and recursion

5.1 Modulus operator

The **Modulus operator** works on integers and yields the remainder when the first operand is divided by the second.

```

>> quotient = 7 / 3
>> print quotient
2
>> remainder = 7 % 3
>> print remainder
1

```

The modulus operator turns out to be surprisingly useful. For example, you can check whether one number is divisible by another. If $x \% y$ is zero, then x is divisible by y .

Also, you can extract the right-most digit or digits from a number. For example, $x \% 10$ yields the right-most digit of x (in base 10). Similarly $x \% 100$ yields the last two digits.

5.2 Boolean expressions

```

>> 5 == 5
True
>> 5 == 6
False

```

True and False are special values that belong to the type `bool`; they are not strings.

Relational operators:

- `==`
- `!=`
- `>`
- `<`
- `>=`
- `<=`

5.3 Logical operators

- `and`
- `or`
- `not`

The `not` operator negates a boolean expression, so `not (x > y)` is true if `x > y` is false, that is, if `x` is less than or equal to `y`.

Strictly speaking, the operands of the logical operators should be boolean expressions, but Python is not very strict. Any nonzero number is interpreted as “true.”

```
>>> 17 and True
True
```

This flexibility can be useful, but there are some subtleties to it that might be confusing. You might want to avoid it (unless you know what you are doing).

5.4 Conditional execution

The `if` **statement**:

```
if x > 0:
    print ,x is positive,
```

The boolean expression after `if` is called the **condition**. If it is true, then the indented statement gets executed. If not, nothing happens. `if` statements have the same structure as function definitions: a header followed by an indented body. Statements like this are called **compound statements**.

There is no limit on the number of statements that can appear in the body, but there has to be at least one. Occasionally, it is useful to have a body with no statements (usually as a place keeper for code you haven’t written yet). In that case, you can use the `pass` statement, which does nothing.

```
if x < 0:
    pass    # Need to handle negative values
```

5.5 Alternative execution

5.6

6 Fruitful functions

7 Iteration

8 Strings

8.1 A string is a sequence

8.2 len

8.3 Traversal with a for loop

8.4 String slices

8.5 Strings are immutable

8.6 Searching

8.7 Looping and counting

8.8 String methods

A **method** is similar to a function - it takes arguments and returns a value, but the syntax is different. For example, the method `upper` takes a string and returns a new string with all uppercase letters:

Instead of the function syntax `upper(word)`, it uses the method syntax `word.upper()`.

```
>> word = 'banana',
>> new_word = word.upper()
>> print new_word
BANANA
```

This form of dot notation specifies the name of the method, `upper`, and the name of the string to apply the method to, `word`. The empty parentheses indicate that this method takes no argument.

A method call is called an **invocation**; in this case, we would say that we are invoking `upper` on the `word`.

As it turns out, there is a string method named `find` that is remarkably similar to the function we wrote:

```
>> word = 'banana',
>> index = word.find('a')
>> print index
1
```

In this example, we invoke `find` on `word` and pass the letter we are looking for as a parameter.

Actually, the `find` method is more general than our function; it can find substrings, not just characters:

```
>> word.find('na')
2
```

It can take as a second argument the index where it should start:

```
>> word.find('na', 3)
4
```

And as a third argument the index where it should stop:

```
>> name = 'bob',
>> name.find('b', 1, 2)
-1
```

This search fails because `b` does not appear in the index range from `1` to `2` (not including `2`).

8.9 The in operator

8.10 String comparison

8.11 Debugging

9 Case study: word play

10 Lists

10.1 A list is a sequence

Like a string, a **list** is a sequence of values. In a string, the values are characters; in a list, they can be any type. The values in a list are called **elements** or sometimes **items**.

There are several ways to create a new list; the simplest is to enclose the elements in square brackets:

```
[10, 20, 30, 40]
[,crunchy frog,, ,ram bladder,, ,lark vomit,]
```

The elements of a list don't have to be the same type. The following list contains a string, a float, an integer, and (lo!) another list:

```
[,spam,, 2.0, 5, [10, 20]]
```

A list within another list is **nested**.

A list that contains no elements is called an *empty list*; you can create one with empty brackets, `[]`.

As you might expect, you can assign list values to variables:

```
>> cheeses = [,Cheddar,, ,Edam,, ,Gouda,]
>> numbers = [17, 123]
>> empty = []
>> print cheeses, numbers, empty
[,Cheddar,, ,Edam,, ,Gouda,] [17, 123] []
```

10.2 Lists are mutable

The syntax for *accessing* the elements of a list is the same as for accessing the characters of a string - the bracket operator. The expression inside the brackets specifies the index. Remember that the indices start at 0:

```
>> print cheeses[0]
Cheddar
```

Unlike strings, lists are mutable. When the bracket operator appears on the left side of an assignment, it identifies the element of the list that will be assigned.

```
>> numbers = [17, 123]
>> numbers[1] = 5
>> print numbers
[17, 5]
```

The one-eth element of numbers, which used to be 123, is now 5.

You can think of a list as a relationship between indices and elements. This relationship is called a **mapping**; each index “maps to” one of the elements.

List indices work the same way as string indices:

- Any integer expression can be used as an index.
- If you try to read or write an element that does not exist, you get an `IndexError`.
- If an index has a negative value, it counts backward from the end of the list.

The `in` operator also works on lists.


```
>> cheeses = ['Cheddar', 'Edam', 'Gouda']
>> 'Edam' in cheeses
True
>> 'Brie' in cheeses
False
```

10.3 Traversing a list

The most common way to traverse the elements of a list is with a `for` loop. The syntax is the same as for strings:

```
for cheese in cheeses:
    print cheese
```

This works well if you only need to read the elements of the list. But if you want to write or update the elements, you need the indices. A common way to do that is to combine the functions `range` and `len`:

```
for i in range(len(numbers)):
    numbers[i] = numbers[i] * 2
```

This loop traverses the list and updates each element. `len` returns the number of elements in the list. `range` returns a list of indices from 0 to $n - 1$, where n is the length of the list. Each time through the loop `i` gets the index of the next element. The assignment statement in the body uses `i` to read the old value of the element and to assign the new value.

A `for` loop over an *empty* list never executes the body:

```
for x in []:
    print 'This never happens.'
```

Although a list can contain another list, *the nested list still counts as a single element*. The length of this list is 4:

```
['spam', 1, ['Brie', 'Roquefort', 'Pol le Veq'], [1, 2, 3]]
```

10.4 List operations

IMPORTANT: these are not mathematical operations for lists. Convert to numpy arrays: `a = np.array(a)`

The following doesn't work because `x` is a list, not an array.

```
>> x = [1,2,3]
>> y = x**2
```

The `+` operator concatenates lists:

```
>> a = [1, 2, 3]
>> b = [4, 5, 6]
>> c = a + b
>> print c
[1, 2, 3, 4, 5, 6]
```

Similarly, the `*` operator repeats a list a given number of times:

```
>> [0] * 4
[0, 0, 0, 0]
>> [1, 2, 3] * 3
[1, 2, 3, 1, 2, 3, 1, 2, 3]
```

The first example repeats `[0]` four times. The second example repeats the list `[1,2,3]` three times.

10.5 List slices

10.6 List methods

10.7 Map, filter, and reduce

10.8 Deleting elements

10.9 Lists and strings

10.10 Objects and values

10.11 Aliasing

10.12 List arguments

10.13 Debugging

11 Dictionaries

12 Tuples

12.1 Tuples are immutable

A tuple is a sequence of values. The values can be any type, and they are indexed by integers, so in that respect tuples are a lot like lists. *The important difference is that tuples are immutable.*

Syntactically, a tuple is a comma-separated list of values:

```
>> t = ('a', 'b', 'c', 'd', 'e')
```

Parentheses are common, but not necessary.

To create a tuple with a single element, you have to include a final comma:

```
>> t1 = 'a',  
>> type(t1)  
<type 'tuple',>
```

A value in parentheses is not a tuple:

```
>> t2 = ('a')  
>> type(t2)  
<type 'str',>
```

Another way to create a tuple is the built-in function `tuple`. With no argument, it creates an empty tuple:

```
>> t = tuple()  
>> print t  
()
```

If the argument is a sequence (string, list or tuple), the result is a tuple with the elements of the sequence:

```
>> t = tuple('lupins')  
>> print t  
(,l,, ,u,, ,p,, ,i,, ,n,, ,s,)
```

Most list operators also work on tuples. The bracket operator indexes an element:

```
>> t = ('a', 'b', 'c', 'd', 'e')
>> print t[0]
'a'
```

And the slice operator selects a range of elements.

```
>> print t[1:3]
('b', 'c')
```

But if you try to modify one of the elements of the tuple, you get an error:

```
>> t[0] = 'A'
TypeError: object doesn't support item assignment
```

You can't modify the elements of a tuple, but you can *replace* one tuple with another:

```
>> t = ('A',) + t[1:]
>> print t
('A', 'b', 'c', 'd', 'e')
```

12.2 Tuple assignment

It is often useful to swap the values of two variables. With conventional assignments, you have to use a temporary variable. For example, to swap `a` and `b`:

```
>> temp = a
>> a = b
>> b = temp
```

This solution is cumbersome; **tuple assignment** is more elegant:

```
>> a, b = b, a
```

The left side is a tuple of variables; the right side is a tuple of expressions. Each value is assigned to its respective variable. All the expressions on the right side are evaluated before any of the assignments.

The number of variables on the left and the number of values on the right have to be the same:

```
>> a, b = 1, 2, 3
ValueError: too many values to unpack
```

More generally, the right side can be any kind of sequence (string, list or tuple). For example, to split an email address into a user name and a domain, you could write:

```
>> addr = 'monty@python.org'
>> uname, domain = addr.split('@')
```

The return value from `split` is a list with two elements; the first element is assigned to `uname`, the second to `domain`.

```
>> print uname
monty
>> print domain
python.org
```

12.3 Tuples as return values

Strictly speaking, a function can only return one value, but if the value is a tuple, the effect is the same as returning multiple values. For example, if you want to divide two integers and compute the quotient and remainder, it is inefficient to compute `x/y` and then `x%y`. It is better to compute them both at the same time.

The built-in function `divmod` takes two arguments and returns a tuple of two values, the quotient and remainder. You can store the result as a tuple:

```
>> t = divmod(7, 3)
>> print t
(2, 1)
```

Or use tuple assignment to store the elements separately:

```
>> quot, rem = divmod(7, 3)
>> print quot
2
>> print rem
1
```

Here is an example of a function that returns a tuple:

```
def min_max(t):
    return min(t), max(t)
```

`max` and `min` are built-in functions that find the largest and smallest elements of a sequence. `min_max` computes both and returns a tuple of two values.

12.4 Variable-length argument tuples

Functions can take a variable number of arguments. A parameter name that begins with `*` **gathers** arguments into a tuple. For example, `printall` takes any number of arguments and prints them:

```
def printall(*args):
    print args
```

The gather parameter can have any name you like, but `args` is conventional. Here's how the function works:

```
>> printall(1, 2.0, ,3,)
(1, 2.0, ,3,)
```

The complement of gather is `scatter`. If you have a sequence of values and you want to pass it to a function as multiple arguments, you can use the `*` operator. For example, `divmod` takes exactly two arguments; it doesn't work with a tuple:

```
>> t = (7, 3)
>> divmod(t)
TypeError: divmod expected 2 arguments, got 1
```

But if you scatter the tuple, it works:

```
>> divmod(*t)
(2, 1)
```

12.5 Lists and tuples

`zip` is a built-in function that takes two or more sequences and “zips” them into a list of tuples where each tuple contains one element from each sequence. In Python 3, `zip` returns an iterator of tuples, but for most purposes, an iterator behaves like a list.

This example zips a string and a list:

```
>> s = ,abc,
>> t = [0, 1, 2]
>> zip(s, t)
[(,a,, 0), (,b,, 1), (,c,, 2)]
```

The result is a list of tuples where each tuple contains a character from the string and the corresponding element from the list.

If the sequences are not the same length, the result has the length of the shorter one.

```
>> zip(,Anne,, ,Elk,)
[(,A,, ,E,),(,n,, ,l,),(,n,, ,k,)]
```

You can use tuple assignment in a `for` loop to traverse a list of tuples:

```
t = [(,a,, 0), (,b,, 1), (,c,, 2)]
for letter, number in t:
    print number, letter
```

Each time through the loop, Python selects the next tuple in the list and assigns the elements to `letter` and `number`. The output of this loop is:

```
0 a
1 b
2 c
```

If you combine `zip`, `for` and tuple assignment, you get a useful idiom for traversing two (or more) sequences at the same time. For example, `has_match` takes two sequences, `t1` and `t2`, and returns `True` if there is an index `i` such that `t1[i] == t2[i]`:

```
def has_match(t1, t2):
    for x, y in zip(t1, t2):
        if x == y:
            return True
    return False
```

If you need to traverse the elements of a sequence and their indices, you can use the built-in function `enumerate`:

```
for index, element in enumerate(,abc,):
    print index, element
```

The output of this loop is:

```
0 a
1 b
2 c
```

Again.

12.6 Dictionaries and tuples

Dictionaries have a method called `items` that returns a list of tuples, where each tuple is a key-value pair.

```
>> d = {'a':0, 'b':1, 'c':2}
>> t = d.items()
>> print t
[('a', 0), ('c', 2), ('b', 1)]
```

As you should expect from a dictionary, the items are in no particular order. In Python 3, `items` returns an iterator, but for many purposes, iterators behave like lists.

Going in the other direction, you can use a list of tuples to initialize a new dictionary:

```
>> t = [('a', 0), ('c', 2), ('b', 1)]
>> d = dict(t)
>> print d
{'a': 0, 'c': 2, 'b': 1}
```

Combining `dict` with `zip` yields a concise way to create a dictionary:

```
>> d = dict(zip('abc', range(3)))
>> print d
{'a': 0, 'c': 2, 'b': 1}
```

The dictionary method `update` also takes a list of tuples and adds them, as key-value pairs, to an existing dictionary.

Combining `items`, tuple assignment and `for`, you get the idiom for traversing the keys and values of a dictionary:

```
for key, val in d.items():
    print val, key
```

The output of this loop is:

```
0 a
2 c
1 b
```

Again. It is common to use tuples as keys in dictionaries (primarily because you can't use lists). For example, a telephone directory might map from last-name, first-name pairs to telephone numbers. Assuming that we have defined `last`, `first` and `number`, we could write:

```
directory[last,first] = number
```

The expression in brackets is a tuple. We could use tuple assignment to traverse this dictionary.

```
for last, first in directory:
    print first, last, directory[last,first]
```

This loop traverses the keys in `directory`, which are tuples. It assigns the elements of each tuple to `last` and `first`, then prints the name and corresponding telephone number.

12.7 Comparing tuples

The relational operators work with tuples and other sequences; Python starts by comparing the first element from each sequence. If they are equal, it goes on to the next elements, and so on, until it finds elements that differ. Subsequent elements are not considered (even if they are really big).

```
>> (0, 1, 2) < (0, 3, 4)
True
>> (0, 1, 2000000) < (0, 3, 4)
True
```

The `sort` function works the same way. It sorts primarily by first element, but in the case of a tie, it sorts by second element, and so on.

This feature lends itself to a pattern called **DSU** for

Decorate	a sequence by building a list of tuples with one or more sort keys preceding the elements from the sequence,
Sort	the list of tuples, and
Undecorate	by extracting the sorted elements of the sequence.

For example, suppose you have a list of words and you want to sort them from longest to shortest:

```
def sort_by_length(words):
    t = []
    for word in words:
        t.append((len(word), word))

    t.sort(reverse=True)

    res = []
    for length, word in t:
        res.append(word)
    return res
```

The first loop builds a list of tuples, where each tuple is a word preceded by its length.

`sort` compares the first element, length, first, and only considers the second element to break ties. The keyword argument `reverse=True` tells `sort` to go in decreasing order.

The second loop traverses the list of tuples and builds a list of words in descending order of length.

12.8 Sequences of sequences

I have focused on lists of tuples, but almost all of the examples in this chapter also work with lists of lists, tuples of tuples, and tuples of lists. To avoid enumerating the possible combinations, it is sometimes easier to talk about sequences of sequences.

In many contexts, the different kinds of sequences (strings, lists and tuples) can be used interchangeably. So how and why do you choose one over the others?

To start with the obvious, strings are more limited than other sequences because the elements have to be characters. They are also immutable. If you need the ability to change the characters in a string (as opposed to creating a new string), you might want to use a list of characters instead.

Lists are more common than tuples, mostly because they are mutable. But there are a few cases where you might prefer tuples:

1. In some contexts, like a `return` statement, it is syntactically simpler to create a tuple than a list. In other contexts, you might prefer a list.
2. If you want to use a sequence as a dictionary key, you have to use an immutable type like a tuple or string.
3. If you are passing a sequence as an argument to a function, using tuples reduces the potential for unexpected behavior due to aliasing.

Because tuples are immutable, they don't provide methods like `sort` and `reverse`, which modify existing lists. But Python provides the built-in functions `sorted` and `reversed`, which take any sequence as a parameter and return a new list with the same elements in a different order.

12.9 Debugging

Lists, dictionaries and tuples are known generically as **data structures**; in this chapter we are starting to see compound data structures, like lists of tuples, and dictionaries that contain tuples as keys and lists as values. Compound data structures are useful, but they are prone to what I call **shape errors**; that is, errors caused when a data structure has the wrong type, size or composition. For example, if you are expecting a list with one integer and I give you a plain old integer (not in a list), it won't work.

To help debug these kinds of errors, I have written a module called `structshape` that provides a function, also called `structshape`, that takes any kind of data structure as an argument and returns a string that summarizes its shape. You can download it from <http://thinkpython.com/code/structshape.py>

Here's the result for a simple list:

```
>> from structshape import structshape
>> t = [1,2,3]
>> print structshape(t)
list of 3 int
```

A fancier program might write "list of 3 ints," but it was easier not to deal with plurals. Here's a list of lists:

```
>> t2 = [[1,2], [3,4], [5,6]]
>> print structshape(t2)
list of 3 list of 2 int
```

If the elements of the list are not the same type, `structshape` groups them, in order, by type:

```
>> t3 = [1, 2, 3, 4.0, ,5,, ,6,, [7], [8], 9]
>> print structshape(t3)
list of (3 int, float, 2 str, 2 list of int, int)
```

Here's a list of tuples:

```
>> s = ,abc,
>> lt = zip(t, s)
>> print structshape(lt)
list of 3 tuple of (int, str)
```

And here's a dictionary with 3 items that map integers to strings.

```
>> d = dict(lt)
>> print structshape(d)
dict of 3 int->str
```

If you are having trouble keeping track of your data structures, `structshape` can help.

13 Case study: data structure selection

14 Files

14.1 Persistence

Most of the programs we have seen so far are transient in the sense that they run for a short time and produce some output, but when they end, their data disappears. If you run the program again, it starts with a clean slate.

Other programs are **persistent**: they run for a long time (or all the time); they keep at least some of their data in permanent storage (a hard drive, for example); and if they

<http://www.greenteapress.com/thinkpython/html/thinkpython015.html>

shut down and restart, they pick up where they left off.

Examples of persistent programs are operating systems, which run pretty much whenever a computer is on, and web servers, which run all the time, waiting for requests to come in on the network.

One of the simplest ways for programs to maintain their data is by reading and writing text files. We have already seen programs that read text files; in this chapter we will see programs that write them.

An alternative is to store the state of the program in a database. In this chapter I will present a simple database and a module, `pickle`, that makes it easy to store program data.

14.2 Reading and writing

```
file:
f=open('file.txt','rwa') [read, write, append]
s=f.readline()
f.close(),
alternatively:
for line in f:
    print line
```

The `write` method puts data into the file. To write a file, you have to open it with mode 'w' as a second parameter:

```
>>> fout = open('output.txt', 'w')
>>> print fout
<open file 'output.txt', mode 'w' at 0
x7fa44614c420>
>>> line1 = 'This here's the wattle,\n'
>>> fout.write(line1)
```

If the file already exists, opening it in write mode clears out the old data and starts fresh, so be careful! If the file doesn't exist, a new one is created. The file object keeps track of where it is, so if you call `write` again, it adds the new data to the end.

```
>>> line2 = "the emblem of our land.\n"
>>> fout.write(line2)
```

When you are done writing, you have to close the file.

```
>>> fout.close()
```

14.3 Format operator

```
'''
Formatted output
> print 'the number is {:.#e|:nd|:n.nf|:ns}'.
    format(x)
    exponential, integer, float, string
General syntax:
'''
template.format(var_1,var_2,...var_n)
# template:
#'{[field][!conversion]:[spec]}'
field = index of variables listed in .format()
conversion = int, float, string, etc.
spec = specifier
[[ fill ][ align ][ sign ][#][0][minwidth][.prec][type
]
```

```
align:
<(left,default)
>(right)
=(padding after sign, before digits)
^(center)
0: zero padding (same as '=' and fill char of
0)
type: e,f,g(general)

# Including text:
print 'Variable 2 is {1} and variable 1 is {0}'
    .format(var_1,var_2)

'{:8d}asdfad{:8.2f}'.format(i,f)
formats: {:nd},{:n.nf},{:ns}
# n=number (width.precision), d=integer, f=
float, s=string
#----- How to use a variable for width
?? -----#
```

The argument of `write` has to be a string, so if we want to put other values in a file, we have to convert them to strings. The easiest way to do that is with `str`:

```
>>> x = 52
>>> fout.write(str(x))
```

An alternative is to use the **format operator**, `%`. When applied to integers, `%` is the modulus operator. But when the first operand is a string, `%` is the format operator.

The first operand is the **format string**, which contains one or more **format sequences**, which specify how the second operand is formatted. The result is a string.

For example, the format sequence `'%d'` means that the second operand should be formatted as an integer (`d` stands for "decimal"):

```
>>> camels = 42
>>> '%d' % camels
'42'
```

The result is the string `'42'`, which is not to be confused with the integer value 42.

A format sequence can appear anywhere in the string, so you can embed a value in a sentence:

```
>>> camels = 42
>>> 'I have spotted %d camels.' % camels
'I have spotted 42 camels.'
```

If there is more than one format sequence in the string, the second argument has to be a tuple. Each format sequence is matched with an element of the tuple, in order.

The following example uses `'%d'` to format an integer, `'%g'` to format a floating-point number, and `'%s'` to format a string:

```
>>> 'In %d years I have spotted %g %s.' % (3,
    0.1, 'camels')
'In 3 years I have spotted 0.1 camels.'
```

The number of elements in the tuple has to match the number of format sequences in the string. Also, the types of the elements have to match the format sequences:

```
>>> '%d %d %d' % (1, 2)
TypeError: not enough arguments for format
string
>>> '%d' % 'dollars'
TypeError: illegal argument type for built-in
operation
```

In the first example, there aren't enough elements; in the second, the element is the wrong type.

The format operator is powerful, but it can be difficult to use. You can read more about it at <http://docs.python.org/2/library/stdtypes.html#string-formatting>.

14.4 Filenames and paths

The `os` ('operating system') module provides functions for working with files and directories. `os.getcwd` returns the current working directory.

```
>>> import os
>>> cwd = os.getcwd()
>>> print cwd
/home/dinsdale
```

To find the absolute path to a *file*:

```
>>> os.path.abspath('memo.txt')
'/home/dinsdale/memo.txt'
```

`os.path.exists` checks whether a file or directory exists.

```
>>> os.path.exists('memo.txt')
True
```

If it exists, `os.path.isdir` checks whether it's a directory:

```
>>> os.path.isdir('memo.txt')
False
>>> os.path.isdir('music')
True
```

Similarly, `os.path.isfile` checks whether it's a file:

`os.listdir` returns a list of the files (and other directories) in the given directory:

```
>>> os.listdir(cwd)
['music', 'photos', 'memo.txt']
```

To demonstrate these functions, the following example "walks" through a directory, prints the names of all the files, and calls itself recursively on all the directories.

```
def walk(dirname):
    for name in os.listdir(dirname):
        path = os.path.join(dirname, name)

        if os.path.isfile(path):
            print path
        else:
            walk(path)
```

`os.path.join` takes a directory and a file name and joins them into a complete path.

14.5 Catching exceptions

The `try` statement:

```
try:
    fin = open('bad_file')
    for line in fin:
        print line
    fin.close()
except:
    print 'Something went wrong.'
```

The syntax is similar to an `if` statement. Python starts by executing the `try` clause. If all goes well, it skips the `except` clause and proceeds. If an exception occurs, it jumps out of the `try` clause and executes the `except` clause.

Handling an exception with a `try` statement is called **catching** an exception. In this example, the `except` clause prints an error message that is not very helpful. In general, catching an exception gives you a chance to fix the problem, or try again, or at least end the program gracefully.

14.6 Databases

A **database** is a file that is organized for storing data. Most databases are organized like a dictionary in the sense that they map from keys to values. The biggest difference is that the database is on disk (or other permanent storage), so it persists after the program ends.

The module `anydbm` provides an interface for creating and updating database files. As an example, I'll create a database that contains captions for image files.

Opening a database is similar to opening other files:

```
>>> import anydbm
>>> db = anydbm.open('captions.db', 'c')
```

The mode `'c'` means that the database should be created if it doesn't already exist. The result is a database object that can be used (for most operations) like a dictionary. If you create a new item, `anydbm` updates the database file.

```
>>> db['cleese.png'] = 'Photo of John Cleese.'
```

When you access one of the items, `anydbm` reads the file:

```
>>> print db['cleese.png']
Photo of John Cleese.
```

If you make another assignment to an existing key, `anydbm` replaces the old value:

```
>>> db['cleese.png'] = 'Photo of John Cleese
doing a silly walk.'
>>> print db['cleese.png']
Photo of John Cleese doing a silly walk.
```

Many dictionary methods, like `keys` and `items`, also work with database objects. So does iteration with a `for` statement.

```
for key in db:
    print key
```

As with other files, you should close the database when you are done:

```
>>> db.close()
```

14.7 Pickling

A limitation of `anydbm` is that the keys and values have to be strings. The `pickle` module translates almost any type of object into a string suitable for storage in a database, and then translates strings back into objects. `pickle.dumps` takes an object as a parameter and returns a string representation (`dumps` is short for “dump string”):

```
>>> import pickle
>>> t = [1, 2, 3]
>>> pickle.dumps(t)
'(\x00\x01\x02\x03\x00.'
```

`pickle.loads` reconstitutes the object:

```
>>> t1 = [1, 2, 3]
>>> s = pickle.dumps(t1)
>>> t2 = pickle.loads(s)
>>> print t2
[1, 2, 3]
```

Although the new object has the same value as the old, it is not (in general) the same object:

```
>>> t1 == t2
True
>>> t1 is t2
False
```

In other words, pickling and then unpickling has the same effect as copying the object.

You can use `pickle` to store non-strings in a database. In fact, this combination is so common that it has been encapsulated in a module called `shelve`.

From my notes:

```
pickle.dump(var_name, open('save.p', 'wb'))
var_name = pickle.load(open('save.p', 'rb'))
```

14.8 Pipes

Any program that you can launch from the shell can also be launched from Python using a **pipe**. A pipe is an object that represents a running program.

You can launch `ls -l` with `popen`:

```
>>> cmd = 'ls -l'
>>> fp = os.popen(cmd)
```

The argument is a string that contains a shell command. The return value is an object that behaves just like an open file. You can read the output from the `ls` process one line at a time with `readline` or get the whole thing at once with `read`:

```
>>> res = fp.read()
```

When you are done, you close the pipe like a file:

```
>>> stat = fp.close()
>>> print stat
None
```

The return value is the final status of the `ls` process; `None` means that it ended normally (with no errors).

For example, most Unix systems provide a command called `md5sum` that reads the contents of a file and computes a “checksum”. You can read about MD5 at <http://en.wikipedia.org/wiki/Md5>. This command provides an efficient way to check whether two files have the same contents. The probability that different contents yield the same checksum is very small (that is, unlikely to happen before the universe collapses).

You can use a pipe to run `md5sum` from Python and get the result:

```
>>> filename = 'book.tex'
>>> cmd = 'md5sum ' + filename
>>> fp = os.popen(cmd)
>>> res = fp.read()
>>> stat = fp.close()
>>> print res
1e0033f0ed0656636de0d75144ba32e0 book.tex
>>> print stat
None
```

14.9 Writing modules

Any file that contains Python code can be imported as a module. For example, suppose you have a file named `wc.py` with the following code:

```
def linecount(filename):
    count = 0
    for line in open(filename):
        count += 1
    return count

print linecount('wc.py')
```

You can import this program:

```
>>> import wc
7
```

Now you have a module object `wc` that provides a function called `linecount`:

```
>>> print wc
<module 'wc' from 'wc.py'>
>>> wc.linecount('wc.py')
7
```

The only problem with this example is that when you import the module it executes the test code at the bottom. Normally when you import a module, it defines new functions but it doesn't execute them.

Programs that will be imported as modules often use the following idiom:

```
if __name__ == '__main__':
    print linecount('wc.py')
```

`__name__` is a built-in variable that is set when the program starts. If the program is running as a script, `__name__` has the value `__main__`; in that case, the test code is executed.

Otherwise, if the module is being imported, the test code is skipped.

14.10 Debugging

When you are reading and writing files, you might run into problems with whitespace. These errors can be hard to debug because spaces, tabs, and newlines are normally invisible:

```
>>> s = '1 2\t 3\n 4'
>>> print s
1 2 3
 4
```

The built-in function `repr` takes any object as an argument and returns a string representation of the object. For

strings, it represents whitespace characters with backslash sequences:

```
>>> print repr(s)
'1 2\t 3\n 4'
```

This can be helpful for debugging.

One other problem you might run into is that different systems use different characters to indicate the end of a line. Some systems use a newline, represented `\n`. Others use a return character, represented `\r`. Some use both. If you move files between different systems, these inconsistencies might cause problems.

For most systems, there are applications to convert from one format to another. You can find them (and read more about this issue) at <http://en.wikipedia.org/wiki/Newline>. Or, of course, you could write one yourself.

15 Classes and objects

15.1 User-defined types

We have used many of Python's built-in types; now we are going to define a new type. As an example, we will create a type called `Point` that represents a point in two-dimensional space.

In mathematical notation, points are often written as (x,y) . There are several ways we might represent points in Python:

- We could store the coordinates separately in two variables, `x` and `y`.
- We could store the coordinates as elements in a list or tuple.
- We could create a new type to represent points as objects.

Creating a new type is (a little) more complicated than the other options, but it has advantages that will be apparent soon.

A user-defined type is also called a **class**. A class definition looks like this:

```
class Point(object):  
    """Represents a point in 2-D space."""
```

This header indicates that the new class is a `Point`, which is a kind of `object`, which is a built-in type.

The body is a docstring that explains what the class is for. You can define variables and functions inside a class definition,

Defining a class named `Point` creates a class object.

```
>>> print Point  
<class '__main__.Point',>
```

Because `Point` is defined at the top level, its “full name” is `__main__.Point`.

The class object is like a factory for creating objects. To create a `Point`, you call `Point` as if it were a function.

```
>>> blank = Point()  
>>> print blank  
<__main__.Point instance at 0xb7e9d3ac>
```

The return value is a reference to a `Point` object, which we assign to `blank`. Creating a new object is called **instantiation**, and the object is an **instance** of the class.

When you print an instance, Python tells you what class it belongs to and where it is stored in memory (the prefix `0x` means that the following number is in hexadecimal).

15.2 Attributes

You can assign values to an instance using dot notation:

```
>>> blank.x = 3.0  
>>> blank.y = 4.0
```

This syntax is similar to the syntax for selecting a variable from a module, such as `math.pi` or `string.whitespace`. In this case, though, we are assigning values to named elements of an object. These elements are called **attributes**. The variable `blank` refers to a `Point` object, which contains two attributes. Each attribute refers to a floating-point number.

You can read the value of an attribute using the same syntax:

```
>>> print blank.y  
4.0  
>>> x = blank.x  
>>> print x  
3.0
```

The expression `blank.x` means, “Go to the object `blank` refers to and get the value of `x`.” In this case, we assign that value to a variable named `x`. There is no conflict between the variable `x` and the attribute `x`.

You can use dot notation as part of any expression. For example:

```
>> print ,(%g, %g), % (blank.x, blank.y)
(3.0, 4.0)
>> distance = math.sqrt(blank.x**2 + blank.y**2)
>> print distance
5.0
```

You can pass an instance as an argument in the usual way. For example:

```
def print_point(p):
    print ,(%g, %g), % (p.x, p.y)
```

`print_point` takes a point as an argument and displays it in mathematical notation. To invoke it, you can pass `blank` as an argument:

```
>> print_point(blank)
(3.0, 4.0)
```

Inside the function, `p` is an alias for `blank`, so if the function modifies `p`, `blank` changes.

15.3 Rectangles

Sometimes it is obvious what the attributes of an object should be, but other times you have to make decisions. For example, imagine you are designing a class to represent rectangles. What attributes would you use to specify the location and size of a rectangle? You can ignore angle; to keep things simple, assume that the rectangle is either vertical or horizontal.

There are at least two possibilities:

- You could specify one corner of the rectangle (or the center), the width, and the height.
- You could specify two opposing corners.

At this point it is hard to say whether either is better than the other, so we’ll implement the first one, just as an example.

Here is the class definition:

```
class Rectangle(object):
    """Represents a rectangle.

    attributes: width, height, corner.
```

The docstring lists the attributes: `width` and `height` are numbers; `corner` is a `Point` object that specifies the lower-left corner.

To represent a rectangle, you have to instantiate a `Rectangle` object and assign values to the attributes:

```
box = Rectangle()
box.width = 100.0
box.height = 200.0
box.corner = Point()
box.corner.x = 0.0
box.corner.y = 0.0
```

The expression `box.corner.x` means, “Go to the object `box` refers to and select the attribute named `corner`; then go to that object and select the attribute named `x`.”

An object that is an attribute of another object is **embedded**.

15.4 Instances as return values

Functions can return instances. For example, `find_center` takes a `Rectangle` as an argument and returns a `Point` that contains the coordinates of the center of the `Rectangle`:

```
def find_center(rect):
    p = Point()
    p.x = rect.corner.x + rect.width/2.0
    p.y = rect.corner.y + rect.height/2.0
    return p
```

Here is an example that passes `box` as an argument as assigns the resulting `Point` to `center`:

```
>> center = find_center(box)
>> print_point(center)
(50.0, 100.0)
```

15.5 Objects are mutable

You can change the state of an object by making an assignment to one of its attributes. For example, to change the size of a rectangle without changing its position, you can modify the values of `width` and `height`:

```
box.width = box.width + 50
box.height = box.width + 100
```

You can also write functions that modify objects. For example, `grow_rectangle` takes a `Rectangle` object and two numbers, `dwidth` and `dheight`, and adds the numbers to the width and height of the rectangle:

```
def grow_rectangle(rect, dwidth, dheight):
    rect.width += dwidth
    rect.height += dheight
```

Here is an example that demonstrates the effect:

```
>> print box.width
100.0
>> print box.height
200.0
>> grow_rectangle(box, 50, 100)
>> print box.width
150.0
>> print box.height
300.0
```

Inside the function, `rect` is an alias for `box`, so if the function modifies `rect`, `box` changes.

15.6 Copying

Aliasing can make a program difficult to read because changes in one place might have unexpected effects in another place. It is hard to keep track of all the variables that might refer to a given object.

Copying an object is often an alternative to aliasing. The `copy` module contains a function called `copy` that can duplicate any object:

```
>> p1 = Point()
>> p1.x = 3.0
>> p1.y = 4.0

>> import copy
>> p2 = copy.copy(p1)
```

`p1` and `p2` contain the same data, but they are not the same `Point`.

```
>> print_point(p1)
(3.0, 4.0)
>> print_point(p2)
(3.0, 4.0)
>> p1 is p2
False
>> p1 == p2
False
```

The `is` operator indicates that `p1` and `p2` are not the same object, which is what we expected. But you might have expected `==` to yield `True` because these points contain the same data. In that case, you will be disappointed to learn that for instances, the default behavior of the `==` operator is the same as the `is` operator; it checks object identity, not object equivalence. This behavior can be changed—we'll see how later. If you use `copy.copy` to duplicate a `Rectangle`, you will find that it copies the `Rectangle` object but not the embedded `Point`.

```
>> box2 = copy.copy(box)
>> box2 is box
False
>> box2.corner is box.corner
True
```

This operation is called a **shallow copy** because it copies the object and any references it contains, but not the embedded objects.

For most applications, this is not what you want. In this example, invoking `grow_rectangle` on one of the `Rectangles` would not affect the other, but invoking `move_rectangle` on either would affect both! This behavior is confusing and error-prone.

Fortunately, the `copy` module contains a method named `deepcopy` that copies not only the object but also the objects it refers to, and the objects *they* refer to, and so on. You will not be surprised to learn that this operation is called a **deep copy**.

```
>> box3 = copy.deepcopy(box)
>> box3 is box
False
>> box3.corner is box.corner
False
```

`box3` and `box` are completely separate objects.

15.7 Debugging

When you start working with objects, you are likely to encounter some new exceptions. If you try to access an attribute that doesn't exist, you get an `AttributeError`:

```
>> p = Point()
>> print p.z
AttributeError: Point instance has no attribute ,z,
```

If you are not sure what type an object is, you can ask:

```
>> type(p)
<type ,__main__.Point,>
```

If you are not sure whether an object has a particular attribute, you can use the built-in function `hasattr`:

```
>> hasattr(p, ,x,)
True
>> hasattr(p, ,z,)
False
```


The first argument can be any object; the second argument is a *string* that contains the name of the attribute.

16 Classes and functions

17 Classes and methods

18 Inheritance

19 Case study: Tkinter

20 Debugging

21 Analysis of Algorithms

22 Lumpy

Glossary

accumulator	A variable used in a loop to add up or accumulate a result.
aliasing	A circumstance where two or more variables refer to the same object.
argument	A value provided to a function when the function is called. This value is assigned to the corresponding parameter in the function.
augmented assignment	A statement that updates the value of a variable using an operator like <code>+=</code> .
body	The sequence of statements inside a function definition.
composition	Using an expression as part of a larger expression, or a statement as part of a larger statement.
data structure	A collection of related values, often organized in lists, dictionaries, tuples, etc.
delimiter	A character or string used to indicate where a string should be split.
dot notation	The syntax for calling a function in another module by specifying the module name followed by a dot (period) and the function name.
DSU	Abbreviation of “decorate-sort-undecorate,” a pattern that involves building a list of tuples, sorting, and extracting part of the result.
element	One of the values in a list (or other sequence), also called items.
equivalent	Having the same value.
filter	A processing pattern that traverses a list and selects the elements that satisfy some criterion.
flow of execution	The order in which statements are executed during a program run.
frame	A box in a stack diagram that represents a function call. It contains the local variables and parameters of the function.
fruitful function	A function that returns a value.
function	A named sequence of statements that performs some useful operation. Functions may or may not take arguments and may or may not produce a result.
function call	A statement that executes a function. It consists of the function name followed by an argument list.
function definition	A statement that creates a new function, specifying its name, parameters, and the statements it executes.
function object	A value created by a function definition. The name of the function is a variable that refers to a function object.
gather	The operation of assembling a variable-length argument tuple.
header	The first line of a function definition.
identical	Being the same object (which implies equivalence).
import statement	A statement that reads a module file and creates a module object.
index	An integer value that indicates an element in a list.
list	A sequence of values.
list traversal	The sequential accessing of each element in a list.
local variable	A variable defined inside a function. A local variable can only be used inside its function.
map	A processing pattern that traverses a sequence and performs an operation on each element.
mapping	A relationship in which each element of one set corresponds to an element of another set. For example, a list is a mapping from indices to elements.
module	A file that contains a collection of related functions and other definitions.
module object	A value created by an <code>import</code> statement that provides access to the values defined in a module.
nested list	A list that is an element of another list.
object	Something a variable can refer to. An object has a type and a value.
parameter	A name used inside a function to refer to the value passed as an argument.
reduce	A processing pattern that traverses a sequence and accumulates the elements into a single result.
reference	The association between a variable and its value.
return value	The result of a function. If a function call is used as an expression, the return value is the value of the expression.
scatter	The operation of treating a sequence as a list of arguments.
shape (of a data structure)	A summary of the type, size and composition of a data structure.
stack diagram	A graphical representation of a stack of functions, their variables, and the values they refer to.
traceback	A list of the functions that are executing, printed when an exception occurs.
tuple	An immutable sequence of elements.
tuple assignment	An assignment with a sequence on the right side and a tuple of variables on the left. The right side is evaluated and then its elements are assigned to the variables on the left.
void function	A function that doesn't return a value.

23 Quick reference

Execution

```
cl> export PYTHONPATH="${PYTHONPATH}:/new/path"

>>> import sys
>>> sys.path

cl> python program_name.py

#!/bin/bash
...
cl> ./program_name.py
```

Debugging

```
import pdb
pdb.set_trace() #equivalent of 'STOP' in IDL
cl> python code.py
...
(Pdb) continue
```

Type 'continue' at the end to keep going. Type 'q' to quit.
Can also print variables, types, etc. in this mode.

Strings

```
>>> s1 = "/home/users/laurel/"
>>> s2 = "file.dat"
>>> s1 + s2
"/home/users/laurel/file.dat"
>>> s2[0:5]
'file.'
>>> s2[:5]
'file.'
>>> s2[-5:]
'e.dat'
>>> len(s2)
8
```

Mathematical operators

+, -, *, /, **, +, -, *, /, ++, --

bitwise operators

```
& # and
| # or
^ # xor
! # not
```

logical operators

relational

==, !=, >, >=, <, <=

boolean

and, or, not

conditionals

```
if (condition):
    statements
elif (condition):
    statements
else:
    statements
    pass # need to have 'something' here. ???
if (condition):
    break
else:
    continue
```

Looping

Python is not inclusive!

```
for i in list:
for i in range(len(list)):
for i in range(0, 10, 0.1)

for i in range([start,]stop[, step])
```

(by default, start = 0 and step = 1)

```
>>> root = "output."
>>> for i in range(1,101):
...     outfile = root + repr(i).zfill(3) + '.txt'
...     print outfile
```

```
output.001.txt
...
output.100.txt
```

repr(i) returns a string and zfill(3) pads with leading zeros.

```
while (condition):
    statements
```

I/O

Simple output:

```
print 'characters', string, variable
```

Simple reading from terminal and file:

```
terminal:
s = raw_input('prompt')
```

Higher level file reading routines:

```
data = numpy.loadtxt(file,
dtype=[('name', 'a12'), ('ra', f4), ('dec', 'f4')])
data = astropy.io.ascii(file)
```

Type changes

```
str(x)      # num to string
abs(x)      # absolute value
int(x)      # float to integer (truncated)
long(x)     # long data type
float(x)    # takes string or int, NOT array
```

Math

```
import math
# Use the following as math.funcname(x), unless
# specified otherwise
pow(x,y)    # x^y
sqrt
log
log10
exp
fabs
sin, cos, tan, asin, acos, atan
atan2(y,x)  # vector to (x,y) makes this angle
             # with the positive x-axis. Returns values
             # between -pi and +pi
radians(x)  # degrees -> radians
degrees(x)  # radians -> degrees

from scipy.interpolate import interp1d
interp1d(x, y, 'cubic') # x is data, y = f(x)
from scipy.interpolate import interp2d
interp2d(x, y, z, 'cubic') # x and y are data,
                           # z = f(x,y)
```

Lists

```
>>> x = range(5)
      [0,1,2,3,4]
>>> len(x)
      5
>>> x.append(5)
      [0,1,2,3,4,5]

>>> A = [1,2,3]
      [1,2,3]
>>> A*2 # Get A back twice
      [1,2,3,1,2,3]
```

numpy arrays

Compare to list example above:

```
import numpy as np
>>> B = np.array([1,2,3])
      [1 2 3]
>>> B+2 # Element by element
      [3 4 5]
>>> B*2
      [2 4 6]

A.shape      # (rows, columns)
A.ndim       # Number of dimensions
A.size       # Number of elements
A.astype(float) # Change to type float

np.log(A)    # Natural log
np.log10(A)  # log base 10
np.atan2(A)  # array of angles between -pi and
             # +pi

np.array(object, dtype=None)
np.arange([start,] stop, [step,] dtype=None)
np.arange(n) # [0,1,2,...,n-1]; if n is a float
             # , A will be a float
np.zeros([n,m]) # n=rows, m=columns
np.linspace([start,] stop, [step,] dtype=None)
             # num_steps = 50 by default
np.logspace
np.ndarray(...) # two-dimensional array
np.argmax(x) # returns INDEX of max value of x
              # array
```

```
np.append(A, values, axis=None)
np.roll(x,2) # (~IDL's SHIFT); shifts array
             # elements 2 to the right
             # -> [3,4,0,1,2] # note x is still the same,
             # unless do x = np.roll(...)
np.where(condition) -> array

# np.funcname(array, axis=None, dtype=None) ~ A
# .funcname(...)
sum, max, min, mean, std
np.std(A, axis=None); A.std()
A.var() # Normalized with N (not N-1)
np.median(A, axis=None)
             # axis - along which median is computed. Get
             # array back, or if no
             # axis is specified, get a single number back
             # .

A = [[1 2 3]
      [4 5 6]
      [7 8 9]]

np.median(A) -> 5.0
np.median(A, axis=0) -> [4 5 6]
np.median(A, axis=1) -> [2 5 8]
np.median(A, axis=2) -> Error
```

```
A = complex(3.2, 5.4)
A = (3.2 + 5.4j) # (equivalent)
A.imag -> 5.4
A.real -> 3.2 # return value is same type as
              # input. If input is complex, returns a float

np.roll(A, n, axis=None) # By default (no axis
                         # specified), array is flattened, shifted,
                         # then restored
np.reshape(A, shape)
np.stack
np.broadcast_to(array, shape)
np.repeat(array, num_repeats, axis=...)
A.reshape(shape)
A.flatten() # Returns 1D array

# Matrices
A = np.matrix(A)
B = (np.matrix(B)).reshape(3,1)
B*A # Matrix multiplication

# Fourier transform
f = np.fft.fft(A, n=None, axis=-1, norm=None)
```

Functions

```
def lag(m, *v): # v is a parameter
    var = lag(m, "hi")

def lag(m, v=None): # v is a keyword
    var = lag(m, v="hi")

if v: ...
if not v: ...
```

FITS files

```
import glob
fls = glob.glob('*.*fits') # list of filenames

from astropy.io import fits
hdu = fits.open('name.fits') # Create list
                                object.
hdu.info()
info = hdu[0].header
image = hdu[0].data # type(image) —> numpy.
                    ndarray
image.shape # shape (dimensions) of numpy.
            ndarray
hdu.close() # Always do this
```

Dynamic memory allocation

```
# structures (dictionaries)
var={'name':'test', ra:1.}
print var['name'], var['test']
dicname = { 'A':[1,2,3], 'B':[2,4,6], 'C'
            :[3,9,15] }
print dicname
# dictionaries are indexed by keys (A, B, C),
  rather than numbers.
# Keys can be any immutable type. Can't use
  lists, since they can be modified.
profile = { 'density':rho_r, 'mass':mass, ...}
my_density = np.array(profile['density'])

# structure arrays
sarray = np.zeros(nelem,
  dtype=[('name', 'a12'), ('ra', 'f4'), ('dec', 'f4')
  ])
sarray=np.zeros(nelem,
  dtype={'names': ('name', 'ra', 'dec'),
        'formats': ('S12', 'f4', 'f4')})
```

Classes

```
# To allow import:
def main():
    # program statements
    print "hello world."
if __name__=="__main__": # flexible way of
    running routines
    main()
```

Plotting

- <http://latexcolor.com/>
- http://matplotlib.org/api/axes_api.html

```
# Draw streamlines of a vector flow!
ax.streamplot()

import matplotlib.pyplot as plt
fig = plt.figure()
fig.set_size_inches(width, height)
fig.suptitle(
    'bold figure suptitle',
    fontsize = 14, fontweight='bold'
)
plt.xlabel('labelname', fontsize=14, color='red')
plt.ylabel('ylabel')

plt.tight_layout()
plt.axis('tight')
# difference?

plt.colorbar()
```

Individual axes:

```
ax.set_xlabel('labelname',
    fontsize = 14,
    color='#eeeeff') # Maybe...
)
ax.set_xticklabels(
    columnlabels, # ?
    rotation=(45),
    fontsize=10,
    va='bottom', ha='left',
)
ax.set_xticks(
    np.arange(start, stop, step)
)
ax.tick_params(
    axis=['x'|'y'|'both'],
    labelsize='large' # dif. bet. this and ax.
    set_xticklabel?
)
ax.set_yscale('log')
ax.axis('tight')
```

Loop to get indefinite number of plots in one figure:

```
for i in range(0, some_number):
    ax = fig.add_subplot(n, m, i+1)
    # n - vertical; m - horizontal; i+1 - plot
    # being defined as 'ax'
```

Put two plots on the same axes:

```
ax1.plot(x, y1, 'r')
ax2 = ax1.twinx()
ax2.plot(x, y2, 'g')
for tl in ax2.get_yticklabels():
    tl.set_color('g')
ax.tick_params(labelsize="small") # size of
    numbers on each tick mark,
    not
    axis titles
savefig('fig.png', bbox_inches='tight')
```

x and y limits: order matters! Put after set x ticks.

No idea what this stuff is doing:

```
set_data_interval()
subplots_adjust
set_ylim(min, max)
fig, ax = plt.subplots() # Simpler?

plt.figure(figsize=(20, 10))
fig, ax = plt.subplots(figsize=(20, 10))
plt.savefig("im.png", bbox_inches='tight',
    dpi = 100)
```

Imaging

```
ax.imshow(hdu.data, cmap='gray')
cube = np.array([im1, im2, im3])
np.power(image, 0.1)
```

Legend

```
ax.plot(x, y1, 'k—', label='line 1')
ax.plot(x, y2, 'k:', label='line 2')
ax.plot(x, y3, 'k', label='line 3')
legend = ax.legend(loc='upper center',
    = 'lower left',
    shadow = True)
```

Save figures

```
pyplot.show()
pyplot.savefig('tmp.pdf') # rewritten each time
!
```