



2.75W Compact Fixed Blade Charger



Features

- Fixed Blade
- CC & CV control
- Level VI Compliant
- Low Cost
- 5 Star Standby power <0.03W
- No Y Cap

Applications

- MPEG Players
- PDA
- Personal Electronics
- Digital Camera

Safety Approvals

- cUL/UL
- IEEE1725 Approved

Mechanical Characteristics

- Length: 42mm (1.65in)
- Width: 43mm (1.65in)
- Height: 21.0mm (0.87in)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Case Color
		Min.	Max.		Line	Load	
PSM03A-050Q-R	5V	0A	0.55A	100mV	±5%		Black
PSM03A-050Q-3W-R	5V	0A	0.55A	100mV	±5%		White

Note: (1) Measured after 10 minutes with by-pass capacitors 0.1uf // 10uf at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error and change. Content is subject to change without notice. Please consult the Phihong directly or visit www.phihong.com for the most up-to-date specifications.

INPUT:**AC Input Voltage Rating**

100 to 240VAC

AC Input Voltage Range

90 to 264VAC

AC Input Current

0.1A(RMS) max.

Leakage Current

<0.20uA @ 264VAC/63Hz

Input Power Saving

<0.75mW @ 115VAC/230VAC)

OUTPUT:**Power**

2.75W Maximum

Efficiency

DOE Level VI

No-Load Power Saving $\leq 75\text{mW}$ @ 115VAC/230VAC**Hold-up Time**

10mS min. @ 120VAC and max. load

ENVIRONMENTAL:**Temperature**

Operation 0 to +40°C

Non-operation -40 to +85°C

Humidity 90%

Immunity

ESD: EN61000-4-2. Level 4

Surge: EN61000-4-5. Level 4

Harmonic: EN61000-3-2

Flicker: EN61000-3-3

Emissions

Complies with FCC Class B

Complies with EN55022 Class B

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000VAC

Insulation Resistance

Primary to Secondary: 7M ohm 500VDC

FEATURES:**Short Circuit Protection**

The output can be shorted permanently without damage

Over Voltage Protection

<8.5V

DC Output Connector

USB A

D+ and D- pins shorted together inside the charger

