

Aspera Orchestrator Plugin Development Guide

IBM Aspera

2026/06/22

Contents

1	Introduction	3
1.1	What is a Plugin?	3
1.2	How Plugins are Detected and Loaded	3
2	Plugin Structure	4
2.1	Additional Ruby Files	4
2.2	File Naming Conventions	4
2.3	Directory Location	5
3	Plugin Architecture Patterns	6
3.1	Class Structure	6
3.2	Core Methods	6
3.2.1	Required Methods	6
3.2.2	Optional Methods (for advanced features)	6
3.3	Execution Patterns	7
4	Required Elements	8
4.1	Main Ruby Class	8
4.2	Required Methods	8
4.2.1	<code>self.version</code>	8
4.2.2	<code>self.display_name</code> (Optional but Recommended)	8
4.2.3	<code>name</code> (Optional)	8
4.2.4	<code>inputs_spec</code>	9
4.2.5	<code>outputs_spec</code>	9
4.2.6	<code>category</code>	9
4.2.7	<code>execute</code>	10
4.3	<code>metadata.yml</code> File	10
5	API Reference	11
5.1	Data Types	11
5.2	Execution Status	11
6	Simple Example: "Hello World" Plugin	12
6.1	Directory Structure	12
6.2	<code>hello_world_simple.rb</code>	12
6.3	<code>metadata.yml</code>	13
6.4	How It Works	13
7	Testing Your Plugin	14
7.1	Development vs Production Paths	14
7.2	Testing Steps	14
7.3	Important Notes	14
8	Advanced Features	15
8.1	Database Migrations	15
8.2	Asynchronous Execution	15
8.3	Trigger Plugins	16
8.4	Lifecycle Control (Pause/Resume/Cancel/Rollback)	17

8.5	Input Validation	17
8.6	Helper Methods	18
8.7	Dynamic Input/Output Specifications	18
9	Plugin Patterns Usage Statistics	19
9.1	Common Patterns	19
9.2	Key Takeaways	19
10	Best Practices	20
11	Advanced Usage Patterns	21
11.1	Using Payload Variables	21
11.2	Remote Node Integration	21
11.3	Multi-Type Conversion	21
12	Plugin Development Alternatives and Possibilities	22
12.1	Plugin Types and Use Cases	22
12.2	Configuration UI Options	22
12.2.1	Standard Form Fields	22
12.2.2	Dynamic Configuration	23
12.2.3	Help Documentation	23
12.3	External Dependencies Management	23
12.3.1	Using Gemfile	23
12.3.2	System Dependencies	23
12.4	Plugin Versioning and Upgrades	23
12.4.1	Version Management	23
12.4.2	Upgrade Process	23
12.4.3	Deprecation	24
12.5	Plugin Distribution	24
12.5.1	Installation	24
12.6	Performance Considerations	24
12.7	Testing and Debugging	24
12.7.1	Development Workflow	24
12.7.2	Common Issues	24
12.8	Security Considerations	24
12.8.1	Input Sanitization	24
12.8.2	Credential Management	24
12.8.3	Code Execution	25
13	Conclusion	26
14	Additional Resources	27
14.1	Learning Ruby	27
14.2	Plugin Development Tips	27
15	Annex	28
15.1	Adding a gem to Orchestrator 4.1.x	28
15.1.1	Global Gem	28
15.1.2	Plugin Gem	28

Chapter 1

Introduction

This guide explains how to develop a plugin (action) for Aspera Orchestrator. Plugins allow you to extend Orchestrator's functionality by adding custom actions that can be used in workflows.

1.1 What is a Plugin?

A plugin (also called an "action") is a Ruby class that extends Orchestrator's capabilities.

Plugins can:

- Execute custom business logic
- Integrate with external systems (APIs, databases, file systems)
- Transform data and files
- Monitor events and trigger workflows
- Implement custom triggers that watch for specific conditions

1.2 How Plugins are Detected and Loaded

Orchestrator automatically discovers and loads plugins through the following mechanism:

1. Discovery: Plugins are stored in the `actions/` directory (configurable via config parameter `actionplugins_load_directory`)
2. Registration: The system scans the actions directory and registers each plugin in the database
3. Loading: When enabled, the system loads the Ruby class files and executes any migration files
4. Instantiation: The `Action` module provides the base interface that all plugins must implement
5. Execution: When a workflow step runs, Orchestrator instantiates the plugin class and calls its `execute` method

The plugin system uses `ActiveRecord` for persistence, allowing plugins to store configuration in database tables that are automatically created via migration files.

Chapter 2

Plugin Structure

An Aspera Orchestrator plugin consists of several files organized in a dedicated directory:

```
actions/my_plugins/
├── my_plugin.rb           # Main plugin class (required)
├── metadata.yml          # Metadata and version history (required)
├── edit.html.erb         # Configuration UI (optional)
├── help.html.erb         # Help documentation (optional)
├── MyPlugin.png          # Plugin icon (optional, 48x48px recommended)
├── YYYYMMDDHHMMSS_*.rb   # Migration files (optional, for database schema)
├── my_plugin_controller.rb # Controller for complex UI logic (optional)
├── my_plugin_helper.rb   # Helper methods for views (optional)
├── my_plugin_service.rb  # Service classes for business logic (optional)
├── additional_files/     # Additional support files (optional)
│   ├── payloads/        # XML/JSON templates
│   ├── wsdl/            # WSDL files for SOAP integrations
│   └── sample_config/    # Configuration examples
```

2.1 Additional Ruby Files

Based on analysis of 205 plugins:

File Type	Usage	Purpose	Example
<u>Controllers</u>	21 plugins	Complex UI interactions and AJAX operations	akamai_transcoding_controll
<u>Helpers</u>	8 plugins	View helper methods for formatting data and generating UI elements	ateme_transcoding_helper.rb
<u>Services</u>	5 plugins	Encapsulate business logic and external API calls	faspex5_package_monitor_aut

2.2 File Naming Conventions

File Type	Naming Convention	Example
<u>Main class file</u>	Must match the class name in snake_case	HelloWorld → hello_world.rb
<u>Migration files</u>	Format YYYYMMDDHHMMSS_description.rb (timestamp ensures execution order)	20231201120000_create_tabl
<u>Icon file</u>	Must match the class name	HelloWorld.png
<u>View files</u>	edit.html.erb for configuration, help.html.erb for documentation	edit.html.erb, help.html.erb

2.3 Directory Location

Plugins are installed in the directory specified by parameter `actionplugins_load_directory`, which defaults to `config/orchestrator/actions`. During development, plugins are typically placed in the `actions/` directory at the Orchestrator application root.

Chapter 3

Plugin Architecture Patterns

Plugins follow the following patterns and mechanisms:

3.1 Class Structure

All plugins must follow this structure:

```
class MyPlugin < ActiveRecord::Base
  include Action

  # Constants for input/output variable names
  INPUT_PARAM = "input_param"
  OUTPUT_RESULT = "result"

  # Instance variables (inherited from Action module)
  # @inputs, @outputs, @status, @status_details, @percent_complete, @state_id
end
```

Key Points:

- Inherit from `ActiveRecord::Base` for database persistence
- Include the `Action` module which provides the plugin interface
- Define constants for all input/output variable names
- Use instance variables provided by the Action module

3.2 Core Methods

Every plugin must implement these essential methods defined in the `Action` module:

3.2.1 Required Methods

Method	Description
<code>self.version</code>	Returns plugin version as array <code>[major, minor, release]</code>
<code>inputs_spec</code>	Returns two <code>Hash</code> es: <code>required_inputs</code> and <code>optional_inputs</code>
<code>outputs_spec</code>	Returns <code>Hash</code> of output variables
<code>category</code>	Returns array defining plugin category
<code>execute</code>	Contains main execution logic

3.2.2 Optional Methods (for advanced features)

Method	Description
<code>validate_inputs</code>	Custom input validation

Method	Description
<code>pause</code> , <code>resume</code> , <code>cancel</code> , <code>rollback</code>	Lifecycle control
<code>timeout</code>	Returns timeout in seconds (0 = no timeout, nil = default)
<code>check_status</code>	Polls status for async operations
<code>synchronous_execution?</code>	Returns false for async execution
<code>multiple_execution?</code>	Returns true for trigger-type plugins
<code>remote_execution?</code>	Returns false to prevent remote execution
<code>recover</code>	Recovers from partial execution

3.3 Execution Patterns

Pattern	Configuration	Behavior	Examples
<u>Synchronous Execution</u> (default)	Default settings	<code>execute</code> method completes the work and returns final status: <code>[status, status_details]</code>	Simple file operations, API calls, data transformations
<u>Asynchronous Execution</u>	Override <code>synchronous_execution?</code> to return <code>false</code>	<code>execute</code> starts the operation and returns <code>STATUS_INPROGRESS</code> . Implement <code>check_status</code> to poll for completion	Transcoding jobs, large file transfers, batch processing
<u>Trigger Pattern</u>	Set <code>synchronous_execution?</code> to <code>false</code> and <code>multiple_execution?</code> to <code>true</code>	Use <code>check_status</code> to detect events and return <code>STATUS_COMPLETE</code> when triggered. Include <code>ModuleTriggerTools</code> module for trigger persistence	File monitoring, package arrival detection, webhook listeners

Chapter 4

Required Elements

4.1 Main Ruby Class

Each plugin must:

- Inherit from `ActiveRecord::Base`
- Include the `Action` module
- Define essential methods

4.2 Required Methods

4.2.1 `self.version`

Returns the plugin version by reading from `metadata.yml`.

```
def self.version
  return @@plugin_version_loaded if defined?(@@plugin_version_loaded)
  versions = SafeYaml.load_file(File.join(__dir__, 'metadata.yml'))[:revision_history].map { |change|
    ↪ change[:version].split(".").map { |num| num.to_i } }
  @@plugin_version_loaded = versions.sort_by { |major, minor, revision, patch| [major, minor, revision,
    ↪ (patch.nil? ? 0 : patch)] }.last
  return @@plugin_version_loaded
end
```

4.2.2 `self.display_name` (Optional but Recommended)

Customizes the display name in the UI. Used by ₁₀₀ plugins.

```
def self.display_name
  return @@display_name if defined?(@@display_name)
  @@display_name = SafeYaml.load_file(File.join(__dir__, 'metadata.yml'))[:display_name]
end
```

Note

If not defined, the system generates a name from the class name (e.g., `MyPlugin` → "My plugin").

4.2.3 `name` (Optional)

Provides a human-readable identifier for a configured instance.

Used by ₃ plugins for dynamic naming.

```
def name
  if attributes["name"].present?
    return attributes["name"]
  end
end
```

```
# Generate dynamic name based on configuration
return "#{workflow.name} sub-workflow" if workflow
return "#{self.class.name}_#{id}"
end
```

Example: generates names based on the referenced workflow.

4.2.4 inputs_spec

Defines required and optional input parameters. This method is used for validation when saving a workflow.

```
def inputs_spec
  required_inputs = { "param1" => TYPE_STRING }
  optional_inputs = { "param2" => TYPE_INT }
  return required_inputs, optional_inputs
end
```

Available Input/Output Types:

Type	Description
TYPE_STRING	String value
TYPE_INT	Integer value
TYPE_ARRAY	Array value
TYPE_HASH	Hash/dictionary value
TYPE_FLAG	Boolean flag
TYPE_DATE	Date value
TYPE_OBJECT	Generic object
TYPE_PASSWORD	Password (masked in UI)
TYPE_ATTACHMENT	File attachment

4.2.5 outputs_spec

Defines output variables produced by the plugin. Sets the parameter name, type, and value to be output.

```
def outputs_spec
  return { "result" => TYPE_STRING }
end
```

4.2.6 category

Defines the plugin's category in the UI. Available categories:

```
def category
  return [CATEGORY_FILEOPERATIONS]
end
```

Available Categories:

Category	Description
CATEGORY_OTHER	Other Utilities
CATEGORY_SYSTEM	System
CATEGORY_TRIGGERS	Triggers
CATEGORY_FILEOPERATIONS	File Operations
CATEGORY_FILETRANSFORMATIONS	File Transformations
CATEGORY_FILETRANSFER	File Transfer
CATEGORY_USERINTERACTIONS	User Interactions
CATEGORY_INTEGRATION	Integration
CATEGORY_SCHEDULING	Scheduling
CATEGORY_TRANSCODING	Transcoding
CATEGORY_QUALITY_CONTROL	Quality Control

CATEGORY_ASSET CATEGORY_FILEOPERATIONS CATEGORY_FILETRANSFER CATEGORY_FILETRANSFORMATIONS CATEGORY_INTEGRATION CATEGORY_LIST CATEGORY_OTHER CATEGORY_QUALITY CATEGORY_RESOURCE CATEGORY_SYSTEM CATEGORY_TRANSCODING CATEGORY_TRIGGERS CATEGORY_USERINTERACTIONS CATEGORY_VIRUS

4.2.7 execute

Contains the main execution logic. This method must return three values:

```
def execute
  @outputs = {}
  # Execution logic here
  @outputs["result"] = "value"
  return STATUS_COMPLETE, "Execution successful", @outputs
end
```

Return Values:

1. @status - Plugin execution status (see Status Constants below)
2. @status_details - String describing the current state (e.g., "Processing complete", "Error occurred")
3. @outputs - Hash containing output variables defined in `outputs_spec`

Instance Variables:

- @inputs - Hash of input values provided by the workflow engine
- @outputs - Hash of output values to return to the workflow engine

Status Constants:

Status	Description
STATUS_COMPLETE	Execution completed successfully
STATUS_INPROGRESS	Execution in progress (for asynchronous plugins)
STATUS_FAILED	Execution failed
STATUS_ERROR	Error occurred during execution
STATUS_PAUSED	Execution paused
STATUS_PAUSING	Execution is pausing
STATUS_CANCELING	Execution is being canceled
STATUS_RESUMING	Execution is resuming
STATUS_ROLLINGBACK	Execution is rolling back
STATUS_INACTIVE	Plugin is inactive
STATUS_ACTIVATING	Plugin is activating
STATUS_OBSOLETE	Plugin is obsolete
STATUS_UNDEFINED	Status could not be determined
STATUS_TRUE	Boolean true status
STATUS_FALSE	Boolean false status

4.3 metadata.yml File

The `metadata.yml` file contains plugin metadata:

```
---
:revision_history:
  - :author: "Your Name"
    :change_description: Initial release
    :version: 1.0.0
    :date: "2024-01-01"
    :minimum_server_version: 4.1.0

:display_name: My Plugin
:category: File Operations
:help: "Description of what the plugin does"
:plugin_name: MyPlugin
:description: Short description of the plugin
```

Chapter 5

API Reference

This section provides reference information for constants and types used in plugin development.

5.1 Data Types

Available data types for inputs/outputs:

Type	Description
TYPE_STRING	String value
TYPE_INT	Integer number
TYPE_FLOAT	Float/Decimal number
TYPE_FLAG	Boolean (true/false)
TYPE_HASH	Hash/Dictionary structure
TYPE_ARRAY	Array/List structure

5.2 Execution Status

Possible statuses returned by `execute` :

Status	Description
STATUS_COMPLETE	Successful execution
STATUS_FAILED	Execution failed
STATUS_ERROR	System error
STATUS_INPROGRESS	In progress (for asynchronous execution)
STATUS_PAUSED	Paused

Chapter 6

Simple Example: "Hello World" Plugin

Here's a minimal plugin example that displays a personalized message:

6.1 Directory Structure

```
actions/hello_world_simple/  
├─ hello_world_simple.rb  
└─ metadata.yml
```

6.2 `hello_world_simple.rb`

```
require 'yaml'  
  
class HelloWorldSimple < ActiveRecord::Base  
  include Action  
  
  # Output variable name  
  MESSAGE_OUTPUT = "message"  
  
  # Input variable name  
  NAME_INPUT = "name"  
  
  # Version method - reads from metadata.yml  
  def self.version  
    return @@plugin_version_loaded if defined?(@@plugin_version_loaded)  
    versions = SafeYaml.load_file("#{File.dirname(__FILE__)}/metadata.yml")[:revision_history].map {  
      ↪ |change| change[:version].split(".").map { |num| num.to_i } }  
    @@plugin_version_loaded = versions.sort_by { |major, minor, revision, patch| [major, minor,  
      ↪ revision, (patch.nil? ? 0 : patch)] }.last  
    return @@plugin_version_loaded  
  end  
  
  # Define inputs: one required parameter "name"  
  def inputs_spec  
    required_inputs = { NAME_INPUT => TYPE_STRING }  
    optional_inputs = {}  
    return required_inputs, optional_inputs  
  end  
  
  # Define outputs: one output "message"  
  def outputs_spec  
    return { MESSAGE_OUTPUT => TYPE_STRING }  
  end  
  
  # Plugin category  
  def category  
    return [CATEGORY_OTHER]
```

```

end

# Main execution method
def execute
  begin
    # Initialize outputs
    @outputs = {}

    # Get the name from inputs
    name = @inputs[NAME_INPUT]

    # Create the message
    message = "Hello, #{name}!"

    # Set the output
    @outputs[MESSAGE_OUTPUT] = message

    # Return success status
    return STATUS_COMPLETE, "Message created successfully", @outputs

  rescue Exception => e
    # Handle errors
    return STATUS_ERROR, "Error: #{e.message}", {}
  end
end
end

```

6.3 metadata.yml

```

---
:revision_history:
  - :author: "Developer"
    :change_description: Initial release
    :version: 1.0.0
    :date: "2024-01-01"
    :minimum_server_version: 4.1.0

:display_name: Hello World Simple
:category: Other Utilities
:help: "This plugin creates a personalized greeting message"
:plugin_name: HelloWorldSimple
:description: A simple plugin that demonstrates the basic structure of an Orchestrator action

```

6.4 How It Works

1. Input: The plugin receives a `name` parameter
2. Processing: It creates a greeting message: "Hello, [name]!"
3. Output: Returns the message in the `message` output variable
4. Status: Returns `STATUS_COMPLETE` on success

Chapter 7

Testing Your Plugin

7.1 Development vs Production Paths

- Development path: `/opt/aspera/orchestrator/actions` - Place plugins here during development
- Production path: `/opt/aspera/var/config/orchestrator/actions` - Plugins are loaded from here (configurable via `actionplugins_load_directory`)
- Database tables are updated when plugins are moved from development to production path

7.2 Testing Steps

1. Place your plugin directory in the development `actions/` directory
2. Restart Orchestrator to load the plugin
3. The plugin will appear in the action list under the specified category
4. Create a workflow step using your plugin
5. Provide the required inputs
6. Execute and verify the outputs

7.3 Important Notes

- No empty classes: Orchestrator will attempt to process empty classes and throw errors if they are present
- JavaScript in views: JavaScript code should be added directly to the `edit.html.erb` file, not in separate files
- Database columns: All plugins inherit standard columns from the `Action` base class (name, comments, etc.)

Chapter 8

Advanced Features

8.1 Database Migrations

Plugins can create and modify database tables using migration files. This is essential for storing plugin configuration and state.

Migration File Structure:

```
# File: 20240101120000_create_my_plugins.rb
class CreateMyPlugins < ActiveRecord::Migration[7.2]
  def change
    create_table :action_my_plugins do |t|
      t.string :name
      t.text :comments
      t.string :my_config_field
      t.timestamps
    end
  end
end
```

Key Points:

- Migration files must be prefixed with timestamp: `YYYYMMDDHHMMSS_description.rb`
- File must start with underscore: `_create_my_plugins.rb`
- File name must be plural and match the folder name (tableize is used to validate)
- Table name must follow pattern: `action_#{plugin_name.tableize}` (e.g., `action_my_plugins`)
- Migrations are executed automatically when plugin is loaded
- Use standard `Rails` migration methods: `create_table`, `add_column`, `change_column`, etc.
- Multiple migration files can exist in a plugin directory

Versioning Migrations: When updating a plugin, create new migration files with later timestamps:

```
# File: 20240201120000_my_plugins_add_new_field.rb
class MyPluginsAddNewField < ActiveRecord::Migration[7.2]
  def change
    add_column :action_my_plugins, :new_field, :string
  end
end
```

8.2 Asynchronous Execution

For long-running operations that shouldn't block the workflow engine:

```
def synchronous_execution?
  return false # Indicates asynchronous execution
end

def execute
  # Start the operation (e.g., submit job to external system)
  @job_id = submit_job_to_external_system(@inputs)
end
```



```

    @status = STATUS_INPROGRESS
    return @status, "Job submitted: #{@job_id}", @outputs
end

def check_status
  # Poll external system for job status
  job_status = query_external_system(@job_id)

  if job_status == "complete"
    @outputs["result"] = get_job_result(@job_id)
    return STATUS_COMPLETE, "Job finished", @outputs
  elsif job_status == "failed"
    return STATUS_FAILED, "Job failed", @outputs
  else
    # Return polling interval (in seconds) as third parameter
    return STATUS_INPROGRESS, "Still processing", 30
  end
end
end

```

Important Notes:

- `synchronous_execution?` should return `false` to indicate asynchronous execution
- This prevents the action from blocking the Slave Queue Thread
- The third return value from `check_status` specifies the polling interval in seconds
- Only use for triggers and long-running processes - synchronous execution should be `true` for most plugins

8.3 Trigger Plugins

Triggers watch for events and spawn new workflow instances. They use the trigger pattern:

```

class MyTrigger < ActiveRecord::Base
  include Action
  include ModuleTriggerTools # Provides trigger persistence methods

  def synchronous_execution?
    return false # Triggers are always async
  end

  def multiple_execution?
    return (keep_ongoing == true) && (@is_canceled != true)
  end

  def execute
    @outputs = {}
    return nil, "Initializing trigger", nil
  end

  def check_status
    # Check for trigger condition
    if event_detected?
      @outputs["event_data"] = get_event_data

      # Persist trigger to avoid re-triggering
      register_triggers([event_identifier])
      persist_triggers(@current_triggers)

      return STATUS_COMPLETE, "Event detected", @outputs
    else
      return nil, "Waiting for event", polling_frequency
    end
  end
end
end

```

Trigger Persistence:

- Use `@current_triggers` to get previously triggered events
- Use `register_triggers([event_id])` to mark new events

- Use `persist_triggers(@current_triggers)` to save state
- Include `ModuleTriggerTools` module for trigger persistence methods

Important Notes:

- `synchronous_execution?` must return `false` for triggers
- `multiple_execution?` should return `true` to allow multiple workflow instances
- Triggers sit idle until an event occurs, so they shouldn't block the queue
- Use trigger persistence to avoid re-triggering on the same event

8.4 Lifecycle Control (Pause/Resume/Cancel/Rollback)

Plugins can support workflow control operations:

```
def pausable?
  return true # Indicates pause is supported
end

def pause
  # Pause the operation
  @is_paused = true
  report_progress(STATUS_PAUSED, "Operation paused")
  return true
end

def resumable?
  return true
end

def resume
  # Resume the operation
  @is_paused = false
  return true
end

def cancelable?
  return true
end

def cancel
  # Cancel the operation
  cleanup_resources
  @status = STATUS_FAILED
  @status_details = "Operation canceled"
  return true
end

def rollbackable?
  return true
end

def rollback
  # Undo changes made by this plugin
  undo_changes
  return true
end
```

Note: By default, Orchestrator checks if these methods are overridden using `is_overloaded?`. See for a complete implementation.

8.5 Input Validation

Custom validation beyond type checking:

```
def validate_inputs(inputs_hash = @inputs)
```

```

# First perform default validation
return false unless default_inputs_validation(inputs_hash)

# Custom validation logic
if inputs_hash["number"].present?
  return false if inputs_hash["number"].to_i < 0
end

if inputs_hash["email"].present?
  return false unless
    ↪ inputs_hash["email"].match?(/\A[\w+\-\.]+\@[a-z\d\-\-]+\(\.[a-z\d\-\-]+\)*\.[a-z]+\z/i)
end

return true
end

```

8.6 Helper Methods

Common patterns for accessing configuration:

```

# Get value from runtime inputs or fall back to database configuration
def default_get(field_name)
  var_name = field_name.upcase
  return @inputs[var_name] if @inputs && @inputs[var_name].present?
  return self.send(field_name) if self.respond_to?(field_name)
  return nil
end

# Example usage
def polling_frequency_get
  return default_get(:polling_frequency) || DEFAULT_POLLING_FREQUENCY
end

```

8.7 Dynamic Input/Output Specifications

For plugins with variable inputs based on configuration:

```

def inputs_spec
  required_inputs = {}
  optional_inputs = {}

  # Parse configuration to determine required inputs
  if command.present?
    Payload.variables(command).each do |var_name|
      required_inputs[var_name] = TYPE_STRING
    end
  end

  # Add standard optional inputs
  optional_inputs["timeout"] = TYPE_INT

  return required_inputs, optional_inputs
end

```

Chapter 9

Plugin Patterns Usage Statistics

Based on analysis of 205 plugins in the Orchestrator codebase:

9.1 Common Patterns

Pattern	Usage	Description
SafeYaml for version	203/205 (99%)	Standard pattern for reading <code>metadata.yml</code>
self.display_name	100/205 (49%)	Custom display names in UI
MultiType utilities	88/205 (43%)	Type conversion and validation
Asynchronous execution	80/205 (39%)	Long-running operations
dependencies method	74/205 (36%)	External entity dependencies
Payload variables	58/205 (28%)	Dynamic input extraction
cancel support	58/205 (28%)	Cancellation capability
timeout definition	54/205 (26%)	Custom timeout logic
validate_inputs	40/205 (20%)	Custom validation
Trigger type	37/205 (18%)	Event-driven workflows
pause / resume	34/205 (17%)	Lifecycle control
Gemfile dependencies	34/205 (17%)	External Ruby gems
recover method	29/205 (14%)	Partial execution recovery
remote_execution? = false	25/205 (12%)	Local-only execution
Controller files	21/205 (10%)	Complex UI logic
Helper files	8/205 (4%)	View helpers
Service files	5/205 (2%)	Business logic separation
rollback support	2/205 (1%)	Undo capability

9.2 Key Takeaways

1. Version Management: Nearly all plugins use the standard `SafeYaml` pattern for version reading
2. Display Names: Half of plugins customize their display name for better UX
3. Type Handling: `MultiType` is widely used for robust type conversion
4. Async Operations: 39% of plugins use asynchronous execution for long-running tasks
5. Dependencies: Over a third declare dependencies on other entities
6. Advanced Features: Pause/resume, cancel, and recover are used selectively where needed

Chapter 10

Best Practices

1. Error Handling: Always wrap execution logic in try/catch blocks
2. Logging: Use `Rails.logger` for debugging and error messages
3. Constants: Define constants for variable names and default values
4. Documentation: Provide clear help text and parameter descriptions
5. Versioning: Update `metadata.yml` with each change
6. Testing: Test with various input combinations
7. Cleanup: Clean up temporary files and resources
8. Progress Reporting: Use `report_progress` for long operations

Chapter 11

Advanced Usage Patterns

11.1 Using Payload Variables

```
def inputs_spec
  required_inputs = {}
  # Extract variables from a payload string
  Payload.variables(command).each do |var_name|
    required_inputs[var_name] = TYPE_STRING
  end
  return required_inputs, {}
end

def execute
  # Expand payload with actual values
  expanded_command = Payload.expand(command, @inputs, self)
  # ... use expanded_command ...
end
```

11.2 Remote Node Integration

```
def dependencies
  return [{
    entity: "RemoteNode",
    id_key: "name",
    id_value: remote_node,
    dependent_field: "remote_node"
  }]
end
```

11.3 Multi-Type Conversion

```
# Convert string to typed value
value = MultiType.convert_value(string_value, TYPE_INT)

# Convert value to string
string = MultiType.convert_to_string(value)

# Convert hash representation
hash = MultiType.convert_value_hash(string_hash)
```

Chapter 12

Plugin Development Alternatives and Possibilities

12.1 Plugin Types and Use Cases

Orchestrator supports several types of plugins, each suited for different scenarios:

Plugin Type	Purpose	Execution	Examples	Best For	Key Features
<u>Standard Action Plugins</u>	Execute specific tasks within a workflow	Synchronous or asynchronous	File operations, API calls, data transformations	One-time operations with clear inputs and outputs	-
<u>Trigger Plugins</u>	Monitor for events and spawn new workflow instances	Always asynchronous with <code>multiple_execution = true</code>	File system monitors, message queue listeners	Event-driven workflows, continuous monitoring	Include <code>ModuleTriggerTools</code> for trigger persistence
<u>Integration Plugins</u>	Connect to external systems and services	Varies	SOAP/REST APIs, databases, cloud services	System integration, data exchange	Use <code>Gemfile</code> for dependencies, store WSDL files, use payload templates
<u>Custom Trigger with Code Evaluation</u>	Maximum flexibility for custom logic	User-defined	Custom Ruby code execution	Power users who need complete control	Allows custom Ruby code for inputs, outputs, validation, and execution. <u>Warning: Security implications</u>

12.2 Configuration UI Options

Plugins can provide custom configuration interfaces:

12.2.1 Standard Form Fields

Use Rails form helpers in :

```
<%= form_with model: @my_plugin, url: action_update_path(action_type: "my_plugin", id: @my_plugin.id)
  do |f| %>
  <li>
    <%= f.label :name %>
    <%= f.text_field :name %>
  </li>
  <li>
```

```

    <%= f.label :config_value %>
    <%= f.text_area :config_value %>
  </li>
<% end %>

```

12.2.2 Dynamic Configuration

Display runtime-calculated values:

```

<% if @view == 'show' %>
  <li>
    <%= f.label 'Required Variables' %>
    <%= h.Payload.variables(@my_plugin.command).join(', ') %>
  </li>
<% end %>

```

12.2.3 Help Documentation

Provide detailed help in `help.html.erb` with HTML formatting, examples, and usage instructions.

12.3 External Dependencies Management

12.3.1 Using Gemfile

For plugins requiring external Ruby gems:

```

# File: actions/my_plugin/Gemfile
source 'https://rubygems.org'

gem 'aws-sdk-sqs', '~> 1.0'
gem 'rest-client', '~> 2.1'

```

Dependencies are automatically installed when the plugin is loaded.

12.3.2 System Dependencies

For external tools (e.g., ffmpeg, exiftool):

- Document in `metadata.yml` under `:external_dependencies`
- Check availability in plugin code
- Provide clear error messages if missing

12.4 Plugin Versioning and Upgrades

12.4.1 Version Management

- Versions are defined in key `:revision_history` in `metadata.yml`
- Format: `major.minor.release` (e.g., "1.2.3")
- Each version entry includes: author, change_description, version, date
- Optionally specify `minimum_server_version` and `maximum_server_version`

12.4.2 Upgrade Process

When upgrading a plugin:

1. Create new migration files with later timestamps
2. Update version in `metadata.yml`
3. The system automatically detects version changes
4. Migrations are executed in order
5. Old plugin instances are preserved for rollback

12.4.3 Deprecation

Mark plugins as deprecated:

```
:revision_history:  
- :deprecation_orch_version: "4.2.0"
```

12.5 Plugin Distribution

12.5.1 Installation

Place in `actions/` directory and reload

12.6 Performance Considerations

Efficient Execution

- Use asynchronous execution for long-running operations
- Implement proper timeout values via `timeout` method
- Return appropriate polling intervals in `check_status`

Resource Management

- Clean up temporary files and connections
- Use `remote_execution?` = true to allow execution on remote nodes
- Implement proper error handling and recovery

12.7 Testing and Debugging

12.7.1 Development Workflow

1. Place plugin in `actions/` directory
2. Reload plugins via UI or API
3. Test in workflow designer
4. Check logs: `Rails.logger.info`, `Rails.logger.error`
5. Use Action Tester for isolated testing

12.7.2 Common Issues

- Plugin not appearing: Check `metadata.yml` syntax, verify file naming
- Migration errors: Ensure table name follows `action_*` pattern
- Version conflicts: Verify version comparison logic
- Loading failures: Check Ruby syntax, verify all required methods are implemented

12.8 Security Considerations

12.8.1 Input Sanitization

- Always validate and sanitize user inputs
- Use parameterized queries for database operations
- Escape shell commands properly

12.8.2 Credential Management

- Never hardcode credentials
- Use Orchestrator's credential management
- Support environment variables for sensitive data

12.8.3 Code Execution

- Be cautious with `eval`
- Validate file paths to prevent directory traversal
- Limit file system access to designated directories

Chapter 13

Conclusion

This comprehensive guide provides the foundation for developing Aspera Orchestrator plugins. Key takeaways:

1. Start Simple: Begin with the basic example and gradually add complexity
2. Follow Patterns: Study existing plugins in `actions/` for proven patterns
3. Use the Framework: Leverage the `Action` module and helper methods
4. Test Thoroughly: Use the Action Tester and test with various input combinations
5. Document Well: Provide clear `metadata.yml`, help files, and inline comments
6. Consider Performance: Use async execution and proper resource management
7. Plan for Upgrades: Use migrations for schema changes and version properly

For more examples and advanced techniques, explore the existing plugins in the `actions/` directory, particularly:

- Basic plugin with pause/resume/cancel
- Trigger pattern with persistence
- Dynamic code evaluation
- External gem dependencies

Chapter 14

Additional Resources

14.1 Learning Ruby

For developers new to Ruby, these resources are recommended:

- [Ruby Tutorial - TutorialsPoint](#) - Comprehensive Ruby tutorial
- [Codecademy Ruby Track](#) - Interactive Ruby learning
- [Try Ruby](#) - Browser-based Ruby introduction
- [Ruby Monk](#) - Interactive Ruby tutorials

14.2 Plugin Development Tips

1. Folder Naming: Plugin folder must be plural (e.g., `cerify_file_verifications`)
2. Migration Naming: Must start with underscore, be plural, and match folder name
3. Controller Usage: Add controllers for plugins requiring server-supplied data for the action template
 - Name: `{plugin_name}_controller.rb` (e.g., `cerify_file_verifications_controller.rb`)
4. View Files: All forms push data to the back-end from fields present in `edit.html.erb`
5. Engine Variables: The engine only sees `@inputs` and `@outputs` variables in the plugin
6. Return Format: All plugins must return `[@status, @status_details, @outputs]`
7. Empty Classes: No empty classes are allowed - Orchestrator will attempt to process them and throw errors

Chapter 15

Annex

15.1 Adding a gem to Orchestrator 4.1.x

15.1.1 Global Gem

Edit the file: `/opt/aspera/orchestrator/Gemfile`

Example, add:

```
gem 'prawn'  
gem 'prawn-table'
```

Then do:

```
cd /opt/aspera/orchestrator/  
bundle install  
orchestrator restart
```

15.1.2 Plugin Gem

Each plugin can have its own dependencies in:

```
/opt/aspera/orchestrator/actions/<PLUGIN_NAME>/Gemfile
```

Install dependencies like for global gems.

End of document