

MyDas

Gurnard Life History Relationships

Laurie Kell & Alex Tidd

17 enero, 2018

```
dirMy="/home/laurence/Desktop/sea++/mydas"  
#dirMy =getwd()  
dirInp=file.path(dirMy,"tasks/inputs")  
dirDat=file.path(dirMy,"tasks/data")
```

```
library(ggplot2)  
library(GGally)
```

```
library(FLife)  
library(plyr)  
library(reshape)
```

Life history parameters

```
load(file.path(dirDat,"gurnards.RData"))
```



Create an FLPar

Then use life history relationships to estimate missing values

```
par=lhPar(wkpar)
```

2

```
library(FLBRP)

eq1=lhEq1(par)

ggplot(FLQuants(eq1,"m","catch.sel","mat","catch.wt"))+
  geom_line(aes(age,data,col=attributes(wkpar)$name[iter]))+
  facet_wrap(~qname,scale="free")+
  scale_x_continuous(limits=c(0,15))+
  guides(colour=guide_legend(title="Species",title.position="top"))
```

Figure 2 Vectors of m , selection pattern, maturity and weight-at-age.
and estimate equilibrium dynamics and reference points, e.g. for lemon sole

```
plot(iter(eq1,7))
```

Figure 3 Equilibrium curves for lemon sole.

Simulation

Create a forward projection, i.e. an `FLStock` from an equilibrium object

```
lmsl=as(iter(eq1,7),"FLStock")

plot(lmsl)
```

Figure 4 Simulate a stock with increasing F