

Case 28: Overnight spread-rate adjustment

1 Verification purpose

This case verifies coupling among the simulation clock, solar burn-period calculation, and surface-fire diurnal multiplier. With uniform fuel, moisture, wind, and slope, the question is whether ELMFIRE reduces and restores radial advance at the prescribed clock hours, each within 1 hour. The case exposes clock offsets, failed midnight wrapping, reversed interval tests, or an unapplied multiplier; it does not calibrate the multiplier.

The scientific setup and historical expected response are reconstructed from Section 3.2 of the supplied *ELMFIRE Guide*. The Guide is used as reference provenance, not as an instruction or a substitute for evidence. Configuration statements below are checked against the generated GeoTIFFs and namelist; current results and decisions come only from case-specific outputs and generated metrics. Where the generated experiment differs from the historical example, the report states that difference explicitly.

2 Mathematical formulation and numerical implementation

For simulation time t seconds and forecast start H_0 , ELMFIRE uses

$$H(t) = \text{mod}(H_0 + t/3600, 24). \quad (1)$$

The solar routine calculates sunrise and sunset from the lower-left coordinate, year, and hour of year. With default center fraction $f_c = 0.667$ and burn length $L_b = 10$ hour,

$$H_c = H_{\text{rise}} + f_c(H_{\text{set}} - H_{\text{rise}}), \quad (2)$$

$$H_b = H_c - L_b/2, \quad H_e = H_c + L_b/2. \quad (3)$$

The stop hour is wrapped above 24. For this non-wrapping interval,

$$D(t) = \begin{cases} 1, & H_b \leq H(t) \leq H_e, \\ 0.1, & H(t) < H_b \text{ or } H(t) > H_e. \end{cases} \quad (4)$$

The spread-rate calculation multiplies its unadjusted rate by $D(t)$. Uniform flat, wind-free conditions produce an approximately circular fire whose equivalent radius $r(t) = \sqrt{A(t)/\pi}$ has full and reduced slope plateaus.

3 Derivation of expected behavior

The controlled response specifies burn-period start 7.5 hour and stop 17.5 hour. Full-to-reduced and reduced-to-full transitions are therefore expected at those respective clock hours. Since $H_0 = 10$ hour, the events first occur approximately 7.5 hour and 21.5 hour after ignition and repeat during the three-day run. This reference calculation follows from the controlled targets and clock equations; calculated times are independently inferred from the arrival raster.

For the generated astronomical inputs, local sunrise and sunset are approximately $H_r = 4.5$ h and $H_s = 16.5$ h. The operational cutoff with fractional daylight $f_c = 0.667$ is

$$H_c = H_r + f_c(H_s - H_r) = 4.5 + 0.667(16.5 - 4.5) = 12.504 \text{ h} \simeq 12.5 \text{ h}.$$

A ten-hour operating window centered on H_c therefore has bounds $H_c \pm 5 = \{7.5, 17.5\}$ h. Relative to the 10:00 forecast start, the first reduction occurs after $(17.5 - 10)(3600) = 27000$ s; after midnight wrapping, full operation resumes after $(24 - 10 + 7.5)(3600) = 77400$ s. The transition metrics compare detected changes with these reference times using the tabulated timing tolerance.

4 Verification metrics and acceptance criteria

The evaluator selects the lexically latest fire arrival time GeoTIFF, masks nodata and values outside $0 \leq t < 10^8$ seconds, and requires 50 burned cells. Analysis ends at the earliest domain-edge arrival so boundary truncation cannot mimic slowdown. At 30 minute intervals, burned-cell count is converted to equivalent radius and differenced. After radius exceeds three cells, rates below half the 80th percentile of positive rates are reduced. Median full-to-reduced and reduced-to-full clock hours are then calculated.

Metric	Target	Acceptance rule	Role
Reduction starts	17.5 hour	absolute error ≤ 1 hour	burn-period stop
Reduction ends	7.5 hour	absolute error ≤ 1 hour	burn-period start

Both rows are required. A missing raster, insufficient burned area or duration, or undetected transition produces NOT EVALUABLE, never PASS.

5 Simulation configuration and predicted outcome

Input	Value	Verification role
Domain/grid	126×126 ; 30 m	circular-front resolution
CRS	EPSG:32635	location for solar calculation
Fuel/terrain	uniform FM3; zero slope	constant baseline spread
Wind/dead moisture	zero; 6, 7, 8 percent	constant forcing
Live moisture	herb 60; woody 90 percent	constant forcing
Ignition	(1890, 1890) m at $t = 0$	centered radial growth
Time control	1 s; 259 200 s stop	three daily cycles
Calendar	year 2025; hour 2890; start 10	clock coupling
Diurnal control	enabled; factor 0.1	two rate plateaus
Output	final time of arrival (TOA), spread rate, FLIN	case-specific evidence

The predicted arrival field is concentric; contour spacing contracts overnight and expands during the burn period, with both transitions inside their acceptance bands.

Figure 1 shows the prescribed spatial condition used in this experiment. The displayed field represents the initial level-set geometry or a controlling fuel, terrain, moisture, wind, or canopy quantity, as identified by the figure labels. The plotted values come from the prepared simulation inputs, not from the expected response.

Whole-domain input configuration — data; WS=0 mph, WD=0 deg




Figure 1: Prepared input conditions from the prescribed spatial fields. Coordinates are in metres; the colorbar identifies the displayed field and its physical units or category. The ignition panel is derived directly from $\phi \leq 0$.

6 Actual simulation results

The current calculated status is **PASS**; 2 of 2 required comparisons pass across 1 completed simulation conditions. The displayed measurements come from these simulations, not from the historical Guide. Missing evidence would remain NOT EVALUABLE.




Figure 2: Final whole-domain time of arrival, in seconds, when a case-specific result figure has been generated. The figure must identify its selected GeoTIFF and simulation condition; the generated metrics table, not visual appearance, determines acceptance.

7 Calculated metrics and verification decision

Simulation condition / metric	Expected	Calculated	Status
main / reduction starts (hr)	17.5 hr	17.75 hr	PASS
main / reduction ends (hr)	7.5 hr	7.75 hr	PASS

The table and the decision **PASS** report the existing calculated metrics. Missing required evidence yields NOT EVALUABLE; no metric values are inferred from the appearance of the simulated fire.

8 Technical interpretation

The recorded transition measurements satisfy the stated one-hour bands, supporting the coupling between simulation time, the solar window, and the diurnal spread factor for the prescribed conditions. A common shift in both transitions would instead suggest an error in the clock, calendar, coordinates, or solar timing; missing contrast would suggest an unapplied multiplier or insufficient simulation history before the transition. This interpretation uses the established calculated metrics and does not extend the claim beyond the configured experiment.

9 Scope and limitations

This synthetic case covers one date, location, fuel, factor, and grid. It does not validate factor magnitude, other seasons or coordinate systems, a burn interval wrapping midnight, heterogeneity, wind, or crown-fire, spotting, suppression, and interpolation interactions. The estimator assumes circular growth, discards post-edge behavior, samples every 30 minute, and infers rather than records the internal factor. This is implementation verification, not validation of real-fire nocturnal behavior.