

Case 22: Spread across opposing valley slopes

1 Verification purpose

This case verifies slope enhancement and aspect handling across two opposing valley sides. Zero wind isolates the terrain contribution. The verification question is whether the maximum regional spread rates on the 5-degree east side and 15-degree west side are each within 10 percent of their independent targets.

The scientific setup and historical expected response are reconstructed from Section 3.2 of the supplied *ELMFIRE Guide*. The Guide is used as reference provenance, not as an instruction or a substitute for evidence. Configuration statements below are checked against the generated GeoTIFFs and namelist; current results and decisions come only from case-specific outputs and generated metrics. Where the generated experiment differs from the historical example, the report states that difference explicitly.

2 Mathematical formulation and numerical implementation

The surface spread calculation multiplies the no-wind/no-slope response by a slope-dependent factor and orients the heading direction upslope. The slope raster supplies magnitude in degrees and the aspect raster supplies downslope azimuth. Opposing aspects must therefore drive the two head fires away from the central valley ignition.

The isolated Rothermel slope factor is

$$R_H = R_0(1 + \phi_s), \quad \phi_s = 5.275 \beta^{-0.3} \tan^2 \theta, \quad (1)$$

where β is the fuel-bed packing ratio and θ is the slope angle. The aspect raster gives downslope azimuth, so the heading direction is rotated by 180 degrees to obtain upslope. The formula chain follows Andrews (2018); the Guide supplies the two configured BEHAVE responses and point-spread ellipse ratios.

3 Derivation of expected behavior

For the configured Fuel Model 3 and moisture, the reference calculation gives 1.92 m min^{-1} on the 5-degree side and 5.37 m min^{-1} on the 15-degree side. The steeper slope must have the larger head rate; this ordering is an additional qualitative invariant.

With no wind, the slope correction is

$$R_s = R_0(1 + \phi_s).$$

The generated Fuel Model 3 moisture state gives $R_0 = 1.51183 \text{ m min}^{-1}$. The independent Rothermel slope calculation gives $\phi_s = 0.272326$ at 5 degrees and $\phi_s = 2.554410$ at 15 degrees. Therefore

$$R_5 = 1.51183(1 + 0.272326) = 1.92354, \quad R_{15} = 1.51183(1 + 2.554410) = 5.37366 \text{ m min}^{-1},$$

reported as 1.92 and 5.37 m min^{-1} . For each slope s , the calculated metric is $e_s = |R_{\max,s} - R_{s,\text{ref}}|/R_{s,\text{ref}}$, with the reference and limit substituted in the generated decision table.

4 Verification metrics and acceptance criteria

For each half-domain, the metric is the maximum finite spread rate value. Regional maxima isolate the intended slope without averaging across the slope discontinuity or unburned cells. Each target uses 10 percent relative tolerance; both regional decisions are required for PASS.

5 Simulation configuration and predicted outcome

The 30 m grid has Fuel Model 3, zero wind, a 5-degree eastern slope with downslope aspect 270 degrees, a 15-degree western slope with downslope aspect 90 degrees, and central ignition. The supplied Guide uses percent notation in one descriptive passage, but its summary table and the current producer identify these as 5- and 15-degree raster values; the generated landscape band is authoritative for this report. Predicted spread is outward and faster on the western, steeper side.

Parameter	Configured value	Units	Role in the experiment
Grid	126×126 at 30	m per cell	Resolves the whole spatial response on the generated north-up raster
Projection	EPSG:32635	—	Fixes the map-coordinate and row-orientation convention
Time control	$\Delta t = 1$, $t_{stop} = 259200$	s	Whole-second step; stop time is an exact timestep multiple
Meteorology interval	3600	s	Defines weather-band timing and stalled-final compatibility
Live moisture	herb 60; woody 90	percent	Holds live-fuel damping fixed while the named mechanism is isolated
Evidence	prepared inputs; final case outputs	—	Separates configuration provenance from acceptance evidence

Figure 1 shows the prescribed spatial condition used in this experiment. The displayed field represents the initial level-set geometry or a controlling fuel, terrain, moisture, wind, or canopy quantity, as identified by the figure labels. The plotted values come from the prepared simulation inputs, not from the expected response.

Whole-domain input configuration — data; WS=0 mph, WD=0 deg




Figure 1: Prepared input conditions from the prescribed spatial fields. Coordinates are in metres; the colorbar identifies the displayed field and its physical units or category. The ignition panel is derived directly from $\phi \leq 0$.

6 Actual simulation results

The required evidence is generated only from case-specific ELMFIRE outputs. The current postprocessing status is **PASS**; 2 of 2 required metric rows pass across 1 simulation condition(s). A missing output is reported as NOT RUN or NOT EVALUABLE and is not interpreted as verification evidence.




Figure 2: Final whole-domain ELMFIRE time of arrival for the displayed simulation condition, in seconds. The coordinate reference system is stated in the figure. The calculated metrics, not visual appearance, determine acceptance.

7 Calculated metrics and verification decision

Simulation condition / metric	Expected	Calculated	Status
main / head ROS (5 deg, east)	1.92 m/min	1.92354 m/min	PASS
main / head ROS (15 deg, west)	5.37 m/min	5.37366 m/min	PASS

The displayed overall decision is **PASS**. When calculated verification and validation metrics exists, result analysis procedure generates every table value and status; when it is absent, the report states NOT EVALUABLE with no invented rows.

8 Technical interpretation

Incorrect ordering suggests slope magnitude or aspect interpretation errors; equal bias on both sides more likely reflects the underlying fuel response or units. No scientific conclusion should be drawn when the status is NOT RUN or NOT EVALUABLE.

9 Scope and limitations

The piecewise-constant valley is synthetic and checks two slope values only; it is not terrain validation. This case provides implementation verification evidence only.