

Java recursive (O(logn) space) and iterative solutions (O(1) space) with ex

14.7K VIEWS

Last Edit: September 22, 2018 11:40 AM

214

U (/yfcheng) yfcheng (/yfcheng)

2269

This is not a very intuitive problem for me, I have to spent quite a while drawing figures to understand it. As shown in the figure, 1 shows the original tree, you can think about it as a comb, with 1, 2, 4 form the bone, and 3, 5 as the teeth. All we need to do is flip the teeth direction as shown in figure 2. We will remove the link 1--3, 2--5, and add link 2--3, and 4--5. And node 4 will be the new root.


As the recursive solution, we will keep recurse on the left child and once we are are done, we found the newRoot, which is 4 for this case. At this point, we will need to set the new children for node 2, basically the new left node is 3, and right node is 1. Here is the recursive solution:




Recursive:

```
public TreeNode upsideDownBinaryTree(TreeNode root) {
    if(root == null || root.left == null) {
        return root;
    }
   TreeNode newRoot = upsideDownBinaryTree(root.left);
    root.left.left = root.right; // node 2 left children
    root.left.right = root;  // node 2 right children
    root.left = null;
    root.right = null;
    return newRoot;
}
```

For the iterative solution, it follows the same thought, the only thing we need to pay attention to is to save the node information that will be overwritten.



```
public TreeNode upsideDownBinaryTree(TreeNode root) {
    TreeNode curr = root;
    TreeNode next = null;
    TreeNode temp = null;
    TreeNode prev = null;
    while(curr != null) {
        next = curr.left;
        // swapping nodes now, need temp to keep the previous right child
        curr.left = temp;
        temp = curr.right;
        curr.right = prev;
        prev = curr;
        curr = next;
    return prev;
}
```



1/2018 (5) Java recursive (O(logn) space) and iterative solutions (O(1) space) with explanation and figure - LeetCode Discuss			
,		Read Mo	re
3 A V Share	◆ Reply		
new2500 (/new2500)	★ 151 ② May 27, 2017 1:21 PM		:
Thumb UP. Thank you	u for the clear explanation and process of thoughts.		
I think for the recursiv	re space, Should it be O(depth of tree) than O(logN) since it's random binary to	ree?	9 4 5
0 ▲ ✔ ☐ Share	← Reply		Notes
sonali3 (/sonali3) ★ 8	8 ② May 26, 2017 10:39 AM		:
Thanks for explaining	using diagram. This helps a lot.		
0 ∧ ∨ C Share	← Reply		
knowledge2thepeople	e (/knowledge2thepeople) 🖈 128 🧿 May 17, 2017 9:55 PM		:
@yfcheng Nice iterative	ve solution. Here's my iterative solution. I'm using more variables than I need:		
		Read Mo	re
0 ∧ ∨ C Share	◆ Reply		
GardenAAA (/gardena	aaa) ★ 86 ② February 3, 2017 1:32 PM		:
Really smart answer a	and detailed explanation. Thanks for sharing.		
2 ^ V Share	← Reply		
feyhi (/feyhi) ★ 30 €	December 22, 2016 3:28 AM		:
Nice write-up, but sind 0(logn) space it	ce the tree is not a typical tree (more like a trunk), I don't think the recursive satisfies $0(n)$.	olution is	
12 ∧ ∨ C Share	e Reply		

SHOW 1 REPLY

<12>

Privacy Policy (/privacy/)

United States (/region/)

J Notes