

# 1 Black-box Testing

## 1.A linalg.dot

### 1.A.1 documentation

For 2-D arrays it is equivalent to matrix multiplication, and for 1-D arrays to inner product of vectors (without complex conjugation). For N dimensions it is a sum product over the last axis of a and the second-to-last of b:

$$\text{dot}(a, b)[i,j,k,m] = \text{sum}(a[i,j,:]\ast b[k,:,m])$$

**Parameters** : two arrays a: array\_like First argument.

b : array\_like Second argument.

out : ndarray, optional output argument. This must have the exact kind that would be returned if it was not used. In particular, it must have the right type, must be C-contiguous, and its dtype must be the dtype that would be returned for dot(a,b). This is a performance feature. Therefore, if these conditions are not met, an exception is raised, instead of attempting to be flexible.

**Returns** : output : ndarray

Returns the dot product of a and b. If a and b are both scalars or both 1-D arrays then a scalar is returned; otherwise an array is returned. If out is given, then it is returned. Raises: ValueError If the last dimension of a is not the same size as the second-to-last dimension of b.

## 1.B linalg.multidot

Compute the dot product of two or more arrays in a single function call, while automatically selecting the fastest evaluation order.

multi\_dot chains numpy.dot and uses optimal parenthesization of the matrices [R44] [R45]. Depending on the shapes of the matrices, this can speed up the multiplication a lot.

If the first argument is 1-D it is treated as a row vector. If the last argument is 1-D it is treated as a column vector. The other arguments must be 2-D.

### 1.B.1 tests

## 1.C linalg.vdot

### 1.C.1 documentation

Return the dot product of two vectors.

The vdot(a, b) function handles complex numbers differently than dot(a, b). If the first argument is complex the complex conjugate of the first argument is used for the calculation of the dot product.

Note that vdot handles multidimensional arrays differently than dot: it does not perform a matrix product, but flattens input arguments to 1-D vectors first. Consequently, it should only be used for vectors.

### 1.C.2 tests

## 1.D linalg.inner

### 1.D.1 documentation

Inner product of two arrays.

Ordinary inner product of vectors for 1-D arrays (without complex conjugation), in higher dimensions a sum product over the last axes.

### 1.D.2 tests

## 1.E linalg.outer

### 1.E.1 documentation

Compute the outer product of two vectors.

**Parameters** : a : (M,) array\_like First input vector. Input is flattened if not already 1-dimensional. b : (N,) array\_like Second input vector. Input is flattened if not already 1-dimensional.

out : (M, N) ndarray, optional A location where the result is stored

**Returns** : out : (M, N) ndarray  $out[i, j] = a[i] * b[j]$

### 1.E.2 tests

## 1.F linalg.matmul

### 1.F.1 documentation

Matrix product of two arrays.

The behavior depends on the arguments in the following way.

If both arguments are 2-D they are multiplied like conventional matrices.

If either argument is N-D,  $N \geq 2$ , it is treated as a stack of matrices residing in the last two indexes and broadcast accordingly.

If the first argument is 1-D, it is promoted to a matrix by prepending a 1 to its dimensions. After matrix multiplication the prepended 1 is removed.

If the second argument is 1-D, it is promoted to a matrix by appending a 1 to its dimensions. After matrix multiplication the appended 1 is removed.

Multiplication by a scalar is not allowed, use \* instead. Note that multiplying a stack of matrices with a vector will result in a stack of vectors, but matmul will not recognize it as such.

### 1.F.2 tests

## 1.G linalg.tensordot

### 1.G.1 documentation

Compute tensor dot product along specified axes for arrays  $\geq$  1-D.

Given two tensors (arrays of dimension greater than or equal to one), a and b, and an array\_like object containing two array\_like objects, (a\_axes, b\_axes), sum the products of as and bs elements (components) over the axes specified by a\_axes and b\_axes. The third argument can be a single non-negative integer-like scalar, N; if it is such, then the last N dimensions of a and the first N dimensions of b are summed over.

## 1.G.2 tests

## 1.H linalg.matrix\_power

### 1.H.1 documentation

Raise a square matrix to the (integer) power n.

For positive integers n, the power is computed by repeated matrix squarings and matrix multiplications. If n == 0, the identity matrix of the same shape as M is returned. If n < 0, the inverse is computed and then raised to the abs(n).

### 1.H.2 tests

## 1.I linalg.eig

Compute the eigenvalues and right eigenvectors of a square array.

**Parameters** : a : (... , M, M) array

**Returns** : w : (... , M) array

Raises: LinAlgError If the eigenvalue computation does not converge.

### 1.I.1 documentation

### 1.I.2 tests

## 1.J linalg.eigh

### 1.J.1 documentation

Return the eigenvalues and eigenvectors of a Hermitian or symmetric matrix.

Returns two objects, a 1-D array containing the eigenvalues of a, and a 2-D square array or matrix (depending on the input type) of the corresponding eigenvectors (in columns).

**Parameters** : a : (... , M, M) array

**Returns** : w : (... , M) ndarray The eigenvalues in ascending order, each repeated according to its multiplicity.

Raises: LinAlgError If the eigenvalue computation does not converge.

### 1.J.2 tests

## 1.K linalg.eigvalsh

### 1.K.1 documentation

Compute the eigenvalues of a Hermitian or real symmetric matrix.

Main difference from `eigh`: the eigenvectors are not computed.

**Parameters** : `a` : (... , M, M) array\_like

**Returns** : `w` : (... , M,) ndarray The eigenvalues in ascending order, each repeated according to its multiplicity.

Raises: `LinAlgError` if the eigenvalue computation does not converge.

### 1.K.2 tests

## 1.L linalg.eigvals

### 1.L.1 documentation

Compute the eigenvalues of a general matrix.

Main difference between `eigvals` and `eig`: the eigenvectors are not returned.

**Parameters** : `a` : (... , M, M) array\_like A complex- or real-valued matrix whose eigenvalues will be computed.

**Returns** : `w` : (... , M,) ndarray The eigenvalues, each repeated according to its multiplicity. They are not necessarily ordered, nor are they necessarily real for real matrices.

Raises: `LinAlgError` If the eigenvalue computation does not converge.

### 1.L.2 tests

## 1.M linalg.norm

### 1.M.1 documentation

Matrix or vector norm.

This function is able to return one of eight different matrix norms, or one of an infinite number of vector norms (described below), depending on the value of the `ord` parameter.

**Parameters** : `x` : array\_like Input array. If `axis` is `None`, `x` must be 1-D or 2-D. `ord` : non-zero int, inf, -inf, fro, nuc, optional Order of the norm (see table under Notes). `inf` means `numpy.inf` object. `axis` : int, 2-tuple of ints, `None`, optional If `axis` is an integer, it specifies the axis of `x` along which to compute the vector norms. If `axis` is a 2-tuple, it specifies the axes that hold 2-D matrices, and the matrix norms of these matrices are computed. If `axis` is `None` then either a vector norm (when `x` is 1-D) or a matrix norm (when `x` is 2-D) is returned. `keepdims` : bool, optional If this is set to `True`, the axes which are normed over are left in the result as dimensions

with size one. With this option the result will broadcast correctly against the original x. New in version 1.10.0.

**Returns** : n : float or ndarray Norm of the matrix or vector(s).

## **1.M.2 tests**

## **1.N linalg.cond**

### **1.N.1 documentation**

### **1.N.2 tests**

## **1.O linalg.det**

### **1.O.1 documentation**

### **1.O.2 tests**

## **1.P linalg.matrix\_rank**

### **1.P.1 documentation**

### **1.P.2 tests**

## **1.Q linalg.slogdet**

### **1.Q.1 documentation**

### **1.Q.2 tests**

## **1.R linalg.trace**

### **1.R.1 documentation**

### **1.R.2 tests**

## **1.S linalg.det**

### **1.S.1 documentation**

### **1.S.2 tests**

## **1.T linalg.multidot (Black box tests)**

sdfs

### **1.T.1 documentation**

Compute the dot product of two or more arrays in a single function call, while automatically selecting the fastest evaluation order. ‘multi\_dot’ chains ‘numpy.dot’ and uses optimal parenthesization of the matrices. Depending on the shapes of the matrices, this can speed up the multiplication a lot. If the first argument is 1-D it is treated as a row vector. If the last argument is 1-D it is treated as a column vector. The other arguments must be 2-D.

TestCases: Test cases are created so that vectors when multiplied share the same dimensions.

When matrices are multiplied they need to be organized so that the first dimension of the first matrix is the same as the second dimension of the second matrix etc.

### 1.T.2 Tests

`test_three_inputs_vectors`: This tests the `multidot` function with three vectors. The assert is the following: `assert_almost_equal(multi_dot([A, B]), A.dot(B))`

`test_three_inputs_matrices`: This tests the `multidot` function with three matrices

`test_four_inputs_matrices`: This tests the `multidot` function with four matrices

`test_shape_vector_first`: This tests the `multidot` function with a vector with `n` rows as the first argument followed by three matrices with dimensions `n, m` and `m, n`. The shape result sought is the same as the vector, i.e. 1 dimensional with `n` rows.

`test_shape_vector_last`: This tests the `multidot` function with a `n` rows vector as the last argument preceded by three matrices with dimensions `m, n` and `n, m`. The shape result sought is `m`.

`test_shape_vector_first_and_last`: This tests the `multidot` function with `n` rows vector as the first and last arguments with two matrices with dimensions `n, m` and `m, n` in the middle. The shape result sought is `()` since the result is a scalar. `assert_equal(multi_dot([A1d, B, C, D1d]).shape, ())`

## 2 White-Box Test